

---

FIX.Latest

**FIX.Latest\_EP296**

## Contents

<b>1</b>	<b>Message Set Overview</b>	<b>19</b>
1.1	List of Messages . . . . .	19
<b>2</b>	<b>AccountSummaryReport</b>	<b>45</b>
2.1	Message Functionality . . . . .	45
2.2	Structure . . . . .	45
<b>3</b>	<b>AdjustedPositionReport</b>	<b>47</b>
3.1	Message Functionality . . . . .	47
3.2	Structure . . . . .	47
<b>4</b>	<b>Advertisement</b>	<b>48</b>
4.1	Message Functionality . . . . .	48
4.2	Structure . . . . .	48
<b>5</b>	<b>AlgoCertificateReport</b>	<b>50</b>
5.1	Message Functionality . . . . .	50
5.2	Structure . . . . .	50
<b>6</b>	<b>AlgoCertificateReportAck</b>	<b>52</b>
6.1	Message Functionality . . . . .	52
6.2	Structure . . . . .	52
<b>7</b>	<b>AlgoCertificateRequest</b>	<b>53</b>
7.1	Message Functionality . . . . .	53
7.2	Structure . . . . .	53
<b>8</b>	<b>AlgoCertificateRequestAck</b>	<b>55</b>
8.1	Message Functionality . . . . .	55
8.2	Structure . . . . .	55
<b>9</b>	<b>AllocationInstruction</b>	<b>56</b>
9.1	Message Functionality . . . . .	56
9.2	Structure . . . . .	56
<b>10</b>	<b>AllocationInstructionAck</b>	<b>62</b>
10.1	Message Functionality . . . . .	62
10.2	Structure . . . . .	62

<b>11</b>	<b>AllocationInstructionAlert</b>	<b>64</b>
11.1	Message Functionality . . . . .	64
11.2	Structure . . . . .	64
<b>12</b>	<b>AllocationInstructionAlertRequest</b>	<b>70</b>
12.1	Message Functionality . . . . .	70
12.2	Structure . . . . .	70
<b>13</b>	<b>AllocationInstructionAlertRequestAck</b>	<b>71</b>
13.1	Message Functionality . . . . .	71
13.2	Structure . . . . .	71
<b>14</b>	<b>AllocationReport</b>	<b>72</b>
14.1	Message Functionality . . . . .	72
14.2	Structure . . . . .	72
<b>15</b>	<b>AllocationReportAck</b>	<b>78</b>
15.1	Message Functionality . . . . .	78
15.2	Structure . . . . .	78
<b>16</b>	<b>ApplicationMessageReport</b>	<b>81</b>
16.1	Message Functionality . . . . .	81
16.2	Structure . . . . .	81
<b>17</b>	<b>ApplicationMessageRequest</b>	<b>82</b>
17.1	Message Functionality . . . . .	82
17.2	Structure . . . . .	82
<b>18</b>	<b>ApplicationMessageRequestAck</b>	<b>83</b>
18.1	Message Functionality . . . . .	83
18.2	Structure . . . . .	83
<b>19</b>	<b>AssignmentReport</b>	<b>84</b>
19.1	Message Functionality . . . . .	84
19.2	Structure . . . . .	84
<b>20</b>	<b>BidRequest</b>	<b>86</b>
20.1	Message Functionality . . . . .	86
20.2	Structure . . . . .	86
<b>21</b>	<b>BidResponse</b>	<b>88</b>

21.1	Message Functionality . . . . .	88
21.2	Structure . . . . .	88
<b>22</b>	<b>BusinessMessageReject</b>	<b>89</b>
22.1	Message Functionality . . . . .	89
22.2	Structure . . . . .	89
<b>23</b>	<b>CollateralAssignment</b>	<b>91</b>
23.1	Message Functionality . . . . .	91
23.2	Structure . . . . .	91
<b>24</b>	<b>CollateralInquiry</b>	<b>94</b>
24.1	Message Functionality . . . . .	94
24.2	Structure . . . . .	94
<b>25</b>	<b>CollateralInquiryAck</b>	<b>97</b>
25.1	Message Functionality . . . . .	97
25.2	Structure . . . . .	97
<b>26</b>	<b>CollateralReport</b>	<b>99</b>
26.1	Message Functionality . . . . .	99
26.2	Structure . . . . .	99
<b>27</b>	<b>CollateralReportAck</b>	<b>102</b>
27.1	Message Functionality . . . . .	102
27.2	Structure . . . . .	102
<b>28</b>	<b>CollateralRequest</b>	<b>103</b>
28.1	Message Functionality . . . . .	103
28.2	Structure . . . . .	103
<b>29</b>	<b>CollateralResponse</b>	<b>105</b>
29.1	Message Functionality . . . . .	105
29.2	Structure . . . . .	105
<b>30</b>	<b>Confirmation</b>	<b>108</b>
30.1	Message Functionality . . . . .	108
30.2	Structure . . . . .	108
<b>31</b>	<b>ConfirmationAck</b>	<b>113</b>
31.1	Message Functionality . . . . .	113

31.2	Structure . . . . .	113
<b>32</b>	<b>ConfirmationRequest</b>	<b>114</b>
32.1	Message Functionality . . . . .	114
32.2	Structure . . . . .	114
<b>33</b>	<b>ContraryIntentionReport</b>	<b>115</b>
33.1	Message Functionality . . . . .	115
33.2	Structure . . . . .	115
<b>34</b>	<b>CrossOrderCancelReplaceRequest</b>	<b>116</b>
34.1	Message Functionality . . . . .	116
34.2	Structure . . . . .	116
<b>35</b>	<b>CrossOrderCancelRequest</b>	<b>120</b>
35.1	Message Functionality . . . . .	120
35.2	Structure . . . . .	120
<b>36</b>	<b>CrossRequest</b>	<b>122</b>
36.1	Message Functionality . . . . .	122
36.2	Structure . . . . .	122
<b>37</b>	<b>CrossRequestAck</b>	<b>123</b>
37.1	Message Functionality . . . . .	123
37.2	Structure . . . . .	123
<b>38</b>	<b>DerivativeSecurityList</b>	<b>124</b>
38.1	Message Functionality . . . . .	124
38.2	Structure . . . . .	124
<b>39</b>	<b>DerivativeSecurityListRequest</b>	<b>126</b>
39.1	Message Functionality . . . . .	126
39.2	Structure . . . . .	126
<b>40</b>	<b>DerivativeSecurityListUpdateReport</b>	<b>127</b>
40.1	Message Functionality . . . . .	127
40.2	Structure . . . . .	127
<b>41</b>	<b>DontKnowTrade</b>	<b>129</b>
41.1	Message Functionality . . . . .	129
41.2	Structure . . . . .	129

<b>42</b>	<b>Email</b>	<b>130</b>
42.1	Message Functionality . . . . .	130
42.2	Structure . . . . .	130
<b>43</b>	<b>ExecutionAck</b>	<b>131</b>
43.1	Message Functionality . . . . .	131
43.2	Structure . . . . .	131
<b>44</b>	<b>ExecutionReport</b>	<b>133</b>
44.1	Message Functionality . . . . .	133
44.2	Structure . . . . .	133
<b>45</b>	<b>Heartbeat</b>	<b>147</b>
45.1	Message Functionality . . . . .	147
45.2	Structure . . . . .	147
<b>46</b>	<b>IOI</b>	<b>148</b>
46.1	Message Functionality . . . . .	148
46.2	Structure . . . . .	148
<b>47</b>	<b>ListCancelRequest</b>	<b>151</b>
47.1	Message Functionality . . . . .	151
47.2	Structure . . . . .	151
<b>48</b>	<b>ListExecute</b>	<b>152</b>
48.1	Message Functionality . . . . .	152
48.2	Structure . . . . .	152
<b>49</b>	<b>ListStatus</b>	<b>153</b>
49.1	Message Functionality . . . . .	153
49.2	Structure . . . . .	153
<b>50</b>	<b>ListStatusRequest</b>	<b>154</b>
50.1	Message Functionality . . . . .	154
50.2	Structure . . . . .	154
<b>51</b>	<b>ListStrikePrice</b>	<b>155</b>
51.1	Message Functionality . . . . .	155
51.2	Structure . . . . .	155
<b>52</b>	<b>Logon</b>	<b>156</b>

52.1	Message Functionality . . . . .	156
52.2	Structure . . . . .	156
<b>53</b>	<b>Logout</b>	<b>158</b>
53.1	Message Functionality . . . . .	158
53.2	Structure . . . . .	158
<b>54</b>	<b>MarginRequirementInquiry</b>	<b>159</b>
54.1	Message Functionality . . . . .	159
54.2	Structure . . . . .	159
<b>55</b>	<b>MarginRequirementInquiryAck</b>	<b>161</b>
55.1	Message Functionality . . . . .	161
55.2	Structure . . . . .	161
<b>56</b>	<b>MarginRequirementReport</b>	<b>163</b>
56.1	Message Functionality . . . . .	163
56.2	Structure . . . . .	163
<b>57</b>	<b>MarketDataIncrementalRefresh</b>	<b>165</b>
57.1	Message Functionality . . . . .	165
57.2	Structure . . . . .	165
<b>58</b>	<b>MarketDataReport</b>	<b>166</b>
58.1	Message Functionality . . . . .	166
58.2	Structure . . . . .	166
<b>59</b>	<b>MarketDataRequest</b>	<b>167</b>
59.1	Message Functionality . . . . .	167
59.2	Structure . . . . .	167
<b>60</b>	<b>MarketDataRequestReject</b>	<b>169</b>
60.1	Message Functionality . . . . .	169
60.2	Structure . . . . .	169
<b>61</b>	<b>MarketDataSnapshotFullRefresh</b>	<b>170</b>
61.1	Message Functionality . . . . .	170
61.2	Structure . . . . .	170
<b>62</b>	<b>MarketDataStatisticsReport</b>	<b>172</b>
62.1	Message Functionality . . . . .	172

62.2	Structure . . . . .	172
<b>63</b>	<b>MarketDataStatisticsRequest</b>	<b>174</b>
63.1	Message Functionality . . . . .	174
63.2	Structure . . . . .	174
<b>64</b>	<b>MarketDefinition</b>	<b>176</b>
64.1	Message Functionality . . . . .	176
64.2	Structure . . . . .	176
<b>65</b>	<b>MarketDefinitionRequest</b>	<b>179</b>
65.1	Message Functionality . . . . .	179
65.2	Structure . . . . .	179
<b>66</b>	<b>MarketDefinitionUpdateReport</b>	<b>180</b>
66.1	Message Functionality . . . . .	180
66.2	Structure . . . . .	180
<b>67</b>	<b>MassOrder</b>	<b>182</b>
67.1	Message Functionality . . . . .	182
67.2	Structure . . . . .	182
<b>68</b>	<b>MassOrderAck</b>	<b>184</b>
68.1	Message Functionality . . . . .	184
68.2	Structure . . . . .	184
<b>69</b>	<b>MassQuote</b>	<b>186</b>
69.1	Message Functionality . . . . .	186
69.2	Structure . . . . .	186
<b>70</b>	<b>MassQuoteAck</b>	<b>188</b>
70.1	Message Functionality . . . . .	188
70.2	Structure . . . . .	188
<b>71</b>	<b>MultilegOrderCancelReplace</b>	<b>190</b>
71.1	Message Functionality . . . . .	190
71.2	Structure . . . . .	190
<b>72</b>	<b>NetworkCounterpartySystemStatusRequest</b>	<b>196</b>
72.1	Message Functionality . . . . .	196
72.2	Structure . . . . .	196



<b>73</b>	<b>NetworkCounterpartySystemStatusResponse</b>	<b>197</b>
73.1	Message Functionality . . . . .	197
73.2	Structure . . . . .	197
<b>74</b>	<b>NewOrderCross</b>	<b>198</b>
74.1	Message Functionality . . . . .	198
74.2	Structure . . . . .	198
<b>75</b>	<b>NewOrderList</b>	<b>202</b>
75.1	Message Functionality . . . . .	202
75.2	Structure . . . . .	202
<b>76</b>	<b>NewOrderMultileg</b>	<b>204</b>
76.1	Message Functionality . . . . .	204
76.2	Structure . . . . .	204
<b>77</b>	<b>NewOrderSingle</b>	<b>210</b>
77.1	Message Functionality . . . . .	210
77.2	Structure . . . . .	210
<b>78</b>	<b>News</b>	<b>217</b>
78.1	Message Functionality . . . . .	217
78.2	Structure . . . . .	217
<b>79</b>	<b>OrderCancelReject</b>	<b>219</b>
79.1	Message Functionality . . . . .	219
79.2	Structure . . . . .	219
<b>80</b>	<b>OrderCancelReplaceRequest</b>	<b>221</b>
80.1	Message Functionality . . . . .	221
80.2	Structure . . . . .	221
<b>81</b>	<b>OrderCancelRequest</b>	<b>228</b>
81.1	Message Functionality . . . . .	228
81.2	Structure . . . . .	228
<b>82</b>	<b>OrderMassActionReport</b>	<b>231</b>
82.1	Message Functionality . . . . .	231
82.2	Structure . . . . .	231
<b>83</b>	<b>OrderMassActionRequest</b>	<b>234</b>

83.1	Message Functionality . . . . .	234
83.2	Structure . . . . .	234
<b>84</b>	<b>OrderMassCancelReport</b>	<b>236</b>
84.1	Message Functionality . . . . .	236
84.2	Structure . . . . .	236
<b>85</b>	<b>OrderMassCancelRequest</b>	<b>238</b>
85.1	Message Functionality . . . . .	238
85.2	Structure . . . . .	238
<b>86</b>	<b>OrderMassStatusRequest</b>	<b>240</b>
86.1	Message Functionality . . . . .	240
86.2	Structure . . . . .	240
<b>87</b>	<b>OrderStatusRequest</b>	<b>241</b>
87.1	Message Functionality . . . . .	241
87.2	Structure . . . . .	241
<b>88</b>	<b>PartyActionReport</b>	<b>243</b>
88.1	Message Functionality . . . . .	243
88.2	Structure . . . . .	243
<b>89</b>	<b>PartyActionRequest</b>	<b>245</b>
89.1	Message Functionality . . . . .	245
89.2	Structure . . . . .	245
<b>90</b>	<b>PartyDetailsDefinitionRequest</b>	<b>246</b>
90.1	Message Functionality . . . . .	246
90.2	Structure . . . . .	246
<b>91</b>	<b>PartyDetailsDefinitionRequestAck</b>	<b>247</b>
91.1	Message Functionality . . . . .	247
91.2	Structure . . . . .	247
<b>92</b>	<b>PartyDetailsListReport</b>	<b>248</b>
92.1	Message Functionality . . . . .	248
92.2	Structure . . . . .	248
<b>93</b>	<b>PartyDetailsListRequest</b>	<b>249</b>
93.1	Message Functionality . . . . .	249

93.2	Structure . . . . .	249
<b>94</b>	<b>PartyDetailsListUpdateReport</b>	<b>250</b>
94.1	Message Functionality . . . . .	250
94.2	Structure . . . . .	250
<b>95</b>	<b>PartyEntitlementsDefinitionRequest</b>	<b>251</b>
95.1	Message Functionality . . . . .	251
95.2	Structure . . . . .	251
<b>96</b>	<b>PartyEntitlementsDefinitionRequestAck</b>	<b>252</b>
96.1	Message Functionality . . . . .	252
96.2	Structure . . . . .	252
<b>97</b>	<b>PartyEntitlementsReport</b>	<b>253</b>
97.1	Message Functionality . . . . .	253
97.2	Structure . . . . .	253
<b>98</b>	<b>PartyEntitlementsRequest</b>	<b>254</b>
98.1	Message Functionality . . . . .	254
98.2	Structure . . . . .	254
<b>99</b>	<b>PartyEntitlementsUpdateReport</b>	<b>255</b>
99.1	Message Functionality . . . . .	255
99.2	Structure . . . . .	255
<b>100</b>	<b>PartyRiskLimitCheckRequest</b>	<b>256</b>
100.1	Message Functionality . . . . .	256
100.2	Structure . . . . .	256
<b>101</b>	<b>PartyRiskLimitCheckRequestAck</b>	<b>258</b>
101.1	Message Functionality . . . . .	258
101.2	Structure . . . . .	258
<b>102</b>	<b>PartyRiskLimitsDefinitionRequest</b>	<b>260</b>
102.1	Message Functionality . . . . .	260
102.2	Structure . . . . .	260
<b>103</b>	<b>PartyRiskLimitsDefinitionRequestAck</b>	<b>261</b>
103.1	Message Functionality . . . . .	261
103.2	Structure . . . . .	261

<b>104</b>	<b>PartyRiskLimitsReport</b>	<b>262</b>
104.1	Message Functionality . . . . .	262
104.2	Structure . . . . .	262
<b>105</b>	<b>PartyRiskLimitsReportAck</b>	<b>263</b>
105.1	Message Functionality . . . . .	263
105.2	Structure . . . . .	263
<b>106</b>	<b>PartyRiskLimitsRequest</b>	<b>264</b>
106.1	Message Functionality . . . . .	264
106.2	Structure . . . . .	264
<b>107</b>	<b>PartyRiskLimitsUpdateReport</b>	<b>265</b>
107.1	Message Functionality . . . . .	265
107.2	Structure . . . . .	265
<b>108</b>	<b>PayManagementReport</b>	<b>266</b>
108.1	Message Functionality . . . . .	266
108.2	Structure . . . . .	266
<b>109</b>	<b>PayManagementReportAck</b>	<b>268</b>
109.1	Message Functionality . . . . .	268
109.2	Structure . . . . .	268
<b>110</b>	<b>PayManagementRequest</b>	<b>269</b>
110.1	Message Functionality . . . . .	269
110.2	Structure . . . . .	269
<b>111</b>	<b>PayManagementRequestAck</b>	<b>271</b>
111.1	Message Functionality . . . . .	271
111.2	Structure . . . . .	271
<b>112</b>	<b>PositionMaintenanceReport</b>	<b>272</b>
112.1	Message Functionality . . . . .	272
112.2	Structure . . . . .	272
<b>113</b>	<b>PositionMaintenanceRequest</b>	<b>275</b>
113.1	Message Functionality . . . . .	275
113.2	Structure . . . . .	275
<b>114</b>	<b>PositionReport</b>	<b>277</b>

114.1	Message Functionality . . . . .	277
114.2	Structure . . . . .	277
<b>115</b>	<b>PositionTransferInstruction</b>	<b>281</b>
115.1	Message Functionality . . . . .	281
115.2	Structure . . . . .	281
<b>116</b>	<b>PositionTransferInstructionAck</b>	<b>283</b>
116.1	Message Functionality . . . . .	283
116.2	Structure . . . . .	283
<b>117</b>	<b>PositionTransferReport</b>	<b>285</b>
117.1	Message Functionality . . . . .	285
117.2	Structure . . . . .	285
<b>118</b>	<b>Quote</b>	<b>287</b>
118.1	Message Functionality . . . . .	287
118.2	Structure . . . . .	287
<b>119</b>	<b>QuoteAck</b>	<b>292</b>
119.1	Message Functionality . . . . .	292
119.2	Structure . . . . .	292
<b>120</b>	<b>QuoteCancel</b>	<b>293</b>
120.1	Message Functionality . . . . .	293
120.2	Structure . . . . .	293
<b>121</b>	<b>QuoteRequest</b>	<b>295</b>
121.1	Message Functionality . . . . .	295
121.2	Structure . . . . .	295
<b>122</b>	<b>QuoteRequestReject</b>	<b>297</b>
122.1	Message Functionality . . . . .	297
122.2	Structure . . . . .	297
<b>123</b>	<b>QuoteResponse</b>	<b>298</b>
123.1	Message Functionality . . . . .	298
123.2	Structure . . . . .	298
<b>124</b>	<b>QuoteStatusReport</b>	<b>303</b>
124.1	Message Functionality . . . . .	303

124.2	Structure . . . . .	303
<b>125</b>	<b>QuoteStatusRequest</b>	<b>308</b>
125.1	Message Functionality . . . . .	308
125.2	Structure . . . . .	308
<b>126</b>	<b>RFQRequest</b>	<b>310</b>
126.1	Message Functionality . . . . .	310
126.2	Structure . . . . .	310
<b>127</b>	<b>RegistrationInstructions</b>	<b>311</b>
127.1	Message Functionality . . . . .	311
127.2	Structure . . . . .	311
<b>128</b>	<b>RegistrationInstructionsResponse</b>	<b>312</b>
128.1	Message Functionality . . . . .	312
128.2	Structure . . . . .	312
<b>129</b>	<b>Reject</b>	<b>313</b>
129.1	Message Functionality . . . . .	313
129.2	Structure . . . . .	313
<b>130</b>	<b>RequestForPositions</b>	<b>315</b>
130.1	Message Functionality . . . . .	315
130.2	Structure . . . . .	315
<b>131</b>	<b>RequestForPositionsAck</b>	<b>317</b>
131.1	Message Functionality . . . . .	317
131.2	Structure . . . . .	317
<b>132</b>	<b>ResendRequest</b>	<b>319</b>
132.1	Message Functionality . . . . .	319
132.2	Structure . . . . .	319
<b>133</b>	<b>SecurityDefinition</b>	<b>320</b>
133.1	Message Functionality . . . . .	320
133.2	Structure . . . . .	320
<b>134</b>	<b>SecurityDefinitionRequest</b>	<b>322</b>
134.1	Message Functionality . . . . .	322
134.2	Structure . . . . .	322

<b>135</b>	<b>SecurityDefinitionUpdateReport</b>	<b>324</b>
135.1	Message Functionality . . . . .	324
135.2	Structure . . . . .	324
<b>136</b>	<b>SecurityList</b>	<b>326</b>
136.1	Message Functionality . . . . .	326
136.2	Structure . . . . .	326
<b>137</b>	<b>SecurityListRequest</b>	<b>328</b>
137.1	Message Functionality . . . . .	328
137.2	Structure . . . . .	328
<b>138</b>	<b>SecurityListUpdateReport</b>	<b>330</b>
138.1	Message Functionality . . . . .	330
138.2	Structure . . . . .	330
<b>139</b>	<b>SecurityMassStatus</b>	<b>332</b>
139.1	Message Functionality . . . . .	332
139.2	Structure . . . . .	332
<b>140</b>	<b>SecurityMassStatusRequest</b>	<b>333</b>
140.1	Message Functionality . . . . .	333
140.2	Structure . . . . .	333
<b>141</b>	<b>SecurityRiskMetricsReport</b>	<b>334</b>
141.1	Message Functionality . . . . .	334
141.2	Structure . . . . .	334
<b>142</b>	<b>SecurityStatus</b>	<b>335</b>
142.1	Message Functionality . . . . .	335
142.2	Structure . . . . .	335
<b>143</b>	<b>SecurityStatusRequest</b>	<b>337</b>
143.1	Message Functionality . . . . .	337
143.2	Structure . . . . .	337
<b>144</b>	<b>SecurityTypeRequest</b>	<b>339</b>
144.1	Message Functionality . . . . .	339
144.2	Structure . . . . .	339
<b>145</b>	<b>SecurityTypes</b>	<b>340</b>

145.1	Message Functionality . . . . .	340
145.2	Structure . . . . .	340
<b>146</b>	<b>SequenceReset</b>	<b>342</b>
146.1	Message Functionality . . . . .	342
146.2	Structure . . . . .	342
<b>147</b>	<b>SettlementInstructionRequest</b>	<b>343</b>
147.1	Message Functionality . . . . .	343
147.2	Structure . . . . .	343
<b>148</b>	<b>SettlementInstructions</b>	<b>345</b>
148.1	Message Functionality . . . . .	345
148.2	Structure . . . . .	345
<b>149</b>	<b>SettlementObligationReport</b>	<b>346</b>
149.1	Message Functionality . . . . .	346
149.2	Structure . . . . .	346
<b>150</b>	<b>SettlementStatusReport</b>	<b>347</b>
150.1	Message Functionality . . . . .	347
150.2	Structure . . . . .	347
<b>151</b>	<b>SettlementStatusReportAck</b>	<b>349</b>
151.1	Message Functionality . . . . .	349
151.2	Structure . . . . .	349
<b>152</b>	<b>SettlementStatusRequest</b>	<b>350</b>
152.1	Message Functionality . . . . .	350
152.2	Structure . . . . .	350
<b>153</b>	<b>SettlementStatusRequestAck</b>	<b>351</b>
153.1	Message Functionality . . . . .	351
153.2	Structure . . . . .	351
<b>154</b>	<b>StreamAssignmentReport</b>	<b>352</b>
154.1	Message Functionality . . . . .	352
154.2	Structure . . . . .	352
<b>155</b>	<b>StreamAssignmentReportACK</b>	<b>353</b>
155.1	Message Functionality . . . . .	353



155.2	Structure . . . . .	353
<b>156</b>	<b>StreamAssignmentRequest</b>	<b>354</b>
156.1	Message Functionality . . . . .	354
156.2	Structure . . . . .	354
<b>157</b>	<b>TestActionReport</b>	<b>355</b>
157.1	Message Functionality . . . . .	355
157.2	Structure . . . . .	355
<b>158</b>	<b>TestActionRequest</b>	<b>356</b>
158.1	Message Functionality . . . . .	356
158.2	Structure . . . . .	356
<b>159</b>	<b>TestActionRequestAck</b>	<b>357</b>
159.1	Message Functionality . . . . .	357
159.2	Structure . . . . .	357
<b>160</b>	<b>TestRequest</b>	<b>358</b>
160.1	Message Functionality . . . . .	358
160.2	Structure . . . . .	358
<b>161</b>	<b>TestSuiteDefinitionRequest</b>	<b>359</b>
161.1	Message Functionality . . . . .	359
161.2	Structure . . . . .	359
<b>162</b>	<b>TestSuiteDefinitionRequestAck</b>	<b>360</b>
162.1	Message Functionality . . . . .	360
162.2	Structure . . . . .	360
<b>163</b>	<b>TradeAggregationReport</b>	<b>361</b>
163.1	Message Functionality . . . . .	361
163.2	Structure . . . . .	361
<b>164</b>	<b>TradeAggregationRequest</b>	<b>363</b>
164.1	Message Functionality . . . . .	363
164.2	Structure . . . . .	363
<b>165</b>	<b>TradeCaptureReport</b>	<b>364</b>
165.1	Message Functionality . . . . .	364
165.2	Structure . . . . .	364

<b>166</b>	<b>TradeCaptureReportAck</b>	<b>372</b>
166.1	Message Functionality . . . . .	372
166.2	Structure . . . . .	372
<b>167</b>	<b>TradeCaptureReportRequest</b>	<b>376</b>
167.1	Message Functionality . . . . .	376
167.2	Structure . . . . .	376
<b>168</b>	<b>TradeCaptureReportRequestAck</b>	<b>379</b>
168.1	Message Functionality . . . . .	379
168.2	Structure . . . . .	379
<b>169</b>	<b>TradeMatchReport</b>	<b>381</b>
169.1	Message Functionality . . . . .	381
169.2	Structure . . . . .	381
<b>170</b>	<b>TradeMatchReportAck</b>	<b>383</b>
170.1	Message Functionality . . . . .	383
170.2	Structure . . . . .	383
<b>171</b>	<b>TradingSessionList</b>	<b>384</b>
171.1	Message Functionality . . . . .	384
171.2	Structure . . . . .	384
<b>172</b>	<b>TradingSessionListRequest</b>	<b>385</b>
172.1	Message Functionality . . . . .	385
172.2	Structure . . . . .	385
<b>173</b>	<b>TradingSessionListUpdateReport</b>	<b>386</b>
173.1	Message Functionality . . . . .	386
173.2	Structure . . . . .	386
<b>174</b>	<b>TradingSessionStatus</b>	<b>387</b>
174.1	Message Functionality . . . . .	387
174.2	Structure . . . . .	387
<b>175</b>	<b>TradingSessionStatusRequest</b>	<b>389</b>
175.1	Message Functionality . . . . .	389
175.2	Structure . . . . .	389
<b>176</b>	<b>UserNotification</b>	<b>390</b>

176.1	Message Functionality . . . . .	390
176.2	Structure . . . . .	390
<b>177</b>	<b>UserRequest</b>	<b>391</b>
177.1	Message Functionality . . . . .	391
177.2	Structure . . . . .	391
<b>178</b>	<b>UserResponse</b>	<b>392</b>
178.1	Message Functionality . . . . .	392
178.2	Structure . . . . .	392
<b>179</b>	<b>XMLnonFIX</b>	<b>393</b>
179.1	Message Functionality . . . . .	393
179.2	Structure . . . . .	393
<b>180</b>	<b>Message Elements</b>	<b>394</b>
180.1	Data Types . . . . .	394
180.2	Data Dictionary . . . . .	397

## 1 Message Set Overview

### 1.1 List of Messages

The following table lists all messages described in this report.

Name	Category	Description
AccountSummaryReport	AccountReporting	The AccountSummaryReport is provided by the clearinghouse to its clearing members on a daily basis. It contains margin, settlement, collateral and pay/collect data for each clearing member level account type. Clearing member account types will be described through use of the Parties component and PtysSubGrp sub-component.
AllocationInstruction	Allocation	The AllocationInstruction(35=J) message provides the ability to specify how an order or set of orders should be subdivided amongst one or more accounts.
AllocationInstructionAck	Allocation	In versions of FIX prior to version 4.4, this message was known as the Allocation ACK message.
AllocationInstructionAlert	Allocation	This message is used in a 3-party allocation model (buy-side and sell-side using a central clearing entity) where notification of group creation and group updates to counterparties is needed. The message will also carry trade information that comprised the group to the counterparties.
AllocationInstructionAlertRequest	Allocation	This message is used in a clearinghouse 3-party allocation model to request for AllocationInstructionAlert(35=BM) from the clearinghouse. The request may be used to obtain a one-time notification of the status of an allocation group.

Name	Category	Description
AllocationInstructionAlertRequestAck	Allocation	This message is used in a clearinghouse 3-party allocation model to acknowledge a AllocationInstructionAlertRequest(35=DU) message for an AllocationInstructionAlert(35=BM) message from the clearinghouse.
AllocationReport	Allocation	Sent from sell-side to buy-side, sell-side to 3rd-party or 3rd-party to buy-side, the AllocationReport(35=AS) message (Claim) provides account breakdown of an order or set of orders plus any additional follow-up front-office information developed post-trade during the trade allocation, matching and calculation phase.
AllocationReportAck	Allocation	The Allocation Report Ack message is used to acknowledge the receipt of and provide status for an Allocation Report message.
ApplicationMessageReport	Application	This message is used for three difference purposes: to reset the ApplSeqNum (1181) of a specified ApplID (1180). to indicate that the last message has been sent for a particular ApplID, or as a keep-alive mechanism for ApplIDs with infrequent message traffic.
ApplicationMessageRequest	Application	This message is used to request a retransmission of a set of one or more messages generated by the application specified in RefApplID (1355).
ApplicationMessageRequestAck	Application	This message is used to acknowledge an Application Message Request providing a status on the request (i.e. whether successful or not). This message does not provide the actual content of the messages to be resent.

Name	Category	Description
BusinessMessageReject	BusinessReject	The Business Message Reject message can reject an application-level message which fulfills session-level rules and cannot be rejected via any other means. Note if the message fails a session-level rule (e.g. body length is incorrect), a session-level Reject message should be issued.
CollateralAssignment	CollateralManagement	Used to assign collateral to cover a trading position. This message can be sent unsolicited or in reply to a Collateral Request message.
CollateralInquiry	CollateralManagement	Used to inquire for collateral status.
CollateralInquiryAck	CollateralManagement	Used to respond to a Collateral Inquiry in the following situations:
CollateralReport	CollateralManagement	Used to report collateral status when responding to a Collateral Inquiry message.
CollateralReportAck	CollateralManagement	CollateralReportAck(35=DQ) is used as a response to the CollateralReport(35=BA). It can be used to reject a CollateralReport(35=BA) when the content of the report is invalid based on the business rules of the receiver. The message may also be used to acknowledge receipt of a valid CollateralReport(35=BA).
CollateralRequest	CollateralManagement	An initiator that requires collateral from a respondent sends a Collateral Request. The initiator can be either counterparty to a trade in a two party model or an intermediary such as an ATS or clearinghouse in a three party model. A Collateral Assignment is expected as a response to a request for collateral.
CollateralResponse	CollateralManagement	Used to respond to a Collateral Assignment message.

Name	Category	Description
Confirmation	Confirmation	The Confirmation messages are used to provide individual trade level confirmations from the sell side to the buy side. In versions of FIX prior to version 4.4, this role was performed by the allocation message. Unlike the allocation message, the confirmation message operates at an allocation account (trade) level rather than block level, allowing for the affirmation or rejection of individual confirmations.
ConfirmationAck	Confirmation	The Confirmation Ack (aka Affirmation) message is used to respond to a Confirmation message.
ConfirmationRequest	Confirmation	The Confirmation Request message is used to request a Confirmation message.
CrossOrderCancelReplaceRequest	CrossOrders	Used to modify a cross order previously submitted using the New Order - Cross message. See Order Cancel Replace Request for details concerning message usage.
CrossOrderCancelRequest	CrossOrders	Used to fully cancel the remaining open quantity of a cross order.
NewOrderCross	CrossOrders	Used to submit a cross order into a market. The cross order contains two order sides (a buy and a sell). The cross order is identified by its CrossID.
Email	EventCommunication	The email message is similar to the format and purpose of the News message, however, it is intended for private use between two parties.
News	EventCommunication	The news message is a general free format message between the broker and institution. The message contains flags to identify the news item's urgency and to allow sorting by subject company (symbol). The News message can be originated at either the broker or institution side, or exchanges and other marketplace venues.

Name	Category	Description
Advertisement	Indication	Advertisement messages are used to announce completed transactions. The advertisement message can be transmitted in various transaction types; NEW, CANCEL and REPLACE. All message types other than NEW modify the state of a previously transmitted advertisement identified in AdvRefID.
CrossRequest	Indication	The CrossRequest(35=DS) message is used to indicate the submission of orders or quotes that may result in a crossed trade.
CrossRequestAck	Indication	The CrossRequestAck(35=DT) message is used to confirm the receipt of a CrossRequest(35=DS) message.
IOI	Indication	Indication of interest messages are used to market merchandise which the broker is buying or selling in either a proprietary or agency capacity. The indications can be time bound with a specific expiration value. Indications are distributed with the understanding that other firms may react to the message first and that the merchandise may no longer be available due to prior trade.
MarginRequirementInquiry	MarginRequirementManagement	The purpose of this message is to initiate a margin requirement inquiry for a margin account. The inquiry may be submitted at the detail level or the summary level. It can also be used to inquire margin excess/deficit or net position information. Margin excess/deficit will provide information about the surplus or shortfall compared to the previous trading day or a more recent margin calculation. An inquiry for net position information will trigger one or more PositionReport messages instead of one or more MarginRequirementReport messages.
MarginRequirementInquiryAck	MarginRequirementManagement	Used to respond to a Margin Requirement Inquiry.



Name	Category	Description
MarginRequirementReport	MarginRequirementManagement	The Margin Requirement Report returns information about margin requirement either as an overview across all margin accounts or on a detailed level due to the inquiry making use of the optional Instrument component block. Application sequencing can be used to re-request a range of reports.
MarketDataIncrementalRefresh	MarketData	The Market Data message for incremental updates may contain any combination of new, changed, or deleted Market Data Entries, for any combination of instruments, with any combination of trades, imbalances, quotes, index values, open, close, settlement, high, low, and VWAP prices, trade volume and open interest so long as the maximum FIX message size is not exceeded. All of these types of Market Data Entries can be changed and deleted.
MarketDataReport	MarketData	The MarketDataReport(35=DR) message is used to provide delimiting references (e.g. start and end markers in a continuous broadcast) and details about the number of market data messages sent in a given distribution cycle.
MarketDataRequest	MarketData	Some systems allow the transmission of real-time quote, order, trade, trade volume, open interest, and/or other price information on a subscription basis. A MarketDataRequest(35=V) is a general request for market data on specific securities or forex quotes. The values in the fields provided within the request will serve as further filter criteria for the result set.

Name	Category	Description
MarketDataRequestReject	MarketData	The Market Data Request Reject is used when the broker cannot honor the Market Data Request, due to business or technical reasons. Brokers may choose to limit various parameters, such as the size of requests, whether just the top of book or the entire book may be displayed, and whether Full or Incremental updates must be used.
MarketDataSnapshotFullRefresh	MarketData	The Market Data messages are used as the response to a Market Data Request message. In all cases, one Market Data message refers only to one Market Data Request. It can be used to transmit a 2-sided book of orders or list of quotes, a list of trades, index values, opening, closing, settlement, high, low, or VWAP prices, the trade volume or open interest for a security, or any combination of these.
MarketDataStatisticsReport	MarketData	The MarketDataStatisticsReport(35=DP) is used to provide unsolicited statistical information or in response to a specific request. Each report contains a set of statistics for a single entity which could be a market, a market segment, a security list or an instrument.
MarketDataStatisticsRequest	MarketData	The MarketDataStatisticsRequest(35=DO) is used to request for statistical data. The simple form is to use an identifier (MDStatisticID(2475)) assigned by the market place which would denote a pre-defined statistical report. Alternatively, or also in addition, the request can define a number of parameters for the desired statistical information.

Name	Category	Description
StreamAssignmentReport	MarketData	The StreamAssignmentReport(35=CD) message is in response to the StreamAssignmentRequest(35=CC) message. It provides information back to the aggregator as to which clients to assign to receive which price stream based on requested CCY pair. This message can be sent unsolicited to the Aggregator from the Price Maker.
StreamAssignmentReportACK	MarketData	This message is used to respond to the Stream Assignment Report, to either accept or reject an unsolicited assignment.
StreamAssignmentRequest	MarketData	In certain markets where market data aggregators fan out to end clients the pricing streams provided by the price makers, the price maker may assign the clients to certain pricing streams that the price maker publishes via the aggregator. An example of this use is in the FX markets where clients may be assigned to different pricing streams based on volume bands and currency pairs.
MarketDefinition	MarketStructureReferenceData	The MarketDefinition(35=BU) message is used to respond to MarketDefinitionRequest(35=BT). In a subscription, it will be used to provide the initial snapshot of the information requested. Subsequent updates are provided by the MarketDefinitionUpdateReport(35=BV).
MarketDefinitionRequest	MarketStructureReferenceData	The Market Definition Request message is used to request for market structure information from the Respondent that receives this request.
MarketDefinitionUpdateReport	MarketStructureReferenceData	In a subscription for market structure information, this message is used once the initial snapshot of the information has been sent using the MarketDefinition(35=BU) message.

Name	Category	Description
TradingSessionList	MarketStructureReferenceData	The Trading Session List message is sent as a response to a Trading Session List Request. The Trading Session List should contain the characteristics of the trading session and the current state of the trading session.
TradingSessionListRequest	MarketStructureReferenceData	The Trading Session List Request is used to request a list of trading sessions available in a market place and the state of those trading sessions. A successful request will result in a response from the counterparty of a Trading Session List (MsgType=BJ) message that contains a list of zero or more trading sessions.
TradingSessionListUpdateReport	MarketStructureReferenceData	The Trading Session List Update Report is used by marketplaces to provide intra-day updates of trading sessions when there are changes to one or more trading sessions.
TradingSessionStatus	MarketStructureReferenceData	The Trading Session Status provides information on the status of a market. For markets multiple trading sessions on multiple-markets occurring (morning and evening sessions for instance), this message is able to provide information on what products are trading on what market during what trading session.
TradingSessionStatusRequest	MarketStructureReferenceData	The Trading Session Status Request is used to request information on the status of a market. With the move to multiple sessions occurring for a given trading party (morning and evening sessions for instance) there is a need to be able to provide information on what product is trading on what market.
MultilegOrderCancelReplace	MultilegOrders	Used to modify a multileg order previously submitted using the New Order - Multileg message. See Order Cancel Replace Request for details concerning message usage.

Name	Category	Description
NewOrderMultileg	MultilegOrders	The New Order - Multileg is provided to submit orders for securities that are made up of multiple securities, known as legs.
NetworkCounterpartySystemStatusRequest	Network	This message is send either immediately after logging on to inform a network (counterparty system) of the type of updates required or to at any other time in the FIX conversation to change the nature of the types of status updates required. It can also be used with a NetworkRequestType of Snapshot to request a one-off report of the status of a network (or counterparty) system. Finally this message can also be used to cancel a request to receive updates into the status of the counterparties on a network by sending a NetworkRequestStatusMessage with a NetworkRequestType of StopSubscribing.
NetworkCounterpartySystemStatusRespon	Network	This message is sent in response to a Network (Counterparty System) Status Request Message.
MassOrder	OrderMassHandling	The MassOrder(35=DJ) message can be used to add, modify or delete multiple unrelated orders with a single message. Apart from clearing related attributes, only the key order attributes for high performance trading are available.
MassOrderAck	OrderMassHandling	The mass order acknowledgement message is used to acknowledge the receipt of and the status for a MassOrder(35=DJ) message.
OrderMassActionReport	OrderMassHandling	The Order Mass Action Report is used to acknowledge an Order Mass Action Request. Note that each affected order that is suspended or released or canceled is acknowledged with a separate Execution Report for each order.

Name	Category	Description
OrderMassActionRequest	OrderMassHandling	The Order Mass Action Request message can be used to request the suspension or release of a group of orders that match the criteria specified within the request. This is equivalent to individual Order Cancel Replace Requests for each order with or without adding “S” to the ExecInst values. It can also be used for mass order cancellation.
OrderMassCancelReport	OrderMassHandling	The Order Mass Cancel Report is used to acknowledge an Order Mass Cancel Request. Note that each affected order that is canceled is acknowledged with a separate Execution Report or Order Cancel Reject message.
OrderMassCancelRequest	OrderMassHandling	The order mass cancel request message requests the cancellation of all of the remaining quantity of a group of orders matching criteria specified within the request. NOTE: This message can only be used to cancel order messages (reduce the full quantity).
OrderMassStatusRequest	OrderMassHandling	The order mass status request message requests the status for orders matching criteria specified within the request.
PartyActionReport	PartiesAction	Used to respond to the PartyActionRequest(35=DH) message, indicating whether the request has been received, accepted or rejected. Can also be used in an unsolicited manner to report party actions, e.g. reinstatements after a manual intervention out of band.
PartyActionRequest	PartiesAction	The PartyActionRequest message is used suspend or halt the specified party from further trading activities at the Respondent. The Respondent must respond with a PartyActionReport(35=DI) message.
PartyRiskLimitCheckRequest	PartiesAction	PartyRiskLimitCheckRequest is used to request for approval of credit or risk limit amount intended to be used by a party in a transaction from another party that holds the information.

Name	Category	Description
PartyRiskLimitCheckRequestAck	PartiesAction	PartyRiskLimitCheckRequestAck is used to acknowledge a PartyRiskLimitCheckRequest(35=DF) message and to respond whether the limit check request was approved or not. When used to accept the PartyRiskLimitCheckRequest(35=DF) message the Respondent may also include the limit amount that was approved.
PartyDetailsDefinitionRequest	PartiesReferenceData	The PartyDetailsDefinitionRequest(35=CX) is used for defining new parties and modifying or deleting existing parties information, including the relationships between parties.
PartyDetailsDefinitionRequestAck	PartiesReferenceData	The PartyDetailsDefinitionRequestAck(35=CY) is used as a response to the PartyDetailsDefinitionRequest(35=CX) message. The request can be accepted (with or without changes) or rejected.
PartyDetailsListReport	PartiesReferenceData	The PartyDetailsListReport message is used to disseminate party details between counterparties. PartyDetailsListReport messages may be sent in response to a PartyDetailsListRequest message or sent unsolicited.
PartyDetailsListRequest	PartiesReferenceData	The PartyDetailsListRequest is used to request party detail information.
PartyDetailsListUpdateReport	PartiesReferenceData	The PartyDetailsListUpdateReport(35=CK) is used to disseminate updates to party detail information.
PartyEntitlementsDefinitionRequest	PartiesReferenceData	The PartyEntitlementsDefinitionRequest(35=DA) is used for defining new entitlements, and modifying or deleting existing entitlements for the specified party(-ies).

Name	Category	Description
PartyEntitlementsDefinitionRequestAck	PartiesReferenceData	The PartyEntitlementsDefinitionRequestAck(35=DB) is used as a response to the PartyEntitlementsDefinitionRequest(35=DA) to accept (with or without changes) or reject the definition of party entitlements.
PartyEntitlementsReport	PartiesReferenceData	The PartyEntitlementsReport is used to report entitlements for one or more parties, party role(s), or specific instrument(s).
PartyEntitlementsRequest	PartiesReferenceData	The PartyEntitlementsRequest message is used to request for entitlement information for one or more party(-ies), specific party role(s), or specific instruments(s).
PartyEntitlementsUpdateReport	PartiesReferenceData	The PartyEntitlementsUpdateReport(35=CZ) is used to convey incremental changes to party entitlements. It is similar to the PartyEntitlementsReport(35=CV). This message uses the PartyEntitlementsUpdateGrp component which includes the ability to specify an update action using ListUpdateAction(1324).
PartyRiskLimitsDefinitionRequest	PartiesReferenceData	PartyRiskLimitDefinitionRequest is used for defining new risk limits.
PartyRiskLimitsDefinitionRequestAck	PartiesReferenceData	PartyRiskLimitDefinitionRequestAck is used for accepting (with or without changes) or rejecting the definition of risk limits.
PartyRiskLimitsReport	PartiesReferenceData	The PartyRiskLimitsReport message is used to communicate party risk limits. The message can either be sent as a response to the PartyRiskLimitsRequest message or can be published unsolicited.
PartyRiskLimitsReportAck	PartiesReferenceData	PartyRiskLimitsReportAck is an optional message used as a response to the PartyRiskLimitReport(35=CM) or PartyRiskLimitUpdateReport(35=CR) messages to acknowledge or reject those messages.



Name	Category	Description
PartyRiskLimitsRequest	PartiesReferenceData	The PartyRiskLimitsRequest message is used to request for risk information for specific parties, specific party roles or specific instruments.
PartyRiskLimitsUpdateReport	PartiesReferenceData	The PartyRiskLimitsUpdateReport(35=CR) is used to convey incremental changes to risk limits. It is similar to the regular report but uses the PartyRiskLimitsUpdateGrp component instead of the PartyRiskLimitsGrp component to include an update action.
PayManagementReport	PayManagement	PayManagementReport(35=EA) may be used to respond to the PayManagementRequest(35=DY) message. It provides the status of the request (e.g. accepted, disputed) and may provide additional information related to the request.
PayManagementReportAck	PayManagement	PayManagementReportAck(35=EB) is used as a response to the PayManagementReport(35=EA) message. It may be used to accept, reject or dispute the details of the PayManagementReport(35=EA) depending on the business rules of the receiver. This message may also be used to acknowledge the receipt of a PayManagementReport(35=EA) message.
PayManagementRequest	PayManagement	PayManagementRequest(35=DY) message is used to communicate a future or expected payment to be made or received related to a trade or contract after its settlement.
PayManagementRequestAck	PayManagement	PayManagementRequestAck(35=DZ) is used to acknowledge the receipt of the PayManagementRequest(35=DY) message (i.e. a technical acknowledgement of receipt). Acceptance or rejection of the request is reported in the corresponding PayManagementReport(35=EA).

Name	Category	Description
AdjustedPositionReport	PositionMaintenance	Used to report changes in position, primarily in equity options, due to modifications to the underlying due to corporate actions
AssignmentReport	PositionMaintenance	Assignment Reports are sent from a clearing house to counterparties, such as a clearing firm as a result of the assignment process.
ContraryIntentionReport	PositionMaintenance	The Contrary Intention Report is used for reporting of contrary expiration quantities for Saturday expiring options. This information is required by options exchanges for regulatory purposes.
PositionMaintenanceReport	PositionMaintenance	The Position Maintenance Report message is sent by the holder of a position in response to a Position Maintenance Request and is used to confirm that a request has been successfully processed or rejected.
PositionMaintenanceRequest	PositionMaintenance	The Position Maintenance Request message allows the position owner to submit requests to the holder of a position which will result in a specific action being taken which will affect the position. Generally, the holder of the position is a central counter party or clearing organization but can also be a party providing investment services.
PositionReport	PositionMaintenance	The Position Report message is returned by the holder of a position in response to a Request for Position message. The purpose of the message is to report all aspects of a position and may be provided on a standing basis to report end of day positions to an owner.
PositionTransferInstruction	PositionMaintenance	The PositionTransferInstruction(35=DL) is sent by clearing firms to CCPs to initiate position transfers, or to accept or decline position transfers.

Name	Category	Description
PositionTransferInstructionAck	PositionMaintenance	The PositionTransferInstructionAck(35=DM) is sent by CCPs to clearing firms to acknowledge position transfer instructions, and to report errors processing position transfer instructions.
PositionTransferReport	PositionMaintenance	The PositionTransferReport(35=DN) is sent by CCPs to clearing firms indicating of positions that are to be transferred to the clearing firm, or to report on status of the transfer to the clearing firms involved in the transfer process.
RequestForPositions	PositionMaintenance	The Request For Positions message is used by the owner of a position to request a Position Report from the holder of the position, usually the central counter party or clearing organization. The request can be made at several levels of granularity.
RequestForPositionsAck	PositionMaintenance	The Request for Positions Ack message is returned by the holder of the position in response to a Request for Positions message. The purpose of the message is to acknowledge that a request has been received and is being processed.
BidRequest	ProgramTrading	The BidRequest Message can be used in one of two ways depending on which market conventions are being followed.
BidResponse	ProgramTrading	The Bid Response message can be used in one of two ways depending on which market conventions are being followed.
ListCancelRequest	ProgramTrading	The List Cancel Request message type is used by institutions wishing to cancel previously submitted lists either before or during execution.
ListExecute	ProgramTrading	The List Execute message type is used by institutions to instruct the broker to begin execution of a previously submitted list. This message may or may not be used, as it may be mirroring a phone conversation.

Name	Category	Description
ListStatus	ProgramTrading	The list status message is issued as the response to a List Status Request message sent in an unsolicited fashion by the sell-side. It indicates the current state of the orders within the list as they exist at the broker's site. This message may also be used to respond to the List Cancel Request.
ListStatusRequest	ProgramTrading	The list status request message type is used by institutions to instruct the broker to generate status messages for a list.
ListStrikePrice	ProgramTrading	The strike price message is used to exchange strike price information for principal trades. It can also be used to exchange reference prices for agency trades.
NewOrderList	ProgramTrading	The NewOrderList Message can be used in one of two ways depending on which market conventions are being followed.
MassQuote	QuotationNegotiation	The Mass Quote message can contain quotes for multiple securities to support applications that allow for the mass quoting of an option series. Two levels of repeating groups have been provided to minimize the amount of data required to submit a set of quotes for a class of options (e.g. all option series for IBM).
MassQuoteAck	QuotationNegotiation	Mass Quote Acknowledgement is used as the application level response to a Mass Quote message.
Quote	QuotationNegotiation	The Quote message is used as the response to a Quote Request or a Quote Response message in both indicative, tradeable, and restricted tradeable quoting markets.
QuoteAck	QuotationNegotiation	The QuoteAck(35=CW) message is used to acknowledge a Quote(35=S) submittal or request to cancel an individual quote using the QuoteCancel(35=Z) message during a Quote/Negotiation dialog.
QuoteCancel	QuotationNegotiation	The Quote Cancel message is used by an originator of quotes to cancel quotes.

Name	Category	Description
QuoteRequest	QuotationNegotiation	In some markets it is the practice to request quotes from brokers prior to placement of an order. The quote request message is used for this purpose. This message is commonly referred to as an Request For Quote (RFQ)
QuoteRequestReject	QuotationNegotiation	The Quote Request Reject message is used to reject Quote Request messages for all quoting models.
QuoteResponse	QuotationNegotiation	The QuoteResponse(35=AJ) message is used for the following purposes:
QuoteStatusReport	QuotationNegotiation	The quote status report message is used:
QuoteStatusRequest	QuotationNegotiation	The quote status request message is used for the following purposes in markets that employ tradeable or restricted tradeable quotes:
RFQRequest	QuotationNegotiation	In tradeable and restricted tradeable quoting markets – Quote Requests are issued by counterparties interested in ascertaining the market for an instrument. Quote Requests are then distributed by the market to liquidity providers who make markets in the instrument. The RFQ Request is used by liquidity providers to indicate to the market for which instruments they are interested in receiving Quote Requests. It can be used to register interest in receiving quote requests for a single instrument or for multiple instruments
RegistrationInstructions	RegistrationInstruction	The Registration Instructions message type may be used by institutions or retail intermediaries wishing to electronically submit registration information to a broker or fund manager (for CIV) for an order or for an allocation.

Name	Category	Description
RegistrationInstructionsResponse	RegistrationInstruction	The Registration Instructions Response message type may be used by broker or fund manager (for CIV) in response to a Registration Instructions message submitted by an institution or retail intermediary for an order or for an allocation.
DerivativeSecurityList	SecuritiesReferenceData	The Derivative Security List message is used to return a list of securities that matches the criteria specified in a Derivative Security List Request.
DerivativeSecurityListRequest	SecuritiesReferenceData	The Derivative Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request
DerivativeSecurityListUpdateReport	SecuritiesReferenceData	The Derivative Security List Update Report message is used to send updates to an option family or the strikes that comprise an option family.
SecurityDefinition	SecuritiesReferenceData	The SecurityDefinition(35=d) message is used for the following:
SecurityDefinitionRequest	SecuritiesReferenceData	The SecurityDefinitionRequest(35=c) message is used for the following:
SecurityDefinitionUpdateReport	SecuritiesReferenceData	This message is used for reporting updates to a product security master file. Updates could be the result of corporate actions or other business events. Updates may include additions, modifications or deletions.
SecurityList	SecuritiesReferenceData	The Security List message is used to return a list of securities that matches the criteria specified in a Security List Request.
SecurityListRequest	SecuritiesReferenceData	The Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request

Name	Category	Description
SecurityListUpdateReport	SecuritiesReferenceData	The Security List Update Report is used for reporting updates to a Contract Security Masterfile. Updates could be due to Corporate Actions or other business events. Update may include additions, modifications and deletions.
SecurityMassStatus	SecuritiesReferenceData	
SecurityMassStatusRequest	SecuritiesReferenceData	
SecurityRiskMetricsReport	SecuritiesReferenceData	SecurityRiskMetricsReport(35=EG) is used for publishing the risk metrics, valuation metrics or analytics of one or more securities, or for an option series.
SecurityStatus	SecuritiesReferenceData	The Security Status message provides for the ability to report changes in status to a security. The Security Status message contains fields to indicate trading status, corporate actions, financial status of the company. The Security Status message is used by one trading entity (for instance an exchange) to report changes in the state of a security.
SecurityStatusRequest	SecuritiesReferenceData	The Security Status Request message provides for the ability to request the status of a security. One or more Security Status messages are returned as a result of a Security Status Request message.
SecurityTypeRequest	SecuritiesReferenceData	The Security Type Request message is used to return a list of security types available from a counterparty or market.
SecurityTypes	SecuritiesReferenceData	The Security Type Request message is used to return a list of security types available from a counterparty or market.
Heartbeat	Session	The Heartbeat monitors the status of the communication link and identifies when the last of a string of messages was not received.
Logon	Session	The logon message authenticates a user establishing a connection to a remote system. The logon message must be the first message sent by the application requesting to initiate a FIX session.

Name	Category	Description
Logout	Session	The logout message initiates or confirms the termination of a FIX session. Disconnection without the exchange of logout messages should be interpreted as an abnormal condition.
Reject	Session	The reject message should be issued when a message is received but cannot be properly processed due to a session-level rule violation. An example of when a reject may be appropriate would be the receipt of a message with invalid basic data which successfully passes de-encryption, CheckSum and BodyLength checks.
ResendRequest	Session	The resend request is sent by the receiving application to initiate the retransmission of messages. This function is utilized if a sequence number gap is detected, if the receiving application lost a message, or as a function of the initialization process.
SequenceReset	Session	The sequence reset message is used by the sending application to reset the incoming sequence number on the opposing side.
TestRequest	Session	The test request message forces a heartbeat from the opposing application. The test request message checks sequence numbers or verifies communication line status. The opposite application responds to the Test Request with a Heartbeat containing the TestReqID.
XMLnonFIX	Session	
SettlementInstructionRequest	SettlementInstruction	The Settlement Instruction Request message is used to request standing settlement instructions from another party.



Name	Category	Description
SettlementInstructions	SettlementInstruction	The Settlement Instructions message provides the broker's, the institution's, or the intermediary's instructions for trade settlement. This message has been designed so that it can be sent from the broker to the institution, from the institution to the broker, or from either to an independent "standing instructions" database or matching system or, for CIV, from an intermediary to a fund manager.
SettlementObligationReport	SettlementInstruction	The Settlement Obligation Report message provides a central counterparty, institution, or individual counterparty with a capacity for reporting the final details of a currency settlement obligation.
SettlementStatusReport	SettlementStatusManagement	SettlementStatusReport(35=EE) is a response to the SettlementStatusRequest(35=EC) to provide settlement status for the requested trade. It may also be sent unsolicited without an explicit request message by the party able to provide the settlement status for the trade identified in the report message.
SettlementStatusReportAck	SettlementStatusManagement	SettlementStatusReportAck(35=EF) is used to respond to the SettlementStatusReport(35=EE) to acknowledge or reject the report.
SettlementStatusRequest	SettlementStatusManagement	SettlementStatusRequest(35=EC) is used to request for the settlement status of a trade.
SettlementStatusRequestAck	SettlementStatusManagement	SettlementStatusRequestAck(35=ED) is used to respond to the SettlementStatusRequest(35=EC) to acknowledge the request and provide status for the request message.
DontKnowTrade	SingleGeneralOrderHandling	The Don't Know Trade (DK) message notifies a trading partner that an electronically received execution has been rejected. This message can be thought of as an execution reject message.

Name	Category	Description
ExecutionAck	SingleGeneralOrderHandling	The Execution Report Acknowledgement message is an optional message that provides dual functionality to notify a trading partner that an electronically received execution has either been accepted or rejected (DK'd).
ExecutionReport	SingleGeneralOrderHandling	The execution report message is used to:
NewOrderSingle	SingleGeneralOrderHandling	The new order message type is used by institutions wishing to electronically submit securities and forex orders to a broker for execution.
OrderCancelReject	SingleGeneralOrderHandling	The order cancel reject message is issued by the broker upon receipt of a cancel request or cancel/replace request message which cannot be honored.
OrderCancelReplaceRequest	SingleGeneralOrderHandling	The order cancel/replace request is used to change the parameters of an existing order.
OrderCancelRequest	SingleGeneralOrderHandling	The order cancel request message requests the cancellation of all of the remaining quantity of an existing order. Note that the Order Cancel/Replace Request should be used to partially cancel (reduce) an order).
OrderStatusRequest	SingleGeneralOrderHandling	The order status request message is used by the institution to generate an order status message back from the broker.
AlgoCertificateReport	Testing	AlgoCertificateReport(35=EJ) is a response to the AlgoCertificateRequest(35=EH) to certify an algo. It may also be sent unsolicited without an explicit request message by the party able to provide certificate information for the algo identified in the report message.
AlgoCertificateReportAck	Testing	AlgoCertificateReportAck(35=EK) is used to respond to the AlgoCertificateReport(35=EJ) to acknowledge or reject the report message.

Name	Category	Description
AlgoCertificateRequest	Testing	AlgoCertificateRequest(35=EH) is used to request algo testing certificate information for one or more algorithms.
AlgoCertificateRequestAck	Testing	AlgoCertificateRequestAck(35=EI) is used to respond to the AlgoCertificateRequest(35=EH) to acknowledge the request and provide status for the request message.
TestActionReport	Testing	TestActionReport(35=EP) is used to report the testing results of the identified test suite that has been executed with TestActionRequest(35=EN). In the context of algorithmic trading, the results may be used to create a certificate for the algorithm upon meeting the success criteria.
TestActionRequest	Testing	TestActionRequest(35=EN) is used to manage test executions or request for testing activity state of the identified test suite.
TestActionRequestAck	Testing	TestActionRequestAck(35=EO) is used to respond to the TestActionRequest(35=EN) to acknowledge the request and provide status for the request message.
TestSuiteDefinitionRequest	Testing	TestSuiteDefinitionRequest(35=EL) is used to convey to the test system the suite of test scenarios to perform.
TestSuiteDefinitionRequestAck	Testing	TestSuiteDefinitionRequestAck(35=EM) is used to respond to the TestSuiteDefinitionRequest(35=EL) to acknowledge the request and provide status for the request message.
TradeCaptureReport	TradeCapture	The Trade Capture Report message can be:
TradeCaptureReportAck	TradeCapture	The Trade Capture Report Ack message can be:
TradeCaptureReportRequest	TradeCapture	The Trade Capture Report Request can be used to:
TradeCaptureReportRequestAck	TradeCapture	The Trade Capture Request Ack message is used to:

Name	Category	Description
TradeMatchReport	TradeCapture	The TradeMatchReport(35=DC) message is used by exchanges and ECN's to report matched trades to central counterparties (CCPs) as an atomic event. The message is used to express the one-to-one, one-to-many and many-to-many matches as well as implied matches in which more complex instruments can match with simpler instruments.
TradeMatchReportAck	TradeCapture	The TradeMatchReportAck(35=DD) is used to respond to theTradeMatchReport(35=DC) message. It may be used to report on the status of the request (e.g. accepting the request or rejecting the request).
TradeAggregationReport	TradeManagement	TradeAggregationReport(35=DX) is used to respond to the TradeAggregationRequest(35=DW) message. It provides the status of the request (e.g. accepted or rejected) and may also provide additional information supplied by the respondent.
TradeAggregationRequest	TradeManagement	TradeAggregationRequest(35=DW) is used to request that the identified trades between the initiator and respondent be aggregated together for further processing.
UserNotification	UserManagement	The User Notification message is used to notify one or more users of an event or information from the sender of the message. This message is usually sent unsolicited from a marketplace (e.g. Exchange, ECN) to a market participant.
UserRequest	UserManagement	This message is used to initiate a user action, logon, logout or password change. It can also be used to request a report on a user's status.

**UserResponse****UserManagement**

This message is used to respond to a user request message, it reports the status of the user after the completion of any action requested in the user request message.

---

## 2 AccountSummaryReport

Category: AccountReporting

### 2.1 Message Functionality

The AccountSummaryReport is provided by the clearinghouse to its clearing members on a daily basis. It contains margin, settlement, collateral and pay/collect data for each clearing member level account type. Clearing member account types will be described through use of the Parties component and PtysSubGrp sub-component.

In certain usages, the clearing members can send the AccountSummaryReport message to the clearinghouse as needed. For example, clearing members can send this message to the clearinghouse to identify the value of collateral for each customer (to satisfy CFTC Legally Segregated Operationally Commingled (LSOC) regulatory reporting obligations).

Clearing organizations can also send the AccountSummaryReport message to regulators to meet regulatory reporting obligations. For example, clearing organizations can use this message to submit daily reports for each clearing member ("CM") by house origin and by each customer origin for all futures, options, and swaps positions, and all securities positions held in a segregated account or pursuant to a cross margining agreement, to a regulator (e.g. to the CFTC to meet Part 39, Section 39.19 reporting obligations).

### 2.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CQ
ApplicationSequenceControl	[0..1]	Component	
AccountSummaryReportID	[1..1]	String	
ClearingBusinessDate	[1..1]	LocalMktDate	
Currency	[0..1]	Currency	Identifies the base reporting currency used in this report.
TotalNetValue	[0..1]	Amt	
MarginExcess	[0..1]	Amt	
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
TransactTime	[0..1]	UTCTimestamp	

Name	Mult.	Type	Description
SettlementAmountGrp	[0..*]	Group	
MarginAmount	[0..*]	Group	
Parties	[1..*]	Group	Used to identify the parties for the account (clearing organization, clearing firm, account type, etc.)
CollateralAmountGrp	[0..*]	Group	
PayCollectGrp	[0..*]	Group	
PositionAmountData	[0..*]	Group	Can be used to identify mark to market information for the position.
StandardTrailer	[0..1]	Component	

### 3 AdjustedPositionReport

Category: PositionMaintenance

#### 3.1 Message Functionality

Used to report changes in position, primarily in equity options, due to modifications to the underlying due to corporate actions

#### 3.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BL
PosMaintRptID	[1..1]	String	Unique identifier for this Adjusted Position report
PosReqType	[0..1]	CodeSet	
ClearingBusinessDate	[1..1]	LocalMktDate	The Clearing Business Date referred to by this maintenance request
SettlSessID	[0..1]	CodeSet	
PosMaintRptRefID	[0..1]	String	
Parties	[1..*]	Group	Position Account
PositionQty	[1..*]	Group	Insert here here the set of "Position Qty" fields defined in "Common Components of Application Messages"
InstrmtGrp	[0..*]	Group	
SettlPrice	[0..1]	Price	Settlement Price
PriorSettlPrice	[0..1]	Price	Prior Settlement Price
StandardTrailer	[1..1]	Component	



## 4 Advertisement

Category: Indication

### 4.1 Message Functionality

Advertisement messages are used to announce completed transactions. The advertisement message can be transmitted in various transaction types; NEW, CANCEL and REPLACE. All message types other than NEW modify the state of a previously transmitted advertisement identified in AdvRefID.

### 4.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 7
AdvId	[1..1]	String	
AdvTransType	[1..1]	CodeSet	
AdvRefID	[0..1]	String	Required for Cancel and Replace AdvTransType messages
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
InstrmtLegGrp	[0..*]	Group	Number of legs. Identifies a Multi-leg Execution if present and non-zero.
UndInstrmtGrp	[0..*]	Group	Number of underlyings
RelatedInstrumentGrp	[0..*]	Group	
AdvSide	[1..1]	CodeSet	
Quantity	[1..1]	Qty	
QtyType	[0..1]	CodeSet	
Price	[0..1]	Price	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
TradeDate	[0..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	

Name	Mult.	Type	Description
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
URLLink	[0..1]	String	A URL (Uniform Resource Locator) link to additional information (i.e. <a href="http://www.XYZ.com/research.html">http://www.XYZ.com/research.html</a> )
LastMkt	[0..1]	Exchange	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
RoutingGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 5 AlgoCertificateReport

Category: Testing

### 5.1 Message Functionality

AlgoCertificateReport(35=EJ) is a response to the AlgoCertificateRequest(35=EH) to certify an algo. It may also be sent unsolicited without an explicit request message by the party able to provide certificate information for the algo identified in the report message.

### 5.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EJ
AlgoCertificateReportID	[1..1]	String	Unique identifier assigned by sender of this message.
AlgoCertificateRequestID	[0..1]	String	Identifier of the AlgoCertificateRequest(35=EH) this message is responding to.
AlgoCertificateReportTransType	[1..1]	CodeSet	
AlgoCertificateReportType	[0..1]	CodeSet	
AlgoCertificateReportRefID	[0..1]	String	Required for AlgoCertificateReportTransType(3020)=1 (Cancel) or 2 (Replace).
AlgoCertificateID	[1..1]	String	
AlgoCertificateDesc	[0..1]	String	
AlgoCertificateStatus	[1..1]	CodeSet	
Parties	[1..*]	Group	Required to specify the algo for which a certification is reported and the firm using it. Requires the authorized person for AlgoCertificateStatus(3022)=1 (Approved) or 2 (Submitted).
EffectiveTime	[0..1]	UTCTimestamp	Required for AlgoCertificateStatus(3022)=1 (Approved) or 2 (Submitted).
ApprovalTime	[0..1]	UTCTimestamp	Required for AlgoCertificateStatus(3022)=1 (Approved) or 2 (Submitted).
LastUpdateTime	[1..1]	UTCTimestamp	
TransactTime	[0..1]	UTCTimestamp	

Name	Mult.	Type	Description
AlgoTestDesc	[0..1]	String	Required for AlgoCertificateStatus(3022)=1 (Approved) or 2 (Submitted).
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StrategyParametersGrp	[0..*]	Group	
AlgoSystemModuleGrp	[0..*]	Group	
TestScenarioGrp	[0..*]	Group	
TestSuiteStatus	[0..1]	CodeSet	Overall status across all individual test scenarios defined in TestScenarioGrp.
StandardTrailer	[1..1]	Component	

## 6 AlgoCertificateReportAck

Category: Testing

### 6.1 Message Functionality

AlgoCertificateReportAck(35=EK) is used to respond to the AlgoCertificateReport(35=EJ) to acknowledge or reject the report message.

### 6.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EK
AlgoCertificateReportID	[1..1]	String	Identifier of report message assigned by report sender.
AlgoCertificateReportStatus	[1..1]	CodeSet	
AlgoCertificateReportType	[0..1]	CodeSet	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 7 AlgoCertificateRequest

Category: Testing

### 7.1 Message Functionality

AlgoCertificateRequest(35=EH) is used to request algo testing certificate information for one or more algorithms.

### 7.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EH
AlgoCertificateRequestID	[1..1]	String	Unique identifier assigned by request initiator.
AlgoCertificateRequestTransType	[1..1]	CodeSet	
AlgoCertificateRequestType	[1..1]	CodeSet	
AlgoCertificateRequestRefID	[0..1]	String	Required for AlgoCertificateRequestTransType(3016)=1 (Cancel) or 2 (Replace).
AlgoCertificateID	[0..1]	String	May be used when the certificate identifier is already known to the requesting party. Conditionally required when AlgoCertificateRequestType(3077)=2 (Change certificate status) or 3 (Forward certificate).
AlgoCertificateDesc	[0..1]	String	
AlgoCertificateStatus	[0..1]	CodeSet	May be used to change the status of the certificate.
Parties	[0..*]	Group	May be used to specify the algos and/or venues subject to the request identified by AlgoCertificateRequestType(3077).
TargetParties	[0..*]	Group	May be used to identify a venue to send the certificate to. Requires AlgoCertificateRequestType(3077)=3 (Forward certificate).
TestScenarioGroupID	[0..1]	String	May be used to reference a group of test scenarios to be included in the certificate. Requires AlgoCertificateRequestType(3077)=1 (Generate certificate).

Name	Mult.	Type	Description
TestScenarioGrp	[0..*]	Group	May be used to provide details for the test scenarios to be included in the certificate. Requires AlgoCertificateRequestType(3077)=1 (Generate certificate).
EffectiveTime	[0..1]	UTCTimestamp	May be used to provide the activation time of the certificate to the test system.
ApprovalTime	[0..1]	UTCTimestamp	May be used to provide the approval time of the certificate to the test system.
TransactTime	[1..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 8 AlgoCertificateRequestAck

Category: Testing

### 8.1 Message Functionality

AlgoCertificateRequestAck(35=EI) is used to respond to the AlgoCertificateRequest(35=EH) to acknowledge the request and provide status for the request message.

### 8.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EI
AlgoCertificateRequestID	[1..1]	String	Identifier of request assigned by request initiator.
AlgoCertificateRequestType	[1..1]	CodeSet	
AlgoCertificateRequestStatus	[1..1]	CodeSet	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	



## 9 AllocationInstruction

Category: Allocation

### 9.1 Message Functionality

The AllocationInstruction(35=J) message provides the ability to specify how an order or set of orders should be subdivided amongst one or more accounts.

### 9.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = J
AllocID	[1..1]	String	Unique identifier for this allocation instruction message
AllocRequestID	[0..1]	String	May be used to link to a previously submitted AllocationInstructionAlertRequest(35=DU) message.
AllocTransType	[1..1]	CodeSet	
AllocType	[1..1]	CodeSet	Specifies the purpose or type of Allocation message
SecondaryAllocID	[0..1]	String	Optional second identifier for this allocation instruction (need not be unique)
RefAllocID	[0..1]	String	Required for AllocTransType = Replace or Cancel
AllocCancReplaceReason	[0..1]	CodeSet	Required for AllocTransType = Replace or Cancel. Gives the reason for replacing or cancelling the allocation instruction
AllocIntermedReqType	[0..1]	CodeSet	Required if AllocType = 8 (Request to Intermediary). Indicates status that is requested to be transmitted to counterparty by the intermediary (i.e. clearing house)
AllocLinkID	[0..1]	String	Can be used to link two different Allocation messages (each with unique AllocID) together, i.e. for F/X "Netting" or "Swaps"
AllocLinkType	[0..1]	CodeSet	Can be used to link two different Allocation messages and identifies the type of link. Required if AllocLinkID is specified.
AllocGroupID	[0..1]	String	Group identifier assigned by the clearinghouse

Name	Mult.	Type	Description
FirmGroupID	[0..1]	String	Group identifier assigned by the firm.
BookingRefID	[0..1]	String	Can be used with AllocType=" Ready-To-Book "
AllocNoOrdersType	[0..1]	CodeSet	Indicates how the orders being booked and allocated by an AllocationInstruction or AllocationReport message are identified, e.g. by explicit definition in the OrdAllocGrp or ExecAllocGrp components, or not identified explicitly.
OrdAllocGrp	[0..*]	Group	Indicates number of orders to be combined for allocation. If order(s) were manually delivered set to 1 (one). Required when AllocNoOrdersType = 1
ExecAllocGrp	[0..*]	Group	Indicates number of individual execution or trade entries. Absence indicates that no individual execution or trade entries are included. Primarily used to support step-outs.
PreviouslyReported	[0..1]	CodeSet	
ReversalIndicator	[0..1]	Boolean	
MatchType	[0..1]	CodeSet	
Side	[1..1]	CodeSet	
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". For NDFs fixing date and time can be optionally specified using MaturityDate and MaturityTime.
InstrumentExtension	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "Common Components of Application Messages"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
Quantity	[1..1]	Qty	Total quantity (e.g. number of shares) allocated to all accounts, or that is Ready-To-Book
QtyType	[0..1]	CodeSet	
AllocGroupSubQtyID	[0..1]	String	May be used as an alternative to attribute based subgrouping.
LastMkt	[0..1]	Exchange	Market of the executions.
TradeOriginationDate	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
AvgPx	[0..1]	Price	For FX orders, should be the "all-in" rate (spot rate adjusted for forward points), expressed in terms of Currency(15). For 3rd party allocations used to convey either basic price or averaged price. Optional for average price allocations in the listed derivatives markets where the central counterparty calculates and manages average price across an allocation group.
AvgParPx	[0..1]	Price	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
Currency	[0..1]	Currency	Currency of AvgPx. Should be the currency of the local market or exchange where the trade was conducted.
CurrencyCodeSource	[0..1]	CodeSet	
AvgPxPrecision	[0..1]	int	Absence of this field indicates that default precision arranged by the broker/institution is to be used
OffshoreIndicator	[0..1]	CodeSet	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TradeDate	[1..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	Date/time when allocation is generated
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values. Required for NDFs to specify the "value date".
BookingType	[0..1]	CodeSet	Method for booking. Used to provide notification that this is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.

Name	Mult.	Type	Description
GrossTradeAmt	[0..1]	Amt	Expressed in same currency as AvgPx(6). (Quantity(53) * AvgPx(6) or AvgParPx(860)) or sum of (AllocQty(80) * AllocAvgPx(153) or AllocPrice(366)). For Fixed Income, AvgParPx(860) is used when AvgPx(6) is not expressed as "percent of par" price.
Concession	[0..1]	Amt	
TotalTakedown	[0..1]	Amt	
NetMoney	[0..1]	Amt	Expressed in same currency as AvgPx. Sum of AllocNetMoney. For FX, if specified, expressed in terms of Currency(15).
PositionEffect	[0..1]	CodeSet	
AutoAcceptIndicator	[0..1]	Boolean	Indicates if Allocation has been automatically accepted on behalf of the Take-up Firm by the Clearing House
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
NumDaysInterest	[0..1]	int	Applicable for Convertible Bonds and fixed income
AccruedInterestRate	[0..1]	Percentage	Applicable for Convertible Bonds and fixed income
AccruedInterestAmt	[0..1]	Amt	Applicable for Convertible Bonds and fixed income
TotalAccruedInterestAmt	[0..1]	Amt	
InterestAtMaturity	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	For repurchase agreements the accrued interest on termination.
StartCash	[0..1]	Amt	For repurchase agreements the start (dirty) cash consideration
EndCash	[0..1]	Amt	For repurchase agreements the end (dirty) cash consideration
LegalConfirm	[0..1]	CodeSet	
Stipulations	[0..*]	Group	
YieldData	[0..1]	Component	
RegulatoryTradeIDGrp	[0..*]	Group	
TrdRegTimestamps	[0..*]	Group	

Name	Mult.	Type	Description
PositionAmountData	[0..*]	Group	Insert here the set of "Position Amount Data" fields defined in "Common Components of Application Messages"
TotNoAllocs	[0..1]	int	Indicates total number of allocation groups (used to support fragmentation). Must equal the sum of all NoAllocs values across all message fragments making up this allocation instruction. Only required where message has been fragmented.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
AllocGrp	[0..*]	Group	Conditionally required except when AllocTransType(71) = 2 (Cancel), or when AllocType(626) = 5 (Ready-To-Book single order) or 7 (Warehouse instruction).
AvgPxIndicator	[0..1]	CodeSet	Indicates if an allocation is to be average priced. Is also used to indicate if average price allocation group is complete or incomplete.
AvgPxGroupID	[0..1]	String	Firm designated group identifier for average pricing
ClearingBusinessDate	[0..1]	LocalMktDate	Indicates Clearing Business Date for which transaction will be settled.
TrdType	[0..1]	CodeSet	Indicates trade type of allocation. May be used as an alternative to AllocGroupSubQtyID(2974) for subgrouping.
TrdSubType	[0..1]	CodeSet	Indicates trade subtype of allocation.
SecondaryTrdType	[0..1]	CodeSet	
TertiaryTrdType	[0..1]	CodeSet	
TradePublishIndicator	[0..1]	CodeSet	May be used as an alternative to AllocGroupSubQtyID(2974) for subgrouping.
CustOrderHandlingInst	[0..1]	CodeSet	May be used as an alternative to AllocGroupSubQtyID(2974) for subgrouping.
TradeContinuation	[0..1]	CodeSet	
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
CustOrderCapacity	[0..1]	CodeSet	Indicates CTI of original trade marked for allocation.
TradeInputSource	[0..1]	String	Indicates input source of original trade marked for allocation.
MultiLegReportingType	[0..1]	CodeSet	Indicates MultiLegReportType of original trade marked for allocation.
MessageEventSource	[0..1]	String	Used to identify the event or source which gave rise to a message.
RndPx	[0..1]	Price	Specifies the rounded price to quoted precision.
RateSource	[0..*]	Group	
VenueType	[0..1]	CodeSet	Used to identify on what kind of venue the trade originated when communicating with a party that may not have access to all trade details, e.g. a clearing organization.
RefRiskLimitCheckID	[0..1]	String	Conditionally required when RefRiskLimitCheckIDType(2335) is specified.
RefRiskLimitCheckIDType	[0..1]	CodeSet	Conditionally required when RefRiskLimitCheckID(2334) is specified.
RiskLimitCheckStatus	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 10 AllocationInstructionAck

Category: Allocation

### 10.1 Message Functionality

In versions of FIX prior to version 4.4, this message was known as the Allocation ACK message.

The Allocation Instruction Ack message is used to acknowledge the receipt of and provide status for an Allocation Instruction message.

### 10.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = P
AllocID	[1..1]	String	
AllocRequestID	[0..1]	String	May be used to link to a previously submitted AllocationInstructionAlertRequest(35=DU) message.
Instrument	[0..1]	Component	
Parties	[0..*]	Group	
SecondaryAllocID	[0..1]	String	Optional second identifier for the allocation instruction being acknowledged (need not be unique)
AllocGroupID	[0..1]	String	Group identifier assigned by the clearinghouse
FirmGroupID	[0..1]	String	Firm assigned entity identifier for the allocation
AvgPxGroupID	[0..1]	String	Firm designated group identifier for average pricing
TradeDate	[0..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	Date/Time Allocation Instruction Ack generated
AllocStatus	[1..1]	CodeSet	Denotes the status of the allocation instruction; received (but not yet processed), rejected (at block or account level) or accepted (and processed).
AllocRejCode	[0..1]	CodeSet	Required for AllocStatus = 1 ( block level reject) and for AllocStatus 2 (account level reject) if the individual accounts and reject reasons are not provided in this message
AllocType	[0..1]	CodeSet	

Name	Mult.	Type	Description
AllocIntermedReqType	[0..1]	CodeSet	Required if AllocType = 8 (Request to Intermediary). Indicates status that is requested to be transmitted to counterparty by the intermediary (i.e. clearing house)
MatchStatus	[0..1]	CodeSet	Denotes whether the financial details provided on the Allocation Instruction were successfully matched.
Text	[0..1]	String	Can include explanation for AllocRejCode = 7 (other)
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
RegulatoryTradeIDGrp	[0..*]	Group	
AllocAckGrp	[0..*]	Group	This repeating group is optionally used for messages with AllocStatus = 2 (account level reject) to provide details of the individual accounts that caused the rejection, together with reject reasons. This group should not be populated when AllocStatus has any other value. Indicates number of allocation groups to follow.
StandardTrailer	[1..1]	Component	



## 11 AllocationInstructionAlert

Category: Allocation

### 11.1 Message Functionality

This message is used in a 3-party allocation model (buy-side and sell-side using a central clearing entity) where notification of group creation and group updates to counterparties is needed. The message will also carry trade information that comprised the group to the counterparties.

### 11.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BM
AllocID	[1..1]	String	Unique identifier for this allocation instruction alert message
AllocTransType	[1..1]	CodeSet	
AllocType	[1..1]	CodeSet	Specifies the purpose or type of Allocation message
AllocRequestID	[0..1]	String	Identifier of the request this message is responding to when responding to an AllocationInstructionAlertRequest(35=DU).
SecondaryAllocID	[0..1]	String	Optional second identifier for this allocation instruction (need not be unique)
RefAllocID	[0..1]	String	Required for AllocTransType = Replace or Cancel
AllocCancReplaceReason	[0..1]	CodeSet	Required for AllocTransType = Replace or Cancel. Gives the reason for replacing or cancelling the allocation instruction
AllocIntermedReqType	[0..1]	CodeSet	Required if AllocType = 8 (Request to Intermediary). Indicates status that is requested to be transmitted to counterparty by the intermediary (i.e. clearing house)
AllocLinkID	[0..1]	String	Can be used to link two different Allocation messages (each with unique AllocID) together, i.e. for F/X "Netting" or "Swaps"
AllocLinkType	[0..1]	CodeSet	Can be used to link two different Allocation messages and identifies the type of link. Required if AllocLinkID is specified.

Name	Mult.	Type	Description
AllocGroupID	[0..1]	String	Group identifier assigned by the clearinghouse
FirmGroupID	[0..1]	String	Firm assigned entity identifier for the allocation
BookingRefID	[0..1]	String	Can be used with AllocType=" Ready-To-Book "
AllocNoOrdersType	[0..1]	CodeSet	Indicates how the orders being booked and allocated by an Allocation Instruction or Allocation Report message are identified, e.g. by explicit definition in the OrdAllocGrp or ExecAllocGrp components , or not identified explicitly.
OrdAllocGrp	[0..*]	Group	Indicates number of orders to be combined for allocation. If order(s) were manually delivered set to 1 (one).Required when AllocNoOrdersType = 1
ExecAllocGrp	[0..*]	Group	Indicates number of individual execution or trade entries. Absence indicates that no individual execution or trade entries are included. Primarily used to support step-outs.
PreviouslyReported	[0..1]	CodeSet	
ReversalIndicator	[0..1]	Boolean	
MatchType	[0..1]	CodeSet	
Side	[1..1]	CodeSet	
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "common components of application messages"
InstrumentExtension	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "common components of application messages"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "common components of application messages"
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	

Name	Mult.	Type	Description
Quantity	[0..1]	Qty	When not using allocation groups, this is the total quantity (e.g. number of shares) allocated to all accounts, or that is Ready-To-Book. When using allocation groups, this is the quantity added or removed when trades are added to or removed from an allocation group. To remove quantity from the allocation group a negative value is specified in Quantity(53). When the allocation group quantity is unchanged, such as when AllocType(626) changes from 12(Incomplete group) to 13(Complete group) , the value for Quantity(53) should be zero (0).
QtyType	[0..1]	CodeSet	
AllocGroupQuantity	[0..1]	Qty	
AllocGroupRemainingQuantity	[0..1]	Qty	
AllocGroupSubQtyGrp	[0..*]	Group	
GroupAmount	[0..1]	Amt	
GroupRemainingAmount	[0..1]	Amt	
LastMkt	[0..1]	Exchange	Market of the executions.
TradeOriginationDate	[0..1]	LocalMktDate	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
AvgPx	[0..1]	Price	For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points). For 3rd party allocations used to convey either basic price or averaged price. Optional for average price allocations in the listed derivatives markets where the central counterparty calculates and manages average price across an allocation group.
AvgParPx	[0..1]	Price	
HighPx	[0..1]	Price	Maybe used to indicate the highest price within the specified allocation group.
LowPx	[0..1]	Price	Maybe used to indicate the lowest price within the specified allocation group.
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "common components of application messages"

Name	Mult.	Type	Description
Currency	[0..1]	Currency	Currency of AvgPx. Should be the currency of the local market or exchange where the trade was conducted.
CurrencyCodeSource	[0..1]	CodeSet	
AvgPxPrecision	[0..1]	int	Absence of this field indicates that default precision arranged by the broker/institution is to be used
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "common components of application messages"
TradeDate	[1..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	Date/time when allocation is generated
AllocStatus	[0..1]	CodeSet	Identifies status of allocation.
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values.
BookingType	[0..1]	CodeSet	Method for booking. Used to provide notification that this is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
GrossTradeAmt	[0..1]	Amt	Expressed in same currency as AvgPx. Sum of (AllocQty * AllocAvgPx or AllocPrice).
Concession	[0..1]	Amt	
TotalTakedown	[0..1]	Amt	
NetMoney	[0..1]	Amt	Expressed in same currency as AvgPx. Sum of AllocNetMoney.
PositionEffect	[0..1]	CodeSet	
AutoAcceptIndicator	[0..1]	Boolean	Indicates if Allocation has been automatically accepted on behalf of the Carry Firm by the Clearing House
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
NumDaysInterest	[0..1]	int	Applicable for Convertible Bonds and fixed income

Name	Mult.	Type	Description
AccruedInterestRate	[0..1]	Percentage	Applicable for Convertible Bonds and fixed income
AccruedInterestAmt	[0..1]	Amt	Applicable for Convertible Bonds and fixed income (REMOVED FROM THIS LOCATION AS OF FIX 4.4, REPLACED BY AllocAccruedInterest)
TotalAccruedInterestAmt	[0..1]	Amt	(Deprecated) use AccruedInterestAmt Sum of AccruedInterestAmt within repeating group.
InterestAtMaturity	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	For repurchase agreements the accrued interest on termination.
StartCash	[0..1]	Amt	For repurchase agreements the start (dirty) cash consideration
EndCash	[0..1]	Amt	For repurchase agreements the end (dirty) cash consideration
LegalConfirm	[0..1]	CodeSet	
Stipulations	[0..*]	Group	
YieldData	[0..1]	Component	
PositionAmountData	[0..*]	Group	Insert here here the set of "Position Amount Data" fields defined in "Common Components of Application Messages"
TotNoAllocs	[0..1]	int	Indicates total number of allocation groups (used to support fragmentation). Must equal the sum of all NoAllocs values across all message fragments making up this allocation instruction. Only required where message has been fragmented.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
AllocGrp	[0..*]	Group	Indicates number of allocation groups to follow. Not required for AllocTransType=Cancel. Not required for AllocType="Ready-To-Book" or "Warehouse instruction".
AvgPxIndicator	[0..1]	CodeSet	Indicates if an allocation is to be average priced. Is also used to indicate if average price allocation group is complete or incomplete.
AvgPxGroupID	[0..1]	String	Firm designated group identifier for average pricing.
ClearingBusinessDate	[0..1]	LocalMktDate	Indicates Clearing Business Date for which transaction will be settled.
TrdType	[0..1]	CodeSet	Indicates trade type of allocation.

Name	Mult.	Type	Description
TrdSubType	[0..1]	CodeSet	Indicates trade subtype of allocation.
SecondaryTrdType	[0..1]	CodeSet	
TertiaryTrdType	[0..1]	CodeSet	
CustOrderCapacity	[0..1]	CodeSet	Indicates CTI of original trade marked for allocation.
TradeInputSource	[0..1]	String	Indicates input source of original trade marked for allocation.
MultiLegReportingType	[0..1]	CodeSet	Indicates MultiLegReportType of original trade marked for allocation.
MessageEventSource	[0..1]	String	Used to identify the event or source which gave rise to a message.
RndPx	[0..1]	Price	Specifies the rounded price to quoted precision.
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 12 AllocationInstructionAlertRequest

Category: Allocation

### 12.1 Message Functionality

This message is used in a clearinghouse 3-party allocation model to request for AllocationInstructionAlert(35=BM) from the clearinghouse. The request may be used to obtain a one-time notification of the status of an allocation group.

### 12.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType(35)=DU
AllocRequestID	[0..1]	String	Unique identifier for this message. If used, other allocation messages may link to the request through this field.
AllocGroupID	[0..1]	String	
AvgPxGroupID	[0..1]	String	
TradeDate	[0..1]	LocalMktDate	
Parties	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 13 AllocationInstructionAlertRequestAck

Category: Allocation

### 13.1 Message Functionality

This message is used in a clearinghouse 3-party allocation model to acknowledge a AllocationInstructionAlertRequest(35=DU) message for an AllocationInstructionAlert(35=BM) message from the clearinghouse.

### 13.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DV
AllocRequestID	[1..1]	String	Used when responding to an AllocationInstructionAlertRequest(35=DU).
AllocRequestStatus	[1..1]	CodeSet	
RejectText	[0..1]	String	May be used to further describe rejection reasons when AllocRequestStatus(2768)=1 (Rejected).
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	



## 14 AllocationReport

Category: Allocation

### 14.1 Message Functionality

Sent from sell-side to buy-side, sell-side to 3rd-party or 3rd-party to buy-side, the AllocationReport(35=AS) message (Claim) provides account breakdown of an order or set of orders plus any additional follow-up front-office information developed post-trade during the trade allocation, matching and calculation phase.

### 14.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AS
AllocReportID	[1..1]	String	Unique identifier for this message
AllocID	[0..1]	String	
AllocRequestID	[0..1]	String	May be used to link to a previously submitted AllocationInstructionAlertRequest(35=DU).
AllocTransType	[1..1]	CodeSet	
AllocReportRefID	[0..1]	String	Required for AllocTransType = Replace or Cancel
AllocCancReplaceReason	[0..1]	CodeSet	Required for AllocTransType = Replace or Cancel. Gives the reason for replacing or cancelling the allocation report
SecondaryAllocID	[0..1]	String	Optional second identifier for this allocation instruction (need not be unique)
AllocGroupID	[0..1]	String	Group identifier assigned by the clearinghouse
PreviousAllocGroupID	[0..1]	String	May be used to identify the previous AllocGroupID(1730) being changed by this message when AllocGroupStatus(2767)=3 (Changed).
GroupAmount	[0..1]	Amt	
AllocGroupStatus	[0..1]	CodeSet	
FirmGroupID	[0..1]	String	Firm assigned entity identifier for the allocation
AllocReportType	[1..1]	CodeSet	Specifies the purpose or type of Allocation Report message
AllocStatus	[1..1]	CodeSet	

Name	Mult.	Type	Description
AllocRejCode	[0..1]	CodeSet	Required for AllocStatus = 1 (rejected)
RefAllocID	[0..1]	String	Required for AllocTransType = Replace or Cancel
AllocReversalStatus	[0..1]	CodeSet	Can be used for reporting on status of reversal transaction when AllocReportType(794) is 18 (Alleged reversal) or 17 (Reversal).
AllocIntermedReqType	[0..1]	CodeSet	Required if AllocReportType = 8 (Request to Intermediary). Indicates status that is requested to be transmitted to counterparty by the intermediary (i.e. clearing house)
AllocLinkID	[0..1]	String	Can be used to link two different Allocation messages (each with unique AllocID) together, i.e. for F/X "Netting" or "Swaps"
AllocLinkType	[0..1]	CodeSet	Can be used to link two different Allocation messages and identifies the type of link. Required if AllocLinkID is specified.
BookingRefID	[0..1]	String	
ClearingBusinessDate	[0..1]	LocalMktDate	Indicates Clearing Business Date for which transaction will be settled.
TrdType	[0..1]	CodeSet	Indicates trade type of allocation.
TrdSubType	[0..1]	CodeSet	Indicates trade subtype of allocation.
SecondaryTrdType	[0..1]	CodeSet	
TertiaryTrdType	[0..1]	CodeSet	
TradeContinuation	[0..1]	CodeSet	
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
MultiLegReportingType	[0..1]	CodeSet	Indicates MultiLegReportType of original trade marked for allocation.
CustOrderCapacity	[0..1]	CodeSet	Indicates CTI of original trade marked for allocation.
TradeInputSource	[0..1]	String	Indicates input source of original trade marked for allocation.
RndPx	[0..1]	Price	Specifies the rounded price to quoted precision.

Name	Mult.	Type	Description
MessageEventSource	[0..1]	String	Used to identify the event or source which gave rise to a message.
TradeInputDevice	[0..1]	String	Specific device number, terminal number or station where trade was entered
AvgPxIndicator	[0..1]	CodeSet	Indicates if an allocation is to be average priced. Is also used to indicate if average price allocation group is complete or incomplete.
AvgPxGroupID	[0..1]	String	Firm designated group identifier for average pricing
AllocNoOrdersType	[0..1]	CodeSet	Indicates how the orders being booked and allocated by an AllocationInstruction or AllocationReport message are identified, e.g. by explicit definition in the OrdAllocGrp or ExecAllocGrp components, or not identified explicitly.
OrdAllocGrp	[0..*]	Group	Indicates number of orders to be combined for allocation. If order(s) were manually delivered set to 1 (one). Required when AllocNoOrdersType = 1
ExecAllocGrp	[0..*]	Group	Indicates number of individual execution or trade entries. Absence indicates that no individual execution or trade entries are included. Primarily used to support step-outs.
PreviouslyReported	[0..1]	CodeSet	
ReversalIndicator	[0..1]	Boolean	
MatchType	[0..1]	CodeSet	
Side	[1..1]	CodeSet	
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". For NDFs, fixing date (specified in MaturityDate(541)) is required. Fixing time (specified in MaturityTime(1079)) is optional.
InstrumentExtension	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "Common Components of Application Messages"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	

Name	Mult.	Type	Description
Quantity	[1..1]	Qty	Total quantity (e.g. number of shares) allocated to all accounts, or that is Ready-To-Book
QtyType	[0..1]	CodeSet	
AllocGroupQuantity	[0..1]	Qty	
AllocGroupRemainingQuantity	[0..1]	Qty	
LastMkt	[0..1]	Exchange	Market of the executions.
TradeOriginationDate	[0..1]	LocalMktDate	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
AvgPx	[1..1]	Price	For FX orders, should be the "all-in" rate (spot rate adjusted for forward points), expressed in terms of Currency(15).
AvgParPx	[0..1]	Price	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
Currency	[0..1]	Currency	Currency of AvgPx. Should be the currency of the local market or exchange where the trade was conducted.
CurrencyCodeSource	[0..1]	CodeSet	
AvgPxPrecision	[0..1]	int	Absence of this field indicates that default precision arranged by the broker/institution is to be used
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TradeDate	[1..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	Date/time when allocation is generated
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values. Required for NDFs to specify the "value date".

Name	Mult.	Type	Description
BookingType	[0..1]	CodeSet	Method for booking. Used to provide notification that this is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
GrossTradeAmt	[0..1]	Amt	Expressed in same currency as AvgPx(6). (Quantity(53) * AvgPx(6) or AvgParPx(860)) or sum of (AllocQty(80) * AllocAvgPx(153) or AllocPrice(366)). For Fixed Income, AvgParPx(860) is used when AvgPx(6) is not expressed as "percent of par" price.
Concession	[0..1]	Amt	
TotalTakedown	[0..1]	Amt	
NetMoney	[0..1]	Amt	Expressed in same currency as AvgPx. Sum of AllocNetMoney. For FX expressed in terms of Currency(15).
PositionEffect	[0..1]	CodeSet	
AutoAcceptIndicator	[0..1]	Boolean	Indicates if Allocation has been automatically accepted on behalf of the Carry Firm by the Clearing House
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
NumDaysInterest	[0..1]	int	Applicable for Convertible Bonds and fixed income
AccruedInterestRate	[0..1]	Percentage	Applicable for Convertible Bonds and fixed income
AccruedInterestAmt	[0..1]	Amt	Sum of AllocAccruedInterestAmt within repeating group.
TotalAccruedInterestAmt	[0..1]	Amt	
InterestAtMaturity	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	For repurchase agreements the accrued interest on termination.
StartCash	[0..1]	Amt	For repurchase agreements the start (dirty) cash consideration
EndCash	[0..1]	Amt	For repurchase agreements the end (dirty) cash consideration
LegalConfirm	[0..1]	CodeSet	
Stipulations	[0..*]	Group	

Name	Mult.	Type	Description
YieldData	[0..1]	Component	
RegulatoryTradeIDGrp	[0..*]	Group	
TrdRegTimestamps	[0..*]	Group	
PositionAmountData	[0..*]	Group	Insert here here the set of "Position Amount Data" fields defined in "Common Components of Application Messages"
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
TotNoAllocs	[0..1]	int	Indicates total number of allocation groups (used to support fragmentation). Must equal the sum of all NoAllocs values across all message fragments making up this allocation instruction. Only required where message has been fragmented.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
AllocGrp	[0..*]	Group	Conditionally required except when AllocTransType(71) = 2 (Cancel).
RateSource	[0..*]	Group	
VenueType	[0..1]	CodeSet	Used to identify on what kind of venue the trade originated when communicating with a party that may not have access to all trade details, e.g. a clearing organization.
RefRiskLimitCheckID	[0..1]	String	Conditionally required when RefRiskLimitCheckIDType(2335) is specified.
RefRiskLimitCheckIDType	[0..1]	CodeSet	Conditionally required when RefRiskLimitCheckID(2334) is specified.
RiskLimitCheckStatus	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 15 AllocationReportAck

Category: Allocation

### 15.1 Message Functionality

The Allocation Report Ack message is used to acknowledge the receipt of and provide status for an Allocation Report message.

### 15.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AT
AllocReportID	[1..1]	String	
AllocID	[0..1]	String	
AllocRequestID	[0..1]	String	May be used to link to a previously submitted AllocationInstructionAlertRequest(35=DU) message.
ClearingBusinessDate	[0..1]	LocalMktDate	Indicates Clearing Business Date for which transaction will be settled.
AvgPxIndicator	[0..1]	CodeSet	Indicates if an allocation is to be average priced. Is also used to indicate if average price allocation group is complete or incomplete.
Quantity	[0..1]	Qty	
AllocTransType	[0..1]	CodeSet	
Instrument	[0..1]	Component	
Parties	[0..*]	Group	
SecondaryAllocID	[0..1]	String	Optional second identifier for the allocation report being acknowledged (need not be unique)
AllocGroupID	[0..1]	String	Group identifier assigned by the clearinghouse
FirmGroupID	[0..1]	String	Firm assigned entity identifier for the allocation
AvgPxGroupID	[0..1]	String	Firm designated group identifier for average pricing
TradeDate	[0..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	Date/Time Allocation Report Ack generated

Name	Mult.	Type	Description
AllocStatus	[0..1]	CodeSet	Denotes the status of the allocation report; received (but not yet processed), rejected (at block or account level) or accepted (and processed). AllocStatus will be conditionally required in a 2-party model when used by a counterparty to convey a change in status. It will be optional in a 3-party model in which only the central counterparty may issue the status of an allocation
AllocRejCode	[0..1]	CodeSet	Required for AllocStatus = 1 ( block level reject) and for AllocStatus 2 (account level reject) if the individual accounts and reject reasons are not provided in this message
AllocReportType	[0..1]	CodeSet	
AllocIntermedReqType	[0..1]	CodeSet	Required if AllocReportType = 8 (Request to Intermediary). Indicates status that is requested to be transmitted to counterparty by the intermediary (i.e. clearing house)
MatchStatus	[0..1]	CodeSet	Denotes whether the financial details provided on the Allocation Report were successfully matched.
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
Text	[0..1]	String	Can include explanation for AllocRejCode = 7 (other)
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
RegulatoryTradeIDGrp	[0..*]	Group	



Name	Mult.	Type	Description
AllocAckGrp	[0..*]	Group	This repeating group is optionally used for messages with AllocStatus = 2 (account level reject) to provide details of the individual accounts that caused the rejection, together with reject reasons. This group should not be populated where AllocStatus has any other value. Indicates number of allocation groups to follow.
StandardTrailer	[1..1]	Component	

## 16 ApplicationMessageReport

Category: Application

### 16.1 Message Functionality

This message is used for three different purposes: to reset the ApplSeqNum (1181) of a specified ApplID (1180), to indicate that the last message has been sent for a particular ApplID, or as a keep-alive mechanism for ApplIDs with infrequent message traffic.

### 16.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BY
ApplReportID	[1..1]	String	Identifier for the Application Message Report
ApplReqID	[0..1]	String	If the application message report is generated in response to an ApplicationMessageRequest(MsgType=BW), then this tag contains the ApplReqID(1346) of that request.
ApplReportType	[1..1]	CodeSet	Type of report
ApplIDReportGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 17 ApplicationMessageRequest

Category: Application

### 17.1 Message Functionality

This message is used to request a retransmission of a set of one or more messages generated by the application specified in RefApplID (1355).

### 17.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BW
ApplReqID	[1..1]	String	Unique identifier for request
ApplReqType	[1..1]	CodeSet	Type of Application Message Request being made
ApplIDRequestGrp	[0..*]	Group	
Parties	[0..*]	Group	
Text	[0..1]	String	Allows user to provide reason for request
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 18 ApplicationMessageRequestAck

Category: Application

### 18.1 Message Functionality

This message is used to acknowledge an Application Message Request providing a status on the request (i.e. whether successful or not). This message does not provide the actual content of the messages to be resent.

### 18.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BX
ApplResponseID	[1..1]	String	Identifier for the Application Message Request Ack
ApplReqID	[0..1]	String	Identifier of the request associated with this ACK message
ApplReqType	[0..1]	CodeSet	
ApplResponseType	[0..1]	CodeSet	
ApplTotalMessageCount	[0..1]	int	Total number of messages included in transmission
ApplIDRequestAckGrp	[0..*]	Group	
Parties	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 19 AssignmentReport

Category: PositionMaintenance

### 19.1 Message Functionality

Assignment Reports are sent from a clearing house to counterparties, such as a clearing firm as a result of the assignment process.

### 19.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AW
ApplicationSequenceControl	[0..1]	Component	
AsgnRptID	[1..1]	String	Unique identifier for the Assignment report
PosReqID	[0..1]	String	If specified,the identifier of the RequestForPositions(MsgType=AN) to which this message is sent in response.
TotNumAssignmentReports	[0..1]	int	Total Number of Assignment Reports being returned to a firm
LastRptRequested	[0..1]	CodeSet	
Parties	[1..*]	Group	Clearing Organization. Clearing Firm. Contra Clearing Organization. Contra Clearing Firm. Position Account
Account	[0..1]	String	Customer Account
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
Instrument	[0..1]	Component	CFI Code - Market Indicator (col 4) used to indicate Market of Assignment
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	Number of legs that make up the Security
UndInstrmtGrp	[0..*]	Group	Number of legs that make up the Security
PositionQty	[0..*]	Group	Insert here here the set of "PositionQty" fields defined in "Common Components of Application Messages."

Name	Mult.	Type	Description
PositionAmountData	[0..*]	Group	Insert here the set of "PositionAmountData" fields defined in "Common Components of Application Messages."
ThresholdAmount	[0..1]	PriceOffset	
SettlPrice	[0..1]	Price	Settlement Price of Option
SettlPriceType	[0..1]	CodeSet	Values = Final, Theoretical
UnderlyingSettlPrice	[0..1]	Price	Settlement Price of Underlying
PriorSettlPrice	[0..1]	Price	
PositionContingentPrice	[0..1]	Price	
ExpireDate	[0..1]	LocalMktDate	Expiration Date of Option
AssignmentMethod	[0..1]	CodeSet	Method under which assignment was conducted
AssignmentUnit	[0..1]	Qty	Quantity Increment used in performing assignment
OpenInterest	[0..1]	Amt	Open interest that was eligible for assignment
ExerciseMethod	[0..1]	CodeSet	Exercise Method used to in performing assignment. Values = Automatic, Manual
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
ClearingBusinessDate	[1..1]	LocalMktDate	Business date of assignment
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 20 BidRequest

Category: ProgramTrading

### 20.1 Message Functionality

The BidRequest Message can be used in one of two ways depending on which market conventions are being followed.

In the "Non disclosed" convention (e.g. US/European model) the BidRequest message can be used to request a bid based on the sector, country, index and liquidity information contained within the message itself. In the "Non disclosed" convention the entry repeating group is used to define liquidity of the program. See " Program/Basket/List Trading" for an example.

In the "Disclosed" convention (e.g. Japanese model) the BidRequest message can be used to request bids based on the ListOrderDetail messages sent in advance of BidRequest message. In the "Disclosed" convention the list repeating group is used to define which ListOrderDetail messages a bid is being sort for and the directions of the required bids.

### 20.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = k (lowercase)
BidID	[0..1]	String	Required to relate the bid response
ClientBidID	[1..1]	String	
BidRequestTransType	[1..1]	CodeSet	Identifies the Bid Request message transaction type
ListName	[0..1]	String	
TotNoRelatedSym	[1..1]	int	
BidType	[1..1]	CodeSet	e.g. "Non Disclosed", "Disclosed", No Bidding Process
NumTickets	[0..1]	int	Total number of tickets/allocations assuming fully executed
Currency	[0..1]	Currency	Used to represent the currency of monetary amounts.
CurrencyCodeSource	[0..1]	CodeSet	
SideValue1	[0..1]	Amt	Expressed in Currency
SideValue2	[0..1]	Amt	Expressed in Currency

Name	Mult.	Type	Description
BidDescReqGrp	[0..*]	Group	Used if BidType="Non Disclosed"
BidCompReqGrp	[0..*]	Group	Used if BidType="Disclosed"
LiquidityIndType	[0..1]	CodeSet	
WtAverageLiquidity	[0..1]	Percentage	Overall weighted average liquidity expressed as a % of average daily volume
ExchangeForPhysical	[0..1]	CodeSet	
OutMainCntryUIndex	[0..1]	Amt	% value of stocks outside main country in Currency
CrossPercent	[0..1]	Percentage	% of program that crosses in Currency
ProgRptReqs	[0..1]	CodeSet	
ProgPeriodInterval	[0..1]	int	Time in minutes between each ListStatus report sent by SellSide. Zero means don't send status.
IncTaxInd	[0..1]	CodeSet	Net/Gross
ForexReq	[0..1]	CodeSet	Is foreign exchange required
NumBidders	[0..1]	int	Indicates the total number of bidders on the list
TradeDate	[0..1]	LocalMktDate	
BidTradeType	[1..1]	CodeSet	
BasisPxType	[1..1]	CodeSet	
StrikeTime	[0..1]	UTCTimestamp	Used when BasisPxType = "C"
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	



## 21 BidResponse

Category: ProgramTrading

### 21.1 Message Functionality

The Bid Response message can be used in one of two ways depending on which market conventions are being followed.

In the "Non disclosed" convention the Bid Response message can be used to supply a bid based on the sector, country, index and liquidity information contained within the corresponding bid request message. See "Program/Basket/List Trading" for an example.

In the "Disclosed" convention the Bid Response message can be used to supply bids based on the List Order Detail messages sent in advance of the corresponding Bid Request message.

### 21.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = l (lowercase L)
BidID	[0..1]	String	
ClientBidID	[0..1]	String	
BidCompRspGrp	[1..*]	Group	Number of bid repeating groups
StandardTrailer	[1..1]	Component	

## 22 BusinessMessageReject

Category: BusinessReject

### 22.1 Message Functionality

The Business Message Reject message can reject an application-level message which fulfills session-level rules and cannot be rejected via any other means. Note if the message fails a session-level rule (e.g. body length is incorrect), a session-level Reject message should be issued.

### 22.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = j (lowercase)
RefSeqNum	[0..1]	SeqNum	MsgSeqNum of rejected message
RefMsgType	[1..1]	CodeSet	The MsgType of the FIX message being referenced.
RefApplVerID	[0..1]	CodeSet	Recommended when rejecting an application message that does not explicitly provide ApplVerID ( 1128) on the message being rejected. In this case the value from the DefaultApplVerID(1137) or the default value specified in the NoMsgTypes repeating group on the logon message should be provided.
RefApplExtID	[0..1]	int	Recommended when rejecting an application message that does not explicitly provide ApplExtID(1156) on the rejected message. In this case the value from the DefaultApplExtID(1407) or the default value specified in the NoMsgTypes repeating group on the logon message should be provided.
RefCstmApplVerID	[0..1]	String	Recommended when rejecting an application message that does not explicitly provide CstmApplVerID(1129) on the message being rejected. In this case the value from the DefaultCstmApplVerID(1408) or the default value specified in the NoMsgTypes repeating group on the logon message should be provided.

Name	Mult.	Type	Description
BusinessRejectRefID	[0..1]	String	The value of the business-level "ID" field on the message being referenced. Required unless the corresponding ID field (see list above) was not specified.
BusinessRejectReason	[1..1]	CodeSet	Code to identify reason for a Business Message Reject message.
Text	[0..1]	String	Where possible, message to explain reason for rejection
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 23 CollateralAssignment

Category: CollateralManagement

### 23.1 Message Functionality

Used to assign collateral to cover a trading position. This message can be sent unsolicited or in reply to a Collateral Request message.

### 23.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AY
CollAsgnID	[1..1]	String	Unique Identifier for collateral assignment
CollReqID	[0..1]	String	Identifier of CollReqID to which the Collateral Assignment is in response
CollAsgnReason	[1..1]	CodeSet	Reason for collateral assignment
CollAsgnTransType	[1..1]	CodeSet	Collateral Transaction Type
CollAsgnRefID	[0..1]	String	Collateral assignment to which this transaction refers
TransactTime	[1..1]	UTCTimestamp	
ExpireTime	[0..1]	UTCTimestamp	For an Initial assignment, time by which a response is expected
Parties	[0..*]	Group	
Account	[0..1]	String	Customer Account
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
ClOrdID	[0..1]	String	Identifier of order for which collateral is required
OrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryOrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryClOrdID	[0..1]	String	Identifier of order for which collateral is required
ExecCollGrp	[0..*]	Group	Executions for which collateral is required
TrdCollGrp	[0..*]	Group	Trades for which collateral is required
Instrument	[0..1]	Component	
FinancingDetails	[0..1]	Component	

Name	Mult.	Type	Description
SettlDate	[0..1]	LocalMktDate	Can be used to provide the value date of the collateral transaction where the deposit or withdrawal is for a specific future date.
Quantity	[0..1]	Qty	
QtyType	[0..1]	CodeSet	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	Number of legs that make up the Security
UndInstrmtCollGrp	[0..*]	Group	Number of legs that make up the Security
MarginExcess	[0..1]	Amt	
TotalNetValue	[0..1]	Amt	
CashOutstanding	[0..1]	Amt	
TrdRegTimestamps	[0..*]	Group	Insert here the set of "TrdRegTimestamps" fields defined in "Common Components of Application Messages"
Side	[0..1]	CodeSet	
MiscFeesGrp	[0..*]	Group	Required if any miscellaneous fees are reported.
Price	[0..1]	Price	
PriceType	[0..1]	CodeSet	
AccruedInterestAmt	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	
StartCash	[0..1]	Amt	
EndCash	[0..1]	Amt	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" fields defined in "Common Components of Application Messages"
SettlInstructionsData	[0..1]	Component	Insert here the set of "SettlInstructionsData" fields defined in "Common Components of Application Messages"
TradingSessionID	[0..1]	CodeSet	Trading Session in which trade occurred
TradingSessionSubID	[0..1]	CodeSet	Trading Session Subid in which trade occurred
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
WireReference	[0..1]	String	

Name	Mult.	Type	Description
TradeDate	[0..1]	LocalMktDate	
TransactionID	[0..1]	String	The unique transaction entity identifier assigned by counterparty to the transaction receiving this message, if known.
FirmTransactionID	[0..1]	String	The unique transaction entity identifier assigned by the firm sending the CollateralAssignment(35=AY).
ClearingBusinessDate	[0..1]	LocalMktDate	The clearing business date of the collateral assignment.
CollateralRequestLinkID	[0..1]	String	
TotNumCollateralRequests	[0..1]	int	
CollateralRequestNumber	[0..1]	int	
CollateralRequestInstruction	[0..1]	String	Values are custom to a particular implementation and will be maintained externally.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 24 CollateralInquiry

Category: CollateralManagement

### 24.1 Message Functionality

Used to inquire for collateral status.

### 24.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BB
CollInquiryID	[1..1]	String	Unique identifier for this message.
CollInqQualGrp	[0..*]	Group	Number of qualifiers to inquiry
SubscriptionRequestType	[0..1]	CodeSet	Used to subscribe / unsubscribe for collateral status reports. If the field is absent, the default will be snapshot request only - no subscription.
ResponseTransportType	[0..1]	CodeSet	Ability to specify whether the response to the request should be delivered inband or via pre-arranged out-of-band transport.
ResponseDestination	[0..1]	String	URI destination name. Used if ResponseTransportType is out-of-band.
Parties	[0..*]	Group	
Account	[0..1]	String	Customer Account
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
ClOrdID	[0..1]	String	Identifier of order for which collateral is required
OrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryOrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryClOrdID	[0..1]	String	Identifier of order for which collateral is required
ExecCollGrp	[0..*]	Group	Executions for which collateral is required
TrdCollGrp	[0..*]	Group	Trades for which collateral is required
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages".
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "Common Components of Application Messages"

Name	Mult.	Type	Description
SettlDate	[0..1]	LocalMktDate	
Quantity	[0..1]	Qty	
QtyType	[0..1]	CodeSet	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	Number of legs that make up the Security
UndInstrmtGrp	[0..*]	Group	Number of legs that make up the Security
MarginExcess	[0..1]	Amt	
TotalNetValue	[0..1]	Amt	
CashOutstanding	[0..1]	Amt	
TrdRegTimestamps	[0..*]	Group	Insert here the set of "TrdRegTimestamps" fields defined in "Common Components of Application Messages"
Side	[0..1]	CodeSet	
Price	[0..1]	Price	
PriceType	[0..1]	CodeSet	
AccruedInterestAmt	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	
StartCash	[0..1]	Amt	
EndCash	[0..1]	Amt	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" fields defined in "Common Components of Application Messages"
SettlInstructionsData	[0..1]	Component	Insert here the set of "SettlInstructionsData" fields defined in "Common Components of Application Messages"
TradingSessionID	[0..1]	CodeSet	Trading Session in which trade occurred
TradingSessionSubID	[0..1]	CodeSet	Trading Session Subid in which trade occurred
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
ClearingBusinessDate	[0..1]	LocalMktDate	
Text	[0..1]	String	



Name	Mult.	Type	Description
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 25 CollateralInquiryAck

Category: CollateralManagement

### 25.1 Message Functionality

Used to respond to a Collateral Inquiry in the following situations:

- When the CollateralInquiry will result in an out of band response (such as a file transfer).
- When the inquiry is otherwise valid but no collateral is found to match the criteria specified on the Collateral Inquiry message.
- When the Collateral Inquiry is invalid based upon the business rules of the counterparty.

### 25.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BG
CollInquiryID	[1..1]	String	Identifier for the collateral inquiry to which this message is a reply
CollInquiryStatus	[1..1]	CodeSet	Status of the Collateral Inquiry referenced by CollInquiryID
CollInquiryResult	[0..1]	CodeSet	Result of the Collateral Inquiry referenced by CollInquiryID - specifies any errors or warnings
CollInqQualGrp	[0..*]	Group	Number of qualifiers to inquiry
TotNumReports	[0..1]	int	Total number of reports generated in response to this inquiry
Parties	[0..*]	Group	
Account	[0..1]	String	Customer Account
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
CIOrdID	[0..1]	String	Identifier of order for which collateral is required
OrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryOrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryCIOrdID	[0..1]	String	Identifier of order for which collateral is required
ExecCollGrp	[0..*]	Group	Executions for which collateral is required
TrdCollGrp	[0..*]	Group	Trades for which collateral is required

Name	Mult.	Type	Description
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages".
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "Common Components of Application Messages"
SettlDate	[0..1]	LocalMktDate	
Quantity	[0..1]	Qty	
QtyType	[0..1]	CodeSet	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	Number of legs that make up the Security
UndInstrmtGrp	[0..*]	Group	Number of legs that make up the Security
TradingSessionID	[0..1]	CodeSet	Trading Session in which trade occurred
TradingSessionSubID	[0..1]	CodeSet	Trading Session Subid in which trade occurred
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
ClearingBusinessDate	[0..1]	LocalMktDate	
ResponseTransportType	[0..1]	CodeSet	Ability to specify whether the response to the request should be delivered inband or via pre-arranged out-of-band transport.
ResponseDestination	[0..1]	String	URI destination name. Used if ResponseTransportType is out-of-band.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 26 CollateralReport

Category: CollateralManagement

### 26.1 Message Functionality

Used to report collateral status when responding to a Collateral Inquiry message.

### 26.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BA
CollRptID	[1..1]	String	Unique Identifier for collateral report
CollInquiryID	[0..1]	String	Identifier for the collateral inquiry to which this message is a reply
TransactTime	[0..1]	UTCTimestamp	
CollApplType	[0..1]	CodeSet	Differentiates collateral pledged specifically against a position from collateral pledged against an entire portfolio on a valued basis.
FinancialStatus	[0..1]	CodeSet	Tells whether security has been restricted.
CollStatus	[1..1]	CodeSet	Collateral status
TotNumReports	[0..1]	int	
LastRptRequested	[0..1]	CodeSet	
Parties	[0..*]	Group	
Account	[0..1]	String	Customer Account
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
ClOrdID	[0..1]	String	Identifier of order for which collateral is required
OrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryOrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryClOrdID	[0..1]	String	Identifier of order for which collateral is required
ExecCollGrp	[0..*]	Group	Executions for which collateral is required
TrdCollGrp	[0..*]	Group	Trades for which collateral is required
Instrument	[0..1]	Component	
FinancingDetails	[0..1]	Component	
SettlDate	[0..1]	LocalMktDate	
Quantity	[0..1]	Qty	

Name	Mult.	Type	Description
QtyType	[0..1]	CodeSet	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	
UndInstrmtGrp	[0..*]	Group	
MarginExcess	[0..1]	Amt	
TotalNetValue	[0..1]	Amt	
CashOutstanding	[0..1]	Amt	
CollateralAmountGrp	[0..*]	Group	
CollateralizationValueDate	[0..1]	LocalMktDate	
TradeCollateralization	[0..1]	CodeSet	
RegulatoryTradeIDGrp	[0..*]	Group	
TrdRegTimestamps	[0..*]	Group	
Side	[0..1]	CodeSet	
MiscFeesGrp	[0..*]	Group	Required if any miscellaneous fees are reported.
Price	[0..1]	Price	
PriceType	[0..1]	CodeSet	
AccruedInterestAmt	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	
StartCash	[0..1]	Amt	
EndCash	[0..1]	Amt	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" fields defined in "Common Components of Application Messages"
SettlInstructionsData	[0..1]	Component	Insert here the set of "SettlInstructionsData" fields defined in "Common Components of Application Messages"
TradingSessionID	[0..1]	CodeSet	Trading Session in which trade occurred
TradingSessionSubID	[0..1]	CodeSet	Trading Session Subid in which trade occurred
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
RegulatoryReportType	[0..1]	CodeSet	

Name	Mult.	Type	Description
RegulatoryReportTypeBusinessDate	[0..1]	LocalMktDate	May be used when the business event date differs from when the regulatory report is actually being submitted (typically specified in TrdRegTimestamps component).
ClearingBusinessDate	[0..1]	LocalMktDate	The clearing business date of the report.
WireReference	[0..1]	String	
TradeDate	[0..1]	LocalMktDate	
TransactionID	[0..1]	String	The unique transaction entity identifier assigned by the firm sending the CollateralReport(35=BA).
FirmTransactionID	[0..1]	String	The unique transaction entity identifier assigned by the counterparty to the transaction receiving this message, if known.
FundingSourceGrp	[0..*]	Group	
TransactionAttributeGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 27 CollateralReportAck

Category: CollateralManagement

### 27.1 Message Functionality

CollateralReportAck(35=DQ) is used as a response to the CollateralReport(35=BA). It can be used to reject a CollateralReport(35=BA) when the content of the report is invalid based on the business rules of the receiver. The message may also be used to acknowledge receipt of a valid CollateralReport(35=BA).

### 27.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	
CollRptID	[1..1]	String	Identifier of the CollateralReport(35=BA) being acknowledged.
TransactTime	[0..1]	UTCTimestamp	
CollRptStatus	[1..1]	CodeSet	
CollRptRejectReason	[0..1]	CodeSet	Conditionally required when CollRptStatus(2488) = 2 (Rejected).
RejectText	[0..1]	String	Conditionally required when CollRptStatus(2488) = 2 (Rejected).
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
Parties	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 28 CollateralRequest

Category: CollateralManagement

### 28.1 Message Functionality

An initiator that requires collateral from a respondent sends a Collateral Request. The initiator can be either counterparty to a trade in a two party model or an intermediary such as an ATS or clearinghouse in a three party model. A Collateral Assignment is expected as a response to a request for collateral.

### 28.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AX
CollReqID	[1..1]	String	Unique identifier for collateral request
CollAsgnReason	[1..1]	CodeSet	Reason collateral assignment is being requested
TransactTime	[1..1]	UTCTimestamp	
ExpireTime	[0..1]	UTCTimestamp	Time until when Respondent has to assign collateral
Parties	[0..*]	Group	
Account	[0..1]	String	Customer Account
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
ClOrdID	[0..1]	String	Identifier of order for which collateral is required
OrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryOrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryClOrdID	[0..1]	String	Identifier of order for which collateral is required
ExecCollGrp	[0..*]	Group	Executions for which collateral is required
TrdCollGrp	[0..*]	Group	Trades for which collateral is required
Instrument	[0..1]	Component	Instrument that was traded for which collateral is required
FinancingDetails	[0..1]	Component	Details of the Agreement and Deal
SettlDate	[0..1]	LocalMktDate	
Quantity	[0..1]	Qty	
QtyType	[0..1]	CodeSet	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	



Name	Mult.	Type	Description
InstrmtLegGrp	[0..*]	Group	Number of legs that make up the Security
UndInstrmtCollGrp	[0..*]	Group	Number of legs that make up the Security
MarginExcess	[0..1]	Amt	
TotalNetValue	[0..1]	Amt	
CashOutstanding	[0..1]	Amt	
TrdRegTimestamps	[0..*]	Group	Insert here the set of "TrdRegTimestamps" fields defined in "Common Components of Application Messages"
Side	[0..1]	CodeSet	
MiscFeesGrp	[0..*]	Group	Required if any miscellaneous fees are reported.
Price	[0..1]	Price	
PriceType	[0..1]	CodeSet	
AccruedInterestAmt	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	
StartCash	[0..1]	Amt	
EndCash	[0..1]	Amt	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" fields defined in "Common Components of Application Messages"
TradingSessionID	[0..1]	CodeSet	Trading Session in which trade occurred
TradingSessionSubID	[0..1]	CodeSet	Trading Session Subid in which trade occurred
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
ClearingBusinessDate	[0..1]	LocalMktDate	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 29 CollateralResponse

Category: CollateralManagement

### 29.1 Message Functionality

Used to respond to a Collateral Assignment message.

### 29.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AZ
CollRespID	[1..1]	String	Unique identifier for the collateral response
CollAsgnID	[0..1]	String	Conditionally required when responding to a Collateral Assignment message
CollReqID	[0..1]	String	Identifier of CollReqID to which the Collateral Assignment is in response
CollAsgnReason	[0..1]	CodeSet	Conditionally required when responding to a Collateral Assignment message
CollAsgnTransType	[0..1]	CodeSet	Collateral Transaction Type - not recommended because it causes confusion
CollAsgnRespType	[1..1]	CodeSet	Collateral Assignment Response Type
CollAsgnRejectReason	[0..1]	CodeSet	Conditionally required when CollAsgnRespType(905) = 3 (Rejected).
TransactTime	[1..1]	UTCTimestamp	
CollApplType	[0..1]	CodeSet	
FinancialStatus	[0..1]	CodeSet	Tells whether security has been restricted.
ClearingBusinessDate	[0..1]	LocalMktDate	The clearing business date of the assignment. The date on which the transaction was entered.
Parties	[0..*]	Group	
Account	[0..1]	String	Customer Account
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
ClOrdID	[0..1]	String	Identifier of order for which collateral is required
OrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryOrderID	[0..1]	String	Identifier of order for which collateral is required
SecondaryClOrdID	[0..1]	String	Identifier of order for which collateral is required

Name	Mult.	Type	Description
ExecCollGrp	[0..*]	Group	Executions for which collateral is required
TrdCollGrp	[0..*]	Group	Trades for which collateral is required
Instrument	[0..1]	Component	
FinancingDetails	[0..1]	Component	
SettlDate	[0..1]	LocalMktDate	Can be used to specify the value date of the collateral transaction where the transaction is for a specific future date (e.g. to be "settled" on a future date).
Quantity	[0..1]	Qty	
QtyType	[0..1]	CodeSet	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	Number of legs that make up the Security
UndInstrmtCollGrp	[0..*]	Group	Number of legs that make up the Security
MarginExcess	[0..1]	Amt	
TotalNetValue	[0..1]	Amt	
CashOutstanding	[0..1]	Amt	
CollateralAmountGrp	[0..*]	Group	
TrdRegTimestamps	[0..*]	Group	
Side	[0..1]	CodeSet	
MiscFeesGrp	[0..*]	Group	Required if any miscellaneous fees are reported.
Price	[0..1]	Price	
PriceType	[0..1]	CodeSet	
AccruedInterestAmt	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	
StartCash	[0..1]	Amt	
EndCash	[0..1]	Amt	
SpreadOrBenchmarkCurveData	[0..1]	Component	
Stipulations	[0..*]	Group	
WireReference	[0..1]	String	
TradeDate	[0..1]	LocalMktDate	
TransactionID	[0..1]	String	The unique transaction entity identifier assigned by the firm sending the CollateralResponse(35=AZ).

Name	Mult.	Type	Description
FirmTransactionID	[0..1]	String	The unique transaction entity identifier assigned by the counterparty to the transaction, if known. Echoes the value from CollateralAssignment(35=AY) if provided.
CollateralRequestLinkID	[0..1]	String	
TotNumCollateralRequests	[0..1]	int	
CollateralRequestNumber	[0..1]	int	
CollateralRequestInstruction	[0..1]	String	Values are custom to a particular implementation and will be maintained externally.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
WarningText	[0..1]	String	Conditionally required when CollAsgnRespType(905) = 5 (Completed with warning).
EncodedWarningTextLen	[0..1]	Length	Must be set if EncodedWarningText(2521) field is specified and must immediately precede it.
EncodedWarningText	[0..1]	data	Encoded (non-ASCII characters) representation of the WarningText(2520) field in the encoded format specified via the MessageEncoding field.
RejectText	[0..1]	String	Conditionally required when CollAsgnRespType(905) = 3 (Rejected).
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 30 Confirmation

Category: Confirmation

### 30.1 Message Functionality

The Confirmation messages are used to provide individual trade level confirmations from the sell side to the buy side. In versions of FIX prior to version 4.4, this role was performed by the allocation message. Unlike the allocation message, the confirmation message operates at an allocation account (trade) level rather than block level, allowing for the affirmation or rejection of individual confirmations.

### 30.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AK
ConfirmID	[1..1]	String	Unique ID for this message
ConfirmRefID	[0..1]	String	Mandatory if ConfirmTransType is Replace or Cancel
ConfirmReqID	[0..1]	String	Only used when this message is used to respond to a confirmation request (to which this ID refers)
ConfirmTransType	[1..1]	CodeSet	New, Cancel or Replace
ConfirmType	[1..1]	CodeSet	Denotes whether this message represents a confirmation or a trade status message
CopyMsgIndicator	[0..1]	Boolean	Denotes whether or not this message represents copy confirmation (or status message). Absence of this field indicates message is not a drop copy.
LegalConfirm	[0..1]	CodeSet	Denotes whether this message represents the legally binding confirmation. Absence of this field indicates message is not a legal confirm.
ConfirmStatus	[1..1]	CodeSet	
MatchStatus	[0..1]	CodeSet	
AffirmStatus	[0..1]	CodeSet	Used to communicate an "affirmed" Confirmation(35=AK) status message (i.e. when ConfirmType(773) = 1 (Status)) to interested parties that need to or should receive such confirmation status message. This field must not be used when sending a Confirmation(35=AK) message that needs to be affirmed.

Name	Mult.	Type	Description
RegulatoryTradeIDGrp	[0..*]	Group	
TradeConfirmationReferenceID	[0..1]	String	
ClearedIndicator	[0..1]	CodeSet	Used to communicate the status of the central clearing workflow.
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages". Required for fixed income. Also to be used in associated with ProcessCode for broker of credit (e.g. for directed brokerage trades). Also to be used to specify party-specific regulatory details (e.g. full legal name of contracting legal entity, registered address, regulatory status, any registration details)
OrdAllocGrp	[0..*]	Group	Indicates number of orders to be combined for allocation. If order(s) were manually delivered set to 1 (one). Required when AllocNoOrdersType = 1
ExecAllocGrp	[0..*]	Group	
AllocID	[0..1]	String	Used to refer to an earlier Allocation Instruction.
SecondaryAllocID	[0..1]	String	Used to refer to an earlier Allocation Instruction via its secondary identifier
IndividualAllocID	[0..1]	String	Used to refer to an allocation account within an earlier Allocation Instruction.
TrdType	[0..1]	CodeSet	
TrdSubType	[0..1]	CodeSet	
SecondaryTrdType	[0..1]	CodeSet	
TradeContinuation	[0..1]	CodeSet	
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
MatchType	[0..1]	CodeSet	
TransactTime	[1..1]	UTCTimestamp	Represents the time this message was generated
TradeDate	[1..1]	LocalMktDate	

Name	Mult.	Type	Description
TrdRegTimestamps	[0..*]	Group	Time of last execution being confirmed by this message. Use ExecutionTimestamp(2749) in ExecAllocGrp component when there are multiple trades.
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
InstrumentExtension	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "Common Components of Application Messages"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
YieldData	[0..1]	Component	If traded on Yield, price must be calculated "to worst" and the <Yield> component block must specify how calculated, redemption date and price (if not par). If traded on Price, the <Yield> component block must specify how calculated - "Worst", and include redemptiondate and price (if not par).
AllocQty	[1..1]	Qty	The quantity being confirmed by this message (this is at a trade level, not block or order level)
QtyType	[0..1]	CodeSet	
Side	[1..1]	CodeSet	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
LastMkt	[0..1]	Exchange	
CpctyConfGrp	[1..*]	Group	
AllocAccount	[1..1]	String	Account number for the trade being confirmed by this message
AllocAcctIDSource	[0..1]	CodeSet	
AllocAccountType	[0..1]	CodeSet	
AvgPx	[1..1]	Price	Gross price for the trade being confirmed. Always expressed in percent-of-par for Fixed Income
AvgPxPrecision	[0..1]	int	Absence of this field indicates that default precision arranged by the broker/institution is to be used

Name	Mult.	Type	Description
PriceType	[0..1]	CodeSet	Price type for the AvgPx field
PriceQualifierGrp	[0..*]	Group	
AvgParPx	[0..1]	Price	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
ReportedPx	[0..1]	Price	Reported price (may be different to AvgPx in the event of a marked-up or marked-down principal trade)
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
ProcessCode	[0..1]	CodeSet	Used to identify whether the trade was a soft dollar trade, step in/out etc. Broker of credit, where relevant, can be specified using the Parties nested block above.
GrossTradeAmt	[1..1]	Amt	Gross trade amount for the allocated account being confirmed.
NumDaysInterest	[0..1]	int	
ExDate	[0..1]	LocalMktDate	Optional "next coupon date" for Fixed Income
AccruedInterestRate	[0..1]	Percentage	
AccruedInterestAmt	[0..1]	Amt	Required for Fixed Income products that trade with accrued interest
InterestAtMaturity	[0..1]	Amt	Required for Fixed Income products that pay lump sum interest at maturity
EndAccruedInterestAmt	[0..1]	Amt	For repurchase agreements the accrued interest on termination.
StartCash	[0..1]	Amt	For repurchase agreements the start (dirty) cash consideration
EndCash	[0..1]	Amt	For repurchase agreements the end (dirty) cash consideration
Concession	[0..1]	Amt	
TotalTakedown	[0..1]	Amt	
NetMoney	[1..1]	Amt	
MaturityNetMoney	[0..1]	Amt	Net Money at maturity if Zero Coupon and maturity value is different from par value
SettlCurrAmt	[0..1]	Amt	



Name	Mult.	Type	Description
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
SettlCurrFxRate	[0..1]	float	
SettlCurrFxRateCalc	[0..1]	CodeSet	
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	
SettlInstructionsData	[0..1]	Component	Insert here the set of "SettlInstructionsData" fields defined in "Common Components of Application Messages". Used to communicate settlement instructions for this Confirmation.
CommissionData	[0..1]	Component	
SharedCommission	[0..1]	Amt	Used to identify any commission shared with a third party (e.g. directed brokerage)
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData if multiple commissions or enhanced attributes are needed.
Stipulations	[0..*]	Group	
MiscFeesGrp	[0..*]	Group	Required if any miscellaneous fees are reported.
MatchExceptionGrp	[0..*]	Group	
MatchingDataPointGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 31 ConfirmationAck

Category: Confirmation

### 31.1 Message Functionality

The Confirmation Ack (aka Affirmation) message is used to respond to a Confirmation message.

### 31.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AU
ConfirmID	[1..1]	String	
TradeDate	[1..1]	LocalMktDate	
TransactTime	[1..1]	UTCTimestamp	Date/Time Allocation Instruction Ack generated
AffirmStatus	[1..1]	CodeSet	
RegulatoryTradeIDGrp	[0..*]	Group	
TradeConfirmationReferenceID	[0..1]	String	
ConfirmRejReason	[0..1]	CodeSet	Conditionally required for AffirmStatus(940) = 2 (Confirm rejected).
MatchStatus	[0..1]	CodeSet	Denotes whether the financial details provided on the Confirmation were successfully matched.
MatchExceptionGrp	[0..*]	Group	
MatchingDataPointGrp	[0..*]	Group	
Text	[0..1]	String	Can include explanation for ConfirmRejReason(774) = 99 (Other)
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 32 ConfirmationRequest

Category: Confirmation

### 32.1 Message Functionality

The Confirmation Request message is used to request a Confirmation message.

### 32.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BH
ConfirmReqID	[1..1]	String	Unique identifier for this message
ConfirmType	[1..1]	CodeSet	Denotes whether this message is being used to request a confirmation or a trade status message
OrdAllocGrp	[0..*]	Group	Indicates number of orders to be combined for allocation. If order(s) were manually delivered set to 1 (one).Required when AllocNoOrdersType = 1
AllocID	[0..1]	String	Used to refer to an earlier Allocation Instruction.
SecondaryAllocID	[0..1]	String	Used to refer to an earlier Allocation Instruction via its secondary identifier
IndividualAllocID	[0..1]	String	Used to refer to an allocation account within an earlier Allocation Instruction.
TransactTime	[1..1]	UTCTimestamp	Represents the time this message was generated
AllocAccount	[0..1]	String	Account number for the trade being confirmed by this message
AllocAcctIDSource	[0..1]	CodeSet	
AllocAccountType	[0..1]	CodeSet	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 33 ContraryIntentionReport

Category: PositionMaintenance

### 33.1 Message Functionality

The Contrary Intention Report is used for reporting of contrary expiration quantities for Saturday expiring options. This information is required by options exchanges for regulatory purposes.

### 33.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BO
ApplicationSequenceControl	[0..1]	Component	
ContIntRptID	[1..1]	String	Unique identifier for the Contrary Intention report
TransactTime	[0..1]	UTCTimestamp	Time the contrary intention was received by clearing organization.
LateIndicator	[0..1]	Boolean	Indicates if the contrary intention was received after the exchange imposed cutoff time
InputSource	[0..1]	String	Source of the contrary intention
ClearingBusinessDate	[1..1]	LocalMktDate	Business date of contrary intention
Parties	[1..*]	Group	Clearing Organization. Clearing Firm. Position Account
ExpirationQty	[1..*]	Group	Expiration Quantities
Instrument	[1..1]	Component	
UndInstrmtGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 34 CrossOrderCancelReplaceRequest

Category: CrossOrders

### 34.1 Message Functionality

Used to modify a cross order previously submitted using the New Order - Cross message. See Order Cancel Replace Request for details concerning message usage.

### 34.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = t (lowercase T)
OrderID	[0..1]	String	Unique identifier of most recent order as assigned by sell-side (broker, exchange, ECN).
OrderRequestID	[0..1]	int	Required if provided on the order being replaced (or cancelled). Echo back the value provided by the requester.
CrossID	[1..1]	String	CrossID for the replacement order
OrigCrossID	[1..1]	String	Must match the CrossID of the previous cross order. Same order chaining mechanism as CLOrdID/OrigCLOrdID with single order Cancel/Replace.
HostCrossID	[0..1]	String	Host assigned entity ID that can be used to reference all components of a cross; sides + strategy + legs
CrossType	[1..1]	CodeSet	
CrossPrioritization	[1..1]	CodeSet	
RootParties	[0..*]	Group	Insert here the set of "Root Parties" fields defined in "common components of application messages" Used for acting parties that applies to the whole message, not individual sides.
SideCrossOrdModGrp	[1..*]	Group	Must be 1 or 2
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	Number of underlyings
InstrmtLegGrp	[0..*]	Group	Number of Legs

Name	Mult.	Type	Description
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values.
HandlInst	[0..1]	CodeSet	
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited. If OrdType=P, exactly one of the following values (ExecInst = L, R, M, P, O, T, or W) must be specified.
MinQty	[0..1]	Qty	
MinQtyMethod	[0..1]	CodeSet	
MatchIncrement	[0..1]	Qty	
MaxPriceLevels	[0..1]	int	
DisplayInstruction	[0..1]	Component	Insert here the set of "DisplayInstruction" fields defined in "common components of application messages"
MaxFloor	[0..1]	Qty	
MarketSegmentID	[0..1]	String	
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
ProcessCode	[0..1]	CodeSet	Used to identify soft trades at order entry.
PrevClosePx	[0..1]	Price	Useful for verifying security identification
LocateReqd	[0..1]	CodeSet	Required for short sell orders
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary.
TransBkdTime	[0..1]	UTCTimestamp	A date and time stamp to indicate when this order was booked with the agent prior to submission to the VMU
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" (repeating group of Fixed Income stipulations) fields defined in "Common Components of Application Messages"
OrdType	[1..1]	CodeSet	
PriceType	[0..1]	CodeSet	

Name	Mult.	Type	Description
Price	[0..1]	Price	Required for limit OrdTypes. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points). Can be used to specify a limit price for a pegged order, previously indicated, etc.
PriceProtectionScope	[0..1]	CodeSet	
StopPx	[0..1]	Price	Required for OrdType = "Stop" or OrdType = "Stop limit".
TriggeringInstruction	[0..1]	Component	Insert here the set of "TriggeringInstruction" fields defined in "common components of application messages"
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" (Fixed Income spread or benchmark curve) fields defined in "Common Components of Application Messages"
YieldData	[0..1]	Component	Insert here the set of "YieldData" (yield-related) fields defined in "Common Components of Application Messages"
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
ComplianceID	[0..1]	String	
IOIID	[0..1]	String	Required for Previously Indicated Orders (OrdType=E)
QuoteID	[0..1]	String	Required for Previously Quoted Orders (OrdType=D)
TimeInForce	[0..1]	CodeSet	Absence of this field indicates Day order
EffectiveTime	[0..1]	UTCTimestamp	Can specify the time at which the order should be considered valid
ExpireDate	[0..1]	LocalMktDate	Conditionally required if TimeInForce = GTD and ExpireTime is not specified.
ExpireTime	[0..1]	UTCTimestamp	Conditionally required if TimeInForce = GTD and ExpireDate is not specified.
GTBookingInst	[0..1]	CodeSet	States whether executions are booked out or accumulated on a partially filled GT order
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)=10 (Good for Time)
ExposureDurationUnit	[0..1]	CodeSet	
TradingCapacity	[0..1]	CodeSet	
MaxShow	[0..1]	Qty	

Name	Mult.	Type	Description
PegInstructions	[0..1]	Component	Insert here the set of "PegInstruction" fields defined in "Common Components of Application Messages"
DiscretionInstructions	[0..1]	Component	Insert here the set of "DiscretionInstruction" fields defined in "Common Components of Application Messages"
TargetStrategy	[0..1]	CodeSet	The target strategy of the order
StrategyParametersGrp	[0..*]	Group	Strategy parameter block
TargetStrategyParameters	[0..1]	String	For further specification of the TargetStrategy
ParticipationRate	[0..1]	Percentage	Mandatory for a TargetStrategy=Participate order and specifies the target participation rate. For other order types optionally specifies a volume limit (i.e. do not be more than this percent of the market volume)
CancellationRights	[0..1]	CodeSet	For CIV - Optional
MoneyLaunderingStatus	[0..1]	CodeSet	
RegistID	[0..1]	String	Reference to Registration Instructions message for this Order.
Designation	[0..1]	String	Supplementary registration information for this Order
ThrottleInst	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	



## 35 CrossOrderCancelRequest

Category: CrossOrders

### 35.1 Message Functionality

Used to fully cancel the remaining open quantity of a cross order.

### 35.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = u (lowercase U)
OrderID	[0..1]	String	Unique identifier of most recent order as assigned by sell-side (broker, exchange, ECN).
OrderRequestID	[0..1]	int	Required if provided on the order being cancelled. Echo back the value provided by the requester.
CrossID	[1..1]	String	CrossID for the replacement order
OrigCrossID	[1..1]	String	Must match the CrossID of previous cross order. Same order chaining mechanism as ClOrdID/OrigClOrdID with single order Cancel/Replace.
HostCrossID	[0..1]	String	Host assigned entity ID that can be used to reference all components of a cross; sides + strategy + legs
CrossType	[1..1]	CodeSet	
CrossPrioritization	[1..1]	CodeSet	
RootParties	[0..*]	Group	Insert here the set of "Root Parties" fields defined in "common components of application messages" Used for acting parties that applies to the whole message, not individual sides.
SideCrossOrdCxlGrp	[1..*]	Group	Must be 1 or 2
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	Number of underlyings
InstrmtLegGrp	[0..*]	Group	Number of Leg
MarketSegmentID	[0..1]	String	

Name	Mult.	Type	Description
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary.
StandardTrailer	[1..1]	Component	

## 36 CrossRequest

Category: Indication

### 36.1 Message Functionality

The CrossRequest(35=DS) message is used to indicate the submission of orders or quotes that may result in a crossed trade.

### 36.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = DS
CrossRequestID	[1..1]	String	Unique identifier for cross request message.
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
Instrument	[1..1]	Component	
OrderQty	[0..1]	Qty	Can be used to announce a maximum quantity that is subject to crossing.
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
StandardTrailer	[1..1]	Component	

## 37 CrossRequestAck

Category: Indication

### 37.1 Message Functionality

The CrossRequestAck(35=DT) message is used to confirm the receipt of a CrossRequest(35=DS) message.

### 37.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = DT
CrossRequestID	[1..1]	String	Unique identifier for the cross request message being confirmed.
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
Instrument	[1..1]	Component	
OrderQty	[0..1]	Qty	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
StandardTrailer	[1..1]	Component	

## 38 DerivativeSecurityList

Category: SecuritiesReferenceData

### 38.1 Message Functionality

The Derivative Security List message is used to return a list of securities that matches the criteria specified in a Derivative Security List Request.

### 38.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AA (2 A's)
ApplicationSequenceControl	[0..1]	Component	
SecurityReportID	[0..1]	int	
SecurityReqID	[0..1]	String	
SecurityResponseID	[0..1]	String	Identifier for the Derivative Security List message
SecurityRequestResult	[0..1]	CodeSet	Result of the Security Request identified by SecurityReqID
SecurityRejectReason	[0..1]	CodeSet	Used to specify a rejection reason when SecurityResponseType (323) is equal to 1 (Invalid or unsupported request) or 5 (Request for instrument data not supported).
ClearingBusinessDate	[0..1]	LocalMktDate	
UnderlyingInstrument	[0..1]	Component	Underlying security for which derivatives are being returned
DerivativeSecurityDefinition	[0..1]	Component	Group block which contains all information for an option family. If provided DerivativeSecurityDefinition qualifies the strikes specified in the Instrument block.
LastUpdateTime	[0..1]	UTCTimestamp	Represents the time at which a security was last updated
TransactTime	[0..1]	UTCTimestamp	
TotNoRelatedSym	[0..1]	int	Used to indicate the total number of securities being returned for this request. Used in the event that message fragmentation is required.

Name	Mult.	Type	Description
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
RelSymDerivSecGrp	[0..*]	Group	Specifies the number of repeating symbols (instruments) specified
StandardTrailer	[1..1]	Component	

## 39 DerivativeSecurityListRequest

Category: SecuritiesReferenceData

### 39.1 Message Functionality

The Derivative Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request

### 39.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = z (lowercase Z)
SecurityReqID	[1..1]	String	
SecurityListRequestType	[1..1]	CodeSet	
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
UnderlyingInstrument	[0..1]	Component	Specifies the underlying instrument
DerivativeInstrument	[0..1]	Component	Group block which contains all information for an option family.
SecuritySubType	[0..1]	String	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
Text	[0..1]	String	Comment, instructions, or other identifying information.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
TradingSessionID	[0..1]	CodeSet	Optional Trading Session Identifier to specify a particular trading session for which you want to obtain a list of securities that are tradeable.
TradingSessionSubID	[0..1]	CodeSet	
SubscriptionRequestType	[0..1]	CodeSet	Subscribe or unsubscribe for security status to security specified in request.
StandardTrailer	[1..1]	Component	

## 40 DerivativeSecurityListUpdateReport

Category: SecuritiesReferenceData

### 40.1 Message Functionality

The Derivative Security List Update Report message is used to send updates to an option family or the strikes that comprise an option family.

### 40.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BR
ApplicationSequenceControl	[0..1]	Component	
SecurityReqID	[0..1]	String	
SecurityResponseID	[0..1]	String	Identifier for the Derivative Security List message
SecurityRequestResult	[0..1]	CodeSet	Result of the Security Request identified by SecurityReqID
SecurityUpdateAction	[0..1]	CodeSet	Updates can be applied to Underlying or option class. If Series information provided, then Series has explicitly changed
UnderlyingInstrument	[0..1]	Component	Underlying security for which derivatives are being returned
DerivativeSecurityDefinition	[0..1]	Component	Group block which contains all information for an option family. If provided DerivativeSecurityDefinition qualifies the strikes specified in the Instrument block. DerivativeSecurityDefinition contains the following components: DerivativeInstrument, DerivativeInstrumentExtension, MarketSegmentGrp
LastUpdateTime	[0..1]	UTCTimestamp	Represents the time at which a security was last updated
TransactTime	[0..1]	UTCTimestamp	
TotNoRelatedSym	[0..1]	int	Used to indicate the total number of securities being returned for this request. Used in the event that message fragmentation is required.



Name	Mult.	Type	Description
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
RelSymDerivSecUpdGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 41 DontKnowTrade

Category: SingleGeneralOrderHandling

### 41.1 Message Functionality

The Don't Know Trade (DK) message notifies a trading partner that an electronically received execution has been rejected. This message can be thought of as an execution reject message.

### 41.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = Q
OrderID	[1..1]	String	Broker Order ID as identified on problem execution
SecondaryOrderID	[0..1]	String	
ExecID	[1..1]	String	Execution ID of problem execution
DKReason	[1..1]	CodeSet	
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	Number of underlyings
InstrmtLegGrp	[0..*]	Group	Number of Legs
Side	[1..1]	CodeSet	
OrderQtyData	[1..1]	Component	Insert here the set of "OrderQtyData" fields defined in "Common Components of Application Messages"
LastQty	[0..1]	Qty	Required if specified on the ExecutionRpt
LastPx	[0..1]	Price	Required if specified on the ExecutionRpt
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 42 Email

Category: EventCommunication

### 42.1 Message Functionality

The email message is similar to the format and purpose of the News message, however, it is intended for private use between two parties.

### 42.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = C
EmailThreadID	[1..1]	String	Unique identifier for the email message thread
EmailType	[1..1]	CodeSet	
OrigTime	[0..1]	UTCTimestamp	
Subject	[1..1]	String	Specifies the Subject text
EncodedSubjectLen	[0..1]	Length	Must be set if EncodedSubject field is specified and must immediately precede it.
EncodedSubject	[0..1]	data	Encoded (non-ASCII characters) representation of the Subject field in the encoded format specified via the MessageEncoding field.
RoutingGrp	[0..*]	Group	
InstrmtGrp	[0..*]	Group	Specifies the number of repeating symbols (instruments) specified
UndInstrmtGrp	[0..*]	Group	Number of underlyings
InstrmtLegGrp	[0..*]	Group	
OrderID	[0..1]	String	
ClOrdID	[0..1]	String	
LinesOfTextGrp	[1..*]	Group	Specifies the number of repeating lines of text specified
RawDataLength	[0..1]	Length	
RawData	[0..1]	data	
AttachmentGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 43 ExecutionAck

Category: SingleGeneralOrderHandling

### 43.1 Message Functionality

The Execution Report Acknowledgement message is an optional message that provides dual functionality to notify a trading partner that an electronically received execution has either been accepted or rejected (DK'd).

### 43.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BN
OrderID	[1..1]	String	
SecondaryOrderID	[0..1]	String	
ClOrdID	[0..1]	String	Conditionally required if the Execution Report message contains a ClOrdID.
ExecAckStatus	[1..1]	CodeSet	Indicates the status of the execution acknowledgement. The "received, not yet processed" is an optional intermediary status that can be used to notify the counterparty that the Execution Report has been received.
ExecID	[1..1]	String	The ExecID of the Execution Report being acknowledged.
DKReason	[0..1]	CodeSet	Conditionally required when ExecAckStatus = 2 (Don't know / Rejected).
Instrument	[1..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
Side	[1..1]	CodeSet	
OrderQtyData	[0..1]	Component	Conditionally required if specified in the ExecutionReport(35=8).
LastQty	[0..1]	Qty	Conditionally required if specified on the Execution Report
LastPx	[0..1]	Price	Conditionally Required if specified on the Execution Report

Name	Mult.	Type	Description
PriceType	[0..1]	CodeSet	Conditionally required if specified on the Execution Report
PriceQualifierGrp	[0..*]	Group	
LastParPx	[0..1]	Price	Conditionally required if specified on the Execution Report
CumQty	[0..1]	Qty	Conditionally required if specified on the Execution Report
AvgPx	[0..1]	Price	Conditionally required if specified on the Execution Report
RegulatoryTradeIDGrp	[0..*]	Group	
Text	[0..1]	String	Conditionally required if DKReason = "other"
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 44 ExecutionReport

Category: SingleGeneralOrderHandling

### 44.1 Message Functionality

The execution report message is used to:

1. confirm the receipt of an order
2. confirm changes to an existing order (i.e. accept cancel and replace requests)
3. relay order status information
4. relay fill information on working orders
5. relay fill information on tradeable or restricted tradeable quotes
6. reject orders
7. report post-trade fees calculations associated with a trade

### 44.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 8
ApplicationSequenceControl	[0..1]	Component	For use in drop copy applications. NOT FOR USE in transactional applications.
OrderID	[1..1]	String	OrderID is required to be unique for each chain of orders.
OrderRequestID	[0..1]	int	Required if provided on the order message. Echo back the value provided in the order message.
MassOrderRequestID	[0..1]	String	Can be used to link execution to the MassOrder(35=DJ) message.
SecondaryOrderID	[0..1]	String	Can be used to provide order id used by exchange or executing system. Can alternatively be used to convey implicit order priority.
SecondaryClOrdID	[0..1]	String	
SecondaryExecID	[0..1]	String	

Name	Mult.	Type	Description
ClOrdID	[0..1]	String	Required when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID(11). In the case of quotes can be mapped to: - QuoteID(117) of a single Quote(35=S). - QuoteEntryID(299) of a MassQuote(35=i). - BidID(390) or OfferID(1867) of a two-sided Quote(35=S). - MassOrderReportID(2424) of a MassOrderAck(35=DK)
QuoteMsgID	[0..1]	String	In the case of quotes can be mapped to: o QuoteMsgID(1166) of a single Quote(35=S). o QuoteID(117) of a MassQuote(35=i)
OrigClOrdID	[0..1]	String	Conditionally required for response to a Cancel or Cancel/Replace request (ExecType(150) = 6 (Pending Cancel, 5 (Replaced), or 4 (Canceled)) when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID(11). ClOrdID(11) of the previous accepted order (NOT the initial order of the day) when canceling or replacing an order.
ClOrdLinkID	[0..1]	String	
MDEntryID	[0..1]	String	Reference to the MDEntryID(278) of this order or quote in the market data.
QuoteRespID	[0..1]	String	Required if responding to a QuoteResponse(35=AJ) message. Echo back the Initiator's value specified in the message.
OrdStatusReqID	[0..1]	String	Required if responding to and if provided on the OrderStatusRequest(35=H) message. Echo back the value provided by the requester.
MassStatusReqID	[0..1]	String	Required if responding to a OrderMassStatusRequest(35=AF). Echo back the value provided by the requester.
HostCrossID	[0..1]	String	Host assigned entity ID that can be used to reference all components of a cross; sides + strategy + legs
TotNumReports	[0..1]	int	Can be used when responding to an OrderMassStatusRequest(35=AF) to identify the total number of ExecutionReport(35=8) messages which will be returned.

Name	Mult.	Type	Description
LastRptRequested	[0..1]	CodeSet	Can be used when responding to an OrderMassStatusRequest(35=AF) to indicate that this is the last ExecutionReport(35=8) messages which will be returned as a result of the request.
Parties	[0..*]	Group	Specifies party information related to the submitter.
TargetParties	[0..*]	Group	Specifies parties not directly associated with or owning the order, who are to be informed to effect processing of the order.
TradeOriginationDate	[0..1]	LocalMktDate	
ContraGrp	[0..*]	Group	
ListID	[0..1]	String	Required for executions against orders which were submitted as part of a list.
CrossID	[0..1]	String	CrossID for the replacement order
OrigCrossID	[0..1]	String	Must match original cross order. Same order chaining mechanism as CLOrdID(11)/OrigCLOrdID(41) with OrderCancelReplaceRequest(35=G).
CrossType	[0..1]	CodeSet	
RefRiskLimitCheckID	[0..1]	String	
RefRiskLimitCheckIDType	[0..1]	CodeSet	Conditionally required when RefRiskLimitCheckID(2334) is specified.
TrdMatchID	[0..1]	String	
TrdMatchSubID	[0..1]	String	
ExecID	[1..1]	String	Unique identifier of execution message as assigned by sell-side (broker, exchange, ECN) (will be 0 (zero) for ExecType(150) = I (Order Status)).
ExecRefID	[0..1]	String	Required for ExecType(150) = H (Trade Cancel) and ExecType(150) = G (Trade Correct).
ExecType	[1..1]	CodeSet	Describes the purpose of the execution report.
ExecTypeReason	[0..1]	CodeSet	Can be used to provide further detail for ExecType(150) field.
OrdStatus	[1..1]	CodeSet	Describes the current state of a CHAIN of orders, same scope as OrderQty, CumQty, LeavesQty, and AvgPx
WorkingIndicator	[0..1]	CodeSet	For optional use with OrdStatus = 0 (New)
CurrentWorkingPrice	[0..1]	Price	
OrdRejReason	[0..1]	CodeSet	For optional use with ExecType = 8 (Rejected)



Name	Mult.	Type	Description
RejectText	[0..1]	String	Reason description for rejecting the transaction request.
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
ExecRestatementReason	[0..1]	CodeSet	Required for ExecType = D (Restated).
AnonymousTradeIndicator	[0..1]	Boolean	
AlgorithmicTradeIndicator	[0..1]	CodeSet	
TrdType	[0..1]	CodeSet	For optional use in reporting trades.
TrdSubType	[0..1]	CodeSet	For optional use in reporting trades.
SecondaryTrdType	[0..1]	CodeSet	For optional use in reporting trades. Conditionally requires presence of TrdType(828).
TertiaryTrdType	[0..1]	CodeSet	For optional use in reporting trades. Conditionally requires presence of SecondaryTrdType(855).
TradeTypeGrp	[0..*]	Group	For optional use in reporting trades as alternative to the use of individual fields.
RegulatoryTransactionType	[0..1]	CodeSet	
RegulatoryTradeIDGrp	[0..*]	Group	
PreviouslyReported	[0..1]	CodeSet	
TradeReportingIndicator	[0..1]	CodeSet	May be used to bilaterally inform counterparty of trade reporting status.
Account	[0..1]	String	Required for executions against electronically submitted orders which were assigned an account by the institution or intermediary
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Specifies type of account
DayBookingInst	[0..1]	CodeSet	
BookingUnit	[0..1]	CodeSet	
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	
PreAllocGrp	[0..*]	Group	Pre-trade allocation instructions.
SettlType	[0..1]	CodeSet	

Name	Mult.	Type	Description
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettleType values. Required for NDFs to specify the "value date".
MatchType	[0..1]	CodeSet	
OrderCategory	[0..1]	CodeSet	
CashMargin	[0..1]	CodeSet	
ClearingFeeIndicator	[0..1]	CodeSet	
Instrument	[1..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	Number of underlyings
PaymentGrp	[0..*]	Group	
Side	[1..1]	CodeSet	
ShortMarkingExemptIndicator	[0..1]	Boolean	
ShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when Side(54) = 6(Sell short exempt).
Stipulations	[0..*]	Group	
QtyType	[0..1]	CodeSet	
OrderQtyData	[0..1]	Component	Conditionally required when the OrderQtyData component is required or specified in a prior, related message. For example, when used in a work flow including a NewOrderSingle(35=D) or NewOrderCross(35=s) message, the OrderQtyData component is a required component in these messages and thus the component is required here. When the OrderQtyData component is optional in a related message, such as the NewOrderMultileg(35=AB), the component is required here when specified in the prior, related NewOrderMultileg(35=AB) message.
LotType	[0..1]	CodeSet	
OrdType	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
Price	[0..1]	Price	Required if specified on the order
PriceProtectionScope	[0..1]	CodeSet	
StopPx	[0..1]	Price	Required if specified on the order
TriggeringInstruction	[0..1]	Component	

Name	Mult.	Type	Description
Triggered	[0..1]	CodeSet	
PegInstructions	[0..1]	Component	
DiscretionInstructions	[0..1]	Component	
PeggedPrice	[0..1]	Price	The current price the order is pegged at
PeggedRefPrice	[0..1]	Price	The reference price of a pegged order.
DiscretionPrice	[0..1]	Price	The current discretionary price of the order
TradePriceNegotiationMethod	[0..1]	CodeSet	
UpfrontPrice	[0..1]	Price	Required if specified on the order
UpfrontPriceType	[0..1]	CodeSet	
TargetStrategy	[0..1]	CodeSet	The target strategy of the order
StrategyParametersGrp	[0..*]	Group	Strategy parameter block
TargetStrategyParameters	[0..1]	String	For further specification of the TargetStrategy
ParticipationRate	[0..1]	Percentage	Mandatory for a TargetStrategy=Participate order and specifies the target participation rate. For other order types optionally specifies a volume limit (i.e. do not be more than this percent of the market volume)
TargetStrategyPerformance	[0..1]	float	For communication of the performance of the order versus the target strategy
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
TimeInForce	[0..1]	CodeSet	Absence of this field indicates Day order
EffectiveTime	[0..1]	UTCTimestamp	Time specified on the order at which the order should be considered valid
ExpireDate	[0..1]	LocalMktDate	Conditionally required if TimeInForce(59) = 6 (GTD) and ExpireTime(126) is not specified.
ExpireTime	[0..1]	UTCTimestamp	Conditionally required if TimeInForce(59) = 6 (GTD) and ExpireDate(432) is not specified.

Name	Mult.	Type	Description
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)=10 (Good for Time)
ExposureDurationUnit	[0..1]	CodeSet	
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited.
AuctionInstruction	[0..1]	CodeSet	
AggressorIndicator	[0..1]	CodeSet	
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
TradingCapacity	[0..1]	CodeSet	
RegulatoryReportType	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	
TradePublishIndicator	[0..1]	CodeSet	Applies to trades resulting from the order.
CustOrderCapacity	[0..1]	CodeSet	
OrderAttributeGrp	[0..*]	Group	
LastQty	[0..1]	Qty	Quantity (e.g. shares) bought/sold on this (last) fill. Required if ExecType(150) = F (Trade) or ExecType(150) = G (Trade Correct) unless FillsGrp or OrderEventGrp is used. If ExecType(150) = 7 (Stopped), represents the quantity stopped/guaranteed/protected for.
CalculatedCcyLastQty	[0..1]	Qty	Used for FX trades to express the quantity or amount of the other side of the currency. Conditionally required if ExecType(150) = F (Trade) or G (Trade Correct) and is an FX trade.
LastSwapPoints	[0..1]	PriceOffset	Optionally used when ExecType(150) = F (Trade) or G (Trade Correct) and is a FX Swap trade. Used to express the swap points for the swap trade event.
UnderlyingLastQty	[0..1]	Qty	
LastQtyVariance	[0..1]	Qty	

Name	Mult.	Type	Description
LastPx	[0..1]	Price	Price of this (last) fill. Required if ExecType(150) = ExecType = F (Trade) or G (Trade Correct) unless FillsGrp or OrderEventGrp or TradePriceCondition(1839)=17 (Price is pending) or 18 (Price is not applicable) is used. Should represent the "all-in" (LastSpotRate(194) + LastForwardPoints(195)) rate for F/X orders.). If ExecType(150) = 7 (Stopped), represents the price stopped/guaranteed/protected at. Not required for FX Swap when ExecType(150) = F (Trade) or G (Trade Correct) as there is no "all-in" rate that applies to both legs of the FX Swap.
UnderlyingLastPx	[0..1]	Price	
LastParPx	[0..1]	Price	Last price expressed in percent-of-par. Conditionally required for Fixed Income trades when LastPx(31) is expressed in Yield, Spread, Discount or any other price type that is not percent-of-par.
MidPx	[0..1]	Price	
LastSpotRate	[0..1]	Price	Applicable for F/X orders
LastForwardPoints	[0..1]	PriceOffset	Applicable for F/X orders
LastUpfrontPrice	[0..1]	Price	Upfront Price for CDS transactions. Conditionally required if TradePriceNegotiationMethod(1740) = 4(Percent of par and upfront amount), 5(Deal spread and upfront amount) or 6(Upfront points and upfront amount).
ReportingPx	[0..1]	Price	
ReportingQty	[0..1]	Qty	
LastMkt	[0..1]	Exchange	If ExecType(150) = F (Trade), indicates the market where the trade was executed. If ExecType(150) = 0 (New (0)), indicates the market where the order was routed.
VenueType	[0..1]	CodeSet	
MarketSegmentID	[0..1]	String	
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	
ExDestinationType	[0..1]	CodeSet	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	

Name	Mult.	Type	Description
TimeBracket	[0..1]	String	
LastCapacity	[0..1]	CodeSet	
LimitAmts	[0..*]	Group	Insert here the set of "LimitAmts" fields defined in "Common Components"
LeavesQty	[1..1]	Qty	Quantity open for further execution. If the OrdStatus(39) is = 4 (Canceled), 3 (Done For Day), C (Expired), B (Calculated), or 8 (Rejected) (in which case the order is no longer active) then LeavesQty(151) could be 0, otherwise $\text{LeavesQty}(151) = \text{OrderQty}(38) - \text{CumQty}(14)$ .
CumQty	[1..1]	Qty	Currently executed quantity for chain of orders.
CxlQty	[0..1]	Qty	Can be used to specify the remaining quantity that was cancelled prior to order reaching terminal state (i.e. when $\text{LeavesQty}(151)=0$ ). If specified, $\text{OrderQty}(38) = \text{CumQty}(14) + \text{CxlQty}(84)$ .
AvgPx	[0..1]	Price	Not required for markets where average price is not calculated by the market. Conditionally required otherwise.
DayOrderQty	[0..1]	Qty	For GT orders on days following the day of the first trade.
DayCumQty	[0..1]	Qty	For GT orders on days following the day of the first trade.
DayAvgPx	[0..1]	Price	For GT orders on days following the day of the first trade.
TotNoFills	[0..1]	int	Used to support fragmentation. Sum of NoFills(1362) across all messages with the same ExecID(17).
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
FillsGrp	[0..*]	Group	Specifies the partial fills included in this ExecutionReport(35=8), mutually exclusive with OrderEventGrp component.
OrderEventGrp	[0..*]	Group	Specifies the order events included in this ExecutionReport(35=8), mutually exclusive with FillsGrp component.
EventInitiatorType	[0..1]	CodeSet	
GTBookingInst	[0..1]	CodeSet	States whether executions are booked out or accumulated on a partially filled GT order

Name	Mult.	Type	Description
TradeDate	[0..1]	LocalMktDate	Used when reporting other than current day trades.
TransactTime	[0..1]	UTCTimestamp	Time the transaction represented by this ExecutionReport(35=8) occurred.
ReportToExch	[0..1]	CodeSet	
CommissionData	[0..1]	Component	Note: On a fill/partial-fill message, it represents value for that fill/partial fill. On ExecType(150) = B (Calculated), it represents cumulative value for the order.
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData component if multiple commissions or enhanced attributes are needed.
SpreadOrBenchmarkCurveData	[0..1]	Component	
RelativeValueGrp	[0..*]	Group	
YieldData	[0..1]	Component	
GrossTradeAmt	[0..1]	Amt	
NumDaysInterest	[0..1]	int	
ExDate	[0..1]	LocalMktDate	
AccruedInterestRate	[0..1]	Percentage	
AccruedInterestAmt	[0..1]	Amt	
InterestAtMaturity	[0..1]	Amt	For fixed income products which pay lump-sum interest at maturity.
EndAccruedInterestAmt	[0..1]	Amt	For repurchase agreements the accrued interest on termination.
StartCash	[0..1]	Amt	For repurchase agreements the start (dirty) cash consideration.
EndCash	[0..1]	Amt	For repurchase agreements the end (dirty) cash consideration.
TradedFlatSwitch	[0..1]	CodeSet	
BasisFeatureDate	[0..1]	LocalMktDate	
BasisFeaturePrice	[0..1]	Price	
Concession	[0..1]	Amt	
TotalTakedown	[0..1]	Amt	
NetMoney	[0..1]	Amt	On a fill/partial fill message, it represents value for that fill/partial fill. On a ExecType(150) = B (Calculated) message, it represents cumulative value for the order. Value expressed in the currency reflected by the Currency(15) field.

Name	Mult.	Type	Description
SettlCurrAmt	[0..1]	Amt	Used to report results of forex accommodation trade.
SettlCurrency	[0..1]	Currency	Used to report results of forex accommodation trade. Required for Non-Deliverable Forwards.
SettlCurrencyCodeSource	[0..1]	CodeSet	
RateSource	[0..*]	Group	
OffshoreIndicator	[0..1]	CodeSet	
SettlCurrFxRate	[0..1]	float	Foreign exchange rate used to compute SettlCurrAmt(119) from Currency(15) to SettlCurrency(120).
SettlCurrFxRateCalc	[0..1]	CodeSet	Specifies whether the SettlCurrFxRate(155) should be multiplied or divided.
HandlInst	[0..1]	CodeSet	
MinQty	[0..1]	Qty	
MinQtyMethod	[0..1]	CodeSet	
MatchIncrement	[0..1]	Qty	
MaxPriceLevels	[0..1]	int	
MaximumPriceDeviation	[0..1]	Percentage	
ValueChecksGrp	[0..*]	Group	
MatchingInstructions	[0..*]	Group	
SelfMatchPreventionID	[0..1]	String	May be used as an alternative to MatchingInstructions when the identifier does not appear in another field.
SelfMatchPreventionInstruction	[0..1]	CodeSet	May be used to return the self-match prevention instruction provided on the order placement message. Omit for unsolicited cancellations and use ExecRestatementReason(378) to convey the self-match prevention instruction that caused the cancellation.
CrossedIndicator	[0..1]	CodeSet	
DisplayInstruction	[0..1]	Component	
DisclosureInstructionGrp	[0..*]	Group	
MaxFloor	[0..1]	Qty	
ClearingAccountType	[0..1]	CodeSet	
PositionEffect	[0..1]	CodeSet	For use in derivatives omnibus accounting
MaxShow	[0..1]	Qty	



Name	Mult.	Type	Description
BookingType	[0..1]	CodeSet	Method for booking out this order. Used when notifying a broker that an order to be settled by that broker is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
LastForwardPoints2	[0..1]	PriceOffset	Can be used with OrdType = "Forex - Swap" to specify the forward points (added to LastSpotRate) for the future portion of a F/X swap.
MultiLegReportingType	[0..1]	CodeSet	Default is a single security if not specified.
ContingencyType	[0..1]	CodeSet	For contingency orders, the type of contingency as specified in the order.
CancellationRights	[0..1]	CodeSet	For CIV - Optional
MoneyLaunderingStatus	[0..1]	CodeSet	
RegistID	[0..1]	String	Reference to Registration Instructions message for this Order.
Designation	[0..1]	String	Supplementary registration information for this Order
TransBkdTime	[0..1]	UTCTimestamp	For CIV - Optional
ExecValuationPoint	[0..1]	UTCTimestamp	For CIV - Optional
ExecPriceType	[0..1]	CodeSet	For CIV - Optional
ExecPriceAdjustment	[0..1]	float	For CIV - Optional
PriorityIndicator	[0..1]	CodeSet	
PriceImprovement	[0..1]	PriceOffset	
LastLiquidityInd	[0..1]	CodeSet	Applicable only on OrdStatus(39) = 1 of (Partially filled) or 2(Filled).
ContAmtGrp	[0..*]	Group	

Name	Mult.	Type	Description
InstrmtLegExecGrp	[0..*]	Group	Specifies the leg executions of a multi-leg order or quote.
CopyMsgIndicator	[0..1]	Boolean	
MiscFeesGrp	[0..*]	Group	Required if any miscellaneous fees are reported.
DividendYield	[0..1]	Percentage	
ManualOrderIndicator	[0..1]	Boolean	
CustDirectedOrder	[0..1]	Boolean	
ReceivedDeptID	[0..1]	String	
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
OrderOrigination	[0..1]	CodeSet	
ContraOrderOrigination	[0..1]	CodeSet	May be used for cross orders submitted with single order messages.
OriginatingDeptID	[0..1]	String	
ReceivingDeptID	[0..1]	String	
RoutingArrangementIndicator	[0..1]	CodeSet	
ContraRoutingArrangementIndicator	[0..1]	CodeSet	May be used for cross orders submitted with single order messages.
AffiliatedFirmsTradeIndicator	[0..1]	Boolean	
OwnerType	[0..1]	CodeSet	
OrderOwnershipIndicator	[0..1]	CodeSet	Can be used to highlight change of order ownership.
TrdRegTimestamps	[0..*]	Group	
TrdRegPublicationGrp	[0..*]	Group	
TradePriceConditionGrp	[0..*]	Group	
TradeContinuation	[0..1]	CodeSet	May be used to indicate the post-execution trade continuation or lifecycle event. This should echo the value in the message that resulted in this report.
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
Volatility	[0..1]	float	
TimeToExpiration	[0..1]	float	
RiskFreeRate	[0..1]	float	
PriceDelta	[0..1]	float	
CoverPrice	[0..1]	Price	
ThrottleResponse	[0..1]	Component	
RefOrderID	[0..1]	String	
RefOrderIDSource	[0..1]	CodeSet	
RefClOrdID	[0..1]	String	
RelatedOrderGrp	[0..*]	Group	May be used to provide a list of orders and their relationship to the order identified in this message.
AuctionType	[0..1]	CodeSet	
AuctionAllocationPct	[0..1]	Percentage	
LockedQty	[0..1]	Qty	
SecondaryLockedQty	[0..1]	Qty	
LockType	[0..1]	CodeSet	
ReleaseInstruction	[0..1]	CodeSet	
ReleaseQty	[0..1]	Qty	
RelatedHighPrice	[0..1]	Price	
RelatedLowPrice	[0..1]	Price	
RelatedPriceSource	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 45 Heartbeat

Category: Session

### 45.1 Message Functionality

The Heartbeat monitors the status of the communication link and identifies when the last of a string of messages was not received.

### 45.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 0
TestReqID	[0..1]	String	Required when the heartbeat is the result of a Test Request message.
StandardTrailer	[1..1]	Component	

## 46 IOI

Category: Indication

### 46.1 Message Functionality

Indication of interest messages are used to market merchandise which the broker is buying or selling in either a proprietary or agency capacity. The indications can be time bound with a specific expiration value. Indications are distributed with the understanding that other firms may react to the message first and that the merchandise may no longer be available due to prior trade.

Indication messages can be transmitted in various transaction types; NEW, CANCEL, and REPLACE. All message types other than NEW modify the state of the message identified in IOIRefID.

### 46.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 6
ApplicationSequenceControl	[0..1]	Component	
IOIID	[1..1]	String	
IOITransType	[1..1]	CodeSet	
IOIRefID	[0..1]	String	Required for Cancel and Replace IOITransType messages
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
InstrumentExtension	[0..1]	Component	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages".
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	Number of underlyings
RelatedInstrumentGrp	[0..*]	Group	
Side	[1..1]	CodeSet	Side of Indication. Valid subset of values:. 1 = Buy. 2 = Sell. 7 = Undisclosed. B = As Defined (for multilegs). C = Opposite (for multilegs)

Name	Mult.	Type	Description
QtyType	[0..1]	CodeSet	
OrderQtyData	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". The value zero is used if NoLegs repeating group is used. Applicable if needed to express CashOrder Qty (tag 152)
IOIQty	[1..1]	CodeSet	The value zero is used if NoLegs repeating group is used
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" (symbology) fields defined in "Common Components of Application Messages"
InstrmtLegIOIGrp	[0..*]	Group	Required for multileg IOIs
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
Price	[0..1]	Price	
ValidUntilTime	[0..1]	UTCTimestamp	
IOIQtyInd	[0..1]	CodeSet	
IOINaturalFlag	[0..1]	CodeSet	
IOIQualGrp	[0..*]	Group	Required if any IOIQualifiers are specified. Indicates the number of repeating IOIQualifiers.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
TransactTime	[0..1]	UTCTimestamp	
URLLink	[0..1]	String	A URL (Uniform Resource Locator) link to additional information (i.e. <a href="http://www.XYZ.com/research.html">http://www.XYZ.com/research.html</a> )
RoutingGrp	[0..*]	Group	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" (Fixed Income spread or benchmark curve) fields defined in "Common Components of Application Messages"
RelativeValueGrp	[0..*]	Group	

Name	Mult.	Type	Description
YieldData	[0..1]	Component	
StandardTrailer	[1..1]	Component	

## 47 ListCancelRequest

Category: ProgramTrading

### 47.1 Message Functionality

The List Cancel Request message type is used by institutions wishing to cancel previously submitted lists either before or during execution.

### 47.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = K
ListID	[1..1]	String	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "common components of application messages"
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader or trading system.
TradeOriginationDate	[0..1]	LocalMktDate	
TradeDate	[0..1]	LocalMktDate	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	



## 48 ListExecute

Category: ProgramTrading

### 48.1 Message Functionality

The List Execute message type is used by institutions to instruct the broker to begin execution of a previously submitted list. This message may or may not be used, as it may be mirroring a phone conversation.

### 48.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = L
ListID	[1..1]	String	Must be unique, by customer, for the day
ClientBidID	[0..1]	String	Used with BidType=Disclosed to provide the sell side the ability to determine the direction of the trade to execute.
BidID	[0..1]	String	
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader or trading system.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 49 ListStatus

Category: ProgramTrading

### 49.1 Message Functionality

The list status message is issued as the response to a List Status Request message sent in an unsolicited fashion by the sell-side. It indicates the current state of the orders within the list as they exist at the broker's site. This message may also be used to respond to the List Cancel Request.

### 49.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = N
ListID	[1..1]	String	
ListStatusType	[1..1]	CodeSet	
NoRpts	[1..1]	int	Total number of messages required to status complete list.
ListOrderStatus	[1..1]	CodeSet	
ContingencyType	[0..1]	CodeSet	
ListRejectReason	[0..1]	CodeSet	
RptSeq	[1..1]	int	Sequence number of this report message.
ListStatusText	[0..1]	String	
EncodedListStatusTextLen	[0..1]	Length	Must be set if EncodedListStatusText field is specified and must immediately precede it.
EncodedListStatusText	[0..1]	data	Encoded (non-ASCII characters) representation of the ListStatusText field in the encoded format specified via the MessageEncoding field.
TransactTime	[0..1]	UTCTimestamp	
TotNoOrders	[1..1]	int	Used to support fragmentation. Sum of NoOrders across all messages with the same ListID.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
OrdListStatGrp	[1..*]	Group	Number of orders statused in this message, i.e. number of repeating groups to follow.
StandardTrailer	[1..1]	Component	

## 50 ListStatusRequest

Category: ProgramTrading

### 50.1 Message Functionality

The list status request message type is used by institutions to instruct the broker to generate status messages for a list.

### 50.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = M
ListID	[1..1]	String	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 51 ListStrikePrice

Category: ProgramTrading

### 51.1 Message Functionality

The strike price message is used to exchange strike price information for principal trades. It can also be used to exchange reference prices for agency trades.

### 51.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = m (lowercase)
ListID	[1..1]	String	
TotNoStrikes	[1..1]	int	Used to support fragmentation. Sum of NoStrikes across all messages with the same ListID.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
InstrmtStrkPxGrp	[1..*]	Group	Number of strike price entries
StandardTrailer	[1..1]	Component	

## 52 Logon

Category: Session

### 52.1 Message Functionality

The logon message authenticates a user establishing a connection to a remote system. The logon message must be the first message sent by the application requesting to initiate a FIX session.

### 52.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = A
EncryptMethod	[1..1]	CodeSet	(Always unencrypted)
HeartBtInt	[1..1]	int	Note same value used by both sides
RawDataLength	[0..1]	Length	Required for some authentication methods
RawData	[0..1]	data	Required for some authentication methods
ResetSeqNumFlag	[0..1]	CodeSet	Indicates both sides of a FIX session should reset sequence numbers
NextExpectedMsgSeqNum	[0..1]	SeqNum	Optional, alternative via counterparty bi-lateral agreement message gap detection and recovery approach (see "Logon Message NextExpectedMsgSeqNum Processing" section)
MaxMessageSize	[0..1]	Length	Can be used to specify the maximum number of bytes supported for messages received
MsgTypeGrp	[0..*]	Group	
TestMessageIndicator	[0..1]	CodeSet	Can be used to specify that this FIX session will be sending and receiving "test" vs. "production" messages.
Username	[0..1]	String	
Password	[0..1]	String	Note: minimal security exists without transport-level encryption.
NewPassword	[0..1]	String	Specifies a new password for the FIX Logon. The new password is used for subsequent logons.
EncryptedPasswordMethod	[0..1]	int	
EncryptedPasswordLen	[0..1]	Length	
EncryptedPassword	[0..1]	data	

Name	Mult.	Type	Description
EncryptedNewPasswordLen	[0..1]	Length	
EncryptedNewPassword	[0..1]	data	Encrypted new password- encrypted via the method specified in the field EncryptedPasswordMethod(1400)
SessionStatus	[0..1]	CodeSet	Session status at time of logon. Field is intended to be used when the logon is sent as an acknowledgement from acceptor of the FIX session.
DefaultApplVerID	[1..1]	CodeSet	The default version of FIX messages used in this session.
DefaultApplExtID	[0..1]	int	The default extension pack for FIX messages used in this session
DefaultCstmApplVerID	[0..1]	String	The default custom application version (dictionary) for FIX messages used in this session
Text	[0..1]	String	Available to provide a response to logon when used as a logon acknowledgement from acceptor back to the logon initiator.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 53 Logout

Category: Session

### 53.1 Message Functionality

The logout message initiates or confirms the termination of a FIX session. Disconnection without the exchange of logout messages should be interpreted as an abnormal condition.

### 53.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 5
SessionStatus	[0..1]	CodeSet	Session status at time of logout.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 54 MarginRequirementInquiry

Category: MarginRequirementManagement

### 54.1 Message Functionality

The purpose of this message is to initiate a margin requirement inquiry for a margin account. The inquiry may be submitted at the detail level or the summary level. It can also be used to inquire margin excess/deficit or net position information. Margin excess/deficit will provide information about the surplus or shortfall compared to the previous trading day or a more recent margin calculation. An inquiry for net position information will trigger one or more PositionReport messages instead of one or more MarginRequirementReport messages.

If the inquiry is made at the detail level, an Instrument block must be provided with the desired level of detail. If the inquiry is made at the summary level, the Instrument block is not provided, implying a summary request is being made. For example, if the inquiring firm specifies the Security Type of “FUT” in the Instrument block, then a detail report will be generated containing the margin requirements for all futures positions for the inquiring account. Similarly, if the inquiry is made at the summary level, the report will contain the total margin requirement aggregated to the margin account level.

### 54.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CH
MarginReqmtInqID	[1..1]	String	Unique identifier for this message
MarginReqmtInqQualGrp	[1..*]	Group	Type of margin requirement inquiry
SubscriptionRequestType	[0..1]	CodeSet	Used to subscribe / unsubscribe for margin requirement reports. If the field is absent, the default will be snapshot request only - no subscription.
ResponseTransportType	[0..1]	CodeSet	Ability to specify whether the response to the request should be delivered inband or via pre-arranged out-of-band transport.
ResponseDestination	[0..1]	String	URI destination name. Used if ResponseTransportType is out-of-band.
Parties	[0..*]	Group	
ClearingBusinessDate	[0..1]	LocalMktDate	Indicates the date for which the margin is to be calculated



Name	Mult.	Type	Description
SettlSessID	[0..1]	CodeSet	Indicates the settlement session for which the margin is to be calculated – End Of Day or Intraday
SettlSessSubID	[0..1]	String	
MarginClass	[0..1]	String	Used to identify a group of instruments with similar risk profile.
Instrument	[0..1]	Component	
TransactTime	[0..1]	UTCTimestamp	Represents the time the inquiry was submitted
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 55 MarginRequirementInquiryAck

Category: MarginRequirementManagement

### 55.1 Message Functionality

Used to respond to a Margin Requirement Inquiry.

### 55.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CI
MarginReqmtInqID	[1..1]	String	Unique identifier for this message
MarginReqmtInqQualGrp	[1..*]	Group	Type of margin requirement inquiry
MarginReqmtInqStatus	[1..1]	CodeSet	Status of the Margin Requirement Inquiry referenced by MarginReqmtInqID
MarginReqmtInqResult	[0..1]	CodeSet	Result of the Margin Requirement Inquiry referenced by MarginReqmtInqID – specifies any errors or warnings
TotNumReports	[0..1]	int	Total number of reports generated in response to this inquiry
SubscriptionRequestType	[0..1]	CodeSet	Used to subscribe / unsubscribe for margin requirement reports. If the field is absent, the default will be snapshot request only - no subscription.
ResponseTransportType	[0..1]	CodeSet	Ability to specify whether the response to the request should be delivered inband or via pre-arranged out-of-band transport.
ResponseDestination	[0..1]	String	URI destination name. Used if ResponseTransportType is out-of-band.
Parties	[0..*]	Group	
ClearingBusinessDate	[0..1]	LocalMktDate	Indicates the date for which the margin is to be calculated
SettlSessID	[0..1]	CodeSet	Indicates the settlement session for which the margin is to be calculated – End Of Day or Intraday
SettlSessSubID	[0..1]	String	
MarginClass	[0..1]	String	Used to identify a group of instruments with similar risk profile.

Name	Mult.	Type	Description
Instrument	[0..1]	Component	
TransactTime	[0..1]	UTCTimestamp	Represents the time this message was generated
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 56 MarginRequirementReport

Category: MarginRequirementManagement

### 56.1 Message Functionality

The Margin Requirement Report returns information about margin requirement either as an overview across all margin accounts or on a detailed level due to the inquiry making use of the optional Instrument component block. Application sequencing can be used to re-request a range of reports.

### 56.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CJ
ApplicationSequenceControl	[0..1]	Component	
MarginReqmtRptID	[1..1]	String	Unique identifier for this margin requirement report
MarginReqmtInqID	[0..1]	String	Unique identifier for the inquiry associated with this report. This field should not be provided if the report was sent unsolicited.
MarginReqmtRptType	[1..1]	CodeSet	Type of report provided
TotNumReports	[0..1]	int	Total number of reports generated in response to inquiry referenced by MarginReqmtInqID
LastRptRequested	[0..1]	CodeSet	
UnsolicitedIndicator	[0..1]	CodeSet	Set to 'Y' if message is sent as a result of a subscription request or out of band configuration as opposed to a Margin Requirement Inquiry.
Parties	[0..*]	Group	
RegulatoryReportType	[0..1]	CodeSet	
RegulatoryReportTypeBusinessDate	[0..1]	LocalMktDate	May be used when the business event date differs from when the regulatory report is actually being submitted (typically specified in TrdRegTimestamps component).
TrdRegTimestamps	[0..*]	Group	
ClearingBusinessDate	[0..1]	LocalMktDate	Indicates the date for which the margin is to be calculated
ClearingPortfolioID	[0..1]	String	

Name	Mult.	Type	Description
SettlSessID	[0..1]	CodeSet	Indicates the settlement session for which the margin is to be calculated – End Of Day or Intraday
SettlSessSubID	[0..1]	String	
MarginClass	[0..1]	String	Used to identify a group of instruments with similar risk profile.
Currency	[0..1]	Currency	Base currency of the margin requirement
CurrencyCodeSource	[0..1]	CodeSet	
Instrument	[0..1]	Component	
MarginAmount	[1..*]	Group	Margin requirement amounts
TransactTime	[0..1]	UTCTimestamp	Represents the time this message was generated
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 57 MarketDataIncrementalRefresh

Category: MarketData

### 57.1 Message Functionality

The Market Data message for incremental updates may contain any combination of new, changed, or deleted Market Data Entries, for any combination of instruments, with any combination of trades, imbalances, quotes, index values, open, close, settlement, high, low, and VWAP prices, trade volume and open interest so long as the maximum FIX message size is not exceeded. All of these types of Market Data Entries can be changed and deleted.

### 57.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = X
ApplicationSequenceControl	[0..1]	Component	
MDBookType	[0..1]	CodeSet	Describes the type of book for which the feed is intended. Can be used when multiple feeds are provided over the same connection
MDFeedType	[0..1]	String	Describes a class of service for a given data feed, ie Regular and Market Maker
MDSubFeedType	[0..1]	String	
TradeDate	[0..1]	LocalMktDate	Used to specify the trading date for which a set of market data applies
MDReqID	[0..1]	String	Conditionally required if this message is in response to a Market Data Request.
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
MDIncGrp	[1..*]	Group	Number of entries following.
ApplQueueDepth	[0..1]	int	Depth of application messages queued for transmission as of delivery of this message
ApplQueueResolution	[0..1]	CodeSet	Action taken to resolve application queuing
RoutingGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 58 MarketDataReport

Category: MarketData

### 58.1 Message Functionality

The MarketDataReport(35=DR) message is used to provide delimiting references (e.g. start and end markers in a continuous broadcast) and details about the number of market data messages sent in a given distribution cycle.

### 58.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = DR
ApplicationSequenceControl	[0..1]	Component	
MDReportID	[0..1]	int	Unique identifier for MarketDataReport(35=DR).
MDReportEvent	[1..1]	CodeSet	
MDReportCount	[1..1]	int	
TransactTime	[0..1]	UTCTimestamp	
TotNumReports	[0..1]	int	
TotNoMarketSegmentReports	[0..1]	int	
TotNoInstrumentReports	[0..1]	int	
TotNoPartyDetailReports	[0..1]	int	
TotNoEntitlementReports	[0..1]	int	
TotNoRiskLimitReports	[0..1]	int	
StandardTrailer	[1..1]	Component	

## 59 MarketDataRequest

Category: MarketData

### 59.1 Message Functionality

Some systems allow the transmission of real-time quote, order, trade, trade volume, open interest, and/or other price information on a subscription basis. A MarketDataRequest(35=V) is a general request for market data on specific securities or forex quotes. The values in the fields provided within the request will serve as further filter criteria for the result set.

### 59.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = V
MDReqID	[1..1]	String	Must be unique, or the ID of previous Market Data Request to disable if SubscriptionRequestType(263) = 2(Disable previous Snapshot + Updates Request).
SubscriptionRequestType	[1..1]	CodeSet	SubscriptionRequestType(263) indicates to the other party what type of response is expected. A snapshot request only asks for current information. A subscribe request asks for updates as the status changes. Unsubscribe will cancel any future update messages from the counter party.
Parties	[0..*]	Group	
MarketDepth	[1..1]	int	
MDUpdateType	[0..1]	CodeSet	Required if SubscriptionRequestType(263) = 1(Snapshot + Updates).
AggregatedBook	[0..1]	CodeSet	
OpenCloseSettlFlag	[0..1]	CodeSet	Can be used to clarify a request if MDEntryType(269) = 4 (Opening price), 5 (Closing price), or 6 (Settlement price).
Scope	[0..1]	CodeSet	Defines the scope(s) of the request
MDImplicitDelete	[0..1]	CodeSet	Can be used when MarketDepth(254) >= 2 and MDUpdateType(265) = 1(Incremental Refresh).
MDReqGrp	[1..*]	Group	



Name	Mult.	Type	Description
MarketSegmentScopeGrp	[0..*]	Group	Can be used to limit the result set to the specified markets or market segments.
InstrmtMDReqGrp	[1..*]	Group	
TrdgSesGrp	[0..*]	Group	
ApplQueueAction	[0..1]	CodeSet	Action to take if application level queuing exists
ApplQueueMax	[0..1]	int	Maximum application queue depth that must be exceeded before queuing action is taken.
MDQuoteType	[0..1]	CodeSet	
FastMarketIndicator	[0..1]	Boolean	
StandardTrailer	[1..1]	Component	

## 60 MarketDataRequestReject

Category: MarketData

### 60.1 Message Functionality

The Market Data Request Reject is used when the broker cannot honor the Market Data Request, due to business or technical reasons. Brokers may choose to limit various parameters, such as the size of requests, whether just the top of book or the entire book may be displayed, and whether Full or Incremental updates must be used.

### 60.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = Y
MDReqID	[1..1]	String	Must refer to the MDReqID of the request.
Parties	[0..*]	Group	Insert here the set of Parties (firm identification) fields defined in "Common Components of Application Messages".
MDReqRejReason	[0..1]	CodeSet	
MDRjctGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 61 MarketDataSnapshotFullRefresh

Category: MarketData

### 61.1 Message Functionality

The Market Data messages are used as the response to a Market Data Request message. In all cases, one Market Data message refers only to one Market Data Request. It can be used to transmit a 2-sided book of orders or list of quotes, a list of trades, index values, opening, closing, settlement, high, low, or VWAP prices, the trade volume or open interest for a security, or any combination of these.

### 61.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = W
ApplicationSequenceControl	[0..1]	Component	
TotNumReports	[0..1]	int	Total number of reports returned in response to a request.
MDReportID	[0..1]	int	Unique identifier for the market data report.
ClearingBusinessDate	[0..1]	LocalMktDate	
MDBookType	[0..1]	CodeSet	Describes the type of book for which the feed is intended. Can be used when multiple feeds are provided over the same connection
MDSubBookType	[0..1]	int	Can be used to define a subordinate book.
MarketDepth	[0..1]	int	Can be used to define the current depth of the book.
MDFeedType	[0..1]	String	Describes a class of service for a given data feed, ie Regular and Market Maker
MDSubFeedType	[0..1]	String	
RefreshIndicator	[0..1]	Boolean	
TradeDate	[0..1]	LocalMktDate	Used to specify the trading date for which a set of market data applies
MDReqID	[0..1]	String	Conditionally required if this message is in response to a MarketDataRequest(35=V).
MDStreamID	[0..1]	String	
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	

Name	Mult.	Type	Description
Instrument	[1..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	Required for multileg quotes
RelatedInstrumentGrp	[0..*]	Group	
LastUpdateTime	[1..1]	UTCTimestamp	
FinancialStatus	[0..1]	CodeSet	
CorporateAction	[0..1]	CodeSet	
NetChgPrevDay	[0..1]	PriceOffset	
MDSecurityTradingStatus	[0..1]	CodeSet	
MDHaltReason	[0..1]	CodeSet	
MDFullGrp	[1..*]	Group	
ApplQueueDepth	[0..1]	int	Depth of application messages queued for transmission as of delivery of this message
ApplQueueResolution	[0..1]	CodeSet	Action taken to resolve application queuing
RoutingGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 62 MarketDataStatisticsReport

Category: MarketData

### 62.1 Message Functionality

The MarketDataStatisticsReport(35=DP) is used to provide unsolicited statistical information or in response to a specific request. Each report contains a set of statistics for a single entity which could be a market, a market segment, a security list or an instrument.

### 62.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = DP
ApplicationSequenceControl	[0..1]	Component	
MDStatisticRptID	[1..1]	String	Unique message identifier for the report.
MDStatisticReqID	[0..1]	String	Unique message identifier for the request. Conditionally required if report is sent in response to a MarketDataStatisticsRequest(35=DO) message.
MDStatisticRequestResult	[0..1]	CodeSet	Conditionally required if report is sent in response to a MarketDataStatisticsRequest(35=DO) message.
UnsolicitedIndicator	[0..1]	CodeSet	Set to 'Y' if message is sent as a result of a subscription request not a snapshot request
Parties	[0..*]	Group	
CustOrderCapacity	[0..1]	CodeSet	
TradeDate	[0..1]	LocalMktDate	
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
MarketSegmentDesc	[0..1]	String	
EncodedMktSegmDescLen	[0..1]	Length	Must be set if EncodedMktSegmDesc(1398) field is specified and must immediately precede it.
EncodedMktSegmDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the MarketDesgmentDesc(1396) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
SecurityListID	[0..1]	String	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
Instrument	[0..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
MDStatisticRptGrp	[1..*]	Group	Specifies the resulting statistics information and corresponding statistical parameters.
TransactTime	[0..1]	UTCTimestamp	Time that the report was provided.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 63 MarketDataStatisticsRequest

Category: MarketData

### 63.1 Message Functionality

The MarketDataStatisticsRequest(35=DO) is used to request for statistical data. The simple form is to use an identifier (MDStatisticID(2475)) assigned by the market place which would denote a pre-defined statistical report. Alternatively, or also in addition, the request can define a number of parameters for the desired statistical information.

### 63.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DO
MDStatisticReqID	[1..1]	String	Unique message identifier for the request or the identifier of a previous request when unsubscribing.
SubscriptionRequestType	[1..1]	CodeSet	Used to subscribe / unsubscribe for market data statistics reports or to request a one-time snapshot of the current information.
Parties	[0..*]	Group	
TradeDate	[0..1]	LocalMktDate	Used to specify the business date.
MarketID	[0..1]	Exchange	Used to specify a single market.
MarketSegmentID	[0..1]	String	Used to specify a single market segment.
MarketSegmentDesc	[0..1]	String	
EncodedMktSegmDescLen	[0..1]	Length	Must be set if EncodedMktSegmDesc(1398) field is specified and must immediately precede it.
EncodedMktSegmDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the MarketSegmentDesc(1396) field in the encoded format specified via the MessageEncoding(347) field.
SecurityListID	[0..1]	String	Used to reference an entire group of instruments for which a single set of statistics is to be calculated.
Instrument	[0..1]	Component	Used to specify an individual instrument or instrument attributes for which a single set of statistics is to be calculated.

Name	Mult.	Type	Description
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
MDStatisticReqGrp	[1..*]	Group	Used to specify the parameters for the calculation of statistics.
TransactTime	[0..1]	UTCTimestamp	Time that the request was submitted.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[0..1]	Component	



## 64 MarketDefinition

Category: MarketStructureReferenceData

### 64.1 Message Functionality

The MarketDefinition(35=BU) message is used to respond to MarketDefinitionRequest(35=BT). In a subscription, it will be used to provide the initial snapshot of the information requested. Subsequent updates are provided by the MarketDefinitionUpdateReport(35=BV).

### 64.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BU
ApplicationSequenceControl	[0..1]	Component	
MarketReportID	[1..1]	String	Unique identifier for each market definition message.
MarketReqID	[0..1]	String	
MarketID	[1..1]	Exchange	
MarketSegmentID	[0..1]	String	
MarketSegmentDesc	[0..1]	String	
EncodedMktSegmDescLen	[0..1]	Length	Must be set if EncodedMktSegmDesc(1398) field is specified and must immediately precede it.
EncodedMktSegmDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the MarketSegmDesc(1396) field in the encoded format specified via the MessageEncoding(347) field.
ParentMktSegmID	[0..1]	String	Specifies that the market segment specified in this message is a sub-segment of the market segment defined in this field.
MarketSegmentStatus	[0..1]	CodeSet	
MarketSegmentType	[0..1]	CodeSet	Used to specify the purpose of a special market segment identified by MarketSegmentID(1300). Conditionally required if MarketSegmentSubType(2544) is specified.
MarketSegmentSubType	[0..1]	CodeSet	
InstrumentScopeGrp	[0..*]	Group	Used to specify the types of securities that belong to the market segment.

Name	Mult.	Type	Description
RelatedMarketSegmentGrp	[0..*]	Group	Used to specify market segments that have a relationship to the market segment defined in this message.
Currency	[0..1]	Currency	The default trading currency
CurrencyCodeSource	[0..1]	CodeSet	
BaseTradingRules	[0..1]	Component	Used to specify the base trading rules for the identified market or market segment.
OrdTypeRules	[0..*]	Group	Used to specify the order types that are valid for trading on the identified market or market segment.
TimeInForceRules	[0..*]	Group	Used to specify the time in force rules that are valid for trading on the identified market or market segment.
ExecInstRules	[0..*]	Group	Used to specify the execution instructions that are valid for trading on the identified market or market segment.
AuctionTypeRuleGrp	[0..*]	Group	Used to specify the auction order types that are valid for trading on the identified market or market segment.
MarketDataFeedTypes	[0..*]	Group	Used to specify the market data feed types that are valid for trading on the identified market or market segment.
MatchRules	[0..*]	Group	Used to specify the matching rules that are valid for trading on the identified market or market segment.
FlexProductEligibilityGrp	[0..*]	Group	Specifies the eligibility indicators for the creation of flexible securities.
Parties	[0..*]	Group	Specifies parties relevant for the market or market segment, e.g. market makers.
MiscFeesGrp	[0..*]	Group	
EffectiveBusinessDate	[0..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.

StandardTrailer

[1..1] Component

---

## 65 MarketDefinitionRequest

Category: MarketStructureReferenceData

### 65.1 Message Functionality

The Market Definition Request message is used to request for market structure information from the Respondent that receives this request.

### 65.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BT
MarketReqID	[1..1]	String	Must be unique, or the ID of previous Market Segment Request to disable if SubscriptionRequestType = Disable previous Snapshot + Updates Request(2).
SubscriptionRequestType	[1..1]	CodeSet	
MarketID	[0..1]	Exchange	Conditionally required if MarketSegmentID(1300) is specified on the request
MarketSegmentID	[0..1]	String	
ParentMktSegmID	[0..1]	String	Specifies that the Market Segment is a sub segment of the Market Segment defined in this field.
StandardTrailer	[1..1]	Component	

## 66 MarketDefinitionUpdateReport

Category: MarketStructureReferenceData

### 66.1 Message Functionality

In a subscription for market structure information, this message is used once the initial snapshot of the information has been sent using the MarketDefinition(35=BU) message.

### 66.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BV
ApplicationSequenceControl	[0..1]	Component	
MarketReportID	[1..1]	String	Unique identifier for each market definition message.
MarketReqID	[0..1]	String	
MarketUpdateAction	[0..1]	CodeSet	Specifies the action taken
MarketID	[1..1]	Exchange	
MarketSegmentID	[0..1]	String	
MarketSegmentDesc	[0..1]	String	
EncodedMktSegmDescLen	[0..1]	Length	Must be set if EncodedMktSegmDesc(1398) field is specified and must immediately precede it.
EncodedMktSegmDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the MarketSegmDesc(1396) field in the encoded format specified via the MessageEncoding(347) field.
ParentMktSegmID	[0..1]	String	Specifies that the market segment specified in this message is a sub-segment of the market segment defined in this field.
MarketSegmentStatus	[0..1]	CodeSet	
MarketSegmentType	[0..1]	CodeSet	Used to specify the purpose of a special market segment identified by MarketSegmentID(1300). Conditionally required if MarketSegmentSubType(2544) is specified.
MarketSegmentSubType	[0..1]	CodeSet	
InstrumentScopeGrp	[0..*]	Group	Used to specify the types of securities that belong to the market segment.

Name	Mult.	Type	Description
RelatedMarketSegmentGrp	[0..*]	Group	Used to specify market segments that have a relationship to the market segment defined in this message.
Currency	[0..1]	Currency	The default trading currency
CurrencyCodeSource	[0..1]	CodeSet	
BaseTradingRules	[0..1]	Component	Used to specify the valid base trading rules for the identified market or market segment.
OrdTypeRules	[0..*]	Group	Used to specify the order types that are valid for trading on the identified market or market segment.
TimeInForceRules	[0..*]	Group	Used to specify the time in force rules that are valid for trading on the identified market or market segment.
ExecInstRules	[0..*]	Group	Used to specify the execution instructions that are valid for trading on the identified market or market segment.
AuctionTypeRuleGrp	[0..*]	Group	Used to specify the auction order types that are valid for trading on the identified market or market segment.
MarketDataFeedTypes	[0..*]	Group	Used to specify the market data feed types that are valid for trading on the identified market or market segment.
MatchRules	[0..*]	Group	Used to specify the matching rules that are valid for trading on the identified market or market segment.
FlexProductEligibilityGrp	[0..*]	Group	Specifies the eligibility indicators for the creation of flexible securities.
Parties	[0..*]	Group	Specifies parties relevant for the market or market segment, e.g. market makers.
EffectiveBusinessDate	[0..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 67 MassOrder

Category: OrderMassHandling

### 67.1 Message Functionality

The MassOrder(35=DJ) message can be used to add, modify or delete multiple unrelated orders with a single message. Apart from clearing related attributes, only the key order attributes for high performance trading are available.

### 67.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DJ
MassOrderRequestID	[1..1]	String	
OrderResponseLevel	[0..1]	CodeSet	
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
Parties	[0..*]	Group	This is party information related to the submitter.
TradingCapacity	[0..1]	CodeSet	
ClearingAccountType	[0..1]	CodeSet	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
CustOrderCapacity	[0..1]	CodeSet	
ManualOrderIndicator	[0..1]	Boolean	
CustOrderHandlingInst	[0..1]	CodeSet	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
ThrottleInst	[0..1]	CodeSet	
TotNoOrderEntries	[0..1]	int	Used to support fragmentation. Sum of NoOrderEntries(2428) within the OrderEntryGrp across all messages with the same MassOrderRequestID(2423).
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
OrderEntryGrp	[1..*]	Group	
StandardTrailer	[1..1]	Component	



## 68 MassOrderAck

Category: OrderMassHandling

### 68.1 Message Functionality

The mass order acknowledgement message is used to acknowledge the receipt of and the status for a MassOrder(35=DJ) message.

### 68.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DK
ApplicationSequenceControl	[0..1]	Component	For use in drop copy applications. NOT FOR USE in transactional applications.
MassOrderRequestID	[0..1]	String	
MassOrderReportID	[0..1]	String	
MassOrderRequestStatus	[1..1]	CodeSet	Message level request status
MassOrderRequestResult	[0..1]	CodeSet	Message level request result
OrderResponseLevel	[0..1]	CodeSet	Level of response requested from receiver of MassOrder (35=DJ) message.
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
Parties	[0..*]	Group	
TradingCapacity	[1..1]	CodeSet	
ClearingAccountType	[0..1]	CodeSet	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
OrderCapacity	[0..1]	CodeSet	

Name	Mult.	Type	Description
OrderRestrictions	[0..1]	CodeSet	
CustOrderCapacity	[0..1]	CodeSet	
ManualOrderIndicator	[0..1]	Boolean	
CustOrderHandlingInst	[0..1]	CodeSet	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedRejectText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
CopyMsgIndicator	[0..1]	Boolean	
TotNoOrderEntries	[0..1]	int	Used to support fragmentation. Sum of NoOrderEntries(2428) within the OrderEntryAckGrp across all messages with the same MassOrderRequestID(2423).
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
ThrottleResponse	[0..1]	Component	
OrderEntryAckGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 69 MassQuote

Category: QuotationNegotiation

### 69.1 Message Functionality

The Mass Quote message can contain quotes for multiple securities to support applications that allow for the mass quoting of an option series. Two levels of repeating groups have been provided to minimize the amount of data required to submit a set of quotes for a class of options (e.g. all option series for IBM).

### 69.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = i (lowercase)
QuoteReqID	[0..1]	String	Required when quote is in response to a Quote Request message
QuoteID	[1..1]	String	
QuoteType	[0..1]	CodeSet	Type of Quote. Default is Indicative if not specified
QuoteModelType	[0..1]	CodeSet	
QuoteResponseLevel	[0..1]	CodeSet	Level of Response requested from receiver of quote messages.
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
DefBidSize	[0..1]	Qty	Default Bid Size for quote contained within this quote message - if not explicitly provided.
DefOfferSize	[0..1]	Qty	Default Offer Size for quotes contained within this quote message - if not explicitly provided.
QuotSetGrp	[1..*]	Group	The number of sets of quotes in the message
SelfMatchPreventionID	[0..1]	String	
SelfMatchPreventionInstruction	[0..1]	CodeSet	
ThrottleInst	[0..1]	CodeSet	

Name	Mult.	Type	Description
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 70 MassQuoteAck

Category: QuotationNegotiation

### 70.1 Message Functionality

Mass Quote Acknowledgement is used as the application level response to a Mass Quote message.

### 70.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = b (lowercase)
QuoteReqID	[0..1]	String	Required when acknowledgment is in response to a Quote Request message
QuoteID	[0..1]	String	Required when acknowledgment is in response to a Mass Quote, mass Quote Cancel or mass Quote Status Request message. Maps to: - QuoteID(117) of a Mass Quote. - QuoteMsgID(1166) of Quote Cancel. - QuoteStatusReqID(649) of Quote Status Request
QuoteStatus	[1..1]	CodeSet	Status of the mass quote acknowledgement.
QuoteRejectReason	[0..1]	CodeSet	Reason Quote was rejected.
QuoteResponseLevel	[0..1]	CodeSet	Level of Response requested from receiver of quote messages. Is echoed back to the counterparty.
QuoteType	[0..1]	CodeSet	Type of Quote
QuoteCancelType	[0..1]	CodeSet	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TargetParties	[0..*]	Group	Should be populated if the Mass Quote Acknowledgement is acknowledging a mass quote cancellation by party.
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	

Name	Mult.	Type	Description
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
QuotSetAckGrp	[0..*]	Group	The number of sets of quotes in the message
ThrottleResponse	[0..1]	Component	
StandardTrailer	[1..1]	Component	

## 71 MultilegOrderCancelReplace

Category: MultilegOrders

### 71.1 Message Functionality

Used to modify a multileg order previously submitted using the New Order - Multileg message. See Order Cancel Replace Request for details concerning message usage.

### 71.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AC
OrderID	[0..1]	String	Unique identifier of most recent order as assigned by sell-side (broker, exchange, ECN).
OrderRequestID	[0..1]	int	Required if provided on the order being replaced (or cancelled). Echo back the value provided by the requester.
OrigClOrdID	[0..1]	String	ClOrdID of the previous order (NOT the initial order of the day) when canceling or replacing an order. Required when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID.
ClOrdID	[0..1]	String	Unique identifier of replacement order as assigned by institution or by the intermediary with closest association with the investor. Note that this identifier will be used in ClOrdID field of the Cancel Reject message if the replacement request is rejected.
SecondaryClOrdID	[0..1]	String	
ClOrdLinkID	[0..1]	String	
OrigOrdModTime	[0..1]	UTCTimestamp	
Parties	[0..*]	Group	This is party information related to the submitter of the request.
TargetParties	[0..*]	Group	Identifies parties not directly associated with or owning the order, who are to be informed to effect processing of the order.
TradeOriginationDate	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
TradeDate	[0..1]	LocalMktDate	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
DayBookingInst	[0..1]	CodeSet	
BookingUnit	[0..1]	CodeSet	
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	Used to assign an identifier to the block of individual preallocations
PreAllocMlegGrp	[0..*]	Group	Number of repeating groups for pre-trade allocation
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values.
CashMargin	[0..1]	CodeSet	
ClearingFeeIndicator	[0..1]	CodeSet	
HandlInst	[0..1]	CodeSet	
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited. If OrdType=P, exactly one of the following values (ExecInst = L, R, M, P, O, T, or W) must be specified.
AuctionInstruction	[0..1]	CodeSet	
MinQty	[0..1]	Qty	
MinQtyMethod	[0..1]	CodeSet	
MatchIncrement	[0..1]	Qty	
MaxPriceLevels	[0..1]	int	
MaximumPriceDeviation	[0..1]	Percentage	
ValueChecksGrp	[0..*]	Group	
MatchingInstructions	[0..*]	Group	
SelfMatchPreventionID	[0..1]	String	May be used as an alternative to MatchingInstructions when the identifier does not appear in another field.
SelfMatchPreventionInstruction	[0..1]	CodeSet	
DisplayInstruction	[0..1]	Component	
DisclosureInstructionGrp	[0..*]	Group	Specifies instructions to disclose certain order level information in market data.



Name	Mult.	Type	Description
MaxFloor	[0..1]	Qty	
MarketSegmentID	[0..1]	String	
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	
ExDestinationType	[0..1]	CodeSet	
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
ProcessCode	[0..1]	CodeSet	Used to identify soft trades at order entry.
Side	[1..1]	CodeSet	Additional enumeration that indicates this is an order for a multileg order and that the sides are specified in the Instrument Leg component block.
ShortMarkingExemptIndicator	[0..1]	Boolean	
Instrument	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	Number of underlyings
PrevClosePx	[0..1]	Price	Useful for verifying security identification
SwapPoints	[0..1]	PriceOffset	
LegOrdGrp	[0..*]	Group	Number of legs
LocateReqd	[0..1]	CodeSet	Required for short sell orders
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary.
QtyType	[0..1]	CodeSet	
OrderQtyData	[0..1]	Component	Conditionally required when the OrderQtyData component is specified in the NewOrderMultileg(35=AB) message.
OrdType	[1..1]	CodeSet	
MultilegModel	[0..1]	CodeSet	
MultilegPriceMethod	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
Price	[0..1]	Price	Required for limit OrdTypes. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points). Can be used to specify a limit price for a pegged order, previously indicated, etc.
PriceProtectionScope	[0..1]	CodeSet	
StopPx	[0..1]	Price	Required for OrdType = "Stop" or OrdType = "Stop limit".

Name	Mult.	Type	Description
TriggeringInstruction	[0..1]	Component	Insert here the set of "TriggeringInstruction" fields defined in "common components of application messages"
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
IOIID	[0..1]	String	Required for Previously Indicated Orders (OrdType=E)
QuotelD	[0..1]	String	Required for Previously Quoted Orders (OrdType=D)
TimeInForce	[0..1]	CodeSet	Absence of this field indicates Day order
EffectiveTime	[0..1]	UTCTimestamp	Can specify the time at which the order should be considered valid
ExpireDate	[0..1]	LocalMktDate	Conditionally required if TimeInForce = GTD and ExpireTime is not specified.
ExpireTime	[0..1]	UTCTimestamp	Conditionally required if TimeInForce = GTD and ExpireDate is not specified.
GTBookingInst	[0..1]	CodeSet	States whether executions are booked out or accumulated on a partially filled GT order
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)=10 (Good for Time)
ExposureDurationUnit	[0..1]	CodeSet	
CommissionData	[0..1]	Component	
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData component if multiple commissions or enhanced attributes are needed.
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
TradingCapacity	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	

Name	Mult.	Type	Description
TradePublishIndicator	[0..1]	CodeSet	
CustOrderCapacity	[0..1]	CodeSet	
OrderOrigination	[0..1]	CodeSet	
OrderAttributeGrp	[0..*]	Group	
ForexReq	[0..1]	CodeSet	Indicates that broker is requested to execute a Forex accommodation trade in conjunction with the security trade.
SettlCurrency	[0..1]	Currency	Required if ForexReq = Y.
SettlCurrencyCodeSource	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	Method for booking out this order. Used when notifying a broker that an order to be settled by that broker is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
ClearingAccountType	[0..1]	CodeSet	
PositionEffect	[0..1]	CodeSet	For use in derivatives omnibus accounting
CoveredOrUncovered	[0..1]	CodeSet	For use with derivatives, such as options
MaxShow	[0..1]	Qty	
PegInstructions	[0..1]	Component	Insert here the set of "PegInstruction" fields defined in "Common Components of Application Messages"
DiscretionInstructions	[0..1]	Component	Insert here the set of "DiscretionInstruction" fields defined in "Common Components of Application Messages"
TargetStrategy	[0..1]	CodeSet	The target strategy of the order
StrategyParametersGrp	[0..*]	Group	Strategy parameter block
TargetStrategyParameters	[0..1]	String	For further specification of the TargetStrategy
RiskFreeRate	[0..1]	float	

Name	Mult.	Type	Description
ParticipationRate	[0..1]	Percentage	Mandatory for a TargetStrategy=Participate order and specifies the target participation rate. For other order types optionally specifies a volume limit (i.e. do not be more than this percent of the market volume)
CancellationRights	[0..1]	CodeSet	For CIV - Optional
MoneyLaunderingStatus	[0..1]	CodeSet	
RegistID	[0..1]	String	Reference to Registration Instructions message for this Order.
Designation	[0..1]	String	Supplementary registration information for this Order
OwnerType	[0..1]	CodeSet	
OrderOwnershipIndicator	[0..1]	CodeSet	Can be used to request change of order ownership.
MultiLegRptTypeReq	[0..1]	CodeSet	Indicates the method of execution reporting requested by issuer of the order.
ThrottleInst	[0..1]	CodeSet	
AuctionType	[0..1]	CodeSet	Conditionally required for auction orders.
AuctionAllocationPct	[0..1]	Percentage	
RelatedHighPrice	[0..1]	Price	
RelatedLowPrice	[0..1]	Price	
RelatedPriceSource	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 72 NetworkCounterpartySystemStatusRequest

Category: Network

### 72.1 Message Functionality

This message is send either immediately after logging on to inform a network (counterparty system) of the type of updates required or to at any other time in the FIX conversation to change the nature of the types of status updates required. It can also be used with a NetworkRequestType of Snapshot to request a one-off report of the status of a network (or counterparty) system. Finally this message can also be used to cancel a request to receive updates into the status of the counterparties on a network by sending a NetworkRequestStatusMessage with a NetworkRequestType of StopSubscribing.

### 72.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = "BC"
NetworkRequestType	[1..1]	CodeSet	
NetworkRequestID	[1..1]	String	
CompIDReqGrp	[0..*]	Group	Used to restrict updates/request to a list of specific CompID/SubID/LocationID/DeskID combinations. If not present request applies to all applicable available counterparties. EG Unless one sell side broker was a customer of another you would not expect to see information about other brokers, similarly one fund manager etc.
StandardTrailer	[1..1]	Component	

## 73 NetworkCounterpartySystemStatusResponse

Category: Network

### 73.1 Message Functionality

This message is sent in response to a Network (Counterparty System) Status Request Message.

### 73.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = "BD"
NetworkStatusResponseType	[1..1]	CodeSet	
NetworkRequestID	[0..1]	String	
NetworkResponseID	[1..1]	String	
LastNetworkResponseID	[0..1]	String	Required when NetworkStatusResponseType=2
ComplDStatGrp	[1..*]	Group	Specifies the number of repeating Compld's
StandardTrailer	[1..1]	Component	

## 74 NewOrderCross

Category: CrossOrders

### 74.1 Message Functionality

Used to submit a cross order into a market. The cross order contains two order sides (a buy and a sell). The cross order is identified by its CrossID.

### 74.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = s (lowercase S)
CrossID	[1..1]	String	
OrderRequestID	[0..1]	int	
CrossType	[1..1]	CodeSet	
CrossPrioritization	[1..1]	CodeSet	
RootParties	[0..*]	Group	Insert here the set of "Root Parties" fields defined in "common components of application messages" Used for acting parties that applies to the whole message, not individual sides.
SideCrossOrdModGrp	[1..*]	Group	Must be 1 or 2. 1 or 2 if CrossType=1. 2 otherwise
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	Number of underlyings
InstrmtLegGrp	[0..*]	Group	Number of Legs
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values.
HandlInst	[0..1]	CodeSet	
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited. If OrdType=P, exactly one of the following values (ExecInst = L, R, M, P, O, T, or W) must be specified.
MinQty	[0..1]	Qty	

Name	Mult.	Type	Description
MinQtyMethod	[0..1]	CodeSet	
MatchIncrement	[0..1]	Qty	
MaxPriceLevels	[0..1]	int	
DisplayInstruction	[0..1]	Component	Insert here the set of "DisplayInstruction" fields defined in "common components of application messages"
MaxFloor	[0..1]	Qty	
MarketSegmentID	[0..1]	String	
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
ProcessCode	[0..1]	CodeSet	Used to identify soft trades at order entry.
PrevClosePx	[0..1]	Price	Useful for verifying security identification
LocateReqd	[0..1]	CodeSet	Required for short sell orders
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary.
TransBkdTime	[0..1]	UTCTimestamp	A date and time stamp to indicate when this order was booked with the agent prior to submission to the VMU
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" (repeating group of Fixed Income stipulations) fields defined in "Common Components of Application Messages"
OrdType	[1..1]	CodeSet	
PriceType	[0..1]	CodeSet	
Price	[0..1]	Price	Required for limit OrdTypes. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points). Can be used to specify a limit price for a pegged order, previously indicated, etc.
PriceProtectionScope	[0..1]	CodeSet	
StopPx	[0..1]	Price	Required for OrdType = "Stop" or OrdType = "Stop limit".
TriggeringInstruction	[0..1]	Component	Insert here the set of "TriggeringInstruction" fields defined in "common components of application messages"



Name	Mult.	Type	Description
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" (Fixed Income spread or benchmark curve) fields defined in "Common Components of Application Messages"
YieldData	[0..1]	Component	Insert here the set of "YieldData" (yield-related) fields defined in "Common Components of Application Messages"
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
ComplianceID	[0..1]	String	
IOIID	[0..1]	String	Required for Previously Indicated Orders (OrdType=E)
QuotelD	[0..1]	String	Required for Previously Quoted Orders (OrdType=D)
TimeInForce	[0..1]	CodeSet	Absence of this field indicates Day order
EffectiveTime	[0..1]	UTCTimestamp	Can specify the time at which the order should be considered valid
ExpireDate	[0..1]	LocalMktDate	Conditionally required if TimeInForce = GTD and ExpireTime is not specified.
ExpireTime	[0..1]	UTCTimestamp	Conditionally required if TimeInForce = GTD and ExpireDate is not specified.
GTBookingInst	[0..1]	CodeSet	States whether executions are booked out or accumulated on a partially filled GT order
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)=10 (Good for Time)
ExposureDurationUnit	[0..1]	CodeSet	
TradingCapacity	[0..1]	CodeSet	
MaxShow	[0..1]	Qty	
PegInstructions	[0..1]	Component	Insert here the set of "PegInstruction" fields defined in "Common Components of Application Messages"
DiscretionInstructions	[0..1]	Component	Insert here the set of "DiscretionInstruction" fields defined in "Common Components of Application Messages"
TargetStrategy	[0..1]	CodeSet	The target strategy of the order
StrategyParametersGrp	[0..*]	Group	Strategy parameter block
TargetStrategyParameters	[0..1]	String	For further specification of the TargetStrategy

Name	Mult.	Type	Description
ParticipationRate	[0..1]	Percentage	Mandatory for a TargetStrategy=Participate order and specifies the target participation rate. For other order types optionally specifies a volume limit (i.e. do not be more than this percent of the market volume)
CancellationRights	[0..1]	CodeSet	For CIV - Optional
MoneyLaunderingStatus	[0..1]	CodeSet	
RegistID	[0..1]	String	Reference to Registration Instructions message for this Order.
Designation	[0..1]	String	Supplementary registration information for this Order
ThrottleInst	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 75 NewOrderList

Category: ProgramTrading

### 75.1 Message Functionality

The NewOrderList Message can be used in one of two ways depending on which market conventions are being followed.

### 75.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = E
ListID	[1..1]	String	Must be unique, by customer, for the day
BidID	[0..1]	String	Should refer to an earlier program if bidding took place.
ClientBidID	[0..1]	String	
ProgRptReqs	[0..1]	CodeSet	
BidType	[1..1]	CodeSet	e.g. Non Disclosed Model, Disclosed Model, No Bidding Process
ProgPeriodInterval	[0..1]	int	
CancellationRights	[0..1]	CodeSet	For CIV - Optional
MoneyLaunderingStatus	[0..1]	CodeSet	
RegistID	[0..1]	String	Reference to Registration Instructions message applicable to all Orders in this List.
ListExecInstType	[0..1]	CodeSet	Controls when execution should begin For CIV Orders indicates order of execution.
ListExecInst	[0..1]	String	Free-form text.
ContingencyType	[0..1]	CodeSet	Used for contingency orders.
EncodedListExecInstLen	[0..1]	Length	Must be set if EncodedListExecInst field is specified and must immediately precede it.
EncodedListExecInst	[0..1]	data	Encoded (non-ASCII characters) representation of the ListExecInst field in the encoded format specified via the MessageEncoding field.
AllowableOneSidednessPct	[0..1]	Percentage	The maximum percentage that execution of one side of a program trade can exceed execution of the other.

Name	Mult.	Type	Description
AllowableOneSidednessValue	[0..1]	Amt	The maximum amount that execution of one side of a program trade can exceed execution of the other.
AllowableOneSidednessCurr	[0..1]	Currency	The currency that AllowableOneSidedness is expressed in if AllowableOneSidednessValue is used.
ListManualOrderIndicator	[0..1]	Boolean	
TotNoOrders	[1..1]	int	Used to support fragmentation. Sum of NoOrders across all messages with the same ListID.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
RootParties	[0..*]	Group	Insert here the set of "Root Parties" fields defined in "common components of application messages" Used for acting parties that applies to the whole message, not individual orders.
ListOrdGrp	[1..*]	Group	Number of orders in this message (number of repeating groups to follow)
ThrottleInst	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 76 NewOrderMultileg

Category: MultilegOrders

### 76.1 Message Functionality

The New Order - Multileg is provided to submit orders for securities that are made up of multiple securities, known as legs.

### 76.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AB
ClOrdID	[1..1]	String	Unique identifier of the order as assigned by institution or by the intermediary with closest association with the investor.
OrderRequestID	[0..1]	int	
SecondaryClOrdID	[0..1]	String	
ClOrdLinkID	[0..1]	String	
Parties	[0..*]	Group	This is party information related to the submitter of the request.
TargetParties	[0..*]	Group	Identifies parties not directly associated with or owning the order, who are to be informed to effect processing of the order.
TradeOriginationDate	[0..1]	LocalMktDate	
TradeDate	[0..1]	LocalMktDate	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
DayBookingInst	[0..1]	CodeSet	
BookingUnit	[0..1]	CodeSet	
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	Used to assign an identifier to the block of individual preallocations
PreAllocMlegGrp	[0..*]	Group	Number of repeating groups for pre-trade allocation
SettlType	[0..1]	CodeSet	

Name	Mult.	Type	Description
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values.
CashMargin	[0..1]	CodeSet	
ClearingFeeIndicator	[0..1]	CodeSet	
HandlInst	[0..1]	CodeSet	
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited. If OrdType=P, exactly one of the following values (ExecInst = L, R, M, P, O, T, or W) must be specified.
AuctionInstruction	[0..1]	CodeSet	
MinQty	[0..1]	Qty	
MinQtyMethod	[0..1]	CodeSet	
MatchIncrement	[0..1]	Qty	
MaxPriceLevels	[0..1]	int	
MaximumPriceDeviation	[0..1]	Percentage	
ValueChecksGrp	[0..*]	Group	
MatchingInstructions	[0..*]	Group	
SelfMatchPreventionID	[0..1]	String	May be used as an alternative to MatchingInstructions when the identifier does not appear in another field.
SelfMatchPreventionInstruction	[0..1]	CodeSet	
DisplayInstruction	[0..1]	Component	
DisclosureInstructionGrp	[0..*]	Group	Specifies instructions to disclose certain order level information in market data.
MaxFloor	[0..1]	Qty	
MarketSegmentID	[0..1]	String	
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	
ExDestinationType	[0..1]	CodeSet	
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
ProcessCode	[0..1]	CodeSet	Used to identify soft trades at order entry.
Side	[1..1]	CodeSet	Additional enumeration that indicates this is an order for a multileg order and that the sides are specified in the Instrument Leg component block.
ShortMarkingExemptIndicator	[0..1]	Boolean	

Name	Mult.	Type	Description
Instrument	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	Number of underlyings
PrevClosePx	[0..1]	Price	Useful for verifying security identification
SwapPoints	[0..1]	PriceOffset	For FX Swaps. Used to express the differential between the far leg's bid/offer and the near leg's bid/offer.
LegOrdGrp	[0..*]	Group	Number of legs
LocateReqd	[0..1]	CodeSet	Required for short sell orders
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary.
QtyType	[0..1]	CodeSet	
OrderQtyData	[0..1]	Component	Conditionally required when the multileg order is not for a FX Swap, or any other swaps or multilegged transaction where having OrderQty(38) is irrelevant as the amounts are expressed in the LegOrderQty(685).
OrdType	[1..1]	CodeSet	
MultilegModel	[0..1]	CodeSet	
MultilegPriceMethod	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
Price	[0..1]	Price	Required for limit OrdTypes. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points). Can be used to specify a limit price for a pegged order, previously indicated, etc.
PriceProtectionScope	[0..1]	CodeSet	
StopPx	[0..1]	Price	Required for OrdType = "Stop" or OrdType = "Stop limit".
TriggeringInstruction	[0..1]	Component	Insert here the set of "TriggeringInstruction" fields defined in "common components of application messages"
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
TradePriceNegotiationMethod	[0..1]	CodeSet	
UpfrontPriceType	[0..1]	CodeSet	

Name	Mult.	Type	Description
UpfrontPrice	[0..1]	Price	Upfront Price for CDS transactions. Conditionally required if TradePriceNegotiationMethod(1740) = 4(Percent of par and upfront amount), 5(Deal spread and upfront amount) or 6(Upfront points and upfront amount).
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
IOIID	[0..1]	String	Required for Previously Indicated Orders (OrdType=E)
QuoteID	[0..1]	String	Required for Previously Quoted Orders (OrdType=D)
RefOrderID	[0..1]	String	Required for counter-order selection / Hit / Take Orders. (OrdType = Q)
RefOrderIDSource	[0..1]	CodeSet	Conditionally required if RefOrderID is specified.
RefClOrdID	[0..1]	String	
TimeInForce	[0..1]	CodeSet	Absence of this field indicates Day order
EffectiveTime	[0..1]	UTCTimestamp	Can specify the time at which the order should be considered valid
ExpireDate	[0..1]	LocalMktDate	Conditionally required if TimeInForce = GTD and ExpireTime is not specified.
ExpireTime	[0..1]	UTCTimestamp	Conditionally required if TimeInForce = GTD and ExpireDate is not specified.
GTBookingInst	[0..1]	CodeSet	States whether executions are booked out or accumulated on a partially filled GT order
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)=10 (Good for Time)
ExposureDurationUnit	[0..1]	CodeSet	
CommissionData	[0..1]	Component	
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData component if multiple commissions or enhanced attributes are needed.



Name	Mult.	Type	Description
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
TradingCapacity	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	
TradePublishIndicator	[0..1]	CodeSet	
CustOrderCapacity	[0..1]	CodeSet	
OrderOrigination	[0..1]	CodeSet	
OrderAttributeGrp	[0..*]	Group	
ForexReq	[0..1]	CodeSet	Indicates that broker is requested to execute a Forex accommodation trade in conjunction with the security trade.
SettlCurrency	[0..1]	Currency	Required if ForexReq = Y.
SettlCurrencyCodeSource	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	Method for booking out this order. Used when notifying a broker that an order to be settled by that broker is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
ClearingAccountType	[0..1]	CodeSet	
PositionEffect	[0..1]	CodeSet	For use in derivatives omnibus accounting
CoveredOrUncovered	[0..1]	CodeSet	For use with derivatives, such as options
MaxShow	[0..1]	Qty	
PegInstructions	[0..1]	Component	Insert here the set of "PegInstruction" fields defined in "Common Components of Application Messages"
DiscretionInstructions	[0..1]	Component	Insert here the set of "DiscretionInstruction" fields defined in "Common Components of Application Messages"
TargetStrategy	[0..1]	CodeSet	The target strategy of the order
StrategyParametersGrp	[0..*]	Group	Strategy parameter block
TargetStrategyParameters	[0..1]	String	For further specification of the TargetStrategy

Name	Mult.	Type	Description
RiskFreeRate	[0..1]	float	
ParticipationRate	[0..1]	Percentage	Mandatory for a TargetStrategy=Participate order and specifies the target participation rate. For other order types optionally specifies a volume limit (i.e. do not be more than this percent of the market volume)
CancellationRights	[0..1]	CodeSet	For CIV - Optional
MoneyLaunderingStatus	[0..1]	CodeSet	
RegistID	[0..1]	String	Reference to Registration Instructions message for this Order.
Designation	[0..1]	String	Supplementary registration information for this Order
MultiLegRptTypeReq	[0..1]	CodeSet	Indicates the method of execution reporting requested by issuer of the order.
ThrottleInst	[0..1]	CodeSet	
AuctionType	[0..1]	CodeSet	Conditionally required for auction orders.
AuctionAllocationPct	[0..1]	Percentage	
RelatedHighPrice	[0..1]	Price	
RelatedLowPrice	[0..1]	Price	
RelatedPriceSource	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 77 NewOrderSingle

Category: SingleGeneralOrderHandling

### 77.1 Message Functionality

The new order message type is used by institutions wishing to electronically submit securities and forex orders to a broker for execution.

The New Order message type may also be used by institutions or retail intermediaries wishing to electronically submit Collective Investment Vehicle (CIV) orders to a broker or fund manager for execution.

### 77.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = D
ClOrdID	[1..1]	String	Unique identifier of the order as assigned by institution or by the intermediary (CIV term, not a hub/service bureau) with closest association with the investor.
OrderRequestID	[0..1]	int	
SecondaryClOrdID	[0..1]	String	
ClOrdLinkID	[0..1]	String	
DuplicateClOrdIDIndicator	[0..1]	CodeSet	
Parties	[0..*]	Group	This is party information related to the submitter of the request.
TargetParties	[0..*]	Group	Identifies parties not directly associated with or owning the order, who are to be informed to effect processing of the order.
TradeOriginationDate	[0..1]	LocalMktDate	
TradeDate	[0..1]	LocalMktDate	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
DayBookingInst	[0..1]	CodeSet	
BookingUnit	[0..1]	CodeSet	

Name	Mult.	Type	Description
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	Used to assign an overall allocation id to the block of preallocations
PreAllocGrp	[0..*]	Group	Number of repeating groups for pre-trade allocation
SettlType	[0..1]	CodeSet	For NDFs either SettlType or SettlDate should be specified.
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values. For NDFs either SettlType or SettlDate should be specified.
CashMargin	[0..1]	CodeSet	
ClearingFeeIndicator	[0..1]	CodeSet	
HandlInst	[0..1]	CodeSet	
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited. If OrdType=P, exactly one of the following values (ExecInst = L, R, M, P, O, T, W, a, d) must be specified.
AuctionInstruction	[0..1]	CodeSet	
MinQty	[0..1]	Qty	
MinQtyMethod	[0..1]	CodeSet	
MatchIncrement	[0..1]	Qty	
MaxPriceLevels	[0..1]	int	
MaximumPriceDeviation	[0..1]	Percentage	
ValueChecksGrp	[0..*]	Group	
MatchingInstructions	[0..*]	Group	
SelfMatchPreventionID	[0..1]	String	May be used as an alternative to MatchingInstructions when the identifier does not appear in another field.
SelfMatchPreventionInstruction	[0..1]	CodeSet	
DisplayInstruction	[0..1]	Component	
DisclosureInstructionGrp	[0..*]	Group	Specifies instructions to disclose certain order level information in market data.
MaxFloor	[0..1]	Qty	
MarketSegmentID	[0..1]	String	
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	

Name	Mult.	Type	Description
ExDestinationType	[0..1]	CodeSet	
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
ProcessCode	[0..1]	CodeSet	Used to identify soft trades at order entry.
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	Number of underlyings
PrevClosePx	[0..1]	Price	Useful for verifying security identification
Side	[1..1]	CodeSet	
ShortMarkingExemptIndicator	[0..1]	Boolean	
ShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when Side(54) = 6(Sell short exempt).
LocateReqd	[0..1]	CodeSet	Required for short sell orders
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary.
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" (repeating group of Fixed Income stipulations) fields defined in "Common Components of Application Messages"
QtyType	[0..1]	CodeSet	
OrderQtyData	[1..1]	Component	
OrdType	[1..1]	CodeSet	
PriceType	[0..1]	CodeSet	
Price	[0..1]	Price	Required for limit OrdTypes. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points). Can be used to specify a limit price for a pegged order, previously indicated, etc.
CurrentWorkingPrice	[0..1]	Price	May be used for new (child) orders stemming from the split of a parent order. Refers to the working price of the parent order.
PriceProtectionScope	[0..1]	CodeSet	
StopPx	[0..1]	Price	Required for OrdType = "Stop" or OrdType = "Stop limit".

Name	Mult.	Type	Description
TriggeringInstruction	[0..1]	Component	Insert here the set of "TriggeringInstruction" fields defined in "common components of application messages"
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" (Fixed Income spread or benchmark curve) fields defined in "Common Components of Application Messages"
YieldData	[0..1]	Component	Insert here the set of "YieldData" (yield-related) fields defined in "Common Components of Application Messages"
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
TradePriceNegotiationMethod	[0..1]	CodeSet	
UpfrontPriceType	[0..1]	CodeSet	
UpfrontPrice	[0..1]	Price	Upfront Price for CDS transactions. Conditionally required if TradePriceNegotiationMethod(1740) = 4(Percent of par and upfront amount), 5(Deal spread and upfront amount) or 6(Upfront points and upfront amount).
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
CopyMsgIndicator	[0..1]	Boolean	May be used when intentionally sending an order more than once, e.g. an order being received manually as well as electronically in conjunction with a regulatory requirement to report both events.
IOIID	[0..1]	String	Required for Previously Indicated Orders (OrdType=E)
QuoteID	[0..1]	String	Required for Previously Quoted Orders (OrdType=D)
TimeInForce	[0..1]	CodeSet	Absence of this field indicates Day order

Name	Mult.	Type	Description
EffectiveTime	[0..1]	UTCTimestamp	Can specify the time at which the order should be considered valid
ExpireDate	[0..1]	LocalMktDate	Conditionally required if TimeInForce = GTD and ExpireTime is not specified.
ExpireTime	[0..1]	UTCTimestamp	Conditionally required if TimeInForce = GTD and ExpireDate is not specified.
GTBookingInst	[0..1]	CodeSet	States whether executions are booked out or accumulated on a partially filled GT order
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)=10 (Good for Time)
ExposureDurationUnit	[0..1]	CodeSet	
CommissionData	[0..1]	Component	
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData component if multiple commissions or enhanced attributes are needed.
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
TradingCapacity	[0..1]	CodeSet	
RegulatoryReportType	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	
TradePublishIndicator	[0..1]	CodeSet	Applies to trades resulting from the order.
CustOrderCapacity	[0..1]	CodeSet	
OrderAttributeGrp	[0..*]	Group	
ForexReq	[0..1]	CodeSet	Indicates that broker is requested to execute a Forex accommodation trade in conjunction with the security trade.
SettlCurrency	[0..1]	Currency	Required if ForexReq=Y. Required for NDFs.
SettlCurrencyCodeSource	[0..1]	CodeSet	
RateSource	[0..*]	Group	
OffshoreIndicator	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	Method for booking out this order. Used when notifying a broker that an order to be settled by that broker is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
Text	[0..1]	String	

Name	Mult.	Type	Description
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
Price2	[0..1]	Price	Can be used with OrdType = "Forex - Swap" to specify the price for the future portion of a F/X swap which is also a limit order. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points).
ClearingAccountType	[0..1]	CodeSet	
PositionEffect	[0..1]	CodeSet	For use in derivatives omnibus accounting
CoveredOrUncovered	[0..1]	CodeSet	For use with derivatives, such as options
MaxShow	[0..1]	Qty	
PegInstructions	[0..1]	Component	Insert here the set of "PegInstruction" fields defined in "Common Components of Application Messages"
DiscretionInstructions	[0..1]	Component	Insert here the set of "DiscretionInstruction" fields defined in "Common Components of Application Messages"
TargetStrategy	[0..1]	CodeSet	The target strategy of the order
StrategyParametersGrp	[0..*]	Group	Strategy parameter block
TargetStrategyParameters	[0..1]	String	For further specification of the TargetStrategy
ParticipationRate	[0..1]	Percentage	Mandatory for a TargetStrategy=Participate order and specifies the target participation rate. For other order types optionally specifies a volume limit (i.e. do not be more than this percent of the market volume)
CancellationRights	[0..1]	CodeSet	For CIV - Optional
MoneyLaunderingStatus	[0..1]	CodeSet	
RegistID	[0..1]	String	Reference to Registration Instructions message for this Order.



Name	Mult.	Type	Description
Designation	[0..1]	String	Supplementary registration information for this Order
ManualOrderIndicator	[0..1]	Boolean	
CustDirectedOrder	[0..1]	Boolean	
ReceivedDeptID	[0..1]	String	
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
OrderOrigination	[0..1]	CodeSet	
ContraOrderOrigination	[0..1]	CodeSet	May be used for cross orders submitted with single order messages.
OriginatingDeptID	[0..1]	String	
ReceivingDeptID	[0..1]	String	
RoutingArrangementIndicator	[0..1]	CodeSet	
ContraRoutingArrangementIndicator	[0..1]	CodeSet	May be used for cross orders submitted with single order messages.
AffiliatedFirmsTradeIndicator	[0..1]	Boolean	
OwnerType	[0..1]	CodeSet	
TrdRegTimestamps	[0..*]	Group	
TrdRegPublicationGrp	[0..*]	Group	
TradeReportingIndicator	[0..1]	CodeSet	
RefOrderID	[0..1]	String	Required for counter-order selection / Hit / Take Orders. (OrdType = Q)
RefOrderIDSource	[0..1]	CodeSet	Conditionally required if RefOrderID is specified.
ThrottleInst	[0..1]	CodeSet	
RefClOrdID	[0..1]	String	
AuctionType	[0..1]	CodeSet	Conditionally required for auction orders
AuctionAllocationPct	[0..1]	Percentage	
StandardTrailer	[1..1]	Component	

## 78 News

Category: EventCommunication

### 78.1 Message Functionality

The news message is a general free format message between the broker and institution. The message contains flags to identify the news item's urgency and to allow sorting by subject company (symbol). The News message can be originated at either the broker or institution side, or exchanges and other marketplace venues.

### 78.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = B
ApplicationSequenceControl	[0..1]	Component	
NewsID	[0..1]	String	Unique identifier for News message
NewsRefGrp	[0..*]	Group	News items referenced by this News message
NewsCategory	[0..1]	CodeSet	
LanguageCode	[0..1]	Language	Used to optionally specify the national language used for the News item.
OrigTime	[0..1]	UTCTimestamp	
Urgency	[0..1]	CodeSet	
Headline	[1..1]	String	Specifies the headline text
EncodedHeadlineLen	[0..1]	Length	Must be set if EncodedHeadline field is specified and must immediately precede it.
EncodedHeadline	[0..1]	data	Encoded (non-ASCII characters) representation of the Headline field in the encoded format specified via the MessageEncoding field.
RoutingGrp	[0..*]	Group	
MarketID	[0..1]	Exchange	Used to optionally specify the market to which this News applies.
MarketSegmentID	[0..1]	String	Used to optionally specify the market segment to which this News applies.
InstrmtGrp	[0..*]	Group	Specifies the number of repeating symbols (instruments) specified
InstrmtLegGrp	[0..*]	Group	

Name	Mult.	Type	Description
UndInstrmtGrp	[0..*]	Group	Number of underlyings
LinesOfTextGrp	[1..*]	Group	Specifies the number of repeating lines of text specified
URLLink	[0..1]	String	A URL (Uniform Resource Locator) link to additional information (i.e. <a href="http://www.XYZ.com/research.html">http://www.XYZ.com/research.html</a> )
RawDataLength	[0..1]	Length	
RawData	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 79 OrderCancelReject

Category: SingleGeneralOrderHandling

### 79.1 Message Functionality

The order cancel reject message is issued by the broker upon receipt of a cancel request or cancel/replace request message which cannot be honored.

### 79.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 9
OrderID	[1..1]	String	If CxlRejReason="Unknown order", specify "NONE".
OrderRequestID	[0..1]	int	Required if provided on the order cancel or cancel/replace request. Echo back the value provided by the requester.
SecondaryOrderID	[0..1]	String	Can be used to provide order id used by exchange or executing system.
SecondaryCLOrdID	[0..1]	String	
CLOrdID	[1..1]	String	Unique order id assigned by institution or by the intermediary with closest association with the investor. to the cancel request or to the replacement order.
CLOrdLinkID	[0..1]	String	
OrigCLOrdID	[0..1]	String	CLOrdID(11) which could not be canceled/replaced. CLOrdID of the previous accepted order (NOT the initial order of the day) when canceling or replacing an order. Required when referring to orders that were electronically submitted over FIX or otherwise assigned a CLOrdID.
OrdStatus	[1..1]	CodeSet	OrdStatus value after this cancel reject is applied. If CxlRejReason = "Unknown Order", specify Rejected.
WorkingIndicator	[0..1]	CodeSet	For optional use with OrdStatus = 0 (New)
OrigOrdModTime	[0..1]	UTCTimestamp	

Name	Mult.	Type	Description
ListID	[0..1]	String	Required for rejects against orders which were submitted as part of a list.
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
TradeOriginationDate	[0..1]	LocalMktDate	
TradeDate	[0..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	
CxlRejResponseTo	[1..1]	CodeSet	
CxlRejReason	[0..1]	CodeSet	
RejectText	[0..1]	String	Reason description for rejecting the transaction request.
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	
Parties	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 80 OrderCancelReplaceRequest

Category: SingleGeneralOrderHandling

### 80.1 Message Functionality

The order cancel/replace request is used to change the parameters of an existing order.

Do not use this message to cancel the remaining quantity of an outstanding order, use the Order Cancel Request message for this purpose.

### 80.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = G
OrderID	[0..1]	String	Unique identifier of most recent order as assigned by sell-side (broker, exchange, ECN).
OrderRequestID	[0..1]	int	Required if provided on the order being replaced (or cancelled). Echo back the value provided by the requester.
Parties	[0..*]	Group	This is party information related to the submitter of the request.
TargetParties	[0..*]	Group	Identifies parties not directly associated with or owning the order, who are to be informed to effect processing of the order.
TradeOriginationDate	[0..1]	LocalMktDate	
TradeDate	[0..1]	LocalMktDate	
OrigClOrdID	[0..1]	String	ClOrdID(11) of the previous non rejected order (NOT the initial order of the day) when canceling or replacing an order. Required when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID
ClOrdID	[1..1]	String	Unique identifier of replacement order as assigned by institution or by the intermediary with closest association with the investor. Note that this identifier will be used in ClOrdID field of the Cancel Reject message if the replacement request is rejected.
SecondaryClOrdID	[0..1]	String	

Name	Mult.	Type	Description
ClOrdLinkID	[0..1]	String	
DuplicateClOrdIDIndicator	[0..1]	CodeSet	
ListID	[0..1]	String	Required for List Orders
OrigOrdModTime	[0..1]	UTCTimestamp	TransactTime of the last state change that occurred to the original order
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
DayBookingInst	[0..1]	CodeSet	
BookingUnit	[0..1]	CodeSet	
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	Used to assign an overall allocation id to the block of preallocations
PreAllocGrp	[0..*]	Group	Number of repeating groups for pre-trade allocation
SettlType	[0..1]	CodeSet	For NDFs either SettlType or SettlDate should be specified.
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values. For NDFs either SettlType or SettlDate should be specified.
CashMargin	[0..1]	CodeSet	
ClearingFeeIndicator	[0..1]	CodeSet	
HandlInst	[0..1]	CodeSet	
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited. Replacement order must be created with new parameters (i.e. original order values will not be brought forward to replacement order unless redefined within this message).
AuctionInstruction	[0..1]	CodeSet	
MinQty	[0..1]	Qty	
MinQtyMethod	[0..1]	CodeSet	
MatchIncrement	[0..1]	Qty	
MaxPriceLevels	[0..1]	int	
MaximumPriceDeviation	[0..1]	Percentage	
ValueChecksGrp	[0..*]	Group	
MatchingInstructions	[0..*]	Group	

Name	Mult.	Type	Description
SelfMatchPreventionID	[0..1]	String	May be used as an alternative to MatchingInstructions when the identifier does not appear in another field.
SelfMatchPreventionInstruction	[0..1]	CodeSet	
DisplayInstruction	[0..1]	Component	
DisclosureInstructionGrp	[0..*]	Group	Specifies instructions to disclose certain order level information in market data.
MaxFloor	[0..1]	Qty	
MarketSegmentID	[0..1]	String	
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	
ExDestinationType	[0..1]	CodeSet	
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". Must match original order
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages". Must match original order
UndInstrmtGrp	[0..*]	Group	Number of underlyings
Side	[1..1]	CodeSet	Should match original order's side, however, if bilaterally agreed to the following groups could potentially be interchanged: Buy and Buy Minus, Sell, Sell Plus, Sell Short, and Sell Short Exempt, Cross, Cross Short, and Cross Short Exempt
ShortMarkingExemptIndicator	[0..1]	Boolean	
ShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when Side(54) = 6(Sell short exempt).
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader or trading system.
Stipulations	[0..*]	Group	
QtyType	[0..1]	CodeSet	
OrderQtyData	[1..1]	Component	Note: OrderQty(38) value should be the "Total Intended Order Quantity" (including the amount already executed for this chain of orders).
OrdType	[1..1]	CodeSet	



Name	Mult.	Type	Description
PriceType	[0..1]	CodeSet	
Price	[0..1]	Price	Required for limit OrdTypes. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points). Can be used to specify a limit price for a pegged order, previously indicated, etc.
CurrentWorkingPrice	[0..1]	Price	May be used to correct the initial working price of the parent order when this (child) order was entered.
PriceProtectionScope	[0..1]	CodeSet	
StopPx	[0..1]	Price	Required for OrdType = "Stop" or OrdType = "Stop limit".
TriggeringInstruction	[0..1]	Component	Insert here the set of "TriggeringInstruction" fields defined in "common components of application messages"
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" (Fixed Income spread or benchmark curve) fields defined in "Common Components of Application Messages"
YieldData	[0..1]	Component	Insert here the set of "YieldData" (yield-related) fields defined in "Common Components of Application Messages"
PegInstructions	[0..1]	Component	Insert here the set of "PegInstruction" fields defined in "Common Components of Application Messages"
DiscretionInstructions	[0..1]	Component	Insert here the set of "DiscretionInstruction" fields defined in "Common Components of Application Messages"
TargetStrategy	[0..1]	CodeSet	The target strategy of the order
StrategyParametersGrp	[0..*]	Group	Strategy parameter block
TargetStrategyParameters	[0..1]	String	For further specification of the TargetStrategy
ParticipationRate	[0..1]	Percentage	Mandatory for a TargetStrategy=Participate order and specifies the target participation rate. For other order types optionally specifies a volume limit (i.e. do not be more than this percent of the market volume)
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
Currency	[0..1]	Currency	Must match original order.
CurrencyCodeSource	[0..1]	CodeSet	
TimeInForce	[0..1]	CodeSet	Absence of this field indicates Day order
EffectiveTime	[0..1]	UTCTimestamp	Can specify the time at which the order should be considered valid
ExpireDate	[0..1]	LocalMktDate	Conditionally required if TimeInForce = GTD and ExpireTime is not specified.
ExpireTime	[0..1]	UTCTimestamp	Conditionally required if TimeInForce = GTD and ExpireDate is not specified.
GTBookingInst	[0..1]	CodeSet	States whether executions are booked out or accumulated on a partially filled GT order
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)=10 (Good for Time)
ExposureDurationUnit	[0..1]	CodeSet	
CommissionData	[0..1]	Component	
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData component if multiple commissions or enhanced attributes are needed.
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
TradingCapacity	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	
TradePublishIndicator	[0..1]	CodeSet	Applies to trades resulting from the order.
CustOrderCapacity	[0..1]	CodeSet	
OrderAttributeGrp	[0..*]	Group	
ForexReq	[0..1]	CodeSet	Indicates that broker is requested to execute a Forex accommodation trade in conjunction with the security trade.
SettlCurrency	[0..1]	Currency	Required if ForexReq=Y. Required for NDFs.
SettlCurrencyCodeSource	[0..1]	CodeSet	
RateSource	[0..*]	Group	
OffshoreIndicator	[0..1]	CodeSet	

Name	Mult.	Type	Description
BookingType	[0..1]	CodeSet	Method for booking out this order. Used when notifying a broker that an order to be settled by that broker is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
Price2	[0..1]	Price	Can be used with OrdType = "Forex - Swap" to specify the price for the future portion of a F/X swap.
ClearingAccountType	[0..1]	CodeSet	
PositionEffect	[0..1]	CodeSet	For use in derivatives omnibus accounting
CoveredOrUncovered	[0..1]	CodeSet	For use with derivatives, such as options
MaxShow	[0..1]	Qty	
LocateReqd	[0..1]	CodeSet	Required for short sell orders
CancellationRights	[0..1]	CodeSet	For CIV - Optional
MoneyLaunderingStatus	[0..1]	CodeSet	
RegistID	[0..1]	String	Reference to Registration Instructions message for this Order.
Designation	[0..1]	String	Supplementary registration information for this Order
ManualOrderIndicator	[0..1]	Boolean	
CustDirectedOrder	[0..1]	Boolean	
ReceivedDeptID	[0..1]	String	
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
OrderOrigination	[0..1]	CodeSet	

Name	Mult.	Type	Description
ContraOrderOrigination	[0..1]	CodeSet	May be used for cross orders submitted with single order messages.
OriginatingDeptID	[0..1]	String	
ReceivingDeptID	[0..1]	String	
RoutingArrangementIndicator	[0..1]	CodeSet	
ContraRoutingArrangementIndicator	[0..1]	CodeSet	May be used for cross orders submitted with single order messages.
OwnerType	[0..1]	CodeSet	
OrderOwnershipIndicator	[0..1]	CodeSet	Can be used to request change of order ownership.
TrdRegTimestamps	[0..*]	Group	
ThrottleInst	[0..1]	CodeSet	
AuctionType	[0..1]	CodeSet	Conditionally required for auction orders.
AuctionAllocationPct	[0..1]	Percentage	
ReleaseInstruction	[0..1]	CodeSet	
ReleaseQty	[0..1]	Qty	
StandardTrailer	[1..1]	Component	

## 81 OrderCancelRequest

Category: SingleGeneralOrderHandling

### 81.1 Message Functionality

The order cancel request message requests the cancellation of all of the remaining quantity of an existing order. Note that the Order Cancel/Replace Request should be used to partially cancel (reduce) an order).

### 81.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = F
OrderRequestID	[0..1]	int	Required if provided on the order being cancelled. Echo back the value provided by the requester.
OrigClOrdID	[0..1]	String	ClOrdID(11) of the previous non-rejected order (NOT the initial order of the day) when canceling or replacing an order. Required when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID
OrderID	[0..1]	String	Unique identifier of most recent order as assigned by sell-side (broker, exchange, ECN).
ClOrdID	[1..1]	String	Unique ID of cancel request as assigned by the institution.
SecondaryClOrdID	[0..1]	String	
ClOrdLinkID	[0..1]	String	
ListID	[0..1]	String	Required for List Orders
OrigOrdModTime	[0..1]	UTCTimestamp	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"

Name	Mult.	Type	Description
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages". Must match original order
UndInstrmtGrp	[0..*]	Group	Number of underlyings
MarketSegmentID	[0..1]	String	
ExDestination	[0..1]	Exchange	Execution destination when referring to orders that were not electronically submitted over FIX and ClOrdID has not been assigned or is not available to the recipient of the request.
ExDestinationIDSource	[0..1]	CodeSet	
Side	[1..1]	CodeSet	
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader or trading system.
OrderQtyData	[0..1]	Component	Conditionally required when the OrderQtyData component is required or specified in a prior, related message. For example, when used in a work flow including a NewOrderSingle(35=D) or NewOrderCross(35=s) message, the OrderQtyData component is a required component in these messages and thus the component is required here. When the OrderQtyData component is optional in a related message, such as the NewOrderMultileg(35=AB), the component is required here when specified in the prior, related NewOrderMultileg(35=AB) message.
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Name	Mult.	Type	Description
StandardTrailer	[1..1]	Component	

## 82 OrderMassActionReport

Category: OrderMassHandling

### 82.1 Message Functionality

The Order Mass Action Report is used to acknowledge an Order Mass Action Request. Note that each affected order that is suspended or released or canceled is acknowledged with a separate Execution Report for each order.

### 82.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BZ
ClOrdID	[0..1]	String	ClOrdID provided on the Order Mass Action Request.
SecondaryClOrdID	[0..1]	String	
MassActionReportID	[1..1]	String	Unique Identifier for the Order Mass Action Report
MassActionType	[1..1]	CodeSet	Order Mass Action Request Type accepted by the system
MassActionScope	[1..1]	CodeSet	Specifies the scope of the action
MassActionReason	[0..1]	CodeSet	Specifies the reason for the action taken.
MassActionResponse	[1..1]	CodeSet	Indicates the action taken by the counterparty order handling system as a result of the Action Request.
MassActionRejectReason	[0..1]	CodeSet	Indicates why Order Mass Action Request was rejected. Required if MassActionResponse(1375) = 0 (Rejected).
TotalAffectedOrders	[0..1]	int	Optional field used to indicate the total number of orders affected by the Order Mass Action Request
TotalNotAffectedOrders	[0..1]	int	Optional field used to indicate the total number of orders within the scope but not affected by the OrderMassActionRequest(35=CA).
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
AffectedOrdGrp	[0..*]	Group	List of orders affected by the Order Mass Action Request.



Name	Mult.	Type	Description
NotAffectedOrdGrp	[0..*]	Group	List of orders not affected by the Order Mass Action Request.
AffectedMarketSegmentGrp	[0..*]	Group	List of market segments affected by the Order Mass Action Request. Should only be used when request uses TargetMarketSegmentGrp component.
NotAffectedMarketSegmentGrp	[0..*]	Group	List of market segments not affected by the Order Mass Action Request. Should only be used when request uses TargetMarketSegmentGrp component.
MarketID	[0..1]	Exchange	MarketID for which orders are to be affected
MarketSegmentID	[0..1]	String	MarketSegmentID for which orders are to be affected. Mutually exclusive with TargetMarketSegmentGrp component.
TargetMarketSegmentGrp	[0..*]	Group	Mutually exclusive with MarketSegmentID(1300).
TradingSessionID	[0..1]	CodeSet	TradingSessionID for which orders are to be affected
TradingSessionSubID	[0..1]	CodeSet	TradingSessionSubID for which orders are to be affected
Parties	[0..*]	Group	
TargetParties	[0..*]	Group	Should be populated with the values provided on the associated OrderMassActionRequest(MsgType=CA).
Instrument	[0..1]	Component	
UnderlyingInstrument	[0..1]	Component	
Side	[0..1]	CodeSet	Side of the market specified on the Order Mass Action Request
Price	[0..1]	Price	
TransactTime	[0..1]	UTCTimestamp	Time this report was initiated/released by the sells-side (broker, exchange, ECN) or sell-side executing system.
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 83 OrderMassActionRequest

Category: OrderMassHandling

### 83.1 Message Functionality

The Order Mass Action Request message can be used to request the suspension or release of a group of orders that match the criteria specified within the request. This is equivalent to individual Order Cancel Replace Requests for each order with or without adding "S" to the ExecInst values. It can also be used for mass order cancellation.

### 83.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CA
ClOrdID	[1..1]	String	Unique ID of Order Mass Action Request as assigned by the institution.
SecondaryClOrdID	[0..1]	String	
MassActionType	[1..1]	CodeSet	Specifies the type of action requested
MassActionScope	[1..1]	CodeSet	Specifies the scope of the action
MassActionReason	[0..1]	CodeSet	Specifies the reason for the action requested.
MarketID	[0..1]	Exchange	MarketID for which orders are to be affected
MarketSegmentID	[0..1]	String	MarketSegmentID for which orders are to be affected. Mutually exclusive with TargetMarketSegmentGrp component.
TargetMarketSegmentGrp	[0..*]	Group	List of market segments for which orders are to be affected. Mutually exclusive with MarketSegmentID(1300).
TradingSessionID	[0..1]	CodeSet	Trading Session in which orders are to be affected
TradingSessionSubID	[0..1]	CodeSet	
Parties	[0..*]	Group	
TargetParties	[0..*]	Group	Can be used to specify the parties to whom the Order Mass Action should apply.
Instrument	[0..1]	Component	
UnderlyingInstrument	[0..1]	Component	
Side	[0..1]	CodeSet	Can be used to filter for orders of a single instrument.

Name	Mult.	Type	Description
Price	[0..1]	Price	Can be used to filter for orders of a single instrument.
TransactTime	[1..1]	UTCTimestamp	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 84 OrderMassCancelReport

Category: OrderMassHandling

### 84.1 Message Functionality

The Order Mass Cancel Report is used to acknowledge an Order Mass Cancel Request. Note that each affected order that is canceled is acknowledged with a separate Execution Report or Order Cancel Reject message.

### 84.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = r (lowercase R)
ClOrdID	[0..1]	String	ClOrdID provided on the Order Mass Cancel Request. Unavailable in case of an unsolicited report, such as after a trading halt or a corporate action requiring the deletion of outstanding orders.
SecondaryClOrdID	[0..1]	String	
OrderID	[1..1]	String	Unique Identifier for the Order Mass Cancel Request assigned by the recipient of the Order Mass Cancel Request.
MassActionReportID	[1..1]	String	Unique Identifier for the Order Mass Cancel Report assigned by the recipient of the Order Mass Cancel Request
SecondaryOrderID	[0..1]	String	Secondary Order ID assigned by the recipient of the Order Mass Cancel Request.
MassCancelRequestType	[1..1]	CodeSet	Order Mass Cancel Request Type accepted by the system
MassCancelResponse	[1..1]	CodeSet	Indicates the action taken by the counterparty order handling system as a result of the Cancel Request. 0 - Indicates Order Mass Cancel Request was rejected.
MassCancelRejectReason	[0..1]	CodeSet	Indicates why Order Mass Cancel Request was rejected. Required if MassCancelResponse = 0
TotalAffectedOrders	[0..1]	int	Optional field used to indicate the total number of orders affected by the Order Mass Cancel Request

Name	Mult.	Type	Description
AffectedOrdGrp	[0..*]	Group	List of orders affected by the Order Mass Cancel Request
NotAffectedOrdGrp	[0..*]	Group	List of orders not affected by Order Mass Cancel Request.
TradingSessionID	[0..1]	CodeSet	Trading Session in which orders are to be canceled
TradingSessionSubID	[0..1]	CodeSet	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "common components of application messages"
TargetParties	[0..*]	Group	Should be populated with the values provided on the associated OrderMassCancelRequest(MsgType=Q).
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
UnderlyingInstrument	[0..1]	Component	Insert here the set of "UnderlyingInstrument" (underlying symbology) fields defined in "Common Components of Application Messages"
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
Side	[0..1]	CodeSet	Side of the market specified on the Order Mass Cancel Request
TransactTime	[0..1]	UTCTimestamp	Time this report was initiated/released by the sells-side (broker, exchange, ECN) or sell-side executing system.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 85 OrderMassCancelRequest

Category: OrderMassHandling

### 85.1 Message Functionality

The order mass cancel request message requests the cancellation of all of the remaining quantity of a group of orders matching criteria specified within the request. NOTE: This message can only be used to cancel order messages (reduce the full quantity).

### 85.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = q (lowercase Q)
ClOrdID	[1..1]	String	Unique ID of Order Mass Cancel Request as assigned by the institution.
SecondaryClOrdID	[0..1]	String	
MassCancelRequestType	[1..1]	CodeSet	Specifies the type of cancellation requested
TradingSessionID	[0..1]	CodeSet	Trading Session in which orders are to be canceled
TradingSessionSubID	[0..1]	CodeSet	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "common components of application messages"
TargetParties	[0..*]	Group	Can be used to specify the parties to whom the Order Mass Cancel should apply.
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
UnderlyingInstrument	[0..1]	Component	Insert here the set of "UnderlyingInstrument" (underlying symbology) fields defined in "Common Components of Application Messages"
MarketID	[0..1]	Exchange	Required for MassCancelRequestType = 8 (Cancel orders for a market)
MarketSegmentID	[0..1]	String	Required for MassCancelRequestType = 9 (Cancel orders for a market segment)

Name	Mult.	Type	Description
Side	[0..1]	CodeSet	Optional qualifier used to indicate the side of the market for which orders are to be canceled. Absence of this field indicates that orders are to be canceled regardless of side.
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader or trading system.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	



## 86 OrderMassStatusRequest

Category: OrderMassHandling

### 86.1 Message Functionality

The order mass status request message requests the status for orders matching criteria specified within the request.

### 86.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AF
MassStatusReqID	[1..1]	String	Unique ID of mass status request as assigned by the institution.
MassStatusReqType	[1..1]	CodeSet	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TargetParties	[0..*]	Group	Can be used to specify the parties to whom the Order Mass Status Request should apply.
Account	[0..1]	String	Account
AcctIDSource	[0..1]	CodeSet	
TradingSessionID	[0..1]	CodeSet	Trading Session
TradingSessionSubID	[0..1]	CodeSet	
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
UnderlyingInstrument	[0..1]	Component	Insert here the set of "UnderlyingInstrument" (underlying symbology) fields defined in "Common Components of Application Messages"
Side	[0..1]	CodeSet	Optional qualifier used to indicate the side of the market for which orders will be returned.
StandardTrailer	[1..1]	Component	

## 87 OrderStatusRequest

Category: SingleGeneralOrderHandling

### 87.1 Message Functionality

The order status request message is used by the institution to generate an order status message back from the broker.

### 87.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = H
OrderID	[0..1]	String	Conditionally required if CIOrdID(11) is not provided. Either OrderID or CIOrdID must be provided.
CIOrdID	[0..1]	String	The CIOrdID of the order whose status is being requested. Conditionally required if the OrderID(37) is not provided. Either OrderID or CIOrdID must be provided.
SecondaryCIOrdID	[0..1]	String	
CIOrdLinkID	[0..1]	String	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
OrdStatusReqID	[0..1]	String	Optional, can be used to uniquely identify a specific Order Status Request message. Echoed back on Execution Report if provided.
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages". Must match original order
UndInstrmtGrp	[0..*]	Group	Number of underlyings

Name	Mult.	Type	Description
MarketSegmentID	[0..1]	String	
Side	[1..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 88 PartyActionReport

Category: PartiesAction

### 88.1 Message Functionality

Used to respond to the PartyActionRequest(35=DH) message, indicating whether the request has been received, accepted or rejected. Can also be used in an unsolicited manner to report party actions, e.g. reinstatements after a manual intervention out of band.

### 88.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DI
EffectiveBusinessDate	[0..1]	LocalMktDate	
PartyActionRequestID	[0..1]	String	Conditionally required when responding to a PartyActionRequest(35=DH) message.
PartyActionReportID	[1..1]	String	
PartyActionType	[1..1]	CodeSet	
PartyActionResponse	[1..1]	CodeSet	
PartyActionRejectReason	[0..1]	CodeSet	Conditionally required when PartyActionResponse(2332) = 2 (Rejected).
ApplTestMessageIndicator	[0..1]	Boolean	Conditionally required if present in the PartyActionRequest(35=DH) message.
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
InstrumentScope	[0..1]	Component	
RequestingPartyGrp	[0..*]	Group	May be used to identify the party making the request and their role.

Name	Mult.	Type	Description
Parties	[1..*]	Group	Used to specify the trading party on which the action is applied to. If in response to PartyActionRequest(35=DH) message, this should echo back the values from the request.
RelatedPartyDetailGrp	[0..*]	Group	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
CopyMsgIndicator	[0..1]	Boolean	
StandardTrailer	[1..1]	Component	

## 89 PartyActionRequest

Category: PartiesAction

### 89.1 Message Functionality

The PartyActionRequest message is used suspend or halt the specified party from further trading activities at the Respondent. The Respondent must respond with a PartyActionReport(35=DI) message.

### 89.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DH
PartyActionRequestID	[1..1]	String	
PartyActionType	[1..1]	CodeSet	
ApplTestMessageIndicator	[0..1]	Boolean	
MarketID	[0..1]	Exchange	Use to reduce the scope to a market
MarketSegmentID	[0..1]	String	Use to reduce the scope to a market segment
InstrumentScope	[0..1]	Component	Use to reduce the scope of instruments
RequestingPartyGrp	[0..*]	Group	May be used to identify the party making the request and their role.
Parties	[1..*]	Group	Used to specify the trading party on which the action is applied to.
RelatedPartyDetailGrp	[0..*]	Group	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 90 PartyDetailsDefinitionRequest

Category: PartiesReferenceData

### 90.1 Message Functionality

The PartyDetailsDefinitionRequest(35=CX) is used for defining new parties and modifying or deleting existing parties information, including the relationships between parties.

The recipient of the message responds with a PartyDetailsDefinitionRequestAck(35=CY) to indicate whether the request was accepted or rejected.

### 90.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=CX
PartyDetailsListRequestID	[1..1]	String	
RequestingPartyGrp	[0..*]	Group	Can be used to identify the party making the request and their role.
PartyDetailsUpdateGrp	[1..*]	Group	Specifies the parties and relationships between parties to be defined, modified, or deleted.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 91 PartyDetailsDefinitionRequestAck

Category: PartiesReferenceData

### 91.1 Message Functionality

The PartyDetailsDefinitionRequestAck(35=CY) is used as a response to the PartyDetailsDefinitionRequest(35=CX) message. The request can be accepted (with or without changes) or rejected.

### 91.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=CY
PartyDetailsListRequestID	[1..1]	String	
PartyDetailRequestStatus	[1..1]	CodeSet	
PartyDetailRequestResult	[0..1]	CodeSet	
RequestingPartyGrp	[0..*]	Group	
PartyDetailAckGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	



## 92 PartyDetailsListReport

Category: PartiesReferenceData

### 92.1 Message Functionality

The PartyDetailsListReport message is used to disseminate party details between counterparties. PartyDetailsListReport messages may be sent in response to a PartyDetailsListRequest message or sent unsolicited.

### 92.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CG
ApplicationSequenceControl	[0..1]	Component	
PartyDetailsListReportID	[1..1]	String	
PartyDetailsListRequestID	[0..1]	String	Conditionally required when responding to the PartyDetailsListRequest message.
RequestResult	[0..1]	CodeSet	Conditionally required when responding to the PartyDetailsListRequest message.
TotNoParties	[0..1]	int	
LastFragment	[0..1]	CodeSet	
PartyDetailGrp	[0..*]	Group	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 93 PartyDetailsListRequest

Category: PartiesReferenceData

### 93.1 Message Functionality

The PartyDetailsListRequest is used to request party detail information.

### 93.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CF
PartyDetailsListRequestID	[1..1]	String	
RequestingPartyGrp	[0..*]	Group	May be used to identify the party making the request and their role.
Parties	[0..*]	Group	Scope of the query/request for specific party(-ies).
RequestedPartyRoleGrp	[0..*]	Group	Scope of the query/request for specific party role(s)
PartyRelationshipGrp	[0..*]	Group	Scope of the query/request for specific party relationship(s)
SubscriptionRequestType	[0..1]	CodeSet	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 94 PartyDetailsListUpdateReport

Category: PartiesReferenceData

### 94.1 Message Functionality

The PartyDetailsListUpdateReport(35=CK) is used to disseminate updates to party detail information.

### 94.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CK
ApplicationSequenceControl	[0..1]	Component	
PartyDetailsListReportID	[1..1]	String	
PartyDetailsListRequestID	[0..1]	String	Conditionally required when responding to the PartyDetailsListRequest(35=CF) message.
TotNoParties	[0..1]	int	
LastFragment	[0..1]	CodeSet	
RequestingPartyGrp	[0..*]	Group	May be used to specify the requesting party in the event the request was made verbally or via other means.
PartyDetailsUpdateGrp	[0..*]	Group	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 95 PartyEntitlementsDefinitionRequest

Category: PartiesReferenceData

### 95.1 Message Functionality

The PartyEntitlementsDefinitionRequest(35=DA) is used for defining new entitlements, and modifying or deleting existing entitlements for the specified party(-ies).

### 95.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DA
EntitlementRequestID	[1..1]	String	
RequestingPartyGrp	[0..*]	Group	Can be used to identify the party making the request and their role.
PartyEntitlementUpdateGrp	[1..*]	Group	Specifies the entitlements to be defined, modified or deleted for the given party(-ies) and related party(-ies).
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 96 PartyEntitlementsDefinitionRequestAck

Category: PartiesReferenceData

### 96.1 Message Functionality

The PartyEntitlementsDefinitionRequestAck(35=DB) is used as a response to the PartyEntitlementsDefinitionRequest(35=DA) to accept (with or without changes) or reject the definition of party entitlements.

### 96.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DB
EntitlementRequestID	[1..1]	String	
EntitlementRequestStatus	[1..1]	CodeSet	
EntitlementRequestResult	[0..1]	CodeSet	
RequestingPartyGrp	[0..*]	Group	
PartyEntitlementAckGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 97 PartyEntitlementsReport

Category: PartiesReferenceData

### 97.1 Message Functionality

The PartyEntitlementsReport is used to report entitlements for one or more parties, party role(s), or specific instrument(s).

### 97.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=CV
ApplicationSequenceControl	[0..1]	Component	
EntitlementReportID	[1..1]	String	
EntitlementRequestID	[0..1]	String	Conditionally required when responding to PartyEntitlementsRequest(35=CU).
RequestResult	[0..1]	CodeSet	Conditionally required when responding to Party Entitlements Request.
TotNoParties	[0..1]	int	
LastFragment	[0..1]	CodeSet	
PartyEntitlementGrp	[0..*]	Group	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 98 PartyEntitlementsRequest

Category: PartiesReferenceData

### 98.1 Message Functionality

The PartyEntitlementsRequest message is used to request for entitlement information for one or more party(-ies), specific party role(s), or specific instruments(s).

### 98.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=CU
EntitlementRequestID	[0..1]	String	
SubscriptionRequestType	[0..1]	CodeSet	
RequestingPartyGrp	[0..*]	Group	May be used to identify the party making the request and their role.
Parties	[0..*]	Group	Scope of the query/request for specific party(-ies).
RequestedPartyRoleGrp	[0..*]	Group	Scope of the query/request for specific party roles. For example, "all information for PartyRole=24".
EntitlementStatus	[0..1]	CodeSet	
EntitlementTypeGrp	[0..*]	Group	
EntitlementPlatform	[0..1]	String	
InstrumentScopeGrp	[0..*]	Group	Scope of the query/request for specific securities.
MarketSegmentScopeGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 99 PartyEntitlementsUpdateReport

Category: PartiesReferenceData

### 99.1 Message Functionality

The PartyEntitlementsUpdateReport(35=CZ) is used to convey incremental changes to party entitlements. It is similar to the PartyEntitlementsReport(35=CV). This message uses the PartyEntitlementsUpdateGrp component which includes the ability to specify an update action using ListUpdateAction(1324).

### 99.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=CZ
ApplicationSequenceControl	[0..1]	Component	
EntitlementReportID	[1..1]	String	
EntitlementRequestID	[0..1]	String	Conditionally required when responding to a PartyEntitlementsRequest(35=CU) message.
TotNoParties	[0..1]	int	
LastFragment	[0..1]	CodeSet	
RequestingPartyGrp	[0..*]	Group	May be used to specify the requesting party in the event the request was made verbally or via other means.
PartyEntitlementUpdateGrp	[1..*]	Group	Specifies the updated entitlements to be enforced for the given party(-ies) and related party(-ies).
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	



## 100 PartyRiskLimitCheckRequest

Category: PartiesAction

### 100.1 Message Functionality

PartyRiskLimitCheckRequest is used to request for approval of credit or risk limit amount intended to be used by a party in a transaction from another party that holds the information.

### 100.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DE
RiskLimitCheckRequestID	[0..1]	String	Either RiskLimitCheckRequestID(2318) or RiskLimitCheckID(2319) must be specified. RiskLimitCheckRequestID(2318) is conditionally required in a message-chaining model in which a subsequent message may refer to a prior message via RiskLimitCheckRequestRefID(2322). The alternative is an entity-based model in which RiskLimitCheckID(2319) is used to statically identify a given request. In this case RiskLimitCheckID(2319) is required and RiskLimitRequestID(1666) can be optionally specified.
RiskLimitCheckID	[0..1]	String	Either RiskLimitCheckRequestID(2318) or RiskLimitCheckID(2319) must be specified.
RiskLimitCheckTransType	[1..1]	CodeSet	
RiskLimitCheckType	[1..1]	CodeSet	
RiskLimitCheckRequestRefID	[0..1]	int	Conditionally required when RiskLimitCheckTransType(2320) = 1 (Cancel) or 2 (Replace), and message-chaining model is used.
RefOrderID	[0..1]	String	Used to specify the transaction reference for this limit check request.
RefOrderIDSource	[0..1]	CodeSet	Identifies the type of reference specified in RefOrderID(1080) for this limit check request.
RiskLimitCheckRequestType	[0..1]	CodeSet	

Name	Mult.	Type	Description
RiskLimitCheckAmount	[0..1]	Amt	Specifies the amount being requested or consumed, as indicated by RiskLimitCheckType(2321).
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
RiskLimitID	[0..1]	String	
RequestingPartyGrp	[0..*]	Group	May be used to identify the party making the limit check request and their role.
Parties	[0..*]	Group	May be used to specify the trading party on which the limit check request is for. Each request is for a single trading party and the specified transaction reference.
RelatedPartyDetailGrp	[0..*]	Group	
Instrument	[0..1]	Component	
LegOrdGrp	[0..*]	Group	
UndInstrmtGrp	[0..*]	Group	
Side	[0..1]	CodeSet	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 101 PartyRiskLimitCheckRequestAck

Category: PartiesAction

### 101.1 Message Functionality

PartyRiskLimitCheckRequestAck is used to acknowledge a PartyRiskLimitCheckRequest(35=DF) message and to respond whether the limit check request was approved or not. When used to accept the PartyRiskLimitCheckRequest(35=DF) message the Respondent may also include the limit amount that was approved.

### 101.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DG
RiskLimitCheckRequestID	[0..1]	String	Either RiskLimitCheckRequestID(2318) or RiskLimitCheckID(2319) must be provided from the request message
RiskLimitCheckID	[0..1]	String	Either RiskLimitCheckRequestID(2318) or RiskLimitCheckID(2319) must be provided from the request message.
RiskLimitCheckRequestStatus	[1..1]	CodeSet	
RiskLimitCheckRequestResult	[0..1]	CodeSet	
RiskLimitCheckTransType	[1..1]	CodeSet	Identifies the RiskLimitCheckTransType(2320) this message is responding to as specified in the request message.
RiskLimitCheckType	[1..1]	CodeSet	Identifies the RiskLimitCheckType(2321) this message is responding to as specified in the request message.
RiskLimitCheckRequestRefID	[0..1]	int	Conditionally required when RiskLimitCheckTransType(2320) = 1 (Cancel) or 2 (Replace)
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
RefOrderID	[0..1]	String	
RefOrderIDSource	[0..1]	CodeSet	
Side	[0..1]	CodeSet	
RiskLimitApprovedAmount	[0..1]	Amt	Conditionally required when RiskLimitCheckRequestStatus(2325)=1 (Partially approved)
RiskLimitCheckAmount	[0..1]	Amt	
RiskLimitID	[0..1]	String	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
ExpireTime	[0..1]	UTCTimestamp	Optionally used to specify when the approved credit limit being reserved will expire.
RequestingPartyGrp	[0..*]	Group	
Parties	[0..*]	Group	The trading party identified in the limit check request.
RelatedPartyDetailGrp	[0..*]	Group	
Instrument	[0..1]	Component	
LegOrdGrp	[0..*]	Group	
UndInstrmtGrp	[0..*]	Group	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 102 PartyRiskLimitsDefinitionRequest

Category: PartiesReferenceData

### 102.1 Message Functionality

PartyRiskLimitDefinitionRequest is used for defining new risk limits.

### 102.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=CS
RiskLimitRequestID	[1..1]	String	
RequestingPartyGrp	[0..*]	Group	May be used to identify the party making the request and their role.
PartyRiskLimitsUpdateGrp	[0..*]	Group	Risk limits to be enforced for given party(-ies) and related party(-ies).
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 103 PartyRiskLimitsDefinitionRequestAck

Category: PartiesReferenceData

### 103.1 Message Functionality

PartyRiskLimitDefinitionRequestAck is used for accepting (with or without changes) or rejecting the definition of risk limits.

### 103.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=CT
RiskLimitRequestID	[1..1]	String	
RiskLimitRequestResult	[0..1]	CodeSet	
RiskLimitRequestStatus	[1..1]	CodeSet	
RequestingPartyGrp	[0..*]	Group	
PartyRiskLimitsAckGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 104 PartyRiskLimitsReport

Category: PartiesReferenceData

### 104.1 Message Functionality

The PartyRiskLimitsReport message is used to communicate party risk limits. The message can either be sent as a response to the PartyRiskLimitsRequest message or can be published unsolicited.

### 104.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CM
ApplicationSequenceControl	[0..1]	Component	
RiskLimitReportID	[1..1]	String	
RiskLimitRequestID	[0..1]	String	Conditionally required when responding to PartyRiskLimitsRequest(35=CL).
RiskLimitRequestType	[0..1]	CodeSet	Can be used when responding to a PartyRiskLimitsRequest(35=CL).
RequestResult	[0..1]	CodeSet	Conditionally required when responding to a PartyRiskLimitsRequest(35=CL).
UnsolicitedIndicator	[0..1]	CodeSet	
TotNoParties	[0..1]	int	
LastFragment	[0..1]	CodeSet	
PartyRiskLimitsGrp	[0..*]	Group	Optionally includes utilization (consumption) information.
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 105 PartyRiskLimitsReportAck

Category: PartiesReferenceData

### 105.1 Message Functionality

PartyRiskLimitsReportAck is an optional message used as a response to the PartyRiskLimitReport(35=CM) or PartyRiskLimitUpdateReport(35=CR) messages to acknowledge or reject those messages.

### 105.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DE
RiskLimitReportID	[1..1]	String	The identifier of the PartyRiskLimitReport(35=CM) or PartyRiskLimitUpdateReport(35=CR) message.
RiskLimitRequestID	[0..1]	String	
RiskLimitReportStatus	[1..1]	CodeSet	
RiskLimitReportRejectReason	[0..1]	CodeSet	Conditionally required when RiskLimitReportStatus(2316)=1 (Rejected).
PartyRiskLimitsUpdateGrp	[0..*]	Group	
TransactTime	[0..1]	UTCTimestamp	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	



## 106 PartyRiskLimitsRequest

Category: PartiesReferenceData

### 106.1 Message Functionality

The PartyRiskLimitsRequest message is used to request for risk information for specific parties, specific party roles or specific instruments.

### 106.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CL
RiskLimitRequestID	[1..1]	String	
RiskLimitRequestType	[0..1]	CodeSet	Scope of risk limit information.
SubscriptionRequestType	[0..1]	CodeSet	
RequestingPartyGrp	[0..*]	Group	May be used to identify the party making the request and their role.
Parties	[0..*]	Group	Scope of the query/request for specific party(-ies)
RequestedPartyRoleGrp	[0..*]	Group	Scope of the query/request for specific party role(s). For example, "all information for PartyRole=24."
RequestedRiskLimitTypesGrp	[0..*]	Group	
RiskLimitPlatform	[0..1]	String	
RiskInstrumentScopeGrp	[0..*]	Group	Scope of the query/request for specific securities. Absence means all instruments for a given party or party role.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 107 PartyRiskLimitsUpdateReport

Category: PartiesReferenceData

### 107.1 Message Functionality

The PartyRiskLimitsUpdateReport(35=CR) is used to convey incremental changes to risk limits. It is similar to the regular report but uses the PartyRiskLimitsUpdateGrp component instead of the PartyRiskLimitsGrp component to include an update action.

### 107.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=CR
ApplicationSequenceControl	[0..1]	Component	
RiskLimitReportID	[1..1]	String	
RiskLimitRequestID	[0..1]	String	Conditionally required when sent as part of a subscription requested by a PartyRiskLimitsRequest(35=CL).
RiskLimitRequestType	[0..1]	CodeSet	Can be used if sent as part of a subscription started by a PartyRiskLimitsRequest(35=CL).
TotNoParties	[0..1]	int	
LastFragment	[0..1]	CodeSet	
RequestingPartyGrp	[0..*]	Group	May be used to specify the requesting party in the event the request was made verbally or via other means.
PartyRiskLimitsUpdateGrp	[0..*]	Group	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 108 PayManagementReport

Category: PayManagement

### 108.1 Message Functionality

PayManagementReport(35=EA) may be used to respond to the PayManagementRequest(35=DY) message. It provides the status of the request (e.g. accepted, disputed) and may provide additional information related to the request.

PayManagementReport(35=EA) may also be sent unsolicited by the broker to a client. In which case the client may acknowledge and resolve disputes out-of-band or with a simple PayManagementReportAck(35=EB).

PayManagementReport(35=EA) may also be sent unsolicited to report the progress status of the payment itself with PayReportTransType(2804)=2 (Status).

### 108.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EA
PayReportID	[1..1]	String	
PayRequestID	[0..1]	String	Conditionally required when responding to PayManagementRequest(35=DY).
PayReportTransType	[1..1]	CodeSet	
PayReportRefID	[0..1]	String	Required for PayReportTransType(2804)=1 (Replace).
ReplaceText	[0..1]	String	May be used to provide reason for PayReportTransType(2804)=1 (Replace).
EncodedReplaceTextLen	[0..1]	Length	Must be set if EncodedReplaceText(2801) field is specified and must immediately precede it.
EncodedReplaceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ReplaceText(2805) field in the encoded format specified via the MessageEncoding(347) field.
PayRequestStatus	[0..1]	CodeSet	PayRequestStatus(2813)=0 (Received) is not applicable in this message.
PayDisputeReason	[0..1]	int	May be used to provide reason for PayRequestStatus(2813)=3 (Disputed).

Name	Mult.	Type	Description
RejectText	[0..1]	String	May be used to elaborate the reason for rejection or dispute.
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
ClearingBusinessDate	[0..1]	LocalMktDate	Echos back the business date of the PayManagementRequest(35=DY) message if this report is responding to a request. When the report is sent unsolicited, this is the business date of the report. This may carry the same date as the payment calculation date in PostTradePaymentCalculationDate(2825).
TransactTime	[1..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
Instrument	[0..1]	Component	May be included with minimal detail to identify the security or contract for which payments are to be made.
RelatedTradeGrp	[0..*]	Group	May be included to identify the trade(s) for which payments are to be made. Each instance identifies a separate trade.
Parties	[0..*]	Group	Identifies the parties to the contracts or trades. The account to be debited or credited is identified in the PostTradePayment component.
PostTradePayment	[1..1]	Component	
SettlDetails	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 109 PayManagementReportAck

Category: PayManagement

### 109.1 Message Functionality

PayManagementReportAck(35=EB) is used as a response to the PayManagementReport(35=EA) message. It may be used to accept, reject or dispute the details of the PayManagementReport(35=EA) depending on the business rules of the receiver. This message may also be used to acknowledge the receipt of a PayManagementReport(35=EA) message.

### 109.2 Structure

Name	Mult.	Type	Description
StandardHeader	[0..1]	Component	MsgType=EB
PayReportID	[1..1]	String	
PayReportStatus	[1..1]	CodeSet	
PayDisputeReason	[0..1]	int	May be used to provide reason for PayReportStatus(2806)=3 (Disputed).
RejectText	[0..1]	String	May be used to elaborate the reason for rejection or dispute.
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 110 PayManagementRequest

Category: PayManagement

### 110.1 Message Functionality

PayManagementRequest(35=DY) message is used to communicate a future or expected payment to be made or received related to a trade or contract after its settlement.

### 110.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DY
PayRequestID	[1..1]	String	
PayRequestTransType	[1..1]	CodeSet	
PayRequestRefID	[0..1]	String	Required for PayRequestTransType(2811)=1 (Cancel).
CancelText	[0..1]	String	May be used to provide reason for PayRequestTransType(2811)=1 (Cancel).
EncodedCancelTextLen	[0..1]	Length	Must be set if EncodedCancelText(2808) field is specified and must immediately precede it.
EncodedCancelText	[0..1]	data	Encoded (non-ASCII characters) representation of the CancelText(2807) field in the encoded format specified via the MessageEncoding(347) field.
ClearingBusinessDate	[0..1]	LocalMktDate	The business date of the request. This may carry the same date as the payment calculation date in PostTradePaymentCalculationDate(2825).
TransactTime	[1..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
Instrument	[0..1]	Component	May be included with minimal detail to identify the security or contract for which payments are to be made.

Name	Mult.	Type	Description
RelatedTradeGrp	[0..*]	Group	May be included to identify the trade(s) for which payments are to be made. Each instance identifies a separate trade.
Parties	[0..*]	Group	Identifies the parties to the contracts or trades. The account to be debited or credited is identified in the PostTradePayment component.
PostTradePayment	[1..1]	Component	
SettlDetails	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 111 PayManagementRequestAck

Category: PayManagement

### 111.1 Message Functionality

PayManagementRequestAck(35=DZ) is used to acknowledge the receipt of the PayManagementRequest(35=DY) message (i.e. a technical acknowledgement of receipt). Acceptance or rejection of the request is reported in the corresponding PayManagementReport(35=EA).

### 111.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgTyp=DZ
PayRequestID	[1..1]	String	
PayRequestStatus	[1..1]	CodeSet	Only PayRequestStatus(2813)=0 (Received) is applicable in this message.
StandardTrailer	[1..1]	Component	



## 112 PositionMaintenanceReport

Category: PositionMaintenance

### 112.1 Message Functionality

The Position Maintenance Report message is sent by the holder of a position in response to a Position Maintenance Request and is used to confirm that a request has been successfully processed or rejected.

### 112.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AM
PosMaintRptID	[1..1]	String	Unique identifier for this position report
PosTransType	[1..1]	CodeSet	
PositionID	[0..1]	String	Unique identifier for this position entity.
PosReqID	[0..1]	String	Unique identifier for the position maintenance request associated with this report
PosMaintAction	[1..1]	CodeSet	
OrigPosReqRefID	[0..1]	String	Reference to the PosReqID of a previous maintenance request that is being replaced or canceled.
PosMaintStatus	[0..1]	CodeSet	Status of PositionMaintenanceRequest. Conditionally required when responding to a PositionMaintenanceRequest.
PosMaintResult	[0..1]	CodeSet	
ClearingBusinessDate	[1..1]	LocalMktDate	The Clearing Business Date covered by this request
PreviousClearingBusinessDate	[0..1]	LocalMktDate	The business date previous to the clearing business date referred to by this maintenance request.
ValuationDate	[0..1]	LocalMktDate	Valuation date of the position(s) in this report.
ValuationTime	[0..1]	LocalMktTime	Valuation time of the position(s) in this report.
ValuationBusinessCenter	[0..1]	String	Business center of ValuationDate(2085) and ValuationTime(2086). Single value only.

Name	Mult.	Type	Description
DiscountFactor	[0..1]	float	For a forward position this is an appropriate value to discount the mark to market amount from the contract's maturity date back to present value.
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
ClearedIndicator	[0..1]	CodeSet	
ContractRefPosType	[0..1]	CodeSet	
PositionCapacity	[0..1]	CodeSet	
TerminatedIndicator	[0..1]	Boolean	
InputSource	[0..1]	String	
Parties	[0..*]	Group	Position Account
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
PosMaintRptRefID	[0..1]	String	Reference to a PosMaintRptID (Tag 721) from a previous Position Maintenance Report that is being replaced or canceled
Instrument	[1..1]	Component	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
ContraryInstructionIndicator	[0..1]	Boolean	Can be set to true when a position maintenance request is being performed contrary to current money position, i.e. for an exercise of an out of the money position or an abandonment (do not exercise ) of an in the money position
PriorSpreadIndicator	[0..1]	Boolean	
InstrmtLegGrp	[0..*]	Group	Specifies the number of legs that make up the Security
RelatedInstrumentGrp	[0..*]	Group	
UndInstrmtGrp	[0..*]	Group	Specifies the number of underlying legs that make up the Security

Name	Mult.	Type	Description
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
TransactTime	[0..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary. Conditionally required except when requests for reports are processed in batch, transaction time is not available, or when PosReqID is not present.
PositionQty	[0..*]	Group	Conditionally required when PosMaintAction(712) = 1(New), 2(Replace) or 4(Reverse).
PositionAmountData	[0..*]	Group	Insert here here the set of "Position Amount Data" fields defined in "Common Components of Application Messages"
RegulatoryTradeIDGrp	[0..*]	Group	The source, value and relationship of multiple trade identifiers for the same trade, e.g. Unique Swap Identifiers.
PaymentGrp	[0..*]	Group	Additional payments or bullet payments.
AdjustmentType	[0..1]	CodeSet	Type of adjustment to be applied. Delta_plus, Delta_minus, Final. If Adjustment Type is null, the PCS request will be processed as Margin Disposition only
ThresholdAmount	[0..1]	PriceOffset	
RelatedTradeGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 113 PositionMaintenanceRequest

Category: PositionMaintenance

### 113.1 Message Functionality

The Position Maintenance Request message allows the position owner to submit requests to the holder of a position which will result in a specific action being taken which will affect the position. Generally, the holder of the position is a central counter party or clearing organization but can also be a party providing investment services.

### 113.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AL
PosReqID	[0..1]	String	Unique identifier for the position maintenance request as assigned by the submitter. Conditionally required when used in a request/reply scenario (i.e. not required in batch scenario)
PosTransType	[1..1]	CodeSet	
PosMaintAction	[1..1]	CodeSet	
OrigPosReqRefID	[0..1]	String	Reference to the PosReqID of a previous maintenance request that is being replaced or canceled.
PosMaintRptRefID	[0..1]	String	Reference to a PosMaintRptID from a previous Position Maintenance Report that is being replaced or canceled.
ClearingBusinessDate	[1..1]	LocalMktDate	The Clearing Business Date referred to by this maintenance request
SettlDate	[0..1]	LocalMktDate	
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
Parties	[1..*]	Group	The Following PartyRoles can be specified:. ClearingOrganization. Clearing Firm. Position Account
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	

Name	Mult.	Type	Description
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
Instrument	[1..1]	Component	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	Specifies the number of legs that make up the Security
RelatedInstrumentGrp	[0..*]	Group	
UndInstrmtGrp	[0..*]	Group	Specifies the number of underlying legs that make up the Security
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
TransactTime	[0..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary.
PositionQty	[1..*]	Group	
PositionAmountData	[0..*]	Group	
AdjustmentType	[0..1]	CodeSet	Type of adjustment to be applied, used for PCS & PAJ. Delta_plus, Delta_minus, Final, If Adjustment Type is null, the request will be processed as Margin Disposition
ContraryInstructionIndicator	[0..1]	Boolean	Boolean - if Y then indicates you are requesting a position maintenance that acting
PriorSpreadIndicator	[0..1]	Boolean	Boolean - Y indicates you are requesting rollover of prior day's spread submissions
ThresholdAmount	[0..1]	PriceOffset	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 114 PositionReport

Category: PositionMaintenance

### 114.1 Message Functionality

The Position Report message is returned by the holder of a position in response to a Request for Position message. The purpose of the message is to report all aspects of a position and may be provided on a standing basis to report end of day positions to an owner.

### 114.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AP
ApplicationSequenceControl	[0..1]	Component	
PosMaintRptID	[1..1]	String	Unique identifier for this position report
PositionID	[0..1]	String	Unique identifier for this position entity.
PosReqID	[0..1]	String	Unique identifier for the Request for Positions associated with this report. This field should not be provided if the report was sent unsolicited.
PosReqType	[0..1]	CodeSet	Will be 7=Net Position if the report contains net position information for margin requirements.
PosReportAction	[0..1]	CodeSet	
MarginReqmtInqID	[0..1]	String	Unique identifier for the inquiry associated with this report. This field should not be provided if the report was sent unsolicited.
SubscriptionRequestType	[0..1]	CodeSet	Used to subscribe / unsubscribe for trade capture reports. If the field is absent, the value 0 will be the default
TotalNumPosReports	[0..1]	int	Total number of Position Reports being returned
TotNumReports	[0..1]	int	
LastRptRequested	[0..1]	CodeSet	
PosReqResult	[0..1]	CodeSet	Result of a Request for Position
UnsolicitedIndicator	[0..1]	CodeSet	Set to 'Y' if message is sent as a result of a subscription request or out of band configuration as opposed to a Position Request.
RegulatoryReportType	[0..1]	CodeSet	

Name	Mult.	Type	Description
RegulatoryReportTypeBusinessDate	[0..1]	LocalMktDate	May be used when the business event date differs from when the regulatory report is actually being submitted (typically specified in TrdRegTimestamps component).
TransactionAttributeGrp	[0..*]	Group	
TrdRegTimestamps	[0..*]	Group	
ClearingBusinessDate	[1..1]	LocalMktDate	The Clearing Business Date referred to by this maintenance request
PreviousClearingBusinessDate	[0..1]	LocalMktDate	The business date previous to the clearing business date referred to by this maintenance request.
ClearingPortfolioID	[0..1]	String	
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
PriceType	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
MessageEventSource	[0..1]	String	Used to identify the event or source which gave rise to a message
ClearedIndicator	[0..1]	CodeSet	
ContractRefPosType	[0..1]	CodeSet	
PositionCapacity	[0..1]	CodeSet	
TerminatedIndicator	[0..1]	Boolean	
TerminationDate	[0..1]	LocalMktDate	
IntraFirmTradeIndicator	[0..1]	Boolean	
TradeContinuation	[0..1]	CodeSet	
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
TradeCollateralization	[0..1]	CodeSet	
Parties	[1..*]	Group	Position Account

Name	Mult.	Type	Description
Account	[0..1]	String	Account may also be specified through via Parties Block using Party Role 27 which signifies Account
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin). Account may also be specified through via Parties Block using Party Role 27 which signifies Account
TaxonomyType	[0..1]	CodeSet	
Instrument	[0..1]	Component	
FinancingDetails	[0..1]	Component	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Position Settlement Date
SettlPrice	[0..1]	Price	
SettlPriceFxRateCalc	[0..1]	CodeSet	Expresses whether to multiply or divide SettlPrice(730) to arrive at the amount reported in PosAmt(708).
SettlForwardPoints	[0..1]	PriceOffset	
SettlPriceUnitOfMeasure	[0..1]	CodeSet	
SettlPriceUnitOfMeasureCurrency	[0..1]	Currency	
SettlPriceUnitOfMeasureCurrency-CodeSource	[0..1]	CodeSet	
SettlPriceType	[0..1]	CodeSet	Values = Final, Theoretical
PriorSettlPrice	[0..1]	Price	
PositionContingentPrice	[0..1]	Price	
DiscountFactor	[0..1]	float	For a forward position this is an appropriate value to discount the mark to market amount from the contract's maturity date back to present value.
ValuationDate	[0..1]	LocalMktDate	Valuation date of the position(s) in this report
ValuationTime	[0..1]	LocalMktTime	Valuation time of the position(s) in this report
ValuationBusinessCenter	[0..1]	String	Business center of ValuationDate(2085) and ValuationTime(2086). Single value only.
MatchStatus	[0..1]	CodeSet	Used to indicate if a Position Report is matched or unmatched
InstrmtLegGrp	[0..*]	Group	Specifies the number of legs that make up the Security
RelatedInstrumentGrp	[0..*]	Group	
CollateralAmountGrp	[0..*]	Group	



Name	Mult.	Type	Description
CollateralizationValueDate	[0..1]	LocalMktDate	
PosUndInstrmtGrp	[0..*]	Group	Specifies the number of underlying legs that make up the Security
TransactTime	[0..1]	UTCTimestamp	
PositionQty	[0..*]	Group	Insert here the set of "Position Qty" fields defined in "Common Components of Application Messages"
PositionAmountData	[0..*]	Group	Insert here the set of "Position Amount Data" fields defined in "Common Components of Application Messages"
RegulatoryTradeIDGrp	[0..*]	Group	
PaymentGrp	[0..*]	Group	
RegistStatus	[0..1]	CodeSet	RegNonRegInd
DeliveryDate	[0..1]	LocalMktDate	
ModelType	[0..1]	CodeSet	
PriceDelta	[0..1]	float	
RelatedTradeGrp	[0..*]	Group	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 115 PositionTransferInstruction

Category: PositionMaintenance

### 115.1 Message Functionality

The PositionTransferInstruction(35=DL) is sent by clearing firms to CCPs to initiate position transfers, or to accept or decline position transfers.

### 115.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = DL
TransferInstructionID	[1..1]	String	Submitting, cancelling, changing, accepting, and declining a transfer are all considered separate instructions, and each must have a unique ID. Chaining of firm generated IDs is not supported; TransferID(2437) assigned by the CCP must be used when sending an instruction referencing a previously submitted transfer.
TransferID	[0..1]	String	Conditionally required when responding to a PositionTransferReport(35=DN) message (e.g. when accepting or declining a transfer) or performing an action on a transfer (e.g. cancel or replace).
TransferTransType	[0..1]	CodeSet	
TransferType	[0..1]	CodeSet	
TransferScope	[0..1]	CodeSet	
Parties	[1..*]	Group	Specifies the source of the position transfer, e.g. the transferor.
TargetParties	[1..*]	Group	Specifies the target of the position transfer.
ClearingBusinessDate	[0..1]	LocalMktDate	Business date the transfer would clear.
TradeDate	[0..1]	LocalMktDate	Trade date associated with the position being transferred.
TransactTime	[0..1]	UTCTimestamp	
Instrument	[0..1]	Component	If not specified, indicates the transfer is for all instruments.
UndInstrmtGrp	[0..*]	Group	

Name	Mult.	Type	Description
PositionQty	[0..*]	Group	Position to transfer from the perspective of the source party prior to the transfer. If not specified, indicates transfer of all positions for a specified instrument, if Instrument is specified, or transfer of all positions if Instrument is not specified.
ClearingTradePrice	[0..1]	Price	Price at which the position is transferred.
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
PositionAmountData	[0..*]	Group	Optionally used to include cash residuals, etc., from the perspective of the source party prior to the transfer.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 116 PositionTransferInstructionAck

Category: PositionMaintenance

### 116.1 Message Functionality

The PositionTransferInstructionAck(35=DM) is sent by CCPs to clearing firms to acknowledge position transfer instructions, and to report errors processing position transfer instructions.

### 116.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DM
TransferInstructionID	[1..1]	String	The identifier of the PositionTransferInstruction(35=DL) this message is responding to.
TransferID	[0..1]	String	Optional when responding to a "new" transfer. When responding to a PositionTransferInstruction(35=DM) accepting, declining, or cancelling a transfer already initiated, this field can echo the TransferID(2437) sent.
TransferTransType	[0..1]	CodeSet	
TransferType	[0..1]	CodeSet	
TransferStatus	[0..1]	CodeSet	
TransferRejectReason	[0..1]	CodeSet	Conditionally required when TransferStatus(2442) = 1(Rejected by intermediary).
TransferScope	[0..1]	CodeSet	
Parties	[0..*]	Group	Specifies the source of the position transfer, e.g. the transferor.
TargetParties	[0..*]	Group	Specifies the target of the position transfer.
TransactTime	[0..1]	UTCTimestamp	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	

Name	Mult.	Type	Description
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 117 PositionTransferReport

Category: PositionMaintenance

### 117.1 Message Functionality

The PositionTransferReport(35=DN) is sent by CCPs to clearing firms indicating of positions that are to be transferred to the clearing firm, or to report on status of the transfer to the clearing firms involved in the transfer process.

### 117.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = DN
TransferInstructionID	[0..1]	String	Conditionally required when sent in response to a PositionTransferInstruction(35=DM).
TransferReportID	[1..1]	String	
TransferID	[1..1]	String	
TransferTransType	[1..1]	CodeSet	
TransferReportType	[1..1]	CodeSet	
TransferStatus	[1..1]	CodeSet	
TransferRejectReason	[0..1]	CodeSet	Conditionally required when TransferStatus(2422) = 1(Rejected by intermediary).
TransferScope	[0..1]	CodeSet	
Parties	[1..*]	Group	Specifies the source of the position transfer, e.g. the transferor.
TargetParties	[1..*]	Group	Specifies the target of the position transfer.
ClearingBusinessDate	[0..1]	LocalMktDate	Business date the transfer would clear.
TradeDate	[0..1]	LocalMktDate	Trade date associated with the position being transferred.
TransactTime	[0..1]	UTCTimestamp	
Instrument	[0..1]	Component	If not specified, indicates the transfer is for all instruments.
UndInstrmtGrp	[0..*]	Group	

Name	Mult.	Type	Description
PositionQty	[0..*]	Group	Position to transfer from the perspective of the source party prior to the transfer. If not specified, indicates transfer of all positions for a specified instrument, if Instrument is specified, or transfer of all positions if Instrument is not specified.
ClearingTradePrice	[0..1]	Price	Price at which the position is transferred.
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
PositionAmountData	[0..*]	Group	Optionally used to include cash residuals, etc., from the perspective of the source party prior to the transfer.
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[0..1]	Component	

## 118 Quote

Category: QuotationNegotiation

### 118.1 Message Functionality

The Quote message is used as the response to a Quote Request or a Quote Response message in both indicative, tradeable, and restricted tradeable quoting markets.

### 118.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = S
QuoteReqID	[0..1]	String	Required when quote is in response to a QuoteRequest(35=R) message.
QuoteID	[1..1]	String	
BidID	[0..1]	String	Unique identifier for the bid side of the quote.
OfferID	[0..1]	String	Unique identifier for the ask side of the quote.
SecondaryQuoteID	[0..1]	String	Can be used when modifying an existing quote.
QuoteMsgID	[0..1]	String	Optionally used to supply a message identifier for a quote.
QuoteRespID	[0..1]	String	Required when responding to the QuoteResponse(35=AJ) message. The counterparty specified ID of the QuoteResponse(35=AJ) message.
RefOrderID	[0..1]	String	May be used to refer to a related quote.
RefOrderIDSource	[0..1]	CodeSet	Conditionally required if RefOrderID(1080) is specified.
QuoteType	[0..1]	CodeSet	If not specified, the default is an indicative quote.
QuoteModelType	[0..1]	CodeSet	
PrivateQuote	[0..1]	CodeSet	Used to indicate whether a private negotiation is requested or if the response should be public. Only relevant in markets supporting both Private and Public quotes. If field is not provided in message, the model used must be bilaterally agreed.
SingleQuoteIndicator	[0..1]	CodeSet	
QuotQualGrp	[0..*]	Group	



Name	Mult.	Type	Description
TrdType	[0..1]	CodeSet	
NegotiationMethod	[0..1]	CodeSet	
QuoteResponseLevel	[0..1]	CodeSet	
QuoteAttributeGrp	[0..*]	Group	May be used by the quote provider to indicate pre-trade transparency waiver determination in the context of MiFID II.
ValueChecksGrp	[0..*]	Group	
Parties	[0..*]	Group	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
Instrument	[1..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
Side	[0..1]	CodeSet	Required for 1-sided tradeable or counter quotes of single instruments. Omit for 2-sided tradeable quote.
OrderQtyData	[0..1]	Component	Conditionally required for Tradeable or Counter quotes of single instruments when applicable for the type of instrument.
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Can be used with forex quotes to specify a specific "value date". For NDFs this is required.
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
Currency	[0..1]	Currency	Can be used to specify the currency of the quoted prices. May differ from the 'normal' trading currency of the instrument being quoted
CurrencyCodeSource	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	Required for NDFs to specify the settlement currency (fixing currency).
SettlCurrencyCodeSource	[0..1]	CodeSet	
RateSource	[0..*]	Group	
Stipulations	[0..*]	Group	

Name	Mult.	Type	Description
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
OwnerType	[0..1]	CodeSet	
SolicitedFlag	[0..1]	CodeSet	
LegQuotGrp	[0..*]	Group	Required for multileg quotes
BidPx	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
OfferPx	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
MktBidPx	[0..1]	Price	Can be used by markets that require showing the current best bid and offer
MktOfferPx	[0..1]	Price	Can be used by markets that require showing the current best bid and offer
MinBidSize	[0..1]	Qty	Used for markets that use a minimum and maximum bid size.
BidSize	[0..1]	Qty	If MinBidSize(647) is specified, BidSize(134) is interpreted to contain the maximum bid size.
TotalBidSize	[0..1]	Qty	
MinOfferSize	[0..1]	Qty	Used for markets that use a minimum and maximum offer size.
OfferSize	[0..1]	Qty	If MinOfferSize(648) is specified, OfferSize(135) is interpreted to contain the maximum offer size.
TotalOfferSize	[0..1]	Qty	
MinQty	[0..1]	Qty	For use in private/directed quote negotiations.
ExposureDuration	[0..1]	int	
ExposureDurationUnit	[0..1]	CodeSet	
ValidUntilTime	[0..1]	UTCTimestamp	The time when the quote will expire
BidSpotRate	[0..1]	Price	
OfferSpotRate	[0..1]	Price	
BidForwardPoints	[0..1]	PriceOffset	
OfferForwardPoints	[0..1]	PriceOffset	
BidSwapPoints	[0..1]	PriceOffset	
OfferSwapPoints	[0..1]	PriceOffset	
MidPx	[0..1]	Price	

Name	Mult.	Type	Description
BidYield	[0..1]	Percentage	
MidYield	[0..1]	Percentage	
OfferYield	[0..1]	Percentage	
TransactTime	[0..1]	UTCTimestamp	
TrdRegTimestamps	[0..*]	Group	
OrdType	[0..1]	CodeSet	Can be used to specify the type of order the quote is for
BidForwardPoints2	[0..1]	PriceOffset	Bid F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
OfferForwardPoints2	[0..1]	PriceOffset	Offer F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
SettlCurrBidFxRate	[0..1]	float	Can be used when the quote is provided in a currency other than the instrument's 'normal' trading currency. Applies to all bid prices contained in this quote message
SettlCurrOfferFxRate	[0..1]	float	Can be used when the quote is provided in a currency other than the instrument's 'normal' trading currency. Applies to all offer prices contained in this quote message
SettlCurrFxRateCalc	[0..1]	CodeSet	Can be used when the quote is provided in a currency other than the instruments trading currency.
CommissionData	[0..1]	Component	Can be used to show the counterparty the commission associated with the transaction.
CustOrderCapacity	[0..1]	CodeSet	
ExDestination	[0..1]	Exchange	Used when routing quotes to multiple markets
ExDestinationIDSource	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
RegulatoryReportType	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
BidSpread	[0..1]	float	SpreadOrBenchmarkCurveData component may be used to specify the benchmark.

Name	Mult.	Type	Description
OfferSpread	[0..1]	float	SpreadOrBenchmarkCurveData component may be used to specify the benchmark.
SpreadOrBenchmarkCurveData	[0..1]	Component	Spread(218) may be used for a mid-spread value.
RelativeValueGrp	[0..*]	Group	
YieldData	[0..1]	Component	
RoutingGrp	[0..*]	Group	
TradeContinuation	[0..1]	CodeSet	May be used to indicate the quote/negotiation is for the specified post-execution trade continuation or lifecycle event.
TradeContinuationText	[0..1]	String	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationTextLen	[0..1]	Length	
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
SelfMatchPreventionID	[0..1]	String	
SelfMatchPreventionInstruction	[0..1]	CodeSet	
ThrottleInst	[0..1]	CodeSet	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StrikeTime	[0..1]	UTCTimestamp	Conditionally required when QuoteQual(695) = d (Deferred spot) is specified.
StandardTrailer	[1..1]	Component	

## 119 QuoteAck

Category: QuotationNegotiation

### 119.1 Message Functionality

The QuoteAck(35=CW) message is used to acknowledge a Quote(35=S) submittal or request to cancel an individual quote using the QuoteCancel(35=Z) message during a Quote/Negotiation dialog.

### 119.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	35=CW
QuoteID	[0..1]	String	Contains the QuoteID(117) of a single Quote(35=S).
QuoteMsgID	[0..1]	String	Contains the QuoteMsgID(1166) of a single Quote(35=S) or QuoteCancel(35=Z).
QuoteReqID	[0..1]	String	
QuoteType	[0..1]	CodeSet	
QuoteCancelType	[0..1]	CodeSet	
SecondaryQuoteID	[0..1]	String	
QuoteAckStatus	[1..1]	CodeSet	
QuoteRejectReason	[0..1]	CodeSet	Conditionally required when QuoteAckStatus(1865) = 2(Rejected).
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
Parties	[0..*]	Group	
QuoteAttributeGrp	[0..*]	Group	May be used by the quote receiver to inform quote provider of pre-trade transparency waiver determination in the context of MiFID II.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 120 QuoteCancel

Category: QuotationNegotiation

### 120.1 Message Functionality

The Quote Cancel message is used by an originator of quotes to cancel quotes.

The Quote Cancel message supports cancellation of:

- All quotes
- Quotes for a specific symbol or security ID
- All quotes for a security type
- All quotes for an underlying

### 120.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = Z
QuoteReqID	[0..1]	String	Required when quote is in response to a Quote Request message
QuoteID	[0..1]	String	Conditionally required when QuoteCancelType(298) = 5 (Cancel specified single quote) and SecondaryQuoteID(1751) is not specified. Maps to QuoteID(117) of a single Quote(35=S) or QuoteEntryID(299) of a MassQuote(35=i)
SecondaryQuoteID	[0..1]	String	Conditionally required when QuoteCancelType(298) = 5 (Cancel specific single quote) and QuoteID(117) is not specified.
QuoteMsgID	[0..1]	String	Optionally used to supply a message identifier for a quote cancel.
QuoteCancelType	[1..1]	CodeSet	Identifies the type of Quote Cancel request.
QuoteType	[0..1]	CodeSet	Conditionally required when QuoteCancelType(298)=6(Cancel by type of quote).
QuoteResponseLevel	[0..1]	CodeSet	Level of Response requested from receiver of quote messages.

Name	Mult.	Type	Description
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TargetParties	[0..*]	Group	Can be used to specify the parties to whom the Quote Cancel should be applied.
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
QuotCxlEntriesGrp	[0..*]	Group	The number of securities (instruments) whose quotes are to be canceled. Not required when cancelling all quotes.
StandardTrailer	[1..1]	Component	

## 121 QuoteRequest

Category: QuotationNegotiation

### 121.1 Message Functionality

In some markets it is the practice to request quotes from brokers prior to placement of an order. The quote request message is used for this purpose. This message is commonly referred to as an Request For Quote (RFQ)

### 121.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = R
QuoteReqID	[1..1]	String	
RFQReqID	[0..1]	String	For tradeable quote model - used to indicate to which RFQ Request this Quote Request is in response.
ClOrdID	[0..1]	String	Required only in two party models when QuoteType(537) = '1' (Tradeable) and the OrdType(40) = '2' (Limit).
BookingType	[0..1]	CodeSet	
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
PrivateQuote	[0..1]	CodeSet	Used to indicate whether a private negotiation is requested or if the response should be public. Only relevant in markets supporting both Private and Public quotes. If field is not provided in message, the model used must be bilaterally agreed.
RespondentType	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	
RootParties	[0..*]	Group	Insert here the set of "Root Parties" fields defined in "common components of application messages". Used for acting parties that applies to the whole message, not individual legs, sides, etc.
QuotReqGrp	[1..*]	Group	Number of related symbols (instruments) in Request



Name	Mult.	Type	Description
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 122 QuoteRequestReject

Category: QuotationNegotiation

### 122.1 Message Functionality

The Quote Request Reject message is used to reject Quote Request messages for all quoting models.

### 122.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AG
QuoteReqID	[1..1]	String	
RFQReqID	[0..1]	String	For tradeable quote model - used to indicate to which RFQ Request this Quote Request is in response.
QuoteRequestRejectReason	[1..1]	CodeSet	Reason Quote was rejected
PrivateQuote	[0..1]	CodeSet	Used to indicate whether a private negotiation is requested or if the response should be public. Only relevant in markets supporting both Private and Public quotes.
RespondentType	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	
RootParties	[0..*]	Group	Insert here the set of "Root Parties" fields defined in "common components of application messages". Used for acting parties that applies to the whole message, not individual legs, sides, etc.
QuotReqRjctGrp	[1..*]	Group	Number of related symbols (instruments) in Request
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 123 QuoteResponse

Category: QuotationNegotiation

### 123.1 Message Functionality

The QuoteResponse(35=AJ) message is used for the following purposes:

1. Respond to an IOI(35=6) message
2. Respond to a Quote(35=S) message
3. Counter a Quote
4. End a negotiation dialog
5. Follow-up or end a QuoteRequest(35=R) dialog that did not receive a response.

### 123.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AJ
QuoteRespID	[1..1]	String	Unique ID as assigned by the Initiator
QuoteID	[0..1]	String	Required only when responding to a Quote.
QuoteMsgID	[0..1]	String	Optionally used when responding to a Quote.
QuoteReqID	[0..1]	String	Contains the QuoteReqID(131) of the QuoteRequest(35=R).
QuoteRespType	[1..1]	CodeSet	
ClOrdID	[0..1]	String	Unique ID as assigned by the Initiator. Required only in two-party models when QuoteRespType(694) = 1 (Hit/Lift) or 2 (Counter quote).
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
IOIID	[0..1]	String	Required only when responding to an IOI.
QuoteType	[0..1]	CodeSet	Default is Indicative.
PreTradeAnonymity	[0..1]	Boolean	
QuotQualGrp	[0..*]	Group	
TrdType	[0..1]	CodeSet	May be used by SEFs (Swap Execution Facilities) to indicate a block swap transaction.
RegulatoryTransactionType	[0..1]	CodeSet	

Name	Mult.	Type	Description
NegotiationMethod	[0..1]	CodeSet	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". For multilegs supply minimally a value for Symbol (55).
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages". For multilegs supply minimally a value for Symbol (55).
UndInstrmtGrp	[0..*]	Group	Number of underlyings
Side	[0..1]	CodeSet	Required when countering a single instrument quote or "hit/lift" an IOI or Quote.
OrderQtyData	[0..1]	Component	Conditionally required when countering a single instrument quote or "hit/lift" an IOI or Quote when applicable for the type of instrument.
MinQty	[0..1]	Qty	
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Can be used with forex quotes to specify a specific "value date"
TerminationDate	[0..1]	LocalMktDate	
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
Currency	[0..1]	Currency	Can be used to specify the currency of the quoted prices. May differ from the 'normal' trading currency of the instrument being quoted
CurrencyCodeSource	[0..1]	CodeSet	
Stipulations	[0..*]	Group	Optional
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	Used to identify the source of the Account code.

Name	Mult.	Type	Description
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
LegQuotGrp	[0..*]	Group	Required for multileg quote response
BidPx	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
OfferPx	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
MktBidPx	[0..1]	Price	Can be used by markets that require showing the current best bid and offer
MktOfferPx	[0..1]	Price	Can be used by markets that require showing the current best bid and offer
MinBidSize	[0..1]	Qty	Specifies the minimum bid size. Used for markets that use a minimum and maximum bid size.
BidSize	[0..1]	Qty	Specifies the bid size. If MinBidSize is specified, BidSize is interpreted to contain the maximum bid size.
MinOfferSize	[0..1]	Qty	Specifies the minimum offer size. If MinOfferSize is specified, OfferSize is interpreted to contain the maximum offer size.
OfferSize	[0..1]	Qty	Specified the offer size. If MinOfferSize is specified, OfferSize is interpreted to contain the maximum offer size.
ValidUntilTime	[0..1]	UTCTimestamp	The time when the QuoteResponse(35=AJ) will expire. Required for FI when the QuoteRespType(694) is either 1 (Hit/Lift) or 2 (Counter quote) to indicate to the respondent when the offer is valid until.
BidSpotRate	[0..1]	Price	May be applicable for F/X quotes
OfferSpotRate	[0..1]	Price	May be applicable for F/X quotes
BidForwardPoints	[0..1]	PriceOffset	May be applicable for F/X quotes
OfferForwardPoints	[0..1]	PriceOffset	May be applicable for F/X quotes
MidPx	[0..1]	Price	
BidYield	[0..1]	Percentage	
MidYield	[0..1]	Percentage	
OfferYield	[0..1]	Percentage	
TransactTime	[0..1]	UTCTimestamp	

Name	Mult.	Type	Description
OrdType	[0..1]	CodeSet	Can be used to specify the type of order the quote is for.
BidForwardPoints2	[0..1]	PriceOffset	Bid F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
OfferForwardPoints2	[0..1]	PriceOffset	Offer F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
SettlCurrBidFxRate	[0..1]	float	Can be used when the quote is provided in a currency other than the instrument's 'normal' trading currency. Applies to all bid prices contained in this quote message
SettlCurrOfferFxRate	[0..1]	float	Can be used when the quote is provided in a currency other than the instrument's 'normal' trading currency. Applies to all offer prices contained in this quote message
SettlCurrFxRateCalc	[0..1]	CodeSet	Can be used when the quote is provided in a currency other than the instruments trading currency.
CommissionData	[0..1]	Component	Can be used to show the counterparty the commission associated with the transaction.
CustOrderCapacity	[0..1]	CodeSet	For Futures Exchanges
ExDestination	[0..1]	Exchange	Used when routing quotes to multiple markets
ExDestinationIDSource	[0..1]	CodeSet	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
Price	[0..1]	Price	
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
CoverPrice	[0..1]	Price	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
YieldData	[0..1]	Component	Insert here the set of "YieldData" fields defined in "Common Components of Application Messages"

Name	Mult.	Type	Description
TradeContinuation	[0..1]	CodeSet	May be used to indicate the quote/negotiation is for the specified post-execution trade continuation or lifecycle event.
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
StrikeTime	[0..1]	UTCTimestamp	Conditionally required when QuoteQual(695) = d (Deferred spot) is specified.
StandardTrailer	[1..1]	Component	

## 124 QuoteStatusReport

Category: QuotationNegotiation

### 124.1 Message Functionality

The quote status report message is used:

- as the response to a Quote Status Request message
- as a response to a Quote Cancel message
- as a response to a Quote Response message in a negotiation dialog (see Volume 7 – PRODUCT: FIXED INCOME and USER GROUP: EXCHANGES AND MARKETS)

### 124.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AI
QuoteStatusReqID	[0..1]	String	
QuoteReqID	[0..1]	String	Required when quote is in response to a Quote Request message
QuoteID	[0..1]	String	Contains the QuoteID(117) of a single Quote(MsgType=S) or QuoteEntryID(299) of a MassQuote(MsgType=i).
BidID	[0..1]	String	Contains the BidID(390) of a single Quote(35=S).
OfferID	[0..1]	String	Contains the QuoteID(1867) of a single Quote(35=S).
SecondaryQuoteID	[0..1]	String	
QuoteMsgID	[0..1]	String	Contains the QuoteMsgID(1166) of a single Quote(MsgType=S) or QuoteID(117) of a MassQuote(MsgType=i).
QuoteRespID	[0..1]	String	Required when responding to a QuoteResponse(35=AJ) message.
QuoteType	[0..1]	CodeSet	If not specified, the default is an indicative quote.
QuoteCancelType	[0..1]	CodeSet	
Parties	[0..*]	Group	
TargetParties	[0..*]	Group	Can be populated with the values provided on the associated QuoteStatusRequest(MsgType=A).



Name	Mult.	Type	Description
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
Instrument	[0..1]	Component	Conditionally required when reporting status of a single security quote.
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
Side	[0..1]	CodeSet	
OrderQtyData	[0..1]	Component	Conditionally required for quotes of single instrument depending on the type of instrument when QuoteType(537)=1 (Tradeable).
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Can be used with forex quotes to specify a specific "value date"
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
TerminationDate	[0..1]	LocalMktDate	
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
Currency	[0..1]	Currency	Can be used to specify the currency of the quoted prices. May differ from the 'normal' trading currency of the instrument being quoted
CurrencyCodeSource	[0..1]	CodeSet	
Stipulations	[0..*]	Group	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
LegQuotStatGrp	[0..*]	Group	Conditionally required for multileg quote status reports.
QuotQualGrp	[0..*]	Group	
QuoteAttributeGrp	[0..*]	Group	
EventInitiatorType	[0..1]	CodeSet	
NegotiationMethod	[0..1]	CodeSet	
ExpireTime	[0..1]	UTCTimestamp	
Price	[0..1]	Price	
PriceType	[0..1]	CodeSet	

Name	Mult.	Type	Description
PriceQualifierGrp	[0..*]	Group	
SpreadOrBenchmarkCurveData	[0..1]	Component	
YieldData	[0..1]	Component	
BidQuotID	[0..1]	String	
OfferQuotID	[0..1]	String	
BidMDEntryID	[0..1]	String	
OfferMDEntryID	[0..1]	String	
BidPx	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
OfferPx	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
MktBidPx	[0..1]	Price	Can be used by markets that require showing the current best bid and offer
MktOfferPx	[0..1]	Price	Can be used by markets that require showing the current best bid and offer
MinBidSize	[0..1]	Qty	Used for markets that use a minimum and maximum bid size.
BidSize	[0..1]	Qty	If MinBidSize(647) is specified, BidSize(134) is interpreted to contain the maximum bid size.
TotalBidSize	[0..1]	Qty	
MinOfferSize	[0..1]	Qty	Used for markets that use a minimum and maximum offer size.
OfferSize	[0..1]	Qty	If MinOfferSize(648) is specified, OfferSize(135) is interpreted to contain the maximum offer size.
TotalOfferSize	[0..1]	Qty	
MinQty	[0..1]	Qty	
ValidUntilTime	[0..1]	UTCTimestamp	
BidSpotRate	[0..1]	Price	
OfferSpotRate	[0..1]	Price	
BidForwardPoints	[0..1]	PriceOffset	
OfferForwardPoints	[0..1]	PriceOffset	
MidPx	[0..1]	Price	
BidYield	[0..1]	Percentage	
MidYield	[0..1]	Percentage	
OfferYield	[0..1]	Percentage	

Name	Mult.	Type	Description
TransactTime	[0..1]	UTCTimestamp	
TrdRegTimestamps	[0..*]	Group	
OrdType	[0..1]	CodeSet	Can be used to specify the type of order the quote is for
BidForwardPoints2	[0..1]	PriceOffset	Bid F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
OfferForwardPoints2	[0..1]	PriceOffset	Offer F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
SettlCurrBidFxRate	[0..1]	float	Can be used when the quote is provided in a currency other than the instrument's 'normal' trading currency. Applies to all bid prices contained in this message
SettlCurrOfferFxRate	[0..1]	float	Can be used when the quote is provided in a currency other than the instrument's 'normal' trading currency. Applies to all offer prices contained in this message
SettlCurrFxRateCalc	[0..1]	CodeSet	Can be used when the quote is provided in a currency other than the instruments trading currency.
CommissionData	[0..1]	Component	Can be used to show the counterparty the commission associated with the transaction.
CustOrderCapacity	[0..1]	CodeSet	
ExDestination	[0..1]	Exchange	Used when routing quotes to multiple markets
ExDestinationIDSource	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
RegulatoryReportType	[0..1]	CodeSet	
QuoteStatus	[0..1]	CodeSet	
QuoteRejectReason	[0..1]	CodeSet	
RejectText	[0..1]	String	Reason description for rejecting the quote.
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
TradeContinuation	[0..1]	CodeSet	If specified, this should echo the value in the message this status message is in response to.
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
ThrottleResponse	[0..1]	Component	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StrikeTime	[0..1]	UTCTimestamp	Conditionally required when QuoteQual(695) = d (Deferred spot) is specified.
StandardTrailer	[1..1]	Component	

## 125 QuoteStatusRequest

Category: QuotationNegotiation

### 125.1 Message Functionality

The quote status request message is used for the following purposes in markets that employ tradeable or restricted tradeable quotes:

- For the issuer of a quote in a market to query the status of that quote (using the QuoteID to specify the target quote).
- To subscribe and unsubscribe for Quote Status Report messages for one or more securities.

### 125.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = a (lowercase)
QuoteStatusReqID	[0..1]	String	
QuoteID	[0..1]	String	Maps to: - QuoteID(117) of a single Quote. - QuoteEntryID(299) of a Mass Quote.
Instrument	[0..1]	Component	Conditionally required when requesting status of a single security quote.
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	Number of underlyings
InstrmtLegGrp	[0..*]	Group	Required for multileg quotes
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TargetParties	[0..*]	Group	Can be used to specify the parties to whom the Quote Status Request should apply.
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	

Name	Mult.	Type	Description
SubscriptionRequestType	[0..1]	CodeSet	Used to subscribe for Quote Status Report messages
StandardTrailer	[1..1]	Component	

## 126 RFQRequest

Category: QuotationNegotiation

### 126.1 Message Functionality

In tradeable and restricted tradeable quoting markets – Quote Requests are issued by counterparties interested in ascertaining the market for an instrument. Quote Requests are then distributed by the market to liquidity providers who make markets in the instrument. The RFQ Request is used by liquidity providers to indicate to the market for which instruments they are interested in receiving Quote Requests. It can be used to register interest in receiving quote requests for a single instrument or for multiple instruments

### 126.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AH
RFQReqID	[1..1]	String	
Parties	[0..*]	Group	Insert here the set of Parties (firm identification) fields defined in COMMON COMPONENTS OF APPLICATION MESSAGES
RFQReqGrp	[1..*]	Group	Number of related symbols (instruments) in Request
SubscriptionRequestType	[0..1]	CodeSet	Used to subscribe for Quote Requests that are sent into a market
PrivateQuote	[0..1]	CodeSet	Used to indicate whether a private negotiation is requested or if the response should be public. Only relevant in markets supporting both Private and Public quotes. If field is not provided in message, the model used must be bilaterally agreed.
StandardTrailer	[1..1]	Component	

## 127 RegistrationInstructions

Category: RegistrationInstruction

### 127.1 Message Functionality

The Registration Instructions message type may be used by institutions or retail intermediaries wishing to electronically submit registration information to a broker or fund manager (for CIV) for an order or for an allocation.

### 127.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = o (lowercase O)
RegistID	[1..1]	String	
ClearingBusinessDate	[0..1]	LocalMktDate	
RegistTransType	[1..1]	CodeSet	
RegistRefID	[1..1]	String	Required for Cancel and Replace RegistTransType messages
ClOrdID	[0..1]	String	Unique identifier of the order as assigned by institution or intermediary to which Registration relates
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
RegistAcctType	[0..1]	String	
TaxAdvantageType	[0..1]	CodeSet	
OwnershipType	[0..1]	CodeSet	
RgstDtIsGrp	[0..*]	Group	Number of registration details in this message (number of repeating groups to follow)
RgstDistInstGrp	[0..*]	Group	Number of Distribution instructions in this message (number of repeating groups to follow)
StandardTrailer	[1..1]	Component	



## 128 RegistrationInstructionsResponse

Category: RegistrationInstruction

### 128.1 Message Functionality

The Registration Instructions Response message type may be used by broker or fund manager (for CIV) in response to a Registration Instructions message submitted by an institution or retail intermediary for an order or for an allocation.

### 128.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = p (lowercase P)
RegistID	[1..1]	String	Unique identifier of the original Registration Instructions details
RegistTransType	[1..1]	CodeSet	Identifies original Registration Instructions transaction type
RegistRefID	[1..1]	String	Required for Cancel and Replace RegistTransType messages
ClOrdID	[0..1]	String	Unique identifier of the order as assigned by institution or intermediary.
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
RegistStatus	[1..1]	CodeSet	
RegistRejReasonCode	[0..1]	CodeSet	
RegistRejReasonText	[0..1]	String	
StandardTrailer	[1..1]	Component	

## 129 Reject

Category: Session

### 129.1 Message Functionality

The reject message should be issued when a message is received but cannot be properly processed due to a session-level rule violation. An example of when a reject may be appropriate would be the receipt of a message with invalid basic data which successfully passes de-encryption, CheckSum and BodyLength checks.

### 129.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 3
RefSeqNum	[1..1]	SeqNum	MsgSeqNum of rejected message
RefTagID	[0..1]	int	The tag number of the FIX field being referenced.
RefMsgType	[0..1]	CodeSet	The MsgType of the FIX message being referenced.
RefApplVerID	[0..1]	CodeSet	Recommended when rejecting an application message that does not explicitly provide ApplVerID ( 1128) on the message being rejected. In this case the value from the DefaultApplVerID(1137) or the default value specified in the NoMsgTypes repeating group on the logon message should be provided.
RefApplExtID	[0..1]	int	Recommended when rejecting an application message that does not explicitly provide ApplExtID(1156) on the rejected message. In this case the value from the DefaultApplExtID(1407) or the default value specified in the NoMsgTypes repeating group on the logon message should be provided.
RefCstmApplVerID	[0..1]	String	Recommended when rejecting an application message that does not explicitly provide CstmApplVerID(1129) on the message being rejected. In this case the value from the DefaultCstmApplVerID(1408) or the default value specified in the NoMsgTypes repeating group on the logon message should be provided.

Name	Mult.	Type	Description
SessionRejectReason	[0..1]	CodeSet	Code to identify reason for a session-level Reject message.
Text	[0..1]	String	Where possible, message to explain reason for rejection
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 130 RequestForPositions

Category: PositionMaintenance

### 130.1 Message Functionality

The Request For Positions message is used by the owner of a position to request a Position Report from the holder of the position, usually the central counter party or clearing organization. The request can be made at several levels of granularity.

### 130.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AN
PosReqID	[1..1]	String	Unique identifier for the Request for Positions as assigned by the submitter
PosReqType	[1..1]	CodeSet	
MatchStatus	[0..1]	CodeSet	
SubscriptionRequestType	[0..1]	CodeSet	Used to subscribe / unsubscribe for trade capture reports. If the field is absent, the value 0 will be the default
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
Parties	[1..*]	Group	Position Account
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
Instrument	[0..1]	Component	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	Specifies the number of legs that make up the Security
UndInstrmtGrp	[0..*]	Group	Specifies the number of underlying legs that make up the Security
ClearingBusinessDate	[1..1]	LocalMktDate	The Clearing Business Date referred to by this request

Name	Mult.	Type	Description
SettlDate	[0..1]	LocalMktDate	
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
TrdgSesGrp	[0..*]	Group	Specifies the number of repeating TradingSessionIDs
TransactTime	[1..1]	UTCTimestamp	Time this order request was initiated/released by the trader, trading system, or intermediary.
ResponseTransportType	[0..1]	CodeSet	Ability to specify whether the response to the request should be delivered inband or via pre-arranged out-of-band transport.
ResponseDestination	[0..1]	String	URI destination name. Used if ResponseTransportType is out-of-band.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 131 RequestForPositionsAck

Category: PositionMaintenance

### 131.1 Message Functionality

The Request for Positions Ack message is returned by the holder of the position in response to a Request for Positions message. The purpose of the message is to acknowledge that a request has been received and is being processed.

### 131.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AO
PosMaintRptID	[1..1]	String	Unique identifier for this position report
PosReqID	[0..1]	String	Unique identifier for the Request for Position associated with this report. This field should not be provided if the report was sent unsolicited.
TotalNumPosReports	[0..1]	int	Total number of Position Reports being returned
TotNumReports	[0..1]	int	
UnsolicitedIndicator	[0..1]	CodeSet	Set to 'Y' if message is sent as a result of a subscription request or out of band configuration as opposed to a Position Request.
PosReqResult	[1..1]	CodeSet	
PosReqStatus	[1..1]	CodeSet	
PosReqType	[0..1]	CodeSet	
MatchStatus	[0..1]	CodeSet	
ClearingBusinessDate	[0..1]	LocalMktDate	
SubscriptionRequestType	[0..1]	CodeSet	
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
Parties	[1..*]	Group	Position Account
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	

Name	Mult.	Type	Description
AccountType	[0..1]	CodeSet	Type of account associated with the order (Origin)
Instrument	[0..1]	Component	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	Specifies the number of legs that make up the Security
UndInstrmtGrp	[0..*]	Group	Specifies the number of underlying legs that make up the Security
ResponseTransportType	[0..1]	CodeSet	Ability to specify whether the response to the request should be delivered inband or via pre-arranged out-of-band transport.
ResponseDestination	[0..1]	String	URI destination name. Used if ResponseTransportType is out-of-band.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 132 ResendRequest

Category: Session

### 132.1 Message Functionality

The resend request is sent by the receiving application to initiate the retransmission of messages. This function is utilized if a sequence number gap is detected, if the receiving application lost a message, or as a function of the initialization process.

### 132.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 2
BeginSeqNo	[1..1]	SeqNum	
EndSeqNo	[1..1]	SeqNum	
StandardTrailer	[1..1]	Component	



## 133 SecurityDefinition

Category: SecuritiesReferenceData

### 133.1 Message Functionality

The SecurityDefinition(35=d) message is used for the following:

1. Accept the security defined in a SecurityDefinition(35=d) message.
2. Accept the security defined in a SecurityDefinition(35=d) message with changes to the definition and/or identity of the security.
3. Reject the security requested in a SecurityDefinition(35=d) message.
4. Respond to a request for securities within a specified market segment.
5. Convey comprehensive security definition for all market segments that the security participates in.
6. Convey the security's trading rules that differ from default rules for the market segment.

### 133.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = d (lowercase)
ApplicationSequenceControl	[0..1]	Component	
SecurityReportID	[0..1]	int	Used to identify the SecurityDefinition(35=d) message.
ClearingBusinessDate	[0..1]	LocalMktDate	
SecurityReqID	[0..1]	String	
OrderRequestID	[0..1]	int	
SecurityResponseID	[0..1]	String	Used to identify the response to a SecurityDefinitionRequest(35=c) message.
SecurityResponseType	[0..1]	CodeSet	
SecurityRequestResult	[0..1]	CodeSet	Allow result of query request to be returned to requester
SecurityRejectReason	[0..1]	CodeSet	Used to specify a rejection reason when SecurityResponseType(323)=5 (Reject security proposal).
CorporateAction	[0..1]	CodeSet	
Instrument	[0..1]	Component	

Name	Mult.	Type	Description
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
SecurityClassificationGrp	[0..*]	Group	Used to specify forms of product classifications
Currency	[0..1]	Currency	Currency in which the price is denominated
CurrencyCodeSource	[0..1]	CodeSet	
PreviousAdjustedOpenInterest	[0..1]	Amt	
PreviousUnadjustedOpenInterest	[0..1]	Amt	
PriorSettlPrice	[0..1]	Price	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
Stipulations	[0..*]	Group	
NumOfSimpleInstruments	[0..1]	int	
NumOfComplexInstruments	[0..1]	int	
InstrmtLegGrp	[0..*]	Group	
SpreadOrBenchmarkCurveData	[0..1]	Component	
YieldData	[0..1]	Component	
MarketSegmentGrp	[0..*]	Group	Contains all the security details related to listing and trading the security
LastUpdateTime	[0..1]	UTCTimestamp	Represents the time at which a security was last updated
EffectiveBusinessDate	[0..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	
StandardTrailer	[1..1]	Component	

## 134 SecurityDefinitionRequest

Category: SecuritiesReferenceData

### 134.1 Message Functionality

The SecurityDefinitionRequest(35=c) message is used for the following:

1. Request a specific security to be traded with the second party. The requested security can be defined as a multileg security made up of one or more instrument legs.
2. Request a set of individual securities for a single market segment.
3. Request all securities, independent of market segment.

### 134.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = c (lowercase)
SecurityReqID	[1..1]	String	
SecurityRequestType	[1..1]	CodeSet	
MarketID	[0..1]	Exchange	Identifies the market for which the security definition request is being made.
MarketSegmentID	[0..1]	String	Identifies the segment of the market for which the security definition request is being made.
Instrument	[0..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
TradingSessionID	[0..1]	CodeSet	Optional trading session identifier to specify a particular trading session for which you want to obtain a list of securities that are tradeable.
TradingSessionSubID	[0..1]	CodeSet	
Stipulations	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
SpreadOrBenchmarkCurveData	[0..1]	Component	
YieldData	[0..1]	Component	
ExpirationCycle	[0..1]	CodeSet	
SubscriptionRequestType	[0..1]	CodeSet	Subscribe or unsubscribe for security status to security specified in request.
StandardTrailer	[1..1]	Component	

## 135 SecurityDefinitionUpdateReport

Category: SecuritiesReferenceData

### 135.1 Message Functionality

This message is used for reporting updates to a product security master file. Updates could be the result of corporate actions or other business events. Updates may include additions, modifications or deletions.

### 135.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BP
ApplicationSequenceControl	[0..1]	Component	
SecurityReportID	[0..1]	int	Used to identify the SecurityDefinitionUpdateReport(35=BP) message in a bulk message transfer. Not used in request/response messaging.
SecurityReqID	[0..1]	String	Conditionally required when responding to the SecurityDefinitionRequest(35=c) message.
SecurityResponseID	[0..1]	String	Used to identify the SecurityDefinitionUpdateReport(35=BP) message.
SecurityResponseType	[0..1]	CodeSet	
ClearingBusinessDate	[0..1]	LocalMktDate	
SecurityUpdateAction	[0..1]	CodeSet	
CorporateAction	[0..1]	CodeSet	
Instrument	[0..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
PreviousAdjustedOpenInterest	[0..1]	Amt	
PreviousUnadjustedOpenInterest	[0..1]	Amt	

Name	Mult.	Type	Description
PriorSettlPrice	[0..1]	Price	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
Stipulations	[0..*]	Group	
NumOfSimpleInstruments	[0..1]	int	
NumOfComplexInstruments	[0..1]	int	
InstrmtLegGrp	[0..*]	Group	
SpreadOrBenchmarkCurveData	[0..1]	Component	
YieldData	[0..1]	Component	
MarketSegmentGrp	[0..*]	Group	Contains all the security details related to listing and trading the security
LastUpdateTime	[0..1]	UTCTimestamp	Represents the time at which a security was last updated
EffectiveBusinessDate	[0..1]	LocalMktDate	
TransactTime	[0..1]	UTCTimestamp	
StandardTrailer	[1..1]	Component	

## 136 SecurityList

Category: SecuritiesReferenceData

### 136.1 Message Functionality

The Security List message is used to return a list of securities that matches the criteria specified in a Security List Request.

### 136.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = y (lowercase Y)
ApplicationSequenceControl	[0..1]	Component	
SecurityReportID	[0..1]	int	
ClearingBusinessDate	[0..1]	LocalMktDate	
SecurityListID	[0..1]	String	Identifies a specific Security List Entry
SecurityListRefID	[0..1]	String	Provides a reference to another Security List
SecurityListDesc	[0..1]	String	
EncodedSecurityListDescLen	[0..1]	Length	
EncodedSecurityListDesc	[0..1]	data	
SecurityListType	[0..1]	CodeSet	Identifies a list type
SecurityListTypeSource	[0..1]	CodeSet	Identifies the source of a list type
SecurityReqID	[0..1]	String	
SecurityResponseID	[0..1]	String	Identifier for the Security List message
SecurityRequestResult	[0..1]	CodeSet	Result of the Security Request identified by the SecurityReqID
SecurityRejectReason	[0..1]	CodeSet	Used to specify a rejection reason when SecurityResponseType (323) is equal to 1 (Invalid or unsupported request) or 5 (Request for instrument data not supported).
TransactTime	[0..1]	UTCTimestamp	
TotNoRelatedSym	[0..1]	int	Used to indicate the total number of securities being returned for this request. Used in the event that message fragmentation is required.
MarketID	[0..1]	Exchange	Identifies the market which lists and trades the instrument.

Name	Mult.	Type	Description
MarketSegmentID	[0..1]	String	Identifies the segment of the market to which the specify trading rules and listing rules apply. The segment may indicate the venue, whether retail or wholesale, or even segregation by nationality.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
SecListGrp	[0..*]	Group	Specifies the number of repeating symbols (instruments) specified
StandardTrailer	[1..1]	Component	



## 137 SecurityListRequest

Category: SecuritiesReferenceData

### 137.1 Message Functionality

The Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request

### 137.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = x (lowercase X)
SecurityReqID	[1..1]	String	
SecurityListRequestType	[1..1]	CodeSet	Type of Security List Request being made
SecurityListID	[0..1]	String	Identifies a specific list
SecurityListType	[0..1]	CodeSet	Identifies a list type.
SecurityListTypeSource	[0..1]	CodeSet	Identifies the source a list type
MarketID	[0..1]	Exchange	Identifies the market which lists and trades the instrument.
MarketSegmentID	[0..1]	String	Identifies the segment of the market to which the specify trading rules and listing rules apply. The segment may indicate the venue, whether retail or wholesale, or even segregation by nationality.
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". of the requested Security
InstrumentExtension	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "Common Components of Application Messages"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	Number of underlyings
InstrmtLegGrp	[0..*]	Group	Number of legs that make up the Security
RelatedInstrumentGrp	[0..*]	Group	
Currency	[0..1]	Currency	

Name	Mult.	Type	Description
CurrencyCodeSource	[0..1]	CodeSet	
Text	[0..1]	String	Comment, instructions, or other identifying information.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
TradingSessionID	[0..1]	CodeSet	Optional Trading Session Identifier to specify a particular trading session for which you want to obtain a list of securities that are tradeable.
TradingSessionSubID	[0..1]	CodeSet	
SubscriptionRequestType	[0..1]	CodeSet	Subscribe or unsubscribe for security status to security specified in request.
StandardTrailer	[1..1]	Component	

## 138 SecurityListUpdateReport

Category: SecuritiesReferenceData

### 138.1 Message Functionality

The Security List Update Report is used for reporting updates to a Contract Security Masterfile. Updates could be due to Corporate Actions or other business events. Update may include additions, modifications and deletions.

### 138.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BK
ApplicationSequenceControl	[0..1]	Component	
SecurityReportID	[0..1]	int	Identifier for the Security List Update message in a bulk transfer environment (No Request/Response)
SecurityListID	[0..1]	String	Identifies a specific Security List entity
SecurityListRefID	[0..1]	String	Provides a reference to another Security List
SecurityListDesc	[0..1]	String	
EncodedSecurityListDescLen	[0..1]	Length	
EncodedSecurityListDesc	[0..1]	data	
SecurityListType	[0..1]	CodeSet	Identifies a list type
SecurityListTypeSource	[0..1]	CodeSet	Identifies the source as a list type
SecurityReqID	[0..1]	String	
SecurityResponseID	[0..1]	String	Identifier for the Security List message.
SecurityRequestResult	[0..1]	CodeSet	Result of the Security Request identified by the SecurityReqID.
TotNoRelatedSym	[0..1]	int	Used to indicate the total number of securities being returned for this request. Used in the event that message fragmentation is required.
ClearingBusinessDate	[0..1]	LocalMktDate	
SecurityUpdateAction	[0..1]	CodeSet	
CorporateAction	[0..1]	CodeSet	Identifies the type of Corporate Action that triggered the update

Name	Mult.	Type	Description
MarketID	[0..1]	Exchange	Identifies the market which lists and trades the instrument.
MarketSegmentID	[0..1]	String	Identifies the segment of the market to which the specific trading rules and listing rules apply. The segment may indicate the venue, whether retail or wholesale, or even segregation by nationality.
TransactTime	[0..1]	UTCTimestamp	
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
SecLstUpdRelSymGrp	[0..*]	Group	Specifies the number of repeating symbols (instruments) specified
StandardTrailer	[1..1]	Component	

## 139 SecurityMassStatus

Category: SecuritiesReferenceData

### 139.1 Message Functionality

### 139.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CO
ApplicationSequenceControl	[0..1]	Component	
SecurityStatusReqID	[0..1]	String	Required when mass status is in response to a SecurityMassStatusRequest(35=CN) message.
SecurityListID	[0..1]	String	Identifies all securities for a security list identifier.
MarketID	[0..1]	Exchange	Identifies all securities for a market.
MarketSegmentID	[0..1]	String	Identifies all securities for a market segment.
TradeDate	[0..1]	LocalMktDate	Business day that the state change applies to.
TradingSessionID	[0..1]	CodeSet	Identifies all securities for a trading session.
TradingSessionSubID	[0..1]	CodeSet	Identifies all securities for a trading sub-session.
InstrumentScope	[0..1]	Component	
UnsolicitedIndicator	[0..1]	CodeSet	Set to "Y" if message is sent as a result of a subscription request not a snapshot request.
SecurityMassTradingStatus	[0..1]	CodeSet	
FastMarketIndicator	[0..1]	Boolean	
SecurityMassTradingEvent	[0..1]	CodeSet	
MassHaltReason	[0..1]	CodeSet	
MDBookType	[0..1]	CodeSet	Used to relay changes in the book type.
MarketDepth	[0..1]	int	Used to relay changes in Market Depth.
TransactTime	[0..1]	UTCTimestamp	Time of state change for security list.
Adjustment	[0..1]	CodeSet	
SecMassStatGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 140 SecurityMassStatusRequest

Category: SecuritiesReferenceData

### 140.1 Message Functionality

### 140.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CN
SecurityStatusReqID	[1..1]	String	Must be unique, or the ID of previous Security Mass Status Request to disable if SubscriptionRequestType = Disable previous Snapshot + Updates Request (2).
InstrumentScope	[0..1]	Component	
SubscriptionRequestType	[1..1]	CodeSet	SubscriptionRequestType indicates to the other party what type of response is expected. A snapshot request only asks for current information. A subscribe request asks for updates as the status changes. Unsubscribe will cancel any future update messages from the counter party.
SecurityListID	[0..1]	String	
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 141 SecurityRiskMetricsReport

Category: SecuritiesReferenceData

### 141.1 Message Functionality

SecurityRiskMetricsReport(35=EG) is used for publishing the risk metrics, valuation metrics or analytics of one or more securities, or for an option series.

### 141.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType(35)=EG
SecurityRiskMetricsReportID	[1..1]	String	
RiskMetricsSecurityGroup	[0..1]	String	May be used to identify the group of related instruments provided in SecurityRiskMetricGrp. Conditionally required when RiskMetricsSecuritySubGroup(2990) is present.
RiskMetricsSecuritySubGroup	[0..1]	String	May be used with RiskMetricsSecurityGroup(2989) to provide a more granular group identification.
TransactTime	[0..1]	UTCTimestamp	
UnderlyingInstrument	[0..1]	Component	UnderlyingPx(810) within the component may be used when valuation calculation uses a single reference price.
UnderlyingBidPx	[0..1]	Price	May be used to specify the (best) bid of the underlying instrument when valuation calculation uses real-time prices.
UnderlyingOfferPx	[0..1]	Price	May be used to specify the (best) offer of the underlying instrument when valuation calculation uses real-time prices.
MetricsCalculationPriceSource	[0..1]	CodeSet	
RiskFreeRate	[0..1]	float	May be used to identify the risk free rate used in the pricing model specified.
AssetValuationModel	[0..1]	CodeSet	
LastFragment	[0..1]	CodeSet	
SecurityRiskMetricGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 142 SecurityStatus

Category: SecuritiesReferenceData

### 142.1 Message Functionality

The Security Status message provides for the ability to report changes in status to a security. The Security Status message contains fields to indicate trading status, corporate actions, financial status of the company. The Security Status message is used by one trading entity (for instance an exchange) to report changes in the state of a security.

### 142.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = f (lowercase)
ApplicationSequenceControl	[0..1]	Component	
SecurityStatusReqID	[0..1]	String	
Instrument	[1..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
TradeDate	[0..1]	LocalMktDate	Business day that the state change applies to.
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
UnsolicitedIndicator	[0..1]	CodeSet	Set to 'Y' if message is sent as a result of a subscription request not a snapshot request
SecurityTradingStatus	[0..1]	CodeSet	
MarketMakerActivity	[0..1]	CodeSet	
FastMarketIndicator	[0..1]	Boolean	



Name	Mult.	Type	Description
SecurityTradingEvent	[0..1]	CodeSet	
NextAuctionTime	[0..1]	UTCTimestamp	
FinancialStatus	[0..1]	CodeSet	
CorporateAction	[0..1]	CodeSet	
HaltReason	[0..1]	CodeSet	
InViewOfCommon	[0..1]	CodeSet	
DueToRelated	[0..1]	CodeSet	
MDBookType	[0..1]	CodeSet	Used to relay changes in the book type
MarketDepth	[0..1]	int	Used to relay changes in market depth.
BuyVolume	[0..1]	Qty	
SellVolume	[0..1]	Qty	
HighPx	[0..1]	Price	
LowPx	[0..1]	Price	
LastPx	[0..1]	Price	Represents the last price for that security either on a consolidated or an individual participant basis at the time it is disseminated.
ClearingPriceParametersGrp	[0..*]	Group	
SettlPrice	[0..1]	Price	
SettlPriceType	[0..1]	CodeSet	
SettlPriceDeterminationMethod	[0..1]	CodeSet	
TransactTime	[0..1]	UTCTimestamp	Time of status information.
Adjustment	[0..1]	CodeSet	
FirstPx	[0..1]	Price	Represents the price of the first fill of the trading session.
LinkageHandlingIndicator	[0..1]	Boolean	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 143 SecurityStatusRequest

Category: SecuritiesReferenceData

### 143.1 Message Functionality

The Security Status Request message provides for the ability to request the status of a security. One or more Security Status messages are returned as a result of a Security Status Request message.

### 143.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = e (lowercase)
SecurityStatusReqID	[1..1]	String	Must be unique, or the ID of previous Security Status Request to disable if SubscriptionRequestType = Disable previous Snapshot + Updates Request (2).
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
InstrumentExtension	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "Common Components of Application Messages"
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	Number of underlyings
InstrmtLegGrp	[0..*]	Group	Number of legs that make up the Security
RelatedInstrumentGrp	[0..*]	Group	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
SubscriptionRequestType	[1..1]	CodeSet	SubscriptionRequestType indicates to the other party what type of response is expected. A snapshot request only asks for current information. A subscribe request asks for updates as the status changes. Unsubscribe will cancel any future update messages from the counter party.
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
TradingSessionID	[0..1]	CodeSet	

Name	Mult.	Type	Description
TradingSessionSubID	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 144 SecurityTypeRequest

Category: SecuritiesReferenceData

### 144.1 Message Functionality

The Security Type Request message is used to return a list of security types available from a counterparty or market.

### 144.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = v (lowercase V)
SecurityReqID	[1..1]	String	
Text	[0..1]	String	Comment, instructions, or other identifying information.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
MarketID	[0..1]	Exchange	Optional MarketID to specify a particular trading session for which you want to obtain a list of securities that are tradeable.
MarketSegmentID	[0..1]	String	Optional Market Segment Identifier to specify a particular trading session for which you want to obtain a list of securities that are tradeable.
TradingSessionID	[0..1]	CodeSet	Optional Trading Session Identifier to specify a particular trading session for which you want to obtain a list of securities that are tradeable.
TradingSessionSubID	[0..1]	CodeSet	
Product	[0..1]	CodeSet	Used to qualify which security types are returned
SecurityType	[0..1]	CodeSet	Used to qualify which security type is returned
SecuritySubType	[0..1]	String	Used to qualify which security types are returned
StandardTrailer	[1..1]	Component	

## 145 SecurityTypes

Category: SecuritiesReferenceData

### 145.1 Message Functionality

The Security Type Request message is used to return a list of security types available from a counterparty or market.

### 145.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = w (lowercase W)
ApplicationSequenceControl	[0..1]	Component	
SecurityReqID	[1..1]	String	
SecurityResponseID	[1..1]	String	Identifier for the security response message
SecurityResponseType	[1..1]	CodeSet	The result of the security request identified by SecurityReqID
TotNoSecurityTypes	[0..1]	int	Indicates total number of security types in the event that multiple Security Type messages are used to return results
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
SecTypesGrp	[0..*]	Group	
Text	[0..1]	String	Comment, instructions, or other identifying information.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
MarketID	[0..1]	Exchange	Optional MarketID to specify a particular trading session for which you want to obtain a list of securities that are tradeable.
MarketSegmentID	[0..1]	String	Optional Market Segment Identifier to specify a particular trading session for which you want to obtain a list of securities that are tradeable.

Name	Mult.	Type	Description
TradingSessionID	[0..1]	CodeSet	Optional Trading Session Identifier to specify a particular trading session for which you want to obtain a list of securities that are tradeable.
TradingSessionSubID	[0..1]	CodeSet	
SubscriptionRequestType	[0..1]	CodeSet	Subscribe or unsubscribe for security status to security specified in request.
StandardTrailer	[1..1]	Component	

## 146 SequenceReset

Category: Session

### 146.1 Message Functionality

The sequence reset message is used by the sending application to reset the incoming sequence number on the opposing side.

### 146.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 4
GapFillFlag	[0..1]	CodeSet	
NewSeqNo	[1..1]	SeqNum	
StandardTrailer	[1..1]	Component	

## 147 SettlementInstructionRequest

Category: SettlementInstruction

### 147.1 Message Functionality

The Settlement Instruction Request message is used to request standing settlement instructions from another party.

### 147.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AV
SettlInstReqID	[1..1]	String	Unique message ID
TransactTime	[1..1]	UTCTimestamp	Date/Time this request message was generated
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages". Used here for party whose instructions this message is requesting and (optionally) for settlement location. Not required if database identifiers are being used to request settlement instructions. Required otherwise.
AllocAccount	[0..1]	String	Should not be populated if StandInstDbType is populated
AllocAcctIDSource	[0..1]	CodeSet	Required if AllocAccount populated. Should not be populated if StandInstDbType is populated
Side	[0..1]	CodeSet	Should not be populated if StandInstDbType is populated
Product	[0..1]	CodeSet	Should not be populated if StandInstDbType is populated
SecurityType	[0..1]	CodeSet	Should not be populated if StandInstDbType is populated
CFICode	[0..1]	String	Should not be populated if StandInstDbType is populated
UPICode	[0..1]	String	Should not be populated if StandInstDbType is populated
SettlCurrency	[0..1]	Currency	Should not be populated if StandInstDbType is populated



Name	Mult.	Type	Description
SettlCurrencyCodeSource	[0..1]	CodeSet	
EffectiveTime	[0..1]	UTCTimestamp	Should not be populated if StandInstDbType is populated
ExpireTime	[0..1]	UTCTimestamp	Should not be populated if StandInstDbType is populated
LastUpdateTime	[0..1]	UTCTimestamp	Should not be populated if StandInstDbType is populated
StandInstDbType	[0..1]	CodeSet	Should not be populated if any of AllocAccount through to LastUpdateTime are populated
StandInstDbName	[0..1]	String	Should not be populated if any of AllocAccount through to LastUpdateTime are populated
StandInstDbID	[0..1]	String	The identifier of the standing instructions within the database specified in StandInstDbType. Required if StandInstDbType populated. Should not be populated if any of AllocAccount through to LastUpdateTime are populated
StandardTrailer	[1..1]	Component	

## 148 SettlementInstructions

Category: SettlementInstruction

### 148.1 Message Functionality

The Settlement Instructions message provides the broker's, the institution's, or the intermediary's instructions for trade settlement. This message has been designed so that it can be sent from the broker to the institution, from the institution to the broker, or from either to an independent "standing instructions" database or matching system or, for CIV, from an intermediary to a fund manager.

### 148.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = T
SettlInstMsgID	[1..1]	String	Unique identifier for this message
SettlInstReqID	[0..1]	String	Only used when this message is used to respond to a settlement instruction request (to which this ID refers)
SettlInstMode	[1..1]	CodeSet	1=Standing Instructions, 2=Specific Allocation Account Overriding, 3=Specific Allocation Account Standing, 4=Specific Order, 5=Reject SSI request
SettlInstReqRejCode	[0..1]	CodeSet	Required for SettlInstMode = 5. Used to provide reason for rejecting a Settlement Instruction Request message.
Text	[0..1]	String	Can be used to provide any additional rejection text where rejecting a Settlement Instruction Request message.
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
ClOrdID	[0..1]	String	Required for SettlInstMode(160) = 4 and when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID.
TransactTime	[1..1]	UTCTimestamp	Date/time this message was generated
SettlInstGrp	[0..*]	Group	Required except where SettlInstMode is 5=Reject SSI request
StandardTrailer	[1..1]	Component	

## 149 SettlementObligationReport

Category: SettlementInstruction

### 149.1 Message Functionality

The Settlement Obligation Report message provides a central counterparty, institution, or individual counterparty with a capacity for reporting the final details of a currency settlement obligation.

### 149.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BQ
ApplicationSequenceControl	[0..1]	Component	
ClearingBusinessDate	[0..1]	LocalMktDate	
SettlementCycleNo	[0..1]	int	Settlement cycle in which the settlement obligation was generated
SettlObligMsgID	[1..1]	String	Unique identifier for this message
SettlObligMode	[1..1]	CodeSet	Used to identify the reporting mode of the settlement obligation which is either preliminary or final
Text	[0..1]	String	Can be used to provide any additional rejection text where rejecting a Settlement Instruction Request message.
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
TransactTime	[0..1]	UTCTimestamp	Time when the Settlement Obligation Report was created.
SettlementObligationInstructions	[1..*]	Group	
StandardTrailer	[1..1]	Component	

## 150 SettlementStatusReport

Category: SettlementStatusManagement

### 150.1 Message Functionality

SettlementStatusReport(35=EE) is a response to the SettlementStatusRequest(35=EC) to provide settlement status for the requested trade. It may also be sent unsolicited without an explicit request message by the party able to provide the settlement status for the trade identified in the report message.

### 150.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType(35)=EE
SettlStatusReportID	[1..1]	String	Unique identifier assigned by sender of this message.
SettlStatusRequestID	[0..1]	String	Identifier of SettlementStatusRequest(35=EC) message being responded to.
SettlStatus	[1..1]	String	
SettlStatusReason	[0..1]	String	May be used when additional settlement status reason is available.
SettlStatusReasonText	[0..1]	String	May be used to provide additional textual status reason accompanying SettlStatusReason(2969).
EncodedSettlStatusReasonTextLen	[0..1]	Length	Must be set if EncodedSettlStatusReasonText(2972) is specified and must immediately precede it.
EncodedSettlStatusReasonText	[0..1]	data	Encoded (non-ASCII characters) representation of SettlStatusReasonText(2970) field in the encoded format specified via the MessageEncoding(347) field.
Parties	[0..*]	Group	
RegulatoryTradeIDGrp	[0..*]	Group	May be used to specify the UTI (ISO 23897) of the trade this status report is for. Either RegulatoryTradeIDGrp or SettleTradeDetails must be present.
SettleTradeDetails	[0..1]	Component	May be used to provide trade details this status report is for. Either RegulatoryTradeIDGrp or SettleTradeDetails must be present.

Name	Mult.	Type	Description
TransactTime	[1..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 151 SettlementStatusReportAck

Category: SettlementStatusManagement

### 151.1 Message Functionality

SettlementStatusReportAck(35=EF) is used to respond to the SettlementStatusReport(35=EE) to acknowledge or reject the report.

### 151.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType(35)=EF
SettlStatusReportID	[1..1]	String	Identifier of SettlementStatusReport(35=EE) message being responded to.
SettlStatusReportStatus	[1..1]	CodeSet	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[0..1]	Component	

## 152 SettlementStatusRequest

Category: SettlementStatusManagement

### 152.1 Message Functionality

SettlementStatusRequest(35=EC) is used to request for the settlement status of a trade.

### 152.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType(35)=EC
SettlStatusRequestID	[1..1]	String	Unique identifier assigned by sender of this message.
SubscriptionRequestType	[1..1]	CodeSet	
Parties	[0..*]	Group	
RegulatoryTradeIDGrp	[0..*]	Group	May be used to specify the UTI (ISO 23897) of the trade this status request is for. Either RegulatoryTradeIDGrp or SettlTradeDetails must be present.
SettlTradeDetails	[0..1]	Component	May be used to provide trade details to look-up the trade this status request is for. Either RegulatoryTradeIDGrp or SettlTradeDetails must be present.
TransactTime	[1..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 153 SettlementStatusRequestAck

Category: SettlementStatusManagement

### 153.1 Message Functionality

SettlementStatusRequestAck(35=ED) is used to respond to the SettlementStatusRequest(35=EC) to acknowledge the request and provide status for the request message.

### 153.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType(35)=ED
SettlStatusRequestID	[1..1]	String	Identifier of SettlementStatusRequest(35=EC) message being responded to.
SettlStatusRequestStatus	[1..1]	CodeSet	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	



## 154 StreamAssignmentReport

Category: MarketData

### 154.1 Message Functionality

The StreamAssignmentReport(35=CD) message is in response to the StreamAssignmentRequest(35=CC) message. It provides information back to the aggregator as to which clients to assign to receive which price stream based on requested CCY pair. This message can be sent unsolicited to the Aggregator from the Price Maker.

### 154.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CD
StreamAsgnRptID	[1..1]	String	Unique identifier of the Stream Assignment Report.
StreamAsgnReqType	[0..1]	CodeSet	Required if report is being sent in response to a StreamAssignmentRequest. The value should be the same as the value in the corresponding request.
StreamAsgnReqID	[0..1]	String	Conditionally required if Stream Assignment Report is being sent in response to a StreamAssignmentRequest(MsgType=CC). Not required for unsolicited stream assignments.
StrmAsgnRptGrp	[0..*]	Group	Stream assignments
StandardTrailer	[1..1]	Component	

## 155 StreamAssignmentReportACK

Category: MarketData

### 155.1 Message Functionality

This message is used to respond to the Stream Assignment Report, to either accept or reject an unsolicited assignment.

### 155.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CE
StreamAsgnAckType	[1..1]	CodeSet	
StreamAsgnRptID	[1..1]	String	
StreamAsgnRejReason	[0..1]	CodeSet	
Text	[0..1]	String	Can be used to provide additional information regarding the assignment report, such as reject description.
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	

## 156 StreamAssignmentRequest

Category: MarketData

### 156.1 Message Functionality

In certain markets where market data aggregators fan out to end clients the pricing streams provided by the price makers, the price maker may assign the clients to certain pricing streams that the price maker publishes via the aggregator. An example of this use is in the FX markets where clients may be assigned to different pricing streams based on volume bands and currency pairs.

### 156.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CC
StreamAsgnReqID	[1..1]	String	Unique identifier of the request.
StreamAsgnReqType	[1..1]	CodeSet	Type of assignment being requested.
StrmAsgnReqGrp	[1..*]	Group	Assignment requests
StandardTrailer	[1..1]	Component	

## 157 TestActionReport

Category: Testing

### 157.1 Message Functionality

TestActionReport(35=EP) is used to report the testing results of the identified test suite that has been executed with TestActionRequest(35=EN). In the context of algorithmic trading, the results may be used to create a certificate for the algorithm upon meeting the success criteria.

### 157.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EP
TestActionReportID	[1..1]	String	Identifier of report assigned by report initiator.
TestSuiteRequestID	[1..1]	String	Use to identify the test suite.
StrategyParametersGrp	[0..*]	Group	
AlgoSystemModuleGrp	[0..*]	Group	
TestScenarioGrp	[0..*]	Group	Must contain all scenarios of the test suite identified by TestSuiteRequestID(3062). Set TestScenarioStatus(3030) to 0=Undefined for test scenarios that have not been executed yet, e.g. because the TestActionRequest(35=EN) message used the TestScenarioGrp to limit the test scenarios to be executed.
TestSuiteStatus	[0..1]	CodeSet	Overall status across all individual test scenarios defined in TestScenarioGrp.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 158 TestActionRequest

Category: Testing

### 158.1 Message Functionality

TestActionRequest(35=EN) is used to manage test executions or request for testing activity state of the identified test suite.

### 158.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EN
TestActionRequestID	[1..1]	String	Unique identifier assigned by request initiator.
TestActionType	[1..1]	CodeSet	
TestSuiteRequestID	[1..1]	String	Use to identify the test suite the TestActionType(3067) applies to.
Parties	[0..*]	Group	May be used to specify the algorithm related to the test suite.
TestScenarioGrp	[0..*]	Group	May be used to provide a list of references to test scenarios of the test suite identified by TestSuiteRequestID(3062) to be executed, using TestScenarioID(3029) with TestScenarioStatus(3030)=0 (Undefined).
TransactTime	[1..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 159 TestActionRequestAck

Category: Testing

### 159.1 Message Functionality

TestActionRequestAck(35=EO) is used to respond to the TestActionRequest(35=EN) to acknowledge the request and provide status for the request message.

### 159.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EO
TestActionRequestID	[1..1]	String	Identifier of request assigned by request initiator.
TestSuiteRequestID	[1..1]	String	
TestSuiteActivityState	[1..1]	CodeSet	
TestActionRequestStatus	[1..1]	CodeSet	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 160 TestRequest

Category: Session

### 160.1 Message Functionality

The test request message forces a heartbeat from the opposing application. The test request message checks sequence numbers or verifies communication line status. The opposite application responds to the Test Request with a Heartbeat containing the TestReqID.

### 160.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = 1
TestReqID	[1..1]	String	
StandardTrailer	[1..1]	Component	

## 161 TestSuiteDefinitionRequest

Category: Testing

### 161.1 Message Functionality

TestSuiteDefinitionRequest(35=EL) is used to convey to the test system the suite of test scenarios to perform.

### 161.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EL
TestSuiteRequestID	[1..1]	String	Unique identifier assigned by request initiator.
TestSuiteRequestTransType	[1..1]	CodeSet	
TestSuiteRequestRefID	[0..1]	String	Required for TestSuiteRequestTransType(3064)=1 (Cancel).
Parties	[0..*]	Group	May be used to specify the algorithm related to the test schedule.
StrategyParametersGrp	[0..*]	Group	
AlgoSystemModuleGrp	[0..*]	Group	May be used with test suites related to the testing of algorithms.
TestScenarioGroupID	[0..1]	String	May be used to define a shortcut for TestScenarioGrp. The shortcut always references all test scenarios of the test suite. It must not be used to define shortcuts for a subset of test scenarios of a test suite.
TestScenarioGrp	[1..*]	Group	
TransactTime	[1..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	



## 162 TestSuiteDefinitionRequestAck

Category: Testing

### 162.1 Message Functionality

TestSuiteDefinitionRequestAck(35=EM) is used to respond to the TestSuiteDefinitionRequest(35= EL) to acknowledge the request and provide status for the request message.

### 162.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=EM
TestSuiteRequestID	[1..1]	String	Identifier of request assigned by request initiator.
TestSuiteRequestStatus	[1..1]	CodeSet	
TestGatewayDetailGrp	[0..*]	Group	May be used to return information about market data and order entry gateways for execution venues.
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 163 TradeAggregationReport

Category: TradeManagement

### 163.1 Message Functionality

TradeAggregationReport(35=DX) is used to respond to the TradeAggregationRequest(35=DW) message. It provides the status of the request (e.g. accepted or rejected) and may also provide additional information supplied by the respondent.

### 163.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DX
TradeAggregationReportID	[1..1]	String	Unique identifier for the report message.
TradeAggregationRequestID	[0..1]	String	Unique identifier for the TradeAggregationRequest(35=DW) message being responded to.
TradeAggregationRequestStatus	[1..1]	CodeSet	
TradeID	[0..1]	String	Conditionally required when TradeAggregationRequestStatus(2790)=0 (Accepted). The trade identifier for the group of aggregated trades.
TradeAggregationRejectReason	[0..1]	CodeSet	
AggregatedQty	[0..1]	Qty	Conditionally required when TradeAggregationRequestStatus(2790)=0 (Accepted).
AvgPx	[0..1]	Price	
AvgSpotRate	[0..1]	Price	
AvgForwardPoints	[0..1]	PriceOffset	
SettlDate	[0..1]	LocalMktDate	
Instrument	[0..1]	Component	Conditionally required when TradeAggregationRequestStatus(2790)=0 (Accepted).
Side	[0..1]	CodeSet	Conditionally required when TradeAggregationRequestStatus(2790)=0 (Accepted).
RejectText	[0..1]	String	

Name	Mult.	Type	Description
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
StandardTrailer	[1..1]	Component	

## 164 TradeAggregationRequest

Category: TradeManagement

### 164.1 Message Functionality

TradeAggregationRequest(35=DW) is used to request that the identified trades between the initiator and respondent be aggregated together for further processing.

### 164.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DW
TradeAggregationRequestID	[1..1]	String	Unique identifier for the message.
TradeAggregationRequestRefID	[0..1]	String	Required when TradeAggregationTransType(2788)=1 (Cancel) or 2 (Replace)
TradeAggregationTransType	[1..1]	CodeSet	
AggregatedQty	[0..1]	Qty	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
AvgPx	[0..1]	Price	
Side	[1..1]	CodeSet	
PricePrecision	[0..1]	int	
OrderAggregationGrp	[0..*]	Group	Maybe used to specify the IDs of the orders being aggregated together.
ExecutionAggregationGrp	[0..*]	Group	Maybe used to specify the IDs of the execution fills being aggregated together.
Account	[0..1]	String	
Instrument	[1..1]	Component	
Parties	[0..*]	Group	
StandardTrailer	[1..1]	Component	

## 165 TradeCaptureReport

Category: TradeCapture

### 165.1 Message Functionality

The Trade Capture Report message can be:

- Used to report trades between counterparties.
- Used to report trades to a trade matching system.
- Sent unsolicited between counterparties.
- Sent as a reply to a Trade Capture Report Request.
- Used to report unmatched and matched trades.

### 165.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AE
ApplicationSequenceControl	[0..1]	Component	
TradeReportID	[0..1]	String	TradeReportID(571) is conditionally required in a message-chaining model in which a subsequent message may refer to a prior message via TradeReportRefID(572). The alternative to a message-chain model is an entity-based model in which TradeID(1003) is used to identify a trade. In this case, TradeID(1003) is required and TradeReportID(571) can be optionally specified.
TradeID	[0..1]	String	
SecondaryTradeID	[0..1]	String	
FirmTradeID	[0..1]	String	
SecondaryFirmTradeID	[0..1]	String	
PackageID	[0..1]	String	
TradeNumber	[0..1]	int	
TradeReportTransType	[0..1]	CodeSet	
TradeReportType	[0..1]	CodeSet	

Name	Mult.	Type	Description
TrdRptStatus	[0..1]	CodeSet	Status of the trade report. In 3-party listed derivatives model, this is used to convey status of a trade to a counterparty. Used specifically in a "give-up" (also known as "claim") model.
TradeRequestID	[0..1]	String	Identifier for the trade capture report request associated with this trade capture report.
TrdType	[0..1]	CodeSet	For optional use in reporting trades.
TrdSubType	[0..1]	CodeSet	For optional use in reporting trades.
SecondaryTrdType	[0..1]	CodeSet	For optional use in reporting trades. Conditionally requires presence of TrdType(828).
TertiaryTrdType	[0..1]	CodeSet	For optional use in reporting trades. Conditionally requires presence of SecondaryTrdType(855).
TradeTypeGrp	[0..*]	Group	For optional use in reporting trades as alternative to the use of individual fields.
AnonymousTradeIndicator	[0..1]	Boolean	
AlgorithmicTradeIndicator	[0..1]	CodeSet	
OffsetInstruction	[0..1]	CodeSet	
TradePriceConditionGrp	[0..*]	Group	
TradeHandlingInstr	[0..1]	CodeSet	
OrigTradeHandlingInstr	[0..1]	CodeSet	
OrigTradeDate	[0..1]	LocalMktDate	
OrigTradeID	[0..1]	String	
OrigSecondaryTradeID	[0..1]	String	
TransferReason	[0..1]	String	
ExecType	[0..1]	CodeSet	Type of execution being reported. Uses subset of ExecType(150) for trade capture reports.
TotNumTradeReports	[0..1]	int	
LastRptRequested	[0..1]	CodeSet	
ManualOrderIndicator	[0..1]	Boolean	May be used to indicate manual reporting of the trade.
UnsolicitedIndicator	[0..1]	CodeSet	Set to 'Y' if message is sent as a result of a subscription request or out of band configuration.
SubscriptionRequestType	[0..1]	CodeSet	If the field is absent, SubscriptionRequestType(263)=0(Snapshot) will be the default.
TradeReportRefID	[0..1]	String	The TradeReportID(571) that is being referenced for trade correction or cancelation.

Name	Mult.	Type	Description
SecondaryTradeReportRefID	[0..1]	String	
SecondaryTradeReportID	[0..1]	String	
TradeLinkID	[0..1]	String	
TrdMatchID	[0..1]	String	
ExecID	[0..1]	String	Market (exchange) assigned execution identifier as provided in the ExecutionReport(35=8) message. Conditionally required if ExecRefID(19) is present and refers to the new execution identifier assigned by the market (exchange).
ExecRefID	[0..1]	String	Reference to an execution identifier previously assigned by the market (exchange). If specified, ExecID(17) is required.
SecondaryExecID	[0..1]	String	
ExecRestatementReason	[0..1]	CodeSet	
RegulatoryTransactionType	[0..1]	CodeSet	
RegulatoryTradeIDGrp	[0..*]	Group	
PreviouslyReported	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	Can be used to indicate cabinet trade pricing.
PriceQualifierGrp	[0..*]	Group	
CrossType	[0..1]	CodeSet	
RootParties	[0..*]	Group	Used for acting parties that applies to the whole message, not individual legs, sides, etc.
AsOfIndicator	[0..1]	CodeSet	
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
VenueType	[0..1]	CodeSet	
MarketSegmentID	[0..1]	String	
MarketID	[0..1]	Exchange	
TaxonomyType	[0..1]	CodeSet	
Instrument	[1..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
PaymentGrp	[0..*]	Group	
QtyType	[0..1]	CodeSet	
YieldData	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	

Name	Mult.	Type	Description
RelatedInstrumentGrp	[0..*]	Group	
CollateralAmountGrp	[0..*]	Group	
CollateralizationValueDate	[0..1]	LocalMktDate	
RateSource	[0..*]	Group	
TransactionAttributeGrp	[0..*]	Group	
UnderlyingTradingSessionID	[0..1]	String	
UnderlyingTradingSessionSubID	[0..1]	String	
LastQty	[0..1]	Qty	Conditionally required except when reporting trades to parties who will derive trade level quantity from the leg level information for multi-legged trades
LastQtyVariance	[0..1]	Qty	
LastQtyChanged	[0..1]	Qty	
LastMultipliedQty	[0..1]	Qty	
TotalTradeQty	[0..1]	Qty	
TotalTradeMultipliedQty	[0..1]	Qty	
LastPx	[0..1]	Price	Conditionally required except when reporting trades to parties who will derive trade level price from the leg level information for multi-legged trades
MidPx	[0..1]	Price	
DifferentialPrice	[0..1]	PriceOffset	Used to specify the differential price when reporting the individual leg of a spread trade.
CalculatedCcyLastQty	[0..1]	Qty	
PriceMarkup	[0..1]	PriceOffset	Dealer's markup of market price to LastPx(31).
AveragePriceDetail	[0..1]	Component	
Currency	[0..1]	Currency	Primary currency of the specified currency pair. Used to qualify LastQty(32) and GrossTradeAmt(381).
CurrencyCodeSource	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	Contra currency of the deal. Used to qualify CalculatedCcyLastQty(1056).
SettlCurrencyCodeSource	[0..1]	CodeSet	
SettlPriceFxRateCalc	[0..1]	CodeSet	For FX trades expresses whether to multiply or divide LastPx(31) to arrive at GrossTradeAmt(381).
LastParPx	[0..1]	Price	
LastSpotRate	[0..1]	Price	Applicable for F/X orders



Name	Mult.	Type	Description
LastForwardPoints	[0..1]	PriceOffset	Applicable for F/X orders
LastSwapPoints	[0..1]	PriceOffset	
PricePrecision	[0..1]	int	
LastMkt	[0..1]	Exchange	
ClearingTradePrice	[0..1]	Price	Used when clearing price differs from execution price.
TradePriceNegotiationMethod	[0..1]	CodeSet	
LastUpfrontPrice	[0..1]	Price	Upfront Price for CDS transactions. Conditionally required if TradePriceNegotiationMethod(1740) = 4(Percent of par and upfront amount), 5(Deal spread and upfront amount) or 6(Upfront points and upfront amount).
UpfrontPriceType	[0..1]	CodeSet	
TradeDate	[0..1]	LocalMktDate	Used when reporting other than current day trades.
ClearingBusinessDate	[0..1]	LocalMktDate	
ClearingPortfolioID	[0..1]	String	
AvgPx	[0..1]	Price	If used then the LastPx(31) will contain the original price on the execution.
SpreadOrBenchmarkCurveData	[0..1]	Component	
AvgPxGroupID	[0..1]	String	
AvgPxIndicator	[0..1]	CodeSet	
ValuationDate	[0..1]	LocalMktDate	
ValuationTime	[0..1]	LocalMktTime	
ValuationBusinessCenter	[0..1]	String	
PositionAmountData	[0..*]	Group	
MultiLegReportingType	[0..1]	CodeSet	Type of report if multileg instrument. Provided to support a scenario for trades of multileg instruments between two parties.
TradeLegRefID	[0..1]	String	Reference to the leg of a multileg instrument to which this trade refers. Used when MultiLegReportingType(442) = 2 (Individual leg of a multileg security).
TrdInstrmtLegGrp	[0..*]	Group	Identifies a multileg execution if present and non-zero.

Name	Mult.	Type	Description
TransactTime	[0..1]	UTCTimestamp	Time the transaction represented by when this TradeCaptureReport(35=AE) occurred. Execution time of trade. Also describes the time of block trades.
TrdRegTimestamps	[0..*]	Group	
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType(63) value and conditionally required/omitted for specific SettlType(63) values.
TerminationDate	[0..1]	LocalMktDate	
UnderlyingSettlementDate	[0..1]	LocalMktDate	The settlement date for the underlying instrument of a derivatives security.
MatchStatus	[0..1]	CodeSet	
ExecMethod	[0..1]	CodeSet	
MatchType	[0..1]	CodeSet	
TradeQtyGrp	[0..*]	Group	
TrdCapRptSideGrp	[1..*]	Group	
Volatility	[0..1]	float	
TimeToExpiration	[0..1]	float	
DividendYield	[0..1]	Percentage	
RiskFreeRate	[0..1]	float	
PriceDelta	[0..1]	float	
CurrencyRatio	[0..1]	float	
CopyMsgIndicator	[0..1]	Boolean	
TrdRepIndicatorsGrp	[0..*]	Group	
TradeReportingIndicator	[0..1]	CodeSet	
PublishTrdIndicator	[0..1]	CodeSet	
TradePublishIndicator	[0..1]	CodeSet	
TrdRegPublicationGrp	[0..*]	Group	
ShortSaleReason	[0..1]	CodeSet	
TierCode	[0..1]	String	Indicates the algorithm (tier) used to match a trade.
MessageEventSource	[0..1]	String	
LastUpdateTime	[0..1]	UTCTimestamp	Used to indicate reports after a specific time.
RndPx	[0..1]	Price	Specifies the rounded price to quoted precision.
TZTransactTime	[0..1]	TZTimestamp	

Name	Mult.	Type	Description
ReportedPxDiff	[0..1]	Boolean	
GrossTradeAmt	[0..1]	Amt	(LastQty(32) * LastPx(31) or LastParPx(669)). For Fixed Income, LastParPx(669) is used when LastPx(31) is not expressed as "percent of par" price.
TotalGrossTradeAmt	[0..1]	Amt	
TradeReportRejectReason	[0..1]	CodeSet	Indicates the reason that a trade report was rejected.
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
FeeMultiplier	[0..1]	float	
ClearedIndicator	[0..1]	CodeSet	
ClearingIntention	[0..1]	CodeSet	
TradeClearingInstruction	[0..1]	CodeSet	
BackloadedTradeIndicator	[0..1]	Boolean	
ConfirmationMethod	[0..1]	CodeSet	
MandatoryClearingIndicator	[0..1]	Boolean	
MandatoryClearingJurisdictionGrp	[0..*]	Group	
MixedSwapIndicator	[0..1]	Boolean	
MultiAssetSwapIndicator	[0..1]	Boolean	
InternationalSwapIndicator	[0..1]	Boolean	
OffMarketPriceIndicator	[0..1]	Boolean	
VerificationMethod	[0..1]	CodeSet	
ClearingRequirementException	[0..1]	CodeSet	
IRSDirection	[0..1]	CodeSet	
RegulatoryReportType	[0..1]	CodeSet	
RegulatoryReportTypeBusinessDate	[0..1]	LocalMktDate	May be used when the business event date differs from when the regulatory report is actually being submitted (typically specified in TrdRegTimestamps component).
VoluntaryRegulatoryReport	[0..1]	Boolean	
MultiJurisdictionReportingIndicator	[0..1]	CodeSet	
TradeCollateralization	[0..1]	CodeSet	
TradeContinuation	[0..1]	CodeSet	
TradeContingency	[0..1]	CodeSet	

Name	Mult.	Type	Description
TradeVersion	[0..1]	String	
HistoricalReportIndicator	[0..1]	Boolean	
DeltaCrossed	[0..1]	Boolean	
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
IntraFirmTradeIndicator	[0..1]	Boolean	
AffiliatedFirmsTradeIndicator	[0..1]	Boolean	
AttachmentGrp	[0..*]	Group	
RiskLimitCheckStatus	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 166 TradeCaptureReportAck

Category: TradeCapture

### 166.1 Message Functionality

The Trade Capture Report Ack message can be:

- Used to acknowledge trade capture reports received from a counterparty.
- Used to reject a trade capture report received from a counterparty.

### 166.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AR
TradeReportID	[0..1]	String	
TradeID	[0..1]	String	
SecondaryTradeID	[0..1]	String	
FirmTradeID	[0..1]	String	
SecondaryFirmTradeID	[0..1]	String	
TradeReportTransType	[0..1]	CodeSet	
TradeReportType	[0..1]	CodeSet	Indicates action to take on trade.
TrdType	[0..1]	CodeSet	
TrdSubType	[0..1]	CodeSet	
SecondaryTrdType	[0..1]	CodeSet	
OffsetInstruction	[0..1]	CodeSet	
TradeHandlingInstr	[0..1]	CodeSet	
OrigTradeHandlingInstr	[0..1]	CodeSet	
OrigTradeDate	[0..1]	LocalMktDate	
OrigTradeID	[0..1]	String	
OrigSecondaryTradeID	[0..1]	String	
TransferReason	[0..1]	String	
RootParties	[0..*]	Group	
ExecType	[0..1]	CodeSet	Type of execution being reported. Uses subset of ExecType(150) for trade capture reports.

Name	Mult.	Type	Description
TradeReportRefID	[0..1]	String	The TradeReportID(571) that is being referenced for trade correction or cancellation.
SecondaryTradeReportRefID	[0..1]	String	The SecondaryTradeReportID that is being referenced for some action, such as correction or cancellation
TrdRptStatus	[0..1]	CodeSet	Status of trade report.
TrdAckStatus	[0..1]	CodeSet	
TradeReportRejectReason	[0..1]	CodeSet	
RejectText	[0..1]	String	Reason description for rejecting the TradeCaptureReport(35=AE).
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
SecondaryTradeReportID	[0..1]	String	
SubscriptionRequestType	[0..1]	CodeSet	If the field is absent, SubscriptionRequestType(263)=0(Snapshot) will be the default.
TradeLinkID	[0..1]	String	
TrdMatchID	[0..1]	String	
ExecID	[0..1]	String	Exchanged assigned execution identifier (trade identifier).
SecondaryExecID	[0..1]	String	
ExecRestatementReason	[0..1]	CodeSet	
PreviouslyReported	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
CrossType	[0..1]	CodeSet	
UnderlyingTradingSessionID	[0..1]	String	
UnderlyingTradingSessionSubID	[0..1]	String	
SettlSessID	[0..1]	CodeSet	
SettlSessSubID	[0..1]	String	
QtyType	[0..1]	CodeSet	
LastQty	[0..1]	Qty	
LastPx	[0..1]	Price	
VenueType	[0..1]	CodeSet	

Name	Mult.	Type	Description
MarketSegmentID	[0..1]	String	
MarketID	[0..1]	Exchange	
Instrument	[1..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
LastParPx	[0..1]	Price	
CalculatedCcyLastQty	[0..1]	Qty	
LastSwapPoints	[0..1]	PriceOffset	
PriceMarkup	[0..1]	PriceOffset	Dealer's markup of market price to LastPx(31).
AveragePriceDetail	[0..1]	Component	
Currency	[0..1]	Currency	Primary currency of the specified currency pair. Used to qualify LastQty(32) and GrossTradeAmt(381).
CurrencyCodeSource	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	Contra currency of the deal. Used to qualify CalculatedCcyLastQty(1056).
SettlCurrencyCodeSource	[0..1]	CodeSet	
LastSpotRate	[0..1]	Price	
LastForwardPoints	[0..1]	PriceOffset	
LastMkt	[0..1]	Exchange	
TradeDate	[0..1]	LocalMktDate	
ClearingBusinessDate	[0..1]	LocalMktDate	
AvgPx	[0..1]	Price	
AvgPxGroupID	[0..1]	String	
AvgPxIndicator	[0..1]	CodeSet	
MultiLegReportingType	[0..1]	CodeSet	
TradeLegRefID	[0..1]	String	
TransactTime	[0..1]	UTCTimestamp	Time this message was issued by matching system, trading system or counterparty.
SettlType	[0..1]	CodeSet	
UndInstrmtGrp	[0..*]	Group	
MatchStatus	[0..1]	CodeSet	
MatchType	[0..1]	CodeSet	
CopyMsgIndicator	[0..1]	Boolean	
TrdRepIndicatorsGrp	[0..*]	Group	

Name	Mult.	Type	Description
PublishTrdIndicator	[0..1]	CodeSet	
TradePublishIndicator	[0..1]	CodeSet	
ShortSaleReason	[0..1]	CodeSet	
TrdInstrmtLegGrp	[0..*]	Group	
TrdRegTimestamps	[0..*]	Group	
ResponseTransportType	[0..1]	CodeSet	
ResponseDestination	[0..1]	String	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	
AsOfIndicator	[0..1]	CodeSet	
ClearingFeeIndicator	[0..1]	CodeSet	
PositionAmountData	[0..*]	Group	
TierCode	[0..1]	String	Indicates the algorithm (tier) used to match a trade.
MessageEventSource	[0..1]	String	
LastUpdateTime	[0..1]	UTCTimestamp	Used to indicate reports after a specific time.
RndPx	[0..1]	Price	Specifies the rounded price to quoted precision.
TradeQtyGrp	[0..*]	Group	
TrdCapRptAckSideGrp	[0..*]	Group	
RptSys	[0..1]	String	
GrossTradeAmt	[0..1]	Amt	(LastQty(32) * LastPx(31) or LastParPx(669)). For Fixed Income, LastParPx(669) is used when LastPx(31) is not expressed as "percent of par" price.
SettlDate	[0..1]	LocalMktDate	
FeeMultiplier	[0..1]	float	
RiskLimitCheckStatus	[0..1]	CodeSet	
StandardTrailer	[1..1]	Component	



## 167 TradeCaptureReportRequest

Category: TradeCapture

### 167.1 Message Functionality

The Trade Capture Report Request can be used to:

- Request one or more trade capture reports based upon selection criteria provided on the trade capture report request
- Subscribe for trade capture reports based upon selection criteria provided on the trade capture report request.

### 167.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AD
TradeRequestID	[1..1]	String	Unique identifier for the trade request.
TradeID	[0..1]	String	
SecondaryTradeID	[0..1]	String	
FirmTradeID	[0..1]	String	
SecondaryFirmTradeID	[0..1]	String	
TradeRequestType	[1..1]	CodeSet	
SubscriptionRequestType	[0..1]	CodeSet	If the field is absent, SubscriptionRequestType(263)=0(Snapshot) will be the default.
TradeReportID	[0..1]	String	Can be used to request a specific trade report.
SecondaryTradeReportID	[0..1]	String	To request a specific trade report
SecondaryExecID	[0..1]	String	To request all trades based on secondary execution identifier
ExecID	[0..1]	String	
ExecType	[0..1]	CodeSet	Can be used to request all trades of a specific execution type.
OrderID	[0..1]	String	
ClOrdID	[0..1]	String	
MatchStatus	[0..1]	CodeSet	

Name	Mult.	Type	Description
TrdType	[0..1]	CodeSet	Can be used to request all trades of a specific trade type.
TrdSubType	[0..1]	CodeSet	Can be used to request all trades of a specific trade sub type.
OffsetInstruction	[0..1]	CodeSet	
TradeHandlingInstr	[0..1]	CodeSet	
TransferReason	[0..1]	String	Can be used to request all trades for a specific transfer reason.
SecondaryTrdType	[0..1]	CodeSet	Can be used to request all trades of a specific secondary trade type.
TradeLinkID	[0..1]	String	Can be used to request all trades of a specific trade link identifier.
TrdMatchID	[0..1]	String	Can be used to request a trade matching a specific TrdMatchID(880).
Parties	[0..*]	Group	Used to specify the parties for the trades to be returned (clearing firm, execution broker, trader id, etc.). ExecutingBroker. ClearingFirm. ContraBroker. ContraClearingFirm. SettlementLocation - depository, CSD, or other settlement party. ExecutingTrader. InitiatingTrader. OrderOriginator
Instrument	[0..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
TrdCapDtGrp	[0..*]	Group	Number of date ranges provided (must be 1 or 2 if specified)
ClearingBusinessDate	[0..1]	LocalMktDate	Can be used to request trades for a specific clearing business date.
TradingSessionID	[0..1]	CodeSet	Can be used to request trades for a specific trading session.
TradingSessionSubID	[0..1]	CodeSet	Can be used to request trades for a specific trading session.
TimeBracket	[0..1]	String	Can be used to request trades within a specific time bracket.
Side	[0..1]	CodeSet	Can be used to request trades for a specific side of a trade.

Name	Mult.	Type	Description
MultiLegReportingType	[0..1]	CodeSet	Used to indicate if trades are to be returned for the individual legs of a multileg instrument or for the overall instrument.
TradeInputSource	[0..1]	String	Can be used to requests trades that were submitted from a specific trade input source.
TradeInputDevice	[0..1]	String	Can be used to request trades that were submitted from a specific trade input device.
ResponseTransportType	[0..1]	CodeSet	
ResponseDestination	[0..1]	String	
Text	[0..1]	String	Used to match specific values within Text(58) fields.
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
MessageEventSource	[0..1]	String	
StandardTrailer	[1..1]	Component	

## 168 TradeCaptureReportRequestAck

Category: TradeCapture

### 168.1 Message Functionality

The Trade Capture Request Ack message is used to:

- Provide an acknowledgement to a Trade Capture Report Request in the case where the Trade Capture Report Request is used to specify a subscription or delivery of reports via an out-of-band ResponseTransmissionMethod.
- Provide an acknowledgement to a Trade Capture Report Request in the case when the return of the Trade Capture Reports matching that request will be delayed or delivered asynchronously. This is useful in distributed trading system environments.
- Indicate that no trades were found that matched the selection criteria specified on the Trade Capture Report Request or the Trade Capture Request was invalid for some business reason, such as request is not authorized, invalid or unknown instrument, party, trading session, etc.

### 168.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = AQ
TradeRequestID	[1..1]	String	Identifier for the trade request
TradeID	[0..1]	String	
SecondaryTradeID	[0..1]	String	
FirmTradeID	[0..1]	String	
SecondaryFirmTradeID	[0..1]	String	
TradeRequestType	[1..1]	CodeSet	
SubscriptionRequestType	[0..1]	CodeSet	Used to subscribe / unsubscribe for trade capture reports. If the field is absent, the value 0 will be the default
TotNumTradeReports	[0..1]	int	Number of trade reports returned
TradeRequestResult	[1..1]	CodeSet	Result of Trade Request
TradeRequestStatus	[1..1]	CodeSet	Status of Trade Request

Name	Mult.	Type	Description
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
InstrumentExtension	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	Number of legs. NoLegs > 0 identifies a Multi-leg Execution
MultiLegReportingType	[0..1]	CodeSet	Specify type of multileg reporting to be returned.
ResponseTransportType	[0..1]	CodeSet	Ability to specify whether the response to the request should be delivered inband or via pre-arranged out-of-band transport.
ResponseDestination	[0..1]	String	URI destination name. Used if ResponseTransportType is out-of-band.
Text	[0..1]	String	May be used by the executing market to record any execution Details that are particular to that market
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
MessageEventSource	[0..1]	String	Used to identify the event or source which gave rise to a message
StandardTrailer	[1..1]	Component	

## 169 TradeMatchReport

Category: TradeCapture

### 169.1 Message Functionality

The TradeMatchReport(35=DC) message is used by exchanges and ECN's to report matched trades to central counterparties (CCPs) as an atomic event. The message is used to express the one-to-one, one-to-many and many-to-many matches as well as implied matches in which more complex instruments can match with simpler instruments.

### 169.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DC
ApplicationSequenceControl	[0..1]	Component	
TrdMatchID	[1..1]	String	Unique identifier common for all trades included in a match event.
MatchType	[0..1]	CodeSet	
TradeReportType	[0..1]	CodeSet	
ClearingBusinessDate	[0..1]	LocalMktDate	
TrdType	[0..1]	CodeSet	
TrdSubType	[0..1]	CodeSet	
TradeDate	[0..1]	LocalMktDate	Used when reporting other than current day trades.
MarketID	[0..1]	Exchange	
MarketSegmentID	[0..1]	String	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
VenueType	[0..1]	CodeSet	
TradeMatchTimestamp	[0..1]	UTCTimestamp	
TransactTime	[0..1]	UTCTimestamp	Time of the match event or transaction that resulted in this match report.

Name	Mult.	Type	Description
MultiLegReportingType	[0..1]	CodeSet	Differentiates match events involving complex instruments (MultiLegReportingType(442)=3(multileg security)) from those only involving simple instruments (MultiLegReportingType(442)=1(single security)). MultiLegReportingType(442)=2(individual leg of multileg security) should not be used.
InstrmtMatchSideGrp	[0..*]	Group	Conditionally required when TradeReportType(856) = Submit(0).
StandardTrailer	[1..1]	Component	

## 170 TradeMatchReportAck

Category: TradeCapture

### 170.1 Message Functionality

The TradeMatchReportAck(35=DD) is used to respond to the TradeMatchReport(35=DC) message. It may be used to report on the status of the request (e.g. accepting the request or rejecting the request).

### 170.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType=DD
ApplicationSequenceControl	[0..1]	Component	
TrdMatchID	[1..1]	String	Identifier of the TradeMatchReport(35=DC) being acknowledged.
TradeMatchAckStatus	[1..1]	CodeSet	
TradeMatchRejectReason	[0..1]	CodeSet	Conditionally required when TradeMatchAckStatus(1896) = Rejected(2).
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	
StandardTrailer	[1..1]	Component	



## 171 TradingSessionList

Category: MarketStructureReferenceData

### 171.1 Message Functionality

The Trading Session List message is sent as a response to a Trading Session List Request. The Trading Session List should contain the characteristics of the trading session and the current state of the trading session.

### 171.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BJ
ApplicationSequenceControl	[0..1]	Component	
TradSesReqID	[0..1]	String	Provided for a response to a specific Trading Session List Request message (snapshot).
TrdSessLstGrp	[1..*]	Group	
StandardTrailer	[1..1]	Component	

## 172 TradingSessionListRequest

Category: MarketStructureReferenceData

### 172.1 Message Functionality

The Trading Session List Request is used to request a list of trading sessions available in a market place and the state of those trading sessions. A successful request will result in a response from the counterparty of a Trading Session List (MsgType=BJ) message that contains a list of zero or more trading sessions.

### 172.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BI
TradSesReqID	[1..1]	String	Must be unique, or the ID of previous Trading Session List Request to disable if SubscriptionRequestType(263) = 2 (Disable previous Snapshot + Update Request).
MarketID	[0..1]	Exchange	Market for which Trading Session applies
MarketSegmentID	[0..1]	String	Market Segment for which Trading Session applies
TradingSessionID	[0..1]	CodeSet	Trading Session for which status is being requested
TradingSessionSubID	[0..1]	CodeSet	
SecurityExchange	[0..1]	Exchange	
TradSesMethod	[0..1]	CodeSet	Method of Trading
TradSesMode	[0..1]	CodeSet	Trading Session Mode
SubscriptionRequestType	[1..1]	CodeSet	
StandardTrailer	[1..1]	Component	

## 173 TradingSessionListUpdateReport

Category: MarketStructureReferenceData

### 173.1 Message Functionality

The Trading Session List Update Report is used by marketplaces to provide intra-day updates of trading sessions when there are changes to one or more trading sessions.

### 173.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = BS
ApplicationSequenceControl	[0..1]	Component	
TradSesReqID	[0..1]	String	Provided for a response to a specific Trading Session List Request message (snapshot).
TrdSessLstGrp	[1..*]	Group	
StandardTrailer	[1..1]	Component	

## 174 TradingSessionStatus

Category: MarketStructureReferenceData

### 174.1 Message Functionality

The Trading Session Status provides information on the status of a market. For markets multiple trading sessions on multiple-markets occurring (morning and evening sessions for instance), this message is able to provide information on what products are trading on what market during what trading session.

### 174.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = h (lowercase)
ApplicationSequenceControl	[0..1]	Component	
TradSesReqID	[0..1]	String	Conditionally required when responding to a specific TradingSessionStatusRequest(35=g)
MarketID	[0..1]	Exchange	Market for which trading session applies
MarketSegmentID	[0..1]	String	Market Segment for which trading session applies
TradeDate	[0..1]	LocalMktDate	Business day for which trading session applies to.
TradingSessionID	[1..1]	CodeSet	Identifier for trading session
TradingSessionSubID	[0..1]	CodeSet	
TradSesMethod	[0..1]	CodeSet	
TradSesMode	[0..1]	CodeSet	
UnsolicitedIndicator	[0..1]	CodeSet	Set to 'Y' if message is sent unsolicited as a result of a previous subscription request.
TradSesStatus	[1..1]	CodeSet	
TradSesEvent	[0..1]	CodeSet	Identifies an event related to the trading status of a trading session
FastMarketIndicator	[0..1]	Boolean	Indicates if trading session is in fast market.
TradSesStatusRejReason	[0..1]	CodeSet	Use with TradSesStatus(340) = 6(Request Rejected).
TradSesStartTime	[0..1]	UTCTimestamp	Starting time of the trading session
TradSesOpenTime	[0..1]	UTCTimestamp	Time of the opening of the trading session
TradSesPreCloseTime	[0..1]	UTCTimestamp	Time of the pre-close of the trading session

Name	Mult.	Type	Description
TradSesCloseTime	[0..1]	UTCTimestamp	Closing time of the trading session
TradSesEndTime	[0..1]	UTCTimestamp	End time of the trading session
TradSesControl	[0..1]	CodeSet	Indicates how control of trading session and subsession transitions are performed
TotalVolumeTraded	[0..1]	Qty	
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
Instrument	[0..1]	Component	Use if status information applies only to a subset of all instruments. Use SecurityStatus(35=f) message instead for status on a single instrument.
StandardTrailer	[1..1]	Component	

## 175 TradingSessionStatusRequest

Category: MarketStructureReferenceData

### 175.1 Message Functionality

The Trading Session Status Request is used to request information on the status of a market. With the move to multiple sessions occurring for a given trading party (morning and evening sessions for instance) there is a need to be able to provide information on what product is trading on what market.

### 175.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = g (lowercase)
TradSesReqID	[1..1]	String	Must be unique, or the ID of previous Trading Session Status Request to disable if SubscriptionRequestType = Disable previous Snapshot + Updates Request (2).
MarketID	[0..1]	Exchange	Market for which Trading Session applies
MarketSegmentID	[0..1]	String	Market Segment for which Trading Session applies
TradingSessionID	[0..1]	CodeSet	Trading Session for which status is being requested
TradingSessionSubID	[0..1]	CodeSet	
TradSesMethod	[0..1]	CodeSet	Method of trading
TradSesMode	[0..1]	CodeSet	Trading Session Mode
SubscriptionRequestType	[1..1]	CodeSet	
SecurityExchange	[0..1]	Exchange	
StandardTrailer	[1..1]	Component	

## 176 UserNotification

Category: UserManagement

### 176.1 Message Functionality

The User Notification message is used to notify one or more users of an event or information from the sender of the message. This message is usually sent unsolicited from a marketplace (e.g. Exchange, ECN) to a market participant.

### 176.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = CB
UsernameGrp	[0..*]	Group	List of users to which the notification is directed
UserStatus	[1..1]	CodeSet	Reason for notification - when possible provide an explanation.
ThrottleParamsGrp	[0..*]	Group	
Text	[0..1]	String	Explanation for user notification.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
StandardTrailer	[1..1]	Component	

## 177 UserRequest

Category: UserManagement

### 177.1 Message Functionality

This message is used to initiate a user action, logon, logout or password change. It can also be used to request a report on a user's status.

### 177.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = "BE"
UserRequestID	[1..1]	String	
UserRequestType	[1..1]	CodeSet	
Username	[1..1]	String	
Password	[0..1]	String	
NewPassword	[0..1]	String	
EncryptedPasswordMethod	[0..1]	int	
EncryptedPasswordLen	[0..1]	Length	
EncryptedPassword	[0..1]	data	
EncryptedNewPasswordLen	[0..1]	Length	
EncryptedNewPassword	[0..1]	data	
RawDataLength	[0..1]	Length	
RawData	[0..1]	data	Can be used to hand structures etc to other API's etc
StandardTrailer	[1..1]	Component	



## 178 UserResponse

Category: UserManagement

### 178.1 Message Functionality

This message is used to respond to a user request message, it reports the status of the user after the completion of any action requested in the user request message.

### 178.2 Structure

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	MsgType = "BF"
UserRequestID	[1..1]	String	
Username	[1..1]	String	
UserStatus	[0..1]	CodeSet	
ThrottleParamsGrp	[0..*]	Group	
UserStatusText	[0..1]	String	Reason a request was not carried out
StandardTrailer	[1..1]	Component	

## 179 XMLnonFIX

Category: Session

### 179.1 Message Functionality

### 179.2 Structure

---

Name	Mult.	Type	Description
StandardHeader	[1..1]	Component	
AttachmentGrp	[0..*]	Group	
StandardTrailer	[1..1]	Component	

---

## 180 Message Elements

### 180.1 Data Types

Data type	Base type	Description
Amt	float	float field typically representing a Price times a Qty
Boolean	char	char field containing one of two values: 'Y' = True/Yes. 'N' = False/No
char		Single character value, can include any alphanumeric character or punctuation except the delimiter. All char fields are case sensitive (i.e. m != M).
Country	String	string field representing a country using ISO 3166 Country code (2 character) values (see Appendix 6-B).
Currency	String	string field representing a currency type using ISO 4217 Currency code (3 character) values (see Appendix 6-A).
data		string field containing opaque or non-ASCII data with no format or content restrictions. Data fields are always immediately preceded by a length field. The length field should specify the number of bytes of the value of the data field (up to but not including the terminating SOH). The number of bytes does not equal the number of characters when multibyte character sets are used. Caution: The value of these fields may contain the delimiter (SOH) character. Note that the value specified for these fields must be followed by the delimiter (SOH) character as all tag-value fields are terminated with an SOH.
Exchange	String	string field representing a market or exchange using ISO 10383 Market Identifier Code (MIC) values (see Appendix 6-C).
float		Sequence of digits with optional decimal point and sign character (ASCII characters "-", "0" - "9" and "."); the absence of the decimal point within the string will be interpreted as the float representation of an integer value. All float fields must accommodate up to fifteen significant digits. The number of decimal places used should be a factor of business/market needs and mutual agreement between counterparties. Note that float values may contain leading zeros (e.g. "00023.23" = "23.23") and may contain or omit trailing zeros after the decimal point (e.g. "23.0" = "23.0000" = "23" = "23."). Note that fields which are derived from float may contain negative values unless explicitly specified otherwise.
int		Sequence of digits without commas or decimals and optional sign character (ASCII characters "-" and "0" - "9" ). The sign character utilizes one byte (i.e. positive int is "99999" while negative int is "-99999"). Note that int values may contain leading zeros (e.g. "00023" = "23").
Language	String	Identifier for a national language - uses ISO 639-1 standard
Length	int	int field representing the length in bytes. Value must be positive.

Data type	Base type	Description
LocalMktDate	String	string field representing a Date of Local Market (as opposed to UTC) in YYYYMMDD format. This is the "normal" date field used by the FIX Protocol. Valid values:. YYYY = 0000-9999, MM = 01-12, DD = 01-31
LocalMktTime	String	string field representing the time local to a particular market center. Used where offset to UTC varies throughout the year and the defining market center is identified in a corresponding field. Format is HH:MM:SS where HH = 00-23 hours, MM = 00-59 minutes, SS = 00-59 seconds. In general only the hour token is non-zero.
MonthYear	String	string field representing month of a year. An optional day of the month can be appended or an optional week code. Valid formats:. YYYYMM. YYYYMMDD. YYYYMMWW. Valid values:. YYYY = 0000-9999; MM = 01-12; DD = 01-31; WW = w1, w2, w3, w4, w5.
MultipleCharValue	String	string field containing one or more space delimited single character values (e.g.
MultipleStringValue	String	string field containing one or more space delimited multiple character values (e.g.
NumInGroup	int	int field representing the number of entries in a repeating group. Value must be positive.
Percentage	float	float field representing a percentage (e.g. 0.05 represents 5% and 0.9525 represents 95.25%). Note the number of decimal places may vary.
Price	float	float field representing a price. Note the number of decimal places may vary. For certain asset classes prices may be negative values. For example, prices for options strategies can be negative under certain market conditions. Refer to Volume 7: FIX Usage by Product for asset classes that support negative price values.
PriceOffset	float	float field representing a price offset, which can be mathematically added to a "Price". Note the number of decimal places may vary and some fields such as LastForwardPoints may be negative.
Qty	float	float field capable of storing either a whole number (no decimal places) of "shares" (securities denominated in whole units) or a decimal value containing decimal places for non-share quantity asset classes (securities denominated in fractional units).
SeqNum	int	int field representing a message sequence number. Value must be positive.
String		Alpha-numeric free format strings, can include any character or punctuation except the delimiter. All String fields are case sensitive (i.e. morstatt != Morstatt).
TagNum	int	int field representing a field's tag number when using FIX "Tag=Value" syntax. Value must be positive and may not contain leading zeros.

Data type	Base type	Description
TZTimeOnly	String	string field representing the time represented based on ISO 8601. This is the time with a UTC offset to allow identification of local time and timezone of that time. Format is HH:MM[:SS][Z]
TZTimestamp	String	string field representing a time/date combination representing local time with an offset to UTC to allow identification of local time and timezone offset of that time. The representation is based on ISO 8601. Format is YYYYMMDD-HH:MM:SS.sss*[Z]
UTCDateOnly	String	string field representing Date represented in UTC (Universal Time Coordinated, also known as "GMT") in YYYYMMDD format. This special-purpose field is paired with UTCTimeOnly to form a proper UTCTimestamp for bandwidth-sensitive messages. Valid values: YYYY = 0000-9999, MM = 01-12, DD = 01-31.
UTCTimeOnly	String	string field representing time-only represented in UTC (Universal Time Coordinated, also known as "GMT") in either HH:MM:SS (whole seconds) or HH:MM:SS.sss* (milliseconds) format, colons, and period required. This special-purpose field is paired with UTCDateOnly to form a proper UTCTimestamp for bandwidth-sensitive messages. Valid values: HH = 00-23, MM = 00-59, SS = 00-60 (60 only if UTC leap second), sss* fractions of seconds. The fractions of seconds may be empty when no fractions of seconds are conveyed (in such a case the period is not conveyed), it may include 3 digits to convey milliseconds, 6 digits to convey microseconds, 9 digits to convey nanoseconds, 12 digits to convey picoseconds; Other number of digits may be used with bilateral agreement.
UTCTimestamp	String	string field representing time/date combination represented in UTC (Universal Time Coordinated, also known as "GMT") in either YYYYMMDD-HH:MM:SS (whole seconds) or YYYYMMDD-HH:MM:SS.sss* format, colons, dash, and period required. Valid values: YYYY = 0000-9999, MM = 01-12, DD = 01-31, HH = 00-23, MM = 00-59, SS = 00-60 (60 only if UTC leap second), sss* fractions of seconds. The fractions of seconds may be empty when no fractions of seconds are conveyed (in such a case the period is not conveyed), it may include 3 digits to convey milliseconds, 6 digits to convey microseconds, 9 digits to convey nanoseconds, 12 digits to convey picoseconds; Other number of digits may be used with bilateral agreement. Leap Seconds: Note that UTC includes corrections for leap seconds, which are inserted to account for slowing of the rotation of the earth. Leap second insertion is declared by the International Earth Rotation Service (IERS) and has, since 1972, only occurred on the night of Dec. 31 or Jun 30. The IERS considers March 31 and September 30 as secondary dates for leap second insertion, but has never utilized these dates. During a leap second insertion, a UTCTimestamp field may read "19981231-23:59:59", "19981231-23:59:60", "19990101-00:00:00". (see <a href="http://tycho.usno.navy.mil/leapsec.html">http://tycho.usno.navy.mil/leapsec.html</a> )

Data type	Base type	Description
XID	String	The purpose of the XID datatype is to define a unique identifier that is global to a FIX message. An identifier defined using this datatype uniquely identifies its containing element, whatever its type and name is. The constraint added by this datatype is that the values of all the fields that have an XID datatype in a FIX message must be unique.
XIDREF	String	The XIDREF datatype defines a reference to an identifier defined by the XID datatype.
XMLData	String	Contains an XML document raw data with no format or content restrictions. XMLData fields are always immediately preceded by a length field. The length field should specify the number of bytes of the value of the data field (up to but not including the terminating SOH).

## 180.2 Data Dictionary

### 180.2.1 Account

Account mnemonic as agreed between buy and sell sides, e.g. broker and institution or investor/intermediary and fund manager.

Type: **String**

Used in groups: **BidCompReqGrp, ListOrdGrp, QuotReqGrp, QuotReqRjctGrp, SideCrossOrdModGrp, TrdCapRptAckSideGrp, TrdCapRptSideGrp**

Used in messages: **AssignmentReport, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralRequest, CollateralResponse, ExecutionReport, MassOrder, MassOrderAck, MassQuote, MassQuoteAck, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassStatusRequest, OrderStatusRequest, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, Quote, QuoteCancel, QuoteResponse, QuoteStatusReport, QuoteStatusRequest, RegistrationInstructions, RegistrationInstructionsResponse, RequestForPositions, RequestForPositionsAck, TradeAggregationRequest**

### 180.2.2 AccountSummaryReportID

Unique identifier for the AccountSummaryReport(35=CQ).

Type: **String**

Used in messages: **AccountSummaryReport**

### 180.2.3 AccountType

Type of account associated with an order

Type: **int**

Allowed values in AccountTypeCodeSet:

Code	Name	Description
1	CarriedCustomerSide	Account is carried on customer side of the books
2	CarriedNonCustomerSide	Account is carried on non-customer side of books
3	HouseTrader	House Trader
4	FloorTrader	Floor Trader
6	CarriedNonCustomerSideCross-Margined	Account is carried on non-customer side of books and is cross margined
7	HouseTraderCrossMargined	Account is house trader and is cross margined
8	JointBackOfficeAccount	Joint back office account (JBO)
9	EquitiesSpecialist	Equities specialist
10	OptionsMarketMaker	Options market maker
11	OptionsFirmAccount	Options firm account
12	AccountCustomerNonCustomerOrders	Account for customer and non-customer orders. Account aggregates orders from customers and non-customers. In the context of IROC UMIR this account type can be used for bundled orders (BU), i.e. orders including client, non-client and principal orders.
13	AccountOrdersMultipleCustomers	Account for orders from multiple customers. Account aggregates orders from multiple customers. In the context of IROC UMIR this account type can be used for multiple client orders (MC), i.e. orders including orders from more than one client but no principal or non-client orders.

Used in groups: **ListOrdGrp**, **QuotReqGrp**, **QuotReqRjctGrp**, **SideCrossOrdModGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AssignmentReport**, **CollateralAssignment**, **CollateralInquiry**, **CollateralInquiryAck**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**, **ExecutionReport**, **MassOrder**, **MassOrderAck**, **MassQuote**, **MassQuoteAck**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReject**, **OrderCancelReplaceRequest**, **OrderCancelRequest**, **PositionMaintenanceReport**, **PositionMaintenanceRequest**, **PositionReport**, **Quote**, **QuoteCancel**, **QuoteResponse**, **QuoteStatusReport**, **QuoteStatusRequest**, **RequestForPositions**, **RequestForPositionsAck**

**180.2.4 AccruedInterestAmt**

Amount of Accrued Interest for convertible bonds and fixed income

Type: **Amt**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **CollateralAssignment**, **CollateralInquiry**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**, **Confirmation**, **ExecutionReport**

**180.2.5 AccruedInterestRate**

The amount the buyer compensates the seller for the portion of the next coupon interest payment the seller has earned but will not receive from the issuer because the issuer will send the next coupon payment to the buyer. Accrued Interest Rate is the annualized Accrued Interest amount divided by the purchase price of the bond.

Type: **Percentage**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **Confirmation**, **ExecutionReport**

**180.2.6 AcctIDSource**

Used to identify the source of the Account (1) code. This is especially useful if the account is a new account that the Respondent may not have setup yet in their system.

Type: **int**

Allowed values in AcctIDSourceCodeSet:

---

Code	Name	Description
1	BIC	BIC
2	SIDCode	SID Code
3	TFM	TFM (GSPTA)
4	OMGEO	OMGEO (Alert ID)
5	DTCCCode	DTCC Code

---



Code	Name	Description
6	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
99	Other	Other (custom or proprietary)

Used in groups: [BidCompReqGrp](#), [ListOrdGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [SideCrossOrdModGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [ExecutionReport](#), [MassOrder](#), [MassOrderAck](#), [MassQuote](#), [MassQuoteAck](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReject](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [OrderMassStatusRequest](#), [OrderStatusRequest](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [PositionReport](#), [Quote](#), [QuoteCancel](#), [QuoteResponse](#), [QuoteStatusReport](#), [QuoteStatusRequest](#), [RegistrationInstructions](#), [RegistrationInstructionsResponse](#), [RequestForPositions](#), [RequestForPositionsAck](#)

#### 180.2.7 AccumulatedReturnModifiedVariationMargin

The economic cost of the variation margin from one trading day to the next.

Type: [float](#)

Used in groups: [ClearingPriceParametersGrp](#)

#### 180.2.8 AdditionalDividendsIndicator

Indicates whether additional dividends are applicable.

Type: [Boolean](#)

Used in components: [DividendConditions](#)

#### 180.2.9 AdditionalTermBondCouponFrequencyPeriod

Time unit multiplier for the frequency of the bond's coupon payment.

Type: [int](#)

Used in groups: [AdditionalTermBondRefGrp](#)

**180.2.10 AdditionalTermBondCouponFrequencyUnit**

Time unit associated with the frequency of the bond's coupon payment.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in groups: **AdditionalTermBondRefGrp**

**180.2.11 AdditionalTermBondCouponRate**

Coupon rate of the bond. See also CouponRate(223).

Type: **Percentage**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.12 AdditionalTermBondCouponType**

Coupon type of the bond.

Type: **int**

Allowed values in CouponTypeCodeSet:

Code	Name	Description
0	Zero	Zero
1	FixedRate	Fixed rate

Code	Name	Description
2	FloatingRate	Floating rate
3	Structured	Structured

Used in groups: [AdditionalTermBondRefGrp](#)

### 180.2.13 AdditionalTermBondCurrency

Specifies the currency the bond value is denominated in. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [AdditionalTermBondRefGrp](#)

### 180.2.14 AdditionalTermBondCurrentTotalIssuedAmount

Total issued amount of the bond.

Type: [Amt](#)

Used in groups: [AdditionalTermBondRefGrp](#)

### 180.2.15 AdditionalTermBondDayCount

The day count convention used in interest calculations for a bond or an interest bearing security.

Type: [int](#)

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.

Code	Name	Description
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.

Code	Name	Description
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.

Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in groups: **AdditionalTermBondRefGrp**

#### 180.2.16 AdditionalTermBondDesc

Description of the bond.

Type: **String**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.17 AdditionalTermBondIssuer**

Issuer of the bond.

Type: **String**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.18 AdditionalTermBondMaturityDate**

The maturity date of the bond.

Type: **LocalMktDate**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.19 AdditionalTermBondParValue**

The par value of the bond.

Type: **Amt**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.20 AdditionalTermBondRefGrp**

The AdditionalTermBondRefGrp is a repeating group subcomponent of the AdditionalTermGrp component used to identify an underlying reference bond for a swap.

Name	Mult.	Type	Description
NoAdditionalTermBondRefs	[1..1]	NumInGroup	
AdditionalTermBondSecurityID	[0..1]	String	Required if NoAdditionalTermBondRefs(40000) > 0.
AdditionalTermBondSecurityIDSource	[0..1]	CodeSet	Conditionally required when AdditionalTermBondSecurityID(40001) is specified.
AdditionalTermBondDesc	[0..1]	String	
EncodedAdditionalTermBondDescLen	[0..1]	Length	Must be set if EncodedAdditionalTermBondDesc(40005) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedAdditionalTermBondDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the AdditionalTermBondDesc(40003) field in the encoded format specified via the MessageEncoding(347) field.
AdditionalTermBondCurrency	[0..1]	Currency	
AdditionalTermBondIssuer	[0..1]	String	
EncodedAdditionalTermBondIssuerLen	[0..1]	Length	Must be set if EncodedAdditionalTermBondIssuer(40009) field is specified and must immediately precede it.
EncodedAdditionalTermBondIssuer	[0..1]	data	Encoded (non-ASCII characters) representation of the AdditionalTermBondIssuer(40007) field in the encoded format specified via the MessageEncoding(347) field.
AdditionalTermBondSeniority	[0..1]	CodeSet	
AdditionalTermBondCouponType	[0..1]	CodeSet	
AdditionalTermBondCouponRate	[0..1]	Percentage	
AdditionalTermBondMaturityDate	[0..1]	LocalMktDate	
AdditionalTermBondParValue	[0..1]	Amt	
AdditionalTermBondCurrentTotalIssuedAmount	[0..1]	Amt	
AdditionalTermBondCouponFrequencyPeriod	[0..1]	int	Conditionally required when AdditionalTermBondCouponFrequencyUnit(40017) is specified.
AdditionalTermBondCouponFrequencyUnit	[0..1]	CodeSet	Conditionally required when AdditionalTermBondCouponFrequencyPeriod(40016) is specified.
AdditionalTermBondDayCount	[0..1]	CodeSet	

Used in groups: **AdditionalTermGrp**

#### 180.2.21 AdditionalTermBondSecurityID

Security identifier of the bond.

Type: **String**

Used in groups: **AdditionalTermBondRefGrp**



**180.2.22 AdditionalTermBondSecurityIDSource**

Identifies the source scheme of the AdditionalTermBondSecurityID(40001) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **AdditionalTermBondRefGrp**

### 180.2.23 AdditionalTermBondSeniority

Specifies the bond's payment priority in the event of a default.

Type: **String**

Allowed values in SeniorityCodeSet:

Code	Name	Description
SD	SeniorSecured	Senior Secured
SR	Senior	Senior
SB	Subordinated	Subordinated
JR	Junior	Junior. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
MZ	Mezzanine	Mezzanine. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
SN	SeniorNonPreferred	Senior Non-Preferred. For CDS reference obligations of non-preferred senior debt issued by European Financials that constitute a layer of debt ranking between the bank's normal senior debt but above the bank's normal tier 2 subordinated debt (reference: ISDA Credit Market Infrastructure Group).

Used in groups: [AdditionalTermBondRefGrp](#)

#### 180.2.24 AdditionalTermConditionPrecedentBondIndicator

Indicates whether the condition precedent bond is applicable. The swap contract is only valid if the bond is issued and if there is any dispute over the terms of fixed stream then the bond terms would be used.

Type: [Boolean](#)

Used in groups: [AdditionalTermGrp](#)

#### 180.2.25 AdditionalTermDiscrepancyClauseIndicator

Indicates whether the discrepancy clause is applicable.

Type: [Boolean](#)

Used in groups: [AdditionalTermGrp](#)

#### 180.2.26 AdditionalTermGrp

The AdditionalTermGrp is a repeating subcomponent of the Instrument component used to report additional contract terms.

Name	Mult.	Type	Description
<a href="#">NoAdditionalTerms</a>	[1..1]	NumInGroup	
<a href="#">AdditionalTermConditionPrecedent-BondIndicator</a>	[0..1]	Boolean	Required if NoAdditionalTerms(40019) > 0.
<a href="#">AdditionalTermDiscrepancyClauseIndicator</a>	[0..1]	Boolean	
<a href="#">AdditionalTermBondRefGrp</a>	[0..*]	Group	

Used in components: [Instrument](#)

#### 180.2.27 Adjustment

Identifies the type of adjustment.

Type: [int](#)

Allowed values in AdjustmentCodeSet:

Code	Name	Description
1	Cancel	Cancel
2	Error	Error
3	Correction	Correction

Used in messages: [SecurityMassStatus](#), [SecurityStatus](#)

### 180.2.28 AdjustmentType

Type of adjustment to be applied. Used for Position Change Submission (PCS), Position Adjustment (PAJ), and Customer Gross Margin (CGM).

Type: [int](#)

Allowed values in AdjustmentTypeCodeSet:

Code	Name	Description
0	ProcessRequestAsMarginDisposition	Process request as margin disposition
1	DeltaPlus	Delta plus
2	DeltaMinus	Delta minus
3	Final	Final
4	CustomerSpecificPosition	Customer specific position

Used in messages: [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#)

### 180.2.29 AdvId

Unique identifier of advertisement message.

(Prior to FIX 4.1 this field was of type int)

Type: [String](#)

Used in messages: [Advertisement](#)

**180.2.30 AdvRefID**

Reference identifier used with CANCEL and REPLACE transaction types.

(Prior to FIX 4.1 this field was of type int)

Type: **String**

Used in messages: **Advertisement**

**180.2.31 AdvSide**

Broker's side of advertised trade

Type: **char**

Allowed values in AdvSideCodeSet:

Code	Name	Description
B	Buy	Buy
S	Sell	Sell
T	Trade	Trade
X	Cross	Cross

Used in messages: **Advertisement**

**180.2.32 AdvTransType**

Identifies advertisement message transaction type

Type: **String**

Allowed values in AdvTransTypeCodeSet:

Code	Name	Description
N	New	New
C	Cancel	Cancel
R	Replace	Replace

Used in messages: **Advertisement**

**180.2.33 AffectedMarketSegmentGrp**

List of market segments that have been affected by a mass action.

Name	Mult.	Type	Description
NoAffectedMarketSegments	[1..1]	NumInGroup	
AffectedMarketSegmentID	[0..1]	String	Required when NoAffectedMarketSegments(1791) > 0.

Used in messages: **OrderMassActionReport**

**180.2.34 AffectedMarketSegmentID**

Market segment within an affected market repeating segment group.

Type: **String**

Used in groups: **AffectedMarketSegmentGrp**

**180.2.35 AffectedOrderID**

OrderID(37) of an order affected by a mass cancel or mass action request.

Type: **String**

Used in groups: **AffectedOrdGrp**

**180.2.36 AffectedOrdGrp**

Name	Mult.	Type	Description
NoAffectedOrders	[1..1]	NumInGroup	
AffectedOrigCLOrdID	[0..1]	String	Required if NoAffectedOrders(534) > 0. Indicates the client order id of an order affected by this request. If order(s) were manually delivered (or otherwise not delivered over FIX and not assigned a CLOrdID(11)) this field should contain string "MANUAL".

Name	Mult.	Type	Description
AffectedOrderID	[0..1]	String	Contains the OrderID(37) assigned by the counterparty of an affected order. Conditionally required when AffectedOrigClOrdID(1824) = "MANUAL".
AffectedSecondaryOrderID	[0..1]	String	Contains the SecondaryOrderID(198) assigned by the counterparty of an affected order.

Used in messages: [OrderMassActionReport](#), [OrderMassCancelReport](#)

#### 180.2.37 AffectedOrigClOrdID

OrigClOrdID(41) of an order affected by a mass cancel or mass action request.

Type: [String](#)

Used in groups: [AffectedOrdGrp](#)

#### 180.2.38 AffectedSecondaryOrderID

SecondaryOrderID(198) of an order affected by a mass cancel or mass action request.

Type: [String](#)

Used in groups: [AffectedOrdGrp](#)

#### 180.2.39 AffiliatedFirmsTradeIndicator

Indicates whether the transaction or position was entered into between two affiliated firms. I.e. one counterparty has an ownership interest in the other counterparty but less than the majority interest.

Type: [Boolean](#)

Used in messages: [ExecutionReport](#), [NewOrderSingle](#), [TradeCaptureReport](#)

#### 180.2.40 AffirmStatus

Specifies the affirmation status of the confirmation.

Type: [int](#)

Allowed values in AffirmStatusCodeSet:

Code	Name	Description
1	Received	Received
2	ConfirmRejected	Confirm rejected, i.e. not affirmed
3	Affirmed	Affirmed

Used in messages: [Confirmation](#), [ConfirmationAck](#)

#### 180.2.41 AggregatedBook

Specifies whether or not book entries should be aggregated. (Not specified) = broker option

Type: [Boolean](#)

Allowed values in AggregatedBookCodeSet:

Code	Name	Description
Y	BookEntriesToBeAggregated	book entries to be aggregated
N	BookEntriesShouldNotBeAggregated	book entries should not be aggregated

Used in messages: [MarketDataRequest](#)

#### 180.2.42 AggregatedQty

Total quantity of orders or fills quantity aggregated.

Type: [Qty](#)

Used in messages: [TradeAggregationReport](#), [TradeAggregationRequest](#)

#### 180.2.43 AggressorIndicator

Used to identify whether the order initiator is an aggressor or not in the trade.

Type: [Boolean](#)

Allowed values in AggressorIndicatorCodeSet:



Code	Name	Description
Y	OrderInitiatorIsAggressor	Order initiator is aggressor
N	OrderInitiatorIsPassive	Order initiator is passive

Used in components: [MDStatisticParameters](#)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [ExecutionReport](#)

#### 180.2.44 AggressorSide

Side of aggressive order or quote resulting in match event.

Type: [char](#)

Allowed values in SideCodeSet:

Code	Name	Description
1	Buy	Buy. For Securities Financing indicates the receipt of securities or collateral.
2	Sell	Sell. For Securities Financing indicates the delivery of securities or collateral.
3	BuyMinus	Buy minus
4	SellPlus	Sell plus
5	SellShort	Sell short
6	SellShortExempt	Sell short exempt
7	Undisclosed	Undisclosed
8	Cross	Cross (orders where counterparty is an exchange, valid for all messages except IOIs)
9	CrossShort	Cross short
A	CrossShortExempt	Cross short exempt
B	AsDefined	"As Defined" (for use with multileg instruments)
C	Opposite	"Opposite" (for use with multileg instruments)
D	Subscribe	Subscribe (e.g. CIV)
E	Redeem	Redeem (e.g. CIV)
F	Lend	Lend (FINANCING - identifies direction of collateral)
G	Borrow	Borrow (FINANCING - identifies direction of collateral)

Code	Name	Description
H	SellUndisclosed	Sell undisclosed. In the context of ESMA RTS 22, this allows for reporting of transactions where the investment firm (broker) is not able to determine whether the sell is a short sale transaction. Corresponds to RTS 22 "short selling indicator" value of 'UNDI'.

Used in groups: [MDFullGrp](#), [MDIncGrp](#)

#### 180.2.45 AggressorTime

Timestamp of aggressive order or quote resulting in match event.

Type: [UTCTimestamp](#)

Used in groups: [MDFullGrp](#), [MDIncGrp](#)

#### 180.2.46 AgreementCurrency

Contractual currency forming the basis of a financing agreement and associated transactions. Usually, but not always, the same as the trade currency.

Type: [Currency](#)

Used in components: [FinancingDetails](#)

#### 180.2.47 AgreementCurrencyCodeSource

Identifies class or source of the AgreementCurrency(918) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [FinancingDetails](#)

#### **180.2.48 AgreementDate**

A reference to the date the underlying agreement specified by AgreementID and AgreementDesc was executed.

Type: [LocalMktDate](#)

Used in components: [FinancingDetails](#)

#### **180.2.49 AgreementDesc**

The full name of the base standard agreement, annexes and amendments in place between the principals applicable to a financing transaction. See <http://www.fpml.org/coding-scheme/master-agreement-type> for derivative values.

Type: [String](#)

Used in components: [FinancingDetails](#)

#### **180.2.50 AgreementID**

A common reference to the applicable standing agreement between the counterparties to a financing transaction.

Type: [String](#)

Used in components: [FinancingDetails](#)

#### **180.2.51 AgreementVersion**

The version of the master agreement

Type: **String**

Used in components: **FinancingDetails**

#### **180.2.52 AlgoCertificateDesc**

Description of a certificate issued by an algorithmic trading firm.

Type: **String**

Used in messages: **AlgoCertificateReport**, **AlgoCertificateRequest**

#### **180.2.53 AlgoCertificateID**

Unique identifier for a certificate issued by an algorithmic trading firm.

Type: **String**

Used in messages: **AlgoCertificateReport**, **AlgoCertificateRequest**

#### **180.2.54 AlgoCertificateReportID**

Unique identifier of the AlgoCertificateReport(35=EJ).

Type: **String**

Used in messages: **AlgoCertificateReport**, **AlgoCertificateReportAck**

#### **180.2.55 AlgoCertificateReportRefID**

Reference identifier of the AlgoCertificateReport(35=EJ).

Type: **String**

Used in messages: **AlgoCertificateReport**

#### **180.2.56 AlgoCertificateReportStatus**

Status of the report being responded to.

Type: **int**

Allowed values in AlgoCertificateReportStatusCodeSet:

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected. Rejection reason provided in RejectText(1328).

Used in messages: [AlgoCertificateReportAck](#)

### 180.2.57 AlgoCertificateReportTransType

Identifies the message transaction type.

Type: [int](#)

Allowed values in AlgoCertificateReportTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Cancel	Cancel
2	Replace	Replace

Used in messages: [AlgoCertificateReport](#)

### 180.2.58 AlgoCertificateReportType

Specifies the type of business event related to an algo certification report.

Type: [int](#)

Allowed values in AlgoCertificateReportTypeCodeSet:

Code	Name	Description
0	CertificateInformation	Certificate information. The recipient of the report is informed about a certificate.
1	CertificateStateChanged	Certificate state changed. The recipient of the report is informed that the status of a certificate has changed. The new state is provided with AlgoCertificateStatus(3022).

Used in messages: [AlgoCertificateReport](#), [AlgoCertificateReportAck](#)

**180.2.59 AlgoCertificateRequestID**

Unique identifier of the AlgoCertificateRequest(35=EH).

Type: **String**

Used in messages: **AlgoCertificateReport**, **AlgoCertificateRequest**, **AlgoCertificateRequestAck**

**180.2.60 AlgoCertificateRequestRefID**

Reference identifier of the AlgoCertificateRequest(35=EH).

Type: **String**

Used in messages: **AlgoCertificateRequest**

**180.2.61 AlgoCertificateRequestStatus**

Status of the AlgoCertificateRequest(35=EH) message being responded to.

Type: **int**

Allowed values in AlgoCertificateRequestStatusCodeSet:

---

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected. Rejection reason provided in RejectText(1328).

---

Used in messages: **AlgoCertificateRequestAck**

**180.2.62 AlgoCertificateRequestTransType**

Identifies the message transaction type.

Type: **int**

Allowed values in AlgoCertificateRequestTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Cancel	Cancel
2	Replace	Replace

Used in messages: [AlgoCertificateRequest](#)

### 180.2.63 AlgoCertificateRequestType

Specifies the type of business event related to an algo certification request.

Type: [int](#)

Allowed values in AlgoCertificateRequestTypeCodeSet:

Code	Name	Description
0	CertificateInformation	Certificate information. The recipient of the request is asked to provide certificates based on the criteria defined as part of the request.
1	GenerateCertificate	Generate certificate. The recipient of the request is asked to generate a new certificate based on the information defined or referenced in the request.
2	ChangeCertificateStatus	Change certificate status. The recipient of the request is asked to update the status of the certificate referenced in the request. The requested status is provided with <a href="#">AlgoCertificateStatus(3022)</a> .
3	ForwardCertificate	Forward certificate. The recipient of the request is asked to submit the certificate referenced in the request to the venue identified in the TargetParties component.

Used in messages: [AlgoCertificateRequest](#), [AlgoCertificateRequestAck](#)

### 180.2.64 AlgoCertificateStatus

Status of the certification as provided by the regulatory authority.

Type: [int](#)

Allowed values in AlgoCertificateStatusCodeSet:

Code	Name	Description
0	Draft	Draft. Algo certificate created.
1	Approved	Approved. Algo certificate approved by authorized person.
2	Submitted	Submitted. Algo certificate sent to venue.
3	Registered	Registered. Algo certificate accepted and registered by venue.

Used in messages: [AlgoCertificateReport](#), [AlgoCertificateRequest](#)

### 180.2.65 AlgorithmicTradeIndicator

Indicates that the order or trade originates from a computer program or algorithm requiring little-to-no human intervention.

Type: [int](#)

Allowed values in AlgorithmicTradeIndicatorCodeSet:

Code	Name	Description
0	NonAlgorithmicTrade	Non-algorithmic trade
1	AlgorithmicTrade	Algorithmic trade. In the context of ESMA MiFID II, a trade has to be flagged as "algorithmic" if at least one of the matched orders was submitted by a trading algorithm. See Directive 2014/65/EU Article 4(1)(39).

Used in groups: [MDFullGrp](#), [MDIncGrp](#)

Used in messages: [ExecutionReport](#), [TradeCaptureReport](#)

### 180.2.66 AlgoSystemModuleGrp

AlgoSystemModuleGrp is a repeating group used to provide information regarding the modules of a system for algorithmic trading.

Name	Mult.	Type	Description
<a href="#">NoAlgoSystemModules</a>	[1..1]	NumInGroup	
<a href="#">AlgoSystemModuleName</a>	[0..1]	String	Required if NoAlgoSystemModules(3025)>0.
<a href="#">AlgoSystemModuleVersion</a>	[0..1]	String	Required if NoAlgoSystemModules(3025)>0.



Name	Mult.	Type	Description
AlgoSystemModuleLastUpdateTime	[0..1]	UTCTimestamp	

Used in messages: [AlgoCertificateReport](#), [TestActionReport](#), [TestSuiteDefinitionRequest](#)

#### **180.2.67 AlgoSystemModuleLastUpdateTime**

Support Timestamp of last update to Algo System Module.

Type: [UTCTimestamp](#)

Used in groups: [AlgoSystemModuleGrp](#)

#### **180.2.68 AlgoSystemModuleName**

Name of the component of a system for algorithmic trading.

Type: [String](#)

Used in groups: [AlgoSystemModuleGrp](#)

#### **180.2.69 AlgoSystemModuleVersion**

Version (e.g. build or commit number) of the component of a system for algorithmic trading.

Type: [String](#)

Used in groups: [AlgoSystemModuleGrp](#)

#### **180.2.70 AlgoTestDesc**

Description of means of testing for an algorithm.

Type: [String](#)

Used in messages: [AlgoCertificateReport](#)

**180.2.71 AllDividendsIndicator**

Represents the European Master Confirmation value of 'All Dividends' which, when applicable, signifies that, for a given Ex-Date, the daily observed share price for that day is adjusted (reduced) by the cash dividend and/or the cash value of any non-cash dividend per share (including extraordinary dividends) declared by the issuer.

Type: **Boolean**

Used in components: **DividendConditions**

**180.2.72 AllocAccount**

Sub-account mnemonic

Type: **String**

Used in components: **SettlTradeDetails**

Used in groups: **AllocAckGrp, AllocGrp, PreAllocGrp, PreAllocMlegGrp, TrdAllocGrp**

Used in messages: **Confirmation, ConfirmationRequest, SettlementInstructionRequest**

**180.2.73 AllocAccountType**

Type of account associated with a confirmation or other trade-level message

Type: **int**

Allowed values in AllocAccountTypeCodeSet:

Code	Name	Description
1	CarriedCustomerSide	Account is carried on customer side of books
2	CarriedNonCustomerSide	Account is carried on non-customer side of books
3	HouseTrader	House trader
4	FloorTrader	Floor trader
6	CarriedNonCustomerSideCross-Margined	Account is carried on non-customer side of books and is cross margined
7	HouseTraderCrossMargined	Account is house trader and is cross margined
8	JointBackOfficeAccount	Joint back office account (JBO)

Used in messages: **Confirmation, ConfirmationRequest**

**180.2.74 AllocAccruedInterestAmt**

Amount of Accrued Interest for convertible bonds and fixed income at the allocation-level.

Type: **Amt**

Used in groups: **AllocGrp**

**180.2.75 AllocAcctIDSource**

Used to identify the source of the AllocAccount (79) code.

See AcctIDSource (660) for valid values.

Type: **int**

Allowed values in AcctIDSourceCodeSet:

Code	Name	Description
1	BIC	BIC
2	SIDCode	SID Code
3	TFM	TFM (GSPTA)
4	OMGEO	OMGEO (Alert ID)
5	DTCCCode	DTCC Code
6	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
99	Other	Other (custom or proprietary)

Used in groups: **AllocAckGrp**, **AllocGrp**, **PreAllocGrp**, **PreAllocMlegGrp**, **TrdAllocGrp**

Used in messages: **Confirmation**, **ConfirmationRequest**, **SettlementInstructionRequest**

**180.2.76 AllocAckGrp**

This repeating group is optionally used for messages with AllocStatus(87) = 2 (Account level reject), to provide details of the individual accounts that were accepted or rejected. In the case of a reject, the reasons for the rejection should be specified.

Name	Mult.	Type	Description
NoAllocs	[1..1]	NumInGroup	Indicates number of allocation groups to follow.
AllocAccount	[0..1]	String	Required if NoAllocs(78) > 0. Must be first field in repeating group.
AllocAcctIDSource	[0..1]	CodeSet	
AllocPrice	[0..1]	Price	Used when performing "executed price" vs. "average price" allocations (e.g. Japan). AllocAccount(79) plus AllocPrice(366) form a unique Allocs entry. Used in lieu of AllocAvgPx(153).
AllocPositionEffect	[0..1]	CodeSet	
IndividualAllocID	[0..1]	String	
ParentAllocID	[0..1]	String	
FirmMnemonic	[0..1]	String	
ClearedIndicator	[0..1]	CodeSet	Used to communicate the status of central clearing workflow.
AllocLegRefID	[0..1]	String	The field may not be used in any message where there are no legs.
AllocRegulatoryTradeIDGrp	[0..*]	Group	
IndividualAllocRejCode	[0..1]	CodeSet	Required if NoAllocs(78) > 0 and AllocStatus(87) = 2 (Account level reject).
NestedParties	[0..*]	Group	
AllocHandlInst	[0..1]	CodeSet	
AllocText	[0..1]	String	Can be used here to hold text relating to the rejection of this AllocAccount(366))
EncodedAllocTextLen	[0..1]	Length	Must be set if EncodedAllocText(361) field is specified and must immediately precede it.
EncodedAllocText	[0..1]	data	Encoded (non-ASCII characters) representation of the AllocText(161) field in the encoded format specified via the MessageEncoding(347) field.
FirmAllocText	[0..1]	String	
EncodedFirmAllocTextLen	[0..1]	Length	Must be set if EncodedFirmAllocText(1734) field is specified and must immediately precede it.
EncodedFirmAllocText	[0..1]	data	Encoded (non-ASCII characters) representation of the FirmAllocText(1732) field in the encoded format specified via the MessageEncoding(347) field.
SecondaryIndividualAllocID	[0..1]	String	
AllocCustomerCapacity	[0..1]	String	

Name	Mult.	Type	Description
IndividualAllocType	[0..1]	CodeSet	
AllocQty	[0..1]	Qty	
AllocCalculatedCcyQty	[0..1]	Qty	
CustodialLotID	[0..1]	String	Only used for specific lot trades.
VersusPurchaseDate	[0..1]	LocalMktDate	Only used for specific lot trades. If this field is used, either VersusPurchasePrice(1754) or CurrentCostBasis(1755) should be specified.
VersusPurchasePrice	[0..1]	Price	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified.
CurrentCostBasis	[0..1]	Amt	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified
AllocAvgPxGroupID	[0..1]	String	
AllocAvgPxIndicator	[0..1]	CodeSet	

Used in messages: [AllocationInstructionAck](#), [AllocationReportAck](#)

### 180.2.77 AllocationRollupInstruction

An indicator to override the normal procedure to roll up allocations for the same take-up firm.

Type: [int](#)

Allowed values in AllocationRollupInstructionCodeSet:

Code	Name	Description
0	Rollup	Roll up
1	DoNotRollUp	Do not roll up

Used in groups: [AllocGrp](#), [TrdAllocGrp](#)

### 180.2.78 AllocAvgPx

AvgPx (6) for a specific AllocAccount (79)

For Fixed Income this is always expressed as "percent of par" price type.

Type: **Price**

Used in groups: **AllocGrp**

#### **180.2.79 AllocAvgPxGroupID**

Used by submitting firm to group trades being sub-allocated into an average price group. The trades in the average price group will be used to calculate an average price for the group.

Type: **String**

Used in groups: **AllocAckGrp**, **AllocGrp**

#### **180.2.80 AllocAvgPxIndicator**

Average pricing indicator at the allocation level.

Type: **int**

Allowed values in AvgPxIndicatorCodeSet:

Code	Name	Description
0	NoAveragePricing	No average pricing
1	Trade	Trade is part of an average price group identified by the AvgPxGroupID(1731)
2	LastTrade	Last trade of the average price group identified by the AvgPxGroupID(1731)
3	NotionalValueAveragePxGroupTrade	Trade is part of a notional value average price group. A notional value average price (NVAP) group is effectively closed and available for allocation as long as the NVAP of the group is non-zero.
4	AveragePricedTrade	Trade is average priced

Used in groups: **AllocAckGrp**, **AllocGrp**

#### **180.2.81 AllocCalculatedCcyQty**

Used for the calculated quantity of the other side of the currency trade applicable to the allocation instance.

Type: **Qty**

Used in groups: **AllocAckGrp**, **AllocGrp**, **TrdAllocGrp**

**180.2.82 AllocCancReplaceReason**

Reason for cancelling or replacing an Allocation Instruction or Allocation Report message

Type: **int**

Allowed values in AllocCancReplaceReasonCodeSet:

Code	Name	Description
1	OriginalDetailsIncomplete	Original details incomplete/incorrect
2	ChangeInUnderlyingOrderDetails	Change in underlying order details
3	CancelledByGiveupFirm	Cancelled by give-up firm
99	Other	Other

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**

**180.2.83 AllocClearingFeeIndicator**

ClearingFeeIndicator(635) for Allocation, see ClearingFeeIndicator(635) for permitted values.

Type: **String**

Used in groups: **TrdAllocGrp**

**180.2.84 AllocCommissionAmount**

The commission amount.

Type: **Amt**

Used in groups: **AllocCommissionDataGrp**

**180.2.85 AllocCommissionAmountShared**

Commission amount to be shared with a third party, e.g. as part of a directed brokerage commission sharing arrangement. If specified, this amount should not exceed the amount in AllocCommissionAmount(2654).

Type: **Amt**

Used in groups: **AllocCommissionDataGrp**

**180.2.86 AllocCommissionAmountSubType**

Further sub classification of the AllocCommissionAmountType(2655).

Type: **int**

Allowed values in CommissionAmountSubTypeCodeSet:

Code	Name	Description
0	ResearchPaymentAccount	Research payment account (RPA)
1	CommissionSharingAgreement	Commission sharing agreement (CSA)
2	OtherTypeResearchPayment	Other type of research payment. A type of research payment other than RPA or CSA.

Used in groups: **AllocCommissionDataGrp**

**180.2.87 AllocCommissionAmountType**

Indicates what type of commission is being expressed in AllocCommissionAmount(2654).

Type: **int**

Allowed values in CommissionAmountTypeCodeSet:

Code	Name	Description
0	Unspecified	Unspecified
1	Acceptance	Acceptance. The bank's charge for issuing a Letter of Credit.
2	Broker	Broker. The executing broker's commission.
3	ClearingBroker	Clearing broker. The clearing broker's commission.
4	Retail	Retail. Commission charged by or related to retail sales.
5	SalesCommission	Sales commission. The commission charged by the sales desk.
6	LocalCommission	Local commission. Commission paid to local broker in a cross-border transaction.
7	ResearchPayment	Research payment

Used in groups: **AllocCommissionDataGrp**



**180.2.88 AllocCommissionBasis**

Specifies the basis or unit used to calculate the commission.

Type: **char**

Allowed values in CommTypeCodeSet:

Code	Name	Description
1	PerUnit	Amount per unit. Implying shares, par, currency, physical unit etc. Use CommissionUnitOfMeasure(1238) to clarify for commodities.
2	Percent	Percent
3	Absolute	Absolute. Total monetary amount.
4	PercentageWaivedCashDiscount	Percentage waived, cash discount basis. For use with CIV buy orders.
5	PercentageWaivedEnhancedUnits	Percentage waived, enhanced units basis. For use with CIV buy orders.
6	PointsPerBondOrContract	Points per bond or contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention, e.g. 1000 par for bonds.
7	BasisPoints	Basis points. The commission is expressed in basis points in reference to the gross price of the reference asset.
8	AmountPerContract	Amount per contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention.

Used in groups: **AllocCommissionDataGrp**

**180.2.89 AllocCommissionCurrency**

Specifies the currency denomination of the commission amount if different from the trade's currency.

AllocCommissionCurrencyCodeSource(2925) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **AllocCommissionDataGrp**

**180.2.90 AllocCommissionCurrencyCodeSource**

Identifies class or source of the AllocCommissionCurrency(2657) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **AllocCommissionDataGrp**

**180.2.91 AllocCommissionDataGrp**

The AllocCommissionDataGrp component block is used to carry commission information such as the type of commission and the rate at the allocation level. It provides a means to express commission applicable for the specified allocation account.

Name	Mult.	Type	Description
<b>NoAllocCommissions</b>	[1..1]	NumInGroup	
<b>AllocCommissionAmount</b>	[0..1]	Amt	Required if NoAllocCommissions(2653) > 0. If the commission is based on a percentage of trade quantity or a factor of "unit of measure", AllocCommissionRate(2660) and AllocCommissionUnitOfMeasure(2658) may also be specified as appropriate.
<b>AllocCommissionAmountType</b>	[0..1]	CodeSet	Required if NoAllocCommissions(2653) > 0.
<b>AllocCommissionAmountSubType</b>	[0..1]	CodeSet	
<b>AllocCommissionBasis</b>	[0..1]	CodeSet	Required if NoAllocCommissions(2653) > 0.
<b>AllocCommissionCurrency</b>	[0..1]	Currency	

Name	Mult.	Type	Description
<a href="#">AllocCommissionCurrencyCodeSource</a>	[0..1]	CodeSet	
<a href="#">AllocCommissionUnitOfMeasure</a>	[0..1]	CodeSet	
<a href="#">AllocCommissionUnitOfMeasureCurrency</a>	[0..1]	Currency	
<a href="#">AllocCommissionUnitOfMeasureCurrencyCodeSource</a>	[0..1]	CodeSet	
<a href="#">AllocCommissionRate</a>	[0..1]	float	
<a href="#">AllocCommissionSharedIndicator</a>	[0..1]	Boolean	
<a href="#">AllocCommissionAmountShared</a>	[0..1]	Amt	If specified, <a href="#">AllocCommissionSharedIndicator</a> (2661) must be set to "Y".
<a href="#">AllocCommissionLegRefID</a>	[0..1]	String	This field may be used for multi-leg trades sent as a single message to indicate that the entry applies only to a specific leg.
<a href="#">AllocCommissionDesc</a>	[0..1]	String	
<a href="#">EncodedAllocCommissionDescLen</a>	[0..1]	Length	Must be set if <a href="#">EncodedAllocCommissionDesc</a> (2666) is specified and must immediately precede it.
<a href="#">EncodedAllocCommissionDesc</a>	[0..1]	data	Encoded (non-ASCII characters) representation of the <a href="#">AllocCommissionDesc</a> (2664) field in the encoded format specified via the <a href="#">MessageEncoding</a> (347) field.

Used in groups: [AllocGrp](#), [TrdAllocGrp](#)

### 180.2.92 [AllocCommissionDesc](#)

Description of the commission.

Type: [String](#)

Used in groups: [AllocCommissionDataGrp](#)

### 180.2.93 [AllocCommissionLegRefID](#)

Identifies the leg of the trade the entry applies to by referencing the leg's [LegID](#)(1788).

Type: [String](#)

Used in groups: [AllocCommissionDataGrp](#)

**180.2.94 AllocCommissionRate**

The commission rate when AllocCommissionAmount(2654) is based on a percentage of quantity, amount per unit or a factor of "unit of measure". If the rate is a percentage or expressed in basis points, use the decimalized form, e.g. "0.05" for a 5% commission or "0.005" for 50 basis points.

Type: **float**

Used in groups: **AllocCommissionDataGrp**

**180.2.95 AllocCommissionSharedIndicator**

Indicates whether the amount in AllocCommissionAmount(2654) is to be shared with a third party, e.g. as part of a directed brokerage commission sharing arrangement.

Type: **Boolean**

Used in groups: **AllocCommissionDataGrp**

**180.2.96 AllocCommissionUnitOfMeasure**

The commission rate unit of measure.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)

Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter

Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [AllocCommissionDataGrp](#)

### 180.2.97 AllocCommissionUnitOfMeasureCurrency

Indicates the currency of the unit of measure. Conditionally required when AllocCommissionUnitOfMeasure(2658) = Ccy (Currency).

Type: [Currency](#)

Used in groups: [AllocCommissionDataGrp](#)

### 180.2.98 AllocCommissionUnitOfMeasureCurrencyCodeSource

Identifies class or source of the AllocCommissionUnitOfMeasureCurrency(2659) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [AllocCommissionDataGrp](#)

**180.2.99 AllocCustomerCapacity**

Capacity of customer in the allocation block.

Type: **String**

Used in groups: **AllocAckGrp**, **AllocGrp**, **TrdAllocGrp**

**180.2.100 AllocGrossTradeAmt**

Total amount traded for this account (i.e. quantity \* price) expressed in units of currency.

Type: **Amt**

Used in groups: **AllocGrp**

**180.2.101 AllocGroupAmount**

Indicates the notional units or amount being allocated.

Type: **Amt**

Used in groups: **AllocGrp**

**180.2.102 AllocGroupID**

Intended to be used by a central counterparty to assign an identifier to allocations of trades for the same instrument traded at the same price.

Type: **String**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAck**, **AllocationInstructionAlert**, **AllocationInstructionAlertRequest**, **AllocationReport**, **AllocationReportAck**

**180.2.103 AllocGroupQuantity**

Indicates the total quantity of an allocation group. Includes any allocated quantity.

Type: **Qty**

Used in messages: **AllocationInstructionAlert**, **AllocationReport**



**180.2.104 AllocGroupRemainingQuantity**

Indicates the remaining quantity of an allocation group that has not yet been allocated.

Type: Qty

Used in messages: AllocationInstructionAlert, AllocationReport

**180.2.105 AllocGroupRemainingSubQty**

Remaining quantity in the subgroup of an allocation group.

Type: Qty

Used in groups: AllocGroupSubQtyGrp

**180.2.106 AllocGroupStatus**

Status of the trade give-up relative to the group identified in AllocGroupID(1730).

Type: int

Allowed values in AllocGroupStatusCodeSet:

Code	Name	Description
0	Added	Added. This trade has been associated with the group for the first time.
1	Canceled	Canceled. This trade has been removed from the group.
2	Replaced	Replaced. This trade already in the group has been updated.
3	Changed	Changed. An allocated trade or give-up has moved from one allocation group to another.
4	Pending	Pending. A request to assign or change an allocation group is pending.

Used in groups: TrdCapRptAckSideGrp, TrdCapRptSideGrp

Used in messages: AllocationReport

**180.2.107 AllocGroupSubQty**

Total quantity in the subgroup of an allocation group.

Type: Qty

Used in groups: AllocGroupSubQtyGrp

### 180.2.108 AllocGroupSubQtyAttributeGrp

This repeating group is used to identify attributes of trades in subgroups of an average pricing group.

Name	Mult.	Type	Description
NoAllocGroupSubQtyAttributes	[1..1]	NumInGroup	
AllocGroupSubQtyType	[0..1]	CodeSet	Required if NoAllocGroupSubQtyAttributes (2979) > 0.
AllocGroupSubQtyValue	[0..1]	String	Required if NoAllocGroupSubQtyAttributes (2979) > 0.

Used in groups: AllocGroupSubQtyGrp

### 180.2.109 AllocGroupSubQtyGrp

This repeating group is used to identify subgroups of an average pricing group. The total and remaining quantities of the average pricing group are split into sub-quantities based on trade attributes.

Name	Mult.	Type	Description
NoAllocGroupSubQtys	[1..1]	NumInGroup	
AllocGroupSubQty	[0..1]	Qty	Required if NoAllocGroupSubQtys(2975) > 0.
AllocGroupSubQtyOffset	[0..1]	Qty	
AllocGroupRemainingSubQty	[0..1]	Qty	
AllocGroupSubQtyID	[0..1]	String	Conditionally required if AllocGroupSubQtyAttributeGrp is not present.
AllocGroupSubQtyAttributeGrp	[0..*]	Group	Conditionally required if AllocGroupSubQtyID(2974) is not present.

Used in messages: AllocationInstructionAlert

**180.2.110 AllocGroupSubQtyID**

Identifier for quantity subgroup assigned by the clearinghouse.

Type: **String**

Used in groups: **AllocGroupSubQtyGrp**

Used in messages: **AllocationInstruction**

**180.2.111 AllocGroupSubQtyOffset**

Change in quantity in the subgroup of an allocation group.

Type: **Qty**

Used in groups: **AllocGroupSubQtyGrp**

**180.2.112 AllocGroupSubQtyType**

Type of trade attribute defining a subgroup in an allocation group.

Type: **int**

Allowed values in AllocGroupSubQtyTypeCodeSet:

Code	Name	Description
1	TradeType	Trade type
2	TradePublicationIndicator	Trade publication indicator
3	OrderHandlingInstruction	Order handling instruction

Used in groups: **AllocGroupSubQtyAttributeGrp**

**180.2.113 AllocGroupSubQtyValue**

Value of the trade attribute defining a subgroup in an allocation group.

Type: **String**

Used in groups: **AllocGroupSubQtyAttributeGrp**

**180.2.114 AllocGrp**

The AllocGrp component conveys the details of each account when a trade (or block trade) is allocated into one or more accounts.

Name	Mult.	Type	Description
NoAllocs	[1..1]	NumInGroup	
AllocAccount	[0..1]	String	Required if NoAllocs(78) > 0. May specify the broker of credit if ProcessCode(81) is step-out or soft-dollar step-out and Institution does not wish to disclose individual account breakdowns to the executing broker.
AllocAcctIDSource	[0..1]	CodeSet	
MatchStatus	[0..1]	CodeSet	
AllocPrice	[0..1]	Price	Used when performing "executed price" vs. "average price" allocations (e.g. Japan). AllocAccount(79) plus AllocPrice(366) form a unique Allocs entry. Used in lieu of AllocAvgPx(153).
AllocQty	[0..1]	Qty	Conditionally required except when for AllocTransType="Cancel", or when AllocType="Ready-To-Book" or "Warehouse instruction".
AllocCalculatedCcyQty	[0..1]	Qty	
CustodialLotID	[0..1]	String	Only used for specific lot trades.
VersusPurchaseDate	[0..1]	LocalMktDate	Only used for specific lot trades. If this field is used, either VersusPurchasePrice(1754) or CurrentCostBasis(1755) should be specified.
VersusPurchasePrice	[0..1]	Price	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified.
CurrentCostBasis	[0..1]	Amt	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified
IndividualAllocID	[0..1]	String	
FirmMnemonic	[0..1]	String	Allocation identifier assigned by the Firm submitting the allocation for an individual allocation instruction (as opposed to the overall message level identifier).
ParentAllocID	[0..1]	String	
AllocLegRefID	[0..1]	String	The field may not be used in any message where there are no legs.

Name	Mult.	Type	Description
AllocRegulatoryTradeIDGrp	[0..*]	Group	
AllocTrdRegTimestamps	[0..*]	Group	
ProcessCode	[0..1]	CodeSet	
SecondaryIndividualAllocID	[0..1]	String	Can be used by an intermediary to specify an allocation ID assigned by the intermediary's system.
AllocMethod	[0..1]	CodeSet	Specifies the method under which a trade quantity was allocated.
AllocationRollupInstruction	[0..1]	CodeSet	An indicator to override the normal procedure to roll up allocations for the same Carry Firm.
AllocCustomerCapacity	[0..1]	String	Can be used for granular reporting of separate allocation detail within a single trade report or allocation message.
AllocPositionEffect	[0..1]	CodeSet	
IndividualAllocType	[0..1]	CodeSet	
NestedParties	[0..*]	Group	Insert here the set of "Nested Parties" (firm identification "nested" within additional repeating group) fields defined in "Common Components of Application Messages". Used for NestedPartyRole=BrokerOfCredit, ClientID, Settlement location (PSET), etc. Note: this field can be used for settlement location (PSET) information.
NotifyBrokerOfCredit	[0..1]	CodeSet	
AllocHandlInst	[0..1]	CodeSet	
AllocText	[0..1]	String	Free format text field related to this AllocAccount
EncodedAllocTextLen	[0..1]	Length	Must be set if EncodedAllocText field is specified and must immediately precede it.
EncodedAllocText	[0..1]	data	Encoded (non-ASCII characters) representation of the AllocText field in the encoded format specified via the MessageEncoding field.
FirmAllocText	[0..1]	String	
EncodedFirmAllocTextLen	[0..1]	Length	
EncodedFirmAllocText	[0..1]	data	
CommissionData	[0..1]	Component	
AllocCommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData component if multiple commissions or enhanced attributes are needed.

Name	Mult.	Type	Description
AllocAvgPx	[0..1]	Price	AvgPx for this AllocAccount. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points) for this allocation, expressed in terms of Currency(15). For Fixed Income always express value as "percent of par".
AllocNetMoney	[0..1]	Amt	NetMoney for this AllocAccount. $((\text{AllocQty} * \text{AllocAvgPx}) - \text{Commission} - \text{sum of MiscFeeAmt} + \text{AccruedInterestAmt})$ if a Sell. $((\text{AllocQty} * \text{AllocAvgPx}) + \text{Commission} + \text{sum of MiscFeeAmt} + \text{AccruedInterestAmt})$ if a Buy. For FX, if specified, expressed in terms of Currency(15).
SettlCurrAmt	[0..1]	Amt	Replaced by AllocSettlCurrAmt
AllocGrossTradeAmt	[0..1]	Amt	
AllocSettlCurrAmt	[0..1]	Amt	AllocNetMoney in AllocSettlCurrency for this AllocAccount if AllocSettlCurrency is different from "overall" Currency
SettlCurrency	[0..1]	Currency	Replaced by AllocSettlCurrency. SettlCurrency for this AllocAccount if different from "overall" Currency. Required if SettlCurrAmt is specified.
AllocSettlCurrency	[0..1]	Currency	AllocSettlCurrency for this AllocAccount if different from "overall" Currency. Required if AllocSettlCurrAmt is specified. Required for NDFs.
AllocSettlCurrencyCodeSource	[0..1]	CodeSet	
SettlCurrFxRate	[0..1]	float	Foreign exchange rate used to compute AllocSettlCurrAmt from Currency to AllocSettlCurrency
SettlCurrFxRateCalc	[0..1]	CodeSet	Specifies whether the SettlCurrFxRate should be multiplied or divided
AllocAccruedInterestAmt	[0..1]	Amt	Applicable for Convertible Bonds and fixed income
AllocInterestAtMaturity	[0..1]	Amt	Applicable for securities that pay interest in lump-sum at maturity
MiscFeesGrp	[0..*]	Group	
ClrInstGrp	[0..*]	Group	
ClearingFeeIndicator	[0..1]	CodeSet	
AllocSettlInstType	[0..1]	CodeSet	Used to indicate whether settlement instructions are provided on this message, and if not, how they are to be derived. Absence of this field implies use of default instructions.

Name	Mult.	Type	Description
SettlInstructionsData	[0..1]	Component	Insert here the set of "SettlInstructionsData" fields defined in "Common Components of Application Messages". Used to communicate settlement instructions for this AllocAccount detail. Required if AllocSettlInstType = 2 or 3.
AllocRefRiskLimitCheckID	[0..1]	String	Conditionally required when AllocRefRiskLimitCheckIDType(2393) is specified.
AllocRefRiskLimitCheckIDType	[0..1]	CodeSet	Conditionally required when AllocRefRiskLimitCheckID(2392) is specified.
AllocRiskLimitCheckStatus	[0..1]	CodeSet	
AllocGroupAmount	[0..1]	Amt	
AllocAvgPxGroupID	[0..1]	String	
AllocAvgPxIndicator	[0..1]	CodeSet	
TradeAllocAmtGrp	[0..*]	Group	

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#)

### 180.2.115 AllocHandlInst

Indicates how the receiver (i.e. third party) of allocation information should handle/process the account details.

Type: [int](#)

Allowed values in AllocHandlInstCodeSet:

Code	Name	Description
1	Match	Match
2	Forward	Forward
3	ForwardAndMatch	Forward and Match
4	AutoClaimGiveUp	Auto claim give-up. Indicates that the give-up and take-up party are the same and that trade give-up is to be claimed automatically.

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [PreAllocGrp](#), [TrdAllocGrp](#)

**180.2.116 AllocID**

Unique identifier for allocation message.

(Prior to FIX 4.1 this field was of type int)

Type: **String**

Used in components: **SettlTradeDetails**

Used in groups: **ListOrdGrp**, **SideCrossOrdModGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAck**, **AllocationInstructionAlert**, **AllocationReport**, **AllocationReportAck**, **Confirmation**, **ConfirmationRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.117 AllocInterestAtMaturity**

Amount of interest (i.e. lump-sum) at maturity at the account-level.

Type: **Amt**

Used in groups: **AllocGrp**

**180.2.118 AllocIntermedReqType**

Response to allocation to be communicated to a counterparty through an intermediary, i.e. clearing house. Used in conjunction with AllocType = "Request to Intermediary" and AllocReportType = "Request to Intermediary"

Type: **int**

Allowed values in AllocIntermedReqTypeCodeSet:

Code	Name	Description
1	PendingAccept	Pending Accept
2	PendingRelease	Pending Release
3	PendingReversal	Pending Reversal
4	Accept	Accept
5	BlockLevelReject	Block Level Reject
6	AccountLevelReject	Account Level Reject



Used in messages: [AllocationInstruction](#), [AllocationInstructionAck](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#)

#### **180.2.119 AllocLegRefID**

Unique identifier for a specific leg (uniqueness not defined as part of the FIX specification). AllocLegRefID(2727) references the value from LegID(1788) in the current multileg order or trade message specifying to which leg the allocation instance applies.

Type: [String](#)

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [PreAllocGrp](#), [PreAllocMlegGrp](#), [TrdAllocGrp](#)

#### **180.2.120 AllocLinkID**

Can be used to link two different Allocation messages (each with unique AllocID (70)) together, i.e. for F/X "Netting" or "Swaps". Should be unique.

Type: [String](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#)

#### **180.2.121 AllocLinkType**

Identifies the type of Allocation linkage when AllocLinkID(196) is used.

Type: [int](#)

Allowed values in AllocLinkTypeCodeSet:

Code	Name	Description
0	FXNetting	FX Netting
1	FXSwap	FX Swap

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#)

#### **180.2.122 AllocMethod**

Specifies the method under which a trade quantity was allocated.

Type: **int**

Allowed values in AllocMethodCodeSet:

Code	Name	Description
1	Automatic	Automatic
2	Guarantor	Guarantor
3	Manual	Manual
4	BrokerAssigned	Broker assigned

Used in groups: **AllocGrp**, **TrdAllocGrp**

### **180.2.123 AllocNetMoney**

NetMoney(118) for a specific AllocAccount(79).

Type: **Amt**

Used in groups: **AllocGrp**

### **180.2.124 AllocNoOrdersType**

Indicates how the orders being booked and allocated by an AllocationInstruction or AllocationReport message are identified, e.g. by explicit definition in the OrdAllocGrp or ExecAllocGrp components, or not identified explicitly.

Type: **int**

Allowed values in AllocNoOrdersTypeCodeSet:

Code	Name	Description
0	NotSpecified	Not specified
1	ExplicitListProvided	Explicit list provided

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**

**180.2.125 AllocPositionEffect**

Indicates whether the resulting position after a trade should be an opening position or closing position. Used for omnibus accounting - where accounts are held on a gross basis instead of being netted together.

Type: **char**

Allowed values in AllocPositionEffectCodeSet:

Code	Name	Description
O	Open	Open
C	Close	Close
R	Rolled	Rolled
F	FIFO	FIFO

Used in groups: **AllocAckGrp**, **AllocGrp**

**180.2.126 AllocPrice**

Executed price for an AllocAccount (79) entry used when using "executed price" vs. "average price" allocations (e.g. Japan).

Type: **Price**

Used in groups: **AllocAckGrp**, **AllocGrp**

**180.2.127 AllocQty**

Quantity to be allocated to specific sub-account

(Prior to FIX 4.2 this field was of type int)

Type: **Qty**

Used in components: **SettlTradeDetails**

Used in groups: **AllocAckGrp**, **AllocGrp**, **PreAllocGrp**, **PreAllocMlegGrp**, **TrdAllocGrp**

Used in messages: **Confirmation**

**180.2.128 AllocRefRiskLimitCheckID**

The reference identifier to the PartyRiskLimitCheckRequest(35=DF), or a similar out of band message, message that contained the approval or rejection for risk/credit limit check for this allocation.

Type: **String**

Used in groups: **AllocGrp, TrdAllocGrp**

**180.2.129 AllocRefRiskLimitCheckIDType**

Specifies which type of identifier is specified in AllocRefRiskLimitCheckID(2392) field.

Type: **int**

Allowed values in RefRiskLimitCheckIDTypeCodeSet:

Code	Name	Description
0	RiskLimitRequestID	RiskLimitRequestID(1666)
1	RiskLimitCheckID	RiskLimitCheckID(2319)
3	OutOfBandID	Out of band identifier

Used in groups: **AllocGrp, TrdAllocGrp**

**180.2.130 AllocRegulatoryLegRefID**

Identifies the leg of the trade the entry applies to by referencing the leg's LegID(1788).

Type: **String**

Used in groups: **AllocRegulatoryTradeIDGrp**

**180.2.131 AllocRegulatoryTradeID**

Trade identifier required by government regulators or other regulatory organizations for regulatory reporting purposes. For example, unique swap identifier (USI) as required by the U.S. Commodity Futures Trading Commission.

Type: **String**

Used in groups: **AllocRegulatoryTradeIDGrp**

### 180.2.132 AllocRegulatoryTradeIDEvent

Identifies the event which caused the origination of the identifier in AllocRegulatoryTradeID(1909). When more than one event is the cause, use the higher enumeration value. For example, if the identifier is originated due to an allocated trade which was cleared and reported, use the enumeration value 2(Clearing).

Type: **int**

Allowed values in RegulatoryTradeIDEventCodeSet:

Code	Name	Description
0	InitialBlockTrade	Initial block trade.
1	Allocation	Allocation. Determination that the block trade will not be further allocated.
2	Clearing	Clearing
3	Compression	Compression
4	Novation	Novation
5	Termination	Termination
6	PostTrdVal	Post-trade valuation

Used in groups: **AllocRegulatoryTradeIDGrp**

### 180.2.133 AllocRegulatoryTradeIDGrp

The AllocRegulatoryTradeIDGrp is a repeating component within the TrdAllocGrp component used to report the source, value and relationship of multiple trade identifiers for the same trade allocation instance.

This component can be used to meet regulatory trade reporting requirements where identifiers such as the Unique Swaps Identifier (USI) are required to be reported, showing the chaining of these identifiers as needed.

Name	Mult.	Type	Description
NoAllocRegulatoryTradeIDs	[1..1]	NumInGroup	
AllocRegulatoryTradeID	[0..1]	String	Required if NoAllocRegulatoryTradeIDs(1908) > 0.
AllocRegulatoryTradeIDSource	[0..1]	CodeSet	
AllocRegulatoryTradeIDEvent	[0..1]	CodeSet	

Name	Mult.	Type	Description
<a href="#">AllocRegulatoryTradeIDType</a>	[0..1]	CodeSet	
<a href="#">AllocRegulatoryLegRefID</a>	[0..1]	String	This field may be used for multi-leg trades sent as a single message to indicate that the entry applies only to a specific leg.
<a href="#">AllocRegulatoryTradeIDScope</a>	[0..1]	CodeSet	

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [TrdAllocGrp](#)

#### 180.2.134 AllocRegulatoryTradeIDScope

Specifies the scope to which the [AllocRegulatoryTradeID](#)(1909) applies. Used when a trade must be assigned more than one identifier, e.g. one for the clearing member and another for the client on a cleared trade as with the principal model in Europe.

Type: [int](#)

Allowed values in [RegulatoryTradeIDScopeCodeSet](#):

Code	Name	Description
1	ClearingMember	Clearing member
2	Client	Client

Used in groups: [AllocRegulatoryTradeIDGrp](#)

#### 180.2.135 AllocRegulatoryTradeIDSource

Identifies the reporting entity that originated the value in [RegulatoryTradeID](#)(1903). The reporting entity identifier may be assigned by a regulator or from a supported standard identifier source scheme.

Type: [String](#)

Allowed values in [RegulatoryTradeIDSourceCodeSet](#):

Code	Name	Description
1	UniqueTransactionIdentifier	Unique Transaction Identifier (ISO 23897)

Used in groups: [AllocRegulatoryTradeIDGrp](#)

**180.2.136 AllocRegulatoryTradeIDType**

Specifies the type of trade identifier provided in AllocRegulatoryTradeID(1909), within the context of the hierarchy of trade events.

Type: **int**

Allowed values in RegulatoryTradeIDTypeCodeSet:

Code	Name	Description
0	Current	Current. The default if not specified.
1	Previous	Previous. The previous trade's identifier when reporting a cleared trade or novation of a previous trade.
2	Block	Block. The block trade's identifier when reporting an allocated subtrade.
3	Related	Related. The related trade identifier when reporting a mixed swap.
4	ClearedBlockTrade	Cleared block trade. Assigned by the CCP to a bunched order/trade when it needs to be cleared with the standby clearing firm prior to post-trade allocation.
5	TradingVenueTransactionIdentifier	Trading venue transaction identifier. Assigned by the trading venue to a transaction. In the context of ESMA RTS 22 and RTS 24, this is a unique transaction identification "number generated by trading venues and disseminated to both the buying and selling parties in accordance with Article 12 of [RTS 24 on the maintenance of relevant data relating to orders in financial instruments under Article 25 of Regulation 600/2014 EU]." (quoted text from RTS 22). "Uniqueness" may be defined per relevant regulations.
6	ReportTrackingNumber	Report tracking number. In the context of EMIR Refit this is a "unique code assigned to the execution of an order and common for a group of reports related to the same execution" (see Q28 in <a href="https://www.esma.europa.eu/sites/default/files/library/esma74-362-2281_final_report_guidelines_emir_refit.pdf">https://www.esma.europa.eu/sites/default/files/library/esma74-362-2281_final_report_guidelines_emir_refit.pdf</a> ). Also referred to as the RTN.

Used in groups: **AllocRegulatoryTradeIDGrp**

**180.2.137 AllocRejCode**

Identifies reason for rejection.

Type: **int**

Allowed values in AllocRejCodeCodeSet:

Code	Name	Description
0	UnknownAccount	Unknown or missing account(s)
1	IncorrectQuantity	Incorrect or missing block quantity
2	IncorrectAveragePrice	Incorrect or missing average price
3	UnknownExecutingBrokerMnemonic	Unknown executing broker mnemonic
4	CommissionDifference	Incorrect or missing commission
5	UnknownOrderID	Unknown OrderID(37)
6	UnknownListID	Unknown ListID(66)
7	OtherSeeText	Other (further in Text (58))
8	IncorrectAllocatedQuantity	Incorrect or missing allocated quantity
9	CalculationDifference	Calculation difference
10	UnknownOrStaleExecID	Unknown or Stale ExecID(17)
11	MismatchedData	Mismatched data
12	UnknownClOrdID	Unknown ClOrdID(11)
13	WarehouseRequestRejected	Warehouse request rejected
14	DuplicateOrMissingIndividualAllocID	Duplicate or missing IndividualAllocID(467)
15	TradeNotRecognized	Trade not recognized
16	DuplicateTrade	Trade previously allocated
17	IncorrectOrMissingInstrument	Incorrect or missing instrument
18	IncorrectOrMissingSettlDate	Incorrect or missing settlement date
19	IncorrectOrMissingFundIDOrFund-Name	Incorrect or missing fund ID or fund name
20	IncorrectOrMissingSettlInstructions	Incorrect or missing settlement instructions
21	IncorrectOrMissingFees	Incorrect or missing fees
22	IncorrectOrMissingTax	Incorrect or missing tax
23	UnknownOrMissingParty	Unknown or missing party
24	IncorrectOrMissingSide	Incorrect or missing side
25	IncorrectOrMissingNetMoney	Incorrect or missing net-money
26	IncorrectOrMissingTradeDate	Incorrect or missing trade date
27	IncorrectOrMissingSettlCcyInstructions	Incorrect or missing settlement currency instructions
28	IncorrectOrMissingProcessCode	Incorrect or missing ProcessCode(81)
99	Other	Other. Use Text(58) for further reject reasons.



Used in messages: [AllocationInstructionAck](#), [AllocationReport](#), [AllocationReportAck](#)

#### **180.2.138 AllocReportID**

Unique identifier for Allocation Report message.

Type: [String](#)

Used in messages: [AllocationReport](#), [AllocationReportAck](#)

#### **180.2.139 AllocReportRefID**

Reference identifier to be used with AllocTransType (7) = Replace or Cancel

Type: [String](#)

Used in messages: [AllocationReport](#)

#### **180.2.140 AllocReportType**

Describes the specific type or purpose of an Allocation Report message

Type: [int](#)

Allowed values in AllocReportTypeCodeSet:

Code	Name	Description
2	PreliminaryRequestToIntermediary	Preliminary request to intermediary
3	SellsideCalculatedUsingPreliminary	Sellside calculated using preliminary (includes MiscFees and NetMoney)
4	SellsideCalculatedWithoutPreliminary	Sellside calculated without preliminary (sent unsolicited by sellside, includes MiscFees and NetMoney)
5	WarehouseRecap	Warehouse recap
8	RequestToIntermediary	Request to intermediary
9	Accept	Accept
10	Reject	Reject
11	AcceptPending	Accept Pending
12	Complete	Complete
14	ReversePending	Reverse Pending
15	Giveup	Give-up

Code	Name	Description
16	Takeup	Take-up
17	Reversal	Reversal
18	Alleged	Alleged reversal
19	SubAllocationGiveup	Sub-allocation give-up

Used in messages: [AllocationReport](#), [AllocationReportAck](#)

#### **180.2.141 AllocRequestID**

Unique identifier for the request message.

Type: [String](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAck](#), [AllocationInstructionAlert](#), [AllocationInstructionAlertRequest](#), [AllocationInstructionAlertRequestAck](#), [AllocationReport](#), [AllocationReportAck](#)

#### **180.2.142 AllocRequestStatus**

Status of the AllocationInstructionAlertRequest(35=DU).

Type: [int](#)

Allowed values in AllocRequestStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	Rejected	Rejected

Used in messages: [AllocationInstructionAlertRequestAck](#)

#### **180.2.143 AllocReversalStatus**

Identifies the status of a reversal transaction.

Type: [int](#)

Allowed values in AllocReversalStatusCodeSet:

Code	Name	Description
0	Completed	Completed
1	Refused	Refused
2	Cancelled	Cancelled

Used in messages: **AllocationReport**

#### 180.2.144 AllocRiskLimitCheckStatus

Indicates the status of the risk limit check performed on a trade for this allocation instance.

Type: **int**

Allowed values in RiskLimitCheckStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted. For use when none of the more specific status enumerations apply.
1	Rejected	Rejected. For use when none of the more specific status enumerations apply.
2	ClaimRequired	Claim required. Indicates that the clearing firm is required to accept or decline the trade.
3	PreDefinedLimitCheckSucceeded	Pre-defined limit check succeeded. Indicates a check enforced automatically by the clearing house.
4	PreDefinedLimitCheckFailed	Pre-defined limit check failed. Indicates a check enforced automatically by the clearing house.
5	PreDefinedAutoAcceptRuleInvoked	Pre-defined auto-accept rule invoked. Indicates that the clearing firm is required to accept or decline the trade because no limit or rule applies.
6	PreDefinedAutoRejectRuleInvoked	Pre-defined auto-reject rule invoked. Indicates a check enforced automatically by the clearing house. Note that clearing house rules of engagement may still require a clearing firm accept or reject the trade.
7	AcceptedByClearingFirm	Accepted by clearing firm. Indicates that explicit action by the clearing firm, and not an automatic check by the clearing house, was the basis for accepting the trade.
8	RejectedByClearingFirm	Rejected by clearing firm. Indicates that explicit action by the clearing firm, and not an automatic check by the clearing house, was the basis for rejecting the trade.

Code	Name	Description
9	Pending	Pending. Indicates that one or more side level risk checks are in progress.
10	AcceptedByCreditHub	Accepted by credit hub. Indicates that a credit hub accepted the trade. An identifier assigned by the credit hub may appear in the appropriate RefRiskLimitCheckID(2334) field.
11	RejectedByCreditHub	Rejected by credit hub. Indicates that a credit hub rejected the trade.
12	PendingCreditHubCheck	Pending credit hub check. Indicates that a check is pending at a credit hub.
13	AcceptedByExecVenue	Accepted by execution venue. Indicates acceptance by an execution venue, such as a SEF.
14	RejectedByExecVenue	Rejected by execution venue. Indicates that the trade was rejected by an execution venue, such as a SEF.

Used in groups: **AllocGrp**

#### **180.2.145 AllocSettlCurrAmt**

Total amount due expressed in settlement currency (includes the effect of the forex transaction) for a specific AllocAccount (79).

Type: **Amt**

Used in groups: **AllocGrp**

#### **180.2.146 AllocSettlCurrency**

Currency code of settlement denomination for a specific AllocAccount (79).

Type: **Currency**

Used in groups: **AllocGrp**, **PreAllocGrp**, **PreAllocMlegGrp**, **TrdAllocGrp**

#### **180.2.147 AllocSettlCurrencyCodeSource**

Identifies class or source of the AllocSettlCurrency(736) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [AllocGrp](#), [PreAllocGrp](#), [PreAllocMlegGrp](#), [TrdAllocGrp](#)

#### 180.2.148 AllocSettlInstType

Used to indicate whether settlement instructions are provided on an allocation instruction message, and if not, how they are to be derived.

Type: [int](#)

Allowed values in AllocSettlInstTypeCodeSet:

Code	Name	Description
0	UseDefaultInstructions	Use default instructions
1	DeriveFromParametersProvided	Derive from parameters provided
2	FullDetailsProvided	Full details provided
3	SSIDBIDsProvided	SSI DB IDs provided
4	PhoneForInstructions	Phone for instructions

Used in groups: [AllocGrp](#)

#### 180.2.149 AllocStatus

Identifies status of allocation.

Type: [int](#)

Allowed values in AllocStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted (successfully processed)
1	BlockLevelReject	Block level reject
2	AccountLevelReject	Account level reject
3	Received	Received (received not yet processed)
4	Incomplete	Incomplete
5	RejectedByIntermediary	Rejected by intermediary
6	AllocationPending	Allocation pending
7	Reversed	Reversed
8	CancelledByIntermediary	Cancelled by intermediary.
9	Claimed	Claimed
10	Refused	Refused
11	PendingGiveUpApproval	Pending give-up approval
12	Cancelled	Cancelled
13	PendingTakeUpApproval	Pending take-up approval
14	ReversalPending	Reversal pending

Used in messages: [AllocationInstructionAck](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Allocation-ReportAck](#)

#### **180.2.150 AllocText**

Free format text related to a specific AllocAccount (79).

Type: [String](#)

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [TrdAllocGrp](#)

#### **180.2.151 AllocTransType**

Identifies allocation transaction type \*\*\* SOME VALUES HAVE BEEN REPLACED - See "Replaced Features and Supported Approach" \*\*\*

Type: [char](#)

Allowed values in AllocTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Replace	Replace
2	Cancel	Cancel
6	Reversal	Reversal

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#)

#### 180.2.152 AllocTrdRegTimestamp

Same as TrdRegTimestamp(769). Used to provide relevant timestamp for the allocation account.

Type: [UTCTimestamp](#)

Used in groups: [AllocTrdRegTimestamps](#)

#### 180.2.153 AllocTrdRegTimestamps

The AllocTrdRegTimestamps component block is used to convey trading or regulatory timestamps associated with an allocation for one account.

Name	Mult.	Type	Description
<a href="#">NoAllocTrdRegTimestamps</a>	[1..1]	NumInGroup	
<a href="#">AllocTrdRegTimestamp</a>	[0..1]	UTCTimestamp	Required if NoAllocTrdRegTimestamps(3008) > 0.
<a href="#">AllocTrdRegTimestampType</a>	[0..1]	CodeSet	Required if NoAllocTrdRegTimestamps(3008) > 0.
<a href="#">AllocTrdRegTimestampSrc</a>	[0..1]	String	

Used in groups: [AllocGrp](#)

#### 180.2.154 AllocTrdRegTimestampSrc

Same as TrdRegTimestampOrigin(771). Used to indicate the "origin" or source of the timestamp relevant for the allocation account.

Type: [String](#)

Used in groups: [AllocTrdRegTimestamps](#)

**180.2.155 AllocTrdRegTimestampType**

Same as TrdRegTimestampType(770). Used to indicate the timestamp type relevant for the allocation account.

Type: **int**

Allowed values in TrdRegTimestampTypeCodeSet:

Code	Name	Description
1	ExecutionTime	Execution time. Timestamp for the order execution. In the context of US futures markets (CFTC regulated) this is the non-qualified reporting time of order execution.
2	TimeIn	Time in. Timestamp for receiving an order, quote or trade. In the context of US futures markets (CFTC) this is the timestamp of when the order was received on the trading floor (booth).
3	TimeOut	Time out. Timestamp for sending an order, quote or trade. In the context of US futures markets (CFTC) this is the timestamp when the trade was received from the pit.
4	BrokerReceipt	Broker receipt. Timestamp for a broker receiving an order, quote or trade. In the context of US futures markets (CFTC) this is the time at which the broker received the order.
5	BrokerExecution	Broker execution. Timestamp for the broker executing an order. In the context of US futures markets (CFTC regulated) this is the time at which a broker executed the order for another broker.
6	DeskReceipt	Desk receipt. Timestamp for the transmission of an order to an internal desk or department on the same day the firm received the order.
7	SubmissionToClearing	Submission to clearing. The timestamp when the trade was officially acknowledged by the Clearing House.
8	TimePriority	Time priority. A timestamp (manually or electronically) assigned by a market to specify time priority for an order or quote.
9	OrderbookEntryTime	Orderbook entry time. Timestamp for an order representing the time it was entered in the orderbook of the execution venue. The orderbook entry time cannot change during the lifetime of the order.
10	OrderSubmissionTime	Order submission time. Time the order was sent by the submitter.
11	PubliclyReported	Publicly reported. In the context of MiFID II, this is used to identify the time at which the transaction was first published to the market.



Code	Name	Description
12	PublicReportUpdated	Public report updated. In the context of MiFID II, this is used to identify the time at which the transaction's publication to the market was last updated
13	NonPubliclyReported	Non-publicly reported
14	NonPublicReportUpdated	Non-public report updated
15	SubmittedForConfirmation	Submitted for confirmation
16	UpdatedForConfirmation	Updated for confirmation
17	Confirmed	Confirmed
18	UpdatedForClearing	Updated for clearing
19	Cleared	Cleared
20	AllocationsSubmitted	Allocations submitted
21	AllocationsUpdated	Allocations updated
22	AllocationsCompleted	Allocations completed
23	SubmittedToRepository	Submitted to repository
24	PostTrdContntnEvtnt	Post-trade continuation event
25	PostTradeValuation	Post-trade valuation
26	PreviousTimePriority	Previous time priority. Can be used in conjunction with TrdRegTimestampType(770) = 8 (Time priority) to provide the current and last priority timestamp in a single message.
27	IdentifierAssigned	Identifier assigned. Timestamp for the assignment of a (unique) identifier to an entity (e.g. order, quote, trade).
28	PreviousIdentifierAssigned	Previous identifier assigned. Timestamp of previous assignment of a (unique) identifier to an entity (e.g. order, quote, trade).
29	OrderCancellationTime	Order cancellation time. Timestamp for the cancellation of an order or quote.
30	OrderModificationTime	Order modification time. Timestamp for the modification of an order or quote.
31	OrderRoutingTime	Order routing time. Timestamp for the routing of an order to another broker or electronic execution venue.
32	TradeCancellationTime	Trade cancellation time. Timestamp for the cancellation of an execution (ExecType(150) = H (Trade Cancel)) or trade (TradeReportType(856) = 6 (Trade Report Cancel)).
33	TradeModificationTime	Trade modification time. Timestamp for the modification of an execution (ExecType(150) = G (Trade Correct)) or trade (TradeReportType(856) = 5 (No/Was)).
34	ReferenceTimeForNBBO	Reference time for NBBO. Timestamp for an NBBO reference price.

Code	Name	Description
35	Affirmed	Affirmed

Used in groups: [AllocTrdRegTimestamps](#)

### 180.2.156 AllocType

Describes the specific type or purpose of an Allocation message (i.e. "Buyside Calculated")  
(see Volume : "Glossary" for value definitions)

\*\*\* SOME VALUES HAVE BEEN REPLACED - See "Replaced Features and Supported Approach" \*\*\*

Type: [int](#)

Allowed values in AllocTypeCodeSet:

Code	Name	Description
1	Calculated	Calculated (includes MiscFees and NetMoney)
2	Preliminary	Preliminary (without MiscFees and NetMoney)
5	ReadyToBook	Ready-To-Book
7	WarehouseInstruction	Warehouse instruction
8	RequestToIntermediary	Request to intermediary
9	Accept	Accept
10	Reject	Reject
11	AcceptPending	Accept Pending
12	IncompleteGroup	Incomplete group
13	CompleteGroup	Complete group
14	ReversalPending	Reversal Pending
15	ReopenGroup	Reopen group
16	CancelGroup	Cancel group
17	Giveup	Give-up
18	Takeup	Take-up
19	RefuseTakeup	Refuse take-up
20	InitiateReversal	Initiate reversal
21	Reverse	Reverse
22	RefuseReversal	Refuse reversal

Code	Name	Description
23	SubAllocationGiveup	Sub-allocation give-up
24	ApproveGiveup	Approve give-up
25	ApproveTakeup	Approve take-up
26	NotionalValueAveragePxGroupAlloc	Notional value average price group allocation. Used when conducting notional value average price (NVAP) group allocation with a clearinghouse.

Used in messages: [AllocationInstruction](#), [AllocationInstructionAck](#), [AllocationInstructionAlert](#)

#### **180.2.157 AllowableOneSidednessCurr**

The currency that AllowableOneSidednessValue (766) is expressed in if AllowableOneSidednessValue is used.

Type: [Currency](#)

Used in messages: [NewOrderList](#)

#### **180.2.158 AllowableOneSidednessPct**

The maximum percentage that execution of one side of a program trade can exceed execution of the other.

Type: [Percentage](#)

Used in messages: [NewOrderList](#)

#### **180.2.159 AllowableOneSidednessValue**

The maximum amount that execution of one side of a program trade can exceed execution of the other.

Type: [Amt](#)

Used in messages: [NewOrderList](#)

#### **180.2.160 AltMDSourceID**

Session layer source for market data

(For the standard FIX session layer, this would be the TargetCompID (56) where market data can be obtained).

Type: **String**

Used in groups: **MDRjctGrp**

#### **180.2.161 AnnualTradingBusinessDays**

Number of trading business days in a year.

Type: **int**

Used in components: **MDStatisticParameters**

Used in groups: **ClearingPriceParametersGrp**

#### **180.2.162 AnonymousTradeIndicator**

Indicates whether the trade or transaction was executed anonymously.

Type: **Boolean**

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **ExecutionReport**, **TradeCaptureReport**

#### **180.2.163 ApplBegSeqNum**

Beginning range of application sequence numbers

Type: **SeqNum**

Used in groups: **ApplIDRequestAckGrp**, **ApplIDRequestGrp**

#### **180.2.164 ApplEndSeqNum**

Ending range of application sequence numbers

Type: **SeqNum**

Used in groups: **ApplIDRequestAckGrp**, **ApplIDRequestGrp**

**180.2.165 ApplExtID**

The extension pack number associated with an application message.

Type: **int**

Used in components: **StandardHeader**

**180.2.166 ApplicationSequenceControl**

The ApplicationSequenceControl is used for application sequencing and recovery. Consisting of ApplSeqNum (1181), ApplID (1180), ApplLastSeqNum (1350), and ApplResendFlag (1352), FIX application messages that carries this component block will be able to use application level sequencing. ApplID, ApplSeqNum and ApplLastSeqNum fields identify the application id, application sequence number and the previous application sequence number (in case of intentional gaps) on each application message that carries this block.

Name	Mult.	Type	Description
ApplID	[0..1]	String	Identifies the application with which a message is associated. Used only if application sequencing is in effect.
ApplSeqNum	[0..1]	SeqNum	Application sequence number assigned to the message by the application generating the message. Used only if application sequencing is in effect. Conditionally required if ApplID has been specified.
ApplLastSeqNum	[0..1]	SeqNum	The previous sequence number in the application sequence stream. Permits an application to publish messages with sequence gaps where it cannot be avoided. Used only if application sequencing is in effect. Conditionally required if ApplID has been specified
ApplResendFlag	[0..1]	Boolean	Used to indicate that a message is being sent in response to an Application Message Request. Used only if application sequencing is in effect. It is possible for both ApplResendFlag and PossDupFlag to be set on the same message if the Sender's cache size is greater than zero and the message is being resent due to a session level resend request.

Used in messages: **AccountSummaryReport**, **AssignmentReport**, **ContraryIntentionReport**, **Deriva-**

tiveSecurityList, DerivativeSecurityListUpdateReport, ExecutionReport, IOI, MarginRequirementReport, MarketDataIncrementalRefresh, MarketDataReport, MarketDataSnapshotFullRefresh, MarketDataStatisticsReport, MarketDefinition, MarketDefinitionUpdateReport, MassOrderAck, News, PartyDetailsListReport, PartyDetailsListUpdateReport, PartyEntitlementsReport, PartyEntitlementsUpdateReport, PartyRiskLimitsReport, PartyRiskLimitsUpdateReport, PositionReport, SecurityDefinition, SecurityDefinitionUpdateReport, SecurityList, SecurityListUpdateReport, SecurityMassStatus, SecurityStatus, SecurityTypes, SettlementObligationReport, TradeCaptureReport, TradeMatchReport, TradeMatchReportAck, TradingSessionList, TradingSessionListUpdateReport, TradingSessionStatus

### 180.2.167 ApplID

Identifies the application with which a message is associated. Used only if application sequencing is in effect.

Type: **String**

Used in components: **ApplicationSequenceControl**

### 180.2.168 ApplIDReportGrp

Name	Mult.	Type	Description
NoApplIDs	[1..1]	NumInGroup	Number of applications
RefApplID	[0..1]	String	
ApplNewSeqNum	[0..1]	SeqNum	
RefApplLastSeqNum	[0..1]	SeqNum	

Used in messages: **ApplicationMessageReport**

### 180.2.169 ApplIDRequestAckGrp

Name	Mult.	Type	Description
NoApplIDs	[1..1]	NumInGroup	Number of applications
RefApplID	[0..1]	String	
RefApplReqID	[0..1]	String	
ApplBegSeqNum	[0..1]	SeqNum	

Name	Mult.	Type	Description
ApplEndSeqNum	[0..1]	SeqNum	
RefApplLastSeqNum	[0..1]	SeqNum	
ApplResponseError	[0..1]	CodeSet	
NestedParties	[0..*]	Group	

Used in messages: [ApplicationMessageRequestAck](#)

#### 180.2.170 ApplIDRequestGrp

Name	Mult.	Type	Description
NoApplIDs	[1..1]	NumInGroup	Specifies number of application id occurrences
RefApplID	[0..1]	String	
RefApplReqID	[0..1]	String	
ApplBegSeqNum	[0..1]	SeqNum	Message sequence number of first message in range to be resent
ApplEndSeqNum	[0..1]	SeqNum	Message sequence number of last message in range to be resent. If request is for a single message ApplBeginSeqNo = ApplEndSeqNo. If request is for all messages subsequent to a particular message, ApplEndSeqNo = "0" (representing infinity).
NestedParties	[0..*]	Group	

Used in messages: [ApplicationMessageRequest](#)

#### 180.2.171 ApplLastSeqNum

Application sequence number of last message in transmission

Type: [SeqNum](#)

Used in components: [ApplicationSequenceControl](#)

#### 180.2.172 ApplNewSeqNum

Used to specify a new application sequence number.

Type: **SeqNum**

Used in groups: **ApplIDReportGrp**

### **180.2.173 ApplQueueAction**

Action to take to resolve an application message queue (backlog).

Type: **int**

Allowed values in ApplQueueActionCodeSet:

Code	Name	Description
0	NoActionTaken	No Action Taken
1	QueueFlushed	Queue Flushed
2	OverlayLast	Overlay Last
3	EndSession	End Session

Used in messages: **MarketDataRequest**

### **180.2.174 ApplQueueDepth**

Current number of application messages that were queued at the time that the message was created by the counterparty.

Type: **int**

Used in messages: **MarketDataIncrementalRefresh**, **MarketDataSnapshotFullRefresh**

### **180.2.175 ApplQueueMax**

Used to specify the maximum number of application messages that can be queued before a corrective action needs to take place to resolve the queuing issue.

Type: **int**

Used in messages: **MarketDataRequest**



**180.2.176 ApplQueueResolution**

Resolution taken when ApplQueueDepth (813) exceeds ApplQueueMax (812) or system specified maximum queue size.

Type: **int**

Allowed values in ApplQueueResolutionCodeSet:

Code	Name	Description
0	NoActionTaken	No Action Taken
1	QueueFlushed	Queue Flushed
2	OverlayLast	Overlay Last
3	EndSession	End Session

Used in messages: **MarketDataIncrementalRefresh**, **MarketDataSnapshotFullRefresh**

**180.2.177 ApplReportID**

Identifier for the Application Sequence Reset

Type: **String**

Used in messages: **ApplicationMessageReport**

**180.2.178 ApplReportType**

Type of report

Type: **int**

Allowed values in ApplReportTypeCodeSet:

Code	Name	Description
0	ApplSeqNumReset	Reset ApplSeqNum to new value specified in ApplNewSeqNum(1399)
1	LastMessageSent	Reports that the last message has been sent for the ApplIDs Refer to RefApplLastSeqNum(1357) for the application sequence number of the last message.

Code	Name	Description
2	ApplicationAlive	Heartbeat message indicating that Application identified by RefApplID(1355) is still alive. Refer to RefApplLastSeqNum(1357) for the application sequence number of the previous message.
3	ResendComplete	Application message re-send completed.

Used in messages: [ApplicationMessageReport](#)

### 180.2.179 ApplReqID

Unique identifier for request

Type: [String](#)

Used in messages: [ApplicationMessageReport](#), [ApplicationMessageRequest](#), [ApplicationMessageRequestAck](#)

### 180.2.180 ApplReqType

Type of Application Message Request being made.

Type: [int](#)

Allowed values in ApplReqTypeCodeSet:

Code	Name	Description
0	Retransmission	Retransmission of application messages for the specified Applications
1	Subscription	Subscription to the specified Applications
2	RequestLastSeqNum	Request for the last ApplLastSeqNum published for the specified Applications
3	RequestApplications	Request valid set of Applications
4	Unsubscribe	Unsubscribe to the specified Applications
5	CancelRetransmission	Cancel retransmission
6	CancelRetransmissionUnsubscribe	Cancel retransmission and unsubscribe to the specified applications

Used in messages: [ApplicationMessageRequest](#), [ApplicationMessageRequestAck](#)

**180.2.181 ApplResendFlag**

Used to indicate that a message is being sent in response to an Application Message Request. It is possible for both ApplResendFlag and PossDupFlag to be set on the same message if the Sender's cache size is greater than zero and the message is being resent due to a session level resend request

Type: **Boolean**

Used in components: **ApplicationSequenceControl**

**180.2.182 ApplResponseError**

Used to return an error code or text associated with a response to an Application Request.

Type: **int**

Allowed values in ApplResponseErrorCodeSet:

Code	Name	Description
0	ApplicationDoesNotExist	Application does not exist
1	MessagesRequestedAreNotAvailable	Messages requested are not available
2	UserNotAuthorizedForApplication	User not authorized for application

Used in groups: **ApplIDRequestAckGrp**

**180.2.183 ApplResponseID**

Identifier for the Applicaton Message Request Ack

Type: **String**

Used in messages: **ApplicationMessageRequestAck**

**180.2.184 ApplResponseType**

Used to indicate the type of acknowledgement being sent.

Type: **int**

Allowed values in ApplResponseTypeCodeSet:

Code	Name	Description
0	RequestSuccessfullyProcessed	Request successfully processed
1	ApplicationDoesNotExist	Application does not exist
2	MessagesNotAvailable	Messages not available

Used in messages: [ApplicationMessageRequestAck](#)

#### **180.2.185 ApplSeqNum**

Data sequence number to be used when FIX session is not in effect

Type: [SeqNum](#)

Used in components: [ApplicationSequenceControl](#)

#### **180.2.186 ApplTestMessageIndicator**

Used to indicate whether the message being sent is to test the receiving application's availability to process the message. When set to "Y" the message is a test message. If not specified, the message is by default not a test message.

Type: [Boolean](#)

Used in messages: [PartyActionReport](#), [PartyActionRequest](#)

#### **180.2.187 ApplTotalMessageCount**

Total number of messages included in transmission.

Type: [int](#)

Used in messages: [ApplicationMessageRequestAck](#)

#### **180.2.188 ApplVerID**

Specifies the application layer version being applied at the message level.

Type: [String](#)

Allowed values in ApplVerIDCodeSet:

Code	Name	Description
0	FIX27	FIX27
1	FIX30	FIX30
2	FIX40	FIX40
3	FIX41	FIX41
4	FIX42	FIX42
5	FIX43	FIX43
6	FIX44	FIX44
7	FIX50	FIX50
8	FIX50SP1	FIX50SP1
9	FIX50SP2	FIX50SP2
10	FIXLatest	FIXLatest

Used in components: [StandardHeader](#)

#### **180.2.189 ApprovalTime**

Date and time the details within the message have been approved.

Type: [UTCTimestamp](#)

Used in messages: [AlgoCertificateReport](#), [AlgoCertificateRequest](#)

#### **180.2.190 AsgnRptID**

Unique identifier for the Assignment Report

Type: [String](#)

Used in messages: [AssignmentReport](#)

#### **180.2.191 AsOfIndicator**

A trade that is being submitted for a trade date prior to the current trade or clearing date, e.g. in an open outcry market an out trade being submitted for the previous trading session or trading day.

Type: [char](#)

Allowed values in AsOfIndicatorCodeSet:

Code	Name	Description
0	False	false - trade is not an AsOf trade
1	True	true - trade is an AsOf trade

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.192 AssetAttributeGrp

The AssetAttributeGrp is a repeating subcomponent of the Instrument component used to detail attributes of the instrument asset.

Name	Mult.	Type	Description
<a href="#">NoAssetAttributes</a>	[1..1]	NumInGroup	
<a href="#">AssetAttributeType</a>	[0..1]	String	Required if NoAssetAttributes(2304) > 0.
<a href="#">AssetAttributeValue</a>	[0..1]	String	
<a href="#">AssetAttributeLimit</a>	[0..1]	String	

Used in components: [Instrument](#)

### 180.2.193 AssetAttributeLimit

Limit or lower acceptable value of the attribute.

Type: [String](#)

Used in groups: [AssetAttributeGrp](#)

### 180.2.194 AssetAttributeType

Specifies the name of the attribute.

See [http://www.fixtradingcommunity.org/codelists#Asset\\_Attribute\\_Types](http://www.fixtradingcommunity.org/codelists#Asset_Attribute_Types) for code list of applicable asset attribute types.

Type: [String](#)

Used in groups: [AssetAttributeGrp](#)

**180.2.195 AssetAttributeValue**

Specifies the value of the asset attribute.

Type: **String**

Used in groups: **AssetAttributeGrp**

**180.2.196 AssetClass**

The broad asset category for assessing risk exposure.

Type: **int**

Allowed values in AssetClassCodeSet:

Code	Name	Description
1	InterestRate	Interest rate
2	Currency	Currency
3	Credit	Credit
4	Equity	Equity
5	Commodity	Commodity
6	Other	Other
7	Cash	Cash
8	Debt	Debt
9	Fund	Fund. Such as mutual fund, collective investment vehicle, investment program, specialized account program.
10	LoanFacility	Loan facility
11	Index	Index. A main index identified as a security type, for example under EU SFTR reporting.

Used in components: **Instrument**

**180.2.197 AssetGroup**

Indicates the broad product or asset classification. May be used to provide grouping for the product taxonomy (Product(460), SecurityType(167), etc.) and/or the risk taxonomy (AssetClass(1938), AssetSubClass(1939), AssetType(1940), etc.).

Type: **int**

Allowed values in AssetGroupCodeSet:

Code	Name	Description
1	Financials	Financials. A categorization which usually includes rates, foreign exchange, credit, bonds and equity products or assets.
2	Commodities	Commodities. A categorization which usually includes hard commodities such as agricultural, metals, freight, energy products or assets.
3	AlternativeInvestments	Alternative investments. A categorization which usually includes weather, housing, and commodity indices products or assets.

Used in components: **Instrument**

### 180.2.198 AssetSubClass

The subcategory description of the asset class.

Type: **int**

Allowed values in AssetSubClassCodeSet:

Code	Name	Description
1	SingleCurrency	Single currency
2	CrossCurrency	Cross currency
3	Basket	Basket [for multi-currency]
4	SingleName	Single name
5	CreditIndex	Credit index
6	IndexTranche	Index tranche
7	CreditBasket	Credit basket
8	Exotic	Exotic
9	Common	Common
10	Preferred	Preferred
11	EquityIndex	Equity index
12	EquityBasket	Equity basket
13	Metals	Metals
14	Bullion	Bullion
15	Energy	Energy



Code	Name	Description
16	CommodityIndex	Commodity index
17	Agricultural	Agricultural
18	Environmental	Environmental
19	Freight	Freight
20	Government	Government
21	Agency	Agency
22	Corporate	Corporate
23	Financing	Financing
24	MoneyMarket	Money market
25	Mortgage	Mortgage
26	Municipal	Municipal
27	MutualFund	Mutual fund
28	CollectiveInvestmentVehicle	Collective investment vehicle
29	InvestmentProgram	Investment program. A generalized fund for major investors.
30	SpecializedAccountProgram	Specialized account program. A specialized fund setup for a particular account or group of accounts.
31	TermLoan	Term loan
32	BridgeLoan	Bridge loan
33	LetterOfCredit	Letter of credit
34	DividendIndex	Dividend index
35	StockDividend	Stock dividend
36	ExchangeTradedFund	Exchange traded fund
37	VolatilityIndex	Volatility index
38	FXCrossRates	FX cross rates
39	FXEmergingMarkets	FX emerging markets
40	FXMajors	FX Majors
41	Fertilizer	Fertilizer
42	IndustrialProduct	Industrial product
43	Inflation	Inflation
44	Paper	Paper
45	Polypropylene	Polypropylene
46	OfficialEconomicStatistics	Official economic statistics

Code	Name	Description
47	OtherC10	Other C10. Defined under MiFID II (Directive 2014/65/EU) Section C(10) of Annex I and paraphrased in ESMA RTS 2 Annex III Section 10, "Other C10" is a financial instrument "which is not a 'Freight derivative', any of the following interest rate derivatives sub-asset classes: 'Inflation multi-currency swap or cross-currency swap', a 'Future/forward on inflation multi-currency swaps or cross-currency swaps', an 'Inflation single currency swap', a 'Future/forward on inflation single currency swap' and any of the following equity derivatives sub-asset classes: a 'Volatility index option', a 'Volatility index future/forward', a swap with parameter return variance, a swap with parameter return volatility, a portfolio swap with parameter return variance, a portfolio swap with parameter return volatility".
48	Other	Other. May be used with any AssetClass(1938) values.

Used in components: **Instrument**

### 180.2.199 AssetSubType

Used to provide a more specific description of the asset specified in AssetType(1940).

See <https://www.fixtrading.org/codelists/AssetSubType> for code list of applicable values.

Type: **String**

Used in components: **Instrument**

### 180.2.200 AssetType

Used to provide more specific description of the asset specified in AssetSubClass(1939).

See <https://www.fixtrading.org/codelists/AssetType> for code list of applicable values. ISO 4721 Currency Code values are to be used when specific currency as an asset type is to be expressed.

Other values may be used by mutual agreement of the counterparties.

Type: **String**

Used in components: **Instrument**

**180.2.201 AssetValuationModel**

Identifies the model used for asset valuation or pricing calculations.

Type: **int**

Allowed values in AssetValuationModelCodeSet:

Code	Name	Description
1	BlackScholes	Black-Scholes
2	Whaley	Whaley
3	Bachelier	Bachelier
4	Kirk	Kirk
5	Curran	Curran
6	Black76	Black-76
7	Binomial	Binomial
99	OtherModel	Other model

Used in messages: **SecurityRiskMetricsReport**

**180.2.202 AssignmentMethod**

Method by which short positions are assigned to an exercise notice during exercise and assignment processing

Type: **char**

Allowed values in AssignmentMethodCodeSet:

Code	Name	Description
P	ProRata	Pro rata
R	Random	Random

Used in messages: **AssignmentReport**

**180.2.203 AssignmentUnit**

Quantity Increment used in performing assignment.

Type: **Qty**

Used in messages: **AssignmentReport**

#### **180.2.204 AttachmentClassification**

Specifies semantically the type of the attached document from a business perspective. The default classification scheme reuses the FIX standard classification scheme of a high level section (pretrade, trade, posttrade, etc.) and a category, then a specific application or document type. The expression follows {"section/category/application type"}.

The goal here is to map the attachment into the sections and categories of the FIX business messages if possible. The classification scheme can be expanded or replaced by counterparty agreement. This approach permits the introduction and reference to other business ontologies.

Example:

posttrade/confirmation/confirm

pretrade//termsheet

Type: **String**

Used in groups: **AttachmentGrp**

#### **180.2.205 AttachmentEncodingType**

The encoding type of the content provided in EncodedAttachment(2112).

Type: **int**

Allowed values in AttachmentEncodingTypeCodeSet:

Code	Name	Description
0	Base64	Base64 encoding.
1	RawBinary	Raw binary. Unencoded binary content.

Used in groups: **AttachmentGrp**

#### **180.2.206 AttachmentExternalURL**

Used to specify an external URL where the attachment can be obtained.

Type: **String**

Used in groups: **AttachmentGrp**

### 180.2.207 AttachmentGrp

The AttachmentGrp component provides the ability to attach other media type documents to a FIX message for transmission. The media type can be any of the media types (previously referred to as MIME types) that are listed by IANA ([www.iana.org](http://www.iana.org)) [RFC2046].

The AttachmentGrp is intended to be used to attach documents in other formats, such as PDF, TIFF, and Microsoft Word, for example to a FIX message.

Note when the AttachmentGrp is used within a business message, such as the TradeCaptureReport(35=AE), the attachment should supplement the data already contained in the business message. It is not intended to replace the content of the business message. The standard fields within the business message should be populated, even if they duplicate data expressed within the attachment(s).

Name	Mult.	Type	Description
NoAttachments	[1..1]	NumInGroup	
AttachmentName	[0..1]	String	Required if NoAttachments(2104) > 0.
AttachmentMediaType	[0..1]	String	Required if EncodedAttachment(2112) is present.
AttachmentClassification	[0..1]	String	
AttachmentExternalURL	[0..1]	String	Either AttachmentExternalURL(2108) or EncodedAttachment(2112) must be specified if NoAttachments(2104) > 0.
AttachmentEncodingType	[0..1]	CodeSet	Required if EncodedAttachment(2112) is present.
UnencodedAttachmentLen	[0..1]	int	
EncodedAttachmentLen	[0..1]	Length	Must be set if EncodedAttachment(2112) is specified and must immediately precede it.
EncodedAttachment	[0..1]	data	Either AttachmentExternalURL(2108) or EncodedAttachment(2112) must be specified if NoAttachments(2104) > 0.
AttachmentKeywordGrp	[0..*]	Group	

Used in messages: **Email**, **TradeCaptureReport**, **XMLnonFIX**

### 180.2.208 AttachmentKeyword

Can be used to provide data or keyword tagging of the content of the attachment.

Type: **String**

Used in groups: **AttachmentKeywordGrp**

### **180.2.209 AttachmentKeywordGrp**

The AttachmentKeywordGrp component provides a place to associate keywords with an attachment document to support the current approach of tagging to support metadata.

Name	Mult.	Type	Description
NoAttachmentKeywords	[1..1]	NumInGroup	
AttachmentKeyword	[0..1]	String	Required if NoAttachmentKeywords(2113) > 0.

Used in groups: **AttachmentGrp**

### **180.2.210 AttachmentMediaType**

The MIME media type (and optional subtype) of the attachment. The values used are those assigned, listed and maintained by IANA ([www.iana.org](http://www.iana.org)) [RFC2046]. See <http://www.iana.org/assignments/media-types/index.html> for available types.

Examples values (RFC number provided for reference here only):

"application/pdf" (see [RFC3778])

"application/msword" (for .doc files)

"multipart/signed" (see [RFC1847])

"application/vnd.openxmlformats-officedocument.wordprocessingml.document" (for .docx files)

Type: **String**

Used in groups: **AttachmentGrp**

### **180.2.211 AttachmentName**

Specifies the file name of the attachment.

Type: **String**

Used in groups: **AttachmentGrp**

**180.2.212 AttachmentPoint**

Lower bound percentage of the loss that the tranche can endure.

Type: **Percentage**

Used in components: **Instrument**

**180.2.213 AttrbGrp**

Name	Mult.	Type	Description
NoInstrAttrb	[1..1]	NumInGroup	
InstrAttrbType	[0..1]	CodeSet	
InstrAttrbValue	[0..1]	String	

Used in components: **InstrumentExtension**

**180.2.214 AuctionAllocationPct**

Percentage of matched quantity to be allocated to the submitter of the response to an auction order.

Type: **Percentage**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.215 AuctionInstruction**

Instruction related to system generated auctions, e.g. flash order auctions.

Type: **int**

Allowed values in AuctionInstructionCodeSet:

Code	Name	Description
0	AutomatedAuctionPermitted	Automatic auction permitted (default)
1	AutomatedAuctionNotPermitted	Automatic auction not permitted

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.216 AuctionType**

Type of auction order.

Type: **int**

Allowed values in AuctionTypeCodeSet:

Code	Name	Description
0	None	None
1	BlockOrderAuction	Block order auction
2	DirectedOrderAuction	Directed order auction
3	ExposureOrderAuction	Exposure order auction
4	FlashOrderAuction	Flash order auction
5	FacilitationOrderAuction	Facilitation order auction
6	SolicitationOrderAuction	Solicitation order auction
7	PriceImprovementMechanism	Price improvement mechanism (PIM)
8	DirectedOrderPriceImprovement-Mechanism	Directed Order price improvement mechanism (PIM)

Used in groups: **AuctionTypeRuleGrp**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.217 AuctionTypeProductComplex**

Identifies an entire suite of products for which the auction order type rule applies.

Type: **String**

Used in groups: **AuctionTypeRuleGrp**

**180.2.218 AuctionTypeRuleGrp**

The AuctionTypeRuleGrp component is used to specify the auction rule applicable for a given product group or complex, for example.



Name	Mult.	Type	Description
NoAuctionTypeRules	[1..1]	NumInGroup	
AuctionType	[0..1]	CodeSet	Required if NoAuctionTypeRules(2548) > 0. AuctionType(1803) = 0 (None) can be used to invalidate all auction types on the instrument level that are defined on a market segment level.
AuctionTypeProductComplex	[0..1]	String	Can be used to limit auction order type to specific product suite. Use multiple entries with the same AuctionType(1803) if multiple but not all product suites are supported.

Used in components: [TradingSessionRules](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

#### **180.2.219 AutoAcceptIndicator**

Identifies whether or not an allocation has been automatically accepted on behalf of the Carry Firm by the Clearing House.

Type: [Boolean](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#)

#### **180.2.220 AutomaticExerciseIndicator**

Indicates (when 'Y') that exercise is automatic when the strike price is crossed or the underlying trade is in the money.

Type: [Boolean](#)

Used in components: [OptionExercise](#)

#### **180.2.221 AutomaticExerciseThresholdRate**

The threshold rate for triggering automatic exercise.

Type: [float](#)

Used in components: [OptionExercise](#)

**180.2.222 AveragePriceDetail**

The AveragePriceDetail component provides average pricing details in a trade report, including the average pricing model and the start and end times of averaging period.

Name	Mult.	Type	Description
AveragePriceType	[0..1]	CodeSet	
AveragePriceStartTime	[0..1]	UTCTimestamp	Required if AveragePriceType(2763)=2 (Percent of volume average price) or 0 (Time weighted average price).
AveragePriceEndTime	[0..1]	UTCTimestamp	Required if AveragePriceType(2763)=2 (Percent of volume average price) or 0 (Time weighted average price).

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

**180.2.223 AveragePriceEndTime**

End of the time period during which price averaging occurred.

Type: [UTCTimestamp](#)

Used in components: [AveragePriceDetail](#)

**180.2.224 AveragePriceStartTime**

Start of the time period during which price averaging occurred.

Type: [UTCTimestamp](#)

Used in components: [AveragePriceDetail](#)

**180.2.225 AveragePriceType**

The average pricing model used for block trades.

Type: [int](#)

Allowed values in AveragePriceTypeCodeSet:

Code	Name	Description
0	TimeWeightedAveragePrice	Time weighted average price. TWAP is the simple average price of a security over a specified time without regard to the volume traded.
1	VolumeWeightedAveragePrice	Volume weighted average price. VWAP is the sum of the currency amount traded for all trades in the averaging group (price times quantity) divided by the total quantity.
2	PercentOfVolumeAveragePrice	Percent of volume average price. POV is the sum of the currency amount traded for all trades executed as part of an order intended to purchase a specified percentage of the total volume of an instrument, divided by the total quantity.
3	LimitOrderAveragePrice	Limit order average price. The limit order average price is the currency amount of all trades executed to fill a limit order, divided by the total quantity.

Used in components: [AveragePriceDetail](#)

#### **180.2.226 AvgForwardPoints**

The average forward points. May be a negative value.

Type: [PriceOffset](#)

Used in messages: [TradeAggregationReport](#)

#### **180.2.227 AvgParPx**

Used to express average price as percent of par (used where AvgPx field is expressed in some other way)

Type: [Price](#)

Used in components: [SettlTradeDetails](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#)

#### **180.2.228 AvgPx**

Calculated average price of all fills on this order.

For Fixed Income trades AvgPx is always expressed as percent-of-par, regardless of the PriceType (423) of LastPx (31). I.e., AvgPx will contain an average of percent-of-par values (see LastParPx (669)) for issues traded in Yield, Spread or Discount.

Type: **Price**

Used in components: **SettlTradeDetails**

Used in groups: **OrdListStatGrp**

Used in messages: **AllocationInstruction, AllocationInstructionAlert, AllocationReport, Confirmation, ExecutionAck, ExecutionReport, TradeAggregationReport, TradeAggregationRequest, TradeCaptureReport, TradeCaptureReportAck**

### **180.2.229 AvgPxGroupID**

Used by submitting firm to group trades being allocated into an average price group. The trades in average price group will be used to calculate an average price for the group.

Type: **String**

Used in groups: **TrdMatchSideGrp**

Used in messages: **AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationInstructionAlertRequest, AllocationReport, AllocationReportAck, TradeCaptureReport, TradeCaptureReportAck**

### **180.2.230 AvgPxIndicator**

Average pricing indicator.

Type: **int**

Allowed values in AvgPxIndicatorCodeSet:

Code	Name	Description
0	NoAveragePricing	No average pricing
1	Trade	Trade is part of an average price group identified by the AvgPxGroupID(1731)
2	LastTrade	Last trade of the average price group identified by the AvgPxGroupID(1731)

Code	Name	Description
3	NotionalValueAveragePxGroupTrade	Trade is part of a notional value average price group. A notional value average price (NVAP) group is effectively closed and available for allocation as long as the NVAP of the group is non-zero.
4	AveragePricedTrade	Trade is average priced

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [TrdMatchSideGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.231 AvgPxPrecision**

Indicates number of decimal places to be used for average pricing. Absence of this field indicates that default precision arranged by the broker/institution is to be used.

Type: [int](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#)

#### **180.2.232 AvgSpotRate**

The average FX spot rate.

Type: [Price](#)

Used in messages: [TradeAggregationReport](#)

#### **180.2.233 BackloadedTradeIndicator**

Indicates that the trade being reported occurred in the past and is still in effect or active.

Type: [Boolean](#)

Used in messages: [TradeCaptureReport](#)

#### **180.2.234 BaseTradingRules**

Trading rules that are applicable to a market, market segment or individual security independent of a trading session.

Name	Mult.	Type	Description
TickRules	[0..*]	Group	Specifies price tick rules for the security.
LotTypeRules	[0..*]	Group	Specifies the lot types that are valid for trading.
PriceLimits	[0..1]	Component	Specifies the price limits that are valid for trading.
PriceRangeRuleGrp	[0..*]	Group	Specifies the valid price range tables for trading.
QuoteSizeRuleGrp	[0..*]	Group	Specifies the valid quote sizes for trading.
ExpirationCycle	[0..1]	CodeSet	
TradeVolType	[0..1]	CodeSet	
MinTradeVol	[0..1]	Qty	
MaxTradeVol	[0..1]	Qty	For listed derivatives this indicates the minimum quantity necessary for an order or trade to qualify as a block trade.
MaxPriceVariation	[0..1]	float	
ImpliedMarketIndicator	[0..1]	CodeSet	
TradingCurrency	[0..1]	Currency	
TradingCurrencyCodeSource	[0..1]	CodeSet	
RoundLot	[0..1]	Qty	
MultilegModel	[0..1]	CodeSet	Used for multileg security only.
MultilegPriceMethod	[0..1]	CodeSet	Used for multileg security only.
PriceType	[0..1]	CodeSet	Defines the default price type used for trading.
FastMarketPercentage	[0..1]	Percentage	Can be used as a factor to be applied to other base trading rules during a fast market, e.g. to widen price or size ranges by the specified percentage factor.
QuoteSideIndicator	[0..1]	CodeSet	

Used in components: [SecurityTradingRules](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

### 180.2.235 BasisFeatureDate

BasisFeatureDate allows requesting firms within fixed income the ability to request an alternative yield-to-worst, -maturity, -extended or other call. This flows through the confirm process.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCDate)

Type: **LocalMktDate**

Used in messages: **ExecutionReport**

### **180.2.236 BasisFeaturePrice**

Price for BasisFeatureDate.

See BasisFeatureDate (259)

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **Price**

Used in messages: **ExecutionReport**

### **180.2.237 BasisPxType**

Code to represent the basis price type.

Type: **char**

Allowed values in BasisPxTypeCodeSet:

Code	Name	Description
2	ClosingPriceAtMorningSession	Closing price at morning session
3	ClosingPrice	Closing price
4	CurrentPrice	Current price
5	SQ	SQ
6	VWAPThroughADay	VWAP through a day
7	VWAPThroughAMorningSession	VWAP through a morning session
8	VWAPThroughAnAfternoonSession	VWAP through an afternoon session
9	VWAPThroughADayExcept	VWAP through a day except "YORI" (an opening auction)
A	VWAPThroughAMorningSessionExcept	VWAP through a morning session except "YORI" (an opening auction)
B	VWAPThroughAnAfternoonSessionExcept	VWAP through an afternoon session except "YORI" (an opening auction)
C	Strike	Strike
D	Open	Open
Z	Others	Others

Used in messages: **BidRequest**

**180.2.238 BeginSeqNo**

Message sequence number of first message in range to be resent

Type: **SeqNum**

Used in messages: **ResendRequest**

**180.2.239 BeginString**

Identifies beginning of new message and session protocol version by means of a session profile identifier (see FIX Session Layer for details). ALWAYS FIRST FIELD IN MESSAGE. (Always unencrypted).

Type: **String**

Allowed values in BeginStringCodeSet:

Code	Name	Description
FIX.4.2	FIX42	Session profile FIX.4.2
FIX.4.4	FIX44	Session profile FIX4
FIXT.1.1	FIXT11	Session profile FIXT or LFIXT. The choice between FIXT and LFIXT is subject to counterparty agreement.

Used in components: **StandardHeader**

**180.2.240 BenchmarkCurveCurrency**

Specifies currency used for benchmark curve.

BenchmarkCurveCurrencyCodeSource(2950) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in components: **SpreadOrBenchmarkCurveData**

**180.2.241 BenchmarkCurveCurrencyCodeSource**

Identifies class or source of the BenchmarkCurveCurrency(220) value.

Type: **String**



Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [SpreadOrBenchmarkCurveData](#)

#### 180.2.242 BenchmarkCurveName

Name of benchmark curve.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: [String](#)

Allowed values in BenchmarkCurveNameCodeSet:

Code	Name	Description
EONIA	EONIA	EONIA
EUREPO	EUREPO	EUREPO
Euribor	Euribor	EURIBOR (deprecated use enum EURIBOR instead). Deprecated use of EURIBOR for the enumeration.
FutureSWAP	FutureSWAP	FutureSWAP
LIBID	LIBID	LIBID
LIBOR	LIBOR	LIBOR (London Inter-Bank Offer)
MuniAAA	MuniAAA	MuniAAA
OTHER	OTHER	OTHER
Pfandbriefe	Pfandbriefe	Pfandbriefe
SONIA	SONIA	SONIA
SWAP	SWAP	SWAP
Treasury	Treasury	Treasury

Code	Name	Description
FEDEFF	FedFundRateEffective	US Federal Reserve fed funds effective rate. US Federal Reserve fed funds effective rate or the weighted average of the actual negotiated rates banks pay each other to to borrow funds.
FEDOPEN	FedOpen	US fed funds target rate. Fed funds target rate as determined by the US Federal Reserve Federal Open Market Committee.
EURIBOR	EURIBOR	Euro interbank offer rate
AUBSW	AUBSW	Australian Bank Bill Swap Rate
BUBOR	BUBOR	Budapest Bank Offered Rate
CDOR	CDOR	Canadian Dollar Offered Rate
CIBOR	CIBOR	Copenhagen Interbank Offered Rate
EONIASWAP	EONIASWAP	Euro Overnight Index Average Swap Rate
ESTR	ESTR	Euro Short Term Rate. Replaces EONIA.
EURODOLLAR	EURODOLLAR	Euro Dollar Rate
EUROSWISS	EUROSWISS	Euro Swiss Franc Rate
GCFREPO	GCFREPO	DTCC General Collateral Finance Repo Index
ISDAFIX	ISDAFIX	ICE Swap Rate
JIBAR	JIBAR	Johannesburg Interbank Agreed Rate
MOSPRIM	MOSPRIM	Moscow Prime Offered Rate
NIBOR	NIBOR	Nigeria Three Month Interbank Rate
PRIBOR	PRIBOR	Czech Republic Interbank Offered Rate
SOFR	SOFR	Secured Overnight Financing Rate. Replaces LIBOR.
STIBOR	STIBOR	Stockholm Interbank Offered Rate
TELBOR	TELBOR	Bank of Israel Interbank Offered Rate
TIBOR	TIBOR	Tokyo Interbank Offered Rate
WIBOR	WIBOR	Warsaw Interbank Offered Rate
AONIA	AONIA	Reserve Bank of Australia Interbank Overnight Cash Rate. Also known as AUD Overnight Index Average.
AONIA-R	AONIA-R	Realised AONIA. "Realised AONIA applies a compounding formula to the daily AONIA rate, to determine the compounded average rate over the prior 1 to 6 month period." (source <a href="https://www.asx.com.au/documents/products/realised-aonia-explained.pdf">https://www.asx.com.au/documents/products/realised-aonia-explained.pdf</a> ).
BKBM	BKBM	New Zealand Bank Bill Market Rate
CD91D	CD91D	Republic of Korea 90-Day Certificate of Deposit Rate

Code	Name	Description
CORRA	CORRA	Canadian Overnight Repo Rate Average
DIRR-TN	DIRRTN	Danish Interbank Interest Rate-Tomorrow or Next
EIBOR	EIBOR	Emirates Interbank Offered Rate
FixingRepoRate	FixingRepoRate	China Interbank Overnight Repo Rate
HIBOR	HIBOR	Hong Kong Interbank Offered Rate
IBR	IBR	Colombia Overnight Interbank Reference Rate
KLIBOR	KLIBOR	Kuala Lumpur Interbank Offered Rate
MIBOR	MIBOR	Mumbia Interbank Offered Rate
NZONIA	NZONIA	New Zealand Overnight Indexed Swaps (OIS)
PHIREF	PHIREF	Philippines Interbank Reference Rate
REIBOR	REIBOR	Reykjavik Interbank Offered Rate
SAIBOR	SAIBOR	Saudi Arabian Interbank Offered Rate
SARON	SARON	Swiss Average Rate Overnight
SORA	SORA	Singapore Swap Offer Rate
TLREF	TLREF	Turkish Lira Overnight Reference Rate
TIIE	TIIE	Mexico Interbank Equilibrium Interest Rate
THBFX	THBFX	Thai Baht Interest Rate Fixing
TONAR	TONAR	Tokyo Overnight Average Rate

Used in components: **SpreadOrBenchmarkCurveData**

### 180.2.243 BenchmarkCurvePoint

Point on benchmark curve. Free form values: e.g. "Y", "7Y", "INTERPOLATED".

Sample values:

M = combination of a number between 1-12 and a "M" for month

Y = combination of number between 1-100 and a "Y" for year}

10Y-OLD = see above, then add "-OLD" when appropriate

INTERPOLATED = the point is mathematically derived

2/2031 5 3/8 = the point is stated via a combination of maturity month / year and coupon

See Fixed Income-specific documentation at <http://www.fixtradingcommunity.org> for additional values.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **String**

Used in components: **SpreadOrBenchmarkCurveData**

#### **180.2.244 BenchmarkPrice**

Specifies the price of the benchmark.

Type: **Price**

Used in components: **SpreadOrBenchmarkCurveData**

#### **180.2.245 BenchmarkPriceType**

Identifies type of BenchmarkPrice (662).

See PriceType (423) for valid values.

Type: **int**

Allowed values in PriceTypeCodeSet:

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
2	PerUnit	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points spread). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	Yield	Yield
10	FixedCabinetTradePrice	Fixed cabinet trade price (primarily for listed futures and options)
11	VariableCabinetTradePrice	Variable cabinet trade price (primarily for listed futures and options)

Code	Name	Description
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example, the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)
22	BasisPoints	Basis points. When the price is not spread based.
23	UpfrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageNotional	Percentage of notional

Used in components: [SpreadOrBenchmarkCurveData](#)

#### 180.2.246 BenchmarkSecurityID

The identifier of the benchmark security, e.g. Treasury against Corporate bond.

See SecurityID (tag 48) for description and valid values.

Type: [String](#)

Used in components: [SpreadOrBenchmarkCurveData](#)

#### 180.2.247 BenchmarkSecurityIDSource

Identifies class or source of the BenchmarkSecurityID(699) value.

Required if BenchmarkSecurityID is specified.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier

Code	Name	Description
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [SpreadOrBenchmarkCurveData](#)

### 180.2.248 BidCompReqGrp

Name	Mult.	Type	Description
<a href="#">NoBidComponents</a>	[1..1]	NumInGroup	Used if BidType="Disclosed"
<a href="#">ListID</a>	[0..1]	String	Required if NoBidComponents > 0. Must be first field in repeating group.
<a href="#">Side</a>	[0..1]	CodeSet	When used in request for a "Disclosed" bid indicates that bid is required on assumption that SideValue1 is Buy or Sell. SideValue2 can be derived by inference.
<a href="#">TradingSessionID</a>	[0..1]	CodeSet	Indicates off-exchange type activities for Detail.
<a href="#">TradingSessionSubID</a>	[0..1]	CodeSet	
<a href="#">NetGrossInd</a>	[0..1]	CodeSet	Indicates Net or Gross for selling Detail.
<a href="#">SettlType</a>	[0..1]	CodeSet	
<a href="#">SettlDate</a>	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values.
<a href="#">Account</a>	[0..1]	String	
<a href="#">AcctIDSource</a>	[0..1]	CodeSet	

Used in messages: [BidRequest](#)

### 180.2.249 BidCompRspGrp

Name	Mult.	Type	Description
NoBidComponents	[1..1]	NumInGroup	Number of bid repeating groups
CommissionData	[1..1]	Component	First element Commission required if NoBidComponents > 0.
ListID	[0..1]	String	
Country	[0..1]	Country	ISO Country Code
Side	[0..1]	CodeSet	When used in response to a "Disclosed" request indicates whether SideValue1 is Buy or Sell. SideValue2 can be derived by inference.
Price	[0..1]	Price	Second element of price
PriceType	[0..1]	CodeSet	
FairValue	[0..1]	Amt	The difference between the value of a future and the value of the underlying equities after allowing for the discounted cash flows associated with the underlying stocks (E.g. Dividends etc).
NetGrossInd	[0..1]	CodeSet	Net/Gross
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values.
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: **BidResponse**

### 180.2.250 BidDescReqGrp

Name	Mult.	Type	Description
NoBidDescriptors	[1..1]	NumInGroup	Used if BidType="Non Disclosed"
BidDescriptorType	[0..1]	CodeSet	Required if NoBidDescriptors > 0. Must be first field in repeating group.



Name	Mult.	Type	Description
BidDescriptor	[0..1]	String	
SideValueInd	[0..1]	CodeSet	Refers to the SideValue1 or SideValue2. These are used as opposed to Buy or Sell so that the basket can be quoted either way as Buy or Sell.
LiquidityValue	[0..1]	Amt	Value between LiquidityPctLow and LiquidityPctHigh in Currency
LiquidityNumSecurities	[0..1]	int	Number of Securites between LiquidityPctLow and LiquidityPctHigh in Currency
LiquidityPctLow	[0..1]	Percentage	Liquidity indicator or lower limit if LiquidityNumSecurities > 1
LiquidityPctHigh	[0..1]	Percentage	Upper liquidity indicator if LiquidityNumSecurities > 1
EFPTackingError	[0..1]	Percentage	Eg Used in EFP (Exchange For Physical) trades 12%
FairValue	[0..1]	Amt	Used in EFP trades
OutsideIndexPct	[0..1]	Percentage	Used in EFP trades
ValueOfFutures	[0..1]	Amt	Used in EFP trades

Used in messages: **BidRequest**

### 180.2.251 BidDescriptor

BidDescriptor value. Usage depends upon BidDescriptorTyp (399).

If BidDescriptorType = 1

Industrials etc - Free text

If BidDescriptorType = 2

"FR" etc - ISO Country Codes

If BidDescriptorType = 3

FT00, FT250, STOX - Free text

Type: **String**

Used in groups: **BidDescReqGrp**

### 180.2.252 BidDescriptorType

Code to identify the type of BidDescriptor (400).

Type: **int**

Allowed values in BidDescriptorTypeCodeSet:

Code	Name	Description
1	Sector	Sector
2	Country	Country
3	Index	Index

Used in groups: **BidDescReqGrp**

#### **180.2.253 BidForwardPoints**

Bid F/X forward points added to spot rate. May be a negative value.

Type: **PriceOffset**

Used in groups: **QuotEntryAckGrp**, **QuotEntryGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

#### **180.2.254 BidForwardPoints2**

Bid F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value.

Type: **PriceOffset**

Used in groups: **QuotEntryAckGrp**, **QuotEntryGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

#### **180.2.255 BidID**

For bid lists, unique identifier for BidResponse(35=I) as assigned by sell-side (broker, exchange, ECN). Uniqueness must be guaranteed within a single trading day.

For quotes, unique identifier for the bid side of the quote assigned by the quote issuer.

Type: **String**

Used in messages: **BidRequest**, **BidResponse**, **ListExecute**, **NewOrderList**, **Quote**, **QuoteStatusReport**

**180.2.256 BidMDEntryID**

The market data entry identifier of the bid side of a quote

Type: **String**

Used in messages: **QuoteStatusReport**

**180.2.257 BidPx**

Bid price/rate

Type: **Price**

Used in groups: **QuotEntryAckGrp, QuotEntryGrp, SecurityRiskMetricGrp**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

**180.2.258 BidQuoteID**

Marketplace assigned quote identifier for the bid side. Can be used to indicate priority.

Type: **String**

Used in messages: **QuoteStatusReport**

**180.2.259 BidRequestTransType**

Identifies the Bid Request message type.

Type: **char**

Allowed values in BidRequestTransTypeCodeSet:

Code	Name	Description
C	Cancel	Cancel
N	New	New

Used in messages: **BidRequest**

#### **180.2.260 BidSize**

Quantity of bid

(Prior to FIX 4.2 this field was of type int)

Type: Qty

Used in groups: QuotEntryAckGrp, QuotEntryGrp

Used in messages: Quote, QuoteResponse, QuoteStatusReport

#### **180.2.261 BidSpotRate**

Bid F/X spot rate.

Type: Price

Used in groups: QuotEntryAckGrp, QuotEntryGrp

Used in messages: Quote, QuoteResponse, QuoteStatusReport

#### **180.2.262 BidSpread**

Basis points relative to a benchmark curve on the bid side, such as LIBOR, or a known security, such as 10Y US Treasury bond. The benchmark security or curve name is specified in the SpreadOrBenchmarkCurveData component.

Type: float

Used in messages: Quote

#### **180.2.263 BidSwapPoints**

The bid FX Swap points for an FX Swap. It is the "far bid forward points - near offer forward point". Value can be negative. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199

Type: PriceOffset

Used in messages: Quote

**180.2.264 BidTradeType**

Code to represent the type of trade.

(Prior to FIX 4.4 this field was named "TradeType")

Type: **char**

Allowed values in BidTradeTypeCodeSet:

Code	Name	Description
A	Agency	Agency
G	VWAPGuarantee	VWAP Guarantee
J	GuaranteedClose	Guaranteed Close
R	RiskTrade	Risk Trade

Used in messages: **BidRequest**

**180.2.265 BidType**

Code to identify the type of Bid Request.

Type: **int**

Allowed values in BidTypeCodeSet:

Code	Name	Description
1	NonDisclosed	"Non Disclosed" style (e.g. US/European)
2	Disclosed	"Disclosed" style (e.g. Japanese)
3	NoBiddingProcess	No bidding process

Used in messages: **BidRequest**, **NewOrderList**

**180.2.266 BidVolatility**

Volatility based on bid prices.

Type: **float**

Used in groups: **SecurityRiskMetricGrp**

**180.2.267 BidYield**

Bid yield

Type: **Percentage**

Used in groups: **QuotEntryAckGrp**, **QuotEntryGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

**180.2.268 BlockTradeEligibilityIndicator**

Indicates if a given instrument is eligible for block trading.

Type: **Boolean**

Used in components: **Instrument**

**180.2.269 BlockTrdAllocIndicator**

Indication that a block trade will be allocated.

Type: **int**

Allowed values in BlockTrdAllocIndicatorCodeSet:

Code	Name	Description
0	BlockToBeAllocated	Block to be allocated
1	BlockNotToBeAllocated	Block not to be allocated
2	AllocatedTrade	Allocated trade. A sub-trade of a block trade.

Used in groups: **TrdCapRptSideGrp**

**180.2.270 BodyLength**

Message length, in bytes, forward to the CheckSum field. ALWAYS SECOND FIELD IN MESSAGE. (Always unencrypted)

Type: **Length**

Used in components: **StandardHeader**

**180.2.271 BookingRefID**

Common reference passed to a post-trade booking process (e.g. industry matching utility).

Type: **String**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**

**180.2.272 BookingType**

Method for booking out this order. Used when notifying a broker that an order to be settled by that broker is to be booked out as an OTC derivative (e.g. CFD or similar).

Type: **int**

Allowed values in BookingTypeCodeSet:

Code	Name	Description
0	RegularBooking	Regular booking
1	CFD	CFD (Contract for difference)
2	TotalReturnSwap	Total Return Swap

Used in components: **TradeReportOrderDetail**

Used in groups: **ListOrdGrp**, **QuotEntryAckGrp**, **QuotEntryGrp**, **SideCrossOrdModGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **Quote**, **QuoteRequest**, **QuoteStatusReport**

**180.2.273 BookingUnit**

Indicates what constitutes a bookable unit.

Type: **char**

Allowed values in BookingUnitCodeSet:

Code	Name	Description
0	EachPartialExecutionIsABookableUnit	Each partial execution is a bookable unit

Code	Name	Description
1	AggregatePartialExecutionsOn-ThisOrder	Aggregate partial executions on this order, and book one trade per order
2	AggregateExecutionsForThisSymbol	Aggregate executions for this symbol, side, and settlement date

Used in groups: [ListOrdGrp](#), [SideCrossOrdModGrp](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

#### 180.2.274 BrokerConfirmationDesc

Describes the type of broker confirmation executed between the parties. Can be used as an alternative to MasterConfirmationDesc(1962). See <http://www.fpml.org/coding-scheme/broker-confirmation-type> for values.

Type: [String](#)

Used in components: [FinancingDetails](#)

#### 180.2.275 BusinessCenter

A business center whose calendar is used for date adjustment, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [BusinessCenterGrp](#)

#### 180.2.276 BusinessCenterGrp

BusinessCenterGrp is a repeating subcomponent within the DateAdjustment component. It is used to specify the set of business centers whose calendars drive the date adjustment. The business centers defined here apply to all adjustable dates in the instrument unless specifically overridden in the respective specified components elsewhere.

Name	Mult.	Type	Description
<a href="#">NoBusinessCenters</a>	[1..1]	NumInGroup	



Name	Mult.	Type	Description
BusinessCenter	[0..1]	String	Required if NoBusinessCenters(40278) > 0.

Used in components: [DateAdjustment](#)

### 180.2.277 BusinessDayConvention

The business day convention used for adjusting dates. The value defined here applies to all adjustable dates in the instrument unless specifically overridden.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [DateAdjustment](#)

### 180.2.278 BusinessDayType

Relative identification of a business day.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)

Code	Name	Description
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [ClearingPriceParametersGrp](#)

### 180.2.279 BusinessRejectReason

Code to identify reason for a Business Message Reject message.

Type: [int](#)

Allowed values in BusinessRejectReasonCodeSet:

Code	Name	Description
0	Other	Other
1	UnknownID	Unknown ID
2	UnknownSecurity	Unknown Security
3	UnsupportedMessageType	Unsupported Message Type
4	ApplicationNotAvailable	Application not available
5	ConditionallyRequiredFieldMissing	Conditionally required field missing
6	NotAuthorized	Not Authorized
7	DeliverToFirmNotAvailableAtThis-Time	DeliverTo firm not available at this time
8	ThrottleLimitExceeded	Throttle limit exceeded
9	ThrottleLimitExceededSessionDis-connected	Throttle limit exceeded, session will be disconnected
10	ThrottledMessagesRejectedOnRe-quest	Throttled messages rejected on request
18	InvalidPriceIncrement	Invalid price increment

Used in messages: [BusinessMessageReject](#)

**180.2.280 BusinessRejectRefID**

The value of the business-level "ID" field on the message being referenced.

Type: **String**

Used in messages: **BusinessMessageReject**

**180.2.281 BuyVolume**

Quantity bought.

Type: **Qty**

Used in messages: **SecurityStatus**

**180.2.282 CalculatedCcyLastQty**

Used for the calculated quantity of the other side of the currency trade. Can be derived from LastQty and LastPx.

Type: **Qty**

Used in messages: **ExecutionReport**, **TradeCaptureReport**, **TradeCaptureReportAck**

**180.2.283 CalculationMethod**

Specifies how the calculation will be made.

Type: **int**

Allowed values in CalculationMethodCodeSet:

Code	Name	Description
0	Automatic	Automatic (default).
1	Manual	Manual.

Used in groups: **ClearingPriceParametersGrp**

**180.2.284 CancellationRights**

For CIV - A one character code identifying whether Cancellation rights/Cooling off period applies.

Type: **char**

Allowed values in CancellationRightsCodeSet:

Code	Name	Description
Y	Yes	Yes
N	NoExecutionOnly	No - Execution Only
M	NoWaiverAgreement	No - Waiver agreement
O	NoInstitutional	No - Institutional

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderList**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.285 CancelText**

Identifies the reason for cancelation.

Type: **String**

Used in messages: **PayManagementRequest**

**180.2.286 CapPrice**

Used to express the ceiling price of a capped call

Type: **Price**

Used in components: **Instrument**

**180.2.287 CardExpDate**

The expiry date of the payment card as specified on the card being used for payment.

Type: **LocalMktDate**

Used in groups: **SettlInstGrp**

#### **180.2.288 CardHolderName**

The name of the payment card holder as specified on the card being used for payment.

Type: **String**

Used in groups: **SettlInstGrp**

#### **180.2.289 CardIssNum**

The issue number of the payment card as specified on the card being used for payment. This is only applicable to certain types of card.

Type: **String**

Used in groups: **SettlInstGrp**

#### **180.2.290 CardNumber**

The number of the payment card as specified on the card being used for payment.

Type: **String**

Used in groups: **SettlInstGrp**

#### **180.2.291 CardStartDate**

The start date of the card as specified on the card being used for payment.

Type: **LocalMktDate**

Used in groups: **SettlInstGrp**

#### **180.2.292 CashDistribAgentAcctName**

Name of account at agent bank for distributions.

Type: **String**

Used in groups: **RgstDistInstGrp**

#### **180.2.293 CashDistribAgentAcctNumber**

Account number at agent bank for distributions.

Type: **String**

Used in groups: **RgstDistInstGrp**

#### **180.2.294 CashDistribAgentCode**

BIC (Bank Identification Code–Swift managed) code of agent bank for cash distributions

Type: **String**

Used in groups: **RgstDistInstGrp**

#### **180.2.295 CashDistribAgentName**

Name of local agent bank if for cash distributions

Type: **String**

Used in groups: **RgstDistInstGrp**

#### **180.2.296 CashDistribCurr**

Specifies currency to be used for Cash Distributions see "Appendix 6-A Valid Currency Codes".

Type: **Currency**

Used in groups: **RgstDistInstGrp**

#### **180.2.297 CashDistribPayRef**

Free format Payment reference to assist with reconciliation of distributions.

Type: **String**

Used in groups: **RgstDistInstGrp**

**180.2.298 CashMargin**

Identifies whether an order is a margin order or a non-margin order. This is primarily used when sending orders to Japanese exchanges to indicate sell margin or buy to cover. The same tag could be assigned also by buy-side to indicate the intent to sell or buy margin and the sell-side to accept or reject (base on some validation criteria) the margin request.

Type: **char**

Allowed values in CashMarginCodeSet:

Code	Name	Description
1	Cash	Cash
2	MarginOpen	Margin Open
3	MarginClose	Margin Close

Used in groups: **ListOrdGrp**, **SideCrossOrdModGrp**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.299 CashOrderQty**

Specifies the approximate order quantity desired in total monetary units vs. as tradeable units (e.g. number of shares). The broker or fund manager (for CIV orders) would be responsible for converting and calculating a tradeable unit (e.g. share) quantity (OrderQty (38)) based upon this amount to be used for the actual order and subsequent messages.

Type: **Qty**

Used in components: **OrderQtyData**

**180.2.300 CashOutstanding**

Starting consideration less repayments

Type: **Amt**

Used in messages: **CollateralAssignment**, **CollateralInquiry**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**

**180.2.301 CashSettlAccruedInterestIndicator**

Indicates whether accrued interest is included or not in the value provided in CashSettlAmount(40034). For cash settlement this specifies whether quotations should be obtained inclusive or not of accrued interest.

For physical settlement this specifies whether the buyer should deliver the obligation with an outstanding principal balance that includes or excludes accrued interest.

Type: **Boolean**

Used in groups: **CashSettlTermGrp**

**180.2.302 CashSettlAmount**

The amount paid between the trade parties, seller to the buyer, for cash settlement on the cash settlement date.

Type: **Amt**

Used in groups: **CashSettlTermGrp**

**180.2.303 CashSettlBusinessCenter**

Identifies the business center calendar used at valuation time for cash settlement purposes e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **CashSettlTermGrp**

**180.2.304 CashSettlBusinessDays**

The number of business days used in the determination of the cash settlement payment date.

Type: **int**

Used in groups: **CashSettlTermGrp**

**180.2.305 CashSettlCurrency**

Specifies the currency the CashSettlAmount(40034) is denominated in. Uses ISO 4217 currency codes.



Type: **Currency**

Used in groups: **CashSettlTermGrp**

### **180.2.306 CashSettlDateAdjusted**

The adjusted cash settlement date.

Type: **LocalMktDate**

Used in components: **CashSettlDate**

### **180.2.307 CashSettlDateBusinessCenter**

The business center calendar used for date adjustment of the cash settlement unadjusted or relative date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **CashSettlDateBusinessCenterGrp**

### **180.2.308 CashSettlDateBusinessCenterGrp**

CashSettlDateBusinessCenterGrp is a repeating subcomponent within the CashSettlDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component within the Instrument component.

Name	Mult.	Type	Description
<b>NoCashSettlDateBusinessCenters</b>	[1..1]	NumInGroup	
<b>CashSettlDateBusinessCenter</b>	[0..1]	String	Required if NoCashSettlDateBusinessCenters(42214) > 0.

Used in components: **CashSettlDate**

### 180.2.309 CashSettlDateBusinessDayConvention

The business day convention used to adjust the cash settlement provision's date. Used only to override the business day convention defined in the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **CashSettlDate**

### 180.2.310 CashSettlDate

The CashSettlDate component is a subcomponent within the CashSettlTermGrp component used to report the cash settlement date defined in the settlement provision.

Name	Mult.	Type	Description
<b>CashSettlDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>CashSettlDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in the Instrument component. The specified value would be specific to this instance of the cash settlement provision.
<b>CashSettlDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in the Instrument component. The specified values would be specific to this instance of the cash settlement provision.
<b>CashSettlDateRelativeTo</b>	[0..1]	int	

Name	Mult.	Type	Description
CashSettlDateOffsetPeriod	[0..1]	int	Conditionally required when CashSettlDateOffsetUnit(42211) is specified.
CashSettlDateOffsetUnit	[0..1]	CodeSet	Conditionally required when CashSettlDateOffsetPeriod(42210) is specified.
CashSettlDateOffsetDayType	[0..1]	CodeSet	
CashSettlDateAdjusted	[0..1]	LocalMktDate	

Used in groups: [CashSettlTermGrp](#)

### 180.2.311 CashSettlDateOffsetDayType

Specifies the day type of the relative cash settlement date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [CashSettlDate](#)

### 180.2.312 CashSettlDateOffsetPeriod

Time unit multiplier for the relative cash settlement date offset.

Type: [int](#)

Used in components: [CashSettlDate](#)

**180.2.313 CashSettlDateOffsetUnit**

Time unit associated with the relative cash settlement date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **CashSettlDate**

**180.2.314 CashSettlDateRelativeTo**

Specifies the anchor date when the cash settlement date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **CashSettlDate**

**180.2.315 CashSettlDateUnadjusted**

The unadjusted cash settlement date.

Type: **LocalMktDate**

Used in components: **CashSettlDate**

**180.2.316 CashSettlDealer**

Identifies the dealer from whom price quotations for the reference obligation are obtained for the purpose of cash settlement valuation calculation.

Type: **String**

Used in groups: **CashSettlDealerGrp**

**180.2.317 CashSettlDealerGrp**

CashSettlDealerGrp is a repeating subcomponent within the CashSettlTermGrp component. It is used to specify the dealers from whom price quotations for the reference obligation are obtained for the purpose of cash settlement valuation.

Name	Mult.	Type	Description
NoCashSettlDealers	[1..1]	NumInGroup	
CashSettlDealer	[0..1]	String	Required if NoCashSettlDealers(40277) > 0.

Used in groups: [CashSettlTermGrp](#)

**180.2.318 CashSettlFixedTermIndicator**

Indicates whether fixed settlement is applicable or not applicable in a recovery lock.

Type: [Boolean](#)

Used in groups: [CashSettlTermGrp](#)

**180.2.319 CashSettlMinimumQuoteAmount**

When determining the cash settlement amount, if weighted average price quotes are to be obtained for the reference obligation, this is the minimum intended threshold amount of outstanding principal balance of the reference obligation for which the quote should be obtained. If not specified, the ISDA definitions provide for a fallback amount of the lower of either USD1,000,000 (or its equivalent in the relevant obligation currency) or the (minimum) quoted amount.

Type: [Amt](#)

Used in groups: [CashSettlTermGrp](#)

**180.2.320 CashSettlMinimumQuoteCurrency**

Specifies the currency the CashSettlMinimumQuoteAmount(40030) is denominated in. Uses ISO 4217 Currency Code.

Type: [Currency](#)

Used in groups: [CashSettlTermGrp](#)

**180.2.321 CashSettlNumOfValuationDates**

Where multiple valuation dates are specified as being applicable for cash settlement, this specifies the number of applicable valuation dates.

Type: **int**

Used in groups: **CashSettlTermGrp**

**180.2.322 CashSettlPriceDefault**

The default election for determining settlement price.

Type: **int**

Allowed values in CashSettlPriceDefaultCodeSet:

Code	Name	Description
0	Close	Close. Official closing price.
1	Hedge	Hedge. Determined by the hedging party.

Used in groups: **CashSettlTermGrp**

**180.2.323 CashSettlPriceSource**

The source from which the settlement price is to be obtained.

See <http://www.fpml.org/coding-scheme/settlement-price-source> for values.

Type: **String**

Used in groups: **CashSettlTermGrp**

**180.2.324 CashSettlQuoteAmount**

When determining the cash settlement amount, if weighted average price quotes are to be obtained for the reference obligation, this is the upper limit to the outstanding principal balance of the reference obligation for which the quote should be obtained. If not specified, the ISDA definitions provide for a fallback amount equal to floating rate payer calculation amount.

Type: **Amt**

Used in groups: **CashSettlTermGrp**

**180.2.325 CashSettlQuoteCurrency**

Specifies the currency the CashSettlQuoteAmount(40028) is denominated in. Uses ISO 4217 Currency Code.

Type: **Currency**

Used in groups: **CashSettlTermGrp**

**180.2.326 CashSettlQuoteMethod**

The type of quote used to determine the cash settlement price.

Type: **int**

Allowed values in CashSettlQuoteMethodCodeSet:

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer

Used in groups: **CashSettlTermGrp**

**180.2.327 CashSettlRecoveryFactor**

Used for fixed recovery, this specifies the recovery level as determined at contract inception, to be applied in the event of a default. The factor is used to calculate the amount paid by the seller to the buyer for cash settlement on the cash settlement date. The amount calculated is  $(1 - \text{CashSettlRecoveryFactor}(40035)) \times \text{floating rate payer calculation amount}$ . The currency is derived from the floating rate payer calculation amount.

Type: **float**

Used in groups: **CashSettlTermGrp**

**180.2.328 CashSettlTermGrp**

The CashSettlTermGrp is a repeating component within the Instrument component used to report cash settlement terms referenced from UnderlyingInstruments.

Name	Mult.	Type	Description
NoCashSettlTerms	[1..1]	NumInGroup	
CashSettlCurrency	[0..1]	Currency	Required if NoCashSettlTerms(40022) > 0.
CashSettlValuationFirstBusinessDay-Offset	[0..1]	int	
CashSettlValuationSubsequentBusinessDaysOffset	[0..1]	int	
CashSettlNumOfValuationDates	[0..1]	int	
CashSettlValuationTime	[0..1]	LocalMktTime	
CashSettlBusinessCenter	[0..1]	String	
CashSettlQuoteMethod	[0..1]	CodeSet	
CashSettlQuoteAmount	[0..1]	Amt	
CashSettlQuoteCurrency	[0..1]	Currency	
CashSettlMinimumQuoteAmount	[0..1]	Amt	
CashSettlMinimumQuoteCurrency	[0..1]	Currency	
CashSettlDealerGrp	[0..*]	Group	
CashSettlPriceSource	[0..1]	String	
CashSettlPriceDefault	[0..1]	CodeSet	
CashSettlBusinessDays	[0..1]	int	
CashSettlAmount	[0..1]	Amt	
CashSettlDate	[0..1]	Component	
CashSettlRecoveryFactor	[0..1]	float	
CashSettlFixedTermIndicator	[0..1]	Boolean	
CashSettlAccruedInterestIndicator	[0..1]	Boolean	
CashSettlValuationMethod	[0..1]	CodeSet	
CashSettlTermXID	[0..1]	XID	

Used in components: **Instrument**

### 180.2.329 CashSettlTermXID

A named string value referenced by UnderlyingSettlTermXIDRef(41315).

Type: **XID**

Used in groups: **CashSettlTermGrp**



**180.2.330 CashSettlValuationFirstBusinessDayOffset**

The number of business days after settlement conditions have been satisfied, when the calculation agent is to obtain a price quotation on the reference obligation for the purpose of cash settlement.

Type: **int**

Used in groups: **CashSettlTermGrp**

**180.2.331 CashSettlValuationMethod**

The ISDA defined methodology for determining the final price of the reference obligation for purposes of cash settlement.

Type: **int**

Allowed values in CashSettlValuationMethodCodeSet:

Code	Name	Description
0	Market	Market
1	Highest	Highest
2	AverageMarket	Average market
3	AverageHighest	Average highest
4	BlendedMarket	Blended market
5	BlendedHighest	Blended highest
6	AverageBlendedMarket	Average blended market
7	AverageBlendedHighest	Average blended highest

Used in groups: **CashSettlTermGrp**

**180.2.332 CashSettlValuationSubsequentBusinessDaysOffset**

The number of business days between successive valuation dates when multiple valuation dates are applicable for cash settlement.

Type: **int**

Used in groups: **CashSettlTermGrp**

**180.2.333 CashSettlValuationTime**

The time of valuation.

Type: **LocalMktTime**

Used in groups: **CashSettlTermGrp**

**180.2.334 CcyAmt**

Net flow of Currency 1

Type: **Amt**

Used in groups: **SettlObligationInstructions**

**180.2.335 CFICode**

Indicates the type of security using ISO 10962 standard, Classification of Financial Instruments (CFI code) values. ISO 10962 is maintained by ANNA (Association of National Numbering Agencies) acting as Registration Authority. See "Appendix 6-B FIX Fields Based Upon Other Standards". See also the Product (460) and SecurityType (167) fields. It is recommended that CFICode be used instead of SecurityType (167) for non-Fixed Income instruments.

A subset of possible values applicable to FIX usage are identified in "Appendix 6-D CFICode Usage - ISO 10962 Classification of Financial Instruments (CFI code)"

Type: **String**

Used in components: **Instrument**

Used in groups: **SecTypesGrp**, **SettlInstGrp**

Used in messages: **SettlementInstructionRequest**

**180.2.336 CheckSum**

Three byte, simple checksum (see Volume 2: "Checksum Calculation" for description). ALWAYS LAST FIELD IN MESSAGE; i.e. serves, with the trailing <SOH>, as the end-of-message delimiter. Always defined as three characters. (Always unencrypted)

Type: **String**

Used in components: **StandardTrailer**

**180.2.337 ClearedIndicator**

Indicates whether the trade or position being reported was cleared through a clearing organization.

Type: **int**

Allowed values in ClearedIndicatorCodeSet:

Code	Name	Description
0	NotCleared	Not cleared. Trade or position has not yet been submitted for clearing.
1	Cleared	Cleared. Trade or position has been successfully cleared.
2	Submitted	Submitted. Trade or position has been submitted for clearing.
3	Rejected	Rejected. Trade or position was rejected by clearing.

Used in groups: **AllocAckGrp**

Used in messages: **Confirmation**, **PositionMaintenanceReport**, **PositionReport**, **TradeCaptureReport**

**180.2.338 ClearingAccountType**

Designates the account type to be used for the order when submitted to clearing.

Type: **int**

Allowed values in ClearingAccountTypeCodeSet:

Code	Name	Description
1	Customer	Customer
2	Firm	Firm
3	MarketMaker	Market maker

Used in groups: **ClearingAccountTypeGrp**, **SideCrossOrdModGrp**

Used in messages: **ExecutionReport**, **MassOrder**, **MassOrderAck**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.339 ClearingAccountTypeGrp**

The ClearingAccountTypeGrp component is used specify the type of clearing account types.

Name	Mult.	Type	Description
NoClearingAccountTypes	[1..1]	NumInGroup	
ClearingAccountType	[0..1]	CodeSet	Required if NoClearingAccountTypes(1918) > 0.

Used in groups: [PriceMovementGrp](#)

### 180.2.340 ClearingBusinessDate

The business date for which the trade is expected to be cleared.

Type: [LocalMktDate](#)

Used in messages: [AccountSummaryReport](#), [AdjustedPositionReport](#), [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#), [AssignmentReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [ContraryIntentionReport](#), [DerivativeSecurityList](#), [MarginRequirementInquiry](#), [MarginRequirementInquiryAck](#), [MarginRequirementReport](#), [MarketDataSnapshotFullRefresh](#), [PayManagementReport](#), [PayManagementRequest](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [PositionReport](#), [PositionTransferInstruction](#), [PositionTransferReport](#), [RegistrationInstructions](#), [RequestForPositions](#), [RequestForPositionsAck](#), [SecurityDefinition](#), [SecurityDefinitionUpdateReport](#), [SecurityList](#), [SecurityListUpdateReport](#), [SettlementObligationReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#), [TradeMatchReport](#)

### 180.2.341 ClearingFeeIndicator

Indicates type of fee being assessed of the customer for trade executions at an exchange. Applicable for futures markets only at this time.

(Values source CBOT, CME, NYBOT, and NYMEX):

Type: [String](#)

Allowed values in ClearingFeeIndicatorCodeSet:

Code	Name	Description
1	FirstYearDelegate	1st year delegate trading for own account
2	SecondYearDelegate	2nd year delegate trading for own account
3	ThirdYearDelegate	3rd year delegate trading for own account

Code	Name	Description
4	FourthYearDelegate	4th year delegate trading for own account
5	FifthYearDelegate	5th year delegate trading for own account
9	SixthYearDelegate	6th year delegate trading for own account
B	CBOEMember	CBOE Member
C	NonMemberAndCustomer	Non-member and Customer
E	EquityMemberAndClearingMember	Equity Member and Clearing Member
F	FullAndAssociateMember	Full and Associate Member trading for own account and as floor brokers
H	Firms106HAnd106J	106.H and 106.J firms
I	GIM	GIM, IDEM and COM Membership Interest Holders
L	Lessee106FEmployees	Lessee 106.F Employees
M	AllotherOwnershipTypes	All other ownership types

Used in groups: [AllocGrp](#), [ListOrdGrp](#), [SideCrossOrdModGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [TradeCaptureReportAck](#)

### 180.2.342 ClearingInstruction

Eligibility of this trade for clearing and central counterparty processing.

Type: [int](#)

Allowed values in ClearingInstructionCodeSet:

Code	Name	Description
0	ProcessNormally	Process normally
1	ExcludeFromAllNetting	Exclude from all netting
2	BilateralNettingOnly	Bilateral netting only
3	ExClearing	Ex clearing
4	SpecialTrade	Special trade
5	MultilateralNetting	Multilateral netting
6	ClearAgainstCentralCounterparty	Clear against central counterparty
7	ExcludeFromCentralCounterparty	Exclude from central counterparty
8	ManualMode	Manual mode (pre-posting and/or pre-giveup)

Code	Name	Description
9	AutomaticPostingMode	Automatic posting mode (trade posting to the position account number specified)
10	AutomaticGiveUpMode	Automatic give-up mode (trade give-up to the give-up destination number specified)
11	QualifiedServiceRepresentativeQSR	Qualified Service Representative QSR
12	CustomerTrade	Customer trade
13	SelfClearing	Self clearing
14	BuyIn	Buy-in

Used in groups: [ClrInstGrp](#)

#### 180.2.343 ClearingIntention

Specifies the party's or parties' intention to clear the trade.

Type: [int](#)

Allowed values in ClearingIntentionCodeSet:

Code	Name	Description
0	DoNotIntendToClear	Do not intend to clear
1	IntendToClear	Intend to clear

Used in messages: [TradeCaptureReport](#)

#### 180.2.344 ClearingPortfolioID

When the transaction is cleared and included in a portfolio of transactions this identifies the portfolio by its unique identifier.

Type: [String](#)

Used in messages: [MarginRequirementReport](#), [PositionReport](#), [TradeCaptureReport](#)

**180.2.345 ClearingPriceOffset**

Constant value required for the calculation of the clearing price, e.g. for variance futures.

Type: **PriceOffset**

Used in groups: **ClearingPriceParametersGrp**

**180.2.346 ClearingPriceParametersGrp**

This component is used convey parameters that are relevant for the calculation of clearing prices that are different from the trading prices due to the nature of the product, e.g. variance futures.

Name	Mult.	Type	Description
NoClearingPriceParameters	[1..1]	NumInGroup	Number of parameter sets.
BusinessDayType	[0..1]	CodeSet	Required if NoClearingPriceParameters (2580) > 0. Use to identify the relative business day to which the parameters apply.
ClearingPriceOffset	[0..1]	PriceOffset	
VegaMultiplier	[0..1]	float	
AnnualTradingBusinessDays	[0..1]	int	
TotalTradingBusinessDays	[0..1]	int	
TradingBusinessDays	[0..1]	int	
StandardVariance	[0..1]	float	
RealizedVariance	[0..1]	float	
RelatedClosePrice	[0..1]	Price	
RiskFreeRate	[0..1]	float	Interest rate until the instrument expires and used to calculate DiscountFactor(1592).
OvernightInterestRate	[0..1]	float	Used to calculate AccumulatedReturnModified-VariationMargin(2591).
AccumulatedReturnModifiedVariation-Margin	[0..1]	float	
DiscountFactor	[0..1]	float	
Volatility	[0..1]	float	
ClearingSettlPrice	[0..1]	Price	
CalculationMethod	[0..1]	CodeSet	

Used in messages: **SecurityStatus**

**180.2.347 ClearingRequirementException**

Specifies whether a party to a swap is using an exception to a clearing requirement. In the US, one such clearing requirement is CFTC's rule pursuant to CEA Section 2(h)(1).

Type: **int**

Allowed values in ClearingRequirementExceptionCodeSet:

Code	Name	Description
0	NoException	No exception
1	Exception	Exception. Used to indicate an exception to a clearing requirement without elaborating on the type of exception.
2	EndUserException	End-user exception. In the US, see CFTC Final Rule on End-User Exception to Clearing Requirements for Swaps Fact Sheet <a href="http://www.cftc.gov/ucm/groups/public/@newsroom/documents/file/eue_factsheet.pdf">http://www.cftc.gov/ucm/groups/public/@newsroom/documents/file/eue_factsheet.pdf</a>
3	InterAffiliateException	Inter-affiliate exception. In the US, see CFTC Final Rule - Clearing Exemption for Swaps Between Certain Affiliated Entities <a href="http://www.cftc.gov/ucm/groups/public/@lfederalregister/documents/file/2013-07970a.pdf">http://www.cftc.gov/ucm/groups/public/@lfederalregister/documents/file/2013-07970a.pdf</a>
4	TreasuryAffiliateException	Treasury affiliate exception. In the US, see CFTC No Action Letter 13-22 No Action Relief from the Clearing Requirement for Swaps Entered into by Eligible Treasury Affiliates <a href="http://www.cftc.gov/ucm/groups/public/@lrlattergeneral/documents/letter/13-22.pdf">http://www.cftc.gov/ucm/groups/public/@lrlattergeneral/documents/letter/13-22.pdf</a>
5	CooperativeException	Cooperative exception. Clearing exception for certain swaps entered into by cooperatives. In the US, see Regulation 50.51(a) Definition of Exempt Cooperative: <a href="https://www.federalregister.gov/articles/2013/08/22/2013-19945/clearing-exemption-for-certain-swaps-entered-into-by-cooperatives">https://www.federalregister.gov/articles/2013/08/22/2013-19945/clearing-exemption-for-certain-swaps-entered-into-by-cooperatives</a>

Used in messages: **TradeCaptureReport**

**180.2.348 ClearingSettlPrice**

Clearing settlement price.

Type: **Price**

Used in groups: **ClearingPriceParametersGrp**



**180.2.349 ClearingTradePrice**

Alternate clearing price

Type: **Price**

Used in messages: **PositionTransferInstruction, PositionTransferReport, TradeCaptureReport**

**180.2.350 ClientBidID**

Unique identifier for a Bid Request as assigned by institution. Uniqueness must be guaranteed within a single trading day.

Type: **String**

Used in messages: **BidRequest, BidResponse, ListExecute, NewOrderList**

**180.2.351 ClOrdID**

Unique identifier for Order as assigned by the buy-side (institution, broker, intermediary etc.) (identified by SenderCompID(49) or OnBehalfOfCompID(115) as appropriate). Uniqueness must be guaranteed within a single trading day. Firms, particularly those which electronically submit multi-day orders, trade globally or throughout market close periods, should ensure uniqueness across days, for example by embedding a date within the ClOrdID(11) field.

Type: **String**

Used in components: **TradeReportOrderDetail**

Used in groups: **InstrmtStrkPxGrp, ListOrdGrp, OrdAllocGrp, OrdListStatGrp, OrderAggregationGrp, OrderEntryAckGrp, OrderEntryGrp, SideCrossOrdCxlGrp, SideCrossOrdModGrp**

Used in messages: **CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralRequest, CollateralResponse, Email, ExecutionAck, ExecutionReport, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderStatusRequest, QuoteRequest, QuoteResponse, RegistrationInstructions, RegistrationInstructionsResponse, SettlementInstructions, TradeCaptureReportRequest**

**180.2.352 ClOrdLinkID**

Permits order originators to tie together groups of orders in which trades resulting from orders are associated for a specific purpose, for example the calculation of average execution price for a customer

or to associate lists submitted to a broker as waves of a larger program trade.

Type: **String**

Used in groups: **ListOrdGrp**, **SideCrossOrdCxlGrp**, **SideCrossOrdModGrp**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReject**, **OrderCancelReplaceRequest**, **OrderCancelRequest**, **OrderStatusRequest**

### 180.2.353 CrlInstGrp

Name	Mult.	Type	Description
<b>NoClearingInstructions</b>	[1..1]	NumInGroup	
<b>ClearingInstruction</b>	[0..1]	CodeSet	Required if NoClearingInstructions > 0

Used in groups: **AllocGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

### 180.2.354 CollAction

Action proposed for an Underlying Instrument instance.

Type: **int**

Allowed values in CollActionCodeSet:

Code	Name	Description
0	Retain	Retain
1	Add	Add
2	Remove	Remove

Used in groups: **UndInstrmtCollGrp**

### 180.2.355 CollApplType

conveys how the collateral should be/has been applied

Type: **int**

Allowed values in CollApplTypeCodeSet:

Code	Name	Description
0	SpecificDeposit	Specific Deposit
1	General	General

Used in messages: [CollateralReport](#), [CollateralResponse](#)

### 180.2.356 CollAsgnID

Collateral Assignment Identifier

Type: [String](#)

Used in messages: [CollateralAssignment](#), [CollateralResponse](#)

### 180.2.357 CollAsgnReason

Reason for Collateral Assignment

Type: [int](#)

Allowed values in CollAsgnReasonCodeSet:

Code	Name	Description
0	Initial	Initial
1	Scheduled	Scheduled
2	TimeWarning	Time Warning
3	MarginDeficiency	Margin Deficiency. In a CollateralRequest(35=AX), this indicates there is a margin deficiency. In a CollateralAssignment(35=AY), this indicates that the assignment is a deposit to meet margin deficiency.
4	MarginExcess	Margin Excess. In a CollateralRequest(35=AX), this indicates there is excess margin. In a CollateralAssignment(35=AY), this indicates that the assignment is a withdrawal of the margin excess.
5	ForwardCollateralDemand	Forward Collateral Demand
6	EventOfDefault	Event of default
7	AdverseTaxEvent	Adverse tax event

Code	Name	Description
8	TransferDeposit	Transfer deposit. Collateral deposit in which the asset is to be transferred from an undesignated holding into collateral. I.e. there is no intermediate conversion to cash.
9	TransferWithdrawal	Transfer withdrawal. Collateral withdrawal in which the asset is to be transferred from collateral into an undesignated holding. I.e. there is no intermediate conversion to cash.
10	Pledge	Pledge. The purpose of the collateral assignment is to pledge or "lock up" a value of a basket of securities, individual security or fund as collateral.

Used in messages: [CollateralAssignment](#), [CollateralRequest](#), [CollateralResponse](#)

#### **180.2.358 CollAsgnRefID**

Collateral Assignment Identifier to which a transaction refers

Type: [String](#)

Used in messages: [CollateralAssignment](#)

#### **180.2.359 CollAsgnRejectReason**

Collateral Assignment Reject Reason

Type: [int](#)

Allowed values in CollAsgnRejectReasonCodeSet:

Code	Name	Description
0	UnknownDeal	Unknown deal (order / trade)
1	UnknownOrInvalidInstrument	Unknown or invalid instrument
2	UnauthorizedTransaction	Unauthorized transaction
3	InsufficientCollateral	Insufficient collateral
4	InvalidTypeOfCollateral	Invalid type of collateral
5	ExcessiveSubstitution	Excessive substitution
99	Other	Other

Used in messages: [CollateralResponse](#)

**180.2.360 CollAsgnRespType**

Type of collateral assignment response.

Type: **int**

Allowed values in CollAsgnRespTypeCodeSet:

Code	Name	Description
0	Received	Received
1	Accepted	Accepted
2	Declined	Declined
3	Rejected	Rejected
4	TransactionPending	Transaction pending. The collateral assignment transaction is pending at the recipient.
5	TransactionCompletedWithWarning	Transaction completed with warning - see Text(58) for further information. The collateral assignment transaction was accepted and completed but with warnings.

Used in messages: **CollateralResponse**

**180.2.361 CollAsgnTransType**

Collateral Assignment Transaction Type

Type: **int**

Allowed values in CollAsgnTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Replace	Replace
2	Cancel	Cancel
3	Release	Release
4	Reverse	Reverse

Used in messages: **CollateralAssignment**, **CollateralResponse**

**180.2.362 CollateralAmountGrp**

The Collateral Amount Group component block is a repeating group that provides the current value of the collateral type on deposit. The currency of the collateral value may be optionally included.

Name	Mult.	Type	Description
NoCollateralAmounts	[1..1]	NumInGroup	
CurrentCollateralAmount	[0..1]	Amt	Required if NoCollateralAmounts(1703) > 0.
CollateralCurrency	[0..1]	Currency	Can be used to specify the currency of CollateralAmount(1704) if Currency(15) is not specified or is not the same.
CollateralCurrencyCodeSource	[0..1]	CodeSet	
CollateralAmountType	[0..1]	CodeSet	
CollateralFXRate	[0..1]	float	
CollateralFXRateCalc	[0..1]	CodeSet	
CollateralType	[0..1]	String	
CollateralAmountMarketSegmentID	[0..1]	String	
CollateralAmountMarketID	[0..1]	String	
HaircutIndicator	[0..1]	Boolean	
CollateralPortfolioID	[0..1]	String	
CollateralPercentOverage	[0..1]	Percentage	
CollateralMarketPrice	[0..1]	Price	
CollateralReinvestmentRate	[0..1]	Percentage	May be used to specify the average reinvestment rate when there are multiple instances of the CollateralReinvestmentGrp.
CollateralReinvestmentGrp	[0..*]	Group	
UnderlyingRefID	[0..1]	String	May be used to indicate that this entry applies to the underlying collateral instrument being referenced by the value in UnderlyingID(2874).

Used in messages: [AccountSummaryReport](#), [CollateralReport](#), [CollateralResponse](#), [PositionReport](#), [TradeCaptureReport](#)

**180.2.363 CollateralAmountMarketID**

Market associated with the collateral amount.

Type: [String](#)

Used in groups: **CollateralAmountGrp**

#### **180.2.364 CollateralAmountMarketSegmentID**

Market segment associated with the collateral amount.

Type: **String**

Used in groups: **CollateralAmountGrp**

#### **180.2.365 CollateralAmountType**

The type of value in CurrentCollateralAmount(1704).

Type: **int**

Allowed values in CollateralAmountTypeCodeSet:

Code	Name	Description
0	MarketValuation	Market valuation (the default)
1	PortfolioValue	Portfolio value before processing pledge request
2	ValueConfirmed	Value confirmed as "locked-up" for processing a pledge request
3	CollateralCreditValue	Credit value of collateral at CCP processing a pledge request
4	AdditionalCollateralValue	Additional collateral value. Additional collateral deposited by the collateral provider at trade or post-trade. CollateralPercentOverage(2690) gives the overage percent
5	EstimatedMarketValuation	Estimated market valuation. Estimated market valuation of collateral. In the context of EU SFTR this may be used for value of re-use of collateral.

Used in groups: **CollateralAmountGrp**

#### **180.2.366 CollateralCurrency**

Currency of the collateral; optional, defaults to the Settlement Currency if not specified.

Type: **Currency**

Used in groups: **CollateralAmountGrp**

**180.2.367 CollateralCurrencyCodeSource**

Identifies class or source of the CollateralCurrency(1705) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **CollateralAmountGrp**

**180.2.368 CollateralFXRate**

Foreign exchange rate used to compute the CurrentCollateralAmount(1704) from the CollateralCurrency(1646) and the Currency(15).

Type: **float**

Used in groups: **CollateralAmountGrp**

**180.2.369 CollateralFXRateCalc**

Specifies whether or not CollateralFXRate(2090) should be multiplied or divided.

Type: **char**

Allowed values in UnderlyingFXRateCalcCodeSet:

Code	Name	Description
D	Divide	Divide
M	Multiply	Multiply



Used in groups: [CollateralAmountGrp](#)

#### **180.2.370 CollateralizationValueDate**

Date when the collateral is to be assessed or assigned.

Type: [LocalMktDate](#)

Used in messages: [CollateralReport](#), [PositionReport](#), [TradeCaptureReport](#)

#### **180.2.371 CollateralMarketPrice**

Market price of the collateral, either from market sources or pre-agreed by the counterparties.

Type: [Price](#)

Used in groups: [CollateralAmountGrp](#)

#### **180.2.372 CollateralPercentOverage**

Percentage of over-collateralization particularly when [CollateralAmountType](#)(2632) = 4 (Additional collateral value)

Type: [Percentage](#)

Used in groups: [CollateralAmountGrp](#)

#### **180.2.373 CollateralPortfolioID**

Identifier of the collateral portfolio when reporting on a portfolio basis.

Type: [String](#)

Used in groups: [CollateralAmountGrp](#)

#### **180.2.374 CollateralReinvestmentAmount**

The cash amount of the specified re-investment type.

Type: [Amt](#)

Used in groups: [CollateralReinvestmentGrp](#)

**180.2.375 CollateralReinvestmentCurrency**

The currency denomination of the re-invested cash amount.

CollateralReinvestmentCurrencyCodeSource(2931) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **CollateralReinvestmentGrp**

**180.2.376 CollateralReinvestmentCurrencyCodeSource**

Identifies class or source of the CollateralReinvestmentCurrency(2843) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **CollateralReinvestmentGrp**

**180.2.377 CollateralReinvestmentGrp**

The CollateralReinvestmentGrp component block is a repeating group that may be used to provide a breakdown of the cash collateral's reinvestment types and amounts (e.g. Collateral-Type(1704)="CASH").

Name	Mult.	Type	Description
NoCollateralReinvestments	[1..1]	NumInGroup	

Name	Mult.	Type	Description
CollateralReinvestmentType	[0..1]	CodeSet	Required if NoCollateralReinvestments(2845) > 0.
CollateralReinvestmentAmount	[0..1]	Amt	
CollateralReinvestmentCurrency	[0..1]	Currency	
CollateralReinvestmentCurrency-CodeSource	[0..1]	CodeSet	

Used in groups: **CollateralAmountGrp**

### 180.2.378 CollateralReinvestmentRate

Interest rate received for collateral reinvestment.

Type: **Percentage**

Used in groups: **CollateralAmountGrp**

### 180.2.379 CollateralReinvestmentType

Indicates the type of investment the cash collateral is re-invested in.

Type: **int**

Allowed values in CollateralReinvestmentTypeCodeSet:

Code	Name	Description
0	MoneyMarketFund	Money market fund. Registered money market fund. In the context of EU SFTR reporting this corresponds to code "MMFT".
1	OtherComingledPool	Other comingled pool. Any commingled pool other than money market fund. In the context of EU SFTR reporting this corresponds to code "OCMP".
2	RepoMarket	Repo market. The repurchase agreement market. In the context of EU SFTR reporting this corresponds to code "REPM".
3	DirectPurchaseOfSecurities	Direct purchase of securities. In the context of EU SFTR reporting this corresponds to code "SDPU".
4	OtherInvestments	Other investments. In the context of EU SFTR reporting this corresponds to code "OTHR".

Used in groups: **CollateralReinvestmentGrp**

#### **180.2.380 CollateralRequestInstruction**

An encoded collateral request processing instruction to the receiver.

Type: **String**

Used in messages: **CollateralAssignment**, **CollateralResponse**

#### **180.2.381 CollateralRequestLinkID**

A unique identifier to link together a set or group of requests.

Type: **String**

Used in messages: **CollateralAssignment**, **CollateralResponse**

#### **180.2.382 CollateralRequestNumber**

Ordinal number of the request within a set or group of requests.

Type: **int**

Used in messages: **CollateralAssignment**, **CollateralResponse**

#### **180.2.383 CollateralType**

Type of collateral on deposit being reported.

Type: **String**

Used in groups: **CollateralAmountGrp**

#### **180.2.384 CollectAmount**

Amount to be collected by the clearinghouse from the clearing firm.

Type: **Amt**

Used in groups: **PayCollectGrp**

#### **180.2.385 CollInqQualGrp**

Name	Mult.	Type	Description
NoCollInquiryQualifier	[1..1]	NumInGroup	Number of qualifiers to inquiry
CollInquiryQualifier	[0..1]	CodeSet	Required if NoCollInquiryQualifier > 0. Type of collateral inquiry

Used in messages: [CollateralInquiry](#), [CollateralInquiryAck](#)

### 180.2.386 CollInquiryID

Collateral Inquiry Identifier

Type: [String](#)

Used in messages: [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#)

### 180.2.387 CollInquiryQualifier

Collateral inquiry qualifiers:

Type: [int](#)

Allowed values in CollInquiryQualifierCodeSet:

Code	Name	Description
0	TradeDate	Trade Date
1	GCInstrument	GC Instrument
2	CollateralInstrument	Collateral Instrument
3	SubstitutionEligible	Substitution Eligible
4	NotAssigned	Not Assigned
5	PartiallyAssigned	Partially Assigned
6	FullyAssigned	Fully Assigned
7	OutstandingTrades	Outstanding Trades (Today < end date)

Used in groups: [CollInqQualGrp](#)

**180.2.388 CollInquiryResult**

Result returned in response to Collateral Inquiry

4000+ Reserved and available for bi-laterally agreed upon user-defined values

Type: **int**

Allowed values in CollInquiryResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidOrUnknownInstrument	Invalid or unknown instrument
2	InvalidOrUnknownCollateralType	Invalid or unknown collateral type
3	InvalidParties	Invalid Parties
4	InvalidTransportTypeRequested	Invalid Transport Type requested
5	InvalidDestinationRequested	Invalid Destination requested
6	NoCollateralFoundForTheTrade-Specified	No collateral found for the trade specified
7	NoCollateralFoundForTheOrder-Specified	No collateral found for the order specified
8	CollateralInquiryTypeNotSupported	Collateral inquiry type not supported
9	UnauthorizedForCollateralInquiry	Unauthorized for collateral inquiry
99	Other	Other (further information in Text (58) field)

Used in messages: **CollateralInquiryAck**

**180.2.389 CollInquiryStatus**

Status of Collateral Inquiry

Type: **int**

Allowed values in CollInquiryStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithWarnings	Accepted With Warnings
2	Completed	Completed

Code	Name	Description
3	CompletedWithWarnings	Completed With Warnings
4	Rejected	Rejected

Used in messages: [CollateralInquiryAck](#)

### **180.2.390 CollReqID**

Collateral Request Identifier

Type: [String](#)

Used in messages: [CollateralAssignment](#), [CollateralRequest](#), [CollateralResponse](#)

### **180.2.391 CollRespID**

Collateral Response Identifier

Type: [String](#)

Used in messages: [CollateralResponse](#)

### **180.2.392 CollRptID**

Collateral Report Identifier

Type: [String](#)

Used in messages: [CollateralReport](#), [CollateralReportAck](#)

### **180.2.393 CollRptRejectReason**

Reject reason code for rejecting the collateral report.

Type: [int](#)

Allowed values in CollRptRejectReasonCodeSet:

Code	Name	Description
0	UnknownTrade	Unknown trade or transaction

Code	Name	Description
1	UnknownInstrument	Unknown or invalid instrument
2	UnknownCounterparty	Unknown or invalid counterparty
3	UnknownPosition	Unknown or invalid position
4	UnacceptableCollateral	Unacceptable or invalid type of collateral
99	Other	Other

Used in messages: [CollateralReportAck](#)

### 180.2.394 CollRptStatus

The status of the collateral report.

Type: [int](#)

Allowed values in CollRptStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted (successfully processed)
1	Received	Received (not yet processed)
2	Rejected	Rejected

Used in messages: [CollateralReportAck](#)

### 180.2.395 CollStatus

Collateral Status

Type: [int](#)

Allowed values in CollStatusCodeSet:

Code	Name	Description
0	Unassigned	Unassigned
1	PartiallyAssigned	Partially Assigned
2	AssignmentProposed	Assignment Proposed
3	Assigned	Assigned (Accepted)



Code	Name	Description
4	Challenged	Challenged
5	Reused	Reused. A modification of the details of the collateral re-use. In the context of EU SFTR reporting, to be used with RegulatoryReportType(1934)=31 (Collateral update).

Used in messages: **CollateralReport**

### 180.2.396 CommCurrency

Specifies currency to be used for Commission(12) if the commission currency is different from the deal currency.

CommCurrencyCodeSource(2922) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in components: **CommissionData**

### 180.2.397 CommCurrencyCodeSource

Identifies class or source of the CommCurrency(479) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **CommissionData**

**180.2.398 Commission**

Commission. Note if CommType (13) is percentage, Commission of 5% should be represented as .05.

Type: **Amt**

Used in components: **CommissionData**

**180.2.399 CommissionAmount**

The commission amount.

Type: **Amt**

Used in groups: **CommissionDataGrp**

**180.2.400 CommissionAmountShared**

Commission amount to be shared with a third party, e.g. as part of a directed brokerage commission sharing arrangement. If specified, this amount should not exceed the amount in CommissionAmount(2640).

Type: **Amt**

Used in groups: **CommissionDataGrp**

**180.2.401 CommissionAmountSubType**

Further sub classification of the CommissionAmountType(2641).

Type: **int**

Allowed values in CommissionAmountSubTypeCodeSet:

Code	Name	Description
0	ResearchPaymentAccount	Research payment account (RPA)
1	CommissionSharingAgreement	Commission sharing agreement (CSA)
2	OtherTypeResearchPayment	Other type of research payment. A type of research payment other than RPA or CSA.

Used in groups: **CommissionDataGrp**

**180.2.402 CommissionAmountType**

Indicates what type of commission is being expressed in CommissionAmount(2640).

Type: **int**

Allowed values in CommissionAmountTypeCodeSet:

Code	Name	Description
0	Unspecified	Unspecified
1	Acceptance	Acceptance. The bank's charge for issuing a Letter of Credit.
2	Broker	Broker. The executing broker's commission.
3	ClearingBroker	Clearing broker. The clearing broker's commission.
4	Retail	Retail. Commission charged by or related to retail sales.
5	SalesCommission	Sales commission. The commission charged by the sales desk.
6	LocalCommission	Local commission. Commission paid to local broker in a cross-border transaction.
7	ResearchPayment	Research payment

Used in groups: **CommissionDataGrp**

**180.2.403 CommissionBasis**

Specifies the basis or unit used to calculate the commission.

Type: **char**

Allowed values in CommTypeCodeSet:

Code	Name	Description
1	PerUnit	Amount per unit. Implying shares, par, currency, physical unit etc. Use CommissionUnitOfMeasure(1238) to clarify for commodities.
2	Percent	Percent
3	Absolute	Absolute. Total monetary amount.
4	PercentageWaivedCashDiscount	Percentage waived, cash discount basis. For use with CIV buy orders.
5	PercentageWaivedEnhancedUnits	Percentage waived, enhanced units basis. For use with CIV buy orders.

Code	Name	Description
6	PointsPerBondOrContract	Points per bond or contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention, e.g. 1000 par for bonds.
7	BasisPoints	Basis points. The commission is expressed in basis points in reference to the gross price of the reference asset.
8	AmountPerContract	Amount per contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention.

Used in groups: **CommissionDataGrp**

#### 180.2.404 CommissionCurrency

Specifies the currency denomination of the commission amount if different from the trade's currency.

CommissionCurrencyCodeSource(2923) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **CommissionDataGrp**

#### 180.2.405 CommissionCurrencyCodeSource

Identifies class or source of the CommissionCurrency(2643) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Code	Name	Description
------	------	-------------

Used in groups: [CommissionDataGrp](#)

#### 180.2.406 CommissionData

The CommissionData component block is used to carry commission information such as the type of commission and the rate. Use the CommissionDataGrp component as an alternative if multiple commissions or enhanced attributes are needed.

Name	Mult.	Type	Description
<a href="#">Commission</a>	[0..1]	Amt	
<a href="#">CommType</a>	[0..1]	CodeSet	
<a href="#">CommCurrency</a>	[0..1]	Currency	
<a href="#">CommCurrencyCodeSource</a>	[0..1]	CodeSet	
<a href="#">CommRate</a>	[0..1]	float	
<a href="#">CommUnitOfMeasure</a>	[0..1]	CodeSet	
<a href="#">FundRenewWaiv</a>	[0..1]	CodeSet	

Used in groups: [AllocGrp](#), [BidCompRspGrp](#), [ListOrdGrp](#), [SideCrossOrdModGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [Confirmation](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

#### 180.2.407 CommissionDataGrp

The CommissionDataGrp component block is used to carry commission information such as the type of commission and the rate. It provides an alternative to the CommissionData component if multiple commissions or enhanced attributes are needed.

Name	Mult.	Type	Description
<a href="#">NoCommissions</a>	[1..1]	NumInGroup	

Name	Mult.	Type	Description
CommissionAmount	[0..1]	Amt	Required if NoCommissions(2639) > 0. If the commission is based on a percentage of trade quantity or a factor of "unit of measure", CommissionRate(2646) and CommissionUnitOfMeasure(2644) may also be specified as appropriate.
CommissionAmountType	[0..1]	CodeSet	Required if NoCommissions(2639) > 0.
CommissionAmountSubType	[0..1]	CodeSet	
CommissionBasis	[0..1]	CodeSet	Required if NoCommissions(2639) > 0.
CommissionCurrency	[0..1]	Currency	
CommissionCurrencyCodeSource	[0..1]	CodeSet	
CommissionUnitOfMeasure	[0..1]	CodeSet	
CommissionUnitOfMeasureCurrency	[0..1]	Currency	
CommissionUnitOfMeasureCurrency-CodeSource	[0..1]	CodeSet	
CommissionRate	[0..1]	float	
CommissionSharedIndicator	[0..1]	Boolean	
CommissionAmountShared	[0..1]	Amt	If specified, CommissionSharedIndicator(2647) must be set to "Y".
CommissionLegRefID	[0..1]	String	This field may be used for multi-leg trades sent as a single message to indicate that the entry applies only to a specific leg.
CommissionDesc	[0..1]	String	
EncodedCommissionDescLen	[0..1]	Length	Must be set if EncodedCommissionDesc(2652) is specified and must immediately precede it.
EncodedCommissionDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the CommissionDesc(2650) field in the encoded format specified via the MessageEncoding(347) field.

Used in groups: ListOrdGrp, SideCrossOrdModGrp, TrdCapRptAckSideGrp, TrdCapRptSideGrp

Used in messages: Confirmation, ExecutionReport, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest

#### 180.2.408 CommissionDesc

Description of the commission.

Type: **String**

Used in groups: **CommissionDataGrp**

#### **180.2.409 CommissionLegRefID**

Identifies the leg of the trade the entry applies to by referencing the leg's LegID(1788).

Type: **String**

Used in groups: **CommissionDataGrp**

#### **180.2.410 CommissionRate**

The commission rate when CommissionAmount(2640) is based on a percentage of quantity, amount per unit or a factor of "unit of measure". If the rate is a percentage or expressed in basis points, use the decimalized form, e.g. "0.05" for a 5% commission or "0.005" for 50 basis points.

Type: **float**

Used in groups: **CommissionDataGrp**

#### **180.2.411 CommissionSharedIndicator**

Indicates whether the amount in CommissionAmount(2640) is to be shared with a third party, e.g. as part of a directed brokerage commission sharing arrangement.

Type: **Boolean**

Used in groups: **CommissionDataGrp**

#### **180.2.412 CommissionUnitOfMeasure**

The commission rate unit of measure.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet

---

Code	Name	Description
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)



Code	Name	Description
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint

Code	Name	Description
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
Sqcm	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
Sqkm	SquareKilometer	Square kilometer
Sqm	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
Sqmm	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [CommissionDataGrp](#)

#### 180.2.413 CommissionUnitOfMeasureCurrency

Indicates the currency of the unit of measure. Conditionally required when CommissionUnitOfMeasure(2644) = Ccy (Amount of currency).

Type: [Currency](#)

Used in groups: [CommissionDataGrp](#)

#### 180.2.414 CommissionUnitOfMeasureCurrencyCodeSource

Identifies class or source of the CommissionUnitOfMeasureCurrency(2645) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP

Code	Name	Description
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **CommissionDataGrp**

### 180.2.415 CommodityFinalPriceType

Final price type of the commodity as specified by the trading venue.

Type: **int**

Allowed values in CommodityFinalPriceTypeCodeSet:

Code	Name	Description
0	ArgusMcCloskey	Argus McCloskey
1	Baltic	Baltic
2	Exchange	Exchange
3	GlobalCoal	Global Coal
4	IHSMcCloskey	IHS McCloskey
5	Platts	Platts
99	Other	Other

Used in components: **InstrumentExtension**

### 180.2.416 CommonPricingIndicator

When this element is specified and set to 'Y', it indicates that common pricing applies. Common pricing may be relevant for a transaction that references more than one commodity reference price.

Type: **Boolean**

Used in components: **Instrument**

**180.2.417 CommRate**

The commission rate when Commission(12) is based on a percentage of quantity, amount per unit or a factor of "unit of measure". If the rate is a percentage, use the decimalized form, e.g. "0.05" for a 5% commission or "0.005" for 50 basis points.

Type: **float**

Used in components: **CommissionData**

**180.2.418 CommType**

Specifies the basis or unit used to calculate the total commission based on the rate.

Type: **char**

Allowed values in CommTypeCodeSet:

Code	Name	Description
1	PerUnit	Amount per unit. Implying shares, par, currency, physical unit etc. Use CommissionUnitOfMeasure(1238) to clarify for commodities.
2	Percent	Percent
3	Absolute	Absolute. Total monetary amount.
4	PercentageWaivedCashDiscount	Percentage waived, cash discount basis. For use with CIV buy orders.
5	PercentageWaivedEnhancedUnits	Percentage waived, enhanced units basis. For use with CIV buy orders.
6	PointsPerBondOrContract	Points per bond or contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention, e.g. 1000 par for bonds.
7	BasisPoints	Basis points. The commission is expressed in basis points in reference to the gross price of the reference asset.
8	AmountPerContract	Amount per contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention.

Used in components: **CommissionData**

**180.2.419 CommUnitOfMeasure**

The commission rate unit of measure.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [CommissionData](#)

### 180.2.420 CompIDReqGrp

Name	Mult.	Type	Description
NoCompIDs	[1..1]	NumInGroup	Used to restrict updates/request to a list of specific CompID/SubID/LocationID/DeskID combinations. If not present request applies to all applicable available counterparties. EG Unless one sell side broker was a customer of another you would not expect to see information about other brokers, similarly one fund manager etc.

Name	Mult.	Type	Description
RefCompID	[0..1]	String	Used to restrict updates/request to specific CompID
RefSubID	[0..1]	String	Used to restrict updates/request to specific SubID
LocationID	[0..1]	String	Used to restrict updates/request to specific LocationID
DeskID	[0..1]	String	Used to restrict updates/request to specific DeskID

Used in messages: [NetworkCounterpartySystemStatusRequest](#)

### 180.2.421 CompIDStatGrp

Name	Mult.	Type	Description
NoCompIDs	[1..1]	NumInGroup	Specifies the number of repeating CompID's
RefCompID	[1..1]	String	CompID that status is being report for. Required if NoCompIDs > 0,
RefSubID	[0..1]	String	SubID that status is being report for.
LocationID	[0..1]	String	LocationID that status is being report for.
DeskID	[0..1]	String	DeskID that status is being report for.
StatusValue	[1..1]	CodeSet	
StatusText	[0..1]	String	Additional Information, i.e. "National Holiday"

Used in messages: [NetworkCounterpartySystemStatusResponse](#)

### 180.2.422 ComplexEventAveragingObservationGrp

The ComplexEventAveragingObservationGrp is an optional subcomponent of ComplexEventPeriodGrp for specifying the weight of each of the dated observations.

Name	Mult.	Type	Description
NoComplexEventAveragingObservations	[1..1]	NumInGroup	
ComplexEventAveragingObservation-Number	[0..1]	int	Required if NoComplexEventAveragingObservations(40994) > 0.



Name	Mult.	Type	Description
ComplexEventAveragingWeight	[0..1]	float	

Used in groups: [ComplexEventPeriodGrp](#)

#### **180.2.423 ComplexEventAveragingObservationNumber**

Cross reference to the ordinal observation as specified either in the ComplexEventScheduleGrp or ComplexEventPeriodDateGrp components.

Type: [int](#)

Used in groups: [ComplexEventAveragingObservationGrp](#)

#### **180.2.424 ComplexEventAveragingWeight**

The weight factor to be applied to the observation.

Type: [float](#)

Used in groups: [ComplexEventAveragingObservationGrp](#)

#### **180.2.425 ComplexEventBusinessCenter**

The business center used to determine dates and times in the schedule or date-time group.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [ComplexEventPeriodGrp](#)

#### **180.2.426 ComplexEventCalculationAgent**

Used to identify the calculation agent.

Type: [int](#)

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreement	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

Used in groups: **ComplexEvents**

### 180.2.427 ComplexEventCondition

Specifies the condition between complex events when more than one event is specified.

Multiple barrier events would use an "or" condition since only one can be effective at a given time. A set of digital range events would use an "and" condition since both conditions must be in effect for a payout to result.

Type: **int**

Allowed values in ComplexEventConditionCodeSet:

Code	Name	Description
1	And	And
2	Or	Or

Used in groups: **ComplexEvents**

### 180.2.428 ComplexEventCreditEventBusinessCenter

The local business center for which the credit event is to be determined. The inclusion of this business center implies that Greenwich Mean Time in Section 3.3 of the 2003 ISDA Credit Derivatives Definitions is replaced by the local time of the specified business center.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ComplexEvents**

**180.2.429 ComplexEventCreditEventCurrency**

Specifies the applicable currency when ComplexEventCreditEventValue(40999) is an amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **ComplexEventCreditEventGrp**

**180.2.430 ComplexEventCreditEventDayType**

Specifies the day type for the complex credit events.

Type: **int**

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **ComplexEventCreditEventGrp**

**180.2.431 ComplexEventCreditEventGrp**

The ComplexEventCreditEventGrp is a repeating component within the ComplexEventGrp component used to report applicable option credit events.

Name	Mult.	Type	Description
<b>NoComplexEventCreditEvents</b>	[1..1]	NumInGroup	
<b>ComplexEventCreditEventType</b>	[0..1]	String	Required if NoComplexEventCreditEvents(40996) > 0.
<b>ComplexEventCreditEventValue</b>	[0..1]	String	
<b>ComplexEventCreditEventCurrency</b>	[0..1]	Currency	

Name	Mult.	Type	Description
ComplexEventCreditEventPeriod	[0..1]	int	Conditionally required when ComplexEventCreditEventUnit(41002) is specified.
ComplexEventCreditEventUnit	[0..1]	CodeSet	Conditionally required when ComplexEventCreditEventPeriod(41001) is specified.
ComplexEventCreditEventDayType	[0..1]	CodeSet	
ComplexEventCreditEventRateSource	[0..1]	int	
ComplexEventCreditEventQualifierGrp	[0..*]	Group	

Used in groups: [ComplexEvents](#)

#### 180.2.432 ComplexEventCreditEventMinimumSources

The minimum number of the specified public information sources that must publish information that reasonably confirms that a credit event has occurred. The market convention is two.

Type: [int](#)

Used in groups: [ComplexEvents](#)

#### 180.2.433 ComplexEventCreditEventNotifyingParty

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring.

Type: [int](#)

Allowed values in ComplexEventCreditEventNotifyingPartyCodeSet:

Code	Name	Description
0	SellerNotifies	Seller notifies
1	BuyerNotifies	Buyer notifies
2	SellerOrBuyerNotifies	Seller or buyer notifies

Used in groups: [ComplexEvents](#)

**180.2.434 ComplexEventCreditEventPeriod**

Time unit multiplier for complex credit events.

Type: **int**

Used in groups: **ComplexEventCreditEventGrp**

**180.2.435 ComplexEventCreditEventQualifier**

Specifies a complex event qualifier. Used to further qualify ComplexEventCreditEventType(40998).

Type: **char**

Allowed values in ProtectionTermEventQualifierCodeSet:

Code	Name	Description
H	RestructuringMultipleHoldingObligations	Restructuring - multiple holding obligations. In relation to a restructuring credit event, unless multiple holder obligation is not specified restructurings are limited to multiple holder obligations. A multiple holder obligation means an obligation that is held by more than three holders that are not affiliates of each other and where at least two thirds of the holders must agree to the event that constitutes the restructuring credit event. ISDA 2003 Term: Multiple Holder Obligation.
E	RestructuringMultipleCreditEvent-Notices	Restructuring - multiple credit event notices. Presence of this element and value set to 'true' indicates that Section 3.9 of the 2003 Credit Derivatives Definitions shall apply. Absence of this element indicates that Section 3.9 shall not apply. NOTE: Not allowed under ISDA Credit 1999.
C	FloatingRateInterestShortfall	Floating rate interest shortfall. Indicates compounding.

Used in groups: **ComplexEventCreditEventQualifierGrp**

**180.2.436 ComplexEventCreditEventQualifierGrp**

The ComplexEventCreditEventQualifierGrp is a repeating component within the ComplexEventCreditEventGrp component used to specify qualifying attributes to an event.

Name	Mult.	Type	Description
NoComplexEventCreditEventQualifiers	[1..1]	NumInGroup	
ComplexEventCreditEventQualifier	[0..1]	CodeSet	Required if NoComplexEventCreditEventQualifiers(41005) > 0.

Used in groups: **ComplexEventCreditEventGrp**

### 180.2.437 ComplexEventCreditEventRateSource

Identifies the source of rate information used for credit events.

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Rate\\_Source](http://www.fixtradingcommunity.org/codelists#Credit_Event_Rate_Source) for code list of applicable sources.

Type: **int**

Used in groups: **ComplexEventCreditEventGrp**

### 180.2.438 ComplexEventCreditEventSource

A newspaper or electronic news service that may publish relevant information used in the determination of whether or not a credit event has occurred.

Type: **String**

Used in groups: **ComplexEventCreditEventSourceGrp**

### 180.2.439 ComplexEventCreditEventSourceGrp

The ComplexEventCreditEventSourceGrp is a repeating subcomponent of the ComplexEvents component used to specify the particular newspapers or electronic news services that may publish relevant information used in the determination of whether or not a credit event has occurred.

Name	Mult.	Type	Description
NoComplexEventCreditEventSources	[1..1]	NumInGroup	
ComplexEventCreditEventSource	[0..1]	String	Required if NoComplexEventCreditEventSources(41029) > 0.

Used in groups: **ComplexEvents**

**180.2.440 ComplexEventCreditEventStandardSources**

When this element is specified and set to 'Y', indicates that ISDA defined Standard Public Sources are applicable.

Type: **Boolean**

Used in groups: **ComplexEvents**

**180.2.441 ComplexEventCreditEventsXIDRef**

Reference to credit event table elsewhere in the message.

Type: **XIDREF**

Used in groups: **ComplexEvents**

**180.2.442 ComplexEventCreditEventType**

Specifies the type of credit event.

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Credit_Event_Types) for code list of applicable event types.

Type: **String**

Used in groups: **ComplexEventCreditEventGrp**

**180.2.443 ComplexEventCreditEventUnit**

Time unit associated with complex credit events.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **ComplexEventCreditEventGrp**

**180.2.444 ComplexEventCreditEventValue**

The credit event value appropriate to ComplexEventCreditEventType(40998).

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Credit_Event_Types) for applicable event type values.

Type: **String**

Used in groups: **ComplexEventCreditEventGrp**

**180.2.445 ComplexEventCurrencyOne**

Specifies the first or only reference currency of the trade.

ComplexEventCurrencyOneCodeSource(2942) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **ComplexEvents**

**180.2.446 ComplexEventCurrencyOneCodeSource**

Identifies class or source of the ComplexEventCurrencyOne(2124) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **ComplexEvents**



**180.2.447 ComplexEventCurrencyTwo**

Specifies the second reference currency of the trade.

ComplexEventCurrencyTwoCodeSource(2943) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **ComplexEvents**

**180.2.448 ComplexEventCurrencyTwoCodeSource**

Identifies class or source of the ComplexEventCurrencyTwo(2125) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **ComplexEvents**

**180.2.449 ComplexEventDateAdjusted**

The adjusted complex event date.

Type: **LocalMktDate**

Used in components: **ComplexEventRelativeDate**

**180.2.450 ComplexEventDateBusinessCenter**

The business center calendar used to adjust the complex event date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ComplexEventDateBusinessCenterGrp**

**180.2.451 ComplexEventDateBusinessCenterGrp**

The ComplexEventDateBusinessCenterGrp is a repeating subcomponent of the ComplexEventRelativeDate component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoComplexEventDateBusinessCenters	[1..1]	NumInGroup	
ComplexEventDateBusinessCenter	[0..1]	String	Required if NoComplexEventDateBusinessCenters(41018) > 0.

Used in components: **ComplexEventRelativeDate**

**180.2.452 ComplexEventDateBusinessDayConvention**

The business day convention used to adjust the complex event date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.

Code	Name	Description
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [ComplexEventRelativeDate](#)

#### **180.2.453 ComplexEventDateOffsetDayType**

Specifies the day type of the relative date offset.

Type: [int](#)

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [ComplexEventRelativeDate](#)

#### **180.2.454 ComplexEventDateOffsetPeriod**

Time unit multiplier for the relative date offset.

Type: [int](#)

Used in components: [ComplexEventRelativeDate](#)

#### **180.2.455 ComplexEventDateOffsetUnit**

Time unit associated with the relative date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [ComplexEventRelativeDate](#)

### 180.2.456 ComplexEventDataRelativeTo

Specifies the anchor date when the complex event date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [ComplexEventRelativeDate](#)

### 180.2.457 ComplexEventDates

The ComplexEventDate and ComplexEventTime components are used to constrain a complex event to a specific date range or time range. If specified the event is only effective on or within the specified dates and times.

Name	Mult.	Type	Description
<a href="#">NoComplexEventDates</a>	[1..1]	NumInGroup	
<a href="#">ComplexEventStartDate</a>	[0..1]	UTCDateOnly	Required if NoComplexEventDates(1491) > 0.
<a href="#">ComplexEventEndDate</a>	[0..1]	UTCDateOnly	Required if NoComplexEventDates(1491) > 0.
<a href="#">ComplexEventTimes</a>	[0..*]	Group	

Used in groups: [ComplexEvents](#)

### 180.2.458 ComplexEventDateUnadjusted

The unadjusted complex event date.

Type: [LocalMktDate](#)

Used in components: [ComplexEventRelativeDate](#)

**180.2.459 ComplexEventDeterminationMethod**

Specifies the method according to which an amount or a date is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **ComplexEvents**

**180.2.460 ComplexEventEndDate**

Specifies the end date of the date range on which a complex event is effective. The start date will be set equal to the end date for single day events such as Bermuda options

ComplexEventEndDate must always be greater than or equal to ComplexEventStartDate.

Type: **UTCDateOnly**

Used in groups: **ComplexEventDates**

**180.2.461 ComplexEventEndTime**

Specifies the end time of the time range on which a complex event date is effective.

ComplexEventEndTime must always be greater than or equal to ComplexEventStartTime.

Type: **UTCTimeOnly**

Used in groups: **ComplexEventTimes**

**180.2.462 ComplexEventFixedFXRate**

Specifies the fixed FX rate alternative for FX Quanto options.

Type: **float**

Used in groups: **ComplexEvents**

**180.2.463 ComplexEventFixingTime**

The local market fixing time.

Type: **LocalMktTime**

Used in components: **ComplexEventRelativeDate**

**180.2.464 ComplexEventFixingTimeBusinessCenter**

The business center calendar used to determine the actual fixing times.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **ComplexEventRelativeDate**

**180.2.465 ComplexEventForwardPoints**

FX forward points added to spot rate. May be a negative value.

Type: **PriceOffset**

Used in groups: **ComplexEvents**

**180.2.466 ComplexEventFuturesPriceValuation**

Indicates whether the official settlement price as announced by the related exchange is applicable, in accordance with the ISDA 2002 definitions. Applicable only to futures contracts.

Type: **Boolean**

Used in groups: **ComplexEvents**

**180.2.467 ComplexEventOptionsPriceValuation**

Indicates whether the official settlement price as announced by the related exchange is applicable, in accordance with the ISDA 2002 definitions. Applicable only to options contracts.

Type: **Boolean**

Used in groups: **ComplexEvents**

**180.2.468 ComplexEventPeriodDate**

The averaging date for an Asian option.

The trigger date for a Barrier or Knock option.

Type: **LocalMktDate**

Used in groups: **ComplexEventPeriodDateGrp**

**180.2.469 ComplexEventPeriodDateGrp**

The ComplexEventPeriodDateGrp is a subcomponent of ComplexEventPeriodGrp for specifying fixed period dates and times for an Asian or Strike Schedule option or trigger dates for a Barrier or Knock option.

Name	Mult.	Type	Description
NoComplexEventPeriodDateTimes	[1..1]	NumInGroup	
ComplexEventPeriodDate	[0..1]	LocalMktDate	Required if NoComplexEventPeriodDateTimes(41007) > 0.
ComplexEventPeriodTime	[0..1]	LocalMktTime	

Used in groups: [ComplexEventPeriodGrp](#)

**180.2.470 ComplexEventPeriodGrp**

The ComplexEventPeriodGrp is a subcomponent of ComplexEvents for specifying the periods for an Asian, Barrier, Knock or Strike Schedule option feature.

Name	Mult.	Type	Description
NoComplexEventPeriods	[1..1]	NumInGroup	
ComplexEventPeriodType	[0..1]	CodeSet	Required if NoComplexEventPeriods(41010) > 0.
ComplexEventBusinessCenter	[0..1]	String	
ComplexEventScheduleGrp	[0..*]	Group	
ComplexEventPeriodDateGrp	[0..*]	Group	
ComplexEventAveragingObservation-Grp	[0..*]	Group	

Used in groups: [ComplexEvents](#)

**180.2.471 ComplexEventPeriodTime**

The averaging time for an Asian option.

Type: [LocalMktTime](#)

Used in groups: [ComplexEventPeriodDateGrp](#)

**180.2.472 ComplexEventPeriodType**

Specifies the period type.

Type: **int**

Allowed values in ComplexEventPeriodTypeCodeSet:

Code	Name	Description
0	AsianOut	Asian Out
1	AsianIn	Asian In
2	BarrierCap	Barrier Cap
3	BarrierFloor	Barrier Floor
4	KnockOut	Knock Out
5	KnockIn	Knock In

Used in groups: **ComplexEventPeriodGrp**

**180.2.473 ComplexEventPrice**

Specifies the price at which the complex event takes effect. Impact of the event price is determined by the ComplexEventType(1484).

Type: **Price**

Used in groups: **ComplexEvents**

**180.2.474 ComplexEventPriceBoundaryMethod**

Specifies the boundary condition to be used for the event price relative to the underlying price at the point the complex event outcome takes effect as determined by the ComplexEventPriceTimeType.

Type: **int**

Allowed values in ComplexEventPriceBoundaryMethodCodeSet:

Code	Name	Description
1	LessThanComplexEventPrice	Less than ComplexEventPrice(1486)
2	LessThanOrEqualToComplexEvent- Price	Less than or equal to ComplexEventPrice(1486)



Code	Name	Description
3	EqualToComplexEventPrice	Equal to ComplexEventPrice(1486)
4	GreaterThanOrEqualToComplex-EventPrice	Greater than or equal to ComplexEventPrice(1486)
5	GreaterThanComplexEventPrice	Greater than ComplexEventPrice(1486)

Used in groups: **ComplexEvents**

### 180.2.475 ComplexEventPriceBoundaryPrecision

Used in combination with ComplexEventPriceBoundaryMethod to specify the percentage of the strike price in relation to the underlying price. The percentage is generally 100 or greater for puts and 100 or less for calls.

Type: **Percentage**

Used in groups: **ComplexEvents**

### 180.2.476 ComplexEventPricePercentage

Specifies the price percentage at which the complex event takes effect. Impact of the event price is determined by the ComplexEventType(1484).

Type: **Percentage**

Used in groups: **ComplexEvents**

### 180.2.477 ComplexEventPriceTimeType

Specifies when the complex event outcome takes effect. The outcome of a complex event is a payout or barrier action as specified by the ComplexEventType(1484).

Type: **int**

Allowed values in ComplexEventPriceTimeTypeCodeSet:

Code	Name	Description
1	Expiration	Expiration
2	Immediate	Immediate (At Any Time)

Code	Name	Description
3	SpecifiedDate	Specified Date/Time
4	Close	Close. Official closing time of the exchange on valuation date.
5	Open	Open. Official opening time of the exchange on valuation date.
6	OfficialSettlPrice	Official settlement price. Official settlement price determination time.
7	DerivativesClose	Derivatives close. Official closing time of the derivatives exchange.
8	AsSpecifiedMasterConfirmation	As specified in Master Confirmation

Used in groups: **ComplexEvents**

#### 180.2.478 ComplexEventPVFinalPriceElectionFallback

Specifies the fallback provisions for the hedging party in the determination of the final settlement price.

Type: **int**

Allowed values in ComplexEventPVFinalPriceElectionFallbackCodeSet:

Code	Name	Description
0	Close	Close. In respect of the "early final valuation date", the provisions for "future present value close" shall apply.
1	HedgeElection	Hedge election. In respect of the "early final valuation date", the provisions for "future present value hedge execution" shall apply.

Used in groups: **ComplexEvents**

#### 180.2.479 ComplexEventQuoteBasis

For foreign exchange Quanto option feature.

Type: **int**

Allowed values in ComplexEventQuoteBasisCodeSet:

Code	Name	Description
0	Currency1PerCurrency2	Currency 1 per currency 2
1	Currency2PerCurrency1	Currency 2 per currency 1

Used in groups: **ComplexEvents**

### 180.2.480 ComplexEventRateSource

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: **ComplexEventRateSourceGrp**

### 180.2.481 ComplexEventRateSourceGrp

The ComplexEventRateSourceGrp is a subcomponent of ComplexEvents for specifying primary and secondary rate sources.

Name	Mult.	Type	Description
NoComplexEventRateSources	[1..1]	NumInGroup	
ComplexEventRateSource	[0..1]	CodeSet	Required if NoComplexEventRateSources(41013) > 0.
ComplexEventRateSourceType	[0..1]	CodeSet	Required if NoComplexEventRateSources(41013) > 0.

Name	Mult.	Type	Description
ComplexEventReferencePage	[0..1]	String	Conditionally required when ComplexEventRateSource(41014) = 99 (Other).
ComplexEventReferencePageHeading	[0..1]	String	

Used in groups: **ComplexEvents**

### 180.2.482 ComplexEventRateSourceType

Indicates whether the rate source specified is a primary or secondary source.

Type: **int**

Allowed values in RateSourceTypeCodeSet:

Code	Name	Description
0	Primary	Primary
1	Secondary	Secondary

Used in groups: **ComplexEventRateSourceGrp**

### 180.2.483 ComplexEventReferencePage

Identifies the reference page from the rate source.

For FX, the reference page to the spot rate is to be used for the reference FX spot rate.

When ComplexEventRateSource(41014) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>.

Type: **String**

Used in groups: **ComplexEventRateSourceGrp**

### 180.2.484 ComplexEventReferencePageHeading

Identifies the reference page heading from the rate source.

Type: **String**

Used in groups: **ComplexEventRateSourceGrp**

**180.2.485 ComplexEventRelativeDate**

The ComplexEventRelativeDate is a subcomponent of ComplexEvents for specifying the event date and time for an FX or Calendar Spread option or the payout date for a Barrier or Knock option.

Name	Mult.	Type	Description
ComplexEventDateUnadjusted	[0..1]	LocalMktDate	
ComplexEventDateRelativeTo	[0..1]	int	
ComplexEventDateOffsetPeriod	[0..1]	int	Conditionally required when ComplexEventDateOffsetUnit(41023) is specified.
ComplexEventDateOffsetUnit	[0..1]	CodeSet	Conditionally required when ComplexEventDateOffsetPeriod(41022) is specified.
ComplexEventDateOffsetDayType	[0..1]	CodeSet	
ComplexEventDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the instrument provisions.
ComplexEventDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the instrument provisions.
ComplexEventDateAdjusted	[0..1]	LocalMktDate	
ComplexEventFixingTime	[0..1]	LocalMktTime	
ComplexEventFixingTimeBusinessCenter	[0..1]	String	

Used in groups: **ComplexEvents**

**180.2.486 ComplexEventScheduleEndDate**

The end date of the schedule.

Type: **LocalMktDate**

Used in groups: **ComplexEventScheduleGrp**

**180.2.487 ComplexEventScheduleFrequencyPeriod**

Time unit multiplier for the schedule date frequency.

Type: **int**

Used in groups: **ComplexEventScheduleGrp**

**180.2.488 ComplexEventScheduleFrequencyUnit**

Time unit associated with the schedule date frequency.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **ComplexEventScheduleGrp**

**180.2.489 ComplexEventScheduleGrp**

The ComplexEventScheduleGrp is a subcomponent of ComplexEventPeriodGrp for specifying a periodic schedule for an Asian, Barrier or Strike Schedule option feature.

Name	Mult.	Type	Description
NoComplexEventSchedules	[1..1]	NumInGroup	
ComplexEventScheduleStartDate	[0..1]	LocalMktDate	Required if NoComplexEventSchedules(41031) > 0.
ComplexEventScheduleEndDate	[0..1]	LocalMktDate	
ComplexEventScheduleFrequencyPeriod	[0..1]	int	Conditionally required when ComplexEventScheduleFrequencyUnit(41035) is specified.
ComplexEventScheduleFrequencyUnit	[0..1]	CodeSet	Conditionally required when ComplexEventScheduleFrequencyPeriod(41034) is specified.

Name	Mult.	Type	Description
ComplexEventScheduleRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the schedule.

Used in groups: **ComplexEventPeriodGrp**

### 180.2.490 ComplexEventScheduleRollConvention

The convention for determining the sequence of dates. It is used in conjunction with a specified frequency. Used only to override the roll convention defined in the DateAdjustment component in Instrument.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month

Code	Name	Description
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighthDay	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in groups: [ComplexEventScheduleGrp](#)



**180.2.491 ComplexEventScheduleStartDate**

The start date of the schedule.

Type: [LocalMktDate](#)

Used in groups: [ComplexEventScheduleGrp](#)

**180.2.492 ComplexEvents**

The ComplexEvent Group is a repeating block which allows specifying an unlimited number and types of advanced events, such as observation and pricing over the lifetime of an option, futures, commodities or equity swap contract. Use EvntGrp to specify more straightforward events.

Name	Mult.	Type	Description
<a href="#">NoComplexEvents</a>	[1..1]	NumInGroup	
<a href="#">ComplexEventType</a>	[0..1]	CodeSet	Required if NoComplexEvents(1483) > 0.
<a href="#">ComplexOptPayoutPaySide</a>	[0..1]	CodeSet	
<a href="#">ComplexOptPayoutReceiveSide</a>	[0..1]	CodeSet	
<a href="#">ComplexOptPayoutUnderlier</a>	[0..1]	String	
<a href="#">ComplexOptPayoutAmount</a>	[0..1]	Amt	
<a href="#">ComplexOptPayoutPercentage</a>	[0..1]	Percentage	
<a href="#">ComplexOptPayoutTime</a>	[0..1]	CodeSet	
<a href="#">ComplexOptPayoutCurrency</a>	[0..1]	Currency	
<a href="#">ComplexOptPayoutCurrencyCodeSource</a>	[0..1]	CodeSet	
<a href="#">ComplexEventPrice</a>	[0..1]	Price	
<a href="#">ComplexEventPricePercentage</a>	[0..1]	Percentage	
<a href="#">ComplexEventPriceBoundaryMethod</a>	[0..1]	CodeSet	
<a href="#">ComplexEventPriceBoundaryPrecision</a>	[0..1]	Percentage	
<a href="#">ComplexEventPriceTimeType</a>	[0..1]	CodeSet	

Name	Mult.	Type	Description
ComplexEventCondition	[0..1]	CodeSet	Conditionally required when there are more than one ComplexEvents occurrences. A chain of ComplexEvents must be linked together through use of the ComplexEventCondition(1490) in which the relationship between any two events is described. For any two ComplexEvents the first occurrence will specify the ComplexEventCondition(1490) which links it with the second event.
ComplexEventDates	[0..*]	Group	
ComplexEventCurrencyOne	[0..1]	Currency	
ComplexEventCurrencyOneCodeSource	[0..1]	CodeSet	
ComplexEventCurrencyTwo	[0..1]	Currency	
ComplexEventCurrencyTwoCodeSource	[0..1]	CodeSet	
ComplexEventQuoteBasis	[0..1]	CodeSet	
ComplexEventFixedFXRate	[0..1]	float	
ComplexEventSpotRate	[0..1]	Price	
ComplexEventForwardPoints	[0..1]	PriceOffset	
ComplexEventDeterminationMethod	[0..1]	String	
ComplexEventCalculationAgent	[0..1]	CodeSet	
ComplexEventStrikePrice	[0..1]	Price	
ComplexEventStrikeFactor	[0..1]	float	
ComplexEventStrikeNumberOfOptions	[0..1]	int	
ComplexEventRateSourceGrp	[0..*]	Group	
ComplexEventRelativeDate	[0..1]	Component	
ComplexEventPeriodGrp	[0..*]	Group	
ComplexEventCreditEventsXIDRef	[0..1]	XIDREF	
ComplexEventCreditEventNotifying-Party	[0..1]	CodeSet	
ComplexEventCreditEventBusiness-Center	[0..1]	String	
ComplexEventCreditEventStandard-Sources	[0..1]	Boolean	
ComplexEventCreditEventMinimum-Sources	[0..1]	int	

Name	Mult.	Type	Description
ComplexEventCreditEventSourceGrp	[0..*]	Group	
ComplexEventCreditEventGrp	[0..*]	Group	
ComplexEventFuturesPriceValuation	[0..1]	Boolean	
ComplexEventOptionsPriceValuation	[0..1]	Boolean	
ComplexEventPVFinalPriceElection-Fallback	[0..1]	CodeSet	
ComplexEventXID	[0..1]	XID	
ComplexEventXIDRef	[0..1]	XIDREF	

Used in components: **Instrument**

#### **180.2.493 ComplexEventSpotRate**

FX spot rate.

Type: **Price**

Used in groups: **ComplexEvents**

#### **180.2.494 ComplexEventStartDate**

Specifies the start date of the date range on which a complex event is effective. The start date will be set equal to the end date for single day events such as Bermuda options

ComplexEventStartDate must always be less than or equal to ComplexEventEndDate.

Type: **UTCDateOnly**

Used in groups: **ComplexEventDates**

#### **180.2.495 ComplexEventStartTime**

Specifies the start time of the time range on which a complex event date is effective.

ComplexEventStartTime must always be less than or equal to ComplexEventEndTime.

Type: **UTCTimeOnly**

Used in groups: **ComplexEventTimes**

**180.2.496 ComplexEventStrikeFactor**

Strike factor for Asian option feature. Upper strike percentage for a Strike Spread.

Type: **float**

Used in groups: **ComplexEvents**

**180.2.497 ComplexEventStrikeNumberOfOptions**

Upper string number of options for a Strike Spread.

Type: **int**

Used in groups: **ComplexEvents**

**180.2.498 ComplexEventStrikePrice**

Upper strike price for Asian option feature. Strike percentage for a Strike Spread.

Type: **Price**

Used in groups: **ComplexEvents**

**180.2.499 ComplexEventTimes**

The ComplexEventTime component is nested within the ComplexEventDate in order to further qualify any dates placed on the event and is used to specify time ranges for which a complex event is effective. It is always provided within the context of start and end dates. The time range is assumed to be in effect for the entirety of the date or date range specified.

Name	Mult.	Type	Description
NoComplexEventTimes	[1..1]	NumInGroup	
ComplexEventStartTime	[0..1]	UTCTimeOnly	Required if NoComplexEventTimes(1494) > 0.
ComplexEventEndTime	[0..1]	UTCTimeOnly	Required if NoComplexEventTimes(1494) > 0.

Used in groups: **ComplexEventDates**

**180.2.500 ComplexEventType**

Identifies the type of complex event.

Type: **int**

Allowed values in ComplexEventTypeCodeSet:

Code	Name	Description
1	Capped	Capped
2	Trigger	Trigger
3	KnockInUp	Knock-in up
4	KnockInDown	Knock-in down
5	KnockOutUp	Knock-out up
6	KnockOutDown	Knock-out down
7	Underlying	Underlying
8	ResetBarrier	Reset Barrier
9	RollingBarrier	Rolling Barrier
10	OneTouch	One-touch
11	NoTouch	No-touch
12	DblOneTouch	Double one-touch
13	DblNoTouch	Double no-touch
14	FXComposite	Foreign exchange composite
15	FXQuanto	Foreign exchange Quanto
16	FXCrssCcy	Foreign exchange cross currency
17	StrkSpread	Strike spread
18	ClndrSpread	Calendar spread
19	PxObsvtn	Price observation (Asian or Lookback)
20	PassThrough	Pass-through
21	StrkSched	Strike schedule
22	EquityValuation	Equity valuation
23	DividendValuation	Dividend valuation

Used in groups: **ComplexEvents**

**180.2.501 ComplexEventXID**

Identifier of this complex event for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **ComplexEvents**

#### **180.2.502 ComplexEventXIDRef**

Reference to a complex event elsewhere in the message.

Type: **XIDREF**

Used in groups: **ComplexEvents**

#### **180.2.503 ComplexOptPayoutAmount**

Cash amount indicating the pay out associated with an event. For binary options this is a fixed amount.

Type: **Amt**

Used in groups: **ComplexEvents**

#### **180.2.504 ComplexOptPayoutCurrency**

Specifies the currency of the payout amount.

ComplexOptPayoutCurrencyCodeSource(2941) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **ComplexEvents**

#### **180.2.505 ComplexOptPayoutCurrencyCodeSource**

Identifies class or source of the ComplexOptPayoutCurrency(2122) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

---

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL

---

Code	Name	Description
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **ComplexEvents**

#### **180.2.506 ComplexOptPayoutPaySide**

Trade side of payout payer.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **ComplexEvents**

#### **180.2.507 ComplexOptPayoutPercentage**

Percentage of observed price for calculating the payout associated with the event.

Type: **Percentage**

Used in groups: **ComplexEvents**

#### **180.2.508 ComplexOptPayoutReceiveSide**

Trade side of payout receiver.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **ComplexEvents**

### **180.2.509 ComplexOptPayoutTime**

Specifies when the payout is to occur.

Type: **int**

Allowed values in ComplexOptPayoutTimeCodeSet:

Code	Name	Description
0	Close	Close
1	Open	Open
2	OfficialSettl	Official settlement
3	ValuationTime	Valuation time
4	ExchagneSettlTime	Exchange settlement time
5	DerivativesClose	Derivatives close
6	AsSpecified	As specified in master confirmation

Used in groups: **ComplexEvents**

### **180.2.510 ComplexOptPayoutUnderlier**

Reference to the underlier whose payments are being passed through.

Type: **String**

Used in groups: **ComplexEvents**

### **180.2.511 ComplianceID**

ID used to represent this transaction for compliance purposes (e.g. OATS reporting).

Type: **String**



Used in groups: [ListOrdGrp](#), [SideCrossOrdCxlGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [CrossRequest](#), [CrossRequestAck](#), [ExecutionReport](#), [MassQuote](#), [MassQuoteAck](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [OrderMassActionReport](#), [OrderMassActionRequest](#), [Quote](#), [QuoteRequest](#), [SecurityDefinitionRequest](#)

#### **180.2.512 ComplianceText**

Free text for compliance information required for regulatory reporting.

Type: [String](#)

Used in groups: [ListOrdGrp](#), [SideCrossOrdCxlGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [CrossRequest](#), [CrossRequestAck](#), [ExecutionReport](#), [MassQuote](#), [MassQuoteAck](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [OrderMassActionReport](#), [OrderMassActionRequest](#), [Quote](#), [QuoteRequest](#), [SecurityDefinitionRequest](#)

#### **180.2.513 CompressionGroupID**

Use to identify a netting or compression group where trades in the group were netted or compressed. This includes both terminating trades and any remnant trades that result from the operation.

Type: [String](#)

Used in groups: [TrdCapRptSideGrp](#)

#### **180.2.514 Concession**

Provides the reduction in price for the secondary market in Municipals.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: [Amt](#)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#), [ExecutionReport](#)

**180.2.515 ConfirmationMethod**

Specifies how a trade was confirmed.

Type: **int**

Allowed values in ConfirmationMethodCodeSet:

Code	Name	Description
0	NonElectronic	Non-electronic
1	Electronic	Electronic
2	Unconfirmed	Unconfirmed

Used in messages: **TradeCaptureReport**

**180.2.516 ConfirmID**

Message reference for Confirmation

Type: **String**

Used in components: **SettlTradeDetails**

Used in messages: **Confirmation**, **ConfirmationAck**

**180.2.517 ConfirmRefID**

Reference identifier to be used with ConfirmTransType (666) = Replace or Cancel

Type: **String**

Used in messages: **Confirmation**

**180.2.518 ConfirmRejReason**

Identifies the reason for rejecting a Confirmation.

Type: **int**

Allowed values in ConfirmRejReasonCodeSet:

Code	Name	Description
1	MismatchedAccount	Incorrect or missing account
2	MissingSettlementInstructions	Incorrect or missing settlement instructions
3	UnknownOrMissingIndividualAllocId	Unknown or missing IndividualAllocId(467)
4	TransactionNotRecognized	Transaction not recognized
5	DuplicateTransaction	Duplicate transaction
6	IncorrectOrMissingInstrument	Incorrect or missing instrument
7	IncorrectOrMissingPrice	Incorrect or missing price
8	IncorrectOrMissingCommission	Incorrect or missing commission
9	IncorrectOrMissingSettleDate	Incorrect or missing settlement date
10	IncorrectOrMissingFundIDOrFund- Name	Incorrect or missing fund ID or fund name
11	IncorrectOrMissingQuantity	Incorrect or missing quantity
12	IncorrectOrMissingFees	Incorrect or missing fees
13	IncorrectOrMissingTax	Incorrect or missing tax
14	IncorrectOrMissingParty	Incorrect or missing party
15	IncorrectOrMissingSide	Incorrect or missing side
16	IncorrectOrMissingNetMoney	Incorrect or missing net-money
17	IncorrectOrMissingTradeDate	Incorrect or missing trade date
18	IncorrectOrMissingSettleCcyInstruc- tions	Incorrect or missing settlement currency instructions
19	IncorrectOrMissingCapacity	Incorrect or missing capacity
99	Other	Other. Use Text(58) for further reject reasons.

Used in messages: **ConfirmationAck**

#### **180.2.519 ConfirmReqID**

Unique identifier for a Confirmation Request message

Type: **String**

Used in messages: **Confirmation**, **ConfirmationRequest**

#### **180.2.520 ConfirmStatus**

Identifies the status of the Confirmation.

Type: **int**

Allowed values in ConfirmStatusCodeSet:

---

Code	Name	Description
1	Received	Received
2	MismatchedAccount	Mismatched Account
3	MissingSettlementInstructions	Missing Settlement Instructions
4	Confirmed	Confirmed
5	RequestRejected	Request Rejected

---

Used in messages: **Confirmation**

### **180.2.521 ConfirmTransType**

Identifies the Confirmation transaction type.

Type: **int**

Allowed values in ConfirmTransTypeCodeSet:

---

Code	Name	Description
0	New	New
1	Replace	Replace
2	Cancel	Cancel

---

Used in messages: **Confirmation**

### **180.2.522 ConfirmType**

Identifies the type of Confirmation message being sent.

Type: **int**

Allowed values in ConfirmTypeCodeSet:

---

Code	Name	Description
1	Status	Status

---

Code	Name	Description
2	Confirmation	Confirmation
3	ConfirmationRequestRejected	Confirmation Request Rejected (reason can be stated in Text (58) field)

Used in messages: [Confirmation](#), [ConfirmationRequest](#)

#### 180.2.523 ContAmtCurr

Specifies currency for the Contract amount if different from the Deal Currency - see "Appendix 6-A; Valid Currency Codes".

Type: [Currency](#)

Used in groups: [ContAmtGrp](#)

#### 180.2.524 ContAmtGrp

Name	Mult.	Type	Description
<a href="#">NoContAmts</a>	[1..1]	NumInGroup	Number of contract details in this message (number of repeating groups to follow)
<a href="#">ContAmtType</a>	[0..1]	CodeSet	Must be first field in the repeating group.
<a href="#">ContAmtValue</a>	[0..1]	float	
<a href="#">ContAmtCurr</a>	[0..1]	Currency	

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [ExecutionReport](#)

#### 180.2.525 ContAmtType

Type of ContAmtValue (520).

NOTE That Commission Amount / % in Contract Amounts is the commission actually charged, rather than the commission instructions given in Fields 2/3.

Type: [int](#)

Allowed values in ContAmtTypeCodeSet:

Code	Name	Description
1	CommissionAmount	Commission amount (actual)
2	CommissionPercent	Commission percent (actual)
3	InitialChargeAmount	Initial Charge Amount
4	InitialChargePercent	Initial Charge Percent
5	DiscountAmount	Discount Amount
6	DiscountPercent	Discount Percent
7	DilutionLevyAmount	Dilution Levy Amount
8	DilutionLevyPercent	Dilution Levy Percent
9	ExitChargeAmount	Exit Charge Amount
10	ExitChargePercent	Exit Charge Percent
11	FundBasedRenewalCommissionPercent	Fund-Based Renewal Commission Percent (a.k.a. Trail commission)
12	ProjectedFundValue	Projected Fund Value (i.e. for investments intended to realise or exceed a specific future value)
13	FundBasedRenewalCommissionOnOrder	Fund-Based Renewal Commission Amount (based on Order value)
14	FundBasedRenewalCommissionOnFund	Fund-Based Renewal Commission Amount (based on Projected Fund value)
15	NetSettlementAmount	Net Settlement Amount

Used in groups: **ContAmtGrp**

### 180.2.526 ContAmtValue

Value of Contract Amount, e.g. a financial amount or percentage as indicated by ContAmtType (519).

Type: **float**

Used in groups: **ContAmtGrp**

### 180.2.527 ContingencyType

Defines the type of contingency.

Type: **int**

Allowed values in ContingencyTypeCodeSet:

Code	Name	Description
1	OneCancelsTheOther	One Cancels the Other (OCO)
2	OneTriggersTheOther	One Triggers the Other (OTO)
3	OneUpdatesTheOtherAbsolute	One Updates the Other (OUO) - Absolute Quantity Reduction
4	OneUpdatesTheOtherProportional	One Updates the Other (OUO) - Proportional Quantity Reduction
5	BidAndOffer	Bid and Offer
6	BidAndOfferOCO	Bid and Offer OCO

Used in messages: [ExecutionReport](#), [ListStatus](#), [NewOrderList](#)

#### **180.2.528 ContIntRptID**

Unique identifier for the Contrary Intention report

Type: [String](#)

Used in messages: [ContraryIntentionReport](#)

#### **180.2.529 ContraBroker**

Identifies contra broker. Standard NASD market-maker mnemonic is preferred.

Type: [String](#)

Used in groups: [ContraGrp](#)

#### **180.2.530 ContractMultiplier**

Specifies the ratio or multiply factor to convert from "nominal" units (e.g. contracts) to total units (e.g. shares) (e.g. 1.0, 100, 1000, etc). Applicable For Fixed Income, Convertible Bonds, Derivatives, etc.

Type: [float](#)

Used in components: [Instrument](#)

**180.2.531 ContractMultiplierUnit**

Indicates the type of multiplier being applied to the contract. Can be optionally used to further define what unit ContractMultiplier(tag 231) is expressed in.

Type: **int**

Allowed values in ContractMultiplierUnitCodeSet:

Code	Name	Description
0	Shares	Shares
1	Hours	Hours
2	Days	Days

Used in components: **Instrument**

**180.2.532 ContractPriceRefMonth**

Reference month if there is no applicable MaturityMonthYear(200) value for the contract or security.

Type: **MonthYear**

Used in components: **Instrument**

**180.2.533 ContractRefPosType**

Additional information related to the pricing of a commodity swaps position, specifically an indicator referring to the position type.

Type: **int**

Allowed values in ContractRefPosTypeCodeSet:

Code	Name	Description
0	TwoComponentIntercommoditySpread	Two component intercommodity spread
1	IndexOrBasket	Index or basket
2	TwoComponentLocationBasis	Two component locational basis
99	Other	Other

Used in messages: **PositionMaintenanceReport**, **PositionReport**



**180.2.534 ContractSettlMonth**

Specifies when the contract (i.e. MBS/TBA) will settle.

Type: **MonthYear**

Used in components: **Instrument**

**180.2.535 ContractualDefinition**

Specifies which contract definition, such as those published by ISDA, will apply for the terms of the trade. See <http://www.fpml.org/coding-scheme/contractual-definitions> for values.

Type: **String**

Used in groups: **FinancingContractualDefinitionGrp**

**180.2.536 ContractualMatrixDate**

The publication date of the applicable version of the contract matrix. If not specified, the ISDA Standard Terms Supplement defines rules for which version of the matrix is applicable.

Type: **LocalMktDate**

Used in groups: **FinancingContractualMatrixGrp**

**180.2.537 ContractualMatrixSource**

Identifies the applicable contract matrix. See <http://www.fpml.org/coding-scheme/matrix-type-1-0.xml> for values.

Type: **String**

Used in groups: **FinancingContractualMatrixGrp**

**180.2.538 ContractualMatrixTerm**

Specifies the applicable key into the relevant contract matrix. In the case of 2000 ISDA Definitions Settlement Matrix for Early Termination and Swaptions, the ContractualMatrixTerm(40045) is not applicable and is to be omitted.

See <http://www.fpml.org/coding-scheme/credit-matrix-transaction-type> for values.

Type: **String**

Used in groups: **FinancingContractualMatrixGrp**

### 180.2.539 ContraGrp

Name	Mult.	Type	Description
NoContraBrokers	[1..1]	NumInGroup	Number of ContraBrokers repeating group instances.
ContraBroker	[0..1]	String	First field in repeating group. Required if NoContraBrokers > 0.
ContraTrader	[0..1]	String	
ContraTradeQty	[0..1]	Qty	
ContraTradeTime	[0..1]	UTCTimestamp	
ContraLegRefID	[0..1]	String	

Used in messages: **ExecutionReport**

### 180.2.540 ContraLegRefID

Unique indicator for a specific leg for the ContraBroker (375).

Type: **String**

Used in groups: **ContraGrp**

### 180.2.541 ContraOrderOrigination

Identifies the origin of the order from the counterparty of the execution or trade.

Type: **int**

Allowed values in OrderOriginationCodeSet:

Code	Name	Description
1	OrderReceivedFromCustomer	Order received from a customer
2	OrderReceivedFromWithinFirm	Order received from within the firm

Code	Name	Description
3	OrderReceivedFromAnotherBrokerDealer	Order received from another broker-dealer
4	OrderReceivedFromCustomerOrWithFirm	Order received from a customer or originated from within the firm
5	OrderReceivedFromDirectAccessCustomer	Order received from a direct access or sponsored access customer
6	OrderReceivedFromForeignDealerEquivalent	Order received from a foreign dealer equivalent. A foreign dealer equivalent is a person in the business of trading securities in a foreign jurisdiction in a manner analogous to an investment dealer and that is subject to the regulatory jurisdiction of a signatory to the International Organization of Securities Commissions' (IOSCO) Multilateral Memorandum of Understanding in that foreign jurisdiction.
7	OrderReceivedFromExecutionOnlyService	Order received from an execution-only service. The acceptance and execution of orders from customers for trades that the broker-dealer has not recommended and for which the broker-dealer takes no responsibility as to the appropriateness or suitability of orders accepted or account positions held.

Used in messages: [ExecutionReport](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

#### 180.2.542 ContraRoutingArrangementIndicator

Indicates whether a routing arrangement is in place, e.g. between two brokers. May be used together with [ContraOrderOrigination\(2882\)](#) to further describe the origin of an order.

Type: [int](#)

Allowed values in [RoutingArrangementIndicatorCodeSet](#):

Code	Name	Description
0	NoRoutingArrangementInPlace	No routing arrangement in place
1	RoutingArrangementInPlace	Routing arrangement in place

Used in messages: [ExecutionReport](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

**180.2.543 ContraryInstructionEligibilityIndicator**

Identifies whether the option instrument is eligible for contrary instructions at the time of exercise. The contrariness of an instruction will be determined in the context of InTheMoneyCondition(2681). When not specified, the eligibility is undefined or not applicable.

Type: **Boolean**

Used in components: **Instrument**

**180.2.544 ContraryInstructionIndicator**

Used to indicate when a contrary instruction for exercise or abandonment is being submitted

Type: **Boolean**

Used in messages: **PositionMaintenanceReport**, **PositionMaintenanceRequest**

**180.2.545 ContraTradeQty**

Quantity traded with the ContraBroker (375).

Type: **Qty**

Used in groups: **ContraGrp**

**180.2.546 ContraTrader**

Identifies the trader (e.g. "badge number") of the ContraBroker.

Type: **String**

Used in groups: **ContraGrp**

**180.2.547 ContraTradeTime**

Identifies the time of the trade with the ContraBroker (375). (always expressed in UTC (Universal Time Coordinated, also known as "GMT"))

Type: **UTCTimestamp**

Used in groups: **ContraGrp**

**180.2.548 ConvertibleBondEquityID**

Identifies the equity in which a convertible bond can be converted to.

Type: **String**

Used in components: **Instrument**

**180.2.549 ConvertibleBondEquityIDSource**

Identifies class or source of the ConvertibleBondEquityID(1951) value.

100+ are reserved for private security.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))

Code	Name	Description
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **Instrument**

### 180.2.550 CopyMsgIndicator

Indicates whether or not this message is a drop copy of another message.

Type: **Boolean**

Used in messages: **Confirmation**, **ExecutionReport**, **MassOrderAck**, **NewOrderSingle**, **PartyActionReport**, **TradeCaptureReport**, **TradeCaptureReportAck**

### 180.2.551 CorporateAction

Identifies the type of Corporate Action.

Type: **MultipleCharValue**

Allowed values in CorporateActionCodeSet:

Code	Name	Description
A	ExDividend	Ex-Dividend
B	ExDistribution	Ex-Distribution
C	ExRights	Ex-Rights
D	New	New
E	ExInterest	Ex-Interest
F	CashDividend	Cash Dividend
G	StockDividend	Stock Dividend
H	NonIntegerStockSplit	Non-Integer Stock Split
I	ReverseStockSplit	Reverse Stock Split
J	StandardIntegerStockSplit	Standard-Integer Stock Split
K	PositionConsolidation	Position Consolidation
L	LiquidationReorganization	Liquidation Reorganization
M	MergerReorganization	Merger Reorganization
N	RightsOffering	Rights Offering
O	ShareholderMeeting	Shareholder Meeting
P	Spinoff	Spinoff
Q	TenderOffer	Tender Offer
R	Warrant	Warrant
S	SpecialAction	Special Action
T	SymbolConversion	Symbol Conversion
U	CUSIP	CUSIP / Name Change
V	LeapRollover	Leap Rollover
W	SuccessionEvent	Succession Event

Used in groups: **MDIncGrp**, **RelSymDerivSecGrp**, **RelSymDerivSecUpdGrp**, **SecMassStatGrp**

Used in messages: **MarketDataSnapshotFullRefresh**, **SecurityDefinition**, **SecurityDefinitionUpdateReport**, **SecurityListUpdateReport**, **SecurityStatus**

### **180.2.552 Country**

ISO Country Code in field

Type: **Country**

Used in groups: **BidCompRspGrp**

**180.2.553 CountryOfIssue**

ISO Country code of instrument issue (e.g. the country portion typically used in ISIN). Can be used in conjunction with non-ISIN SecurityID (48) (e.g. CUSIP for Municipal Bonds without ISIN) to provide uniqueness.

Type: **Country**

Used in components: **Instrument**

**180.2.554 CouponDayCount**

The day count convention used in interest calculations for a bond or an interest bearing security. Absence of this field for a bond or an interest bearing security transaction implies a "flat" trade, i.e. no accrued interest determined at time of the transaction.

Type: **int**

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.



Code	Name	Description
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.

Code	Name	Description
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.

Code	Name	Description
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: **Instrument**

### 180.2.555 CouponFrequencyPeriod

Time unit multiplier for the frequency of the bond's coupon payment.

Type: **int**

Used in components: **Instrument**

### 180.2.556 CouponFrequencyUnit

Time unit associated with the frequency of the bond's coupon payment.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second

Code	Name	Description
T	Term	Term

Used in components: **Instrument**

#### **180.2.557 CouponOtherDayCount**

The industry name of the day count convention not listed in CouponDayCount(1950).

Type: **String**

Used in components: **Instrument**

#### **180.2.558 CouponPaymentDate**

Date interest is to be paid. Used in identifying Corporate Bond issues.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCDate)

Type: **LocalMktDate**

Used in components: **Instrument**

#### **180.2.559 CouponRate**

The rate of interest that, when multiplied by the principal, par value, or face value of a bond, provides the currency amount of the periodic interest payment. The coupon is always cited, along with maturity, in any quotation of a bond's price.

Type: **Percentage**

Used in components: **Instrument**

#### **180.2.560 CouponType**

Coupon type of the bond.

Type: **int**

Allowed values in CouponTypeCodeSet:

Code	Name	Description
0	Zero	Zero
1	FixedRate	Fixed rate
2	FloatingRate	Floating rate
3	Structured	Structured

Used in components: **Instrument**

#### **180.2.561 CoveredOrUncovered**

Used for derivative products, such as options

Type: **int**

Allowed values in CoveredOrUncoveredCodeSet:

Code	Name	Description
0	Covered	Covered
1	Uncovered	Uncovered

Used in groups: **ListOrdGrp**, **SideCrossOrdModGrp**

Used in messages: **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

#### **180.2.562 CoveredQty**

Used to specify the portion of the short contract quantity that is considered covered (e.g. used for short option position).

Type: **Qty**

Used in groups: **PositionQty**, **TradePositionQty**

#### **180.2.563 CoverPrice**

The best quoted price received among those not traded.

Type: **Price**

Used in messages: **ExecutionReport**, **QuoteResponse**

**180.2.564 CpctyConfGrp**

Name	Mult.	Type	Description
NoCapacities	[1..1]	NumInGroup	
OrderCapacity	[1..1]	CodeSet	Specifies the capacity of the firm executing the order(s)
OrderRestrictions	[0..1]	CodeSet	
OrderCapacityQty	[0..1]	Qty	The quantity that was executed under this capacity (e.g. quantity executed as agent, as principal etc.). If any are specified, all entries in the component must have OrderCapacityQty specified and the sum of OrderCapacityQty values must equal this message's AllocQty.

Used in messages: **Confirmation**

**180.2.565 CPProgram**

The program under which a commercial paper offering is exempt from SEC registration identified by the paragraph number(s) within the US Securities Act of 1933 or as identified below.

Type: **int**

Allowed values in CPProgramCodeSet:

Code	Name	Description
1	Program3a3	3(a)(3). Arising out of a current transaction with a maturity less than 9 months.
2	Program42	4(2). Issued not involving any public offering.
3	Program3a2	3(a)(2). Issued or guaranteed by the US, state or territorial government.
4	Program3a3And3c7	3(a)(3) & 3(c)(7). Combination of 3(a)(3) and 3(c)(7).
5	Program3a4	3(a)(4). Religious, education, benevolent, fraternal, charitable or reformatory purposes.
6	Program3a5	3(a)(5). Issued by an institution supervised by state or federal authority or by an exempt farmer's cooperative.
7	Program3a7	3(a)(7). Issued by a receiver or trustee in bankruptcy.
8	Program3c7	3(c)(7). Qualified hedge-fund under the Investment Company Act of 1940.

---

Code	Name	Description
99	Other	Other

---

Used in components: **Instrument**

#### **180.2.566 CPRegType**

The description of commercial paper registration or rule under which exempt commercial paper is offered. For example "144a", "Tax Exempt" or "REG. S".

Type: **String**

Used in components: **Instrument**

#### **180.2.567 CreditRating**

An evaluation of a company's ability to repay obligations or its likelihood of not defaulting. These evaluation are provided by Credit Rating Agencies, i.e. S&P, Moody's.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **String**

Used in components: **Instrument**

#### **180.2.568 CreditSupportAgreementDate**

The date of the ISDA Credit Support Agreement executed between the parties and intended to govern collateral arrangements for all OTC derivatives transactions between those parties.

Type: **LocalMktDate**

Used in components: **FinancingDetails**

#### **180.2.569 CreditSupportAgreementDesc**

The type of ISDA Credit Support Agreement. See <http://www.fpml.org/coding-scheme/credit-support-agreement-type> for values.

Type: **String**

Used in components: **FinancingDetails**

**180.2.570 CreditSupportAgreementID**

A common reference or unique identifier to identify the ISDA Credit Support Agreement executed between the parties.

Type: **String**

Used in components: **FinancingDetails**

**180.2.571 CrossedIndicator**

Indicates whether the order or quote was crossed with another order or quote having the same context, e.g. having accounts with a common ownership.

Type: **int**

Allowed values in CrossedIndicatorCodeSet:

Code	Name	Description
0	NoCross	No cross. Crossing did not occur.
1	CrossRejected	Cross rejected. Crossing occurred but execution was prevented, e.g. due to self-match prevention.
2	CrossAccepted	Cross accepted. Crossing occurred but execution was permitted.

Used in messages: **ExecutionReport**

**180.2.572 CrossID**

Identifier for a cross order. Must be unique during a given trading day. Recommend that firms use the order date as part of the CrossID for Good Till Cancel (GT) orders.

Type: **String**

Used in messages: **CrossOrderCancelReplaceRequest**, **CrossOrderCancelRequest**, **ExecutionReport**, **NewOrderCross**

**180.2.573 CrossPercent**

Percentage of program that crosses in Currency. Represented as a percentage.



Type: **Percentage**

Used in messages: **BidRequest**

#### **180.2.574 CrossPrioritization**

Indicates if one side or the other of a cross order should be prioritized.

The definition of prioritization is left to the market. In some markets prioritization means which side of the cross order is applied to the market first. In other markets - prioritization may mean that the prioritized side is fully executed (sometimes referred to as the side being protected).

Type: **int**

Allowed values in CrossPrioritizationCodeSet:

Code	Name	Description
0	None	None
1	BuySidsPrioritized	Buy side is prioritized
2	SellSidsPrioritized	Sell side is prioritized

Used in messages: **CrossOrderCancelReplaceRequest**, **CrossOrderCancelRequest**, **NewOrderCross**

#### **180.2.575 CrossRequestID**

Unique message identifier for a cross request as assigned by the submitter of the request.

Type: **String**

Used in messages: **CrossRequest**, **CrossRequestAck**

#### **180.2.576 CrossType**

Type of cross being submitted to a market

Type: **int**

Allowed values in CrossTypeCodeSet:

Code	Name	Description
1	CrossAON	All-or-none cross. A cross order which is executed completely or not at all. Both sides of the cross are treated in the same manner.
2	CrossIOC	Immediate-or-cancel cross. A cross order which is immediately executed with any unfilled quantity cancelled. CrossPrioritization(550) may be used to indicate whether one side should have execution priority and any remaining quantity of the partially executed side be cancelled. Using CrossPrioritization(550)="Y" and CrossType(549)=2(Immediate-or-cancel cross) is equivalent to non-prioritized leg having a TimeInForce(59)=3(IOC) Immediate-or-cancel.
3	CrossOneSide	One sided cross. A cross order which is executed on one side with any unfilled quantity remaining active. CrossPrioritization(550) may be used to indicate which side should have execution priority.
4	CrossSamePrice	Cross executed against book. A cross order which is executed against existing orders in the order book. The quantity on one side of the cross is executed against existing orders and quotes with the same price, and any remaining quantity of the cross is executed against the other side of the cross. The two sides of the cross may have different quantities.
5	BasisCross	Basis cross. A cross order where a basket of securities or an index participation unit is transacted at prices achieved through the execution of related exchange-traded derivative instruments in an amount that will correspond to an equivalent market exposure.
6	ContingentCross	Contingent cross. A cross order resulting from a paired order placed by a participant to execute an order on a security that is contingent on the execution of a second order for an offsetting volume of a related security.
7	VWAPCross	Volume-weighted-average-price (VWAP) cross. A cross order for the purpose of executing a trade at a volume-weighted-average-price (VWAP) of a security traded for a continuous period on or during a trading day.
8	STSCross	Special trading session cross. A closing price cross resulting from an order placed by a participant for execution in a special trading session at the last sale price.
9	CustomerToCustomer	Customer to customer cross. Cross order where both sides of the cross represent agency orders.

Used in messages: [CrossOrderCancelReplaceRequest](#), [CrossOrderCancelRequest](#), [ExecutionReport](#), [NewOrderCross](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.577 CstmAppVerID**

Specifies a custom extension to a message being applied at the message level. Enumerated field

Type: [String](#)

Used in components: [StandardHeader](#)

#### **180.2.578 CumQty**

Total quantity (e.g. number of shares) filled.

(Prior to FIX 4.2 this field was of type int)

Type: [Qty](#)

Used in components: [TradeReportOrderDetail](#)

Used in groups: [OrdListStatGrp](#), [OrderEntryAckGrp](#)

Used in messages: [ExecutionAck](#), [ExecutionReport](#)

#### **180.2.579 Currency**

Identifies currency used for price or quantity fields, depending on the asset class being traded. CurrencyCodeSource(2897) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Absence of this field is interpreted as the default currency for the security as defined by the respective reference data. It is recommended that systems provide the currency value whenever possible.

Type: [Currency](#)

Used in components: [SettlTradeDetails](#)

Used in groups: [InstrmtMDReqGrp](#), [InstrmtMatchSideGrp](#), [InstrmtStrkPxGrp](#), [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#), [QuotEntryAckGrp](#), [QuotEntryGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [RelSymDerivSecGrp](#), [RelSymDerivSecUpdGrp](#), [SecListGrp](#), [SecLstUpdRelSymGrp](#), [SettlObligationInstructions](#)

Used in messages: [AccountSummaryReport](#), [Advertisement](#), [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AssignmentReport](#), [BidRequest](#), [CollateralAssignment](#), [CollateralInquiry](#),

CollateralInquiryAck, CollateralReport, CollateralRequest, CollateralResponse, Confirmation, CrossOrderCancelReplaceRequest, DerivativeSecurityListRequest, ExecutionReport, IOI, MarginRequirementReport, MarketDataStatisticsReport, MarketDefinition, MarketDefinitionUpdateReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferReport, Quote, QuoteResponse, QuoteStatusReport, RequestForPositions, RequestForPositionsAck, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityListRequest, SecurityStatus, SecurityStatusRequest, TradeAggregationRequest, TradeCaptureReport, TradeCaptureReportAck

### 180.2.580 CurrencyCodeSource

Identifies class or source of the Currency(15) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **SettlTradeDetails**

Used in groups: InstrmtMDReqGrp, InstrmtMatchSideGrp, InstrmtStrkPxGrp, ListOrdGrp, MDFullGrp, MDIncGrp, QuotEntryAckGrp, QuotEntryGrp, QuotReqGrp, QuotReqRjctGrp, RelSymDerivSecGrp, RelSymDerivSecUpdGrp, SecListGrp, SecLstUpdRelSymGrp, SettlObligationInstructions

Used in messages: Advertisement, AllocationInstruction, AllocationInstructionAlert, AllocationReport, AssignmentReport, BidRequest, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralRequest, CollateralResponse, Confirmation, CrossOrderCancelReplaceRequest, DerivativeSecurityListRequest, ExecutionReport, IOI, MarginRequirementReport, MarketDataStatisticsReport, MarketDefinition, MarketDefinitionUpdateReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, PartyRiskLimitCheckRequest,

PartyRiskLimitCheckRequestAck, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferReport, Quote, QuoteResponse, QuoteStatusReport, RequestForPositions, RequestForPositionsAck, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityListRequest, SecurityStatus, SecurityStatusRequest, TradeAggregationRequest, TradeCaptureReport, TradeCaptureReportAck

#### **180.2.581 CurrencyRatio**

Specifies the currency ratio between the currency used for a multileg price and the currency used by the outright book defined by the leg. Example: Multileg quoted in EUR, outright leg in USD and 1 EUR = 0,7 USD then CurrencyRatio = 0.7

Type: **float**

Used in messages: **TradeCaptureReport**

#### **180.2.582 CurrentCollateralAmount**

Currency value currently attributed to the collateral.

Type: **Amt**

Used in groups: **CollateralAmountGrp**

#### **180.2.583 CurrentCostBasis**

The amount that the current shares are worth. If this lot was liquidated, the total gain/loss for a trade is equal to the trade amount minus the current cost basis.

Type: **Amt**

Used in groups: **AllocAckGrp, AllocGrp, PreAllocGrp, PreAllocMlegGrp, TrdAllocGrp**

#### **180.2.584 CurrentDisplayPrice**

Price at which the order is currently displayed to the market. Can be used on order messages, e.g. NewOrderSingle(35=D), to provide the current displayed price of a parent order when splitting it into smaller child orders.

Type: **Price**

Used in components: **DisplayInstruction**

**180.2.585 CurrentWorkingPrice**

Current working price of the order relative to the state of the order.

Type: **Price**

Used in messages: **ExecutionReport**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.586 CustDirectedOrder**

Indicates if the customer directed this order to a specific execution venue "Y" or not "N".

A default of "N" customer did not direct this order should be used in the case where the information is both missing and essential.

Type: **Boolean**

Used in messages: **ExecutionReport**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.587 CustodialLotID**

An opaque identifier used to communicate the custodian's identifier for the lot. It is expected that this information would be provided by the custodian as part of a reconciliation process that occurs before trading.

Type: **String**

Used in groups: **AllocAckGrp**, **AllocGrp**, **PreAllocGrp**, **PreAllocMlegGrp**, **TrdAllocGrp**

**180.2.588 CustomerPriority**

Specifies the kind of priority given to customers.

Type: **int**

Allowed values in CustomerPriorityCodeSet:

Code	Name	Description
0	NoPriority	No priority.
1	UnconditionalPriority	Unconditional priority.

Used in groups: **MatchRules**

**180.2.589 CustOrderCapacity**

Capacity of customer placing the order.

Type: **int**

Allowed values in CustOrderCapacityCodeSet:

Code	Name	Description
1	MemberTradingForTheirOwnAccount	Member trading for their own account
2	ClearingFirmTradingForItsProprietaryAccount	Clearing firm trading for its proprietary account
3	MemberTradingForAnotherMember	Member trading for another member
4	AllOther	All other
5	RetailCustomer	Retail customer. An order that originated from a retail customer (a natural person). In the context of the US Securities and Exchange Commission, this also means an order originated from a natural person where, prior to submission, no change was made to the terms of the order with respect to price or side of market and the order does not originate from an algorithm or other computerized trading method.

Used in groups: **ListOrdGrp**, **SideCrossOrdModGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **ExecutionReport**, **MarketDataStatisticsReport**, **MassOrder**, **MassOrderAck**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **Quote**, **QuoteResponse**, **QuoteStatusReport**

**180.2.590 CustOrderHandlingInst**

Codes that apply special information that the Broker / Dealer needs to report, as specified by the customer.

NOTE: This field and its values have no bearing on the ExecInst and TimeInForce fields. These values should not be used instead of ExecInst or TimeInForce. This field and its values are intended for compliance reporting and/or billing purposes only.

For OrderHandlingInstSrc(1032) = 1 (FINRA OATS), valid values are (as of OATS Phase 3 as provided by FINRA. See also <http://www.finra.org/Industry/Compliance/MarketTransparency/OATS/PhaseIII/index.htm> for a complete list.

For OrderHandlingInstSrc(1032) = 2 (FIA Execution Source Code), only one enumeration value may be specified.

Type: **MultipleStringValue**

Allowed values in CustOrderHandlingInstCodeSet:

Code	Name	Description
A	PhoneSimple	Phone simple
G	GOrderAndFCMAPlorFIX	G Order(FINRA OATS), FCM API or FIX(FIA Execution Source)
ADD	AddOnOrder	Add-on order
B	PhoneComplex	Phone complex
AON	AllOrNone	All or none
C	FCMProvidedScreen	FCM provided screen
CND	ConditionalOrder	Conditional order
D	OtherProvidedScreen	Other provided screen
CNH	CashNotHeld	Cash not held
E	ClientProvidedPlatformControlled-ByFCM	Client provided platform controlled by FCM
CSH	DeliveryInstructionsCash	Delivery instructions - cash
F	ClientProvidedPlatformDirectToExchange	Client provided platform direct to exchange
DIR	DirectedOrder	Directed order
DLO	DiscretionaryLimitOrder	Discretionary limit order
H	AlgoEngine	Algo engine
E.W	ExchangeForPhysicalTransaction	Exchange for physical transaction
J	PriceAtExecution	Price at execution (price added at initial order entry, trading, middle office or time of give-up)
FOK	FillOrKill	Fill or kill
W	DeskElectronic	Desk - electronic
X	DeskPit	Desk - pit
IDX	IntraDayCross	Intraday cross
Y	ClientElectronic	Client - electronic
IO	ImbalanceOnly	Imbalance only
Z	ClientPit	Client - pit
IOC	ImmediateOrCancel	Immediate or cancel
ISO	IntermarketSweepOrder	Intermarket sweep order
LOO	LimitOnOpen	Limit on open



Code	Name	Description
LOC	LimitOnClose	Limit on Close
MAO	MarketAtOpen	Market at Open
MAC	MarketAtClose	Market at close
MOO	MarketOnOpen	Market on open
MOC	MarketOnClose	Market on close
MPT	MergerRelatedTransferPosition	Merger related transfer position
MQT	MinimumQuantity	Minimum quantity
MTL	MarketToLimit	Market to limit
ND	DeliveryInstructionsNextDay	Delivery instructions - next day
NH	NotHeld	Not held
OPT	OptionsRelatedTransaction	Options related transaction
OVD	OverTheDay	Over the day
PEG	Pegged	Pegged
RSV	ReserveSizeOrder	Reserve size order
S.W	StopStockTransaction	Stop stock transaction
SCL	Scale	Scale
SLR	DeliveryInstructionsSellersOption	Delivery instructions - sellers option
TMO	TimeOrder	Time order
TS	TrailingStop	Trailing stop
WRK	Work	Work
F0	StayOnOfferside	Stay on offerside
F3	GoAlong	Go along
F6	ParticipateDoNotInitiate	Participate do not initiate
F7	StrictScale	Strict scale
F8	TryToScale	Try to scale
F9	StayOnBidside	Stay on bidside
FA	NoCross	No cross
FB	OKToCross	OK to cross
FC	CallFirst	Call first
FD	PercentOfVolume	Percent of volume
FH	ReinstateOnSystemFailure	Reinstate on system failure
FI	InstitutionOnly	Institution only
FJ	ReinstateOnTradingHalt	Reinstate on trading halt
FK	CancelOnTradingHalf	Cancel on trading half

Code	Name	Description
FL	LastPeg	Last peg
FM	MidPricePeg	Mid-price peg
FN	NonNegotiable	Non-negotiable
FO	OpeningPeg	Opening peg
FP	MarketPeg	Market peg
FQ	CancelOnSystemFailure	Cancel on system failure
FR	PrimaryPeg	Primary peg
FS	Suspend	Suspend
FT	FixedPegToLocalBBO	Fixed peg to local best bid or offer at time of order
FW	PegToVWAP	Peg to VWAP
FX	TradeAlong	Trade along
FY	TryToStop	Try to stop
FZ	CancelIfNotBest	Cancel if not best
Fb	StrictLimit	Strict limit
Fc	IgnorePriceValidityChecks	Ignore price validity checks
Fd	PegToLimitPrice	Peg to Limit Price
Fe	WorkToTargetStrategy	Work to target strategy

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#), [ExecutionReport](#), [MassOrder](#), [MassOrderAck](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.591 CxlQty

Total quantity canceled for this order.

(Prior to FIX 4.2 this field was of type int)

Type: [Qty](#)

Used in groups: [OrdListStatGrp](#), [OrderEntryAckGrp](#)

Used in messages: [ExecutionReport](#)

### 180.2.592 CxlRejReason

Code to identify reason for cancel rejection.

Type: **int**

Allowed values in CxlRejReasonCodeSet:

Code	Name	Description
0	TooLateToCancel	Too late to cancel
1	UnknownOrder	Unknown order
2	BrokerCredit	Broker / Exchange Option
3	OrderAlreadyInPendingStatus	Order already in Pending Cancel or Pending Replace status
4	UnableToProcessOrderMassCancel-Request	Unable to process Order Mass Cancel Request
5	OrigOrdModTime	OrigOrdModTime (586) did not match last TransactTime (60) of order
6	DuplicateCLOrdID	Duplicate CLOrdID (11) received
7	PriceExceedsCurrentPrice	Price exceeds current price
8	PriceExceedsCurrentPriceBand	Price exceeds current price band
18	InvalidPriceIncrement	Invalid price increment
99	Other	Other

Used in messages: **OrderCancelReject**

### 180.2.593 CxlRejResponseTo

Identifies the type of request that a Cancel Reject is in response to.

Type: **char**

Allowed values in CxlRejResponseToCodeSet:

Code	Name	Description
1	OrderCancelRequest	Order cancel request
2	OrderCancelReplaceRequest	Order cancel/replace request

Used in messages: **OrderCancelReject**

**180.2.594 DateAdjustment**

DateAdjustment is a subcomponent in the Instrument component. It is used to specify date adjustment parameters and rules. The date adjustments specified here applies to all adjustable dates for the instrument, unless specifically overridden in the respective specified components elsewhere.

Name	Mult.	Type	Description
BusinessDayConvention	[0..1]	CodeSet	
BusinessCenterGrp	[0..*]	Group	
DateRollConvention	[0..1]	CodeSet	

Used in components: **Instrument**

**180.2.595 DatedDate**

The effective date of a new securities issue determined by its underwriters. Often but not always the same as the Issue Date and the Interest Accrual Date

Type: **LocalMktDate**

Used in components: **Instrument**

**180.2.596 DateOfBirth**

The date of birth applicable to the individual, e.g. required to open some types of tax-exempt account.

Type: **LocalMktDate**

Used in groups: **RgstDtIsGrp**

**180.2.597 DateRollConvention**

The convention for determining a sequence of dates. It is used in conjunction with a specified frequency. The value defined here applies to all adjustable dates in the instrument unless specifically overridden. Additional values may be used by mutual agreement of the counterparties.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelfthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	FourteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighthDay	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.

Code	Name	Description
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [DateAdjustment](#)

### **180.2.598 DayAvgPx**

The average price for quantity on a GT order that has traded today.

Type: [Price](#)

Used in messages: [ExecutionReport](#)

### **180.2.599 DayBookingInst**

Indicates whether or not automatic booking can occur.

Type: [char](#)

Allowed values in DayBookingInstCodeSet:

Code	Name	Description
0	Auto	Can trigger booking without reference to the order initiator ("auto")
1	SpeakWithOrderInitiatorBeforeBooking	Speak with order initiator before booking ("speak first")
2	Accumulate	Accumulate

Used in groups: [ListOrdGrp](#), [SideCrossOrdModGrp](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

#### **180.2.600 DayCumQty**

Quantity on a GT order that has traded today.

Type: [Qty](#)

Used in messages: [ExecutionReport](#)

#### **180.2.601 DayOrderQty**

For GT orders, the OrderQty (38) less all quantity (adjusted for stock splits) that traded on previous days.  $\text{DayOrderQty (424)} = \text{OrderQty} - (\text{CumQty (14)} - \text{DayCumQty (425)})$

Type: [Qty](#)

Used in messages: [ExecutionReport](#)

#### **180.2.602 DealingCapacity**

Identifies role of dealer; Agent, Principal, RisklessPrincipal

Type: [char](#)

Allowed values in DealingCapacityCodeSet:

Code	Name	Description
A	Agent	Agent
P	Principal	Principal

Code	Name	Description
R	RisklessPrincipal	Riskless Principal

Used in groups: [MDFullGrp](#), [MDIncGrp](#)

### 180.2.603 DefaultApplExtID

The extension pack number that is the default for a FIX session.

Type: [int](#)

Used in messages: [Logon](#)

### 180.2.604 DefaultApplVerID

Specifies the service pack release being applied, by default, to message at the session level. Enumerated field with values assigned at time of service pack release. Uses same values as ApplVerID

Type: [String](#)

Allowed values in ApplVerIDCodeSet:

Code	Name	Description
0	FIX27	FIX27
1	FIX30	FIX30
2	FIX40	FIX40
3	FIX41	FIX41
4	FIX42	FIX42
5	FIX43	FIX43
6	FIX44	FIX44
7	FIX50	FIX50
8	FIX50SP1	FIX50SP1
9	FIX50SP2	FIX50SP2
10	FIXLatest	FIXLatest

Used in messages: [Logon](#)



**180.2.605 DefaultCstmApplVerID**

The default custom application version ID that is the default for a session.

Type: **String**

Used in messages: **Logon**

**180.2.606 DefaultVerIndicator**

Indicates that the application version identified in the fields RefApplVerID(1130), RefApplExtID(1406), and RefCstmApplVerID(1131) is the default for the message type identified in RefMsgType(372) field.

Type: **Boolean**

Used in groups: **MsgTypeGrp**

**180.2.607 DefBidSize**

Default Bid Size.

Type: **Qty**

Used in messages: **MassQuote**

**180.2.608 DefOfferSize**

Default Offer Size.

Type: **Qty**

Used in messages: **MassQuote**

**180.2.609 DeleteReason**

Reason for deletion.

Type: **char**

Allowed values in DeleteReasonCodeSet:

---

Code	Name	Description
0	Cancellation	Cancellation / Trade Bust

---

Code	Name	Description
1	Error	Error

Used in groups: [MDIncGrp](#)

#### **180.2.610 DeliverToCompID**

Assigned value used to identify the firm targeted to receive the message if the message is delivered by a third party i.e. the third party firm identifier would be delivered in the TargetCompID (56) field and the ultimate receiver firm ID in this field.

Type: [String](#)

Used in components: [StandardHeader](#)

#### **180.2.611 DeliverToLocationID**

Assigned value used to identify specific message recipient's location (i.e. geographic location and/or desk, trader) if the message was delivered by a third party

Type: [String](#)

Used in components: [StandardHeader](#)

#### **180.2.612 DeliverToSubID**

Assigned value used to identify specific message recipient (i.e. trader) if the message is delivered by a third party

Type: [String](#)

Used in components: [StandardHeader](#)

#### **180.2.613 DeliveryDate**

Date of delivery.

Type: [LocalMktDate](#)

Used in messages: [PositionReport](#)

**180.2.614 DeliveryForm**

Identifies the form of delivery.

Type: **int**

Allowed values in DeliveryFormCodeSet:

Code	Name	Description
1	BookEntry	Book Entry (default)
2	Bearer	Bearer

Used in components: **InstrumentExtension**

**180.2.615 DeliveryRouteOrCharter**

Specific delivery route or time charter average. Applicable to commodity freight contracts.

Type: **String**

Used in components: **Instrument**

**180.2.616 DeliveryScheduleGrp**

The DeliveryScheduleGrp is a repeating subcomponent of the Stream component used to detail step schedules associated with a delivery stream.

Name	Mult.	Type	Description
NoDeliverySchedules	[1..1]	NumInGroup	
DeliveryScheduleType	[0..1]	CodeSet	Required if NoDeliverySchedules(41037) > 0.
DeliveryScheduleXID	[0..1]	XID	
DeliveryScheduleNotional	[0..1]	Qty	
DeliveryScheduleNotionalUnitOfMeasure	[0..1]	CodeSet	
DeliveryScheduleNotionalCommodityFrequency	[0..1]	CodeSet	
DeliveryScheduleNegativeTolerance	[0..1]	float	
DeliverySchedulePositiveTolerance	[0..1]	float	

Name	Mult.	Type	Description
<a href="#">DeliveryScheduleToleranceUnitOfMeasure</a>	[0..1]	CodeSet	
<a href="#">DeliveryScheduleToleranceType</a>	[0..1]	CodeSet	Conditionally required when <a href="#">DeliveryScheduleNegativeTolerance(41043)</a> or <a href="#">DeliverySchedulePositiveTolerance(41044)</a> is specified.
<a href="#">DeliveryScheduleSettlCountry</a>	[0..1]	Country	
<a href="#">DeliveryScheduleSettlTimeZone</a>	[0..1]	String	
<a href="#">DeliveryScheduleSettlFlowType</a>	[0..1]	CodeSet	
<a href="#">DeliveryScheduleSettlHolidaysProcessingInstruction</a>	[0..1]	CodeSet	
<a href="#">DeliveryScheduleSettlDayGrp</a>	[0..*]	Group	

Used in groups: [StreamGrp](#)

#### **180.2.617 DeliveryScheduleNegativeTolerance**

Specifies the negative tolerance value. The value may be an absolute quantity or a percentage, as specified in [DeliveryScheduleToleranceType\(41046\)](#). Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: [float](#)

Used in groups: [DeliveryScheduleGrp](#)

#### **180.2.618 DeliveryScheduleNotional**

Physical delivery quantity.

Type: [Qty](#)

Used in groups: [DeliveryScheduleGrp](#)

#### **180.2.619 DeliveryScheduleNotionalCommodityFrequency**

The frequency of notional delivery.

Type: [int](#)

Allowed values in StreamNotionalCommodityFrequencyCodeSet:

Code	Name	Description
0	Term	Term
1	PerBusinessDay	Per business day
2	PerCalculationPeriod	Per calculation period
3	PerSettlPeriod	Per settlement period
4	PerCalendarDay	Per calendar day
5	PerHour	Per hour
6	PerMonth	Per month

Used in groups: **DeliveryScheduleGrp**

#### **180.2.620 DeliveryScheduleNotionalUnitOfMeasure**

Specifies the delivery quantity unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.

Code	Name	Description
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces

Code	Name	Description
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard

Code	Name	Description
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [DeliveryScheduleGrp](#)

#### 180.2.621 DeliverySchedulePositiveTolerance

Specifies the positive tolerance value. The value may be an absolute quantity or a percentage, as specified in [DeliveryScheduleToleranceType\(41046\)](#). Value may exceed agreed upon value. Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: [float](#)

Used in groups: [DeliveryScheduleGrp](#)

#### 180.2.622 DeliveryScheduleSettlCountry

Specifies the country where delivery takes place. Uses ISO 3166 2-character country code.

Type: [Country](#)

Used in groups: [DeliveryScheduleGrp](#)

#### 180.2.623 DeliveryScheduleSettlDay

Specifies the day or group of days for delivery.

Type: [int](#)

Allowed values in [DeliveryScheduleSettlDayCodeSet](#):

Code	Name	Description
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday



Code	Name	Description
7	Sunday	Sunday
8	AllWeekdays	All weekdays
9	AllDays	All days
10	AllWeekends	All weekends

Used in groups: [DeliveryScheduleSettlDayGrp](#)

#### 180.2.624 DeliveryScheduleSettlDayGrp

The DeliveryScheduleSettlDayGrp is a repeating subcomponent of the DeliveryScheduleGrp component used to detail commodity delivery days.

Name	Mult.	Type	Description
<a href="#">NoDeliveryScheduleSettlDays</a>	[1..1]	NumInGroup	
<a href="#">DeliveryScheduleSettlDay</a>	[0..1]	CodeSet	Required if NoDeliveryScheduleSettlDays(41051) > 0.
<a href="#">DeliveryScheduleSettlTotalHours</a>	[0..1]	int	
<a href="#">DeliveryScheduleSettlTimeGrp</a>	[0..*]	Group	

Used in groups: [DeliveryScheduleGrp](#)

#### 180.2.625 DeliveryScheduleSettlEnd

The scheduled end time for the delivery of the commodity where delivery occurs over specified times. The format of the time value is specified in DeliveryScheduleSettlTimeType(41057).

Type: [String](#)

Used in groups: [DeliveryScheduleSettlTimeGrp](#)

#### 180.2.626 DeliveryScheduleSettlFlowType

Specifies the commodity delivery flow type.

Type: [int](#)

Allowed values in DeliveryScheduleSettlFlowTypeCodeSet:

Code	Name	Description
0	AllTimes	All times
1	OnPeak	On peak
2	OffPeak	Off peak
3	Base	Base
4	BlockHours	Block hours
5	Other	Other

Used in groups: [DeliveryScheduleGrp](#)

#### **180.2.627 DeliveryScheduleSettlHolidaysProcessingInstruction**

Indicates whether holidays are included in the settlement periods. Required for electricity contracts.

Type: [int](#)

Allowed values in DeliveryScheduleSettlHolidaysProcessingInstructionCodeSet:

Code	Name	Description
0	DoNotIncludeHolidays	Do not include holidays
1	IncludeHolidays	Include holidays

Used in groups: [DeliveryScheduleGrp](#)

#### **180.2.628 DeliveryScheduleSettlStart**

The scheduled start time for the delivery of the commodity where delivery occurs over specified times. The format of the time value is specified in DeliveryScheduleSettlTimeType(41057).

Type: [String](#)

Used in groups: [DeliveryScheduleSettlTimeGrp](#)

**180.2.629 DeliveryScheduleSettlTimeGrp**

The DeliveryScheduleSettlTimeGrp is a repeating subcomponent of the DeliveryScheduleSettlDayGrp component used to detail commodity delivery time period.

Name	Mult.	Type	Description
NoDeliveryScheduleSettlTimes	[1..1]	NumInGroup	
DeliveryScheduleSettlStart	[0..1]	String	Required if NoDeliveryScheduleSettlTimes(41054) > 0.
DeliveryScheduleSettlEnd	[0..1]	String	Required if NoDeliveryScheduleSettlTimes(41054) > 0.
DeliveryScheduleSettlTimeType	[0..1]	CodeSet	May be defaulted to market convention or bilaterally agreed if not specified.

Used in groups: [DeliveryScheduleSettlDayGrp](#)

**180.2.630 DeliveryScheduleSettlTimeType**

Specifies the format of the delivery start and end time values.

Type: [int](#)

Allowed values in DeliveryScheduleSettlTimeTypeCodeSet:

Code	Name	Description
0	Hour	Hour of the day. Applicable for electricity contracts. Time value is expressed as an integer hour of the day (1-24). The delivery start/end hour is specified as the end of the included hour. For example, a start hour of "4" begins at 3 a.m.; an end hour of "20" ends at 8 p.m.; a start hour of "1" and end hour of "24" indicates midnight to midnight delivery.
1	Timestamp	HH:MM time format. Applicable for gas contracts. Time value is expressed using a 24-hour time format. For example, a time value of "13:30" is 1:30 p.m.

Used in groups: [DeliveryScheduleSettlTimeGrp](#)

**180.2.631 DeliveryScheduleSettlTimeZone**

Delivery timezone specified as "prevailing" rather than "standard" or "daylight".

See [http://www.fixtradingcommunity.org/codelists#Prevailing\\_Timezones](http://www.fixtradingcommunity.org/codelists#Prevailing_Timezones) for code list of applicable prevailing timezones.

Type: **String**

Used in groups: **DeliveryScheduleGrp**

**180.2.632 DeliveryScheduleSettlTotalHours**

The sum of the total hours specified in the DeliveryScheduleSettlTimeGrp component.

Type: **int**

Used in groups: **DeliveryScheduleSettlDayGrp**

**180.2.633 DeliveryScheduleToleranceType**

Specifies the tolerance value type.

Type: **int**

Allowed values in DeliveryScheduleToleranceTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in groups: **DeliveryScheduleGrp**

**180.2.634 DeliveryScheduleToleranceUnitOfMeasure**

Specifies the tolerance value's unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms

Code	Name	Description
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce

Code	Name	Description
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
Sqcm	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
Sqkm	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
Sqmm	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: **DeliveryScheduleGrp**

### 180.2.635 DeliveryScheduleType

Specifies the type of delivery schedule.

Type: **int**

Allowed values in DeliveryScheduleTypeCodeSet:

Code	Name	Description
0	Notional	Notional
1	Delivery	Delivery
2	PhysicalSettlPeriods	Physical settlement period

Used in groups: **DeliveryScheduleGrp**

**180.2.636 DeliveryScheduleXID**

Identifier for this instance of delivery schedule for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **DeliveryScheduleGrp**

**180.2.637 DeliveryStreamCommoditySource**

The SCoTA coal cargo origin, mining region, mine(s), mining complex(es), loadout(s) or river dock(s) or other point(s) of origin that seller and buyer agree are acceptable origins for the coal product. For international coal transactions, this is the origin of the coal product.

See <http://www.fpml.org/coding-scheme/commodity-coal-product-source> for values.

Type: **String**

Used in groups: **DeliveryStreamCommoditySourceGrp**

**180.2.638 DeliveryStreamCommoditySourceGrp**

The DeliveryStreamCommoditySourceGrp is a repeating subcomponent of the DeliveryStream component used to detail the origins or sources of the commodity.

Name	Mult.	Type	Description
<b>NoDeliveryStreamCommoditySources</b>	[1..1]	NumInGroup	
<b>DeliveryStreamCommoditySource</b>	[0..1]	String	Required if NoDeliveryStreamCommoditySources(41085) > 0.

Used in components: **DeliveryStream**

**180.2.639 DeliveryStream**

The DeliveryStream component is used to optionally specify the attributes of a physical delivery stream in a swap.

Name	Mult.	Type	Description
<b>DeliveryStreamType</b>	[0..1]	CodeSet	



Name	Mult.	Type	Description
DeliveryStreamCommoditySourceGrp	[0..*]	Group	
DeliveryStreamPipeline	[0..1]	String	
DeliveryStreamEntryPoint	[0..1]	String	
DeliveryStreamWithdrawalPoint	[0..1]	String	
DeliveryStreamDeliveryPoint	[0..1]	String	
DeliveryStreamDeliveryPointSource	[0..1]	CodeSet	
DeliveryStreamDeliveryPointDesc	[0..1]	String	
DeliveryStreamDeliveryRestriction	[0..1]	CodeSet	
DeliveryStreamDeliveryContingency	[0..1]	String	
DeliveryStreamDeliveryContingentPartySide	[0..1]	CodeSet	
DeliveryStreamDeliverAtSourceIndicator	[0..1]	Boolean	
DeliveryStreamRiskApportionment	[0..1]	String	
DeliveryStreamRiskApportionmentSource	[0..1]	String	
DeliveryStreamCycleGrp	[0..*]	Group	
DeliveryStreamTitleTransferLocation	[0..1]	String	
DeliveryStreamTitleTransferCondition	[0..1]	CodeSet	
DeliveryStreamImporterOfRecord	[0..1]	String	
DeliveryStreamNegativeTolerance	[0..1]	float	
DeliveryStreamPositiveTolerance	[0..1]	float	
DeliveryStreamToleranceUnitOfMeasure	[0..1]	CodeSet	
DeliveryStreamToleranceType	[0..1]	CodeSet	
DeliveryStreamToleranceOptionSide	[0..1]	CodeSet	
DeliveryStreamTotalPositiveTolerance	[0..1]	Percentage	
DeliveryStreamTotalNegativeTolerance	[0..1]	Percentage	
DeliveryStreamNotionalConversionFactor	[0..1]	float	
DeliveryStreamTransportEquipment	[0..1]	String	
DeliveryStreamElectingPartySide	[0..1]	CodeSet	
DeliveryStreamRouteOrCharter	[0..1]	String	

Used in groups: **StreamGrp**

**180.2.640 DeliveryStreamCycleDesc**

The delivery cycles during which the oil product will be transported in the pipeline.

Type: **String**

Used in groups: **DeliveryStreamCycleGrp**

**180.2.641 DeliveryStreamCycleGrp**

The DeliveryStreamCycleGrp is a repeating subcomponent of the DeliveryStream component used to detail delivery cycles during which the oil product will be transported in the pipeline.

Name	Mult.	Type	Description
NoDeliveryStreamCycles	[1..1]	NumInGroup	
DeliveryStreamCycleDesc	[0..1]	String	Required if NoDeliveryStreamCycles(41081) > 0.
EncodedDeliveryStreamCycleDescLen	[0..1]	Length	Must be set if EncodedDeliveryStreamCycleDesc(41084) field is specified and must immediately precede it.
EncodedDeliveryStreamCycleDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the DeliveryStreamCycleDesc(41082) field in the encoded format specified via the MessageEncoding(347) field.

Used in components: **DeliveryStream**

**180.2.642 DeliveryStreamDeliverAtSourceIndicator**

When this element is specified and set to 'Y', delivery of the coal product is to be at its source.

Type: **Boolean**

Used in components: **DeliveryStream**

**180.2.643 DeliveryStreamDeliveryContingency**

Specifies the electricity delivery contingency.

See <http://www.fpml.org/coding-scheme/electricity-transmission-contingency> for values.

Type: **String**

Used in components: **DeliveryStream**

**180.2.644 DeliveryStreamDeliveryContingentPartySide**

The trade side value of the party responsible for electricity delivery contingency.

Type: **int**

Allowed values in DeliveryStreamElectingPartySideCodeSet:

Code	Name	Description
0	Buyer	Buyer
1	Seller	Seller

Used in components: **DeliveryStream**

**180.2.645 DeliveryStreamDeliveryPoint**

The point at which the commodity product will be delivered and received. Value specified should follow market convention appropriate for the commodity product.

For bullion, see <http://www.fpml.org/coding-scheme/bullion-delivery-location> for values.

Type: **String**

Used in components: **DeliveryStream**

**180.2.646 DeliveryStreamDeliveryPointDesc**

Description of the delivery point identified in DeliveryStreamDeliveryPoint(41062).

Type: **String**

Used in components: **DeliveryStream**

**180.2.647 DeliveryStreamDeliveryPointSource**

Identifies the class or source of DeliveryStreamDeliveryPoint(41062).

Type: **int**

Allowed values in DeliveryStreamDeliveryPointSourceCodeSet:

Code	Name	Description
0	Proprietary	Proprietary
1	EIC	Energy Identification Code (EIC). Energy Identification Code specifies the location or connection point codes of energy delivery. See <a href="http://www.entsog.eu/eic-codes/eic-location-codes-v">http://www.entsog.eu/eic-codes/eic-location-codes-v</a> or <a href="http://www.eiccodes.eu">http://www.eiccodes.eu</a> for more information and allocated values to use in DeliveryStreamDeliveryPoint(41062).

Used in components: **DeliveryStream**

### 180.2.648 DeliveryStreamDeliveryRestriction

Specifies under what conditions the buyer and seller should be excused of their delivery obligations.

Type: **int**

Allowed values in DeliveryStreamDeliveryRestrictionCodeSet:

Code	Name	Description
1	Firm	Firm. Never excused of delivery obligations.
2	NonFirm	Interruptable or non-firm. Excused when interrupted for any reason or for no reason without liability.
3	ForceMajeure	Force majeure. Excused when prevented by force majeure.
4	SystemFirm	System firm. Must be supplied from the owned or controlled generation of pre-existing purchased power assets of the system specified.
5	UnitFirm	Unit firm. Must be supplied from the generation asset specified.

Used in components: **DeliveryStream**

### 180.2.649 DeliveryStreamElectingPartySide

A reference to the party able to choose whether the gas is delivered for a particular period as found in a swing or interruptible contract.

Type: **int**

Allowed values in DeliveryStreamElectingPartySideCodeSet:

Code	Name	Description
0	Buyer	Buyer
1	Seller	Seller

Used in components: [DeliveryStream](#)

#### **180.2.650 DeliveryStreamEntryPoint**

The point at which the commodity will enter the delivery mechanism or pipeline.

Type: [String](#)

Used in components: [DeliveryStream](#)

#### **180.2.651 DeliveryStreamImporterOfRecord**

A party, not necessarily of the trade, who is the Importer of Record for the purposes of paying customs duties and applicable taxes or costs related to importation.

Type: [String](#)

Used in components: [DeliveryStream](#)

#### **180.2.652 DeliveryStreamNegativeTolerance**

Specifies the negative tolerance value. The value may be an absolute quantity or a percentage, as specified in DeliveryStreamToleranceType(41074). Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: [float](#)

Used in components: [DeliveryStream](#)

#### **180.2.653 DeliveryStreamNotionalConversionFactor**

If the notional quantity is specified in a unit that does not match the unit in which the commodity reference price is quoted, the scaling or conversion factor used to convert the commodity reference

price unit into the notional quantity unit should be stated here. If there is no conversion, this field is not intended to be used.

Type: **float**

Used in components: **DeliveryStream**

#### **180.2.654 DeliveryStreamPipeline**

The name of the oil delivery pipeline.

Type: **String**

Used in components: **DeliveryStream**

#### **180.2.655 DeliveryStreamPositiveTolerance**

Specifies the positive tolerance value. The value may be an absolute quantity or a percentage, as specified in **DeliveryStreamToleranceType**(41074). Value may exceed agreed upon value. Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **float**

Used in components: **DeliveryStream**

#### **180.2.656 DeliveryStreamRiskApportionment**

Specifies how the parties to the trade apportion responsibility for the delivery of the commodity product.

See [http://www.fixtradingcommunity.org/codelists#Risk\\_Apportionment](http://www.fixtradingcommunity.org/codelists#Risk_Apportionment) for the details of the external code list.

Type: **String**

Used in components: **DeliveryStream**

#### **180.2.657 DeliveryStreamRiskApportionmentSource**

Specifies the source or legal framework for the risk apportionment.

See [http://www.fixtradingcommunity.org/codelists#Risk\\_Apportionment\\_Source](http://www.fixtradingcommunity.org/codelists#Risk_Apportionment_Source) for the details of the external code list.

Type: **String**

Used in components: **DeliveryStream**

#### **180.2.658 DeliveryStreamRouteOrCharter**

Specific delivery route or time charter average. Applicable to commodity freight swaps.

Type: **String**

Used in components: **DeliveryStream**

#### **180.2.659 DeliveryStreamTitleTransferCondition**

Specifies the condition of title transfer.

Type: **int**

Allowed values in DeliveryStreamTitleTransferConditionCodeSet:

Code	Name	Description
0	Transfers	Transfers with risk of loss
1	DoesNotTransfer	Does not transfer with risk of loss

Used in components: **DeliveryStream**

#### **180.2.660 DeliveryStreamTitleTransferLocation**

Specifies the title transfer location.

Type: **String**

Used in components: **DeliveryStream**

#### **180.2.661 DeliveryStreamToleranceOptionSide**

Indicates whether the tolerance is at the seller's or buyer's option.

Type: **int**

Allowed values in DeliveryStreamToleranceOptionSideCodeSet:

Code	Name	Description
1	Buyer	Buyer
2	Seller	Seller

Used in components: [DeliveryStream](#)

### 180.2.662 DeliveryStreamToleranceType

Specifies the tolerance value type.

Type: [int](#)

Allowed values in DeliveryScheduleToleranceTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in components: [DeliveryStream](#)

### 180.2.663 DeliveryStreamToleranceUnitOfMeasure

Specifies the tolerance value's unit of measure (UOM).

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels



Code	Name	Description
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters

Code	Name	Description
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot

Code	Name	Description
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [DeliveryStream](#)

#### **180.2.664 DeliveryStreamTotalNegativeTolerance**

The negative percent tolerance which applies to the total quantity delivered over all shipment periods.

Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: [Percentage](#)

Used in components: [DeliveryStream](#)

#### **180.2.665 DeliveryStreamTotalPositiveTolerance**

The positive percent tolerance which applies to the total quantity delivered over all shipment periods.

Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: [Percentage](#)

Used in components: [DeliveryStream](#)

#### **180.2.666 DeliveryStreamTransportEquipment**

The transportation equipment with which the commodity product will be delivered and received.

Type: **String**

Used in components: **DeliveryStream**

### **180.2.667 DeliveryStreamType**

Specifies the type of delivery stream.

Type: **int**

Allowed values in DeliveryStreamTypeCodeSet:

Code	Name	Description
0	Periodic	Periodic (default if not specified)
1	Initial	Initial
2	Single	Single

Used in components: **DeliveryStream**

### **180.2.668 DeliveryStreamWithdrawalPoint**

The point at which the commodity product will be withdrawn prior to delivery.

Type: **String**

Used in components: **DeliveryStream**

### **180.2.669 DeliveryType**

Identifies type of settlement

Type: **int**

Allowed values in DeliveryTypeCodeSet:

Code	Name	Description
0	VersusPayment	"Versus Payment": Deliver (if sell) or Receive (if buy) vs. (against) Payment
1	Free	"Free": Deliver (if sell) or Receive (if buy) Free
2	TriParty	Tri-Party

Code	Name	Description
3	HoldInCustody	Hold In Custody
4	DeliverByValue	Deliver-by-Value. In the context of EU SFTR reporting, indicates that the transaction is to be or was settled using the DBV mechanism.

Used in components: **FinancingDetails**

#### **180.2.670 DeltaCrossed**

Indicates that the party has taken a position on both a put and a call on the same underlying asset.

Type: **Boolean**

Used in messages: **TradeCaptureReport**

#### **180.2.671 DerivativeCapPrice**

Used to express the ceiling price of a capped call.

See CapPrice(1199) for complete definition.

Type: **Price**

Used in components: **DerivativeInstrument**

#### **180.2.672 DerivativeCFIcode**

The type of security using ISO 10962 standard, Classification of Financial Instruments (CFI code) values.

See CFIcode(461) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

#### **180.2.673 DerivativeContractMultiplier**

Specifies the ratio or multiply factor to convert from nominal units (e.g. contracts) to total units (e.g. shares) (e.g. 1.0, 100, 1000, etc.).

See ContractMultiplier(231) for complete definition.

Type: **float**

Used in components: **DerivativeInstrument**

#### **180.2.674 DerivativeContractMultiplierUnit**

Indicates the type of multiplier being applied to the contract. Can be optionally used to further define what unit DerivativeContractMultiplier(1266) is expressed in.

See ContractMultiplierUnit(1435) for complete definition.

Type: **int**

Allowed values in ContractMultiplierUnitCodeSet:

Code	Name	Description
0	Shares	Shares
1	Hours	Hours
2	Days	Days

Used in components: **DerivativeInstrument**

#### **180.2.675 DerivativeContractSettlMonth**

Specifies when the contract (i.e. MBS/TBA) will settle.

See ContractSettlMonth(667) for complete definition.

Type: **MonthYear**

Used in components: **DerivativeInstrument**

#### **180.2.676 DerivativeContraryInstructionEligibilityIndicator**

Identifies whether the option instrument is eligible for contrary instructions at the time of exercise. The contrariness of an instruction will be determined in the context of DerivativeInTheMoneyCondition(2684). When not specified, the eligibility is undefined or not applicable.

See ContraryInstructionEligibilityIndicator(2685) for complete definition.

Type: **Boolean**

Used in components: **DerivativeInstrument**

**180.2.677 DerivativeCountryOfIssue**

ISO Country code of instrument issue (e.g. the country portion typically used in ISIN).

See CountryOfIssue(470) for complete definition.

Type: **Country**

Used in components: **DerivativeInstrument**

**180.2.678 DerivativeEncodedIssuer**

Encoded (non-ASCII characters) representation of the DerivativeIssuer(1275) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the DerivativeIssuer(1275) field.

See EncodedIssuer(349) for complete definition.

Type: **data**

Used in components: **DerivativeInstrument**

**180.2.679 DerivativeEncodedIssuerLen**

Byte length of encoded (non-ASCII characters) DerivativeEncodedSecurityDesc (1281) field.

See EncodedIssuerLen(348) for complete definition.

Type: **Length**

Used in components: **DerivativeInstrument**

**180.2.680 DerivativeEncodedSecurityDesc**

Encoded (non-ASCII characters) representation of the DerivativeSecurityDesc(1279) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the DerivativeSecurityDesc(1279) field.

See EncodedSecurityDesc(351) for complete definition.

Type: **data**

Used in components: **DerivativeInstrument**

**180.2.681 DerivativeEncodedSecurityDescLen**

Byte length of encoded (non-ASCII characters) DerivativeEncodedSecurityDesc (1281) field.

See EncodedSecurityDescLen(350) for complete definition.

Type: **Length**

Used in components: **DerivativeInstrument**

**180.2.682 DerivativeEventDate**

Date of event.

See EventDate(866) for complete definition.

Type: **LocalMktDate**

Used in groups: **DerivativeEventsGrp**

**180.2.683 DerivativeEventPx**

Predetermined price of issue at event.

See EventPx(867) for complete definition.

Type: **Price**

Used in groups: **DerivativeEventsGrp**

**180.2.684 DerivativeEventsGrp**

---

Name	Mult.	Type	Description
NoDerivativeEvents	[1..1]	NumInGroup	
DerivativeEventType	[0..1]	CodeSet	
DerivativeEventDate	[0..1]	LocalMktDate	
DerivativeEventTime	[0..1]	UTCTimestamp	
DerivativeEventPx	[0..1]	Price	
DerivativeEventText	[0..1]	String	

---

Used in components: **DerivativeInstrument**



**180.2.685 DerivativeEventText**

Comments related to the event.

See EventText(868) for complete definition.

Type: **String**

Used in groups: **DerivativeEventsGrp**

**180.2.686 DerivativeEventTime**

Specific time of event. To be used in combination with DerivativeEventDate(1288).

See EventTime(1145) for complete definition.

Type: **UTCTimestamp**

Used in groups: **DerivativeEventsGrp**

**180.2.687 DerivativeEventType**

Code to represent the type of event.

See EventType(865) for complete definition.

Type: **int**

Allowed values in EventTypeCodeSet:

Code	Name	Description
1	Put	Put
2	Call	Call
3	Tender	Tender
4	SinkingFundCall	Sinking fund call
5	Activation	Activation
6	Inactivation	Inactivation
7	LastEligibleTradeDate	Last eligible trade date
8	SwapStartDate	Swap start date
9	SwapEndDate	Swap end date
10	SwapRollDate	Swap roll date
11	SwapNextStartDate	Swap next start date

Code	Name	Description
12	SwapNextRollDate	Swap next roll date
13	FirstDeliveryDate	First delivery date
14	LastDeliveryDate	Last delivery date
15	InitialInventoryDueDate	Initial inventory due date
16	FinalInventoryDueDate	Final inventory due date
17	FirstIntentDate	First intent date
18	LastIntentDate	Last intent date
19	PositionRemovalDate	Position removal date
20	MinimumNotice	Minimum notice
21	DeliveryStartTime	Delivery start time
22	DeliveryEndTime	Delivery end time
23	FirstNoticeDate	First notice date. The first day that a notice of intent to deliver a commodity can be made by a clearing house to a buyer in fulfillment of a given month's futures contract.
24	LastNoticeDate	Last notice date. The last day on which a clearing house may inform an investor that a seller intends to make delivery of a commodity that the investor previously bought in a futures contract. The date is governed by the rules of different exchanges and clearing houses, but may also be stated in the futures contract itself.
25	FirstExerciseDate	First exercise date
26	RedemptionDate	Redemption date
27	TrdCntntnEfctvDt	Trade continuation effective date
99	Other	Other

Used in groups: [DerivativeEventsGrp](#)

### 180.2.688 DerivativeExerciseStyle

Type of exercise.

See ExerciseStyle(1194) for complete definition.

Type: [int](#)

Allowed values in ExerciseStyleCodeSet:

Code	Name	Description
0	European	European
1	American	American
2	Bermuda	Bermuda
99	Other	Other

Used in components: [DerivativeInstrument](#)

### 180.2.689 DerivativeFloorPrice

Used to express the floor price of a capped put.

See FloorPrice(1200) for complete definition.

Type: [Price](#)

Used in components: [DerivativeInstrument](#)

### 180.2.690 DerivativeFlowScheduleType

The industry standard flow schedule by which electricity or natural gas is traded. Schedules exist by regions and on-peak and off-peak status, such as "Western Peak".

See FlowScheduleType(1439) for complete definition.

Type: [int](#)

Allowed values in FlowScheduleTypeCodeSet:

Code	Name	Description
0	NERCEasternOffPeak	NERC Eastern Off-Peak
1	NERCWesternOffPeak	NERC Western Off-Peak
2	NERCCalendarAllDaysInMonth	NERC Calendar-All Days in month
3	NERCEasternPeak	NERC Eastern Peak
4	NERCWesternPeak	NERC Western Peak
5	AllTimes	All times
6	OnPeak	On peak
7	OffPeak	Off peak
8	Base	Base

Code	Name	Description
9	Block	Block
99	Other	Other

Used in components: [DerivativeInstrument](#)

### 180.2.691 DerivativeInstrAttribType

Type of instrument attribute.

See InstrAttribType(871) for complete definition.

Type: [int](#)

Allowed values in InstrAttribTypeCodeSet:

Code	Name	Description
1	Flat	Flat (securities pay interest on a current basis but are traded without interest)
2	ZeroCoupon	Zero coupon
3	InterestBearing	Interest bearing (for Euro commercial paper when not issued at discount)
4	NoPeriodicPayments	No periodic payments
5	VariableRate	Variable rate
6	LessFeeForPut	Less fee for put
7	SteppedCoupon	Stepped coupon
8	CouponPeriod	Coupon period (if not semi-annual). Supply redemption date in the InstrAttribValue(872) field.
9	When	When [and if] issued
10	OriginalIssueDiscount	Original issue discount
11	Callable	Callable, puttable
12	EscrowedToMaturity	Escrowed to Maturity
13	EscrowedToRedemptionDate	Escrowed to redemption date - callable. Supply redemption date in the InstrAttribValue(872) field.
14	PreRefunded	Pre-refunded
15	InDefault	In default
16	Unrated	Unrated
17	Taxable	Taxable

Code	Name	Description
18	Indexed	Indexed
19	SubjectToAlternativeMinimumTax	Subject To Alternative Minimum Tax
20	OriginalIssueDiscountPrice	Original issue discount price. Supply price in the InstrAttribValue(872) field.
21	CallableBelowMaturityValue	Callable below maturity value
22	CallableWithoutNotice	Callable without notice by mail to holder unless registered
23	PriceTickRulesForSecurity	Price tick rules for security
24	TradeTypeEligibilityDetailsForSecurity	Trade type eligibility details for security
25	InstrumentDenominator	Instrument denominator
26	InstrumentNumerator	Instrument numerator
27	InstrumentPricePrecision	Instrument price precision
28	InstrumentStrikePrice	Instrument strike price
29	TradeableIndicator	Tradeable indicator
30	InstrumentEligibleAnonOrders	Instrument is eligible to accept anonymous orders
31	MinGuaranteedFillVolume	Minimum guaranteed fill volume
32	MinGuaranteedFillStatus	Minimum guaranteed fill status
33	TradeAtSettlementEligibility	Trade at settlement (TAS) eligibility
34	TestInstrument	Test instrument. Instrument that is tradable but has no effect on the positions, exchange turnover etc.
35	DummyInstrument	Dummy instrument. Instrument that is normally halted and is only activated for trading under very special conditions (e.g. temporarily assigned for newly listed instrument). Use of a dummy instrument generally applies to systems that are unable to add reference data for new instruments intraday.
36	NegativeSettlementPriceEligibility	Negative settlement price eligibility
37	NegativeStrikePriceEligibility	Negative strike price eligibility
38	USStdContractInd	US standard contract indicator. Indicates through InstrAttribValue(872) - values Y or N - whether the underlying asset in the trade references or is economically related to a contract listed in Appendix B of CFTC Part 43 regulation. See <a href="http://www.ecfr.gov/cgi-bin/text-idx?SID=4b2d1078ad68f6564a89d7ff6c52ec43&amp;node=17:2.0.1.1.3.0.1.8.2&amp;rgn=div">http://www.ecfr.gov/cgi-bin/text-idx?SID=4b2d1078ad68f6564a89d7ff6c52ec43&amp;node=17:2.0.1.1.3.0.1.8.2&amp;rgn=div</a> or refer to Appendix B to Part 43 in the final rule at <a href="http://www.cftc.gov/ucm/groups/public/@lrfederalregister/documents/file/2013-12133a.pdf">http://www.cftc.gov/ucm/groups/public/@lrfederalregister/documents/file/2013-12133a.pdf</a>
39	AdmittedToTradingOnTradingVenue	Admitted to trading on a trading venue
40	AverageDailyNotionalAmount	Average daily notional amount

Code	Name	Description
41	AverageDailyNumberTrades	Average daily number of trades
99	Text	Text. Supply the text value in InstrAttribValue(872).

Used in groups: [DerivativeInstrumentAttribute](#)

#### **180.2.692 DerivativeInstrAttribValue**

Attribute value appropriate to the DerivativeInstrAttribValue(1313) field.

See InstrAttribValue(872) for complete definition.

Type: [String](#)

Used in groups: [DerivativeInstrumentAttribute](#)

#### **180.2.693 DerivativeInstrmtAssignmentMethod**

Method under which assignment was conducted.

See InstrmtAssignmentMethod(1049) for complete definition.

Type: [char](#)

Allowed values in InstrmtAssignmentMethodCodeSet:

Code	Name	Description
P	ProRata	Pro rata
R	Random	Random

Used in components: [DerivativeInstrument](#)

#### **180.2.694 DerivativeInstrRegistry**

Values may include BIC for the depository or custodian who maintain ownership records, the ISO country code for the location of the record, or the value ZZ to specify physical ownership of the security (e.g. stock certificate).

See InstrRegistry(543) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

### 180.2.695 DerivativeInstrumentAttribute

Name	Mult.	Type	Description
NoDerivativeInstrAttrib	[1..1]	NumInGroup	
DerivativeInstrAttribType	[0..1]	CodeSet	
DerivativeInstrAttribValue	[0..1]	String	

Used in components: **DerivativeSecurityDefinition**

### 180.2.696 DerivativeInstrument

Name	Mult.	Type	Description
DerivativeSymbol	[0..1]	String	Common, "human understood" representation of the security. SecurityID value can be specified if no symbol exists (e.g. non-exchange traded Collective Investment Vehicles). Use "[N/A]" for products which do not have a symbol. Required if DerivativeInstrument component is marked as required where the component is used.
DerivativeSymbolSfx	[0..1]	CodeSet	
DerivativeSecurityID	[0..1]	String	Takes precedence in identifying security to counterparty over SecurityAltID block
DerivativeSecurityIDSource	[0..1]	CodeSet	
DerivativeSecurityAltIDGrp	[0..*]	Group	
DerivativeProduct	[0..1]	CodeSet	
DerivativeProductComplex	[0..1]	String	Identifies an entire suite of products for a given market. In Futures this may be "interest rates", "agricultural", "equity indexes", etc
DerivFlexProductEligibilityIndicator	[0..1]	Boolean	Used to indicate if a product or group of product supports the creation of flexible securities
DerivativeSecurityGroup	[0..1]	String	
DerivativeCFIcode	[0..1]	String	It is recommended that CFIcode be used instead of SecurityType for non-Fixed Income instruments.

Name	Mult.	Type	Description
DerivativeUPICode	[0..1]	String	
DerivativeSecurityType	[0..1]	CodeSet	It is recommended that CFICode be used instead of SecurityType for non-Fixed Income instruments. Required for Fixed Income. Refer to Volume 7 - Fixed Income. Futures and Options should be specified using the CFICode[461] field instead of SecurityType[167] (Refer to Volume 7 - Recommendations and Guidelines for Futures and Options Markets.)
DerivativeSecuritySubType	[0..1]	String	
DerivativeMaturityMonthYear	[0..1]	MonthYear	Applicable for standardized derivatives which are typically only referenced by month and year (e.g. S and P futures). Note MaturityDate (a full date) can also be specified.
DerivativeMaturityDate	[0..1]	LocalMktDate	Note that standardized derivatives which are typically only referenced by month and year (e.g. S and P futures).may use MaturityMonthYear and or this field. When using MaturityMonthYear, it is recommended that markets and sell sides report the MaturityDate on all outbound messages as a means of data enrichment.
DerivativeMaturityTime	[0..1]	TZTimeOnly	
DerivativeSettleOnOpenFlag	[0..1]	String	
DerivativeInstrmtAssignmentMethod	[0..1]	CodeSet	
DerivativeSecurityStatus	[0..1]	CodeSet	
DerivativeIssueDate	[0..1]	LocalMktDate	Date instrument was issued. For Fixed Income IOIs for new issues, specifies the issue date.
DerivativeInstrRegistry	[0..1]	String	Can be used in conjunction with ISIN to address ISIN uniqueness issues.
DerivativeCountryOfIssue	[0..1]	Country	Can be used in conjunction with non-ISIN SecurityID (e.g. CUSIP for Municipal Bonds without ISIN) to provide uniqueness.
DerivativeStateOrProvinceOfIssue	[0..1]	String	
DerivativeLocaleOfIssue	[0..1]	String	
DerivativeStrikePrice	[0..1]	Price	
DerivativeStrikeCurrency	[0..1]	Currency	
DerivativeStrikeCurrencyCodeSource	[0..1]	CodeSet	
DerivativeStrikeMultiplier	[0..1]	float	
DerivativeStrikeValue	[0..1]	float	



Name	Mult.	Type	Description
DerivativeOptAttribute	[0..1]	char	
DerivativeContractMultiplier	[0..1]	float	
DerivativeContractMultiplierUnit	[0..1]	CodeSet	
DerivativeFlowScheduleType	[0..1]	CodeSet	
DerivativeMinPriceIncrement	[0..1]	float	
DerivativeMinPriceIncrementAmount	[0..1]	Amt	
DerivativeUnitOfMeasure	[0..1]	CodeSet	
DerivativeUnitOfMeasureQty	[0..1]	Qty	
DerivativeUnitOfMeasureCurrency	[0..1]	Currency	
DerivativeUnitOfMeasureCurrency-CodeSource	[0..1]	CodeSet	
DerivativePriceUnitOfMeasure	[0..1]	CodeSet	
DerivativePriceUnitOfMeasureQty	[0..1]	Qty	
DerivativePriceUnitOfMeasureCurrency	[0..1]	Currency	
DerivativePriceUnitOfMeasureCurrencyCodeSource	[0..1]	CodeSet	
DerivativeSettlMethod	[0..1]	CodeSet	
DerivativePriceQuoteMethod	[0..1]	CodeSet	
DerivativeValuationMethod	[0..1]	CodeSet	
DerivativePriceQuoteCurrency	[0..1]	Currency	
DerivativePriceQuoteCurrencyCodeSource	[0..1]	CodeSet	
DerivativeListMethod	[0..1]	CodeSet	
DerivativeCapPrice	[0..1]	Price	
DerivativeFloorPrice	[0..1]	Price	
DerivativePutOrCall	[0..1]	CodeSet	
DerivativeInTheMoneyCondition	[0..1]	CodeSet	Used to express in-the-moneyness behavior in general terms for the option without the use of DerivativeStrikePrice(1261) and DerivativePutOrCall(1323).
DerivativeContraryInstructionEligibilityIndicator	[0..1]	Boolean	
DerivativeExerciseStyle	[0..1]	CodeSet	
DerivativeOptPayoutAmount	[0..1]	Amt	
DerivativeTimeUnit	[0..1]	CodeSet	

Name	Mult.	Type	Description
DerivativeSecurityExchange	[0..1]	Exchange	Can be used to identify the security.
DerivativePositionLimit	[0..1]	int	
DerivativeNTPositionLimit	[0..1]	int	
DerivativeIssuer	[0..1]	String	
DerivativeEncodedIssuerLen	[0..1]	Length	Must be set if DerivativeEncodedIssuer(1278) field is specified and must immediately precede it.
DerivativeEncodedIssuer	[0..1]	data	
DerivativeSecurityDesc	[0..1]	String	
DerivativeEncodedSecurityDescLen	[0..1]	Length	Must be set if DerivativeEncodedSecurityDesc(1280) field is specified and must immediately precede it.
DerivativeEncodedSecurityDesc	[0..1]	data	
DerivativeSecurityXML	[0..1]	Component	Embedded XML document describing security.
DerivativeContractSettlMonth	[0..1]	MonthYear	Must be present for MBS or TBA
DerivativeEventsGrp	[0..*]	Group	
DerivativeInstrumentParties	[0..*]	Group	

Used in components: [DerivativeSecurityDefinition](#)

Used in messages: [DerivativeSecurityListRequest](#)

### 180.2.697 DerivativeInstrumentParties

Name	Mult.	Type	Description
NoDerivativeInstrumentParties	[1..1]	NumInGroup	Should contain unique combinations of DerivativeInstrumentPartyID, DerivativeInstrumentPartyIDSource, and DerivativeInstrumentPartyRole
DerivativeInstrumentPartyID	[0..1]	String	Used to identify party id related to instrument series
DerivativeInstrumentPartyIDSource	[0..1]	CodeSet	Used to identify source of instrument series party id
DerivativeInstrumentPartyRole	[0..1]	CodeSet	Used to identify the role of instrument series party id
DerivativeInstrumentPartyRoleQualifier	[0..1]	CodeSet	

Name	Mult.	Type	Description
DerivativeInstrumentPartySubIDsGrp	[0..*]	Group	

Used in components: [DerivativeInstrument](#)

### 180.2.698 DerivativeInstrumentPartyID

Party identifier/code.

See PartyID(448) for complete definition.

Type: [String](#)

Used in groups: [DerivativeInstrumentParties](#)

### 180.2.699 DerivativeInstrumentPartyIDSource

Identifies class or source of the DerivativeInstrumentPartyID (1293) value.

Required if DerivativeInstrumentPartyID(1293) is specified.

See PartyIDSource(447) for complete definition.

Type: [char](#)

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number

Code	Name	Description
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).

Code	Name	Description
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **DerivativeInstrumentParties**

### 180.2.700 DerivativeInstrumentPartyRole

Identifies the type or role of the DerivativeInstrumentPartyID (1293) specified.

See PartyRole(452) for complete definition.

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)

Code	Name	Description
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange

Code	Name	Description
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.

Code	Name	Description
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.



Code	Name	Description
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.

Code	Name	Description
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **DerivativeInstrumentParties**

### 180.2.701 DerivativeInstrumentPartyRoleQualifier

Used to further qualify the value of DerivativeInstrumentPartyRole(1295).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member

Code	Name	Description
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.

Code	Name	Description
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: [DerivativeInstrumentParties](#)

### 180.2.702 DerivativeInstrumentPartySubID

Party sub-identifier.

See PartySubID(523) for complete definition.

Type: [String](#)

Used in groups: [DerivativeInstrumentPartySubIDsGrp](#)

### 180.2.703 DerivativeInstrumentPartySubIDsGrp

Name	Mult.	Type	Description
<a href="#">NoDerivativeInstrumentPartySubIDs</a>	[1..1]	NumInGroup	
<a href="#">DerivativeInstrumentPartySubID</a>	[0..1]	String	
<a href="#">DerivativeInstrumentPartySubIDType</a>	[0..1]	CodeSet	

Used in groups: [DerivativeInstrumentParties](#)

**180.2.704 DerivativeInstrumentPartySubIDType**

Type of party sub-identifier.

See PartySubIDType(803) for complete definition.

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type

Code	Name	Description
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.

Code	Name	Description
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.



Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **DerivativeInstrumentPartySubIDsGrp**

**180.2.705 DerivativeInTheMoneyCondition**

Specifies an option instrument's "in the money" condition in general terms.

See InTheMoneyCondition(2681) for complete definition.

Type: **int**

Allowed values in InTheMoneyConditionCodeSet:

Code	Name	Description
0	StandardITM	Standard in-the-money. The option's strike price is less than the underlying settlement price for a call or greater than the underlying settlement price for a put.
1	ATMITM	At-the-money is in-the-money. The option's strike price of either the put or call is equal to the underlying settlement price in addition to standard in-the-money behavior.
2	ATMCallITM	At-the-money call is in-the-money. The call option's strike price is equal to the underlying settlement price in addition to standard in-the-money behavior.
3	ATMPutITM	At-the-money put is in-the-money. The put option's strike price is equal to the underlying settlement price in addition to standard in-the-money behavior.

Used in components: **DerivativeInstrument**

**180.2.706 DerivativeIssueDate**

The date on which the security is issued.

See IssueDate(225) for complete definition.

Type: **LocalMktDate**

Used in components: **DerivativeInstrument**

**180.2.707 DerivativeIssuer**

Name of security issuer.

See Issuer(106) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

**180.2.708 DerivativeListMethod**

Indicates whether instruments are pre-listed only or can also be defined via user request.

See ListMethod(1198) for complete definition.

Type: **int**

Allowed values in ListMethodCodeSet:

Code	Name	Description
0	PreListedOnly	pre-listed only
1	UserRequested	user requested

Used in components: **DerivativeInstrument**

**180.2.709 DerivativeLocaleOfIssue**

Identifies the locale or region of issue.

See LocaleOfIssue(472) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

**180.2.710 DerivativeMaturityDate**

Date of maturity.

See MaturityDate(541) for complete definition.

Type: **LocalMktDate**

Used in components: **DerivativeInstrument**

**180.2.711 DerivativeMaturityMonthYear**

Month and Year of the maturity (used for standardized futures and options).

See MaturityMonthYear(200) for complete definition.

Type: **MonthYear**

Used in components: **DerivativeInstrument**

**180.2.712 DerivativeMaturityTime**

Time of security's maturity expressed in local time with offset to UTC specified.

See MaturityTime(1079) for complete definition.

Type: **TZTimeOnly**

Used in components: **DerivativeInstrument**

**180.2.713 DerivativeMinPriceIncrement**

Minimum price increase for a given exchange-traded Instrument.

See MinPriceIncrement(969) for complete definition.

Type: **float**

Used in components: **DerivativeInstrument**

**180.2.714 DerivativeMinPriceIncrementAmount**

Minimum price increment amount associated with the minimum price increment.

See MinPriceIncrementAmount(1146) for complete definition.

Type: **Amt**

Used in components: **DerivativeInstrument**

**180.2.715 DerivativeNTPositionLimit**

Position limit in the near-term contract for a given exchange-traded product.

See NTPositionLimit(971) for complete definition.

Type: **int**

Used in components: **DerivativeInstrument**

**180.2.716 DerivativeOptAttribute**

Provided to support versioning of option contracts as a result of corporate actions or events. Use of this field is defined by counterparty agreement or market conventions.

See OptAttribute(206) for complete definition.

Type: **char**

Used in components: **DerivativeInstrument**

#### **180.2.717 DerivativeOptPayoutAmount**

Cash amount indicating the pay out associated with an option. For binary options this is a fixed amount.

See OptPayoutAmount(1195) for complete definition.

Type: **Amt**

Used in components: **DerivativeInstrument**

#### **180.2.718 DerivativePositionLimit**

Position limit for a given exchange-traded product.

See PositionLimit(970) for complete definition.

Type: **int**

Used in components: **DerivativeInstrument**

#### **180.2.719 DerivativePriceQuoteCurrency**

Default currency in which the price is quoted. Defined at the instrument level. Used in place of Currency(tag 15) to express the currency of a product when the former is implemented as the FX dealt currency.

See PriceQuoteCurrency(1524) for complete definition.

Type: **Currency**

Used in components: **DerivativeInstrument**

#### **180.2.720 DerivativePriceQuoteCurrencyCodeSource**

Identifies class or source of the DerivativePriceQuoteCurrency(1576) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [DerivativeInstrument](#)

#### 180.2.721 DerivativePriceQuoteMethod

Specifies the method for price quotation.

See PriceQuoteMethod(1196) for complete definition.

Type: [String](#)

Allowed values in PriceQuoteMethodCodeSet:

Code	Name	Description
STD	Standard	Standard, money per unit of a physical
INX	Index	Index
INT	InterestRateIndex	Interest rate Index
PCTPAR	PercentOfPar	Percent of Par

Used in components: [DerivativeInstrument](#)

#### 180.2.722 DerivativePriceUnitOfMeasure

Used to express the UOM of the price if different from the contract.

See PriceUnitOfMeasureQty(1191) for complete definition.

Type: [String](#)

## Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point



Code	Name	Description
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter

Code	Name	Description
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: **DerivativeInstrument**

#### **180.2.723 DerivativePriceUnitOfMeasureCurrency**

Indicates the currency of the price unit of measure.

Conditionally required when DerivativePriceUnitOfMeasure(1315) = Ccy.

See PriceUnitOfMeasureCurrency(1717) for complete definition.

Type: **Currency**

Used in components: **DerivativeInstrument**

#### **180.2.724 DerivativePriceUnitOfMeasureCurrencyCodeSource**

Identifies class or source of the DerivativePriceUnitOfMeasureCurrency(1723) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [DerivativeInstrument](#)

#### **180.2.725 DerivativePriceUnitOfMeasureQty**

Used to express the UOM Quantity of the price if different from the contract.

See PriceUnitOfMeasureQty(1192) for complete definition.

Type: [Qty](#)

Used in components: [DerivativeInstrument](#)

#### **180.2.726 DerivativeProduct**

The type of product the security is associated with.

See Product(460) for complete definition.

Type: [int](#)

Allowed values in ProductCodeSet:

Code	Name	Description
1	AGENCY	AGENCY
2	COMMODITY	COMMODITY
3	CORPORATE	CORPORATE
4	CURRENCY	CURRENCY
5	EQUITY	EQUITY

Code	Name	Description
6	GOVERNMENT	GOVERNMENT
7	INDEX	INDEX
8	LOAN	LOAN
9	MONEYMARKET	MONEYMARKET
10	MORTGAGE	MORTGAGE
11	MUNICIPAL	MUNICIPAL
12	OTHER	OTHER
13	FINANCING	FINANCING

Used in components: [DerivativeInstrument](#)

#### **180.2.727 DerivativeProductComplex**

Identifies an entire suite of products for a given market.

See ProductComplex(1227) for complete definition.

Type: [String](#)

Used in components: [DerivativeInstrument](#)

#### **180.2.728 DerivativePutOrCall**

Indicates whether an option contract is a put, call, chooser or undetermined.

See PutOrCall(201) for complete definition.

Type: [int](#)

Allowed values in PutOrCallCodeSet:

Code	Name	Description
0	Put	Put. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate receiver or into a CDS contract as a seller of protection or for the case of a Floor.

Code	Name	Description
1	Call	Call. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate payer or into a CDS contract as a buyer of protection or for the case of a Cap.
2	Other	Other. In the context of ESMA RTS 22 reporting, this value may be used when, at the time of execution, the option right cannot be determined.
3	Chooser	Chooser. Indicates that the option buyer may choose to buy or sell the underlying security on exercise or if a Swaption to pay or receive the underlying IRS cash flow stream or to buy or sell CDS protection.

Used in components: [DerivativeInstrument](#)

#### 180.2.729 DerivativeSecurityAltID

Alternate derivative security identifier value of DerivativeSecurityAltIDSource(1220) type.

Requires DerivativeSecurityAltIDSource(1220).

Type: [String](#)

Used in groups: [DerivativeSecurityAltIDGrp](#)

#### 180.2.730 DerivativeSecurityAltIDGrp

Name	Mult.	Type	Description
<a href="#">NoDerivativeSecurityAltID</a>	[1..1]	NumInGroup	
<a href="#">DerivativeSecurityAltID</a>	[0..1]	String	
<a href="#">DerivativeSecurityAltIDSource</a>	[0..1]	CodeSet	

Used in components: [DerivativeInstrument](#)

#### 180.2.731 DerivativeSecurityAltIDSource

Identifies class or source of the DerivativeSecurityAltID(1219) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier

Code	Name	Description
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [DerivativeSecurityAltIDGrp](#)

### 180.2.732 DerivativeSecurityDefinition

Name	Mult.	Type	Description
<a href="#">DerivativeInstrument</a>	[0..1]	Component	Optional block which can be used to to summarize common attributes shared across a set of option instruments which belong to the same series.
<a href="#">DerivativeInstrumentAttribute</a>	[0..*]	Group	Additional attribution for the instrument series
<a href="#">MarketSegmentGrp</a>	[0..*]	Group	Security trading and listing attributes for the series level
<a href="#">SecurityClassificationGrp</a>	[0..*]	Group	Used to specify forms of product classifications

Used in messages: [DerivativeSecurityList](#), [DerivativeSecurityListUpdateReport](#)

### 180.2.733 DerivativeSecurityDesc

Can be used by the venue or one of the trading parties to provide a non-normative textual description for the financial instrument.

See SecurityDesc(107) for complete definition.

Type: [String](#)

Used in components: [DerivativeInstrument](#)

**180.2.734 DerivativeSecurityExchange**

Market used to help identify a security.

See SecurityExchange(207) for complete definition.

Type: **Exchange**

Used in components: **DerivativeInstrument**

**180.2.735 DerivativeSecurityGroup**

An exchange specific name assigned to a group of related securities which may be concurrently affected by market events and actions.

See SecurityGroup(1151) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

**180.2.736 DerivativeSecurityID**

Security identifier value (e.g. CUSIP, SEDOL, ISIN, etc).

Requires DerivativeSecurityIDSource(1217).

See SecurityID(48) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

**180.2.737 DerivativeSecurityIDSource**

Identifies class or source of the DerivativeSecurityID(1217) value.

See SecurityIDSource(22) for complete definition.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

---

Code	Name	Description
1	CUSIP	CUSIP

---



Code	Name	Description
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".

Code	Name	Description
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **DerivativeInstrument**

### 180.2.738 DerivativeSecurityStatus

Indicates the current state of the derivative instrument.

See SecurityStatus(965) for complete definition.

Type: **String**

Allowed values in SecurityStatusCodeSet:

Code	Name	Description
1	Active	Active. Instrument is active, i.e. trading is possible.
2	Inactive	Inactive. Instrument has previously been active and is now no longer traded but has not expired yet. The instrument may become active again.
3	ActiveClosingOrdersOnly	Active, closing orders only. Instrument is active but only orders closing positions (reducing risk) are allowed.
4	Expired	Expired. Instrument has expired. E.g. An instrument may expire due to reaching maturity or expired based on contract definitions or exchange rules.
5	Delisted	Delisted. Instrument has been removed from securities reference data. Delisting rules varies from exchange to exchange, which may include non-compliance of capitalization, revenue, consecutive minimum closing price. The instrument may become listed again once the instrument is back in compliance. A delisted instrument would not trade on the exchange but it may still be traded over-the-counter (e.g. OTCBB) or on Pink Sheets, or other similar trading service.
6	KnockedOut	Knocked-out. Instrument has breached a pre-defined price threshold.
7	KnockOutRevoked	Knock-out revoked. Instrument reinstated, i.e. threshold has not been breached.

Code	Name	Description
8	PendingExpiry	Pending Expiry. Instrument is currently still active but will expire after the current business day. For example, a contract that expires intra-day (e.g. at noon time) and is no longer tradeable but will still show up in the current day's order book with related statistics.
9	Suspended	Suspended. Instrument has been temporarily disabled for trading (i.e. halted).
10	Published	Published. Instrument information is provided prior to its first activation.
11	PendingDeletion	Pending Deletion. Instrument is awaiting deletion from security reference data.

Used in components: [DerivativeInstrument](#)

### 180.2.739 DerivativeSecuritySubType

Sub-type qualification/identification of the security type.

See SecuritySubType(762) for complete definition.

Type: [String](#)

Used in components: [DerivativeInstrument](#)

### 180.2.740 DerivativeSecurityType

The type of security.

See SecurityType(167) for complete definition.

Type: [String](#)

Allowed values in SecurityTypeCodeSet:

Code	Name	Description
ABS	AssetBackedSecurities	Asset-backed Securities
AN	OtherAnticipationNotes	Other Anticipation Notes (BAN, GAN, etc.)
BA	BankersAcceptance	Bankers Acceptance
BRADY	BradyBond	Brady Bond

Code	Name	Description
CORP	CorporateBond	Corporate Bond
CS	CommonStock	Common Stock
EUSUPRA	EuroSupranationalCoupons	Euro Supranational Coupons. Identify the issuer name in Issuer(106).
FOR	ForeignExchangeContract	Foreign Exchange Contract
MF	MutualFund	Mutual Fund
REPO	Repurchase	Repurchase
TERM	TermLoan	Term Loan
BDN	BankDepositoryNote	Bank Depository Note
CAN	CanadianTreasuryNotes	Canadian Treasury Notes
CAP	Cap	Cap. In an interest rate cap, the buyer receives payments at the end of each period in which the rate indec exceeds the agreed strike rate.
CMB	CanadianMortgageBonds	Canadian Mortgage Bonds
COFO	CertificateOfObligation	Certificate Of Obligation
CPP	CorporatePrivatePlacement	Corporate Private Placement
FAC	FederalAgencyCoupon	Federal Agency Coupon
FORWARD	Forward	Forward
FXNDF	NonDeliverableForward	Non-deliverable forward
MLEG	MultilegInstrument	Multileg Instrument
PS	PreferredStock	Preferred Stock
RVLV	RevolverLoan	Revolver Loan
BN	BankNotes	Bank Notes
BUYSELL	BuySellback	Buy Sellback
CB	ConvertibleBond	Convertible Bond
CDS	CreditDefaultSwap	Credit Default Swap
CMBS	Corp	Corp. Mortgage-backed Securities
COFP	CertificateOfParticipation	Certificate Of Participation
CTB	CanadianTreasuryBills	Canadian Treasury Bills
DR	DepositoryReceipts	Depository Receipts
FADN	FederalAgencyDiscountNote	Federal Agency Discount Note
FXSPOT	FXSpot	FX Spot
NONE	NoSecurityType	No Security Type
RVLVTRM	Revolver	Revolver/Term Loan
BOX	BillofExchanges	Bill Of Exchanges

Code	Name	Description
BRIDGE	BridgeLoan	Bridge Loan
CLLR	Collar	Collar. In an interest rate collar, this is a combination of a cap and a floor.
CMO	CollateralizedMortgageObligation	Collateralized Mortgage Obligation
DUAL	DualCurrency	Dual Currency
EUSOV	EuroSovereigns	Euro Sovereigns. Identify the issuer name in Issuer(106).
FXFWD	FXForward	FX Forward
GO	GeneralObligationBonds	General Obligation Bonds
PEF	PrivateExportFunding	Private Export Funding. Identify the issuer name in Issuer(106).
SECLOAN	SecuritiesLoan	Securities Loan
UST	USTreasuryNoteOld	US Treasury Note (Deprecated Value Use TNOTE)
CAMM	CanadianMoneyMarkets	Canadian Money Markets
CMDTYSWAP	CommoditySwap	Commodity swap
EUCORP	EuroCorporateBond	Euro Corporate Bond
FXSWAP	FXSwap	FX Swap
IET	IOETTEMortgage	IOETTE Mortgage
LOFC	LetterOfCredit	Letter Of Credit
MT	MandatoryTender	Mandatory Tender
PROV	CanadianProvincialBonds	Canadian Provincial Bonds
SECPLEDGE	SecuritiesPledge	Securities Pledge
SUPRA	USDSupranationalCoupons	USD Supranational Coupons. Identify the issuer name in Issuer(106).
USTB	USTreasuryBillOld	US Treasury Bill (Deprecated Value Use TBILL)
?	Wildcard	Wildcard entry for use on Security Definition Request
CD	CertificateOfDeposit	Certificate Of Deposit
DVPLDG	DeliveryVersusPledge	Delivery versus pledge
EUFRN	EuroCorporateFloatingRateNotes	Euro Corporate Floating Rate Notes
EXOTIC	Exotic	Exotic
FXNDS	NonDeliverableSwap	Non-deliverable Swap
MBS	MortgageBackedSecurities	Mortgage-backed Securities
RAN	RevenueAnticipationNote	Revenue Anticipation Note
SWING	SwingLineFacility	Swing Line Facility
TB	TreasuryBill	Treasury Bill - non US
CASH	Cash	Cash
CL	CallLoans	Call Loans

Code	Name	Description
COLLBSKT	CollateralBasket	Collateral basket. A collection of securities held as collateral in the customer's collateral fund. The collateral fund is usually managed by a custodian.
DINP	DebtorInPossession	Debtor In Possession
FLR	Floor	Floor. In an interest rate floor, the buyer receives payments at the end of each period in which the rate index is below the agreed strike rate.
FRN	USCorporateFloatingRateNotes	US Corporate Floating Rate Notes
FXBN	FXBankNote	FX Bank Note
MIO	MortgageInterestOnly	Mortgage Interest Only
OOC	OptionsOnCombo	Options on Combo
REV	RevenueBonds	Revenue Bonds
TBOND	USTreasuryBond	US Treasury Bond
CP	CommercialPaper	Commercial Paper
DEFLTED	Defaulted	Defaulted
FRA	FRA	Forward Rate Agreement
FXDN	ForeignCurrencyDiscountNote	Foreign Currency Discount Note. Discount notes issued in foreign currency by Fannie Mae.
MPO	MortgagePrincipalOnly	Mortgage Principal Only
Other	Other	Other
SFP	StructuredFinanceProduct	Structured finance product
SPCLA	SpecialAssessment	Special Assessment
TINT	InterestStripFromAnyBondOrNote	Interest Strip From Any Bond Or Note
XLINKD	IndexedLinked	Indexed Linked
DN	DepositNotes	Deposit Notes
ETN	ExchangeTradedNote	Exchange traded note
FUT	Future	Future
MPP	MortgagePrivatePlacement	Mortgage Private Placement
SPCLO	SpecialObligation	Special Obligation
STRUCT	StructuredNotes	Structured Notes
TBILL	USTreasuryBill	US Treasury Bill
TIPS	TreasuryInflationProtectedSecurities	Treasury Inflation Protected Securities
WITHDRN	Withdrawn	Withdrawn
EUCD	EuroCertificateOfDeposit	Euro Certificate Of Deposit
FWD	DerivativeForward	Derivative forward

Code	Name	Description
MPT	MiscellaneousPassThrough	Miscellaneous Pass-through
MARGNLOAN	MarginLoan	Margin loan
REPLACD	Replaced	Replaced
SPCLT	SpecialTax	Special Tax
TCAL	PrincipalStripOfACallableBondOrNote	Principal Strip Of A Callable Bond Or Note
YANK	YankeeCorporateBond	Yankee Corporate Bond
DIMSUMCORP	OffshoreIssuedChineseYuanCorporateBond	Offshore issued Chinese Yuan (CNY) denominated corporate bond
EUCP	EuroCommercialPaper	Euro Commercial Paper
IRS	InterestRateSwap	Interest Rate Swap
MATURED	Matured	Matured
PFAND	Pfandbrief	Pfandbrief. Identify the issuer name in Issuer(106).
SECDERIV	SecuritizedDerivative	Securitized derivative
TAN	TaxAnticipationNote	Tax Anticipation Note
TPRN	PrincipalStripFromANonCallableBondOrNote	Principal Strip From A Non-Callable Bond Or Note
TRS	TotalReturnSwap	Total return swap
AMENDED	Amended	Amended and restated
ETF	ExchangeTradedFund	Exchange Traded Fund
LOANLEASE	LoanLease	Loan/lease
LQN	LiquidityNote	Liquidity Note
PRCORP	PreferredCorporateBond	Preferred Corporate Bond
TAXA	TaxAllocation	Tax Allocation
TBA	ToBeAnnounced	To Be Announced
TNOTE	USTreasuryNote	US Treasury Note
DIGITAL	DigitalAsset	Digital Asset. Asset that exists only in digital form or which is the digital representation of another asset (Source: ISO 24165 - Terms and Definitions).
DIMSUMSOV	OffshoreIssuedChineseYuanSovereignBond	Offshore issued Chinese Yuan (CNY) denominated sovereign bond
MTN	MediumTermNotes	Medium Term Notes
RETIRED	Retired	Retired
TECP	TaxExemptCommercialPaper	Tax Exempt Commercial Paper
ONITE	Overnight	Overnight
OOF	OptionsOnFutures	Options on Futures

Code	Name	Description
SOV	SovereignBond	Sovereign Bond. Sovereign or government bond other than Euro and US issuer. Specify sovereign issuer in Issuer(106).
TMCP	TaxableMunicipalCP	Taxable Municipal CP
OOP	OptionsOnPhysical	Options on Physical - use not recommended
PN	PromissoryNote	Promissory Note
STN	ShortTermLoanNote	Short Term Loan Note
TFRN	USTreasuryFloatingRateNote	US Treasury Floating Rate Note
TRAN	TaxRevenueAnticipationNote	Tax Revenue Anticipation Note
OPT	Option	Option
PZFJ	PlazosFijos	Plazos Fijos
VRDN	VariableRateDemandNote	Variable Rate Demand Note
SLQN	SecuredLiquidityNote	Secured Liquidity Note
SPOTFWD	SpotForward	Spot forward
WAR	Warrant	Warrant
MCPIB	MunicipalInterestBearingCommercialPaper	Municipal Interest Bearing Commercial Paper
SWAPTION	SwapOption	Swap option
TD	TimeDeposit	Time Deposit
TMB	TaxableMunicipalBond	Taxable Municipal Bond
XMISSION	Transmission	Transmission
INDEX	Index	General type for a contract based on an established index
TLQN	TermLiquidityNote	Term Liquidity Note
VRDO	VariableRateDemandObligation	Variable Rate Demand Obligation
BDBSKT	BondBasket	Bond basket
XCN	ExtendedCommNote	Extended Comm Note
CFD	ContractForDifference	Contract for difference
YCD	YankeeCertificateOfDeposit	Yankee Certificate Of Deposit
BAB	BankAcceptedBill	Bank Accepted Bill. Also known as Bank Bill.
CRLTNSWAP	CorrelationSwap	Correlation swap
BNST	ShortTermBankNote	Short Term Bank Note
DVDNDSWAP	DividendSwap	Dividend swap
CLCP	CallableCommercialPaper	Callable Commercial Paper
EQBSKT	EquityBasket	Equity basket
CN	CommercialNote	Commercial Note
EQFWD	EquityForward	Equity forward



Code	Name	Description
CPIB	InterestBearingCommercialPaper	Interest Bearing Commercial Paper
RTRNSWAP	ReturnSwap	Return swap
EUMTN	EuroMediumTermNote	Euro Medium Term Note
VARSWAP	VarianceSwap	Variance swap
EUNCP	EuroNegotiableCommercialPaper	Euro Negotiable Commercial Paper
PRTFLIOSWAP	PortfolioSwaps	Portfolio swap
EUSTLQN	EuroStructuredLiquidityNote	Euro Structured Liquidity Note
FUTSWAP	FuturesOnASwap	Futures on a Swap
EUTD	EuroTimeDeposit	Euro Time Deposit
FWDSWAP	ForwardsOnASwap	Forwards on a Swap
FWDFRTAGMT	ForwardFreightAgreement	Forward Freight Agreement
JCD	JumboCertificateOfDeposit	Jumbo Certificate of Deposit
MMF	MoneyMarketFund	Money Market Fund
SPREADBET	SpreadBetting	Spread Betting
ETC	ExchangeTradedCommodity	Exchange traded commodity
MN	MasterNote	Master Note. Short term notes issued by Federal Farm Credit Banks Funding Corporation to provide loans and funding under Federal Farm Credit System (FFCS).
NCD	NegotiableCertificateOfDeposit	Negotiable Certificate of Deposit
NCP	NegotiableCommercialPaper	Negotiable Commercial Paper
RCD	RetailCertificateOfDeposit	Retail Certificate of Deposit
TDR	TermDepositReceipt	Term Deposit Receipt

Used in components: [DerivativeInstrument](#)

#### 180.2.741 DerivativeSecurityXML

XML definition for the security.

See SecurityXML(1185) for complete definition.

Type: [XMLData](#)

Used in components: [DerivativeSecurityXML](#)

#### 180.2.742 DerivativeSecurityXML

Name	Mult.	Type	Description
DerivativeSecurityXMLLen	[0..1]	Length	Must be set if DerivativeSecurityXML(1283) field is specified and must immediately precede it.
DerivativeSecurityXML	[0..1]	XMLData	
DerivativeSecurityXMLSchema	[0..1]	String	

Used in components: [DerivativeInstrument](#)

#### **180.2.743 DerivativeSecurityXMLLen**

The length of the DerivativeSecurityXML(1283) data block.

See SecurityXMLLen(1184) for complete definition.

Type: [Length](#)

Used in components: [DerivativeSecurityXML](#)

#### **180.2.744 DerivativeSecurityXMLSchema**

The schema used to validate the contents of DerivativeSecurityXML(1283).

See SecurityXMLSchema(1186) for complete definition.

Type: [String](#)

Used in components: [DerivativeSecurityXML](#)

#### **180.2.745 DerivativeSettleOnOpenFlag**

Indicator to determine if instrument is settle on open.

See SettleOnOpenFlag(966) for complete definition.

Type: [String](#)

Used in components: [DerivativeInstrument](#)

**180.2.746 DerivativeSettlMethod**

Settlement method for a contract or instrument.

See SettlMethod(1193) for complete definition.

Type: **String**

Allowed values in SettlMethodCodeSet:

Code	Name	Description
C	CashSettlementRequired	Cash settlement required
P	PhysicalSettlementRequired	Physical settlement required
E	Election	Election at exercise. The settlement method will be elected at the time of contract exercise.

Used in components: **DerivativeInstrument**

**180.2.747 DerivativeStateOrProvinceOfIssue**

A two-character state or province abbreviation.

See StateOrProvinceOfIssue(471) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

**180.2.748 DerivativeStrikeCurrency**

Currency in which the strike price is denominated.

See StrikeCurrency(947) for complete definition.

Type: **Currency**

Used in components: **DerivativeInstrument**

**180.2.749 DerivativeStrikeCurrencyCodeSource**

Identifies class or source of the DerivativeStrikeCurrency(1262) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [DerivativeInstrument](#)

#### **180.2.750 DerivativeStrikeMultiplier**

Multiplier applied to the strike price for the purpose of calculating the settlement value.

See StrikeMultiplier(967) for complete definition.

Type: [float](#)

Used in components: [DerivativeInstrument](#)

#### **180.2.751 DerivativeStrikePrice**

Strike price for an option.

See StrikePrice(202) for complete definition.

Type: [Price](#)

Used in components: [DerivativeInstrument](#)

#### **180.2.752 DerivativeStrikeValue**

The number of shares/units for the financial instrument involved in the option trade.

See StrikeValue(968) for complete definition.

Type: [float](#)

Used in components: [DerivativeInstrument](#)

**180.2.753 DerivativeSymbol**

Ticker symbol. Common, human understood representation of the security.

See Symbol(55) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

**180.2.754 DerivativeSymbolSfx**

Additional information about the security (e.g. preferred, warrants, etc.).

See SymbolSfx(65) for complete definition.

Type: **String**

Allowed values in SymbolSfxCodeSet:

Code	Name	Description
CD	EUCPWithLumpSumInterest	EUCP with lump-sum interest rather than discount price
WI	WhenIssued	"When Issued" for a security to be reissued under an old CUSIP or ISIN

Used in components: **DerivativeInstrument**

**180.2.755 DerivativeTimeUnit**

Unit of time associated with the contract.

NOTE: Additional values may be used by mutual agreement of the counterparties.

See TimeUnit(997) for complete definition.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in components: **DerivativeInstrument**

### 180.2.756 DerivativeUnitOfMeasure

The unit of measure of the underlying commodity upon which the contract is based.

See UnitOfMeasure(996) for complete definition.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)

Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter



Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [DerivativeInstrument](#)

### 180.2.757 DerivativeUnitOfMeasureCurrency

Indicates the currency of the unit of measure.

Conditionally required when DerivativeUnitOfMeasure(1269) = Ccy.

See UnitOfMeasureCurrency(1716) for complete definition.

Type: [Currency](#)

Used in components: [DerivativeInstrument](#)

### 180.2.758 DerivativeUnitOfMeasureCurrencyCodeSource

Identifies class or source of the DerivativeUnitOfMeasureCurrency(1722) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [DerivativeInstrument](#)

**180.2.759 DerivativeUnitOfMeasureQty**

Used to indicate the quantity of the underlying commodity unit of measure on which the contract is based.

See UnitOfMeasureQty(1147) for complete definition.

Type: **Qty**

Used in components: **DerivativeInstrument**

**180.2.760 DerivativeUPICode**

Uniquely identifies the product of a derivative instrument using ISO 4914. See UPICode(2891) for complete definition.

Type: **String**

Used in components: **DerivativeInstrument**

**180.2.761 DerivativeValuationMethod**

Specifies the method for price quotation.

See ValuationMethod(1197) for complete definition.

Type: **String**

Allowed values in ValuationMethodCodeSet:

Code	Name	Description
EQTY	PremiumStyle	premium style
FUT	FuturesStyleMarkToMarket	futures style mark-to-market
FUTDA	FuturesStyleWithAnAttachedCashAdjustment	futures style with an attached cash adjustment
CDS	CDSStyleCollateralization	CDS style collateralization of market to market and coupon
CDSD	CDSInDeliveryUseRecoveryRateToCalculate	CDS in delivery - use recovery rate to calculate obligation

Used in components: **DerivativeInstrument**

**180.2.762 DerivFlexProductEligibilityIndicator**

Used to indicate if a product or group of product supports the creation of flexible securities.

See FlexProductEligibilityIndicator(1242) for complete definition.

Type: **Boolean**

Used in components: **DerivativeInstrument**

**180.2.763 Designation**

Free format text defining the designation to be associated with a holding on the register. Used to identify assets of a specific underlying investor using a common registration, e.g. a broker's nominee or street name.

Type: **String**

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.764 DeskID**

Identification of a Market Maker's desk

Type: **String**

Used in groups: **CompIDReqGrp**, **CompIDStatGrp**, **MDFullGrp**, **MDIncGrp**

**180.2.765 DeskOrderHandlingInst**

Codes that apply special information that the broker-dealer needs to report.

Type: **MultipleStringValue**

Allowed values in CustOrderHandlingInstCodeSet:

---

Code	Name	Description
A	PhoneSimple	Phone simple
G	GOrderAndFCMAPlorFIX	G Order(FINRA OATS), FCM API or FIX(FIA Execution Source)
ADD	AddOnOrder	Add-on order

---

Code	Name	Description
B	PhoneComplex	Phone complex
AON	AllOrNone	All or none
C	FCMProvidedScreen	FCM provided screen
CND	ConditionalOrder	Conditional order
D	OtherProvidedScreen	Other provided screen
CNH	CashNotHeld	Cash not held
E	ClientProvidedPlatformControlled-ByFCM	Client provided platform controlled by FCM
CSH	DeliveryInstructionsCash	Delivery instructions - cash
F	ClientProvidedPlatformDirectToExchange	Client provided platform direct to exchange
DIR	DirectedOrder	Directed order
DLO	DiscretionaryLimitOrder	Discretionary limit order
H	AlgoEngine	Algo engine
E.W	ExchangeForPhysicalTransaction	Exchange for physical transaction
J	PriceAtExecution	Price at execution (price added at initial order entry, trading, middle office or time of give-up)
FOK	FillOrKill	Fill or kill
W	DeskElectronic	Desk - electronic
X	DeskPit	Desk - pit
IDX	IntraDayCross	Intraday cross
Y	ClientElectronic	Client - electronic
IO	ImbalanceOnly	Imbalance only
Z	ClientPit	Client - pit
IOC	ImmediateOrCancel	Immediate or cancel
ISO	IntermarketSweepOrder	Intermarket sweep order
LOO	LimitOnOpen	Limit on open
LOC	LimitOnClose	Limit on Close
MAO	MarketAtOpen	Market at Open
MAC	MarketAtClose	Market at close
MOO	MarketOnOpen	Market on open
MOC	MarketOnClose	Market on close
MPT	MergerRelatedTransferPosition	Merger related transfer position
MQT	MinimumQuantity	Minimum quantity
MTL	MarketToLimit	Market to limit

Code	Name	Description
ND	DeliveryInstructionsNextDay	Delivery instructions - next day
NH	NotHeld	Not held
OPT	OptionsRelatedTransaction	Options related transaction
OVD	OverTheDay	Over the day
PEG	Pegged	Pegged
RSV	ReserveSizeOrder	Reserve size order
S.W	StopStockTransaction	Stop stock transaction
SCL	Scale	Scale
SLR	DeliveryInstructionsSellersOption	Delivery instructions - sellers option
TMO	TimeOrder	Time order
TS	TrailingStop	Trailing stop
WRK	Work	Work
F0	StayOnOfferside	Stay on offerside
F3	GoAlong	Go along
F6	ParticipateDoNotInitiate	Participate do not initiate
F7	StrictScale	Strict scale
F8	TryToScale	Try to scale
F9	StayOnBidside	Stay on bidside
FA	NoCross	No cross
FB	OKToCross	OK to cross
FC	CallFirst	Call first
FD	PercentOfVolume	Percent of volume
FH	ReinstateOnSystemFailure	Reinstate on system failure
FI	InstitutionOnly	Institution only
FJ	ReinstateOnTradingHalt	Reinstate on trading halt
FK	CancelOnTradingHalf	Cancel on trading half
FL	LastPeg	Last peg
FM	MidPricePeg	Mid-price peg
FN	NonNegotiable	Non-negotiable
FO	OpeningPeg	Opening peg
FP	MarketPeg	Market peg
FQ	CancelOnSystemFailure	Cancel on system failure
FR	PrimaryPeg	Primary peg
FS	Suspend	Suspend

Code	Name	Description
FT	FixedPegToLocalBBO	Fixed peg to local best bid or offer at time of order
FW	PegToVWAP	Peg to VWAP
FX	TradeAlong	Trade along
FY	TryToStop	Try to stop
FZ	CancelIfNotBest	Cancel if not best
Fb	StrictLimit	Strict limit
Fc	IgnorePriceValidityChecks	Ignore price validity checks
Fd	PegToLimitPrice	Peg to Limit Price
Fe	WorkToTargetStrategy	Work to target strategy

Used in groups: **TrdRegTimestamps**

### 180.2.766 DeskType

Identifies the type of Trading Desk.

Conditionally required when InformationBarrierID(1727) is specified for OATS.

Type: **String**

Allowed values in DeskTypeCodeSet:

Code	Name	Description
A	Agency	Agency
AR	Arbitrage	Arbitrage
B	BlockTrading	Block trading
C	ConvertibleDesk	Convertible desk
CR	CentralRiskBooks	Central risk books
D	Derivatives	Derivatives
EC	EquityCapitalMarkets	Equity capital markets
IN	International	International
IS	Institutional	Institutional
O	Other	Other
PF	PreferredTrading	Preferred trading
PR	Proprietary	Proprietary
PT	ProgramTrading	Program trading

Code	Name	Description
S	Sales	Sales
SW	Swaps	Swaps
T	TradingDeskSystem	Trading desk or system non-market maker
TR	Treasury	Treasury
FB	FloorBroker	Floor Broker

Used in groups: **TrdRegTimestamps**

#### **180.2.767 DeskTypeSource**

Identifies the class or source of DeskType(1033) values. Conditionally required when DeskType(1033) is specified.

Type: **int**

Allowed values in DeskTypeSourceCodeSet:

Code	Name	Description
1	FINRAOATS	FINRA OATS

Used in groups: **TrdRegTimestamps**

#### **180.2.768 DetachmentPoint**

Upper bound percentage of the loss the tranche can endure.

Type: **Percentage**

Used in components: **Instrument**

#### **180.2.769 DifferentialPrice**

Used to specify the differential price when reporting the individual leg of a spread trade. Both leg price and differential price may be provided on such a report. Note that MultiLegReportingType(442) will be set to 2 (Individual leg of a multi-leg security) in this case.

Also used in pricing Trade at Settlement (TAS) and Trade At Marker (TAM) contracts for which the value is the negotiated currency offset either at settlement (TAS) or at time specified in the product definition (TAM). The final contract price is specified in LastPx(31).

Type: **PriceOffset**

Used in messages: **TradeCaptureReport**

### 180.2.770 DisclosureInstruction

Instruction to disclose information or to use default value of the receiver.

Type: **int**

Allowed values in DisclosureInstructionCodeSet:

Code	Name	Description
0	No	No
1	Yes	Yes
2	UseDefaultSetting	Use default setting

Used in groups: **DisclosureInstructionGrp**

### 180.2.771 DisclosureInstructionGrp

Repeating group of instructions, each of which relates to one or more elements of an order. The instruction itself conveys whether the information should be disclosed, e.g. in market data, or not.

Name	Mult.	Type	Description
<b>NoDisclosureInstructions</b>	[1..1]	NumInGroup	
<b>DisclosureType</b>	[0..1]	CodeSet	Required when NoDisclosureInstructions(1812) > 0.
<b>DisclosureInstruction</b>	[0..1]	CodeSet	

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**



**180.2.772 DisclosureType**

Information subject to disclosure.

Type: **int**

Allowed values in DisclosureTypeCodeSet:

Code	Name	Description
1	Volume	Volume
2	Price	Price
3	Side	Side
4	AON	AON
5	General	General. General is used for bilateral agreed disclosure information type(s).
6	ClearingAccount	Clearing account
7	CMTAAccount	CMTA account

Used in groups: **DisclosureInstructionGrp**

**180.2.773 DiscountFactor**

Used to calculate the present value of an amount to be paid in the future.

Type: **float**

Used in groups: **ClearingPriceParametersGrp**, **MDFullGrp**, **MDIncGrp**

Used in messages: **PositionMaintenanceReport**, **PositionReport**

**180.2.774 DiscretionInst**

Code to identify the price a DiscretionOffsetValue (389) is related to and should be mathematically added to.

Type: **char**

Allowed values in DiscretionInstCodeSet:

Code	Name	Description
0	RelatedToDisplayedPrice	Related to displayed price
1	RelatedToMarketPrice	Related to market price
2	RelatedToPrimaryPrice	Related to primary price
3	RelatedToLocalPrimaryPrice	Related to local primary price
4	RelatedToMidpointPrice	Related to midpoint price
5	RelatedToLastTradePrice	Related to last trade price
6	RelatedToVWAP	Related to VWAP
7	AveragePriceGuarantee	Average Price Guarantee

Used in components: [DiscretionInstructions](#)

### 180.2.775 DiscretionInstructions

The presence of DiscretionInstructions component block on an order indicates that the trader wishes to display one price but will accept trades at another price.

Name	Mult.	Type	Description
<a href="#">DiscretionInst</a>	[0..1]	CodeSet	What the discretionary price is related to (e.g. primary price, display price etc)
<a href="#">DiscretionOffsetValue</a>	[0..1]	float	Amount (signed) added to the "related to" price specified via DiscretionInst, in the context of DiscretionOffsetType
<a href="#">DiscretionMoveType</a>	[0..1]	CodeSet	Describes whether discretion price is static/fixed or floats
<a href="#">DiscretionOffsetType</a>	[0..1]	CodeSet	Type of Discretion Offset (e.g. price offset, tick offset etc)
<a href="#">DiscretionLimitType</a>	[0..1]	CodeSet	Specifies the nature of the resulting discretion price (e.g. or better limit, strict limit etc)
<a href="#">DiscretionRoundDirection</a>	[0..1]	CodeSet	If the calculated discretion price is not a valid tick price, specifies how to round the price (e.g. to be more or less aggressive)
<a href="#">DiscretionScope</a>	[0..1]	CodeSet	The scope of "related to" price of the discretion (e.g. local, global etc)

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.776 DiscretionLimitType

Type of Discretion Limit

Type: [int](#)

Allowed values in DiscretionLimitTypeCodeSet:

Code	Name	Description
0	OrBetter	Or better (default) - price improvement allowed
1	Strict	Strict - limit is a strict limit
2	OrWorse	Or worse - for a buy the discretion price is a minimum and for a sell the discretion price is a maximum (for use for orders which have a price range)

Used in components: [DiscretionInstructions](#)

### 180.2.777 DiscretionMoveType

Describes whether discretionary price is static or floats

Type: [int](#)

Allowed values in DiscretionMoveTypeCodeSet:

Code	Name	Description
0	Floating	Floating (default)
1	Fixed	Fixed

Used in components: [DiscretionInstructions](#)

### 180.2.778 DiscretionOffsetType

Type of Discretion Offset value

Type: [int](#)

Allowed values in DiscretionOffsetTypeCodeSet:

Code	Name	Description
0	Price	Price (default)
1	BasisPoints	Basis Points
2	Ticks	Ticks
3	PriceTier	Price Tier / Level

Used in components: [DiscretionInstructions](#)

#### **180.2.779 DiscretionOffsetValue**

Amount (signed) added to the "related to" price specified via DiscretionInst (388), in the context of DiscretionOffsetType (842)

(Prior to FIX 4.4 this field was of type PriceOffset)

Type: [float](#)

Used in components: [DiscretionInstructions](#)

#### **180.2.780 DiscretionPrice**

The current discretionary price of the order

Type: [Price](#)

Used in messages: [ExecutionReport](#)

#### **180.2.781 DiscretionRoundDirection**

If the calculated discretionary price is not a valid tick price, specifies whether to round the price to be more or less aggressive

Type: [int](#)

Allowed values in DiscretionRoundDirectionCodeSet:

Code	Name	Description
1	MoreAggressive	More aggressive - on a buy order round the price up to the nearest tick; on a sell round down to the nearest tick
2	MorePassive	More passive - on a buy order round down to the nearest tick; on a sell order round up to the nearest tick

Used in components: [DiscretionInstructions](#)

### 180.2.782 DiscretionScope

The scope of the discretion

Type: [int](#)

Allowed values in DiscretionScopeCodeSet:

Code	Name	Description
1	Local	Local (Exchange, ECN, ATS)
2	National	National
3	Global	Global
4	NationalExcludingLocal	National excluding local

Used in components: [DiscretionInstructions](#)

### 180.2.783 DisplayHighQty

Defines the upper quantity limit to a randomized refresh of DisplayQty.

Type: [Qty](#)

Used in components: [DisplayInstruction](#)

### 180.2.784 DisplayInstruction

The DisplayInstruction component block is used to convey instructions on how a reserved order is to be handled in terms of when and how much of the order quantity is to be displayed to the market.

Name	Mult.	Type	Description
DisplayQty	[0..1]	Qty	
SecondaryDisplayQty	[0..1]	Qty	
InitialDisplayQty	[0..1]	Qty	Only to be used in the ExecutionReport
CurrentDisplayPrice	[0..1]	Price	
DisplayWhen	[0..1]	CodeSet	
DisplayMethod	[0..1]	CodeSet	
DisplayLowQty	[0..1]	Qty	Required when DisplayMethod = 3
DisplayHighQty	[0..1]	Qty	Required when DisplayMethod = 3
DisplayMinIncr	[0..1]	Qty	Can be used to specify larger increments than the standard increment provided by the market. Optionally used when DisplayMethod = 3
RefreshQty	[0..1]	Qty	Required when DisplayMethod = 2

Used in components: [TradeReportOrderDetail](#)

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.785 DisplayLowQty

Defines the lower quantity limit to a randomized refresh of DisplayQty.

Type: [Qty](#)

Used in components: [DisplayInstruction](#)

### 180.2.786 DisplayMethod

Defines what value to use in DisplayQty (1138). If not specified the default DisplayMethod is "1"

Type: [char](#)

Allowed values in DisplayMethodCodeSet:

Code	Name	Description
1	Initial	Initial (use original DisplayQty)

Code	Name	Description
2	New	New (use RefreshQty)
3	Random	Random (randomize value)
4	Undisclosed	Undisclosed (invisible order)

Used in components: **DisplayInstruction**

#### **180.2.787 DisplayMinIncr**

Defines the minimum increment to be used when calculating a random refresh of DisplayQty. A user specifies this when he wants a larger increment than the standard provided by the market (e.g. the round lot size).

Type: **Qty**

Used in components: **DisplayInstruction**

#### **180.2.788 DisplayQty**

The quantity to be displayed . Required for reserve orders. On orders specifies the qty to be displayed, on execution reports the currently displayed quantity.

Type: **Qty**

Used in components: **DisplayInstruction**

#### **180.2.789 DisplayWhen**

Instructs when to refresh DisplayQty (1138).

Type: **char**

Allowed values in DisplayWhenCodeSet:

Code	Name	Description
1	Immediate	Immediate (after each fill)
2	Exhaust	Exhaust (when DisplayQty = 0)

Used in components: **DisplayInstruction**

**180.2.790 DistribPaymentMethod**

Identifies the payment method for a (fractional) distribution. Used for CIV.

Type: **int**

Allowed values in DistribPaymentMethodCodeSet:

Code	Name	Description
1	CREST	CREST
2	NSCC	NSCC
3	Euroclear	Euroclear
4	Clearstream	Clearstream
5	Cheque	Cheque
6	TelegraphicTransfer	Telegraphic Transfer
7	FedWire	Fed Wire
8	DirectCredit	Direct Credit (BECS, BACS)
9	ACHCredit	ACH Credit
10	BPAY	BPAY
11	HighValueClearingSystemHVACS	High Value Clearing System HVACS
12	ReinvestInFund	Reinvest In Fund
999	Other	Other

Used in groups: **RgstDistInstGrp**

**180.2.791 DistribPercentage**

The amount of each distribution to go to this beneficiary, expressed as a percentage

Type: **Percentage**

Used in groups: **RgstDistInstGrp**

**180.2.792 DividendAccrualFixedRate**

The dividend accrual fixed rate per annum expressed as a decimal.

A value of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **DividendConditions**



### 180.2.793 DividendAccrualFloatingRate

The DividendAccrualFloatingRate component is a subcomponent of DividendConditions used to define the dividend accrual floating rate attributes of dividend payment conditions.

Name	Mult.	Type	Description
DividendFloatingRateIndex	[0..1]	String	
DividendFloatingRateIndexCurvePeriod	[0..1]	int	Conditionally required when DividendFloatingRateIndexCurveUnit(42220) is specified.
DividendFloatingRateIndexCurveUnit	[0..1]	CodeSet	Conditionally required when DividendFloatingRateIndexCurvePeriod(42219) is specified.
DividendFloatingRateMultiplier	[0..1]	float	
DividendFloatingRateSpread	[0..1]	PriceOffset	
DividendFloatingRateSpreadPosition-Type	[0..1]	CodeSet	
DividendFloatingRateTreatment	[0..1]	CodeSet	
DividendCapRate	[0..1]	Percentage	
DividendCapRateBuySide	[0..1]	CodeSet	
DividendCapRateSellSide	[0..1]	CodeSet	
DividendFloorRate	[0..1]	Percentage	
DividendFloorRateBuySide	[0..1]	CodeSet	
DividendFloorRateSellSide	[0..1]	CodeSet	
DividendInitialRate	[0..1]	Percentage	
DividendFinalRateRoundingDirection	[0..1]	CodeSet	
DividendFinalRatePrecision	[0..1]	int	
DividendAveragingMethod	[0..1]	CodeSet	
DividendNegativeRateTreatment	[0..1]	CodeSet	

Used in components: [DividendConditions](#)

### 180.2.794 DividendAccrualPaymeentDateBusinessDayConvention

Accrual payment date adjustment business day convention.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **DividendAccrualPaymentDate**

#### **180.2.795 DividendAccrualPaymentDateAdjusted**

The adjusted accrual payment date.

Type: **LocalMktDate**

Used in components: **DividendAccrualPaymentDate**

#### **180.2.796 DividendAccrualPaymentDateBusinessCenter**

The business center calendar used for date adjustment of the instrument's dividend accrual payment date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **DividendAccrualPaymentDateBusinessCenterGrp**

#### **180.2.797 DividendAccrualPaymentDateBusinessCenterGrp**

DividendAccrualPaymentDateBusinessCenterGrp is a repeating subcomponent within the DividendAccrualPaymentDate component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
NoDividendAccrualPaymentDateBusinessCenters	[1..1]	NumInGroup	
DividendAccrualPaymentDateBusinessCenter	[0..1]	String	Required if NoDividendAccrualPaymentDateBusinessCenters(42236) > 0.

Used in components: [DividendAccrualPaymentDate](#)

### 180.2.798 DividendAccrualPaymentDate

The DividendAccrualPaymentDate component is a subcomponent of DividendConditions used to report the dividend accrual payment date.

Name	Mult.	Type	Description
DividendAccrualPaymentDateRelativeTo	[0..1]	int	
DividendAccrualPaymentDateOffsetPeriod	[0..1]	int	Conditionally required when DividendAccrualPaymentDateOffsetUnit(42240) is specified.
DividendAccrualPaymentDateOffsetUnit	[0..1]	CodeSet	Conditionally required when DividendAccrualPaymentDateOffsetPeriod(42239) is specified.
DividendAccrualPaymentDateOffsetDayType	[0..1]	CodeSet	
DividendAccrualPaymentDateUnadjusted	[0..1]	LocalMktDate	
DividendAccrualPaymentDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The value would be specific to this instance of DividendAccrualPaymentDate.
DividendAccrualPaymentDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The values would be specific to this instance of DividendAccrualPaymentDate.
DividendAccrualPaymentDateAdjusted	[0..1]	LocalMktDate	

Used in components: [DividendConditions](#)

**180.2.799 DividendAccrualPaymentDateOffsetDayType**

Specifies the day type of the relative accrual payment date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **DividendAccrualPaymentDate**

**180.2.800 DividendAccrualPaymentDateOffsetPeriod**

Time unit multiplier for the relative accrual payment date offset.

Type: **int**

Used in components: **DividendAccrualPaymentDate**

**180.2.801 DividendAccrualPaymentDateOffsetUnit**

Time unit associated with the relative accrual payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **DividendAccrualPaymentDate**

**180.2.802 DividendAccrualPaymentDateRelativeTo**

Specifies the anchor date when the accrual payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **DividendAccrualPaymentDate**

**180.2.803 DividendAccrualPaymentDateUnadjusted**

The unadjusted accrual payment date.

Type: **LocalMktDate**

Used in components: **DividendAccrualPaymentDate**

**180.2.804 DividendAmountType**

Indicates how the gross cash dividend amount per share is determined.

Type: **int**

Allowed values in DividendAmountTypeCodeSet:

Code	Name	Description
0	RecordAmount	Record amount. 100% of the gross cash dividend per share paid over record date during relevant dividend period.
1	ExAmount	Ex amount. 100% of gross cash dividend per share paid after the ex-dividend date during relevant dividend period.
2	PaidAmount	Paid amount. 100% of gross cash dividend per share paid during relevant dividend period.
3	PerMasterConfirm	As specified in master confirmation. The amount is determined as provided in the relevant master confirmation.

Used in components: **DividendConditions**

**180.2.805 DividendAveragingMethod**

When averaging is applicable, used to specify whether a weighted or unweighted average method of calculation is to be used.

Type: **int**

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: **DividendAccrualFloatingRate**

#### **180.2.806 DividendCapRate**

The cap rate, if any, which applies to the floating rate. It is only required where the floating rate is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **DividendAccrualFloatingRate**

#### **180.2.807 DividendCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **DividendAccrualFloatingRate**

#### **180.2.808 DividendCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [DividendAccrualFloatingRate](#)

#### **180.2.809 DividendCashEquivalentPercentage**

Declared cash-equivalent dividend percentage.

A value of 5% would be represented as "0.05".

Type: [Percentage](#)

Used in components: [DividendConditions](#)

#### **180.2.810 DividendCashPercentage**

Declared cash dividend percentage.

A value of 5% would be represented as "0.05".

Type: [Percentage](#)

Used in components: [DividendConditions](#)

#### **180.2.811 DividendComposition**

Defines how the composition of dividends is to be determined.

Type: [int](#)

Allowed values in DividendCompositionCodeSet:

Code	Name	Description
0	EquityAmountReceiver	Equity amount receiver election. The equity amount receiver determines the composition of dividends (subject to conditions).

Code	Name	Description
1	CalculationAgent	Calculation agent election. The calculation agent determines the composition of dividends (subject to conditions).

Used in components: [DividendConditions](#)

### 180.2.812 DividendCompoundingMethod

The compounding method to be used when more than one dividend period contributes to a single payment.

Type: [int](#)

Allowed values in PaymentStreamCompoundingMethodCodeSet:

Code	Name	Description
0	None	None
1	Flat	Flat
2	Straight	Straight
3	SpreadExclusive	Spread exclusive

Used in components: [DividendConditions](#)

### 180.2.813 DividendConditions

The DividendConditions component is a subcomponent of PaymentStream used to specify the conditions' valuations and dates governing the payment of dividends.

Name	Mult.	Type	Description
<a href="#">DividendReinvestmentIndicator</a>	[0..1]	Boolean	
<a href="#">DividendEntitlementEvent</a>	[0..1]	CodeSet	
<a href="#">DividendAmountType</a>	[0..1]	CodeSet	
<a href="#">DividendUnderlierRefID</a>	[0..1]	String	
<a href="#">DividendPeriodGrp</a>	[0..*]	Group	
<a href="#">ExtraordinaryDividendPartySide</a>	[0..1]	CodeSet	
<a href="#">ExtraordinaryDividendAmountType</a>	[0..1]	CodeSet	



Name	Mult.	Type	Description
ExtraordinaryDividendCurrency	[0..1]	Currency	
ExtraordinaryDividendDetermination-Method	[0..1]	String	
DividendFXTriggerDate	[0..1]	Component	
DividendAccrualFloatingRate	[0..1]	Component	
DividendAccrualFixedRate	[0..1]	Percentage	
DividendAccrualPaymentDate	[0..1]	Component	
DividendCompoundingMethod	[0..1]	CodeSet	
DividendNumOfIndexUnits	[0..1]	int	
DividendCashPercentage	[0..1]	Percentage	
DividendCashEquivalentPercentage	[0..1]	Percentage	
NonCashDividendTreatment	[0..1]	CodeSet	
DividendComposition	[0..1]	CodeSet	
SpecialDividendsIndicator	[0..1]	Boolean	
MaterialDividendsIndicator	[0..1]	Boolean	
OptionsExchangeDividendsIndicator	[0..1]	Boolean	
AdditionalDividendsIndicator	[0..1]	Boolean	
AllDividendsIndicator	[0..1]	Boolean	

Used in components: [PaymentStreamFloatingRate](#)

#### 180.2.814 DividendEntitlementEvent

Defines the contract event which the receiver of the derivative is entitled to the dividend.

Type: [int](#)

Allowed values in DividendEntitlementEventCodeSet:

Code	Name	Description
0	ExDate	Ex-date. Dividend entitlement is on the dividend ex-date.
1	RecordDate	Record date. Dividend entitlement is on the dividend record date.

Used in components: [DividendConditions](#)

**180.2.815 DividendFinalRatePrecision**

Specifies the rounding precision of the final rate in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **DividendAccrualFloatingRate**

**180.2.816 DividendFinalRateRoundingDirection**

Specifies the rounding direction of the final rate.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **DividendAccrualFloatingRate**

**180.2.817 DividendFloatingRateIndex**

The dividend accrual floating rate index.

Type: **String**

Used in components: **DividendAccrualFloatingRate**

**180.2.818 DividendFloatingRateIndexCurvePeriod**

Time unit multiplier for the dividend accrual floating rate index curve.

Type: **int**

Used in components: **DividendAccrualFloatingRate**

**180.2.819 DividendFloatingRateIndexCurveUnit**

Time unit associated with the dividend accrual floating rate index curve period.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **DividendAccrualFloatingRate**

**180.2.820 DividendFloatingRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This should only be included if the multiplier is not equal to 1 (one) for the term of the contract.

Type: **float**

Used in components: **DividendAccrualFloatingRate**

**180.2.821 DividendFloatingRateSpread**

The basis points spread from the index specified in DividendFloatingRateIndex(42218).

Type: **PriceOffset**

Used in components: **DividendAccrualFloatingRate**

**180.2.822 DividendFloatingRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: [DividendAccrualFloatingRate](#)

#### **180.2.823 DividendFloatingRateTreatment**

Specifies the yield calculation treatment for the index.

Type: [int](#)

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: [DividendAccrualFloatingRate](#)

#### **180.2.824 DividendFloorRate**

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate. The rate is expressed as a decimal, e.g. 5% is represented as "0.05".

Type: [Percentage](#)

Used in components: [DividendAccrualFloatingRate](#)

#### **180.2.825 DividendFloorRateBuySide**

Reference to the buyer of the floor rate option through its trade side.

Type: [int](#)

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [DividendAccrualFloatingRate](#)

#### **180.2.826 DividendFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: [int](#)

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [DividendAccrualFloatingRate](#)

#### **180.2.827 DividendFXTriggerDateAdjusted**

The adjusted FX trigger date.

Type: [LocalMktDate](#)

Used in components: [DividendFXTriggerDate](#)

#### **180.2.828 DividendFXTriggerDateBusinessCenter**

The business center calendar used for date adjustment of the instrument's FX trigger date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [DividendFXTriggerDateBusinessCenterGrp](#)

### 180.2.829 DividendFXTriggerDateBusinessCenterGrp

DividendFXTriggerDateBusinessCenterGrp is a repeating subcomponent within the DividendFXTriggerDate component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
NoDividendFXTriggerDateBusinessCenters	[1..1]	NumInGroup	
DividendFXTriggerDateBusinessCenter	[0..1]	String	Required if NoDividendFXTriggerDateBusinessCenters(42272) > 0.

Used in components: [DividendFXTriggerDate](#)

### 180.2.830 DividendFXTriggerDateBusinessDayConvention

The business day convention used for the FX trigger date adjustment.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [DividendFXTriggerDate](#)

### 180.2.831 DividendFXTriggerDate

The DividendFXTriggerDate component is a subcomponent of DividendConditions used to report the dividend date when a foreign exchange trade is triggered.

Name	Mult.	Type	Description
DividendFXTriggerDateRelativeTo	[0..1]	int	
DividendFXTriggerDateOffsetPeriod	[0..1]	int	Conditionally required when DividendFXTriggerDateOffsetUnit(42267) is specified.
DividendFXTriggerDateOffsetUnit	[0..1]	CodeSet	Conditionally required when DividendFXTriggerDateOffsetPeriod(42266) is specified.
DividendFXTriggerDateOffsetDayType	[0..1]	CodeSet	
DividendFXTriggerDateUnadjusted	[0..1]	LocalMktDate	
DividendFXTriggerDateBusinessDay-Convention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The value would be specific to this instance of DividendFXTriggerDate.
DividendFXTriggerDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The values would be specific to this instance of DividendFXTriggerDate.
DividendFXTriggerDateAdjusted	[0..1]	LocalMktDate	

Used in components: [DividendConditions](#)

### 180.2.832 DividendFXTriggerDateOffsetDayType

Specifies the day type of the relative FX trigger date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [DividendFXTriggerDate](#)

**180.2.833 DividendFXTriggerDateOffsetPeriod**

Time unit multiplier for the relative FX trigger date offset.

Type: **int**

Used in components: **DividendFXTriggerDate**

**180.2.834 DividendFXTriggerDateOffsetUnit**

Time unit associated with the relative FX trigger date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **DividendFXTriggerDate**

**180.2.835 DividendFXTriggerDateRelativeTo**

Specifies the anchor date when the FX trigger date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **DividendFXTriggerDate**

**180.2.836 DividendFXTriggerDateUnadjusted**

The unadjusted FX trigger date.

Type: **LocalMktDate**

Used in components: **DividendFXTriggerDate**



**180.2.837 DividendInitialRate**

The initial floating rate reset agreed between the principal parties involved in the trade. This is assumed to be the first required reset rate for the first regular calculation period. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. The initial rate is expressed in decimal form, e.g. 5% is represented as "0.05".

Type: **Percentage**

Used in components: **DividendAccrualFloatingRate**

**180.2.838 DividendNegativeRateTreatment**

The specification of any provisions for calculating payment obligations when a floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: **DividendAccrualFloatingRate**

**180.2.839 DividendNumOfIndexUnits**

The number of index units applicable to dividends.

Type: **int**

Used in components: **DividendConditions**

**180.2.840 DividendPeriodBusinessCenter**

The business center calendar used for date adjustment of the instrument's dividend period date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **DividendPeriodBusinessCenterGrp**

#### **180.2.841 DividendPeriodBusinessCenterGrp**

DividendPeriodBusinessCenterGrp is a repeating subcomponent within the DividendPeriodGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
NoDividendPeriodBusinessCenters	[1..1]	NumInGroup	
DividendPeriodBusinessCenter	[0..1]	String	Required if NoDividendPeriodBusinessCenters(42294) > 0.

Used in groups: **DividendPeriodGrp**

#### **180.2.842 DividendPeriodBusinessDayConvention**

The dividend period dates business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: **DividendPeriodGrp**

**180.2.843 DividendPeriodEndDateUnadjusted**

The unadjusted date on which the dividend period will end.

Type: **LocalMktDate**

Used in groups: **DividendPeriodGrp**

**180.2.844 DividendPeriodGrp**

DividendPeriodGrp is a repeating subcomponent within the DividendConditions component. It is used to specify the valuation and payments dates of the dividend leg of a dividend swap.

Name	Mult.	Type	Description
NoDividendPeriods	[1..1]	NumInGroup	
DividendPeriodSequence	[0..1]	int	Required if NoDividendPeriods(42274) > 0.
DividendPeriodStartDateUnadjusted	[0..1]	LocalMktDate	
DividendPeriodEndDateUnadjusted	[0..1]	LocalMktDate	
DividendPeriodUnderlierRefID	[0..1]	String	When specified, this overrides DividendUnderlierRefID(42248). The specified value would be specific to this dividend period instance.
DividendPeriodStrikePrice	[0..1]	Price	
DividendPeriodBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this dividend period instance.
DividendPeriodBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this dividend period instance.
DividendPeriodValuationDateUnadjusted	[0..1]	LocalMktDate	
DividendPeriodValuationDateRelativeTo	[0..1]	int	
DividendPeriodValuationDateOffsetPeriod	[0..1]	int	Conditionally required when DividendPeriodValuationDateOffsetUnit(42284) is specified.
DividendPeriodValuationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when DividendPeriodValuationDateOffsetPeriod(42283) is specified.

Name	Mult.	Type	Description
DividendPeriodValuationDateOffset-DayType	[0..1]	CodeSet	
DividendPeriodValuationDateAdjusted	[0..1]	LocalMktDate	
DividendPeriodPaymentDateUnadjusted	[0..1]	LocalMktDate	
DividendPeriodPaymentDateRelativeTo	[0..1]	int	
DividendPeriodPaymentDateOffsetPeriod	[0..1]	int	Conditionally required when DividendPeriodPaymentDateOffsetUnit(42290) is specified.
DividendPeriodPaymentDateOffsetUnit	[0..1]	CodeSet	Conditionally required when DividendPeriodPaymentDateOffsetPeriod(42289) is specified.
DividendPeriodPaymentDateOffset-DayType	[0..1]	CodeSet	
DividendPeriodPaymentDateAdjusted	[0..1]	LocalMktDate	
DividendPeriodXID	[0..1]	XID	

Used in components: [DividendConditions](#)

#### 180.2.845 DividendPeriodPaymentDateAdjusted

The adjusted dividend period payment date.

Type: [LocalMktDate](#)

Used in groups: [DividendPeriodGrp](#)

#### 180.2.846 DividendPeriodPaymentDateOffsetDayType

Specifies the day type of the relative dividend period payment date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business

Code	Name	Description
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **DividendPeriodGrp**

#### **180.2.847 DividendPeriodPaymentDateOffsetPeriod**

Time unit multiplier for the relative dividend period payment date offset.

Type: **int**

Used in groups: **DividendPeriodGrp**

#### **180.2.848 DividendPeriodPaymentDateOffsetUnit**

Time unit associated with the relative dividend period payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **DividendPeriodGrp**

#### **180.2.849 DividendPeriodPaymentDateRelativeTo**

Specifies the anchor date when the dividend period payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **DividendPeriodGrp**

#### **180.2.850 DividendPeriodPaymentDateUnadjusted**

The unadjusted dividend period payment date.

Type: **LocalMktDate**

Used in groups: **DividendPeriodGrp**

#### **180.2.851 DividendPeriodSequence**

Defines the ordinal dividend period. E.g. 1 = First period, 2 = Second period, etc.

Type: **int**

Used in groups: **DividendPeriodGrp**

#### **180.2.852 DividendPeriodStartDateUnadjusted**

The unadjusted date on which the dividend period will begin.

Type: **LocalMktDate**

Used in groups: **DividendPeriodGrp**

#### **180.2.853 DividendPeriodStrikePrice**

Specifies the fixed strike price of the dividend period.

Type: **Price**

Used in groups: **DividendPeriodGrp**

#### **180.2.854 DividendPeriodUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in groups: **DividendPeriodGrp**

**180.2.855 DividendPeriodValuationDateAdjusted**

The adjusted dividend period valuation date.

Type: **LocalMktDate**

Used in groups: **DividendPeriodGrp**

**180.2.856 DividendPeriodValuationDateOffsetDayType**

Specifies the day type of the relative dividend period valuation date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **DividendPeriodGrp**

**180.2.857 DividendPeriodValuationDateOffsetPeriod**

Time unit multiplier for the relative dividend period valuation date offset.

Type: **int**

Used in groups: **DividendPeriodGrp**

**180.2.858 DividendPeriodValuationDateOffsetUnit**

Time unit associated with the relative dividend period valuation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [DividendPeriodGrp](#)

#### **180.2.859 DividendPeriodValuationDateRelativeTo**

Specifies the anchor date when the dividend period valuation date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in groups: [DividendPeriodGrp](#)

#### **180.2.860 DividendPeriodValuationDateUnadjusted**

The unadjusted dividend period valuation date.

Type: [LocalMktDate](#)

Used in groups: [DividendPeriodGrp](#)

#### **180.2.861 DividendPeriodXID**

Identifier for linking this stream dividend period to an underlier through an instance of RelatedInstrumentGrp.

Type: [XID](#)

Used in groups: [DividendPeriodGrp](#)

#### **180.2.862 DividendReinvestmentIndicator**

Indicates whether the dividend will be reinvested.

Type: [Boolean](#)

Used in components: [DividendConditions](#)



**180.2.863 DividendUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in components: **DividendConditions**

**180.2.864 DividendYield**

The continuously-compounded annualized dividend yield of the underlying(s) of an option. Used as a parameter to theoretical option pricing models.

Type: **Percentage**

Used in messages: **ExecutionReport**, **TradeCaptureReport**

**180.2.865 DKReason**

Reason for execution rejection.

Type: **char**

Allowed values in DKReasonCodeSet:

Code	Name	Description
A	UnknownSymbol	Unknown security
B	WrongSide	Wrong side
C	QuantityExceedsOrder	Quantity exceeds order
D	NoMatchingOrder	No matching order
E	PriceExceedsLimit	Price exceeds limit
F	CalculationDifference	Calculation difference
G	NoMatchingExecutionReport	No matching ExecutionReport(35=8)
Z	Other	Other

Used in messages: **DontKnowTrade**, **ExecutionAck**

**180.2.866 DlvInstGrp**

Name	Mult.	Type	Description
NoDlvInst	[1..1]	NumInGroup	
SettlInstSource	[0..1]	CodeSet	
DlvInstType	[0..1]	CodeSet	
SettlParties	[0..*]	Group	

Used in components: [SettlInstructionsData](#)

**180.2.867 DlvInstType**

Used to indicate whether a delivery instruction is used for securities or cash settlement.

Type: [char](#)

Allowed values in DlvInstTypeCodeSet:

Code	Name	Description
C	Cash	Cash
S	Securities	Securities

Used in groups: [DlvInstGrp](#)

**180.2.868 DocumentationText**

A sentence or phrase pertinent to the trade, not a reference to an external document. E.g. "To be registered with the U.S. Environmental Protection Agency, Acid Rain Division, SO2 Allowance Tracking System"

Type: [String](#)

Used in components: [FinancingDetails](#)

**180.2.869 DueToRelated**

Indicates whether or not the halt was due to the Related Security being halted.

Type: **Boolean**

Allowed values in DueToRelatedCodeSet:

Code	Name	Description
N	NotRelatedToSecurityHalt	Halt was not related to a halt of the related security
Y	RelatedToSecurityHalt	Halt was due to related security being halted

Used in messages: **SecurityStatus**

#### **180.2.870 DuplicateCLOrdIDIndicator**

Used to indicate that a CLOrdID(11) value is an intentional duplicate of a previously sent value. Allows to avoid the rejection of an order with OrdRejReason(103) = 6 (Duplicate Order).

Type: **Boolean**

Allowed values in DuplicateCLOrdIDIndicatorCodeSet:

Code	Name	Description
N	UniqueCLOrdID	Unique CLOrdID(11)
Y	DuplicateCLOrdID	Duplicate CLOrdID(11)

Used in messages: **NewOrderSingle**, **OrderCancelReplaceRequest**

#### **180.2.871 EffectiveBusinessDate**

Specifies an explicit business date for associated reference data or transaction. Used when an implicit date is not sufficiently specific.

Type: **LocalMktDate**

Used in messages: **MarketDefinition**, **MarketDefinitionUpdateReport**, **PartyActionReport**, **SecurityDefinition**, **SecurityDefinitionUpdateReport**

#### **180.2.872 EffectiveTime**

Time the details within the message should take effect (always expressed in UTC (Universal Time Coordinated, also known as "GMT"))

Type: **UTCTimestamp**

Used in groups: **ListOrdGrp**, **SettlInstGrp**, **SettlObligationInstructions**

Used in messages: **AlgoCertificateReport**, **AlgoCertificateRequest**, **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **SettlementInstructionRequest**

### **180.2.873 EFPTrackingError**

Eg Used in EFP trades 2% (EFP - Exchange for Physical ). Represented as a percentage.

Type: **Percentage**

Used in groups: **BidDescReqGrp**

### **180.2.874 EmailThreadID**

Unique identifier for an email thread (new and chain of replies)

Type: **String**

Used in messages: **Email**

### **180.2.875 EmailType**

Email message type.

Type: **char**

Allowed values in EmailTypeCodeSet:

Code	Name	Description
0	New	New
1	Reply	Reply
2	AdminReply	Admin Reply

Used in messages: **Email**

**180.2.876 EncodedAdditionalTermBondDesc**

Encoded (non-ASCII characters) representation of the AdditionalTermBondDesc(40003) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the AdditionalTermBondDesc(40003) field.

Type: **data**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.877 EncodedAdditionalTermBondDescLen**

Byte length of encoded (non-ASCII characters) EncodedAdditionalTermBondDesc(40005) field.

Type: **Length**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.878 EncodedAdditionalTermBondIssuer**

Encoded (non-ASCII characters) representation of the AdditionalTermBondIssuer(40007) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the AdditionalTermBondIssuer(40007) field.

Type: **data**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.879 EncodedAdditionalTermBondIssuerLen**

Byte length of encoded (non-ASCII characters) EncodedAdditionalTermBondIssuer(40009) field.

Type: **Length**

Used in groups: **AdditionalTermBondRefGrp**

**180.2.880 EncodedAllocCommissionDesc**

Encoded (non-ASCII characters) representation of the AllocCommissionDesc(2664) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the AllocCommissionDesc(2664) field.

Type: **data**

Used in groups: [AllocCommissionDataGrp](#)

#### **180.2.881 EncodedAllocCommissionDescLen**

Byte length of the encoded (non-ASCII characters) EncodedAllocCommissionDesc(2666) field.

Type: [Length](#)

Used in groups: [AllocCommissionDataGrp](#)

#### **180.2.882 EncodedAllocText**

Encoded (non-ASCII characters) representation of the AllocText (161) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the AllocText field.

Type: [data](#)

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [TrdAllocGrp](#)

#### **180.2.883 EncodedAllocTextLen**

Byte length of encoded (non-ASCII characters) EncodedAllocText (361) field.

Type: [Length](#)

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [TrdAllocGrp](#)

#### **180.2.884 EncodedAttachment**

The content of the attachment in the encoding format specified in the AttachmentEncodingType(2109) field.

Type: [data](#)

Used in groups: [AttachmentGrp](#)

#### **180.2.885 EncodedAttachmentLen**

Byte length of encoded the EncodedAttachment(2112) field.

Type: [Length](#)

Used in groups: [AttachmentGrp](#)

**180.2.886 EncodedCancelText**

Encoded (non-ASCII characters) representation of the CancelText(2807) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the CancelText(2807) field.

Type: **data**

Used in messages: **PayManagementRequest**

**180.2.887 EncodedCancelTextLen**

Byte length of encoded (non-ASCII characters) EncodedCancelText(2808) field.

Type: **Length**

Used in messages: **PayManagementRequest**

**180.2.888 EncodedCommissionDesc**

Encoded (non-ASCII characters) representation of the CommissionDesc(2650) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the CommissionDesc(2650) field.

Type: **data**

Used in groups: **CommissionDataGrp**

**180.2.889 EncodedCommissionDescLen**

Byte length of the encoded (non-ASCII characters) EncodedCommissionDesc(2652) field.

Type: **Length**

Used in groups: **CommissionDataGrp**

**180.2.890 EncodedComplianceText**

Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the ComplianceText(2404) field.

Type: **data**

Used in groups: [ListOrdGrp](#), [SideCrossOrdCxlGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [ExecutionReport](#), [MassQuote](#), [MassQuoteAck](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [OrderMassActionReport](#), [OrderMassActionRequest](#), [Quote](#), [QuoteRequest](#), [SecurityDefinitionRequest](#)

#### **180.2.891 EncodedComplianceTextLen**

Byte length of encoded (non-ASCII characters) [EncodedComplianceText\(2352\)](#) field.

Type: [Length](#)

Used in groups: [ListOrdGrp](#), [SideCrossOrdCxlGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [ExecutionReport](#), [MassQuote](#), [MassQuoteAck](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [OrderMassActionReport](#), [OrderMassActionRequest](#), [Quote](#), [QuoteRequest](#), [SecurityDefinitionRequest](#)

#### **180.2.892 EncodedDeliveryStreamCycleDesc**

Encoded (non-ASCII characters) representation of the [DeliveryStreamCycleDesc\(41082\)](#) field in the encoded format specified via the [MessageEncoding\(347\)](#) field. If used, the ASCII (English) representation should also be specified in the [DeliveryStreamCycleDesc\(41082\)](#) field.

Type: [data](#)

Used in groups: [DeliveryStreamCycleGrp](#)

#### **180.2.893 EncodedDeliveryStreamCycleDescLen**

Byte length of encoded (non-ASCII characters) [EncodedDeliveryStreamCycleDesc\(41084\)](#) field.

Type: [Length](#)

Used in groups: [DeliveryStreamCycleGrp](#)

#### **180.2.894 EncodedDocumentationText**

Encoded (non-ASCII characters) representation of the [DocumentationText\(1513\)](#) field in the encoded format specified via the [MessageEncoding\(347\)](#) field. If used, the ASCII (English) representation should also be specified in the [DocumentationText\(1513\)](#) field.



Type: **data**

Used in components: **FinancingDetails**

#### **180.2.895 EncodedDocumentationTextLen**

Byte length of encoded (non-ASCII characters) EncodedDocumentationText(1527) field.

Type: **Length**

Used in components: **FinancingDetails**

#### **180.2.896 EncodedEventText**

Encoded (non-ASCII characters) representation of the EventText(868) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the EventText(868) field.

Type: **data**

Used in groups: **EvntGrp**

#### **180.2.897 EncodedEventTextLen**

Byte length of encoded (non-ASCII characters) EncodedEventText(868) field.

Type: **Length**

Used in groups: **EvntGrp**

#### **180.2.898 EncodedExerciseDesc**

Encoded (non-ASCII characters) representation of the ExerciseDesc(41106) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the ExerciseDesc(41106) field.

Type: **data**

Used in components: **OptionExercise**

**180.2.899 EncodedExerciseDescLen**

Byte length of encoded (non-ASCII characters) EncodedExerciseDesc(41102) field.

Type: **Length**

Used in components: **OptionExercise**

**180.2.900 EncodedFinancialInstrumentFullName**

Encoded (non-ASCII characters) representation of the FinancialInstrumentFullName(2714) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the FinancialInstrumentFullName(2714) field.

Type: **data**

Used in components: **Instrument**

**180.2.901 EncodedFinancialInstrumentFullNameLen**

Byte length of encoded (non-ASCII characters) EncodedFinancialInstrumentFullName(2716) field.

Type: **Length**

Used in components: **Instrument**

**180.2.902 EncodedFirmAllocText**

Encoded (non-ASCII characters) representation of the FirmAllocText(1732) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in FirmAllocText(1732) field.

Type: **data**

Used in groups: **AllocAckGrp, AllocGrp, TrdAllocGrp**

**180.2.903 EncodedFirmAllocTextLen**

Byte length of encoded (non-ASCII characters) EncodedFirmAllocText(1734) field.

Type: **Length**

Used in groups: **AllocAckGrp, AllocGrp, TrdAllocGrp**

**180.2.904 EncodedHeadline**

Encoded (non-ASCII characters) representation of the Headline (148) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the Headline field.

Type: **data**

Used in messages: **News**

**180.2.905 EncodedHeadlineLen**

Byte length of encoded (non-ASCII characters) EncodedHeadline (359) field.

Type: **Length**

Used in messages: **News**

**180.2.906 EncodedIssuer**

Encoded (non-ASCII characters) representation of the Issuer field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the Issuer field.

Type: **data**

Used in components: **Instrument**

**180.2.907 EncodedIssuerLen**

Byte length of encoded (non-ASCII characters) EncodedIssuer (349) field.

Type: **Length**

Used in components: **Instrument**

**180.2.908 EncodedLegAdditionalTermBondDesc**

Encoded (non-ASCII characters) representation of the LegAdditionalTermBondDesc(41319) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegAdditionalTermBondDesc(41319) field.

Type: **data**

Used in groups: [LegAdditionalTermBondRefGrp](#)

#### **180.2.909 EncodedLegAdditionalTermBondDescLen**

Byte length of encoded (non-ASCII characters) EncodedLegAdditionalTermBondDesc(41321) field.

Type: [Length](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

#### **180.2.910 EncodedLegAdditionalTermBondIssuer**

Encoded (non-ASCII characters) representation of the LegAdditionalTermBondIssuer(41323) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegAdditionalTermBondIssuer(41323) field.

Type: [data](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

#### **180.2.911 EncodedLegAdditionalTermBondIssuerLen**

Byte length of encoded (non-ASCII characters) EncodedLegAdditionalTermBondIssuer(41325) field.

Type: [Length](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

#### **180.2.912 EncodedLegDeliveryStreamCycleDesc**

Encoded (non-ASCII characters) representation of the LegDeliveryStreamCycleDesc(41457) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegLeg DeliveryStream(41457) field.

Type: [data](#)

Used in groups: [LegDeliveryStreamCycleGrp](#)

#### **180.2.913 EncodedLegDeliveryStreamCycleDescLen**

Byte length of encoded (non-ASCII characters) EncodedLegDeliveryStreamCycleDesc(41459) field.

Type: **Length**

Used in groups: **LegDeliveryStreamCycleGrp**

#### **180.2.914 EncodedLegDocumentationText**

Encoded (non-ASCII characters) representation of the LegDocumentationText(2505) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the LegDocumentationText(2505) field.

Type: **data**

Used in components: **LegFinancingDetails**

#### **180.2.915 EncodedLegDocumentationTextLen**

Byte length of encoded (non-ASCII characters) EncodedLegDocumentationText(2493) field.

Type: **Length**

Used in components: **LegFinancingDetails**

#### **180.2.916 EncodedLegEventText**

Encoded (non-ASCII characters) representation of the LegEventText(2066) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegEventText(2066) field.

Type: **data**

Used in groups: **LegEvntGrp**

#### **180.2.917 EncodedLegEventTextLen**

Byte length of encoded (non-ASCII characters) EncodedLegEventText(2075) field.

Type: **Length**

Used in groups: **LegEvntGrp**

**180.2.918 EncodedLegExerciseDesc**

Encoded (non-ASCII characters) representation of the LegExerciseDesc(41481) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegExerciseDesc(41481) field.

Type: **data**

Used in components: **LegOptionExercise**

**180.2.919 EncodedLegExerciseDescLen**

Byte length of encoded (non-ASCII characters) EncodedLegExerciseDesc(41483) field.

Type: **Length**

Used in components: **LegOptionExercise**

**180.2.920 EncodedLegFinancialInstrumentFullName**

Encoded (non-ASCII characters) representation of the LegFinancialInstrumentFullName(2717) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the LegFinancialInstrumentFullName(2717) field.

Type: **data**

Used in components: **InstrumentLeg**

**180.2.921 EncodedLegFinancialInstrumentFullNameLen**

Byte length of encoded (non-ASCII characters) individual multileg instrument's EncodedLegFinancialInstrumentFullName(2719).

Type: **Length**

Used in components: **InstrumentLeg**

**180.2.922 EncodedLegIssuer**

Multileg instrument's individual security's EncodedIssuer.

See EncodedIssuer (349) field for description

Type: **data**

Used in components: **InstrumentLeg**

### **180.2.923 EncodedLegIssuerLen**

Multileg instrument's individual security's EncodedIssuerLen.

See EncodedIssuerLen (348) field for description

Type: **Length**

Used in components: **InstrumentLeg**

### **180.2.924 EncodedLegMarketDisruptionFallbackUnderlierSecurityDesc**

Encoded (non-ASCII characters) representation of the LegMarketDisruptionFallbackUnderlierSecurityDesc(41475) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegMarketDisruptionFallbackUnderlierSecurityDesc(41475) field.

Type: **data**

Used in groups: **LegMarketDisruptionFallbackReferencePriceGrp**

### **180.2.925 EncodedLegMarketDisruptionFallbackUnderlierSecurityDescLen**

Byte length of encoded (non-ASCII characters) EncodedLegMarketDisruptionFallbackUnderlierSecurityDesc (41477) field.

Type: **Length**

Used in groups: **LegMarketDisruptionFallbackReferencePriceGrp**

### **180.2.926 EncodedLegOptionExpirationDesc**

Encoded (non-ASCII characters) representation of the LegOptionExpirationDesc(2178) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegOptionExpirationDesc(2178).

Type: **data**

Used in components: **InstrumentLeg**

**180.2.927 EncodedLegOptionExpirationDescLen**

Byte length of encoded (non-ASCII characters) EncodedLegOptionExpirationDesc(2180) field.

Type: **Length**

Used in components: **InstrumentLeg**

**180.2.928 EncodedLegProvisionText**

Encoded (non-ASCII characters) representation of the LegProvisionText(40472) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegProvisionText(40472) field.

Type: **data**

Used in groups: **LegProvisionGrp**

**180.2.929 EncodedLegProvisionTextLen**

Byte length of encoded (non-ASCII characters) EncodedLegProvisionText(40472) field.

Type: **Length**

Used in groups: **LegProvisionGrp**

**180.2.930 EncodedLegSecurityDesc**

Multileg instrument's individual security's EncodedSecurityDesc.

See EncodedSecurityDesc (35) field for description

Type: **data**

Used in components: **InstrumentLeg**

**180.2.931 EncodedLegSecurityDescLen**

Multileg instrument's individual security's EncodedSecurityDescLen.

See EncodedSecurityDescLen (350) field for description

Type: **Length**

Used in components: **InstrumentLeg**



**180.2.932 EncodedLegStreamCommodityDesc**

Encoded (non-ASCII characters) representation of the LegStreamCommodityDesc(41652) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegStreamCommodityDesc(41652) field.

Type: **data**

Used in components: **LegStreamCommodity**

**180.2.933 EncodedLegStreamCommodityDescLen**

Byte length of encoded (non-ASCII characters) EncodedLegStreamCommodityDesc(41654) field.

Type: **Length**

Used in components: **LegStreamCommodity**

**180.2.934 EncodedLegStreamText**

Encoded (non-ASCII characters) representation of the LegStreamText(40248) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the LegStreamText(40248) field.

Type: **data**

Used in groups: **LegStreamGrp**

**180.2.935 EncodedLegStreamTextLen**

Byte length of encoded (non-ASCII characters) EncodedLegStreamText(40979) field.

Type: **Length**

Used in groups: **LegStreamGrp**

**180.2.936 EncodedListExecInst**

Encoded (non-ASCII characters) representation of the ListExecInst (69) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the ListExecInst field.

Type: **data**

Used in messages: [NewOrderList](#)

#### **180.2.937 EncodedListExecInstLen**

Byte length of encoded (non-ASCII characters) EncodedListExecInst (353) field.

Type: [Length](#)

Used in messages: [NewOrderList](#)

#### **180.2.938 EncodedListStatusText**

Encoded (non-ASCII characters) representation of the ListStatusText (444) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the ListStatusText field.

Type: [data](#)

Used in messages: [ListStatus](#)

#### **180.2.939 EncodedListStatusTextLen**

Byte length of encoded (non-ASCII characters) EncodedListStatusText (446) field.

Type: [Length](#)

Used in messages: [ListStatus](#)

#### **180.2.940 EncodedMarketDisruptionFallbackUnderlierSecurityDesc**

Encoded (non-ASCII characters) representation of the MarketDisruptionFallbackUnderlierSecurityDesc(41100) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the MarketDisruptionFallbackUnderlierSecurityDesc(41100) field.

Type: [data](#)

Used in groups: [MarketDisruptionFallbackReferencePriceGrp](#)

**180.2.941 EncodedMarketDisruptionFallbackUnderlierSecurityDescLen**

Byte length of encoded (non-ASCII characters) EncodedMarketDisruptionFallbackUnderlierSecurityDesc(41102) field.

Type: **Length**

Used in groups: **MarketDisruptionFallbackReferencePriceGrp**

**180.2.942 EncodedMatchExceptionText**

Encoded (non-ASCII characters) representation of the MatchExceptionText(2780) field in the encoded format specified via the MessageEncoding(347) field.

If used, the ASCII (English) representation should also be specified in the MatchExceptionText(2780) field.

Type: **data**

Used in groups: **MatchExceptionGrp**

**180.2.943 EncodedMatchExceptionTextLen**

Byte length of encoded (non-ASCII characters) EncodedMatchExceptionText(2798) field.

Type: **Length**

Used in groups: **MatchExceptionGrp**

**180.2.944 EncodedMDStatisticDesc**

Encoded (non-ASCII characters) representation of the MDStatisticDesc(2455) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the MDStatisticDesc(2455) field.

Type: **data**

Used in components: **MDStatisticParameters**

**180.2.945 EncodedMDStatisticDescLen**

Byte length of encoded (non-ASCII characters) EncodedMDStatisticDesc(2482) field.

Type: **Length**

Used in components: **MDStatisticParameters**

#### **180.2.946 EncodedMiscFeeSubTypeDesc**

Encoded (non-ASCII characters) representation of the MiscFeeSubTypeDesc(2636) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the MiscFeeSubTypeDesc(2636) field.

Type: **data**

Used in groups: **MiscFeesSubGrp**

#### **180.2.947 EncodedMiscFeeSubTypeDescLen**

Byte length of encoded (non-ASCII characters) EncodedMiscFeeSubTypeDesc(2638) field.

Type: **Length**

Used in groups: **MiscFeesSubGrp**

#### **180.2.948 EncodedMktSegmDesc**

Encoded (non-ASCII characters) representation of the MarketSegmDesc(1396) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the MarketSegmDesc field.

Type: **data**

Used in messages: **MarketDataStatisticsReport**, **MarketDataStatisticsRequest**, **MarketDefinition**, **MarketDefinitionUpdateReport**

#### **180.2.949 EncodedMktSegmDescLen**

Byte length of encoded (non-ASCII characters) EncodedMktSegmDesc(1324) field.

Type: **Length**

Used in messages: **MarketDataStatisticsReport**, **MarketDataStatisticsRequest**, **MarketDefinition**, **MarketDefinitionUpdateReport**

**180.2.950 EncodedOptionExpirationDesc**

Encoded (non-ASCII characters) representation of the OptionExpirationDesc(1581) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the OptionExpirationDesc(1581).

Type: **data**

Used in components: **Instrument**

**180.2.951 EncodedOptionExpirationDescLen**

Byte length of encoded (non-ASCII characters) EncodedOptionExpirationDesc(1697) field.

Type: **Length**

Used in components: **Instrument**

**180.2.952 EncodedPaymentText**

Encoded (non-ASCII characters) representation of the PaymentText(40229) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the PaymentText(40229) field.

Type: **data**

Used in groups: **PaymentGrp**

**180.2.953 EncodedPaymentTextLen**

Byte length of encoded (non-ASCII characters) EncodedPaymentText(40985) field.

Type: **Length**

Used in groups: **PaymentGrp**

**180.2.954 EncodedPostTradePaymentDesc**

Encoded (non-ASCII characters) representation of the PostTradePaymentDesc(2820) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the PostTradePaymentDesc(2820) field.

Type: **data**

Used in components: [PostTradePayment](#)

#### **180.2.955 EncodedPostTradePaymentDescLen**

Byte length of encoded (non-ASCII characters) EncodedPostTradePaymentDesc(2814) field.

Type: [Length](#)

Used in components: [PostTradePayment](#)

#### **180.2.956 EncodedProvisionText**

Encoded (non-ASCII characters) representation of the ProvisionText(40113) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the ProvisionText(40113) field.

Type: [data](#)

Used in groups: [ProvisionGrp](#)

#### **180.2.957 EncodedProvisionTextLen**

Byte length of encoded (non-ASCII characters) EncodedProvisionText(40987) field.

Type: [Length](#)

Used in groups: [ProvisionGrp](#)

#### **180.2.958 EncodedRejectText**

Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the RejectText(1328) field.

Type: [data](#)

Used in groups: [PartyDetailAckGrp](#), [PartyEntitlementAckGrp](#), [PartyRiskLimitsAckGrp](#)

Used in messages: [AlgoCertificateReportAck](#), [AlgoCertificateRequestAck](#), [AllocationInstructionAck](#), [AllocationInstructionAlertRequestAck](#), [AllocationReportAck](#), [CollateralReportAck](#), [CollateralResponse](#),

ExecutionReport, MassOrderAck, OrderCancelReject, PartyActionReport, PartyDetailsListReport, PartyEntitlementsReport, PartyRiskLimitCheckRequestAck, PartyRiskLimitsReport, PartyRiskLimitsReportAck, PayManagementReport, PayManagementReportAck, PositionMaintenanceReport, PositionTransferInstructionAck, PositionTransferReport, QuoteAck, QuoteStatusReport, SettlementStatusReportAck, SettlementStatusRequestAck, TestActionRequestAck, TestSuiteDefinitionRequestAck, TradeAggregationReport, TradeCaptureReport, TradeCaptureReportAck, TradeMatchReportAck

#### **180.2.959 EncodedRejectTextLen**

Byte length of encoded (non-ASCII characters) EncodedRejectText(1665) field.

Type: **Length**

Used in groups: **PartyDetailAckGrp**, **PartyEntitlementAckGrp**, **PartyRiskLimitsAckGrp**

Used in messages: **AlgoCertificateReportAck**, **AlgoCertificateRequestAck**, **AllocationInstructionAck**, **AllocationInstructionAlertRequestAck**, **AllocationReportAck**, **CollateralReportAck**, **CollateralResponse**, **ExecutionReport**, **MassOrderAck**, **OrderCancelReject**, **PartyActionReport**, **PartyDetailsListReport**, **PartyEntitlementsReport**, **PartyRiskLimitCheckRequestAck**, **PartyRiskLimitsReport**, **PartyRiskLimitsReportAck**, **PayManagementReport**, **PayManagementReportAck**, **PositionMaintenanceReport**, **PositionTransferInstructionAck**, **PositionTransferReport**, **QuoteAck**, **QuoteStatusReport**, **SettlementStatusReportAck**, **SettlementStatusRequestAck**, **TestActionRequestAck**, **TestSuiteDefinitionRequestAck**, **TradeAggregationReport**, **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeMatchReportAck**

#### **180.2.960 EncodedReplaceText**

Encoded (non-ASCII characters) representation of the ReplaceText(2805) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the ReplaceText(2805) field.

Type: **data**

Used in messages: **PayManagementReport**

#### **180.2.961 EncodedReplaceTextLen**

Byte length of encoded (non-ASCII characters) EncodedReplaceText(2801) field.

Type: **Length**

Used in messages: **PayManagementReport**

**180.2.962 EncodedSecurityDesc**

Encoded (non-ASCII characters) representation of the SecurityDesc (107) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the SecurityDesc field.

Type: **data**

Used in components: **Instrument**

**180.2.963 EncodedSecurityDescLen**

Byte length of encoded (non-ASCII characters) EncodedSecurityDesc (351) field.

Type: **Length**

Used in components: **Instrument**

**180.2.964 EncodedSecurityListDesc**

Encoded (non-ASCII characters) representation of the SecurityListDesc(1467) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the SecurityListDesc(1467) field.

Type: **data**

Used in messages: **SecurityList, SecurityListUpdateReport**

**180.2.965 EncodedSecurityListDescLen**

Byte length of encoded (non-ASCII characters) EncodedSecurityListDesc(1469) field.

Type: **Length**

Used in messages: **SecurityList, SecurityListUpdateReport**

**180.2.966 EncodedSettlStatusReasonText**

Encoded (non-ASCII characters) representation of the SettlStatusReasonText(2970) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the SettlStatusReasonText(2970) field.

Type: **data**



Used in messages: [SettlementStatusReport](#)

#### **180.2.967 EncodedSettlStatusReasonTextLen**

Byte length of encoded (non-ASCII characters) EncodedSettlStatusReasonText(2972) field.

Type: [Length](#)

Used in messages: [SettlementStatusReport](#)

#### **180.2.968 EncodedStreamCommodityDesc**

Encoded (non-ASCII characters) representation of the StreamCommodityDesc(41255) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the StreamCommodityDesc(41255) field.

Type: [data](#)

Used in components: [StreamCommodity](#)

#### **180.2.969 EncodedStreamCommodityDescLen**

Byte length of encoded (non-ASCII characters) EncodedStreamCommodityDesc(41257) field.

Type: [Length](#)

Used in components: [StreamCommodity](#)

#### **180.2.970 EncodedStreamText**

Encoded (non-ASCII characters) representation of the StreamText(40056) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the StreamText(40056) field.

Type: [data](#)

Used in groups: [StreamGrp](#)

#### **180.2.971 EncodedStreamTextLen**

Byte length of encoded (non-ASCII characters) EncodedStreamText(40983) field.

Type: **Length**

Used in groups: **StreamGrp**

### **180.2.972 EncodedSubject**

Encoded (non-ASCII characters) representation of the Subject (147) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the Subject field.

Type: **data**

Used in messages: **Email**

### **180.2.973 EncodedSubjectLen**

Byte length of encoded (non-ASCII characters) EncodedSubject (357) field.

Type: **Length**

Used in messages: **Email**

### **180.2.974 EncodedText**

Encoded (non-ASCII characters) representation of the Text (58) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the Text(58) field.

Type: **data**

Used in groups: **BidCompRspGrp, InstrmtStrkPxGrp, LinesOfTextGrp, ListOrdGrp, MDFullGrp, MDIncGrp, OrdListStatGrp, RelSymDerivSecGrp, RelSymDerivSecUpdGrp, SecListGrp, SecLstUpdRelSymGrp, SecMassStatGrp, SideCrossOrdCxlGrp, SideCrossOrdModGrp, StrmAsgnRptInstrmtGrp, TrdCapRptSideGrp, TrdMatchSideGrp, TrdSessLstGrp**

Used in messages: **Advertisement, AlgoCertificateReport, AlgoCertificateRequest, AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationReport, AllocationReportAck, ApplicationMessageReport, ApplicationMessageRequest, ApplicationMessageRequestAck, AssignmentReport, BidRequest, BusinessMessageReject, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralReportAck, CollateralRequest, CollateralResponse, Confirmation, ConfirmationAck, ConfirmationRequest, ContraryIntentionReport, DerivativeSecurityListRequest, DontKnowTrade, ExecutionAck, ExecutionReport, IOI, ListCancelRequest, ListExecute, ListStatusRequest,**

Logon, Logout, MarginRequirementInquiry, MarginRequirementInquiryAck, MarginRequirementReport, MarketDataRequestReject, MarketDataStatisticsReport, MarketDataStatisticsRequest, MarketDefinition, MarketDefinitionUpdateReport, MassOrder, MassOrderAck, MassQuoteAck, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, PartyActionReport, PartyActionRequest, PartyDetailsDefinitionRequest, PartyDetailsDefinitionRequestAck, PartyDetailsListReport, PartyDetailsListRequest, PartyDetailsListUpdateReport, PartyEntitlementsDefinitionRequest, PartyEntitlementsDefinitionRequestAck, PartyEntitlementsReport, PartyEntitlementsRequest, PartyEntitlementsUpdateReport, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PartyRiskLimitsDefinitionRequest, PartyRiskLimitsDefinitionRequestAck, PartyRiskLimitsReport, PartyRiskLimitsReportAck, PartyRiskLimitsRequest, PartyRiskLimitsUpdateReport, PayManagementReport, PayManagementRequest, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport, Quote, QuoteAck, QuoteRequest, QuoteRequestReject, QuoteResponse, QuoteStatusReport, Reject, RequestForPositions, RequestForPositionsAck, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityListRequest, SecurityStatus, SecurityTypeRequest, SecurityTypes, SettlementInstructions, SettlementObligationReport, SettlementStatusReport, SettlementStatusRequest, StreamAssignmentReportACK, TestActionReport, TestActionRequest, TestSuiteDefinitionRequest, TradeCaptureReportAck, TradeCaptureReportRequest, TradeCaptureReportRequestAck, TradeMatchReportAck, TradingSessionStatus, UserNotification

### **180.2.975 EncodedTextLen**

Byte length of encoded (non-ASCII characters) EncodedText (355) field.

Type: Length

Used in groups: BidCompRspGrp, InstrmtStrkPxGrp, LinesOfTextGrp, ListOrdGrp, MDFullGrp, MDIncGrp, OrdListStatGrp, RelSymDerivSecGrp, RelSymDerivSecUpdGrp, SecListGrp, SecLstUpdRelSymGrp, SecMassStatGrp, SideCrossOrdCxlGrp, SideCrossOrdModGrp, StrmAsgnRptInstrmtGrp, TrdCapRptSideGrp, TrdMatchSideGrp, TrdSessLstGrp

Used in messages: Advertisement, AlgoCertificateReport, AlgoCertificateRequest, AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationReport, AllocationReportAck, ApplicationMessageReport, ApplicationMessageRequest, ApplicationMessageRequestAck, AssignmentReport, BidRequest, BusinessMessageReject, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralReportAck, CollateralRequest, CollateralResponse, Confirmation, ConfirmationAck, ConfirmationRequest, ContraryIntentionReport, DerivativeSecurityListRequest, DontKnowTrade, ExecutionAck, ExecutionReport, IOI, ListCancelRequest, ListExecute, ListStatusRequest,

Logon, Logout, MarginRequirementInquiry, MarginRequirementInquiryAck, MarginRequirementReport, MarketDataRequestReject, MarketDataStatisticsReport, MarketDataStatisticsRequest, MarketDefinition, MarketDefinitionUpdateReport, MassOrder, MassOrderAck, MassQuoteAck, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, PartyActionReport, PartyActionRequest, PartyDetailsDefinitionRequest, PartyDetailsDefinitionRequestAck, PartyDetailsListReport, PartyDetailsListRequest, PartyDetailsListUpdateReport, PartyEntitlementsDefinitionRequest, PartyEntitlementsDefinitionRequestAck, PartyEntitlementsReport, PartyEntitlementsRequest, PartyEntitlementsUpdateReport, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PartyRiskLimitsDefinitionRequest, PartyRiskLimitsDefinitionRequestAck, PartyRiskLimitsReport, PartyRiskLimitsReportAck, PartyRiskLimitsRequest, PartyRiskLimitsUpdateReport, PayManagementReport, PayManagementRequest, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport, Quote, QuoteAck, QuoteRequest, QuoteRequestReject, QuoteResponse, QuoteStatusReport, Reject, RequestForPositions, RequestForPositionsAck, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityListRequest, SecurityStatus, SecurityTypeRequest, SecurityTypes, SettlementInstructions, SettlementObligationReport, SettlementStatusReport, SettlementStatusRequest, StreamAssignmentReportACK, TestActionReport, TestActionRequest, TestSuiteDefinitionRequest, TradeCaptureReportAck, TradeCaptureReportRequest, TradeCaptureReportRequestAck, TradeMatchReportAck, TradingSessionStatus, UserNotification

#### **180.2.976 EncodedTradeContinuationText**

Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the TradeContinuationText(2374) field.

Type: **data**

Used in groups: **QuotReqGrp**

Used in messages: **AllocationInstruction, AllocationReport, Confirmation, ExecutionReport, PositionReport, Quote, QuoteResponse, QuoteStatusReport, TradeCaptureReport**

#### **180.2.977 EncodedTradeContinuationTextLen**

Byte length of encoded (non-ASCII characters) EncodedTradeContinuationText(2371) field.

Type: **Length**

Used in groups: **QuotReqGrp**

Used in messages: [AllocationInstruction](#), [AllocationReport](#), [Confirmation](#), [ExecutionReport](#), [Position-Report](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [TradeCaptureReport](#)

#### **180.2.978 EncodedUnderlyingAdditionalTermBondDesc**

Encoded (non-ASCII characters) representation of the UnderlyingAdditionalTermBondDesc(41709) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingAdditionalTermBondDesc(41709) field.

Type: [data](#)

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### **180.2.979 EncodedUnderlyingAdditionalTermBondDescLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingAdditionalTermBondDesc(41711) field.

Type: [Length](#)

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### **180.2.980 EncodedUnderlyingAdditionalTermBondIssuer**

Encoded (non-ASCII characters) representation of the UnderlyingAdditionalTermBondIssuer(42017) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingAdditionalTermBondIssuer(42017) field.

Type: [data](#)

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### **180.2.981 EncodedUnderlyingAdditionalTermBondIssuerLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingAdditionalTermBondIssuer(42026) field.

Type: [Length](#)

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

**180.2.982 EncodedUnderlyingDeliveryStreamCycleDesc**

Encoded (non-ASCII characters) representation of the UnderlyingDeliveryStreamCycleDesc(41805) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingDeliveryStreamCycleDesc(41805) field.

Type: **data**

Used in groups: **UnderlyingDeliveryStreamCycleGrp**

**180.2.983 EncodedUnderlyingDeliveryStreamCycleDescLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingDeliveryStreamCycleDesc(41807) field.

Type: **Length**

Used in groups: **UnderlyingDeliveryStreamCycleGrp**

**180.2.984 EncodedUnderlyingEventText**

Encoded (non-ASCII characters) representation of the UnderlyingEventText(2071) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingEventText(2071) field.

Type: **data**

Used in groups: **UnderlyingEvntGrp**

**180.2.985 EncodedUnderlyingEventTextLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingEventText(2073) field.

Type: **Length**

Used in groups: **UnderlyingEvntGrp**

**180.2.986 EncodedUnderlyingExerciseDesc**

Encoded (non-ASCII characters) representation of the UnderlyingExerciseDesc(41810) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingExerciseDesc(41810) field.

Type: **data**

Used in components: **UnderlyingOptionExercise**

#### **180.2.987 EncodedUnderlyingExerciseDescLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingExerciseDesc(41812) field.

Type: **Length**

Used in components: **UnderlyingOptionExercise**

#### **180.2.988 EncodedUnderlyingFinancialInstrumentFullName**

Encoded (non-ASCII characters) representation of the UnderlyingFinancialInstrumentFullName(2720) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingFinancialInstrumentFullName(2720) field.

Type: **data**

Used in components: **UnderlyingInstrument**

#### **180.2.989 EncodedUnderlyingFinancialInstrumentFullNameLen**

Byte length of encoded (non-ASCII characters) underlying instrument's EncodedUnderlyingFinancialInstrumentFullName(2722).

Type: **Length**

Used in components: **UnderlyingInstrument**

#### **180.2.990 EncodedUnderlyingIssuer**

Encoded (non-ASCII characters) representation of the UnderlyingIssuer (306) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingIssuer field.

Type: **data**

Used in components: **UnderlyingInstrument**

**180.2.991 EncodedUnderlyingIssuerLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingIssuer (363) field.

Type: **Length**

Used in components: **UnderlyingInstrument**

**180.2.992 EncodedUnderlyingMarketDisruptionFallbackUnderlierSecDescLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingMarketDisruptionFallbackUnderlierSecurityDesc(41874) field.

Type: **Length**

Used in groups: **UnderlyingMarketDisruptionFallbackReferencePriceGrp**

**180.2.993 EncodedUnderlyingMarketDisruptionFallbackUnderlierSecurityDesc**

Encoded (non-ASCII characters) representation of the UnderlyingMarketDisruptionFallbackUnderlierSecurityDesc(41872) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingMarketDisruptionFallbackUnderlierSecurityDesc(41872).

Type: **data**

Used in groups: **UnderlyingMarketDisruptionFallbackReferencePriceGrp**

**180.2.994 EncodedUnderlyingOptionExpirationDesc**

Encoded (non-ASCII characters) representation of the UnderlyingOptionExpirationDesc(2286) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingOptionExpirationDesc(2286).

Type: **data**

Used in components: **UnderlyingInstrument**

**180.2.995 EncodedUnderlyingOptionExpirationDescLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingOptionExpirationDesc(2288) field.

Type: **Length**



Used in components: [UnderlyingInstrument](#)

#### **180.2.996 EncodedUnderlyingProvisionText**

Encoded (non-ASCII characters) representation of the UnderlyingProvisionText(42170) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingProvisionText(42170) field.

Type: [data](#)

Used in groups: [UnderlyingProvisionGrp](#)

#### **180.2.997 EncodedUnderlyingProvisionTextLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingProvisionText(42712) field.

Type: [Length](#)

Used in groups: [UnderlyingProvisionGrp](#)

#### **180.2.998 EncodedUnderlyingSecurityDesc**

Encoded (non-ASCII characters) representation of the UnderlyingSecurityDesc (307) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingSecurityDesc field.

Type: [data](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.999 EncodedUnderlyingSecurityDescLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingSecurityDesc (365) field.

Type: [Length](#)

Used in components: [UnderlyingInstrument](#)

**180.2.1000 EncodedUnderlyingStreamCommodityDesc**

Encoded (non-ASCII characters) representation of the UnderlyingStreamCommodityDesc(41968) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingStreamCommodityDesc(41968) field.

Type: **data**

Used in components: **UnderlyingStreamCommodity**

**180.2.1001 EncodedUnderlyingStreamCommodityDescLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingStreamCommodityDesc(41970) field.

Type: **Length**

Used in components: **UnderlyingStreamCommodity**

**180.2.1002 EncodedUnderlyingStreamText**

Encoded (non-ASCII characters) representation of the UnderlyingStreamText(40547) field in the encoded format specified via the MessageEncoding (347) field. If used, the ASCII (English) representation should also be specified in the UnderlyingStreamText(40547) field.

Type: **data**

Used in groups: **UnderlyingStreamGrp**

**180.2.1003 EncodedUnderlyingStreamTextLen**

Byte length of encoded (non-ASCII characters) EncodedUnderlyingStreamText(40989) field.

Type: **Length**

Used in groups: **UnderlyingStreamGrp**

**180.2.1004 EncodedWarningText**

Encoded (non-ASCII characters) representation of the WarningText(2520) field in the encoded format specified via the MessageEncoding(347) field. If used, the ASCII (English) representation should also be specified in the WarningText(2520) field.

Type: **data**

Used in messages: **CollateralResponse**

#### **180.2.1005 EncodedWarningTextLen**

Byte length of encoded (non-ASCII characters) EncodedWarningText(2521) field.

Type: **Length**

Used in messages: **CollateralResponse**

#### **180.2.1006 EncryptedNewPassword**

Encrypted new password - encrypted via the method specified in the field EncryptedPassword-Method(1400)

Type: **data**

Used in messages: **Logon, UserRequest**

#### **180.2.1007 EncryptedNewPasswordLen**

Length of the EncryptedNewPassword(1404) field

Type: **Length**

Used in messages: **Logon, UserRequest**

#### **180.2.1008 EncryptedPassword**

Encrypted password - encrypted via the method specified in the field EncryptedPassword-Method(1400)

Type: **data**

Used in messages: **Logon, UserRequest**

#### **180.2.1009 EncryptedPasswordLen**

Length of the EncryptedPassword(1402) field

Type: **Length**

Used in messages: **Logon, UserRequest**

**180.2.1010 EncryptedPasswordMethod**

Enumeration defining the encryption method used to encrypt password fields.

At this time there are no encryption methods defined by FPL.

Type: **int**

Used in messages: **Logon**, **UserRequest**

**180.2.1011 EncryptMethod**

Method of encryption.

Type: **int**

Allowed values in EncryptMethodCodeSet:

Code	Name	Description
0	None	None / Other
1	PKCS	PKCS (Proprietary)
2	DES	DES (ECB Mode)
3	PKCSDES	PKCS / DES (Proprietary)
4	PGPDES	PGP / DES (Defunct)
5	PGPDESMD5	PGP / DES-MD5 (See app note on FIX web site)
6	PEM	PEM / DES-MD5 (see app note on FIX web site)

Used in messages: **Logon**

**180.2.1012 EndAccruedInterestAmt**

Accrued Interest Amount applicable to a financing transaction on the End Date.

Type: **Amt**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **CollateralAssignment**, **CollateralInquiry**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**, **Confirmation**, **ExecutionReport**

**180.2.1013 EndCash**

Ending dirty cash consideration of a financing deal. i.e. reimbursed to the buyer on the End Date.

Type: **Amt**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **CollateralAssignment**, **CollateralInquiry**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**, **Confirmation**, **ExecutionReport**

**180.2.1014 EndDate**

End date of a financing deal, i.e. the date the seller reimburses the buyer and takes back control of the collateral

Type: **LocalMktDate**

Used in components: **FinancingDetails**

**180.2.1015 EndMaturityMonthYear**

Ending maturity month year for an option class

Type: **MonthYear**

Used in groups: **MaturityRules**

**180.2.1016 EndPriceRange**

Upper boundary for price range.

Type: **Price**

Used in groups: **PriceRangeRuleGrp**

**180.2.1017 EndSeqNo**

Message sequence number of last message in range to be resent. If request is for a single message **BeginSeqNo** (7) = **EndSeqNo**. If request is for all messages subsequent to a particular message, **EndSeqNo** = "0" (representing infinity).

Type: **SeqNum**

Used in messages: **ResendRequest**

#### **180.2.1018 EndStrikePxRange**

Ending price of the range to which the StrikeIncrement applies. Price refers to the price of the underlying

Type: **Price**

Used in groups: **StrikeRules**

#### **180.2.1019 EndTickPriceRange**

Ending price range for the specified tick increment

Type: **Price**

Used in groups: **TickRules**

#### **180.2.1020 EntitlementAttribCurrency**

Currency for EntitlementAttribValue(1780). Can be used if these fields represent a price, price offset, or amount.

Type: **Currency**

Used in groups: **EntitlementAttribGrp**

#### **180.2.1021 EntitlementAttribCurrencyCodeSource**

Identifies class or source of the EntitlementAttribCurrency(1781) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

---

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN

---

Code	Name	Description
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **EntitlementAttribGrp**

### 180.2.1022 EntitlementAttribDatatype

Datatype of the entitlement attribute.

Type: **int**

Allowed values in EntitlementAttribDatatypeCodeSet:

Code	Name	Description
1	Int	int
2	Length	Length
3	NumInGroup	NumInGroup
4	SeqNum	SeqNum
5	TagNum	TagNum
6	Float	float
7	Qty	Qty
8	Price	Price
9	PriceOffset	PriceOffset
10	Amt	Amt
11	Percentage	Percentage
12	Char	char
13	Boolean	Boolean
14	String	String
15	MultipleCharValue	MultipleCharValue
16	Currency	Currency
17	Exchange	Exchange
18	MonthYear	MonthYear

Code	Name	Description
19	UTCTimestamp	UTCTimestamp
20	UTCTimeOnly	UTCTimeOnly
21	LocalMktDate	LocalMktDate
22	UTCDateOnly	UTCDateOnly
23	Data	data
24	MultipleStringValue	MultipleStringValue
25	Country	Country
26	Language	Language
27	TZTimeOnly	TZTimeOnly
28	TZTimestamp	TZTimestamp
29	Tenor	Tenor
30	DayOfMonth	DayOfMonth
31	XMLData	XMLData
32	Pattern	Pattern
33	Reserved100Plus	Reserved100Plus
34	Reserved1000Plus	Reserved1000Plus
35	Reserved4000Plus	Reserved4000Plus

Used in groups: **EntitlementAttribGrp**

### 180.2.1023 EntitlementAttribGrp

conveys a list of one or more attributes related to an entitlement. An entitlement may contain an EntitlementType, which states what can be done at a gross level, e.g. that a party can make markets. It may be limited further within EntitlementGrp, e.g. that such market making is allowed only for a list of stocks. The EntitlementAttribGrp contains fine details clarifying or limiting the EntitlementType, e.g. that such market making must be conducted with a specific minimum quote size and a specific maximum spread.

Name	Mult.	Type	Description
NoEntitlementAttrib	[1..1]	NumInGroup	
EntitlementAttribType	[0..1]	int	Required if NoEntitlementAttrib(1777) > 0.



Name	Mult.	Type	Description
EntitlementAttribDatatype	[0..1]	CodeSet	If specified, and this is an attribute published by FPL in the external code list, this must agree with the published datatype.
EntitlementAttribValue	[0..1]	String	Required if NoEntitlementAttrib(1777) > 0.
EntitlementAttribCurrency	[0..1]	Currency	
EntitlementAttribCurrencyCodeSource	[0..1]	CodeSet	

Used in groups: **EntitlementGrp**

#### **180.2.1024 EntitlementAttribType**

Name of the entitlement attribute type. A code list of allowed values will be maintained on the FIX Protocol website.

Values "4000" and above are reserved for bilaterally agreed upon user defined enumerations.

Type: **int**

Used in groups: **EntitlementAttribGrp**

#### **180.2.1025 EntitlementAttribValue**

Value of the entitlement attribute.

Type: **String**

Used in groups: **EntitlementAttribGrp**

#### **180.2.1026 EntitlementEndDate**

Indicates the ending date of the entitlement.

Type: **LocalMktDate**

Used in groups: **EntitlementGrp**

#### **180.2.1027 EntitlementGrp**

Conveys a list of entitlements for one specific party, or relationship between two parties. Each entitlement may be further limited or clarified using optional fields and components.

Name	Mult.	Type	Description
NoEntitlements	[1..1]	NumInGroup	
EntitlementIndicator	[0..1]	Boolean	Required if NoEntitlements(1773) > 0.
EntitlementType	[0..1]	CodeSet	Absence of this field indicates the meaning of the entitlement is implicit.
EntitlementSubType	[0..1]	CodeSet	
EntitlementAttribGrp	[0..*]	Group	
EntitlementID	[0..1]	String	
EntitlementPlatform	[0..1]	String	
InstrumentScopeGrp	[0..*]	Group	
MarketSegmentScopeGrp	[0..*]	Group	
EntitlementStartDate	[0..1]	LocalMktDate	
EntitlementEndDate	[0..1]	LocalMktDate	

Used in groups: **PartyEntitlementAckGrp**, **PartyEntitlementGrp**, **PartyEntitlementUpdateGrp**

#### 180.2.1028 EntitlementID

Unique identifier for a specific NoEntitlements(1773) repeating group instance.

Type: **String**

Used in groups: **EntitlementGrp**

#### 180.2.1029 EntitlementIndicator

Used to indicate if a party is entitled to an entitlement type specified in the EntitlementType(1775) field.

Type: **Boolean**

Used in groups: **EntitlementGrp**

#### 180.2.1030 EntitlementPlatform

The area to which the entitlement is applicable. This can be a trading platform or an offering.

Type: **String**

Used in groups: [EntitlementGrp](#)

Used in messages: [PartyEntitlementsRequest](#)

#### **180.2.1031 EntitlementRefID**

Reference to an EntitlementID(1776). Used for modification or deletion of an entitlement.

Type: [String](#)

Used in groups: [PartyEntitlementAckGrp](#), [PartyEntitlementUpdateGrp](#)

#### **180.2.1032 EntitlementReportID**

Identifier for the PartyEntitlementsReport(35=CV).

Type: [String](#)

Used in messages: [PartyEntitlementsReport](#), [PartyEntitlementsUpdateReport](#)

#### **180.2.1033 EntitlementRequestID**

Unique identifier for PartyEntitlementsRequest(35=CU).

Type: [String](#)

Used in messages: [PartyEntitlementsDefinitionRequest](#), [PartyEntitlementsDefinitionRequestAck](#), [PartyEntitlementsReport](#), [PartyEntitlementsRequest](#), [PartyEntitlementsUpdateReport](#)

#### **180.2.1034 EntitlementRequestResult**

Result of risk limit definition request.

Type: [int](#)

Allowed values in EntitlementRequestResultCodeSet:

---

Code	Name	Description
0	Successful	Successful (default)
1	InvalidParty	Invalid party(-ies)
2	InvalidRelatedParty	Invalid related party(-ies)
3	InvalidEntitlementType	Invalid entitlement type(s)

---

Code	Name	Description
4	InvalidEntitlementID	Invalid entitlement ID(s) / ref ID(s)
5	InvalidEntitlementAttribute	Invalid entitlement attribute(s)
6	InvalidInstrumentScope	Invalid instrument scope(s)
7	InvalidMarketSegmentScope	Invalid market segment scope(s)
8	InvalidStartDate	Invalid start date
9	InvalidEndDate	Invalid end date
10	InstrumentScopeNotSupported	Instrument scope not supported
11	MarketSegmentScopeNotSupported	Market segment scope not supported
12	EntitlementNotApprovedForParty	Entitlement not approved for party(-ies)
13	EntitlementAlreadyDefinedForParty	Entitlement already defined for party(-ies)
14	InstrumentNotApprovedForParty	Instrument not approved for party(-ies)
98	NotAuthorized	Not authorized
99	Other	Other

Used in messages: [PartyEntitlementsDefinitionRequestAck](#)

#### **180.2.1035 EntitlementRequestStatus**

Status of party entitlements definition request.

Type: [int](#)

Allowed values in [PartyDetailRequestStatusCodeSet](#):

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithChanges	Accepted with changes
2	Rejected	Rejected
3	AcceptancePending	Acceptance pending

Used in messages: [PartyEntitlementsDefinitionRequestAck](#)

#### **180.2.1036 EntitlementResult**

Result of entitlement definition for one party.

Type: **int**

Allowed values in EntitlementRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidParty	Invalid party(-ies)
2	InvalidRelatedParty	Invalid related party(-ies)
3	InvalidEntitlementType	Invalid entitlement type(s)
4	InvalidEntitlementID	Invalid entitlement ID(s) / ref ID(s)
5	InvalidEntitlementAttribute	Invalid entitlement attribute(s)
6	InvalidInstrumentScope	Invalid instrument scope(s)
7	InvalidMarketSegmentScope	Invalid market segment scope(s)
8	InvalidStartDate	Invalid start date
9	InvalidEndDate	Invalid end date
10	InstrumentScopeNotSupported	Instrument scope not supported
11	MarketSegmentScopeNotSupported	Market segment scope not supported
12	EntitlementNotApprovedForParty	Entitlement not approved for party(-ies)
13	EntitlementAlreadyDefinedForParty	Entitlement already defined for party(-ies)
14	InstrumentNotApprovedForParty	Instrument not approved for party(-ies)
98	NotAuthorized	Not authorized
99	Other	Other

Used in groups: **PartyEntitlementAckGrp**

#### **180.2.1037 EntitlementStartDate**

Indicates the starting date of the entitlement.

Type: **LocalMktDate**

Used in groups: **EntitlementGrp**

#### **180.2.1038 EntitlementStatus**

Status of entitlement definition for one party.

Type: **int**

Allowed values in EntitlementStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithChanges	Accepted with changes
2	Rejected	Rejected
3	Pending	Pending. Entitlement definition request submitted that still requires an action to be taken (e.g. approval or setting up).
4	Requested	Requested. Entitlement definition has been requested.
5	Deferred	Deferred. Entitlement definition request is being postponed or delayed.

Used in groups: [PartyEntitlementAckGrp](#), [PartyEntitlementGrp](#), [PartyEntitlementUpdateGrp](#)

Used in messages: [PartyEntitlementsRequest](#)

### 180.2.1039 EntitlementSubType

Subtype of an entitlement specified in EntitlementType(1775).

Type: [int](#)

Allowed values in EntitlementSubTypeCodeSet:

Code	Name	Description
1	OrderEntry	Order entry. Entitle to enter new orders
2	HitLift	Hit/Lift. Entitle to Hit/Lift
3	ViewIndicativePx	View indicative prices. Entitle to subscribe to indicative prices
4	ViewExecutablePx	View executable prices. Entitle to subscribe to executable prices
5	SingleQuote	Single quote. Entitle to submit quote request for a single quote
6	StreamingQuotes	Streaming quotes. Entitle to submit quote request for streaming quotes
7	SingleBroker	Single broker. Entitle to submit quote request for a single broker
8	MultiBrokers	Multi brokers. Entitle to submit quote request for multiple brokers

Used in groups: [EntitlementGrp](#), [EntitlementTypeGrp](#)

**180.2.1040 EntitlementType**

Type of entitlement.

Type: **int**

Allowed values in EntitlementTypeCodeSet:

Code	Name	Description
0	Trade	Trade
1	MakeMarkets	Make markets
2	HoldPositions	Hold positions
3	PerformGiveUps	Perform give-ups
4	SubmitIOIs	Submit Indications of Interest (IOIs)
5	SubscribeMarketData	Subscribe to market data
6	ShortWithPreBorrow	Short with pre-borrow. Short sell order is allowed with pre-borrowing.
7	SubmitQuoteRequests	Submit quote requests. Entitled to submit quote requests into the market in order to receive quotes from the market.
8	RespondToQuoteRequests	Respond to quote requests. Entitled to respond to quote requests from the market.

Used in groups: **EntitlementGrp**, **EntitlementTypeGrp**

**180.2.1041 EntitlementTypeGrp**

The EntitlementTypeGrp conveys a list of entitlement types.

Name	Mult.	Type	Description
<b>NoEntitlementTypes</b>	[1..1]	NumInGroup	Number of Entitlement Types.
<b>EntitlementType</b>	[0..1]	CodeSet	Required if NoEntitlementTypes(2345) > 0.
<b>EntitlementSubType</b>	[0..1]	CodeSet	

Used in messages: **PartyEntitlementsRequest**

**180.2.1042 EventDate**

Date of event

Type: **LocalMktDate**

Used in groups: **EvntGrp**

### **180.2.1043 EventInitiatorType**

Indicates the type of entity who initiated an event, e.g. modification or cancellation of an order or quote.

Type: **char**

Allowed values in EventInitiatorTypeCodeSet:

Code	Name	Description
C	CustomerOrClient	Customer or client
E	ExchangeOrExecutionVenue	Exchange or execution venue
F	FirmOrBroker	Firm or broker

Used in messages: **ExecutionReport**, **QuoteStatusReport**

### **180.2.1044 EventMonthYear**

Used with derivatives when an event is express as a month-year with optional day or month or week of month.

Format:

YYYYMM (e.g. 199903)

YYYYMMDD (e.g. 20030323)

YYYYMMwN (e.g. 200303w2) for week

A specific date can be appended to the month-year. For instance, if multiple event types exist in the same Year and Month, but actually at a different time, a value can be appended, such as "w" or "w2" to indicate week. Likewise, the day of monty (0-31) can be appended to indicate a specific event date.

Type: **MonthYear**

Used in groups: **EvntGrp**



**180.2.1045 EventPx**

Predetermined price of issue at event, if applicable

Type: **Price**

Used in groups: **EvntGrp**

**180.2.1046 EventText**

Comments related to the event.

Type: **String**

Used in groups: **EvntGrp**

**180.2.1047 EventTime**

Specific time of event. To be used in combination with EventDate [866]

Type: **UTCTimestamp**

Used in groups: **EvntGrp**

**180.2.1048 EventTimePeriod**

Time unit multiplier for the event.

Type: **int**

Used in groups: **EvntGrp**

**180.2.1049 EventTimeUnit**

Time unit associated with the event.

Type: **String**

Allowed values in EventTimeUnitCodeSet:

---

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute

---

Code	Name	Description
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **EvntGrp**

### 180.2.1050 EventType

Code to represent the type of event

Type: **int**

Allowed values in EventTypeCodeSet:

Code	Name	Description
1	Put	Put
2	Call	Call
3	Tender	Tender
4	SinkingFundCall	Sinking fund call
5	Activation	Activation
6	Inactivation	Inactivation
7	LastEligibleTradeDate	Last eligible trade date
8	SwapStartDate	Swap start date
9	SwapEndDate	Swap end date
10	SwapRollDate	Swap roll date
11	SwapNextStartDate	Swap next start date
12	SwapNextRollDate	Swap next roll date
13	FirstDeliveryDate	First delivery date
14	LastDeliveryDate	Last delivery date
15	InitialInventoryDueDate	Initial inventory due date
16	FinalInventoryDueDate	Final inventory due date
17	FirstIntentDate	First intent date
18	LastIntentDate	Last intent date

Code	Name	Description
19	PositionRemovalDate	Position removal date
20	MinimumNotice	Minimum notice
21	DeliveryStartTime	Delivery start time
22	DeliveryEndTime	Delivery end time
23	FirstNoticeDate	First notice date. The first day that a notice of intent to deliver a commodity can be made by a clearing house to a buyer in fulfillment of a given month's futures contract.
24	LastNoticeDate	Last notice date. The last day on which a clearing house may inform an investor that a seller intends to make delivery of a commodity that the investor previously bought in a futures contract. The date is governed by the rules of different exchanges and clearing houses, but may also be stated in the futures contract itself.
25	FirstExerciseDate	First exercise date
26	RedemptionDate	Redemption date
27	TrdCntntnEfctvDt	Trade continuation effective date
99	Other	Other

Used in groups: **EvntGrp**

### 180.2.1051 EvntGrp

The EvntGrp is a repeating subcomponent of the Instrument component used to specify straightforward events associated with the instrument. Examples include put and call dates for bonds and options; first exercise date for options; inventory and delivery dates for commodities; start, end and roll dates for swaps. Use ComplexEvents for more advanced dates such as option, futures, commodities and equity swap observation and pricing events.

Name	Mult.	Type	Description
NoEvents	[1..1]	NumInGroup	
EventType	[0..1]	CodeSet	Required if NoEvents(864) > 0.
EventDate	[0..1]	LocalMktDate	Conditionally required when EventType(1145) is specified.
EventTime	[0..1]	UTCTimestamp	
EventTimeUnit	[0..1]	CodeSet	Conditionally required when EventTimePeriod(1826) is specified.

Name	Mult.	Type	Description
EventTimePeriod	[0..1]	int	Conditionally required when EventTimeUnit(1827) is specified.
EventMonthYear	[0..1]	MonthYear	
EventPx	[0..1]	Price	
EventText	[0..1]	String	
EncodedEventTextLen	[0..1]	Length	Must be set if EncodedEventText(1579) field is specified and must immediately precede it.
EncodedEventText	[0..1]	data	Encoded (non-ASCII characters) representation of the EventText(868) field in the encoded format specified via the MessageEncoding(347) field.

Used in components: **Instrument**

### 180.2.1052 ExchangeForPhysical

Indicates whether or not to exchange for physical.

Type: **Boolean**

Allowed values in ExchangeForPhysicalCodeSet:

Code	Name	Description
N	False	False
Y	True	True

Used in messages: **BidRequest**

### 180.2.1053 ExchangeLookAlike

For a share option trade, indicates whether the instrument is to be treated as an 'exchange look-alike'.

Type: **Boolean**

Used in components: **Instrument**

**180.2.1054 ExchangeRule**

Used to report any exchange rules that apply to this trade.

Primarily intended for US futures markets. Certain trading practices are permitted by the CFTC, such as large lot trading, block trading, all or none trades. If the rules are used, the exchanges are required to indicate these rules on the trade.

Type: **String**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.1055 ExchangeSpecialInstructions**

Free format text string related to exchange.

Type: **String**

Used in groups: **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.1056 ExDate**

The date when a distribution of interest is deducted from a securities assets or set aside for payment to bondholders. On the ex-date, the securities price drops by the amount of the distribution (plus or minus any market activity).

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCDate)

Type: **LocalMktDate**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **Confirmation**, **ExecutionReport**

**180.2.1057 ExDestination**

Execution destination as defined by institution when order is entered.

Valid values:

See "Appendix 6-C"

Type: **Exchange**

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReject](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

### 180.2.1058 ExDestinationIDSource

The ID source of ExDestination

Type: [char](#)

Allowed values in ExDestinationIDSourceCodeSet:

Code	Name	Description
B	BIC	BIC (Bank Identification Code) (ISO 9362)
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
D	Proprietary	Proprietary / Custom code
E	ISOCountryCode	ISO Country Code
G	MIC	MIC (ISO 10383 - Market Identifier Code)

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReject](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

### 180.2.1059 ExDestinationType

Identifies the type of execution destination for the order.

Type: [int](#)

Allowed values in ExDestinationTypeCodeSet:

Code	Name	Description
0	NoRestriction	No restriction. May be used for MiFID II to indicate no restriction on where the order is executed.

Code	Name	Description
1	TradedOnlyOnTradingVenue	Can be traded only on a trading venue. May be used for MiFID II to indicate the order can only be executed on a trading venue.
2	TradedOnlyOnSI	Can be traded only on a Systematic Internaliser (SI). May be used for MiFID II to indicate the order can only be executed on a Systematic Internaliser.
3	TradedOnTradingVenueOrSI	Can be traded on a trading venue or Systematic internaliser (SI). May be used for MiFID II to indicate the order can be executed on either a trading venue or a Systematic Internaliser.

Used in components: [TradeReportOrderDetail](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

#### **180.2.1060 ExecAckStatus**

The status of this execution acknowledgement message.

Type: [char](#)

Allowed values in ExecAckStatusCodeSet:

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	DontKnow	Don't know / Rejected

Used in messages: [ExecutionAck](#)

#### **180.2.1061 ExecAllocGrp**

This repeating group is used to identify individual executions or trades, including key fields such as quantity and price of the execution or trade, that are part of the allocation.

Name	Mult.	Type	Description
NoExecs	[1..1]	NumInGroup	Indicates number of individual execution or trade entries. Absence indicates that no individual execution or trade entries are included. Primarily used to support step-outs.
LastQty	[0..1]	Qty	Amount of quantity (e.g. number of shares) in individual execution. Required if NoExecs > 0
ExecID	[0..1]	String	
SecondaryExecID	[0..1]	String	
LastPx	[0..1]	Price	Price of individual execution. Required if NoExecs > 0. For FX, if specified, expressed in terms of Currency(15).
LastParPx	[0..1]	Price	Last price expressed in percent-of-par. Conditionally required for Fixed Income trades when LastPx is expressed in Yield, Spread, Discount or any other price type
LastCapacity	[0..1]	CodeSet	Used to identify whether the trade was executed on an agency or principal basis.
TradeID	[0..1]	String	
FirmTradeID	[0..1]	String	
TrdMatchID	[0..1]	String	Used to identify the match event resulting in the execution or trade.
ExecutionTimestamp	[0..1]	UTCTimestamp	
TradeReportingIndicator	[0..1]	CodeSet	
TrdRegPublicationGrp	[0..*]	Group	
TradePriceConditionGrp	[0..*]	Group	

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#)

### 180.2.1062 ExecCollGrp

Name	Mult.	Type	Description
NoExecs	[1..1]	NumInGroup	Executions for which collateral is required
ExecID	[0..1]	String	Required if NoExecs > 0

Used in messages: [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#)



**180.2.1063 ExecID**

Unique identifier of execution message as assigned by sell-side (broker, exchange, ECN) (will be 0 (zero) for ExecType (150)=I (Order Status)).

Uniqueness must be guaranteed within a single trading day or the life of a multi-day order. Firms which accept multi-day orders should consider embedding a date within the ExecID field to assure uniqueness across days.

(Prior to FIX 4.1 this field was of type int).

Type: **String**

Used in groups: **ExecAllocGrp**, **ExecCollGrp**, **ExecutionAggregationGrp**

Used in messages: **DontKnowTrade**, **ExecutionAck**, **ExecutionReport**, **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**

**180.2.1064 ExecInst**

Instructions for order handling on exchange trading floor. If more than one instruction is applicable to an order, this field can contain multiple instructions separated by space. \*\*\* SOME VALUES HAVE BEEN REPLACED - See "Replaced Features and Supported Approach" \*\*\* (see Volume : "Glossary" for value definitions)

Type: **MultipleCharValue**

Allowed values in ExecInstCodeSet:

Code	Name	Description
0	StayOnOfferSide	Stay on offer side
1	NotHeld	Not held
2	Work	Work
3	GoAlong	Go along
4	OverTheDay	Over the day
5	Held	Held
6	ParticipateDoNotInitiate	Participate don't initiate
7	StrictScale	Strict scale
8	TryToScale	Try to scale
9	StayOnBidSide	Stay on bid side
A	NoCross	No cross. Cross is forbidden.

Code	Name	Description
B	OKToCross	OK to cross
C	CallFirst	Call first
D	PercentOfVolume	Percent of volume. Indicates that the sender does not want the order to be all of the volume on the floor vs. a specific percentage.
E	DoNotIncrease	Do not increase - DNI
F	DoNotReduce	Do not reduce - DNR
G	AllOrNone	All or none - AON
H	ReinstateOnSystemFailure	Reinstate on system failure. Mutually exclusive with Q and I (lower case L).
I	InstitutionsOnly	Institutions only
J	ReinstateOnTradingHalt	Reinstate on trading halt. Mutually exclusive with K and m.
K	CancelOnTradingHalt	Cancel on trading halt. Mutually exclusive with J and m.
L	LastPeg	Last peg (last sale)
M	MidPricePeg	Mid-price peg (midprice of inside quote)
N	NonNegotiable	Non-negotiable
O	OpeningPeg	Opening peg
P	MarketPeg	Market peg
Q	CancelOnSystemFailure	Cancel on system failure. Mutually exclusive with H and I(lower case L).
R	PrimaryPeg	Primary peg. Primary market - buy at bid, sell at offer.
S	Suspend	Suspend
T	FixedPegToLocalBestBidOrOfferAt-TimeOfOrder	Fixed peg to local best bid or offer at time of order
U	CustomerDisplayInstruction	Customer display instruction. Used in US Markets for: SEC Rule 11Ac1-1/4.
V	Netting	Netting (for Forex)
W	PegToVWAP	Peg to VWAP
X	TradeAlong	Trade along
Y	TryToStop	Try to stop
Z	CancelIfNotBest	Cancel if not best
a	TrailingStopPeg	Trailing stop peg
b	StrictLimit	Strict limit. No price improvement.
c	IgnorePriceValidityChecks	Ignore price validity checks
d	PegToLimitPrice	Peg to limit price
e	WorkToTargetStrategy	Work to target strategy

Code	Name	Description
f	IntermarketSweep	Intermarket sweep
g	ExternalRoutingAllowed	External routing allowed
h	ExternalRoutingNotAllowed	External routing not allowed
i	ImbalanceOnly	Imbalance only
j	SingleExecutionRequestedForBlock-Trade	Single execution requested for block trade
k	BestExecution	Best execution
l	SuspendOnSystemFailure	Suspend on system failure. Mutually exclusive with H and Q.
m	SuspendOnTradingHalt	Suspend on trading halt. Mutually exclusive with J and K.
n	ReinstateOnConnectionLoss	Reinstate on connection loss. Mutually exclusive with o and p.
o	CancelOnConnectionLoss	Cancel on connection loss. Mutually exclusive with n and p.
p	SuspendOnConnectionLoss	Suspend on connection loss. Mutually exclusive with n and o.
q	Release	Release. Mutually exclusive with S and w.
r	ExecuteAsDeltaNeutral	Execute as delta neutral using volatility provided
s	ExecuteAsDurationNeutral	Execute as duration neutral
t	ExecuteAsFXNeutral	Execute as FX neutral
u	MinGuaranteedFillEligible	Minimum guaranteed fill eligible
v	BypassNonDisplayLiquidity	Bypass non-displayed liquidity
w	Lock	Lock. Mutually exclusive with q.
x	IgnoreNotionalValueChecks	Ignore notional value checks
y	TrdAtRefPx	Trade at reference price. In the context of Reg NMS and the Tick Size Pilot Program, this is intended to indicate the order should Trade At Intermarket Sweep Order (TAISO) price.
z	AllowFacilitation	Allow facilitation. Express explicit consent to receive facilitation services from the counterparty. Facilitation services are when an institutional client allows a broker to assume a risk-taking principal position rather than an agency position, to obtain liquidity or achieve a guaranteed execution price on the client's behalf. Interpretation of absence of this value needs to be bilaterally agreed, if applicable. In the context of Hong Kong's SFC, this can be used to comply with SFC regulations for disclosure of client facilitation.

Used in components: [TradeReportOrderDetail](#)

Used in groups: [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#),

[NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.1065 ExecInstRules

Name	Mult.	Type	Description
<a href="#">NoExecInstRules</a>	[1..1]	NumInGroup	Number of execution instructions
<a href="#">ExecInstValue</a>	[0..1]	CodeSet	Indicates execution instructions that are valid for the specified market segment

Used in components: [TradingSessionRules](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

### 180.2.1066 ExecInstValue

Indicates execution instructions that are valid for the specified market segment

Type: [MultipleCharValue](#)

Allowed values in ExecInstCodeSet:

Code	Name	Description
0	StayOnOfferSide	Stay on offer side
1	NotHeld	Not held
2	Work	Work
3	GoAlong	Go along
4	OverTheDay	Over the day
5	Held	Held
6	ParticipateDoNotInitiate	Participate don't initiate
7	StrictScale	Strict scale
8	TryToScale	Try to scale
9	StayOnBidSide	Stay on bid side
A	NoCross	No cross. Cross is forbidden.
B	OKToCross	OK to cross
C	CallFirst	Call first

Code	Name	Description
D	PercentOfVolume	Percent of volume. Indicates that the sender does not want the order to be all of the volume on the floor vs. a specific percentage.
E	DoNotIncrease	Do not increase - DNI
F	DoNotReduce	Do not reduce - DNR
G	AllOrNone	All or none - AON
H	ReinstateOnSystemFailure	Reinstate on system failure. Mutually exclusive with Q and I (lower case L).
I	InstitutionsOnly	Institutions only
J	ReinstateOnTradingHalt	Reinstate on trading halt. Mutually exclusive with K and m.
K	CancelOnTradingHalt	Cancel on trading halt. Mutually exclusive with J and m.
L	LastPeg	Last peg (last sale)
M	MidPricePeg	Mid-price peg (midprice of inside quote)
N	NonNegotiable	Non-negotiable
O	OpeningPeg	Opening peg
P	MarketPeg	Market peg
Q	CancelOnSystemFailure	Cancel on system failure. Mutually exclusive with H and I (lower case L).
R	PrimaryPeg	Primary peg. Primary market - buy at bid, sell at offer.
S	Suspend	Suspend
T	FixedPegToLocalBestBidOrOfferAt-TimeOfOrder	Fixed peg to local best bid or offer at time of order
U	CustomerDisplayInstruction	Customer display instruction. Used in US Markets for: SEC Rule 11Ac1-1/4.
V	Netting	Netting (for Forex)
W	PegToVWAP	Peg to VWAP
X	TradeAlong	Trade along
Y	TryToStop	Try to stop
Z	CancelIfNotBest	Cancel if not best
a	TrailingStopPeg	Trailing stop peg
b	StrictLimit	Strict limit. No price improvement.
c	IgnorePriceValidityChecks	Ignore price validity checks
d	PegToLimitPrice	Peg to limit price
e	WorkToTargetStrategy	Work to target strategy
f	IntermarketSweep	Intermarket sweep
g	ExternalRoutingAllowed	External routing allowed

Code	Name	Description
h	ExternalRoutingNotAllowed	External routing not allowed
i	ImbalanceOnly	Imbalance only
j	SingleExecutionRequestedForBlock-Trade	Single execution requested for block trade
k	BestExecution	Best execution
l	SuspendOnSystemFailure	Suspend on system failure. Mutually exclusive with H and Q.
m	SuspendOnTradingHalt	Suspend on trading halt. Mutually exclusive with J and K.
n	ReinstateOnConnectionLoss	Reinstate on connection loss. Mutually exclusive with o and p.
o	CancelOnConnectionLoss	Cancel on connection loss. Mutually exclusive with n and p.
p	SuspendOnConnectionLoss	Suspend on connection loss. Mutually exclusive with n and o.
q	Release	Release. Mutually exclusive with S and w.
r	ExecuteAsDeltaNeutral	Execute as delta neutral using volatility provided
s	ExecuteAsDurationNeutral	Execute as duration neutral
t	ExecuteAsFXNeutral	Execute as FX neutral
u	MinGuaranteedFillEligible	Minimum guaranteed fill eligible
v	BypassNonDisplayLiquidity	Bypass non-displayed liquidity
w	Lock	Lock. Mutually exclusive with q.
x	IgnoreNotionalValueChecks	Ignore notional value checks
y	TrdAtRefPx	Trade at reference price. In the context of Reg NMS and the Tick Size Pilot Program, this is intended to indicate the order should Trade At Intermarket Sweep Order (TAISO) price.
z	AllowFacilitation	Allow facilitation. Express explicit consent to receive facilitation services from the counterparty. Facilitation services are when an institutional client allows a broker to assume a risk-taking principal position rather than an agency position, to obtain liquidity or achieve a guaranteed execution price on the client's behalf. Interpretation of absence of this value needs to be bilaterally agreed, if applicable. In the context of Hong Kong's SFC, this can be used to comply with SFC regulations for disclosure of client facilitation.

Used in groups: **ExecInstRules**

### 180.2.1067 ExecMethod

Specifies how the transaction was executed, e.g. via an automated execution platform or other method.

Type: **int**

Allowed values in ExecMethodCodeSet:

Code	Name	Description
0	Unspecified	Undefined/unspecified - (default when not specified). In the context of Market Model Typology (MMT), this value represents an off book non-automated transaction type.
1	Manual	Manual. The transaction was executed in a manual or other non-automated manner, e.g. by voice directly between the counterparties. Also used to identify MTT code M "Off Book Non-Automated".
2	Automated	Automated. The transaction was executed on an automated execution platform such as an automated systematic internaliser system, broker crossing network, broker crossing system, dark pool trading, "direct to capital" systems, broker position unwind mechanisms, etc.
3	VoiceBrokered	Voice brokered. The transaction was negotiated by voice through an intermediary.

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **TradeCaptureReport**

### **180.2.1068 ExecPriceAdjustment**

For CIV the amount or percentage by which the fund unit/share price was adjusted, as indicated by ExecPriceType (484)

Type: **float**

Used in messages: **ExecutionReport**

### **180.2.1069 ExecPriceType**

For CIV - Identifies how the execution price LastPx (31) was calculated from the fund unit/share price(s) calculated at the fund valuation point.

Type: **char**

Allowed values in ExecPriceTypeCodeSet:

Code	Name	Description
B	BidPrice	Bid price
C	CreationPrice	Creation price
D	CreationPricePlusAdjustmentPercent	Creation price plus adjustment percent
E	CreationPricePlusAdjustmentAmount	Creation price plus adjustment amount
O	OfferPrice	Offer price
P	OfferPriceMinusAdjustmentPercent	Offer price minus adjustment percent
Q	OfferPriceMinusAdjustmentAmount	Offer price minus adjustment amount
S	SinglePrice	Single price

Used in messages: **ExecutionReport**

#### 180.2.1070 ExecRefID

Reference identifier used with Trade, Trade Cancel and Trade Correct execution types.

(Prior to FIX 4.1 this field was of type int)

Type: **String**

Used in messages: **ExecutionReport**, **TradeCaptureReport**

#### 180.2.1071 ExecRestatementReason

The reason for restatement when an ExecutionReport(35=8) or TradeCaptureReport(35=AE) message is sent with ExecType(150) = D (Restated) or used when communicating an unsolicited cancel.

Type: **int**

Allowed values in ExecRestatementReasonCodeSet:

Code	Name	Description
0	GTCorporateAction	GT corporate action
1	GTRenewal	GT renewal / restatement (no corporate action)
2	VerbalChange	Verbal change
3	RepricingOfOrder	Repricing of order
4	BrokerOption	Broker option



Code	Name	Description
5	PartialDeclineOfOrderQty	Partial decline of OrderQty (e.g. exchange initiated partial cancel)
6	CancelOnTradingHalt	Cancel on Trading Halt
7	CancelOnSystemFailure	Cancel on System Failure
8	Market	Market (Exchange) option
9	Canceled	Canceled, not best
10	WarehouseRecap	Warehouse Recap
11	PegRefresh	Peg Refresh
12	CancelOnConnectionLoss	Cancel On Connection Loss
13	CancelOnLogout	Cancel On Logout
14	AssignTimePriority	Assign Time Priority
15	CancelledForTradePriceViolation	Cancelled, Trade Price Violation
16	CancelledForCrossImbalance	Cancelled, Cross Imbalance
17	CxldSMP	Cancelled, self-match prevention. Cancelled order based on standing rules for self-match prevention (i.e. SelfMatchPreventionInstruction(2964) not specified or used).
18	CxldSMPAggressive	Cancelled, self-match prevention aggressive order. Cancelled due to incoming order with the same SelfMatchPreventionID(2362) and SelfMatchPreventionInstruction(2964)=1 (Cancel aggressive).
19	CxldSMPPassive	Cancelled, self-match prevention passive order. Cancelled due to incoming order with the same SelfMatchPreventionID(2362) and SelfMatchPreventionInstruction(2964)=2 (Cancel passive).
20	CxldSMPAggressivePassive	Cancelled, self-match prevention aggressive and passive order. Cancelled due to incoming order with the same SelfMatchPreventionID(2362) and SelfMatchPreventionInstruction(2964)=3 (Cancel aggressive and passive).
99	Other	Other

Used in messages: **ExecutionReport**, **TradeCaptureReport**, **TradeCaptureReportAck**

### 180.2.1072 ExecType

Describes the specific ExecutionRpt (e.g. Pending Cancel) while OrdStatus(39) will always identify the current order status (e.g. Partially Filled).

Type: **char**

Allowed values in ExecTypeCodeSet:

Code	Name	Description
0	New	New
3	DoneForDay	Done for day
4	Canceled	Canceled
5	Replaced	Replaced
6	PendingCancel	Pending Cancel (e.g. result of Order Cancel Request)
7	Stopped	Stopped
8	Rejected	Rejected
9	Suspended	Suspended
A	PendingNew	Pending New
B	Calculated	Calculated
C	Expired	Expired
D	Restated	Restated (Execution Report sent unsolicited by sellside, with ExecRestatementReason (378) set)
E	PendingReplace	Pending Replace (e.g. result of Order Cancel/Replace Request)
F	Trade	Trade (partial fill or fill)
G	TradeCorrect	Trade Correct
H	TradeCancel	Trade Cancel
I	OrderStatus	Order Status
J	TradeInAClearingHold	Trade in a Clearing Hold
K	TradeHasBeenReleasedToClearing	Trade has been released to Clearing
L	TriggeredOrActivatedBySystem	Triggered or Activated by System
M	Locked	Locked
N	Released	Released

Used in groups: **OrderEntryAckGrp**

Used in messages: **ExecutionReport**, **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**

### **180.2.1073 ExecTypeReason**

The initiating event when an ExecutionReport(35=8) is sent.

Type: **int**

Allowed values in ExecTypeReasonCodeSet:

Code	Name	Description
1	OrdAddedOnRequest	Order added upon request
2	OrdReplacedOnRequest	Order replaced upon request
3	OrdCxlOnRequest	Order cancelled upon request
4	UnsolicitedOrdCxl	Unsolicited order cancellation
5	NonRestingOrdAddedOnRequest	Non-resting order added upon request
6	OrdReplacedWithNonRestingOrdOnRequest	Order replaced with non-resting order upon request
7	TriggerOrdReplacedOnRequest	Trigger order replaced upon request
8	SuspendedOrdReplacedOnRequest	Suspended order replaced upon request
9	SuspendedOrdCxlOnRequest	Suspended order canceled upon request
10	OrdCxlPending	Order cancellation pending
11	PendingCxlExecuted	Pending cancellation executed
12	RestingOrdTriggered	Resting order triggered
13	SuspendedOrdActivated	Suspended order activated
14	ActiveOrdSuspended	Active order suspended
15	OrdExpired	Order expired

Used in groups: **OrderEntryAckGrp**

Used in messages: **ExecutionReport**

### 180.2.1074 ExecutionAggregationGrp

Identifies the fills being aggregated together.

Name	Mult.	Type	Description
NoExecs	[1..1]	NumInGroup	
LastQty	[0..1]	Qty	Required if NoExecs(124) > 0
ExecID	[0..1]	String	Either ExecID(17) or TradeID(1003) must be specified.
TradeID	[0..1]	String	Either ExecID(17) or TradeID(1003) must be specified.

Name	Mult.	Type	Description
LastPx	[0..1]	Price	

Used in messages: [TradeAggregationRequest](#)

#### 180.2.1075 ExecutionTimestamp

Time of the individual execution.

Type: [UTCTimestamp](#)

Used in groups: [ExecAllocGrp](#)

#### 180.2.1076 ExecValuationPoint

For CIV - a date and time stamp to indicate the fund valuation point with respect to which a order was priced by the fund manager.

Type: [UTCTimestamp](#)

Used in messages: [ExecutionReport](#)

#### 180.2.1077 ExerciseConfirmationMethod

Indicates whether follow-up confirmation of exercise (written or electronic) is required following telephonic notice by the buyer to the seller or seller's agent.

Type: [int](#)

Allowed values in ExerciseConfirmationMethodCodeSet:

Code	Name	Description
0	NotRequired	Not required
1	NonElectronic	Non-electronic
2	Electronic	Electronic
3	Unknown	Unknown at time of report

Used in components: [OptionExercise](#)

**180.2.1078 ExerciseDesc**

A description of the option exercise.

Type: **String**

Used in components: **OptionExercise**

**180.2.1079 ExerciseMethod**

Exercise Method used to in performing assignment.

Type: **char**

Allowed values in ExerciseMethodCodeSet:

Code	Name	Description
A	Automatic	Automatic
M	Manual	Manual

Used in messages: **AssignmentReport**

**180.2.1080 ExerciseSplitTicketIndicator**

Indicates in physical settlement of bond and convertible bond options whether the party required to deliver the bonds will divide those to be delivered as notifying party desires to facilitate delivery obligations.

Type: **Boolean**

Used in components: **OptionExercise**

**180.2.1081 ExerciseStyle**

Type of exercise of a derivatives security

Type: **int**

Allowed values in ExerciseStyleCodeSet:

Code	Name	Description
0	European	European
1	American	American
2	Bermuda	Bermuda
99	Other	Other

Used in components: **Instrument**

### 180.2.1082 ExpirationCycle

Part of trading cycle when an instrument expires. Field is applicable for derivatives.

Type: **int**

Allowed values in ExpirationCycleCodeSet:

Code	Name	Description
0	ExpireOnTradingSessionClose	Expire on trading session close (default)
1	ExpireOnTradingSessionOpen	Expire on trading session open
2	SpecifiedExpiration	Trading eligibility expiration specified in the date and time fields [EventDate(866) and EventTime(1145)] associated with EventType(865)=7(Last Eligible Trade Date)

Used in components: **BaseTradingRules**

Used in messages: **SecurityDefinitionRequest**

### 180.2.1083 ExpirationQty

The ExpirationQty component block identified the expiration quantities and type of expiration.

Name	Mult.	Type	Description
NoExpiration	[1..1]	NumInGroup	
ExpirationQtyType	[0..1]	CodeSet	Required if NoExpiration > 1
ExpQty	[0..1]	Qty	

Used in messages: **ContraryIntentionReport**

**180.2.1084 ExpirationQtyType**

Expiration Quantity type

Type: **int**

Allowed values in ExpirationQtyTypeCodeSet:

Code	Name	Description
1	AutoExercise	Auto Exercise
2	NonAutoExercise	Non Auto Exercise
3	FinalWillBeExercised	Final Will Be Exercised
4	ContraryIntention	Contrary Intention
5	Difference	Difference

Used in groups: **ExpirationQty**

**180.2.1085 ExpireDate**

Date of order expiration (last day the order can trade), always expressed in terms of the local market date. The time at which the order expires is determined by the local market's business practices

Type: **LocalMktDate**

Used in groups: **ListOrdGrp**, **MDFullGrp**, **MDIncGrp**

Used in messages: **AssignmentReport**, **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **Multi-legOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.1086 ExpireTime**

Time/Date of order expiration (always expressed in UTC (Universal Time Coordinated, also known as "GMT"))

The meaning of expiration is specific to the context where the field is used.

For orders, this is the expiration time of a Good Til Date TimeInForce.

For Quotes - this is the expiration of the quote.

Expiration time is provided across the quote message dialog to control the length of time of the overall quoting process.

For collateral requests, this is the time by which collateral must be assigned.

For collateral assignments, this is the time by which a response to the assignment is expected.

For credit/risk limit checks, this is the time when the reserved credit limit will expire for the requested transaction.

Type: **UTCTimestamp**

Used in components: **TradeReportOrderDetail**

Used in groups: **ListOrdGrp, MDFullGrp, MDIncGrp, QuotReqGrp, QuotReqRjctGrp, SettlInstGrp, SettlementObligationInstructions**

Used in messages: **CollateralAssignment, CollateralRequest, CrossOrderCancelReplaceRequest, ExecutionReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, PartyRiskLimitCheckRequestAck, QuoteStatusReport, SettlementInstructionRequest**

#### **180.2.1087 ExposureDuration**

This is the time in seconds of a "Good for Time" (GFT) TimeInForce.

Positive integer value which represents the time in seconds in which the new order remains active in the market before it is automatically cancelled (e.g. expired).

Bi-lateral agreements will dictate the maximum value of this field. It is assumed that most systems will impose a max limit of 86,400 seconds (i.e. 24 hours).

For Quotes: The period of time a quoted price is tradable (i.e. on-the-wire) before it becomes indicative (i.e. off-the-wire).

Type: **int**

Used in components: **MDStatisticParameters, TradeReportOrderDetail**

Used in groups: **ListOrdGrp, MDFullGrp, MDIncGrp, QuotReqGrp**

Used in messages: **CrossOrderCancelReplaceRequest, ExecutionReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, Quote**

#### **180.2.1088 ExposureDurationUnit**

Time unit in which the ExposureDuration(1629) is expressed.

Type: **int**



Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in components: [MDStatisticParameters](#), [TradeReportOrderDetail](#)

Used in groups: [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#), [QuotReqGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [Quote](#)

### **180.2.1089 ExpQty**

Expiration Quantity associated with the Expiration Type

Type: [Qty](#)

Used in groups: [ExpirationQty](#)

### **180.2.1090 ExtraordinaryDividendAmountType**

Indicates how the extraordinary gross cash dividend per share is determined.

Type: [int](#)

Allowed values in DividendAmountTypeCodeSet:

Code	Name	Description
0	RecordAmount	Record amount. 100% of the gross cash dividend per share paid over record date during relevant dividend period.
1	ExAmount	Ex amount. 100% of gross cash dividend per share paid after the ex-dividend date during relevant dividend period.
2	PaidAmount	Paid amount. 100% of gross cash dividend per share paid during relevant dividend period.
3	PerMasterConfirm	As specified in master confirmation. The amount is determined as provided in the relevant master confirmation.

Used in components: **DividendConditions**

#### **180.2.1091 ExtraordinaryDividendCurrency**

The currency in which the excess dividend is denominated. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **DividendConditions**

#### **180.2.1092 ExtraordinaryDividendDeterminationMethod**

Specifies the method in which the excess amount is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in components: **DividendConditions**

#### **180.2.1093 ExtraordinaryDividendPartySide**

Reference to the party through its side in the trade who makes the determination whether dividends are extraordinary in relation to normal levels.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [DividendConditions](#)

### 180.2.1094 ExtraordinaryEventAdjustmentMethod

Defines how adjustments will be made to the contract should one or more of the extraordinary events occur.

Type: [int](#)

Allowed values in ExtraordinaryEventAdjustmentMethodCodeSet:

Code	Name	Description
0	CalculationAgent	Calculation agent. The Calculation Agent has the right to adjust the terms of the trade following a corporate action.
1	OptionsExchange	Options exchange. The trade will be adjusted in accordance with any adjustment made by the exchange on which options on the underlying are listed.

Used in components: [Instrument](#)

### 180.2.1095 ExtraordinaryEventGrp

The ExtraordinaryEventGrp is a repeating component within the Instrument component. It is used to report extraordinary and disruptive events applicable to the reference entity that affects the contract.

Name	Mult.	Type	Description
<a href="#">NoExtraordinaryEvents</a>	[1..1]	NumInGroup	
<a href="#">ExtraordinaryEventType</a>	[0..1]	String	Required if NoExtraordinaryEvents(42296) > 0.
<a href="#">ExtraordinaryEventValue</a>	[0..1]	String	Required if NoExtraordinaryEvents(42296) > 0.

Used in components: [Instrument](#)

**180.2.1096 ExtraordinaryEventType**

Identifies the type of extraordinary or disruptive event applicable to the reference entity.

See [http://www.fixtradingcommunity.org/codelists#Extraordinary\\_Event\\_Type](http://www.fixtradingcommunity.org/codelists#Extraordinary_Event_Type) for code list of extraordinary event types and values.

Type: **String**

Used in groups: **ExtraordinaryEventGrp**

**180.2.1097 ExtraordinaryEventValue**

The extraordinary or disruptive event value appropriate to ExtraordinaryEventType(42297).

See [http://www.fixtradingcommunity.org/codelists#Extraordinary\\_Event\\_Type](http://www.fixtradingcommunity.org/codelists#Extraordinary_Event_Type) for code list of extraordinary event types and values.

Type: **String**

Used in groups: **ExtraordinaryEventGrp**

**180.2.1098 Factor**

For Fixed Income: Amorization Factor for deriving Current face from Original face for ABS or MBS securities, note the fraction may be greater than, equal to or less than . In TIPS securities this is the Inflation index.

$\text{Qty} * \text{Factor} * \text{Price} = \text{Gross Trade Amount}$

For Derivatives: Contract Value Factor by which price must be adjusted to determine the true nominal value of one futures/options contract.

$(\text{Qty} * \text{Price}) * \text{Factor} = \text{Nominal Value}$

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **float**

Used in components: **Instrument**

**180.2.1099 FairValue**

Used in EFP trades

Type: **Amt**

Used in groups: [BidCompRspGrp](#), [BidDescReqGrp](#)

#### **180.2.1100 FallbackExerciseIndicator**

Indicates whether the notional amount of the underlying swap, not previously exercised under the option, will be automatically exercised at the expiration time on the expiration date if at such time the buyer is in-the-money, provided that the difference between the settlement rate and the fixed rate under the relevant underlying swap is not less than one tenth of a percentage point (0.10% or 0.001).

Type: [Boolean](#)

Used in components: [OptionExercise](#)

#### **180.2.1101 FastMarketIndicator**

Indicates if the instrument is in "fast market" state.

Type: [Boolean](#)

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [QuoteSizeRuleGrp](#)

Used in messages: [MarketDataRequest](#), [SecurityMassStatus](#), [SecurityStatus](#), [TradingSessionStatus](#)

#### **180.2.1102 FastMarketPercentage**

The percentage factor to be applied to trading rule parameters (e.g. price ranges, size ranges, etc.) when fast market conditions are applicable.

Type: [Percentage](#)

Used in components: [BaseTradingRules](#)

#### **180.2.1103 FeeMultiplier**

This is a multiplier that Clearing (Fee system) will use to calculate fees and will be sent to the firms on their confirms.

Type: [float](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

**180.2.1104 FillExecID**

Refer to ExecID(17). Used when multiple partial fills are reported in single Execution Report. ExecID and FillExecID should not overlap,

Type: **String**

Used in groups: **FillsGrp**

**180.2.1105 FillLiquidityInd**

Indicator to identify whether this fill was a result of a liquidity provider providing or liquidity taker taking the liquidity. Applicable only for OrdStatus of Partial or Filled

Type: **int**

Allowed values in LastLiquidityIndCodeSet:

Code	Name	Description
0	NeitherAddedNorRemovedLiquidity	Neither added nor removed liquidity. May be used by venues where market rules do not define "add" or "remove" liquidity. In the context of the SEC amendment of Regulation NMS Rule 606(b), may be used to identify executions that are only reported as part of total shares executed and not as part of shares providing or removing liquidity (see <a href="https://www.sec.gov/rules/final/2018/34-84528.pdf">https://www.sec.gov/rules/final/2018/34-84528.pdf</a> for details).
1	AddedLiquidity	Added Liquidity
2	RemovedLiquidity	Removed Liquidity
3	LiquidityRoutedOut	Liquidity Routed Out
4	Auction	Auction execution
5	TriggeredStopOrder	Triggered stop order. Fill was the result of a stop order being triggered and immediately executed.
6	TriggeredContingencyOrder	Triggered contingency order. Fill was the result of a contingency order (OCO, OTO, OUO) becoming active (after cancelling or updating another order) and being immediately executed.
7	TriggeredMarketOrder	Triggered market order. Fill was the result of a market order being triggered due to an executable orderbook situation.
8	RemovedLiquidityAfterFirmOrder-Commitment	Removed liquidity after firm order commitment. An order that was submitted for continuous trading that required a firm order commit prior to execution. "Conditional order" is an alternate term used for such orders.

Code	Name	Description
9	AuctionExecutionAfterFirmOrder-Commitment	Auction execution after firm order commitment. An order that was submitted for auction trading that required a firm order commit prior to execution. "Conditional order" is an alternate term used for such orders.
10	Unknown	Unknown. The liquidity indicator of the execution cannot be determined or was not provided upon execution.
11	Other	Other. None of the existing liquidity indicators are applicable for the execution (e.g. due to a venue's new order type that does not fit existing values).

Used in groups: **FillsGrp**

#### **180.2.1106 FillMatchID**

Identifier assigned by a matching system to a match event containing multiple executions.

Type: **String**

Used in groups: **FillsGrp**

#### **180.2.1107 FillMatchSubID**

Identifier assigned by a matching system to a price level (e.g. match step, clip) within a match event containing multiple executions.

Type: **String**

Used in groups: **FillsGrp**

#### **180.2.1108 FillPx**

Price of Fill. Refer to LastPx(31).

Type: **Price**

Used in groups: **FillsGrp**

**180.2.1109 FillQty**

Quantity of Fill. Refer to LastQty(32).

Type: Qty

Used in groups: FillsGrp

**180.2.1110 FillRefID**

A reference to either the value of the FillExecID(1363) or an implicit position of a fills instance in the FillsGrp component.

Type: String

Used in groups: InstrmtLegExecGrp

**180.2.1111 FillsGrp**

Name	Mult.	Type	Description
NoFills	[1..1]	NumInGroup	Specifies the number of partial fills included in this Execution Report
FillExecID	[0..1]	String	Unique identifier of execution as assigned by sell-side (broker, exchange, ECN). Must not overlap ExecID(17). Required if NoFills(1362) > 0.
FillPx	[0..1]	Price	Price of this partial fill. Required if NoFills(1362) > 0. Refer to LastPx(31).
FillQty	[0..1]	Qty	Quantity (e.g. shares) bought/sold on this partial fill. Required if NoFills(1362) > 0.
FillMatchID	[0..1]	String	Can be used to refer to the related match event.
FillMatchSubID	[0..1]	String	Can be used to refer to a price level (e.g. match step, clip) within the related match event.
FillLiquidityInd	[0..1]	CodeSet	
FillYieldType	[0..1]	String	
FillYield	[0..1]	Percentage	
NestedParties4	[0..*]	Group	Counterparty information

Used in messages: ExecutionReport



**180.2.1112 FillYield**

Yield Percentage, using same values as Yield (236)

Type: **Percentage**

Used in groups: **FillsGrp**

**180.2.1113 FillYieldType**

Yield Type, using same values as YieldType (235)

Type: **String**

Used in groups: **FillsGrp**

**180.2.1114 FinancialInstrumentFullName**

The full normative name of the financial instrument.

Type: **String**

Used in components: **Instrument**

**180.2.1115 FinancialInstrumentShortName**

Short name of the financial instrument. Uses ISO 18774 (FINS) values.

Type: **String**

Used in components: **Instrument**

**180.2.1116 FinancialStatus**

Identifies a firm's or a security's financial status

Type: **MultipleCharValue**

Allowed values in FinancialStatusCodeSet:

---

Code	Name	Description
1	Bankrupt	Bankrupt
2	PendingDelisting	Pending delisting

---

Code	Name	Description
3	Restricted	Restricted

Used in groups: [MDIncGrp](#), [SecMassStatGrp](#)

Used in messages: [CollateralReport](#), [CollateralResponse](#), [MarketDataSnapshotFullRefresh](#), [SecurityStatus](#)

### 180.2.1117 FinancingContractualDefinitionGrp

The FinancingContractualDefinitionGrp is a repeating component within the FinancingDetails component used to report the definitions published by ISDA that define the terms of a derivative trade.

Name	Mult.	Type	Description
<a href="#">NoContractualDefinitions</a>	[1..1]	NumInGroup	
<a href="#">ContractualDefinition</a>	[0..1]	String	Required if NoContractualDefinitions(40040) > 0.

Used in components: [FinancingDetails](#)

### 180.2.1118 FinancingContractualMatrixGrp

The FinancingContractualMatrixGrp is a repeating component within the FinancingDetails component used to report the ISDA Physical Settlement Matrix Transaction Type.

Name	Mult.	Type	Description
<a href="#">NoContractualMatrices</a>	[1..1]	NumInGroup	
<a href="#">ContractualMatrixSource</a>	[0..1]	String	Required if NoContractualMatrices(40042) > 0.
<a href="#">ContractualMatrixDate</a>	[0..1]	LocalMktDate	
<a href="#">ContractualMatrixTerm</a>	[0..1]	String	

Used in components: [FinancingDetails](#)

### 180.2.1119 FinancingDetails

Component block is optionally used for financial transaction where legal contracts, master agreements or master confirmations is to be referenced. This component identifies the legal agreement under which the deal was made and other unique characteristics of the transaction. For example, the AgreementDesc(913) field refers to base standard documents such as MRA 1996 Repurchase Agreement, GMRA 2000 Bills Transaction (U.K.), MSLA 1993 Securities Loan – Amended 1998, for example.

Name	Mult.	Type	Description
AgreementDesc	[0..1]	String	The full name of the base standard agreement, annexes and amendments in place between the principals and applicable to this deal
AgreementID	[0..1]	String	A common reference to the applicable standing agreement between the principals
AgreementVersion	[0..1]	String	
AgreementDate	[0..1]	LocalMktDate	A reference to the date the underlying agreement was executed.
AgreementCurrency	[0..1]	Currency	Currency of the underlying agreement.
AgreementCurrencyCodeSource	[0..1]	CodeSet	
MasterConfirmationDesc	[0..1]	String	
MasterConfirmationDate	[0..1]	LocalMktDate	
MasterConfirmationAnnexDesc	[0..1]	String	
MasterConfirmationAnnexDate	[0..1]	LocalMktDate	
BrokerConfirmationDesc	[0..1]	String	
FinancingContractualDefinitionGrp	[0..*]	Group	
FinancingTermSupplementGrp	[0..*]	Group	
FinancingContractualMatrixGrp	[0..*]	Group	
CreditSupportAgreementDesc	[0..1]	String	
CreditSupportAgreementDate	[0..1]	LocalMktDate	
CreditSupportAgreementID	[0..1]	String	
GoverningLaw	[0..1]	String	
DocumentationText	[0..1]	String	
EncodedDocumentationTextLen	[0..1]	Length	Must be set if EncodedDocumentationText(1527) field is specified and must immediately precede it.
EncodedDocumentationText	[0..1]	data	Encoded (non-ASCII characters) representation of the DocumentationText(1513) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
TerminationType	[0..1]	CodeSet	For Repos the timing or method for terminating the agreement.
StartDate	[0..1]	LocalMktDate	Settlement date of the beginning of the deal
EndDate	[0..1]	LocalMktDate	Repayment / repurchase date
DeliveryType	[0..1]	CodeSet	Delivery or custody arrangement for the underlying securities
MarginRatio	[0..1]	Percentage	Percentage of cash value that underlying security collateral must meet.

Used in groups: InstrmtGrp, InstrmtMDReqGrp, MDIncGrp, QuotCxlEntriesGrp, QuotReqGrp, QuotReqRjctGrp, SecListGrp, SecLstUpdRelSymGrp, SecMassStatGrp

Used in messages: Advertisement, AllocationInstruction, AllocationInstructionAlert, AllocationReport, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralRequest, CollateralResponse, Confirmation, ExecutionReport, IOI, MarketDataSnapshotFullRefresh, MarketDataStatisticsReport, MarketDataStatisticsRequest, NewOrderSingle, OrderCancelReplaceRequest, OrderCancelRequest, OrderStatusRequest, PositionReport, Quote, QuoteResponse, QuoteStatusReport, QuoteStatusRequest, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityListRequest, SecurityStatus, SecurityStatusRequest, TradeCaptureReport, TradeCaptureReportAck, TradeCaptureReportRequest

#### 180.2.1120 FinancingTermSupplementDate

The publication date of the applicable version of the contractual supplement.

Type: LocalMktDate

Used in groups: FinancingTermSupplementGrp

#### 180.2.1121 FinancingTermSupplementDesc

Identifies the applicable contractual supplement. See <http://www.fpml.org/coding-scheme/contractual-supplement> for values.

Type: String

Used in groups: FinancingTermSupplementGrp

**180.2.1122 FinancingTermSupplementGrp**

The FinancingTermSupplementGrp is a repeating component within the FinancingDetails component used to report contractual terms supplements of derivative trades.

Name	Mult.	Type	Description
NoFinancingTermSupplements	[1..1]	NumInGroup	
FinancingTermSupplementDesc	[0..1]	String	Required if NoFinancingTermSupplements(40046) > 0.
FinancingTermSupplementDate	[0..1]	LocalMktDate	

Used in components: [FinancingDetails](#)

**180.2.1123 FirmAllocText**

Firm reference information, usually internal information, that is part of the initial message. The information would not be carried forward (e.g to Take-up Firm) and preserved with the transaction.

Type: [String](#)

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [TrdAllocGrp](#)

**180.2.1124 FirmGroupID**

Firm assigned group allocation entity identifier.

Type: [String](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAck](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#)

**180.2.1125 FirmMnemonic**

Allocation identifier assigned by the Firm submitting the allocation for an individual allocation instruction (as opposed to the overall message level identifier).

Type: [String](#)

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [TrdAllocGrp](#)

**180.2.1126 FirmTradeEventID**

An identifier created by the trading party for the life cycle event associated with this report.

Type: **String**

Used in groups: **TrdCapRptSideGrp**

**180.2.1127 FirmTradeID**

The ID assigned to a trade by the Firm to track a trade within the Firm system. This ID can be assigned either before or after submission to the exchange or central counterparty

Type: **String**

Used in groups: **ExecAllocGrp**

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**, **TradeCaptureReportRequestAck**

**180.2.1128 FirmTransactionID**

The unique transaction entity identifier assigned by the firm.

Type: **String**

Used in messages: **CollateralAssignment**, **CollateralReport**, **CollateralResponse**

**180.2.1129 FirstPx**

Indicates the first trade price of the day/session

Type: **Price**

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **SecurityStatus**

**180.2.1130 FlexibleIndicator**

Used to indicate a derivatives security that can be defined using flexible terms. The terms commonly permitted to be defined by market participants are expiration date and strike price. FlexibleIndicator is an alternative CFICode(461) Standard/Non-standard attribute.

Type: **Boolean**

Used in components: **Instrument**

### **180.2.1131 FlexProductEligibilityComplex**

Identifies an entire suite of products which are eligible for the creation of flexible securities.

Type: **String**

Used in groups: **FlexProductEligibilityGrp**

### **180.2.1132 FlexProductEligibilityGrp**

The FlexProductEligibilityGrp component is used to specify whether securities within a product group or complex are eligible for creating flexible securities.

Name	Mult.	Type	Description
NoFlexProductEligibilities	[1..1]	NumInGroup	
FlexProductEligibilityIndicator	[0..1]	Boolean	Required if NoFlexProductEligibilities(2560) > 0.
FlexProductEligibilityComplex	[0..1]	String	Required if NoFlexProductEligibilities(2560) > 0. Used to specify a product suite related to an eligibility indicator.

Used in messages: **MarketDefinition**, **MarketDefinitionUpdateReport**

### **180.2.1133 FlexProductEligibilityIndicator**

Used to indicate if a product or group of product supports the creation of flexible securities

Type: **Boolean**

Used in components: **Instrument**

Used in groups: **FlexProductEligibilityGrp**

### **180.2.1134 FloatingRateIndex**

Used to identify the rate index for a floating rate coupon.

Name	Mult.	Type	Description
FloatingRateIndexID	[0..1]	String	Conditionally required when FloatingRateIndexIDSource(2732) is specified.
FloatingRateIndexIDSource	[0..1]	CodeSet	Conditionally required when FloatingRateIndexID(2731) is specified.
FloatingRateIndexCurveUnit	[0..1]	CodeSet	Conditionally required when FloatingRateIndexCurvePeriod(2728) is specified.
FloatingRateIndexCurvePeriod	[0..1]	int	Conditionally required when FloatingRateIndexCurveUnit(2730) is specified.
FloatingRateIndexCurveSpread	[0..1]	PriceOffset	

Used in components: **InstrumentExtension**

#### 180.2.1135 FloatingRateIndexCurvePeriod

Time unit multiplier for the floating rate index identified in FloatingRateIndexID(2731).

Type: **int**

Used in components: **FloatingRateIndex**

#### 180.2.1136 FloatingRateIndexCurveSpread

Spread from the floating rate index.

Type: **PriceOffset**

Used in components: **FloatingRateIndex**

#### 180.2.1137 FloatingRateIndexCurveUnit

Time unit associated with the floating rate index identified in FloatingRateIndexID(2731).

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day



Code	Name	Description
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [FloatingRateIndex](#)

### 180.2.1138 FloatingRateIndexID

Security identifier of the floating rate index.

Type: [String](#)

Used in components: [FloatingRateIndex](#)

### 180.2.1139 FloatingRateIndexIDSource

Source for the floating rate index identified in FloatingRateIndexID(2731).

Type: [String](#)

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch

Code	Name	Description
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **FloatingRateIndex**

### 180.2.1140 FloorPrice

Used to express the floor price of a capped put

Type: **Price**

Used in components: **Instrument**

**180.2.1141 FlowScheduleType**

The industry standard flow schedule by which electricity or natural gas is traded. Schedules may exist by regions and on-peak and off-peak status, such as "Western Peak".

Type: **int**

Allowed values in FlowScheduleTypeCodeSet:

Code	Name	Description
0	NERCEasternOffPeak	NERC Eastern Off-Peak
1	NERCWesternOffPeak	NERC Western Off-Peak
2	NERCCalendarAllDaysInMonth	NERC Calendar-All Days in month
3	NERCEasternPeak	NERC Eastern Peak
4	NERCWesternPeak	NERC Western Peak
5	AllTimes	All times
6	OnPeak	On peak
7	OffPeak	Off peak
8	Base	Base
9	Block	Block
99	Other	Other

Used in components: **Instrument**

**180.2.1142 ForexReq**

Indicates request for forex accommodation trade to be executed along with security transaction.

Type: **Boolean**

Allowed values in ForexReqCodeSet:

Code	Name	Description
N	DoNotExecuteForexAfterSecurity-Trade	Do Not Execute Forex After Security Trade
Y	ExecuteForexAfterSecurityTrade	Execute Forex After Security Trade

Used in groups: **ListOrdGrp**, **SideCrossOrdModGrp**

Used in messages: [BidRequest](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.1143 FundingSource

Specifies the funding source used to finance margin or collateralized loan.

Type: [int](#)

Allowed values in FundingSourceCodeSet:

Code	Name	Description
0	Repo	Repurchase agreement. Repurchase agreements or Buy Sellbacks. In the context of EU SFTR reporting this corresponds to code "REPO".
1	Cash	Cash. Cash collateral from securities lending. In the context of EU SFTR reporting this corresponds to code "SECL".
2	FreeCredits	Free credits. In the context of EU SFTR reporting this corresponds to code "FREE".
3	CustomerShortSales	Customer short sales. Proceeds from customer short sales. In the context of EU SFTR reporting this corresponds to code "CSHS".
4	BrokerShortSales	Broker short sales. Proceeds from broker short sales. In the context of EU SFTR reporting this corresponds to code "BSHS".
5	UnsecuredBorrowing	Unsecured borrowing. In the context of EU SFTR reporting this corresponds to code "UBOR".
99	Other	Other. In the context of EU SFTR reporting this corresponds to code "OTHR".

Used in groups: [FundingSourceGrp](#)

### 180.2.1144 FundingSourceCurrency

Currency denomination of the market value of the funding source.

FundingSourceCurrencyCodeSource(2954) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: [Currency](#)

Used in groups: [FundingSourceGrp](#)

**180.2.1145 FundingSourceCurrencyCodeSource**

Identifies class or source of the FundingSourceCurrency(2847) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **FundingSourceGrp**

**180.2.1146 FundingSourceGrp**

This component is used to specify the funding source(s) used to finance a margin loan or collateralized loan.

Name	Mult.	Type	Description
NoFundingSources	[1..1]	NumInGroup	
FundingSource	[0..1]	CodeSet	Required if NoFundingSources(2849) > 0.
FundingSourceMarketValue	[0..1]	Amt	
FundingSourceCurrency	[0..1]	Currency	
FundingSourceCurrencyCodeSource	[0..1]	CodeSet	

Used in messages: **CollateralReport**

**180.2.1147 FundingSourceMarketValue**

Market value of the funding source.

Type: **Amt**

Used in groups: **FundingSourceGrp**

#### **180.2.1148 FundRenewWaiv**

A one character code identifying whether the Fund based renewal commission is to be waived.

Type: **char**

Allowed values in FundRenewWaivCodeSet:

Code	Name	Description
N	No	No
Y	Yes	Yes

Used in components: **CommissionData**

#### **180.2.1149 FXBenchmark**

The source of where to obtain the FX benchmark rate to use for fixing the rate.

Type: **int**

Allowed values in FXBenchmarkCodeSet:

Code	Name	Description
1	Bloomberg	Bloomberg. Also referred to as BFIX.
2	CentralBank	Central Bank
3	WMR	WMR
4	MitsubishiUFJ	Mitsubishi-UFJ. Also referred to as the Tokyo Fix.
5	LondonBullionMarketAssociation	London Bullion Market Association. Gold and Silver fixes are LBMA rates generated by ICE; Platinum and palladium fixes are LBMA rates generated by LME.
6	LondonMetalExchange	London Metal Exchange. Base metal prices come from the LME. LBMA should be used for platinum and palladium even though these are LME rates.
99	Other	Other. An appropriate reference page, ReferencePage(1448), at the specified RateSource(1446) needs to be specified.

Used in groups: **RateSource**

**180.2.1150 FXBenchmarkBusinessCenter**

A business center whose calendar is used for date/time adjustment. See <https://www.fpml.org/coding-scheme/business-center> to download the current (ISDA/FpML) standard 4-character code values for business center identification.

Type: **String**

Used in groups: **RateSource**

**180.2.1151 FXBenchmarkDate**

The local date of the FX rate fixing. The time applicable on the fixing date is specified in FXBenchmarkTime(3075).

Type: **LocalMktDate**

Used in groups: **RateSource**

**180.2.1152 FXBenchmarkRateFix**

Specifies the foreign exchange benchmark rate fixing to be used in valuing the transaction. For example "London 4 p.m." or "Tokyo 3 p.m."

Type: **String**

Used in groups: **RateSource**

**180.2.1153 FXBenchmarkTime**

The local time of the FX rate fixing. The date applicable for the fixing time is specified in FXBenchmarkDate(3074).

Type: **LocalMktTime**

Used in groups: **RateSource**

**180.2.1154 Gamma**

The rate of change of Delta over time.

Type: **float**

Used in groups: **SecurityRiskMetricGrp**

**180.2.1155 GapFillFlag**

Indicates that the Sequence Reset message is replacing administrative or application messages which will not be resent.

Type: **Boolean**

Allowed values in GapFillFlagCodeSet:

Code	Name	Description
N	SequenceReset	Sequence Reset, Ignore Msg Seq Num (N/A For FIXML - Not Used)
Y	GapFillMessage	Gap Fill Message, Msg Seq Num Field Valid

Used in messages: **SequenceReset**

**180.2.1156 GoverningLaw**

Identification of the law governing the transaction. See <http://www.fpml.org/coding-scheme/governing-law> for values.

Type: **String**

Used in components: **FinancingDetails**

**180.2.1157 GrossTradeAmt**

Total amount traded expressed in units of currency - usually quantity \* price. For FX Futures this is used to express the notional value of a fill when quantity fields are expressed in terms of contract size (i.e. quantity \* price \* contract size).

Type: **Amt**

Used in components: **SettlTradeDetails**

Used in messages: **AllocationInstruction, AllocationInstructionAlert, AllocationReport, Confirmation, ExecutionReport, TradeCaptureReport, TradeCaptureReportAck**

**180.2.1158 GroupAmount**

Indicates the total notional units or amount of an allocation group. Includes any allocated units or amount.



Type: **Amt**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstructionAlert**, **AllocationReport**

#### **180.2.1159 GroupRemainingAmount**

Indicates the remaining notional units or amount of an allocation group that has not yet been allocated.

Type: **Amt**

Used in messages: **AllocationInstructionAlert**

#### **180.2.1160 GTBookingInst**

Code to identify whether to book out executions on a part-filled GT order on the day of execution or to accumulate.

Type: **int**

Allowed values in GTBookingInstCodeSet:

Code	Name	Description
0	BookOutAllTradesOnDayOfExecution	Book out all trades on day of execution
1	AccumulateUntilFilledOrExpired	Accumulate executions until order is filled or expires
2	AccumulateUntilVerballyNotifiedOtherwise	Accumulate until verbally notified otherwise

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

#### **180.2.1161 HaircutIndicator**

Indicates, if "Y", that a stated valuation includes a haircut, e.g. that the stated value reflects the subtraction of the haircut. Note that a value of "N" does not imply a haircut is not applicable, only that the haircut (if any) is not reflected in the stated valuation.

Type: **Boolean**

Used in groups: [CollateralAmountGrp](#)

### 180.2.1162 HaltReason

Denotes the reason for the Opening Delay or Trading Halt.

Type: [int](#)

Allowed values in HaltReasonCodeSet:

Code	Name	Description
0	NewsDissemination	News Dissemination
1	OrderInflux	Order Influx
2	OrderImbalance	Order Imbalance
3	AdditionalInformation	Additional Information
4	NewsPending	News Pending
5	EquipmentChangeover	Equipment Changeover

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [SecMassStatGrp](#)

Used in messages: [SecurityStatus](#)

### 180.2.1163 HandlInst

Instructions for order handling on Broker trading floor

Type: [char](#)

Allowed values in HandlInstCodeSet:

Code	Name	Description
1	AutomatedExecutionNoIntervention	Automated execution order, private, no Broker intervention
2	AutomatedExecutionInterventionOK	Automated execution order, public, Broker intervention OK
3	ManualOrder	Manual order, best execution

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

**180.2.1164 Headline**

The headline of a News message

Type: **String**

Used in messages: **News**

**180.2.1165 HeartBtInt**

Heartbeat interval (seconds)

Type: **int**

Used in messages: **Logon**

**180.2.1166 HighLimitPrice**

Allowable high limit price for the trading day. A key parameter in validating order price. Used as the upper band for validating order prices. Orders submitted with prices above the upper limit will be rejected

Type: **Price**

Used in components: **PriceLimits**

**180.2.1167 HighPx**

Represents an indication of the high end of the price range for a security prior to the open or reopen

Type: **Price**

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **AllocationInstructionAlert**, **SecurityStatus**

**180.2.1168 HistoricalReportIndicator**

Indicates that the trade or event being reported occurred in the past and the trade is terminated or no longer active.

Type: **Boolean**

Used in messages: **TradeCaptureReport**

**180.2.1169 HopCompID**

Assigned value used to identify the third party firm which delivered a specific message either from the firm which originated the message or from another third party (if multiple "hops" are performed). It is recommended that this value be the SenderCompID (49) of the third party.

Applicable when messages are communicated/re-distributed via third parties which function as service bureaus or "hubs". Only applicable if OnBehalfOfCompID (115) is being used.

Type: **String**

Used in groups: **HopGrp**

**180.2.1170 HopGrp**

Name	Mult.	Type	Description
NoHops	[1..1]	NumInGroup	
HopCompID	[0..1]	String	
HopSendingTime	[0..1]	UTCTimestamp	
HopRefID	[0..1]	SeqNum	

Used in components: **StandardHeader**

**180.2.1171 HopRefID**

Reference identifier assigned by HopCompID (628) associated with the message sent. It is recommended that this value be the MsgSeqNum (34) of the message sent by the third party.

Applicable when messages are communicated/re-distributed via third parties which function as service bureaus or "hubs". Only applicable if OnBehalfOfCompID (115) is being used.

Type: **SeqNum**

Used in groups: **HopGrp**

**180.2.1172 HopSendingTime**

Time that HopCompID (628) sent the message. It is recommended that this value be the SendingTime (52) of the message sent by the third party.

Applicable when messages are communicated/re-distributed via third parties which function as service bureaus or "hubs". Only applicable if OnBehalfOfCompID (115) is being used.

Type: **UTCTimestamp**

Used in groups: **HopGrp**

### **180.2.1173 HostCrossID**

Host assigned entity ID that can be used to reference all components of a cross; sides + strategy + legs. Used as the primary key with which to refer to the Cross Order for cancellation and replace. The HostCrossID will also be used to link together components of the Cross Order. For example, each individual Execution Report associated with the order will carry HostCrossID in order to tie back to the original cross order.

Type: **String**

Used in messages: **CrossOrderCancelReplaceRequest**, **CrossOrderCancelRequest**, **ExecutionReport**

### **180.2.1174 ImpliedMarketIndicator**

Indicates that an implied market should be created for either the legs of a multi-leg instrument (Implied-in) or for the multi-leg instrument based on the existence of the legs (Implied-out). Determination as to whether implied markets should be created is generally done at the level of the multi-leg instrument. Commonly used in listed derivatives.

Type: **int**

Allowed values in ImpliedMarketIndicatorCodeSet:

Code	Name	Description
0	NotImplied	Not implied
1	ImpliedIn	Implied-in - The existence of a multi-leg instrument is implied by the legs of that instrument
2	ImpliedOut	Implied-out - The existence of the underlying legs are implied by the multi-leg instrument
3	BothImpliedInAndImpliedOut	Both Implied-in and Implied-out

Used in components: **BaseTradingRules**

**180.2.1175 IncTaxInd**

Code to represent whether value is net (inclusive of tax) or gross.

Type: **int**

Allowed values in IncTaxIndCodeSet:

Code	Name	Description
1	Net	Net
2	Gross	Gross

Used in messages: **BidRequest**

**180.2.1176 IndexAnnexDate**

The date of a credit default swap index series annex.

Type: **LocalMktDate**

Used in components: **Instrument**

**180.2.1177 IndexAnnexSource**

The source of a credit default swap series annex.

Type: **String**

Used in components: **Instrument**

**180.2.1178 IndexAnnexVersion**

The version of a credit default swap index annex.

Type: **int**

Used in components: **Instrument**

**180.2.1179 IndexRollMonth**

Month identified in the index roll.

Type: **String**

Used in groups: **IndexRollMonthGrp**

**180.2.1180 IndexRollMonthGrp**

Used for specifying multiple roll months in a given year for an index.

Name	Mult.	Type	Description
<b>NoIndexRollMonths</b>	[1..1]	NumInGroup	
<b>IndexRollMonth</b>	[0..1]	String	Required if NoIndexRollMonths(2734) > 0.

Used in components: **InstrumentExtension**

**180.2.1181 IndexSeries**

The series identifier of a credit default swap index.

Type: **int**

Used in components: **Instrument**

**180.2.1182 IndividualAllocID**

Unique identifier for a specific NoAllocs (78) repeating group instance (e.g. for an AllocAccount).

Type: **String**

Used in components: **SettlTradeDetails**

Used in groups: **AllocAckGrp**, **AllocGrp**, **PreAllocGrp**, **PreAllocMlegGrp**, **TrdAllocGrp**

Used in messages: **Confirmation**, **ConfirmationRequest**

**180.2.1183 IndividualAllocRejCode**

Identified reason for rejecting an individual AllocAccount (79) detail.

Same values as AllocRejCode (88)

Type: **int**

Allowed values in AllocRejCodeCodeSet:

Code	Name	Description
0	UnknownAccount	Unknown or missing account(s)
1	IncorrectQuantity	Incorrect or missing block quantity
2	IncorrectAveragePrice	Incorrect or missing average price
3	UnknownExecutingBrokerMnemonic	Unknown executing broker mnemonic
4	CommissionDifference	Incorrect or missing commission
5	UnknownOrderID	Unknown OrderID(37)
6	UnknownListID	Unknown ListID(66)
7	OtherSeeText	Other (further in Text (58))
8	IncorrectAllocatedQuantity	Incorrect or missing allocated quantity
9	CalculationDifference	Calculation difference
10	UnknownOrStaleExecID	Unknown or Stale ExecID(17)
11	MismatchedData	Mismatched data
12	UnknownCLOrdID	Unknown CLOrdID(11)
13	WarehouseRequestRejected	Warehouse request rejected
14	DuplicateOrMissingIndividualAllocID	Duplicate or missing IndividualAllocID(467)
15	TradeNotRecognized	Trade not recognized
16	DuplicateTrade	Trade previously allocated
17	IncorrectOrMissingInstrument	Incorrect or missing instrument
18	IncorrectOrMissingSettlDate	Incorrect or missing settlement date
19	IncorrectOrMissingFundIDOrFund- Name	Incorrect or missing fund ID or fund name
20	IncorrectOrMissingSettlInstructions	Incorrect or missing settlement instructions
21	IncorrectOrMissingFees	Incorrect or missing fees
22	IncorrectOrMissingTax	Incorrect or missing tax
23	UnknownOrMissingParty	Unknown or missing party
24	IncorrectOrMissingSide	Incorrect or missing side
25	IncorrectOrMissingNetMoney	Incorrect or missing net-money



Code	Name	Description
26	IncorrectOrMissingTradeDate	Incorrect or missing trade date
27	IncorrectOrMissingSettlCcyInstructions	Incorrect or missing settlement currency instructions
28	IncorrectOrMissingProcessCode	Incorrect or missing ProcessCode(81)
99	Other	Other. Use Text(58) for further reject reasons.

Used in groups: [AllocAckGrp](#)

#### **180.2.1184 IndividualAllocType**

Identifies whether the allocation is to be sub-allocated or allocated to a third party

Type: [int](#)

Allowed values in IndividualAllocTypeCodeSet:

Code	Name	Description
1	SubAllocate	Sub Allocate
2	ThirdPartyAllocation	Third Party Allocation

Used in groups: [AllocAckGrp](#), [AllocGrp](#)

#### **180.2.1185 InformationBarrierID**

The identifier of the information barrier in place for a trading unit that will meet the criteria of the "no-knowledge" exception in FINRA Rule 5320.02.

Type: [String](#)

Used in groups: [TrdRegTimestamps](#)

#### **180.2.1186 InitialDisplayQty**

Used to convey the initially requested display quantity specified in DisplayQty(1138) on order entry and modification messages in ExecutionReport message. Applicable only in ExecutionReport message where DisplayQty(1138) is the currently displayed quantity and the requested display quantity of the

order also needs to be conveyed. The values of the two fields are different as soon as the order is partially filled and also after a refresh of the order whenever DisplayMethod(1084) is not 1=Initial.

Type: **Qty**

Used in components: **DisplayInstruction**

### **180.2.1187 InputSource**

Originating source of the request.

Type: **String**

Used in messages: **ContraryIntentionReport**, **PositionMaintenanceReport**

### **180.2.1188 InstrAttribType**

Code to represent the type of instrument attribute

Type: **int**

Allowed values in InstrAttribTypeCodeSet:

Code	Name	Description
1	Flat	Flat (securities pay interest on a current basis but are traded without interest)
2	ZeroCoupon	Zero coupon
3	InterestBearing	Interest bearing (for Euro commercial paper when not issued at discount)
4	NoPeriodicPayments	No periodic payments
5	VariableRate	Variable rate
6	LessFeeForPut	Less fee for put
7	SteppedCoupon	Stepped coupon
8	CouponPeriod	Coupon period (if not semi-annual). Supply redemption date in the InstrAttribValue(872) field.
9	When	When [and if] issued
10	OriginalIssueDiscount	Original issue discount
11	Callable	Callable, puttable
12	EscrowedToMaturity	Escrowed to Maturity
13	EscrowedToRedemptionDate	Escrowed to redemption date - callable. Supply redemption date in the InstrAttribValue(872) field.

Code	Name	Description
14	PreRefunded	Pre-refunded
15	InDefault	In default
16	Unrated	Unrated
17	Taxable	Taxable
18	Indexed	Indexed
19	SubjectToAlternativeMinimumTax	Subject To Alternative Minimum Tax
20	OriginalIssueDiscountPrice	Original issue discount price. Supply price in the InstrAttribValue(872) field.
21	CallableBelowMaturityValue	Callable below maturity value
22	CallableWithoutNotice	Callable without notice by mail to holder unless registered
23	PriceTickRulesForSecurity	Price tick rules for security
24	TradeTypeEligibilityDetailsForSecurity	Trade type eligibility details for security
25	InstrumentDenominator	Instrument denominator
26	InstrumentNumerator	Instrument numerator
27	InstrumentPricePrecision	Instrument price precision
28	InstrumentStrikePrice	Instrument strike price
29	TradeableIndicator	Tradeable indicator
30	InstrumentEligibleAnonOrders	Instrument is eligible to accept anonymous orders
31	MinGuaranteedFillVolume	Minimum guaranteed fill volume
32	MinGuaranteedFillStatus	Minimum guaranteed fill status
33	TradeAtSettlementEligibility	Trade at settlement (TAS) eligibility
34	TestInstrument	Test instrument. Instrument that is tradable but has no effect on the positions, exchange turnover etc.
35	DummyInstrument	Dummy instrument. Instrument that is normally halted and is only activated for trading under very special conditions (e.g. temporarily assigned for newly listed instrument). Use of a dummy instrument generally applies to systems that are unable to add reference data for new instruments intraday.
36	NegativeSettlementPriceEligibility	Negative settlement price eligibility
37	NegativeStrikePriceEligibility	Negative strike price eligibility

Code	Name	Description
38	USStdContractInd	US standard contract indicator. Indicates through InstrAttribValue(872) - values Y or N - whether the underlying asset in the trade references or is economically related to a contract listed in Appendix B of CFTC Part 43 regulation. See <a href="http://www.ecfr.gov/cgi-bin/text-idx?SID=4b2d1078ad68f6564a89d7ff6c52ec43&amp;node=17:2.0.1.1.3.0.1.8.2&amp;rgn=div">http://www.ecfr.gov/cgi-bin/text-idx?SID=4b2d1078ad68f6564a89d7ff6c52ec43&amp;node=17:2.0.1.1.3.0.1.8.2&amp;rgn=div</a> or refer to Appendix B to Part 43 in the final rule at <a href="http://www.cftc.gov/ucm/groups/public/@lrfederalregister/documents/file/2013-12133a.pdf">http://www.cftc.gov/ucm/groups/public/@lrfederalregister/documents/file/2013-12133a.pdf</a>
39	AdmittedToTradingOnTradingVenue	Admitted to trading on a trading venue
40	AverageDailyNotionalAmount	Average daily notional amount
41	AverageDailyNumberTrades	Average daily number of trades
99	Text	Text. Supply the text value in InstrAttribValue(872).

Used in groups: **AttrbGrp**

#### 180.2.1189 InstrAttribValue

Attribute value appropriate to the InstrAttribType (871) field.

Type: **String**

Used in groups: **AttrbGrp**

#### 180.2.1190 InstrmtAssignmentMethod

Method under which assignment was conducted

Type: **char**

Allowed values in InstrmtAssignmentMethodCodeSet:

Code	Name	Description
P	ProRata	Pro rata
R	Random	Random

Used in components: **Instrument**

**180.2.1191 InstrmtGrp**

Name	Mult.	Type	Description
NoRelatedSym	[1..1]	NumInGroup	Specifies the number of repeating symbols (instruments) specified
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
RelatedInstrumentGrp	[0..*]	Group	

Used in messages: [AdjustedPositionReport](#), [Email](#), [News](#)

**180.2.1192 InstrmtLegExecGrp**

Name	Mult.	Type	Description
NoLegs	[1..1]	NumInGroup	Number of leg executions.
InstrumentLeg	[0..1]	Component	Required if NoLegs(555) > 0.
LegOrderQty	[0..1]	Qty	Quantity ordered for this leg as provided during order entry.
LegQty	[0..1]	Qty	The LegQty(687) field is deprecated. The use of LegOrderQty(685) is recommended instead.
LegMidPx	[0..1]	Price	
LegSwapType	[0..1]	CodeSet	Instead of LegOrderQty(685) requests that the sellside calculate LegOrderQty(685) based on opposite Leg.
LegStipulations	[0..*]	Group	
LegAllocID	[0..1]	String	
LegPreAllocGrp	[0..*]	Group	
LegAccount	[0..1]	String	
LegClearingAccountType	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in ClearingAccountType(1816) in the Instrument component.

Name	Mult.	Type	Description
LegPositionEffect	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in PositionEffect(77) in the Instrument component.
LegCoveredOrUncovered	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in CoveredOrUncovered(203) in the Instrument component.
NestedParties3	[0..*]	Group	
LegRefID	[0..1]	String	Use of LegRefID(654) in this component is deprecated. Recommend the use of LegID(1788) in the InstrumentLeg component.
LegSettlType	[0..1]	CodeSet	
LegSettlDate	[0..1]	LocalMktDate	Takes precedence over a calculated LegSettlType(587) when specified regardless of LegSettlType(587) value. Conditionally required when LegSettlType(587) = B(Broken date).
LegLastPx	[0..1]	Price	Used to report the execution price assigned to the leg of the multileg instrument.
LegSettlCurrency	[0..1]	Currency	
LegSettlCurrencyCodeSource	[0..1]	CodeSet	
LegLastForwardPoints	[0..1]	PriceOffset	
LegCalculatedCcyLastQty	[0..1]	Qty	
LegGrossTradeAmt	[0..1]	Amt	For FX Futures can be used to express the notional value of a trade when LegLastQty(1418) and other quantity fields are expressed in terms of number of contracts - LegContractMultiplier(231) is required in this case.
LegShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when LegSide(624) = 6 (Sell short exempt) in InstrumentLeg component.
LegVolatility	[0..1]	float	
LegDividendYield	[0..1]	Percentage	
LegCurrencyRatio	[0..1]	float	
LegExecInst	[0..1]	CodeSet	
LegLastQty	[0..1]	Qty	Quantity executed for this leg.
FillRefID	[0..1]	String	Use to reference the partial execution of a multi-leg order to which this leg execution belongs.

Used in messages: [ExecutionReport](#)

### 180.2.1193 InstrmtLegGrp

Name	Mult.	Type	Description
<a href="#">NoLegs</a>	[1..1]	NumInGroup	Number of legs
<a href="#">InstrumentLeg</a>	[0..1]	Component	Required if NoLegs(555) > 0.
<a href="#">LegFinancingDetails</a>	[0..1]	Component	

Used in groups: [InstrmtMDReqGrp](#), [InstrmtMatchSideGrp](#), [MDIncGrp](#), [QuotCxlEntriesGrp](#), [QuotEntryAckGrp](#), [QuotEntryGrp](#), [RFQReqGrp](#), [RelSymDerivSecGrp](#), [RelSymDerivSecUpdGrp](#), [SecMassStatGrp](#)

Used in messages: [Advertisement](#), [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AssignmentReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [Confirmation](#), [CrossOrderCancelReplaceRequest](#), [CrossOrderCancelRequest](#), [DontKnowTrade](#), [Email](#), [ExecutionAck](#), [MarketDataSnapshotFullRefresh](#), [MarketDataStatisticsReport](#), [MarketDataStatisticsRequest](#), [NewOrderCross](#), [News](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [PositionReport](#), [QuoteStatusRequest](#), [RequestForPositions](#), [RequestForPositionsAck](#), [SecurityDefinition](#), [SecurityDefinitionRequest](#), [SecurityDefinitionUpdateReport](#), [SecurityListRequest](#), [SecurityStatus](#), [SecurityStatusRequest](#), [TradeCaptureReportRequest](#), [TradeCaptureReportRequestAck](#)

### 180.2.1194 InstrmtLegIOIGrp

Name	Mult.	Type	Description
<a href="#">NoLegs</a>	[1..1]	NumInGroup	Required for multileg IOIs
<a href="#">InstrumentLeg</a>	[0..1]	Component	Required for multileg IOIs. For Swaps one leg is Buy and other leg is Sell
<a href="#">LegIOQty</a>	[0..1]	CodeSet	Required for multileg IOIs and for each leg.
<a href="#">LegStipulations</a>	[0..*]	Group	

Used in messages: [IOI](#)

**180.2.1195 InstrmtLegSecListGrp**

Name	Mult.	Type	Description
NoLegs	[1..1]	NumInGroup	Number of legs that make up the Security
InstrumentLeg	[0..1]	Component	Insert here the set of "Instrument Legs" (leg symbology) fields defined in "Common Components of Application Messages". Required if NoLegs > 0
LegSwapType	[0..1]	CodeSet	
LegSettlType	[0..1]	CodeSet	
LegStipulations	[0..*]	Group	Insert here the set of "LegStipulations" (leg symbology) fields defined in "Common Components of Application Messages". Required if NoLegs > 0
LegBenchmarkCurveData	[0..1]	Component	Insert here the set of "LegBenchmarkCurveData" (leg symbology) fields defined in "Common Components of Application Messages". Required if NoLegs > 0

Used in groups: [SecListGrp](#)

**180.2.1196 InstrmtMatchSideGrp**

The InstrmtMatchSideGrp component is used to convey all trades for a given match event reported by instrument and trade side.

Name	Mult.	Type	Description
NoInstrmtMatchSides	[1..1]	NumInGroup	
Instrument	[0..1]	Component	Required if NoInstrmtMatchSides(1889) > 0.
InstrmtLegGrp	[0..*]	Group	LegID(1788) in the InstrmtLegGrp component can be used to reference individual leg executions referenced in the TrdInstrmtLegExecGrp component with LegRefID(654).
UndInstrmtGrp	[0..*]	Group	
TrdMatchSubID	[0..1]	String	
Quantity	[0..1]	Qty	Total quantity for this instrument in this match event. This is the cumulative sum of LastQty(32) for all match steps for this instrument.



Name	Mult.	Type	Description
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
QtyType	[0..1]	CodeSet	
LastQty	[0..1]	Qty	Required if NoInstrmtMatchSides(1889) > 0. Trade quantity for this instrument within this match step. The value is the greater of the sum of SideLastQty(1009) of each side (i.e. buy or sell) for each TrdMatchSideGrp instance within the current InstrmtMatchSideGrp instance.
PriceType	[0..1]	CodeSet	
LastPx	[0..1]	Price	Required if NoInstrmtMatchSides(1889) > 0.
LastMkt	[0..1]	Exchange	
TrdMatchSideGrp	[0..*]	Group	Required if NoInstrmtMatchSides(1889) > 0.

Used in messages: [TradeMatchReport](#)

### 180.2.1197 InstrmtMDReqGrp

Name	Mult.	Type	Description
NoRelatedSym	[1..1]	NumInGroup	Number of symbols (instruments) requested.
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
SpreadOrBenchmarkCurveData	[0..1]	Component	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
QuoteType	[0..1]	CodeSet	

Name	Mult.	Type	Description
SettlType	[0..1]	CodeSet	For NDFs either SettlType (specifying the tenor) or SettlDate must be specified.
SettlDate	[0..1]	LocalMktDate	SettlType (specifying the tenor) or SettlDate must be specified.
MDEntrySize	[0..1]	Qty	Quantity or volume represented by the Market Data Entry. In the context of the Market Data Request this allows the Initiator to indicate the quantity of the market data request. Specific to FX this field indicates the ceiling amount the customer is seeking prices for.
MDStreamID	[0..1]	String	

Used in messages: [MarketDataRequest](#)

### 180.2.1198 InstrmtStrkPxGrp

Name	Mult.	Type	Description
NoStrikes	[1..1]	NumInGroup	Number of strike price entries
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". Required if NoStrikes > 0. Must be first field in repeating group.
UndInstrmtGrp	[0..*]	Group	Underlying Instruments
PrevClosePx	[0..1]	Price	Useful for verifying security identification
ClOrdID	[0..1]	String	Can use client order identifier or the symbol and side to uniquely identify the stock in the list.
SecondaryClOrdID	[0..1]	String	
Side	[0..1]	CodeSet	
Price	[0..1]	Price	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: **ListStrikePrice**

### 180.2.1199 InstrRegistry

Values may include BIC for the depository or custodian who maintain ownership records, the ISO country code for the location of the record, or the value "ZZ" to specify physical ownership of the security (e.g. stock certificate).

Type: **String**

Used in components: **Instrument**

### 180.2.1200 Instrument

The Instrument component block contains all the fields commonly used to describe a security or instrument. Typically the data elements in this component block are considered the static data of a security, data that may be commonly found in a security master database. The Instrument component block can be used to describe any asset type supported by FIX.

Name	Mult.	Type	Description
Symbol	[0..1]	String	Common, "human understood" representation of the security. SecurityID value can be specified if no symbol exists (e.g. non-exchange traded Collective Investment Vehicles). Use "[N/A]" for products which do not have a symbol. Required if the Instrument component is marked as required where the component is used.
SymbolSfx	[0..1]	CodeSet	Used in Fixed Income with a value of "WI" to indicate "When Issued" for a security to be reissued under an old CUSIP or ISIN or with a value of "CD" to indicate a EUCP with lump-sum interest rather than discount price.

Name	Mult.	Type	Description
SecurityID	[0..1]	String	Takes precedence in identifying security to counterparty over SecurityAltID block. Requires SecurityIDSource if specified.
SecurityIDSource	[0..1]	CodeSet	Conditionally required when SecurityID(48) is specified.
SecAltIDGrp	[0..*]	Group	Number of alternate Security Identifiers
Product	[0..1]	CodeSet	Indicates the type of product the security is associated with (high-level category)
ProductComplex	[0..1]	String	Identifies an entire suite of products for a given market. In Futures this may be "interest rates", "agricultural", "equity indexes", etc
SecurityGroup	[0..1]	String	An exchange specific name assigned to a group of related securities which may be concurrently affected by market events and actions.
CFICode	[0..1]	String	Indicates the type of security using ISO 10962 standard, Classification of Financial Instruments (CFI code) values. It is recommended that CFICode be used instead of SecurityType for non-Fixed Income instruments.
UPICode	[0..1]	String	
SecurityType	[0..1]	CodeSet	It is recommended that CFICode be used instead of SecurityType for non-Fixed Income instruments. Required for Fixed Income. Refer to Volume 7 - Fixed Income. Futures and Options should be specified using the CFICode[461] field instead of SecurityType[167] (Refer to Volume 7 - Recommendations and Guidelines for Futures and Options Markets.)
SecuritySubType	[0..1]	String	Sub-type qualification/identification of the SecurityType (e.g. for SecurityType="MLEG"). If specified, SecurityType is required.
MaturityMonthYear	[0..1]	MonthYear	Specifies the month and year of maturity. Applicable for standardized derivatives which are typically only referenced by month and year (e.g. S&P futures). Note MaturityDate (a full date) can also be specified.

Name	Mult.	Type	Description
MaturityDate	[0..1]	LocalMktDate	Specifies date of maturity (a full date). Note that standardized derivatives which are typically only referenced by month and year (e.g. S&P futures) may use MaturityMonthYear(200) and/or this field. When using MaturityMonthYear(200), it is recommended that markets and sell sides report the MaturityDate(541) on all outbound messages as a means of data enrichment. For NDFs this represents the fixing date of the contract.
MaturityTime	[0..1]	TZTimeOnly	For NDFs this represents the fixing time of the contract. It is optional to specify the fixing time.
MaturityFrequencyUnit	[0..1]	CodeSet	Conditionally required when MaturityFrequencyPeriod(2983) is specified.
MaturityFrequencyPeriod	[0..1]	int	Conditionally required when MaturityFrequencyUnit(2982) is specified and the value is not EOM (End of Month) or F (Flexible).
SettleOnOpenFlag	[0..1]	String	Indicator to determine if Instrument is Settle on Open.
InstrmtAssignmentMethod	[0..1]	CodeSet	
SecurityStatus	[0..1]	CodeSet	Gives the current state of the instrument
CouponPaymentDate	[0..1]	LocalMktDate	Date interest is to be paid. Used in identifying Corporate Bond issues.
RestructuringType	[0..1]	CodeSet	
Seniority	[0..1]	CodeSet	
NotionalPercentageOutstanding	[0..1]	Percentage	
OriginalNotionalPercentageOutstanding	[0..1]	Percentage	
AttachmentPoint	[0..1]	Percentage	
DetachmentPoint	[0..1]	Percentage	
ObligationType	[0..1]	CodeSet	
AssetGroup	[0..1]	CodeSet	
AssetClass	[0..1]	CodeSet	Required if AssetSubClass(1939) is specified.
AssetSubClass	[0..1]	CodeSet	Required if AssetType(1940) is specified.
AssetType	[0..1]	String	Required if AssetSubType(2735) is specified.
AssetSubType	[0..1]	String	
SecondaryAssetGrp	[0..*]	Group	
AssetAttributeGrp	[0..*]	Group	
SwapClass	[0..1]	CodeSet	

Name	Mult.	Type	Description
SwapSubClass	[0..1]	CodeSet	
NthToDefault	[0..1]	int	Conditionally required when MthToDefault(1943) is specified.
MthToDefault	[0..1]	int	
SettledEntityMatrixSource	[0..1]	String	
SettledEntityMatrixPublicationDate	[0..1]	LocalMktDate	
CouponType	[0..1]	CodeSet	
TotalIssuedAmount	[0..1]	Amt	
CouponFrequencyPeriod	[0..1]	int	Conditionally required when CouponFrequencyUnit(1949) is specified.
CouponFrequencyUnit	[0..1]	CodeSet	Conditionally required when CouponFrequencyPeriod(1948) is specified.
CouponDayCount	[0..1]	CodeSet	
CouponOtherDayCount	[0..1]	String	
ConvertibleBondEquityID	[0..1]	String	
ConvertibleBondEquityIDSource	[0..1]	CodeSet	Conditionally required when ConvertibleBondEquityID(1951) is specified.
ContractPriceRefMonth	[0..1]	MonthYear	
LienSeniority	[0..1]	CodeSet	
LoanFacility	[0..1]	CodeSet	
ReferenceEntityType	[0..1]	CodeSet	
IndexSeries	[0..1]	int	
IndexAnnexVersion	[0..1]	int	
IndexAnnexDate	[0..1]	LocalMktDate	
IndexAnnexSource	[0..1]	String	
SettlRateIndex	[0..1]	String	
SettlRateIndexLocation	[0..1]	String	
OptionExpirationDesc	[0..1]	String	
EncodedOptionExpirationDescLen	[0..1]	Length	Must be set if EncodedOptionExpirationDesc(1697) field is specified and must immediately precede it.
EncodedOptionExpirationDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the OptionExpirationDesc(1581) field in the encoded format specified via the MessageEncoding(347) field.
IssueDate	[0..1]	LocalMktDate	Date instrument was issued. For Fixed Income IOIs for new issues, specifies the issue date.

Name	Mult.	Type	Description
RepoCollateralSecurityType	[0..1]	String	
RepurchaseTerm	[0..1]	int	
RepurchaseRate	[0..1]	Percentage	
Factor	[0..1]	float	For Fixed Income: Amortization Factor for deriving Current face from Original face for ABS or MBS securities, note the fraction may be greater than, equal to or less than 1. In TIPS securities this is the Inflation index. Qty * Factor * Price = Gross Trade Amount. For Derivatives: Contract Value Factor by which price must be adjusted to determine the true nominal value of one futures/options contract. (Qty * Price) * Factor = Nominal Value
CreditRating	[0..1]	String	
InstrRegistry	[0..1]	String	The location at which records of ownership are maintained for this instrument, and at which ownership changes must be recorded. Can be used in conjunction with ISIN to address ISIN uniqueness issues.
CountryOfIssue	[0..1]	Country	ISO Country code of instrument issue (e.g. the country portion typically used in ISIN). Can be used in conjunction with non-ISIN SecurityID (e.g. CUSIP for Municipal Bonds without ISIN) to provide uniqueness.
StateOrProvinceOfIssue	[0..1]	String	A two-character state or province abbreviation.
LocaleOfIssue	[0..1]	String	The three-character IATA code for a locale (e.g. airport code for Municipal Bonds).
RedemptionDate	[0..1]	LocalMktDate	
StrikePrice	[0..1]	Price	Used for derivatives, such as options and covered warrants
OrigStrikePrice	[0..1]	Price	
StrikePricePrecision	[0..1]	int	
StrikeCurrency	[0..1]	Currency	Used for derivatives
StrikeCurrencyCodeSource	[0..1]	CodeSet	
StrikeMultiplier	[0..1]	float	Used for derivatives. Multiplier applied to the strike price for the purpose of calculating the settlement value.
StrikeValue	[0..1]	float	Used for derivatives. The number of shares/units for the financial instrument involved in the option trade.

Name	Mult.	Type	Description
StrikeUnitOfMeasure	[0..1]	CodeSet	
StrikeIndex	[0..1]	String	
StrikeIndexCurvePoint	[0..1]	String	
StrikeIndexSpread	[0..1]	PriceOffset	
StrikeIndexQuote	[0..1]	CodeSet	
StrikePriceDeterminationMethod	[0..1]	CodeSet	
StrikePriceBoundaryMethod	[0..1]	CodeSet	When specified, PutOrCall(201), StrikePrice(202), and StrikePriceBoundaryPrecision(1480) must also be specified.
StrikePriceBoundaryPrecision	[0..1]	Percentage	
UnderlyingPriceDeterminationMethod	[0..1]	CodeSet	
OptAttribute	[0..1]	char	Used for derivatives, such as options and covered warrants to indicate a versioning of the contract when required due to corporate actions to the underlying. Should not be used to indicate type of option - use the CFICode[461] for this purpose.
ContractMultiplier	[0..1]	float	For Fixed Income, Convertible Bonds, Derivatives, etc. Note: If used, quantities should be expressed in the "nominal" (e.g. contracts vs. shares) amount.
ContractMultiplierUnit	[0..1]	CodeSet	
TradingUnitPeriodMultiplier	[0..1]	int	
FlowScheduleType	[0..1]	CodeSet	
MinPriceIncrement	[0..1]	float	Minimum price increment for the instrument. Could also be used to represent tick value.
MinPriceIncrementAmount	[0..1]	Amt	Minimum price increment amount associated with the MinPriceIncrement [969]. For listed derivatives, the value can be calculated by multiplying MinPriceIncrement by ContractValueFactor [231]
UnitOfMeasure	[0..1]	CodeSet	
UnitOfMeasureQty	[0..1]	Qty	
UnitOfMeasureCurrency	[0..1]	Currency	
UnitOfMeasureCurrencyCodeSource	[0..1]	CodeSet	
PriceUnitOfMeasure	[0..1]	CodeSet	
PriceUnitOfMeasureQty	[0..1]	Qty	
PriceUnitOfMeasureCurrency	[0..1]	Currency	



Name	Mult.	Type	Description
PriceUnitOfMeasureCurrencyCodeSource	[0..1]	CodeSet	
SettlMethod	[0..1]	CodeSet	Conditionally required if SettlSubMethod(2579) is specified.
SettlSubMethod	[0..1]	CodeSet	
ExerciseStyle	[0..1]	CodeSet	Type of exercise of a derivatives security
OptPayoutType	[0..1]	CodeSet	
OptPayoutAmount	[0..1]	Amt	Conditionally required if OptPayoutType(1482) = 3 (Binary).
ReturnTrigger	[0..1]	CodeSet	
PriceQuoteMethod	[0..1]	CodeSet	Method for price quotation
ValuationMethod	[0..1]	CodeSet	Indicates type of valuation method used.
ValuationSource	[0..1]	String	
ValuationReferenceModel	[0..1]	String	
PriceQuoteCurrency	[0..1]	Currency	
PriceQuoteCurrencyCodeSource	[0..1]	CodeSet	
ListMethod	[0..1]	CodeSet	Indicates whether the instruments are pre-listed only or can also be defined via user request
CapPrice	[0..1]	Price	Used to express the ceiling price of a capped call
FloorPrice	[0..1]	Price	Used to express the floor price of a capped put
PutOrCall	[0..1]	CodeSet	Used to express option right
InTheMoneyCondition	[0..1]	CodeSet	Used to express in-the-moneyness behavior in general terms for the option without the use of StrikePrice(202) and PutOrCall(201).
ContraryInstructionEligibilityIndicator	[0..1]	Boolean	
FlexibleIndicator	[0..1]	Boolean	Used to indicate if a security has been defined as flexible according to "non-standard" means. Analog to CFICode Standard/Non-standard indicator
FlexProductEligibilityIndicator	[0..1]	Boolean	Used to indicate if a product or group of product supports the creation of flexible securities
BlockTradeEligibilityIndicator	[0..1]	Boolean	
LowExercisePriceOptionIndicator	[0..1]	Boolean	
TimeUnit	[0..1]	CodeSet	Used to indicate a time unit for the contract (e.g., days, weeks, months, etc.)
CouponRate	[0..1]	Percentage	For Fixed Income.
SecurityExchange	[0..1]	Exchange	Can be used to identify the security.

Name	Mult.	Type	Description
PositionLimit	[0..1]	int	Position Limit for the instrument.
NTPositionLimit	[0..1]	int	Near-term Position Limit for the instrument.
Issuer	[0..1]	String	
EncodedIssuerLen	[0..1]	Length	Must be set if EncodedIssuer(349) field is specified and must immediately precede it.
EncodedIssuer	[0..1]	data	Encoded (non-ASCII characters) representation of the Issuer(106) field in the encoded format specified via the MessageEncoding(347) field.
FinancialInstrumentShortName	[0..1]	String	
FinancialInstrumentFullName	[0..1]	String	
EncodedFinancialInstrumentFull-NameLen	[0..1]	Length	Must be set if EncodedFinancialInstrumentFullName(2716) field is specified and must immediately precede it.
EncodedFinancialInstrumentFullName	[0..1]	data	Encoded (non-ASCII characters) representation of the FinancialInstrumentFullName(2714) field in the encoded format specified via the MessageEncoding(347) field.
SecurityDesc	[0..1]	String	
EncodedSecurityDescLen	[0..1]	Length	Must be set if EncodedSecurityDesc(351) field is specified and must immediately precede it.
EncodedSecurityDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the SecurityDesc(107) field in the encoded format specified via the MessageEncoding(347) field.
SecurityXML	[0..1]	Component	Embedded XML document describing the instrument.
Pool	[0..1]	String	Identifies MBS / ABS pool
ContractSettlMonth	[0..1]	MonthYear	Must be present for MBS/TBA
CPPProgram	[0..1]	CodeSet	The program under which a commercial paper is issued
CPRegType	[0..1]	String	The registration type of a commercial paper issuance
EvntGrp	[0..*]	Group	Number of repeating EventType group entries.
DatedDate	[0..1]	LocalMktDate	If different from IssueDate
InterestAccrualDate	[0..1]	LocalMktDate	If different from IssueDate and DatedDate
InstrumentParties	[0..*]	Group	Used to identify the parties related to a specific instrument.
ShortSaleRestriction	[0..1]	CodeSet	
ComplexEvents	[0..*]	Group	

Name	Mult.	Type	Description
RefTickTableID	[0..1]	int	Spread table code referred by the security or symbol.
StrategyType	[0..1]	CodeSet	
CommonPricingIndicator	[0..1]	Boolean	
SettlDisruptionProvision	[0..1]	CodeSet	
DeliveryRouteOrCharter	[0..1]	String	
InstrumentRoundingDirection	[0..1]	CodeSet	
InstrumentRoundingPrecision	[0..1]	int	
InstrumentPricePrecision	[0..1]	int	
SecurityReferenceDataSupplement	[0..1]	String	
DateAdjustment	[0..1]	Component	
PricingDateTime	[0..1]	Component	
MarketDisruption	[0..1]	Component	
OptionExercise	[0..1]	Component	
StreamGrp	[0..*]	Group	
ProvisionGrp	[0..*]	Group	
AdditionalTermGrp	[0..*]	Group	
ProtectionTermGrp	[0..*]	Group	
CashSettlTermGrp	[0..*]	Group	
PhysicalSettlTermGrp	[0..*]	Group	
ExtraordinaryEventGrp	[0..*]	Group	
ExtraordinaryEventAdjustmentMethod	[0..1]	CodeSet	
ExchangeLookAlike	[0..1]	Boolean	

Used in components: [SettlTradeDetails](#)

Used in groups: [InstrmtGrp](#), [InstrmtMDReqGrp](#), [InstrmtMatchSideGrp](#), [InstrmtStrkPxGrp](#), [ListOrdGrp](#), [MDIncGrp](#), [OrderEntryAckGrp](#), [OrderEntryGrp](#), [QuotCxlEntriesGrp](#), [QuotEntryAckGrp](#), [QuotEntryGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [RFQReqGrp](#), [RelSymDerivSecGrp](#), [RelSymDerivSecUpdGrp](#), [SecListGrp](#), [SecLstUpdRelSymGrp](#), [SecMassStatGrp](#), [SecurityRiskMetricGrp](#), [SettlObligationInstructions](#), [StrmAsgnReqInstrmtGrp](#), [StrmAsgnRptInstrmtGrp](#)

Used in messages: [Advertisement](#), [AllocationInstruction](#), [AllocationInstructionAck](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#), [AssignmentReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [Confirmation](#), [ContraryIntentionReport](#), [CrossOrderCancelReplaceRequest](#), [CrossOrderCancelRequest](#), [CrossRe-](#)

quest, CrossRequestAck, DontKnowTrade, ExecutionAck, ExecutionReport, IOI, MarginRequirementInquiry, MarginRequirementInquiryAck, MarginRequirementReport, MarketDataSnapshotFullRefresh, MarketDataStatisticsReport, MarketDataStatisticsRequest, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderMassStatusRequest, OrderStatusRequest, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PayManagementReport, PayManagementRequest, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferReport, Quote, QuoteResponse, QuoteStatusReport, QuoteStatusRequest, RequestForPositions, RequestForPositionAck, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityListRequest, SecurityStatus, SecurityStatusRequest, TradeAggregationReport, TradeAggregationRequest, TradeCaptureReport, TradeCaptureReportAck, TradeCaptureReportRequest, TradeCaptureReportRequestAck, TradingSessionStatus

### 180.2.1201 InstrumentExtension

The InstrumentExtension component block identifies additional security attributes that are more commonly found for Fixed Income securities.

Name	Mult.	Type	Description
DeliveryForm	[0..1]	CodeSet	Identifies the form of delivery.
PctAtRisk	[0..1]	Percentage	Percent at risk due to lowest possible call.
AttrbGrp	[0..*]	Group	Number of repeating InstrAttrb group entries.
CommodityFinalPriceType	[0..1]	CodeSet	
IndexRollMonthGrp	[0..*]	Group	
NextIndexRollDate	[0..1]	LocalMktDate	
FloatingRateIndex	[0..1]	Component	
ReferenceDataDateGrp	[0..*]	Group	

Used in groups: InstrmtGrp, InstrmtMDReqGrp, MDIncGrp, RelSymDerivSecGrp, RelSymDerivSecUpdGrp, SecListGrp, SecLstUpdRelSymGrp, SecMassStatGrp

Used in messages: Advertisement, AllocationInstruction, AllocationInstructionAlert, AllocationReport, Confirmation, IOI, MarketDataSnapshotFullRefresh, MarketDataStatisticsReport, MarketDataStatisticsRequest, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityListRequest, SecurityStatus, SecurityStatusRequest, TradeCaptureReport, TradeCaptureReportAck, TradeCaptureReportRequest, TradeCaptureReportRequestAck

### 180.2.1202 InstrumentLeg

The InstrumentLeg component block, like the Instrument component block, contains all the fields commonly used to describe a security or instrument. In the case of the InstrumentLeg component block it describes a security used in multileg-oriented messages.

Name	Mult.	Type	Description
LegSymbol	[0..1]	String	Common, "human understood" representation of the security. SecurityID value can be specified if no symbol exists (e.g. non-exchange traded Collective Investment Vehicles). Use "[N/A]" for products which do not have a symbol. Required if the InstrumentLeg component is marked as required where the component is used.
LegSymbolSfx	[0..1]	CodeSet	
LegSecurityID	[0..1]	String	
LegSecurityIDSource	[0..1]	CodeSet	
LegSecAltIDGrp	[0..*]	Group	
LegID	[0..1]	String	Used for unique identification of the leg that can subsequently be used whenever a simple leg identification is sufficient. It can also serve as input value for LegRefID(654) whenever only a simple leg reference is allowed or needed.
LegProduct	[0..1]	CodeSet	
LegSecurityGroup	[0..1]	String	
LegCFICode	[0..1]	String	
LegUPICode	[0..1]	String	
LegSecurityType	[0..1]	CodeSet	
LegSecuritySubType	[0..1]	String	
LegMaturityMonthYear	[0..1]	MonthYear	
LegMaturityDate	[0..1]	LocalMktDate	
LegMaturityTime	[0..1]	TZTimeOnly	
LegMaturityFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegMaturityFrequencyPeriod(2987) is specified.
LegMaturityFrequencyPeriod	[0..1]	int	Conditionally required when LegMaturityFrequencyUnit(2986) is specified and the value is not EOM (End of Month) or F (Flexible).
LegSettleOnOpenFlag	[0..1]	String	
LegInstrmtAssignmentMethod	[0..1]	CodeSet	

Name	Mult.	Type	Description
LegSecurityStatus	[0..1]	CodeSet	
LegCouponPaymentDate	[0..1]	LocalMktDate	
LegRestructuringType	[0..1]	CodeSet	
LegSeniority	[0..1]	CodeSet	
LegNotionalPercentageOutstanding	[0..1]	Percentage	
LegOriginalNotionalPercentageOutstanding	[0..1]	Percentage	
LegAttachmentPoint	[0..1]	Percentage	
LegDetachmentPoint	[0..1]	Percentage	
LegObligationType	[0..1]	CodeSet	
LegAssetGroup	[0..1]	CodeSet	
LegAssetClass	[0..1]	CodeSet	Required if LegAssetSubClass(2068) is specified.
LegAssetSubClass	[0..1]	CodeSet	Required if LegAssetType(2069) is specified.
LegAssetType	[0..1]	String	Required if LegAssetSubType(2739) is specified.
LegAssetSubType	[0..1]	String	
LegSecondaryAssetGrp	[0..*]	Group	
LegAssetAttributeGrp	[0..*]	Group	
LegSwapClass	[0..1]	CodeSet	
LegSwapSubClass	[0..1]	CodeSet	
LegNthToDefault	[0..1]	int	Conditionally required when LegMthToDefault(2158) is specified.
LegMthToDefault	[0..1]	int	
LegSettledEntityMatrixSource	[0..1]	String	
LegSettledEntityMatrixPublicationDate	[0..1]	LocalMktDate	
LegCouponType	[0..1]	CodeSet	
LegTotalIssuedAmount	[0..1]	Amt	
LegCouponFrequencyPeriod	[0..1]	int	Conditionally required when LegCouponFreqUnit(2164) is specified.
LegCouponFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegCouponFreqPeriod(2163) is specified.
LegCouponDayCount	[0..1]	CodeSet	
LegCouponOtherDayCount	[0..1]	String	
LegConvertibleBondEquityID	[0..1]	String	
LegConvertibleBondEquityIDSource	[0..1]	CodeSet	Conditionally required when LegConvertibleBondEquityID(2166) is specified.

Name	Mult.	Type	Description
LegContractPriceRefMonth	[0..1]	MonthYear	
LegLienSeniority	[0..1]	CodeSet	
LegLoanFacility	[0..1]	CodeSet	
LegReferenceEntityType	[0..1]	CodeSet	
LegIndexSeries	[0..1]	int	
LegIndexAnnexVersion	[0..1]	int	
LegIndexAnnexDate	[0..1]	LocalMktDate	
LegIndexAnnexSource	[0..1]	String	
LegSettlRateIndex	[0..1]	String	
LegSettlRateIndexLocation	[0..1]	String	
LegOptionExpirationDesc	[0..1]	String	
EncodedLegOptionExpirationDescLen	[0..1]	Length	Must be set if EncodedLegOptionExpirationDesc(2180) field is specified and must immediately precede it.
EncodedLegOptionExpirationDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the LegOptionExpirationDesc(2178) field in the encoded format specified via the MessageEncoding(347) field.
LegIssueDate	[0..1]	LocalMktDate	
LegRepoCollateralSecurityType	[0..1]	String	
LegRepurchaseTerm	[0..1]	int	
LegRepurchaseRate	[0..1]	Percentage	
LegFactor	[0..1]	float	
LegCreditRating	[0..1]	String	
LegInstrRegistry	[0..1]	String	
LegCountryOfIssue	[0..1]	Country	
LegStateOrProvinceOfIssue	[0..1]	String	
LegLocaleOfIssue	[0..1]	String	
LegRedemptionDate	[0..1]	LocalMktDate	
LegStrikePrice	[0..1]	Price	
LegStrikeCurrency	[0..1]	Currency	
LegStrikeCurrencyCodeSource	[0..1]	CodeSet	
LegStrikeMultiplier	[0..1]	float	
LegStrikeValue	[0..1]	float	
LegStrikeUnitOfMeasure	[0..1]	CodeSet	

Name	Mult.	Type	Description
LegStrikeIndex	[0..1]	String	
LegStrikeIndexCurvePoint	[0..1]	String	
LegStrikeIndexSpread	[0..1]	PriceOffset	
LegStrikeIndexQuote	[0..1]	CodeSet	
LegStrikePriceDeterminationMethod	[0..1]	CodeSet	
LegStrikePriceBoundaryMethod	[0..1]	CodeSet	When specified, LegPutOrCall(1358), LegStrikePrice(612), and LegStrikePriceBoundaryPrecision(2188) must also be specified.
LegStrikePriceBoundaryPrecision	[0..1]	Percentage	
LegUnderlyingPriceDetermination-Method	[0..1]	CodeSet	
LegOptAttribute	[0..1]	char	
LegContractMultiplier	[0..1]	float	
LegContractMultiplierUnit	[0..1]	CodeSet	
LegTradingUnitPeriodMultiplier	[0..1]	int	
LegFlowScheduleType	[0..1]	CodeSet	
LegMinPriceIncrement	[0..1]	float	
LegMinPriceIncrementAmount	[0..1]	Amt	
LegUnitOfMeasure	[0..1]	CodeSet	
LegUnitOfMeasureQty	[0..1]	Qty	
LegUnitOfMeasureCurrency	[0..1]	Currency	
LegUnitOfMeasureCurrencyCodeS- ource	[0..1]	CodeSet	
LegPriceUnitOfMeasure	[0..1]	CodeSet	
LegPriceUnitOfMeasureQty	[0..1]	Qty	
LegPriceUnitOfMeasureCurrency	[0..1]	Currency	
LegPriceUnitOfMeasureCurrency- CodeSource	[0..1]	CodeSet	
LegSettlMethod	[0..1]	CodeSet	
LegTimeUnit	[0..1]	CodeSet	Used to indicate a time unit for the contract (e.g., days, weeks, months, etc.)
LegExerciseStyle	[0..1]	CodeSet	
LegOptPayoutType	[0..1]	CodeSet	
LegOptPayoutAmount	[0..1]	Amt	Conditionally required if LegOptPayoutTyp(2193) = 3 (Binary).



Name	Mult.	Type	Description
LegReturnTrigger	[0..1]	CodeSet	
LegPriceQuoteMethod	[0..1]	CodeSet	
LegValuationMethod	[0..1]	CodeSet	
LegValuationSource	[0..1]	String	
LegValuationReferenceModel	[0..1]	String	
LegPriceQuoteCurrency	[0..1]	Currency	
LegPriceQuoteCurrencyCodeSource	[0..1]	CodeSet	
LegListMethod	[0..1]	CodeSet	
LegCapPrice	[0..1]	Price	
LegFloorPrice	[0..1]	Price	
LegFlexibleIndicator	[0..1]	Boolean	
LegFlexProductEligibilityIndicator	[0..1]	Boolean	
LegCouponRate	[0..1]	Percentage	
LegSecurityExchange	[0..1]	Exchange	
LegPositionLimit	[0..1]	int	
LegNTPositionLimit	[0..1]	int	
LegIssuer	[0..1]	String	
EncodedLegIssuerLen	[0..1]	Length	Must be set if EncodedLegIssuer(618) field is specified and must immediately precede it.
EncodedLegIssuer	[0..1]	data	Encoded (non-ASCII characters) representation of the LegIssuer(617) field in the encoded format specified via the MessageEncoding(347) field.
LegFinancialInstrumentShortName	[0..1]	String	
LegFinancialInstrumentFullName	[0..1]	String	
EncodedLegFinancialInstrumentFull-NameLen	[0..1]	Length	Must be set if EncodedLegFinancialInstrumentFullName(2719) field is specified and must immediately precede it.
EncodedLegFinancialInstrumentFull-Name	[0..1]	data	Encoded (non-ASCII characters) representation of the LegFinancialInstrumentFullName(2717) field in the encoded format specified via the MessageEncoding(347) field.
LegSecurityDesc	[0..1]	String	
EncodedLegSecurityDescLen	[0..1]	Length	Must be set if LegEncodedSecurityDesc(622) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedLegSecurityDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the LegSecurityDesc(620) field in the encoded format specified via the MessageEncoding(347) field.
LegSecurityXML	[0..1]	Component	Embedded XML document describing the leg instrument.
LegCPPProgram	[0..1]	CodeSet	
LegCPRegType	[0..1]	String	
LegRatioQty	[0..1]	float	Specific to the <InstrumentLeg> (not in <Instrument>)
LegSide	[0..1]	CodeSet	Specific to the <InstrumentLeg> (not in <Instrument>)
LegCurrency	[0..1]	Currency	Specific to the <InstrumentLeg> (not in <Instrument>)
LegCurrencyCodeSource	[0..1]	CodeSet	
LegPool	[0..1]	String	Identifies MBS / ABS pool
LegDatedDate	[0..1]	LocalMktDate	
LegContractSettlMonth	[0..1]	MonthYear	
LegInterestAccrualDate	[0..1]	LocalMktDate	
LegPutOrCall	[0..1]	CodeSet	Used to express option right
LegInTheMoneyCondition	[0..1]	CodeSet	Used to express in-the-moneyness behavior in general terms for the option without the use of LegStrikePrice(612) and LegPutOrCall(1358).
LegContraryInstructionEligibilityIndicator	[0..1]	Boolean	
LegOptionRatio	[0..1]	float	LegOptionRatio is provided on covering leg to create a delta neutral spread. In Listed Derivatives, the delta of the leg is multiplied by LegOptionRatio and OrderQty to determine the covering quantity.
LegPrice	[0..1]	Price	Used to specify an anchor price for a leg as part of the definition or creation of the strategy - not used for execution price.
LegEvtGrp	[0..*]	Group	
LegInstrumentParties	[0..*]	Group	
LegShortSaleRestriction	[0..1]	CodeSet	
LegComplexEvents	[0..*]	Group	
LegStrategyType	[0..1]	CodeSet	
LegCommonPricingIndicator	[0..1]	Boolean	

Name	Mult.	Type	Description
LegSettlDisruptionProvision	[0..1]	CodeSet	
LegDeliveryRouteOrCharter	[0..1]	String	
LegInstrumentRoundingDirection	[0..1]	CodeSet	
LegInstrumentRoundingPrecision	[0..1]	int	
LegDateAdjustment	[0..1]	Component	
LegPricingDateTime	[0..1]	Component	
LegMarketDisruption	[0..1]	Component	
LegOptionExercise	[0..1]	Component	
LegStreamGrp	[0..*]	Group	
LegProvisionGrp	[0..*]	Group	
LegAdditionalTermGrp	[0..*]	Group	
LegProtectionTermGrp	[0..*]	Group	
LegCashSettlTermGrp	[0..*]	Group	
LegPhysicalSettlTermGrp	[0..*]	Group	
LegExtraordinaryEventGrp	[0..*]	Group	
LegExtraordinaryEventAdjustment-Method	[0..1]	CodeSet	
LegExchangeLookAlike	[0..1]	Boolean	

Used in groups: InstrmtLegExecGrp, InstrmtLegGrp, InstrmtLegIOIGrp, InstrmtLegSecListGrp, LegOrdGrp, LegQuotGrp, LegQuotStatGrp, QuotReqLegsGrp, SecLstUpdRelSymsLegGrp, TrdInstrmtLegGrp

### 180.2.1203 InstrumentParties

The use of this component block is restricted to instrument definition only and is not permitted to contain transactional information. Only a specified subset of party roles will be supported within the InstrumentParty block.

Name	Mult.	Type	Description
NoInstrumentParties	[1..1]	NumInGroup	Repeating group below should contain unique combinations of InstrumentPartyID(1019), InstrumentPartyIDSource(1050) and InstrumentPartyRole(1051).
InstrumentPartyID	[0..1]	String	Required if NoInstrumentParties(1018) > 0. Identification of the party.

Name	Mult.	Type	Description
InstrumentPartyIDSource	[0..1]	CodeSet	Required if NoInstrumentParties(1018) > 0. Used to identify classification source.
InstrumentPartyRole	[0..1]	CodeSet	Required if NoInstrumentParties(1018) > 0. Identifies the type of InstrumentPartyID(1019).
InstrumentPartyRoleQualifier	[0..1]	CodeSet	
InstrumentPtySubGrp	[0..*]	Group	Repeating group of party sub-identifiers.

Used in components: **Instrument**

#### 180.2.1204 InstrumentPartyID

PartyID value within an instrument party repeating group. Same values as PartyID (448)

Type: **String**

Used in groups: **InstrumentParties**

#### 180.2.1205 InstrumentPartyIDSource

PartyIDSource value within an instrument partyrepeating group.

Same values as PartyIDSource (447)

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID

Code	Name	Description
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.

Code	Name	Description
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **InstrumentParties**

### 180.2.1206 InstrumentPartyRole

PartyRole value within an instrument party repeating group.

Same values as PartyRole (452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)

Code	Name	Description
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm

Code	Name	Description
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)



Code	Name	Description
71	CompetentAuthorityTransactionV- enue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm

Code	Name	Description
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)

Code	Name	Description
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **InstrumentParties**

### 180.2.1207 InstrumentPartyRoleQualifier

Used to further qualify the value of InstrumentPartyRole(1051).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal

Code	Name	Description
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.

Code	Name	Description
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **InstrumentParties**

#### **180.2.1208 InstrumentPartySubID**

PartySubID value within an instrument party repeating group.

Same values as PartySubID (523)

Type: **String**

Used in groups: **InstrumentPtysSubGrp**

#### **180.2.1209 InstrumentPartySubIDType**

Type of InstrumentPartySubID (1053) value.

Same values as PartySubIDType (803)

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier

Code	Name	Description
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account

Code	Name	Description
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.



Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **InstrumentPtysSubGrp**

**180.2.1210 InstrumentPricePrecision**

Specifies the number of decimal places for instrument prices.

Type: **int**

Used in components: **Instrument**

**180.2.1211 InstrumentPtysSubGrp**

---

Name	Mult.	Type	Description
NoInstrumentPartySubIDs	[1..1]	NumInGroup	
InstrumentPartySubID	[0..1]	String	
InstrumentPartySubIDType	[0..1]	CodeSet	

---

Used in groups: **InstrumentParties**

**180.2.1212 InstrumentRoundingDirection**

Specifies the rounding direction if not overridden elsewhere.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

---

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

---

Used in components: **Instrument**

**180.2.1213 InstrumentRoundingPrecision**

Specifies the rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **Instrument**

**180.2.1214 InstrumentScopeCFIcode**

Used to limit instrument scope to specified CFIcode.

See CFIcode(461) field for description.

Type: **String**

Used in components: **InstrumentScope**

**180.2.1215 InstrumentScope**

Used to specify the instrument

Name	Mult.	Type	Description
InstrumentScopeSymbol	[0..1]	String	
InstrumentScopeSymbolSfx	[0..1]	CodeSet	
InstrumentScopeSecurityID	[0..1]	String	
InstrumentScopeSecurityIDSource	[0..1]	CodeSet	
InstrumentScopeSecurityAltIDGrp	[0..*]	Group	
InstrumentScopeProduct	[0..1]	CodeSet	
InstrumentScopeProductComplex	[0..1]	String	
InstrumentScopeSecurityGroup	[0..1]	String	
InstrumentScopeCFIcode	[0..1]	String	
InstrumentScopeUPIcode	[0..1]	String	
InstrumentScopeSecurityType	[0..1]	CodeSet	
InstrumentScopeSecuritySubType	[0..1]	String	
InstrumentScopeMaturityMonthYear	[0..1]	MonthYear	
InstrumentScopeMaturityTime	[0..1]	TZTimeOnly	
InstrumentScopeRestructuringType	[0..1]	String	
InstrumentScopeSeniority	[0..1]	String	
InstrumentScopePutOrCall	[0..1]	CodeSet	
InstrumentScopeFlexibleIndicator	[0..1]	Boolean	
InstrumentScopeCouponRate	[0..1]	Percentage	
InstrumentScopeSecurityExchange	[0..1]	Exchange	
InstrumentScopeSecurityDesc	[0..1]	String	
InstrumentScopeEncodedSecurityDescLen	[0..1]	Length	

Name	Mult.	Type	Description
InstrumentScopeEncodedSecurity-Desc	[0..1]	data	
InstrumentScopeSettlType	[0..1]	CodeSet	Can be used to specify FX tenors.

Used in groups: [InstrumentScopeGrp](#), [RiskInstrumentScopeGrp](#)

Used in messages: [PartyActionReport](#), [PartyActionRequest](#), [SecurityMassStatus](#), [SecurityMassStatus-Request](#)

#### **180.2.1216 InstrumentScopeCouponRate**

Used to limit instrument scope to specified coupon rate.

See [CouponRate\(223\)](#) field for description.

Type: [Percentage](#)

Used in components: [InstrumentScope](#)

#### **180.2.1217 InstrumentScopeEncodedSecurityDesc**

Encoded (non-ASCII characters) representation of the [InstrumentScopeSecurityDesc\(1556\)](#) field in the encoded format specified via the [MessageEncoding\(347\)](#) field. If used, the ASCII (English) representation should also be specified in the [InstrumentScopeSecurityDesc\(1556\)](#) field.

Type: [data](#)

Used in components: [InstrumentScope](#)

#### **180.2.1218 InstrumentScopeEncodedSecurityDescLen**

Byte length of encoded (non-ASCII characters) [InstrumentScopeEncodedSecurityDesc \(1621\)](#) field

Type: [Length](#)

Used in components: [InstrumentScope](#)

**180.2.1219 InstrumentScopeFlexibleIndicator**

Used to limit instrument scope to securities that can be defined using flexible terms or not.

See FlexibleIndicator(1244) field for description.

Type: **Boolean**

Used in components: **InstrumentScope**

**180.2.1220 InstrumentScopeGrp**

Repeating group of InstrumentScope Components. Used to specify the instruments to which a request applies.

Name	Mult.	Type	Description
<b>NoInstrumentScopes</b>	[1..1]	NumInGroup	
<b>InstrumentScopeOperator</b>	[0..1]	CodeSet	Required when NoInstrumentScopes > 0.
<b>InstrumentScope</b>	[0..1]	Component	

Used in groups: **EntitlementGrp**, **TestScenarioGrp**

Used in messages: **MarketDefinition**, **MarketDefinitionUpdateReport**, **PartyEntitlementsRequest**

**180.2.1221 InstrumentScopeMaturityMonthYear**

Used to limit instrument scope to specified maturity month and year.

See MaturityMonthYear(200) field for description.

Type: **MonthYear**

Used in components: **InstrumentScope**

**180.2.1222 InstrumentScopeMaturityTime**

Used to limit instrument scope to specified maturity time.

See MaturityTime(1079) field for description.

Type: **TZTimeOnly**

Used in components: **InstrumentScope**

**180.2.1223 InstrumentScopeOperator**

Operator to perform on the instrument(s) specified

Type: **int**

Allowed values in InstrumentScopeOperatorCodeSet:

Code	Name	Description
1	Include	Include
2	Exclude	Exclude

Used in groups: **InstrumentScopeGrp**, **RiskInstrumentScopeGrp**

**180.2.1224 InstrumentScopeProduct**

Used to limit instrument scope to specified instrument product category.

See Product (460) field for description.

Type: **int**

Allowed values in ProductCodeSet:

Code	Name	Description
1	AGENCY	AGENCY
2	COMMODITY	COMMODITY
3	CORPORATE	CORPORATE
4	CURRENCY	CURRENCY
5	EQUITY	EQUITY
6	GOVERNMENT	GOVERNMENT
7	INDEX	INDEX
8	LOAN	LOAN
9	MONEYMARKET	MONEYMARKET
10	MORTGAGE	MORTGAGE
11	MUNICIPAL	MUNICIPAL
12	OTHER	OTHER
13	FINANCING	FINANCING

Used in components: **InstrumentScope**



**180.2.1225 InstrumentScopeProductComplex**

Used to limit instrument scope to specified product complex.

See ProductComplex(1227) field for description.

Type: **String**

Used in components: **InstrumentScope**

**180.2.1226 InstrumentScopePutOrCall**

Used to limit instrument scope to puts or calls.

See PutOrCall(201) field for description.

Type: **int**

Allowed values in PutOrCallCodeSet:

Code	Name	Description
0	Put	Put. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate receiver or into a CDS contract as a seller of protection or for the case of a Floor.
1	Call	Call. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate payer or into a CDS contract as a buyer of protection or for the case of a Cap.
2	Other	Other. In the context of ESMA RTS 22 reporting, this value may be used when, at the time of execution, the option right cannot be determined.
3	Chooser	Chooser. Indicates that the option buyer may choose to buy or sell the underlying security on exercise or if a Swaption to pay or receive the underlying IRS cash flow stream or to buy or sell CDS protection.

Used in components: **InstrumentScope**

**180.2.1227 InstrumentScopeRestructuringType**

Used to limit instrument scope to specified restructuring type.

See RestructuringType(1449) field for description.

Type: **String**

Used in components: **InstrumentScope**

#### **180.2.1228 InstrumentScopeSecurityAltID**

Used to limit instrument scope to specified security alternate identifier.

See SecurityAltID(455) field for description.

Type: **String**

Used in groups: **InstrumentScopeSecurityAltIDGrp**

#### **180.2.1229 InstrumentScopeSecurityAltIDGrp**

Alternative SecurityIDs for an instrument specified in the InstrumentScope.

Name	Mult.	Type	Description
NoInstrumentScopeSecurityAltID	[1..1]	NumInGroup	
InstrumentScopeSecurityAltID	[0..1]	String	Required when NoInstrumentScopeSecurityAltID > 0.
InstrumentScopeSecurityAltIDSource	[0..1]	CodeSet	Required when NoInstrumentScopeSecurityAltID > 0.

Used in components: **InstrumentScope**

#### **180.2.1230 InstrumentScopeSecurityAltIDSource**

Used to limit instrument scope to specified security alternate identifier source.

See SecurityAltIDSource(456) field for complete definition.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP

Code	Name	Description
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".

Code	Name	Description
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **InstrumentScopeSecurityAltIDGrp**

#### **180.2.1231 InstrumentScopeSecurityDesc**

Used to limit instrument scope to specified security description.

See SecurityDesc(107) field for description.

Type: **String**

Used in components: **InstrumentScope**

#### **180.2.1232 InstrumentScopeSecurityExchange**

Used to limit instrument scope to specified security exchange.

See SecurityExchange(207) field for description.

Type: **Exchange**

Used in components: **InstrumentScope**

#### **180.2.1233 InstrumentScopeSecurityGroup**

Used to limit instrument scope to specified security group.

See SecurityGroup(1151) field for description.

Type: **String**

Used in components: **InstrumentScope**

#### **180.2.1234 InstrumentScopeSecurityID**

Used to limit instrument scope to specified security identifier.

See SecurityID(48) field for description.

Type: **String**

Used in components: **InstrumentScope**

**180.2.1235 InstrumentScopeSecurityIDSource**

Used to limit instrument scope to specified security identifier source.

See SecurityIDSource(22) field for description.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **InstrumentScope**

#### 180.2.1236 InstrumentScopeSecuritySubType

Used to limit instrument scope to specified security sub-type.

See SecuritySubType(762) field for description.

Type: **String**

Used in components: **InstrumentScope**

#### 180.2.1237 InstrumentScopeSecurityType

Used to limit instrument scope to specified security type.

See SecurityType(167) field for description).

Type: **String**

Allowed values in SecurityTypeCodeSet:

Code	Name	Description
ABS	AssetBackedSecurities	Asset-backed Securities
AN	OtherAnticipationNotes	Other Anticipation Notes (BAN, GAN, etc.)
BA	BankersAcceptance	Bankers Acceptance

Code	Name	Description
BRADY	BradyBond	Brady Bond
CORP	CorporateBond	Corporate Bond
CS	CommonStock	Common Stock
EUSUPRA	EuroSupranationalCoupons	Euro Supranational Coupons. Identify the issuer name in Issuer(106).
FOR	ForeignExchangeContract	Foreign Exchange Contract
MF	MutualFund	Mutual Fund
REPO	Repurchase	Repurchase
TERM	TermLoan	Term Loan
BDN	BankDepositoryNote	Bank Depository Note
CAN	CanadianTreasuryNotes	Canadian Treasury Notes
CAP	Cap	Cap. In an interest rate cap, the buyer receives payments at the end of each period in which the rate indec exceeds the agreed strike rate.
CMB	CanadianMortgageBonds	Canadian Mortgage Bonds
COFO	CertificateOfObligation	Certificate Of Obligation
CPP	CorporatePrivatePlacement	Corporate Private Placement
FAC	FederalAgencyCoupon	Federal Agency Coupon
FORWARD	Forward	Forward
FXNDF	NonDeliverableForward	Non-deliverable forward
MLEG	MultilegInstrument	Multileg Instrument
PS	PreferredStock	Preferred Stock
RVLV	RevolverLoan	Revolver Loan
BN	BankNotes	Bank Notes
BUYSELL	BuySellback	Buy Sellback
CB	ConvertibleBond	Convertible Bond
CDS	CreditDefaultSwap	Credit Default Swap
CMBS	Corp	Corp. Mortgage-backed Securities
COFP	CertificateOfParticipation	Certificate Of Participation
CTB	CanadianTreasuryBills	Canadian Treasury Bills
DR	DepositoryReceipts	Depository Receipts
FADN	FederalAgencyDiscountNote	Federal Agency Discount Note
FXSPOT	FXSpot	FX Spot
NONE	NoSecurityType	No Security Type
RVLVTRM	Revolver	Revolver/Term Loan

Code	Name	Description
BOX	BillOfExchanges	Bill Of Exchanges
BRIDGE	BridgeLoan	Bridge Loan
CLLR	Collar	Collar. In an interest rate collar, this is a combination of a cap and a floor.
CMO	CollateralizedMortgageObligation	Collateralized Mortgage Obligation
DUAL	DualCurrency	Dual Currency
EUSOV	EuroSovereigns	Euro Sovereigns. Identify the issuer name in Issuer(106).
FXFWD	FXForward	FX Forward
GO	GeneralObligationBonds	General Obligation Bonds
PEF	PrivateExportFunding	Private Export Funding. Identify the issuer name in Issuer(106).
SECLOAN	SecuritiesLoan	Securities Loan
UST	USTreasuryNoteOld	US Treasury Note (Deprecated Value Use TNOTE)
CAMM	CanadianMoneyMarkets	Canadian Money Markets
CMDTYSWAP	CommoditySwap	Commodity swap
EUCORP	EuroCorporateBond	Euro Corporate Bond
FXSWAP	FXSwap	FX Swap
IET	IOETTEMortgage	IOETTE Mortgage
LOFC	LetterOfCredit	Letter Of Credit
MT	MandatoryTender	Mandatory Tender
PROV	CanadianProvincialBonds	Canadian Provincial Bonds
SECPLEDGE	SecuritiesPledge	Securities Pledge
SUPRA	USDSupranationalCoupons	USD Supranational Coupons. Identify the issuer name in Issuer(106).
USTB	USTreasuryBillOld	US Treasury Bill (Deprecated Value Use TBILL)
?	Wildcard	Wildcard entry for use on Security Definition Request
CD	CertificateOfDeposit	Certificate Of Deposit
DVPLDG	DeliveryVersusPledge	Delivery versus pledge
EUFRN	EuroCorporateFloatingRateNotes	Euro Corporate Floating Rate Notes
EXOTIC	Exotic	Exotic
FXNDS	NonDeliverableSwap	Non-deliverable Swap
MBS	MortgageBackedSecurities	Mortgage-backed Securities
RAN	RevenueAnticipationNote	Revenue Anticipation Note
SWING	SwingLineFacility	Swing Line Facility
TB	TreasuryBill	Treasury Bill - non US
CASH	Cash	Cash



Code	Name	Description
CL	CallLoans	Call Loans
COLLSKT	CollateralBasket	Collateral basket. A collection of securities held as collateral in the customer's collateral fund. The collateral fund is usually managed by a custodian.
DINP	DebtorInPossession	Debtor In Possession
FLR	Floor	Floor. In an interest rate floor, the buyer receives payments at the end of each period in which the rate index is below the agreed strike rate.
FRN	USCorporateFloatingRateNotes	US Corporate Floating Rate Notes
FXBN	FXBankNote	FX Bank Note
MIO	MortgageInterestOnly	Mortgage Interest Only
OOC	OptionsOnCombo	Options on Combo
REV	RevenueBonds	Revenue Bonds
TBOND	USTreasuryBond	US Treasury Bond
CP	CommercialPaper	Commercial Paper
DEFLTED	Defaulted	Defaulted
FRA	FRA	Forward Rate Agreement
FXDN	ForeignCurrencyDiscountNote	Foreign Currency Discount Note. Discount notes issued in foreign currency by Fannie Mae.
MPO	MortgagePrincipalOnly	Mortgage Principal Only
Other	Other	Other
SFP	StructuredFinanceProduct	Structured finance product
SPCLA	SpecialAssessment	Special Assessment
TINT	InterestStripFromAnyBondOrNote	Interest Strip From Any Bond Or Note
XLINKD	IndexedLinked	Indexed Linked
DN	DepositNotes	Deposit Notes
ETN	ExchangeTradedNote	Exchange traded note
FUT	Future	Future
MPP	MortgagePrivatePlacement	Mortgage Private Placement
SPCLO	SpecialObligation	Special Obligation
STRUCT	StructuredNotes	Structured Notes
TBILL	USTreasuryBill	US Treasury Bill
TIPS	TreasuryInflationProtectedSecurities	Treasury Inflation Protected Securities
WITHDRN	Withdrawn	Withdrawn
EUCD	EuroCertificateOfDeposit	Euro Certificate Of Deposit

Code	Name	Description
FWD	DerivativeForward	Derivative forward
MPT	MiscellaneousPassThrough	Miscellaneous Pass-through
MGRNLOAN	MarginLoan	Margin loan
REPLACD	Replaced	Replaced
SPCLT	SpecialTax	Special Tax
TCAL	PrincipalStripOfACallableBondOrNote	Principal Strip Of A Callable Bond Or Note
YANK	YankeeCorporateBond	Yankee Corporate Bond
DIMSUMCORP	OffshoreIssuedChineseYuanCorporateBond	Offshore issued Chinese Yuan (CNY) denominated corporate bond
EUCP	EuroCommercialPaper	Euro Commercial Paper
IRS	InterestRateSwap	Interest Rate Swap
MATURED	Matured	Matured
PFAND	Pfandbrief	Pfandbrief. Identify the issuer name in Issuer(106).
SECDERIV	SecuritizedDerivative	Securitized derivative
TAN	TaxAnticipationNote	Tax Anticipation Note
TPRN	PrincipalStripFromANonCallableBondOrNote	Principal Strip From A Non-Callable Bond Or Note
TRS	TotalReturnSwap	Total return swap
AMENDED	Amended	Amended and restated
ETF	ExchangeTradedFund	Exchange Traded Fund
LOANLEASE	LoanLease	Loan/lease
LQN	LiquidityNote	Liquidity Note
PRCORP	PreferredCorporateBond	Preferred Corporate Bond
TAXA	TaxAllocation	Tax Allocation
TBA	ToBeAnnounced	To Be Announced
TNOTE	USTreasuryNote	US Treasury Note
DIGITAL	DigitalAsset	Digital Asset. Asset that exists only in digital form or which is the digital representation of another asset (Source: ISO 24165 - Terms and Definitions).
DIMSUMSOV	OffshoreIssuedChineseYuanSovereignBond	Offshore issued Chinese Yuan (CNY) denominated sovereign bond
MTN	MediumTermNotes	Medium Term Notes
RETIRED	Retired	Retired
TECP	TaxExemptCommercialPaper	Tax Exempt Commercial Paper
ONITE	Overnight	Overnight

Code	Name	Description
OOF	OptionsOnFutures	Options on Futures
SOV	SovereignBond	Sovereign Bond. Sovereign or government bond other than Euro and US issuer. Specify sovereign issuer in Issuer(106).
TMCP	TaxableMunicipalCP	Taxable Municipal CP
OOP	OptionsOnPhysical	Options on Physical - use not recommended
PN	PromissoryNote	Promissory Note
STN	ShortTermLoanNote	Short Term Loan Note
TFRN	USTreasuryFloatingRateNote	US Treasury Floating Rate Note
TRAN	TaxRevenueAnticipationNote	Tax Revenue Anticipation Note
OPT	Option	Option
PZFJ	PlazosFijos	Plazos Fijos
VRDN	VariableRateDemandNote	Variable Rate Demand Note
SLQN	SecuredLiquidityNote	Secured Liquidity Note
SPOTFWD	SpotForward	Spot forward
WAR	Warrant	Warrant
MCPIB	MunicipalInterestBearingCommercialPaper	Municipal Interest Bearing Commercial Paper
SWAPTION	SwapOption	Swap option
TD	TimeDeposit	Time Deposit
TMB	TaxableMunicipalBond	Taxable Municipal Bond
XMISSION	Transmission	Transmission
INDEX	Index	General type for a contract based on an established index
TLQN	TermLiquidityNote	Term Liquidity Note
VRDO	VariableRateDemandObligation	Variable Rate Demand Obligation
BDBSKT	BondBasket	Bond basket
XCN	ExtendedCommNote	Extended Comm Note
CFD	ContractForDifference	Contract for difference
YCD	YankeeCertificateOfDeposit	Yankee Certificate Of Deposit
BAB	BankAcceptedBill	Bank Accepted Bill. Also known as Bank Bill.
CRLTNSWAP	CorrelationSwap	Correlation swap
BNST	ShortTermBankNote	Short Term Bank Note
DVDNDSWAP	DividendSwap	Dividend swap
CLCP	CallableCommercialPaper	Callable Commercial Paper
EQBSKT	EquityBasket	Equity basket
CN	CommercialNote	Commercial Note

Code	Name	Description
EQFWD	EquityForward	Equity forward
CPIB	InterestBearingCommercialPaper	Interest Bearing Commercial Paper
RTRNSWAP	ReturnSwap	Return swap
EUMTN	EuroMediumTermNote	Euro Medium Term Note
VARSWAP	VarianceSwap	Variance swap
EUNCP	EuroNegotiableCommercialPaper	Euro Negotiable Commercial Paper
PRTFLIOSWAP	PortfolioSwaps	Portfolio swap
EUSTLQN	EuroStructuredLiquidityNote	Euro Structured Liquidity Note
FUTSWAP	FuturesOnASwap	Futures on a Swap
EUTD	EuroTimeDeposit	Euro Time Deposit
FWDSWAP	ForwardsOnASwap	Forwards on a Swap
FWDFRTAGMT	ForwardFreightAgreement	Forward Freight Agreement
JCD	JumboCertificateOfDeposit	Jumbo Certificate of Deposit
MMF	MoneyMarketFund	Money Market Fund
SPREADBET	SpreadBetting	Spread Betting
ETC	ExchangeTradedCommodity	Exchange traded commodity
MN	MasterNote	Master Note. Short term notes issued by Federal Farm Credit Banks Funding Corporation to provide loans and funding under Federal Farm Credit System (FFCS).
NCD	NegotiableCertificateOfDeposit	Negotiable Certificate of Deposit
NCP	NegotiableCommercialPaper	Negotiable Commercial Paper
RCD	RetailCertificateOfDeposit	Retail Certificate of Deposit
TDR	TermDepositReceipt	Term Deposit Receipt

Used in components: **InstrumentScope**

### 180.2.1238 InstrumentScopeSeniority

Used to limit instrument scope to specified seniority type.

See Seniority(1450) field for description.

Type: **String**

Used in components: **InstrumentScope**

**180.2.1239 InstrumentScopeSettlType**

Used to limit instrument scope to specified settlement type.

See SettlType(63) field for description.

Type: **String**

Allowed values in SettlTypeCodeSet:

Code	Name	Description
0	Regular	Regular / FX Spot settlement (T+1 or T+2 depending on currency)
1	Cash	Cash (TOD / T+0)
2	NextDay	Next Day (TOM / T+1)
3	TPlus2	T+2
4	TPlus3	T+3
5	TPlus4	T+4
6	Future	Future
7	WhenAndIfIssued	When And If Issued
8	SellersOption	Sellers Option
9	TPlus5	T+5
B	BrokenDate	Broken date. Use within FX to specify a non-standard tenor. The use of SettlDate(64) is required to specify the actual settlement date when SettlType(63) = B (Broken date).
C	FXSpotNextSettlement	FX Spot Next settlement (Spot+1, aka next day)

Used in components: **InstrumentScope**

**180.2.1240 InstrumentScopeSymbol**

Used to limit instrument scope to specified symbol.

See Symbol(55) field for description.

Type: **String**

Used in components: **InstrumentScope**

**180.2.1241 InstrumentScopeSymbolSfx**

Used to limit instrument scope to specified symbol suffix.

See SymbolSfx(65) field for description.

Type: **String**

Allowed values in SymbolSfxCodeSet:

Code	Name	Description
CD	EUCPWithLumpSumInterest	EUCP with lump-sum interest rather than discount price
WI	WhenIssued	"When Issued" for a security to be reissued under an old CUSIP or ISIN

Used in components: **InstrumentScope**

**180.2.1242 InstrumentScopeUPICode**

Uniquely identifies the product of a security using ISO 4914 as filter criteria. See UPICode(2891) for further detail.

Type: **String**

Used in components: **InstrumentScope**

**180.2.1243 InterestAccrualDate**

The start date used for calculating accrued interest on debt instruments which are being sold between interest payment dates. Often but not always the same as the Issue Date and the Dated Date

Type: **LocalMktDate**

Used in components: **Instrument**

**180.2.1244 InterestAtMaturity**

Amount of interest (i.e. lump-sum) at maturity.

Type: **Amt**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#), [ExecutionReport](#)

### **180.2.1245 InternationalSwapIndicator**

Identifies the swap trade as an "international" transaction.

Type: [Boolean](#)

Used in messages: [TradeCaptureReport](#)

### **180.2.1246 InTheMoneyCondition**

Specifies an option instrument's "in the money" condition.

Type: [int](#)

Allowed values in InTheMoneyConditionCodeSet:

Code	Name	Description
0	StandardITM	Standard in-the-money. The option's strike price is less than the underlying settlement price for a call or greater than the underlying settlement price for a put.
1	ATMITM	At-the-money is in-the-money. The option's strike price of either the put or call is equal to the underlying settlement price in addition to standard in-the-money behavior.
2	ATMCallITM	At-the-money call is in-the-money. The call option's strike price is equal to the underlying settlement price in addition to standard in-the-money behavior.
3	ATMPutITM	At-the-money put is in-the-money. The put option's strike price is equal to the underlying settlement price in addition to standard in-the-money behavior.

Used in components: [Instrument](#)

### **180.2.1247 IntraFirmTradeIndicator**

Indicates whether the trade or position was entered into as an intra-group transaction, i.e. between two units of the same parent entity having majority ownership interest in both counterparties.

Type: [Boolean](#)

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **PositionReport**, **TradeCaptureReport**

#### **180.2.1248 InvestorCountryOfResidence**

The ISO 3166 Country code (2 character) identifying which country the beneficial investor is resident for tax purposes.

Type: **Country**

Used in groups: **RgstDtIsGrp**

#### **180.2.1249 InViewOfCommon**

Indicates whether or not the halt was due to Common Stock trading being halted.

Type: **Boolean**

Allowed values in InViewOfCommonCodeSet:

Code	Name	Description
N	HaltWasNotRelatedToA-HaltOfTheCommonStock	Halt was not related to a halt of the common stock
Y	HaltWasDueToCommonStockBeing-Halted	Halt was due to common stock being halted

Used in messages: **SecurityStatus**

#### **180.2.1250 IOIID**

Unique identifier of IOI message.

(Prior to FIX 4.1 this field was of type int)

Type: **String**

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest**, **IOI**, **MultilegOrderCancelReplace**, **NewOrder-Cross**, **NewOrderMultileg**, **NewOrderSingle**, **QuoteResponse**



**180.2.1251 IOINaturalFlag**

Indicates that IOI is the result of an existing agency order or a facilitation position resulting from an agency order, not from principal trading or order solicitation activity.

Type: **Boolean**

Allowed values in IOINaturalFlagCodeSet:

Code	Name	Description
N	NotNatural	Not Natural
Y	Natural	Natural

Used in messages: **IOI**

**180.2.1252 IOIQltyInd**

Relative quality of indication

Type: **char**

Allowed values in IOIQltyIndCodeSet:

Code	Name	Description
H	High	High
L	Low	Low
M	Medium	Medium

Used in messages: **IOI**

**180.2.1253 IOIQty**

Quantity (e.g. number of shares) in numeric form or relative size.

Type: **String**

Allowed values in IOIQtyCodeSet:

Code	Name	Description
S	Small	Small
M	Medium	Medium
L	Large	Large
U	UndisclosedQuantity	Undisclosed Quantity

Used in messages: **IOI**

### 180.2.1254 IOIQualGrp

Name	Mult.	Type	Description
NoIOIQualifiers	[1..1]	NumInGroup	Required if any IOIQualifiers are specified. Indicates the number of repeating IOIQualifiers.
IOIQualifier	[0..1]	CodeSet	Required if NoIOIQualifiers > 0

Used in messages: **IOI**

### 180.2.1255 IOIQualifier

Code to qualify IOI use. (see Volume : "Glossary" for value definitions)

Type: **char**

Allowed values in IOIQualifierCodeSet:

Code	Name	Description
A	AllOrNone	All or None (AON)
B	MarketOnClose	Market On Close (MOC) (held to close)
C	AtTheClose	At the close (around/not held to close)
D	VWAP	VWAP (Volume Weighted Average Price)
E	Axe	Axe. Indicates that a quote is an Axe, without specifying a side preference. Mutually exclusive with F(Axe on bid) and G(Axe on offer).
F	AxeOnBid	Axe on bid. Indicates that a quote is an Axe, with a preference to execute on the bid side. Mutually exclusive with E(Axe) and G (Axe on offer)

Code	Name	Description
G	AxeOnOffer	Axe on offer. Indicates that a quote is an Axe, with a preference to execute on the offer side. Mutually exclusive with E(Axe) and F (Axe on bid)
H	ClientNaturalWorking	Client natural working. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type C2 – Client Natural (Working). A client should be able to seek verification (from IOI publisher's management/compliance) that, for any C2 IOIs received, there was a corresponding live client order for at least the advertised size prior to the IOI being generated. Resulting trades are expected to be of a riskless nature.
I	InTouchWith	In touch with. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type P1 - Potential. Post-execution, a client should be able to seek verification (from IOI publisher's management/ compliance) that, for any P1 IOIs received and executed against, there was by time of the execution, an opposing specific client order. Resulting trades are expected to be of a riskless nature. If the anticipated client order does not materialise, and the broker elects to commit capital, this must be disclosed prior to execution.
J	PositionWanted	Position wanted. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type H2 – Position Wanted. Brokers will be likely be sourcing liquidity and therefore may advertise the size of IOI they wish; however, clients can expect the broker to honour the size of IOI shown. The presumption is that there is no intent to immediately unwind the position without notification, however, brokers may provide additional granularity to the category and may offer bilateral post trade commitments. Brokers will also offer clients a feedback mechanism.
K	MarketMaking	Market making. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type H3 – Market Making, no enforcement is required.
L	Limit	Limit
M	MoreBehind	More Behind

Code	Name	Description
N	ClientNaturalBlock	Client natural block. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type C1 - Client Natural (Block). A client should be able to seek verification (from IOI publisher's management/compliance) that, for any C1 IOIs received, there was a corresponding live client order for at least the advertised size prior to the IOI being generated. Resulting trades are expected to be of a riskless nature.
O	AtTheOpen	At the Open
P	TakingAPosition	Taking a Position
Q	AtTheMarket	At the Market (previously called Current Quote)
R	ReadyToTrade	Ready to Trade
S	PortfolioShown	Inventory or Portfolio Shown
T	ThroughTheDay	Through the Day
U	Unwind	Unwind. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type H1 - Unwind. Brokers will be responsible for ensuring that the size of the IOI reflects the actual house position in the relevant business unit and should not inflate the size of the IOI. The presumption is that there is no intent to immediately replace the position without notification, however, brokers may provide additional granularity to the category and may offer bilateral post trade commitments. Brokers will also offer clients a feedback mechanism.
V	Versus	Versus
W	Indication	Indication - Working Away
X	CrossingOpportunity	Crossing Opportunity
Y	AtTheMidpoint	At the Midpoint
Z	PreOpen	Pre-open
1	QuantityNegotiable	Quantity is negotiable. When specified, the dealer may counter with a reduced quantity in its Quotes in response to QuoteRequest(35=R). All-or-none if omitted.
2	AllowLateBids	Allow late bids. When specified in QuoteRequest(35=R) the dealer may submit quotes after curtain time has elapsed.
3	ImmediateOrCounter	Immediate or counter. When specified, the buy-side customer is permitted to counter a firm quote during wiretime.
4	AutoTrade	Auto trade. Trade is in an auto-trading mode whereby the best quote that satisfies user criteria as determined by the trading platform will be accepted automatically.

Code	Name	Description
a	AutomaticSpot	Automatic spot. At completion of price negotiation based on spread the trading platform will propose a benchmark spot price which may be filled immediately by the dealer or countered.
b	PlatformCalculatedSpot	Platform calculated spot. At completion of price negotiation based on spread the trading platform will supply a benchmark spot price and immediately complete the trade reporting fill. There is no dealer last look.
c	OutsideSpread	Outside spread. The IOI is identifiable outside the current bid/offer.
d	DeferredSpot	Deferred spot. At a future time after completion of price negotiation based on spread and reported in StrikeTime(443) the trading platform will propose a benchmark spot price which may be filled immediately by the dealer or countered.
n	NegotiatedSpot	Negotiated spot. Once price negotiation based on spread is completed negotiation of the benchmark spot price proceeds immediately.

Used in groups: **IOIQualGrp**

#### **180.2.1256 IOIRefID**

Reference identifier used with CANCEL and REPLACE, transaction types.

(Prior to FIX 4.1 this field was of type int)

Type: **String**

Used in messages: **IOI**

#### **180.2.1257 IOITransType**

Identifies IOI message transaction type

Type: **char**

Allowed values in IOITransTypeCodeSet:

Code	Name	Description
N	New	New
C	Cancel	Cancel
R	Replace	Replace

Used in messages: **IOI**

### 180.2.1258 IRSDirection

Used to specify whether the principal is paying or receiving the fixed rate in an interest rate swap.

Type: **String**

Allowed values in IRSDirectionCodeSet:

Code	Name	Description
PAY	Pay	Principal is paying fixed rate.
RCV	Rcv	Principal is receiving fixed rate
NA	NA	Swap is float/float or fixed/fixed

Used in messages: **TradeCaptureReport**

### 180.2.1259 IssueDate

The date on which a bond or stock offering is issued. It may or may not be the same as the effective date ("Dated Date") or the date on which interest begins to accrue ("Interest Accrual Date")

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCDate)

Type: **LocalMktDate**

Used in components: **Instrument**

### 180.2.1260 Issuer

Name of security issuer (e.g. International Business Machines, GNMA).

see also Volume 7: "PRODUCT: FIXED INCOME - Euro Issuer Values"

Type: **String**

Used in components: **Instrument**

### **180.2.1261 LanguageCode**

The national language in which the news item is provided.

Type: **Language**

Used in messages: **News**

### **180.2.1262 LastCapacity**

Broker capacity in order execution

Type: **char**

Allowed values in LastCapacityCodeSet:

Code	Name	Description
1	Agent	Agent
2	CrossAsAgent	Cross as agent
3	CrossAsPrincipal	Cross as principal
4	Principal	Principal
5	RisklessPrincipal	Riskless principal

Used in groups: **ExecAllocGrp**, **TrdCapRptSideGrp**

Used in messages: **ExecutionReport**

### **180.2.1263 LastForwardPoints**

F/X forward points added to LastSpotRate(194). May be a negative value. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199.

Type: **PriceOffset**

Used in messages: **ExecutionReport**, **TradeCaptureReport**, **TradeCaptureReportAck**

**180.2.1264 LastForwardPoints2**

F/X forward points of the future part of a F/X swap order added to LastSpotRate(194). May be a negative value.

Type: **PriceOffset**

Used in messages: **ExecutionReport**

**180.2.1265 LastFragment**

Indicates whether this message is the last in a sequence of messages for those messages that support fragmentation, such as Allocation Instruction, Mass Quote, Security List, Derivative Security List

Type: **Boolean**

Allowed values in LastFragmentCodeSet:

Code	Name	Description
N	NotLastMessage	Not Last Message
Y	LastMessage	Last Message

Used in groups: **QuotSetAckGrp**, **QuotSetGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **DerivativeSecurityList**, **DerivativeSecurityListUpdateReport**, **ExecutionReport**, **ListStatus**, **ListStrikePrice**, **MassOrder**, **MassOrderAck**, **NewOrderList**, **OrderMassActionReport**, **PartyDetailsListReport**, **PartyDetailsListUpdateReport**, **PartyEntitlementsReport**, **PartyEntitlementsUpdateReport**, **PartyRiskLimitsReport**, **PartyRiskLimitsUpdateReport**, **SecurityList**, **SecurityListUpdateReport**, **SecurityRiskMetricsReport**, **SecurityTypes**

**180.2.1266 LastLimitAmt**

The amount that has been drawn down against the counterparty for a given trade. The type of limit is specified in LimitAmtType(1631).

Bilateral agreements dictate the units and maximum value of this field.

Type: **Amt**

Used in groups: **LimitAmts**



**180.2.1267 LastLiquidityInd**

Indicator to identify whether this fill was a result of a liquidity provider providing or liquidity taker taking the liquidity.

Type: **int**

Allowed values in LastLiquidityIndCodeSet:

Code	Name	Description
0	NeitherAddedNorRemovedLiquidity	Neither added nor removed liquidity. May be used by venues where market rules do not define "add" or "remove" liquidity. In the context of the SEC amendment of Regulation NMS Rule 606(b), may be used to identify executions that are only reported as part of total shares executed and not as part of shares providing or removing liquidity (see <a href="https://www.sec.gov/rules/final/2018/34-84528.pdf">https://www.sec.gov/rules/final/2018/34-84528.pdf</a> for details).
1	AddedLiquidity	Added Liquidity
2	RemovedLiquidity	Removed Liquidity
3	LiquidityRoutedOut	Liquidity Routed Out
4	Auction	Auction execution
5	TriggeredStopOrder	Triggered stop order. Fill was the result of a stop order being triggered and immediately executed.
6	TriggeredContingencyOrder	Triggered contingency order. Fill was the result of a contingency order (OCO, OTO, OUO) becoming active (after cancelling or updating another order) and being immediately executed.
7	TriggeredMarketOrder	Triggered market order. Fill was the result of a market order being triggered due to an executable orderbook situation.
8	RemovedLiquidityAfterFirmOrder-Commitment	Removed liquidity after firm order commitment. An order that was submitted for continuous trading that required a firm order commit prior to execution. "Conditional order" is an alternate term used for such orders.
9	AuctionExecutionAfterFirmOrder-Commitment	Auction execution after firm order commitment. An order that was submitted for auction trading that required a firm order commit prior to execution. "Conditional order" is an alternate term used for such orders.
10	Unknown	Unknown. The liquidity indicator of the execution cannot be determined or was not provided upon execution.
11	Other	Other. None of the existing liquidity indicators are applicable for the execution (e.g. due to a venue's new order type that does not fit existing values).

Used in messages: [ExecutionReport](#)

#### **180.2.1268 LastMkt**

Market of execution for last fill, or an indication of the market where an order was routed

Valid values:

See "Appendix 6-C"

Type: [Exchange](#)

Used in groups: [InstrmtMatchSideGrp](#)

Used in messages: [Advertisement](#), [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#), [ExecutionReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.1269 LastMsgSeqNumProcessed**

The last MsgSeqNum (34) value received by the FIX engine and processed by downstream application, such as trading engine or order routing system. Can be specified on every message sent. Useful for detecting a backlog with a counterparty.

Type: [SeqNum](#)

Used in components: [StandardHeader](#)

#### **180.2.1270 LastMultipliedQty**

Expresses the quantity bought or sold when LastQty(32) is expressed in number of contracts. Used in addition to LastQty(32). It is the product of LastQty(32) and ContractMultiplier(231).

Type: [Qty](#)

Used in messages: [TradeCaptureReport](#)

#### **180.2.1271 LastNetworkResponseID**

Identifier of the previous Network Response message sent to a counterparty, used to allow incremental updates.

Type: [String](#)

Used in messages: [NetworkCounterpartySystemStatusResponse](#)

**180.2.1272 LastParPx**

Last price expressed in percent-of-par. Conditionally required for Fixed Income trades when LastPx (31) is expressed in Yield, Spread, Discount or any other type.

Usage: Execution Report and Allocation Report repeating executions block (from sellside).

Type: **Price**

Used in groups: **ExecAllocGrp**

Used in messages: **ExecutionAck, ExecutionReport, TradeCaptureReport, TradeCaptureReportAck**

**180.2.1273 LastPx**

Price of this (last) fill.

Type: **Price**

Used in groups: **ExecAllocGrp, ExecutionAggregationGrp, InstrmtMatchSideGrp, MDFullGrp, MDIncGrp**

Used in messages: **DontKnowTrade, ExecutionAck, ExecutionReport, SecurityStatus, TradeCaptureReport, TradeCaptureReportAck**

**180.2.1274 LastQty**

Quantity (e.g. shares) bought/sold on this (last) fill.

(Prior to FIX 4.2 this field was of type int)

Type: **Qty**

Used in groups: **ExecAllocGrp, ExecutionAggregationGrp, InstrmtMatchSideGrp**

Used in messages: **DontKnowTrade, ExecutionAck, ExecutionReport, TradeCaptureReport, TradeCaptureReportAck**

**180.2.1275 LastQtyChanged**

The positive or negative change in quantity when this report is a trade correction or continuation.

Type: **Qty**

Used in messages: **TradeCaptureReport**

**180.2.1276 LastQtyVariance**

When LastQty is an estimated value, e.g. for a Repo “circled” trade, LastQtyVariance specifies the absolute amount that the size may vary up or down when finalized. Omitted when LastQty(32) is already final.

Type: Qty

Used in messages: ExecutionReport, TradeCaptureReport

**180.2.1277 LastRptRequested**

Indicates whether this message is the last report message in response to a request message, e.g. OrderMassStatusRequest(35=AF), TradeCaptureReportRequest(35=AD).

Type: Boolean

Allowed values in LastRptRequestedCodeSet:

Code	Name	Description
N	NotLastMessage	Not last message
Y	LastMessage	Last message

Used in messages: AssignmentReport, CollateralReport, ExecutionReport, MarginRequirementReport, PositionReport, TradeCaptureReport

**180.2.1278 LastSpotRate**

F/X spot rate.

Type: Price

Used in messages: ExecutionReport, TradeCaptureReport, TradeCaptureReportAck

**180.2.1279 LastSwapPoints**

For FX Swap, this is used to express the last market event for the differential between the far leg's bid/offer and the near leg's bid/offer in a fill or partial fill. Value can be negative. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199

Type: PriceOffset

Used in messages: ExecutionReport, TradeCaptureReport, TradeCaptureReportAck

**180.2.1280 LastUpdateTime**

Timestamp of last update to data item (or creation if no updates made since creation).

Type: **UTCTimestamp**

Used in groups: **SettlInstGrp**, **SettlObligationInstructions**, **TrdCapDtGrp**

Used in messages: **AlgoCertificateReport**, **DerivativeSecurityList**, **DerivativeSecurityListUpdateReport**, **MarketDataSnapshotFullRefresh**, **SecurityDefinition**, **SecurityDefinitionUpdateReport**, **SettlementInstructionRequest**, **TradeCaptureReport**, **TradeCaptureReportAck**

**180.2.1281 LastUpfrontPrice**

Price used to determine upfront payment for swaps contracts reported for a deal (trade).

Type: **Price**

Used in messages: **ExecutionReport**, **TradeCaptureReport**

**180.2.1282 LateIndicator**

Indicates if the contrary intention was received after the exchange imposed cutoff time

Type: **Boolean**

Used in messages: **ContraryIntentionReport**

**180.2.1283 LeavesQty**

Quantity open for further execution. If the OrdStatus (39) is Canceled, DoneForTheDay, Expired, Calculated, or Rejected (in which case the order is no longer active) then LeavesQty could be 0, otherwise  $\text{LeavesQty} = \text{OrderQty} (38) - \text{CumQty} (14)$ .

(Prior to FIX 4.2 this field was of type int)

Type: **Qty**

Used in components: **TradeReportOrderDetail**

Used in groups: **OrdListStatGrp**, **OrderEntryAckGrp**

Used in messages: **ExecutionReport**

**180.2.1284 LegAccount**

Account mnemonic as agreed between buy and sell sides, e.g. broker and institution or investor/intermediary and fund manager.

Type: **String**

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **TrdInstrmtLegGrp**

**180.2.1285 LegAdditionalDividendsIndicator**

Indicates whether additional dividends are applicable.

Type: **Boolean**

Used in components: **LegDividendConditions**

**180.2.1286 LegAdditionalTermBondCouponFrequencyPeriod**

Time unit multiplier for the frequency of the bond's coupon payment.

Type: **int**

Used in groups: **LegAdditionalTermBondRefGrp**

**180.2.1287 LegAdditionalTermBondCouponFrequencyUnit**

Time unit associated with the frequency of the bond's coupon payment.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second

Code	Name	Description
T	Term	Term

Used in groups: [LegAdditionalTermBondRefGrp](#)

#### **180.2.1288 LegAdditionalTermBondCouponRate**

Coupon rate of the bond. See also [CouponRate\(223\)](#).

Type: [Percentage](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

#### **180.2.1289 LegAdditionalTermBondCouponType**

Specifies the coupon type of the bond.

Type: [int](#)

Allowed values in [CouponTypeCodeSet](#):

Code	Name	Description
0	Zero	Zero
1	FixedRate	Fixed rate
2	FloatingRate	Floating rate
3	Structured	Structured

Used in groups: [LegAdditionalTermBondRefGrp](#)

#### **180.2.1290 LegAdditionalTermBondCurrency**

Specifies the currency the bond value is denominated in. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

**180.2.1291 LegAdditionalTermBondCurrentTotalIssuedAmount**

Total issued amount of the bond.

Type: **Amt**

Used in groups: **LegAdditionalTermBondRefGrp**

**180.2.1292 LegAdditionalTermBondDayCount**

The day count convention used in interest calculations for a bond or an interest bearing security.

Type: **int**

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.



Code	Name	Description
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.

Code	Name	Description
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in groups: [LegAdditionalTermBondRefGrp](#)

**180.2.1293 LegAdditionalTermBondDesc**

Description of the bond.

Type: [String](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

**180.2.1294 LegAdditionalTermBondIssuer**

Issuer of the bond.

Type: [String](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

**180.2.1295 LegAdditionalTermBondMaturityDate**

The maturity date of the bond.

Type: [LocalMktDate](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

**180.2.1296 LegAdditionalTermBondParValue**

The par value of the bond.

Type: [Amt](#)

Used in groups: [LegAdditionalTermBondRefGrp](#)

**180.2.1297 LegAdditionalTermBondRefGrp**

The LegAdditionalTermBondRefGrp is a repeating group subcomponent of the LegAdditionalTermGrp component used to identify an underlying reference bond for a swap.

---

Name	Mult.	Type	Description
<a href="#">NoLegAdditionalTermBondRefs</a>	[1..1]	NumInGroup	

---

Name	Mult.	Type	Description
LegAdditionalTermBondSecurityID	[0..1]	String	Required if NoLegAdditionalTermBondRefs(41316) > 0.
LegAdditionalTermBondSecurityID-Source	[0..1]	CodeSet	Conditionally required when LegAdditionalTermBondSecurityID(41317) is specified.
LegAdditionalTermBondDesc	[0..1]	String	
EncodedLegAdditionalTermBondDescLen	[0..1]	Length	Must be set if EncodedLegAdditionalTermBondDesc(41321) field is specified and must immediately precede it.
EncodedLegAdditionalTermBondDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the LegAdditionalTermBondDesc(41319) field in the encoded format specified via the MessageEncoding(347) field.
LegAdditionalTermBondCurrency	[0..1]	Currency	
LegAdditionalTermBondIssuer	[0..1]	String	
EncodedLegAdditionalTermBondIssuerLen	[0..1]	Length	Must be set if EncodedLegAdditionalTermBondIssuer(41325) field is specified and must immediately precede it.
EncodedLegAdditionalTermBondIssuer	[0..1]	data	Encoded (non-ASCII characters) representation of the LegAdditionalTermBondIssuer(41323) field in the encoded format specified via the MessageEncoding(347) field.
LegAdditionalTermBondSeniority	[0..1]	CodeSet	
LegAdditionalTermBondCouponType	[0..1]	CodeSet	
LegAdditionalTermBondCouponRate	[0..1]	Percentage	
LegAdditionalTermBondMaturityDate	[0..1]	LocalMktDate	
LegAdditionalTermBondParValue	[0..1]	Amt	
LegAdditionalTermBondCurrentTotalIssuedAmount	[0..1]	Amt	
LegAdditionalTermBondCouponFrequencyPeriod	[0..1]	int	Conditionally required when LegAdditionalTermBondCouponFrequencyUnit(41333) is specified.
LegAdditionalTermBondCouponFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegAdditionalTermBondCouponFrequencyPeriod(41332) is specified.
LegAdditionalTermBondDayCount	[0..1]	CodeSet	

Used in groups: LegAdditionalTermGrp

**180.2.1298 LegAdditionalTermBondSecurityID**

Security identifier of the bond.

Type: **String**

Used in groups: **LegAdditionalTermBondRefGrp**

**180.2.1299 LegAdditionalTermBondSecurityIDSource**

Identifies the source scheme of the LegAdditionalTermBondSecurityID(41317) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit

Code	Name	Description
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **LegAdditionalTermBondRefGrp**

### 180.2.1300 LegAdditionalTermBondSeniority

Specifies the bond's payment priority in the event of a default.

Type: **String**

Allowed values in SeniorityCodeSet:

Code	Name	Description
SD	SeniorSecured	Senior Secured
SR	Senior	Senior
SB	Subordinated	Subordinated
JR	Junior	Junior. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
MZ	Mezzanine	Mezzanine. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".

Code	Name	Description
SN	SeniorNonPreferred	Senior Non-Preferred. For CDS reference obligations of non-preferred senior debt issued by European Financials that constitute a layer of debt ranking between the bank's normal senior debt but above the bank's normal tier 2 subordinated debt (reference: ISDA Credit Market Infrastructure Group).

Used in groups: [LegAdditionalTermBondRefGrp](#)

### 180.2.1301 LegAdditionalTermConditionPrecedentBondIndicator

Indicates whether the condition precedent bond is applicable. The swap contract is only valid if the bond is issued and if there is any dispute over the terms of fixed stream then the bond terms would be used.

Type: [Boolean](#)

Used in groups: [LegAdditionalTermGrp](#)

### 180.2.1302 LegAdditionalTermDiscrepancyClauseIndicator

Indicates whether the discrepancy clause is applicable.

Type: [Boolean](#)

Used in groups: [LegAdditionalTermGrp](#)

### 180.2.1303 LegAdditionalTermGrp

The LegAdditionalTermGrp is a repeating subcomponent of the InstrumentLeg component used to report additional contract terms.

Name	Mult.	Type	Description
<a href="#">NoLegAdditionalTerms</a>	[1..1]	NumInGroup	
<a href="#">LegAdditionalTermConditionPrecedentBondIndicator</a>	[0..1]	Boolean	Required if NoLegAdditionalTerms(41335) > 0.
<a href="#">LegAdditionalTermDiscrepancyClauseIndicator</a>	[0..1]	Boolean	
<a href="#">LegAdditionalTermBondRefGrp</a>	[0..*]	Group	

Name	Mult.	Type	Description
------	-------	------	-------------

Used in components: [InstrumentLeg](#)

#### 180.2.1304 LegAgreementCurrency

Contractual currency forming the basis of a financing agreement and associated transactions. Usually, but not always, the same as the trade currency.

Type: [Currency](#)

Used in components: [LegFinancingDetails](#)

#### 180.2.1305 LegAgreementCurrencyCodeSource

Identifies class or source of the LegAgreementCurrency(2495) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [LegFinancingDetails](#)

#### 180.2.1306 LegAgreementDate

A reference to the date the underlying agreement specified by LegAgreementID(2498) and LegAgreementDesc(2497) was executed.



Type: **LocalMktDate**

Used in components: **LegFinancingDetails**

#### **180.2.1307 LegAgreementDesc**

The full name of the base standard agreement, annexes and amendments in place between the principals applicable to a financing transaction. See <http://www.fpml.org/coding-scheme/master-agreement-type> for derivative values.

Type: **String**

Used in components: **LegFinancingDetails**

#### **180.2.1308 LegAgreementID**

A common reference to the applicable standing agreement between the counterparties to a financing transaction.

Type: **String**

Used in components: **LegFinancingDetails**

#### **180.2.1309 LegAgreementVersion**

The version of the master agreement.

Type: **String**

Used in components: **LegFinancingDetails**

#### **180.2.1310 LegalConfirm**

Indicates that this message is to serve as the final and legal confirmation.

Type: **Boolean**

Allowed values in LegalConfirmCodeSet:

---

Code	Name	Description
N	DoesNotConstituteALegalConfirm	Does not constitute a Legal Confirm
Y	LegalConfirm	Legal Confirm

---

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#)

#### **180.2.1311 LegAllDividendsIndicator**

Represents the European Master Confirmation value of 'All Dividends' which, when applicable, signifies that, for a given Ex-Date, the daily observed share price for that day is adjusted (reduced) by the cash dividend and/or the cash value of any non-cash dividend per share (including extraordinary dividends) declared by the issuer.

Type: [Boolean](#)

Used in components: [LegDividendConditions](#)

#### **180.2.1312 LegAllocAccount**

Allocation Account for the leg

See AllocAccount (79) for description and valid values.

Type: [String](#)

Used in groups: [LegPreAllocGrp](#)

#### **180.2.1313 LegAllocAcctIDSource**

Identifies the source of the LegAllocAccount(671).

Type: [int](#)

Allowed values in AcctIDSourceCodeSet:

Code	Name	Description
1	BIC	BIC
2	SIDCode	SID Code
3	TFM	TFM (GSPTA)
4	OMGEO	OMGEO (Alert ID)
5	DTCCCode	DTCC Code
6	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
99	Other	Other (custom or proprietary)

Used in groups: [LegPreAllocGrp](#)

#### **180.2.1314 LegAllocID**

The AllocID(70) of an individual leg of a multileg order.

Type: [String](#)

Used in groups: [InstrmtLegExecGrp](#), [LegOrdGrp](#), [SideCrossLegGrp](#)

#### **180.2.1315 LegAllocQty**

Leg allocation quantity.

See AllocQty (80) for description and valid values.

Type: [Qty](#)

Used in groups: [LegPreAllocGrp](#)

#### **180.2.1316 LegAllocSettlCurrency**

Identifies settlement currency for the leg level allocation.

Type: [Currency](#)

Used in groups: [LegPreAllocGrp](#)

#### **180.2.1317 LegAllocSettlCurrencyCodeSource**

Identifies class or source of the LegAllocSettlCurrency(1367) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **LegPreAllocGrp**

### 180.2.1318 LegAssetAttributeGrp

The LegAssetAttributeGrp is a repeating subcomponent of the InstrumentLeg component used to detail attributes of the instrument asset.

Name	Mult.	Type	Description
NoLegAssetAttributes	[1..1]	NumInGroup	
LegAssetAttributeType	[0..1]	String	Required if NoLegAssetAttributes(2308) > 0.
LegAssetAttributeValue	[0..1]	String	
LegAssetAttributeLimit	[0..1]	String	

Used in components: **InstrumentLeg**

### 180.2.1319 LegAssetAttributeLimit

Limit or lower acceptable value of the attribute.

Type: **String**

Used in groups: **LegAssetAttributeGrp**

### 180.2.1320 LegAssetAttributeType

Specifies the name of the attribute.

See [http://www.fixtradingcommunity.org/codelists#Asset\\_Attribute\\_Types](http://www.fixtradingcommunity.org/codelists#Asset_Attribute_Types) for code list of applicable asset attribute types.

Type: **String**

Used in groups: **LegAssetAttributeGrp**

**180.2.1321 LegAssetAttributeValue**

Specifies the value of the attribute.

Type: **String**

Used in groups: **LegAssetAttributeGrp**

**180.2.1322 LegAssetClass**

The broad asset category for assessing risk exposure.

Type: **int**

Allowed values in AssetClassCodeSet:

Code	Name	Description
1	InterestRate	Interest rate
2	Currency	Currency
3	Credit	Credit
4	Equity	Equity
5	Commodity	Commodity
6	Other	Other
7	Cash	Cash
8	Debt	Debt
9	Fund	Fund. Such as mutual fund, collective investment vehicle, investment program, specialized account program.
10	LoanFacility	Loan facility
11	Index	Index. A main index identified as a security type, for example under EU SFTR reporting.

Used in components: **InstrumentLeg**

**180.2.1323 LegAssetGroup**

Indicates the broad product or asset classification. May be used to provide grouping for the product taxonomy (Product(460), SecurityType(167), etc.) and/or the risk taxonomy (AssetClass(1938), AssetSubClass(1939), AssetType(1940), etc.).

Type: **int**

Allowed values in AssetGroupCodeSet:

Code	Name	Description
1	Financials	Financials. A categorization which usually includes rates, foreign exchange, credit, bonds and equity products or assets.
2	Commodities	Commodities. A categorization which usually includes hard commodities such as agricultural, metals, freight, energy products or assets.
3	AlternativeInvestments	Alternative investments. A categorization which usually includes weather, housing, and commodity indices products or assets.

Used in components: [InstrumentLeg](#)

### 180.2.1324 LegAssetSubClass

The general subcategory description of the asset class.

Type: [int](#)

Allowed values in AssetSubClassCodeSet:

Code	Name	Description
1	SingleCurrency	Single currency
2	CrossCurrency	Cross currency
3	Basket	Basket [for multi-currency]
4	SingleName	Single name
5	CreditIndex	Credit index
6	IndexTranche	Index tranche
7	CreditBasket	Credit basket
8	Exotic	Exotic
9	Common	Common
10	Preferred	Preferred
11	EquityIndex	Equity index
12	EquityBasket	Equity basket
13	Metals	Metals
14	Bullion	Bullion
15	Energy	Energy

Code	Name	Description
16	CommodityIndex	Commodity index
17	Agricultural	Agricultural
18	Environmental	Environmental
19	Freight	Freight
20	Government	Government
21	Agency	Agency
22	Corporate	Corporate
23	Financing	Financing
24	MoneyMarket	Money market
25	Mortgage	Mortgage
26	Municipal	Municipal
27	MutualFund	Mutual fund
28	CollectiveInvestmentVehicle	Collective investment vehicle
29	InvestmentProgram	Investment program. A generalized fund for major investors.
30	SpecializedAccountProgram	Specialized account program. A specialized fund setup for a particular account or group of accounts.
31	TermLoan	Term loan
32	BridgeLoan	Bridge loan
33	LetterOfCredit	Letter of credit
34	DividendIndex	Dividend index
35	StockDividend	Stock dividend
36	ExchangeTradedFund	Exchange traded fund
37	VolatilityIndex	Volatility index
38	FXCrossRates	FX cross rates
39	FXEmergingMarkets	FX emerging markets
40	FXMajors	FX Majors
41	Fertilizer	Fertilizer
42	IndustrialProduct	Industrial product
43	Inflation	Inflation
44	Paper	Paper
45	Polypropylene	Polypropylene
46	OfficialEconomicStatistics	Official economic statistics

Code	Name	Description
47	OtherC10	Other C10. Defined under MiFID II (Directive 2014/65/EU) Section C(10) of Annex I and paraphrased in ESMA RTS 2 Annex III Section 10, "Other C10" is a financial instrument "which is not a 'Freight derivative', any of the following interest rate derivatives sub-asset classes: 'Inflation multi-currency swap or cross-currency swap', a 'Future/forward on inflation multi-currency swaps or cross-currency swaps', an 'Inflation single currency swap', a 'Future/forward on inflation single currency swap' and any of the following equity derivatives sub-asset classes: a 'Volatility index option', a 'Volatility index future/forward', a swap with parameter return variance, a swap with parameter return volatility, a portfolio swap with parameter return variance, a portfolio swap with parameter return volatility".
48	Other	Other. May be used with any AssetClass(1938) values.

Used in components: **InstrumentLeg**

#### 180.2.1325 LegAssetSubType

Used to provide a more specific description of the asset specified in LegAssetType(2069).

See <https://www.fixtrading.org/codelists/AssetSubType> for code list of applicable values.

Type: **String**

Used in components: **InstrumentLeg**

#### 180.2.1326 LegAssetType

Used to provide more specific description of the asset specified in LegAssetSubClass(2068).

See <https://www.fixtrading.org/codelists/AssetType> for code list of applicable values. ISO 4721 Currency Code values are to be used when specific currency as an asset type is to be expressed.

Other values may be used by mutual agreement of the counterparties.

Type: **String**

Used in components: **InstrumentLeg**



**180.2.1327 LegAttachmentPoint**

Lower bound percentage of the loss that the tranche can endure.

Type: **Percentage**

Used in components: **InstrumentLeg**

**180.2.1328 LegAutomaticExerciseIndicator**

Indicates (when 'Y') that exercise is automatic when the strike price is crossed or the underlying trade is in the money.

Type: **Boolean**

Used in components: **LegOptionExercise**

**180.2.1329 LegAutomaticExerciseThresholdRate**

The threshold rate for triggering automatic exercise.

Type: **float**

Used in components: **LegOptionExercise**

**180.2.1330 LegBenchmarkCurveCurrency**

LegBenchmarkPrice (679) currency

See BenchmarkCurveCurrency (220) for description and valid values.

Type: **Currency**

Used in components: **LegBenchmarkCurveData**

**180.2.1331 LegBenchmarkCurveCurrencyCodeSource**

Identifies class or source of the LegBenchmarkCurveCurrency(676) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [LegBenchmarkCurveData](#)

### 180.2.1332 LegBenchmarkCurveData

The LegBenchmarkCurveData is used to convey the benchmark information used for pricing in a multi-legged Fixed Income security.

Name	Mult.	Type	Description
<a href="#">LegBenchmarkCurveCurrency</a>	[0..1]	Currency	
<a href="#">LegBenchmarkCurveCurrencyCodeSource</a>	[0..1]	CodeSet	
<a href="#">LegBenchmarkCurveName</a>	[0..1]	CodeSet	
<a href="#">LegBenchmarkCurvePoint</a>	[0..1]	String	
<a href="#">LegBenchmarkPrice</a>	[0..1]	Price	
<a href="#">LegBenchmarkPriceType</a>	[0..1]	CodeSet	

Used in groups: [InstrmtLegSecListGrp](#), [LegQuotGrp](#), [QuotReqLegsGrp](#), [SecLstUpdRelSymsLegGrp](#)

### 180.2.1333 LegBenchmarkCurveName

Name of the Leg Benchmark Curve.

See BenchmarkCurveName (22) for description and valid values.

Type: [String](#)

Allowed values in BenchmarkCurveNameCodeSet:

Code	Name	Description
EONIA	EONIA	EONIA
EUREPO	EUREPO	EUREPO
Euribor	Euribor	EURIBOR (deprecated use enum EURIBOR instead). Deprecated use of EURIBOR for the enumeration.
FutureSWAP	FutureSWAP	FutureSWAP
LIBID	LIBID	LIBID
LIBOR	LIBOR	LIBOR (London Inter-Bank Offer)
MuniAAA	MuniAAA	MuniAAA
OTHER	OTHER	OTHER
Pfandbriefe	Pfandbriefe	Pfandbriefe
SONIA	SONIA	SONIA
SWAP	SWAP	SWAP
Treasury	Treasury	Treasury
FEDEFF	FedFundRateEffective	US Federal Reserve fed funds effective rate. US Federal Reserve fed funds effective rate or the weighted average of the actual negotiated rates banks pay each other to to borrow funds.
FEDOPEN	FedOpen	US fed funds target rate. Fed funds target rate as determined by the US Federal Reserve Federal Open Market Committee.
EURIBOR	EURIBOR	Euro interbank offer rate
AUBSW	AUBSW	Australian Bank Bill Swap Rate
BUBOR	BUBOR	Budapest Bank Offered Rate
CDOR	CDOR	Canadian Dollar Offered Rate
CIBOR	CIBOR	Copenhagen Interbank Offered Rate
EONIASWAP	EONIASWAP	Euro Overnight Index Average Swap Rate
ESTR	ESTR	Euro Short Term Rate. Replaces EONIA.
EURODOLLAR	EURODOLLAR	Euro Dollar Rate
EUROSWISS	EUROSWISS	Euro Swiss Franc Rate
GCFREPO	GCFREPO	DTCC General Collateral Finance Repo Index
ISDAFIX	ISDAFIX	ICE Swap Rate
JIBAR	JIBAR	Johannesburg Interbank Agreed Rate
MOSPRIM	MOSPRIM	Moscow Prime Offered Rate
NIBOR	NIBOR	Nigeria Three Month Interbank Rate
PRIBOR	PRIBOR	Czech Republic Interbank Offered Rate
SOFR	SOFR	Secured Overnight Financing Rate. Replaces LIBOR.

Code	Name	Description
STIBOR	STIBOR	Stockholm Interbank Offered Rate
TELBOR	TELBOR	Bank of Israel Interbank Offered Rate
TIBOR	TIBOR	Tokyo Interbank Offered Rate
WIBOR	WIBOR	Warsaw Interbank Offered Rate
AONIA	AONIA	Reserve Bank of Australia Interbank Overnight Cash Rate. Also known as AUD Overnight Index Average.
AONIA-R	AONIAR	Realised AONIA. "Realised AONIA applies a compounding formula to the daily AONIA rate, to determine the compounded average rate over the prior 1 to 6 month period." (source <a href="https://www.asx.com.au/documents/products/realised-aonia-explained.pdf">https://www.asx.com.au/documents/products/realised-aonia-explained.pdf</a> ).
BKBM	BKBM	New Zealand Bank Bill Market Rate
CD91D	CD91D	Republic of Korea 90-Day Certificate of Deposit Rate
CORRA	CORRA	Canadian Overnight Repo Rate Average
DIRR-TN	DIRRTN	Danish Interbank Interest Rate-Tomorrow or Next
EIBOR	EIBOR	Emirates Interbank Offered Rate
FixingRepoRate	FixingRepoRate	China Interbank Overnight Repo Rate
HIBOR	HIBOR	Hong Kong Interbank Offered Rate
IBR	IBR	Colombia Overnight Interbank Reference Rate
KLIBOR	KLIBOR	Kuala Lumpur Interbank Offered Rate
MIBOR	MIBOR	Mumbia Interbank Offered Rate
NZONIA	NZONIA	New Zealand Overnight Indexed Swaps (OIS)
PHIREF	PHIREF	Philippines Interbank Reference Rate
REIBOR	REIBOR	Reykjavik Interbank Offered Rate
SAIBOR	SAIBOR	Saudi Arabian Interbank Offered Rate
SARON	SARON	Swiss Average Rate Overnight
SORA	SORA	Singapore Swap Offer Rate
TLREF	TLREF	Turkish Lira Overnight Reference Rate
TIIE	TIIE	Mexico Interbank Equilibrium Interest Rate
THBFX	THBFX	Thai Baht Interest Rate Fixing
TONAR	TONAR	Tokyo Overnight Average Rate

Used in components: [LegBenchmarkCurveData](#)

**180.2.1334 LegBenchmarkCurvePoint**

Identifies the point on the Leg Benchmark Curve.

See BenchmarkCurvePoint (222) for description and valid values.

Type: **String**

Used in components: **LegBenchmarkCurveData**

**180.2.1335 LegBenchmarkPrice**

Used to identify the price of the benchmark security.

See BenchmarkPrice (662) for description and valid values.

Type: **Price**

Used in components: **LegBenchmarkCurveData**

**180.2.1336 LegBenchmarkPriceType**

The price type of the LegBenchmarkPrice(679).

Type: **int**

Allowed values in PriceTypeCodeSet:

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
2	PerUnit	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points spread). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	Yield	Yield

Code	Name	Description
10	FixedCabinetTradePrice	Fixed cabinet trade price (primarily for listed futures and options)
11	VariableCabinetTradePrice	Variable cabinet trade price (primarily for listed futures and options)
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example, the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)
22	BasisPoints	Basis points. When the price is not spread based.
23	UpfrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageNotional	Percentage of notional

Used in components: [LegBenchmarkCurveData](#)

### 180.2.1337 LegBidForwardPoints

The bid FX forward points for the leg of an FX Swap. Value can be negative. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199

Type: [PriceOffset](#)

Used in groups: [LegQuotGrp](#)

**180.2.1338 LegBidPx**

Bid price of this leg.

See BidPx (32) for description and valid values.

Type: **Price**

Used in groups: **LegQuotGrp**

**180.2.1339 LegBrokerConfirmationDesc**

Describes the type of broker confirmation executed between the parties. Can be used as an alternative to MasterConfirmationDesc(1962). See <http://www.fpml.org/coding-scheme/broker-confirmation-type> for values.

Type: **String**

Used in components: **LegFinancingDetails**

**180.2.1340 LegBusinessCenter**

A business center whose calendar is used for date adjustment, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegBusinessCenterGrp**

**180.2.1341 LegBusinessCenterGrp**

LegBusinessCenterGrp is a repeating subcomponent within the LegDateAdjustment component. It is used to specify the set of business centers whose calendars drive the date adjustment. The business centers defined here apply to all adjustable dates in the instrument leg unless specifically overridden elsewhere in the respective specified components further within the InstrumentLeg component.

Name	Mult.	Type	Description
<b>NoLegBusinessCenters</b>	[1..1]	NumInGroup	
<b>LegBusinessCenter</b>	[0..1]	String	Required if NoLegBusinessCenters(40923) > 0.

Used in components: **LegDateAdjustment**

**180.2.1342 LegBusinessDayConvention**

The business day convention used for adjusting dates. The value defined here applies to all adjustable dates in the instrument leg unless specifically overridden.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **LegDateAdjustment**

**180.2.1343 LegCalculatedCcyLastQty**

Used for the calculated quantity of the other side of the currency for this leg. Can be derived from LegQty and LegLastPx.

Type: **Qty**

Used in groups: **InstrmtLegExecGrp**, **TrdInstrmtLegGrp**

**180.2.1344 LegCapPrice**

Used to express the ceiling price of a capped call.

Type: **Price**

Used in components: **InstrumentLeg**



**180.2.1345 LegCashSettlAccruedInterestIndicator**

Indicates whether accrued interest is included or not in the value provided in LegCashSettlAmount(41357).

For cash settlement this specifies whether quotations should be obtained inclusive or not of accrued interest.

For physical settlement this specifies whether the buyer should deliver the obligation with an outstanding principal balance that includes or excludes accrued interest.

Type: **Boolean**

Used in groups: **LegCashSettlTermGrp**

**180.2.1346 LegCashSettlAmount**

The amount paid between the trade parties, seller to the buyer, for cash settlement on the cash settlement date.

Type: **Amt**

Used in groups: **LegCashSettlTermGrp**

**180.2.1347 LegCashSettlBusinessCenter**

Identifies the business center calendar used at valuation time for cash settlement purposes e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegCashSettlTermGrp**

**180.2.1348 LegCashSettlBusinessDays**

The number of business days used in the determination of the cash settlement payment date.

Type: **int**

Used in groups: **LegCashSettlTermGrp**

**180.2.1349 LegCashSettlCurrency**

Specifies the currency the LegCashSettlAmount(41357) is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegCashSettlTermGrp**

**180.2.1350 LegCashSettlDateAdjusted**

The adjusted cash settlement date.

Type: **LocalMktDate**

Used in components: **LegCashSettlDate**

**180.2.1351 LegCashSettlDateBusinessCenter**

The business center calendar used for date adjustment of the cash settlement unadjusted or relative date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegCashSettlDateBusinessCenterGrp**

**180.2.1352 LegCashSettlDateBusinessCenterGrp**

LegCashSettlDateBusinessCenterGrp is a repeating subcomponent within the LegCashSettlDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoLegCashSettlDateBusinessCenters	[1..1]	NumInGroup	
LegCashSettlDateBusinessCenter	[0..1]	String	Required if NoLegCashSettlDateBusinessCenters(42306) > 0.

Used in components: **LegCashSettlDate**

**180.2.1353 LegCashSettlDateBusinessDayConvention**

The business day convention used to adjust the cash settlement provision's date. Used only to override the business day convention defined in the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **LegCashSettlDate**

**180.2.1354 LegCashSettlDate**

The LegCashSettlDate component is a subcomponent within the LegCashSettlTermGrp component used to report the cash settlement date defined in the settlement provision.

Name	Mult.	Type	Description
<b>LegCashSettlDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>LegCashSettlDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in the Instrument component. The specified value would be specific to this instance of the cash settlement provision.
<b>LegCashSettlDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in the Instrument component. The specified values would be specific to this instance of the cash settlement provision.
<b>LegCashSettlDateRelativeTo</b>	[0..1]	int	

Name	Mult.	Type	Description
LegCashSettlDateOffsetPeriod	[0..1]	int	Conditionally required when LegCashSettlDateOffsetUnit(42303) is specified.
LegCashSettlDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegCashSettlDateOffsetPeriod(42302) is specified.
LegCashSettlDateOffsetDayType	[0..1]	CodeSet	
LegCashSettlDateAdjusted	[0..1]	LocalMktDate	

Used in groups: [LegCashSettlTermGrp](#)

### 180.2.1355 LegCashSettlDateOffsetDayType

Specifies the day type of the relative cash settlement date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegCashSettlDate](#)

### 180.2.1356 LegCashSettlDateOffsetPeriod

Time unit multiplier for the relative cash settlement date offset.

Type: [int](#)

Used in components: [LegCashSettlDate](#)

**180.2.1357 LegCashSettlDateOffsetUnit**

Time unit associated with the relative cash settlement date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegCashSettlDate**

**180.2.1358 LegCashSettlDateRelativeTo**

Specifies the anchor date when the cash settlement date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegCashSettlDate**

**180.2.1359 LegCashSettlDateUnadjusted**

The unadjusted cash settlement date.

Type: **LocalMktDate**

Used in components: **LegCashSettlDate**

**180.2.1360 LegCashSettlDealer**

Identifies the dealer from whom price quotations for the reference obligation are obtained for the purpose of cash settlement valuation calculation.

Type: **String**

Used in groups: **LegCashSettlDealerGrp**

**180.2.1361 LegCashSettlDealerGrp**

LegCashSettlDealerGrp is a repeating subcomponent of the LegCashSettlTermGrp component used to specify the dealers from whom price quotations for the reference obligation are obtained for the purpose of cash settlement valuation.

Name	Mult.	Type	Description
NoLegCashSettlDealers	[1..1]	NumInGroup	
LegCashSettlDealer	[0..1]	String	Required if NoLegCashSettlDealers(41342) > 0.

Used in groups: [LegCashSettlTermGrp](#)

**180.2.1362 LegCashSettlFixedTermIndicator**

Indicates whether fixed settlement is applicable or not applicable in a recovery lock.

Type: [Boolean](#)

Used in groups: [LegCashSettlTermGrp](#)

**180.2.1363 LegCashSettlMinimumQuoteAmount**

When determining the cash settlement amount, if weighted average price quotes are to be obtained for the reference obligation, this is the minimum intended threshold amount of outstanding principal balance of the reference obligation for which the quote should be obtained. If not specified, the ISDA definitions provide for a fallback amount of the lower of either USD1,000,000 (or its equivalent in the relevant obligation currency) or the (minimum) quoted amount.

Type: [Amt](#)

Used in groups: [LegCashSettlTermGrp](#)

**180.2.1364 LegCashSettlMinimumQuoteCurrency**

Specifies the currency the LegCashSettlQuoteMinimumAmount(41354) is denominated in. Uses ISO 4217 Currency Code.

Type: [Currency](#)

Used in groups: [LegCashSettlTermGrp](#)

**180.2.1365 LegCashSettlNumOfValuationDates**

Where multiple valuation dates are specified as being applicable for cash settlement, this element specifies the number of applicable valuation dates.

Type: **int**

Used in groups: **LegCashSettlTermGrp**

**180.2.1366 LegCashSettlPriceDefault**

The default election for determining settlement price.

Type: **int**

Allowed values in CashSettlPriceDefaultCodeSet:

Code	Name	Description
0	Close	Close. Official closing price.
1	Hedge	Hedge. Determined by the hedging party.

Used in groups: **LegCashSettlTermGrp**

**180.2.1367 LegCashSettlPriceSource**

The source from which the settlement price is to be obtained.

See <http://www.fpml.org/coding-scheme/settlement-price-source> for values.

Type: **String**

Used in groups: **LegCashSettlTermGrp**

**180.2.1368 LegCashSettlQuoteAmount**

When determining the cash settlement amount, if weighted average price quotes are to be obtained for the reference obligation, this is the upper limit to the outstanding principal balance of the reference obligation for which the quote should be obtained. If not specified, the ISDA definitions provide for a fallback amount equal to floating rate payer calculation amount.

Type: **Amt**

Used in groups: **LegCashSettlTermGrp**

**180.2.1369 LegCashSettlQuoteCurrency**

Specifies the currency the LegCashSettlQuoteAmount(41352) is denominated in. Uses ISO 4217 Currency Code.

Type: **Currency**

Used in groups: **LegCashSettlTermGrp**

**180.2.1370 LegCashSettlQuoteMethod**

The type of quote used to determine the cash settlement price.

Type: **int**

Allowed values in CashSettlQuoteMethodCodeSet:

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer

Used in groups: **LegCashSettlTermGrp**

**180.2.1371 LegCashSettlRecoveryFactor**

Used for fixed recovery, this specifies the recovery level as determined at contract inception, to be applied in the event of a default. The factor is used to calculate the amount paid by the seller to the buyer for cash settlement on the cash settlement date. The amount calculated is  $(1 - \text{LegCashSettlRecoveryFactor}(41358)) \times \text{floating rate payer calculation amount}$ . The currency is derived from the floating rate payer calculation amount.

Type: **float**

Used in groups: **LegCashSettlTermGrp**

**180.2.1372 LegCashSettlTermGrp**

The LegCashSettlTermGrp is a repeating component within the InstrumentLeg component used to report cash settlement terms.



Name	Mult.	Type	Description
NoLegCashSettlTerms	[1..1]	NumInGroup	
LegCashSettlCurrency	[0..1]	Currency	Required if NoLegCashSettlTerms(41344) > 0.
LegCashSettlValuationFirstBusinessDayOffset	[0..1]	int	
LegCashSettlValuationSubsequentBusinessDaysOffset	[0..1]	int	
LegCashSettlNumOfValuationDates	[0..1]	int	
LegCashSettlValuationTime	[0..1]	LocalMktTime	
LegCashSettlBusinessCenter	[0..1]	String	
LegCashSettlQuoteMethod	[0..1]	CodeSet	
LegCashSettlQuoteAmount	[0..1]	Amt	
LegCashSettlQuoteCurrency	[0..1]	Currency	
LegCashSettlMinimumQuoteAmount	[0..1]	Amt	
LegCashSettlMinimumQuoteCurrency	[0..1]	Currency	
LegCashSettlDealerGrp	[0..*]	Group	
LegCashSettlPriceSource	[0..1]	String	
LegCashSettlPriceDefault	[0..1]	CodeSet	
LegCashSettlBusinessDays	[0..1]	int	
LegCashSettlAmount	[0..1]	Amt	
LegCashSettlDate	[0..1]	Component	
LegCashSettlRecoveryFactor	[0..1]	float	
LegCashSettlFixedTermIndicator	[0..1]	Boolean	
LegCashSettlAccruedInterestIndicator	[0..1]	Boolean	
LegCashSettlValuationMethod	[0..1]	CodeSet	
LegCashSettlTermXID	[0..1]	XID	

Used in components: **InstrumentLeg**

### 180.2.1373 LegCashSettlTermXID

A named string value referenced by UnderlyingSettlTermXIDRef(41315).

Type: **XID**

Used in groups: **LegCashSettlTermGrp**

**180.2.1374 LegCashSettlValuationMethod**

The ISDA defined methodology for determining the final price of the reference obligation for purposes of cash settlement.

Type: **int**

Allowed values in CashSettlValuationMethodCodeSet:

Code	Name	Description
0	Market	Market
1	Highest	Highest
2	AverageMarket	Average market
3	AverageHighest	Average highest
4	BlendedMarket	Blended market
5	BlendedHighest	Blended highest
6	AverageBlendedMarket	Average blended market
7	AverageBlendedHighest	Average blended highest

Used in groups: **LegCashSettlTermGrp**

**180.2.1375 LegCashSettlValuationSubsequentBusinessDaysOffset**

The number of business days between successive valuation dates when multiple valuation dates are applicable for cash settlement.

Type: **int**

Used in groups: **LegCashSettlTermGrp**

**180.2.1376 LegCashSettlValuationTime**

Time of valuation.

Type: **LocalMktTime**

Used in groups: **LegCashSettlTermGrp**

**180.2.1377 LegCasSettlValuationFirstBusinessDayOffset**

The number of business days after settlement conditions have been satisfied, when the calculation agent is to obtain a price quotation on the reference obligation for purposes of cash settlement.

Type: **int**

Used in groups: **LegCashSettlTermGrp**

**180.2.1378 LegCFIcode**

Multileg instrument's individual security's CFIcode.

See CFIcode (461) field for description

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1379 LegClearingAccountType**

Designates the capacity in which the order will be submitted to clearing.

Type: **int**

Allowed values in ClearingAccountTypeCodeSet:

Code	Name	Description
1	Customer	Customer
2	Firm	Firm
3	MarketMaker	Market maker

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**, **TrdInstrmtLegGrp**

**180.2.1380 LegCommonPricingIndicator**

When this element is specified and set to 'Y', it indicates that common pricing applies. Common pricing may be relevant for a transaction that references more than one commodity reference price.

Type: **Boolean**

Used in components: **InstrumentLeg**

**180.2.1381 LegComplexEventReferencePageHeading**

Identifies the reference page heading from the rate source.

Type: **String**

Used in groups: **LegComplexEventRateSourceGrp**

**180.2.1382 LegComplexEventAveragingObservationGrp**

LegComplexEventAveragingObservationGrp is an optional subcomponent of LegComplexEventPeriodGrp for specifying the weight of each of the dated observations.

Name	Mult.	Type	Description
NoLegComplexEventAveragingObservations	[1..1]	NumInGroup	
LegComplexEventAveragingObservationNumber	[0..1]	int	Required if NoLegComplexEventAveragingObservations(41363) > 0.
LegComplexEventAveragingWeight	[0..1]	float	

Used in groups: **LegComplexEventPeriodGrp**

**180.2.1383 LegComplexEventAveragingObservationNumber**

Cross reference to the ordinal observation as specified either in the LegComplexEventScheduleGrp or LegComplexEventPeriodDateGrp components.

Type: **int**

Used in groups: **LegComplexEventAveragingObservationGrp**

**180.2.1384 LegComplexEventAveragingWeight**

The weight factor to be applied to the observation.

Type: **float**

Used in groups: **LegComplexEventAveragingObservationGrp**

**180.2.1385 LegComplexEventBusinessCenter**

The business center for adjusting dates and times in the schedule or date-time group.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegComplexEventPeriodGrp**

**180.2.1386 LegComplexEventCalculationAgent**

Used to identify the calculation agent.

Type: **int**

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreement	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

Used in groups: **LegComplexEvents**

**180.2.1387 LegComplexEventCondition**

Specifies the condition between complex events when more than one event is specified.

Multiple barrier events would use an "or" condition since only one can be effective at a given time. A set of digital range events would use an "and" condition since both conditions must be in effect for a payout to result.

Type: **int**

Allowed values in ComplexEventConditionCodeSet:

Code	Name	Description
1	And	And
2	Or	Or

Used in groups: **LegComplexEvents**

#### **180.2.1388 LegComplexEventCreditEventBusinessCenter**

Specifies the local business center for which the credit event is to be determined. The inclusion of this business center implies that Greenwich Mean Time in Section 3.3 of the 2003 ISDA Credit Derivatives Definitions is replaced by the local time of the specified business center.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegComplexEvents**

#### **180.2.1389 LegComplexEventCreditEventCurrency**

Specifies the applicable currency when LegComplexEventCreditEventCurrency(41368) is an amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegComplexEventCreditEventGrp**

#### **180.2.1390 LegComplexEventCreditEventDayType**

Specifies the day type for the complex credit events.

Type: **int**

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **LegComplexEventCreditEventGrp**

**180.2.1391 LegComplexEventCreditEventGrp**

The LegComplexEventCreditEventGrp is a repeating component within the LegComplexEventGrp component used to report applicable option credit events.

Name	Mult.	Type	Description
NoLegComplexEventCreditEvents	[1..1]	NumInGroup	
LegComplexEventCreditEventType	[0..1]	String	Required if NoLegComplexEventCreditEvents(41366) > 0.
LegComplexEventCreditEventValue	[0..1]	String	
LegComplexEventCreditEventCurrency	[0..1]	Currency	
LegComplexEventCreditEventPeriod	[0..1]	int	Conditionally required when LegComplexEventCreditEventUnit(41371) is specified.
LegComplexEventCreditEventUnit	[0..1]	CodeSet	Conditionally required when LegComplexEventCreditEventPeriod(41370) is specified.
LegComplexEventCreditEventDayType	[0..1]	CodeSet	
LegComplexEventCreditEventRate-Source	[0..1]	int	
LegComplexEventCreditEventQualifierGrp	[0..*]	Group	

Used in groups: **LegComplexEvents**

**180.2.1392 LegComplexEventCreditEventMinimumSources**

The minimum number of the specified public information sources that must publish information that reasonably confirms that a credit event has occurred. The market convention is two.

Type: **int**

Used in groups: **LegComplexEvents**

**180.2.1393 LegComplexEventCreditEventNotifyingParty**

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring.

Type: **int**

Allowed values in ComplexEventCreditEventNotifyingPartyCodeSet:

Code	Name	Description
0	SellerNotifies	Seller notifies
1	BuyerNotifies	Buyer notifies
2	SellerOrBuyerNotifies	Seller or buyer notifies

Used in groups: **LegComplexEvents**

#### **180.2.1394 LegComplexEventCreditEventPeriod**

Time unit multiplier for complex credit events.

Type: **int**

Used in groups: **LegComplexEventCreditEventGrp**

#### **180.2.1395 LegComplexEventCreditEventQualifier**

Specifies a complex event qualifier. Used to further qualify LegComplexEventCreditEvent-Type(41367).

Type: **char**

Allowed values in ProtectionTermEventQualifierCodeSet:

Code	Name	Description
H	RestructuringMultipleHoldingObligations	Retructuring - multiple holding obligations. In relation to a restructuring credit event, unless multiple holder obligation is not specified restructurings are limited to multiple holder obligations. A multiple holder obligation means an obligation that is held by more than three holders that are not affiliates of each other and where at least two thirds of the holders must agree to the event that constitutes the restructuring credit event. ISDA 2003 Term: Multiple Holder Obligation.



Code	Name	Description
E	RestructuringMultipleCreditEvent-Notices	Restructuring - multiple credit event notices. Presence of this element and value set to 'true' indicates that Section 3.9 of the 2003 Credit Derivatives Definitions shall apply. Absence of this element indicates that Section 3.9 shall not apply. NOTE: Not allowed under ISDA Credit 1999.
C	FloatingRateInterestShortfall	Floating rate interest shortfall. Indicates compounding.

Used in groups: [LegComplexEventCreditEventQualifierGrp](#)

### 180.2.1396 LegComplexEventCreditEventQualifierGrp

The LegComplexEventCreditEventQualifierGrp is a repeating component within the LegComplexEventCreditEventGrp component used to specify qualifying attributes to an event.

Name	Mult.	Type	Description
<a href="#">NoLegComplexEventCreditEventQualifiers</a>	[1..1]	NumInGroup	
<a href="#">LegComplexEventCreditEventQualifier</a>	[0..1]	CodeSet	Required if <a href="#">NoLegComplexEventCreditEventQualifiers</a> (41374) > 0.

Used in groups: [LegComplexEventCreditEventGrp](#)

### 180.2.1397 LegComplexEventCreditEventRateSource

Identifies the source of rate information used for credit events.

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Rate\\_Source](http://www.fixtradingcommunity.org/codelists#Credit_Event_Rate_Source) for code list of applicable sources.

Type: [int](#)

Used in groups: [LegComplexEventCreditEventGrp](#)

### 180.2.1398 LegComplexEventCreditEventSource

A newspaper or electronic news service that may publish relevant information used in the determination of whether or not a credit event has occurred.

Type: **String**

Used in groups: **LegComplexEventCreditEventSourceGrp**

#### **180.2.1399 LegComplexEventCreditEventSourceGrp**

LegComplexEventCreditEventSourceGrp is a repeating subcomponent of the LegComplexEvents component used to specify the particular newspapers or electronic news services that may publish relevant information used in the determination of whether or not a credit event has occurred.

Name	Mult.	Type	Description
NoLegComplexEventCreditEventSources	[1..1]	NumInGroup	
LegComplexEventCreditEventSource	[0..1]	String	Required if NoLegComplexEventCreditEventSources(41398) > 0.

Used in groups: **LegComplexEvents**

#### **180.2.1400 LegComplexEventCreditEventStandardSources**

When this element is specified and set to 'Y', indicates that ISDA defined Standard Public Sources are applicable.

Type: **Boolean**

Used in groups: **LegComplexEvents**

#### **180.2.1401 LegComplexEventCreditEventsXIDRef**

Reference to credit event table elsewhere in the message.

Type: **XIDREF**

Used in groups: **LegComplexEvents**

#### **180.2.1402 LegComplexEventCreditEventType**

Specifies the type of credit event.

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Credit_Event_Types) for code list of applicable event types.

Type: **String**

Used in groups: **LegComplexEventCreditEventGrp**

#### **180.2.1403 LegComplexEventCreditEventUnit**

Time unit associated with complex credit events.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegComplexEventCreditEventGrp**

#### **180.2.1404 LegComplexEventCreditEventValue**

The credit event value appropriate to LegComplexEventCreditEventType(41367).

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Credit_Event_Types) for applicable event type values.

Type: **String**

Used in groups: **LegComplexEventCreditEventGrp**

#### **180.2.1405 LegComplexEventCurrencyOne**

Specifies the first or only reference currency of the trade.

LegComplexEventCurrencyOneCodeSource(2945) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **LegComplexEvents**

**180.2.1406 LegComplexEventCurrencyOneCodeSource**

Identifies class or source of the LegComplexEventCurrencyOne(2233) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **LegComplexEvents**

**180.2.1407 LegComplexEventCurrencyTwo**

Specifies the second reference currency of the trade.

LegComplexEventCurrencyTwoCodeSource(2946) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **LegComplexEvents**

**180.2.1408 LegComplexEventCurrencyTwoCodeSource**

Identifies class or source of the LegComplexEventCurrencyTwo(2234) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **LegComplexEvents**

#### **180.2.1409 LegComplexEventDateAdjusted**

The adjusted complex event date.

Type: **LocalMktDate**

Used in components: **LegComplexEventRelativeDate**

#### **180.2.1410 LegComplexEventDateBusinessCenter**

The business center calendar used to adjust the event date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegComplexEventDateBusinessCenterGrp**

#### **180.2.1411 LegComplexEventDateBusinessCenterGrp**

**LegComplexEventDateBusinessCenterGrp** is a repeating subcomponent of the **LegComplexEventRelativeDate** component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the **LegDateAdjustment** component in **InstrumentLeg**.

Name	Mult.	Type	Description
NoLegComplexEventDateBusinessCenters	[1..1]	NumInGroup	
LegComplexEventDateBusinessCenter	[0..1]	String	Required if NoLegComplexEventDateBusinessCenters(41387) > 0.

Used in components: [LegComplexEventRelativeDate](#)

### 180.2.1412 LegComplexEventDateBusinessDayConvention

The business day convention used to adjust the event date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegComplexEventRelativeDate](#)

### 180.2.1413 LegComplexEventDateOffsetDayType

Specifies the day type of the relative date offset.

Type: [int](#)

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegComplexEventRelativeDate](#)

#### **180.2.1414 LegComplexEventDateOffsetPeriod**

Time unit multiplier for the relative date offset.

Type: [int](#)

Used in components: [LegComplexEventRelativeDate](#)

#### **180.2.1415 LegComplexEventDateOffsetUnit**

Time unit associated with the relative date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegComplexEventRelativeDate](#)

#### **180.2.1416 LegComplexEventDateRelativeTo**

Specifies the anchor date when the complex event date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegComplexEventRelativeDate**

#### **180.2.1417 LegComplexEventDates**

The LegComplexEventDates and subcomponent LegComplexEventTimes components are used to constrain a complex event to a specific date range, and optional time range. If specified the event is only effective on or within the specified dates and times.

Name	Mult.	Type	Description
NoLegComplexEventDates	[1..1]	NumInGroup	
LegComplexEventStartDate	[0..1]	UTCDateOnly	Required if NoLegComplexEventDates(2250) > 0.
LegComplexEventEndDate	[0..1]	UTCDateOnly	Required if NoLegComplexEventDates(2250) > 0.
LegComplexEventTimes	[0..*]	Group	

Used in groups: **LegComplexEvents**

#### **180.2.1418 LegComplexEventDateUnadjusted**

The unadjusted complex event date.

Type: **LocalMktDate**

Used in components: **LegComplexEventRelativeDate**

#### **180.2.1419 LegComplexEventDeterminationMethod**

Specifies the method according to which an amount or a date is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **LegComplexEvents**



**180.2.1420 LegComplexEventEndDate**

The end date of the date range on which a complex event is effective. The start date will be set equal to the end date for single day events such as Bermuda options.

The end date must always be greater than or equal to start date.

Type: **UTCDateOnly**

Used in groups: **LegComplexEventDates**

**180.2.1421 LegComplexEventEndTime**

The end time of the time range on which a complex event date is effective.

The end time must always be greater than or equal to the start time.

Type: **UTCTimeOnly**

Used in groups: **LegComplexEventTimes**

**180.2.1422 LegComplexEventFixedFXRate**

Specifies the fixed FX rate alternative for FX Quanto options.

Type: **float**

Used in groups: **LegComplexEvents**

**180.2.1423 LegComplexEventFixingTime**

The local market fixing time.

Type: **LocalMktTime**

Used in components: **LegComplexEventRelativeDate**

**180.2.1424 LegComplexEventFixingTimeBusinessCenter**

The business center for determining the actual fixing times.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **LegComplexEventRelativeDate**

**180.2.1425 LegComplexEventForwardPoints**

FX forward points added to spot rate. May be a negative value.

Type: **PriceOffset**

Used in groups: **LegComplexEvents**

**180.2.1426 LegComplexEventFuturesPriceValuation**

Indicates whether the official settlement price as announced by the related exchange is applicable, in accordance with the ISDA 2002 definitions. Applicable only to futures contracts.

Type: **Boolean**

Used in groups: **LegComplexEvents**

**180.2.1427 LegComplexEventOptionsPriceValuation**

Indicates whether the official settlement price as announced by the related exchange is applicable, in accordance with the ISDA 2002 definitions. Applicable only to options contracts.

Type: **Boolean**

Used in groups: **LegComplexEvents**

**180.2.1428 LegComplexEventPeriodDate**

Averaging date for an Asian option.

Trigger date for a Barrier or Knock option.

Type: **LocalMktDate**

Used in groups: **LegComplexEventPeriodDateGrp**

**180.2.1429 LegComplexEventPeriodDateGrp**

LegComplexEventPeriodDateGrp is a subcomponent of LegComplexEventPeriodGrp for specifying fixed period dates and times for an Asian or Strike Schedule option or trigger dates for a Barrier or Knock option.

Name	Mult.	Type	Description
NoLegComplexEventPeriodDateTimes	[1..1]	NumInGroup	
LegComplexEventPeriodDate	[0..1]	LocalMktDate	Required if NoLegComplexEventPeriodDateTimes(41376) > 0.
LegComplexEventPeriodTime	[0..1]	LocalMktTime	

Used in groups: [LegComplexEventPeriodGrp](#)

### 180.2.1430 LegComplexEventPeriodGrp

LegComplexEventPeriodGrp is a subcomponent of LegComplexEvents for specifying the periods for an Asian, Barrier, Knock or Strike Schedule option feature.

Name	Mult.	Type	Description
NoLegComplexEventPeriods	[1..1]	NumInGroup	
LegComplexEventPeriodType	[0..1]	CodeSet	Required if NoLegComplexEventPeriods(41379) > 0.
LegComplexEventBusinessCenter	[0..1]	String	
LegComplexEventScheduleGrp	[0..*]	Group	
LegComplexEventPeriodDateGrp	[0..*]	Group	
LegComplexEventAveragingObservationGrp	[0..*]	Group	

Used in groups: [LegComplexEvents](#)

### 180.2.1431 LegComplexEventPeriodTime

Averaging time for an Asian option.

Type: [LocalMktTime](#)

Used in groups: [LegComplexEventPeriodDateGrp](#)

### 180.2.1432 LegComplexEventPeriodType

Specifies the period type.

Type: **int**

Allowed values in ComplexEventPeriodTypeCodeSet:

Code	Name	Description
0	AsianOut	Asian Out
1	AsianIn	Asian In
2	BarrierCap	Barrier Cap
3	BarrierFloor	Barrier Floor
4	KnockOut	Knock Out
5	KnockIn	Knock In

Used in groups: **LegComplexEventPeriodGrp**

#### **180.2.1433 LegComplexEventPrice**

Specifies the price at which the complex event takes effect. Impact of the event price is determined by the LegComplexEventType(2219).

Type: **Price**

Used in groups: **LegComplexEvents**

#### **180.2.1434 LegComplexEventPriceBoundaryMethod**

Specifies the boundary condition to be used for the event price relative to the complex event price at the point the complex event outcome takes effect as determined by the LegComplexEventPriceTimeType(2231).

Type: **int**

Allowed values in ComplexEventPriceBoundaryMethodCodeSet:

Code	Name	Description
1	LessThanComplexEventPrice	Less than ComplexEventPrice(1486)
2	LessThanOrEqualToComplexEvent- Price	Less than or equal to ComplexEventPrice(1486)
3	EqualToComplexEventPrice	Equal to ComplexEventPrice(1486)

Code	Name	Description
4	GreaterThanOrEqualToComplex-EventPrice	Greater than or equal to ComplexEventPrice(1486)
5	GreaterThanComplexEventPrice	Greater than ComplexEventPrice(1486)

Used in groups: [LegComplexEvents](#)

#### 180.2.1435 LegComplexEventPriceBoundaryPrecision

Used in combination with LegComplexEventPriceBoundaryMethod(2229) to specify the percentage of the strike price in relation to the underlying price. The percentage is generally 100 or greater for puts and 100 or less for calls.

Type: [Percentage](#)

Used in groups: [LegComplexEvents](#)

#### 180.2.1436 LegComplexEventPricePercentage

Specifies the price percentage at which the complex event takes effect. Impact of the event price is determined by the LegComplexEventType(2219).

Type: [Percentage](#)

Used in groups: [LegComplexEvents](#)

#### 180.2.1437 LegComplexEventPriceTimeType

Specifies when the complex event outcome takes effect. The outcome of a complex event is a payout or barrier action as specified by the LegComplexEventType(2219).

Type: [int](#)

Allowed values in ComplexEventPriceTimeTypeCodeSet:

Code	Name	Description
1	Expiration	Expiration
2	Immediate	Immediate (At Any Time)
3	SpecifiedDate	Specified Date/Time

Code	Name	Description
4	Close	Close. Official closing time of the exchange on valuation date.
5	Open	Open. Official opening time of the exchange on valuation date.
6	OfficialSettlPrice	Official settlement price. Official settlement price determination time.
7	DerivativesClose	Derivatives close. Official closing time of the derivatives exchange.
8	AsSpecifiedMasterConfirmation	As specified in Master Confirmation

Used in groups: **LegComplexEvents**

#### **180.2.1438 LegComplexEventPVFinalPriceElectionFallback**

Specifies the fallback provisions for the hedging party in the determination of the final settlement price

Type: **int**

Allowed values in ComplexEventPVFinalPriceElectionFallbackCodeSet:

Code	Name	Description
0	Close	Close. In respect of the "early final valuation date", the provisions for "future present value close" shall apply.
1	HedgeElection	Hedge election. In respect of the "early final valuation date", the provisions for "future present value hedge execution" shall apply.

Used in groups: **LegComplexEvents**

#### **180.2.1439 LegComplexEventQuoteBasis**

For foreign exchange Quanto option feature.

Type: **int**

Allowed values in ComplexEventQuoteBasisCodeSet:

Code	Name	Description
0	Currency1PerCurrency2	Currency 1 per currency 2
1	Currency2PerCurrency1	Currency 2 per currency 1

Used in groups: **LegComplexEvents**

### 180.2.1440 LegComplexEventRateSource

Identifies the source of rate information.

For FX, the reference source to be used for the FX spot rate.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: **LegComplexEventRateSourceGrp**

### 180.2.1441 LegComplexEventRateSourceGrp

LegComplexEventRateSourceGrp is a subcomponent of LegComplexEvents for specifying primary and secondary rate sources.

Name	Mult.	Type	Description
<b>NoLegComplexEventRateSources</b>	[1..1]	NumInGroup	
<b>LegComplexEventRateSource</b>	[0..1]	CodeSet	Required if NoLegComplexEventRateSources(41382) > 0.

Name	Mult.	Type	Description
<b>LegComplexEventRateSourceType</b>	[0..1]	CodeSet	Required if NoLegComplexEventRateSources(41382) > 0.
<b>LegComplexEventReferencePage</b>	[0..1]	String	Conditionally required when LegComplexEventRateSource(41383) = 99 (Other).
<b>LegComplexEventReferencePageHead- ing</b>	[0..1]	String	

Used in groups: **LegComplexEvents**

#### 180.2.1442 **LegComplexEventRateSourceType**

Indicates whether the rate source specified is a primary or secondary source.

Type: **int**

Allowed values in RateSourceTypeCodeSet:

Code	Name	Description
0	Primary	Primary
1	Secondary	Secondary

Used in groups: **LegComplexEventRateSourceGrp**

#### 180.2.1443 **LegComplexEventReferencePage**

Identifies the reference page from the rate source.

For FX, the reference page to the spot rate is to be used for the reference FX spot rate.

When LegComplexEventRateSource(41383) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>.

Type: **String**

Used in groups: **LegComplexEventRateSourceGrp**



**180.2.1444 LegComplexEventRelativeDate**

LegComplexEventRelativeDate is a subcomponent of LegComplexEvents for specifying the event date and time for an FX or Calendar Spread option or the payout date for a Barrier or Knock option.

Name	Mult.	Type	Description
LegComplexEventDateUnadjusted	[0..1]	LocalMktDate	
LegComplexEventDateRelativeTo	[0..1]	int	
LegComplexEventDateOffsetPeriod	[0..1]	int	Conditionally required when LegComplexEventDateOffsetUnit(41392) is specified.
LegComplexEventDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegComplexEventDateOffsetPeriod(41391) is specified.
LegComplexEventDateOffsetDayType	[0..1]	CodeSet	
LegComplexEventDateBusinessDay-Convention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to complex event dates.
LegComplexEventDateBusinessCenter-Grp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to complex event dates.
LegComplexEventDateAdjusted	[0..1]	LocalMktDate	
LegComplexEventFixingTime	[0..1]	LocalMktTime	
LegComplexEventFixingTimeBusiness-Center	[0..1]	String	

Used in groups: [LegComplexEvents](#)

**180.2.1445 LegComplexEventScheduleEndDate**

The end date of the schedule.

Type: [LocalMktDate](#)

Used in groups: [LegComplexEventScheduleGrp](#)

**180.2.1446 LegComplexEventScheduleFrequencyPeriod**

Time unit multiplier for the schedule date frequency.

Type: **int**

Used in groups: **LegComplexEventScheduleGrp**

**180.2.1447 LegComplexEventScheduleFrequencyUnit**

Time unit associated with the schedule date frequency.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegComplexEventScheduleGrp**

**180.2.1448 LegComplexEventScheduleGrp**

LegComplexEventScheduleGrp is a subcomponent of LegComplexEventPeriodGrp for specifying a periodic schedule for an Asian, Barrier or Strike Schedule option feature.

Name	Mult.	Type	Description
<b>NoLegComplexEventSchedules</b>	[1..1]	NumInGroup	
<b>LegComplexEventScheduleStartDate</b>	[0..1]	LocalMktDate	Required if NoLegComplexEventSchedules(41400) > 0.
<b>LegComplexEventScheduleEndDate</b>	[0..1]	LocalMktDate	
<b>LegComplexEventScheduleFrequencyPeriod</b>	[0..1]	int	Conditionally required when LegComplexEventScheduleFrequencyUnit(41404) is specified.
<b>LegComplexEventScheduleFrequencyUnit</b>	[0..1]	CodeSet	Conditionally required when LegComplexEventScheduleFrequencyPeriod(41403) is specified.

Name	Mult.	Type	Description
<b>LegComplexEventScheduleRollConvention</b>	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the option expiration dates and times.

Used in groups: **LegComplexEventPeriodGrp**

### 180.2.1449 LegComplexEventScheduleRollConvention

The convention for determining the sequence of dates. It is used in conjunction with a specified frequency. Used only to override the roll convention defined in the LegDateAdjustment component in InstrumentLeg.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month

Code	Name	Description
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighthDay	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in groups: [LegComplexEventScheduleGrp](#)

### 180.2.1450 LegComplexEventScheduleStartDate

The start date of the schedule.

Type: [LocalMktDate](#)

Used in groups: [LegComplexEventScheduleGrp](#)

### 180.2.1451 LegComplexEvents

The LegComplexEvent Group is a repeating block which allows specifying an unlimited number and types of advanced events, such as observation and pricing over the lifetime of an option, futures, commodities or equity swap contract. Use LegEvtGrp to specify more straightforward events.

Name	Mult.	Type	Description
<a href="#">NoLegComplexEvents</a>	[1..1]	NumInGroup	
<a href="#">LegComplexEventType</a>	[0..1]	CodeSet	Required if NoLegComplexEvents(2218)) > 0.
<a href="#">LegComplexOptPayoutPaySide</a>	[0..1]	CodeSet	
<a href="#">LegComplexOptPayoutReceiveSide</a>	[0..1]	CodeSet	
<a href="#">LegComplexOptPayoutUnderlier</a>	[0..1]	String	
<a href="#">LegComplexOptPayoutAmount</a>	[0..1]	Amt	
<a href="#">LegComplexOptPayoutPercentage</a>	[0..1]	Percentage	
<a href="#">LegComplexOptPayoutTime</a>	[0..1]	CodeSet	
<a href="#">LegComplexOptPayoutCurrency</a>	[0..1]	Currency	
<a href="#">LegComplexOptPayoutCurrency-CodeSource</a>	[0..1]	CodeSet	
<a href="#">LegComplexEventPrice</a>	[0..1]	Price	
<a href="#">LegComplexEventPricePercentage</a>	[0..1]	Percentage	
<a href="#">LegComplexEventPriceBoundaryMethod</a>	[0..1]	CodeSet	
<a href="#">LegComplexEventPriceBoundaryPrecision</a>	[0..1]	Percentage	
<a href="#">LegComplexEventPriceTimeType</a>	[0..1]	CodeSet	

Name	Mult.	Type	Description
LegComplexEventCondition	[0..1]	CodeSet	Conditionally required when there are more than one LegComplexEvents occurrences. A chain of LegComplexEvents must be linked together through use of the LegComplexEventCondition(2232) in which the relationship between any two events is described. For any two LegComplexEvents the first occurrence will specify the LegComplexEventCondition(2232) which links it with the second event.
LegComplexEventDates	[0..*]	Group	
LegComplexEventCurrencyOne	[0..1]	Currency	
LegComplexEventCurrencyOneCodeSource	[0..1]	CodeSet	
LegComplexEventCurrencyTwo	[0..1]	Currency	
LegComplexEventCurrencyTwoCodeSource	[0..1]	CodeSet	
LegComplexEventQuoteBasis	[0..1]	CodeSet	
LegComplexEventFixedFXRate	[0..1]	float	
LegComplexEventSpotRate	[0..1]	Price	
LegComplexEventForwardPoints	[0..1]	PriceOffset	
LegComplexEventDetermination-Method	[0..1]	String	
LegComplexEventCalculationAgent	[0..1]	CodeSet	
LegComplexEventStrikePrice	[0..1]	Price	
LegComplexEventStrikeFactor	[0..1]	float	
LegComplexEventStrikeNumberOfOptions	[0..1]	int	
LegComplexEventRateSourceGrp	[0..*]	Group	
LegComplexEventRelativeDate	[0..1]	Component	
LegComplexEventPeriodGrp	[0..*]	Group	
LegComplexEventCreditEventsXIDRef	[0..1]	XIDREF	
LegComplexEventCreditEventNotifyingParty	[0..1]	CodeSet	
LegComplexEventCreditEventBusinessCenter	[0..1]	String	
LegComplexEventCreditEventStandardSources	[0..1]	Boolean	

Name	Mult.	Type	Description
LegComplexEventCreditEventMinimumSources	[0..1]	int	
LegComplexEventCreditEventSourceGrp	[0..*]	Group	
LegComplexEventCreditEventGrp	[0..*]	Group	
LegComplexEventFuturesPriceValuation	[0..1]	Boolean	
LegComplexEventOptionsPriceValuation	[0..1]	Boolean	
LegComplexEventPVFinalPriceElectionFallback	[0..1]	CodeSet	
LegComplexEventXID	[0..1]	XID	
LegComplexEventXIDRef	[0..1]	XIDREF	

Used in components: [InstrumentLeg](#)

#### **180.2.1452 LegComplexEventSpotRate**

FX spot rate.

Type: [Price](#)

Used in groups: [LegComplexEvents](#)

#### **180.2.1453 LegComplexEventStartDate**

The start date of the date range on which a complex event is effective. The start date will be set equal to the end date for single day events such as Bermuda options.

The start date must always be less than or equal to end date.

Type: [UTCDateOnly](#)

Used in groups: [LegComplexEventDates](#)

#### **180.2.1454 LegComplexEventStartTime**

The start time of the time range on which a complex event date is effective.

The start time must always be less than or equal to the end time.

Type: **UTCTimeOnly**

Used in groups: **LegComplexEventTimes**

#### **180.2.1455 LegComplexEventStrikeFactor**

Strike factor for Asian option feature. Upper strike percentage for a Strike Spread.

Type: **float**

Used in groups: **LegComplexEvents**

#### **180.2.1456 LegComplexEventStrikeNumberOfOptions**

Upper string number of options for a Strike Spread.

Type: **int**

Used in groups: **LegComplexEvents**

#### **180.2.1457 LegComplexEventStrikePrice**

Upper strike price for Asian option feature. Strike percentage for a Strike Spread.

Type: **Price**

Used in groups: **LegComplexEvents**

#### **180.2.1458 LegComplexEventTimes**

The LegComplexEventTimes is a repeating subcomponent of the LegComplexEventDates component. It is used to further qualify any dates placed on the event and is used to specify time ranges for which a complex event is effective. It is always provided within the context of start and end dates. The time range is assumed to be in effect for the entirety of the date or date range specified.

<b>Name</b>	<b>Mult.</b>	<b>Type</b>	<b>Description</b>
<b>NoLegComplexEventTimes</b>	[1..1]	NumInGroup	
<b>LegComplexEventStartTime</b>	[0..1]	UTCTimeOnly	Required if NoLegComplexEventTimes(2253) > 0.
<b>LegComplexEventEndTime</b>	[0..1]	UTCTimeOnly	Required if NoLegComplexEventTimes(2253) > 0.



Used in groups: [LegComplexEventDates](#)

### **180.2.1459 LegComplexEventType**

Identifies the type of complex event.

Type: [int](#)

Allowed values in ComplexEventTypeCodeSet:

Code	Name	Description
1	Capped	Capped
2	Trigger	Trigger
3	KnockInUp	Knock-in up
4	KnockInDown	Knock-in down
5	KnockOutUp	Knock-out up
6	KnockOutDown	Knock-out down
7	Underlying	Underlying
8	ResetBarrier	Reset Barrier
9	RollingBarrier	Rolling Barrier
10	OneTouch	One-touch
11	NoTouch	No-touch
12	DblOneTouch	Double one-touch
13	DblNoTouch	Double no-touch
14	FXComposite	Foreign exchange composite
15	FXQuanto	Foreign exchange Quanto
16	FXCrssCcy	Foreign exchange cross currency
17	StrkSpread	Strike spread
18	ClndrSpread	Calendar spread
19	PxObsvtn	Price observation (Asian or Lookback)
20	PassThrough	Pass-through
21	StrkSched	Strike schedule
22	EquityValuation	Equity valuation
23	DividendValuation	Dividend valuation

Used in groups: [LegComplexEvents](#)

#### **180.2.1460 LegComplexEventXID**

Identifier of this complex event for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **LegComplexEvents**

#### **180.2.1461 LegComplexEventXIDRef**

Reference to a complex event elsewhere in the message.

Type: **XIDREF**

Used in groups: **LegComplexEvents**

#### **180.2.1462 LegComplexOptPayoutAmount**

Cash amount indicating the pay out associated with an event. For binary options this is a fixed amount.

Type: **Amt**

Used in groups: **LegComplexEvents**

#### **180.2.1463 LegComplexOptPayoutCurrency**

Specifies the currency of the payout amount.

LegComplexOptPayoutCurrencyCodeSource(2944) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **LegComplexEvents**

#### **180.2.1464 LegComplexOptPayoutCurrencyCodeSource**

Identifies class or source of the LegComplexOptPayoutCurrency(2226) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [LegComplexEvents](#)

#### **180.2.1465 LegComplexOptPayoutPaySide**

Trade side of payout payer.

Type: [int](#)

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: [LegComplexEvents](#)

#### **180.2.1466 LegComplexOptPayoutPercentage**

Percentage of observed price for calculating the payout associated with the event.

Type: [Percentage](#)

Used in groups: [LegComplexEvents](#)

#### **180.2.1467 LegComplexOptPayoutReceiveSide**

Trade side of payout receiver.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **LegComplexEvents**

### **180.2.1468 LegComplexOptPayoutTime**

Specifies when the payout is to occur.

Type: **int**

Allowed values in ComplexOptPayoutTimeCodeSet:

Code	Name	Description
0	Close	Close
1	Open	Open
2	OfficialSettl	Official settlement
3	ValuationTime	Valuation time
4	ExchagneSettlTime	Exchange settlement time
5	DerivativesClose	Derivatives close
6	AsSpecified	As specified in master confirmation

Used in groups: **LegComplexEvents**

### **180.2.1469 LegComplexOptPayoutUnderlier**

Reference to the underlier whose payments are being passed through.

Type: **String**

Used in groups: **LegComplexEvents**

**180.2.1470 LegContractMultiplier**

Multileg instrument's individual security's ContractMultiplier.

See ContractMultiplier (23) field for description

Type: **float**

Used in components: **InstrumentLeg**

**180.2.1471 LegContractMultiplierUnit**

Indicates the type of multiplier being applied to the contract. Can be optionally used to further define what unit LegContractMultiplier(614) is expressed in.

Type: **int**

Allowed values in ContractMultiplierUnitCodeSet:

Code	Name	Description
0	Shares	Shares
1	Hours	Hours
2	Days	Days

Used in components: **InstrumentLeg**

**180.2.1472 LegContractPriceRefMonth**

Reference month if there is no applicable LegMaturityMonthYear(610) value for the contract or security.

Type: **MonthYear**

Used in components: **InstrumentLeg**

**180.2.1473 LegContractSettlMonth**

Specifies when the contract (i.e. MBS/TBA) will settle.

Type: **MonthYear**

Used in components: **InstrumentLeg**

**180.2.1474 LegContractualDefinition**

Specifies which contract definition, such as those published by ISDA, will apply for the terms of the trade. See <http://www.fpml.org/coding-scheme/contractual-definitions> for values.

Type: **String**

Used in groups: **LegFinancingContractualDefinitionsGrp**

**180.2.1475 LegContractualMatrixDate**

Specifies the publication date of the applicable version of the contract matrix. If not specified, the ISDA Standard Terms Supplement defines rules for which version of the matrix is applicable.

Type: **LocalMktDate**

Used in groups: **LegFinancingContractualMatrixGrp**

**180.2.1476 LegContractualMatrixSource**

Identifies the applicable contract matrix. See <http://www.fpml.org/coding-scheme/matrix-type-1-0.xml> for values.

Type: **String**

Used in groups: **LegFinancingContractualMatrixGrp**

**180.2.1477 LegContractualMatrixTerm**

Specifies the applicable key into the relevant contract matrix. In the case of 2000 ISDA Definitions Settlement Matrix for Early Termination and Swaptions, the **LegContractualMatrixTerm(42206)** is not applicable and is to be omitted. See <http://www.fpml.org/coding-scheme/credit-matrix-transaction-type> for values.

Type: **String**

Used in groups: **LegFinancingContractualMatrixGrp**

**180.2.1478 LegContraryInstructionEligibilityIndicator**

Identifies whether the option instrument is eligible for contrary instructions at the time of exercise. The contrariness of an instruction will be determined in the context of **LegInTheMoneyCondition(2682)**. When not specified, the eligibility is undefined or not applicable.

Type: **Boolean**

Used in components: **InstrumentLeg**

### **180.2.1479 LegConvertibleBondEquityID**

Identifies the equity in which a convertible bond can be converted to.

Type: **String**

Used in components: **InstrumentLeg**

### **180.2.1480 LegConvertibleBondEquityIDSource**

Identifies class or source of the LegConvertibleBondEquitySecurityID(2166) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization

Code	Name	Description
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [InstrumentLeg](#)

### 180.2.1481 LegCountryOfIssue

Multileg instrument's individual leg security's CountryOfIssue.

See CountryOfIssue (470) field for description

Type: [Country](#)

Used in components: [InstrumentLeg](#)

### 180.2.1482 LegCouponDayCount

The day count convention used in interest calculations for a bond or an interest bearing security.



Type: **int**

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.

Code	Name	Description
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.

Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: [InstrumentLeg](#)

### 180.2.1483 LegCouponFrequencyPeriod

Time unit multiplier for the frequency of the bond's coupon payment.

Type: [int](#)

Used in components: [InstrumentLeg](#)

**180.2.1484 LegCouponFrequencyUnit**

Time unit associated with the frequency of the bond's coupon payment.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: **InstrumentLeg**

**180.2.1485 LegCouponOtherDayCount**

The industry name of the day count convention not listed in LegCouponDayCount(2165).

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1486 LegCouponPaymentDate**

Multileg instrument's individual leg security's CouponPaymentDate.

See CouponPaymentDate (224) field for description

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCDate)

Type: **LocalMktDate**

Used in components: **InstrumentLeg**

**180.2.1487 LegCouponRate**

Multileg instrument's individual security's CouponRate.

See CouponRate (223) field for description

Type: **Percentage**

Used in components: **InstrumentLeg**

**180.2.1488 LegCouponType**

Specifies the coupon type of the bond.

Type: **int**

Allowed values in CouponTypeCodeSet:

Code	Name	Description
0	Zero	Zero
1	FixedRate	Fixed rate
2	FloatingRate	Floating rate
3	Structured	Structured

Used in components: **InstrumentLeg**

**180.2.1489 LegCoveredOrUncovered**

CoveredOrUncovered for leg of a multileg

See CoveredOrUncovered (203) field for description

Type: **int**

Allowed values in CoveredOrUncoveredCodeSet:

Code	Name	Description
0	Covered	Covered
1	Uncovered	Uncovered

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**, **TrdInstrmtLegExecGrp**, **TrdInstrmt-LegGrp**

**180.2.1490 LegCPPProgram**

The program under which a commercial paper is issued.

Type: **int**

Allowed values in CPPProgramCodeSet:

Code	Name	Description
1	Program3a3	3(a)(3). Arising out of a current transaction with a maturity less than 9 months.
2	Program42	4(2). Issued not involving any public offering.
3	Program3a2	3(a)(2). Issued or guaranteed by the US, state or territorial government.
4	Program3a3And3c7	3(a)(3) & 3(c)(7). Combination of 3(a)(3) and 3(c)(7).
5	Program3a4	3(a)(4). Religious, education, benevolent, fraternal, charitable or reformatory purposes.
6	Program3a5	3(a)(5). Issued by an institution supervised by state or federal authority or by an exempt farmer's cooperative.
7	Program3a7	3(a)(7). Issued by a receiver or trustee in bankruptcy.
8	Program3c7	3(c)(7). Qualified hedge-fund under the Investment Company Act of 1940.
99	Other	Other

Used in components: **InstrumentLeg**

**180.2.1491 LegCPRegType**

The registration type of a commercial paper issuance.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1492 LegCreditRating**

Multileg instrument's individual leg security's CreditRating.

See CreditRating (255) field for description

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **String**

Used in components: **InstrumentLeg**

#### **180.2.1493 LegCreditSupportAgreementDate**

The date of the ISDA Credit Support Agreement executed between the parties and intended to govern collateral arrangements for all OTC derivatives transactions between those parties.

Type: **LocalMktDate**

Used in components: **LegFinancingDetails**

#### **180.2.1494 LegCreditSupportAgreementDesc**

The type of ISDA Credit Support Agreement. See <http://www.fpml.org/coding-scheme/credit-support-agreement-type> for values.

Type: **String**

Used in components: **LegFinancingDetails**

#### **180.2.1495 LegCreditSupportAgreementID**

A common reference or unique identifier to identify the ISDA Credit Support Agreement executed between the parties.

Type: **String**

Used in components: **LegFinancingDetails**

#### **180.2.1496 LegCurrency**

Currency associated with a particular Leg's quantity

Type: **Currency**

Used in components: **InstrumentLeg**

**180.2.1497 LegCurrencyCodeSource**

Identifies class or source of the LegCurrency(556) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **InstrumentLeg**

**180.2.1498 LegCurrencyRatio**

Specifies the currency ratio between the currency used for a multileg price and the currency used by the outright book defined by the leg. Example: Multileg quoted in EUR, outright leg in USD and 1 EUR = 0,7 USD then LegCurrencyRatio = 0.7

Type: **float**

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**, **TrdInstrmtLegGrp**

**180.2.1499 LegCurrentCostBasis**

The amount that the current shares are worth. If this lot was liquidated, the total gain/loss for a trade is equal to the trade amount minus the current cost basis.

Type: **Amt**

Used in groups: **LegPreAllocGrp**



**180.2.1500 LegCustodialLotID**

An opaque identifier used to communicate the custodian's identifier for the lot. It is expected that this information would be provided by the custodian as part of a reconciliation process that occurs before trading.

Type: **String**

Used in groups: **LegPreAllocGrp**

**180.2.1501 LegDateAdjustment**

LegDateAdjustment is a subcomponent within the InstrumentLeg component. It is used to specify date adjustment parameters and rules. The date adjustments specified here applies to all adjustable dates for the instrument leg, unless specifically overridden elsewhere in the respective specified components further within the InstrumentLeg component.

Name	Mult.	Type	Description
<b>LegBusinessDayConvention</b>	[0..1]	CodeSet	
<b>LegBusinessCenterGrp</b>	[0..*]	Group	
<b>LegDateRollConvention</b>	[0..1]	CodeSet	

Used in components: **InstrumentLeg**

**180.2.1502 LegDatedDate**

The effective date of a new securities issue determined by its underwriters. Often but not always the same as the Issue Date and the Interest Accrual Date

Type: **LocalMktDate**

Used in components: **InstrumentLeg**

**180.2.1503 LegDateRollConvention**

The convention for determining a sequence of dates. It is used in conjunction with a specified frequency. The value defined here applies to all adjustable dates in the instrument leg unless specifically overridden.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEigthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.

Code	Name	Description
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [LegDateAdjustment](#)

#### **180.2.1504 LegDeliveryRouteOrCharter**

Specific delivery route or time charter average. Applicable to commodity freight contracts.

Type: [String](#)

Used in components: [InstrumentLeg](#)

#### **180.2.1505 LegDeliveryScheduleGrp**

The LegDeliveryScheduleGrp is a repeating subcomponent of the LegStream component used to detail step schedules associated with a delivery stream.

Name	Mult.	Type	Description
NoLegDeliverySchedules	[1..1]	NumInGroup	
LegDeliveryScheduleType	[0..1]	CodeSet	Required if NoLegDeliverySchedules(41408) > 0.
LegDeliveryScheduleXID	[0..1]	XID	
LegDeliveryScheduleNotional	[0..1]	Qty	
LegDeliveryScheduleNotionalUnitOfMeasure	[0..1]	CodeSet	
LegDeliveryScheduleNotionalCommodityFrequency	[0..1]	CodeSet	
LegDeliveryScheduleNegativeTolerance	[0..1]	float	
LegDeliverySchedulePositiveTolerance	[0..1]	float	
LegDeliveryScheduleToleranceUnitOfMeasure	[0..1]	CodeSet	
LegDeliveryScheduleToleranceType	[0..1]	CodeSet	Conditionally required when LegDeliveryScheduleNegativeTolerance(41414) or LegDeliverySchedulePositiveTolerance(41415) is specified.
LegDeliveryScheduleSettlCountry	[0..1]	Country	
LegDeliveryScheduleSettlTimeZone	[0..1]	String	
LegDeliveryScheduleSettlFlowType	[0..1]	CodeSet	
LegDeliveryScheduleSettlHolidaysProcessingInstruction	[0..1]	CodeSet	
LegDeliveryScheduleSettlDayGrp	[0..*]	Group	

Used in groups: [LegStreamGrp](#)

### 180.2.1506 LegDeliveryScheduleNegativeTolerance

Specifies the negative tolerance value. The value may be an absolute quantity or a percentage, as specified in LegDeliveryScheduleToleranceType(41417). Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **float**

Used in groups: [LegDeliveryScheduleGrp](#)

**180.2.1507 LegDeliveryScheduleNotional**

Physical delivery quantity.

Type: Qty

Used in groups: LegDeliveryScheduleGrp

**180.2.1508 LegDeliveryScheduleNotionalCommodityFrequency**

The frequency of notional delivery.

Type: int

Allowed values in StreamNotionalCommodityFrequencyCodeSet:

Code	Name	Description
0	Term	Term
1	PerBusinessDay	Per business day
2	PerCalculationPeriod	Per calculation period
3	PerSettlPeriod	Per settlement period
4	PerCalendarDay	Per calendar day
5	PerHour	Per hour
6	PerMonth	Per month

Used in groups: LegDeliveryScheduleGrp

**180.2.1509 LegDeliveryScheduleNotionalUnitOfMeasure**

Specifies the delivery quantity unit of measure (UOM).

Type: String

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters

Code	Name	Description
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)

Code	Name	Description
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart

Code	Name	Description
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [LegDeliveryScheduleGrp](#)

#### **180.2.1510 LegDeliverySchedulePositiveTolerance**

Specifies the positive tolerance value. The value may be an absolute quantity or a percentage, as specified in [LegDeliveryScheduleToleranceType\(41417\)](#). Value may exceed agreed upon value. Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: [float](#)

Used in groups: [LegDeliveryScheduleGrp](#)

#### **180.2.1511 LegDeliveryScheduleSettlCountry**

Specifies the country where delivery takes place. Uses ISO 3166 2-character country code.

Type: [Country](#)

Used in groups: [LegDeliveryScheduleGrp](#)

#### **180.2.1512 LegDeliveryScheduleSettlDay**

Specifies the day or group of days for delivery.



Type: **int**

Allowed values in DeliveryScheduleSettlDayCodeSet:

Code	Name	Description
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday
8	AllWeekdays	All weekdays
9	AllDays	All days
10	AllWeekends	All weekends

Used in groups: **LegDeliveryScheduleSettlDayGrp**

#### 180.2.1513 LegDeliveryScheduleSettlDayGrp

The LegDeliveryScheduleSettlDayGrp is a repeating subcomponent of the LegDeliveryScheduleGrp component used to detail commodity delivery days.

Name	Mult.	Type	Description
NoLegDeliveryScheduleSettlDays	[1..1]	NumInGroup	
LegDeliveryScheduleSettlDay	[0..1]	CodeSet	Required if NoLegDeliveryScheduleSettlDays(41422) > 0.
LegDeliveryScheduleSettlTotalHours	[0..1]	int	
LegDeliveryScheduleSettlTimeGrp	[0..*]	Group	

Used in groups: **LegDeliveryScheduleGrp**

#### 180.2.1514 LegDeliveryScheduleSettlEnd

The scheduled end time for the delivery of the commodity where delivery occurs over specified times. The format of the time value is specified in LegDeliveryScheduleSettlTimeType(41428).

Type: **String**

Used in groups: **LegDeliveryScheduleSettlTimeGrp**

### **180.2.1515 LegDeliveryScheduleSettlFlowType**

Specifies the delivery flow type.

Type: **int**

Allowed values in DeliveryScheduleSettlFlowTypeCodeSet:

Code	Name	Description
0	AllTimes	All times
1	OnPeak	On peak
2	OffPeak	Off peak
3	Base	Base
4	BlockHours	Block hours
5	Other	Other

Used in groups: **LegDeliveryScheduleGrp**

### **180.2.1516 LegDeliveryScheduleSettlHolidaysProcessingInstruction**

Indicates whether holidays are included in the settlement periods. Required for electricity contracts.

Type: **int**

Allowed values in DeliveryScheduleSettlHolidaysProcessingInstructionCodeSet:

Code	Name	Description
0	DoNotIncludeHolidays	Do not include holidays
1	IncludeHolidays	Include holidays

Used in groups: **LegDeliveryScheduleGrp**

**180.2.1517 LegDeliveryScheduleSettlStart**

The scheduled start time for the delivery of the commodity where delivery occurs over specified times. The format of the time value is specified in LegDeliveryScheduleSettlTimeType(41428).

Type: **String**

Used in groups: **LegDeliveryScheduleSettlTimeGrp**

**180.2.1518 LegDeliveryScheduleSettlTimeGrp**

The LegDeliveryScheduleSettlTimeGrp is a repeating subcomponent of the LegDeliveryScheduleSettlDayGrp component used to detail commodity delivery time periods.

Name	Mult.	Type	Description
NoLegDeliveryScheduleSettlTimes	[1..1]	NumInGroup	
LegDeliveryScheduleSettlStart	[0..1]	String	Required if NoLegDeliveryScheduleSettlTimes(41425) > 0.
LegDeliveryScheduleSettlEnd	[0..1]	String	Required if NoLegDeliveryScheduleSettlTimes(41425) > 0.
LegDeliveryScheduleSettlTimeType	[0..1]	CodeSet	May be defaulted to market convention or bilaterally agreed if not specified.

Used in groups: **LegDeliveryScheduleSettlDayGrp**

**180.2.1519 LegDeliveryScheduleSettlTimeType**

Specifies the format of the delivery start and end time values.

Type: **int**

Allowed values in DeliveryScheduleSettlTimeTypeCodeSet:

Code	Name	Description
0	Hour	Hour of the day. Applicable for electricity contracts. Time value is expressed as an integer hour of the day (1-24). The delivery start/end hour is specified as the end of the included hour. For example, a start hour of "4" begins at 3 a.m.; an end hour of "20" ends at 8 p.m.; a start hour of "1" and end hour of "24" indicates midnight to midnight delivery.

Code	Name	Description
1	Timestamp	HH:MM time format. Applicable for gas contracts. Time value is expressed using a 24-hour time format. For example, a time value of "13:30" is 1:30 p.m.

Used in groups: [LegDeliveryScheduleSettlTimeGrp](#)

#### **180.2.1520 LegDeliveryScheduleSettlTimeZone**

Delivery timezone specified as "prevailing" rather than "standard" or "daylight".

See [http://www.fixtradingcommunity.org/codelists#Prevailing\\_Timezones](http://www.fixtradingcommunity.org/codelists#Prevailing_Timezones) for code list of applicable prevailing timezones.

Type: [String](#)

Used in groups: [LegDeliveryScheduleGrp](#)

#### **180.2.1521 LegDeliveryScheduleSettlTotalHours**

The sum of the total hours specified in the LegDeliveryScheduleSettlTimeGrp component.

Type: [int](#)

Used in groups: [LegDeliveryScheduleSettlDayGrp](#)

#### **180.2.1522 LegDeliveryScheduleToleranceType**

Specifies the tolerance value type.

Type: [int](#)

Allowed values in DeliveryScheduleToleranceTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in groups: [LegDeliveryScheduleGrp](#)

**180.2.1523 LegDeliveryScheduleToleranceUnitOfMeasure**

Specifies the tolerance value's unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: **LegDeliveryScheduleGrp**

### 180.2.1524 LegDeliveryScheduleType

Specifies the type of delivery schedule.

Type: **int**

Allowed values in DeliveryScheduleTypeCodeSet:

Code	Name	Description
0	Notional	Notional
1	Delivery	Delivery

Code	Name	Description
2	PhysicalSettlPeriods	Physical settlement period

Used in groups: [LegDeliveryScheduleGrp](#)

#### 180.2.1525 LegDeliveryScheduleXID

Identifier for this instance of delivery schedule for cross referencing elsewhere in the message.

Type: [XID](#)

Used in groups: [LegDeliveryScheduleGrp](#)

#### 180.2.1526 LegDeliveryStreamCommoditySource

The SCoTA coal cargo origin, mining region, mine(s), mining complex(es), loadout(s) or river dock(s) or other point(s) of origin that seller and buyer agree are acceptable origins for the coal product. For international coal transactions, this is the origin of the coal product.

See <http://www.fpml.org/coding-scheme/commodity-coal-product-source> for values.

Type: [String](#)

Used in groups: [LegDeliveryStreamCommoditySourceGrp](#)

#### 180.2.1527 LegDeliveryStreamCommoditySourceGrp

The LegDeliveryStreamCommoditySourceGrp is a repeating subcomponent of the LegDeliveryStream component used to detail the origins or sources of the commodity.

Name	Mult.	Type	Description
<a href="#">NoLegDeliveryStreamCommoditySources</a>	[1..1]	NumInGroup	
<a href="#">LegDeliveryStreamCommoditySource</a>	[0..1]	String	Required if <a href="#">NoLegDeliveryStreamCommoditySources</a> (41460) > 0.

Used in components: [LegDeliveryStream](#)



**180.2.1528 LegDeliveryStream**

The LegDeliveryStream component is a subcomponent of the LegStream used to detail the attributes of a physical delivery stream in a swap.

Name	Mult.	Type	Description
LegDeliveryStreamType	[0..1]	CodeSet	
LegDeliveryStreamCommoditySource-Grp	[0..*]	Group	
LegDeliveryStreamPipeline	[0..1]	String	
LegDeliveryStreamEntryPoint	[0..1]	String	
LegDeliveryStreamWithdrawalPoint	[0..1]	String	
LegDeliveryStreamDeliveryPoint	[0..1]	String	
LegDeliveryStreamDelivery-PointSource	[0..1]	CodeSet	
LegDeliveryStreamDeliveryPointDesc	[0..1]	String	
LegDeliveryStreamDeliveryRestriction	[0..1]	CodeSet	
LegDeliveryStreamDeliveryContingency	[0..1]	String	
LegDeliveryStreamDeliveryContingent-PartySide	[0..1]	CodeSet	
LegDeliveryStreamDeliverAtSourceIndicator	[0..1]	Boolean	
LegDeliveryStreamRiskApportionment	[0..1]	String	
LegDeliveryStreamRiskApportionmentSource	[0..1]	String	
LegDeliveryStreamCycleGrp	[0..*]	Group	
LegDeliveryStreamTitleTransferLocation	[0..1]	String	
LegDeliveryStreamTitleTransferCondition	[0..1]	CodeSet	
LegDeliveryStreamImporterOfRecord	[0..1]	String	
LegDeliveryStreamNegativeTolerance	[0..1]	float	
LegDeliveryStreamPositiveTolerance	[0..1]	float	
LegDeliveryStreamToleranceUnitOfMeasure	[0..1]	CodeSet	
LegDeliveryStreamToleranceType	[0..1]	CodeSet	

Name	Mult.	Type	Description
LegDeliveryStreamToleranceOption-Side	[0..1]	CodeSet	
LegDeliveryStreamTotalPositiveTolerance	[0..1]	Percentage	
LegDeliveryStreamTotalNegativeTolerance	[0..1]	Percentage	
LegDeliveryStreamNotionalConversionFactor	[0..1]	float	
LegDeliveryStreamTransportEquipment	[0..1]	String	
LegDeliveryStreamElectingPartySide	[0..1]	CodeSet	
LegDeliveryStreamRouteOrCharter	[0..1]	String	

Used in groups: [LegStreamGrp](#)

### 180.2.1529 LegDeliveryStreamCycleDesc

The delivery cycles during which the oil product will be transported in the pipeline.

Type: [String](#)

Used in groups: [LegDeliveryStreamCycleGrp](#)

### 180.2.1530 LegDeliveryStreamCycleGrp

The LegDeliveryStreamCycleGrp is a repeating subcomponent of the LegDeliveryStream component used to detail delivery cycles during which the oil product will be transported in the pipeline.

Name	Mult.	Type	Description
NoLegDeliveryStreamCycles	[1..1]	NumInGroup	
LegDeliveryStreamCycleDesc	[0..1]	String	Required if NoLegDeliveryStreamCycles(41456) > 0.
EncodedLegDeliveryStreamCycleDescLen	[0..1]	Length	Must be set if EncodedLegDeliveryStreamCycleDesc(41459) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedLegDeliveryStreamCycleDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the LegDeliveryStreamCycleDesc(41457) field in the encoded format specified via the MessageEncoding(347) field.

Used in components: [LegDeliveryStream](#)

### 180.2.1531 LegDeliveryStreamDeliverAtSourceIndicator

When this element is specified and set to 'Y', delivery of the coal product is to be at its source.

Type: [Boolean](#)

Used in components: [LegDeliveryStream](#)

### 180.2.1532 LegDeliveryStreamDeliveryContingency

Specifies the electricity delivery contingency. See

<http://www.fpml.org/coding-scheme/electricity-transmission-contingency> for values.

Type: [String](#)

Used in components: [LegDeliveryStream](#)

### 180.2.1533 LegDeliveryStreamDeliveryContingentPartySide

The trade side value of the party responsible for electricity delivery contingency.

Type: [int](#)

Allowed values in DeliveryStreamElectingPartySideCodeSet:

Code	Name	Description
0	Buyer	Buyer
1	Seller	Seller

Used in components: [LegDeliveryStream](#)

**180.2.1534 LegDeliveryStreamDeliveryPoint**

The point at which the commodity product will be delivered and received. Value specified should follow market convention appropriate for the commodity product.

For bullion, see <http://www.fpml.org/coding-scheme/bullion-delivery-location> for values.

Type: **String**

Used in components: **LegDeliveryStream**

**180.2.1535 LegDeliveryStreamDeliveryPointDesc**

Description of the delivery point identified in LegDeliveryStreamDeliveryPoint(41433).

Type: **String**

Used in components: **LegDeliveryStream**

**180.2.1536 LegDeliveryStreamDeliveryPointSource**

Identifies the class or source of LegDeliveryStreamDeliveryPoint(41433).

Type: **int**

Allowed values in DeliveryStreamDeliveryPointSourceCodeSet:

Code	Name	Description
0	Proprietary	Proprietary
1	EIC	Energy Identification Code (EIC). Energy Identification Code specifies the location or connection point codes of energy delivery. See <a href="http://www.entsog.eu/eic-codes/eic-location-codes-v">http://www.entsog.eu/eic-codes/eic-location-codes-v</a> or <a href="http://www.eiccodes.eu">http://www.eiccodes.eu</a> for more information and allocated values to use in DeliveryStreamDeliveryPoint(41062).

Used in components: **LegDeliveryStream**

**180.2.1537 LegDeliveryStreamDeliveryRestriction**

Specifies under what conditions the buyer and seller should be excused of their delivery obligations.

Type: **int**

Allowed values in DeliveryStreamDeliveryRestrictionCodeSet:

Code	Name	Description
1	Firm	Firm. Never excused of delivery obligations.
2	NonFirm	Interruptable or non-firm. Excused when interrupted for any reason or for no reason without liability.
3	ForceMajeure	Force majeure. Excused when prevented by force majeure.
4	SystemFirm	System firm. Must be supplied from the owned or controlled generation of pre-existing purchased power assets of the system specified.
5	UnitFirm	Unit firm. Must be supplied from the generation asset specified.

Used in components: **LegDeliveryStream**

#### **180.2.1538 LegDeliveryStreamElectingPartySide**

A reference to the party able to choose whether the gas is delivered for a particular period e.g. a swing or interruptible contract.

Type: **int**

Allowed values in DeliveryStreamElectingPartySideCodeSet:

Code	Name	Description
0	Buyer	Buyer
1	Seller	Seller

Used in components: **LegDeliveryStream**

#### **180.2.1539 LegDeliveryStreamEntryPoint**

The point at which the commodity will enter the delivery mechanism or pipeline.

Type: **String**

Used in components: **LegDeliveryStream**

**180.2.1540 LegDeliveryStreamImporterOfRecord**

A party, not necessarily of the trade, who is the Importer of Record for the purposes of paying customs duties and applicable taxes or costs related to importation.

Type: **String**

Used in components: **LegDeliveryStream**

**180.2.1541 LegDeliveryStreamNegativeTolerance**

Specifies the negative tolerance value. The value may be an absolute quantity or a percentage, as specified in LegDeliveryStreamToleranceType(41445). Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **float**

Used in components: **LegDeliveryStream**

**180.2.1542 LegDeliveryStreamNotionalConversionFactor**

If the notional quantity is specified in a unit that does not match the unit in which the commodity reference price is quoted, the scaling or conversion factor used to convert the commodity reference price unit into the notional quantity unit should be stated here. If there is no conversion, this field is not intended to be used.

Type: **float**

Used in components: **LegDeliveryStream**

**180.2.1543 LegDeliveryStreamPipeline**

The name of the oil delivery pipeline.

Type: **String**

Used in components: **LegDeliveryStream**

**180.2.1544 LegDeliveryStreamPositiveTolerance**

Specifies the positive tolerance value. The value may be an absolute quantity or a percentage, as specified in LegDeliveryStreamToleranceType(41445). Value may exceed agreed upon value. Percent-

age value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **float**

Used in components: **LegDeliveryStream**

#### **180.2.1545 LegDeliveryStreamRiskApportionment**

Specifies how the parties to the trade apportion responsibility for the delivery of the commodity product.

See [http://www.fixtradingcommunity.org/codelists#Risk\\_Apportionment](http://www.fixtradingcommunity.org/codelists#Risk_Apportionment) for the details of the external code list.

Type: **String**

Used in components: **LegDeliveryStream**

#### **180.2.1546 LegDeliveryStreamRiskApportionmentSource**

Specifies the source or legal framework for the risk apportionment.

See [http://www.fixtradingcommunity.org/codelists#Risk\\_Apportionment\\_Source](http://www.fixtradingcommunity.org/codelists#Risk_Apportionment_Source) for the details of the external code list.

Type: **String**

Used in components: **LegDeliveryStream**

#### **180.2.1547 LegDeliveryStreamRouteOrCharter**

Specific delivery route or time charter average. Applicable to commodity freight swaps.

Type: **String**

Used in components: **LegDeliveryStream**

#### **180.2.1548 LegDeliveryStreamTitleTransferCondition**

Specifies the condition of title transfer.

Type: **int**

Allowed values in DeliveryStreamTitleTransferConditionCodeSet:

Code	Name	Description
0	Transfers	Transfers with risk of loss
1	DoesNotTransfer	Does not transfer with risk of loss

Used in components: [LegDeliveryStream](#)

#### **180.2.1549 LegDeliveryStreamTitleTransferLocation**

Specifies the title transfer location.

Type: [String](#)

Used in components: [LegDeliveryStream](#)

#### **180.2.1550 LegDeliveryStreamToleranceOptionSide**

Indicates whether the tolerance is at the seller's or buyer's option.

Type: [int](#)

Allowed values in DeliveryStreamToleranceOptionSideCodeSet:

Code	Name	Description
1	Buyer	Buyer
2	Seller	Seller

Used in components: [LegDeliveryStream](#)

#### **180.2.1551 LegDeliveryStreamToleranceType**

Specifies the tolerance value type.

Type: [int](#)

Allowed values in DeliveryScheduleToleranceTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute



Code	Name	Description
1	Percentage	Percentage

Used in components: [LegDeliveryStream](#)

### 180.2.1552 LegDeliveryStreamToleranceUnitOfMeasure

Specifies the tolerance value's unit of measure (UOM).

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide

Code	Name	Description
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent

Code	Name	Description
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [LegDeliveryStream](#)

### 180.2.1553 LegDeliveryStreamTotalNegativeTolerance

The negative percent tolerance which applies to the total quantity delivered over all shipment periods.

Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **Percentage**

Used in components: **LegDeliveryStream**

#### **180.2.1554 LegDeliveryStreamTotalPositiveTolerance**

The positive percent tolerance which applies to the total quantity delivered over all shipment periods.

Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **Percentage**

Used in components: **LegDeliveryStream**

#### **180.2.1555 LegDeliveryStreamTransportEquipment**

The transportation equipment with which the commodity product will be delivered and received.

Type: **String**

Used in components: **LegDeliveryStream**

#### **180.2.1556 LegDeliveryStreamType**

Specifies the type of delivery stream.

Type: **int**

Allowed values in DeliveryStreamTypeCodeSet:

Code	Name	Description
0	Periodic	Periodic (default if not specified)
1	Initial	Initial
2	Single	Single

Used in components: **LegDeliveryStream**

**180.2.1557 LegDeliveryStreamWithdrawalPoint**

The point at which the commodity product will be withdrawn prior to delivery.

Type: **String**

Used in components: **LegDeliveryStream**

**180.2.1558 LegDeliveryType**

Identifies type of settlement.

Type: **int**

Allowed values in DeliveryTypeCodeSet:

Code	Name	Description
0	VersusPayment	"Versus Payment": Deliver (if sell) or Receive (if buy) vs. (against) Payment
1	Free	"Free": Deliver (if sell) or Receive (if buy) Free
2	TriParty	Tri-Party
3	HoldInCustody	Hold In Custody
4	DeliverByValue	Deliver-by-Value. In the context of EU SFTR reporting, indicates that the transaction is to be or was settled using the DBV mechanism.

Used in components: **LegFinancingDetails**

**180.2.1559 LegDetachmentPoint**

Upper bound percentage of the loss the tranche can endure.

Type: **Percentage**

Used in components: **InstrumentLeg**

**180.2.1560 LegDifferentialPrice**

Used in pricing a group of individual Trade at Settlement (TAS) and Trade At Marker (TAM) contracts as an atomic unit. The value is the negotiated currency offset either at settlement (TAS) or at the time specified in the product definition (TAM). The final contract price is reported in LegLastPx(637).

Type: **PriceOffset**

Used in groups: **TrdInstrmtLegGrp**

### **180.2.1561 LegDividendAccrualFixedRate**

The dividend accrual fixed rate per annum expressed as a decimal.

A value of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **LegDividendConditions**

### **180.2.1562 LegDividendAccrualFloatingRate**

The LegDividendAccrualFloatingRate component is a subcomponent of LegDividendConditions used to define the dividend accrual floating rate attributes of dividend payment conditions.

<b>Name</b>	<b>Mult.</b>	<b>Type</b>	<b>Description</b>
<b>LegDividendFloatingRateIndex</b>	[0..1]	String	
<b>LegDividendFloatingRateIndex-CurvePeriod</b>	[0..1]	int	Conditionally required when LegDividendFloatingRateIndexCurveUnit(42314) is specified.
<b>LegDividendFloatingRateIndexCurveUnit</b>	[0..1]	CodeSet	Conditionally required when LegDividendFloatingRateIndexCurvePeriod(42313) is specified.
<b>LegDividendFloatingRateMultiplier</b>	[0..1]	float	
<b>LegDividendFloatingRateSpread</b>	[0..1]	PriceOffset	
<b>LegDividendFloatingRateSpreadPositionType</b>	[0..1]	CodeSet	
<b>LegDividendFloatingRateTreatment</b>	[0..1]	CodeSet	
<b>LegDividendCapRate</b>	[0..1]	Percentage	
<b>LegDividendCapRateBuySide</b>	[0..1]	CodeSet	
<b>LegDividendCapRateSellSide</b>	[0..1]	CodeSet	
<b>LegDividendFloorRate</b>	[0..1]	Percentage	
<b>LegDividendFloorRateBuySide</b>	[0..1]	CodeSet	
<b>LegDividendFloorRateSellSide</b>	[0..1]	CodeSet	
<b>LegDividendInitialRate</b>	[0..1]	Percentage	
<b>LegDividendFinalRateRoundingDirection</b>	[0..1]	CodeSet	

Name	Mult.	Type	Description
LegDividendFinalRatePrecision	[0..1]	int	
LegDividendAveragingMethod	[0..1]	CodeSet	
LegDividendNegativeRateTreatment	[0..1]	CodeSet	

Used in components: [LegDividendConditions](#)

### 180.2.1563 LegDividendAccrualPaymentDateAdjusted

The adjusted accrual payment date.

Type: [LocalMktDate](#)

Used in components: [LegDividendAccrualPaymentDate](#)

### 180.2.1564 LegDividendAccrualPaymentDateBusinessCenter

The business center calendar used for date adjustment of the instrument's dividend accrual payment date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [LegDividendAccrualPaymentDateBusinessCenterGrp](#)

### 180.2.1565 LegDividendAccrualPaymentDateBusinessCenterGrp

LegDividendAccrualPaymentDateBusinessCenterGrp is a repeating subcomponent within the LegDividendAccrualPaymentDate component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
NoLegDividendAccrualPaymentDate-BusinessCenters	[1..1]	NumInGroup	
LegDividendAccrualPaymentDateBusinessCenter	[0..1]	String	Required if NoLegDividendAccrualPaymentDate-BusinessCenters(42310) > 0.

Used in components: [LegDividendAccrualPaymentDate](#)

**180.2.1566 LegDividendAccrualPaymentDateBusinessDayConvention**

Accrual payment date adjustment business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **LegDividendAccrualPaymentDate**

**180.2.1567 LegDividendAccrualPaymentDate**

The LegDividendAccrualPaymentDate component is a subcomponent of LegDividendConditions used to report the dividend accrual payment date.

Name	Mult.	Type	Description
<b>LegDividendAccrualPaymentDateRelativeTo</b>	[0..1]	int	
<b>LegDividendAccrualPaymentDateOffsetPeriod</b>	[0..1]	int	Conditionally required when LegDividendAccrualPaymentDateOffsetUnit(42332) is specified.
<b>LegDividendAccrualPaymentDateOffsetUnit</b>	[0..1]	CodeSet	Conditionally required when LegDividendAccrualPaymentDateOffsetPeriod(42331) is specified.
<b>LegDividendAccrualPaymentDateOffsetDayType</b>	[0..1]	CodeSet	
<b>LegDividendAccrualPaymentDateUnadjusted</b>	[0..1]	LocalMktDate	



Name	Mult.	Type	Description
<a href="#">LegDividendAccrualPaymentDateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The value would be specific to this instance of LegDividendAccrualPaymentDate.
<a href="#">LegDividendAccrualPaymentDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The values would be specific to this instance of LegDividendAccrualPaymentDate.
<a href="#">LegDividendAccrualPaymentDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [LegDividendConditions](#)

### 180.2.1568 LegDividendAccrualPaymentDateOffsetDayType

Specifies the day type of the relative accrual payment date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegDividendAccrualPaymentDate](#)

### 180.2.1569 LegDividendAccrualPaymentDateOffsetPeriod

Time unit multiplier for the relative accrual payment date offset.

Type: [int](#)

Used in components: [LegDividendAccrualPaymentDate](#)

#### **180.2.1570 LegDividendAccrualPaymentDateOffsetUnit**

Time unit associated with the relative accrual payment date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegDividendAccrualPaymentDate](#)

#### **180.2.1571 LegDividendAccrualPaymentDateRelativeTo**

Specifies the anchor date when the accrual payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [LegDividendAccrualPaymentDate](#)

#### **180.2.1572 LegDividendAccrualPaymentDateUnadjusted**

The unadjusted accrual payment date.

Type: [LocalMktDate](#)

Used in components: [LegDividendAccrualPaymentDate](#)

#### **180.2.1573 LegDividendAmountType**

Indicates how the gross cash dividend amount per share is determined.

Type: [int](#)

Allowed values in DividendAmountTypeCodeSet:

Code	Name	Description
0	RecordAmount	Record amount. 100% of the gross cash dividend per share paid over record date during relevant dividend period.
1	ExAmount	Ex amount. 100% of gross cash dividend per share paid after the ex-dividend date during relevant dividend period.
2	PaidAmount	Paid amount. 100% of gross cash dividend per share paid during relevant dividend period.
3	PerMasterConfirm	As specified in master confirmation. The amount is determined as provided in the relevant master confirmation.

Used in components: [LegDividendConditions](#)

#### **180.2.1574 LegDividendAveragingMethod**

When averaging is applicable, used to specify whether a weighted or unweighted average method of calculation is to be used.

Type: [int](#)

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: [LegDividendAccrualFloatingRate](#)

#### **180.2.1575 LegDividendCapRate**

The cap rate, if any, which applies to the floating rate. It is only required where the floating rate is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as "0.05".

Type: [Percentage](#)

Used in components: [LegDividendAccrualFloatingRate](#)

**180.2.1576 LegDividendCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1577 LegDividendCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1578 LegDividendCashEquivalentPercentage**

Declared cash-equivalent dividend percentage.

A value of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **LegDividendConditions**

**180.2.1579 LegDividendCashPercentage**

Declared cash dividend percentage.

A value of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **LegDividendConditions**

**180.2.1580 LegDividendComposition**

Defines how the composition of dividends is to be determined.

Type: **int**

Allowed values in DividendCompositionCodeSet:

Code	Name	Description
0	EquityAmountReceiver	Equity amount receiver election. The equity amount receiver determines the composition of dividends (subject to conditions).
1	CalculationAgent	Calculation agent election. The calculation agent determines the composition of dividends (subject to conditions).

Used in components: **LegDividendConditions**

**180.2.1581 LegDividendCompoundingMethod**

The compounding method to be used when more than one dividend period contributes to a single payment.

Type: **int**

Allowed values in PaymentStreamCompoundingMethodCodeSet:

Code	Name	Description
0	None	None
1	Flat	Flat
2	Straight	Straight
3	SpreadExclusive	Spread exclusive

Used in components: [LegDividendConditions](#)

### 180.2.1582 LegDividendConditions

The LegDividendConditions component is a subcomponent of LegPaymentStream used to specify the conditions' valuations and dates governing the payment of dividends.

Name	Mult.	Type	Description
<a href="#">LegDividendReinvestmentIndicator</a>	[0..1]	Boolean	
<a href="#">LegDividendEntitlementEvent</a>	[0..1]	CodeSet	
<a href="#">LegDividendAmountType</a>	[0..1]	CodeSet	
<a href="#">LegDividendUnderlierRefID</a>	[0..1]	String	
<a href="#">LegDividendPeriodGrp</a>	[0..*]	Group	
<a href="#">LegExtraordinaryDividendPartySide</a>	[0..1]	CodeSet	
<a href="#">LegExtraordinaryDividendAmountType</a>	[0..1]	CodeSet	
<a href="#">LegExtraordinaryDividendCurrency</a>	[0..1]	Currency	
<a href="#">LegExtraordinaryDividendDeterminationMethod</a>	[0..1]	String	
<a href="#">LegDividendFXTriggerDate</a>	[0..1]	Component	
<a href="#">LegDividendAccrualFloatingRate</a>	[0..1]	Component	
<a href="#">LegDividendAccrualFixedRate</a>	[0..1]	Percentage	
<a href="#">LegDividendAccrualPaymentDate</a>	[0..1]	Component	
<a href="#">LegDividendCompoundingMethod</a>	[0..1]	CodeSet	
<a href="#">LegDividendNumOfIndexUnits</a>	[0..1]	int	
<a href="#">LegDividendCashPercentage</a>	[0..1]	Percentage	
<a href="#">LegDividendCashEquivalentPercentage</a>	[0..1]	Percentage	
<a href="#">LegNonCashDividendTreatment</a>	[0..1]	CodeSet	
<a href="#">LegDividendComposition</a>	[0..1]	CodeSet	
<a href="#">LegSpecialDividendsIndicator</a>	[0..1]	Boolean	
<a href="#">LegMaterialDividendsIndicator</a>	[0..1]	Boolean	
<a href="#">LegOptionsExchangeDividendsIndicator</a>	[0..1]	Boolean	
<a href="#">LegAdditionalDividendsIndicator</a>	[0..1]	Boolean	
<a href="#">LegAllDividendsIndicator</a>	[0..1]	Boolean	

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.1583 LegDividendEntitlementEvent**

Defines the contract event which the receiver of the derivative is entitled to the dividend.

Type: **int**

Allowed values in DividendEntitlementEventCodeSet:

Code	Name	Description
0	ExDate	Ex-date. Dividend entitlement is on the dividend ex-date.
1	RecordDate	Record date. Dividend entitlement is on the dividend record date.

Used in components: **LegDividendConditions**

**180.2.1584 LegDividendFinalRatePrecision**

Specifies the rounding precision of the final rate in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1585 LegDividendFinalRateRoundingDirection**

Specifies the rounding direction of the final rate.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1586 LegDividendFloatingRateIndex**

The dividend accrual floating rate index.

Type: **String**

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1587 LegDividendFloatingRateIndexCurvePeriod**

Time unit multiplier for the dividend accrual floating rate index curve.

Type: **int**

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1588 LegDividendFloatingRateIndexCurveUnit**

Time unit associated with the dividend accrual floating rate index curve period.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1589 LegDividendFloatingRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This should only be included if the multiplier is not equal to 1 (one) for the term of the contract.

Type: **float**

Used in components: **LegDividendAccrualFloatingRate**



**180.2.1590 LegDividendFloatingRateSpread**

The basis points spread from the index specified in LegDividendFloatingRateIndex(42312).

Type: **PriceOffset**

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1591 LegDividendFloatingRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1592 LegDividendFloatingRateTreatment**

Specifies the yield calculation treatment for the index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1593 LegDividendFloorRate**

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate. The rate is expressed as a decimal, e.g. 5% is represented as "0.05".

Type: **Percentage**

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1594 LegDividendFloorRateBuySide**

Reference to the buyer of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1595 LegDividendFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1596 LegDividendFXTriggerDateAdjusted**

The adjusted FX trigger date.

Type: **LocalMktDate**

Used in components: **LegDividendFXTriggerDate**

**180.2.1597 LegDividendFXTriggerDateBusinessCenter**

The business center calendar used for date adjustment of the instrument's FX trigger date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegDividendFXTriggerDateBusinessCenterGrp**

**180.2.1598 LegDividendFXTriggerDateBusinessCenterGrp**

LegDividendFXTriggerDateBusinessCenterGrp is a repeating subcomponent within the LegDividendFXTriggerDate component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
NoLegDividendFXTriggerDateBusiness-Centers	[1..1]	NumInGroup	
LegDividendFXTriggerDateBusiness-Center	[0..1]	String	Required if NoLegDividendFXTriggerDateBusiness-Centers(42364) > 0.

Used in components: **LegDividendFXTriggerDate**

**180.2.1599 LegDividendFXTriggerDateBusinessDayConvention**

The business day convention used for the FX trigger date adjustment.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegDividendFXTriggerDate](#)

### 180.2.1600 LegDividendFXTriggerDate

The LegDividendFXTriggerDate component is a subcomponent of LegDividendConditions used to report the dividend date when a foreign exchange trade is triggered.

Name	Mult.	Type	Description
<a href="#">LegDividendFXTriggerDateRelativeTo</a>	[0..1]	int	
<a href="#">LegDividendFXTriggerDateOffsetPeriod</a>	[0..1]	int	Conditionally required when <a href="#">LegDividendFXTriggerDateOffsetUnit(42359)</a> is specified.
<a href="#">LegDividendFXTriggerDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when <a href="#">LegDividendFXTriggerDateOffsetPeriod(42358)</a> is specified.
<a href="#">LegDividendFXTriggerDateOffsetDay-Type</a>	[0..1]	CodeSet	
<a href="#">LegDividendFXTriggerDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegDividendFXTriggerDateBusiness-DayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The value would be specific to this instance of LegDividendFXTriggerDate.
<a href="#">LegDividendFXTriggerDateBusiness-CenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The values would be specific to this instance of LegDividendFXTriggerDate.

Name	Mult.	Type	Description
LegDividendFXTriggerDateAdjusted	[0..1]	LocalMktDate	

Used in components: [LegDividendConditions](#)

#### **180.2.1601 LegDividendFXTriggerDateOffsetDayType**

Specifies the day type of the relative FX trigger date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegDividendFXTriggerDate](#)

#### **180.2.1602 LegDividendFXTriggerDateOffsetPeriod**

Time unit multiplier for the relative FX trigger date offset.

Type: [int](#)

Used in components: [LegDividendFXTriggerDate](#)

#### **180.2.1603 LegDividendFXTriggerDateOffsetUnit**

Time unit associated with the relative FX trigger date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegDividendFXTriggerDate](#)

#### **180.2.1604 LegDividendFXTriggerDateRelativeTo**

Specifies the anchor date when the FX trigger date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [LegDividendFXTriggerDate](#)

#### **180.2.1605 LegDividendFXTriggerDateUnadjusted**

The unadjusted FX trigger date.

Type: [LocalMktDate](#)

Used in components: [LegDividendFXTriggerDate](#)

#### **180.2.1606 LegDividendInitialRate**

The initial floating rate reset agreed between the principal parties involved in the trade. This is assumed to be the first required reset rate for the first regular calculation period. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. The initial rate is expressed in decimal form, e.g. 5% is represented as "0.05".

Type: [Percentage](#)

Used in components: [LegDividendAccrualFloatingRate](#)

**180.2.1607 LegDividendNegativeRateTreatment**

The specification of any provisions for calculating payment obligations when a floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: **LegDividendAccrualFloatingRate**

**180.2.1608 LegDividendNumOfIndexUnits**

The number of index units applicable to dividends.

Type: **int**

Used in components: **LegDividendConditions**

**180.2.1609 LegDividendPeriodBusinessCenter**

The business center calendar used for date adjustment of the instrument's dividend period date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegDividendPeriodBusinessCenterGrp**

**180.2.1610 LegDividendPeriodBusinessCenterGrp**

LegDividendPeriodBusinessCenterGrp is a repeating subcomponent within the LegDividendPeriodGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
NoLegDividendPeriodBusinessCenters	[1..1]	NumInGroup	
LegDividendPeriodBusinessCenter	[0..1]	String	Required if NoLegDividendPeriodBusinessCenters(42386) > 0.

Used in groups: [LegDividendPeriodGrp](#)

### 180.2.1611 LegDividendPeriodBusinessDayConvention

The dividend period dates business day convention.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [LegDividendPeriodGrp](#)

### 180.2.1612 LegDividendPeriodEndDateUnadjusted

The unadjusted date on which the dividend period will end.

Type: [LocalMktDate](#)

Used in groups: [LegDividendPeriodGrp](#)



**180.2.1613 LegDividendPeriodGrp**

LegDividendPeriodGrp is a repeating subcomponent within the LegDividendConditions component. It is used to specify the valuation and payments dates of the dividend leg of a dividend swap.

Name	Mult.	Type	Description
NoLegDividendPeriods	[1..1]	NumInGroup	
LegDividendPeriodSequence	[0..1]	int	Required if NoLegDividendPeriods(42366) > 0.
LegDividendPeriodStartDateUnadjusted	[0..1]	LocalMktDate	
LegDividendPeriodEndDateUnadjusted	[0..1]	LocalMktDate	
LegDividendPeriodUnderlierRefID	[0..1]	String	When specified, this overrides LegDividendUnderlierRefID(42340). The specified value would be specific to this dividend period instance.
LegDividendPeriodStrikePrice	[0..1]	Price	
LegDividendPeriodBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this dividend period instance.
LegDividendPeriodBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this dividend period instance.
LegDividendPeriodValuationDateUnadjusted	[0..1]	LocalMktDate	
LegDividendPeriodValuationDateRelativeTo	[0..1]	int	
LegDividendPeriodValuationDateOffsetPeriod	[0..1]	int	Conditionally required when LegDividendPeriodValuationDateOffsetUnit(42376) is specified.
LegDividendPeriodValuationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegDividendPeriodValuationDateOffsetPeriod(42375) is specified.
LegDividendPeriodValuationDateOffsetDayType	[0..1]	CodeSet	
LegDividendPeriodValuationDateAdjusted	[0..1]	LocalMktDate	
LegDividendPeriodPaymentDateUnadjusted	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
LegDividendPeriodPaymentDateRelativeTo	[0..1]	int	
LegDividendPeriodPaymentDateOffsetPeriod	[0..1]	int	Conditionally required when LegDividendPeriodPaymentDateOffsetUnit(42382) is specified.
LegDividendPeriodPaymentDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegDividendPeriodPaymentDateOffsetPeriod(42381) is specified.
LegDividendPeriodPaymentDateOffsetDayType	[0..1]	CodeSet	
LegDividendPeriodPaymentDateAdjusted	[0..1]	LocalMktDate	
LegDividendPeriodXID	[0..1]	XID	

Used in components: [LegDividendConditions](#)

#### 180.2.1614 LegDividendPeriodPaymentDateAdjusted

The adjusted dividend period payment date.

Type: [LocalMktDate](#)

Used in groups: [LegDividendPeriodGrp](#)

#### 180.2.1615 LegDividendPeriodPaymentDateOffsetDayType

Specifies the day type of the relative dividend period payment date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [LegDividendPeriodGrp](#)

#### **180.2.1616 LegDividendPeriodPaymentDateOffsetPeriod**

Time unit multiplier for the relative dividend period payment date offset.

Type: [int](#)

Used in groups: [LegDividendPeriodGrp](#)

#### **180.2.1617 LegDividendPeriodPaymentDateOffsetUnit**

Time unit associated with the relative dividend period payment date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [LegDividendPeriodGrp](#)

#### **180.2.1618 LegDividendPeriodPaymentDateRelativeTo**

Specifies the anchor date when the dividend period payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in groups: [LegDividendPeriodGrp](#)

#### **180.2.1619 LegDividendPeriodPaymentDateUnadjusted**

The unadjusted dividend period payment date.

Type: [LocalMktDate](#)

Used in groups: [LegDividendPeriodGrp](#)

**180.2.1620 LegDividendPeriodSequence**

Defines the ordinal dividend period. E.g. 1 = First period, 2 = Second period, etc.

Type: **int**

Used in groups: **LegDividendPeriodGrp**

**180.2.1621 LegDividendPeriodStartDateUnadjusted**

The unadjusted date on which the dividend period will begin.

Type: **LocalMktDate**

Used in groups: **LegDividendPeriodGrp**

**180.2.1622 LegDividendPeriodStrikePrice**

Specifies the fixed strike price of the dividend period.

Type: **Price**

Used in groups: **LegDividendPeriodGrp**

**180.2.1623 LegDividendPeriodUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in groups: **LegDividendPeriodGrp**

**180.2.1624 LegDividendPeriodValuationDateAdjusted**

The adjusted dividend period valuation date.

Type: **LocalMktDate**

Used in groups: **LegDividendPeriodGrp**

**180.2.1625 LegDividendPeriodValuationDateOffsetDayType**

Specifies the day type of the relative dividend period valuation date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **LegDividendPeriodGrp**

**180.2.1626 LegDividendPeriodValuationDateOffsetPeriod**

Time unit multiplier for the relative dividend period valuation date offset.

Type: **int**

Used in groups: **LegDividendPeriodGrp**

**180.2.1627 LegDividendPeriodValuationDateOffsetUnit**

Time unit associated with the relative dividend period valuation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegDividendPeriodGrp**

**180.2.1628 LegDividendPeriodValuationDateRelativeTo**

Specifies the anchor date when the dividend period valuation date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **LegDividendPeriodGrp**

**180.2.1629 LegDividendPeriodValuationDateUnadjusted**

The unadjusted dividend period valuation date.

Type: **LocalMktDate**

Used in groups: **LegDividendPeriodGrp**

**180.2.1630 LegDividendPeriodXID**

Identifier for linking this stream dividend period to an underlier through an instance of RelatedInstrumentGrp.

Type: **XID**

Used in groups: **LegDividendPeriodGrp**

**180.2.1631 LegDividendReinvestmentIndicator**

Indicates whether the dividend will be reinvested.

Type: **Boolean**

Used in components: **LegDividendConditions**

**180.2.1632 LegDividendUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in components: **LegDividendConditions**

### **180.2.1633 LegDividendYield**

Refer to definition for DividendYield(1380).

Type: **Percentage**

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**, **TrdInstrmtLegGrp**

### **180.2.1634 LegDocumentationText**

A sentence or phrase pertinent to the trade, not a reference to an external document. E.g. "To be registered with the U.S. Environmental Protection Agency, Acid Rain Division, SO2 Allowance Tracking System".

Type: **String**

Used in components: **LegFinancingDetails**

### **180.2.1635 LegEndDate**

End date of a financing deal, i.e. the date the seller reimburses the buyer and takes back control of the collateral.

Type: **LocalMktDate**

Used in components: **LegFinancingDetails**

### **180.2.1636 LegEventDate**

The date of the event.

Type: **LocalMktDate**

Used in groups: **LegEvntGrp**

### **180.2.1637 LegEventMonthYear**

Used with derivatives when an event is express as a month-year with optional day or month or week of month.

Format:

YYYYMM (e.g. 199903)

YYYYMMDD (e.g. 20030323)

YYYYMMwN (e.g. 200303w2) for week

A specific date can be appended to the month-year. For instance, if multiple event types exist in the same Year and Month, but actually at a different time, a value can be appended, such as "w" or "w2" to indicate week. Likewise, the day of month (0-31) can be appended to indicate a specific event date.

Type: **MonthYear**

Used in groups: **LegEvntGrp**

#### **180.2.1638 LegEventPx**

Predetermined price of issue at event, if applicable.

Type: **Price**

Used in groups: **LegEvntGrp**

#### **180.2.1639 LegEventText**

Free form text to specify additional information or enumeration description when a standard value does not apply.

Type: **String**

Used in groups: **LegEvntGrp**

#### **180.2.1640 LegEventTime**

Specific time of event. To be used in combination with LegEventDate(2061).

Type: **UTCTimestamp**

Used in groups: **LegEvntGrp**

#### **180.2.1641 LegEventTimePeriod**

Time unit multiplier for the event.

Type: **int**

Used in groups: **LegEvntGrp**



**180.2.1642 LegEventTimeUnit**

Time unit associated with the event.

Type: **String**

Allowed values in EventTimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegEvtGrp**

**180.2.1643 LegEventType**

Code to represent the type of event.

Type: **int**

Allowed values in EventTypeCodeSet:

Code	Name	Description
1	Put	Put
2	Call	Call
3	Tender	Tender
4	SinkingFundCall	Sinking fund call
5	Activation	Activation
6	Inactivation	Inactivation
7	LastEligibleTradeDate	Last eligible trade date
8	SwapStartDate	Swap start date
9	SwapEndDate	Swap end date
10	SwapRollDate	Swap roll date

Code	Name	Description
11	SwapNextStartDate	Swap next start date
12	SwapNextRollDate	Swap next roll date
13	FirstDeliveryDate	First delivery date
14	LastDeliveryDate	Last delivery date
15	InitialInventoryDueDate	Initial inventory due date
16	FinalInventoryDueDate	Final inventory due date
17	FirstIntentDate	First intent date
18	LastIntentDate	Last intent date
19	PositionRemovalDate	Position removal date
20	MinimumNotice	Minimum notice
21	DeliveryStartTime	Delivery start time
22	DeliveryEndTime	Delivery end time
23	FirstNoticeDate	First notice date. The first day that a notice of intent to deliver a commodity can be made by a clearing house to a buyer in fulfillment of a given month's futures contract.
24	LastNoticeDate	Last notice date. The last day on which a clearing house may inform an investor that a seller intends to make delivery of a commodity that the investor previously bought in a futures contract. The date is governed by the rules of different exchanges and clearing houses, but may also be stated in the futures contract itself.
25	FirstExerciseDate	First exercise date
26	RedemptionDate	Redemption date
27	TrdCntntnEfctvDt	Trade continuation effective date
99	Other	Other

Used in groups: **LegEvntGrp**

### 180.2.1644 LegEvntGrp

The LegEvntGrp is a repeating subcomponent of the InstrumentLeg component used to specify straight-forward events associated with the instrument. Examples include put and call dates for bonds and options; first exercise date for options; inventory and delivery dates for commodities; start, end and roll dates for swaps. Use LegComplexEvents for more advanced dates such as option, futures, commodities and equity swap observation and pricing events.

Name	Mult.	Type	Description
NoLegEvents	[1..1]	NumInGroup	
LegEventType	[0..1]	CodeSet	Required if NoLegEvents(2059) > 0.
LegEventDate	[0..1]	LocalMktDate	Conditionally required when LegEventTime(2062) is specified.
LegEventTime	[0..1]	UTCTimestamp	
LegEventTimeUnit	[0..1]	CodeSet	Conditionally required when LegEventTimePeriod(2064) is specified.
LegEventTimePeriod	[0..1]	int	Conditionally required when LegEventTimeUnit(2063) is specified.
LegEventMonthYear	[0..1]	MonthYear	
LegEventPx	[0..1]	Price	
LegEventText	[0..1]	String	
EncodedLegEventTextLen	[0..1]	Length	Must be set if EncodedLegEventText(2075) field is specified and must immediately precede it.
EncodedLegEventText	[0..1]	data	Encoded (non-ASCII characters) representation of the LegEventText(2066) field in the encoded format specified via the MessageEncoding(347) field.

Used in components: **InstrumentLeg**

#### 180.2.1645 LegExchangeLookAlike

For a share option trade, indicates whether the instrument is to be treated as an 'exchange look-alike'.

Type: **Boolean**

Used in components: **InstrumentLeg**

#### 180.2.1646 LegExecID

The ExecID(17) value corresponding to a trade leg.

Type: **String**

Used in groups: **TrdInstrmtLegExecGrp**

**180.2.1647 LegExecInst**

Refer to ExecInst(18)

Same values as ExecInst(18)

Type: **MultipleCharValue**

Allowed values in ExecInstCodeSet:

Code	Name	Description
0	StayOnOfferSide	Stay on offer side
1	NotHeld	Not held
2	Work	Work
3	GoAlong	Go along
4	OverTheDay	Over the day
5	Held	Held
6	ParticipateDoNotInitiate	Participate don't initiate
7	StrictScale	Strict scale
8	TryToScale	Try to scale
9	StayOnBidSide	Stay on bid side
A	NoCross	No cross. Cross is forbidden.
B	OKToCross	OK to cross
C	CallFirst	Call first
D	PercentOfVolume	Percent of volume. Indicates that the sender does not want the order to be all of the volume on the floor vs. a specific percentage.
E	DoNotIncrease	Do not increase - DNI
F	DoNotReduce	Do not reduce - DNR
G	AllOrNone	All or none - AON
H	ReinstateOnSystemFailure	Reinstate on system failure. Mutually exclusive with Q and I (lower case L).
I	InstitutionsOnly	Institutions only
J	ReinstateOnTradingHalt	Reinstate on trading halt. Mutually exclusive with K and m.
K	CancelOnTradingHalt	Cancel on trading halt. Mutually exclusive with J and m.
L	LastPeg	Last peg (last sale)
M	MidPricePeg	Mid-price peg (midprice of inside quote)
N	NonNegotiable	Non-negotiable
O	OpeningPeg	Opening peg

Code	Name	Description
P	MarketPeg	Market peg
Q	CancelOnSystemFailure	Cancel on system failure. Mutually exclusive with H and I(lower case L).
R	PrimaryPeg	Primary peg. Primary market - buy at bid, sell at offer.
S	Suspend	Suspend
T	FixedPegToLocalBestBidOrOfferAt-TimeOfOrder	Fixed peg to local best bid or offer at time of order
U	CustomerDisplayInstruction	Customer display instruction. Used in US Markets for: SEC Rule 11Ac1-1/4.
V	Netting	Netting (for Forex)
W	PegToVWAP	Peg to VWAP
X	TradeAlong	Trade along
Y	TryToStop	Try to stop
Z	CancelIfNotBest	Cancel if not best
a	TrailingStopPeg	Trailing stop peg
b	StrictLimit	Strict limit. No price improvement.
c	IgnorePriceValidityChecks	Ignore price validity checks
d	PegToLimitPrice	Peg to limit price
e	WorkToTargetStrategy	Work to target strategy
f	IntermarketSweep	Intermarket sweep
g	ExternalRoutingAllowed	External routing allowed
h	ExternalRoutingNotAllowed	External routing not allowed
i	ImbalanceOnly	Imbalance only
j	SingleExecutionRequestedForBlock-Trade	Single execution requested for block trade
k	BestExecution	Best execution
l	SuspendOnSystemFailure	Suspend on system failure. Mutually exclusive with H and Q.
m	SuspendOnTradingHalt	Suspend on trading halt. Mutually exclusive with J and K.
n	ReinstateOnConnectionLoss	Reinstate on connection loss. Mutually exclusive with o and p.
o	CancelOnConnectionLoss	Cancel on connection loss. Mutually exclusive with n and p.
p	SuspendOnConnectionLoss	Suspend on connection loss. Mutually exclusive with n and o.
q	Release	Release. Mutually exclusive with S and w.
r	ExecuteAsDeltaNeutral	Execute as delta neutral using volatility provided
s	ExecuteAsDurationNeutral	Execute as duration neutral
t	ExecuteAsFXNeutral	Execute as FX neutral

Code	Name	Description
u	MinGuaranteedFillEligible	Minimum guaranteed fill eligible
v	BypassNonDisplayLiquidity	Bypass non-displayed liquidity
w	Lock	Lock. Mutually exclusive with q.
x	IgnoreNotionalValueChecks	Ignore notional value checks
y	TrdAtRefPx	Trade at reference price. In the context of Reg NMS and the Tick Size Pilot Program, this is intended to indicate the order should Trade At Intermarket Sweep Order (TAISO) price.
z	AllowFacilitation	Allow facilitation. Express explicit consent to receive facilitation services from the counterparty. Facilitation services are when an institutional client allows a broker to assume a risk-taking principal position rather than an agency position, to obtain liquidity or achieve a guaranteed execution price on the client's behalf. Interpretation of absence of this value needs to be bilaterally agreed, if applicable. In the context of Hong Kong's SFC, this can be used to comply with SFC regulations for disclosure of client facilitation.

Used in groups: [InstrmtLegExecGrp](#), [LegOrdGrp](#), [SideCrossLegGrp](#), [TrdInstrmtLegGrp](#)

#### 180.2.1648 LegExecRefID

Used to reference the value from LegExecID(1893).

Type: [String](#)

Used in groups: [TrdInstrmtLegExecGrp](#)

#### 180.2.1649 LegExerciseConfirmationMethod

Indicates whether follow-up confirmation of exercise (written or electronic) is required following telephonic notice by the buyer to the seller or seller's agent.

Type: [int](#)

Allowed values in ExerciseConfirmationMethodCodeSet:

Code	Name	Description
0	NotRequired	Not required
1	NonElectronic	Non-electronic

Code	Name	Description
2	Electronic	Electronic
3	Unknown	Unknown at time of report

Used in components: [LegOptionExercise](#)

### **180.2.1650 LegExerciseDesc**

A description of the option exercise.

Type: [String](#)

Used in components: [LegOptionExercise](#)

### **180.2.1651 LegExerciseSplitTicketIndicator**

Indicates in physical settlement of bond and convertible bond options whether the party required to deliver the bonds will divide those to be delivered as notifying party desires to facilitate delivery obligations.

Type: [Boolean](#)

Used in components: [LegOptionExercise](#)

### **180.2.1652 LegExerciseStyle**

Type of exercise of a derivatives security

Type: [int](#)

Allowed values in ExerciseStyleCodeSet:

Code	Name	Description
0	European	European
1	American	American
2	Bermuda	Bermuda
99	Other	Other

Used in components: [InstrumentLeg](#)

**180.2.1653 LegExtraordinaryDividendAmountType**

Indicates how the extraordinary gross cash dividend per share is determined.

Type: **int**

Allowed values in DividendAmountTypeCodeSet:

Code	Name	Description
0	RecordAmount	Record amount. 100% of the gross cash dividend per share paid over record date during relevant dividend period.
1	ExAmount	Ex amount. 100% of gross cash dividend per share paid after the ex-dividend date during relevant dividend period.
2	PaidAmount	Paid amount. 100% of gross cash dividend per share paid during relevant dividend period.
3	PerMasterConfirm	As specified in master confirmation. The amount is determined as provided in the relevant master confirmation.

Used in components: **LegDividendConditions**

**180.2.1654 LegExtraordinaryDividendCurrency**

The currency in which the excess dividend is denominated. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegDividendConditions**

**180.2.1655 LegExtraordinaryDividendDeterminationMethod**

Specifies the method in which the excess amount is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in components: **LegDividendConditions**

**180.2.1656 LegExtraordinaryDividendPartySide**

Reference to the party through its side in the trade who makes the determination whether dividends are extraordinary in relation to normal levels.



Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegDividendConditions**

### 180.2.1657 LegExtraordinaryEventAdjustmentMethod

Defines how adjustments will be made to the contract should one or more of the extraordinary events occur.

Type: **int**

Allowed values in ExtraordinaryEventAdjustmentMethodCodeSet:

Code	Name	Description
0	CalculationAgent	Calculation agent. The Calculation Agent has the right to adjust the terms of the trade following a corporate action.
1	OptionsExchange	Options exchange. The trade will be adjusted in accordance with any adjustment made by the exchange on which options on the underlying are listed.

Used in components: **InstrumentLeg**

### 180.2.1658 LegExtraordinaryEventGrp

The LegExtraordinaryEventGrp is a repeating component within the InstrumentLeg component. It is used to report extraordinary and disruptive events applicable to the reference entity that affects the contract.

Name	Mult.	Type	Description
<b>NoLegExtraordinaryEvents</b>	[1..1]	NumInGroup	
<b>LegExtraordinaryEventType</b>	[0..1]	String	Required if NoLegExtraordinaryEvents(42388) > 0.

Name	Mult.	Type	Description
<a href="#">LegExtraordinaryEventValue</a>	[0..1]	String	Required if NoLegExtraordinaryEvents(42388) > 0.

Used in components: [InstrumentLeg](#)

#### **180.2.1659 LegExtraordinaryEventType**

Identifies the type of extraordinary or disruptive event applicable to the reference entity.

See [http://www.fixtradingcommunity.org/codelists#Extraordinary\\_Event\\_Type](http://www.fixtradingcommunity.org/codelists#Extraordinary_Event_Type) for code list of extraordinary event types and values.

Type: [String](#)

Used in groups: [LegExtraordinaryEventGrp](#)

#### **180.2.1660 LegExtraordinaryEventValue**

The extraordinary or disruptive event value appropriate to LegExtraordinaryEventType(42389).

See [http://www.fixtradingcommunity.org/codelists#Extraordinary\\_Event\\_Type](http://www.fixtradingcommunity.org/codelists#Extraordinary_Event_Type) for code list of extraordinary event types and values.

Type: [String](#)

Used in groups: [LegExtraordinaryEventGrp](#)

#### **180.2.1661 LegFactor**

Multileg instrument's individual leg security's Factor.

See Factor (228) field for description

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: [float](#)

Used in components: [InstrumentLeg](#)

**180.2.1662 LegFallbackExerciseIndicator**

Indicates whether the notional amount of the underlying swap, not previously exercised under the option, will be automatically exercised at the expiration time on the expiration date if at such time the buyer is in-the-money, provided that the difference between the settlement rate and the fixed rate under the relevant underlying swap is not less than one tenth of a percentage point (0.10% or 0.001).

Type: **Boolean**

Used in components: **LegOptionExercise**

**180.2.1663 LegFinancialInstrumentFullName**

The full normative name of the multileg's financial instrument.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1664 LegFinancialInstrumentShortName**

Short name of the financial instrument. Uses ISO 18774 (FISN) values.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1665 LegFinancingContractualDefinitionsGrp**

The LegFinancingContractualDefinitionGrp is a repeating component within the LegFinancingDetails component used to report the definitions published by ISDA that define the terms of a derivative trade.

Name	Mult.	Type	Description
NoLegContractualDefinitions	[1..1]	NumInGroup	
LegContractualDefinition	[0..1]	String	Required if NoLegContractualDefinitions(42198) > 0.

Used in components: **LegFinancingDetails**

**180.2.1666 LegFinancingContractualMatrixGrp**

The LegFinancingContractualMatrixGrp is a repeating component within the LegFinancingDetails component used to report the ISDA Physical Settlement Matrix Transaction Type.

Name	Mult.	Type	Description
NoLegContractualMatrices	[1..1]	NumInGroup	
LegContractualMatrixSource	[0..1]	String	Required if NoLegContractualMatrices(42203) > 0.
LegContractualMatrixDate	[0..1]	LocalMktDate	
LegContractualMatrixTerm	[0..1]	String	

Used in components: [LegFinancingDetails](#)

**180.2.1667 LegFinancingDetails**

Component block is optionally used for financial transactions where legal contracts, master agreements or master confirmations are to be referenced. This component identifies the legal agreement under which the deal was made and other unique characteristics of the transaction. For example, the LegAgreementDesc(2497) field refers to base standard documents such as MRA 1996 Repurchase Agreement, GMRA 2000 Bills Transaction (U.K.), MSLA 1993 Securities Loan - Amended 1998, for example.

Name	Mult.	Type	Description
LegAgreementDesc	[0..1]	String	
LegAgreementID	[0..1]	String	
LegAgreementVersion	[0..1]	String	
LegAgreementDate	[0..1]	LocalMktDate	
LegAgreementCurrency	[0..1]	Currency	
LegAgreementCurrencyCodeSource	[0..1]	CodeSet	
LegMasterConfirmationDesc	[0..1]	String	
LegMasterConfirmationDate	[0..1]	LocalMktDate	
LegMasterConfirmationAnnexDesc	[0..1]	String	
LegMasterConfirmationAnnexDate	[0..1]	LocalMktDate	
LegBrokerConfirmationDesc	[0..1]	String	
LegFinancingContractualDefinitions-Grp	[0..*]	Group	
LegFinancingTermSupplementGrp	[0..*]	Group	

Name	Mult.	Type	Description
LegFinancingContractualMatrixGrp	[0..*]	Group	
LegCreditSupportAgreementDesc	[0..1]	String	
LegCreditSupportAgreementDate	[0..1]	LocalMktDate	
LegCreditSupportAgreementID	[0..1]	String	
LegGoverningLaw	[0..1]	String	
LegDocumentationText	[0..1]	String	
EncodedLegDocumentationTextLen	[0..1]	Length	Must be set if EncodedLegDocumentationText(2493) field is specified and must immediately precede it.
EncodedLegDocumentationText	[0..1]	data	Encoded (non-ASCII characters) representation of the LegDocumentationText(2505) field in the encoded format specified via the MessageEncoding(347) field.
LegTerminationType	[0..1]	CodeSet	
LegStartDate	[0..1]	LocalMktDate	
LegEndDate	[0..1]	LocalMktDate	
LegDeliveryType	[0..1]	CodeSet	
LegMarginRatio	[0..1]	Percentage	

Used in groups: InstrmtLegGrp, TrdInstrmtLegGrp

### 180.2.1668 LegFinancingTermSupplementDate

Specifies the publication date of the applicable version of the contractual supplement.

Type: LocalMktDate

Used in groups: LegFinancingTermSupplementGrp

### 180.2.1669 LegFinancingTermSupplementDesc

Identifies the applicable contractual supplement. See <http://www.fpml.org/coding-scheme/contractual-supplement> for values.

Type: String

Used in groups: LegFinancingTermSupplementGrp

**180.2.1670 LegFinancingTermSupplementGrp**

The LegFinancingTermSupplementGrp is a repeating component within the LegFinancingDetails component used to report contractual terms supplements of derivative trades.

Name	Mult.	Type	Description
NoLegFinancingTermSupplements	[1..1]	NumInGroup	
LegFinancingTermSupplementDesc	[0..1]	String	Required if NoLegFinancingTermSupplements(42200) > 0.
LegFinancingTermSupplementDate	[0..1]	LocalMktDate	

Used in components: [LegFinancingDetails](#)

**180.2.1671 LegFlexibleIndicator**

Used to indicate a derivatives security that can be defined using flexible terms. The terms commonly permitted to be defined by market participants are expiration date and strike price. FlexibleIndicator is an alternative to LegCFIcode(608) Standard/Non-standard attribute.

Type: [Boolean](#)

Used in components: [InstrumentLeg](#)

**180.2.1672 LegFlexProductEligibilityIndicator**

Used to indicate if a product or group of product supports the creation of flexible securities.

Type: [Boolean](#)

Used in components: [InstrumentLeg](#)

**180.2.1673 LegFloorPrice**

Used to express the floor price of a capped put.

Type: [Price](#)

Used in components: [InstrumentLeg](#)

**180.2.1674 LegFlowScheduleType**

The industry standard flow schedule by which electricity or natural gas is traded. Schedules exist by regions and on-peak and off-peak status, such as "Western Peak".

Type: **int**

Allowed values in FlowScheduleTypeCodeSet:

Code	Name	Description
0	NERCEasternOffPeak	NERC Eastern Off-Peak
1	NERCWesternOffPeak	NERC Western Off-Peak
2	NERCCalendarAllDaysInMonth	NERC Calendar-All Days in month
3	NERCEasternPeak	NERC Eastern Peak
4	NERCWesternPeak	NERC Western Peak
5	AllTimes	All times
6	OnPeak	On peak
7	OffPeak	Off peak
8	Base	Base
9	Block	Block
99	Other	Other

Used in components: **InstrumentLeg**

**180.2.1675 LegGoverningLaw**

Identification of the law governing the transaction. See <http://www.fpml.org/coding-scheme/governing-law> for values.

Type: **String**

Used in components: **LegFinancingDetails**

**180.2.1676 LegGrossTradeAmt**

The gross trade amount of the leg. For FX Futures this is used to express the notional value of a fill when LegLastQty and other quantity fields are express in terms of contract size.

Type: **Amt**

Used in groups: **InstrmtLegExecGrp**, **TrdInstrmtLegGrp**

**180.2.1677 LegID**

Unique identifier for the leg within the context of a message (the scope of uniqueness to be defined by counterparty agreement). The LegID(1788) can be referenced using LegRefID(654).

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1678 LegIndexAnnexDate**

The date of a credit default swap index series annex.

Type: **LocalMktDate**

Used in components: **InstrumentLeg**

**180.2.1679 LegIndexAnnexSource**

The source of a credit default swap series annex.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1680 LegIndexAnnexVersion**

The version of a credit default swap index annex.

Type: **int**

Used in components: **InstrumentLeg**

**180.2.1681 LegIndexSeries**

The series identifier of a credit default swap index.

Type: **int**

Used in components: **InstrumentLeg**



**180.2.1682 LegIndividualAllocID**

Reference for the individual allocation ticket

See IndividualAllocID (467) for description and valid values.

Type: **String**

Used in groups: **LegPreAllocGrp**

**180.2.1683 LegInstrmtAssignmentMethod**

Specifies the method under which assignment was conducted.

Type: **char**

Allowed values in InstrmtAssignmentMethodCodeSet:

Code	Name	Description
P	ProRata	Pro rata
R	Random	Random

Used in components: **InstrumentLeg**

**180.2.1684 LegInstrRegistry**

Multileg instrument's individual leg security's InstrRegistry.

See InstrRegistry (543) field for description

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1685 LegInstrumentParties**

The use of this component block is restricted to instrument definition only and is not permitted to contain transactional information. Only a specified subset of party roles will be supported within the LegInstrumentParty block.

Name	Mult.	Type	Description
NoLegInstrumentParties	[1..1]	NumInGroup	Repeating group below should contain unique combinations of LegInstrumentPartyID(2255), LegInstrumentPartyIDSource(2256) and LegInstrumentPartyRole(2257).
LegInstrumentPartyID	[0..1]	String	Used to identify the source of PartyID. Required if LegInstrumentPartyIDSource(2256) is specified. Required if NoLegInstrumentParties(2254) > 0.
LegInstrumentPartyIDSource	[0..1]	CodeSet	Used to identify class source of LegInstrumentPartyID(2255) value (e.g. BIC). Required if LegInstrumentPartyID(2255) is specified. Required if NoLegInstrumentParties(2254) > 0.
LegInstrumentPartyRole	[0..1]	CodeSet	Identifies the type of LegInstrumentPartyID(2255) (e.g. Executing Broker). Required if NoLegInstrumentParties(2254) > 0.
LegInstrumentPartyRoleQualifier	[0..1]	CodeSet	
LegInstrumentPtysSubGrp	[0..*]	Group	Repeating group of party sub-identifiers.

Used in components: **InstrumentLeg**

#### **180.2.1686 LegInstrumentPartyID**

Used to identify party id related to instrument.

Type: **String**

Used in groups: **LegInstrumentParties**

#### **180.2.1687 LegInstrumentPartyIDSource**

Used to identify source of instrument party id.

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.

Code	Name	Description
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: [LegInstrumentParties](#)

### 180.2.1688 LegInstrumentPartyRole

Used to identify the role of instrument party id.

Type: [int](#)

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)

Code	Name	Description
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party

Code	Name	Description
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)

Code	Name	Description
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionV- enue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm

Code	Name	Description
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor



Code	Name	Description
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **LegInstrumentParties**

**180.2.1689 LegInstrumentPartyRoleQualifier**

Used to further qualify the value of LegInstrumentPartyRole(2257).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange

Code	Name	Description
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: [LegInstrumentParties](#)

#### 180.2.1690 LegInstrumentPartySubID

PartySubID value within an instrument party repeating group.

Type: [String](#)

Used in groups: [LegInstrumentPtysSubGrp](#)

**180.2.1691 LegInstrumentPartySubIDType**

Type of LegInstrumentPartySubID (2259) value.

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker

Code	Name	Description
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.

Code	Name	Description
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.



Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **LegInstrumentPtysSubGrp**

**180.2.1692 LegInstrumentPtysSubGrp**

Name	Mult.	Type	Description
NoLegInstrumentPartySubIDs	[1..1]	NumInGroup	
LegInstrumentPartySubID	[0..1]	String	Required if NoLegInstrumentPartySubIDs(2258) > 0.
LegInstrumentPartySubIDType	[0..1]	CodeSet	

Used in groups: [LegInstrumentParties](#)

**180.2.1693 LegInstrumentRoundingDirection**

Specifies the rounding direction if not overridden elsewhere.

Type: [char](#)

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: [InstrumentLeg](#)

**180.2.1694 LegInstrumentRoundingPrecision**

Specifies the rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: [int](#)

Used in components: [InstrumentLeg](#)

**180.2.1695 LegInterestAccrualDate**

The start date used for calculating accrued interest on debt instruments which are being sold between interest payment dates. Often but not always the same as the Issue Date and the Dated Date

Type: **LocalMktDate**

Used in components: **InstrumentLeg**

### 180.2.1696 LegInTheMoneyCondition

Specifies an option instrument's "in the money" condition in general terms.

Type: **int**

Allowed values in InTheMoneyConditionCodeSet:

Code	Name	Description
0	StandardITM	Standard in-the-money. The option's strike price is less than the underlying settlement price for a call or greater than the underlying settlement price for a put.
1	ATMITM	At-the-money is in-the-money. The option's strike price of either the put or call is equal to the underlying settlement price in addition to standard in-the-money behavior.
2	ATMCallITM	At-the-money call is in-the-money. The call option's strike price is equal to the underlying settlement price in addition to standard in-the-money behavior.
3	ATMPutITM	At-the-money put is in-the-money. The put option's strike price is equal to the underlying settlement price in addition to standard in-the-money behavior.

Used in components: **InstrumentLeg**

### 180.2.1697 LegIOIQty

Leg-specific IOI quantity.

See IOIQty (27) for description and valid values

Type: **String**

Allowed values in IOIQtyCodeSet:

Code	Name	Description
S	Small	Small
M	Medium	Medium

Code	Name	Description
L	Large	Large
U	UndisclosedQuantity	Undisclosed Quantity

Used in groups: [InstrmtLegIOIGrp](#)

#### **180.2.1698 LegIssueDate**

Multileg instrument's individual leg security's IssueDate.

See IssueDate (225) field for description

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCDate)

Type: [LocalMktDate](#)

Used in components: [InstrumentLeg](#)

#### **180.2.1699 LegIssuer**

Multileg instrument's individual security's Issuer.

See Issuer (106) field for description

Type: [String](#)

Used in components: [InstrumentLeg](#)

#### **180.2.1700 LegLastForwardPoints**

The forward points for this leg's fill event. Value can be negative. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199

Type: [PriceOffset](#)

Used in groups: [InstrmtLegExecGrp](#), [TrdInstrmtLegGrp](#)

**180.2.1701 LegLastMultipliedQty**

Expresses the quantity bought/sold when LastQty is expressed in contracts. Used in addition to LegLastQty(1418), it is the product of LegLastQty(1418) and LegContractMultiplier(614).

Type: Qty

Used in groups: TrdInstrmtLegGrp

**180.2.1702 LegLastPx**

Execution price assigned to a leg of a multileg instrument.

See LastPx (31) field for description and values

Type: Price

Used in groups: InstrmtLegExecGrp, TrdInstrmtLegExecGrp, TrdInstrmtLegGrp

**180.2.1703 LegLastQty**

Fill quantity for the leg instrument

Type: Qty

Used in groups: InstrmtLegExecGrp, TrdInstrmtLegExecGrp, TrdInstrmtLegGrp

**180.2.1704 LegLienSeniority**

Indicates the seniority level of the lien in a loan.

Type: int

Allowed values in LienSeniorityCodeSet:

Code	Name	Description
0	Unknown	Unknown
1	FirstLien	First lien
2	SecondLien	Second lien
3	ThirdLien	Third lien

Used in components: InstrumentLeg

**180.2.1705 LegLimitRightToConfirmIndicator**

Indicates whether the Seller may request the Buyer to confirm its intent to exercise if not done on or before the expiration time on the expiration date. If true ("Y") specific rules will apply in relation to the settlement mode.

Type: **Boolean**

Used in components: **LegOptionExercise**

**180.2.1706 LegListMethod**

Indicates whether instruments are pre-listed only or can also be defined via user request.

Type: **int**

Allowed values in ListMethodCodeSet:

Code	Name	Description
0	PreListedOnly	pre-listed only
1	UserRequested	user requested

Used in components: **InstrumentLeg**

**180.2.1707 LegLoanFacility**

Specifies the type of loan when the credit default swap's reference obligation is a loan.

Type: **int**

Allowed values in LoanFacilityCodeSet:

Code	Name	Description
0	BridgeLoan	Bridge loan
1	LetterOfCredit	Letter of credit
2	RevolvingLoan	Revolving loan
3	SwinglineFunding	Swingline funding
4	TermLoan	Term loan
5	TradeClaim	Trade claim

Used in components: **InstrumentLeg**

**180.2.1708 LegLocaleOfIssue**

Multileg instrument's individual leg security's LocaleOfIssue.

See LocaleOfIssue (472) field for description

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1709 LegMakeWholeAmount**

Amount to be paid by the buyer of the option if the option is exercised prior to the LegMakeWhole-Date(42392).

Type: **Amt**

Used in components: **LegOptionExerciseMakeWholeProvision**

**180.2.1710 LegMakeWholeBenchmarkCurveName**

Identifies the benchmark floating rate index.

Type: **String**

Used in components: **LegOptionExerciseMakeWholeProvision**

**180.2.1711 LegMakeWholeBenchmarkCurvePoint**

The point on the floating rate index curve.

Sample values:

M = combination of a number between 1-12 and an "M" for month, e.g. 3M

Y = combination of number between 1-100 and a "Y" for year, e.g. 10Y

10Y-OLD = see above, then add "-OLD" when appropriate

INTERPOLATED = the point is mathematically derived

2/2031 5 3/8 = the point is stated via a combination of maturity month / year and coupon.

Type: **String**

Used in components: **LegOptionExerciseMakeWholeProvision**

**180.2.1712 LegMakeWholeBenchmarkQuote**

The quote side of the benchmark to be used for calculating the "make whole" amount.

Type: **int**

Allowed values in StrikeIndexQuoteCodeSet:

Code	Name	Description
0	Bid	Bid.
1	Mid	Mid
2	Offer	Offer

Used in components: **LegOptionExerciseMakeWholeProvision**

**180.2.1713 LegMakeWholeDate**

The date through which option cannot be exercised without penalty.

Type: **LocalMktDate**

Used in components: **LegOptionExerciseMakeWholeProvision**

**180.2.1714 LegMakeWholeInterpolationMethod**

The method used when calculating the "make whole" amount. The most common is linear method.

Type: **int**

Allowed values in PaymentStreamInflationInterpolationMethodCodeSet:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: **LegOptionExerciseMakeWholeProvision**



**180.2.1715 LegMakeWholeRecallSpread**

Spread over the floating rate index.

Type: **PriceOffset**

Used in components: **LegOptionExerciseMakeWholeProvision**

**180.2.1716 LegManualNoticeBusinessCenter**

Identifies the business center used for adjusting the time for manual exercise notice.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **LegOptionExercise**

**180.2.1717 LegMarginRatio**

The fraction of the cash consideration that must be collateralized, expressed as a percent. A MarginRatio of 2% indicates that the value of the collateral (after deducting for "haircut") must exceed the cash consideration by 2%.

Type: **Percentage**

Used in components: **LegFinancingDetails**

**180.2.1718 LegMarketDisruption**

The LegMarketDisruption component is a subcomponent of the InstrumentLeg used to specify the market disruption provisions of the swap.

Name	Mult.	Type	Description
<b>LegMarketDisruptionProvision</b>	[0..1]	CodeSet	
<b>LegMarketDisruptionEventGrp</b>	[0..*]	Group	
<b>LegMarketDisruptionFallbackProvision</b>	[0..1]	CodeSet	
<b>LegMarketDisruptionFallbackGrp</b>	[0..*]	Group	
<b>LegMarketDisruptionFallbackReferencePriceGrp</b>	[0..*]	Group	
<b>LegMarketDisruptionMaximumDays</b>	[0..1]	int	

Name	Mult.	Type	Description
<b>LegMarketDisruptionMaterialityPercentage</b>	[0..1]	Percentage	If specified, the disruption event should be specified in LegMarketDisruptionEventGrp.
<b>LegMarketDisruptionMinimumFuturesContracts</b>	[0..1]	int	Applicable only when LegMarketDisruptionEvent(41468)='DeMinimisTrading'.

Used in components: **InstrumentLeg**

### 180.2.1719 LegMarketDisruptionEvent

Specifies the market disruption event.

For commodities see <http://www.fpml.org/coding-scheme/commodity-market-disruption> for values.

For foreign exchange, see [http://www.fixtradingcommunity.org/codelists#Market\\_Disruption\\_Event](http://www.fixtradingcommunity.org/codelists#Market_Disruption_Event) for code list of applicable event types.

Type: **String**

Used in groups: **LegMarketDisruptionEventGrp**

### 180.2.1720 LegMarketDisruptionEventGrp

The LegMarketDisruptionEventGrp is a repeating subcomponent of the LegMarketDisruption component used to specify the market disruption events.

Name	Mult.	Type	Description
<b>NoLegMarketDisruptionEvents</b>	[1..1]	NumInGroup	
<b>LegMarketDisruptionEvent</b>	[0..1]	String	Required if NoLegMarketDisruptionEvents(41467) > 0.
<b>LegMarketDisruptionValue</b>	[0..1]	String	

Used in components: **LegMarketDisruption**

### 180.2.1721 LegMarketDisruptionFallbackBasketCurrency

Specifies the currency if the underlier is a basket. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegMarketDisruptionFallbackReferencePriceGrp**

#### **180.2.1722 LegMarketDisruptionFallbackBasketDivisor**

Specifies the basket divisor amount. This value is normally used to adjust the constituent weight for pricing or to adjust for dividends, or other corporate actions.

Type: **float**

Used in groups: **LegMarketDisruptionFallbackReferencePriceGrp**

#### **180.2.1723 LegMarketDisruptionFallbackGrp**

The LegMarketDisruptionFallbackGrp is a repeating subcomponent of the LegMarketDisruption component used to specify the market disruption fallback provisions.

Name	Mult.	Type	Description
NoLegMarketDisruptionFallbacks	[1..1]	NumInGroup	
LegMarketDisruptionFallbackType	[0..1]	String	Required if NoLegMarketDisruptionFallbacks(41469) > 0. The sequence of entries specifies the order in which the fallback provisions should be applied.
LegMarketDisruptionFallbackValue	[0..1]	String	

Used in components: **LegMarketDisruption**

#### **180.2.1724 LegMarketDisruptionFallbackOpenUnits**

If there are multiple underlying assets, this specifies the number of units (index or securities) that constitute the underlier of the swap. In the case of a basket swap, this is used to reference both the number of basket units, and the number of each asset components of the basket when these are expressed in absolute terms.

Type: **Qty**

Used in groups: **LegMarketDisruptionFallbackReferencePriceGrp**

**180.2.1725 LegMarketDisruptionFallbackProvision**

Specifies the location of the fallback provision documentation.

Type: **int**

Allowed values in MarketDisruptionFallbackProvisionCodeSet:

Code	Name	Description
0	MasterAgreement	As specified in master agreement
1	Confirmation	As specified in confirmation

Used in components: **LegMarketDisruption**

**180.2.1726 LegMarketDisruptionFallbackReferencePriceGrp**

The LegMarketDisruptionFallbackReferencePriceGrp is a repeating subcomponent of the LegMarketDisruption component used to specify the fallback reference price and underlying security provisions

Name	Mult.	Type	Description
NoLegMarketDisruptionFallbackReferencePrices	[1..1]	NumInGroup	
LegMarketDisruptionFallbackUnderlierType	[0..1]	CodeSet	Required if NoLegMarketDisruptionFallbackReferencePrices(41471) > 0.
LegMarketDisruptionFallbackUnderlierSecurityID	[0..1]	String	Conditionally required when LegMarketDisruptionFallbackUnderlierSecurityIDSource(41474) is specified.
LegMarketDisruptionFallbackUnderlierSecurityIDSource	[0..1]	CodeSet	Conditionally required when LegMarketDisruptionFallbackUnderlierSecurityID(41473) is specified.
LegMarketDisruptionFallbackUnderlierSecurityDesc	[0..1]	String	
EncodedLegMarketDisruptionFallbackUnderlierSecurityDescLen	[0..1]	Length	Must be set if EncodedLegMarketDisruptionFallbackUnderlierSecurityDesc(41477) field is specified and must immediately precede it.
EncodedLegMarketDisruptionFallbackUnderlierSecurityDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the LegMarketDisruptionFallbackUnderlierSecurityDesc(41475) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
LegMarketDisruptionFallbackOpenUnits	[0..1]	Qty	
LegMarketDisruptionFallbackBasketCurrency	[0..1]	Currency	
LegMarketDisruptionFallbackBasketDivisor	[0..1]	float	

Used in components: [LegMarketDisruption](#)

#### **180.2.1727 LegMarketDisruptionFallbackType**

Specifies the type of disruption fallback.

See <http://www.fpml.org/coding-scheme/commodity-market-disruption-fallback> for values.

Type: [String](#)

Used in groups: [LegMarketDisruptionFallbackGrp](#)

#### **180.2.1728 LegMarketDisruptionFallbackUnderlierSecurityDesc**

Specifies the description of the underlying security.

Type: [String](#)

Used in groups: [LegMarketDisruptionFallbackReferencePriceGrp](#)

#### **180.2.1729 LegMarketDisruptionFallbackUnderlierSecurityID**

Specifies the identifier value of the security.

Type: [String](#)

Used in groups: [LegMarketDisruptionFallbackReferencePriceGrp](#)

#### **180.2.1730 LegMarketDisruptionFallbackUnderlierSecurityIDSource**

Specifies the class or source scheme of the security identifier.

Type: [String](#)

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.

Code	Name	Description
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [LegMarketDisruptionFallbackReferencePriceGrp](#)

### 180.2.1731 LegMarketDisruptionFallbackUnderlierType

The type of reference price underlier.

Type: [int](#)

Allowed values in MarketDisruptionFallbackUnderlierTypeCodeSet:

Code	Name	Description
0	Basket	Basket
1	Bond	Bond
2	Cash	Cash
3	Commodity	Commodity
4	ConvertibleBond	Convertible bond
5	Equity	Equity
6	ExchangeTradedFund	Exchange traded fund
7	Future	Future
8	Index	Index
9	Loan	Loan
10	Mortgage	Mortgage
11	MutualFund	Mutual fund

Used in groups: [LegMarketDisruptionFallbackReferencePriceGrp](#)

### 180.2.1732 LegMarketDisruptionFallbackValue

Applicable value for LegMarketDisruptionFallbackType(41470).

Type: **String**

Used in groups: **LegMarketDisruptionFallbackGrp**

#### **180.2.1733 LegMarketDisruptionMaterialityPercentage**

Used when a price materiality percentage applies to the price source disruption event and this event has been specified.

Type: **Percentage**

Used in components: **LegMarketDisruption**

#### **180.2.1734 LegMarketDisruptionMaximumDays**

Specifies the maximum number of market disruption days (commodity or bullion business days) in a contract or confirmation. If none are specified, the maximum number of market disruption days is five (5).

Type: **int**

Used in components: **LegMarketDisruption**

#### **180.2.1735 LegMarketDisruptionMinimumFuturesContracts**

Specifies the minimum futures contracts level that dictates whether or not a 'De Minimis Trading' event has occurred.

Type: **int**

Used in components: **LegMarketDisruption**

#### **180.2.1736 LegMarketDisruptionProvision**

The consequences of market disruption events.

Type: **int**

Allowed values in MarketDisruptionProvisionCodeSet:

---

Code	Name	Description
0	NotApplicable	Not applicable

---



Code	Name	Description
1	Applicable	Applicable
2	AsInMasterAgreement	As specified in master agreement
3	AsInConfirmation	As specified in confirmation

Used in components: [LegMarketDisruption](#)

#### **180.2.1737 LegMarketDisruptionValue**

Applicable value for LegMarketDisruptionEvent(41468).

Type: [String](#)

Used in groups: [LegMarketDisruptionEventGrp](#)

#### **180.2.1738 LegMasterConfirmationAnnexDate**

The date that an annexation to the master confirmation was executed between the parties.

Type: [LocalMktDate](#)

Used in components: [LegFinancingDetails](#)

#### **180.2.1739 LegMasterConfirmationAnnexDesc**

The type of master confirmation annexation executed between the parties. See <http://www.fpml.org/coding-scheme/master-confirmation-annex-type> for values.

Type: [String](#)

Used in components: [LegFinancingDetails](#)

#### **180.2.1740 LegMasterConfirmationDate**

Alternative to broker confirmation. The date of the confirmation executed between the parties and intended to govern all relevant transactions between those parties.

Type: [LocalMktDate](#)

Used in components: [LegFinancingDetails](#)

**180.2.1741 LegMasterConfirmationDesc**

The type of master confirmation executed between the parties. See <http://www.fpml.org/coding-scheme/master-confirmation-type> for values.

Type: **String**

Used in components: **LegFinancingDetails**

**180.2.1742 LegMaterialDividendsIndicator**

Indicates whether material non-cash dividends are applicable.

Type: **Boolean**

Used in components: **LegDividendConditions**

**180.2.1743 LegMaturityDate**

Multileg instrument's individual security's MaturityDate.

See MaturityDate(541) field for description.

Type: **LocalMktDate**

Used in components: **InstrumentLeg**

**180.2.1744 LegMaturityFrequencyPeriod**

Time unit multiplier for the minimum frequency of the instrument maturity intervals.

Type: **int**

Used in components: **InstrumentLeg**

**180.2.1745 LegMaturityFrequencyUnit**

Time unit associated with the minimum frequency of the instrument maturity intervals.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in components: [InstrumentLeg](#)

#### **180.2.1746 LegMaturityMonthYear**

Multileg instrument's individual security's MaturityMonthYear.

See MaturityMonthYear (200) field for description

Type: [MonthYear](#)

Used in components: [InstrumentLeg](#)

#### **180.2.1747 LegMaturityTime**

Time of security's maturity expressed in local time with offset to UTC specified

Type: [TZTimeOnly](#)

Used in components: [InstrumentLeg](#)

#### **180.2.1748 LegMidPx**

Leg Mid price/rate.

For OTC swaps, this is the mid-market mark (for example, as defined by CFTC).

For uncleared OTC swaps, LegMidPx(2346) and the MidPx(631) fields are mutually exclusive.

Type: **Price**

Used in groups: **InstrmtLegExecGrp**, **LegQuotGrp**, **LegQuotStatGrp**, **QuotReqLegsGrp**, **TrdInstrmtLegGrp**

#### **180.2.1749 LegMinPriceIncrement**

Minimum price increment for a given exchange-traded instrument. Could also be used to represent tick value.

Type: **float**

Used in components: **InstrumentLeg**

#### **180.2.1750 LegMinPriceIncrementAmount**

Minimum price increment amount associated with the LegMinPriceIncrement(2190). For listed derivatives, the value can be calculated by multiplying LegMinPriceIncrement(2190) by LegContractMultiplier(614).

Type: **Amt**

Used in components: **InstrumentLeg**

#### **180.2.1751 LegMthToDefault**

The Mth reference obligation to default in a CDS reference basket. When an NthToDefault(2157) to MthToDefault(2158) are represented then the CDS payout occurs between the Nth and Mth obligations to default.

Type: **int**

Used in components: **InstrumentLeg**

#### **180.2.1752 LegNonCashDividendTreatment**

Defines the treatment of non-cash dividends.

Type: **int**

Allowed values in NonCashDividendTreatmentCodeSet:

Code	Name	Description
0	PotentialAdjustment	Potential adjustment event. The treatment of any non-cash dividend shall be determined in accordance with the potential adjustment event provisions.
1	CashEquivalent	Cash equivalent. Any non-cash dividend shall be treated as a declared cash equivalent dividend.

Used in components: [LegDividendConditions](#)

### 180.2.1753 LegNonDeliverableFixingDate

The non-deliverable fixing date. Type of date is specified in LegNonDeliverableFixingDateType(40369).

Type: [LocalMktDate](#)

Used in groups: [LegPaymentStreamNonDeliverableFixingDateGrp](#)

### 180.2.1754 LegNonDeliverableFixingDateType

Specifies the type of date (e.g. adjusted for holidays).

Type: [int](#)

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [LegPaymentStreamNonDeliverableFixingDateGrp](#)

### 180.2.1755 LegNotionalPercentageOutstanding

Indicates the notional percentage of the deal that is still outstanding based on the remaining components of the index.

Used to calculate the true value of a CDS trade or position.

Type: **Percentage**

Used in components: **InstrumentLeg**

#### **180.2.1756 LegNthToDefault**

The Nth reference obligation in a CDS reference basket. If specified without LegMthToDefault(2158) the default will trigger a CDS payout. If LegMthToDefault(2158) is also present then payout occurs between the Nth and Mth obligations to default.

Type: **int**

Used in components: **InstrumentLeg**

#### **180.2.1757 LegNTPositionLimit**

Position limit in the near-term contract for a given exchange-traded product.

Type: **int**

Used in components: **InstrumentLeg**

#### **180.2.1758 LegNumber**

Allow sequencing of Legs for a Strategy to be captured

Type: **int**

Used in groups: **TrdInstrmtLegGrp**

#### **180.2.1759 LegObligationType**

Type of reference obligation for credit derivatives contracts.

Type: **String**

Allowed values in ObligationTypeCodeSet:

---

Code	Name	Description
0	Bond	Bond
1	ConvertBond	Convertible bond
2	Mortgage	Mortgage

---

Code	Name	Description
3	Loan	Loan

Used in components: [InstrumentLeg](#)

#### **180.2.1760 LegOfferForwardPoints**

The offer FX forward points for the leg of an FX Swap. Value can be negative. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199

Type: [PriceOffset](#)

Used in groups: [LegQuotGrp](#)

#### **180.2.1761 LegOfferPx**

Offer price of this leg.

See OfferPx (133) for description and valid values

Type: [Price](#)

Used in groups: [LegQuotGrp](#)

#### **180.2.1762 LegOptAttribute**

Multileg instrument's individual security's OptAttribute.

See OptAttribute (206) field for description

Type: [char](#)

Used in components: [InstrumentLeg](#)

#### **180.2.1763 LegOptionExerciseBusinessCenter**

The business center calendar used to adjust the option exercise dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [LegOptionExerciseBusinessCenterGrp](#)

**180.2.1764 LegOptionExerciseBusinessCenterGrp**

LegOptionExerciseBusinessCenterGrp is a repeating subcomponent of the LegOptionExerciseDates component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegOptionExerciseBusinessCenters	[1..1]	NumInGroup	
LegOptionExerciseBusinessCenter	[0..1]	String	Required if NoLegOptionExerciseBusinessCenters(41491) > 0.

Used in components: [LegOptionExerciseDates](#)

**180.2.1765 LegOptionExerciseBusinessDayConvention**

The business day convention used to adjust the option exercise dates. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegOptionExerciseDates](#)



**180.2.1766 LegOptionExercise**

The LegOptionExercise component is a subcomponent of the InstrumentLeg component used to specify option exercise provisions. Its purpose is to identify the opportunities and conditions for exercise, e.g. the schedule of dates on which exercise is allowed. The embedded LegOptionExerciseExpiration component is used to terminate the opportunity for exercise.

Name	Mult.	Type	Description
LegExerciseDesc	[0..1]	String	
EncodedLegExerciseDescLen	[0..1]	Length	Must be set if EncodedLegExerciseDesc (41483) field is specified and must immediately precede it.
EncodedLegExerciseDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the LegExerciseDesc(41481) field in the encoded format specified via the MessageEncoding(347) field.
LegAutomaticExerciseIndicator	[0..1]	Boolean	
LegAutomaticExerciseThresholdRate	[0..1]	float	
LegExerciseConfirmationMethod	[0..1]	CodeSet	
LegManualNoticeBusinessCenter	[0..1]	String	
LegFallbackExerciseIndicator	[0..1]	Boolean	
LegLimitRightToConfirmIndicator	[0..1]	Boolean	
LegExerciseSplitTicketIndicator	[0..1]	Boolean	
LegSettlMethodElectingPartySide	[0..1]	CodeSet	
LegSettlMethodElectionDate	[0..1]	Component	
LegOptionExerciseDates	[0..1]	Component	
LegOptionExerciseExpiration	[0..1]	Component	
LegOptionExerciseMakeWholeProvision	[0..1]	Component	

Used in components: **InstrumentLeg**

**180.2.1767 LegOptionExerciseDate**

The adjusted or unadjusted option exercise fixed date.

Type: **LocalMktDate**

Used in groups: **LegOptionExerciseDateGrp**

**180.2.1768 LegOptionExerciseDateGrp**

The LegOptionExerciseDateGrp is a repeating subcomponent of the LegOptionExerciseDates component used to specify fixed dates for exercise.

Name	Mult.	Type	Description
NoLegOptionExerciseDates	[1..1]	NumInGroup	
LegOptionExerciseDate	[0..1]	LocalMktDate	Required if NoLegOptionExerciseDates(41512) > 0.
LegOptionExerciseDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [LegOptionExerciseDates](#)

**180.2.1769 LegOptionExerciseDates**

The LegOptionExerciseDates component is a subcomponent of the LegOptionExercise component used to specify option exercise dates.

Name	Mult.	Type	Description
LegOptionExerciseBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of option exercise dates.
LegOptionExerciseBusinessCenterGrp	[0..*]	Group	
LegOptionExerciseDateGrp	[0..*]	Group	
LegOptionExerciseEarliestDateOffset-DayType	[0..1]	CodeSet	
LegOptionExerciseEarliestDateOffset-Period	[0..1]	int	Conditionally required when LegOptionExerciseEarliestDateUnit(41496) is specified.
LegOptionExerciseEarliestDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegOptionExerciseEarliestDatePeriod(41495) is specified.
LegOptionExerciseFrequencyPeriod	[0..1]	int	Conditionally required when LegOptionExerciseFrequencyUnit(41498) is specified.

Name	Mult.	Type	Description
LegOptionExerciseFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegOptionExerciseFrequencyPeriod(41497) is specified.
LegOptionExerciseStartDateUnadjusted	[0..1]	LocalMktDate	
LegOptionExerciseStartDateRelativeTo	[0..1]	int	
LegOptionExerciseStartDateOffsetPeriod	[0..1]	int	Conditionally required when LegOptionExerciseStartDateOffsetUnit(41502) is specified.
LegOptionExerciseStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegOptionExerciseStartDateOffsetPeriod(41501) is specified.
LegOptionExerciseStartDateOffsetDayType	[0..1]	CodeSet	
LegOptionExerciseStartDateAdjusted	[0..1]	LocalMktDate	
LegOptionExerciseSkip	[0..1]	int	
LegOptionExerciseNominationDeadline	[0..1]	LocalMktDate	
LegOptionExerciseFirstDateUnadjusted	[0..1]	LocalMktDate	
LegOptionExerciseLastDateUnadjusted	[0..1]	LocalMktDate	
LegOptionExerciseEarliestTime	[0..1]	LocalMktTime	
LegOptionExerciseLatestTime	[0..1]	LocalMktTime	
LegOptionExerciseTimeBusinessCenter	[0..1]	String	

Used in components: **LegOptionExercise**

### 180.2.1770 LegOptionExerciseDateType

Specifies the type of option exercise date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [LegOptionExerciseDateGrp](#)

#### **180.2.1771 LegOptionExerciseEarliestDateOffsetDayType**

Specifies the day type of the relative earliest exercise date offset.

Type: [int](#)

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegOptionExerciseDates](#)

#### **180.2.1772 LegOptionExerciseEarliestDateOffsetPeriod**

Time unit multiplier for the relative earliest exercise date offset.

Type: [int](#)

Used in components: [LegOptionExerciseDates](#)

#### **180.2.1773 LegOptionExerciseEarliestDateOffsetUnit**

Time unit associated with the relative earliest exercise date offset.

Type: [String](#)

Allowed values in ProvisionOptionExerciseEarliestDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegOptionExerciseDates](#)

#### 180.2.1774 LegOptionExerciseEarliestTime

The earliest time at which notice of exercise can be given by the buyer to the seller (or seller's agent) (i) on the expiration date, in the case of a European style option, (ii) on each Bermuda option exercise date and the expiration date, in the case of a Bermuda style option, (iii) the commencement date to, and including, the expiration date, in the case of an American option.

Type: [LocalMktTime](#)

Used in components: [LegOptionExerciseDates](#)

#### 180.2.1775 LegOptionExerciseExpiration

The LegOptionExerciseExpiration component is a subcomponent of the LegOptionExercise component used to specify option exercise expiration dates and times. The purpose of LegOptionExercise is to identify the scheduled opportunities for exercise. LegOptionExerciseExpiration identifies the end of the schedule.

Name	Mult.	Type	Description
<a href="#">LegOptionExerciseExpirationDateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to the option exercise expiration date.
<a href="#">LegOptionExerciseExpirationDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to the option exercise expiration date.
<a href="#">LegOptionExerciseExpirationDateGrp</a>	[0..*]	Group	

Name	Mult.	Type	Description
LegOptionExerciseExpirationDateRelativeTo	[0..1]	int	
LegOptionExerciseExpirationDateOffsetPeriod	[0..1]	int	Conditionally required when LegOptionExerciseExpirationDateOffsetUnit(41520) is specified.
LegOptionExerciseExpirationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegOptionExerciseExpirationDateOffsetPeriod(41519) is specified.
LegOptionExerciseExpirationFrequencyPeriod	[0..1]	int	Conditionally required when LegOptionExerciseExpirationFrequencyUnit(41522) is specified.
LegOptionExerciseExpirationFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegOptionExerciseExpirationFrequencyPeriod(41521) is specified.
LegOptionExerciseExpirationRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the option expiration date.
LegOptionExerciseExpirationDateOffsetDayType	[0..1]	CodeSet	
LegOptionExerciseExpirationTime	[0..1]	LocalMktTime	
LegOptionExerciseExpirationTimeBusinessCenter	[0..1]	String	

Used in components: [LegOptionExercise](#)

### 180.2.1776 LegOptionExerciseExpirationDate

The adjusted or unadjusted option exercise expiration fixed date.

Type: [LocalMktDate](#)

Used in groups: [LegOptionExerciseExpirationDateGrp](#)

### 180.2.1777 LegOptionExerciseExpirationDateBusinessCenter

The business center calendar used to adjust the option exercise expiration dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [LegOptionExerciseExpirationDateBusinessCenterGrp](#)

**180.2.1778 LegOptionExerciseExpirationDateBusinessCenterGrp**

LegOptionExerciseExpirationDateBusinessCenterGrp is a repeating subcomponent of the LegOptionExerciseExpiration component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegOptionExerciseExpirationDateBusinessCenters	[1..1]	NumInGroup	
LegOptionExerciseExpirationDateBusinessCenter	[0..1]	String	Required if NoLegOptionExerciseExpirationDateBusinessCenters(41515) > 0.

Used in components: [LegOptionExerciseExpiration](#)

**180.2.1779 LegOptionExerciseExpirationDateBusinessDayConvention**

The business day convention used to adjust the option exercise expiration dates. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegOptionExerciseExpiration](#)

**180.2.1780 LegOptionExerciseExpirationDateGrp**

The LegOptionExerciseExpirationDateGrp is a repeating subcomponent of the LegOptionExerciseExpiration component used to specify fixed dates for expiration.

Name	Mult.	Type	Description
NoLegOptionExerciseExpirationDates	[1..1]	NumInGroup	
LegOptionExerciseExpirationDate	[0..1]	LocalMktDate	Required if NoLegOptionExerciseExpirationDates(41527) > 0.
LegOptionExerciseExpirationDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [LegOptionExerciseExpiration](#)

**180.2.1781 LegOptionExerciseExpirationDateOffsetDayType**

Specifies the day type of the relative option exercise expiration date offset.

Type: [int](#)

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegOptionExerciseExpiration](#)

**180.2.1782 LegOptionExerciseExpirationDateOffsetPeriod**

Time unit multiplier for the relative exercise expiration date offset.

Type: [int](#)

Used in components: [LegOptionExerciseExpiration](#)



**180.2.1783 LegOptionExerciseExpirationDateOffsetUnit**

Time unit associated with the relative exercise expiration date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegOptionExerciseExpiration**

**180.2.1784 LegOptionExerciseExpirationDateRelativeTo**

Specifies the anchor date when the option exercise expiration date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegOptionExerciseExpiration**

**180.2.1785 LegOptionExerciseExpirationDateType**

Specifies the type of option exercise expiration date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **LegOptionExerciseExpirationDateGrp**

**180.2.1786 LegOptionExerciseExpirationFrequencyPeriod**

Time unit multiplier for the frequency of exercise expiration dates.

Type: **int**

Used in components: **LegOptionExerciseExpiration**

**180.2.1787 LegOptionExerciseExpirationFrequencyUnit**

Time unit associated with the frequency of exercise expiration dates.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegOptionExerciseExpiration**

**180.2.1788 LegOptionExerciseExpirationRollConvention**

The convention for determining the sequence of exercise expiration dates. It is used in conjunction with a specified frequency. Used only to override the roll convention defined in the LegDateAdjustment component in InstrumentLeg.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month

Code	Name	Description
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEigthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.

Code	Name	Description
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [LegOptionExerciseExpiration](#)

#### **180.2.1789 LegOptionExerciseExpirationTime**

The option exercise expiration time.

Type: [LocalMktTime](#)

Used in components: [LegOptionExerciseExpiration](#)

#### **180.2.1790 LegOptionExerciseExpirationTimeBusinessCenter**

The business center used to determine the locale for option exercise expiration time, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in components: [LegOptionExerciseExpiration](#)

#### **180.2.1791 LegOptionExerciseFirstDateUnadjusted**

The unadjusted first exercise date.

Type: [LocalMktDate](#)

Used in components: [LegOptionExerciseDates](#)

**180.2.1792 LegOptionExerciseFrequencyPeriod**

Time unit multiplier for the frequency of exercise dates.

Type: **int**

Used in components: **LegOptionExerciseDates**

**180.2.1793 LegOptionExerciseFrequencyUnit**

Time unit associated with the frequency of exercise dates.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegOptionExerciseDates**

**180.2.1794 LegOptionExerciseLastDateUnadjusted**

The unadjusted last exercise date.

Type: **LocalMktDate**

Used in components: **LegOptionExerciseDates**

**180.2.1795 LegOptionExerciseLatestTime**

The latest exercise time. See also LegOptionExerciseEarliestTime(41509).

Type: **LocalMktTime**

Used in components: **LegOptionExerciseDates**

**180.2.1796 LegOptionExerciseMakeWholeProvision**

LegOptionExerciseMakeWholeProvision is a subcomponent of the LegOptionExercise component used to specify the set of rules of maintaining balance when an option is exercised.

Name	Mult.	Type	Description
LegMakeWholeDate	[0..1]	LocalMktDate	
LegMakeWholeAmount	[0..1]	Amt	
LegMakeWholeBenchmarkCurveName	[0..1]	String	
LegMakeWholeBenchmarkCurvePoint	[0..1]	String	
LegMakeWholeRecallSpread	[0..1]	PriceOffset	
LegMakeWholeBenchmarkQuote	[0..1]	CodeSet	
LegMakeWholeInterpolationMethod	[0..1]	CodeSet	

Used in components: [LegOptionExercise](#)

**180.2.1797 LegOptionExerciseNominationDeadline**

The last date (adjusted) for establishing the option exercise terms.

Type: [LocalMktDate](#)

Used in components: [LegOptionExerciseDates](#)

**180.2.1798 LegOptionExerciseSkip**

The number of periods in the referenced date schedule that are between each date in the relative date schedule. Thus a skip of 2 would mean that dates are relative to every second date in the referenced schedule. If present this should have a value greater than 1.

Type: [int](#)

Used in components: [LegOptionExerciseDates](#)

**180.2.1799 LegOptionExerciseStartDateAdjusted**

The adjusted start date for calculating periodic exercise dates.

Type: [LocalMktDate](#)

Used in components: [LegOptionExerciseDates](#)

**180.2.1800 LegOptionExerciseStartDateOffsetDayType**

Specifies the day type of the relative option exercise start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegOptionExerciseDates**

**180.2.1801 LegOptionExerciseStartDateOffsetPeriod**

Time unit multiplier for the relative exercise start date offset.

Type: **int**

Used in components: **LegOptionExerciseDates**

**180.2.1802 LegOptionExerciseStartDateOffsetUnit**

Time unit associated with the relative exercise start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegOptionExerciseDates**

**180.2.1803 LegOptionExerciseStartDateRelativeTo**

Specifies the anchor date when the option exercise start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegOptionExerciseDates**

**180.2.1804 LegOptionExerciseStartDateUnadjusted**

The unadjusted start date for calculating periodic exercise dates.

Type: **LocalMktDate**

Used in components: **LegOptionExerciseDates**

**180.2.1805 LegOptionExerciseTimeBusinessCenter**

The business center used to determine the locale for option exercise time, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **LegOptionExerciseDates**

**180.2.1806 LegOptionExpirationDesc**

Description of the option expiration.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.1807 LegOptionRatio**

Expresses the risk of an option leg

Value must be between -1 and 1.

A Call Option will require a ratio value between 0 and 1

A Put Option will require a ratio value between -1 and 0



Type: **float**

Used in components: **InstrumentLeg**

#### **180.2.1808 LegOptionsExchangeDividendsIndicator**

Indicates whether option exchange dividends are applicable.

Type: **Boolean**

Used in components: **LegDividendConditions**

#### **180.2.1809 LegOptPayoutAmount**

Cash amount indicating the pay out associated with an option. For binary options this is a fixed amount.

Type: **Amt**

Used in components: **InstrumentLeg**

#### **180.2.1810 LegOptPayoutType**

Indicates the type of valuation method or trigger payout for an in-the-money option.

Type: **int**

Allowed values in OptPayoutTypeCodeSet:

<b>Code</b>	<b>Name</b>	<b>Description</b>
1	Vanilla	Vanilla
2	Capped	Capped
3	Binary	Digital (Binary)
4	Asian	Asian
5	Barrier	Barrier
6	DigitalBarrier	Digital Barrier
7	Lookback	Lookback
8	OtherPathDependent	Other path dependent
99	Other	Other

Used in components: **InstrumentLeg**

**180.2.1811 LegOrderQty**

Quantity ordered of this leg.

See OrderQty (38) for description and valid values

Type: Qty

Used in groups: InstrmtLegExecGrp, LegOrdGrp, LegQuotGrp, LegQuotStatGrp, QuotReqLegsGrp, SideCrossLegGrp, TrdInstrmtLegExecGrp, TrdInstrmtLegGrp

**180.2.1812 LegOrdGrp**

Name	Mult.	Type	Description
NoLegs	[1..1]	NumInGroup	
InstrumentLeg	[0..1]	Component	Required if NoLegs(555) > 0.
LegOrderQty	[0..1]	Qty	Quantity ordered for this leg as provided during order entry.
LegQty	[0..1]	Qty	The LegQty(687) field is deprecated. The use of LegOrderQty(685) is recommended instead.
LegSwapType	[0..1]	CodeSet	Instead of LegOrderQty(685) requests that the sellside calculate LegOrderQty(685) based on opposite Leg.
LegStipulations	[0..*]	Group	
LegAllocID	[0..1]	String	
LegPreAllocGrp	[0..*]	Group	
LegAccount	[0..1]	String	
LegClearingAccountType	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in ClearingAccountType(1816) in the Instrument component.
LegPositionEffect	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in PositionEffect(77) in the Instrument component.
LegCoveredOrUncovered	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in CoveredOrUncovered(203) in the Instrument component
NestedParties	[0..*]	Group	

Name	Mult.	Type	Description
LegRefID	[0..1]	String	Use of LegRefID(654) in this component is deprecated. Recommend the use of LegID(1788) in the InstrumentLeg component.
LegSettlType	[0..1]	CodeSet	
LegSettlDate	[0..1]	LocalMktDate	
LegSettlCurrency	[0..1]	Currency	
LegSettlCurrencyCodeSource	[0..1]	CodeSet	
LegVolatility	[0..1]	float	
LegDividendYield	[0..1]	Percentage	
LegCurrencyRatio	[0..1]	float	
LegExecInst	[0..1]	CodeSet	
LegShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when LegSide(624) = 6 (Sell short exempt) in InstrumentLeg component.

Used in messages: [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#)

#### 180.2.1813 LegOriginalNotionalPercentageOutstanding

Used to reflect the Original value prior to the application of a credit event. See LegNotionalPercentageOutstanding(2151).

Type: [Percentage](#)

Used in components: [InstrumentLeg](#)

#### 180.2.1814 LegPaymentScheduleCurrency

The currency for this step schedule. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### 180.2.1815 LegPaymentScheduleEndDateUnadjusted

The unadjusted end date of a cashflow payment.

Type: **LocalMktDate**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1816 LegPaymentScheduleFixedAmount**

The explicit payment amount for this step schedule.

Type: **Amt**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1817 LegPaymentScheduleFixedCurrency**

The currency of the fixed amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1818 LegPaymentScheduleFixingDateAdjusted**

The adjusted fixing date.

Type: **LocalMktDate**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1819 LegPaymentScheduleFixingDateBusinessCenter**

The business center calendar used to adjust the payment schedule's fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentScheduleFixingDateBusinessCenterGrp**

#### **180.2.1820 LegPaymentScheduleFixingDateBusinessCenterGrp**

**LegPaymentScheduleFixingDateBusinessCenterGrp** is a repeating subcomponent within the **LegPaymentScheduleGrp** component. It is used to specify the set of business centers whose calendars drive

the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPaymentScheduleFixingDate-BusinessCenters	[1..1]	NumInGroup	
LegPaymentScheduleFixingDateBusinessCenter	[0..1]	String	Required if NoLegPaymentScheduleFixingDate-BusinessCenters(40927) > 0.

Used in groups: [LegPaymentScheduleGrp](#)

### 180.2.1821 LegPaymentScheduleFixingDateBusinessDayConvention

The business day convention used to adjust the payment schedule's fixing date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [LegPaymentScheduleGrp](#)

### 180.2.1822 LegPaymentScheduleFixingDateOffsetDayType

Specifies the day type of the relative fixing date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1823 LegPaymentScheduleFixingDateOffsetPeriod**

Time unit multiplier for the relative fixing date offset.

Type: [int](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1824 LegPaymentScheduleFixingDateOffsetUnit**

Time unit associated with the relative fixing date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [LegPaymentScheduleGrp](#)

**180.2.1825 LegPaymentScheduleFixingDateRelativeTo**

Specifies the anchor date when the fixing date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1826 LegPaymentScheduleFixingDateUnadjusted**

The unadjusted fixing date.

Type: **LocalMktDate**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1827 LegPaymentScheduleFixingDayCount**

The number of days over which fixing should take place.

Type: **int**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1828 LegPaymentScheduleFixingDayDistribution**

The distribution of fixing days.

Type: **int**

Allowed values in PaymentStreamPricingDayDistributionCodeSet:

Code	Name	Description
0	All	All
1	First	First
2	Last	Last
3	Penultimate	Penultimate

Used in groups: **LegPaymentScheduleGrp**

**180.2.1829 LegPaymentScheduleFixingDayGrp**

The LegPaymentScheduleFixingDayGrp is a repeating subcomponent of the LegPaymentScheduleGrp component used to detail periodic fixing days.

Name	Mult.	Type	Description
NoLegPaymentScheduleFixingDays	[1..1]	NumInGroup	
LegPaymentScheduleFixingDay-OfWeek	[0..1]	CodeSet	Required if NoLegPaymentScheduleFixingDays(41530) > 0.
LegPaymentScheduleFixingDayNumber	[0..1]	int	

Used in groups: [LegPaymentScheduleGrp](#)

**180.2.1830 LegPaymentScheduleFixingDayNumber**

The occurrence of the day of week on which fixing takes place.

Type: [int](#)

Used in groups: [LegPaymentScheduleFixingDayGrp](#)

**180.2.1831 LegPaymentScheduleFixingDayOfWeek**

The day of the week on which fixing takes place.

Type: [int](#)

Allowed values in PaymentStreamPricingDayOfWeekCodeSet:

Code	Name	Description
0	EveryDay	Every day (the default if not specified)
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday



Code	Name	Description
7	Sunday	Sunday

Used in groups: [LegPaymentScheduleFixingDayGrp](#)

#### **180.2.1832 LegPaymentScheduleFixingFirstObservationDateOffsetPeriod**

Time unit multiplier for the relative first observation date offset.

Type: [int](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1833 LegPaymentScheduleFixingFirstObservationDateOffsetUnit**

Time unit associated with the relative first observation date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1834 LegPaymentScheduleFixingLagPeriod**

Time unit multiplier for the fixing lag duration.

Type: [int](#)

Used in groups: [LegPaymentScheduleGrp](#)

**180.2.1835 LegPaymentScheduleFixingLagUnit**

Time unit associated with the fixing lag duration.

Type: **String**

Allowed values in PaymentStreamInflationLagUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegPaymentScheduleGrp**

**180.2.1836 LegPaymentScheduleFixingTime**

The fixing time associated with the step schedule.

Type: **LocalMktTime**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1837 LegPaymentScheduleFixingTimeBusinessCenter**

Business center for determining fixing time.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1838 LegPaymentScheduleGrp**

The LegPaymentScheduleGrp is a repeating subcomponent of the LegPaymentStream component used to specify notional and rate steps in the payment stream.

Name	Mult.	Type	Description
NoLegPaymentSchedules	[1..1]	NumInGroup	
LegPaymentScheduleType	[0..1]	CodeSet	Required if NoLegPaymentSchedules(40374) > 0.
LegPaymentScheduleXID	[0..1]	XID	
LegPaymentScheduleXIDRef	[0..1]	XIDREF	
LegPaymentScheduleStubType	[0..1]	CodeSet	
LegPaymentScheduleStartDateUnadjusted	[0..1]	LocalMktDate	
LegPaymentScheduleEndDateUnadjusted	[0..1]	LocalMktDate	
LegPaymentSchedulePaySide	[0..1]	CodeSet	
LegPaymentScheduleReceiveSide	[0..1]	CodeSet	
LegPaymentScheduleNotional	[0..1]	Amt	
LegPaymentScheduleCurrency	[0..1]	Currency	
LegPaymentScheduleRate	[0..1]	Percentage	
LegPaymentScheduleRateMultiplier	[0..1]	float	
LegPaymentScheduleRateSpread	[0..1]	PriceOffset	
LegPaymentScheduleRateCurrency	[0..1]	Currency	
LegPaymentScheduleRateUnitOfMeasure	[0..1]	CodeSet	
LegPaymentScheduleRateConversionFactor	[0..1]	float	
LegPaymentScheduleRateSpreadType	[0..1]	CodeSet	
LegPaymentScheduleRateSpreadPositionType	[0..1]	CodeSet	
LegPaymentScheduleRateTreatment	[0..1]	CodeSet	
LegPaymentScheduleFixedAmount	[0..1]	Amt	
LegPaymentScheduleFixedCurrency	[0..1]	Currency	
LegPaymentScheduleSettlPeriodPrice	[0..1]	Price	
LegPaymentScheduleSettlPeriodPriceCurrency	[0..1]	Currency	
LegPaymentScheduleSettlPeriodPriceUnitOfMeasure	[0..1]	CodeSet	
LegPaymentScheduleStepUnitOfMeasure	[0..1]	CodeSet	
LegPaymentScheduleStepFrequencyPeriod	[0..1]	int	Conditionally required when LegPaymentScheduleStepFrequencyUnit(40391) is specified.

Name	Mult.	Type	Description
LegPaymentScheduleStepFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegPaymentScheduleStepFrequencyPeriod(40390) is specified.
LegPaymentScheduleStepOffsetValue	[0..1]	Amt	
LegPaymentScheduleStepRate	[0..1]	Percentage	
LegPaymentScheduleStepOffsetRate	[0..1]	Percentage	
LegPaymentScheduleStepRelativeTo	[0..1]	CodeSet	
LegPaymentScheduleRateSourceGrp	[0..*]	Group	
LegPaymentScheduleFixingDateUnadjusted	[0..1]	LocalMktDate	
LegPaymentScheduleWeight	[0..1]	float	
LegPaymentScheduleFixingDateRelativeTo	[0..1]	int	
LegPaymentScheduleFixingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg payment schedule.
LegPaymentScheduleFixingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg payment schedule.
LegPaymentScheduleFixingDateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentScheduleFixingDatesOffsetUnit(40402) is specified.
LegPaymentScheduleFixingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentScheduleFixingDatesOffsetPeriod(40401) is specified.
LegPaymentScheduleFixingDateOffsetDayType	[0..1]	CodeSet	
LegPaymentScheduleFixingDayDistribution	[0..1]	CodeSet	
LegPaymentScheduleFixingDayCount	[0..1]	int	
LegPaymentScheduleFixingDateAdjusted	[0..1]	LocalMktDate	
LegPaymentScheduleFixingDayGrp	[0..*]	Group	
LegPaymentScheduleFixingLagPeriod	[0..1]	int	Conditionally required when LegPaymentScheduleFixingLagUnit(41546) is specified.

Name	Mult.	Type	Description
LegPaymentScheduleFixingLagUnit	[0..1]	CodeSet	Conditionally required when LegPaymentScheduleFixingLagPeriod(41545) is specified.
LegPaymentScheduleFixingFirstObservationDateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentScheduleFixingFirstObservationDateOffsetUnit(41548) is specified.
LegPaymentScheduleFixingFirstObservationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentScheduleFixingFirstObservationDateOffsetPeriod(41547) is specified.
LegPaymentScheduleFixingTime	[0..1]	LocalMktTime	
LegPaymentScheduleFixingTimeBusinessCenter	[0..1]	String	
LegPaymentScheduleInterimExchangePaymentDateRelativeTo	[0..1]	int	
LegPaymentScheduleInterimExchangeDatesBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg payment schedule.
LegPaymentScheduleInterimExchangeDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg payment schedule.
LegPaymentScheduleInterimExchangeDatesOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentScheduleInterimExchangeDatesOffsetUnit(40411) is specified.
LegPaymentScheduleInterimExchangeDatesOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentScheduleInterimExchangeDatesOffsetPeriod(40410) is specified.
LegPaymentScheduleInterimExchangeDatesOffsetDayType	[0..1]	CodeSet	
LegPaymentScheduleInterimExchangeDateAdjusted	[0..1]	LocalMktDate	

Used in groups: **LegStreamGrp**

**180.2.1839 LegPaymentScheduleInterimExchangeDateAdjusted**

The adjusted interim exchange date.

Type: **LocalMktDate**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1840 LegPaymentScheduleInterimExchangeDateBusinessCenterGrp**

LegPaymentScheduleInterimExchangeDateBusinessCenterGrp is a repeating subcomponent within the LegPaymentScheduleGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPaymentScheduleInterimExchangeDateBusinessCenters	[1..1]	NumInGroup	
LegPaymentScheduleInterimExchangeDatesBusinessCenter	[0..1]	String	Required if NoLegPaymentScheduleInterimExchangeDateBusinessCenters(40928) > 0.

Used in groups: **LegPaymentScheduleGrp**

**180.2.1841 LegPaymentScheduleInterimExchangeDatesBusinessCenter**

The business center calendar used to adjust the payment schedule's interim exchange date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentScheduleInterimExchangeDateBusinessCenterGrp**

**180.2.1842 LegPaymentScheduleInterimExchangeDatesBusinessDayConvention**

The business day convention used to adjust the payment schedule's interim exchange date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1843 LegPaymentScheduleInterimExchangeDatesOffsetDayType**

Specifies the day type of the relative interim exchange date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1844 LegPaymentScheduleInterimExchangeDatesOffsetPeriod**

Time unit multiplier for the relative interim exchange date offset.

Type: [int](#)

Used in groups: [LegPaymentScheduleGrp](#)

**180.2.1845 LegPaymentScheduleInterimExchangeDatesOffsetUnit**

Time unit associated with the relative interim exchange date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegPaymentScheduleGrp**

**180.2.1846 LegPaymentScheduleInterimExchangePaymentDateRelativeTo**

Specifies the anchor date when the interim exchange payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1847 LegPaymentScheduleNotional**

The notional value for this step schedule, or amount of a cashflow payment.

Type: **Amt**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1848 LegPaymentSchedulePaySide**

The side of the party paying the step schedule.

Type: **int**

Allowed values in PaymentPaySideCodeSet:



Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1849 LegPaymentScheduleRate**

The rate value for this step schedule.

Type: [Percentage](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1850 LegPaymentScheduleRateConversionFactor**

The number multiplied by the derived floating rate of the leg's payment schedule in order to arrive at the payment rate. If omitted, the schedule rate conversion factor is 1.

Type: [float](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1851 LegPaymentScheduleRateCurrency**

The currency of the schedule rate. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1852 LegPaymentScheduleRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: [float](#)

Used in groups: [LegPaymentScheduleGrp](#)

**180.2.1853 LegPaymentScheduleRateSource**

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: **LegPaymentScheduleRateSourceGrp**

**180.2.1854 LegPaymentScheduleRateSourceGrp**

LegPaymentScheduleRateSourceGrp is a repeating component within the LegPaymentScheduleGrp component used to identify primary and secondary rate sources.

Name	Mult.	Type	Description
<b>NoLegPaymentScheduleRateSources</b>	[1..1]	NumInGroup	
<b>LegPaymentScheduleRateSource</b>	[0..1]	CodeSet	Required if NoLegPaymentScheduleRateSources(40414) > 0.
<b>LegPaymentScheduleRateSourceType</b>	[0..1]	CodeSet	Required if NoLegPaymentScheduleRateSources(40414) > 0.
<b>LegPaymentScheduleReferencePage</b>	[0..1]	String	Conditionally required when LegPaymentScheduleRateSource(40415) = 99 (Other).

Used in groups: **LegPaymentScheduleGrp**

**180.2.1855 LegPaymentScheduleRateSourceType**

Rate source type.

Type: **int**

Allowed values in RateSourceTypeCodeSet:

Code	Name	Description
0	Primary	Primary
1	Secondary	Secondary

Used in groups: **LegPaymentScheduleRateSourceGrp**

**180.2.1856 LegPaymentScheduleRateSpread**

The spread value for this step schedule.

Type: **PriceOffset**

Used in groups: **LegPaymentScheduleGrp**

**180.2.1857 LegPaymentScheduleRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or a short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in groups: **LegPaymentScheduleGrp**

**180.2.1858 LegPaymentScheduleRateSpreadType**

Identifies whether the rate spread is an absolute value to be added to the index rate or a percentage of the index rate.

Type: **int**

Allowed values in PaymentStreamRateSpreadTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in groups: **LegPaymentScheduleGrp**

**180.2.1859 LegPaymentScheduleRateTreatment**

Specifies the yield calculation treatment for the step schedule.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in groups: **LegPaymentScheduleGrp**

**180.2.1860 LegPaymentScheduleRateUnitOfMeasure**

The schedule rate unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances

Code	Name	Description
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters

Code	Name	Description
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece

Code	Name	Description
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1861 LegPaymentScheduleReceiveSide**

The side of the party receiving the step schedule.

Type: [int](#)

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1862 LegPaymentScheduleReferencePage**

Identifies the reference "page" from the rate source.

For FX, the reference page to the spot rate to be used for the reference FX spot rate.

When RateSource(1446) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in groups: **LegPaymentScheduleRateSourceGrp**

#### **180.2.1863 LegPaymentScheduleSettlPeriodPrice**

The schedule settlement period price.

Type: **Price**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1864 LegPaymentScheduleSettlPeriodPriceCurrency**

The currency of the schedule settlement period price. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1865 LegPaymentScheduleSettlPeriodPriceUnitOfMeasure**

The settlement period price unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels



Code	Name	Description
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters

Code	Name	Description
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot

Code	Name	Description
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1866 LegPaymentScheduleStartDateUnadjusted**

The unadjusted date on which the value is adjusted, or calculated if a future value notional for certain non-deliverable interest rate swaps (e.g. Brazillian Real (BRL) vs. CETIP Interbank Deposit Rate (CDI)), or the start date of a cashflow payment.

Type: [LocalMktDate](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1867 LegPaymentScheduleStepFrequencyPeriod**

Time unit multiplier for the step frequency.

Type: [int](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1868 LegPaymentScheduleStepFrequencyUnit**

Time unit associated with the step frequency.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1869 LegPaymentScheduleStepOffsetRate**

The explicit amount that the rate changes on each step date. This can be a positive or negative value.

Type: [Percentage](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1870 LegPaymentScheduleStepOffsetValue**

The explicit amount that the notional changes on each step date. This can be a positive or negative amount.

Type: [Amt](#)

Used in groups: [LegPaymentScheduleGrp](#)

#### **180.2.1871 LegPaymentScheduleStepRate**

The percentage by which the notional changes on each step date. The percentage is either a percentage applied to the initial notional amount or the previous outstanding notional, depending on the value specified in [LegPaymentScheduleStepRelativeTo\(40395\)](#). The percentage can be either positive or negative.

Type: [Percentage](#)

Used in groups: [LegPaymentScheduleGrp](#)

**180.2.1872 LegPaymentScheduleStepRelativeTo**

Specifies whether the LegPaymentScheduleStepRate(40393) or LegPaymentScheduleStepOffsetValue(40392) should be applied to the initial notional or the previous notional in order to calculate the notional step change amount.

Type: **int**

Allowed values in PaymentScheduleStepRelativeToCodeSet:

Code	Name	Description
0	Initial	Initial
1	Previous	Previous

Used in groups: **LegPaymentScheduleGrp**

**180.2.1873 LegPaymentScheduleStepUnitOfMeasure**

The schedule step unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)

Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter

Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [LegPaymentScheduleGrp](#)

### 180.2.1874 LegPaymentScheduleStubType

Indicates to which stub this schedule applies.

Type: [int](#)

Allowed values in PaymentStubTypeCodeSet:

Code	Name	Description
0	Initial	Initial
1	Final	Final
2	CompoundingInitial	Compounding initial
3	CompoundingFinal	Compounding final

Used in groups: [LegPaymentScheduleGrp](#)

### 180.2.1875 LegPaymentScheduleType

Specifies the type of schedule.

Type: [int](#)

Allowed values in PaymentScheduleTypeCodeSet:

Code	Name	Description
0	Notional	Notional
1	CashFlow	Cash flow
2	FXLinkedNotional	FX linked notional
3	FixedRate	Fixed rate



Code	Name	Description
4	FutureValueNotional	Future value notional
5	KnownAmount	Known amount
6	FloatingRateMultiplier	Floating rate multiplier
7	Spread	Spread
8	CapRate	Cap rate
9	FloorRate	Floor rate
10	NonDeliverableSettlPaymentDates	Non-deliverable settlement payment dates
11	NonDeliverableSettlCalculation-Dates	Non-deliverable settlement calculation dates
12	NonDeliverableFXFixingDates	Non-deliverable fixing dates.
13	SettlPeriodNotnl	Settlement period notional
14	SettlPeriodPx	Settlement period price
15	CalcPeriod	Calculation period
16	DividendAccrualRateMultiplier	Dividend accrual rate multiplier
17	DividendAccrualRateSpread	Dividend accrual rate spread
18	DividendAccrualCapRate	Dividend accrual cap rate
19	DividendAccrualFloorRate	Dividend accrual floor rate
20	CompoundingRateMultiplier	Compounding rate multiplier
21	CompoundingRateSpread	Compounding rate spread
22	CompoundingCapRate	Compounding cap rate
23	CompoundingFloorRate	Compounding floor rate

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1876 LegPaymentScheduleWeight**

Floating rate observation weight for cashflow payment.

Type: **float**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1877 LegPaymentScheduleXID**

Identifier of this LegPaymentSchedule for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1878 LegPaymentScheduleXIDRef**

Reference to payment schedule elsewhere in the message.

Type: **XIDREF**

Used in groups: **LegPaymentScheduleGrp**

#### **180.2.1879 LegPaymentStreamAccrualDays**

The number of days from the adjusted calculation period start date to the adjusted value date, calculated in accordance with the applicable day count fraction.

Type: **int**

Used in components: **LegPaymentStream**

#### **180.2.1880 LegPaymentStreamAveragingMethod**

When averaging is applicable, used to specify whether a weighted or unweighted average method of calculation is to be used.

Type: **int**

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: **LegPaymentStreamFloatingRate**

#### **180.2.1881 LegPaymentStreamBoundsFirstDateUnadjusted**

The unadjusted first date of the compounding schedule. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in components: [LegPaymentStreamCompoundingDates](#)

#### **180.2.1882 LegPaymentStreamBoundsLastDateUnadjusted**

The unadjusted last date of the compounding schedule. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in components: [LegPaymentStreamCompoundingDates](#)

#### **180.2.1883 LegPaymentStreamCalculationLagPeriod**

Time unit multiplier for the calculation lag duration.

Type: [int](#)

Used in components: [LegPaymentStreamFloatingRate](#)

#### **180.2.1884 LegPaymentStreamCalculationLagUnit**

Time unit associated with the calculation lag duration.

Type: [String](#)

Allowed values in PaymentStreamInflationLagUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.1885 LegPaymentStreamCapRate**

The cap rate, if any, which applies to the floating rate. It is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1886 LegPaymentStreamCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1887 LegPaymentStreamCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1888 LegPaymentStreamCashSettlIndicator**

Indicates whether cash settlement is applicable.

Type: **Boolean**

Used in components: **LegPaymentStream**

**180.2.1889 LegPaymentStream**

The LegPaymentStream component is a subcomponent of the LegStreamGrp used to detail the attributes of a payment stream in a swap.

Name	Mult.	Type	Description
LegPaymentStreamType	[0..1]	CodeSet	
LegPaymentStreamMarketRate	[0..1]	int	
LegPaymentStreamDelayIndicator	[0..1]	Boolean	
LegPaymentStreamCashSettlIndicator	[0..1]	Boolean	
LegPaymentStreamSettlCurrency	[0..1]	Currency	
LegPaymentStreamDayCount	[0..1]	CodeSet	
LegPaymentStreamOtherDayCount	[0..1]	String	May be used to specify a count method not listed in LegPaymentStreamDayCount(40283).
LegPaymentStreamAccrualDays	[0..1]	int	
LegPaymentStreamDiscountType	[0..1]	CodeSet	
LegPaymentStreamDiscountRate	[0..1]	Percentage	
LegPaymentStreamDiscountRateDay-Count	[0..1]	CodeSet	
LegPaymentStreamCompounding-Method	[0..1]	CodeSet	
LegPaymentStreamCompoundingX-IDRef	[0..1]	XIDREF	Mutually exclusive with LegPaymentStreamCompoundingFixedRate(42404) or the LegPaymentStreamCompoundingFloatingRate component.
LegPaymentStreamCompoundingSpread	[0..1]	PriceOffset	
LegPaymentStreamInterpolation-Method	[0..1]	CodeSet	
LegPaymentStreamInterpolationPeriod	[0..1]	CodeSet	

Name	Mult.	Type	Description
LegPaymentStreamInitialPrincipalExchangeIndicator	[0..1]	Boolean	
LegPaymentStreamInterimPrincipalExchangeIndicator	[0..1]	Boolean	
LegPaymentStreamFinalPrincipalExchangeIndicator	[0..1]	Boolean	
LegPaymentStreamFlatRateIndicator	[0..1]	Boolean	
LegPaymentStreamFlatRateAmount	[0..1]	Amt	
LegPaymentStreamFlatRateCurrency	[0..1]	Currency	
LegStreamMaximumPaymentAmount	[0..1]	Amt	
LegStreamMaximumPaymentCurrency	[0..1]	Currency	
LegStreamMaximumTransactionAmount	[0..1]	Amt	
LegStreamMaximumTransactionCurrency	[0..1]	Currency	
LegPaymentStreamPaymentDates	[0..1]	Component	
LegPaymentStreamResetDates	[0..1]	Component	
LegPaymentStreamFixedRate	[0..1]	Component	
LegPaymentStreamFloatingRate	[0..1]	Component	
LegPaymentStreamCompoundingFixedRate	[0..1]	float	Mutually exclusive with LegPaymentStreamCompoundingXIDRef(42400) or the LegPaymentStreamCompoundingFloatingRate component.
LegPaymentStreamCompoundingFloatingRate	[0..1]	Component	Mutually exclusive with LegPaymentStreamCompoundingFixedRate(42404) or the LegPaymentStreamCompoundingXIDRef(42400).
LegPaymentStreamCompoundingDates	[0..1]	Component	
LegPaymentStreamNonDeliverableSettlementTerms	[0..1]	Component	

Used in groups: **LegStreamGrp**

**180.2.1890 LegPaymentStreamCompoundingAveragingMethod**

Specifies the averaging method when compounding floating rate averaging is applicable (e.g. weighted or unweighted).

Type: **int**

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1891 LegPaymentStreamCompoundingCapRate**

The cap rate, if any, which applies to the compounding floating rate. It is only required where the compounding floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1892 LegPaymentStreamCompoundingCapRateBuySide**

Reference to the buyer of the compounding cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1893 LegPaymentStreamCompoundingCapRateSellSide**

Reference to the seller of the compounding cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1894 LegPaymentStreamCompoundingDate**

The compounding date. Type of date is specified in LegPaymentStreamCompoundingDateType(42407).

Type: **LocalMktDate**

Used in groups: **LegPaymentStreamCompoundingDateGrp**

**180.2.1895 LegPaymentStreamCompoundingDateGrp**

LegPaymentStreamCompoundingDateGrp is a subcomponent of the LegPaymentStreamCompoundingDates component used to specify predetermined compounding dates.

Name	Mult.	Type	Description
<b>NoLegPaymentStreamCompoundingDates</b>	[1..1]	NumInGroup	
<b>LegPaymentStreamCompoundingDate</b>	[0..1]	LocalMktDate	Required if NoLegPaymentStreamCompoundingDates(42405) > 0.
<b>LegPaymentStreamCompoundingDateType</b>	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in components: **LegPaymentStreamCompoundingDates**



**180.2.1896 LegPaymentStreamCompoundingDatesBusinessCenter**

The business center calendar used for date adjustment of the payment stream compounding dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentStreamCompoundingDatesBusinessCenterGrp**

**180.2.1897 LegPaymentStreamCompoundingDatesBusinessCenterGrp**

LegPaymentStreamCompoundingDatesBusinessCenterGrp is a repeating subcomponent within the LegPaymentStreamCompoundingDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPaymentStreamCompounding-DatesBusinessCenters	[1..1]	NumInGroup	
LegPaymentStreamCompounding-DatesBusinessCenter	[0..1]	String	Required if NoLegPaymentStreamCompounding-DatesBusinessCenters(42419) > 0.

Used in components: **LegPaymentStreamCompoundingDates**

**180.2.1898 LegPaymentStreamCompoundingDatesBusinessDayConvention**

The compounding dates business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.

Code	Name	Description
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegPaymentStreamCompoundingDates](#)

### 180.2.1899 LegPaymentStreamCompoundingDates

LegPaymentStreamCompoundingDates is a subcomponent of the LegPaymentStream component used to specify the compounding dates of the stream - either specific, relative or periodic dates.

Name	Mult.	Type	Description
<a href="#">LegPaymentStreamCompounding-DatesBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to payment stream compounding dates.
<a href="#">LegPaymentStreamCompounding-DatesBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to payment stream compounding dates.
<a href="#">LegPaymentStreamCompounding-DateGrp</a>	[0..*]	Group	
<a href="#">LegPaymentStreamCompounding-DatesRelativeTo</a>	[0..1]	int	
<a href="#">LegPaymentStreamCompounding-DatesOffsetPeriod</a>	[0..1]	int	Conditionally required when LegPaymentStream-CompoundingDatesOffsetUnit(42411) is specified.
<a href="#">LegPaymentStreamCompounding-DatesOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegPaymentStream-CompoundingDatesOffsetPeriod(42410) is specified.
<a href="#">LegPaymentStreamCompounding-DatesOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">LegPaymentStreamCompoundingPeriodSkip</a>	[0..1]	int	

Name	Mult.	Type	Description
LegPaymentStreamCompoundingStartDate	[0..1]	Component	
LegPaymentStreamCompoundingEndDate	[0..1]	Component	
LegPaymentStreamCompoundingFrequencyPeriod	[0..1]	int	Conditionally required when LegPaymentStreamCompoundingFrequencyUnit(42415) is specified.
LegPaymentStreamCompoundingFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamCompoundingFrequencyPeriod(42414) is specified.
LegPaymentStreamCompoundingRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of payment stream compounding dates.
LegPaymentStreamBoundsFirstDateUnadjusted	[0..1]	LocalMktDate	
LegPaymentStreamBoundsLastDateUnadjusted	[0..1]	LocalMktDate	

Used in components: [LegPaymentStream](#)

### 180.2.1900 LegPaymentStreamCompoundingDatesOffsetDayType

Specifies the day type of the relative compounding date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegPaymentStreamCompoundingDates](#)

**180.2.1901 LegPaymentStreamCompoundingDatesOffsetPeriod**

Time unit multiplier for the relative compounding date offset.

Type: **int**

Used in components: **LegPaymentStreamCompoundingDates**

**180.2.1902 LegPaymentStreamCompoundingDatesOffsetUnit**

Time unit associated with the relative compounding date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamCompoundingDates**

**180.2.1903 LegPaymentStreamCompoundingDatesRelativeTo**

Specifies the anchor date when the compounding dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamCompoundingDates**

**180.2.1904 LegPaymentStreamCompoundingDateType**

Specifies the type of payment compounding date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [LegPaymentStreamCompoundingDateGrp](#)

### 180.2.1905 LegPaymentStreamCompoundingEndDateAdjusted

The adjusted compounding end date.

Type: [LocalMktDate](#)

Used in components: [LegPaymentStreamCompoundingEndDate](#)

### 180.2.1906 LegPaymentStreamCompoundingEndDate

LegPaymentStreamCompoundingEndDate is a subcomponent of the LegPaymentStreamCompoundingDates component used to specify the end date for compounding.

Name	Mult.	Type	Description
<a href="#">LegPaymentStreamCompoundingEndDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegPaymentStreamCompoundingEndDateRelativeTo</a>	[0..1]	int	
<a href="#">LegPaymentStreamCompoundingEndDateOffsetPeriod</a>	[0..1]	int	Conditionally required when LegPaymentStreamCompoundingEndDateOffsetUnit(42424) is specified.
<a href="#">LegPaymentStreamCompoundingEndDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegPaymentStreamCompoundingEndDateOffsetPeriod(42423) is specified.
<a href="#">LegPaymentStreamCompoundingEndDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">LegPaymentStreamCompoundingEndDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [LegPaymentStreamCompoundingDates](#)

**180.2.1907 LegPaymentStreamCompoundingEndDateOffsetDayType**

Specifies the day type of the relative compounding end date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegPaymentStreamCompoundingEndDate**

**180.2.1908 LegPaymentStreamCompoundingEndDateOffsetPeriod**

Time unit multiplier for the relative compounding end date offset.

Type: **int**

Used in components: **LegPaymentStreamCompoundingEndDate**

**180.2.1909 LegPaymentStreamCompoundingEndDateOffsetUnit**

Time unit associated with the relative compounding end date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamCompoundingEndDate**

**180.2.1910 LegPaymentStreamCompoundingEndDateRelativeTo**

Specifies the anchor date when the compounding end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamCompoundingEndDate**

**180.2.1911 LegPaymentStreamCompoundingEndDateUnadjusted**

The unadjusted compounding end date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamCompoundingEndDate**

**180.2.1912 LegPaymentStreamCompoundingFinalRatePrecision**

Specifies the compounding floating rate rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1913 LegPaymentStreamCompoundingFinalRateRoundingDirection**

Specifies the rounding direction for the compounding floating rate.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1914 LegPaymentStreamCompoundingFixedRate**

The compounding fixed rate applicable to the payment stream.

Type: **float**

Used in components: **LegPaymentStream**

**180.2.1915 LegPaymentStreamCompoundingFloatingRate**

LegPaymentStreamCompoundingFloatingRate is a subcomponent of the LegPaymentStream component used to report the parameters for determining the compounding floating rate of the stream.

Name	Mult.	Type	Description
LegPaymentStreamCompoundingRateIndex	[0..1]	String	
LegPaymentStreamCompoundingRateIndexCurvePeriod	[0..1]	int	Conditionally required if LegPaymentStreamCompoundingRateIndexCurveUnit(42429) is specified.
LegPaymentStreamCompoundingRateIndexCurveUnit	[0..1]	CodeSet	Conditionally required if LegPaymentStreamCompoundingRateIndexCurvePeriod(42428) is specified.
LegPaymentStreamCompoundingRateMultiplier	[0..1]	float	
LegPaymentStreamCompoundingRateSpread	[0..1]	PriceOffset	
LegPaymentStreamCompoundingRateSpreadPositionType	[0..1]	CodeSet	
LegPaymentStreamCompoundingRateTreatment	[0..1]	CodeSet	
LegPaymentStreamCompoundingCapRate	[0..1]	Percentage	
LegPaymentStreamCompoundingCapRateBuySide	[0..1]	CodeSet	
LegPaymentStreamCompoundingCapRateSellSide	[0..1]	CodeSet	
LegPaymentStreamCompoundingFloorRate	[0..1]	Percentage	
LegPaymentStreamCompoundingFloorRateBuySide	[0..1]	CodeSet	
LegPaymentStreamCompoundingFloorRateSellSide	[0..1]	CodeSet	



Name	Mult.	Type	Description
LegPaymentStreamCompoundingInitialRate	[0..1]	Percentage	
LegPaymentStreamCompoundingFinalRateRoundingDirection	[0..1]	CodeSet	
LegPaymentStreamCompoundingFinalRatePrecision	[0..1]	int	
LegPaymentStreamCompoundingAveragingMethod	[0..1]	CodeSet	
LegPaymentStreamCompoundingNegativeRateTreatment	[0..1]	CodeSet	

Used in components: [LegPaymentStream](#)

#### 180.2.1916 LegPaymentStreamCompoundingFloorRate

The floor rate, if any, which applies to the compounding floating rate. The floor rate (strike) is only required where the compounding floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate. The rate is expressed as a decimal, e.g. 5% is represented as "0.05".

Type: [Percentage](#)

Used in components: [LegPaymentStreamCompoundingFloatingRate](#)

#### 180.2.1917 LegPaymentStreamCompoundingFloorRateBuySide

Reference to the buyer of the compounding floor rate option through its trade side.

Type: [int](#)

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [LegPaymentStreamCompoundingFloatingRate](#)

**180.2.1918 LegPaymentStreamCompoundingFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1919 LegPaymentStreamCompoundingFrequencyPeriod**

Time unit multiplier for the frequency at which compounding dates occur.

Type: **int**

Used in components: **LegPaymentStreamCompoundingDates**

**180.2.1920 LegPaymentStreamCompoundingFrequencyUnit**

Time unit associated with the frequency at which compounding dates occur.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: **LegPaymentStreamCompoundingDates**

**180.2.1921 LegPaymentStreamCompoundingInitialRate**

The initial compounding floating rate reset agreed between the principal parties involved in the trade. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. The initial rate is expressed in decimal form, e.g. 5% is represented as "0.05".

Type: **Percentage**

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1922 LegPaymentStreamCompoundingMethod**

Compounding method.

Type: **int**

Allowed values in PaymentStreamCompoundingMethodCodeSet:

Code	Name	Description
0	None	None
1	Flat	Flat
2	Straight	Straight
3	SpreadExclusive	Spread exclusive

Used in components: **LegPaymentStream**

**180.2.1923 LegPaymentStreamCompoundingNegativeRateTreatment**

Specifies the method for calculating payment obligations when a compounding floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1924 LegPaymentStreamCompoundingPeriodSkip**

The number of periods in the "RelativeTo" schedule that are between each date in the compounding schedule. A skip of 2 would mean that compounding dates are relative to every second date in the "RelativeTo" schedule. If present this should have a value greater than 1.

Type: **int**

Used in components: **LegPaymentStreamCompoundingDates**

**180.2.1925 LegPaymentStreamCompoundingRateIndex**

The payment stream's compounding floating rate index.

Type: **String**

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1926 LegPaymentStreamCompoundingRateIndexCurvePeriod**

Time unit multiplier for the payment stream's compounding floating rate index curve period.

Type: **int**

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1927 LegPaymentStreamCompoundingRateIndexCurveUnit**

Time unit associated with the payment stream's compounding floating rate index curve period.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1928 LegPaymentStreamCompoundingRateMultiplier**

A rate multiplier to apply to the compounding floating rate. The multiplier can be less than or greater than 1 (one). This should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: **float**

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1929 LegPaymentStreamCompoundingRateSpread**

The basis points spread from the index specified in LegPaymentStreamCompoundingRateIndex(42427).

Type: **PriceOffset**

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1930 LegPaymentStreamCompoundingRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: **LegPaymentStreamCompoundingFloatingRate**

**180.2.1931 LegPaymentStreamCompoundingRateTreatment**

Specifies the yield calculation treatment for the index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: [LegPaymentStreamCompoundingFloatingRate](#)

### 180.2.1932 LegPaymentStreamCompoundingRollConvention

The convention for determining the sequence of compounding dates. It is used in conjunction with a specified frequency.

Type: [String](#)

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelfthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	FourteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month

Code	Name	Description
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighthDay	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [LegPaymentStreamCompoundingDates](#)

**180.2.1933 LegPaymentStreamCompoundingSpread**

The spread to be used for compounding. Used in scenarios where the interest payment is based on a compounding formula that uses a compounding spread in addition to the regular spread.

Type: **PriceOffset**

Used in components: **LegPaymentStream**

**180.2.1934 LegPaymentStreamCompoundingStartDateAdjusted**

The adjusted compounding start date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamCompoundingStartDate**

**180.2.1935 LegPaymentStreamCompoundingStartDate**

LegPaymentStreamCompoundingStartDate is a subcomponent of the LegPaymentStreamCompoundingDates component used to specify the start date for compounding.

Name	Mult.	Type	Description
LegPaymentStreamCompoundingStartDateUnadjusted	[0..1]	LocalMktDate	
LegPaymentStreamCompoundingStartDateRelativeTo	[0..1]	int	
LegPaymentStreamCompoundingStartDateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentStreamCompoundingStartDateOffsetUnit(42448) is specified.
LegPaymentStreamCompoundingStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamCompoundingStartDateOffsetPeriod(42447) is specified.
LegPaymentStreamCompoundingStartDateOffsetDayType	[0..1]	CodeSet	
LegPaymentStreamCompoundingStartDateAdjusted	[0..1]	LocalMktDate	

Used in components: **LegPaymentStreamCompoundingDates**



**180.2.1936 LegPaymentStreamCompoundingStartDateOffsetDayType**

Specifies the day type of the relative compounding start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegPaymentStreamCompoundingStartDate**

**180.2.1937 LegPaymentStreamCompoundingStartDateOffsetPeriod**

Time unit multiplier for the relative compounding start date offset.

Type: **int**

Used in components: **LegPaymentStreamCompoundingStartDate**

**180.2.1938 LegPaymentStreamCompoundingStartDateOffsetUnit**

Time unit associated with the relative compounding start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamCompoundingStartDate**

**180.2.1939 LegPaymentStreamCompoundingStartDateRelativeTo**

Specifies the anchor date when the compounding start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamCompoundingStartDate**

**180.2.1940 LegPaymentStreamCompoundingStartDateUnadjusted**

The unadjusted compounding start date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamCompoundingStartDate**

**180.2.1941 LegPaymentStreamCompoundingXIDRef**

Reference to the stream which details the compounding fixed or floating rate.

Type: **XIDREF**

Used in components: **LegPaymentStream**

**180.2.1942 LegPaymentStreamContractPrice**

The price per relevant unit for purposes of the calculation of a fixed amount for a dry voyage charter or time charter commodity swap.

Type: **Price**

Used in components: **LegPaymentStreamFixedRate**

**180.2.1943 LegPaymentStreamContractPriceCurrency**

Specifies the currency of LegPaymentStreamContractPrice(41559). Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegPaymentStreamFixedRate**

**180.2.1944 LegPaymentStreamDayCount**

The day count convention used in the payment stream calculations.

Type: **int**

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.

Code	Name	Description
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.

Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: **LegPaymentStream**

#### 180.2.1945 LegPaymentStreamDaysAdjustmentIndicator

Indicates whether the contract specifies that the notional should be scaled by the number of days in range divided by the estimate trading days or not. The number of "days in range" refers to the number of returns that contribute to the realized volatility.

Type: **Boolean**

Used in components: **LegPaymentStreamFloatingRate**

#### **180.2.1946 LegPaymentStreamDelayIndicator**

Applicable to credit default swaps on mortgage backed securities to specify whether payment delays are applicable to the fixed amount.

Residential mortgage backed securities typically have a payment delay of 5 days between the coupon date of the reference obligation and the payment date of the synthetic swap.

Commercial mortgage backed securities do not typically have a payment delay, with both payment dates (the coupon date of the reference obligation and the payment date of the synthetic swap) being on the 25th of each month.

Type: **Boolean**

Used in components: **LegPaymentStream**

#### **180.2.1947 LegPaymentStreamDiscountRate**

Discount rate. The rate is expressed in decimal, e.g. 5% is expressed as 0.05.

Type: **Percentage**

Used in components: **LegPaymentStream**

#### **180.2.1948 LegPaymentStreamDiscountRateDayCount**

The day count convention applied to the LegPaymentStreamDiscountRate(40286).

Type: **int**

Allowed values in CouponDayCountCodeSet:

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).

---

Code	Name	Description
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.

Code	Name	Description
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.



Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: [LegPaymentStream](#)

### 180.2.1949 LegPaymentStreamDiscountType

The method of calculating discounted payment amounts.

Type: [int](#)

Allowed values in PaymentStreamDiscountTypeCodeSet:

Code	Name	Description
0	Standard	Standard
1	FRA	Forward Rate Agreement (FRA)

Used in components: [LegPaymentStream](#)

### 180.2.1950 LegPaymentStreamFinalPricePaymentDateAdjusted

The adjusted final price payment date.

Type: [LocalMktDate](#)

Used in components: [LegPaymentStreamFinalPricePaymentDate](#)

### 180.2.1951 LegPaymentStreamFinalPricePaymentDate

LegPaymentStreamFinalPricePaymentDate is a subcomponent of the LegPaymentStreamPaymentDates component used to specify the final price payment date, e.g. for an equity return swap.

Name	Mult.	Type	Description
<a href="#">LegPaymentStreamFinalPricePaymentDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegPaymentStreamFinalPricePaymentDateRelativeTo</a>	[0..1]	int	
<a href="#">LegPaymentStreamFinalPricePaymentDateOffsetPeriod</a>	[0..1]	int	Conditionally required when LegPaymentStreamFinalPricePaymentDateOffsetUnit(42456) is specified.
<a href="#">LegPaymentStreamFinalPricePaymentDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegPaymentStreamFinalPricePaymentDateOffsetPeriod(42455) is specified.
<a href="#">LegPaymentStreamFinalPricePaymentDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">LegPaymentStreamFinalPricePaymentDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [LegPaymentStreamPaymentDates](#)

**180.2.1952 LegPaymentStreamFinalPricePaymentDateOffsetDayType**

Specifies the day type of the relative final price payment date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegPaymentStreamFinalPricePaymentDate**

**180.2.1953 LegPaymentStreamFinalPricePaymentDateOffsetPeriod**

Time unit multiplier for the relative final price payment date offset.

Type: **int**

Used in components: **LegPaymentStreamFinalPricePaymentDate**

**180.2.1954 LegPaymentStreamFinalPricePaymentDateOffsetUnit**

Time unit associated with the relative final price payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamFinalPricePaymentDate**

**180.2.1955 LegPaymentStreamFinalPricePaymentDateRelativeTo**

Specifies the anchor date when the final price payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamFinalPricePaymentDate**

**180.2.1956 LegPaymentStreamFinalPricePaymentDateUnadjusted**

The unadjusted final price payment date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamFinalPricePaymentDate**

**180.2.1957 LegPaymentStreamFinalPrincipalExchangeIndicator**

Indicates whether there is a final exchange of principal on the termination date.

Type: **Boolean**

Used in components: **LegPaymentStream**

**180.2.1958 LegPaymentStreamFinalRate**

The floating rate determined at the final reset. The rate is expressed in decimal form, e.g. 5% is represented as 0.05.

Type: **Percentage**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1959 LegPaymentStreamFinalRatePrecision**

Specifies the rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1960 LegPaymentStreamFinalRateRoundingDirection**

Specifies the rounding direction.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1961 LegPaymentStreamFirstObservationDateAdjusted**

The adjusted initial price observation date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1962 LegPaymentStreamFirstObservationDateOffsetDayType**

Specifies the day type of the initial price observation date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1963 LegPaymentStreamFirstObservationDateOffsetPeriod**

Time unit multiplier for the relative first observation date offset.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1964 LegPaymentStreamFirstObservationDateOffsetUnit**

Time unit associated with the relative first observation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1965 LegPaymentStreamFirstObservationDateRelativeTo**

Specifies the anchor date when the initial price observation date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1966 LegPaymentStreamFirstObservationDateUnadjusted**

The unadjusted initial price observation date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1967 LegPaymentStreamFirstPaymentDateUnadjusted**

The unadjusted first payment date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamPaymentDates**

**180.2.1968 LegPaymentStreamFixedAmount**

The leg instrument payment stream's fixed payment amount. In a CDS, this can be an alternative to LegPaymentStreamRate(40326).

Type: **Amt**

Used in components: **LegPaymentStreamFixedRate**

**180.2.1969 LegPaymentStreamFixedAmountUnitOfMeasure**

The fixed payment amount unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.

Code	Name	Description
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces



Code	Name	Description
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard

Code	Name	Description
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [LegPaymentStreamFixedRate](#)

### 180.2.1970 LegPaymentStreamFixedRate

LegPaymentStreamFixedRate is a subcomponent of the LegPaymentStream component used to report the fixed rate or fixed payment amount of the payment stream.

Name	Mult.	Type	Description
<a href="#">LegPaymentStreamRate</a>	[0..1]	Percentage	Mutually exclusive with LegPaymentStreamFixedAmount(40327).
<a href="#">LegPaymentStreamFixedAmount</a>	[0..1]	Amt	Mutually exclusive with LegPaymentStreamRate(40326).
<a href="#">LegPaymentStreamRateOrAmountCurrency</a>	[0..1]	Currency	
<a href="#">LegPaymentStreamFixedAmountUnitOfMeasure</a>	[0..1]	CodeSet	
<a href="#">LegPaymentStreamTotalFixedAmount</a>	[0..1]	Amt	
<a href="#">LegPaymentStreamFutureValueNotional</a>	[0..1]	Amt	
<a href="#">LegPaymentStreamFutureValueDateAdjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegPaymentStreamWorldScaleRate</a>	[0..1]	float	
<a href="#">LegPaymentStreamContractPrice</a>	[0..1]	Price	
<a href="#">LegPaymentStreamContractPriceCurrency</a>	[0..1]	Currency	

Used in components: [LegPaymentStream](#)

### 180.2.1971 LegPaymentStreamFixingDate

The fixing date. Type of date is specified in LegPaymentStreamFixingDateType(42461).

Type: [LocalMktDate](#)

Used in groups: [LegPaymentStreamFixingDateGrp](#)

### **180.2.1972 LegPaymentStreamFixingDateAdjusted**

The adjusted fixing date.

Type: [LocalMktDate](#)

Used in components: [LegPaymentStreamResetDates](#)

### **180.2.1973 LegPaymentStreamFixingDateBusinessCenter**

The business center calendar used to adjust the payment stream's fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [LegPaymentStreamFixingDateBusinessCenterGrp](#)

### **180.2.1974 LegPaymentStreamFixingDateBusinessCenterGrp**

LegPaymentStreamFixingDateBusinessCenterGrp is a repeating subcomponent within the LegPaymentStreamResetDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
<a href="#">NoLegPaymentStreamFixingDateBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">LegPaymentStreamFixingDateBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoLegPaymentStreamFixingDateBusinessCenters</a> (40933) > 0.

Used in components: [LegPaymentStreamResetDates](#)

### **180.2.1975 LegPaymentStreamFixingDateBusinessDayConvention**

The business day convention used to adjust the payment stream's fixing date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **LegPaymentStreamResetDates**

#### 180.2.1976 LegPaymentStreamFixingDateGrp

LegPaymentStreamFixingDateGrp is a subcomponent of the LegPaymentStreamResetDates component used to specify predetermined fixing dates.

Name	Mult.	Type	Description
<b>NoLegPaymentStreamFixingDates</b>	[1..1]	NumInGroup	
<b>LegPaymentStreamFixingDate</b>	[0..1]	LocalMktDate	Required if NoLegPaymentStreamFixingDates(42459) > 0.
<b>LegPaymentStreamFixingDateType</b>	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in components: **LegPaymentStreamResetDates**

#### 180.2.1977 LegPaymentStreamFixingDateOffsetDayType

Specifies the day type of the relative fixing date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegPaymentStreamResetDates](#)

#### **180.2.1978 LegPaymentStreamFixingDateOffsetPeriod**

Time unit multiplier for the relative fixing date offset.

Type: [int](#)

Used in components: [LegPaymentStreamResetDates](#)

#### **180.2.1979 LegPaymentStreamFixingDateOffsetUnit**

Time unit associated with the relative fixing date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegPaymentStreamResetDates](#)

**180.2.1980 LegPaymentStreamFixingDateRelativeTo**

Specifies the anchor date when the fixing date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamResetDates**

**180.2.1981 LegPaymentStreamFixingDateType**

Specifies the type of fixing date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **LegPaymentStreamFixingDateGrp**

**180.2.1982 LegPaymentStreamFlatRateAmount**

Specifies the actual monetary value of the flat rate when LegPaymentStreamFlatRateIndicator(41549) = 'Y'.

Type: **Amt**

Used in components: **LegPaymentStream**

**180.2.1983 LegPaymentStreamFlatRateCurrency**

Specifies the currency of the actual flat rate. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegPaymentStream**

**180.2.1984 LegPaymentStreamFlatRateIndicator**

When this element is specified and set to 'Y', the Flat Rate is the New Worldwide Tanker Nominal Freight Scale for the Freight Index Route taken at the trade date of the transaction "Fixed". If 'N' it is taken on each pricing date "Floating".

Type: **Boolean**

Used in components: **LegPaymentStream**

**180.2.1985 LegPaymentStreamFloatingRate**

LegPaymentStreamFloatingRate is a subcomponent of the LegPaymentStream component used to report the floating rate attributes of the payment stream.

Name	Mult.	Type	Description
LegPaymentStreamRateIndex	[0..1]	String	
LegPaymentStreamRateIndexSource	[0..1]	CodeSet	
LegPaymentStreamRateIndexID	[0..1]	String	Conditionally required when LegPaymentStreamRateIndexIDSource(43089) is specified.
LegPaymentStreamRateIndexIDSource	[0..1]	CodeSet	Conditionally required when LegPaymentStreamRateIndexID(43088) is specified.
LegPaymentStreamRateIndexCurveUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamRateIndexCurvePeriod(40334) is specified.
LegPaymentStreamRateIndexCurvePeriod	[0..1]	int	Conditionally required when LegPaymentStreamRateIndexCurveUnit(40333) is specified.
LegPaymentStreamRateIndex2	[0..1]	String	
LegPaymentStreamRateIndex2Source	[0..1]	CodeSet	
LegPaymentStreamRateIndex2ID	[0..1]	String	Conditionally required when LegPaymentStreamRateIndex2IDSource(43119) is specified.
LegPaymentStreamRateIndex2IDSource	[0..1]	CodeSet	Conditionally required when LegPaymentStreamRateIndex2ID(43118) is specified.
LegPaymentStreamRateIndex2CurveUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamRateIndex2CurvePeriod(41564) is specified.

Name	Mult.	Type	Description
LegPaymentStreamRateIndex2CurvePeriod	[0..1]	int	Conditionally required when LegPaymentStreamRateIndex2CurveUnit(41563) is specified.
LegPaymentStreamRateIndexLocation	[0..1]	String	
LegPaymentStreamRateIndexLevel	[0..1]	Qty	
LegPaymentStreamRateIndexUnitOfMeasure	[0..1]	CodeSet	
LegPaymentStreamSettlLevel	[0..1]	CodeSet	
LegPaymentStreamReferenceLevel	[0..1]	Qty	
LegPaymentStreamReferenceLevelUnitOfMeasure	[0..1]	CodeSet	
LegPaymentStreamReferenceLevelEqualsZeroIndicator	[0..1]	Boolean	
LegPaymentStreamRateMultiplier	[0..1]	float	
LegPaymentStreamRateSpread	[0..1]	PriceOffset	
LegPaymentStreamRateSpreadCurrency	[0..1]	Currency	
LegPaymentStreamRateSpreadUnitOfMeasure	[0..1]	CodeSet	
LegPaymentStreamRateConversionFactor	[0..1]	float	
LegPaymentStreamRateSpreadType	[0..1]	CodeSet	
LegPaymentStreamRateSpreadPositionType	[0..1]	CodeSet	
LegPaymentStreamRateTreatment	[0..1]	CodeSet	
LegPaymentStreamCapRate	[0..1]	Percentage	
LegPaymentStreamCapRateBuySide	[0..1]	CodeSet	
LegPaymentStreamCapRateSellSide	[0..1]	CodeSet	
LegPaymentStreamFloorRate	[0..1]	Percentage	
LegPaymentStreamFloorRateBuySide	[0..1]	CodeSet	
LegPaymentStreamFloorRateSellSide	[0..1]	CodeSet	
LegPaymentStreamInitialRate	[0..1]	Percentage	
LegPaymentStreamLastResetRate	[0..1]	Percentage	
LegPaymentStreamFinalRate	[0..1]	Percentage	
LegPaymentStreamFinalRateRoundingDirection	[0..1]	CodeSet	
LegPaymentStreamFinalRatePrecision	[0..1]	int	



Name	Mult.	Type	Description
LegPaymentStreamAveragingMethod	[0..1]	CodeSet	
LegPaymentStreamNegativeRateTreatment	[0..1]	CodeSet	
LegPaymentStreamCalculationLagPeriod	[0..1]	int	Conditionally required when LegPaymentStreamCalculationLagUnit(41579) is specified.
LegPaymentStreamCalculationLagUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamCalculationLagPeriod(41578) is specified.
LegPaymentStreamFirstObservation-DateUnadjusted	[0..1]	LocalMktDate	
LegPaymentStreamFirstObservation-DateRelativeTo	[0..1]	int	
LegPaymentStreamFirstObservation-DateOffsetDayType	[0..1]	CodeSet	
LegPaymentStreamFirstObservation-DateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentStream-FirstObservationOffsetUnit(41581) is specified.
LegPaymentStreamFirstObservation-DateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStream-FirstObservationOffsetPeriod(41580) is specified.
LegPaymentStreamFirstObservation-DateAdjusted	[0..1]	LocalMktDate	
LegPaymentStreamPricingDayType	[0..1]	CodeSet	
LegPaymentStreamPricingDayDistribution	[0..1]	CodeSet	
LegPaymentStreamPricingDayCount	[0..1]	int	
LegPaymentStreamPricingBusiness-Calendar	[0..1]	String	
LegPaymentStreamPricingBusiness-DayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to the payment stream pricing date.
LegPaymentStreamPricingBusiness-CenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to the the payment stream pricing date.
LegPaymentStreamPricingDayGrp	[0..*]	Group	
LegPaymentStreamPricingDateGrp	[0..*]	Group	

Name	Mult.	Type	Description
LegPaymentStreamInflationLagPeriod	[0..1]	int	Conditionally required when LegPaymentStreamInflationLagUnit(40351) is specified.
LegPaymentStreamInflationLagUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamInflationLagPeriod(40350) is specified.
LegPaymentStreamInflationLagDay-Type	[0..1]	CodeSet	
LegPaymentStreamInflationInterpolationMethod	[0..1]	CodeSet	
LegPaymentStreamInflationIndex-Source	[0..1]	CodeSet	
LegPaymentStreamInflationPublicationSource	[0..1]	String	
LegPaymentStreamInflationInitialIndexLevel	[0..1]	float	
LegPaymentStreamInflationFallbackBondApplicable	[0..1]	Boolean	
LegPaymentStreamFRADiscounting	[0..1]	CodeSet	
LegPaymentStreamUnderlierRefID	[0..1]	String	
LegPaymentStreamFormula	[0..1]	Component	
LegDividendConditions	[0..1]	Component	
LegReturnRateNotionalReset	[0..1]	Boolean	
LegReturnRateGrp	[0..*]	Group	
LegPaymentStreamLinkInitialLevel	[0..1]	Price	
LegPaymentStreamLinkClosingLevelIndicator	[0..1]	Boolean	
LegPaymentStreamLinkExpiringLevelIndicator	[0..1]	Boolean	
LegPaymentStreamLinkEstimatedTradingDays	[0..1]	int	
LegPaymentStreamLinkStrikePrice	[0..1]	Price	
LegPaymentStreamLinkStrikePrice-Type	[0..1]	CodeSet	
LegPaymentStreamLinkMaximumBoundary	[0..1]	float	
LegPaymentStreamLinkMinimumBoundary	[0..1]	float	

Name	Mult.	Type	Description
LegPaymentStreamLinkNumberOfDataSeries	[0..1]	int	
LegPaymentStreamVarianceUnadjustedCap	[0..1]	float	
LegPaymentStreamRealizedVarianceMethod	[0..1]	CodeSet	
LegPaymentStreamDaysAdjustmentIndicator	[0..1]	Boolean	
LegPaymentStreamNearestExchangeContractRefID	[0..1]	String	
LegPaymentStreamVegaNotionalAmount	[0..1]	float	

Used in components: [LegPaymentStream](#)

#### 180.2.1986 LegPaymentStreamFloorRate

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate. The rate is expressed as a decimal, e.g. 5% is represented as 0.05.

Type: [Percentage](#)

Used in components: [LegPaymentStreamFloatingRate](#)

#### 180.2.1987 LegPaymentStreamFloorRateBuySide

Reference to the buyer of the floor rate option through its trade side.

Type: [int](#)

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.1988 LegPaymentStreamFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1989 LegPaymentStreamFormula**

Contains an XML representation of the formula. Defined for flexibility in choice of language (MathML, OpenMath or text).

Type: **XMLData**

Used in groups: **LegPaymentStreamFormulaMathGrp**

**180.2.1990 LegPaymentStreamFormula**

LegPaymentStreamFormula is a subcomponent of the LegPaymentStreamFloatingRate component used to report the parameters for determining the floating rate of the stream e.g. for equity swaps.

Name	Mult.	Type	Description
<b>LegPaymentStreamFormulaCurrency</b>	[0..1]	Currency	
<b>LegPaymentStreamFormulaCurrency-DeterminationMethod</b>	[0..1]	String	
<b>LegPaymentStreamFormulaRefer-enceAmount</b>	[0..1]	int	
<b>LegPaymentStreamFormulaMathGrp</b>	[0..*]	Group	
<b>LegPaymentStreamFormulaImage</b>	[0..1]	Component	

Used in components: **LegPaymentStreamFloatingRate**

**180.2.1991 LegPaymentStreamFormulaCurrency**

The currency in which the formula amount is denominated. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegPaymentStreamFormula**

**180.2.1992 LegPaymentStreamFormulaCurrencyDeterminationMethod**

Specifies the method according to which the formula amount currency is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in components: **LegPaymentStreamFormula**

**180.2.1993 LegPaymentStreamFormulaDesc**

A description of the math formula in LegPaymentStreamFormula(42486).

Type: **String**

Used in groups: **LegPaymentStreamFormulaMathGrp**

**180.2.1994 LegPaymentStreamFormulaImage**

Image of the formula image when represented through an encoded clip in base64Binary.

Type: **data**

Used in components: **LegPaymentStreamFormulaImage**

**180.2.1995 LegPaymentStreamFormulaImage**

LegPaymentStreamFormulaImage is a subcomponent of the LegPaymentStreamFormula component used to include a base64Binary-encoded image clip of the formula.

Name	Mult.	Type	Description
<a href="#">LegPaymentStreamFormulalImageLength</a>	[0..1]	Length	Conditionally required when LegPaymentStreamFormulalImage(42452) is specified.
<a href="#">LegPaymentStreamFormulalImage</a>	[0..1]	data	Conditionally required when LegPaymentStreamFormulalImageLength(42451) is specified.

Used in components: [LegPaymentStreamFormula](#)

### 180.2.1996 [LegPaymentStreamFormulalImageLength](#)

Length in bytes of the LegPaymentStreamFormulalImage(42452) field.

Type: [Length](#)

Used in components: [LegPaymentStreamFormulalImage](#)

### 180.2.1997 [LegPaymentStreamFormulaLength](#)

Byte length of encoded (non-ASCII characters) LegPaymentStreamFormula(42486) field.

Type: [Length](#)

Used in groups: [LegPaymentStreamFormulaMathGrp](#)

### 180.2.1998 [LegPaymentStreamFormulaMathGrp](#)

LegPaymentStreamFormulaMathGrp is a repeating subcomponent within the LegPaymentStreamFormula component. It is used to specify the set of formulas, sub-formulas and descriptions from which the rate is derived.

Name	Mult.	Type	Description
<a href="#">NoLegPaymentStreamFormulas</a>	[1..1]	NumInGroup	
<a href="#">LegPaymentStreamFormulaLength</a>	[0..1]	Length	Required if NoLegPaymentStreamFormulas(42485) > 0.
<a href="#">LegPaymentStreamFormula</a>	[0..1]	XMLData	Required if NoLegPaymentStreamFormulas(42485) > 0.
<a href="#">LegPaymentStreamFormulaDesc</a>	[0..1]	String	

Used in components: [LegPaymentStreamFormula](#)

#### **180.2.1999 LegPaymentStreamFormulaReferenceAmount**

Specifies the reference amount when this term either corresponds to the standard ISDA Definition (either the 2002 Equity Definition for the Equity Amount, or the 2000 Definition for the Interest Amount), or refers to a term defined elsewhere in the swap document.

See [http://www.fixtradingcommunity.org/codelists#Payment\\_Amount\\_Relative\\_To](http://www.fixtradingcommunity.org/codelists#Payment_Amount_Relative_To) for code list of reference amounts.

Type: [int](#)

Used in components: [LegPaymentStreamFormula](#)

#### **180.2.2000 LegPaymentStreamFRADiscounting**

The method of Forward Rate Agreement (FRA) discounting, if any, that will apply.

Type: [int](#)

Allowed values in PaymentStreamFRADiscountingCodeSet:

Code	Name	Description
0	None	None
1	ISDA	International Swaps and Derivatives Association (ISDA)
2	AFMA	Australian Financial Markets Association (AFMA)

Used in components: [LegPaymentStreamFloatingRate](#)

#### **180.2.2001 LegPaymentStreamFutureValueDateAdjusted**

The adjusted value date of the future value amount.

Type: [LocalMktDate](#)

Used in components: [LegPaymentStreamFixedRate](#)

**180.2.2002 LegPaymentStreamFutureValueNotional**

The future value notional is normally only required for certain non-deliverable interest rate swaps (e.g. Brazilian Real (BRL) vs. CETIP Interbank Deposit Rate (CDI)). The value is calculated as follows: Future Value Notional = Notional Amount \* (1 + Fixed Rate) ^ (Fixed Rate Day Count Fraction). The currency is the same as the stream notional.

Type: **Amt**

Used in components: **LegPaymentStreamFixedRate**

**180.2.2003 LegPaymentStreamInflationFallbackBondApplicable**

Indicates whether a fallback bond as defined in the 2006 ISDA Inflation Derivatives Definitions, sections 1.3 and 1.8, is applicable or not. If not specified, the default value is "Y" (True/Yes).

Type: **Boolean**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2004 LegPaymentStreamInflationIndexSource**

The inflation index reference source.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2005 LegPaymentStreamInflationInitialIndexLevel**

Initial known index level for the first calculation period.

Type: **float**

Used in components: **LegPaymentStreamFloatingRate**



**180.2.2006 LegPaymentStreamInflationInterpolationMethod**

The method used when calculating the inflation index level from multiple points. The most common is linear method.

Type: **int**

Allowed values in PaymentStreamInflationInterpolationMethodCodeSet:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2007 LegPaymentStreamInflationLagDayType**

The inflation lag period day type.

Type: **int**

Allowed values in PaymentStreamInflationLagDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2008 LegPaymentStreamInflationLagPeriod**

Time unit multiplier for the inflation lag period. The lag period is the offsetting period from the payment date which determines the reference period for which the inflation index is observed.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2009 LegPaymentStreamInflationLagUnit**

Time unit associated with the inflation lag period.

Type: **String**

Allowed values in PaymentStreamInflationLagUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2010 LegPaymentStreamInflationPublicationSource**

The publication source, such as relevant web site, news publication or a government body, where inflation information is obtained.

Type: **String**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2011 LegPaymentStreamInitialFixingDateAdjusted**

The adjusted initial fixing date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamResetDates**

**180.2.2012 LegPaymentStreamInitialFixingDateBusinessCenter**

The business center calendar used to adjust the payment stream's initial fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentStreamInitialFixingDateBusinessCenterGrp**

**180.2.2013 LegPaymentStreamInitialFixingDateBusinessCenterGrp**

LegPaymentStreamInitialFixingDateBusinessCenterGrp is a repeating subcomponent within the LegPaymentStreamResetDates component used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPaymentStreamInitialFixingDateBusinessCenters	[1..1]	NumInGroup	
LegPaymentStreamInitialFixingDateBusinessCenter	[0..1]	String	Required if NoLegPaymentStreamInitialFixingDateBusinessCenters(40932) > 0.

Used in components: [LegPaymentStreamResetDates](#)

**180.2.2014 LegPaymentStreamInitialFixingDateBusinessDayConvention**

The business day convention used to adjust the payment stream's initial fixing date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegPaymentStreamResetDates](#)

**180.2.2015 LegPaymentStreamInitialFixingDateOffsetDayType**

Specifies the day type of the relative initial fixing date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegPaymentStreamResetDates**

**180.2.2016 LegPaymentStreamInitialFixingDateOffsetPeriod**

Time unit multiplier for the relative initial fixing date offset.

Type: **int**

Used in components: **LegPaymentStreamResetDates**

**180.2.2017 LegPaymentStreamInitialFixingDateOffsetUnit**

Time unit associated with the relative initial fixing date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamResetDates**

**180.2.2018 LegPaymentStreamInitialFixingDateRelativeTo**

Specifies the anchor date when the initial fixing date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamResetDates**

**180.2.2019 LegPaymentStreamInitialPrincipalExchangeIndicator**

Indicates whether there is an initial exchange of principal on the effective date.

Type: **Boolean**

Used in components: **LegPaymentStream**

**180.2.2020 LegPaymentStreamInitialRate**

The initial floating rate reset agreed between the principal parties involved in the trade. This is assumed to be the first required reset rate for the first regular calculation period. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. The initial rate is expressed in decimal form, e.g. 5% is represented as 0.05.

Type: **Percentage**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2021 LegPaymentStreamInterimPrincipalExchangeIndicator**

Indicates whether there are intermediate or interim exchanges of principal during the term of the swap.

Type: **Boolean**

Used in components: **LegPaymentStream**

**180.2.2022 LegPaymentStreamInterpolationMethod**

The method used when calculating the index rate from multiple points on the curve. The most common is linear method.

Type: **int**

Allowed values in PaymentStreamInflationInterpolationMethodCodeSet:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: **LegPaymentStream**

### **180.2.2023 LegPaymentStreamInterpolationPeriod**

Defines applicable periods for interpolation.

Type: **int**

Allowed values in PaymentStreamInterpolationPeriodCodeSet:

Code	Name	Description
0	Initial	Initial. Interpolation is applicable to the initial period only.
1	InitialAndFinal	Initial and final. Interpolation is applicable to the initial and final periods only.
2	Final	Final. Interpolation is applicable to the final period only.
3	AnyPeriod	Any period. Interpolation is applicable to any non-standard period.

Used in components: **LegPaymentStream**

### **180.2.2024 LegPaymentStreamLastRegularPaymentDateUnadjusted**

The unadjusted last regular payment date.

Type: **LocalMktDate**

Used in components: **LegPaymentStreamPaymentDates**

**180.2.2025 LegPaymentStreamLastResetRate**

The floating rate determined at the most recent reset. The rate is expressed in decimal form, e.g. 5% is represented as 0.05.

Type: **Percentage**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2026 LegPaymentStreamLinkClosingLevelIndicator**

Indicates whether the correlation or variance swap contract will ("Y") strike off the closing level of the default exchange traded contract or not.

Type: **Boolean**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2027 LegPaymentStreamLinkEstimatedTradingDays**

The expected number of trading days in the variance or correlation swap stream.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2028 LegPaymentStreamLinkExpiringLevelIndicator**

Indicates whether the correlation or variance swap contract will ("Y") strike off the expiring level of the default exchange traded contract or not.

Type: **Boolean**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2029 LegPaymentStreamLinkInitialLevel**

Price level at which the correlation or variance swap contract will strike.

Type: **Price**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2030 LegPaymentStreamLinkMaximumBoundary**

Specifies the maximum or upper boundary for variance or strike determination.

For a variation swap stream all observations above this price level will be excluded from the variance calculation.

For a correlation swap stream the maximum boundary is a percentage of the strike price.

Type: **float**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2031 LegPaymentStreamLinkMinimumBoundary**

Specifies the minimum or lower boundary for variance or strike determination.

For a variation swap stream all observations below this price level will be excluded from the variance calculation.

For a correlation swap stream the minimum boundary is a percentage of the strike price.

Type: **float**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2032 LegPaymentStreamLinkNumberOfDataSeries**

Number of data series for a correlation swap. Normal market practice is that correlation data sets are drawn from geographic market areas, such as America, Europe and Asia Pacific. Each of these geographic areas will have its own data series to avoid contagion.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2033 LegPaymentStreamLinkStrikePrice**

The strike price of a correlation or variance swap stream.

Type: **Price**

Used in components: **LegPaymentStreamFloatingRate**



**180.2.2034 LegPaymentStreamLinkStrikePriceType**

For a variance swap specifies how LegPaymentStreamLinkStrikePrice(42472) is expressed.

Type: **int**

Allowed values in PaymentStreamLinkStrikePriceTypeCodeSet:

Code	Name	Description
0	Volatility	Volatility
1	Variance	Variance

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2035 LegPaymentStreamMarketRate**

Used only for credit index trade. This contains the credit spread ("fair value") at which the trade was executed. The market rate varies over the life of the index depending on market conditions. This is the price of the index as quoted by trading desks.

Type: **int**

Used in components: **LegPaymentStream**

**180.2.2036 LegPaymentStreamMasterAgreementPaymentDatesIndicator**

When set to 'Y', it indicates that payment dates are specified in the relevant master agreement.

Type: **Boolean**

Used in components: **LegPaymentStreamPaymentDates**

**180.2.2037 LegPaymentStreamNearestExchangeContractRefID**

References a contract listed on an exchange through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2038 LegPaymentStreamNegativeRateTreatment**

The specification of any provisions for calculating payment obligations when a floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2039 LegPaymentStreamNonDeliverableFixingDateGrp**

LegPaymentStreamNonDeliverableFixingDate is a subcomponent of the LegPaymentStreamNonDeliverableSettlTerms component used to specify predetermined fixing dates.

Name	Mult.	Type	Description
<b>NoLegNonDeliverableFixingDates</b>	[1..1]	NumInGroup	
<b>LegNonDeliverableFixingDate</b>	[0..1]	LocalMktDate	Required if NoLegNonDeliverableFixingDates(40367) > 0.
<b>LegNonDeliverableFixingDateType</b>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: **LegPaymentStreamNonDeliverableSettlTerms**

**180.2.2040 LegPaymentStreamNonDeliverableFixingDatesBusinessCenter**

The business center calendar used to adjust the payment stream's fixing date for the non-deliverable terms, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp**

**180.2.2041 LegPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp**

LegPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp is a repeating subcomponent within the LegPaymentStreamNonDeliverableSettlTerms component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPaymentStreamNonDeliverable-FixingDateBusinessCenters	[1..1]	NumInGroup	
LegPaymentStreamNonDeliverableFixingDatesBusinessCenter	[0..1]	String	Required if NoLegPaymentStreamNonDeliverable-FixingDatesBusinessCenters(40929) > 0.

Used in components: [LegPaymentStreamNonDeliverableSettlTerms](#)

**180.2.2042 LegPaymentStreamNonDeliverableFixingDatesBusinessDayConvention**

The business day convention used to adjust the payment stream's fixing date for the non-deliverable settlement terms. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegPaymentStreamNonDeliverableSettlTerms](#)

**180.2.2043 LegPaymentStreamNonDeliverableFixingDatesOffsetDayType**

Specifies the day type of the relative non-deliverable fixing date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegPaymentStreamNonDeliverableSettlTerms](#)

**180.2.2044 LegPaymentStreamNonDeliverableFixingDatesOffsetPeriod**

Time unit multiplier for the relative non-deliverable fixing date offset.

Type: **int**

Used in components: [LegPaymentStreamNonDeliverableSettlTerms](#)

**180.2.2045 LegPaymentStreamNonDeliverableFixingDatesOffsetUnit**

Time unit associated with the relative non-deliverable fixing date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegPaymentStreamNonDeliverableSettlTerms](#)

**180.2.2046 LegPaymentStreamNonDeliverableFixingDatesRelativeTo**

Specifies the anchor date when the non-deliverable fixing dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamNonDeliverableSettlTerms**

**180.2.2047 LegPaymentStreamNonDeliverableRefCurrency**

Non-deliverable settlement reference currency. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegPaymentStreamNonDeliverableSettlTerms**

**180.2.2048 LegPaymentStreamNonDeliverableSettlRateSource**

Identifies the source of the rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in components: **LegPaymentStreamNonDeliverableSettlRateSource**

**180.2.2049 LegPaymentStreamNonDeliverableSettlRateSource**

LegPaymentStreamNonDeliverableSettlRateSource is a subcomponent of the LegPaymentStreamNonDeliverableSettlTerms component used to specify the rate source in the event of payment non-delivery.

Name	Mult.	Type	Description
<a href="#">LegPaymentStreamNonDeliverableSettlRateSource</a>	[0..1]	CodeSet	
<a href="#">LegPaymentStreamNonDeliverableSettlReferencePage</a>	[0..1]	String	Conditionally required when <a href="#">LegPaymentStreamNonDeliverableSettlRateSource(40087)</a> = 3 (ISDA Settlement Rate Option) or 99 (Other).

Used in components: [LegPaymentStreamNonDeliverableSettlTerms](#)

#### 180.2.2050 [LegPaymentStreamNonDeliverableSettlReferencePage](#)

Identifies the reference "page" from the rate source.

When [LegPaymentStreamNonDeliverableSettlRateSource\(40087\)](#) = 3 (ISDA Settlement Rate Option) this contains a value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: [String](#)

Used in components: [LegPaymentStreamNonDeliverableSettlRateSource](#)

#### 180.2.2051 [LegPaymentStreamNonDeliverableSettlTerms](#)

[LegPaymentStreamNonDeliverableSettl](#) is a subcomponent of the [LegPaymentStream](#) component used to specify the non-deliverable settlement terms of the payment stream.

Name	Mult.	Type	Description
<a href="#">LegPaymentStreamNonDeliverableRefCurrency</a>	[0..1]	Currency	
<a href="#">LegPaymentStreamNonDeliverableFixingDatesBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the <a href="#">LegDateAdjustment</a> component in <a href="#">InstrumentLeg</a> . The specified value would be specific to this instance of the non-deliverable currency's fixing date.
<a href="#">LegPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the <a href="#">LegDateAdjustment</a> component in <a href="#">InstrumentLeg</a> . The specified values would be specific to this instance of the non-deliverable currency's fixing date.

Name	Mult.	Type	Description
<a href="#">LegPaymentStreamNonDeliverableFixingDatesRelativeTo</a>	[0..1]	int	
<a href="#">LegPaymentStreamNonDeliverableFixingDatesOffsetPeriod</a>	[0..1]	int	Conditionally required when LegPaymentStreamNonDeliverableFixingDateOffsetUnit(40364) is specified.
<a href="#">LegPaymentStreamNonDeliverableFixingDatesOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegPaymentStreamNonDeliverableFixingDateOffsetPeriod(40363) is specified.
<a href="#">LegPaymentStreamNonDeliverableFixingDatesOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">LegPaymentStreamNonDeliverableSettlRateSource</a>	[0..1]	Component	
<a href="#">LegPaymentStreamNonDeliverableFixingDateGrp</a>	[0..*]	Group	
<a href="#">LegSettlRateDisruptionFallbackGrp</a>	[0..*]	Group	

Used in components: [LegPaymentStream](#)

#### 180.2.2052 LegPaymentStreamOtherDayCount

The industry name of the day count convention not listed in LegPaymentStreamDayCount(40283).

Type: [String](#)

Used in components: [LegPaymentStream](#)

#### 180.2.2053 LegPaymentStreamPaymentDate

The adjusted or unadjusted fixed stream payment date.

Type: [LocalMktDate](#)

Used in groups: [LegPaymentStreamPaymentDateGrp](#)

#### 180.2.2054 LegPaymentStreamPaymentDateBusinessCenter

The business center calendar used to adjust the payment stream's payment date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentStreamPaymentDateBusinessCenterGrp**

### 180.2.2055 **LegPaymentStreamPaymentDateBusinessCenterGrp**

LegPaymentStreamPaymentDateBusinessCenterGrp is a repeating subcomponent of the LegPaymentStreamPaymentDates component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPaymentStreamPaymentDateBusinessCenters	[1..1]	NumInGroup	
LegPaymentStreamPaymentDateBusinessCenter	[0..1]	String	Requirend if NoLegPaymentStreamPaymentDateBusinessCenters(40930) > 0.

Used in components: **LegPaymentStreamPaymentDates**

### 180.2.2056 **LegPaymentStreamPaymentDateBusinessDayConvention**

The business day convention used to adjust the payment stream's payment date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.



Used in components: [LegPaymentStreamPaymentDates](#)

### 180.2.2057 LegPaymentStreamPaymentDateGrp

The LegPaymentStreamPaymentDateGrp is a repeating subcomponent of the LegPaymentStreamPaymentDates component used to detail fixed dates for swap stream payments.

Name	Mult.	Type	Description
<a href="#">NoLegPaymentStreamPaymentDates</a>	[1..1]	NumInGroup	
<a href="#">LegPaymentStreamPaymentDate</a>	[0..1]	LocalMktDate	Required if NoLegPaymentStreamPaymentDates(41589) > 0.
<a href="#">LegPaymentStreamPaymentDateType</a>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [LegPaymentStreamPaymentDates](#)

### 180.2.2058 LegPaymentStreamPaymentDateOffsetDayType

Specifies the day type of the relative payment date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegPaymentStreamPaymentDates](#)

**180.2.2059 LegPaymentStreamPaymentDateOffsetPeriod**

Time unit multiplier for the relative payment date offset.

Type: **int**

Used in components: **LegPaymentStreamPaymentDates**

**180.2.2060 LegPaymentStreamPaymentDateOffsetUnit**

Time unit associated with the relative payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamPaymentDates**

**180.2.2061 LegPaymentStreamPaymentDateRelativeTo**

Specifies the anchor date when payment dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamPaymentDates**

**180.2.2062 LegPaymentStreamPaymentDates**

The LegPaymentStreamPaymentDates component is a subcomponent of the LegPaymentStream component used to specify the payment dates of the stream.

Name	Mult.	Type	Description
LegPaymentStreamPaymentDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg payment stream.
LegPaymentStreamPaymentDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg payment stream.
LegPaymentStreamPaymentDateGrp	[0..*]	Group	
LegPaymentStreamPaymentFrequencyPeriod	[0..1]	int	Conditionally required when LegPaymentStreamPaymentFrequencyUnit(40295) is specified.
LegPaymentStreamPaymentFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamFrequencyPeriod(40294) is specified.
LegPaymentStreamPaymentRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the stream payment dates.
LegPaymentStreamFirstPaymentDateUnadjusted	[0..1]	LocalMktDate	
LegPaymentStreamLastRegularPaymentDateUnadjusted	[0..1]	LocalMktDate	
LegPaymentStreamPaymentDateRelativeTo	[0..1]	int	
LegPaymentStreamPaymentDateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentStreamPaymentDateOffsetUnit(40301) is specified.
LegPaymentStreamPaymentDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamPaymentDateOffsetPeriod(40300) is specified.
LegPaymentStreamPaymentDateOffsetDayType	[0..1]	CodeSet	
LegPaymentStreamMasterAgreementPaymentDatesIndicator	[0..1]	Boolean	
LegPaymentStreamFinalPricePaymentDate	[0..1]	Component	

Used in components: [LegPaymentStream](#)

**180.2.2063 LegPaymentStreamPaymentDateType**

Specifies the type of payment date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **LegPaymentStreamPaymentDateGrp**

**180.2.2064 LegPaymentStreamPaymentFrequencyPeriod**

Time unit multiplier for the frequency of payments.

Type: **int**

Used in components: **LegPaymentStreamPaymentDates**

**180.2.2065 LegPaymentStreamPaymentFrequencyUnit**

Time unit associated with the frequency of payments.

Type: **String**

Allowed values in PaymentStreamPaymentFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
T	Term	Term

Used in components: **LegPaymentStreamPaymentDates**

**180.2.2066 LegPaymentStreamPaymentRollConvention**

The convention for determining the sequence of end dates. It is used in conjunction with a specified frequency. Used only to override the roll convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelfthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	FourteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month

Code	Name	Description
28	TwentyEighthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [LegPaymentStreamPaymentDates](#)

#### 180.2.2067 LegPaymentStreamPricingBusinessCalendar

Specifies the business calendar to use for pricing.

See <http://www.fpml.org/coding-scheme/commodity-business-calendar> for values.

Type: [String](#)

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.2068 LegPaymentStreamPricingBusinessCenter**

The business center calendar used to adjust the pricing dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentStreamPricingBusinessCenterGrp**

**180.2.2069 LegPaymentStreamPricingBusinessCenterGrp**

LegPaymentStreamPricingBusinessCenterGrp is a repeating subcomponent of the LegPaymentStream-FloatingRate component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPaymentStreamPricingBusinessCenters	[1..1]	NumInGroup	
LegPaymentStreamPricingBusinessCenter	[0..1]	String	Required if NoLegPaymentStreamPricingBusinessCenters(41561) > 0.

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2070 LegPaymentStreamPricingBusinessDayConvention**

The business day convention used to adjust the payment stream's pricing dates. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.

Code	Name	Description
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegPaymentStreamFloatingRate](#)

#### 180.2.2071 LegPaymentStreamPricingDate

The adjusted or unadjusted fixed stream pricing date.

Type: [LocalMktDate](#)

Used in groups: [LegPaymentStreamPricingDateGrp](#)

#### 180.2.2072 LegPaymentStreamPricingDateGrp

The LegPaymentStreamPricingDateGrp is a repeating subcomponent of the LegPaymentStreamFloatingRate component used to detail fixed pricing dates.

Name	Mult.	Type	Description
<a href="#">NoLegPaymentStreamPricingDates</a>	[1..1]	NumInGroup	
<a href="#">LegPaymentStreamPricingDate</a>	[0..1]	LocalMktDate	Required if NoPaymentStreamPricingDates(41593) > 0.
<a href="#">LegPaymentStreamPricingDateType</a>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [LegPaymentStreamFloatingRate](#)

#### 180.2.2073 LegPaymentStreamPricingDateType

Specifies the type of pricing date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.



Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **LegPaymentStreamPricingDateGrp**

#### **180.2.2074 LegPaymentStreamPricingDayCount**

The number of days over which pricing should take place.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

#### **180.2.2075 LegPaymentStreamPricingDayDistribution**

The distribution of pricing days.

Type: **int**

Allowed values in PaymentStreamPricingDayDistributionCodeSet:

Code	Name	Description
0	All	All
1	First	First
2	Last	Last
3	Penultimate	Penultimate

Used in components: **LegPaymentStreamFloatingRate**

#### **180.2.2076 LegPaymentStreamPricingDayGrp**

The LegPaymentStreamPricingDayGrp is a repeating subcomponent of the LegPaymentStreamFloatingRate component used to detail periodic pricing days.

Name	Mult.	Type	Description
NoLegPaymentStreamPricingDays	[1..1]	NumInGroup	
LegPaymentStreamPricingDayOfWeek	[0..1]	CodeSet	Required if NoLegPaymentStreamPricingDays(41596) > 0.
LegPaymentStreamPricingDayNumber	[0..1]	int	

Used in components: [LegPaymentStreamFloatingRate](#)

### 180.2.2077 LegPaymentStreamPricingDayNumber

The occurrence of the day of week on which pricing takes place.

Type: [int](#)

Used in groups: [LegPaymentStreamPricingDayGrp](#)

### 180.2.2078 LegPaymentStreamPricingDayOfWeek

The day of the week on which pricing takes place.

Type: [int](#)

Allowed values in PaymentStreamPricingDayOfWeekCodeSet:

Code	Name	Description
0	EveryDay	Every day (the default if not specified)
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday

Used in groups: [LegPaymentStreamPricingDayGrp](#)

**180.2.2079 LegPaymentStreamPricingDayType**

Specifies the commodity pricing day type.

Type: **int**

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2080 LegPaymentStreamRate**

The rate applicable to the fixed rate payment stream.

Type: **Percentage**

Used in components: **LegPaymentStreamFixedRate**

**180.2.2081 LegPaymentStreamRateConversionFactor**

The number to be multiplied by the derived floating rate of the leg's payment stream in order to arrive at the payment rate. If omitted, the floating rate conversion factor is 1.

Type: **float**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2082 LegPaymentStreamRateCutoffDateOffsetDayType**

Specifies the day type of the relative rate cut-off date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegPaymentStreamResetDates](#)

#### **180.2.2083 LegPaymentStreamRateCutoffDateOffsetPeriod**

Time unit multiplier for the relative rate cut-off date offset.

Type: [int](#)

Used in components: [LegPaymentStreamResetDates](#)

#### **180.2.2084 LegPaymentStreamRateCutoffDateOffsetUnit**

Time unit associated with the relative rate cut-off date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegPaymentStreamResetDates](#)

**180.2.2085 LegPaymentStreamRateIndex**

The payment stream floating rate index.

Type: **String**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2086 LegPaymentStreamRateIndex2**

The payment stream's second floating rate index.

Type: **String**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2087 LegPaymentStreamRateIndex2CurvePeriod**

Secondary time unit multiplier for the payment stream's floating rate index curve.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2088 LegPaymentStreamRateIndex2CurveUnit**

Secondary time unit associated with the payment stream's floating rate index curve.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2089 LegPaymentStreamRateIndex2ID**

Security identifier of the second floating rate index.

Type: **String**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2090 LegPaymentStreamRateIndex2IDSource**

Source for the second floating rate index identified in LegPaymentStreamRateIndex2ID(43118).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit

Code	Name	Description
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [LegPaymentStreamFloatingRate](#)

### 180.2.2091 LegPaymentStreamRateIndex2Source

The source of the payment stream's second floating rate index.

Type: [int](#)

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.2092 LegPaymentStreamRateIndexCurvePeriod**

Time unit multiplier for the payment stream's floating rate index curve period.

Type: **int**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2093 LegPaymentStreamRateIndexCurveUnit**

Time unit associated with the payment stream's floating rate index curve period.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2094 LegPaymentStreamRateIndexID**

Security identifier of the floating rate index.

Type: **String**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2095 LegPaymentStreamRateIndexIDSource**

Source for the floating rate index identified in LegPaymentStreamRateIndexID(43088).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:



Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)

Code	Name	Description
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [LegPaymentStreamFloatingRate](#)

#### 180.2.2096 LegPaymentStreamRateIndexLevel

This is the weather Cooling Degree Days (CDD), Heating Degree Days (HDD) or HDD index level specified as the number of (amount of) weather index units specified by the parties in the related confirmation.

Type: [Qty](#)

Used in components: [LegPaymentStreamFloatingRate](#)

#### 180.2.2097 LegPaymentStreamRateIndexLocation

Specifies the location of the floating rate index.

Type: [String](#)

Used in components: [LegPaymentStreamFloatingRate](#)

#### 180.2.2098 LegPaymentStreamRateIndexSource

The source of the payment stream floating rate index.

Type: [int](#)

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.2099 LegPaymentStreamRateIndexUnitOfMeasure**

The unit of measure (UOM) of the rate index level.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [LegPaymentStreamFloatingRate](#)

### **180.2.2100 LegPaymentStreamRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: [float](#)

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.2101 LegPaymentStreamRateOrAmountCurrency**

Specifies the currency in which LegPaymentStreamFixedAmount(40327) or LegPaymentStreamRate(40326) is denominated. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegPaymentStreamFixedRate**

**180.2.2102 LegPaymentStreamRateSpread**

The basis points spread from the index specified in LegPaymentStreamRateIndex(40331).

Type: **PriceOffset**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2103 LegPaymentStreamRateSpreadCurrency**

Specifies the currency of the floating rate spread. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2104 LegPaymentStreamRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2105 LegPaymentStreamRateSpreadType**

Identifies whether the rate spread is an absolute value to be added to the index rate or a percentage of the index rate.

Type: **int**

Allowed values in PaymentStreamRateSpreadTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2106 LegPaymentStreamRateSpreadUnitOfMeasure**

Specifies the unit of measure (UOM) of the floating rate spread.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.

Code	Name	Description
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces



Code	Name	Description
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard

Code	Name	Description
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [LegPaymentStreamFloatingRate](#)

### 180.2.2107 LegPaymentStreamRateTreatment

Specifies the yield calculation treatment for the index.

Type: [int](#)

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: [LegPaymentStreamFloatingRate](#)

### 180.2.2108 LegPaymentStreamRealizedVarianceMethod

Indicates which price to use to satisfy the boundary condition.

Type: [int](#)

Allowed values in PaymentStreamRealizedVarianceMethodCodeSet:

Code	Name	Description
0	Previous	Previous. For a return on day T, the observed price on T-1 must be in range.
1	Last	Last. For a return on day T, the observed price on T must be in range.
2	Both	Both. For a return on day T, the observed prices on both T and T-1 must be in range.

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.2109 LegPaymentStreamReferenceLevel**

This is the weather Cooling Degree Days (CDD), Heating Degree Days (HDD) or HDD reference level specified as the number of (amount of) weather index units specified by the parties in the related confirmation.

Type: **Qty**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2110 LegPaymentStreamReferenceLevelEqualsZeroIndicator**

When set to 'Y', it indicates that the weather reference level equals zero.

Type: **Boolean**

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2111 LegPaymentStreamReferenceLevelUnitOfMeasure**

The unit of measure (UOM) of the rate reference level.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)

Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter

Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [LegPaymentStreamFloatingRate](#)

### 180.2.2112 LegPaymentStreamResetDateBusinessCenter

The business center calendar used to adjust the payment stream's reset date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [LegPaymentStreamResetDateBusinessCenterGrp](#)

### 180.2.2113 LegPaymentStreamResetDateBusinessCenterGrp

LegPaymentStreamResetDateBusinessCenterGrp is a repeating subcomponent within the LegPaymentStreamResetDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
<a href="#">NoLegPaymentStreamResetDateBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">LegPaymentStreamResetDateBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoLegPaymentStreamResetDateBusinessCenters</a> (40931) > 0.

Used in components: [LegPaymentStreamResetDates](#)

### 180.2.2114 LegPaymentStreamResetDateBusinessDayConvention

The business day convention used to adjust the payment stream's reset date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **LegPaymentStreamResetDates**

#### **180.2.2115 LegPaymentStreamResetDateRelativeTo**

Specifies the anchor date when the reset dates are relative to an anchor date.

If the reset frequency is specified as daily this element must not be included.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStreamResetDates**

#### **180.2.2116 LegPaymentStreamResetDates**

The LegPaymentStreamResetDates component is a subcomponent of the LegPaymentStream component used to specify the floating rate reset dates of the stream.

Name	Mult.	Type	Description
<b>LegPaymentStreamResetDateRelativeTo</b>	[0..1]	int	

Name	Mult.	Type	Description
LegPaymentStreamResetDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg payment stream reset dates.
LegPaymentStreamResetDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg payment stream reset dates.
LegPaymentStreamResetFrequencyPeriod	[0..1]	int	Conditionally required when LegPaymentStreamResetFrequencyUnit(40307) is specified.
LegPaymentStreamResetFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamResetFrequencyPeriod(40306) is specified.
LegPaymentStreamResetWeeklyRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the stream payment dates.
LegPaymentStreamInitialFixingDateRelativeTo	[0..1]	int	
LegPaymentStreamInitialFixingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg payment stream reset dates.
LegPaymentStreamInitialFixingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg payment stream reset dates.
LegPaymentStreamInitialFixingDateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentStreamInitialFixingDateOffsetUnit(40313) is specified.
LegPaymentStreamInitialFixingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamInitialFixingDateOffsetPeriod(40312) is specified.
LegPaymentStreamInitialFixingDateOffsetDayType	[0..1]	CodeSet	



Name	Mult.	Type	Description
LegPaymentStreamInitialFixingDateAdjusted	[0..1]	LocalMktDate	
LegPaymentStreamFixingDateRelativeTo	[0..1]	int	
LegPaymentStreamFixingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg payment stream reset dates.
LegPaymentStreamFixingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg payment stream reset dates.
LegPaymentStreamFixingDateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentStreamFixingDateOffsetUnit(40320) is specified.
LegPaymentStreamFixingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamFixingDateOffsetPeriod(40319) is specified.
LegPaymentStreamFixingDateOffsetDayType	[0..1]	CodeSet	
LegPaymentStreamFixingDateAdjusted	[0..1]	LocalMktDate	
LegPaymentStreamRateCutoffDateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentStreamRateCutoffDateOffsetUnit(40324) is specified.
LegPaymentStreamRateCutoffDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStreamRateCutoffDateOffsetPeriod(40323) is specified.
LegPaymentStreamRateCutoffDateOffsetDayType	[0..1]	CodeSet	
LegPaymentStreamFixingDateGrp	[0..*]	Group	

Used in components: [LegPaymentStream](#)

### 180.2.2117 LegPaymentStreamResetFrequencyPeriod

Time unit multiplier for frequency of resets.

Type: [int](#)

Used in components: [LegPaymentStreamResetDates](#)

**180.2.2118 LegPaymentStreamResetFrequencyUnit**

Time unit associated with frequency of resets.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: **LegPaymentStreamResetDates**

**180.2.2119 LegPaymentStreamResetWeeklyRollConvention**

Used to specify the day of the week in which the reset occurs for payments that reset on a weekly basis.

Type: **String**

Allowed values in PaymentStreamResetWeeklyRollConventionCodeSet:

Code	Name	Description
MON	Monday	Monday
TUE	Tuesday	Tuesday
WED	Wednesday	Wednesday
THU	Thursday	Thursday
FRI	Friday	Friday
SAT	Saturday	Saturday
SUN	Sunday	Sunday

Used in components: **LegPaymentStreamResetDates**

**180.2.2120 LegPaymentStreamSettlCurrency**

Specifies the currency that the stream settles in (to support swaps that settle in a currency different from the notional currency). Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegPaymentStream**

**180.2.2121 LegPaymentStreamSettlLevel**

Specifies how weather index units are to be calculated.

Type: **int**

Allowed values in PaymentStreamSettlLevelCodeSet:

Code	Name	Description
0	Average	Average. The cumulative number of weather index units for each day in the calculation period divided by the number of days in the calculation period.
1	Maximum	Maximum. The maximum number of weather index units for any day in the calculation period.
2	Minimum	Minimum. The minimum number of weather index units for any day in the calculation period.
3	Cumulative	Cumulative. The cumulative number of weather index units for each day in the calculation period.

Used in components: **LegPaymentStreamFloatingRate**

**180.2.2122 LegPaymentStreamTotalFixedAmount**

Specifies the total fixed payment amount.

Type: **Amt**

Used in components: **LegPaymentStreamFixedRate**

**180.2.2123 LegPaymentStreamType**

Identifies the type of payment stream applicable to the swap stream associated with the instrument leg.

Type: **int**

Allowed values in PaymentStreamTypeCodeSet:

Code	Name	Description
0	Periodic	Periodic (default)
1	Initial	Initial
2	Single	Single
3	Dividend	Dividend
4	Interest	Interest
5	DividendReturn	Dividend return
6	PriceReturn	Price return
7	TotalReturn	Total return
8	Variance	Variance
9	Correlation	Correlation

Used in components: **LegPaymentStream**

#### **180.2.2124 LegPaymentStreamUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in components: **LegPaymentStreamFloatingRate**

#### **180.2.2125 LegPaymentStreamVarianceUnadjustedCap**

Indicates the scaling factor to be multiplied by the variance strike price thereby making variance cap applicable.

Type: **float**

Used in components: **LegPaymentStreamFloatingRate**

#### **180.2.2126 LegPaymentStreamVegaNotionalAmount**

Vega Notional represents the approximate gain/loss at maturity for a 1% difference between RVol (realized volatility) and KVol (strike volatility). It does not necessarily represent the Vega risk of the

trade.

Type: **float**

Used in components: **LegPaymentStreamFloatingRate**

#### **180.2.2127 LegPaymentStreamWorldScaleRate**

The number of Worldscale points for purposes of the calculation of a fixed amount for a wet voyage charter commodity swap.

Type: **float**

Used in components: **LegPaymentStreamFixedRate**

#### **180.2.2128 LegPaymentStubEndDateAdjusted**

The adjusted stub end date.

Type: **LocalMktDate**

Used in components: **LegPaymentStubEndDate**

#### **180.2.2129 LegPaymentStubEndDateBusinessCenter**

The business center calendar used for date adjustment of the payment stub end date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentStubEndDateBusinessCenterGrp**

#### **180.2.2130 LegPaymentStubEndDateBusinessCenterGrp**

**LegPaymentStubEndDateBusinessCenterGrp** is a repeating subcomponent within the **LegPaymentStubEndDate** component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the **LegDateAdjustment** component in **InstrumentLeg**.

Name	Mult.	Type	Description
NoLegPaymentStubEndDateBusiness-Centers	[1..1]	NumInGroup	
LegPaymentStubEndDateBusiness-Center	[0..1]	String	Required if NoLegPaymentStubEndDateBusiness-Centers(42495) > 0.

Used in components: [LegPaymentStubEndDate](#)

### 180.2.2131 LegPaymentStubEndDateBusinessDayConvention

The stub end date business day convention.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegPaymentStubEndDate](#)

### 180.2.2132 LegPaymentStubEndDate

LegPaymentStubEndDate is a subcomponent of the LegPaymentStubGrp component used to specify the end date of the payment stub.

Name	Mult.	Type	Description
LegPaymentStubEndDateUnadjusted	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
<a href="#">LegPaymentStubEndDateBusiness-DayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this payment stub instance.
<a href="#">LegPaymentStubEndDateBusiness-CenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this payment stub instance.
<a href="#">LegPaymentStubEndDateRelativeTo</a>	[0..1]	int	
<a href="#">LegPaymentStubEndDateOffsetPeriod</a>	[0..1]	int	Conditionally required when LegPaymentStubEndDateOffsetUnit(42492) is specified.
<a href="#">LegPaymentStubEndDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegPaymentStubEndDateOffsetPeriod(42491) is specified.
<a href="#">LegPaymentStubEndDateOffsetDay-Type</a>	[0..1]	CodeSet	
<a href="#">LegPaymentStubEndDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [LegPaymentStubGrp](#)

### 180.2.2133 LegPaymentStubEndDateOffsetDayType

Specifies the day type of the relative stub end date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegPaymentStubEndDate](#)

**180.2.2134 LegPaymentStubEndDateOffsetPeriod**

Time unit multiplier for the relative stub end date offset.

Type: **int**

Used in components: **LegPaymentStubEndDate**

**180.2.2135 LegPaymentStubEndDateOffsetUnit**

Time unit associated with the relative stub end date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegPaymentStubEndDate**

**180.2.2136 LegPaymentStubEndDateRelativeTo**

Specifies the anchor date when the stub end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegPaymentStubEndDate**

**180.2.2137 LegPaymentStubEndDateUnadjusted**

The unadjusted stub end date.

Type: **LocalMktDate**

Used in components: **LegPaymentStubEndDate**



**180.2.2138 LegPaymentStubFixedAmount**

A fixed payment amount for the stub.

Type: **Amt**

Used in groups: **LegPaymentStubGrp**

**180.2.2139 LegPaymentStubFixedCurrency**

The currency of the fixed payment amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegPaymentStubGrp**

**180.2.2140 LegPaymentStubGrp**

The LegPaymentStubGrp is a repeating subcomponent of the LegPaymentStream component used to specify front and back stubs in the payment stream.

Name	Mult.	Type	Description
NoLegPaymentStubs	[1..1]	NumInGroup	
LegPaymentStubType	[0..1]	CodeSet	Required if NoLegPaymentStubs(40418) > 0.
LegPaymentStubLength	[0..1]	CodeSet	
LegPaymentStubStartDate	[0..1]	Component	
LegPaymentStubEndDate	[0..1]	Component	
LegPaymentStubRate	[0..1]	Percentage	
LegPaymentStubFixedAmount	[0..1]	Amt	
LegPaymentStubFixedCurrency	[0..1]	Currency	
LegPaymentStubIndex	[0..1]	String	
LegPaymentStubIndexSource	[0..1]	CodeSet	
LegPaymentStubIndexCurvePeriod	[0..1]	int	Conditionally required when LegPaymentStubIndexCurveUnit(40427) is specified.
LegPaymentStubIndexCurveUnit	[0..1]	CodeSet	Copnditionally required when LegPaymentStubIndexCurvePeriod(40426) is specified.
LegPaymentStubIndexRateMultiplier	[0..1]	float	
LegPaymentStubIndexRateSpread	[0..1]	PriceOffset	

Name	Mult.	Type	Description
LegPaymentStubIndexRateSpreadPositionType	[0..1]	CodeSet	
LegPaymentStubIndexRateTreatment	[0..1]	CodeSet	
LegPaymentStubIndexCapRate	[0..1]	Percentage	
LegPaymentStubIndexCapRateBuy-Side	[0..1]	CodeSet	
LegPaymentStubIndexCapRateSell-Side	[0..1]	CodeSet	
LegPaymentStubIndexFloorRate	[0..1]	Percentage	
LegPaymentStubIndexFloorRateBuy-Side	[0..1]	CodeSet	
LegPaymentStubIndexFloorRateSell-Side	[0..1]	CodeSet	
LegPaymentStubIndex2	[0..1]	String	
LegPaymentStubIndex2Source	[0..1]	CodeSet	
LegPaymentStubIndex2CurvePeriod	[0..1]	int	Conditionally required when LegPaymentStubIndex2CurveUnit(40441) is specified.
LegPaymentStubIndex2CurveUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStubIndex2CurvePeriod(40440) is specified.
LegPaymentStubIndex2RateMultiplier	[0..1]	float	
LegPaymentStubIndex2RateSpread	[0..1]	PriceOffset	
LegPaymentStubIndex2RateSpreadPositionType	[0..1]	CodeSet	
LegPaymentStubIndex2RateTreatment	[0..1]	CodeSet	
LegPaymentStubIndex2CapRate	[0..1]	Percentage	
LegPaymentStubIndex2FloorRate	[0..1]	Percentage	

Used in groups: **LegStreamGrp**

### 180.2.2141 LegPaymentStubIndex

The stub floating rate index.

Type: **String**

Used in groups: **LegPaymentStubGrp**

**180.2.2142 LegPaymentStubIndex2**

The second stub floating rate index.

Type: **String**

Used in groups: **LegPaymentStubGrp**

**180.2.2143 LegPaymentStubIndex2CapRate**

The cap rate, if any, which applies to the second floating rate. The cap rate (strike) is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **LegPaymentStubGrp**

**180.2.2144 LegPaymentStubIndex2CurvePeriod**

Secondary time unit multiplier for the stub floating rate index curve.

Type: **int**

Used in groups: **LegPaymentStubGrp**

**180.2.2145 LegPaymentStubIndex2CurveUnit**

Secondary time unit associated with the stub floating rate index curve.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in groups: **LegPaymentStubGrp**

**180.2.2146 LegPaymentStubIndex2FloorRate**

The floor rate, if any, which applies to the second floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A floor rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **LegPaymentStubGrp**

**180.2.2147 LegPaymentStubIndex2RateMultiplier**

A rate multiplier to apply to the second floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: **float**

Used in groups: **LegPaymentStubGrp**

**180.2.2148 LegPaymentStubIndex2RateSpread**

Spread from the second floating rate index.

Type: **PriceOffset**

Used in groups: **LegPaymentStubGrp**

**180.2.2149 LegPaymentStubIndex2RateSpreadPositionType**

Identifies whether the rate spread is applied to a long or a short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

---

Code	Name	Description
0	Short	Short
1	Long	Long

---

Used in groups: **LegPaymentStubGrp**

**180.2.2150 LegPaymentStubIndex2RateTreatment**

Specifies the yield calculation treatment for the second stub index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in groups: **LegPaymentStubGrp**

**180.2.2151 LegPaymentStubIndex2Source**

The source for the second stub floating rate index.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in groups: **LegPaymentStubGrp**

**180.2.2152 LegPaymentStubIndexCapRate**

The cap rate, if any, which applies to the floating rate. The cap rate (strike) is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **LegPaymentStubGrp**

**180.2.2153 LegPaymentStubIndexCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **LegPaymentStubGrp**

**180.2.2154 LegPaymentStubIndexCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **LegPaymentStubGrp**

**180.2.2155 LegPaymentStubIndexCurvePeriod**

Time unit multiplier for the floating rate index.

Type: **int**

Used in groups: **LegPaymentStubGrp**

**180.2.2156 LegPaymentStubIndexCurveUnit**

Time unit associated with the floating rate index.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegPaymentStubGrp**

**180.2.2157 LegPaymentStubIndexFloorRate**

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A floor rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **LegPaymentStubGrp**

**180.2.2158 LegPaymentStubIndexFloorRateBuySide**

Reference to the buyer of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **LegPaymentStubGrp**

**180.2.2159 LegPaymentStubIndexFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **LegPaymentStubGrp**

**180.2.2160 LegPaymentStubIndexRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: **float**

Used in groups: **LegPaymentStubGrp**

**180.2.2161 LegPaymentStubIndexRateSpread**

Spread from floating rate index.

Type: **PriceOffset**

Used in groups: **LegPaymentStubGrp**

**180.2.2162 LegPaymentStubIndexRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or a short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:



---

Code	Name	Description
------	------	-------------

---

0	Short	Short
---	-------	-------

1	Long	Long
---	------	------

---

Used in groups: [LegPaymentStubGrp](#)

### **180.2.2163 LegPaymentStubIndexRateTreatment**

Specifies the yield calculation treatment for the stub index.

Type: [int](#)

Allowed values in PaymentStreamRateTreatmentCodeSet:

---

Code	Name	Description
------	------	-------------

---

0	BondEquivalentYield	Bond equivalent yield
---	---------------------	-----------------------

1	MoneyMarketYield	Money market yield
---	------------------	--------------------

---

Used in groups: [LegPaymentStubGrp](#)

### **180.2.2164 LegPaymentStubIndexSource**

The source for the stub floating rate index.

Type: [int](#)

Allowed values in PaymentStreamRateIndexSourceCodeSet:

---

Code	Name	Description
------	------	-------------

---

0	Bloomberg	Bloomberg
---	-----------	-----------

1	Reuters	Reuters
---	---------	---------

2	Telerate	Telerate
---	----------	----------

99	Other	Other
----	-------	-------

---

Used in groups: [LegPaymentStubGrp](#)

**180.2.2165 LegPaymentStubLength**

Optional indication whether stub is shorter or longer than the regular swap period.

Type: **int**

Allowed values in PaymentStubLengthCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in groups: **LegPaymentStubGrp**

**180.2.2166 LegPaymentStubRate**

The agreed upon fixed rate for this stub.

Type: **Percentage**

Used in groups: **LegPaymentStubGrp**

**180.2.2167 LegPaymentStubStartDateAdjusted**

The adjusted stub start date.

Type: **LocalMktDate**

Used in components: **LegPaymentStubStartDate**

**180.2.2168 LegPaymentStubStartDateBusinessCenter**

The business center calendar used for date adjustment of the payment stub start date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegPaymentStubStartDateBusinessCenterGrp**

**180.2.2169 LegPaymentStubStartDateBusinessCenterGrp**

LegPaymentStubStartDateBusinessCenterGrp is a repeating subcomponent within the LegPaymentStubStartDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPaymentStubStartDateBusinessCenters	[1..1]	NumInGroup	
LegPaymentStubStartDateBusinessCenter	[0..1]	String	Required if NoLegPaymentStubStartDateBusinessCenters(42504) > 0.

Used in components: [LegPaymentStubStartDate](#)

**180.2.2170 LegPaymentStubStartDateBusinessDayConvention**

The stub start date business day convention.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegPaymentStubStartDate](#)

**180.2.2171 LegPaymentStubStartDate**

LegPaymentStubStartDate is a subcomponent of the LegPaymentStubGrp component used to specify the start date of the payment stub.

Name	Mult.	Type	Description
LegPaymentStubStartDateUnadjusted	[0..1]	LocalMktDate	
LegPaymentStubStartDateBusiness-DayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this payment stub instance.
LegPaymentStubStartDateBusiness-CenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this payment stub instance.
LegPaymentStubStartDateRelativeTo	[0..1]	int	
LegPaymentStubStartDateOffsetPeriod	[0..1]	int	Conditionally required when LegPaymentStubStartDateOffsetUnit(42501) is specified.
LegPaymentStubStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegPaymentStubStartDateOffsetPeriod(42500) is specified.
LegPaymentStubStartDateOffsetDay-Type	[0..1]	CodeSet	
LegPaymentStubStartDateAdjusted	[0..1]	LocalMktDate	

Used in groups: LegPaymentStubGrp

**180.2.2172 LegPaymentStubStartDateOffsetDayType**

Specifies the day type of the relative stub start date offset.

Type: int

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar

Code	Name	Description
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegPaymentStubStartDate](#)

#### **180.2.2173 LegPaymentStubStartDateOffsetPeriod**

Time unit multiplier for the relative stub start date offset.

Type: [int](#)

Used in components: [LegPaymentStubStartDate](#)

#### **180.2.2174 LegPaymentStubStartDateOffsetUnit**

Time unit associated with the relative stub start date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegPaymentStubStartDate](#)

#### **180.2.2175 LegPaymentStubStartDateRelativeTo**

Specifies the anchor date when the stub start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [LegPaymentStubStartDate](#)

**180.2.2176 LegPaymentStubStartDateUnadjusted**

The unadjusted stub start date.

Type: [LocalMktDate](#)

Used in components: [LegPaymentStubStartDate](#)

**180.2.2177 LegPaymentStubType**

Stub type.

Type: [int](#)

Allowed values in PaymentStubTypeCodeSet:

Code	Name	Description
0	Initial	Initial
1	Final	Final
2	CompoundingInitial	Compounding initial
3	CompoundingFinal	Compounding final

Used in groups: [LegPaymentStubGrp](#)

**180.2.2178 LegPhysicalSettlBusinessDays**

The number of business days used in the determination of physical settlement. Its precise meaning depends on the context in which this is used.

Type: [int](#)

Used in groups: [LegPhysicalSettlTermGrp](#)

**180.2.2179 LegPhysicalSettlCurency**

Specifies the currency of physical settlement. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [LegPhysicalSettlTermGrp](#)

**180.2.2180 LegPhysicalSettlDeliverableObligationGrp**

The LegPhysicalSettlDeliverableObligationGrp is a repeating component within the LegPhysicalSettlTermGrp component used to report credit default swap (CDS) physical settlement delivery obligations.

Name	Mult.	Type	Description
NoLegPhysicalSettlDeliverableObligations	[1..1]	NumInGroup	
LegPhysicalSettlDeliverableObligation-Type	[0..1]	String	Required if NoLegPhysicalSettlDeliverableObligations(41604) > 0.
LegPhysicalSettlDeliverableObligation-Value	[0..1]	String	

Used in groups: [LegPhysicalSettlTermGrp](#)

**180.2.2181 LegPhysicalSettlDeliverableObligationType**

Specifies the type of delivery obligation applicable for physical settlement.

See [http://www.fixptradingcommunity.org/codelists#Deliverable\\_Obligation\\_Types](http://www.fixptradingcommunity.org/codelists#Deliverable_Obligation_Types) for code list for applicable deliverable obligation types.

Type: [String](#)

Used in groups: [LegPhysicalSettlDeliverableObligationGrp](#)

**180.2.2182 LegPhysicalSettlDeliverableObligationValue**

Physical settlement delivery obligation value appropriate to LegPhysicalSettlDeliverableObligation-Type(41605).

See [http://www.fixtradingcommunity.org/codelists#Deliverable\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Deliverable_Obligation_Types) for code list for applicable deliverable obligation types.

Type: [String](#)

Used in groups: [LegPhysicalSettlDeliverableObligationGrp](#)

**180.2.2183 LegPhysicalSettlMaximumBusinessDays**

A maximum number of business days. Its precise meaning depends on the context in which this element is used. Intended to be used to limit a particular ISDA fallback provision.

Type: **int**

Used in groups: **LegPhysicalSettlTermGrp**

**180.2.2184 LegPhysicalSettlTermGrp**

The LegPhysicalSettlTermGrp is a repeating component within the InstrumentLeg component used to report physical settlement terms.

Name	Mult.	Type	Description
NoLegPhysicalSettlTerms	[1..1]	NumInGroup	
LegPhysicalSettlDeliverableObligation-Grp	[0..*]	Group	Required if NoLegPhysicalSettlTerms(41599) > 0.
LegPhysicalSettlCurrency	[0..1]	Currency	
LegPhysicalSettlBusinessDays	[0..1]	int	
LegPhysicalSettlMaximumBusiness-Days	[0..1]	int	
LegPhysicalSettlTermXID	[0..1]	XID	

Used in components: **InstrumentLeg**

**180.2.2185 LegPhysicalSettlTermXID**

A named string value referenced by UnderlyingSettlTermXIDRef(41315).

Type: **XID**

Used in groups: **LegPhysicalSettlTermGrp**

**180.2.2186 LegPool**

For Fixed Income, identifies MBS / ABS pool for a specific leg of a multi-leg instrument.

See Pool (691) for description and valid values.



Type: **String**

Used in components: **InstrumentLeg**

### **180.2.2187 LegPosAmt**

Leg position amount.

Type: **Amt**

Used in groups: **LegPositionAmountData**

### **180.2.2188 LegPosAmtReason**

Specifies the reason for an amount type when reported on a position. Useful when multiple instances of the same amount type are reported.

Type: **int**

Allowed values in PosAmtReasonCodeSet:

Code	Name	Description
0	OptionsSettlement	Options settlement
1	PendingErosionAdjustment	Pending erosion adjustment
2	FinalErosionAdjustment	Final erosion adjustment
3	TearUpCouponAmount	Tear-up coupon amount
4	PriceAlignmentInterest	Price alignment interest. To minimize the impact of daily cash variation margin payments on the pricing of interest rate swaps, the Clearing House will charge interest on cumulative variation margin received and pay interest on cumulative variation margin paid in respect of these instruments. This interest element is known as price alignment interest.
5	DeliveryInvoiceCharges	Delivery invoice charges
6	DeliveryStorageCharges	Delivery storage charges

Used in groups: **LegPositionAmountData**

### **180.2.2189 LegPosAmtType**

Type of leg position amount.

Type: **String**

Allowed values in PosAmtTypeCodeSet:

Code	Name	Description
CASH	CashAmount	Cash amount (corporate event)
CRES	CashResidualAmount	Cash residual amount
FMTM	FinalMarkToMarketAmount	Final mark-to-market amount
IMTM	IncrementalMarkToMarketAmount	Incremental mark-to-market
PREM	PremiumAmount	Premium amount
SMTM	StartOfDayMarkToMarketAmount	Start of day mark-to-market
TVAR	TradeVariationAmount	Trade variation amount
VADJ	ValueAdjustedAmount	Value adjusted amount
SETL	SettlementValue	Settlement value
ICPN	InitialTradeCouponAmount	Initial trade coupon amount
ACPN	AccruedCouponAmount	Accrued coupon amount
CPN	CouponAmount	Coupon amount
IACPN	IncrementalAccruedCoupon	Incremental accrued coupon
CMTM	CollateralizedMarkToMarket	Collateralized mark-to-market
ICMTM	IncrementalCollateralizedMark-ToMarket	Incremental collateralized mark-to-market
DLV	CompensationAmount	Compensation amount
BANK	TotalBankedAmount	Total banked amount
COLAT	TotalCollateralizedAmount	Total collateralized amount
LSNV	LongPairedSwapNotionalValue	Long paired swap or swaption notional value
SSNV	ShortPairedSwapNotionalValue	Short paired swap or swaption notional value
SACPN	StartOfDayAccruedCoupon	Start-of-day accrued coupon
NPV	NetPresentValue	Net present value
SNPV	StartOfDayNetPresentValue	Start-of-day net present value
NCF	NetCashFlow	Net cash flow
PVFEES	PresentValueOfFees	Present value of all fees
PV01	PresentValueOneBasisPoints	Present value of one basis points. Change in value if yield curve shifts 0.01%.
5YREN	FiveYearEquivalentNotional	The five year equivalent notional amount
UMTM	UndiscountedMarkToMarket	Undiscounted mark-to-market
MTD	MarkToModel	Mark-to-model
VMTM	MarkToMarketVariance	Mark-to-market variance

Code	Name	Description
VMTD	MarkToModelVariance	Mark-to-model variance
UPFRNT	UpfrontPayment	Upfront payment
ENDV	EndVale	End value. Principal amount of a securities financing transaction on maturity date.
MGNLN	OutstandingMarginLoan	Outstanding margin loan. The amount of the outstanding margin loan. In the event that the loan has a short market value, PosAmt(708) would be a negative value.
LNVL	LoanValue	Loan value. The amount of the loan.

Used in groups: [LegPositionAmountData](#)

### 180.2.2190 LegPosCurrency

Leg position currency.

Type: [Currency](#)

Used in groups: [LegPositionAmountData](#)

### 180.2.2191 LegPosCurrencyCodeSource

Identifies class or source of the LegPosCurrency(1589) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [LegPositionAmountData](#)

**180.2.2192 LegPositionAmountData**

Name	Mult.	Type	Description
NoLegPosAmt	[1..1]	NumInGroup	Number of Position Amount entries
LegPosAmt	[0..1]	Amt	Conditionally required if NoLegPosAmt > 0.
LegPosAmtType	[0..1]	CodeSet	
LegPosCurrency	[0..1]	Currency	
LegPosCurrencyCodeSource	[0..1]	CodeSet	
LegPosAmtReason	[0..1]	CodeSet	

Used in groups: **TrdInstrmtLegGrp**

**180.2.2193 LegPositionEffect**

PositionEffect for leg of a multileg

See PositionEffect (77) field for description

Type: **char**

Allowed values in PositionEffectCodeSet:

Code	Name	Description
C	Close	Close
F	FIFO	FIFO
O	Open	Open
R	Rolled	Rolled
N	CloseButNotifyOnOpen	Close but notify on open
D	Default	Default

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**, **TrdInstrmtLegExecGrp**, **TrdInstrmtLegGrp**

**180.2.2194 LegPositionLimit**

Position Limit for a given exchange-traded product.

Type: **int**

Used in components: **InstrumentLeg**

### 180.2.2195 LegPreAllocGrp

Name	Mult.	Type	Description
NoLegAllocs	[1..1]	NumInGroup	
LegAllocAccount	[0..1]	String	
LegIndividualAllocID	[0..1]	String	
NestedParties2	[0..*]	Group	
LegAllocQty	[0..1]	Qty	
LegAllocAcctIDSource	[0..1]	CodeSet	
LegAllocSettlCurrency	[0..1]	Currency	
LegAllocSettlCurrencyCodeSource	[0..1]	CodeSet	
LegCustodialLotID	[0..1]	String	Only used for specific lot trades.
LegVersusPurchaseDate	[0..1]	LocalMktDate	Only used for specific lot trades. If this field is used, either LegVersusPurchasePrice(1758) or LegCurrentCostBasis(1759) should be specified.
LegVersusPurchasePrice	[0..1]	Price	Only used for specific lot trades. If this field is used, LegVersusPurchaseDate(1757) should be specified.
LegCurrentCostBasis	[0..1]	Amt	Only used for specific lot trades. If this field is used, LegVersusPurchaseDate(1757) should be specified

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**

### 180.2.2196 LegPrice

Price for leg of a multileg

See Price (44) field for description

Type: **Price**

Used in components: **InstrumentLeg**

**180.2.2197 LegPriceQuoteCurrency**

Default currency in which the price is quoted. Defined at the instrument level. Used in place of Currency (tag 15) to express the currency of a product when the former is implemented as the FX dealt currency.

Type: **Currency**

Used in components: **InstrumentLeg**

**180.2.2198 LegPriceQuoteCurrencyCodeSource**

Identifies class or source of the LegPriceQuoteCurrency(1528) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **InstrumentLeg**

**180.2.2199 LegPriceQuoteMethod**

Specifies the method for price quotation.

Type: **String**

Allowed values in PriceQuoteMethodCodeSet:

Code	Name	Description
STD	Standard	Standard, money per unit of a physical
INX	Index	Index

Code	Name	Description
INT	InterestRateIndex	Interest rate Index
PCTPAR	PercentOfPar	Percent of Par

Used in components: [InstrumentLeg](#)

### 180.2.2200 LegPriceType

The price type of the LegBidPx (681) and/or LegOfferPx (684).

See PriceType (423) for description and valid values

Type: [int](#)

Allowed values in PriceTypeCodeSet:

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
2	PerUnit	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points spread). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	Yield	Yield
10	FixedCabinetTradePrice	Fixed cabinet trade price (primarily for listed futures and options)
11	VariableCabinetTradePrice	Variable cabinet trade price (primarily for listed futures and options)
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example, the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools

Code	Name	Description
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)
22	BasisPoints	Basis points. When the price is not spread based.
23	UpfrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageNotional	Percentage of notional

Used in groups: [LegQuotGrp](#), [TrdInstrmtLegExecGrp](#), [TrdInstrmtLegGrp](#)

### 180.2.2201 LegPriceUnitOfMeasure

Refer to definition for PriceUnitOfMeasure(1191)

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.



Code	Name	Description
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)

Code	Name	Description
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
Sqcm	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
Sqkm	SquareKilometer	Square kilometer

Code	Name	Description
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [InstrumentLeg](#)

#### 180.2.2202 LegPriceUnitOfMeasureCurrency

Indicates the currency of the price unit of measure. Conditionally required when LegPriceUnitOfMeasure(1421) = Ccy

Type: [Currency](#)

Used in components: [InstrumentLeg](#)

#### 180.2.2203 LegPriceUnitOfMeasureCurrencyCodeSource

Identifies class or source of the LegPriceUnitOfMeasureCurrency(1721) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [InstrumentLeg](#)

**180.2.2204 LegPriceUnitOfMeasureQty**

Refer to definition of PriceUnitOfMeasureQty(1192)

Type: Qty

Used in components: InstrumentLeg

**180.2.2205 LegPricingDateAdjusted**

The adjusted pricing or fixing date.

Type: LocalMktDate

Used in components: LegPricingDateTime

**180.2.2206 LegPricingDateBusinessCenter**

The business center calendar used to adjust the pricing or fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: String

Used in groups: LegPricingDateBusinessCenterGrp

**180.2.2207 LegPricingDateBusinessCenterGrp**

LegPricingDateBusinessCenterGrp is a repeating subcomponent of the LegPricingDateTime component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegPricingDateBusinessCenters	[1..1]	NumInGroup	
LegPricingDateBusinessCenter	[0..1]	String	Required if NoLegPricingDateBusinessCenters(41607) > 0.

Used in components: LegPricingDateTime

**180.2.2208 LegPricingDateBusinessDayConvention**

The business day convention used to adjust the pricing or fixing date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **LegPricingDateTime**

**180.2.2209 LegPricingDateTime**

The LegPricingDateTime component is a subcomponent of InstrumentLeg used to specify an adjusted or unadjusted pricing or fixing date and optionally the time, e.g. for a commodity or FX forward trade.

Name	Mult.	Type	Description
<b>LegPricingDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>LegPricingDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to the pricing dates.
<b>LegPricingDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to the pricing dates.
<b>LegPricingDateAdjusted</b>	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
LegPricingTime	[0..1]	LocalMktTime	
LegPricingTimeBusinessCenter	[0..1]	String	

Used in components: [InstrumentLeg](#)

#### **180.2.2210 LegPricingDateUnadjusted**

The unadjusted pricing or fixing date.

Type: [LocalMktDate](#)

Used in components: [LegPricingDateTime](#)

#### **180.2.2211 LegPricingTime**

The local market pricing or fixing time.

Type: [LocalMktTime](#)

Used in components: [LegPricingDateTime](#)

#### **180.2.2212 LegPricingTimeBusinessCenter**

Specifies the business center for determining the pricing or fixing time. See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in components: [LegPricingDateTime](#)

#### **180.2.2213 LegProduct**

Multileg instrument's individual security's Product.

See Product (460) field for description

Type: [int](#)

Allowed values in ProductCodeSet:

Code	Name	Description
1	AGENCY	AGENCY
2	COMMODITY	COMMODITY
3	CORPORATE	CORPORATE
4	CURRENCY	CURRENCY
5	EQUITY	EQUITY
6	GOVERNMENT	GOVERNMENT
7	INDEX	INDEX
8	LOAN	LOAN
9	MONEYMARKET	MONEYMARKET
10	MORTGAGE	MORTGAGE
11	MUNICIPAL	MUNICIPAL
12	OTHER	OTHER
13	FINANCING	FINANCING

Used in components: [InstrumentLeg](#)

#### **180.2.2214 LegProtectionTermBuyerNotifies**

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring. LegProtectionTermBuyerNotifies(41621)=Y indicates that the buyer notifies.

Type: [Boolean](#)

Used in groups: [LegProtectionTermGrp](#)

#### **180.2.2215 LegProtectionTermCurrency**

The currency of LegProtectionTermNotional(41618). Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [LegProtectionTermGrp](#)

**180.2.2216 LegProtectionTermEventBusinessCenter**

When used, the business center indicates the local time of the business center that replaces the Greenwich Mean Time in Section 3.3 of the 2003 ISDA Credit Derivatives Definitions.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegProtectionTermGrp**

**180.2.2217 LegProtectionTermEventCurrency**

Applicable currency if the event value is an amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegProtectionTermEventGrp**

**180.2.2218 LegProtectionTermEventDayType**

Day type for events that specify a period and unit.

Type: **int**

Allowed values in PaymentStreamInflationLagDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **LegProtectionTermEventGrp**

**180.2.2219 LegProtectionTermEventGrp**

The LegProtectionTermEventGrp is a repeating component within the LegProtectionTermGrp component used to report applicable CDS credit events.



Name	Mult.	Type	Description
NoLegProtectionTermEvents	[1..1]	NumInGroup	
LegProtectionTermEventType	[0..1]	String	Required if NoLegProtectionTermEvents(41625) > 0.
LegProtectionTermEventValue	[0..1]	String	
LegProtectionTermEventCurrency	[0..1]	Currency	
LegProtectionTermEventPeriod	[0..1]	int	Conditionally required when LegProtectionTermEventUnit(41630).
LegProtectionTermEventUnit	[0..1]	CodeSet	Conditionally required when LegProtectionTermEventPeriod(41629).
LegProtectionTermEventDayType	[0..1]	CodeSet	
LegProtectionTermEventRateSource	[0..1]	String	
LegProtectionTermEventQualifierGrp	[0..*]	Group	

Used in groups: [LegProtectionTermGrp](#)

#### 180.2.2220 LegProtectionTermEventMinimumSources

The minimum number of the specified public information sources that must publish information that reasonably confirms that a credit event has occurred. The market convention is two.

Type: [int](#)

Used in groups: [LegProtectionTermGrp](#)

#### 180.2.2221 LegProtectionTermEventNewsSource

A newspaper or electronic news service that may publish relevant information used in the determination of whether or not a credit event has occurred.

Type: [String](#)

Used in groups: [LegProtectionTermEventNewsSourceGrp](#)

#### 180.2.2222 LegProtectionTermEventNewsSourceGrp

LegProtectionTermEventNewsSourceGrp is a repeating subcomponent of the LegProtectionTermGrp component used to specify the particular newspapers or electronic news services that may publish relevant information used in the determination of whether or not a credit event has occurred.

Name	Mult.	Type	Description
NoLegProtectionTermEventNewsSources	[1..1]	NumInGroup	
LegProtectionTermEventNewsSource	[0..1]	String	Required if NoLegProtectionTermEventNewsSources(41614) > 0.

Used in groups: [LegProtectionTermGrp](#)

### 180.2.2223 LegProtectionTermEventPeriod

Time unit multiplier for protection term events.

Type: [int](#)

Used in groups: [LegProtectionTermEventGrp](#)

### 180.2.2224 LegProtectionTermEventQualifier

Specifies the protection term event qualifier. Used to further qualify LegProtectionTermEvent-Type(41626).

Type: [char](#)

Allowed values in ProtectionTermEventQualifierCodeSet:

Code	Name	Description
H	RestructuringMultipleHoldingObligations	Restructuring - multiple holding obligations. In relation to a restructuring credit event, unless multiple holder obligation is not specified restructurings are limited to multiple holder obligations. A multiple holder obligation means an obligation that is held by more than three holders that are not affiliates of each other and where at least two thirds of the holders must agree to the event that constitutes the restructuring credit event. ISDA 2003 Term: Multiple Holder Obligation.
E	RestructuringMultipleCreditEvent-Notices	Restructuring - multiple credit event notices. Presence of this element and value set to 'true' indicates that Section 3.9 of the 2003 Credit Derivatives Definitions shall apply. Absence of this element indicates that Section 3.9 shall not apply. NOTE: Not allowed under ISDA Credit 1999.
C	FloatingRateInterestShortfall	Floating rate interest shortfall. Indicates compounding.

---

Code	Name	Description
------	------	-------------

---

Used in groups: [LegProtectionTermEventQualifierGrp](#)

#### **180.2.2225 LegProtectionTermEventQualifierGrp**

The LegProtectionTermEventQualifierGrp is a repeating component within the LegProtectionTermEventGrp component used to specify qualifying attributes to the event.

Name	Mult.	Type	Description
<a href="#">NoLegProtectionTermEventQualifiers</a>	[1..1]	NumInGroup	
<a href="#">LegProtectionTermEventQualifier</a>	[0..1]	CodeSet	Required if NoLegProtectionTermEventQualifiers(41633) > 0.

Used in groups: [LegProtectionTermEventGrp](#)

#### **180.2.2226 LegProtectionTermEventRateSource**

Rate source for events that specify a rate source, e.g. floating rate interest shortfall.

Type: [String](#)

Used in groups: [LegProtectionTermEventGrp](#)

#### **180.2.2227 LegProtectionTermEventType**

Specifies the type of credit event applicable to the protection terms.

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Event_Types) for code list of applicable event types.

Type: [String](#)

Used in groups: [LegProtectionTermEventGrp](#)

**180.2.2228 LegProtectionTermEventUnit**

Time unit associated with protection term events.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegProtectionTermEventGrp**

**180.2.2229 LegProtectionTermEventValue**

Specifies the protection term event value appropriate to LegProtectionTermEventType(41626). See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Event_Types) for applicable event type values.

Type: **String**

Used in groups: **LegProtectionTermEventGrp**

**180.2.2230 LegProtectionTermGrp**

The LegProtectionTermGrp is a repeating component within the InstrumentLeg component used to report protection term details.

Name	Mult.	Type	Description
NoLegProtectionTerms	[1..1]	NumInGroup	
LegProtectionTermNotional	[0..1]	Amt	Required if NoLegProtectionTerms(41616) > 0.
LegProtectionTermCurrency	[0..1]	Currency	
LegProtectionTermSellerNotifies	[0..1]	Boolean	
LegProtectionTermBuyerNotifies	[0..1]	Boolean	
LegProtectionTermEventBusinessCenter	[0..1]	String	

Name	Mult.	Type	Description
LegProtectionTermStandardSources	[0..1]	Boolean	
LegProtectionTermEventMinimum-Sources	[0..1]	int	
LegProtectionTermEventNewsSource-Grp	[0..*]	Group	
LegProtectionTermEventGrp	[0..*]	Group	
LegProtectionTermObligationGrp	[0..*]	Group	
LegProtectionTermXID	[0..1]	XID	

Used in components: [InstrumentLeg](#)

### 180.2.2231 LegProtectionTermNotional

The notional amount of protection coverage.

Type: [Amt](#)

Used in groups: [LegProtectionTermGrp](#)

### 180.2.2232 LegProtectionTermObligationGrp

The LegProtectionTermObligationGrp is a repeating component within the LegProtectionTermGrp component used to report applicable credit default swap (CDS) obligations.

Name	Mult.	Type	Description
NoLegProtectionTermObligations	[1..1]	NumInGroup	
LegProtectionTermObligationType	[0..1]	String	Required if NoLegProtectionTermObligations(41635) > 0.
LegProtectionTermObligationValue	[0..1]	String	

Used in groups: [LegProtectionTermGrp](#)

### 180.2.2233 LegProtectionTermObligationType

Specifies the type of obligation applicable to the protection terms.

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Obligation_Types) for code list of applicable obligation types.

Type: **String**

Used in groups: **LegProtectionTermObligationGrp**

#### **180.2.2234 LegProtectionTermObligationValue**

The value associated with the protection term obligation specified in LegProtectionTermObligationType(41636). See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Obligation_Types) for applicable obligation type values.

Type: **String**

Used in groups: **LegProtectionTermObligationGrp**

#### **180.2.2235 LegProtectionTermSellerNotifies**

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring. LegProtectionTermSellerNotifies(41620)=Y indicates that the seller notifies.

Type: **Boolean**

Used in groups: **LegProtectionTermGrp**

#### **180.2.2236 LegProtectionTermStandardSources**

Indicates whether ISDA defined Standard Public Sources are applicable (LegProtectionTermStandardSources(41623)=Y) or not.

Type: **Boolean**

Used in groups: **LegProtectionTermGrp**

#### **180.2.2237 LegProtectionTermXID**

A named string value referenced from UnderlyingProtectionTermXIDRef(41314).

Type: **XID**

Used in groups: **LegProtectionTermGrp**

**180.2.2238 LegProvisionBreakFeeElection**

Type of fee elected for the break provision.

Type: **int**

Allowed values in ProvisionBreakFeeElectionCodeSet:

Code	Name	Description
0	FlatFee	Flat fee
1	AmortizedFee	Amortized fee
2	FundingFee	Funding fee
3	FlatAndFundingFee	Flat fee and funding fee
4	AmortizedAndFundingFee	Amortized fee and funding fee

Used in groups: **LegProvisionGrp**

**180.2.2239 LegProvisionBreakFeeRate**

Break fee election rate when the break fee is proportional to the notional. A fee rate of 5% would be represented as "0.05".

Type: **Percentage**

Used in groups: **LegProvisionGrp**

**180.2.2240 LegProvisionCalculationAgent**

Used to identify the calculation agent. The calculation agent may be identified in LegProvisionCalculationAgent(40456) or in the ProvisionParties component.

Type: **int**

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreement	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

---

Code	Name	Description
------	------	-------------

---

Used in groups: [LegProvisionGrp](#)

#### **180.2.2241 LegProvisionCashSettlCurrency**

Specifies the currency of settlement. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [LegProvisionGrp](#)

#### **180.2.2242 LegProvisionCashSettlCurrency2**

Specifies the currency of settlement for a cross-currency provision. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [LegProvisionGrp](#)

#### **180.2.2243 LegProvisionCashSettlMethod**

An ISDA defined cash settlement method used for the determination of the applicable cash settlement amount. The method is defined in the 2006 ISDA Definitions, Section 18.3. Cash Settlement Methods, paragraph (e).

Type: [int](#)

Allowed values in ProvisionCashSettlMethodCodeSet:

---

Code	Name	Description
------	------	-------------

---

0	CashPrice	Cash price
1	CashPriceAlternate	Cash price alternate
2	ParYieldCurveAdjusted	Par yield curve adjusted
3	ZeroCouponYieldCurveAdjusted	Zero coupon yield curve adjusted
4	ParYieldCurveUnadjusted	Par yield curve unadjusted
5	CrossCurrency	Cross currency
6	CollateralizedPrice	Collateralized price

---

Used in groups: [LegProvisionGrp](#)



**180.2.2244 LegProvisionCashSettlPaymentDate**

The cash settlement payment date, unadjusted or adjusted depending on LegProvisionCashSettlPaymentDateType(40521).

Type: **LocalMktDate**

Used in groups: **LegProvisionCashSettlPaymentFixedDateGrp**

**180.2.2245 LegProvisionCashSettlPaymentDateBusinessCenter**

The business center calendar used to adjust the provisional cash settlement payment's termination, or relative termination, date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegProvisionCashSettlPaymentDateBusinessCenterGrp**

**180.2.2246 LegProvisionCashSettlPaymentDateBusinessCenterGrp**

LegProvisionCashSettlPaymentDateBusinessCenterGrp is a repeating subcomponent within the LegProvisionCashSettlPaymentDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegProvisionCashSettlPaymentDateBusinessCenters	[1..1]	NumInGroup	
LegProvisionCashSettlPaymentDateBusinessCenter	[0..1]	String	Required if NoLegProvisionCashSettlPaymentDateBusinessCenters(40934) > 0.

Used in components: **LegProvisionCashSettlPaymentDates**

**180.2.2247 LegProvisionCashSettlPaymentDateBusinessDayConvention**

The business day convention used to adjust the provisional cash settlement payment's termination, or relative termination, date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **LegProvisionCashSettlPaymentDates**

#### **180.2.2248 LegProvisionCashSettlPaymentDateOffsetDayType**

Specifies the day type of the provision's relative cash settlement payment date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegProvisionCashSettlPaymentDates**

#### **180.2.2249 LegProvisionCashSettlPaymentDateOffsetPeriod**

Time unit multiplier for the relative cash settlement payment date offset.

Type: **int**

Used in components: **LegProvisionCashSettlPaymentDates**

#### **180.2.2250 LegProvisionCashSettlPaymentDateOffsetUnit**

Time unit associated with the relative cash settlement payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegProvisionCashSettlPaymentDates**

#### **180.2.2251 LegProvisionCashSettlPaymentDateRangeFirst**

The first date in range when a settlement date range is provided.

Type: **LocalMktDate**

Used in components: **LegProvisionCashSettlPaymentDates**

#### **180.2.2252 LegProvisionCashSettlPaymentDateRangeLast**

The last date in range when a settlement date range is provided.

Type: **LocalMktDate**

Used in components: **LegProvisionCashSettlPaymentDates**

#### **180.2.2253 LegProvisionCashSettlPaymentDateRelativeTo**

Specifies the anchor date when the cash settlement payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegProvisionCashSettlPaymentDates**

#### **180.2.2254 LegProvisionCashSettlPaymentDates**

The LegProvisionCashSettlPaymentDates component is a sub-component within the LegProvisionGrp component used to report the cash settlement payment dates defined in the provision.

<b>Name</b>	<b>Mult.</b>	<b>Type</b>	<b>Description</b>
<b>LegProvisionCashSettlPaymentDate-BusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg provision cash settlement payment dates.
<b>LegProvisionCashSettlPaymentDate-BusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg provision cash settlement payment dates.
<b>LegProvisionCashSettlPayment-DateRelativeTo</b>	[0..1]	int	
<b>LegProvisionCashSettlPaymentDate-OffsetPeriod</b>	[0..1]	int	Conditionally required when LegProvisionCash-SettlPaymentDateOffsetUnit(40520) is specified.
<b>LegProvisionCashSettlPaymentDate-OffsetUnit</b>	[0..1]	CodeSet	Conditionally required when LegProvisionCash-SettlPaymentDateOffsetPeriod(40519) is specified.
<b>LegProvisionCashSettlPaymentDate-OffsetDayType</b>	[0..1]	CodeSet	
<b>LegProvisionCashSettlPaymentDateRangeFirst</b>	[0..1]	LocalMktDate	
<b>LegProvisionCashSettlPaymentDateRangeLast</b>	[0..1]	LocalMktDate	
<b>LegProvisionCashSettlPaymentFixed-DateGrp</b>	[0..*]	Group	

Used in groups: **LegProvisionGrp**

#### **180.2.2255 LegProvisionCashSettlPaymentDateType**

Specifies the type of date (e.g. adjusted for holidays).

Type: **int**

Allowed values in ProvisionCashSettlPaymentDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **LegProvisionCashSettlPaymentFixedDateGrp**

#### **180.2.2256 LegProvisionCashSettlPaymentFixedDateGrp**

The ProvisionCashSettlPaymentFixedDateGrp is a repeating component within the ProvisionCashSettlPaymentDates component used to report fixed cash settlement payment dates defined in the provision.

Name	Mult.	Type	Description
NoLegProvisionCashSettlPayment-Dates	[1..1]	NumInGroup	
LegProvisionCashSettlPaymentDate	[0..1]	LocalMktDate	Required if NoLegProvisionCashSettlPaymentDates (40473) > 0.
LegProvisionCashSettlPaymentDate-Type	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: **LegProvisionCashSettlPaymentDates**

#### **180.2.2257 LegProvisionCashSettlQuoteReferencePage**

Identifies the reference "page" from the quote source.

Type: **String**

Used in components: **LegProvisionCashSettlQuoteSource**

**180.2.2258 LegProvisionCashSettlQuoteSource**

Identifies the source of quote information.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: **LegProvisionCashSettlQuoteSource**

**180.2.2259 LegProvisionCashSettlQuoteSource**

The LegProvisionCashSettlQuoteSource is a subcomponent of the LEgProvisionGrp component used to specify the reference source for currency or rate quote for cash settlement purposes.

Name	Mult.	Type	Description
<b>LegProvisionCashSettlQuoteSource</b>	[0..1]	CodeSet	
<b>LegProvisionCashSettlQuoteReferencePage</b>	[0..1]	String	

Used in groups: **LegProvisionGrp**

**180.2.2260 LegProvisionCashSettlQuoteType**

Identifies the type of quote to be used.

Type: **int**

Allowed values in ProvisionCashSettlQuoteTypeCodeSet:

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer
3	ExercisingPartyPays	Exercising party pays. See 2000 ISDA Definitions, Section 17.2, Certain Definitions Relating to Cash Settlement, paragraph (j) for definition of "exercising party pays".

Used in groups: [LegProvisionGrp](#)

#### **180.2.2261 LegProvisionCashSettlValueDateAdjusted**

The adjusted cash settlement value date.

Type: [LocalMktDate](#)

Used in components: [LegProvisionCashSettlValueDates](#)

#### **180.2.2262 LegProvisionCashSettlValueDateBusinessCenter**

The business center calendar used to adjust the provision's cash settlement valuation date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [LegProvisionCashSettlValueDateBusinessCenterGrp](#)

#### **180.2.2263 LegProvisionCashSettlValueDateBusinessCenterGrp**

`LegProvisionCashSettlValueDateBusinessCenterGrp` is a repeating subcomponent within the `LegProvisionCashSettlValueDate` component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the `LegDateAdjustment` component in `InstrumentLeg`.

Name	Mult.	Type	Description
NoLegProvisionCashSettlValueDate-BusinessCenters	[1..1]	NumInGroup	
LegProvisionCashSettlValueDateBusinessCenter	[0..1]	String	Required if NoLegProvisionCashSettlValueDate-BusinessCenters(40935) > 0.

Used in components: [LegProvisionCashSettlValueDates](#)

#### 180.2.2264 LegProvisionCashSettlValueDateBusinessDayConvention

The business day convention used to adjust the provision's cash settlement valuation date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegProvisionCashSettlValueDates](#)

#### 180.2.2265 LegProvisionCashSettlValueDateOffsetDayType

Specifies the day type of the provision's relative cash settlement value date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:



Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegProvisionCashSettlValueDates](#)

#### **180.2.2266 LegProvisionCashSettlValueDateOffsetPeriod**

Time unit multiplier for the relative cash settlement value date offset.

Type: [int](#)

Used in components: [LegProvisionCashSettlValueDates](#)

#### **180.2.2267 LegProvisionCashSettlValueDateOffsetUnit**

Time unit associated with the relative cash settlement value date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegProvisionCashSettlValueDates](#)

#### **180.2.2268 LegProvisionCashSettlValueDateRelativeTo**

Specifies the anchor date when the cash settlement value date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegProvisionCashSettlValueDates**

### 180.2.2269 LegProvisionCashSettlValueDates

The LegProvisionCashSettlValueDates component is a subcomponent within the LegProvisionGrp component used to report the cash settlement value date and time defined in the provision.

Name	Mult.	Type	Description
LegProvisionCashSettlValueTime	[0..1]	LocalMktTime	
LegProvisionCashSettlValueTimeBusinessCenter	[0..1]	String	
LegProvisionCashSettlValueDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg provision cash settlement value date.
LegProvisionCashSettlValueDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg provision cash settlement value date.
LegProvisionCashSettlValueDateRelativeTo	[0..1]	int	
LegProvisionCashSettlValueDateOffsetPeriod	[0..1]	int	Conditionally required when LegProvisionCashSettlValueDateOffsetUnit(40530) is specified.
LegProvisionCashSettlValueDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegProvisionCashSettlValueDateOffsetPeriod(40529) is specified.
LegProvisionCashSettlValueDateOffsetDayType	[0..1]	CodeSet	
LegProvisionCashSettlValueDateAdjusted	[0..1]	LocalMktDate	

Used in groups: **LegProvisionGrp**

**180.2.2270 LegProvisionCashSettlValueTime**

A time specified in 24-hour format, e.g. 11am would be represented as 11:00:00. The time of the cash settlement valuation date when the cash settlement amount will be determined according to the cash settlement method if the parties have not otherwise been able to agree to the cash settlement amount.

Type: **LocalMktTime**

Used in components: **LegProvisionCashSettlValueDates**

**180.2.2271 LegProvisionCashSettlValueTimeBusinessCenter**

Identifies the business center calendar used with the provision's cash settlement valuation time.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **LegProvisionCashSettlValueDates**

**180.2.2272 LegProvisionDateAdjusted**

The adjusted date of the provision.

Type: **LocalMktDate**

Used in groups: **LegProvisionGrp**

**180.2.2273 LegProvisionDateBusinessCenter**

The business center calendar used to adjust the instrument leg's provision's date, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegProvisionDateBusinessCenterGrp**

**180.2.2274 LegProvisionDateBusinessCenterGrp**

**LegProvisionDateBusinessCenterGrp** is a repeating subcomponent within the **LegProvisionGrp** component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used

only to override the business centers defined in the LegDateAdjustment component in Instrument-Leg.

Name	Mult.	Type	Description
NoLegProvisionDateBusinessCenters	[1..1]	NumInGroup	
LegProvisionDateBusinessCenter	[0..1]	String	Required if NoLegProvisionDateBusinessCenters(40939) > 0.

Used in groups: [LegProvisionGrp](#)

### 180.2.2275 LegProvisionDateBusinessDayConvention

The business day convention used to adjust the instrument leg's provision's date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [LegProvisionGrp](#)

### 180.2.2276 LegProvisionDateTenorPeriod

Time unit multiplier for the leg provision's tenor period.

Type: [int](#)

Used in groups: [LegProvisionGrp](#)

**180.2.2277 LegProvisionDateTenorUnit**

Time unit associated with the leg provision's tenor period.

Type: **String**

Allowed values in ProvisionDateTenorUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegProvisionGrp**

**180.2.2278 LegProvisionDateUnadjusted**

The unadjusted date of the provision.

Type: **LocalMktDate**

Used in groups: **LegProvisionGrp**

**180.2.2279 LegProvisionGrp**

The LegProvisionGrp is a repeating subcomponent of the InstrumentLeg component used to detail the provisions associated with the instrument.

Name	Mult.	Type	Description
<b>NoLegProvisions</b>	[1..1]	NumInGroup	
<b>LegProvisionType</b>	[0..1]	CodeSet	Required if NoLegProvisions(40448) > 0.
<b>LegProvisionDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>LegProvisionDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the instrument's leg provision.

Name	Mult.	Type	Description
LegProvisionDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the instrument's leg provision.
LegProvisionDateAdjusted	[0..1]	LocalMktDate	
LegProvisionDateTenorPeriod	[0..1]	int	Conditionally required when LegProvisionDateTenorUnit(40455) is specified.
LegProvisionDateTenorUnit	[0..1]	CodeSet	Conditionally required when LegProvisionDateTenorPeriod(40454) is specified.
LegProvisionBreakFeeElection	[0..1]	CodeSet	
LegProvisionBreakFeeRate	[0..1]	Percentage	
LegProvisionCalculationAgent	[0..1]	CodeSet	
LegProvisionOptionSinglePartyBuyer-Side	[0..1]	CodeSet	
LegProvisionOptionSinglePartySeller-Side	[0..1]	CodeSet	
LegProvisionCashSettlValueDates	[0..1]	Component	
LegProvisionOptionExerciseDates	[0..1]	Component	
LegProvisionOptionExpirationDate	[0..1]	Component	
LegProvisionOptionRelevantUnderlyingDate	[0..1]	Component	
LegProvisionOptionExerciseStyle	[0..1]	CodeSet	
LegProvisionOptionExerciseMultipleNotional	[0..1]	Amt	
LegProvisionOptionExerciseMinimumNotional	[0..1]	Amt	
LegProvisionOptionExerciseMaximumNotional	[0..1]	Amt	
LegProvisionOptionMinimumNumber	[0..1]	int	
LegProvisionOptionMaximumNumber	[0..1]	int	
LegProvisionOptionExerciseConfirmation	[0..1]	Boolean	
LegProvisionCashSettlPaymentDates	[0..1]	Component	
LegProvisionCashSettlMethod	[0..1]	CodeSet	
LegProvisionCashSettlCurrency	[0..1]	Currency	
LegProvisionCashSettlCurrency2	[0..1]	Currency	

Name	Mult.	Type	Description
LegProvisionCashSettlQuoteType	[0..1]	CodeSet	
LegProvisionCashSettlQuoteSource	[0..1]	Component	
LegProvisionText	[0..1]	String	
EncodedLegProvisionTextLen	[0..1]	Length	Must be set if EncodedLegProvisionText(40981) field is specified and must immediately precede it.
EncodedLegProvisionText	[0..1]	data	Encoded (non-ASCII characters) representation of the LegProvisionText(40472) field in the encoded format specified via the MessageEncoding(347) field.
LegProvisionParties	[0..*]	Group	

Used in components: **InstrumentLeg**

#### 180.2.2280 LegProvisionOptionExerciseBoundsFirstDateUnadjusted

The unadjusted first date of a schedule. This can be used to restrict the range of exercise dates when they are relative.

Type: **LocalMktDate**

Used in components: **LegProvisionOptionExerciseDates**

#### 180.2.2281 LegProvisionOptionExerciseBoundsLastDateUnadjusted

The unadjusted last date of a schedule. This can be used to restrict the range of exercise dates when they are relative.

Type: **LocalMktDate**

Used in components: **LegProvisionOptionExerciseDates**

#### 180.2.2282 LegProvisionOptionExerciseBusinessCenter

The business center calendar used to adjust the instrument leg's provision's option exercise date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegProvisionOptionExerciseBusinessCenterGrp**

**180.2.2283 LegProvisionOptionExerciseBusinessCenterGrp**

LegProvisionOptionExerciseBusinessCenterGrp is a repeating subcomponent within the LegProvisionOptionExerciseDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegProvisionOptionExerciseBusinessCenters	[1..1]	NumInGroup	
LegProvisionOptionExerciseBusinessCenter	[0..1]	String	Required if NoLegProvisionOptionExerciseBusinessCenters(40936) > 0.

Used in components: [LegProvisionOptionExerciseDates](#)

**180.2.2284 LegProvisionOptionExerciseBusinessDayConvention**

The business day convention used to adjust the instrument leg's provision's option exercise date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegProvisionOptionExerciseDates](#)



**180.2.2285 LegProvisionOptionExerciseConfirmation**

Used to indicate whether follow-up confirmation of exercise (written or electronic) is required following telephonic notice by the buyer to the seller or seller's agent.

Type: **Boolean**

Used in groups: **LegProvisionGrp**

**180.2.2286 LegProvisionOptionExerciseDates**

The LegProvisionOptionExerciseDates is a subcomponent within the LegProvisionGrp component used to report the option exercise dates and times defined in the provision.

Name	Mult.	Type	Description
<b>LegProvisionOptionExerciseBusiness-DayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg provision option exercise dates.
<b>LegProvisionOptionExerciseBusiness-CenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg provision option exercise dates.
<b>LegProvisionOptionExerciseFixedDate-Grp</b>	[0..*]	Group	
<b>LegProvisionOptionExerciseEarliestDateOffsetPeriod</b>	[0..1]	int	Conditionally required when LegProvisionOptionExerciseEarliestDateUnit(40479) is specified.
<b>LegProvisionOptionExerciseEarliestDateOffsetUnit</b>	[0..1]	CodeSet	Conditionally required when LegProvisionOptionExerciseEarliestDatePeriod(40478) is specified.
<b>LegProvisionOptionExerciseFrequencyPeriod</b>	[0..1]	int	Conditionally required when LegProvisionOptionExerciseFrequencyUnit(40481) is specified.
<b>LegProvisionOptionExerciseFrequencyUnit</b>	[0..1]	CodeSet	Conditionally required when LegProvisionOptionExerciseFrequencyPeriod(40480) is specified.
<b>LegProvisionOptionExerciseStartDate-Unadjusted</b>	[0..1]	LocalMktDate	
<b>LegProvisionOptionExerciseStartDateRelativeTo</b>	[0..1]	int	

Name	Mult.	Type	Description
LegProvisionOptionExerciseStartDate-OffsetPeriod	[0..1]	int	Conditionally required when LegProvisionOptionExerciseStartDateOffsetUnit(40485) is specified.
LegProvisionOptionExerciseStartDate-OffsetUnit	[0..1]	CodeSet	Conditionally required when LegProvisionOptionExerciseStartDateOffsetPeriod(40484) is specified.
LegProvisionOptionExerciseStartDate-OffsetDayType	[0..1]	CodeSet	
LegProvisionOptionExerciseStartDateAdjusted	[0..1]	LocalMktDate	
LegProvisionOptionExercisePeriodSkip	[0..1]	int	
LegProvisionOptionExerciseBounds-FirstDateUnadjusted	[0..1]	LocalMktDate	
LegProvisionOptionExerciseBounds-LastDateUnadjusted	[0..1]	LocalMktDate	
LegProvisionOptionExerciseEarliest-Time	[0..1]	LocalMktTime	
LegProvisionOptionExerciseEarliest-TimeBusinessCenter	[0..1]	String	
LegProvisionOptionExerciseLatest-Time	[0..1]	LocalMktTime	
LegProvisionOptionExerciseLatest-TimeBusinessCenter	[0..1]	String	

Used in groups: [LegProvisionGrp](#)

#### 180.2.2287 LegProvisionOptionExerciseEarliestDateOffsetPeriod

Time unit multiplier for the interval to the first (and possibly only) exercise date in the exercise period.

Type: [int](#)

Used in components: [LegProvisionOptionExerciseDates](#)

#### 180.2.2288 LegProvisionOptionExerciseEarliestDateOffsetUnit

Time unit associated with the interval to the first (and possibly only) exercise date in the exercise period.

Type: **String**

Allowed values in ProvisionOptionExerciseEarliestDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegProvisionOptionExerciseDates**

#### **180.2.2289 LegProvisionOptionExerciseEarliestTime**

The earliest time at which notice of exercise can be given by the buyer to the seller (or seller's agent) (i) on the expiration date, in the case of a European style option, (ii) on each bermuda option exercise date and the expiration date, in the case of a Bermuda style option the commencement date to, and including, the expiration date, in the case of an American option.

Type: **LocalMktTime**

Used in components: **LegProvisionOptionExerciseDates**

#### **180.2.2290 LegProvisionOptionExerciseEarliestTimeBusinessCenter**

Identifies the business center calendar used with the provision's earliest time for notice of exercise.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **LegProvisionOptionExerciseDates**

#### **180.2.2291 LegProvisionOptionExerciseFixedDate**

A predetermined option exercise date unadjusted or adjusted depending on LegProvisionOptionExerciseFixedDateType(40497).

Type: **LocalMktDate**

Used in groups: **LegProvisionOptionExerciseFixedDateGrp**

**180.2.2292 LegProvisionOptionExerciseFixedDateGrp**

The LegProvisionOptionExerciseFixedDateGrp is a repeating component within the LegProvisionOptionExerciseDates component used to report an array of unadjusted or adjusted fixed exercise dates.

Name	Mult.	Type	Description
NoLegProvisionOptionExerciseFixedDates	[1..1]	NumInGroup	
LegProvisionOptionExerciseFixedDate	[0..1]	LocalMktDate	Required if NoLegProvisionOptionExerciseFixedDates(40495) > 0.
LegProvisionOptionExerciseFixedDate-Type	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [LegProvisionOptionExerciseDates](#)

**180.2.2293 LegProvisionOptionExerciseFixedDateType**

Specifies the type of date (e.g. adjusted for holidays).

Type: [int](#)

Allowed values in ProvisionOptionExerciseFixedDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [LegProvisionOptionExerciseFixedDateGrp](#)

**180.2.2294 LegProvisionOptionExerciseFrequencyPeriod**

Time unit multiplier for subsequent exercise dates in the exercise period following the earliest exercise date. An interval of 1 day should be used to indicate an American style exercise period.

Type: [int](#)

Used in components: [LegProvisionOptionExerciseDates](#)

**180.2.2295 LegProvisionOptionExerciseFrequencyUnit**

Time unit associated with subsequent exercise dates in the exercise period following the earliest exercise date.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2296 LegProvisionOptionExerciseLatestTime**

For a Bermuda or American style option, the latest time on an exercise business day (excluding the expiration date) within the exercise period that notice can be given by the buyer to the seller or seller's agent. Notice of exercise given after this time will be deemed to have been given on the next exercise business day.

Type: **LocalMktTime**

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2297 LegProvisionOptionExerciseLatestTimeBusinessCenter**

Identifies the business center calendar used with the provision's latest time for notice of exercise.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2298 LegProvisionOptionExerciseMaximumNotional**

The maximum notional amount that can be exercised on a given exercise date.

Type: **Amt**

Used in groups: **LegProvisionGrp**

**180.2.2299 LegProvisionOptionExerciseMinimumNotional**

The minimum notional amount that can be exercised on a given exercise date.

Type: **Amt**

Used in groups: **LegProvisionGrp**

**180.2.2300 LegProvisionOptionExerciseMultipleNotional**

A notional amount which restricts the amount of notional that can be exercised when partial exercise or multiple exercise is applicable. The integral multiple amount defines a lower limit of notional that can be exercised and also defines a unit multiple of notional that can be exercised, i.e. only integer multiples of this amount can be exercised.

Type: **Amt**

Used in groups: **LegProvisionGrp**

**180.2.2301 LegProvisionOptionExercisePeriodSkip**

The number of periods in the referenced date schedule that are between each date in the relative date schedule. Thus a skip of 2 would mean that dates are relative to every second date in the referenced schedule. If present this should have a value greater than 1.

Type: **int**

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2302 LegProvisionOptionExerciseStartDateAdjusted**

The adjusted first day of the exercise period for an American style option.

Type: **LocalMktDate**

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2303 LegProvisionOptionExerciseStartDateOffsetDayType**

Specifies the day type of the provision's relative option exercise start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2304 LegProvisionOptionExerciseStartDateOffsetPeriod**

Time unit multiplier for the relative option exercise start date offset.

Type: **int**

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2305 LegProvisionOptionExerciseStartDateOffsetUnit**

Time unit associated with the relative option exercise start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2306 LegProvisionOptionExerciseStartDateRelativeTo**

Specifies the anchor date when the option exercise start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2307 LegProvisionOptionExerciseStartDateUnadjusted**

The unadjusted first day of the exercise period for an American style option.

Type: **LocalMktDate**

Used in components: **LegProvisionOptionExerciseDates**

**180.2.2308 LegProvisionOptionExerciseStyle**

The instrument provision option exercise style.

Type: **int**

Allowed values in ExerciseStyleCodeSet:

Code	Name	Description
0	European	European
1	American	American
2	Bermuda	Bermuda
99	Other	Other

Used in groups: **LegProvisionGrp**

**180.2.2309 LegProvisionOptionExpirationDateAdjusted**

The adjusted last date within an exercise period for an American style option. For a European style option it is the only date within the exercise period.

Type: **LocalMktDate**

Used in components: **LegProvisionOptionExpirationDate**



**180.2.2310 LegProvisionOptionExpirationDateBusinessCenter**

The business center calendar used to adjust the instrument leg's provision's option expiration date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegProvisionOptionExpirationDateBusinessCenterGrp**

**180.2.2311 LegProvisionOptionExpirationDateBusinessCenterGrp**

LegProvisionOptionExpirationDateBusinessCenterGrp is a repeating subcomponent within the LegProvisionOptionExpirationDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegProvisionOptionExpirationDate-BusinessCenters	[1..1]	NumInGroup	
LegProvisionOptionExpirationDate-BusinessCenter	[0..1]	String	Required if NoLegProvisionOptionExpirationDate-BusinessCenters(40937) > 0.

Used in components: **LegProvisionOptionExpirationDate**

**180.2.2312 LegProvisionOptionExpirationDateBusinessDayConvention**

The business day convention used to adjust the instrument leg's provision's option expiration date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)

Code	Name	Description
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegProvisionOptionExpirationDate](#)

### 180.2.2313 LegProvisionOptionExpirationDate

The LegProvisionOptionExerciseDate is a subcomponent within the LegProvisionGrp component used to report the option expiration date and times defined in the provision.

Name	Mult.	Type	Description
<a href="#">LegProvisionOptionExpirationDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegProvisionOptionExpirationDate-BusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg provision option expiration date.
<a href="#">LegProvisionOptionExpirationDate-BusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg provision option expiration date.
<a href="#">LegProvisionOptionExpirationDateRelativeTo</a>	[0..1]	int	
<a href="#">LegProvisionOptionExpirationDateOffsetPeriod</a>	[0..1]	int	Conditionally required when LegProvisionOptionExpirationDateOffsetUnit(40503) is specified.
<a href="#">LegProvisionOptionExpirationDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegProvisionOptionExpirationDateOffsetPeriod(40502) is specified.
<a href="#">LegProvisionOptionExpirationDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">LegProvisionOptionExpirationDateAdjusted</a>	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
LegProvisionOptionExpirationTime	[0..1]	LocalMktTime	
LegProvisionOptionExpirationTime-BusinessCenter	[0..1]	String	

Used in groups: [LegProvisionGrp](#)

#### 180.2.2314 LegProvisionOptionExpirationDateOffsetDayType

Specifies the day type of the provision's relative option expiration date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegProvisionOptionExpirationDate](#)

#### 180.2.2315 LegProvisionOptionExpirationDateOffsetPeriod

Time unit multiplier for the relative option expiration date offset.

Type: [int](#)

Used in components: [LegProvisionOptionExpirationDate](#)

#### 180.2.2316 LegProvisionOptionExpirationDateOffsetUnit

Time unit associated with the relative option expiration date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegProvisionOptionExpirationDate](#)

#### **180.2.2317 LegProvisionOptionExpirationDateRelativeTo**

Specifies the anchor date when the option expiration date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [LegProvisionOptionExpirationDate](#)

#### **180.2.2318 LegProvisionOptionExpirationDateUnadjusted**

The unadjusted last day within an exercise period for an American style option. For a European style option it is the only day within the exercise period.

Type: [LocalMktDate](#)

Used in components: [LegProvisionOptionExpirationDate](#)

#### **180.2.2319 LegProvisionOptionExpirationTime**

The latest time for exercise on the expiration date.

Type: [LocalMktTime](#)

Used in components: [LegProvisionOptionExpirationDate](#)

**180.2.2320 LegProvisionOptionExpirationTimeBusinessCenter**

Identifies the business center calendar used with the provision's latest exercise time on expiration date.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **LegProvisionOptionExpirationDate**

**180.2.2321 LegProvisionOptionMaximumNumber**

The maximum number of options that can be exercised on a given exercise date. If the number is not specified, it means that the maximum number of options corresponds to the remaining unexercised options.

Type: **int**

Used in groups: **LegProvisionGrp**

**180.2.2322 LegProvisionOptionMinimumNumber**

The minimum number of options that can be exercised on a given exercise date.

Type: **int**

Used in groups: **LegProvisionGrp**

**180.2.2323 LegProvisionOptionRelevantUnderlyingDateAdjusted**

The adjusted date on the underlying set by the exercise of an option. What this date is depends on the option (e.g. in a swaption it is the swap effective date, in an extendible/cancelable provision it is the swap termination date).

Type: **LocalMktDate**

Used in components: **LegProvisionOptionRelevantUnderlyingDate**

**180.2.2324 LegProvisionOptionRelevantUnderlyingDateBusinessCenter**

The business center calendar used to adjust the instrument leg's provision's option underlying date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegProvisionOptionRelevantUnderlyingDateBusinessCenterGrp**

### 180.2.2325 LegProvisionOptionRelevantUnderlyingDateBusinessCenterGrp

LegProvisionOptionRelevantUnderlyingDateBusinessCenterGrp is a repeating subcomponent within the LegProvisionOptionRelevantUnderlyingDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegProvisionOptionRelevantUnderlyingDateBusinessCenters	[1..1]	NumInGroup	
LegProvisionOptionRelevantUnderlyingDateBusinessCenter	[0..1]	String	Required if NoLegProvisionOptionRelevantUnderlyingDateBusinessCenters(40938) > 0.

Used in components: **LegProvisionOptionRelevantUnderlyingDate**

### 180.2.2326 LegProvisionOptionRelevantUnderlyingDateBusinessDayConvention

The business day convention used to adjust the instrument leg's provision's option relevant underlying date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.

Code	Name	Description
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegProvisionOptionRelevantUnderlyingDate](#)

### 180.2.2327 LegProvisionOptionRelevantUnderlyingDate

The LegProvisionOptionRelevantUnderlyingDate is a subcomponent within the LegProvisionGrp component used to report the option relevant underlyingdate defined in the provision.

Name	Mult.	Type	Description
<a href="#">LegProvisionOptionRelevantUnderlyingDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegProvisionOptionRelevantUnderlyingDateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg provision option relevant underlying date.
<a href="#">LegProvisionOptionRelevantUnderlyingDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg provision option relevant underlying date.
<a href="#">LegProvisionOptionRelevantUnderlyingDateRelativeTo</a>	[0..1]	int	
<a href="#">LegProvisionOptionRelevantUnderlyingDateOffsetPeriod</a>	[0..1]	int	Conditionally required when LegProvisionOptionRelevantUnderlyingDateOffsetUnit(40513) is specified.
<a href="#">LegProvisionOptionRelevantUnderlyingDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegProvisionOptionRelevantUnderlyingDateOffsetPeriod(40512) is specified.
<a href="#">LegProvisionOptionRelevantUnderlyingDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">LegProvisionOptionRelevantUnderlyingDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [LegProvisionGrp](#)

**180.2.2328 LegProvisionOptionRelevantUnderlyingDateOffsetDayType**

Specifies the day type of the provision's relative option relevant underlying date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegProvisionOptionRelevantUnderlyingDate**

**180.2.2329 LegProvisionOptionRelevantUnderlyingDateOffsetPeriod**

Time unit multiplier for the relative option relevant underlying date offset.

Type: **int**

Used in components: **LegProvisionOptionRelevantUnderlyingDate**

**180.2.2330 LegProvisionOptionRelevantUnderlyingDateOffsetUnit**

Time unit associated with the relative option relevant underlying date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegProvisionOptionRelevantUnderlyingDate**



**180.2.2331 LegProvisionOptionRelevantUnderlyingDateRelativeTo**

Specifies the anchor date when the date relevant to the underlying trade on exercise is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegProvisionOptionRelevantUnderlyingDate**

**180.2.2332 LegProvisionOptionRelevantUnderlyingDateUnadjusted**

The unadjusted date on the underlying set by the exercise of an option. What this date is depends on the option (e.g. in a swaption it is the swap effective date, in an extendible/cancelable provision it is the swap termination date).

Type: **LocalMktDate**

Used in components: **LegProvisionOptionRelevantUnderlyingDate**

**180.2.2333 LegProvisionOptionSinglePartyBuyerSide**

If optional early termination is not available to both parties then this component identifies the buyer of the option through its side of the trade.

Type: **int**

Allowed values in ProvisionOptionSinglePartyBuyerSideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **LegProvisionGrp**

**180.2.2334 LegProvisionOptionSinglePartySellerSide**

If optional early termination is not available to both parties then this component identifies the seller of the option through its side of the trade.

Type: **int**

Allowed values in ProvisionOptionSinglePartyBuyerSideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: [LegProvisionGrp](#)

### 180.2.2335 LegProvisionParties

LegProvisionParties is a repeating component within the LegProvision component used to report the parties identified in the contract provision.

Name	Mult.	Type	Description
<a href="#">NoLegProvisionPartyIDs</a>	[1..1]	NumInGroup	
<a href="#">LegProvisionPartyID</a>	[0..1]	String	Required if NoLegProvisionPartyIDs(40533) > 0.
<a href="#">LegProvisionPartyIDSource</a>	[0..1]	CodeSet	Required if NoLegProvisionPartyIDs(40533) > 0.
<a href="#">LegProvisionPartyRole</a>	[0..1]	CodeSet	Required if NoLegProvisionPartyIDs(40533) > 0.
<a href="#">LegProvisionPartyRoleQualifier</a>	[0..1]	CodeSet	
<a href="#">LegProvisionPtysSubGrp</a>	[0..*]	Group	

Used in groups: [LegProvisionGrp](#)

### 180.2.2336 LegProvisionPartyID

The party identifier/code for the payment settlement party.

Type: [String](#)

Used in groups: [LegProvisionParties](#)

### 180.2.2337 LegProvisionPartyIDSource

Identifies the class or source of LegProvisionPartyID(40534).

Type: [char](#)

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.

Code	Name	Description
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: [LegProvisionParties](#)

### 180.2.2338 LegProvisionPartyRole

Identifies the type or role of LegProvisionPartyID(40534) specified.

Type: [int](#)

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)

Code	Name	Description
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party

Code	Name	Description
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)

Code	Name	Description
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionV- enue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm

Code	Name	Description
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor



Code	Name	Description
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **LegProvisionParties**

**180.2.2339 LegProvisionPartyRoleQualifier**

Used to further qualify the value of LegProvisionPartyRole(40536).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange

Code	Name	Description
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: [LegProvisionParties](#)

#### 180.2.2340 LegProvisionPartySubID

Party sub-identifier, if applicable, for LegProvisionPartyRole(40536).

Type: [String](#)

Used in groups: [LegProvisionPtysSubGrp](#)

**180.2.2341 LegProvisionPartySubIDType**

The type of LegProvisionPartySubID(40538) value.

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker

Code	Name	Description
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.

Code	Name	Description
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.



Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **LegProvisionPtysSubGrp**

**180.2.2342 LegProvisionPtysSubGrp**

LegProvisionSubParties is a repeating component within the LegProvisionParties component used to extend information to be reported for the party.

Name	Mult.	Type	Description
NoLegProvisionPartySubIDs	[1..1]	NumInGroup	
LegProvisionPartySubID	[0..1]	String	Required if NoLegProvisionPartySubIDs(40537) > 0.
LegProvisionPartySubIDType	[0..1]	CodeSet	Required if NoLegProvisionPartySubIDs(40537) > 0.

Used in groups: [LegProvisionParties](#)

**180.2.2343 LegProvisionText**

Free form text to specify additional information or enumeration description when a standard value does not apply.

Type: [String](#)

Used in groups: [LegProvisionGrp](#)

**180.2.2344 LegProvisionType**

Type of provisions.

Type: [int](#)

Allowed values in ProvisionTypeCodeSet:

Code	Name	Description
0	MandatoryEarlyTermination	Mandatory early termination
1	OptionalEarlyTermination	Optional early termination
2	Cancelable	Cancelable
3	Extendable	Extendable. The contract can be extended by either party usually with a specific time notice prior to the expiry date. In the context of EU SFTR reporting this corresponds to "termination optionality" code "ETSB".

Code	Name	Description
4	MutualEarlyTermination	Mutual early termination
5	Evergreen	Evergreen. The contract automatically renews after the expiry date until one party gives the other notice to terminate. In the context of EU SFTR reporting this corresponds to "termination optionality" code "EGRN".
6	Callable	Callable. Contract is callable.
7	Puttable	Puttable. Contract is puttable.

Used in groups: [LegProvisionGrp](#)

### 180.2.2345 LegPutOrCall

Indicates whether a leg option contract is a put, call, chooser or undetermined.

Type: [int](#)

Allowed values in PutOrCallCodeSet:

Code	Name	Description
0	Put	Put. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate receiver or into a CDS contract as a seller of protection or for the case of a Floor.
1	Call	Call. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate payer or into a CDS contract as a buyer of protection or for the case of a Cap.
2	Other	Other. In the context of ESMA RTS 22 reporting, this value may be used when, at the time of execution, the option right cannot be determined.
3	Chooser	Chooser. Indicates that the option buyer may choose to buy or sell the underlying security on exercise or if a Swaption to pay or receive the underlying IRS cash flow stream or to buy or sell CDS protection.

Used in components: [InstrumentLeg](#)

**180.2.2346 LegQty**

This field is deprecated and has been replaced by LegOrderQty(685). This field will likely be removed from the FIX standard in a future version.

Type: Qty

Used in groups: InstrmtLegExecGrp, LegOrdGrp, LegQuotGrp, LegQuotStatGrp, QuotReqLegsGrp, TrdInstrmtLegGrp

**180.2.2347 LegQtyType**

Type of quantity specified in LegQty field. LegContractMultiplier (614) is required when LegQtyType = 1 (Contracts). LegUnitOfMeasure (tag 999) and LegTimeUnit (tag 1001) are required when LegQtyType = 2 (Units of Measure per Time Unit). LegQtyType can be different for each leg.

Type: int

Allowed values in QtyTypeCodeSet:

Code	Name	Description
0	Units	Units (shares, par, currency)
1	Contracts	Contracts
2	UnitsOfMeasurePerTimeUnit	Unit of Measure per Time Unit

Used in groups: TrdInstrmtLegExecGrp, TrdInstrmtLegGrp

**180.2.2348 LegQuotGrp**

Name	Mult.	Type	Description
NoLegs	[1..1]	NumInGroup	
InstrumentLeg	[0..1]	Component	Required if NoLegs(555) > 0.
LegOrderQty	[0..1]	Qty	
LegQty	[0..1]	Qty	The LegQty(687) field is deprecated. The use of LegOrderQty(685) is recommended instead.
LegMidPx	[0..1]	Price	
LegSwapType	[0..1]	CodeSet	
LegSettlType	[0..1]	CodeSet	

Name	Mult.	Type	Description
LegSettlDate	[0..1]	LocalMktDate	
LegStipulations	[0..*]	Group	
NestedParties	[0..*]	Group	
LegPriceType	[0..1]	CodeSet	Code to represent type of price presented in LegBidPx(681) and LegOfferPx(684). Conditionally required when LegBidPx(681) or PegOfferPx(684) is present.
LegBidPx	[0..1]	Price	
LegOfferPx	[0..1]	Price	
LegBenchmarkCurveData	[0..1]	Component	
LegRefID	[0..1]	String	Use of LegRefID(654) in this component is deprecated. Recommend the use of LegID(1788) in the InstrumentLeg component.
LegBidForwardPoints	[0..1]	PriceOffset	
LegOfferForwardPoints	[0..1]	PriceOffset	

Used in messages: [Quote](#), [QuoteResponse](#)

#### 180.2.2349 LegQuotStatGrp

Name	Mult.	Type	Description
NoLegs	[1..1]	NumInGroup	
InstrumentLeg	[0..1]	Component	Required if NoLegs(555) > 0.
LegOrderQty	[0..1]	Qty	
LegQty	[0..1]	Qty	The LegQty(687) field is deprecated. The use of LegOrderQty(685) is recommended instead.
LegMidPx	[0..1]	Price	
LegSwapType	[0..1]	CodeSet	
LegSettlType	[0..1]	CodeSet	
LegSettlDate	[0..1]	LocalMktDate	
LegStipulations	[0..*]	Group	
NestedParties	[0..*]	Group	

Used in messages: [QuoteStatusReport](#)

**180.2.2350 LegRatioQty**

The ratio of quantity for this individual leg relative to the entire multileg security.

Type: **float**

Used in components: **InstrumentLeg**

**180.2.2351 LegRedemptionDate**

Multileg instrument's individual leg security's RedemptionDate. See RedemptionDate (240) field for description (Note tag # was reserved in FIX 4.1, added in FIX 4.3) (prior to FIX 4.4 field was of type UTCDate)

Type: **LocalMktDate**

Used in components: **InstrumentLeg**

**180.2.2352 LegReferenceEntityType**

Specifies the type of reference entity for first-to-default CDS basket contracts.

Type: **int**

Allowed values in ReferenceEntityTypeCodeSet:

Code	Name	Description
1	Asian	Asian
2	AustralianNewZealand	Australian and New Zealand
3	EuropeanEmergingMarkets	European emerging markets
4	Japanese	Japanese
5	NorthAmericanHighYield	North American high yield
6	NorthAmericanInsurance	North American insurance
7	NorthAmericanInvestmentGrade	North American investment grade
8	Singaporean	Singaporean
9	WesternEuropean	Western European
10	WesternEuropeanInsurance	Western European insurance

Used in components: **InstrumentLeg**

**180.2.2353 LegRefID**

Unique identifier for a specific leg (uniqueness not defined as part of the FIX specification). LegRefID(654) be used to reference the value from LegID(1788).

Type: **String**

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **LegQuotGrp**, **MDFullGrp**, **QuotReqLegsGrp**, **SideCrossLegGrp**, **TrdInstrmtLegExecGrp**, **TrdInstrmtLegGrp**

**180.2.2354 LegRepoCollateralSecurityType**

Multileg instrument's individual leg security's RepoCollateralSecurityType. See RepoCollateralSecurityType (239) field for description (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **String**

Used in components: **InstrumentLeg**

**180.2.2355 LegReportID**

Additional attribute to store the Trade ID of the Leg.

Type: **String**

Used in groups: **TrdInstrmtLegGrp**

**180.2.2356 LegRepurchaseRate**

Multileg instrument's individual leg security's RepurchaseRate. See RepurchaseRate (227) field for description (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **Percentage**

Used in components: **InstrumentLeg**

**180.2.2357 LegRepurchaseTerm**

Multileg instrument's individual leg security's RepurchaseTerm. See RepurchaseTerm (226) field for description (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **int**

Used in components: **InstrumentLeg**

**180.2.2358 LegRestructuringType**

A category of CDS credit event in which the underlying bond experiences a restructuring.

Used to define a CDS instrument.

Type: **String**

Allowed values in RestructuringTypeCodeSet:

Code	Name	Description
FR	FullRestructuring	Full Restructuring
MR	ModifiedRestructuring	Modified Restructuring
MM	ModifiedModRestructuring	Modified Mod Restructuring
XR	NoRestructuringSpecified	No Restructuring specified

Used in components: **InstrumentLeg**

**180.2.2359 LegReturnRateAmountRelativeTo**

Specifies the reference amount when the return rate amount is relative to another amount in the trade.

See [http://www.fixtradingcommunity.org/codelists#Amount\\_Relative\\_To](http://www.fixtradingcommunity.org/codelists#Amount_Relative_To) for code list of relative amounts.

Type: **int**

Used in groups: **LegReturnRateGrp**

**180.2.2360 LegReturnRateCashFlowType**

Specifies the type of cash flows, e.g. coupon payment, premium fee, settlement fee, etc.

See <http://www.fpml.org/coding-scheme/cashflow-type> for values.

Type: **String**

Used in groups: **LegReturnRateGrp**



**180.2.2361 LegReturnRateCommissionAmount**

The commission amount.

Type: **Amt**

Used in groups: **LegReturnRateGrp**

**180.2.2362 LegReturnRateCommissionBasis**

Specifies the basis or unit used to calculate the commission.

Type: **char**

Allowed values in CommTypeCodeSet:

Code	Name	Description
1	PerUnit	Amount per unit. Implying shares, par, currency, physical unit etc. Use CommissionUnitOfMeasure(1238) to clarify for commodities.
2	Percent	Percent
3	Absolute	Absolute. Total monetary amount.
4	PercentageWaivedCashDiscount	Percentage waived, cash discount basis. For use with CIV buy orders.
5	PercentageWaivedEnhancedUnits	Percentage waived, enhanced units basis. For use with CIV buy orders.
6	PointsPerBondOrContract	Points per bond or contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention, e.g. 1000 par for bonds.
7	BasisPoints	Basis points. The commission is expressed in basis points in reference to the gross price of the reference asset.
8	AmountPerContract	Amount per contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention.

Used in groups: **LegReturnRateGrp**

**180.2.2363 LegReturnRateCommissionCurrency**

Specifies the currency the commission amount is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegReturnRateGrp**

### 180.2.2364 LegReturnRateDateGrp

LegReturnRateDateGrp is a repeating subcomponent within the LegReturnRateGrp component. It is used to specify the equity and dividend valuation dates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoLegReturnRateDates	[1..1]	NumInGroup	
LegReturnRateDateMode	[0..1]	CodeSet	Required if NoLegReturnRateDates(42508) > 0.
LegReturnRateValuationDateGrp	[0..*]	Group	
LegReturnRateValuationDateRelativeTo	[0..1]	int	
LegReturnRateValuationDateOffsetPeriod	[0..1]	int	Conditionally required when LegReturnRateValuationDateOffsetUnit(42512) is specified.
LegReturnRateValuationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegReturnRateValuationDateOffsetPeriod(42511) is specified.
LegReturnRateValuationDateOffsetDayType	[0..1]	CodeSet	
LegReturnRateValuationStartDateUnadjusted	[0..1]	LocalMktDate	
LegReturnRateValuationStartDateRelativeTo	[0..1]	int	
LegReturnRateValuationStartDateOffsetPeriod	[0..1]	int	Conditionally required when LegReturnRateValuationStartDateOffsetUnit(42517) is specified.
LegReturnRateValuationStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegReturnRateValuationStartDateOffsetPeriod(42516) is specified.
LegReturnRateValuationStartDateOffsetDayType	[0..1]	CodeSet	
LegReturnRateValuationStartDateAdjusted	[0..1]	LocalMktDate	
LegReturnRateValuationEndDateUnadjusted	[0..1]	LocalMktDate	
LegReturnRateValuationEndDateRelativeTo	[0..1]	int	

Name	Mult.	Type	Description
LegReturnRateValuationEndDateOffsetPeriod	[0..1]	int	Conditionally required when LegReturnRateValuationEndDateOffsetUnit(42523) is specified.
LegReturnRateValuationEndDateOffsetUnit	[0..1]	CodeSet	Conditionally required when LegReturnRateValuationEndDateOffsetPeriod(42522) is specified.
LegReturnRateValuationEndDateOffsetDayType	[0..1]	CodeSet	
LegReturnRateValuationEndDateAdjusted	[0..1]	LocalMktDate	
LegReturnRateValuationFrequencyPeriod	[0..1]	int	Conditionally required when LegReturnRateValuationFrequencyUnit(42527) is specified.
LegReturnRateValuationFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegReturnRateValuationFrequencyPeriod(42526) is specified.
LegReturnRateValuationFrequencyRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of return rate valuation dates.
LegReturnRateValuationDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to payment stream return rate valuation dates.
LegReturnRateValuationDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to payment stream return rate valuation dates.

Used in groups: **LegReturnRateGrp**

### 180.2.2365 LegReturnRateDateMode

Specifies the valuation type applicable to the return rate date.

Type: **int**

Allowed values in ReturnRateDateModeCodeSet:

Code	Name	Description
0	PriceValuation	Price valuation
1	DividendValuation	Dividend valuation

Used in groups: **LegReturnRateDateGrp**

#### 180.2.2366 LegReturnRateDeterminationMethod

Specifies the method by which the underlier prices are determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **LegReturnRateGrp**

#### 180.2.2367 LegReturnRateFinalPriceFallback

Specifies the fallback provision for the hedging party in the determination of the final price.

Type: **int**

Allowed values in ComplexEventPVFinalPriceElectionFallbackCodeSet:

Code	Name	Description
0	Close	Close. In respect of the "early final valuation date", the provisions for "future present value close" shall apply.
1	HedgeElection	Hedge election. In respect of the "early final valuation date", the provisions for "future present value hedge execution" shall apply.

Used in groups: **LegReturnRateGrp**

#### 180.2.2368 LegReturnRateFXConversionGrp

LegReturnRateFXConversionGrp is a repeating subcomponent within the LegReturnRateGrp component. It is used to specify the FX conversion rates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoLegReturnRateFXConversions	[1..1]	NumInGroup	
LegReturnRateFXCurrencySymbol	[0..1]	String	Required if NoLegReturnRateFXConversions(42530) > 0.
LegReturnRateFXRate	[0..1]	float	Required if NoLegReturnRateFXConversions(42530) > 0.
LegReturnRateFXRateCalc	[0..1]	CodeSet	

Used in groups: [LegReturnRateGrp](#)

#### 180.2.2369 LegReturnRateFXCurrencySymbol

Specifies the currency pair for the FX conversion expressed using the CCY1/CCY2 convention. Uses ISO 4217 currency codes.

Type: [String](#)

Used in groups: [LegReturnRateFXConversionGrp](#)

#### 180.2.2370 LegReturnRateFXRate

The rate of exchange between the two currencies specified in LegReturnRateFXCurrencySymbol(42531).

Type: [float](#)

Used in groups: [LegReturnRateFXConversionGrp](#)

#### 180.2.2371 LegReturnRateFXRateCalc

The rate of exchange between the two currencies specified in LegReturnRateFXCurrencySymbol(42531).

Type: [char](#)

Allowed values in SettlCurrFxRateCalcCodeSet:

Code	Name	Description
M	Multiply	Multiply

Code	Name	Description
D	Divide	Divide

Used in groups: [LegReturnRateFXConversionGrp](#)

### 180.2.2372 LegReturnRateGrp

LegReturnRateGrp is a repeating subcomponent within the LegPaymentStreamFloatingRate component. It is used to specify the multiple return rates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoLegReturnRates	[1..1]	NumInGroup	
LegReturnRatePriceSequence	[0..1]	CodeSet	Required if NoLegReturnRates(42534) > 0.
LegReturnRateCommissionBasis	[0..1]	CodeSet	
LegReturnRateCommissionAmount	[0..1]	Amt	
LegReturnRateCommissionCurrency	[0..1]	Currency	If not specified, this is defaulted to the reporting currency.
LegReturnRateTotalCommissionPer-Trade	[0..1]	Amt	
LegReturnRateDeterminationMethod	[0..1]	String	
LegReturnRatePriceGrp	[0..*]	Group	
LegReturnRateFXConversionGrp	[0..*]	Group	
LegReturnRateAmountRelativeTo	[0..1]	int	
LegReturnRateQuoteMeasureType	[0..1]	String	
LegReturnRateQuoteUnits	[0..1]	String	
LegReturnRateQuoteMethod	[0..1]	CodeSet	
LegReturnRateQuoteCurrency	[0..1]	Currency	
LegReturnRateQuoteCurrencyType	[0..1]	String	
LegReturnRateQuoteTimeType	[0..1]	CodeSet	Mutually exclusive with LegReturnRateQuoteTime(42548).
LegReturnRateQuoteTime	[0..1]	LocalMktTime	Mutually exclusive with LegReturnRateQuoteTimeType(42547).
LegReturnRateQuoteDate	[0..1]	LocalMktDate	
LegReturnRateQuoteExpirationTime	[0..1]	LocalMktTime	
LegReturnRateQuoteBusinessCenter	[0..1]	String	

Name	Mult.	Type	Description
LegReturnRateQuoteExchange	[0..1]	Exchange	
LegReturnRateInformationSourceGrp	[0..*]	Group	
LegReturnRateQuotePricingModel	[0..1]	String	
LegReturnRateCashFlowType	[0..1]	String	
LegReturnRateDateGrp	[0..*]	Group	
LegReturnRateValuationTimeType	[0..1]	CodeSet	Mutually exclusive with LegReturnRateValuationTime(42556).
LegReturnRateValuationTime	[0..1]	LocalMktTime	Mutually exclusive with LegReturnRateValuationTimeType(42555).
LegReturnRateValuationTimeBusiness-Center	[0..1]	String	
LegReturnRateValuationPriceOption	[0..1]	CodeSet	
LegReturnRateFinalPriceFallback	[0..1]	CodeSet	

Used in components: [LegPaymentStreamFloatingRate](#)

### 180.2.2373 LegReturnRateInformationSource

Identifies the source of rate information. For FX the references source to be used for the FX spot rate.

Type: [int](#)

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: [LegReturnRateInformationSourceGrp](#)

**180.2.2374 LegReturnRateInformationSourceGrp**

LegReturnRateInformationSourceGrp is a repeating subcomponent within the LegReturnRateGrp component. It is used to specify the information sources for equity prices and FX rates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoLegReturnRateInformationSources	[1..1]	NumInGroup	
LegReturnRateInformationSource	[0..1]	CodeSet	Required if NoLegReturnRateInformationSources(42560) > 0.
LegReturnRateReferencePage	[0..1]	String	
LegReturnRateReferencePageHeading	[0..1]	String	

Used in groups: [LegReturnRateGrp](#)

**180.2.2375 LegReturnRateNotionalReset**

Indicates whether the term "Equity Notional Reset" as defined in the ISDA 2002 Equity Derivatives Definitions is applicable ("Y") or not.

Type: [Boolean](#)

Used in components: [LegPaymentStreamFloatingRate](#)

**180.2.2376 LegReturnRatePrice**

Specifies the price of the underlying swap asset.

Type: [Price](#)

Used in groups: [LegReturnRatePriceGrp](#)

**180.2.2377 LegReturnRatePriceBasis**

The basis of the return price.

Type: [int](#)

Allowed values in ReturnRatePriceBasisCodeSet:



Code	Name	Description
0	Gross	Gross.
1	Net	Net
2	Accrued	Accrued
3	CleanNet	Clean net

Used in groups: [LegReturnRatePriceGrp](#)

#### 180.2.2378 LegReturnRatePriceCurrency

Specifies the currency of the price of the leg swap asset. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [LegReturnRatePriceGrp](#)

#### 180.2.2379 LegReturnRatePriceGrp

LegReturnRatePriceGrp is a repeating subcomponent within the LegReturnRateGrp component. It is used to specify the return rate prices for an equity return swap payment stream.

Name	Mult.	Type	Description
<a href="#">NoLegReturnRatePrices</a>	[1..1]	NumInGroup	
<a href="#">LegReturnRatePriceBasis</a>	[0..1]	CodeSet	Required if NoLegReturnRatePrices(42564) > 0.
<a href="#">LegReturnRatePrice</a>	[0..1]	Price	
<a href="#">LegReturnRatePriceCurrency</a>	[0..1]	Currency	
<a href="#">LegReturnRatePriceType</a>	[0..1]	CodeSet	

Used in groups: [LegReturnRateGrp](#)

#### 180.2.2380 LegReturnRatePriceSequence

Specifies the type of price sequence of the return rate.

Type: [int](#)

Allowed values in ReturnRatePriceSequenceCodeSet:

Code	Name	Description
0	Initial	Initial
1	Interim	Interim
2	Final	Final

Used in groups: **LegReturnRateGrp**

#### **180.2.2381 LegReturnRatePriceType**

Specifies whether the LegReturnRatePrice(42566) is expressed in absolute or relative terms.

Type: **int**

Allowed values in ReturnRatePriceTypeCodeSet:

Code	Name	Description
0	AbsoluteTerms	Absolute terms
1	PercentageOfNotional	Percentage of notional

Used in groups: **LegReturnRatePriceGrp**

#### **180.2.2382 LegReturnRateQuoteBusinessCenter**

The business center calendar used for adjustments associated with LegReturnRateQuoteTimeType(42547) or LegReturnRateQuoteTime(42548) and LegReturnRateQuoteDate(42549), e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegReturnRateGrp**

#### **180.2.2383 LegReturnRateQuoteCurrency**

Specifies the currency the return rate quote is denominated in. Uses ISO 4217 Currency Code.

Type: **Currency**

Used in groups: **LegReturnRateGrp**

**180.2.2384 LegReturnRateQuoteCurrencyType**

Specifies the type of currency, e.g. settlement currency, base currency, etc., that the quote is reported in.

See <http://www.fpml.org/coding-scheme/reporting-currency-type> for values.

Type: **String**

Used in groups: **LegReturnRateGrp**

**180.2.2385 LegReturnRateQuoteDate**

The date when the quote is to be generated.

Type: **LocalMktDate**

Used in groups: **LegReturnRateGrp**

**180.2.2386 LegReturnRateQuoteExchange**

Specifies the exchange (e.g. stock or listed futures/options exchange) from which the quote is obtained.

Type: **Exchange**

Used in groups: **LegReturnRateGrp**

**180.2.2387 LegReturnRateQuoteExpirationTime**

The time when the quote ceases to be valid.

Type: **LocalMktTime**

Used in groups: **LegReturnRateGrp**

**180.2.2388 LegReturnRateQuoteMeasureType**

Specifies the type of the measure applied to the return rate's asset, e.g. valuation, sensitivity risk. This could be an NPV, a cash flow, a clean price, etc.

See <http://www.fpml.org/coding-scheme/asset-measure> for values.

Type: **String**

Used in groups: **LegReturnRateGrp**

**180.2.2389 LegReturnRateQuoteMethod**

Specifies the type of quote used to determine the return rate of the swap.

Type: **int**

Allowed values in CashSettlQuoteMethodCodeSet:

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer

Used in groups: **LegReturnRateGrp**

**180.2.2390 LegReturnRateQuotePricingModel**

Specifies the pricing model used to evaluate the underlying asset price.

See <http://www.fpml.org/coding-scheme/pricing-model> for values.

Type: **String**

Used in groups: **LegReturnRateGrp**

**180.2.2391 LegReturnRateQuoteTime**

The time when the quote is to be generated.

Type: **LocalMktTime**

Used in groups: **LegReturnRateGrp**

**180.2.2392 LegReturnRateQuoteTimeType**

Specifies how or the timing when the quote is to be obtained.

Type: **int**

Allowed values in ReturnRateQuoteTimeTypeCodeSet:

Code	Name	Description
0	Open	Open. The official opening time of the exchange on valuation date.
1	OfficialSettlPx	Official settlement price time. The time at which the official settlement price is determined.
2	Xetra	XETRA. The time at which the official settlement price (following the auction by the exchange) is determined by the exchange.
3	Close	Close. The official closing time of the exchange on valuation date.
4	DerivativesClose	Derivatives close. The official closing time for derivative trading of the exchange on valuation date.
5	High	High. The high price for the day.
6	Low	Low. The low price for the day.
7	AsSpecifiedInMasterConfirmation	As specified in the master confirmation

Used in groups: [LegReturnRateGrp](#)

#### 180.2.2393 LegReturnRateQuoteUnits

Specifies the units that the measure is expressed in. If not specified, the default is a price/value in currency units.

See <http://www.fpml.org/coding-scheme/price-quote-units> for values.

Type: [String](#)

Used in groups: [LegReturnRateGrp](#)

#### 180.2.2394 LegReturnRateReferencePage

Identifies the reference "page" from the rate source.

For FX, the reference page to the spot rate to be used for the reference FX spot rate.

When `LegReturnRateInformationSource(42561) = 3` (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions.

See: <http://www.fpml.org/coding-scheme/settlement-rate-option>.

Type: [String](#)

Used in groups: [LegReturnRateInformationSourceGrp](#)

**180.2.2395 LegReturnRateReferencePageHeading**

Identifies the page heading from the rate source.

Type: **String**

Used in groups: **LegReturnRateInformationSourceGrp**

**180.2.2396 LegReturnRateTotalCommissionPerTrade**

The total commission per trade.

Type: **Amt**

Used in groups: **LegReturnRateGrp**

**180.2.2397 LegReturnRateValuationDate**

The return rate valuation date. The type of date is specified in LegReturnRateValuationDate-Type(42573).

Type: **LocalMktDate**

Used in groups: **LegReturnRateValuationDateGrp**

**180.2.2398 LegReturnRateValuationDateBusinessCenter**

The business center calendar used for date adjustment of the return rate valuation unadjusted or relative dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegReturnRateValuationDateBusinessCenterGrp**

**180.2.2399 LegReturnRateValuationDateBusinessCenterGrp**

LegReturnRateValuationDateBusinessCenterGrp is a repeating subcomponent within the LegReturnRateValuationDateGrp component. It is used to specify the valuation date business center adjustments for an equity return swap payment stream.

Name	Mult.	Type	Description
NoLegReturnRateValuationDateBusinessCenters	[1..1]	NumInGroup	
LegReturnRateValuationDateBusinessCenter	[0..1]	String	Required if NoLegReturnRateValuationDateBusinessCenters(42569) > 0.

Used in groups: [LegReturnRateDateGrp](#)

### 180.2.2400 LegReturnRateValuationDateBusinessDayConvention

The return rate valuation dates business day convention.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [LegReturnRateDateGrp](#)

### 180.2.2401 LegReturnRateValuationDateGrp

LegReturnRateValuationDateGrp is a repeating subcomponent within the LegReturnRateDateGrp component. It is used to specify the fixed valuation dates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoLegReturnRateValuationDates	[1..1]	NumInGroup	

Name	Mult.	Type	Description
<a href="#">LegReturnRateValuationDate</a>	[0..1]	LocalMktDate	Required if NoLegReturnRateValuationDates(42571) > 0.
<a href="#">LegReturnRateValuationDateType</a>	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in groups: [LegReturnRateDateGrp](#)

#### 180.2.2402 [LegReturnRateValuationDateOffsetDayType](#)

Specifies the day type of the relative return rate valuation date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [LegReturnRateDateGrp](#)

#### 180.2.2403 [LegReturnRateValuationDateOffsetPeriod](#)

Time unit multiplier for the relative return rate valuation date offset.

Type: [int](#)

Used in groups: [LegReturnRateDateGrp](#)



**180.2.2404 LegReturnRateValuationDateOffsetUnit**

Time unit associated with the relative return rate valuation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegReturnRateDateGrp**

**180.2.2405 LegReturnRateValuationDateRelativeTo**

Specifies the anchor date when the return rate valuation dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **LegReturnRateDateGrp**

**180.2.2406 LegReturnRateValuationDateType**

Specifies the type of return rate valuation date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **LegReturnRateValuationDateGrp**

**180.2.2407 LegReturnRateValuationEndDateAdjusted**

The adjusted end date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in groups: **LegReturnRateDateGrp**

**180.2.2408 LegReturnRateValuationEndDateOffsetDayType**

Specifies the day type of the relative return rate valuation end date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **LegReturnRateDateGrp**

**180.2.2409 LegReturnRateValuationEndDateOffsetPeriod**

Time unit multiplier for the relative return rate valuation end date offset.

Type: **int**

Used in groups: **LegReturnRateDateGrp**

**180.2.2410 LegReturnRateValuationEndDateOffsetUnit**

Time unit associated with the relative return rate valuation end date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [LegReturnRateDateGrp](#)

#### **180.2.2411 LegReturnRateValuationEndDateRelativeTo**

Specifies the anchor date when the return rate valuation end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in groups: [LegReturnRateDateGrp](#)

#### **180.2.2412 LegReturnRateValuationEndDateUnadjusted**

The unadjusted end date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in groups: [LegReturnRateDateGrp](#)

#### **180.2.2413 LegReturnRateValuationFrequencyPeriod**

Time unit multiplier for the frequency at which return rate valuation dates occur.

Type: [int](#)

Used in groups: [LegReturnRateDateGrp](#)

**180.2.2414 LegReturnRateValuationFrequencyRollConvention**

The convention for determining the sequence of return rate valuation dates. It is used in conjunction with a specified frequency.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighthDay	28th day of the month

Code	Name	Description
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in groups: [LegReturnRateDateGrp](#)

### 180.2.2415 LegReturnRateValuationFrequencyUnit

Time unit associated with the frequency at which return rate valuation dates occur.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day

Code	Name	Description
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in groups: [LegReturnRateDateGrp](#)

#### **180.2.2416 LegReturnRateValuationPriceOption**

Indicates whether an ISDA price option applies, and if applicable which type of price.

Type: [int](#)

Allowed values in ReturnRateValuationPriceOptionCodeSet:

Code	Name	Description
0	None	None (the default)
1	FuturesPrice	Futures price. The official settlement price as announced by the related futures exchange is applicable.
2	OptionsPrice	Options price. The official settlement price as announced by the related options exchange is applicable.

Used in groups: [LegReturnRateGrp](#)

#### **180.2.2417 LegReturnRateValuationStartDateAdjusted**

The adjusted start date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in groups: [LegReturnRateDateGrp](#)

**180.2.2418 LegReturnRateValuationStartDateOffsetDayType**

Specifies the day type of the relative return rate valuation start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **LegReturnRateDateGrp**

**180.2.2419 LegReturnRateValuationStartDateOffsetPeriod**

Time unit multiplier for the relative return rate valuation start date offset.

Type: **int**

Used in groups: **LegReturnRateDateGrp**

**180.2.2420 LegReturnRateValuationStartDateOffsetUnit**

Time unit associated with the relative return rate valuation start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **LegReturnRateDateGrp**

**180.2.2421 LegReturnRateValuationStartDateRelativeTo**

Specifies the anchor date when the return rate valuation start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **LegReturnRateDateGrp**

**180.2.2422 LegReturnRateValuationStartDateUnadjusted**

The unadjusted start date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in groups: **LegReturnRateDateGrp**

**180.2.2423 LegReturnRateValuationTime**

The time at which the calculation agent values the underlying asset.

Type: **LocalMktTime**

Used in groups: **LegReturnRateGrp**

**180.2.2424 LegReturnRateValuationTimeBusinessCenter**

The business center calendar used for adjustments associated with LegReturnRateValuationTime-  
Type(42555) or LegReturnRateValuationTime(42556), e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegReturnRateGrp**

**180.2.2425 LegReturnRateValuationTimeType**

Specifies the timing at which the calculation agent values the underlying.

Type: **int**

Allowed values in ReturnRateQuoteTimeTypeCodeSet:



Code	Name	Description
0	Open	Open. The official opening time of the exchange on valuation date.
1	OfficialSettlPx	Official settlement price time. The time at which the official settlement price is determined.
2	Xetra	XETRA. The time at which the official settlement price (following the auction by the exchange) is determined by the exchange.
3	Close	Close. The official closing time of the exchange on valuation date.
4	DerivativesClose	Derivatives close. The official closing time for derivative trading of the exchange on valuation date.
5	High	High. The high price for the day.
6	Low	Low. The low price for the day.
7	AsSpecifiedInMasterConfirmation	As specified in the master confirmation

Used in groups: [LegReturnRateGrp](#)

### 180.2.2426 LegReturnTrigger

Indicates the type of return or payout trigger for the swap or forward.

Type: [int](#)

Allowed values in ReturnTriggerCodeSet:

Code	Name	Description
1	Dividend	Dividend
2	Variance	Variance
3	Volatility	Volatility
4	TotalReturn	Total return
5	ContractForDifference	Contract for difference
6	CreditDefault	Credit default
7	SpreadBet	Spread bet
8	Price	Price
9	ForwardPriceUnderlyingInstrument	Forward price of underlying instrument
99	Other	Other

Used in components: [InstrumentLeg](#)

**180.2.2427 LegSecAltIDGrp**

Name	Mult.	Type	Description
NoLegSecurityAltID	[1..1]	NumInGroup	
LegSecurityAltID	[0..1]	String	
LegSecurityAltIDSource	[0..1]	CodeSet	
LegSymbolPositionNumber	[0..1]	int	

Used in components: [InstrumentLeg](#)

**180.2.2428 LegSecondaryAssetClass**

The broad asset category for assessing risk exposure for a multi-asset trade.

Type: [int](#)

Allowed values in AssetClassCodeSet:

Code	Name	Description
1	InterestRate	Interest rate
2	Currency	Currency
3	Credit	Credit
4	Equity	Equity
5	Commodity	Commodity
6	Other	Other
7	Cash	Cash
8	Debt	Debt
9	Fund	Fund. Such as mutual fund, collective investment vehicle, investment program, specialized account program.
10	LoanFacility	Loan facility
11	Index	Index. A main index identified as a security type, for example under EU SFTR reporting.

Used in groups: [LegSecondaryAssetGrp](#)

**180.2.2429 LegSecondaryAssetGrp**

LegSecondaryAssetGrp is a repeating subcomponent of the InstrumentLeg component used to specify secondary assets of a multi-asset swap.

Name	Mult.	Type	Description
NoLegSecondaryAssetClasses	[1..1]	NumInGroup	
LegSecondaryAssetClass	[0..1]	CodeSet	Required if NoLegSecondaryAssetClasses(2076) > 0.
LegSecondaryAssetSubClass	[0..1]	CodeSet	Required if LegSecondaryAssetType(2079) is specified.
LegSecondaryAssetType	[0..1]	String	Required if LegSecondaryAssetSubType(2743) is specified.
LegSecondaryAssetSubType	[0..1]	String	

Used in components: **InstrumentLeg**

**180.2.2430 LegSecondaryAssetSubClass**

An indication of the general description of the asset class.

Type: **int**

Allowed values in AssetSubClassCodeSet:

Code	Name	Description
1	SingleCurrency	Single currency
2	CrossCurrency	Cross currency
3	Basket	Basket [for multi-currency]
4	SingleName	Single name
5	CreditIndex	Credit index
6	IndexTranche	Index tranche
7	CreditBasket	Credit basket
8	Exotic	Exotic
9	Common	Common
10	Preferred	Preferred
11	EquityIndex	Equity index
12	EquityBasket	Equity basket

Code	Name	Description
13	Metals	Metals
14	Bullion	Bullion
15	Energy	Energy
16	CommodityIndex	Commodity index
17	Agricultural	Agricultural
18	Environmental	Environmental
19	Freight	Freight
20	Government	Government
21	Agency	Agency
22	Corporate	Corporate
23	Financing	Financing
24	MoneyMarket	Money market
25	Mortgage	Mortgage
26	Municipal	Municipal
27	MutualFund	Mutual fund
28	CollectiveInvestmentVehicle	Collective investment vehicle
29	InvestmentProgram	Investment program. A generalized fund for major investors.
30	SpecializedAccountProgram	Specialized account program. A specialized fund setup for a particular account or group of accounts.
31	TermLoan	Term loan
32	BridgeLoan	Bridge loan
33	LetterOfCredit	Letter of credit
34	DividendIndex	Dividend index
35	StockDividend	Stock dividend
36	ExchangeTradedFund	Exchange traded fund
37	VolatilityIndex	Volatility index
38	FXCrossRates	FX cross rates
39	FXEmergingMarkets	FX emerging markets
40	FXMajors	FX Majors
41	Fertilizer	Fertilizer
42	IndustrialProduct	Industrial product
43	Inflation	Inflation
44	Paper	Paper
45	Polypropylene	Polypropylene

Code	Name	Description
46	OfficialEconomicStatistics	Official economic statistics
47	OtherC10	Other C10. Defined under MiFID II (Directive 2014/65/EU) Section C(10) of Annex I and paraphrased in ESMA RTS 2 Annex III Section 10, "Other C10" is a financial instrument "which is not a 'Freight derivative', any of the following interest rate derivatives sub-asset classes: 'Inflation multi-currency swap or cross-currency swap', a 'Future/forward on inflation multi-currency swaps or cross-currency swaps', an 'Inflation single currency swap', a 'Future/forward on inflation single currency swap' and any of the following equity derivatives sub-asset classes: a 'Volatility index option', a 'Volatility index future/forward', a swap with parameter return variance, a swap with parameter return volatility, a portfolio swap with parameter return variance, a portfolio swap with parameter return volatility".
48	Other	Other. May be used with any AssetClass(1938) values.

Used in groups: [LegSecondaryAssetGrp](#)

#### 180.2.2431 LegSecondaryAssetSubType

Used to provide a more specific description of the asset specified in LegSecondaryAssetType(2079).

See <https://www.fixtrading.org/codelists/AssetSubType> for code list of applicable values.

Type: [String](#)

Used in groups: [LegSecondaryAssetGrp](#)

#### 180.2.2432 LegSecondaryAssetType

Used to provide more specific description of the asset specified in LegSecondaryAssetSub-Class(2078).

See <https://www.fixtrading.org/codelists/AssetType> for code list of applicable values. ISO 4721 Currency Code values are to be used when specific currency as an asset type is to be expressed.

Other values may be used by mutual agreement of the counterparties.

Type: [String](#)

Used in groups: [LegSecondaryAssetGrp](#)

**180.2.2433 LegSecurityAltID**

Multileg instrument's individual security's SecurityAltID.

See SecurityAltID (455) field for description

Type: **String**

Used in groups: **LegSecAltIDGrp**

**180.2.2434 LegSecurityAltIDSource**

Alternate identifier for individual leg security of a multileg instrument.

See SecurityAltIDSource(456) field for complete definition.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))

Code	Name	Description
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **LegSecAltIDGrp**

#### 180.2.2435 LegSecurityDesc

Description of a multileg instrument.

Can be used by the venue or one of the trading parties to provide an optional non-normative textual description of the financial instrument.

Type: **String**

Used in components: **InstrumentLeg**

#### 180.2.2436 LegSecurityExchange

Multileg instrument's individual security's SecurityExchange.

See SecurityExchange (207) field for description

Type: **Exchange**

Used in components: **InstrumentLeg**

#### **180.2.2437 LegSecurityGroup**

Represents the product group of a leg.This is useful in conveying multi-leg instruments where the legs may participate in separate security groups.

Type: **String**

Used in components: **InstrumentLeg**

#### **180.2.2438 LegSecurityID**

Multileg instrument's individual security's SecurityID.

See SecurityID (48) field for description

Type: **String**

Used in components: **InstrumentLeg**

#### **180.2.2439 LegSecurityIDSource**

Multileg instrument's individual security's SecurityIDSource.

See SecurityIDSource (22) field for description

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code



Code	Name	Description
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **InstrumentLeg**

**180.2.2440 LegSecurityStatus**

Indicates the current state of the leg instrument.

Type: **String**

Allowed values in SecurityStatusCodeSet:

Code	Name	Description
1	Active	Active. Instrument is active, i.e. trading is possible.
2	Inactive	Inactive. Instrument has previously been active and is now no longer traded but has not expired yet. The instrument may become active again.
3	ActiveClosingOrdersOnly	Active, closing orders only. Instrument is active but only orders closing positions (reducing risk) are allowed.
4	Expired	Expired. Instrument has expired. E.g. An instrument may expire due to reaching maturity or expired based on contract definitions or exchange rules.
5	Delisted	Delisted. Instrument has been removed from securities reference data. Delisting rules varies from exchange to exchange, which may include non-compliance of capitalization, revenue, consecutive minimum closing price. The instrument may become listed again once the instrument is back in compliance. A delisted instrument would not trade on the exchange but it may still be traded over-the-counter (e.g. OTCBB) or on Pink Sheets, or other similar trading service.
6	KnockedOut	Knocked-out. Instrument has breached a pre-defined price threshold.
7	KnockOutRevoked	Knock-out revoked. Instrument reinstated, i.e. threshold has not been breached.
8	PendingExpiry	Pending Expiry. Instrument is currently still active but will expire after the current business day. For example, a contract that expires intra-day (e.g. at noon time) and is no longer tradeable but will still show up in the current day's order book with related statistics.
9	Suspended	Suspended. Instrument has been temporarily disabled for trading (i.e. halted).
10	Published	Published. Instrument information is provided prior to its first activation.
11	PendingDeletion	Pending Deletion. Instrument is awaiting deletion from security reference data.

Used in components: [InstrumentLeg](#)

#### **180.2.2441 LegSecuritySubType**

SecuritySubType of the leg instrument.

See SecuritySubType (762) field for description

Type: [String](#)

Used in components: [InstrumentLeg](#)

#### **180.2.2442 LegSecurityType**

Refer to definition of SecurityType(167)

Type: [String](#)

Allowed values in SecurityTypeCodeSet:

Code	Name	Description
ABS	AssetBackedSecurities	Asset-backed Securities
AN	OtherAnticipationNotes	Other Anticipation Notes (BAN, GAN, etc.)
BA	BankersAcceptance	Bankers Acceptance
BRADY	BradyBond	Brady Bond
CORP	CorporateBond	Corporate Bond
CS	CommonStock	Common Stock
EUSUPRA	EuroSupranationalCoupons	Euro Supranational Coupons. Identify the issuer name in Issuer(106).
FOR	ForeignExchangeContract	Foreign Exchange Contract
MF	MutualFund	Mutual Fund
REPO	Repurchase	Repurchase
TERM	TermLoan	Term Loan
BDN	BankDepositoryNote	Bank Depository Note
CAN	CanadianTreasuryNotes	Canadian Treasury Notes
CAP	Cap	Cap. In an interest rate cap, the buyer receives payments at the end of each period in which the rate indec exceeds the agreed strike rate.
CMB	CanadianMortgageBonds	Canadian Mortgage Bonds
COFO	CertificateOfObligation	Certificate Of Obligation

Code	Name	Description
CPP	CorporatePrivatePlacement	Corporate Private Placement
FAC	FederalAgencyCoupon	Federal Agency Coupon
FORWARD	Forward	Forward
FXNDF	NonDeliverableForward	Non-deliverable forward
MLEG	MultilegInstrument	Multileg Instrument
PS	PreferredStock	Preferred Stock
RVLV	RevolverLoan	Revolver Loan
BN	BankNotes	Bank Notes
BUYSELL	BuySellback	Buy Sellback
CB	ConvertibleBond	Convertible Bond
CDS	CreditDefaultSwap	Credit Default Swap
CMBS	Corp	Corp. Mortgage-backed Securities
COFP	CertificateOfParticipation	Certificate Of Participation
CTB	CanadianTreasuryBills	Canadian Treasury Bills
DR	DepositoryReceipts	Depository Receipts
FADN	FederalAgencyDiscountNote	Federal Agency Discount Note
FXSPOT	FXSpot	FX Spot
NONE	NoSecurityType	No Security Type
RVLVTRM	Revolver	Revolver/Term Loan
BOX	BillOfExchanges	Bill Of Exchanges
BRIDGE	BridgeLoan	Bridge Loan
CLLR	Collar	Collar. In an interest rate collar, this is a combination of a cap and a floor.
CMO	CollateralizedMortgageObligation	Collateralized Mortgage Obligation
DUAL	DualCurrency	Dual Currency
EUSOV	EuroSovereigns	Euro Sovereigns. Identify the issuer name in Issuer(106).
FXFWD	FXForward	FX Forward
GO	GeneralObligationBonds	General Obligation Bonds
PEF	PrivateExportFunding	Private Export Funding. Identify the issuer name in Issuer(106).
SECLOAN	SecuritiesLoan	Securities Loan
UST	USTreasuryNoteOld	US Treasury Note (Deprecated Value Use TNOTE)
CAMM	CanadianMoneyMarkets	Canadian Money Markets
CMDTYSWAP	CommoditySwap	Commodity swap
EUCORP	EuroCorporateBond	Euro Corporate Bond

Code	Name	Description
FXSWAP	FXSwap	FX Swap
IET	IOETTEMortgage	IOETTE Mortgage
LOFC	LetterOfCredit	Letter Of Credit
MT	MandatoryTender	Mandatory Tender
PROV	CanadianProvincialBonds	Canadian Provincial Bonds
SECPLEDGE	SecuritiesPledge	Securities Pledge
SUPRA	USDSupranationalCoupons	USD Supranational Coupons. Identify the issuer name in Issuer(106).
USTB	USTreasuryBillOld	US Treasury Bill (Deprecated Value Use TBILL)
?	Wildcard	Wildcard entry for use on Security Definition Request
CD	CertificateOfDeposit	Certificate Of Deposit
DVPLDG	DeliveryVersusPledge	Delivery versus pledge
EUFRN	EuroCorporateFloatingRateNotes	Euro Corporate Floating Rate Notes
EXOTIC	Exotic	Exotic
FXNDS	NonDeliverableSwap	Non-deliverable Swap
MBS	MortgageBackedSecurities	Mortgage-backed Securities
RAN	RevenueAnticipationNote	Revenue Anticipation Note
SWING	SwingLineFacility	Swing Line Facility
TB	TreasuryBill	Treasury Bill - non US
CASH	Cash	Cash
CL	CallLoans	Call Loans
COLLBSKT	CollateralBasket	Collateral basket. A collection of securities held as collateral in the customer's collateral fund. The collateral fund is usually managed by a custodian.
DINP	DebtorInPossession	Debtor In Possession
FLR	Floor	Floor. In an interest rate floor, the buyer receives payments at the end of each period in which the rate index is below the agreed strike rate.
FRN	USCorporateFloatingRateNotes	US Corporate Floating Rate Notes
FXBN	FXBankNote	FX Bank Note
MIO	MortgageInterestOnly	Mortgage Interest Only
OOC	OptionsOnCombo	Options on Combo
REV	RevenueBonds	Revenue Bonds
TBOND	USTreasuryBond	US Treasury Bond
CP	CommercialPaper	Commercial Paper

Code	Name	Description
DEFLTED	Defaulted	Defaulted
FRA	FRA	Forward Rate Agreement
FXDN	ForeignCurrencyDiscountNote	Foreign Currency Discount Note. Discount notes issued in foreign currency by Fannie Mae.
MPO	MortgagePrincipalOnly	Mortgage Principal Only
Other	Other	Other
SFP	StructuredFinanceProduct	Structured finance product
SPCLA	SpecialAssessment	Special Assessment
TINT	InterestStripFromAnyBondOrNote	Interest Strip From Any Bond Or Note
XLINKD	IndexedLinked	Indexed Linked
DN	DepositNotes	Deposit Notes
ETN	ExchangeTradedNote	Exchange traded note
FUT	Future	Future
MPP	MortgagePrivatePlacement	Mortgage Private Placement
SPCLO	SpecialObligation	Special Obligation
STRUCT	StructuredNotes	Structured Notes
TBILL	USTreasuryBill	US Treasury Bill
TIPS	TreasuryInflationProtectedSecurities	Treasury Inflation Protected Securities
WITHDRN	Withdrawn	Withdrawn
EUCD	EuroCertificateOfDeposit	Euro Certificate Of Deposit
FWD	DerivativeForward	Derivative forward
MPT	MiscellaneousPassThrough	Miscellaneous Pass-through
MGRNLOAN	MarginLoan	Margin loan
REPLACD	Replaced	Replaced
SPCLT	SpecialTax	Special Tax
TCAL	PrincipalStripOfACallableBondOrNote	Principal Strip Of A Callable Bond Or Note
YANK	YankeeCorporateBond	Yankee Corporate Bond
DIMSUMCORP	OffshoreIssuedChineseYuanCorporateBond	Offshore issued Chinese Yuan (CNY) denominated corporate bond
EUCP	EuroCommercialPaper	Euro Commercial Paper
IRS	InterestRateSwap	Interest Rate Swap
MATURED	Matured	Matured
PFAND	Pfandbrief	Pfandbrief. Identify the issuer name in Issuer(106).
SECDERIV	SecuritizedDerivative	Securitized derivative

Code	Name	Description
TAN	TaxAnticipationNote	Tax Anticipation Note
TPRN	PrincipalStripFromANonCallable-BondOrNote	Principal Strip From A Non-Callable Bond Or Note
TRS	TotalReturnSwap	Total return swap
AMENDED	Amended	Amended and restated
ETF	ExchangeTradedFund	Exchange Traded Fund
LOANLEASE	LoanLease	Loan/lease
LQN	LiquidityNote	Liquidity Note
PRCORP	PreferredCorporateBond	Preferred Corporate Bond
TAXA	TaxAllocation	Tax Allocation
TBA	ToBeAnnounced	To Be Announced
TNOTE	USTreasuryNote	US Treasury Note
DIGITAL	DigitalAsset	Digital Asset. Asset that exists only in digital form or which is the digital representation of another asset (Source: ISO 24165 - Terms and Definitions).
DIMSUMSOV	OffshoreIssuedChineseYuanSovereignBond	Offshore issued Chinese Yuan (CNY) denominated sovereign bond
MTN	MediumTermNotes	Medium Term Notes
RETIRED	Retired	Retired
TECP	TaxExemptCommercialPaper	Tax Exempt Commercial Paper
ONITE	Overnight	Overnight
OOF	OptionsOnFutures	Options on Futures
SOV	SovereignBond	Sovereign Bond. Sovereign or government bond other than Euro and US issuer. Specify sovereign issuer in Issuer(106).
TMCP	TaxableMunicipalCP	Taxable Municipal CP
OOP	OptionsOnPhysical	Options on Physical - use not recommended
PN	PromissoryNote	Promissory Note
STN	ShortTermLoanNote	Short Term Loan Note
TFRN	USTreasuryFloatingRateNote	US Treasury Floating Rate Note
TRAN	TaxRevenueAnticipationNote	Tax Revenue Anticipation Note
OPT	Option	Option
PZFI	PlazosFijos	Plazos Fijos
VRDN	VariableRateDemandNote	Variable Rate Demand Note
SLQN	SecuredLiquidityNote	Secured Liquidity Note
SPOTFWD	SpotForward	Spot forward

Code	Name	Description
WAR	Warrant	Warrant
MCPID	MunicipalInterestBearingCommercialPaper	Municipal Interest Bearing Commercial Paper
SWAPTION	SwapOption	Swap option
TD	TimeDeposit	Time Deposit
TMB	TaxableMunicipalBond	Taxable Municipal Bond
XMISSION	Transmission	Transmission
INDEX	Index	General type for a contract based on an established index
TLQN	TermLiquidityNote	Term Liquidity Note
VRDO	VariableRateDemandObligation	Variable Rate Demand Obligation
BDBSKT	BondBasket	Bond basket
XCN	ExtendedCommNote	Extended Comm Note
CFD	ContractForDifference	Contract for difference
YCD	YankeeCertificateOfDeposit	Yankee Certificate Of Deposit
BAB	BankAcceptedBill	Bank Accepted Bill. Also known as Bank Bill.
CRLNSWAP	CorrelationSwap	Correlation swap
BNST	ShortTermBankNote	Short Term Bank Note
DVDNSWAP	DividendSwap	Dividend swap
CLCP	CallableCommercialPaper	Callable Commercial Paper
EQBSKT	EquityBasket	Equity basket
CN	CommercialNote	Commercial Note
EQFWD	EquityForward	Equity forward
CPIB	InterestBearingCommercialPaper	Interest Bearing Commercial Paper
RTRNSWAP	ReturnSwap	Return swap
EUMTN	EuroMediumTermNote	Euro Medium Term Note
VARSWAP	VarianceSwap	Variance swap
EUNCP	EuroNegotiableCommercialPaper	Euro Negotiable Commercial Paper
PRTFLIOSWAP	PortfolioSwaps	Portfolio swap
EUSTLQN	EuroStructuredLiquidityNote	Euro Structured Liquidity Note
FUTSWAP	FuturesOnASwap	Futures on a Swap
EUTD	EuroTimeDeposit	Euro Time Deposit
FWDSWAP	ForwardsOnASwap	Forwards on a Swap
FWDFRTAGMT	ForwardFreightAgreement	Forward Freight Agreement
JCD	JumboCertificateOfDeposit	Jumbo Certificate of Deposit



Code	Name	Description
MMF	MoneyMarketFund	Money Market Fund
SPREADBET	SpreadBetting	Spread Betting
ETC	ExchangeTradedCommodity	Exchange traded commodity
MN	MasterNote	Master Note. Short term notes issued by Federal Farm Credit Banks Funding Corporation to provide loans and funding under Federal Farm Credit System (FFCS).
NCD	NegotiableCertificateOfDeposit	Negotiable Certificate of Deposit
NCP	NegotiableCommercialPaper	Negotiable Commercial Paper
RCD	RetailCertificateOfDeposit	Retail Certificate of Deposit
TDR	TermDepositReceipt	Term Deposit Receipt

Used in components: [InstrumentLeg](#)

#### 180.2.2443 LegSecurityXML

XML definition for the leg security.

Type: [XMLData](#)

Used in components: [LegSecurityXML](#)

#### 180.2.2444 LegSecurityXML

The LegSecurityXML component is used to provide a definition in an XML format for the leg instrument.

Name	Mult.	Type	Description
<a href="#">LegSecurityXMLLen</a>	[0..1]	Length	Must be provided if LegSecurityXML(1872) field is specified and must immediately precede it.
<a href="#">LegSecurityXML</a>	[0..1]	XMLData	
<a href="#">LegSecurityXMLSchema</a>	[0..1]	String	

Used in components: [InstrumentLeg](#)

**180.2.2445 LegSecurityXMLLen**

The length of the LegSecurityXML(1872) data block.

Type: **Length**

Used in components: **LegSecurityXML**

**180.2.2446 LegSecurityXMLSchema**

The schema used to validate the contents of LegSecurityXML(1872).

Type: **String**

Used in components: **LegSecurityXML**

**180.2.2447 LegSeniority**

Specifies which issue (underlying bond) will receive payment priority in the event of a default.

Used to define a CDS instrument.

Type: **String**

Allowed values in SeniorityCodeSet:

Code	Name	Description
SD	SeniorSecured	Senior Secured
SR	Senior	Senior
SB	Subordinated	Subordinated
JR	Junior	Junior. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
MZ	Mezzanine	Mezzanine. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
SN	SeniorNonPreferred	Senior Non-Preferred. For CDS reference obligations of non-preferred senior debt issued by European Financials that constitute a layer of debt ranking between the bank's normal senior debt but above the bank's normal tier 2 subordinated debt (reference: ISDA Credit Market Infrastructure Group).

Used in components: **InstrumentLeg**

**180.2.2448 LegSettlCurrency**

Identifies settlement currency for the Leg.

See SettlCurrency (20) for description and valid values

Type: **Currency**

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**, **TrdInstrmtLegExecGrp**, **TrdInstrmt-LegGrp**

**180.2.2449 LegSettlCurrencyCodeSource**

Identifies class or source of the LegSettlCurrency(675) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**, **TrdInstrmtLegExecGrp**, **TrdInstrmt-LegGrp**

**180.2.2450 LegSettlDate**

Refer to description for SettlDate[64]

Type: **LocalMktDate**

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **LegQuotGrp**, **LegQuotStatGrp**, **QuotReqLegsGrp**, **SideCrossLegGrp**, **TrdInstrmtLegGrp**

**180.2.2451 LegSettlDisruptionProvision**

Specifies the consequences of bullion settlement disruption events.

Type: **int**

Allowed values in SettlDisruptionProvisionCodeSet:

Code	Name	Description
1	Negotiation	Negotiation
2	Cancellation	Cancellation and payment

Used in components: **InstrumentLeg**

**180.2.2452 LegSettledEntityMatrixPublicationDate**

The publication date of the applicable version of the matrix. When this element is omitted, the Standard Terms Supplement defines rules for which version of the matrix is applicable.

Type: **LocalMktDate**

Used in components: **InstrumentLeg**

**180.2.2453 LegSettledEntityMatrixSource**

Relevant settled entity matrix source.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.2454 LegSettleOnOpenFlag**

Indicator to determine if the instrument is to settle on open.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.2455 LegSettlMethod**

Settlement method for a contract or instrument. Additional values may be used with bilateral agreement.

Type: **String**

Allowed values in SettlMethodCodeSet:

Code	Name	Description
C	CashSettlementRequired	Cash settlement required
P	PhysicalSettlementRequired	Physical settlement required
E	Election	Election at exercise. The settlement method will be elected at the time of contract exercise.

Used in components: **InstrumentLeg**

**180.2.2456 LegSettlMethodElectingPartySide**

Side value of the party electing the settlement method.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in components: **LegOptionExercise**

**180.2.2457 LegSettlMethodElectionDateAdjusted**

The adjusted settlement method election date.

Type: **LocalMktDate**

Used in components: **LegSettlMethodElectionDate**

**180.2.2458 LegSettlMethodElectionDateBusinessCenter**

The business center calendar used for date adjustment of the settlement method election unadjusted or relative date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegSettlMethodElectionDateBusinessCenterGrp**

**180.2.2459 LegSettlMethodElectionDateBusinessCenterGrp**

LegSettlMethodElectionDateBusinessCenterGrp is a repeating subcomponent within the LegSettlMethodElectionDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegSettlMethodElectionDateBusinessCenters	[1..1]	NumInGroup	
LegSettlMethodElectionDateBusinessCenter	[0..1]	String	Required if NoLegSettlMethodElectionDateBusinessCenters(42581) > 0.

Used in components: **LegSettlMethodElectionDate**

**180.2.2460 LegSettlMethodElectionDateBusinessDayConvention**

The settlement method election date adjustment business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.

Code	Name	Description
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegSettlMethodElectionDate](#)

### 180.2.2461 LegSettlMethodElectionDate

The LegSettlMethodElectionDate component is a subcomponent within the LegOptionExercise component used to report the settlement method election date.

Name	Mult.	Type	Description
<a href="#">LegSettlMethodElectionDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegSettlMethodElectionDateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to LegOptionExercise.
<a href="#">LegSettlMethodElectionDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to LegOptionExercise.
<a href="#">LegSettlMethodElectionDateRelativeTo</a>	[0..1]	int	
<a href="#">LegSettlMethodElectionDateOffsetPeriod</a>	[0..1]	int	Conditionally required when LegSettlMethodElectionDateOffsetUnit(42578) is specified.
<a href="#">LegSettlMethodElectionDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegSettlMethodElectionDateOffsetPeriod(42577) is specified.
<a href="#">LegSettlMethodElectionDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">LegSettlMethodElectionDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [LegOptionExercise](#)

**180.2.2462 LegSettlMethodElectionDateOffsetDayType**

Specifies the day type of the relative settlement method election date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **LegSettlMethodElectionDate**

**180.2.2463 LegSettlMethodElectionDateOffsetPeriod**

Time unit multiplier for the relative settlement method election date offset.

Type: **int**

Used in components: **LegSettlMethodElectionDate**

**180.2.2464 LegSettlMethodElectionDateOffsetUnit**

Time unit associated with the relative settlement method election date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegSettlMethodElectionDate**



**180.2.2465 LegSettlMethodElectionDateRelativeTo**

Specifies the anchor date when the settlement method election date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegSettlMethodElectionDate**

**180.2.2466 LegSettlMethodElectionDateUnadjusted**

The unadjusted settlement method election date.

Type: **LocalMktDate**

Used in components: **LegSettlMethodElectionDate**

**180.2.2467 LegSettlRateDisruptionFallbackGrp**

The LegSettlRateDisruptionsFallbackGrp is a repeating subcomponent of the LegPaymentStreamNon-DeliverableSettlTerms component used to specify the method, prioritized by the order it is listed, to get a replacement rate for a disrupted settlement rate option for a non-deliverable settlement currency.

Name	Mult.	Type	Description
<b>NoLegSettlRateFallbacks</b>	[1..1]	NumInGroup	
<b>LegSettlRatePostponementMaximum-Days</b>	[0..1]	int	Required if NoLegSettlRateFallbacks(40902) > 0.
<b>LegSettlRateFallbackRateSource</b>	[0..1]	Component	
<b>LegSettlRatePostponementSurvey</b>	[0..1]	Boolean	
<b>LegSettlRatePostponementCalculationAgent</b>	[0..1]	CodeSet	

Used in components: **LegPaymentStreamNonDeliverableSettlTerms**

**180.2.2468 LegSettlRateFallbackRateSource**

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in components: [LegSettlRateFallbackRateSource](#)

#### 180.2.2469 LegSettlRateFallbackRateSource

LegSettlRateFallbackRateSource is a subcomponent of the LegSettlRateDisruptionFallbackGrp component used to specify the rate source in the event of rate disruption fallback.

Name	Mult.	Type	Description
<a href="#">LegSettlRateFallbackRateSource</a>	[0..1]	CodeSet	
<a href="#">LegSettlRateFallbackReferencePage</a>	[0..1]	String	Conditionally required when LegSettlRateFallbackRateSource(40366) = 3 (ISDA Settlement Rate Option) or 99 (Other).

Used in groups: [LegSettlRateDisruptionFallbackGrp](#)

#### 180.2.2470 LegSettlRateFallbackReferencePage

Identifies the reference "page" from the rate source.

When LegSettlRateFallbackRateSource(40366) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: [String](#)

Used in components: [LegSettlRateFallbackRateSource](#)

**180.2.2471 LegSettlRateIndex**

In an outright or forward commodity trade that is cash settled this is the index used to determine the cash payment.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.2472 LegSettlRateIndexLocation**

This is an optional qualifying attribute of LegSettlementRateIndex(2176) such as the delivery zone for an electricity contract.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.2473 LegSettlRatePostponementCalculationAgent**

Used to identify the settlement rate postponement calculation agent.

Type: **int**

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreement	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

Used in groups: **LegSettlRateDisruptionFallbackGrp**

**180.2.2474 LegSettlRatePostponementMaximumDays**

The maximum number of days to wait for a quote from the disrupted settlement rate option before proceeding to this method.

Type: **int**

Used in groups: **LegSettlRateDisruptionFallbackGrp**

**180.2.2475 LegSettlRatePostponementSurvey**

Indicates whether to request a settlement rate quote from the market.

Type: **Boolean**

Used in groups: **LegSettlRateDisruptionFallbackGrp**

**180.2.2476 LegSettlType**

Indicates order settlement period. If present, LegSettlDate (588) overrides this field. If both LegSettlType (587) and LegSettlDate (588) are omitted, the default for LegSettlType (587) is 0 (Regular)

Regular is defined as the default settlement period for the particular security on the exchange of execution.

In Fixed Income the contents of this field may influence the instrument definition if the LegSecurityID (602) is ambiguous. In the US an active Treasury offering may be re-opened, and for a time one CUSIP will apply to both the current and "when-issued" securities. Supplying a value of "7" clarifies the instrument description; any other value or the absence of this field should cause the respondent to default to the active issue.

Additionally the following patterns may be used as well as enum values

Dx = FX tenor expression for "days", e.g. "D5", where "x" is any integer > 0

Mx = FX tenor expression for "months", e.g. "M3", where "x" is any integer > 0

Wx = FX tenor expression for "weeks", e.g. "W13", where "x" is any integer > 0

Yx = FX tenor expression for "years", e.g. "Y1", where "x" is any integer > 0.

Note that for FX the tenors expressed using Dx, Mx, Wx, and Yx values do not denote business days, but calendar days.

Type: **String**

Allowed values in SettlTypeCodeSet:

Code	Name	Description
0	Regular	Regular / FX Spot settlement (T+1 or T+2 depending on currency)
1	Cash	Cash (TOD / T+0)
2	NextDay	Next Day (TOM / T+1)
3	TPlus2	T+2

Code	Name	Description
4	TPlus3	T+3
5	TPlus4	T+4
6	Future	Future
7	WhenAndIfIssued	When And If Issued
8	SellersOption	Sellers Option
9	TPlus5	T+5
B	BrokenDate	Broken date. Use within FX to specify a non-standard tenor. The use of SettlDate(64) is required to specify the actual settlement date when SettlType(63) = B (Broken date).
C	FXSpotNextSettlement	FX Spot Next settlement (Spot+1, aka next day)

Used in groups: [InstrmtLegExecGrp](#), [InstrmtLegSecListGrp](#), [LegOrdGrp](#), [LegQuotGrp](#), [LegQuotStatGrp](#), [QuotReqLegsGrp](#), [SecLstUpdRelSymsLegGrp](#), [SideCrossLegGrp](#), [TrdInstrmtLegGrp](#)

### 180.2.2477 LegShortSaleExemptionReason

Indicates the reason a short sale is exempted from applicable regulation (e.g. Reg SHO addendum (b)(1) in the U.S.)

Type: [int](#)

Allowed values in ShortSaleExemptionReasonCodeSet:

Code	Name	Description
0	ExemptionReasonUnknown	Exemption reason unknown. An exemption reason not provided or received.
1	IncomingSSE	Income sell short exempt. Agency broker has the customer's exemption reason, which is not explicitly provided to executing broker.
2	AboveNationalBestBid	Above national best bid (broker/dealer provision). Broker / dealer responsible for enforcing exemption rule has determined that the order is priced one or more ticks above the nation best bid of the security to be traded.
3	DelayedDelivery	Delayed delivery. The broker-dealer has a reasonable basis to believe the seller owns the covered security (pursuant to Rule 200 in the U.S.), but is subject to restrictions on delivery, provided that the seller intends to deliver the security as soon as all restrictions on delivery have been removed.

Code	Name	Description
4	OddLot	Odd lot. The broker-dealer has a reasonable basis to believe the sale is by a market maker to offset customer odd-lot orders or to liquidate an odd-lot position that changes such broker's or dealer's position by no more than a unit of trading.
5	DomesticArbitrage	Domestic arbitrage. The sale is connected to a bona-fide domestic arbitrage transaction.
6	InternationalArbitrage	International arbitrage. The sale is connected to an international arbitrage transaction.
7	UnderwriterOrSyndicateDistribution	Underwriter or syndicate distribution. The short sale is (i) by an underwriter or member of a syndicate or group participating in the distribution of a security in connection with an over-allotment of securities; or (ii) is for purposes of a lay-off sale by an underwriter or member of a syndicate or group in connection with a distribution of securities through a rights or standby underwriting commitment.
8	RisklessPrincipal	Riskless principal. The short sale is by a broker or dealer effecting the execution of a customer purchase or the execution of a customer "long" sale on a riskless principal basis.
9	VWAP	VWAP. The short sale order is for the sale of a covered security at the volume weighted average price (VWAP) meeting certain criteria.

Used in groups: [InstrmtLegExecGrp](#), [LegOrdGrp](#), [SideCrossLegGrp](#), [TrdInstrmtLegExecGrp](#), [TrdInstrmtLegGrp](#)

### 180.2.2478 LegShortSaleRestriction

Indicates whether a restriction applies to short selling a security.

Type: [int](#)

Allowed values in ShortSaleRestrictionCodeSet:

Code	Name	Description
0	NoRestrictions	No restrictions
1	SecurityNotShortable	Security is not shortable
2	SecurityNotShortableAtOrBelowBestBid	Security not shortable at or below the best bid

Code	Name	Description
3	SecurityNotShortableWithoutPre-Borrow	Security is not shortable without pre-borrow

Used in components: **InstrumentLeg**

### 180.2.2479 LegSide

The side of this individual leg (multileg security).

See Side (54) field for description and values

Type: **char**

Allowed values in SideCodeSet:

Code	Name	Description
1	Buy	Buy. For Securities Financing indicates the receipt of securities or collateral.
2	Sell	Sell. For Securities Financing indicates the delivery of securities or collateral.
3	BuyMinus	Buy minus
4	SellPlus	Sell plus
5	SellShort	Sell short
6	SellShortExempt	Sell short exempt
7	Undisclosed	Undisclosed
8	Cross	Cross (orders where counterparty is an exchange, valid for all messages except IOIs)
9	CrossShort	Cross short
A	CrossShortExempt	Cross short exempt
B	AsDefined	"As Defined" (for use with multileg instruments)
C	Opposite	"Opposite" (for use with multileg instruments)
D	Subscribe	Subscribe (e.g. CIV)
E	Redeem	Redeem (e.g. CIV)
F	Lend	Lend (FINANCING - identifies direction of collateral)
G	Borrow	Borrow (FINANCING - identifies direction of collateral)

---

Code	Name	Description
H	SellUndisclosed	Sell undisclosed. In the context of ESMA RTS 22, this allows for reporting of transactions where the investment firm (broker) is not able to determine whether the sell is a short sale transaction. Corresponds to RTS 22 "short selling indicator" value of 'UNDI'.

---

Used in components: [InstrumentLeg](#)

#### **180.2.2480 LegSpecialDividendsIndicator**

Indicates whether special dividends are applicable.

Type: [Boolean](#)

Used in components: [LegDividendConditions](#)

#### **180.2.2481 LegStartDate**

Start date of a financing deal, i.e. the date the buyer pays the seller cash and takes control of the collateral.

Type: [LocalMktDate](#)

Used in components: [LegFinancingDetails](#)

#### **180.2.2482 LegStateOrProvinceOfIssue**

Multileg instrument's individual leg security's StateOrProvinceOfIssue.

See StateOrProvinceOfIssue (471) field for description

Type: [String](#)

Used in components: [InstrumentLeg](#)

#### **180.2.2483 LegStipulations**

The LegStipulations component block has the same usage as the Stipulations component block, but for a leg instrument in a multi-legged security.



Name	Mult.	Type	Description
NoLegStipulations	[1..1]	NumInGroup	
LegStipulationType	[0..1]	CodeSet	Required if NoLegStipulations >0
LegStipulationValue	[0..1]	String	

Used in groups: InstrmtLegExecGrp, InstrmtLegIOIGrp, InstrmtLegSecListGrp, LegOrdGrp, LegQuotGrp, LegQuotStatGrp, QuotReqLegsGrp, SecLstUpdRelSymsLegGrp, SideCrossLegGrp, TrdInstrmtLegGrp

### 180.2.2484 LegStipulationType

For Fixed Income, type of Stipulation for this leg.

See StipulationType (233) for description and valid values

Type: String

Allowed values in StipulationTypeCodeSet:

Code	Name	Description
ABS	AbsolutePrepaymentSpeed	Absolute Prepayment Speed
AMT	AlternativeMinimumTax	Alternative Minimum Tax (Y/N)
INCURRCVY	IncurredRecovery	Incurred recovery (Y/N). Specifies whether incurred recovery is applicable (Y) or not (N). Outstanding Swap Notional Amount is defined at any time on any day, as the greater of: (a) Zero; If Incurred Recovery Amount Applicable: (b) The Original Swap Notional Amount minus the sum of all Incurred Loss Amounts and all Incurred Recovery Amounts (if any) determined under this Confirmation at or prior to such time. Incurred Recovery Amount not populated: (b) The Original Swap Notional Amount minus the sum of all Incurred Loss Amounts determined under this Confirmation at or prior to such time. 2009 CDX Tranche Terms.
ADDTRM	AdditionalTerm	Additional term. Used for representing information contained in the Additional Terms field of the 2003 Master Credit Derivatives confirm.
AUTOREINV	AutoReinvestment	Auto Reinvestment at <rate> or better
CPP	ConstantPrepaymentPenalty	Constant Prepayment Penalty
BANKQUAL	BankQualified	Bank qualified (Y/N)
CPR	ConstantPrepaymentRate	Constant Prepayment Rate

Code	Name	Description
MODEQTYDLVY	ModifiedEquityDelivery	Modified equity delivery. Indicates whether delivery of selected obligations having an amount greater than the reference entity notional amount is allowed (Y) or (N). 2005 iTraxx tranching Transactions Standard Terms Supplement.
BGNCON	BargainConditions	Bargain conditions (see StipulationValue (234) for values)
CPY	ConstantPrepaymentYield	Constant Prepayment Yield
NOREFOBLIG	NoReferenceObligation	No reference obligation (Y/N). When specified as "Y" this indicates that there is no Reference Obligation associated with this Credit Default Swap and that there will never be one. 2003 ISDA Credit Derivatives Definitions.
COUPON	CouponRange	Coupon range
HEP	FinalCPRofHomeEquityPrepaymentCurve	final CPR of Home Equity Prepayment Curve
UNKREFOBLIG	UnknownReferenceObligation	Unknown reference obligation (Y/N). When specified as "Y" this indicates that the Reference obligation associated with the Credit Default Swap is currently not known. This is not valid for Legal Confirmation purposes, but is valid for earlier stages in the trade life cycle (e.g. Broker Confirmation). 2003 FpML-CD-4.0.
ALLGUARANTEES	AllGuarantees	All guarantees (Y/N). Indicates whether an obligation of the Reference Entity, guaranteed by the Reference Entity on behalf of a non-Affiliate, is to be considered an Obligation for the purpose of the transaction (Y) or (N). ISDA 2003 Term: All Guarantees.
CURRENCY	ISOCurrencyCode	ISO Currency Code
MHP	PercentOfManufacturedHousingPrepaymentCurve	Percent of Manufactured Housing Prepayment Curve
CUSTOMDATE	CustomStart	Custom start/end date
MPR	MonthlyPrepaymentRate	Monthly Prepayment Rate

Code	Name	Description
REFPX	ReferencePrice	Reference price (Y/N). Specifies the reference price expressed as a percentage between 0 and 1 (e.g. 0.05 is 5%). The reference price is used to determine (a) for physically settled trades, the Physical Settlement Amount, which equals the Floating Rate Payer Calculation Amount times the Reference Price and (b) for cash settled trades, the Cash Settlement Amount, which equals the greater of (i) the difference between the Reference Price and the Final Price and (ii) zero. ISDA 2003 Term: Reference Price.
GEOG	Geographics	Geographics and % range (ex. 234=CA 0-80 [minimum of 80% California assets])
PPC	PercentOfProspectusPrepaymentCurve	Percent of Prospectus Prepayment Curve
REFPOLICY	ReferencePolicy	Reference policy (Y/N). Indicates whether the reference obligation is guaranteed (Y), or not (N), under a reference policy. If the Reference Obligation is guaranteed under a Reference Policy, and such Reference Policy by its terms excludes any component of the Expected Principal Amount for purposes of determining the liability of the relevant Insurer, or the Insurer is otherwise not required to pay any such amounts under the terms of the Reference Policy, the relevant component or amount shall also be excluded for purposes of determining the Expected Principal Amount with respect to any determination of Principal Shortfall hereunder. 2006 ISDA CDS on MBS Terms.
HAIRCUT	ValuationDiscount	Valuation Discount
PSA	PercentOfBMAPrepaymentCurve	Percent of BMA Prepayment Curve
SECRDLIST	SecuredList	Secured list (Y/N). Specifies whether a list of Syndicated Secured Obligations (also known as the Relevant Secured List) exists (Y), or not (N), for the Reference Entity. With respect to any day, the list of Syndicated Secured Obligations of the Designated Priority of the Reference Entity published by Markit Group Limited or any successor thereto appointed by the Specified Dealers (the "Secured List Publisher") on or most recently before such day, which list is currently available at [ <a href="http://www.markit.com">http://www.markit.com</a> ]. ISDA 2003 Term: Relevant Secured List.
INSURED	Insured	Insured (Y/N)
SMM	SingleMonthlyMortality	Single Monthly Mortality

Code	Name	Description
ISSUE	IssueDate	Year Or Year/Month of Issue (ex. 234=2002/09)
ISSUER	Issuer	Issuer's ticker
ISSUESIZE	IssueSizeRange	issue size range
LOOKBACK	LookbackDays	Lookback Days
LOT	ExplicitLotIdentifier	Explicit lot identifier
LOTVAR	LotVariance	Lot Variance (value in percent maximum over- or under-allocation allowed)
MAT	MaturityYearAndMonth	Maturity Year And Month
MATURITY	MaturityRange	Maturity range
MAXSUBS	MaximumSubstitutions	Maximum substitutions (Repo)
MINDNOM	MinimumDenomination	Minimum denomination
MININCR	MinimumIncrement	Minimum increment
MINQTY	MinimumQuantity	Minimum quantity
PAYFREQ	PaymentFrequency	Payment frequency, calendar
PIECES	NumberOfPieces	Number Of Pieces
PMAX	PoolsMaximum	Pools Maximum
PPL	PoolsPerLot	Pools per Lot
PPM	PoolsPerMillion	Pools per Million
PPT	PoolsPerTrade	Pools per Trade
PRICE	PriceRange	Price Range
PRICEFREQ	PricingFrequency	Pricing frequency
PROD	ProductionYear	Production Year
PROTECT	CallProtection	Call protection
PURPOSE	Purpose	Purpose
PXSOURCE	BenchmarkPriceSource	Benchmark price source
RATING	RatingSourceAndRange	Rating source and range
REDEMPTION	TypeOfRedemption	Type Of Redemption - values are: NonCallable, Prefunded, EscrowedToMaturity, Puttable, Convertible
RESTRICTED	Restricted	Restricted (Y/N)
SECTOR	MarketSector	Market Sector
SECTYPE	SecurityTypeIncludedOrExcluded	Security Type included or excluded
STRUCT	Structure	Structure
SUBSFREQ	SubstitutionsFrequency	Substitutions frequency (Repo)
SUBSLEFT	SubstitutionsLeft	Substitutions left (Repo)

Code	Name	Description
TEXT	FreeformText	Freeform Text
TRDVAR	TradeVariance	Trade Variance (value in percent maximum over- or under-allocation allowed)
WAC	WeightedAverageCoupon	Weighted Average Coupon - value in percent (exact or range) plus "Gross" or "Net" of servicing spread (the default) (ex. 234=6.5-Net [minimum of 6.5% net of servicing fee])
WAL	WeightedAverageLifeCoupon	Weighted Average Life Coupon - value in percent (exact or range)
WALA	WeightedAverageLoanAge	Weighted Average Loan Age - value in months (exact or range)
WAM	WeightedAverageMaturity	Weighted Average Maturity - value in months (exact or range)
WHOLE	WholePool	Whole Pool (Y/N)
YIELD	YieldRange	Yield Range
AVFICO	AverageFICOScore	Average FICO Score
ORIGAMT	OriginalAmount	Original amount. The original issued amount of a mortgage backed security or other loan/asset backed security.
AVSIZE	AverageLoanSize	Average Loan Size
POOLEFFDT	PoolEffectiveDate	Pool effective date
MAXBAL	MaximumLoanBalance	Maximum Loan Balance
POOLINITFCTR	PoolInitialFactor	Pool initial factor. For mortgage backed securities, the part of the mortgage that is outstanding on trade inception, i.e. has not been repaid yet as principal. It is expressed as a multiplier factor to the mortgage: where 1 means that the whole mortgage amount is outstanding, 0.8 means that 80% remains to be repaid and 20% has been repaid.
POOL	PoolIdentifier	Pool Identifier
TRANCHE	Tranche	Tranche identifier. Identifies the tranche of a mortgage backed security, loan, collateralized mortgage obligation or similar securities that can be split into different risk or maturity (for example) classes.
ROLLTYPE	TypeOfRollTrade	Type of Roll trade
SUBSTITUTION	Substitution	Substitution (Y/N). Indicates whether substitution is applicable (Y) or (N).

Code	Name	Description
MULTEXCHFLLBCK	MULTEXCHFLLBCK	Multiple exchange fallback (Y/N). For an index option transaction, indicates whether a relevant "Multiple Exchange Index Annex" is applicable (Y) to the transaction or not (N). This annex defines additional provisions which are applicable where an index is comprised of component securities that are traded on multiple exchanges.
REFTRADE	ReferenceToRollingOrClosing-Trade	Reference to rolling or closing trade
COMPSECFLBCK	COMPSECFLBCK	Component security fallback (Y/N). For an index option transaction, indicates whether a relevant "Component Security Index Annex" is applicable (Y) to the transaction or not (N).
REFPRIN	PrincipalOfRollingOrClosing-Trade	Principal to rolling or closing trade
LOCLJRSCTN	LOCLJRSCTN	Local jurisdiction (Y/N). "Local Jurisdiction" is used in the AEJ Master Confirmation to determine applicability (Y), or not (N), of local taxes (including taxes, duties, and similar charges) imposed by the taxing authority of the local jurisdiction.
REFINT	InterestOfRollingOrClosingTrade	Interest of rolling or closing trade
AVAILQTY	AvailableOfferQuantity-ToBeShownToTheStreet	Available offer quantity to be shown to the street
RELVJRSCTN	RELVJRSCTN	Relevant jurisdiction (Y/N). "Relevant Jurisdiction" is used in the AEJ Master Confirmation to determine applicability (Y), or not (N), of local taxes (including taxes, duties and similar charges) that would be imposed by the taxing authority of the "country of underlier" on a "hypothetical broker dealer" assuming that the applicable hedge positions are held by its office in the Relevant Jurisdiction.
BROKERCREDIT	BrokerCredit	Broker's sales credit
INTERNALPX	OfferPriceToBeShownToInternalBrokers	Offer price to be shown to internal brokers
INTERNALQTY	OfferQuantityToBeShownToInternalBrokers	Offer quantity to be shown to internal brokers
LEAVEQTY	TheMinimumResidualOffer-Quantity	The minimum residual offer quantity
MAXORDQTY	MaximumOrderSize	Maximum order size
ORDRINCR	OrderQuantityIncrement	Order quantity increment

Code	Name	Description
PRIMARY	PrimaryOrSecondaryMarketIndicator	Primary or Secondary market indicator
SALESCREDITOVR	BrokerSalesCreditOverride	Broker sales credit override
TRADERCREDIT	TraderCredit	Trader's credit
DISCOUNT	DiscountRate	Discount Rate (when price is denominated in percent of par)
YTM	YieldToMaturity	Yield to Maturity (when YieldType(235) and Yield(236) show a different yield)
PAYOFF	InterestPayoffOfRollingOrAmendingTrade	Interest payoff of rolling or amending trade

Used in groups: [LegStipulations](#)

#### 180.2.2485 LegStipulationValue

For Fixed Income, value of stipulation.

See StipulationValue (234) for description and valid values

Type: [String](#)

Used in groups: [LegStipulations](#)

#### 180.2.2486 LegStrategyType

Specifies the type of trade strategy.

Type: [String](#)

Allowed values in StrategyTypeCodeSet:

Code	Name	Description
STD	Straddle	Straddle
STG	Strangle	Strangle
BF	Butterfly	Butterfly
CNDR	Condor	Condor
CISN	CallableInversibleSnowball	Callable inversible snowball
OTHER	Other	Other

Used in components: [InstrumentLeg](#)

#### **180.2.2487 LegStreamAssetAttributeGrp**

The LegStreamAssetAttributeGrp is a repeating subcomponent of the LegStreamCommodity component used to detail commodity attributes, quality standards and reject limits.

Name	Mult.	Type	Description
<a href="#">NoLegStreamAssetAttributes</a>	[1..1]	NumInGroup	
<a href="#">LegStreamAssetAttributeType</a>	[0..1]	String	Required if NoLegStreamAssetAttributes(41452) > 0.
<a href="#">LegStreamAssetAttributeValue</a>	[0..1]	String	
<a href="#">LegStreamAssetAttributeLimit</a>	[0..1]	String	

Used in components: [LegStreamCommodity](#)

#### **180.2.2488 LegStreamAssetAttributeLimit**

Limit or lower acceptable value of the attribute.

Type: [String](#)

Used in groups: [LegStreamAssetAttributeGrp](#)

#### **180.2.2489 LegStreamAssetAttributeType**

Specifies the name of the attribute.

See [http://www.fixtradingcommunity.org/codelists#Asset\\_Attribute\\_Types](http://www.fixtradingcommunity.org/codelists#Asset_Attribute_Types) for code list of applicable asset attribute types.

Type: [String](#)

Used in groups: [LegStreamAssetAttributeGrp](#)

#### **180.2.2490 LegStreamAssetAttributeValue**

Specifies the value of the attribute.

Type: [String](#)

Used in groups: [LegStreamAssetAttributeGrp](#)



**180.2.2491 LegStreamCalculationBalanceOfFirstPeriod**

When specified and set to 'Y', it indicates that the first calculation period should run from the effective date to the end of the calendar period in which the effective date falls (e.g. Jan 15 - Jan 31 if the calculation periods are one month long and effective date is Jan 15.). If 'N' or not specified, it indicates that the first calculation period should run from the effective date for one whole period (e.g. Jan 15 to Feb 14 if the calculation periods are one month long and the effective date is Jan 15.).

Type: **Boolean**

Used in components: **LegStreamCalculationPeriodDates**

**180.2.2492 LegStreamCalculationCorrectionPeriod**

Time unit multiplier for the length of time after the publication of the data when corrections can be made.

Type: **int**

Used in components: **LegStreamCalculationPeriodDates**

**180.2.2493 LegStreamCalculationCorrectionUnit**

Time unit associated with the length of time after the publication of the data when corrections can be made.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in components: **LegStreamCalculationPeriodDates**

**180.2.2494 LegStreamCalculationFrequencyPeriod**

Time unit multiplier for the frequency at which calculation period end dates occur.

Type: **int**

Used in components: **LegStreamCalculationPeriodDates**

**180.2.2495 LegStreamCalculationFrequencyUnit**

Time unit associated with the frequency at which calculation period end dates occur.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: **LegStreamCalculationPeriodDates**

**180.2.2496 LegStreamCalculationPeriodBusinessCenter**

The business center calendar used to adjust calculation periods, e.g. "GLBO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegStreamCalculationPeriodBusinessCenterGrp**

**180.2.2497 LegStreamCalculationPeriodBusinessCenterGrp**

LegStreamCalculationPeriodBusinessCenterGrp is a repeating subcomponent within the LegStreamCalculationPeriodDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegStreamCalculationPeriodBusinessCenters	[1..1]	NumInGroup	
LegStreamCalculationPeriodBusinessCenter	[0..1]	String	Required if NoLegStreamCalculationPeriodBusinessCenters(40940) > 0.

Used in components: [LegStreamCalculationPeriodDates](#)

**180.2.2498 LegStreamCalculationPeriodBusinessDayConvention**

The business day convention used to adjust calculation periods. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegStreamCalculationPeriodDates](#)

**180.2.2499 LegStreamCalculationPeriodDate**

The adjusted or unadjusted fixed calculation period date.

Type: [LocalMktDate](#)

Used in groups: [LegStreamCalculationPeriodDateGrp](#)

**180.2.2500 LegStreamCalculationPeriodDateGrp**

The LegStreamCalculationPeriodDateGrp is a repeating subcomponent of the LegStreamCalculationPeriodDates component used to detail fixed dates for the swap stream.

Name	Mult.	Type	Description
<a href="#">NoLegStreamCalculationPeriodDates</a>	[1..1]	NumInGroup	
<a href="#">LegStreamCalculationPeriodDate</a>	[0..1]	LocalMktDate	Required if NoLegStreamCalculationPeriodDates(41638) > 0.
<a href="#">LegStreamCalculationPeriodDateType</a>	[0..1]	CodeSet	

Used in components: [LegStreamCalculationPeriodDates](#)

**180.2.2501 LegStreamCalculationPeriodDates**

LegStreamCalculationPeriodDates is a subcomponent of the LegStreamGrp component used to specify the calculation period dates of the stream.

Name	Mult.	Type	Description
<a href="#">LegStreamCalculationPeriodDatesXID</a>	[0..1]	XID	
<a href="#">LegStreamCalculationPeriodDatesX- IDRef</a>	[0..1]	XIDREF	
<a href="#">LegStreamCalculationPeriodBusiness- DayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg stream calculation period dates.

Name	Mult.	Type	Description
LegStreamCalculationPeriodBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg stream calculation period dates.
LegStreamCalculationPeriodDateGrp	[0..*]	Group	
LegStreamFirstPeriodStartDateUnadjusted	[0..1]	LocalMktDate	
LegStreamFirstPeriodStartDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg stream calculation period dates.
LegStreamFirstPeriodStartDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg stream calculation period dates.
LegStreamFirstPeriodStartDateAdjusted	[0..1]	LocalMktDate	
LegStreamFirstRegularPeriodStartDateUnadjusted	[0..1]	LocalMktDate	
LegStreamFirstCompoundingPeriodEndDateUnadjusted	[0..1]	LocalMktDate	
LegStreamLastRegularPeriodEndDateUnadjusted	[0..1]	LocalMktDate	
LegStreamCalculationFrequencyPeriod	[0..1]	int	Conditionally required when LegStreamCalculationFrequencyUnit(40275) is specified.
LegStreamCalculationFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegStreamCalculationFrequencyPeriod(40274) is specified.
LegStreamCalculationRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the stream calculation period dates.
LegStreamCalculationBalanceOfFirstPeriod	[0..1]	Boolean	

Name	Mult.	Type	Description
LegStreamCalculationCorrectionPeriod	[0..1]	int	Conditionally required when LegStreamCalculationCorrectionUnit(41645) is specified.
LegStreamCalculationCorrectionUnit	[0..1]	CodeSet	Conditionally required when LegStreamCalculationCorrectionPeriod(41644) is specified.

Used in groups: [LegStreamGrp](#)

#### 180.2.2502 LegStreamCalculationPeriodDatesXID

Identifier of this calculation period for cross referencing elsewhere in the message.

Type: [XID](#)

Used in components: [LegStreamCalculationPeriodDates](#)

#### 180.2.2503 LegStreamCalculationPeriodDatesXIDRef

Cross reference to another calculation period for duplicating its properties.

Type: [XIDREF](#)

Used in components: [LegStreamCalculationPeriodDates](#)

#### 180.2.2504 LegStreamCalculationPeriodDateType

Specifies the type of fixed calculation period date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: [int](#)

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [LegStreamCalculationPeriodDateGrp](#)

**180.2.2505 LegStreamCalculationRollConvention**

The convention for determining the sequence of end dates. It is used in conjunction with a specified frequency. Used only to override the roll convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelfthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	FourteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month

Code	Name	Description
28	TwentyEighthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [LegStreamCalculationPeriodDates](#)

#### 180.2.2506 LegStreamCommodityAltID

Alternate security identifier value for the commodity.

Type: [String](#)

Used in groups: [LegStreamCommodityAltIDGrp](#)



**180.2.2507 LegStreamCommodityAltIDGrp**

LegStreamCommodityAltIDGrp is a subcomponent of the LegStreamCommodity component used to specify alternate identifiers.

Name	Mult.	Type	Description
NoLegStreamCommodityAltIDs	[1..1]	NumInGroup	
LegStreamCommodityAltID	[0..1]	String	Required if NoLegStreamCommodityAltIDs(41674) > 0.
LegStreamCommodityAltIDSource	[0..1]	String	Required if NoLegStreamCommodityAltIDs(41674) > 0.

Used in components: [LegStreamCommodity](#)

**180.2.2508 LegStreamCommodityAltIDSource**

Identifies the class or source of the alternate commodity security identifier.

Type: [String](#)

Used in groups: [LegStreamCommodityAltIDGrp](#)

**180.2.2509 LegStreamCommodityBase**

Specifies the general base type of the commodity traded. Where possible, this should follow the naming convention used in the 2005 ISDA Commodity Definitions.

Type: [String](#)

Used in components: [LegStreamCommodity](#)

**180.2.2510 LegStreamCommodity**

LegStreamCommodity is a subcomponent of the LegStream component used to identify and describe the underlying commodity.

Name	Mult.	Type	Description
LegStreamCommodityBase	[0..1]	String	
LegStreamCommodityType	[0..1]	String	

Name	Mult.	Type	Description
LegStreamCommoditySecurityID	[0..1]	String	Conditionally required when LegStreamCommoditySecurityIDSource(41651) is specified.
LegStreamCommoditySecurityID-Source	[0..1]	CodeSet	Conditionally required when LegStreamCommoditySecurityID(41650) is specified.
LegStreamCommodityAltIDGrp	[0..*]	Group	
LegStreamCommodityDesc	[0..1]	String	
EncodedLegStreamCommodityDescLen	[0..1]	Length	Must be set if EncodedLegStreamCommodityDesc(41654) field is specified and must immediately precede it.
EncodedLegStreamCommodityDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the LegStreamCommodityDesc(41652) field in the encoded format specified via the MessageEncoding(347) field.
LegStreamCommodityDeliveryPricingRegion	[0..1]	String	May be used to specify the delivery or pricing region of a non-standard commodity swap contract (e.g. when InstrAttribType(871)=38 (US standard contract indicator) and InstrAttribValue(872)=N).
LegStreamAssetAttributeGrp	[0..*]	Group	
LegStreamCommodityUnitOfMeasure	[0..1]	CodeSet	
LegStreamCommodityCurrency	[0..1]	Currency	
LegStreamCommodityExchange	[0..1]	Exchange	
LegStreamCommodityRateSource	[0..1]	int	
LegStreamCommodityRateReferencePage	[0..1]	String	
LegStreamCommodityRateReferencePageHeading	[0..1]	String	
LegStreamDataProvider	[0..1]	String	
LegStreamCommodityDataSourceGrp	[0..*]	Group	
LegStreamCommodityPricingType	[0..1]	String	
LegStreamCommodityNearbySettlementDayPeriod	[0..1]	int	Conditionally required when LegStreamCommodityNearbySettlementDayUnit(41664) is specified.
LegStreamCommodityNearbySettlementDayUnit	[0..1]	CodeSet	Conditionally required when LegStreamCommodityNearbySettlementDayPeriod(41663) is specified.
LegStreamCommoditySettlementDateUnadjusted	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
<a href="#">LegStreamCommoditySettlDateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to the settlement date.
<a href="#">LegStreamCommoditySettlBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to the settlement date.
<a href="#">LegStreamCommoditySettlDateAdjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegStreamCommoditySettlMonth</a>	[0..1]	int	
<a href="#">LegStreamCommoditySettlDateRollPeriod</a>	[0..1]	int	Conditionally required when LegStreamCommoditySettlDateRollUnit(41670) is specified.
<a href="#">LegStreamCommoditySettlDateRollUnit</a>	[0..1]	CodeSet	Conditionally required when LegStreamCommoditySettlDateRollPeriod(41669) is specified.
<a href="#">LegStreamCommoditySettlDayType</a>	[0..1]	CodeSet	
<a href="#">LegStreamCommoditySettlPeriodGrp</a>	[0..*]	Group	
<a href="#">LegStreamCommodityXID</a>	[0..1]	XID	
<a href="#">LegStreamCommodityXIDRef</a>	[0..1]	XIDREF	

Used in groups: [LegStreamGrp](#)

### 180.2.2511 LegStreamCommodityCurrency

Identifies the currency of the commodity asset. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in components: [LegStreamCommodity](#)

### 180.2.2512 LegStreamCommodityDataSourceGrp

LegStreamCommodityDataSourceGrp is a subcomponent of the LegStreamCommodity component used to specify sources of data, e.g. weather stations. The order of entry determines priority – first is the main source, second is fallback, third is second fallback.

Name	Mult.	Type	Description
NoLegStreamCommodityDataSources	[1..1]	NumInGroup	
LegStreamCommodityDataSourceID	[0..1]	String	Required if NoLegStreamCommodityDataSources(41677) > 0.
LegStreamCommodityDataSourceID- Type	[0..1]	CodeSet	Required if NoLegStreamCommodityDataSources(41677) > 0.

Used in components: **LegStreamCommodity**

#### 180.2.2513 LegStreamCommodityDataSourceID

Specifies the data source identifier.

Type: **String**

Used in groups: **LegStreamCommodityDataSourceGrp**

#### 180.2.2514 LegStreamCommodityDataSourceIDType

Specifies the type of data source identifier.

Type: **int**

Allowed values in StreamCommodityDataSourceIDTypeCodeSet:

Code	Name	Description
0	City	City (4 character business center code)
1	Airport	Airport (IATA standard)
2	WeatherStation	Weather station WBAN (Weather Bureau Army Navy)
3	WeatherIndex	Weather index WMO (World Meteorological Organization)

Used in groups: **LegStreamCommodityDataSourceGrp**

#### 180.2.2515 LegStreamCommodityDeliveryPricingRegion

The delivery or pricing region associated with the commodity swap. See [http://www.ecfr.gov/cgi-bin/text-idx?SID=660d6a40f836aa6ddf213cba080c5b22&node=ap17.2.43\\_17.e&rgn=div9](http://www.ecfr.gov/cgi-bin/text-idx?SID=660d6a40f836aa6ddf213cba080c5b22&node=ap17.2.43_17.e&rgn=div9) for the external code list.

Type: **String**

Used in components: **LegStreamCommodity**

#### **180.2.2516 LegStreamCommodityDesc**

Description of the commodity asset.

Type: **String**

Used in components: **LegStreamCommodity**

#### **180.2.2517 LegStreamCommodityExchange**

Identifies the exchange where the commodity is traded.

Type: **Exchange**

Used in components: **LegStreamCommodity**

#### **180.2.2518 LegStreamCommodityNearbySettlDayPeriod**

Time unit multiplier for the nearby settlement day.

Type: **int**

Used in components: **LegStreamCommodity**

#### **180.2.2519 LegStreamCommodityNearbySettlDayUnit**

Time unit associated with the nearby settlement day.

Type: **String**

Allowed values in StreamCommodityNearbySettlDayUnitCodeSet:

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
Wk	Week	Week
Mo	Month	Month

---

Used in components: **LegStreamCommodity**

#### **180.2.2520 LegStreamCommodityPricingType**

Specifies how the pricing or rate setting of the trade is to be determined or based upon.

See [http://www.fixtradingcommunity.org/codelists#Commodity\\_Rate\\_Pricing\\_Type](http://www.fixtradingcommunity.org/codelists#Commodity_Rate_Pricing_Type) for code list of applicable commodity pricing types.

Type: **String**

Used in components: **LegStreamCommodity**

#### **180.2.2521 LegStreamCommodityRateReferencePage**

Identifies the reference "page" from the rate source.

Type: **String**

Used in components: **LegStreamCommodity**

#### **180.2.2522 LegStreamCommodityRateReferencePageHeading**

Identifies the page heading from the rate source.

Type: **String**

Used in components: **LegStreamCommodity**

#### **180.2.2523 LegStreamCommodityRateSource**

Identifies the source of rate information used for commodities.

See [http://www.fixtradingcommunity.org/codelists#Commodity\\_Rate\\_Source](http://www.fixtradingcommunity.org/codelists#Commodity_Rate_Source) for code list of applicable sources.

Type: **int**

Used in components: **LegStreamCommodity**

#### **180.2.2524 LegStreamCommoditySecurityID**

Specifies the market identifier for the commodity.

Type: **String**

Used in components: **LegStreamCommodity**

**180.2.2525 LegStreamCommoditySecurityIDSource**

Identifies the class or source of the LegStreamCommoditySecurityIDSource(41650) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **LegStreamCommodity**

#### 180.2.2526 LegStreamCommoditySettlBusinessCenter

The business center calendar used to adjust the commodity delivery date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegStreamCommoditySettlBusinessCenterGrp**

#### 180.2.2527 LegStreamCommoditySettlBusinessCenterGrp

LegStreamCommoditySettlBusinessCenterGrp is a repeating subcomponent of the LegStreamCommodity component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegStreamCommoditySettlBusinessCenters	[1..1]	NumInGroup	
LegStreamCommoditySettlBusinessCenter	[0..1]	String	Required if NoLegStreamCommoditySettlementBusinessCenters(41646) > 0.



Used in components: [LegStreamCommodity](#)

#### **180.2.2528 LegStreamCommoditySettlCountry**

Specifies the country where delivery takes place. Uses ISO 3166 2-character country code.

Type: [Country](#)

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

#### **180.2.2529 LegStreamCommoditySettlDateAdjusted**

The adjusted commodity delivery date.

Type: [LocalMktDate](#)

Used in components: [LegStreamCommodity](#)

#### **180.2.2530 LegStreamCommoditySettlDateBusinessDayConvention**

The business day convention used to adjust the commodity delivery date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

---

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

---

Used in components: [LegStreamCommodity](#)

**180.2.2531 LegStreamCommoditySettlDateRollPeriod**

Time unit multiplier for the commodity delivery date roll.

Type: **int**

Used in components: **LegStreamCommodity**

**180.2.2532 LegStreamCommoditySettlDateRollUnit**

Time unit associated with the commodity delivery date roll.

Type: **String**

Allowed values in StreamCommoditySettlDateRollUnitCodeSet:

Code	Name	Description
D	Day	Day

Used in components: **LegStreamCommodity**

**180.2.2533 LegStreamCommoditySettlDateUnadjusted**

The unadjusted commodity delivery date.

Type: **LocalMktDate**

Used in components: **LegStreamCommodity**

**180.2.2534 LegStreamCommoditySettlDay**

Specifies the day or group of days for delivery.

Type: **int**

Allowed values in DeliveryScheduleSettlDayCodeSet:

Code	Name	Description
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday

Code	Name	Description
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday
8	AllWeekdays	All weekdays
9	AllDays	All days
10	AllWeekends	All weekends

Used in groups: [LegStreamCommoditySettlDayGrp](#)

#### 180.2.2535 LegStreamCommoditySettlDayGrp

The LegStreamCommoditySettlDayGrp is a repeating subcomponent of the LegStreamCommoditySettlPeriodGrp component used to define the settlement days associated with the commodity contract.

Name	Mult.	Type	Description
<a href="#">NoLegStreamCommoditySettlDays</a>	[1..1]	NumInGroup	
<a href="#">LegStreamCommoditySettlDay</a>	[0..1]	CodeSet	Required if NoLegStreamCommoditySettlementDays(41680) > 0.
<a href="#">LegStreamCommoditySettlTotalHours</a>	[0..1]	int	
<a href="#">LegStreamCommoditySettlTimeGrp</a>	[0..*]	Group	

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

#### 180.2.2536 LegStreamCommoditySettlDayType

Specifies the commodity delivery roll day type.

Type: [int](#)

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegStreamCommodity](#)

#### **180.2.2537 LegStreamCommoditySettlEnd**

The end time for commodity settlement where delivery occurs over time. The time format is specified by the settlement time type.

Type: [String](#)

Used in groups: [LegStreamCommoditySettlTimeGrp](#)

#### **180.2.2538 LegStreamCommoditySettlFlowType**

Specifies the commodity delivery flow type.

Type: [int](#)

Allowed values in DeliveryScheduleSettlFlowTypeCodeSet:

Code	Name	Description
0	AllTimes	All times
1	OnPeak	On peak
2	OffPeak	Off peak
3	Base	Base
4	BlockHours	Block hours
5	Other	Other

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

**180.2.2539 LegStreamCommoditySettlHolidaysProcessingInstruction**

Indicates whether holidays are included in the settlement periods. Required for electricity contracts.

Type: **int**

Allowed values in DeliveryScheduleSettlHolidaysProcessingInstructionCodeSet:

Code	Name	Description
0	DoNotIncludeHolidays	Do not include holidays
1	IncludeHolidays	Include holidays

Used in groups: **LegStreamCommoditySettlPeriodGrp**

**180.2.2540 LegStreamCommoditySettlMonth**

Specifies a fixed single month for commodity delivery.

Type: **int**

Used in components: **LegStreamCommodity**

**180.2.2541 LegStreamCommoditySettlPeriodFrequencyPeriod**

Time unit multiplier for the settlement period frequency.

Type: **int**

Used in groups: **LegStreamCommoditySettlPeriodGrp**

**180.2.2542 LegStreamCommoditySettlPeriodFrequencyUnit**

Time unit associated with the settlement period frequency.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week

Code	Name	Description
Mo	Month	Month
Yr	Year	Year

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

### 180.2.2543 LegStreamCommoditySettlPeriodGrp

The LegStreamCommoditySettlPeriodGrp is a repeating subcomponent of the LegStreamCommodity component used to to define the settlement period details associated with the commodity contract.

Name	Mult.	Type	Description
<a href="#">NoLegStreamCommoditySettlPeriods</a>	[1..1]	NumInGroup	
<a href="#">LegStreamCommoditySettlCountry</a>	[0..1]	Country	Required if <a href="#">NoLegStreamCommoditySettlPeriods</a> (41686) > 0.
<a href="#">LegStreamCommoditySettlTimeZone</a>	[0..1]	String	
<a href="#">LegStreamCommoditySettlFlowType</a>	[0..1]	CodeSet	
<a href="#">LegStreamCommoditySettlPeriodNotional</a>	[0..1]	Qty	
<a href="#">LegStreamCommoditySettlPeriodNotionalUnitOfMeasure</a>	[0..1]	CodeSet	
<a href="#">LegStreamCommoditySettlPeriodFrequencyPeriod</a>	[0..1]	int	Conditionally required when <a href="#">LegStreamCommoditySettlPeriodFrequencyUnit</a> (41693) is specified.
<a href="#">LegStreamCommoditySettlPeriodFrequencyUnit</a>	[0..1]	CodeSet	Conditionally required when <a href="#">LegStreamCommoditySettlPeriodFrequencyPeriod</a> (41692) is specified.
<a href="#">LegStreamCommoditySettlPeriodPrice</a>	[0..1]	Price	
<a href="#">LegStreamCommoditySettlPeriodPriceUnitOfMeasure</a>	[0..1]	CodeSet	
<a href="#">LegStreamCommoditySettlPeriodPriceCurrency</a>	[0..1]	Currency	
<a href="#">LegStreamCommoditySettlHolidaysProcessingInstruction</a>	[0..1]	CodeSet	
<a href="#">LegStreamCommoditySettlDayGrp</a>	[0..*]	Group	
<a href="#">LegStreamCommoditySettlPeriodXID</a>	[0..1]	XID	
<a href="#">LegStreamCommoditySettlPeriodXIDRef</a>	[0..1]	XIDREF	

Used in components: [LegStreamCommodity](#)

#### **180.2.2544 LegStreamCommoditySettlPeriodNotional**

Delivery quantity associated with this settlement period.

Type: [Qty](#)

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

#### **180.2.2545 LegStreamCommoditySettlPeriodNotionalUnitOfMeasure**

Specifies the unit of measure (UOM) of the delivery quantity associated with this settlement period.

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes

Code	Name	Description
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre



Code	Name	Description
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

**180.2.2546 LegStreamCommoditySettlPeriodPrice**

The settlement period price.

Type: **Price**

Used in groups: **LegStreamCommoditySettlPeriodGrp**

**180.2.2547 LegStreamCommoditySettlPeriodPriceCurrency**

The currency of the settlement period price. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegStreamCommoditySettlPeriodGrp**

**180.2.2548 LegStreamCommoditySettlPeriodPriceUnitOfMeasure**

The settlement period price unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction

Code	Name	Description
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument

Code	Name	Description
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

#### **180.2.2549 LegStreamCommoditySettlPeriodXID**

Identifier of this settlement period for cross referencing elsewhere in the message.

Type: [XID](#)

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

#### **180.2.2550 LegStreamCommoditySettlPeriodXIDRef**

Cross reference to another settlement period for duplicating its properties.

Type: [XIDREF](#)

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

#### **180.2.2551 LegStreamCommoditySettlStart**

The start time for commodity settlement where delivery occurs over time. The time format is specified by the settlement time type.

Type: [String](#)

Used in groups: [LegStreamCommoditySettlTimeGrp](#)

#### **180.2.2552 LegStreamCommoditySettlTimeGrp**

The LegStreamCommoditySettlTimeGrp is a repeating subcomponent of the LegStreamCommoditySettlDayGrp component used to define the settlement time periods associated with the commodity contract.

Name	Mult.	Type	Description
<a href="#">NoLegStreamCommoditySettlTimes</a>	[1..1]	NumInGroup	
<a href="#">LegStreamCommoditySettlStart</a>	[0..1]	String	Required if NoLegStreamCommoditySettlTimes(41683) > 0.
<a href="#">LegStreamCommoditySettlEnd</a>	[0..1]	String	Required if NoLegStreamCommoditySettlTimes(41683) > 0.
<a href="#">LegStreamCommoditySettlTimeType</a>	[0..1]	CodeSet	May be defaulted to market convention or bilaterally agreed if not specified.

Used in groups: [LegStreamCommoditySettlDayGrp](#)

### **180.2.2553 LegStreamCommoditySettlTimeType**

Specifies the format of the commodity settlement start and end times.

Type: [int](#)

Allowed values in DeliveryScheduleSettlTimeTypeCodeSet:

Code	Name	Description
0	Hour	Hour of the day. Applicable for electricity contracts. Time value is expressed as an integer hour of the day (1-24). The delivery start/end hour is specified as the end of the included hour. For example, a start hour of "4" begins at 3 a.m.; an end hour of "20" ends at 8 p.m.; a start hour of "1" and end hour of "24" indicates midnight to midnight delivery.
1	Timestamp	HH:MM time format. Applicable for gas contracts. Time value is expressed using a 24-hour time format. For example, a time value of "13:30" is 1:30 p.m.

Used in groups: [LegStreamCommoditySettlTimeGrp](#)

### **180.2.2554 LegStreamCommoditySettlTimeZone**

Commodity delivery timezone specified as "prevailing" rather than "standard" or "daylight".

See [http://www.fixtradingcommunity.org/codelists#Prevailing\\_Timezones](http://www.fixtradingcommunity.org/codelists#Prevailing_Timezones) for code list of applicable prevailing timezones.

Type: [String](#)

Used in groups: [LegStreamCommoditySettlPeriodGrp](#)

### **180.2.2555 LegStreamCommoditySettlTotalHours**

Sum of the hours specified in LegStreamCommoditySettlTimeGrp.

Type: [int](#)

Used in groups: [LegStreamCommoditySettlDayGrp](#)

**180.2.2556 LegStreamCommodityType**

Specifies the type of commodity product.

For coal see <http://www.fpml.org/coding-scheme/commodity-coal-product-type> for values.

For metals see <http://www.fpml.org/coding-scheme/commodity-metal-product-type> for values.

For bullion see [http://www.fixtradingcommunity.org/codelists#Bullion\\_Types](http://www.fixtradingcommunity.org/codelists#Bullion_Types) for the external code list of bullion types.

Type: **String**

Used in components: **LegStreamCommodity**

**180.2.2557 LegStreamCommodityUnitOfMeasure**

The unit of measure (UOM) of the commodity asset.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day

Code	Name	Description
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs



Code	Name	Description
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [LegStreamCommodity](#)

#### **180.2.2558 LegStreamCommodityXID**

Identifier of this stream commodity for cross referencing elsewhere in the message.

Type: **XID**

Used in components: **LegStreamCommodity**

#### **180.2.2559 LegStreamCommodityXIDRef**

Reference to a stream commodity elsewhere in the message.

Type: **XIDREF**

Used in components: **LegStreamCommodity**

#### **180.2.2560 LegStreamCurrency**

Specifies the currency the LegStreamNotional(40246) is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **LegStreamGrp**

#### **180.2.2561 LegStreamDataProvider**

Specifies the commodity data or information provider.

See <http://www.fpml.org/coding-scheme/commodity-information-provider> for values.

Type: **String**

Used in components: **LegStreamCommodity**

#### **180.2.2562 LegStreamDesc**

A short descriptive name given to the payment stream, e.g. CDS, Fixed, Float, Float2, GBP. The description has no intrinsic meaning but should be arbitrarily chosen by the remitter as a reference.

Type: **String**

Used in groups: **LegStreamGrp**

**180.2.2563 LegStreamEffectiveDateAdjusted**

The adjusted effective date.

Type: **LocalMktDate**

Used in components: **LegStreamEffectiveDate**

**180.2.2564 LegStreamEffectiveDateBusinessCenter**

The business center calendar used to adjust the instrument leg's stream's effective date or relative effective date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegStreamEffectiveDateBusinessCenterGrp**

**180.2.2565 LegStreamEffectiveDateBusinessCenterGrp**

LegStreamEffectiveDateBusinessCenterGrp is a repeating subcomponent within the LegStreamEffectiveDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegStreamEffectiveDateBusinessCenters	[1..1]	NumInGroup	
LegStreamEffectiveDateBusinessCenter	[0..1]	String	Required if NoLegStreamEffectiveDateBusinessCenters(40942) > 0.

Used in components: **LegStreamEffectiveDate**

**180.2.2566 LegStreamEffectiveDateBusinessDayConvention**

The business day convention used to adjust the instrument leg's stream's effective date or relative effective date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegStreamEffectiveDate](#)

### 180.2.2567 LegStreamEffectiveDate

LegStreamEffectiveDate is a subcomponent of the LegStreamGrp component used to specify the effective date of the stream.

Name	Mult.	Type	Description
<a href="#">LegStreamEffectiveDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">LegStreamEffectiveDateBusinessDay-Convention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg stream effective date.
<a href="#">LegStreamEffectiveDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg stream stream effective date.
<a href="#">LegStreamEffectiveDateRelativeTo</a>	[0..1]	int	
<a href="#">LegStreamEffectiveDateOffsetPeriod</a>	[0..1]	int	Conditionally required when LegPaymentStream-EffectiveDateOffsetUnit(40254) is specified.
<a href="#">LegStreamEffectiveDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegPaymentStream-EffectiveDateOffsetPeriod(40253) is specified.
<a href="#">LegStreamEffectiveDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">LegStreamEffectiveDateAdjusted</a>	[0..1]	LocalMktDate	

---

Name	Mult.	Type	Description
------	-------	------	-------------

---

Used in groups: [LegStreamGrp](#)

#### **180.2.2568 LegStreamEffectiveDateOffsetDayType**

Specifies the day type of the relative effective date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegStreamEffectiveDate](#)

#### **180.2.2569 LegStreamEffectiveDateOffsetPeriod**

Time unit multiplier for the relative effective date offset.

Type: [int](#)

Used in components: [LegStreamEffectiveDate](#)

#### **180.2.2570 LegStreamEffectiveDateOffsetUnit**

Time unit associated with the relative effective date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [LegStreamEffectiveDate](#)

#### **180.2.2571 LegStreamEffectiveDateRelativeTo**

Specifies the anchor date when the effective date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values

Type: [int](#)

Used in components: [LegStreamEffectiveDate](#)

#### **180.2.2572 LegStreamEffectiveDateUnadjusted**

The unadjusted effective date.

Type: [LocalMktDate](#)

Used in components: [LegStreamEffectiveDate](#)

#### **180.2.2573 LegStreamFirstCompoundingPeriodEndDateUnadjusted**

The unadjusted end date of the initial compounding period.

Type: [LocalMktDate](#)

Used in components: [LegStreamCalculationPeriodDates](#)

#### **180.2.2574 LegStreamFirstPeriodStartDateAdjusted**

The adjusted first calculation period start date, if it is before the effective date.

Type: [LocalMktDate](#)

Used in components: [LegStreamCalculationPeriodDates](#)

**180.2.2575 LegStreamFirstPeriodStartDateBusinessCenter**

The business center calendar used to adjust the instrument leg's stream's first calculation period start date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **LegStreamFirstPeriodStartDateBusinessCenterGrp**

**180.2.2576 LegStreamFirstPeriodStartDateBusinessCenterGrp**

LegStreamFirstPeriodStartDateBusinessCenterGrp is a repeating subcomponent within the LegStreamCalculationPeriodDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
NoLegStreamFirstPeriodStartDateBusinessCenters	[1..1]	NumInGroup	
LegStreamFirstPeriodStartDateBusinessCenter	[0..1]	String	Required if NoLegStreamFirstPeriodStartDateBusinessCenters(40941) > 0.

Used in components: **LegStreamCalculationPeriodDates**

**180.2.2577 LegStreamFirstPeriodStartDateBusinessDayConvention**

The business day convention used to adjust the instrument leg's stream's first calculation period start date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)

Code	Name	Description
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [LegStreamCalculationPeriodDates](#)

#### 180.2.2578 LegStreamFirstPeriodStartDateUnadjusted

The unadjusted first calculation period start date if before the effective date.

Type: [LocalMktDate](#)

Used in components: [LegStreamCalculationPeriodDates](#)

#### 180.2.2579 LegStreamFirstRegularPeriodStartDateUnadjusted

The unadjusted first start date of the regular calculation period, if there is an initial stub period.

Type: [LocalMktDate](#)

Used in components: [LegStreamCalculationPeriodDates](#)

#### 180.2.2580 LegStreamGrp

The LegStreamGrp is a repeating subcomponent of the InstrumentLeg component used to detail the swap streams associated with the instrument.

Name	Mult.	Type	Description
<a href="#">NoLegStreams</a>	[1..1]	NumInGroup	
<a href="#">LegStreamType</a>	[0..1]	CodeSet	Required if NoLegStreams(40241) > 0.
<a href="#">LegStreamXID</a>	[0..1]	XID	
<a href="#">LegStreamDesc</a>	[0..1]	String	
<a href="#">LegStreamVersion</a>	[0..1]	String	



Name	Mult.	Type	Description
LegStreamVersionEffectiveDate	[0..1]	LocalMktDate	
LegStreamPaySide	[0..1]	CodeSet	
LegStreamReceiveSide	[0..1]	CodeSet	
LegStreamNotionalXIDRef	[0..1]	XIDREF	
LegStreamNotional	[0..1]	Amt	
LegStreamCurrency	[0..1]	Currency	
LegStreamNotionalDetermination-Method	[0..1]	String	
LegStreamNotionalAdjustments	[0..1]	CodeSet	
LegStreamNotionalFrequencyPeriod	[0..1]	int	Conditionally required when LegStreamNotionalFrequencyUnit(41704) is specified.
LegStreamNotionalFrequencyUnit	[0..1]	CodeSet	Conditionally required when LegStreamNotionalFrequencyPeriod(41703) is specified.
LegStreamNotionalCommodityFrequency	[0..1]	CodeSet	
LegStreamNotionalUnitOfMeasure	[0..1]	CodeSet	
LegStreamTotalNotional	[0..1]	Qty	
LegStreamTotalNotionalUnitOfMeasure	[0..1]	CodeSet	
LegStreamCommodity	[0..1]	Component	
LegStreamEffectiveDate	[0..1]	Component	
LegStreamTerminationDate	[0..1]	Component	
LegStreamCalculationPeriodDates	[0..1]	Component	
LegPaymentStream	[0..1]	Component	
LegPaymentScheduleGrp	[0..*]	Group	
LegPaymentStubGrp	[0..*]	Group	
LegDeliveryStream	[0..1]	Component	
LegDeliveryScheduleGrp	[0..*]	Group	
LegStreamText	[0..1]	String	
EncodedLegStreamTextLen	[0..1]	Length	Must be set if EncodedLegStreamText(40979) field is specified and must immediately precede it.

EncodedLegStreamText	[0..1]	data	Encoded (non-ASCII characters) representation of the LegStreamText(40248) field in the encoded format specified via the MessageEncoding(347) field.
----------------------	--------	------	---

---

Used in components: [InstrumentLeg](#)

#### **180.2.2581 LegStreamLastRegularPeriodEndDateUnadjusted**

The unadjusted last regular period end date if there is a final stub period.

Type: [LocalMktDate](#)

Used in components: [LegStreamCalculationPeriodDates](#)

#### **180.2.2582 LegStreamMaximumPaymentAmount**

Specifies the limit on the total payment amount.

Type: [Amt](#)

Used in components: [LegPaymentStream](#)

#### **180.2.2583 LegStreamMaximumPaymentCurrency**

Specifies the currency of total payment amount limit. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in components: [LegPaymentStream](#)

#### **180.2.2584 LegStreamMaximumTransactionAmount**

Specifies the limit on the payment amount that goes out in any particular calculation period.

Type: [Amt](#)

Used in components: [LegPaymentStream](#)

**180.2.2585 LegStreamMaximumTransactionCurrency**

Specifies the currency of the period payment amount limit. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **LegPaymentStream**

**180.2.2586 LegStreamNotional**

Notional, or initial notional value for the payment stream. The LegPaymentSchedule component should be used for specifying the steps.

Type: **Amt**

Used in groups: **LegStreamGrp**

**180.2.2587 LegStreamNotionalAdjustments**

For equity swaps this specifies the conditions that govern the adjustment to the number of units of the swap.

Type: **int**

Allowed values in StreamNotionalAdjustmentsCodeSet:

Code	Name	Description
0	Execution	Execution. The adjustments to the number of units are governed by an execution clause.
1	PortfolioRebalancing	Portfolio rebalancing. The adjustments to the number of units are governed by a portfolio rebalancing clause.
2	Standard	Standard. The adjustments to the number of units are not governed by any specific clause.

Used in groups: **LegStreamGrp**

**180.2.2588 LegStreamNotionalCommodityFrequency**

The commodity's notional or quantity delivery frequency.

Type: **int**

Allowed values in StreamNotionalCommodityFrequencyCodeSet:

Code	Name	Description
0	Term	Term
1	PerBusinessDay	Per business day
2	PerCalculationPeriod	Per calculation period
3	PerSettlPeriod	Per settlement period
4	PerCalendarDay	Per calendar day
5	PerHour	Per hour
6	PerMonth	Per month

Used in groups: **LegStreamGrp**

#### **180.2.2589 LegStreamNotionalDeterminationMethod**

Specifies the method for determining the floating notional value for equity swaps.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **LegStreamGrp**

#### **180.2.2590 LegStreamNotionalFrequencyPeriod**

Time unit multiplier for the swap stream's notional frequency.

Type: **int**

Used in groups: **LegStreamGrp**

#### **180.2.2591 LegStreamNotionalFrequencyUnit**

Time unit associated with the swap stream's notional frequency.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in groups: **LegStreamGrp**

### 180.2.2592 LegStreamNotionalUnitOfMeasure

Specifies the delivery quantity unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)

Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter

Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [LegStreamGrp](#)

#### **180.2.2593 LegStreamNotionalXIDRef**

Cross reference to another LegStream notional for duplicating its properties.

Type: [XIDREF](#)

Used in groups: [LegStreamGrp](#)

#### **180.2.2594 LegStreamPaySide**

The side of the party paying the stream.

Type: [int](#)

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: [LegStreamGrp](#)

#### **180.2.2595 LegStreamReceiveSide**

The side of the party receiving the stream.

Type: [int](#)

Allowed values in PaymentPaySideCodeSet:



Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: [LegStreamGrp](#)

### 180.2.2596 LegStreamTerminationDateAdjusted

The adjusted termination date.

Type: [LocalMktDate](#)

Used in components: [LegStreamTerminationDate](#)

### 180.2.2597 LegStreamTerminationDateBusinessCenter

The business center calendar used to adjust the instrument leg's stream's termination, or relative termination, date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [LegStreamTerminationDateBusinessCenterGrp](#)

### 180.2.2598 LegStreamTerminationDateBusinessCenterGrp

LegStreamTerminationDateBusinessCenterGrp is a repeating subcomponent within the LegStreamTerminationDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the LegDateAdjustment component in InstrumentLeg.

Name	Mult.	Type	Description
<a href="#">NoLegStreamTerminationDateBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">LegStreamTerminationDateBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoLegStreamTerminationDateBusinessCenters</a> (40943) > 0.

Used in components: [LegStreamTerminationDate](#)

**180.2.2599 LegStreamTerminationDateBusinessDayConvention**

The business day convention used to adjust the instrument leg's stream's termination, or relative termination, date. Used only to override the business day convention specified in the LegDateAdjustment component within the InstrumentLeg component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **LegStreamTerminationDate**

**180.2.2600 LegStreamTerminationDate**

LegStreamTerminationDate is a subcomponent of the LegStreamGrp component used to specify the termination date of the stream.

Name	Mult.	Type	Description
<b>LegStreamTerminationDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>LegStreamTerminationDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the LegDateAdjustment component in InstrumentLeg. The specified value would be specific to this instance of the leg stream termination date.

Name	Mult.	Type	Description
<a href="#">LegStreamTerminationDateBusiness-CenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the LegDateAdjustment component in InstrumentLeg. The specified values would be specific to this instance of the leg stream termination date.
<a href="#">LegStreamTerminationDateRelativeTo</a>	[0..1]	int	
<a href="#">LegStreamTerminationDateOffsetPeriod</a>	[0..1]	int	Conditionally required when LegStreamTerminationDateOffsetUnit(40262) is specified.
<a href="#">LegStreamTerminationDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when LegStreamTerminationDateOffsetPeriod(40261) is specified.
<a href="#">LegStreamTerminationDateOffsetDay-Type</a>	[0..1]	CodeSet	
<a href="#">LegStreamTerminationDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [LegStreamGrp](#)

### 180.2.2601 [LegStreamTerminationDateOffsetDayType](#)

Specifies the day type of the relative termination date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [LegStreamTerminationDate](#)

**180.2.2602 LegStreamTerminationDateOffsetPeriod**

Time unit multiplier for the relative termination date offset.

Type: **int**

Used in components: **LegStreamTerminationDate**

**180.2.2603 LegStreamTerminationDateOffsetUnit**

Time unit associated with the relative termination date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **LegStreamTerminationDate**

**180.2.2604 LegStreamTerminationDateRelativeTo**

Specifies the anchor date when the termination date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **LegStreamTerminationDate**

**180.2.2605 LegStreamTerminationDateUnadjusted**

The unadjusted termination date.

Type: **LocalMktDate**

Used in components: **LegStreamTerminationDate**

**180.2.2606 LegStreamText**

Free form text to specify additional information or enumeration description when a standard value does not apply.

Type: **String**

Used in groups: **LegStreamGrp**

**180.2.2607 LegStreamTotalNotional**

Specifies the total notional or delivery quantity over the term of the contract.

Type: **Qty**

Used in groups: **LegStreamGrp**

**180.2.2608 LegStreamTotalNotionalUnitOfMeasure**

Specifies the unit of measure (UOM) for the total notional or delivery quantity over the term of the contract.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)

Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter

Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [LegStreamGrp](#)

### 180.2.2609 LegStreamType

Type of swap stream.

Type: [int](#)

Allowed values in StreamTypeCodeSet:

Code	Name	Description
0	PaymentCashSettlement	Payment / cash settlement
1	PhysicalDelivery	Physical delivery

Used in groups: [LegStreamGrp](#)

### 180.2.2610 LegStreamVersion

The stream version identifier when there have been modifications to the contract over time. Helps signal when there are embedded changes.

Type: [String](#)

Used in groups: [LegStreamGrp](#)

### 180.2.2611 LegStreamVersionEffectiveDate

The effective date of the LegStreamVersion(42583).

Type: [LocalMktDate](#)

Used in groups: [LegStreamGrp](#)



**180.2.2612 LegStreamXID**

Identifier of this LegStream for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **LegStreamGrp**

**180.2.2613 LegStrikeCurrency**

Currency in which the strike price of a instrument leg of a multileg instrument is denominated

Type: **Currency**

Used in components: **InstrumentLeg**

**180.2.2614 LegStrikeCurrencyCodeSource**

Identifies class or source of the LegStrikeCurrency(942) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **InstrumentLeg**

**180.2.2615 LegStrikeIndex**

Specifies the index used to calculate the strike price.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.2616 LegStrikeIndexCurvePoint**

The point on the floating rate index curve. Sample values:

M = combination of a number between 1-12 and an "M" for month, e.g. 3M

Y = combination of number between 1-100 and a "Y" for year, e.g. 10Y

10Y-OLD = see above, then add "-OLD" when appropriate

INTERPOLATED = the point is mathematically derived

2/2031 5 3/8 = the point is stated via a combination of maturity month / year and coupon.

Type: **String**

Used in components: **InstrumentLeg**

**180.2.2617 LegStrikeIndexQuote**

The quote side from which the index price is to be determined.

Type: **int**

Allowed values in StrikeIndexQuoteCodeSet:

Code	Name	Description
0	Bid	Bid.
1	Mid	Mid
2	Offer	Offer

Used in components: **InstrumentLeg**

**180.2.2618 LegStrikeIndexSpread**

Specifies the strike price offset from the named index.

Type: **PriceOffset**

Used in components: **InstrumentLeg**

**180.2.2619 LegStrikeMultiplier**

Used for derivatives. Multiplier applied to the strike price for the purpose of calculating the settlement value.

Type: **float**

Used in components: **InstrumentLeg**

**180.2.2620 LegStrikePrice**

Multileg instrument's individual security's StrikePrice.

See StrikePrice (202) field for description

Type: **Price**

Used in components: **InstrumentLeg**

**180.2.2621 LegStrikePriceBoundaryMethod**

Specifies the boundary condition to be used for the strike price relative to the underlying price at the point of option exercise.

Type: **int**

Allowed values in StrikePriceBoundaryMethodCodeSet:

Code	Name	Description
1	LessThan	Less than underlying price is in-the-money (ITM)
2	LessThanOrEqual	Less than or equal to the underlying price is in-the-money(ITM)
3	Equal	Equal to the underlying price is in-the-money(ITM)
4	GreaterThanOrEqual	Greater than or equal to underlying price is in-the-money(ITM)
5	GreaterThan	Greater than underlying is in-the-money(ITM)

Used in components: **InstrumentLeg**

**180.2.2622 LegStrikePriceBoundaryPrecision**

Used in combination with StrikePriceBoundaryMethod(2187) to specify the percentage of the strike price in relation to the underlying price. The percentage is generally 100 or greater for puts and 100 or less for calls.

Type: **Percentage**

Used in components: **InstrumentLeg**

### 180.2.2623 LegStrikePriceDeterminationMethod

Specifies how the strike price is determined at the point of option exercise. The strike may be fixed throughout the life of the option, set at expiration to the value of the underlying, set to the average value of the underlying , or set to the optimal value of the underlying.

Type: **int**

Allowed values in StrikePriceDeterminationMethodCodeSet:

Code	Name	Description
1	FixedStrike	Fixed strike (default if not specified)
2	StrikeSetAtExpiration	Strike set at expiration to underlying or other value (lookback floating)
3	StrikeSetToAverageAcrossLife	Strike set to average of underlying settlement price across the life of the option
4	StrikeSetToOptimalValue	Strike set to optimal value

Used in components: **InstrumentLeg**

### 180.2.2624 LegStrikeUnitOfMeasure

Used to express the unit of measure (UOM) of the price if different from the contract.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules

Code	Name	Description
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)

Code	Name	Description
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
Sqcm	SquareCentimeter	Square centimeter

Code	Name	Description
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [InstrumentLeg](#)

#### 180.2.2625 LegStrikeValue

The number of shares/units for the financial instrument involved in the option trade. Used for derivatives.

Type: [float](#)

Used in components: [InstrumentLeg](#)

#### 180.2.2626 LegSwapClass

Swap type.

Type: [String](#)

Allowed values in SwapClassCodeSet:

Code	Name	Description
BS	BasisSwap	Basis swap
IX	IndexSwap	Index swap
BB	BroadBasedSecuritySwap	Broad-based security swap
SK	BasketSwap	Basket swap

Used in components: [InstrumentLeg](#)

**180.2.2627 LegSwapSubClass**

The sub-classification or notional schedule type of the swap.

Type: **String**

Allowed values in SwapSubClassCodeSet:

Code	Name	Description
AMTZ	Amortizing	Amortizing notional schedule
COMP	Compounding	Compounding
CNST	ConstantNotionalSchedule	Constant notional schedule
ACRT	AccretingNotionalSchedule	Accreting notional schedule
CUST	CustomNotionalSchedule	Custom notional schedule

Used in components: **InstrumentLeg**

**180.2.2628 LegSwapType**

For Fixed Income, used instead of LegOrderQty(685) to requests the respondent to calculate the quantity based on the quantity on the opposite side of the swap.

Type: **int**

Allowed values in LegSwapTypeCodeSet:

Code	Name	Description
1	ParForPar	Par For Par
2	ModifiedDuration	Modified Duration
4	Risk	Risk
5	Proceeds	Proceeds

Used in groups: **InstrmtLegExecGrp**, **InstrmtLegSecListGrp**, **LegOrdGrp**, **LegQuotGrp**, **LegQuotStatGrp**, **QuotReqLegsGrp**, **SecLstUpdRelSymsLegGrp**, **SideCrossLegGrp**, **TrdInstrmtLegGrp**

**180.2.2629 LegSymbol**

Multileg instrument's individual security's Symbol.



See Symbol (55) field for description

Type: **String**

Used in components: **InstrumentLeg**

#### **180.2.2630 LegSymbolPositionNumber**

Reference to the first or second currency or digital asset in LegSymbol(600) for FX-style trading.

Conditionally required when one or both symbols in LegSymbol(600) represent a digital asset.

Type: **int**

Used in groups: **LegSecAltIDGrp**

#### **180.2.2631 LegSymbolSfx**

Multileg instrument's individual security's SymbolSfx.

See SymbolSfx (65) field for description

Type: **String**

Allowed values in SymbolSfxCodeSet:

Code	Name	Description
CD	EUCPWithLumpSumInterest	EUCP with lump-sum interest rather than discount price
WI	WhenIssued	"When Issued" for a security to be reissued under an old CUSIP or ISIN

Used in components: **InstrumentLeg**

#### **180.2.2632 LegTerminationType**

Type of financing termination.

Type: **int**

Allowed values in TerminationTypeCodeSet:

Code	Name	Description
1	Overnight	Overnight
2	Term	Term
3	Flexible	Flexible
4	Open	Open

Used in components: [LegFinancingDetails](#)

### 180.2.2633 LegTimeUnit

See TimeUnit(997) for complete definition.

Type: [String](#)

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in components: [InstrumentLeg](#)

### 180.2.2634 LegTotalGrossTradeAmt

Expresses the full total monetary value of the traded contract. The value is the product of LegLastPx(637) and LegTotalTradeQty(2357) or LegTotalTradeMultipliedQty(2360), if priced in units instead of contracts.

Type: **Amt**

Used in groups: **TrdInstrmtLegGrp**

#### **180.2.2635 LegTotalIssuedAmount**

Specifies the total amount of the issue. Corresponds to the par value multiplied by the number of issued security.

Type: **Amt**

Used in components: **InstrumentLeg**

#### **180.2.2636 LegTotalTradeMultipliedQty**

Expresses the total trade quantity in units where LegContractMultiplier(614) is not 1. The value is the product of LegTotalTradeQty(2357) and LegContractMultiplier(614).

Type: **Qty**

Used in groups: **TrdInstrmtLegGrp**

#### **180.2.2637 LegTotalTradeQty**

Expresses the total quantity traded over the life of the contract when LegLastQty(1418) is to be repeated periodically over the term of the contract. The value is the product of LegLastQty(1418) and LegTradingUnitPeriodMultiplier(2353).

Type: **Qty**

Used in groups: **TrdInstrmtLegGrp**

#### **180.2.2638 LegTradeID**

The TradeID(1003) value corresponding to a trade leg.

Type: **String**

Used in groups: **TrdInstrmtLegExecGrp**

**180.2.2639 LegTradeReportID**

The TradeReportID(571) value corresponding to a trade leg.

Type: **String**

Used in groups: **TrdInstrmtLegExecGrp**

**180.2.2640 LegTradingUnitPeriodMultiplier**

Indicates the number of contract periods associated with the minimum trading unit for a given contract duration resulting in the number of total traded contracts.

Type: **int**

Used in components: **InstrumentLeg**

**180.2.2641 LegUnderlyingPriceDeterminationMethod**

Specifies how the underlying price is determined at the point of option exercise. The underlying price may be set to the current settlement price, set to a special reference, set to the optimal value of the underlying during the defined period ("Look-back") or set to the average value of the underlying during the defined period ("Asian option").

Type: **int**

Allowed values in UnderlyingPriceDeterminationMethodCodeSet:

Code	Name	Description
1	Regular	Regular
2	SpecialReference	Special reference
3	OptimalValue	Optimal value (Lookback)
4	AverageValue	Average value (Asian option)

Used in components: **InstrumentLeg**

**180.2.2642 LegUnitOfMeasure**

Multileg instrument unit of measure.

See UnitOfMeasure(996) for complete definition.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs

Code	Name	Description
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile

Code	Name	Description
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [InstrumentLeg](#)

#### **180.2.2643 LegUnitOfMeasureCurrency**

Indicates the currency of the unit of measure. Conditionally required when LegUnitOfMeasure(999) = Ccy

Type: [Currency](#)

Used in components: [InstrumentLeg](#)

#### **180.2.2644 LegUnitOfMeasureCurrencyCodeSource**

Identifies class or source of the LegUnitOfMeasureCurrency(1720) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [InstrumentLeg](#)

#### **180.2.2645 LegUnitOfMeasureQty**

Refer to definition of UnitOfMeasureQty(1147)

Type: [Qty](#)

Used in components: [InstrumentLeg](#)

#### **180.2.2646 LegUPICode**

Uniquely identifies the product of a leg instrument using ISO 4914. See UPICode(2891) for further detail.

Type: [String](#)

Used in components: [InstrumentLeg](#)

#### **180.2.2647 LegValuationMethod**

Specifies the type of valuation method applied.

Type: [String](#)

Allowed values in ValuationMethodCodeSet:



Code	Name	Description
EQTY	PremiumStyle	premium style
FUT	FuturesStyleMarkToMarket	futures style mark-to-market
FUTDA	FuturesStyleWithAnAttachedCashAdjustment	futures style with an attached cash adjustment
CDS	CDSStyleCollateralization	CDS style collateralization of market to market and coupon
CDSO	CDSInDeliveryUseRecoveryRateToCalculate	CDS in delivery - use recovery rate to calculate obligation

Used in components: [InstrumentLeg](#)

#### **180.2.2648 LegValuationReferenceModel**

Specifies the methodology and/or assumptions used to generate the trade value.

Type: [String](#)

Used in components: [InstrumentLeg](#)

#### **180.2.2649 LegValuationSource**

Specifies the source of trade valuation data.

Type: [String](#)

Used in components: [InstrumentLeg](#)

#### **180.2.2650 LegVersusPurchaseDate**

The effective acquisition date of the lot that would be used for gain-loss trade lot reporting. The versus purchase date used to identify the lot in situations where a custodial lot identifier is not available.

Type: [LocalMktDate](#)

Used in groups: [LegPreAllocGrp](#)

#### **180.2.2651 LegVersusPurchasePrice**

The versus purchase price used to identify the lot in situations where a custodial lot identifier is not available. The value should be calculated based on current cost basis / quantity held.

Type: **Price**

Used in groups: **LegPreAllocGrp**

### **180.2.2652 LegVolatility**

Specifies the volatility of an instrument leg.

Type: **float**

Used in groups: **InstrmtLegExecGrp**, **LegOrdGrp**, **SideCrossLegGrp**, **TrdInstrmtLegGrp**

### **180.2.2653 LienSeniority**

Indicates the seniority level of the lien in a loan.

Type: **int**

Allowed values in LienSeniorityCodeSet:

Code	Name	Description
0	Unknown	Unknown
1	FirstLien	First lien
2	SecondLien	Second lien
3	ThirdLien	Third lien

Used in components: **Instrument**

### **180.2.2654 LimitAmt**

The limit for the counterparty. This represents the total limit amount, independent of any amount already utilized.

Type: **Amt**

Used in groups: **LimitAmts**

**180.2.2655 LimitAmtCurrency**

Indicates the currency that the limit amount is specified in.

Type: **Currency**

Used in groups: **LimitAmts**

**180.2.2656 LimitAmtCurrencyCodeSource**

Identifies class or source of the LimitAmtCurrency(1634) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **LimitAmts**

**180.2.2657 LimitAmtRemaining**

The remaining limit amount available between the counterparties. The type of limit is specified in LimitAmtType(1631).

Bilateral agreements dictate the units and maximum value of this field.

Type: **Amt**

Used in groups: **LimitAmts**

**180.2.2658 LimitAmts**

Name	Mult.	Type	Description
NoLimitAmts	[1..1]	NumInGroup	Number of limit amount occurrences.
LimitAmtType	[0..1]	CodeSet	Required when NoLimitAmts > 0
LastLimitAmt	[0..1]	Amt	Either LastLimitAmt(1632) or LimitAmtRemaining(1633) or LimitUtilizationAmt(2394) must be specified when NoLimitAmts > 0.
LimitAmtRemaining	[0..1]	Amt	Either LastLimitAmt(1632) or LimitAmtRemaining(1633) or LimitUtilizationAmt(2394) must be specified when NoLimitAmts > 0.
LimitUtilizationAmt	[0..1]	Amt	Either LastLimitAmt(1632) or LimitAmtRemaining(1633) or LimitUtilizationAmt(2394) must be specified when NoLimitAmts > 0.
LimitAmt	[0..1]	Amt	
LimitAmtCurrency	[0..1]	Currency	
LimitAmtCurrencyCodeSource	[0..1]	CodeSet	
LimitRole	[0..1]	CodeSet	

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **ExecutionReport**

**180.2.2659 LimitAmtType**

Identifies the type of limit amount expressed in LastLimitAmt(1632) and LimitAmtRemaining(1633).

Type: **int**

Allowed values in LimitAmtTypeCodeSet:

Code	Name	Description
0	CreditLimit	Credit limit
1	GrossPositionLimit	Gross position limit
2	NetPositionLimit	Net position limit
3	RiskExposureLimit	Risk exposure limit

Code	Name	Description
4	LongPositionLimit	Long position limit
5	ShortPositionLimit	Short position limit

Used in groups: **LimitAmts**

### 180.2.2660 LimitedRightToConfirmIndicator

Indicates whether the Seller may request the Buyer to confirm its intent to exercise if not done on or before the expiration time on the expiration date. If true ("Y") specific rules will apply in relation to the settlement mode.

Type: **Boolean**

Used in components: **OptionExercise**

### 180.2.2661 LimitRole

Indicates the scope of the limit by role.

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)

Code	Name	Description
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange

Code	Name	Description
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.

Code	Name	Description
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.



Code	Name	Description
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.

Code	Name	Description
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **LimitAmts**

#### 180.2.2662 LimitUtilizationAmt

The total amount of the limit that has been drawn down against the counterparty. This includes the amount for prior trades. It may or may not include the amount for the given trade, specified in LastLimitAmt(1632), depending upon whether the given trade is considered pending.

Type: **Amt**

Used in groups: **LimitAmts**

#### 180.2.2663 LinesOfTextGrp

Name	Mult.	Type	Description
NoLinesOfText	[1..1]	NumInGroup	Specifies the number of repeating lines of text specified
Text	[1..1]	String	Repeating field, number of instances defined in LinesOfText
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: **Email**, **News**

#### **180.2.2664 LinkageHandlingIndicator**

Indicate whether linkage handling is in effect for an instrument or not.

Type: **Boolean**

Used in messages: **SecurityStatus**

#### **180.2.2665 LiquidityIndType**

Code to identify the type of liquidity indicator.

Type: **int**

Allowed values in LiquidityIndTypeCodeSet:

Code	Name	Description
1	FiveDayMovingAverage	5-day moving average
2	TwentyDayMovingAverage	20-day moving average
3	NormalMarketSize	Normal market size
4	Other	Other

Used in messages: **BidRequest**

#### **180.2.2666 LiquidityNumSecurities**

Number of Securites between LiquidityPctLow (402) and LiquidityPctHigh (403) in Currency.

Type: **int**

Used in groups: **BidDescReqGrp**

#### **180.2.2667 LiquidityPctHigh**

Upper liquidity indicator if TotalNumSecurities (393) > 1. Represented as a percentage.

Type: **Percentage**

Used in groups: **BidDescReqGrp**

#### **180.2.2668 LiquidityPctLow**

Liquidity indicator or lower limit if TotalNumSecurities (393) > 1. Represented as a percentage.

Type: **Percentage**

Used in groups: **BidDescReqGrp**

#### **180.2.2669 LiquidityValue**

Value between LiquidityPctLow (402) and LiquidityPctHigh (403) in Currency

Type: **Amt**

Used in groups: **BidDescReqGrp**

#### **180.2.2670 ListExecInst**

Free format text message containing list handling and execution instructions.

Type: **String**

Used in messages: **NewOrderList**

**180.2.2671 ListExecInstType**

Identifies the type of ListExecInst (69).

Type: **char**

Allowed values in ListExecInstTypeCodeSet:

Code	Name	Description
1	Immediate	Immediate
2	WaitForInstruction	Wait for Execut Instruction (i.e. a List Execut message or phone call before proceeding with execution of the list)
3	SellDriven	Exchange/switch CIV order - Sell driven
4	BuyDrivenCashTopUp	Exchange/switch CIV order - Buy driven, cash top-up (i.e. additional cash will be provided to fulfill the order)
5	BuyDrivenCashWithdraw	Exchange/switch CIV order - Buy driven, cash withdraw (i.e. additional cash will not be provided to fulfill the order)

Used in messages: **NewOrderList**

**180.2.2672 ListID**

Unique identifier for list as assigned by institution, used to associate multiple individual orders. Uniqueness must be guaranteed within a single trading day. Firms which generate multi-day orders should consider embedding a date within the ListID field to assure uniqueness across days.

Type: **String**

Used in components: **TradeReportOrderDetail**

Used in groups: **BidCompReqGrp, BidCompRspGrp, OrdAllocGrp**

Used in messages: **ExecutionReport, ListCancelRequest, ListExecute, ListStatus, ListStatusRequest, ListStrikePrice, NewOrderList, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest**

**180.2.2673 ListManualOrderIndicator**

Indicates if the list of orders was initially received manually (as opposed to electronically) or if it was entered manually (as opposed to entered by automated trading software).

Type: **Boolean**

Used in messages: **NewOrderList**

**180.2.2674 ListMethod**

Indicates whether instruments are pre-listed only or can also be defined via user request

Type: **int**

Allowed values in ListMethodCodeSet:

Code	Name	Description
0	PreListedOnly	pre-listed only
1	UserRequested	user requested

Used in components: **Instrument**

**180.2.2675 ListName**

Descriptive name for list order.

Type: **String**

Used in messages: **BidRequest**

**180.2.2676 ListOrderStatus**

Code to represent the status of a list order.

Type: **int**

Allowed values in ListOrderStatusCodeSet:

Code	Name	Description
1	InBiddingProcess	In bidding process
2	ReceivedForExecution	Received for execution
3	Executing	Executing
4	Cancelling	Cancelling
5	Alert	Alert
6	AllDone	All Done
7	Reject	Reject

Used in messages: **ListStatus**

**180.2.2677 ListOrdGrp**

Name	Mult.	Type	Description
NoOrders	[1..1]	NumInGroup	Number of orders in this message (number of repeating groups to follow)
ClOrdID	[1..1]	String	Must be the first field in the repeating group.
SecondaryClOrdID	[0..1]	String	
ListSeqNo	[1..1]	int	Order number within the list
ClOrdLinkID	[0..1]	String	
SettlInstMode	[0..1]	CodeSet	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TradeOriginationDate	[0..1]	LocalMktDate	
TradeDate	[0..1]	LocalMktDate	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
DayBookingInst	[0..1]	CodeSet	
BookingUnit	[0..1]	CodeSet	
AllocID	[0..1]	String	Use to assign an ID to the block of individual preallocations
PreallocMethod	[0..1]	CodeSet	
PreAllocGrp	[0..*]	Group	
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Takes precedence over SettlType value and conditionally required/omitted for specific SettlType values.
CashMargin	[0..1]	CodeSet	
ClearingFeeIndicator	[0..1]	CodeSet	
HandlInst	[0..1]	CodeSet	
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited. If OrdType=P, exactly one of the following values (ExecInst = L, R, M, P, O, T, or W) must be specified.
MinQty	[0..1]	Qty	
MatchIncrement	[0..1]	Qty	

Name	Mult.	Type	Description
MaxPriceLevels	[0..1]	int	
DisplayInstruction	[0..1]	Component	Insert here the set of "DisplayInstruction" fields defined in "common components of application messages"
MaxFloor	[0..1]	Qty	
ExDestination	[0..1]	Exchange	
ExDestinationIDSource	[0..1]	CodeSet	
TrdgSesGrp	[0..*]	Group	
ProcessCode	[0..1]	CodeSet	
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	
PrevClosePx	[0..1]	Price	Useful for verifying security identification
Side	[1..1]	CodeSet	Note: to indicate the side of SideValue1 or SideValue2, specify Side=Undisclosed and SideValueInd=either the SideValue1 or SideValue2 indicator.
ShortMarkingExemptIndicator	[0..1]	Boolean	
ShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when Side(54) = 6(Sell short exempt).
SideValueInd	[0..1]	CodeSet	Refers to the SideValue1 or SideValue2. These are used as opposed to Buy or Sell so that the basket can be quoted either way as Buy or Sell.
LocateReqd	[0..1]	CodeSet	Required for short sell orders
TransactTime	[0..1]	UTCTimestamp	
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" (repeating group of Fixed Income stipulations) fields defined in "Common Components of Application Messages"
QtyType	[0..1]	CodeSet	
OrderQtyData	[1..1]	Component	Insert here the set of "OrderQtyData" fields defined in "Common Components of Application Messages"
OrdType	[0..1]	CodeSet	
PriceType	[0..1]	CodeSet	
Price	[0..1]	Price	
PriceProtectionScope	[0..1]	CodeSet	



Name	Mult.	Type	Description
StopPx	[0..1]	Price	
TriggeringInstruction	[0..1]	Component	Insert here the set of "TriggeringInstruction" fields defined in "common components of application messages"
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" (Fixed Income spread or benchmark curve) fields defined in "Common Components of Application Messages"
YieldData	[0..1]	Component	Insert here the set of "YieldData" (yield-related) fields defined in "Common Components of Application Messages"
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
IOIID	[0..1]	String	Required for Previously Indicated Orders (OrdType=E)
QuoteID	[0..1]	String	Required for Previously Quoted Orders (OrdType=D)
RefOrderID	[0..1]	String	Required for counter-order selection / Hit / Take Orders (OrdType = Q)
RefOrderIDSource	[0..1]	CodeSet	Conditionally required if RefOrderID is specified.
TimeInForce	[0..1]	CodeSet	
EffectiveTime	[0..1]	UTCTimestamp	
ExpireDate	[0..1]	LocalMktDate	Conditionally required if TimeInForce = GTD and ExpireTime is not specified.
ExpireTime	[0..1]	UTCTimestamp	Conditionally required if TimeInForce = GTD and ExpireDate is not specified.
GTBookingInst	[0..1]	CodeSet	States whether executions are booked out or accumulated on a partially filled GT order

Name	Mult.	Type	Description
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)=10 (Good for Time)
ExposureDurationUnit	[0..1]	CodeSet	
CommissionData	[0..1]	Component	
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData if multiple commissions or enhanced attributes are needed.
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	
CustOrderCapacity	[0..1]	CodeSet	
OrderAttributeGrp	[0..*]	Group	
ForexReq	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	Method for booking out this order. Used when notifying a broker that an order to be settled by that broker is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
Price2	[0..1]	Price	Can be used with OrdType = "Forex - Swap" to specify the price for the future portion of a F/X swap which is also a limit order. For F/X orders, should be the "all-in" rate (spot rate adjusted for forward points).
PositionEffect	[0..1]	CodeSet	

Name	Mult.	Type	Description
CoveredOrUncovered	[0..1]	CodeSet	
MaxShow	[0..1]	Qty	
PegInstructions	[0..1]	Component	Insert here the set of "PegInstruction" fields defined in "Common Components of Application Messages"
DiscretionInstructions	[0..1]	Component	Insert here the set of "DiscretionInstruction" fields defined in "Common Components of Application Messages"
TargetStrategy	[0..1]	CodeSet	The target strategy of the order
StrategyParametersGrp	[0..*]	Group	Strategy parameter block
TargetStrategyParameters	[0..1]	String	For further specification of the TargetStrategy
ParticipationRate	[0..1]	Percentage	Mandatory for a TargetStrategy=Participate order and specifies the target participation rate. For other order types optionally specifies a volume limit (i.e. do not be more than this percent of the market volume)
Designation	[0..1]	String	Supplementary registration information for this Order within the List
ManualOrderIndicator	[0..1]	Boolean	

Used in messages: [NewOrderList](#)

### 180.2.2678 ListRejectReason

Identifies the reason for rejection of a New Order List message. Note that OrdRejReason(103) is used if the rejection is based on properties of an individual order part of the List.

Type: [int](#)

Allowed values in ListRejectReasonCodeSet:

Code	Name	Description
0	BrokerCredit	Broker / Exchange option
2	ExchangeClosed	Exchange closed
4	TooLateToEnter	Too late to enter
5	UnknownOrder	Unknown order
6	DuplicateOrder	Duplicate Order (e.g. dupe ClOrdID)

Code	Name	Description
11	UnsupportedOrderCharacteristic	Unsupported order characteristic
99	Other	Other

Used in messages: [ListStatus](#)

#### **180.2.2679 ListSeqNo**

Sequence of individual order within list (i.e. ListSeqNo of TotNoOrders (68), 2 of 25, 3 of 25, . . . )

Type: [int](#)

Used in groups: [ListOrdGrp](#)

#### **180.2.2680 ListStatusText**

Free format text string related to List Status.

Type: [String](#)

Used in messages: [ListStatus](#)

#### **180.2.2681 ListStatusType**

Code to represent the status type.

Type: [int](#)

Allowed values in ListStatusTypeCodeSet:

Code	Name	Description
1	Ack	Ack
2	Response	Response
3	Timed	Timed
4	ExecStarted	Exec Started
5	AllDone	All Done
6	Alert	Alert

Used in messages: [ListStatus](#)

**180.2.2682 ListUpdateAction**

If provided, then Instrument occurrence has explicitly changed

Type: **char**

Allowed values in ListUpdateActionCodeSet:

Code	Name	Description
A	Add	Add
D	Delete	Delete
M	Modify	Modify
S	Snapshot	Snapshot

Used in groups: **PartyDetailAckGrp**, **PartyDetailsUpdateGrp**, **PartyEntitlementAckGrp**, **PartyEntitlementUpdateGrp**, **PartyRiskLimitsAckGrp**, **PartyRiskLimitsUpdateGrp**, **RelSymDerivSecUpdGrp**, **SecLstUpdRelSymGrp**

**180.2.2683 LoanFacility**

Specifies the type of loan when the credit default swap's reference obligation is a loan.

Type: **int**

Allowed values in LoanFacilityCodeSet:

Code	Name	Description
0	BridgeLoan	Bridge loan
1	LetterOfCredit	Letter of credit
2	RevolvingLoan	Revolving loan
3	SwinglineFunding	Swingline funding
4	TermLoan	Term loan
5	TradeClaim	Trade claim

Used in components: **Instrument**

**180.2.2684 LocaleOfIssue**

Identifies the locale or region of issue.

Type: **String**

Used in components: **Instrument**

**180.2.2685 LocateReqd**

Indicates whether the broker is to locate the stock in conjunction with a short sell order.

Type: **Boolean**

Allowed values in LocateReqdCodeSet:

Code	Name	Description
N	No	Indicates the broker is not required to locate
Y	Yes	Indicates the broker is responsible for locating the stock

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.2686 LocationID**

Identification of a Market Maker's location

Type: **String**

Used in groups: **CompIDReqGrp**, **CompIDStatGrp**, **MDFullGrp**, **MDIncGrp**

**180.2.2687 LockedQty**

Locked order quantity.

Type: **Qty**

Used in messages: **ExecutionReport**

**180.2.2688 LockType**

Indicates whether an order is locked and for what reason.

Type: **int**

Allowed values in LockTypeCodeSet:

Code	Name	Description
0	NotLocked	Not locked
1	AwayMarketNetter	Away market better
2	ThreeTickLocked	Three tick locked
3	LockedByMarketMaker	Locked by market maker
4	DirectedOrderLock	Directed order lock
5	MultilegLock	Multileg lock. Lock in the context of multileg orders where legs are executed independently and the entire order is locked until matching information is available for all legs. A multileg order or quote must be matched in its entirety or not at all. For example, one of the legs may be a stock leg sent to a different execution venue that may or may not be able to fill it.
6	MarketOrderLock	Market order lock
7	PreAssignmentLock	Pre-assignment lock

Used in messages: **ExecutionReport**

**180.2.2689 LongQty**

Long quantity.

Type: **Qty**

Used in groups: **PositionQty**, **TradePositionQty**

**180.2.2690 LotType**

Defines the lot type assigned to the order.

Type: **char**

Allowed values in LotTypeCodeSet:

Code	Name	Description
1	OddLot	Odd Lot
2	RoundLot	Round Lot
3	BlockLot	Block Lot
4	RoundLotBasedUpon	Round lot based upon UnitOfMeasure(996)

Used in components: [TradeReportOrderDetail](#)

Used in groups: [LotTypeRules](#), [MDFullGrp](#), [MDIncGrp](#)

Used in messages: [ExecutionReport](#)

### 180.2.2691 LotTypeRules

Name	Mult.	Type	Description
<a href="#">NoLotTypeRules</a>	[1..1]	NumInGroup	Number of Lot Types
<a href="#">LotType</a>	[0..1]	CodeSet	Defines the lot type assigned to the order. Use as an alternate to RoundLot(561). To be used with MinLotSize(1231). LotType + MinLotSize (max is next level minus 1). Required if NoLotTypeRules(1234) > 0.
<a href="#">MinLotSize</a>	[0..1]	Qty	Minimum lot size allowed based on lot type specified in LotType(1093)

Used in components: [BaseTradingRules](#)

### 180.2.2692 LowExercisePriceOptionIndicator

Indicates if a given option instrument permits low exercise prices (LEPO).

Type: [Boolean](#)

Used in components: [Instrument](#)

### 180.2.2693 LowLimitPrice

Allowable low limit price for the trading day. A key parameter in validating order price. Used as the lower band for validating order prices. Orders submitted with prices below the lower limit will be rejected



Type: **Price**

Used in components: **PriceLimits**

#### **180.2.2694 LowPx**

Represents an indication of the low end of the price range for a security prior to the open or reopen

Type: **Price**

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **AllocationInstructionAlert**, **SecurityStatus**

#### **180.2.2695 MailingDtls**

Set of Correspondence address details, possibly including phone, fax, etc.

Type: **String**

Used in groups: **RgstDtlsGrp**

#### **180.2.2696 MailingInst**

Free format text to specify mailing instruction requirements, e.g. "no third party mailings".

Type: **String**

Used in groups: **RgstDtlsGrp**

#### **180.2.2697 MakeWholeAmount**

Amount to be paid by the buyer of the option if the option is exercised prior to the MakeWhole-Date(42591).

Type: **Amt**

Used in components: **OptionExerciseMakeWholeProvision**

#### **180.2.2698 MakeWholeBenchmarkCurveName**

Identifies the benchmark floating rate index.

Type: **String**

Used in components: **OptionExerciseMakeWholeProvision**

**180.2.2699 MakeWholeBenchmarkCurvePoint**

The point on the floating rate index curve.

Sample values:

M = combination of a number between 1-12 and an "M" for month, e.g. 3M

Y = combination of number between 1-100 and a "Y" for year, e.g. 10Y

10Y-OLD = see above, then add "-OLD" when appropriate

INTERPOLATED = the point is mathematically derived

2/2031 5 3/8 = the point is stated via a combination of maturity month / year and coupon.

Type: **String**

Used in components: **OptionExerciseMakeWholeProvision**

**180.2.2700 MakeWholeBenchmarkQuote**

The quote side of the benchmark to be used for calculating the "make whole" amount.

Type: **int**

Allowed values in StrikeIndexQuoteCodeSet:

Code	Name	Description
0	Bid	Bid.
1	Mid	Mid
2	Offer	Offer

Used in components: **OptionExerciseMakeWholeProvision**

**180.2.2701 MakeWholeDate**

The date through which option cannot be exercised without penalty.

Type: **LocalMktDate**

Used in components: **OptionExerciseMakeWholeProvision**

**180.2.2702 MakeWholeInterpolationMethod**

The method used when calculating the "make whole" amount. The most common is linear method.

Type: **int**

Allowed values in PaymentStreamInflationInterpolationMethodCodeSet:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: **OptionExerciseMakeWholeProvision**

**180.2.2703 MakeWholeRecallSpread**

Spread over the floating rate index.

Type: **PriceOffset**

Used in components: **OptionExerciseMakeWholeProvision**

**180.2.2704 MandatoryClearingIndicator**

An indication that the trade is flagged for mandatory clearing.

Type: **Boolean**

Used in messages: **TradeCaptureReport**

**180.2.2705 MandatoryClearingJurisdiction**

Identifier of the regulatory jurisdiction requiring the trade to be cleared.

Type: **String**

Used in groups: **MandatoryClearingJurisdictionGrp**

**180.2.2706 MandatoryClearingJurisdictionGrp**

MandatoryClearingJurisdictionGrp is a repeating component of TradeCaptureReport used to specify the set of jurisdictions to which mandatory clearing applies.

Name	Mult.	Type	Description
NoMandatoryClearingJurisdictions	[1..1]	NumInGroup	
MandatoryClearingJurisdiction	[0..1]	String	Required if NoNoMandatoryClearingJurisdictions(41312) > 0.

Used in messages: [TradeCaptureReport](#)

**180.2.2707 ManualNoticeBusinessCenter**

Identifies the business center used for adjusting the time for manual exercise notice.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in components: [OptionExercise](#)

**180.2.2708 ManualOrderIndicator**

Indicates if an order, quote or trade was initially received manually (as opposed to electronically) or if it was entered manually (as opposed to entered by automated trading software).

Type: [Boolean](#)

Used in groups: [ListOrdGrp](#)

Used in messages: [ExecutionReport](#), [MassOrder](#), [MassOrderAck](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [TradeCaptureReport](#)

**180.2.2709 MarginAmount**

Name	Mult.	Type	Description
NoMarginAmt	[1..1]	NumInGroup	Number of margin amount entries
MarginAmt	[0..1]	Amt	

Name	Mult.	Type	Description
MarginAmtType	[0..1]	CodeSet	Total margin requirement if not provided
MarginAmtCcy	[0..1]	Currency	Can be used to specify the base settlement currency if Currency(15) is not specified.
MarginAmtFXRate	[0..1]	float	
MarginAmtFXRateCalc	[0..1]	CodeSet	
MarginAmountMarketSegmentID	[0..1]	String	
MarginAmountMarketID	[0..1]	String	
MarginDirection	[0..1]	CodeSet	

Used in messages: [AccountSummaryReport](#), [MarginRequirementReport](#)

#### **180.2.2710 MarginAmountMarketID**

Market associated with the margin amount

Type: [String](#)

Used in groups: [MarginAmount](#)

#### **180.2.2711 MarginAmountMarketSegmentID**

Market segment associated with the margin amount.

Type: [String](#)

Used in groups: [MarginAmount](#)

#### **180.2.2712 MarginAmt**

Amount of margin requirement.

Type: [Amt](#)

Used in groups: [MarginAmount](#)

#### **180.2.2713 MarginAmtCcy**

Currency of the MarginAmt(1645).

Type: **Currency**

Used in groups: **MarginAmount**

#### **180.2.2714 MarginAmtFXRate**

Foreign exchange rate used to compute the MarginAmt(1645) from the MarginAmtCcy(1646) and the Currency(15).

Type: **float**

Used in groups: **MarginAmount**

#### **180.2.2715 MarginAmtFXRateCalc**

Specifies whether or not MarginAmtFXRate(2088) should be multiplied or divided.

Type: **char**

Allowed values in UnderlyingFXRateCalcCodeSet:

Code	Name	Description
D	Divide	Divide
M	Multiply	Multiply

Used in groups: **MarginAmount**

#### **180.2.2716 MarginAmtType**

Type of margin requirement amount being specified.

Type: **int**

Allowed values in MarginAmtTypeCodeSet:

Code	Name	Description
1	AdditionalMargin	Additional Margin. Component of the total margin calculation which allows the CCP to include amounts generated outside of the Margin Deficit. Additional risk charges collected when a firm is placed on higher than normal surveillance. Additional margin serves to cover the additional liquidation costs that potentially could be incurred. Such possible close-out costs could arise if, based on the current market value of a portfolio, the worst case loss were to occur within a 24-hour period. It is used for options (also options on futures) and non-spread futures positions, bonds and equity trades. For bonds and equity trades, the additional margin is calculated for security positions but not for the corresponding cash positions.
2	AdjustedMargin	Adjusted Margin. Unadjusted Margin can be modified to become an Adjusted Margin by assigning a specific collateral to it or by applying an exchange rate.
3	UnadjustedMargin	Unadjusted Margin. Calculated by adding up the options Premium Margin, the current Liquidating Margin, the Futures Spread Margin and the Additional Margin on account and currency level.
4	BinaryAddOnAmount	Binary Add-On Amount. Requirement generated from positions in Binary Options which are considered fully margined. Margin for an individual contract in this category represents the total amount that would be paid upon delivery of a contract should it expire in-the-money. This amount is included as a component of Additional Margin in the Total Margin calculation.
5	CashBalanceAmount	Cash Balance Amount. Information about cash balance posted to the clearing house to cover the current margin requirement.
6	ConcentrationMargin	Concentration Margin. Reflects a riskier portfolio concentration when a set of closely related products is held.
7	CoreMargin	Core Margin. Specific basic requirement of a position. Core margin is equal to Initial Margin plus a percentage of the Variation Margin.
8	DeliveryMargin	Delivery Margin. Margin amount calculated between the Last Trade Date or Options Exercise Date and the Delivery or Settlement Date. Can also represent a commodities or energy delivery.
9	DiscretionaryMargin	Discretionary Margin. Unspecific margin amount added by the risk manager, also called Increase Coverage Amount.

Code	Name	Description
10	FuturesSpreadMargin	Futures Spread Margin. Long and short positions of futures with different expiration dates can be offset against each other and are called “spreads”. The remaining risk stems from the difference in expiration dates which does not provide a perfect price correlation. The purpose of Futures Spread Margin is to cover this risk until the next trading day. This kind of margin is levied in order to cover those risks associated with a futures spread which could arise between today and tomorrow.
11	InitialMargin	Initial Margin. The initial amount required to cover the position.
12	LiquidatingMargin	Liquidating Margin. Calculated for cash, bond and equity positions and is equal to the profits and losses in such positions at the time of calculation. This margin protects the CCP if it is required to close out the position at the current/EOD price. The liquidating margin (also called Current Liquidating Margin or Net Liquidating Margin) is paid by the buyer or the seller of the bonds. This margin covers losses that would occur if a position were to be liquidated today. The liquidating margin is adjusted daily similar to premium margin.
13	MarginCallAmount	Margin Call Amount. If the collateral that has been deposited is no longer sufficient, meaning a lack of coverage exists, then the market participant will be called upon to provide additional cash as collateral.
14	MarginDeficitAmount	Margin Deficit Amount (Shortfall). Base margin risk charge. This amount represents anticipated losses should the value of a portfolio (all positions in the account) fall below predefined level of Historical Value-at-Risk confidence. Also called Expected Shortfall Amount.
15	MarginExcessAmount	Margin Excess Amount (Surplus). Excess long premium value which is generated when long premium value exceeds the sum of any short premium debit requirement and the account's risk charges. Also called Expected Surplus Amount or Margin Credit Amount.
16	OptionPremiumAmount	Option Premium Amount. Premium registered on the given trading date. The amount of money that the options buyer must pay the options seller.
17	PremiumMargin	Premium Margin. Premium margin must be deposited by the seller of a traditional options position. It remains effective until the exercise or expiration of the option, and covers the potential costs of a close-out (liquidation) of the position of the seller at the settlement price.



Code	Name	Description
18	ReserveMargin	Reserve Margin. Reserve margin provides a way to reflect the inflated risk of a position. Reserve margin is equal to a percentage of the variation margin.
19	SecurityCollateralAmount	Security Collateral Amount. Information about the security collateral posted to the clearing house to cover the current margin requirement.
20	StressTestAddOnAmount	Stress Test Add-On Amount. Amount in addition to Margin Deficit in the Risk component of the margin calculation. This charge is based on tests which incorporate changes to distributional and confidence level assumptions to evaluate exposure to security concentration and changes in dependence structure; a predetermined percentage of the calculated exposure is collateralized as this charge.
21	SuperMargin	Super Margin. Additional risk charge applied to predetermined Cross-Margin accounts. The charge is based on the account's level of Margin Deficit. This amount is included as a component of Additional Margin in the Total Margin calculation.
22	TotalMargin	Total Margin. Sum of all margin amounts at value date.
23	VariationMargin	Variation Margin. Variation margin (also called Contingent Variation Margin or Maintenance Margin) is the daily Profit and Loss (P&L) on Open Positions for the given trading date. The current price is compared to the previous day's price. Variation margin (a daily offsetting of profits and losses) occurs as a result of the mark-to-market procedure used for futures and options on futures.
24	SecondaryVariationMargin	Secondary Variation Margin. Variation margin on Option Positions that is calculated based on the market movement. This will be used by CCPs wanting to report the variation for Options and Futures separately.
25	RolledUpMarginDeficit	Rolled up margin deficit
26	SpreadResponseMargin	Spread response margin. Risk factor component associated with spread moves, curve shape changes and recovery rates.
27	SystemicRiskMargin	Systemic risk margin. Risk factor component to capture parallel shift of credit spreads.
28	CurveRiskMargin	Curve risk margin. Risk factor captures curve shifts based on portfolio.
29	IndexSpreadRiskMargin	Index spread risk margin. Risk factor component associated with risks due to widening/tightening spreads of CDS indices relative to each other.
30	SectorRiskMargin	Sector risk margin. Risk factor component to capture sector risk.

Code	Name	Description
31	JumpToDefaultRiskMargin	Jump-to-default risk margin. Risk factor component to capture extreme widening of credit spreads of a reference entity. Also known as Idiosyncratic Risk.
32	BasisRiskMargin	Basis risk margin. Risk factor component to capture basis risk between index and index constituent reference entities.
33	InterestRateRiskMargin	Interest rate risk margin. Risk factor component associated with parallel shift movements in interest rates.
34	JumpToHealthRiskMargin	Jump-to-health risk margin. Risk factor component to capture extreme narrowing of credit spreads of a reference entity. Also known as Idiosyncratic Risk.
35	OtherRiskMargin	Other risk margin. Any other risk factors include in the Margin Model.

Used in groups: **MarginAmount**

#### **180.2.2717 MarginClass**

Identifier for group of instruments with similar risk profile.

Type: **String**

Used in messages: **MarginRequirementInquiry**, **MarginRequirementInquiryAck**, **MarginRequirementReport**

#### **180.2.2718 MarginDirection**

Indicates whether the margin described is posted or received.

Type: **int**

Allowed values in MarginDirectionCodeSet:

Code	Name	Description
0	Posted	Posted. The party or account that is the object of the report posted margin.
1	Received	Received. The party or account that is the object of the report received margin.

Used in groups: **MarginAmount**

**180.2.2719 MarginExcess**

Excess margin amount (deficit if value is negative)

Type: **Amt**

Used in messages: **AccountSummaryReport**, **CollateralAssignment**, **CollateralInquiry**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**

**180.2.2720 MarginRatio**

The fraction of the cash consideration that must be collateralized, expressed as a percent. A MarginRatio of 02% indicates that the value of the collateral (after deducting for "haircut") must exceed the cash consideration by 2%.

Type: **Percentage**

Used in components: **FinancingDetails**

**180.2.2721 MarginReqmtInqID**

Unique identifier of the MarginRequirementInquiry.

Type: **String**

Used in messages: **MarginRequirementInquiry**, **MarginRequirementInquiryAck**, **MarginRequirementReport**, **PositionReport**

**180.2.2722 MarginReqmtInqQualGrp**

---

Name	Mult.	Type	Description
<b>NoMarginReqmtInqQualifier</b>	[1..1]	NumInGroup	Number of qualifier entries
<b>MarginReqmtInqQualifier</b>	[0..1]	CodeSet	

---

Used in messages: **MarginRequirementInquiry**, **MarginRequirementInquiryAck**

**180.2.2723 MarginReqmtInqQualifier**

Qualifier for MarginRequirementInquiry to identify a specific report.

Type: **int**

Allowed values in MarginReqmtInqQualifierCodeSet:

Code	Name	Description
0	Summary	Summary
1	Detail	Detail
2	ExcessDeficit	Excess/Deficit
3	NetPosition	Net Position

Used in groups: **MarginReqmtInqQualGrp**

**180.2.2724 MarginReqmtInqResult**

Result returned in response to MarginRequirementInquiry.

Type: **int**

Allowed values in MarginReqmtInqResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidOrUnknownInstrument	Invalid or unknown instrument
2	InvalidOrUnknownMarginClass	Invalid or unknown margin class
3	InvalidParties	Invalid Parties
4	InvalidTransportTypeReq	Invalid Transport Type requested
5	InvalidDestinationReq	Invalid Destination requested
6	NoMarginReqFound	No margin requirement found
7	MarginReqInquiryQualifierNotSupported	Margin requirement inquiry qualifier not supported
8	UnauthorizedForMarginReqInquiry	Unauthorized for margin requirement inquiry
99	Other	Other (further information in Text (58) field)

Used in messages: **MarginRequirementInquiryAck**

**180.2.2725 MarginReqmtInqStatus**

Status of MarginRequirementInquiry.

Type: **int**

Allowed values in CollInquiryStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithWarnings	Accepted With Warnings
2	Completed	Completed
3	CompletedWithWarnings	Completed With Warnings
4	Rejected	Rejected

Used in messages: **MarginRequirementInquiryAck**

**180.2.2726 MarginReqmtRptID**

Identifier for the MarginRequirementReport message.

Type: **String**

Used in messages: **MarginRequirementReport**

**180.2.2727 MarginReqmtRptType**

Type of MarginRequirementReport.

Type: **int**

Allowed values in MarginReqmtRptTypeCodeSet:

Code	Name	Description
0	Summary	Summary
1	Detail	Detail
2	ExcessDeficit	Excess/Deficit

Used in messages: **MarginRequirementReport**

**180.2.2728 MarketCondition**

Market condition. In the context of ESMA RTS 8 it is important that trading venues communicate the condition of the market, particularly "stressed" and "exceptional", in order to provide incentives for firms contributing to liquidity.

Type: **int**

Allowed values in MarketConditionCodeSet:

Code	Name	Description
0	Normal	Normal. The condition of the market in the absence of "stressed" or "exceptional" conditions.
1	Stressed	Stressed. In the context of ESMA RTS 8 Article 6: Trading venues shall set out the parameters to identify stressed market conditions in terms of significant short-term changes of price and volume. Trading venues shall consider the resumption of trading after volatility interruptions as stressed market conditions.
2	Exceptional	Exceptional. In the context of ESMA RTS 8 Article 3: Due to (a) a situation of extreme volatility; (b) war, industrial action, civil unrest or cyber sabotage; (c) disorderly trading conditions, e.g. due to technical issues; (d) unavailability of risk management facilities.

Used in groups: **MDFullGrp**, **MDIncGrp**

**180.2.2729 MarketDataFeedTypes**

The MarketDataFeedTypes component is used to specify the different available feed types and sub-types, and additional market data feed related attributes, such as the market depth of the specified feed type.

Name	Mult.	Type	Description
<b>NoMDFeedTypes</b>	[1..1]	NumInGroup	
<b>MDFeedType</b>	[0..1]	String	Required if NoMDFeedTypes(1141) > 0.
<b>MDSubFeedType</b>	[0..1]	String	
<b>MarketDepth</b>	[0..1]	int	Specifies the depth of book (or levels of market depth) for the feed type.

Name	Mult.	Type	Description
MarketDepthTimeInterval	[0..1]	int	Conditionally required when MarketDepthTimeIntervalUnit(2564) is specified.
MarketDepthTimeIntervalUnit	[0..1]	CodeSet	Conditionally required when MarketDataTimeInterval(2563) is specified.
MDRecoveryTimeInterval	[0..1]	int	Conditionally required when MDRecoveryTimeIntervalUnit(2566) is specified.
MDRecoveryTimeIntervalUnit	[0..1]	CodeSet	Conditionally required when MDRecoveryTimeInterval(2565) is specified.
MDBookType	[0..1]	CodeSet	
MDSubBookType	[0..1]	int	
PrimaryServiceLocationID	[0..1]	String	
SecondaryServiceLocationID	[0..1]	String	

Used in components: [TradingSessionRules](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

### 180.2.2730 MarketDepth

Depth of market for Book Snapshot / Incremental updates

0 - full book depth

1 - top of book

2 and above - book depth (number of levels)

Type: [int](#)

Used in components: [MDStatisticParameters](#)

Used in groups: [MDIncGrp](#), [MarketDataFeedTypes](#)

Used in messages: [MarketDataRequest](#), [MarketDataSnapshotFullRefresh](#), [SecurityMassStatus](#), [SecurityStatus](#)

### 180.2.2731 MarketDepthTimeInterval

Specifies the time interval used for netting market data in a price depth feed.

Type: [int](#)

Used in groups: [MarketDataFeedTypes](#)

**180.2.2732 MarketDepthTimeIntervalUnit**

The time unit associated with the time interval of the netting of market data in a price depth feed.

Type: **int**

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in groups: **MarketDataFeedTypes**

**180.2.2733 MarketDisruption**

The MarketDisruption component is a subcomponent of the Instrument used to specify the market disruption provisions of the swap.

Name	Mult.	Type	Description
<b>MarketDisruptionProvision</b>	[0..1]	CodeSet	
<b>MarketDisruptionEventGrp</b>	[0..*]	Group	
<b>MarketDisruptionFallbackProvision</b>	[0..1]	CodeSet	
<b>MarketDisruptionFallbackGrp</b>	[0..*]	Group	
<b>MarketDisruptionFallbackReferencePriceGrp</b>	[0..*]	Group	
<b>MarketDisruptionMaximumDays</b>	[0..1]	int	



Name	Mult.	Type	Description
MarketDisruptionMaterialityPercentage	[0..1]	Percentage	If specified, the disruption event should be specified in MarketDisruptionEventGrp.
MarketDisruptionMinimumFuturesContracts	[0..1]	int	Applicable only when MarketDisruptionEvent(41093)='DeMinimisTrading'.

Used in components: **Instrument**

#### 180.2.2734 MarketDisruptionEvent

Specifies the market disruption event.

For commodities see <http://www.fpml.org/coding-scheme/commodity-market-disruption> for values.

For foreign exchange, see [http://www.fixtradingcommunity.org/codelists#Market\\_Disruption\\_Event](http://www.fixtradingcommunity.org/codelists#Market_Disruption_Event) for code list of applicable event types.

Type: **String**

Used in groups: **MarketDisruptionEventGrp**

#### 180.2.2735 MarketDisruptionEventGrp

The MarketDisruptionEventGrp is a repeating subcomponent of the MarketDisruption component used to specify the market disruption events.

Name	Mult.	Type	Description
NoMarketDisruptionEvents	[1..1]	NumInGroup	
MarketDisruptionEvent	[0..1]	String	Required if NoMarketDisruptionEvents(41092) > 0.
MarketDisruptionValue	[0..1]	String	

Used in components: **MarketDisruption**

#### 180.2.2736 MarketDisruptionFallbackBasketCurrency

Specifies the currency if the underlier is a basket. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **MarketDisruptionFallbackReferencePriceGrp**

#### **180.2.2737 MarketDisruptionFallbackBasketDivisor**

Specifies the basket divisor amount. This value is normally used to adjust the constituent weight for pricing or to adjust for dividends, or other corporate actions.

Type: **float**

Used in groups: **MarketDisruptionFallbackReferencePriceGrp**

#### **180.2.2738 MarketDisruptionFallbackGrp**

The MarketDisruptionFallbackGrp is a repeating subcomponent of the MarketDisruption component used to specify the market disruption fallback provisions.

Name	Mult.	Type	Description
<b>NoMarketDisruptionFallbacks</b>	[1..1]	NumInGroup	
<b>MarketDisruptionFallbackType</b>	[0..1]	String	Required if NoMarketDisruptionFallbacks(41094) > 0. The sequence of entries specifies the order in which the fallback provisions should be applied.
<b>MarketDisruptionFallbackValue</b>	[0..1]	String	

Used in components: **MarketDisruption**

#### **180.2.2739 MarketDisruptionFallbackOpenUnits**

If there are multiple underlying assets, this specifies the number of units (index or securities) that constitute the underlier of the swap. In the case of a basket swap, this is used to reference both the number of basket units, and the number of each asset components of the basket when these are expressed in absolute terms.

Type: **Qty**

Used in groups: **MarketDisruptionFallbackReferencePriceGrp**

**180.2.2740 MarketDisruptionFallbackProvision**

Specifies the location of the fallback provision documentation.

Type: **int**

Allowed values in MarketDisruptionFallbackProvisionCodeSet:

Code	Name	Description
0	MasterAgreement	As specified in master agreement
1	Confirmation	As specified in confirmation

Used in components: **MarketDisruption**

**180.2.2741 MarketDisruptionFallbackReferencePriceGrp**

The MarketDisruptionFallbackReferencePriceGrp is a repeating subcomponent of the MarketDisruption component used to specify the fallback reference price and underlying security provisions

Name	Mult.	Type	Description
NoMarketDisruptionFallbackReferencePrices	[1..1]	NumInGroup	
MarketDisruptionFallbackUnderlierType	[0..1]	CodeSet	Required if NoMarketDisruptionFallbackReferencePrices(41096) > 0.
MarketDisruptionFallbackUnderlierSecurityID	[0..1]	String	Conditionally required when MarketDisruptionFallbackUnderlierSecurityIDSource(41099) is specified.
MarketDisruptionFallbackUnderlierSecurityIDSource	[0..1]	CodeSet	Conditionally required when MarketDisruptionFallbackUnderlierSecurityID(41098) is specified.
MarketDisruptionFallbackUnderlierSecurityDesc	[0..1]	String	
EncodedMarketDisruptionFallbackUnderlierSecurityDescLen	[0..1]	Length	Must be set if EncodedMarketDisruptionFallbackUnderlierSecurityDesc(41102) field is specified and must immediately precede it
EncodedMarketDisruptionFallbackUnderlierSecurityDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the MarketDisruptionFallbackUnderlierSecurityDesc(41100) field in the encoded format specified via the MessageEncoding(347) field.
MarketDisruptionFallbackOpenUnits	[0..1]	Qty	

Name	Mult.	Type	Description
MarketDisruptionFallbackBasketCurrency	[0..1]	Currency	
MarketDisruptionFallbackBasketDivisor	[0..1]	float	

Used in components: [MarketDisruption](#)

#### **180.2.2742 MarketDisruptionFallbackType**

Specifies the type of disruption fallback.

See <http://www.fpml.org/coding-scheme/commodity-market-disruption-fallback> for values.

Type: [String](#)

Used in groups: [MarketDisruptionFallbackGrp](#)

#### **180.2.2743 MarketDisruptionFallbackUnderlierSecurityDesc**

Specifies the description of the underlying security.

Type: [String](#)

Used in groups: [MarketDisruptionFallbackReferencePriceGrp](#)

#### **180.2.2744 MarketDisruptionFallbackUnderlierSecurityID**

Specifies the identifier value of the security.

Type: [String](#)

Used in groups: [MarketDisruptionFallbackReferencePriceGrp](#)

#### **180.2.2745 MarketDisruptionFallbackUnderlierSecurityIDSource**

Specifies the class or source scheme of the security identifier.

Type: [String](#)

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)

Code	Name	Description
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **MarketDisruptionFallbackReferencePriceGrp**

### 180.2.2746 MarketDisruptionFallbackUnderlierType

The type of reference price underlier.

Type: **int**

Allowed values in MarketDisruptionFallbackUnderlierTypeCodeSet:

Code	Name	Description
0	Basket	Basket
1	Bond	Bond
2	Cash	Cash
3	Commodity	Commodity
4	ConvertibleBond	Convertible bond
5	Equity	Equity
6	ExchangeTradedFund	Exchange traded fund
7	Future	Future
8	Index	Index
9	Loan	Loan
10	Mortgage	Mortgage
11	MutualFund	Mutual fund

Used in groups: **MarketDisruptionFallbackReferencePriceGrp**

### 180.2.2747 MarketDisruptionFallbackValue

Applicable value for MarketDisruptionFallbackType(41095).

Type: **String**

Used in groups: **MarketDisruptionFallbackGrp**

#### **180.2.2748 MarketDisruptionMaterialityPercentage**

Used when a price materiality percentage applies to the price source disruption event and this event has been specified.

Type: **Percentage**

Used in components: **MarketDisruption**

#### **180.2.2749 MarketDisruptionMaximumDays**

Specifies the maximum number of market disruption days (commodity or bullion business days) in a contract or confirmation. If none are specified, the maximum number of market disruption days is five (5).

Type: **int**

Used in components: **MarketDisruption**

#### **180.2.2750 MarketDisruptionMinimumFuturesContracts**

Specifies the minimum futures contracts level that dictates whether or not a 'De Minimis Trading' event has occurred.

Type: **int**

Used in components: **MarketDisruption**

#### **180.2.2751 MarketDisruptionProvision**

The consequences of market disruption events.

Type: **int**

Allowed values in MarketDisruptionProvisionCodeSet:

---

Code	Name	Description
0	NotApplicable	Not applicable
1	Applicable	Applicable

---

Code	Name	Description
2	AsInMasterAgreement	As specified in master agreement
3	AsInConfirmation	As specified in confirmation

Used in components: [MarketDisruption](#)

### **180.2.2752 MarketDisruptionValue**

Applicable value for MarketDisruptionEvent(41093).

Type: [String](#)

Used in groups: [MarketDisruptionEventGrp](#)

### **180.2.2753 MarketID**

Identifies the market

Type: [Exchange](#)

Used in groups: [MarketSegmentGrp](#), [MarketSegmentScopeGrp](#), [TrdSessLstGrp](#)

Used in messages: [CrossRequest](#), [CrossRequestAck](#), [DerivativeSecurityListRequest](#), [MarketDataIncrementalRefresh](#), [MarketDataSnapshotFullRefresh](#), [MarketDataStatisticsReport](#), [MarketDataStatisticsRequest](#), [MarketDefinition](#), [MarketDefinitionRequest](#), [MarketDefinitionUpdateReport](#), [MassOrder](#), [MassOrderAck](#), [News](#), [OrderMassActionReport](#), [OrderMassActionRequest](#), [OrderMassCancelReport](#), [OrderMassCancelRequest](#), [PartyActionReport](#), [PartyActionRequest](#), [SecurityDefinitionRequest](#), [SecurityList](#), [SecurityListRequest](#), [SecurityListUpdateReport](#), [SecurityMassStatus](#), [SecurityMassStatusRequest](#), [SecurityStatus](#), [SecurityStatusRequest](#), [SecurityTypeRequest](#), [SecurityTypes](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeMatchReport](#), [TradingSessionListRequest](#), [TradingSessionStatus](#), [TradingSessionStatusRequest](#)

### **180.2.2754 MarketMakerActivity**

Indicates market maker participation in security.

Type: [int](#)

Allowed values in MarketMakerActivityCodeSet:



Code	Name	Description
0	NoParticipation	No participation
1	BuyParticipation	Buy participation
2	SellParticipation	Sell participation
3	BothBuyAndSellParticipation	Both buy and sell participation

Used in messages: [SecurityStatus](#)

#### **180.2.2755 MarketReportID**

Market Definition message identifier.

Type: [String](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

#### **180.2.2756 MarketReqID**

Unique ID of a Market Definition Request message.

Type: [String](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionRequest](#), [MarketDefinitionUpdateReport](#)

#### **180.2.2757 MarketSegmentDesc**

Description or name of Market Segment

Type: [String](#)

Used in messages: [MarketDataStatisticsReport](#), [MarketDataStatisticsRequest](#), [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

#### **180.2.2758 MarketSegmentGrp**

Name	Mult.	Type	Description
<a href="#">NoMarketSegments</a>	[1..1]	NumInGroup	Number of Market Segments on which a security may trade.

Name	Mult.	Type	Description
MarketID	[0..1]	Exchange	Identifies the market which lists and trades the instrument.
MarketSegmentID	[0..1]	String	Identifies the segment of the market to which the specify trading rules and listing rules apply.
SecurityTradingRules	[0..1]	Component	
StrikeRules	[0..*]	Group	This block specifies the rules for determining how new strikes should be listed within the stated price range of the underlying instrument.

Used in components: [DerivativeSecurityDefinition](#)

Used in messages: [SecurityDefinition](#), [SecurityDefinitionUpdateReport](#)

### 180.2.2759 MarketSegmentID

Identifies the market segment

Type: [String](#)

Used in groups: [MarketSegmentGrp](#), [MarketSegmentScopeGrp](#), [TrdSessLstGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [CrossOrderCancelRequest](#), [CrossRequest](#), [CrossRequestAck](#), [DerivativeSecurityListRequest](#), [ExecutionReport](#), [MarketDataIncrementalRefresh](#), [MarketDataSnapshotFullRefresh](#), [MarketDataStatisticsReport](#), [MarketDataStatisticsRequest](#), [MarketDefinition](#), [MarketDefinitionRequest](#), [MarketDefinitionUpdateReport](#), [MassOrder](#), [MassOrderAck](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [News](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [OrderMassActionReport](#), [OrderMassActionRequest](#), [OrderMassCancelReport](#), [OrderMassCancelRequest](#), [OrderStatusRequest](#), [PartyActionReport](#), [PartyActionRequest](#), [SecurityDefinitionRequest](#), [SecurityList](#), [SecurityListRequest](#), [SecurityListUpdateReport](#), [SecurityMassStatus](#), [SecurityMassStatusRequest](#), [SecurityStatus](#), [SecurityStatusRequest](#), [SecurityTypeRequest](#), [SecurityTypes](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeMatchReport](#), [TradingSessionListRequest](#), [TradingSessionStatus](#), [TradingSessionStatusRequest](#)

### 180.2.2760 MarketSegmentRelationship

Type of relationship between two or more market segments.

Type: [int](#)

Allowed values in [MarketSegmentRelationshipCodeSet](#):

Code	Name	Description
1	MarketSegmentPoolMember	Market segment pool member. Market segments represent constituents of the pool identified.
2	RetailSegment	Retail segment. Retail segment related to wholesale segment identified.
3	WholesaleSegment	Wholesale segment. Wholesale segment related to retail segment identified.

Used in groups: [RelatedMarketSegmentGrp](#)

### 180.2.2761 MarketSegmentScopeGrp

Conveys a list of markets and, optionally, their market segments. Note that the component MarketSegmentGrp exists, but is not useful for this purpose, as it conveys additional information not appropriate in this context.

Name	Mult.	Type	Description
<a href="#">NoMarketSegments</a>	[1..1]	NumInGroup	
<a href="#">MarketID</a>	[0..1]	Exchange	Required if NoMarketSegments(1310) > 0.
<a href="#">MarketSegmentID</a>	[0..1]	String	

Used in groups: [EntitlementGrp](#)

Used in messages: [MarketDataRequest](#), [PartyEntitlementsRequest](#)

### 180.2.2762 MarketSegmentStatus

Status of market segment.

Type: [int](#)

Allowed values in MarketSegmentStatusCodeSet:

Code	Name	Description
1	Active	Active. Market segment is active, i.e. trading is possible.
2	Inactive	Inactive. Market segment has previously been active and is now inactive.

Code	Name	Description
3	Published	Published. Market segment information is provided prior to its first activation.

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

### 180.2.2763 MarketSegmentSubType

Used to further categorize market segments within a MarketSegmentType(2543).

Type: [int](#)

Allowed values in MarketSegmentSubTypeCodeSet:

Code	Name	Description
1	InterProductSpread	Inter-product spread. Complex instruments which consist of leg instruments from different products, e.g. a location spread which include country-specific products in each leg instrument.

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

### 180.2.2764 MarketSegmentType

Used to classify the type of market segment.

Type: [int](#)

Allowed values in MarketSegmentTypeCodeSet:

Code	Name	Description
1	Pool	Pool. Used when multiple market segments are being grouped or pooled together.
2	Retail	Retail.
3	Wholesale	Wholesale.

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

**180.2.2765 MarketUpdateAction**

Specifies the action taken for the specified MarketID(1301) + MarketSegmentID(1300).

Type: **char**

Allowed values in SecurityUpdateActionCodeSet:

Code	Name	Description
A	Add	Add
D	Delete	Delete
M	Modify	Modify

Used in messages: **MarketDefinitionUpdateReport**

**180.2.2766 MassActionReason**

Reason for submission of mass action.

Type: **int**

Allowed values in MassActionReasonCodeSet:

Code	Name	Description
0	None	No special reason (default)
1	TradingRiskControl	Trading risk control. General violation of trading rules. Can be used if specific reason is unavailable or must not be disclosed.
2	ClearingRiskControl	Clearing risk control. General violation of clearing rules. Can be used if specific reason is unavailable or must not be disclosed.
3	MarketMakerProtection	Market maker protection. Specific action taken to prevent further executions for a market maker.
4	StopTrading	Stop trading. Specific action taken in conjunction with the prevention of further trading. Scope can be defined with TargetParties component.
5	EmergencyAction	Emergency action. Specific action taken due to an emergency condition. Scope can be defined with TargetParties component.
6	SessionLossLogout	Session loss or logout. Protection of trader or firm after having lost connectivity.
7	DuplicateLogin	Duplicate login. Trader only allowed to login once.

Code	Name	Description
8	ProductNotTraded	Product not traded. Product not available for trading, e.g. in a halted state.
9	InstrumentNotTraded	Instrument not traded. Instrument not available for trading, e.g. due to intra-day expiration.
10	CompleInstrumentDeleted	Complex instrument deleted. Removal of complex instrument, e.g. due to expiry, leading to mass action on open orders.
11	CircuitBreakerActivated	Circuit breaker activated. Trading interruption leading to mass action on open orders.
99	Other	Other

Used in messages: [OrderMassActionReport](#), [OrderMassActionRequest](#)

### 180.2.2767 MassActionRejectReason

Reason Order Mass Action Request was rejected

Type: [int](#)

Allowed values in MassActionRejectReasonCodeSet:

Code	Name	Description
0	MassActionNotSupported	Mass action not supported
1	InvalidOrUnknownSecurity	Invalid or unknown security
2	InvalidOrUnknownUnderlyingSecurity	Invalid or unknown underlying security
3	InvalidOrUnknownProduct	Invalid or unknown product
4	InvalidOrUnknownCFIcode	Invalid or unknown CFI Code
5	InvalidOrUnknownSecurityType	Invalid or unknown security type
6	InvalidOrUnknownTradingSession	Invalid or unknown trading session
7	InvalidOrUnknownMarket	Invalid or unknown market
8	InvalidOrUnknownMarketSegment	Invalid or unknown market segment
9	InvalidOrUnknownSecurityGroup	Invalid or unknown security group
10	InvalidOrUnknownSecurityIssuer	Invalid or unknown issuer
11	InvalidOrUnknownIssuerOfUnderlyingSecurity	Invalid or unknown issuer of underlying security
99	Other	Other

Used in messages: [OrderMassActionReport](#)

#### **180.2.2768 MassActionReportID**

Unique identifier of Order Mass Cancel Report or Order Mass Action Report message as assigned by sell-side (broker, exchange, ECN)

Type: [String](#)

Used in messages: [OrderMassActionReport](#), [OrderMassCancelReport](#)

#### **180.2.2769 MassActionResponse**

Specifies the action taken by counterparty order handling system as a result of the action type indicated in MassActionType of the Order Mass Action Request.

Type: [int](#)

Allowed values in MassActionResponseCodeSet:

Code	Name	Description
0	Rejected	Rejected - See MassActionRejectReason(1376)
1	Accepted	Accepted
2	Completed	Completed

Used in messages: [OrderMassActionReport](#)

#### **180.2.2770 MassActionScope**

Specifies scope of Order Mass Action Request.

Type: [int](#)

Allowed values in MassActionScopeCodeSet:

Code	Name	Description
1	AllOrdersForASecurity	All orders for a security
2	AllOrdersForAnUnderlyingSecurity	All orders for an underlying security
3	AllOrdersForAProduct	All orders for a product

Code	Name	Description
4	AllOrdersForACFICode	All orders for a CFI Code
5	AllOrdersForASecurityType	All orders for a security type
6	AllOrdersForATradingSession	All orders for a trading session
7	AllOrders	All orders
8	AllOrdersForAMarket	All orders for a market
9	AllOrdersForAMarketSegment	All orders for a market segment (or multiple segments)
10	AllOrdersForASecurityGroup	All orders for a security group
11	CancelForSecurityIssuer	All orders for an issuer
12	CancelForIssuerOfUnderlyingSecurity	All orders for an issuer of underlying security

Used in messages: [OrderMassActionReport](#), [OrderMassActionRequest](#)

#### **180.2.2771 MassActionType**

Specifies the type of action requested

Type: [int](#)

Allowed values in MassActionCodeSet:

Code	Name	Description
1	SuspendOrders	Suspend orders
2	ReleaseOrdersFromSuspension	Release orders from suspension
3	CancelOrders	Cancel orders

Used in messages: [OrderMassActionReport](#), [OrderMassActionRequest](#)

#### **180.2.2772 MassCancelRejectReason**

Reason Order Mass Cancel Request was rejected

Type: [int](#)

Allowed values in MassCancelRejectReasonCodeSet:



Code	Name	Description
0	MassCancelNotSupported	Mass Cancel Not Supported
1	InvalidOrUnknownSecurity	Invalid or unknown security
2	InvalidOrUnknownUnderlyingSecurity	Invalid or unknown underlying security
3	InvalidOrUnknownProduct	Invalid or unknown product
4	InvalidOrUnknownCFIcode	Invalid or unknown CFI Code
5	InvalidOrUnknownSecurityType	Invalid or unknown security type
6	InvalidOrUnknownTradingSession	Invalid or unknown trading session
7	InvalidOrUnknownMarket	Invalid or unknown market
8	InvalidOrUnknownMarketSegment	Invalid or unknown market segment
9	InvalidOrUnknownSecurityGroup	Invalid or unknown security group
10	InvalidOrUnknownSecurityIssuer	Invalid or unknown security issuer
11	InvalidOrUnknownIssuerOfUnderlyingSecurity	Invalid or unknown issuer of underlying security
99	Other	Other

Used in messages: **OrderMassCancelReport**

### 180.2.2773 MassCancelRequestType

Specifies scope of Order Mass Cancel Request.

Type: **char**

Allowed values in MassCancelRequestTypeCodeSet:

Code	Name	Description
1	CancelOrdersForASecurity	Cancel orders for a security
2	CancelOrdersForAnUnderlyingSecurity	Cancel orders for an underlying security
3	CancelOrdersForAProduct	Cancel orders for a product
4	CancelOrdersForACFIcode	Cancel orders for a CFI Code
5	CancelOrdersForASecurityType	Cancel orders for a security type
6	CancelOrdersForATradingSession	Cancel orders for a trading session
7	CancelAllOrders	Cancel all orders
8	CancelOrdersForAMarket	Cancel orders for a market

Code	Name	Description
9	CancelOrdersForAMarketSegment	Cancel orders for a market segment
A	CancelOrdersForASecurityGroup	Cancel orders for a security group
B	CancelOrdersForSecurityIssuer	Cancel orders for an issuer
C	CancelForIssuerOfUnderlyingSecurity	Cancel orders for an issuer of underlying security

Used in messages: [OrderMassCancelReport](#), [OrderMassCancelRequest](#)

### 180.2.2774 MassCancelResponse

Specifies the action taken by counterparty order handling system as a result of the Order Mass Cancel Request

Type: [char](#)

Allowed values in MassCancelResponseCodeSet:

Code	Name	Description
0	CancelRequestRejected	Cancel Request Rejected - See MassCancelRejectReason (532)
1	CancelOrdersForASecurity	Cancel orders for a security
2	CancelOrdersForAnUnderlyingSecurity	Cancel orders for an underlying security
3	CancelOrdersForAProduct	Cancel orders for a product
4	CancelOrdersForACFICode	Cancel orders for a CFI Code
5	CancelOrdersForASecurityType	Cancel orders for a security type
6	CancelOrdersForATradingSession	Cancel orders for a trading session
7	CancelAllOrders	Cancel all orders
8	CancelOrdersForAMarket	Cancel orders for a market
9	CancelOrdersForAMarketSegment	Cancel orders for a market segment
A	CancelOrdersForASecurityGroup	Cancel orders for a security group
B	CancelOrdersForASecuritiesIssuer	Cancel orders for an issuer
C	CancelOrdersForIssuerOfUnderlyingSecurity	Cancel orders for an issuer of underlying security

Used in messages: [OrderMassCancelReport](#)

**180.2.2775 MassHaltReason**

Denotes the reason for the Opening Delay or Trading halt of a group of securities.

Type: **int**

Allowed values in HaltReasonCodeSet:

Code	Name	Description
0	NewsDissemination	News Dissemination
1	OrderInflux	Order Influx
2	OrderImbalance	Order Imbalance
3	AdditionalInformation	Additional Information
4	NewsPending	News Pending
5	EquipmentChangeover	Equipment Changeover

Used in messages: **SecurityMassStatus**

**180.2.2776 MassOrderReportID**

Unique message identifier for the response to a mass order request as assigned by the receiver of the orders.

Type: **String**

Used in messages: **MassOrderAck**

**180.2.2777 MassOrderRequestID**

Unique message identifier for a mass order request as assigned by the submitter of the orders.

Type: **String**

Used in messages: **ExecutionReport**, **MassOrder**, **MassOrderAck**

**180.2.2778 MassOrderRequestResult**

Request result of mass order request.

Type: **int**

Allowed values in MassOrderRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful
1	ResponseLevelNotSupported	Response level not supported
2	InvalidMarket	Invalid market
3	InvalidMarketSegment	Invalid market segment
99	Other	Other

Used in messages: **MassOrderAck**

#### **180.2.2779 MassOrderRequestStatus**

Status of mass order request.

Type: **int**

Allowed values in MassOrderRequestStatusCodeSet:

Code	Name	Description
1	Accepted	Accepted
2	AcceptedWithAdditionalEvents	Accepted with additional events
3	Rejected	Rejected

Used in messages: **MassOrderAck**

#### **180.2.2780 MassStatusReqID**

Value assigned by issuer of Mass Status Request to uniquely identify the request

Type: **String**

Used in messages: **ExecutionReport**, **OrderMassStatusRequest**

#### **180.2.2781 MassStatusReqType**

Specifies the type or scope of the mass order status request.

Type: **int**

Allowed values in MassStatusReqTypeCodeSet:

Code	Name	Description
1	StatusForOrdersForASecurity	Status for orders for a security
2	StatusForOrdersForAnUnderlyingSecurity	Status for orders for an underlying security
3	StatusForOrdersForAProduct	Status for orders for a product
4	StatusForOrdersForACFICode	Status for orders for a CFI Code
5	StatusForOrdersForASecurityType	Status for orders for a security type
6	StatusForOrdersForATradingSession	Status for orders for a trading session
7	StatusForAllOrders	Status for all orders
8	StatusForOrdersForAPartyID	Status for orders for a party identifier
9	StatusForSecurityIssuer	Status for orders for an issuer
10	StatusForIssuerOfUnderlyingSecurity	Status for orders for an issuer of underlying security

Used in messages: **OrderMassStatusRequest**

#### **180.2.2782 MasterConfirmationAnnexDate**

The date that an annex to the master confirmation was executed between the parties.

Type: **LocalMktDate**

Used in components: **FinancingDetails**

#### **180.2.2783 MasterConfirmationAnnexDesc**

The type of master confirmation annex executed between the parties.

See <http://www.fpml.org/coding-scheme/master-confirmation-annex-type> for values.

Type: **String**

Used in components: **FinancingDetails**

**180.2.2784 MasterConfirmationDate**

Alternative to broker confirmation. The date of the confirmation executed between the parties and intended to govern all relevant transactions between those parties.

Type: **LocalMktDate**

Used in components: **FinancingDetails**

**180.2.2785 MasterConfirmationDesc**

The type of master confirmation executed between the parties.

See <http://www.fpml.org/coding-scheme/master-confirmation-type> for values.

Type: **String**

Used in components: **FinancingDetails**

**180.2.2786 MatchAlgorithm**

The types of algorithm used to match orders in a specific security. Possible value types are FIFO, Allocation, Pro-rata, Lead Market Maker, Currency Calendar.

Type: **String**

Used in groups: **MatchRules**

**180.2.2787 MatchAttribTagID**

Existing FIX field to be applied as a matching criteria to the instruction, bilaterally agreed between parties.

Type: **TagNum**

Used in groups: **MatchingInstructions**

**180.2.2788 MatchAttribValue**

Value of MatchAttribTagID(1626) on which to apply the matching instruction.

Type: **String**

Used in groups: **MatchingInstructions**

**180.2.2789 MatchExceptionAllocValue**

The allocating party's data value used in the match operation.

Type: **String**

Used in groups: **MatchExceptionGrp**

**180.2.2790 MatchExceptionConfirmValue**

The confirming party's data value used in the match operation.

Type: **String**

Used in groups: **MatchExceptionGrp**

**180.2.2791 MatchExceptionElementName**

The matching exception data point name, for example: "Trade currency". This may be used for display purposes, providing a corresponding description for the value in MatchExceptionElementType(2774).

Type: **String**

Used in groups: **MatchExceptionGrp**

**180.2.2792 MatchExceptionElementType**

Identifies the data point used in the matching operation which resulted in an exception.

Type: **int**

Allowed values in MatchExceptionElementTypeCodeSet:

---

Code	Name	Description
1	AccruedInterest	Accrued interest
2	DealPrice	Deal price
3	TradeDate	Trade date. Tolerance not applicable
4	SettlementDate	Settlement date. Tolerance not applicable
5	SideIndicator	Side indicator. Tolerance not applicable
6	TradedCurrency	Traded currency. Tolerance not applicable
7	AccountID	Account ID. Tolerance not applicable

---

Code	Name	Description
8	ExecutingBrokerID	Executing broker ID. Tolerance not applicable
9	SettlementCurrencyAndAmount	Settlement currency and amount
10	InvestmentManagerID	Investment manager ID. Tolerance not applicable
11	NetAmount	Net amount
12	PlaceOfSettlement	Place of settlement. Tolerance not applicable
13	Commissions	Commissions
14	SecurityIdentifier	Security identifier. Tolerance not applicable
15	QualityAllocated	Quantity allocated
16	Principal	Principal
17	Fees	Fees
18	Tax	Tax

Used in groups: **MatchExceptionGrp**

### 180.2.2793 MatchExceptionGrp

The MatchExceptionGrp component details the matching exceptions and variances identified during the matching process based on the defined matching criteria and tolerances.

Name	Mult.	Type	Description
NoMatchExceptions	[1..1]	NumInGroup	
MatchExceptionType	[0..1]	CodeSet	Required if NoMatchExceptions(2772) > 0.
MatchExceptionElementType	[0..1]	CodeSet	Required if NoMatchExceptions(2772) > 0.
MatchExceptionElementName	[0..1]	String	
MatchExceptionAllocValue	[0..1]	String	
MatchExceptionConfirmValue	[0..1]	String	
MatchExceptionToleranceValue	[0..1]	float	
MatchExceptionToleranceValueType	[0..1]	CodeSet	
MatchExceptionText	[0..1]	String	
EncodedMatchExceptionTextLen	[0..1]	Length	Must be set if EncodedMatchExceptionText(2780) field is specified and must immediately precede it.



Name	Mult.	Type	Description
EncodedMatchExceptionText	[0..1]	data	Encoded (non-ASCII characters) representation of the MatchExceptionText(2780) field in the encoded format specified via the MessageEncoding(347) field.

Used in messages: [Confirmation](#), [ConfirmationAck](#)

#### **180.2.2794 MatchExceptionText**

Description of the exception.

Type: [String](#)

Used in groups: [MatchExceptionGrp](#)

#### **180.2.2795 MatchExceptionToleranceValue**

The data element's tolerance value. Omitted if no tolerance is allowed or not applicable.

Type: [float](#)

Used in groups: [MatchExceptionGrp](#)

#### **180.2.2796 MatchExceptionToleranceValueType**

The type of value in MatchExceptionToleranceValue(2778). Omitted if no tolerance is allowed or not applicable.

Type: [int](#)

Allowed values in MatchExceptionToleranceValueTypeCodeSet:

Code	Name	Description
1	FixedAmount	Fixed amount. Default if not specified
2	Percentage	Percentage

Used in groups: [MatchExceptionGrp](#)

**180.2.2797 MatchExceptionType**

Type of matching exception.

Type: **int**

Allowed values in MatchExceptionTypeCodeSet:

Code	Name	Description
0	NoMatchingConfirmation	No matching confirmation
1	NoMatchingAllocation	No matching allocation
2	AllocationDataElementMissing	Allocation data element missing
3	ConfirmationDataElementMissing	Confirmation data element missing
4	DataDifferenceNotWithinTolerance	Data difference not within tolerance
5	MatchWithinTolerance	Match within tolerance
99	Other	Other

Used in groups: **MatchExceptionGrp**

**180.2.2798 MatchIncrement**

Allows orders to specify a minimum quantity that applies to every execution (one execution could be for multiple counter-orders). The order may still fill against smaller orders, but the cumulative quantity of the execution must be in multiples of the MatchIncrement.

Type: **Qty**

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.2799 MatchingDataPointGrp**

The MatchingDataPointGrp component details all the trade attributes and tolerances used for trade matching.

Name	Mult.	Type	Description
<b>NoMatchingDataPoints</b>	[1..1]	NumInGroup	

Name	Mult.	Type	Description
MatchingDataPointIndicator	[0..1]	CodeSet	Required if NoMatchingDataPoints(2781) > 0.
MatchingDataPointValue	[0..1]	String	Required if NoMatchingDataPoints(2781) > 0.
MatchingDataPointType	[0..1]	CodeSet	Required if NoMatchingDataPoints(2781) > 0.
MatchingDataPointName	[0..1]	String	

Used in messages: [Confirmation](#), [ConfirmationAck](#)

#### 180.2.2800 MatchingDataPointIndicator

Data point's matching type.

Type: [int](#)

Allowed values in MatchingDataPointIndicatorCodeSet:

Code	Name	Description
1	Mandatory	Mandatory
2	Optional	Optional

Used in groups: [MatchingDataPointGrp](#)

#### 180.2.2801 MatchingDataPointName

The matching data point name, for example: "Trade currency". This may be used for display purposes, providing a corresponding description for the value in MatchingDataPointType(2784).

Type: [String](#)

Used in groups: [MatchingDataPointGrp](#)

#### 180.2.2802 MatchingDataPointType

Identifies the data point used in the matching operation.

Type: [int](#)

Allowed values in MatchExceptionElementTypeCodeSet:

Code	Name	Description
1	AccruedInterest	Accrued interest
2	DealPrice	Deal price
3	TradeDate	Trade date. Tolerance not applicable
4	SettlementDate	Settlement date. Tolerance not applicable
5	SideIndicator	Side indicator. Tolerance not applicable
6	TradedCurrency	Traded currency. Tolerance not applicable
7	AccountID	Account ID. Tolerance not applicable
8	ExecutingBrokerID	Executing broker ID. Tolerance not applicable
9	SettlementCurrencyAndAmount	Settlement currency and amount
10	InvestmentManagerID	Investment manager ID. Tolerance not applicable
11	NetAmount	Net amount
12	PlaceOfSettlement	Place of settlement. Tolerance not applicable
13	Commissions	Commissions
14	SecurityIdentifier	Security identifier. Tolerance not applicable
15	QualityAllocated	Quantity allocated
16	Principal	Principal
17	Fees	Fees
18	Tax	Tax

Used in groups: **MatchingDataPointGrp**

### 180.2.2803 MatchingDataPointValue

Value of the matching data point.

Type: **String**

Used in groups: **MatchingDataPointGrp**

### 180.2.2804 MatchingInstructions

Name	Mult.	Type	Description
NoMatchInst	[1..1]	NumInGroup	
MatchInst	[0..1]	CodeSet	Required if NoMatchInst > 0.

Name	Mult.	Type	Description
MatchInstMarketID	[0..1]	Exchange	
MatchAttribTagID	[0..1]	TagNum	Required if NoMatchInst > 0.
MatchAttribValue	[0..1]	String	Required if NoMatchInst > 0.

Used in components: [TradeReportOrderDetail](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.2805 MatchInst

Matching Instruction for the order.

Type: [int](#)

Allowed values in MatchInstCodeSet:

Code	Name	Description
1	Match	Match
2	DoNotMatch	Do Not Match

Used in groups: [MatchingInstructions](#)

### 180.2.2806 MatchInstMarketID

Identifies the market to which the matching instruction applies.

Type: [Exchange](#)

Used in groups: [MatchingInstructions](#)

### 180.2.2807 MatchRuleProductComplex

Identifies an entire suite of products for which the matching rule applies.

Type: [String](#)

Used in groups: [MatchRules](#)

### 180.2.2808 MatchRules

The MatchRules component is used to specify the details of order matching rules for specified product group or complex.

Name	Mult.	Type	Description
NoMatchRules	[1..1]	NumInGroup	
MatchAlgorithm	[0..1]	String	Required if NoMatchRules(1235) > 0.
MatchType	[0..1]	CodeSet	
MatchRuleProductComplex	[0..1]	String	Can be used to limit match rule to specific product suite.
CustomerPriority	[0..1]	CodeSet	Can be used to give customer orders priority for the given matching algorithm.

Used in components: [TradingSessionRules](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

### 180.2.2809 MatchStatus

The status of this trade with respect to matching or comparison.

Type: [char](#)

Allowed values in MatchStatusCodeSet:

Code	Name	Description
0	Compared	Compared, matched or affirmed
1	Uncompared	Uncompared, unmatched, or unaffirmed
2	AdvisoryOrAlert	Advisory or alert
3	Mismatched	Mismatched. Indicates that data points from the AllocationInstruction(35=J) and Confirmation(35=AK) are matched but there are variances. MatchExceptionGrp component may be used to detail on the mis-matched data fields.

Used in groups: [AllocGrp](#)

Used in messages: [AllocationInstructionAck](#), [AllocationReportAck](#), [Confirmation](#), [ConfirmationAck](#), [PositionReport](#), [RequestForPositions](#), [RequestForPositionsAck](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#)

**180.2.2810 MatchType**

The point in the matching process at which this trade was matched.

Type: **String**

Allowed values in MatchTypeCodeSet:

Code	Name	Description
A1	ExactMatchPlus4BadgesExecTime	Exact match on Trade Date, Stock Symbol, Quantity, Price, Trade Type, and Special Trade Indicator plus four badges and execution time (within two-minute window)
A2	ExactMatchPlus4Badges	Exact match on Trade Date, Stock Symbol, Quantity, Price, Trade Type, and Special Trade Indicator, plus four badges
A3	ExactMatchPlus2BadgesExecTime	Exact match on Trade Date, Stock Symbol, Quantity, Price, Trade Type, and Special Trade Indicator, plus two badges and execution time (within two-minute window)
M3	ACTAcceptedTrade	ACT Accepted Trade
A4	ExactMatchPlus2Badges	Exact match on Trade Date, Stock Symbol, Quantity, Price, Trade Type, and Special Trade Indicator, plus two badges
M4	ACTDefaultTrade	ACT Default Trade
A5	ExactMatchPlusExecTime	Exact match on Trade Date, Stock Symbol, Quantity, Price, TradeType, and Special Trade Indicator plus execution time (within two-minute window)
M5	ACTDefaultAfterM2	ACT Default After M2
AQ	StampedAdvisoriesOrSpecialistAccepts	Compared records resulting from stamped advisories or specialist accepts/pair-offs
M6	ACTM6Match	ACT M6 Match
S1	A1ExactMatchSummarizedQuantity	Summarized match using A1 exact match criteria except quantity is summarized
S2	A2ExactMatchSummarizedQuantity	Summarized match using A2 exact match criteria except quantity is summarized
S3	A3ExactMatchSummarizedQuantity	Summarized match using A3 exact match criteria except quantity is summarized
S4	A4ExactMatchSummarizedQuantity	Summarized match using A4 exact match criteria except quantity is summarized
S5	A5ExactMatchSummarizedQuantity	Summarized match using A5 exact match criteria except quantity is summarized
M1	ExactMatchMinusBadgesTimes	Exact match on Trade Date, Stock Symbol, Quantity, Price, Trade Type, and Special Trade Indicator minus badges And times: ACT M1 match

Code	Name	Description
M2	SummarizedMatchMinusBadges-Times	Summarized match minus badges and times: ACT M2 Match
MT	OCSLockedIn	OCS Locked In: Non-ACT
1	OnePartyTradeReport	One-Party Trade Report (privately negotiated trade)
2	TwoPartyTradeReport	Two-Party Trade Report (privately negotiated trade)
3	ConfirmedTradeReport	Confirmed Trade Report (reporting from recognized markets)
4	AutoMatch	Auto-match
5	CrossAuction	Cross Auction
6	CounterOrderSelection	Counter-Order Selection
7	CallAuction	Call Auction
8	Issuing	Issuing/Buy Back Auction
9	SystematicInternaliser	Systematic Internaliser (SI)
10	AutoMatchLastLook	Auto-match with last look. Execution that arises from a match against orders or quotes which require a confirmation during continuous trading.
11	CrossAuctionLastLook	Cross auction with last look. Execution that arises from a match against orders or quotes which require a confirmation during an auction.

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [MatchRules](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#), [ExecutionReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeMatchReport](#)

#### **180.2.2811 MaterialDividendsIndicator**

Indicates whether material non-cash dividends are applicable.

Type: [Boolean](#)

Used in components: [DividendConditions](#)

#### **180.2.2812 MaturityDate**

Date of maturity.

Type: [LocalMktDate](#)

Used in components: [Instrument](#)



**180.2.2813 MaturityFrequencyPeriod**

Time unit multiplier for the minimum frequency of the instrument maturity intervals.

Type: **int**

Used in components: **Instrument**

**180.2.2814 MaturityFrequencyUnit**

Time unit associated with the minimum frequency of the instrument maturity intervals.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in components: **Instrument**

**180.2.2815 MaturityMonthYear**

Can be used with standardized derivatives vs. the MaturityDate (541) field. Month and Year of the maturity (used for standardized futures and options).

Format:

YYYYMM (e.g. 199903)

YYYYMMDD (e.g. 20030323)

YYYYMMwN (e.g. 200303w) for week

A specific date or can be appended to the MaturityMonthYear. For instance, if multiple standard products exist that mature in the same Year and Month, but actually mature at a different time, a value can be appended, such as "w" or "w2" to indicate week as opposed to week 2 expiration. Likewise, the date (0-3) can be appended to indicate a specific expiration (maturity date).

Type: **MonthYear**

Used in components: **Instrument**

### **180.2.2816 MaturityMonthYearFormat**

Format used to generate the MaturityMonthYear for each option

Type: **int**

Allowed values in MaturityMonthYearFormatCodeSet:

Code	Name	Description
0	YearMonthOnly	YearMonth Only (default)
1	YearMonthDay	YearMonthDay
2	YearMonthWeek	YearMonthWeek

Used in groups: **MaturityRules**

### **180.2.2817 MaturityMonthYearIncrement**

Increment between successive maturities for an option class

Type: **int**

Used in groups: **MaturityRules**

### **180.2.2818 MaturityMonthYearIncrementUnits**

Unit of measure for the Maturity Month Year Increment

Type: **int**

Allowed values in MaturityMonthYearIncrementUnitsCodeSet:

Code	Name	Description
0	Months	Months
1	Days	Days
2	Weeks	Weeks
3	Years	Years

Used in groups: **MaturityRules**

### 180.2.2819 MaturityNetMoney

Net Money at maturity if Zero Coupon and maturity value is different from par value

Type: **Amt**

Used in messages: **Confirmation**

### 180.2.2820 MaturityRuleID

Allows maturity rule to be referenced via an identifier so that rules do not need to be explicitly enumerated

Type: **String**

Used in groups: **MaturityRules**

### 180.2.2821 MaturityRules

Name	Mult.	Type	Description
<b>NoMaturityRules</b>	[1..1]	NumInGroup	Number of maturity rule entries. This block specifies the rules for determining how new strikes should be listed within the stated price range of the underlying instrument
<b>MaturityRuleID</b>	[0..1]	String	Allows maturity rule to be referenced via an identifier so that rules do not need to be explicitly enumerated
<b>MaturityMonthYearFormat</b>	[0..1]	CodeSet	Format used to generate the MMY for each option contract:
<b>MaturityMonthYearIncrementUnits</b>	[0..1]	CodeSet	enumeration specifying the increment unit:

Name	Mult.	Type	Description
StartMaturityMonthYear	[0..1]	MonthYear	Starting maturity for the range to which the StrikeIncrement applies. Price refers to the price of the underlying
EndMaturityMonthYear	[0..1]	MonthYear	Ending maturity month year to which the StrikeIncrement applies. Price refers to the price of the underlying.
MaturityMonthYearIncrement	[0..1]	int	Value by which maturity month year should be incremented within the specified price range.

Used in groups: **StrikeRules**

### **180.2.2822 MaturityTime**

Time of security's maturity expressed in local time with offset to UTC specified

Type: **TZTimeOnly**

Used in components: **Instrument**

### **180.2.2823 MaxFloor**

The quantity to be displayed . Required for reserve orders. On orders specifies the qty to be displayed, on execution reports the currently displayed quantity.

Type: **Qty**

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

### **180.2.2824 MaximumPriceDeviation**

Maximum deviation, in percentage terms, of an execution price from a reference price, e.g. the initial price of a match event.

Type: **Percentage**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.2825 MaxMessageSize**

Maximum number of bytes supported for a single message.

Type: **Length**

Used in messages: **Logon**

**180.2.2826 MaxPriceLevels**

Allows an order to specify a maximum number of price levels to trade through. Only valid for aggressive orders and during continuous (autoexecution) trading sessions. Property lost when order is put on book. A partially filled order is assigned last trade price as limit price. Non-filled order behaves as ordinary Market or Limit.

Type: **int**

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest, ExecutionReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest**

**180.2.2827 MaxPriceVariation**

The maximum price variation of an execution from one event to the next for a given security. Expressed in absolute price terms.

Type: **float**

Used in components: **BaseTradingRules**

Used in groups: **MDFullGrp, MDIncGrp**

**180.2.2828 MaxShow**

Maximum quantity (e.g. number of shares) within an order to be shown to other customers (i.e. sent via an IOI).

(Prior to FIX 4.2 this field was of type int)

Type: **Qty**

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest, ExecutionReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest**

**180.2.2829 MaxTradeVol**

The maximum order quantity (as expressed by TradeVolType(1786)) that can be submitted for a security.

Type: Qty

Used in components: BaseTradingRules

**180.2.2830 MDBookType**

Describes the type of book for which the feed is intended. Used when multiple feeds are provided over the same connection

Type: int

Allowed values in MDBookTypeCodeSet:

Code	Name	Description
1	TopOfBook	Top of Book
2	PriceDepth	Price Depth
3	OrderDepth	Order Depth

Used in groups: MarketDataFeedTypes

Used in messages: MarketDataIncrementalRefresh, MarketDataSnapshotFullRefresh, SecurityMassStatus, SecurityStatus

**180.2.2831 MDEntryBuyer**

Buying party in a trade

Type: String

Used in groups: MDFullGrp, MDIncGrp

**180.2.2832 MDEntryDate**

Date of Market Data Entry.

(prior to FIX 4.4 field was of type UTCDate)

Type: **UTCDateOnly**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.2833 MDEntryForwardPoints**

Used for an F/X entry. The forward points to be added to or subtracted from the spot rate to get the "all-in" rate in MDEntryPx. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199

Type: **PriceOffset**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.2834 MDEntryID**

Unique Market Data Entry identifier.

Type: **String**

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **ExecutionReport**

#### **180.2.2835 MDEntryOriginator**

Originator of a Market Data Entry

Type: **String**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.2836 MDEntryPositionNo**

Display position of a bid or offer, numbered from most competitive to least competitive, per market side, beginning with 1.

Type: **int**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.2837 MDEntryPx**

Price of the Market Data Entry.

Type: **Price**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.2838 MDEntryRefID**

Refers to a previous MDEntryID (278).

Type: **String**

Used in groups: **MDIncGrp**

#### **180.2.2839 MDEntrySeller**

Selling party in a trade

Type: **String**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.2840 MDEntrySize**

Quantity or volume represented by the Market Data Entry.

Type: **Qty**

Used in groups: **InstrmtMDReqGrp**, **MDFullGrp**, **MDIncGrp**, **StrmAsgnReqInstrmtGrp**

#### **180.2.2841 MDEntrySpotRate**

The spot rate for an FX entry

Type: **float**

Used in groups: **MDFullGrp**, **MDIncGrp**



**180.2.2842 MDEntryTime**

Time of Market Data Entry.

Type: **UTCTimeOnly**

Used in groups: **MDFullGrp**, **MDIncGrp**

**180.2.2843 MDEntryType**

Type of market data entry.

Type: **char**

Allowed values in MDEntryTypeCodeSet:

Code	Name	Description
0	Bid	Bid
1	Offer	Offer
2	Trade	Trade
3	IndexValue	Index value. A reference stock index (e.g. DJIA) or benchmark rate (e.g. LIBOR).
4	OpeningPrice	Opening price
5	ClosingPrice	Closing price
6	SettlementPrice	Settlement price
7	TradingSessionHighPrice	Trading session high price
8	TradingSessionLowPrice	Trading session low price
9	VWAP	Volume Weighted Average Price. VWAP
A	Imbalance	Imbalance
B	TradeVolume	Trade volume
C	OpenInterest	Open interest
D	CompositeUnderlyingPrice	Composite underlying price
E	SimulatedSellPrice	Simulated sell price
F	SimulatedBuyPrice	Simulated buy price
G	MarginRate	Margin rate
H	MidPrice	Mid-price
J	EmptyBook	Empty book
K	SettleHighPrice	Settle high price
L	SettleLowPrice	Settle low price

Code	Name	Description
M	PriorSettlePrice	Prior settle price
N	SessionHighBid	Session high bid
O	SessionLowOffer	Session low offer
P	EarlyPrices	Early prices
Q	AuctionClearingPrice	Auction clearing price
S	SwapValueFactor	Swap Value Factor (SVF) for swaps cleared through a central counterparty (CCP)
R	DailyValueAdjustmentForLongPositions	Daily value adjustment for long positions
T	CumulativeValueAdjustmentForLongPositions	Cumulative value adjustment for long positions
U	DailyValueAdjustmentForShortPositions	Daily value adjustment for short positions
V	CumulativeValueAdjustmentForShortPositions	Cumulative value adjustment for short positions
W	FixingPrice	Fixing price
X	CashRate	Cash rate
Y	RecoveryRate	Recovery rate
Z	RecoveryRateForLong	Recovery rate for long positions
a	RecoveryRateForShort	Recovery rate for short positions
b	MarketBid	Market bid
c	MarketOffer	Market offer
d	ShortSaleMinPrice	Short sale minimum price
e	PreviousClosingPrice	Previous closing price
g	ThresholdLimitPriceBanding	Threshold limits and price banding. Conveys incremental real time change to pre-configured or previously disseminated pricing thresholds and/or banding parameters.
h	DailyFinancingValue	Daily financing value. The financing cost of rolling an analogous total return swap from the previous business day to the current business day. In the context of Adjusted Interest Rate (AIR) futures this is a component of the cleared futures price.
i	AccruedFinancingValue	Accrued financing value. The total of the daily funding values or amounts from a contract's first day of trading to the current day. In the context of Adjusted Interest Rate (AIR) futures this is a component of the cleared futures price.
t	TWAP	Time Weighted Average Price. TWAP

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [MDReqGrp](#)

### 180.2.2844 MDFeedType

Describes a class of service for a given data feed, ie Regular and Market Maker, Bandwidth Intensive or Bandwidth Conservative

Type: [String](#)

Used in components: [MDStatisticParameters](#)

Used in groups: [MarketDataFeedTypes](#)

Used in messages: [MarketDataIncrementalRefresh](#), [MarketDataSnapshotFullRefresh](#)

### 180.2.2845 MDFullGrp

Name	Mult.	Type	Description
<a href="#">NoMDEntries</a>	[1..1]	NumInGroup	Number of entries following.
<a href="#">MDEntryType</a>	[1..1]	CodeSet	Required if NoMDEntries(268) > 0.
<a href="#">MDEntryID</a>	[0..1]	String	Conditionally required when maintaining an order-depth book (AggregatedBook(266) is "N"). Allows subsequent Incremental changes to be applied using MDEntryID(278).
<a href="#">MDEntryPx</a>	[0..1]	Price	Conditionally required if MDEntryType(269) is not A (Imbalance), B (Trade Volume), or C (Open Interest); Conditionally required when MDEntryType(269) = Q (Auction clearing price).
<a href="#">PriceType</a>	[0..1]	CodeSet	
<a href="#">PriceQualifierGrp</a>	[0..*]	Group	
<a href="#">AvgPxIndicator</a>	[0..1]	CodeSet	
<a href="#">YieldData</a>	[0..1]	Component	
<a href="#">SpreadOrBenchmarkCurveData</a>	[0..1]	Component	
<a href="#">OrdType</a>	[0..1]	CodeSet	Used to support market mechanism type; limit order, market order, committed principal order
<a href="#">Currency</a>	[0..1]	Currency	Can be used to specify the currency of the quoted price.
<a href="#">CurrencyCodeSource</a>	[0..1]	CodeSet	
<a href="#">SettlCurrency</a>	[0..1]	Currency	Required for NDFs to specify the settlement currency (fixing currency).

Name	Mult.	Type	Description
SettlCurrencyCodeSource	[0..1]	CodeSet	
RateSource	[0..*]	Group	
MDEntrySize	[0..1]	Qty	Conditionally required when MDUpdateAction(279) = 0 (New) and MDEntryType(269) = 0 (Bid), 1 (Offer), 2 (Trade), B (Trade volume), or C (Open interest).
SecSizesGrp	[0..*]	Group	
LotType	[0..1]	CodeSet	Can be used to specify the lot type of the quoted size in order depth books.
MDEntryDate	[0..1]	UTCDateOnly	
MDEntryTime	[0..1]	UTCTimeOnly	
TickDirection	[0..1]	CodeSet	
MDMkt	[0..1]	Exchange	Market posting quote / trade. Valid values: See Volume 6: Appendix 6-C
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
SecurityTradingStatus	[0..1]	CodeSet	
HaltReason	[0..1]	CodeSet	
FastMarketIndicator	[0..1]	Boolean	
MarketCondition	[0..1]	CodeSet	
QuoteCondition	[0..1]	CodeSet	Space-delimited list of conditions describing a quote.
TradeCondition	[0..1]	CodeSet	Space-delimited list of conditions describing a trade
TradePriceConditionGrp	[0..*]	Group	
AnonymousTradeIndicator	[0..1]	Boolean	
AlgorithmicTradeIndicator	[0..1]	CodeSet	
MDEntryOriginator	[0..1]	String	
LocationID	[0..1]	String	
DeskID	[0..1]	String	
OpenCloseSettlFlag	[0..1]	CodeSet	Used if MDEntryType(269) = 4 (Opening price), 5 (Closing price), or 6 (Settlement price).
TimeInForce	[0..1]	CodeSet	For optional use when this Bid or Offer represents an order
ExpireDate	[0..1]	LocalMktDate	For optional use when this Bid or Offer represents an order. ExpireDate(432) and ExpireTime(126) cannot both be specified in one Market Data Entry.

Name	Mult.	Type	Description
ExpireTime	[0..1]	UTCTimestamp	For optional use when this Bid or Offer represents an order. ExpireDate(432) and ExpireTime(126) cannot both be specified in one Market Data Entry.
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59) = A (Good for Time).
ExposureDurationUnit	[0..1]	CodeSet	
MinQty	[0..1]	Qty	For optional use when this Bid or Offer represents an order
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited.
SellerDays	[0..1]	int	
OrderID	[0..1]	String	For optional use when this Bid, Offer, or Trade represents an order
SecondaryOrderID	[0..1]	String	For optional use to support Hit/Take (selecting a specific order from the feed) without disclosing a private order id.
QuoteEntryID	[0..1]	String	For optional use when this Bid, Offer, or Trade represents a quote
TradeID	[0..1]	String	For optional use in reporting Trades.
StrategyLinkID	[0..1]	String	For optional use in reporting Trades. May be used to link together trades that are reported separately but are part of the same overall trade, e.g. spread trade and their constituent trades.
MDEntryBuyer	[0..1]	String	For optional use in reporting Trades
MDEntrySeller	[0..1]	String	For optional use in reporting Trades
NumberOfBuyOrders	[0..1]	int	For optional use in reporting trades.
NumberOfSellOrders	[0..1]	int	For optional use in reporting trades.
NumberOfOrders	[0..1]	int	In an Aggregated Book, used to show how many individual orders make up an MDEntry
MDEntryPositionNo	[0..1]	int	
Scope	[0..1]	CodeSet	
PriceDelta	[0..1]	float	
TrdType	[0..1]	CodeSet	Specifies trade type when a trade is being reported. For optional use in reporting trades.
TrdSubType	[0..1]	CodeSet	For optional use in reporting trades.
SecondaryTrdType	[0..1]	CodeSet	For optional use in reporting trades. Conditionally requires presence of TrdType(828).

Name	Mult.	Type	Description
TertiaryTrdType	[0..1]	CodeSet	For optional use in reporting trades. Conditionally requires presence of SecondaryTrdType(855).
TradeTypeGrp	[0..*]	Group	For optional use in reporting trades as alternative to the use of individual fields.
RegulatoryReportType	[0..1]	CodeSet	Used only when reporting a trade (MDEntryType(269)=2 (Trade)) that is a regulatory trade report.
MultiJurisdictionReportingIndicator	[0..1]	CodeSet	For optional use in reporting trades.
ExecMethod	[0..1]	CodeSet	
MatchType	[0..1]	CodeSet	For optional use in reporting trades.
OrderCategory	[0..1]	CodeSet	
TradePublishIndicator	[0..1]	CodeSet	For optional use in reporting trades.
TrdRegPublicationGrp	[0..*]	Group	
IntraFirmTradeIndicator	[0..1]	Boolean	
PreviouslyReported	[0..1]	CodeSet	
RelatedTradeGrp	[0..*]	Group	For optional use when reporting trades. Lists trades related to the current market data entry, e.g. leg trades of a multi-leg trade.
Text	[0..1]	String	Text to describe the Market Data Entry. Part of repeating group.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
MDPriceLevel	[0..1]	int	
OrderCapacity	[0..1]	CodeSet	
MDOriOriginType	[0..1]	CodeSet	
HighPx	[0..1]	Price	Used to report high price in association with trade, bid or ask rather than a separate entity
LowPx	[0..1]	Price	Used to report low price in association with trade, bid or ask rather than a separate entity.
FirstPx	[0..1]	Price	Indicates the first price of a trading session; can be a bid, ask, or trade price.
LastPx	[0..1]	Price	Indicates the last price of a trading session; can be a bid, ask, or trade price.
DiscountFactor	[0..1]	float	

Name	Mult.	Type	Description
TradeVolume	[0..1]	Qty	Used to report trade volume in association with trade, bid or ask rather than a separate entity
PriceLimits	[0..1]	Component	
MaxPriceVariation	[0..1]	float	
SettlPriceType	[0..1]	CodeSet	
SettlPriceDeterminationMethod	[0..1]	CodeSet	
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Indicates date on which instrument will settle. For NDFs required for specifying the "value date".
MDQuoteType	[0..1]	CodeSet	
RptSeq	[0..1]	int	Used to identify the sequence number within a feed type
DealingCapacity	[0..1]	CodeSet	
MDEntrySpotRate	[0..1]	float	
MDEntryForwardPoints	[0..1]	PriceOffset	
Parties	[0..*]	Group	
AggressorTime	[0..1]	UTCTimestamp	
AggressorSide	[0..1]	CodeSet	
LegRefID	[0..1]	String	May be specified for an MDEntryType(269)=2 (Trade) entry to indicate that MDEntryPx(270), PriceType(423) and MDEntrySize(271) apply to the instance of the InstrmtLegGrp component with matching LegID(1788).

Used in messages: [MarketDataSnapshotFullRefresh](#)

### 180.2.2846 MDHaltReason

Denotes the reason for the Opening Delay or Trading Halt.

Type: [int](#)

Allowed values in HaltReasonCodeSet:

Code	Name	Description
0	NewsDissemination	News Dissemination
1	OrderInflux	Order Influx

Code	Name	Description
2	OrderImbalance	Order Imbalance
3	AdditionalInformation	Additional Information
4	NewsPending	News Pending
5	EquipmentChangeover	Equipment Changeover

Used in messages: [MarketDataSnapshotFullRefresh](#)

### 180.2.2847 MDImplicitDelete

Defines how a server handles distribution of a truncated book. Defaults to broker option.

Type: [Boolean](#)

Allowed values in MDImplicitDeleteCodeSet:

Code	Name	Description
N	No	Server must send an explicit delete for bids or offers falling outside the requested MarketDepth of the request
Y	Yes	Client has responsibility for implicitly deleting bids or offers falling outside the MarketDepth of the request

Used in messages: [MarketDataRequest](#)

### 180.2.2848 MDIncGrp

Name	Mult.	Type	Description
<a href="#">NoMDEntries</a>	[1..1]	NumInGroup	Number of entries following.
<a href="#">MDUpdateAction</a>	[1..1]	CodeSet	Required if NoMDEntries(268) > 0.
<a href="#">DeleteReason</a>	[0..1]	CodeSet	If MDUpdateAction = Delete(2), can be used to specify a reason for the deletion.
<a href="#">MDSubBookType</a>	[0..1]	int	Can be used to define a subordinate book.
<a href="#">MarketDepth</a>	[0..1]	int	Can be used to define the current depth of the book.
<a href="#">MDEntryType</a>	[0..1]	CodeSet	Conditionally required if MDUpdateAction(279) = 0 (New). Cannot be changed.



Name	Mult.	Type	Description
MDEntryID	[0..1]	String	If specified, must be unique among currently active entries if MDUpdateAction(279) = 0 (New);. must be the same as a previous MDEntryID(278) if MDUpdateAction(279) = 2 (Delete);. must be the same as a previous MDEntryID(278) if MDUpdateAction(279) = 1 (Change) and MDEntryRefID(280) is not specified; or. must be unique among currently active entries if MDUpdateAction(279) = 1 (Change) and MDEntryRefID(280) is specified.
MDEntryRefID	[0..1]	String	If MDUpdateAction(279) = 0 (New), for the first market data entry in a message, either this field or a security symbol must be specified. If MDUpdateAction(279) = 1 (Change), this must refer to a previous MDEntryID(278).
MStreamID	[0..1]	String	
Instrument	[0..1]	Component	
InstrumentExtension	[0..1]	Component	
FinancingDetails	[0..1]	Component	
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
FinancialStatus	[0..1]	CodeSet	
CorporateAction	[0..1]	CodeSet	
MDEntryPx	[0..1]	Price	Conditionally required when MDUpdateAction(279) = 0 (New) and MDEntryType(269) is not A (Imbalance), B (Trade volume), or C (Open interest). Conditionally required when MDEntryType(269) = Q (Auction clearing price).
PriceType	[0..1]	CodeSet	
PriceQualifierGrp	[0..*]	Group	
AvgPxIndicator	[0..1]	CodeSet	
YieldData	[0..1]	Component	Insert here the set of YieldData (yield-related) fields defined in Common Components of Application Messages
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of SpreadOrBenchmarkCurveData (Fixed Income spread or benchmark curve) fields defined in Common Components of Application Messages

Name	Mult.	Type	Description
OrdType	[0..1]	CodeSet	Used to support market mechanism type; limit order, market order, committed principal order
Currency	[0..1]	Currency	Can be used to specify the currency of the quoted price.
CurrencyCodeSource	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	Required for NDFs to specify the settlement currency (fixing currency).
SettlCurrencyCodeSource	[0..1]	CodeSet	
RateSource	[0..*]	Group	
MDEntrySize	[0..1]	Qty	Conditionally required when MDUpdateAction(279) = 0 (New) and MDEntryType(269) = 0 (Bid), 1 (Offer), 2 (Trade), B (Trade volume), or C (Open interest).
SecSizesGrp	[0..*]	Group	
LotType	[0..1]	CodeSet	Can be used to specify the lot type of the quoted size in order depth books.
MDEntryDate	[0..1]	UTCDateOnly	
MDEntryTime	[0..1]	UTCTimeOnly	
TickDirection	[0..1]	CodeSet	
MDMkt	[0..1]	Exchange	Market posting quote / trade. Valid values: See Volume 6: Appendix 6-C
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
SecurityTradingStatus	[0..1]	CodeSet	
HaltReason	[0..1]	CodeSet	
FastMarketIndicator	[0..1]	Boolean	
MarketCondition	[0..1]	CodeSet	
QuoteCondition	[0..1]	CodeSet	Space-delimited list of conditions describing a quote.
TradeCondition	[0..1]	CodeSet	Space-delimited list of conditions describing a trade
TradePriceConditionGrp	[0..*]	Group	
AnonymousTradeIndicator	[0..1]	Boolean	
AlgorithmicTradeIndicator	[0..1]	CodeSet	
RegulatoryReportType	[0..1]	CodeSet	Used only when reporting a trade (MDEntryType(269)=2 (Trade)) that is a regulatory trade report.

Name	Mult.	Type	Description
MultiJurisdictionReportingIndicator	[0..1]	CodeSet	For optional use in reporting trades.
TrdType	[0..1]	CodeSet	For optional use in reporting trades.
TrdSubType	[0..1]	CodeSet	For optional use in reporting trades.
SecondaryTrdType	[0..1]	CodeSet	For optional use in reporting trades. Conditionally requires presence of TrdType(828).
TertiaryTrdType	[0..1]	CodeSet	For optional use in reporting trades. Conditionally requires presence of SecondaryTrdType(855).
TradeTypeGrp	[0..*]	Group	For optional use in reporting trades as alternative to the use of individual fields.
ExecMethod	[0..1]	CodeSet	
MatchType	[0..1]	CodeSet	For optional use in reporting trades.
OrderCategory	[0..1]	CodeSet	
TradePublishIndicator	[0..1]	CodeSet	For optional use in reporting trades.
TrdRegPublicationGrp	[0..*]	Group	
IntraFirmTradeIndicator	[0..1]	Boolean	
PreviouslyReported	[0..1]	CodeSet	
RelatedTradeGrp	[0..*]	Group	For optional use when reporting trades. List of trades related to the current market data entry, e.g. leg trades of a multi-leg trade.
MDEntryOriginator	[0..1]	String	
LocationID	[0..1]	String	
DeskID	[0..1]	String	
OpenCloseSettlFlag	[0..1]	CodeSet	Used if MDEntryType(269) = 4 (Opening Price), 5 (Closing Price), or 6 (Settlement Price).
TimeInForce	[0..1]	CodeSet	For optional use when this Bid or Offer represents an order
ExpireDate	[0..1]	LocalMktDate	For optional use when this Bid or Offer represents an order. ExpireDate(432) and ExpireTime(126) cannot both be specified in one Market Data Entry.
ExpireTime	[0..1]	UTCTimestamp	For optional use when this Bid or Offer represents an order. ExpireDate(432) and ExpireTime(126) cannot both be specified in one Market Data Entry.
ExposureDuration	[0..1]	int	Conditionally required when TimeInForce(59)= 10 (Good for Time).
ExposureDurationUnit	[0..1]	CodeSet	
MinQty	[0..1]	Qty	For optional use when this Bid or Offer represents an order

Name	Mult.	Type	Description
ExecInst	[0..1]	CodeSet	Can contain multiple instructions, space delimited.
SellerDays	[0..1]	int	
OrderID	[0..1]	String	For optional use when this Bid, Offer, or Trade represents an order
SecondaryOrderID	[0..1]	String	For optional use to support Hit/Take (selecting a specific order from the feed) without disclosing a private order id.
QuoteEntryID	[0..1]	String	For optional use when this Bid, Offer, or Trade represents a quote
TradeID	[0..1]	String	For optional use in reporting Trades
StrategyLinkID	[0..1]	String	For optional use in reporting Trades. May be used to link together trades that are reported separately but are part of the same overall trade, e.g. spread trade and their constituent trades.
MDEntryBuyer	[0..1]	String	For optional use in reporting Trades
MDEntrySeller	[0..1]	String	For optional use in reporting Trades
NumberOfBuyOrders	[0..1]	int	For optional use when reporting trades
NumberOfSellOrders	[0..1]	int	For optional use when reporting trades
NumberOfOrders	[0..1]	int	In an Aggregated Book, used to show how many individual orders make up an MDEntry
MDEntryPositionNo	[0..1]	int	
Scope	[0..1]	CodeSet	
PriceDelta	[0..1]	float	
NetChgPrevDay	[0..1]	PriceOffset	
Text	[0..1]	String	Text to describe the Market Data Entry. Part of repeating group.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText(355) field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text(58) field in the encoded format specified via the MessageEncoding(347) field.
MDPriceLevel	[0..1]	int	
OrderCapacity	[0..1]	CodeSet	
MDOriOriginType	[0..1]	CodeSet	
HighPx	[0..1]	Price	
LowPx	[0..1]	Price	

Name	Mult.	Type	Description
FirstPx	[0..1]	Price	Indicates the first price of a trading session; can be a bid, ask, or a trade price.
LastPx	[0..1]	Price	Indicates the last price of a trading session; can be a bid, ask, or a trade price.
DiscountFactor	[0..1]	float	
TradeVolume	[0..1]	Qty	
PriceLimits	[0..1]	Component	
MaxPriceVariation	[0..1]	float	
SettlPriceType	[0..1]	CodeSet	
SettlPriceDeterminationMethod	[0..1]	CodeSet	
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Indicates date on which instrument will settle. For NDFs required for specifying the "value date".
TransBkdTime	[0..1]	UTCTimestamp	For optional use in reporting Trades. Used to specify the time of trade agreement for privately negotiated trades.
TransactTime	[0..1]	UTCTimestamp	For optional use in reporting Trades. Used to specify the time of matching.
AggressorTime	[0..1]	UTCTimestamp	Entry time of the incoming order that triggered the trade
AggressorSide	[0..1]	CodeSet	
MDQuoteType	[0..1]	CodeSet	
RptSeq	[0..1]	int	Allows sequence number to be specified within a feed type
DealingCapacity	[0..1]	CodeSet	
MDEntrySpotRate	[0..1]	float	
MDEntryForwardPoints	[0..1]	PriceOffset	
StatsIndGrp	[0..*]	Group	
Parties	[0..*]	Group	

Used in messages: **MarketDataIncrementalRefresh**

### 180.2.2849 MDMkt

Market posting quote / trade.

Valid values:

See "Appendix 6-C"

Type: **Exchange**

Used in groups: **MDFullGrp**, **MDIncGrp**

### **180.2.2850 MDOriOriginDesc**

Description of the origin of the market data.

Type: **String**

Used in groups: **TestScenarioGrp**

### **180.2.2851 MDOriOriginTime**

Date and time of the market data.

Type: **UTCTimestamp**

Used in groups: **TestScenarioGrp**

### **180.2.2852 MDOriOriginType**

Used to describe the origin of the market data entry.

Type: **int**

Allowed values in MDOriOriginTypeCodeSet:

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
0	Book	Book
1	OffBook	Off-Book
2	Cross	Cross
3	QuoteDrivenMarket	Quote driven market. Examples for quote driven markets are market maker or specialist market models.
4	DarkOrderBook	Dark order book
5	AuctionDrivenMarket	Auction driven market. Markets where matching occurs only in scheduled auctions.
6	QuoteNegotiation	Quote negotiation. Discretionary quoting on request or "request for quote" market.

---

Code	Name	Description
7	VoiceNegotiation	Voice negotiation. A trading system where transactions between members are arranged through voice negotiation.
8	HybridMarket	Hybrid market. A hybrid system falling into two or more types of trading systems. In the context of ESMA reporting, this is for "Hybrid system." In the context of FCA reporting, this is for "Any other, including hybrid."
9	OtherMarket	Other market. A market that does not fall under any of the market types defined for MDOriOriginType(1024). In the context of ESMA reporting, this is for "Any other, excluding hybrid."

Used in components: [MDStatisticParameters](#)

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [TestScenarioGrp](#)

#### 180.2.2853 MDPriceLevel

Integer to convey the level of a bid or offer at a given price level. This is in contrast to MDEntryPositionNo(290) which is used to convey the position of an order within a price level.

Type: [int](#)

Used in groups: [MDFullGrp](#), [MDIncGrp](#)

#### 180.2.2854 MDQuoteType

Identifies market data quote type.

Type: [int](#)

Allowed values in QuoteTypeCodeSet:

Code	Name	Description
0	Indicative	Indicative
1	Tradeable	Tradeable
2	RestrictedTradeable	Restricted tradeable
3	Counter	Counter (tradeable)
4	InitiallyTradeable	Initially tradeable

Used in groups: [MDFullGrp](#), [MDIncGrp](#)

Used in messages: [MarketDataRequest](#)

#### **180.2.2855 MDRecoveryTimeInterval**

Specifies the time interval between two repetitions of the same market data for cyclic recovery feeds.

Type: [int](#)

Used in groups: [MarketDataFeedTypes](#)

#### **180.2.2856 MDRecoveryTimeIntervalUnit**

The time unit associated with the time interval between two cycles of the same market data in cyclic data recovery feeds.

Type: [int](#)

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in groups: [MarketDataFeedTypes](#)

#### **180.2.2857 MDReportCount**

Number of reference and market data messages in-between two MarketDataReport(35=DR) messages.



Type: **int**

Used in messages: **MarketDataReport**

### **180.2.2858 MDReportEvent**

Technical event within market data feed.

Type: **int**

Allowed values in MDReportEventCodeSet:

Code	Name	Description
1	StartInstrumentRefData	Start of instrument reference data.
2	EndInstrumentRefData	End of instrument reference data.
3	StartOffMarketTrades	Start of off-market trades.
4	EndOffMarketTrades	End of off-market trades.
5	StartOrderBookTrades	Start of order book trades.
6	EndOrderBookTrades	End of order book trades.
7	StartOpenInterest	Start of open interest.
8	EndOpenInterest	End of open interest.
9	StartSettlementPrices	Start of settlement prices.
10	EndSettlementPrices	End of settlement prices.
11	StartStatsRefData	Start of statistics reference data.
12	EndStatsRefData	End of statistics reference data.
13	StartStatistics	Start of statistics.
14	EndStatistics	End of statistics.

Used in messages: **MarketDataReport**

### **180.2.2859 MDReportID**

Unique identifier for the Market Data Report.

Type: **int**

Used in messages: **MarketDataReport**, **MarketDataSnapshotFullRefresh**

**180.2.2860 MDReqGrp**

Name	Mult.	Type	Description
NoMDEntryTypes	[1..1]	NumInGroup	Number of MDEntryType fields requested.
MDEntryType	[1..1]	CodeSet	Must be the first field in this repeating group. This is a list of all the types of Market Data Entries that the firm requesting the Market Data is interested in receiving.

Used in messages: [MarketDataRequest](#)

**180.2.2861 MDReqID**

Unique identifier for Market Data Request

Type: [String](#)

Used in messages: [MarketDataIncrementalRefresh](#), [MarketDataRequest](#), [MarketDataRequestReject](#), [MarketDataSnapshotFullRefresh](#)

**180.2.2862 MDReqRejReason**

Reason for the rejection of a Market Data request.

Type: [char](#)

Allowed values in MDReqRejReasonCodeSet:

Code	Name	Description
0	UnknownSymbol	Unknown symbol
1	DuplicateMDReqID	Duplicate MDReqID
2	InsufficientBandwidth	Insufficient Bandwidth
3	InsufficientPermissions	Insufficient Permissions
4	UnsupportedSubscriptionRequestType	Unsupported SubscriptionRequestType
5	UnsupportedMarketDepth	Unsupported MarketDepth
6	UnsupportedMDUpdateType	Unsupported MDUpdateType
7	UnsupportedAggregatedBook	Unsupported AggregatedBook

Code	Name	Description
8	UnsupportedMDEntryType	Unsupported MDEntryType
9	UnsupportedTradingSessionID	Unsupported TradingSessionID
A	UnsupportedScope	Unsupported Scope
B	UnsupportedOpenCloseSettleFlag	Unsupported OpenCloseSettleFlag
C	UnsupportedMDImplicitDelete	Unsupported MDImplicitDelete
D	InsufficientCredit	Insufficient credit

Used in messages: [MarketDataRequestReject](#)

#### 180.2.2863 MDRjctGrp

Name	Mult.	Type	Description
NoAltMDSource	[1..1]	NumInGroup	
AltMDSourceID	[0..1]	String	Alternative Market Data Source

Used in messages: [MarketDataRequestReject](#)

#### 180.2.2864 MDSecSize

A part of the MDEntrySize(271) that represents secondary interest as specified by MDSecSize-Type(1178).

Type: [Qty](#)

Used in groups: [SecSizesGrp](#)

#### 180.2.2865 MDSecSizeType

Specifies the type of secondary size.

Type: [int](#)

Allowed values in MDSecSizeTypeCodeSet:

Code	Name	Description
1	Customer	Customer. Quantity of retail investors.
2	CustomerProfessional	Customer professional. Quantity of high-volume investors acting similar to broker-dealers.
3	DoNotTradeThrough	Do not trade through. Quantity that cannot trade through the away markets.

Used in groups: [SecSizesGrp](#)

### 180.2.2866 MDSecurityTradingStatus

Identifies the trading status applicable to the instrument in the market data message.

Type: [int](#)

Allowed values in SecurityTradingStatusCodeSet:

Code	Name	Description
1	OpeningDelay	Opening delay
2	TradingHalt	Trading halt
3	Resume	Resume
4	NoOpen	No Open / No Resume
5	PriceIndication	Price indication
6	TradingRangeIndication	Trading Range Indication
7	MarketImbalanceBuy	Market Imbalance Buy
8	MarketImbalanceSell	Market Imbalance Sell
9	MarketOnCloseImbalanceBuy	Market on Close Imbalance Buy
10	MarketOnCloseImbalanceSell	Market on Close Imbalance Sell
12	NoMarketImbalance	No Market Imbalance
13	NoMarketOnCloseImbalance	No Market on Close Imbalance
14	ITSPreOpening	ITS Pre-opening
15	NewPriceIndication	New Price Indication
16	TradeDisseminationTime	Trade Dissemination Time
17	ReadyToTrade	Ready to trade (start of session)
18	NotAvailableForTrading	Not available for trading (end of session)
19	NotTradedOnThisMarket	Not traded on this market

Code	Name	Description
20	UnknownOrInvalid	Unknown or Invalid
21	PreOpen	Pre-open
22	OpeningRotation	Opening Rotation
23	FastMarket	Fast Market
24	PreCross	Pre-Cross - system is in a pre-cross state allowing market to respond to either side of cross
25	Cross	Cross - system has crossed a percentage of the orders and allows market to respond prior to crossing remaining portion
26	PostClose	Post-close
27	NoCancel	No-cancel

Used in messages: [MarketDataSnapshotFullRefresh](#)

#### **180.2.2867 MDStatisticDelayPeriod**

Number of time units between the calculation of the statistic and its dissemination. Can be used to defer or delay publication.

Type: [int](#)

Used in components: [MDStatisticParameters](#)

#### **180.2.2868 MDStatisticDelayUnit**

Time unit for MDStatisticDelayPeriod(2462).

Type: [int](#)

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds

Code	Name	Description
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in components: [MDStatisticParameters](#)

#### **180.2.2869 MDStatisticDesc**

Can be used to provide an optional textual description for a statistic.

Type: [String](#)

Used in components: [MDStatisticParameters](#)

#### **180.2.2870 MDStatisticEndDate**

Last day of range for which statistical data is collected.

Type: [UTCTimestamp](#)

Used in components: [MDStatisticParameters](#)

#### **180.2.2871 MDStatisticEndTime**

End time of the time range for which statistical data is collected.

Type: [UTCTimeOnly](#)

Used in components: [MDStatisticParameters](#)

#### **180.2.2872 MDStatisticFrequencyPeriod**

Dissemination frequency of statistics.

Special meaning for a value of zero which represents an event-driven dissemination in real time (e.g. as soon as a new trade occurs).

Type: **int**

Used in components: **MDStatisticParameters**

### **180.2.2873 MDStatisticFrequencyUnit**

Time unit for MDStatisticFrequencyPeriod(2460).

Type: **int**

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in components: **MDStatisticParameters**

### **180.2.2874 MDStatisticID**

Unique identifier for a statistic.

Type: **String**

Used in groups: **MDStatisticReqGrp**, **MDStatisticRptGrp**

### **180.2.2875 MDStatisticIntervalPeriod**

Length of time over which the statistic is calculated. Special meaning for a value of zero to express that there is no aggregation over time. Can be used with other interval types expressing relative date and

time ranges to combine them with sliding window peaks, e.g. highest volume across 1 minute intervals of the previous day.

Type: **int**

Used in components: **MDStatisticParameters**

### **180.2.2876 MDStatisticIntervalType**

Type of interval over which statistic is calculated.

Type: **int**

Allowed values in MDStatisticIntervalTypeCodeSet:

Code	Name	Description
1	SlidingWindow	Sliding window. Window is defined as an interval period up to the current time of dissemination, see MDStatisticIntervalPeriod (2466).
2	SlidingWindowPeak	Sliding window peak. Highest value of all sliding windows across date and/or time range. Omission of date/time range represents current day.
3	FixedDateRange	Fixed date range. Interval may be open ended on either side, see MDStatisticStartDate (2468) and MDStatisticEndDate(2469). Starting/ending time of date fields only apply to the first/last day of the date range. Additional time range may be defined with MDStatisticStartTime(2470) and MDStatisticEndTime(2471) and applies to every business day within date range, i.e. to define an identical time slice across days.
4	FixedTimeRange	Fixed time range. Interval may be open ended on either side, see MDStatisticStartTime(2470) and MDStatisticEndTime(2471).
5	CurrentTimeUnit	Current time unit. Relative time unit which has not ended yet, e.g. current day. Interval ends with the time of dissemination of the statistic. Requires the definition of an actual unit, see MDStatisticIntervalTypeUnit(2465).
6	PreviousTimeUnit	Previous time unit. Relative time unit which has ended in the past. Requires the definition of an actual unit, see MDStatisticIntervalTypeUnit(2465).
7	MaximumRange	Maximum range. Use to convey record values over the lifetime of the system or venue.



Code	Name	Description
8	MaximumRangeUpToPreviousTime-Unit	Maximum range up to previous time unit. Use to convey record values over the lifetime of the system or venue but does not include the most recent time unit as it has not completed yet. Requires the definition of an actual unit, see MDStatisticIntervalTypeUnit(2465)

Used in components: [MDStatisticParameters](#)

### 180.2.2877 MDStatisticIntervalTypeUnit

Time unit for MDStatisticIntervalType(2464).

Type: [String](#)

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in components: [MDStatisticParameters](#)

### 180.2.2878 MDStatisticIntervalUnit

Time unit for MDStatisticIntervalPeriod(2466).

Type: [int](#)

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in components: [MDStatisticParameters](#)

#### **180.2.2879 MDStatisticName**

The short name or acronym for a set of statistic parameters.

Type: [String](#)

Used in components: [MDStatisticParameters](#)

#### **180.2.2880 MDStatisticParameters**

This component comprises all parameters that can be used to describe the market data statistics. These can be part of the request as well as the response. All parameters defined on the MarketDataStatisticRequest(35=DO) message should be echoed in the MarketDataStatisticsReport(35=DP) message as the latter could also be sent unsolicited.

The general category and the entities involved in the statistics are defined by MDStatisticType(2456), MDStatisticScope(2457), and MDStatisticIntervalType(2464) and must always be specified. The remaining fields are optional and restrict the data range in one way or another. The time range for the data can either be specified in terms of an interval for which the statistics are typically calculated on a regular basis or in terms of an absolute date and/or time range.

Name	Mult.	Type	Description
MDStatisticType	[1..1]	CodeSet	
MDStatisticScope	[1..1]	CodeSet	
MDStatisticSubScope	[0..1]	CodeSet	
MDStatisticScopeType	[0..1]	CodeSet	
MDStatisticName	[0..1]	String	
MDStatisticDesc	[0..1]	String	
EncodedMDStatisticDescLen	[0..1]	Length	Must be set if EncodedMDStatisticDesc(2482) field is specified and must immediately precede it.
EncodedMDStatisticDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the MDStatisticDesc(2455) field in the encoded format specified via the MessageEncoding(347) field.
MarketDepth	[0..1]	int	May be used to specify the market depth up to specified level.
MDStatisticFrequencyPeriod	[0..1]	int	Conditionally required when MDStatisticFrequencyUnit(2461) is specified. Omission represents a one-time dissemination.
MDStatisticFrequencyUnit	[0..1]	CodeSet	Conditionally required when MDStatisticFrequencyPeriod(2460) is specified.
MDStatisticDelayPeriod	[0..1]	int	Conditionally required when MDStatisticDelayUnit(2463) is specified.
MDStatisticDelayUnit	[0..1]	CodeSet	Conditionally required when MDStatisticDelayPeriod(2462) is specified.
MDStatisticIntervalType	[1..1]	CodeSet	
MDStatisticIntervalTypeUnit	[0..1]	CodeSet	Conditionally required when MDStatisticIntervalType (2464) = 5(Current time unit), 6(Previous time unit) or 8(Maximum range up to previous time unit).
MDStatisticIntervalPeriod	[0..1]	int	Conditionally required if/when MDStatisticIntervalUnit(2467) is specified. Conditionally required when MDStatisticIntervalType(2464) = 1 (Sliding window) or 2 (Sliding window peak).
MDStatisticIntervalUnit	[0..1]	CodeSet	Conditionally required when MDStatisticIntervalPeriod(2466) is specified.
MDStatisticStartDate	[0..1]	UTCTimestamp	Can be used to define a date range for a sliding window peak other than the current day. Omission represents a date range starting with the first available day.

Name	Mult.	Type	Description
MDStatisticEndDate	[0..1]	UTCTimestamp	Can be used to define a date range for a sliding window peak other than the current day. Omission represents a date range including the current day.
MDStatisticStartTime	[0..1]	UTCTimeOnly	Can be used to define a time range for a sliding window peak other than the complete day. Omission represents a time range starting at midnight.
MDStatisticEndTime	[0..1]	UTCTimeOnly	Can be used to define a time range for a sliding window peak other than the complete day. Omission represents a time range ending with the time of dissemination of the statistical data.
MDStatisticRatioType	[0..1]	CodeSet	Conditionally required when MDStatisticType(2456) = 5(Ratio).
NestedParties	[0..*]	Group	
AnnualTradingBusinessDays	[0..1]	int	
TradingCapacity	[0..1]	CodeSet	
OrdType	[0..1]	CodeSet	
TimeInForce	[0..1]	CodeSet	
QuoteCondition	[0..1]	CodeSet	
TradeCondition	[0..1]	CodeSet	
Side	[0..1]	CodeSet	
TradeInputSource	[0..1]	String	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
MDOriOriginType	[0..1]	CodeSet	
MDValueTier	[0..1]	CodeSet	
TradSesMethod	[0..1]	CodeSet	
MDFeedType	[0..1]	String	
ExposureDuration	[0..1]	int	
ExposureDurationUnit	[0..1]	CodeSet	Conditionally required when ExposureDuration(1629) is specified.
AggressorIndicator	[0..1]	CodeSet	

Used in groups: MDStatisticReqGrp, MDStatisticRptGrp

**180.2.2881 MDStatisticRatioType**

Ratios between various entities.

Type: **int**

Allowed values in MDStatisticRatioTypeCodeSet:

Code	Name	Description
1	BuyersToSellers	Buyers to sellers.
2	UpticksToDownticks	Upticks to downticks. Can also be used with a scope of multiple instruments representing an index.
3	MarketMakerToNonMarketMaker	Market maker to non-market maker. Use to identify share of market making activity.
4	AutomatedToNonAutomated	Automated to non-automated. Use to identify ratio of orders and quotes resulting from automated trading.
5	OrdersToTrades	Orders to trades. Use with scope of trades.
6	QuotesToTrades	Quotes to trades. Use with scope of trades.
7	OrdersAndQuotesToTrades	Orders and quotes to trades. Use with scope of trades.
8	FailedToTotalTradedValue	Failed to total traded value. Total value of failed trades over total traded value.
9	BenefitsToTotalTradedValue	Benefits to total traded value. Total value of all benefits over total traded value.
10	FeesToTotalTradedValue	Fees to total traded value. Total value of all fees excluding rebates over total traded value.
11	TradeVolumeToTotalTradedVolume	Trade volume to total traded volume. Total value of failed trades over total traded value.
12	OrdersToTotalNumberOrders	Orders to total number of orders. Orders pertaining to a type over total number of orders.

Used in components: **MDStatisticParameters**

**180.2.2882 MDStatisticReqGrp**

This component block is used within the MarketDataStatisticsRequest(35=DO) message to define a set of parameters describing the desired statistics.

Name	Mult.	Type	Description
NoMDStatistics	[1..1]	NumInGroup	
MDStatisticID	[0..1]	String	Required if NoMDStatistics(2474) > 0. Unique statistics identifier used as a placeholder for a set of parameters. If an ID is not applicable use "[N/A]".
MDStatisticParameters	[0..1]	Component	Required if NoMDStatistics(2474) > 0 and MDStatisticID(2475) = "[N/A]".

Used in messages: [MarketDataStatisticsRequest](#)

### 180.2.2883 MDStatisticReqID

Message identifier for a statistics request.

Type: [String](#)

Used in messages: [MarketDataStatisticsReport](#), [MarketDataStatisticsRequest](#)

### 180.2.2884 MDStatisticRequestResult

Result returned in response to MarketDataStatisticsRequest (35=DO).

Type: [int](#)

Allowed values in MDStatisticRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidOrUnknownMarket	Invalid or unknown market
2	InvalidOrUnknownMarketSegment	Invalid or unknown market segment
3	InvalidOrUnknownSecurityList	Invalid or unknown security list
4	InvalidOrUnknownInstruments	Invalid or unknown instrument(s)
5	InvalidParties	Invalid parties
6	TradeDateOutOfSupportedRange	Trade date out of supported range
7	UnsupportedStatisticType	Statistic type not supported
8	UnsupportedScopeOrSubScope	Scope or sub-scope not supported
9	UnsupportedScopeType	Scope type not supported

Code	Name	Description
10	MarketDepthNotSupported	Market depth not supported
11	FrequencyNotSupported	Frequency not supported
12	UnsupportedStatisticInterval	Statistic interval not supported
13	UnsupportedStatisticDateRange	Statistic date range not supported
14	UnsupportedStatisticTimeRange	Statistic time range not supported
15	UnsupportedRatioType	Ratio type not supported
16	InvalidOrUnknownTradeInputSource	Invalid or unknown trade input source
17	InvalidOrUnknownTradingSession	Invalid or unknown trading session
18	UnauthorizedForStatisticRequest	Unauthorized for statistic request
99	Other	Other (further information in Text (58) field)

Used in messages: [MarketDataStatisticsReport](#)

### 180.2.2885 MDStatisticRptGrp

This component block is used within the MarketDataStatisticsReport(35=DP) message to provide results together with the related set of parameters.

Name	Mult.	Type	Description
NoMDStatistics	[1..1]	NumInGroup	
MDStatisticParameters	[0..1]	Component	Required if NoMDStatistics(2474) > 0.
MDStatisticID	[0..1]	String	Required if NoMDStatistics(2474) > 0.
MDStatisticTime	[0..1]	UTCTimestamp	Conditionally required when MDStatisticValue(2478) is specified.
MDStatisticStatus	[0..1]	CodeSet	May be used when sending reference data only to establish MDStatisticID(2475) as a reference to a set of parameters specified in MDStatisticParameters component. If not specified the default is MDStatisticStatus(2477)=1 (Active).
MDStatisticValue	[0..1]	float	Conditionally required unless sending reference data only to establish MDStatisticID(2475) as a reference to a set of parameters specified in MDStatisticParameters component.
MDStatisticValueType	[0..1]	CodeSet	
MDStatisticValueUnit	[0..1]	CodeSet	

---

Name	Mult.	Type	Description
------	-------	------	-------------

---

Used in messages: [MarketDataStatisticsReport](#)

### **180.2.2886 MDStatisticRptID**

Message identifier for a statistics report.

Type: [String](#)

Used in messages: [MarketDataStatisticsReport](#)

### **180.2.2887 MDStatisticScope**

Entities used as basis for the statistics.

Type: [int](#)

Allowed values in MDStatisticScopeCodeSet:

---

Code	Name	Description
1	BidPrices	Bid prices
2	OfferPrices	Offer prices
3	BidDepth	Bid depth
4	OfferDepth	Offer depth
5	Orders	Orders
6	Quotes	Quotes
7	OrdersAndQuotes	Orders and Quotes
8	Trades	Trades
9	TradePrices	Trade prices
10	AuctionPrices	Auction prices
11	OpeningPrices	Opening prices
12	ClosingPrices	Closing prices
13	SettlementPrices	Settlement prices
14	UnderlyingPrices	Underlying prices
15	OpenInterest	Open interest
16	IndexValues	Index values

---



Code	Name	Description
17	MarginRates	Margin rates
18	Outages	Outages. System halt due to a technical malfunction or failure.
19	ScheduledAuctions	Scheduled auctions
20	ReferencePrices	Reference prices
21	TradeValue	Trade value. Trade size multiplied by price.
22	MarketDataFeeItems	Market data fee items. Fees related to market data access.
23	Rebates	Rebates. Rebate items offered to the client.
24	Discounts	Discounts. Discounts offered to the client.
25	Payments	Payments. Other benefits offered to the client.
26	Taxes	Taxes. Taxes incurred.
27	Levies	Levies. Levies incurred.
28	Benefits	Benefits. Benefits offered to the client.
29	Fees	Fees
30	OrdersRFQs	Orders and RFQs (Request for quotes)
31	MarketMakers	Market makers
32	TradingInterruptions	Trading interruptions. Disruption in trading due to an automatic or manual decision.
33	TradingSuspensions	Trading suspensions. An instrument is deliberately prevented from being quoted or traded due to a decision by execution venue or a competent authority.
34	NoQuotes	No quotes. Period of no quotes received.
35	RequestForQuotes	Request for quotes
36	TradeVolume	Trade volume. Quantity traded.

Used in components: **MDStatisticParameters**

### 180.2.2888 MDStatisticScopeType

Scope details of the statistics to reduce the number of events being used as basis for the statistics.

Type: **int**

Allowed values in MDStatisticScopeTypeCodeSet:

Code	Name	Description
1	EntryRate	Entry rate
2	ModificationRate	Modification rate
3	CancelRate	Cancel rate
4	DownwardMove	Downward move
5	UpwardMove	Upward move

Used in components: **MDStatisticParameters**

#### **180.2.2889 MDStatisticStartDate**

First day of range for which statistical data is collected.

Type: **UTCTimestamp**

Used in components: **MDStatisticParameters**

#### **180.2.2890 MDStatisticStartTime**

Start time of the time range for which statistical data is collected.

Type: **UTCTimeOnly**

Used in components: **MDStatisticParameters**

#### **180.2.2891 MDStatisticStatus**

Status for a statistic to indicate its availability.

Type: **int**

Allowed values in MDStatisticStatusCodeSet:

Code	Name	Description
1	Active	Active (default)
2	Inactive	Inactive (not disseminated)

Used in groups: **MDStatisticRptGrp**

**180.2.2892 MDStatisticSubScope**

Sub-scope of the statistics to further reduce the entities used as basis for the statistics.

Type: **int**

Allowed values in MDStatisticSubScopeCodeSet:

Code	Name	Description
1	Visible	Visible. Only includes visible orders and/or quotes.
2	Hidden	Hidden. Only includes hidden orders and/or quotes.
3	Indicative	Indicative. Only includes IOIs and non-tradable quotes.
4	Tradeable	Tradeable. Excludes IOIs and indicative quotes.
5	Passive	Passive. Only includes resting orders and tradeable quotes.
6	MarketConsensus	Market consensus. Only includes entities, e.g. trades, conforming to minimum requirements. Details to be defined out of band.
7	Power	Power. Outages due to power failure.
8	HardwareError	Hardware error. Outages due to a hardware malfunction or failure.
9	SoftwareError	Software error. Outages due to a software malfunction or failure.
10	NetworkError	Network error. Outages due to network error.
11	Failed	Failed. Transaction voided by the execution venue.
12	Executed	Executed. Total or partial execution of an order or quote.
13	Entered	Entered. Order or quote entry.
14	Modified	Modified. Order or quote modification.
15	Cancelled	Cancelled. Order or quote cancellation.
16	MarketDataAccess	Market data access
17	TerminalAccess	Terminal access
18	Volume	Volume. Specifies sub-scope of market data per volume.
19	Cleared	Cleared. Cleared trade.
20	Settled	Settled. Settled trade.
21	Other	Other. Any other fees incurred by the client.
22	Monetary	Monetary. Monetary benefits offered to the clients.
23	NonMonetary	Non-monetary. Non-monetary benefits offered to the clients
24	Gross	Gross. Total fees excluding rebates and discounts.
25	LargeInScale	Large in scale. Means an order classified as large in scale in accordance with a regulatory definition.

Code	Name	Description
26	NeitherHiddenNorLargeInScale	Neither hidden nor large in scale. Excluding orders pending disclosures and LIS.
27	CorporateAction	Corporate action. Specifies type of trading suspension.
28	VenueDecision	Venue decision. Specifies type of trading suspension.
29	MinimumTimePeriod	Minimum time period. Minimum time period for the event defined by scope.
30	Open	Open. Open status of RFQs (request for quotes), no quotes have been provided.
31	NotExecuted	Not executed. Orders or quotes that didn't execute.
32	Aggressive	Aggressive. Order or Quote entered into the order book that took liquidity.
33	Directed	Directed. An order where execution venue is specified by the client.

---

Used in components: [MDStatisticParameters](#)

#### **180.2.2893 MDStatisticTime**

Time of calculation of a statistic.

Type: [UTCTimestamp](#)

Used in groups: [MDStatisticRptGrp](#)

#### **180.2.2894 MDStatisticType**

Type of statistic value.

Type: [int](#)

Allowed values in MDStatisticTypeCodeSet:

Code	Name	Description
1	Count	Count. Simple count of entities or events, e.g. orders transactions during a period of time.
2	AverageVolume	Average volume. Average quantity of entities, e.g. average volume of incoming quotes or average trade volume.

Code	Name	Description
3	TotalVolume	Total volume. Aggregated quantities of entities across events, e.g. total trade volume during a period of time.
4	Distribution	Distribution. Distribution of entities across entity types, e.g. percentage of limit orders amongst all order types.
5	Ratio	Ratio. Pre-defined ratio between entities, e.g. ratio of trades triggered by buy orders.
6	Liquidity	Liquidity. Measurement of liquidity of an instrument, e.g. by providing the spread between bid and offer or the trade volume needed to move the price.
7	VWAP	Volume weighted average price (VWAP). Benchmark price.
8	Volatility	Volatility. Volatility of entities, e.g. price movements of incoming orders.
9	Duration	Duration. Time period of events, e.g. resting period of passive orders.
10	Tick	Tick. Price movement of an instrument in number of ticks.
11	AverageValue	Average value. Average quantity multiplied by price.
12	TotalValue	Total value. Aggregated quantity multiplied by price; also described as turnover.
13	High	High. Highest price.
14	Low	Low. Lowest price.
15	Midpoint	Midpoint. Midpoint price between bid and offer.
16	First	First. First price or initial value.
17	Last	Last. Most recent price or value.
18	Final	Final. Final price or confirmed value.
19	ExchangeBest	Exchange best. Best price of a single venue regardless of volume.
20	ExchangeBestWithVolume	Exchange best with volume. Best price of a single venue with volume at or above a pre-defined threshold.
21	ConsolidatedBest	Consolidated best. Best price across multiple venues regardless of volume.
22	ConsolidatedBestWithVolume	Consolidated best with volume. Best price across multiple venues with volume at or above a pre-defined threshold.
23	TWAP	Time weighted average price (TWAP)
24	AverageDuration	Average duration. Average duration of time periods of events.
25	AveragePrice	Average price. Average price across entities e.g. trade prices.
26	TotalFees	Total fees. Aggregated fees.
27	TotalBenefits	Total benefits. Aggregated benefits.

Code	Name	Description
28	MedianValue	Median value. Median quantity multiplied by price for orders or quotes.
29	AverageLiquidity	Average liquidity. Average liquidity of an instrument e.g. average effective spread.
30	MedianDuration	Median duration. Median duration of time periods of events.

Used in components: [MDStatisticParameters](#)

#### **180.2.2895 MDStatisticValue**

Statistical value.

Type: [float](#)

Used in groups: [MDStatisticRptGrp](#)

#### **180.2.2896 MDStatisticValueType**

Type of statistical value.

Type: [int](#)

Allowed values in MDStatisticValueTypeCodeSet:

Code	Name	Description
1	Absolute	Absolute
2	Percentage	Percentage

Used in groups: [MDStatisticRptGrp](#)

#### **180.2.2897 MDStatisticValueUnit**

Unit of time for statistical value.

Type: [int](#)

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in groups: [MDStatisticRptGrp](#)

#### **180.2.2898 MDStreamID**

The identifier or name of the price stream.

Type: [String](#)

Used in groups: [InstrmtMDReqGrp](#), [MDIncGrp](#), [StrmAsgnReqInstrmtGrp](#), [StrmAsgnRptInstrmtGrp](#)

Used in messages: [MarketDataSnapshotFullRefresh](#)

#### **180.2.2899 MDSubBookType**

Describes a class of sub book, e.g. for the separation of various lot types. The Sub Book Type indicates that the following Market Data Entries belong to a non-integrated Sub Book. Whenever provided the Sub Book must be used together with MDPriceLevel and MDEntryPositionNo in order to sort the order properly.

Values are bilaterally agreed.

Type: [int](#)

Used in groups: [MDIncGrp](#), [MarketDataFeedTypes](#)

Used in messages: [MarketDataSnapshotFullRefresh](#)

**180.2.2900 MDSubFeedType**

Describes a sub-class for a given class of service defined by MDFeedType (1022)

Type: **String**

Used in groups: **MarketDataFeedTypes**

Used in messages: **MarketDataIncrementalRefresh**, **MarketDataSnapshotFullRefresh**

**180.2.2901 MDUpdateAction**

Type of Market Data update action.

Type: **char**

Allowed values in MDUpdateActionCodeSet:

Code	Name	Description
0	New	New
1	Change	Change
2	Delete	Delete
3	DeleteThru	Delete Thru
4	DeleteFrom	Delete From
5	Overlay	Overlay

Used in groups: **MDIncGrp**

**180.2.2902 MDUpdateType**

Specifies the type of Market Data update.

Type: **int**

Allowed values in MDUpdateTypeCodeSet:

Code	Name	Description
0	FullRefresh	Full refresh
1	IncrementalRefresh	Incremental refresh

Used in messages: **MarketDataRequest**



**180.2.2903 MDValueTier**

Describes the reporting ranges for executed transactions.

Type: **int**

Allowed values in MDValueTierCodeSet:

Code	Name	Description
1	Range1	Range 1
2	Range2	Range 2
3	Range3	Range 3

Used in components: **MDStatisticParameters**

**180.2.2904 MessageEncoding**

Type of message encoding (non-ASCII (non-English) characters) used in a message's "Encoded" fields.

Type: **String**

Used in components: **StandardHeader**

**180.2.2905 MessageEventSource**

Used to identify the event or source which gave rise to a message.

Valid values will be based on an exchange's implementation.

Example values are:

"MQM" (originated at Firm Back Office)

"Clear" (originated in Clearing System)

"Reg" (static data generated via Register request)

Type: **String**

Used in messages: **AllocationInstruction, AllocationInstructionAlert, AllocationReport, PositionReport, TradeCaptureReport, TradeCaptureReportAck, TradeCaptureReportRequest, TradeCaptureReportRequestAck**

**180.2.2906 MetricsCalculationPriceSource**

Specifies the source of the price(s) of the security used in the calculation of the metrics or analytics data.

Type: **int**

Allowed values in MetricsCalculationPriceSourceCodeSet:

Code	Name	Description
1	Realtime	Real-time. Real-time market prices used as the data source in metrics/analytics calculation.
2	EndOfDay	End of day. Official end of day price (marking) used as the data source in metrics/analytics calculation.

Used in messages: **SecurityRiskMetricsReport**

**180.2.2907 MidPx**

Mid price/rate.

For OTC swaps this is the mid-market mark (for example, as defined by CFTC).

For uncleared OTC swaps, LegMidPx(2346) and the MidPx(631) fields are mutually exclusive.

Type: **Price**

Used in groups: **QuotEntryAckGrp**, **QuotEntryGrp**, **QuotReqGrp**

Used in messages: **ExecutionReport**, **Quote**, **QuoteResponse**, **QuoteStatusReport**, **TradeCaptureReport**

**180.2.2908 MidVolatility**

Volatility based on mid prices.

Type: **float**

Used in groups: **SecurityRiskMetricGrp**

#### **180.2.2909 MidYield**

Mid yield

Type: **Percentage**

Used in groups: **QuotEntryAckGrp, QuotEntryGrp**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

#### **180.2.2910 MinBidSize**

Used to indicate a minimum quantity for a bid.

Type: **Qty**

Used in groups: **QuoteSizeRuleGrp**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

#### **180.2.2911 MinLotSize**

Minimum lot size allowed based on lot type specified in LotType(1093)

Type: **Qty**

Used in groups: **LotTypeRules**

#### **180.2.2912 MinOfferSize**

Used to indicate a minimum quantity for an offer. If this field is used the OfferSize (135) field is interpreted as the maximum offer size.

Type: **Qty**

Used in groups: **QuoteSizeRuleGrp**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

#### **180.2.2913 MinPriceIncrement**

Minimum price increase for a given exchange-traded Instrument

Type: **float**

Used in components: **Instrument**

**180.2.2914 MinPriceIncrementAmount**

Minimum price increment amount associated with MinPriceIncrement(969). For listed derivatives, the value can be calculated by multiplying MinPriceIncrement(969) with ContractMultiplier(231).

Type: **Amt**

Used in components: **Instrument**

**180.2.2915 MinQty**

Minimum quantity of an order to be executed.

(Prior to FIX 4.2 this field was of type int)

Type: **Qty**

Used in groups: **ListOrdGrp, MDFullGrp, MDIncGrp, QuotReqGrp**

Used in messages: **CrossOrderCancelReplaceRequest, ExecutionReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, Quote, QuoteResponse, QuoteStatusReport**

**180.2.2916 MinQtyMethod**

Indicates how the minimum quantity should be applied when executing the order.

Type: **int**

Allowed values in MinQtyMethodCodeSet:

Code	Name	Description
1	Once	Once (applies only to first execution)
2	Multiple	Multiple (applies to every execution)

Used in messages: **CrossOrderCancelReplaceRequest, ExecutionReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest**

**180.2.2917 MinTradeVol**

The minimum order quantity (as expressed by TradeVolType(1786)) that can be submitted for a security.

Type: Qty

Used in components: BaseTradingRules

### 180.2.2918 MiscFeeAmountDue

The fee amount due if different from MiscFeeAmt(137).

Type: Amt

Used in groups: MiscFeesGrp

### 180.2.2919 MiscFeeAmt

Miscellaneous fee value

Type: Amt

Used in groups: MiscFeesGrp

### 180.2.2920 MiscFeeBasis

Defines the unit for a miscellaneous fee.

Type: int

Allowed values in MiscFeeBasisCodeSet:

Code	Name	Description
0	Absolute	Absolute. The fee or markup is a total fixed amount expressed in the currency of the trade.
1	PerUnit	Per Unit. The fee or markup is an amount per quantity unit, i.e. per share or contract, expressed in the currency of the trade.
2	Percentage	Percentage. The percentage is expressed in standard FIX "Percentage" datatype format, i.e. "0.01" for 1 percent and ranges between 0 and 1. It is the number which when multiplied by the trade price and quantity produces the total amount of the fee or markup.

Used in groups: MiscFeesGrp

**180.2.2921 MiscFeeCurr**

Currency of miscellaneous fee

Type: **Currency**

Used in groups: **MiscFeesGrp**

**180.2.2922 MiscFeeDesc**

Can be used to provide a textual description of the fee type.

Type: **String**

Used in groups: **MiscFeesGrp**

**180.2.2923 MiscFeeQualifier**

Identifies whether the current entry contributes to the trade or transaction economics, i.e. affects NetMoney(118).

Type: **int**

Allowed values in MiscFeeQualifierCodeSet:

Code	Name	Description
0	Contributes	Contributes (default). Fee contributes to the trade or transaction economics.
1	DoesNotContribute	Does not contribute. Fee does not contribute to the trade or transaction economics.

Used in groups: **MiscFeesGrp**

**180.2.2924 MiscFeeRate**

The fee rate when MiscFeeAmt(137) is a percentage of trade quantity.

Type: **Percentage**

Used in groups: **MiscFeesGrp**

**180.2.2925 MiscFeesGrp**

The MiscFeesGrp component is used to provide details of trade and transaction fees other than commissions, e.g. regulatory, exchange, taxes, levies, markup, trade reporting, etc. In the context of ESMA RTS 27 Best Execution Reporting, it may also be used to collect and publish the nature and level of current venue fees, rebates and payouts. Use MiscFeeQualifier(2712) to communicate whether the fee affects trade economics.

Name	Mult.	Type	Description
NoMiscFees	[1..1]	NumInGroup	Required if any miscellaneous fees are reported. Indicates number of repeating entries.
MiscFeeAmt	[0..1]	Amt	Required if NoMiscFees(136) > 0.
MiscFeeCurr	[0..1]	Currency	
MiscFeeType	[0..1]	CodeSet	Required if NoMiscFees(136) > 0.
MiscFeeQualifier	[0..1]	CodeSet	
MiscFeesSubGrp	[0..*]	Group	
MiscFeeBasis	[0..1]	CodeSet	
MiscFeeRate	[0..1]	Percentage	
MiscFeeAmountDue	[0..1]	Amt	
MiscFeeDesc	[0..1]	String	

Used in groups: AllocGrp, TrdCapRptAckSideGrp, TrdCapRptSideGrp

Used in messages: CollateralAssignment, CollateralReport, CollateralRequest, CollateralResponse, Confirmation, ExecutionReport, MarketDefinition

**180.2.2926 MiscFeesSubGrp**

The MiscFeesSubGrp component is used to provide further details for a given MiscFeeType(139) value.

Name	Mult.	Type	Description
NoMiscFeeSubTypes	[1..1]	NumInGroup	
MiscFeeSubType	[0..1]	String	Required if NoMiscFeeSubTypes(2633) > 0.
MiscFeeSubTypeAmt	[0..1]	Amt	
MiscFeeSubTypeDesc	[0..1]	String	
EncodedMiscFeeSubTypeDescLen	[0..1]	Length	Must be set if EncodedMiscFeeSubTypeDesc(2638) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedMiscFeeSubTypeDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the MiscFeeSubTypeDesc(2636) field in the encoded format specified via the MessageEncoding(347) field.

Used in groups: **MiscFeesGrp**

#### **180.2.2927 MiscFeeSubType**

Used to provide more granular fee types related to a value of MiscFeeType(139).

See [http://www.fixtradingcommunity.org/codelists#Misc\\_Fee\\_Sub\\_Types](http://www.fixtradingcommunity.org/codelists#Misc_Fee_Sub_Types) for code list of applicable fees. Other fee sub-types may be used by mutual agreement of the counterparties.

Type: **String**

Used in groups: **MiscFeesSubGrp**

#### **180.2.2928 MiscFeeSubTypeAmt**

The amount of the specified MiscFeeSubType(2634).

Type: **Amt**

Used in groups: **MiscFeesSubGrp**

#### **180.2.2929 MiscFeeSubTypeDesc**

Can be used to provide an optional textual description of the fee sub-type.

Type: **String**

Used in groups: **MiscFeesSubGrp**

#### **180.2.2930 MiscFeeType**

Indicates type of miscellaneous fee.

Type: **String**

Allowed values in MiscFeeTypeCodeSet:



Code	Name	Description
1	Regulatory	Regulatory (e.g. SEC)
2	Tax	Tax
3	LocalCommission	Local Commission. DEPRECATE - use <CommissionDataGrp> component instead
4	ExchangeFees	Exchange Fees
5	Stamp	Stamp
6	Levy	Levy
7	Other	Other
8	Markup	Markup
9	ConsumptionTax	Consumption Tax
10	PerTransaction	Per transaction
11	Conversion	Conversion
12	Agent	Agent
13	TransferFee	Transfer Fee
14	SecurityLending	Security Lending
15	TradeReporting	Trade reporting. The fee charged to recover the cost of trade reporting, e.g. corporate bonds and structured products reported to FINRA TRACE.
16	TaxOnPrincipalAmount	Tax on principal amount
17	TaxOnAccruedInterestAmount	Tax on accrued interest amount
18	NewIssuanceFee	New issuance fee
19	ServiceFee	Service fee
20	OddLotFee	Odd lot fee
21	AuctionFee	Auction fee
22	ValueAddedTax	Value Added tax - VAT
23	SalesTax	Sales tax
24	ExecutionFee	Execution venue fee
25	OrderEntryFee	Order or quote entry fee. Order or quote submission fees per transaction.
26	OrderModificationFee	Order or quote modification fee. Order or quote modification fees per transaction.
27	OrdersCancellationFee	Orders or quote cancellation fee. Order or quote cancellation fees per transaction.
28	MarketDataAccessFee	Market data access fee. Fee for market data access.
29	MarketDataTerminalFee	Market data terminal fee. Fee for market data terminal.
30	MarketDataVolumeFee	Market data volume fee. Fee for market data per volume group.

Code	Name	Description
31	ClearingFee	Clearing fee. Fee for clearing of trades.
32	SettlementFee	Settlement fee. Fee for settlement of trades.
33	Rebates	Rebates. Rebates offered to the client.
34	Discounts	Discounts. Discounts offered to the client.
35	Payments	Payments. Other benefits offered to the client.
36	NonMonetaryPayments	Non-monetary payments. Non-monetary benefits offered to the client.

Used in groups: **MiscFeesGrp**

#### **180.2.2931 MixedSwapIndicator**

An indication that the trade is a mixed swap.

Type: **Boolean**

Used in messages: **TradeCaptureReport**

#### **180.2.2932 MktBidPx**

Used to indicate the best bid in a market

Type: **Price**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

#### **180.2.2933 MktOfferPx**

Used to indicate the best offer in a market

Type: **Price**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

#### **180.2.2934 ModelType**

Type of pricing model used

Type: **int**

Allowed values in ModelTypeCodeSet:

Code	Name	Description
0	UtilityProvidedStandardModel	Utility provided standard model
1	ProprietaryModel	Proprietary (user supplied) model

Used in messages: **PositionReport**

### 180.2.2935 MoneyLaunderingStatus

A one character code identifying Money laundering status.

Type: **char**

Allowed values in MoneyLaunderingStatusCodeSet:

Code	Name	Description
Y	Passed	Passed
N	NotChecked	Not Checked
1	ExemptBelowLimit	Exempt - Below the Limit
2	ExemptMoneyType	Exempt - Client Money Type exemption
3	ExemptAuthorised	Exempt - Authorised Credit or financial institution

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderList**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

### 180.2.2936 MsgDirection

Specifies the direction of the message.

Type: **char**

Allowed values in MsgDirectionCodeSet:

Code	Name	Description
R	Receive	Receive
S	Send	Send

Used in groups: **MsgTypeGrp**

**180.2.2937 MsgSeqNum**

Integer message sequence number.

Type: **SeqNum**

Used in components: **StandardHeader**

**180.2.2938 MsgType**

Defines message type ALWAYS THIRD FIELD IN MESSAGE. (Always unencrypted)

Note: A "U" as the first character in the MsgType field (i.e. U, U2, etc) indicates that the message format is privately defined between the sender and receiver.

\*\*\* Note the use of lower case letters \*\*\*

Type: **String**

Allowed values in MsgTypeCodeSet:

Code	Name	Description
0	Heartbeat	Heartbeat. The Heartbeat monitors the status of the communication link and identifies when the last of a string of messages was not received.
1	TestRequest	TestRequest. The test request message forces a heartbeat from the opposing application. The test request message checks sequence numbers or verifies communication line status. The opposite application responds to the Test Request with a Heartbeat containing the TestReqID.
2	ResendRequest	ResendRequest. The resend request is sent by the receiving application to initiate the retransmission of messages. This function is utilized if a sequence number gap is detected, if the receiving application lost a message, or as a function of the initialization process.
3	Reject	Reject. The reject message should be issued when a message is received but cannot be properly processed due to a session-level rule violation. An example of when a reject may be appropriate would be the receipt of a message with invalid basic data which successfully passes de-encryption, CheckSum and BodyLength checks.
4	SequenceReset	SequenceReset. The sequence reset message is used by the sending application to reset the incoming sequence number on the opposing side.

Code	Name	Description
5	Logout	Logout. The logout message initiates or confirms the termination of a FIX session. Disconnection without the exchange of logout messages should be interpreted as an abnormal condition.
6	IOI	IOI. Indication of interest messages are used to market merchandise which the broker is buying or selling in either a proprietary or agency capacity. The indications can be time bound with a specific expiration value. Indications are distributed with the understanding that other firms may react to the message first and that the merchandise may no longer be available due to prior trade. Indication messages can be transmitted in various transaction types; NEW, CANCEL, and REPLACE. All message types other than NEW modify the state of the message identified in IOIRefID.
7	Advertisement	Advertisement. Advertisement messages are used to announce completed transactions. The advertisement message can be transmitted in various transaction types; NEW, CANCEL and REPLACE. All message types other than NEW modify the state of a previously transmitted advertisement identified in AdvRefID.
8	ExecutionReport	ExecutionReport. The execution report message is used to: 1. confirm the receipt of an order. 2. confirm changes to an existing order (i.e. accept cancel and replace requests). 3. relay order status information. 4. relay fill information on working orders. 5. relay fill information on tradeable or restricted tradeable quotes. 6. reject orders. 7. report post-trade fees calculations associated with a trade
9	OrderCancelReject	OrderCancelReject. The order cancel reject message is issued by the broker upon receipt of a cancel request or cancel/replace request message which cannot be honored.
A	Logon	Logon. The logon message authenticates a user establishing a connection to a remote system. The logon message must be the first message sent by the application requesting to initiate a FIX session.
B	News	News. The news message is a general free format message between the broker and institution. The message contains flags to identify the news item's urgency and to allow sorting by subject company (symbol). The News message can be originated at either the broker or institution side, or exchanges and other marketplace venues.
C	Email	Email. The email message is similar to the format and purpose of the News message, however, it is intended for private use between two parties.

Code	Name	Description
D	NewOrderSingle	NewOrderSingle. The new order message type is used by institutions wishing to electronically submit securities and forex orders to a broker for execution. The New Order message type may also be used by institutions or retail intermediaries wishing to electronically submit Collective Investment Vehicle (CIV) orders to a broker or fund manager for execution.
E	NewOrderList	NewOrderList. The NewOrderList Message can be used in one of two ways depending on which market conventions are being followed.
F	OrderCancelRequest	OrderCancelRequest. The order cancel request message requests the cancellation of all of the remaining quantity of an existing order. Note that the Order Cancel/Replace Request should be used to partially cancel (reduce) an order).
G	OrderCancelReplaceRequest	OrderCancelReplaceRequest. The order cancel/replace request is used to change the parameters of an existing order. Do not use this message to cancel the remaining quantity of an outstanding order, use the Order Cancel Request message for this purpose.
H	OrderStatusRequest	OrderStatusRequest. The order status request message is used by the institution to generate an order status message back from the broker.
J	AllocationInstruction	AllocationInstruction. The AllocationInstruction(35=J) message provides the ability to specify how an order or set of orders should be subdivided amongst one or more accounts.
K	ListCancelRequest	ListCancelRequest. The List Cancel Request message type is used by institutions wishing to cancel previously submitted lists either before or during execution.
L	ListExecute	ListExecute. The List Execute message type is used by institutions to instruct the broker to begin execution of a previously submitted list. This message may or may not be used, as it may be mirroring a phone conversation.
M	ListStatusRequest	ListStatusRequest. The list status request message type is used by institutions to instruct the broker to generate status messages for a list.
N	ListStatus	ListStatus. The list status message is issued as the response to a List Status Request message sent in an unsolicited fashion by the sell-side. It indicates the current state of the orders within the list as they exist at the broker's site. This message may also be used to respond to the List Cancel Request.

Code	Name	Description
P	AllocationInstructionAck	AllocationInstructionAck. In versions of FIX prior to version 4.4, this message was known as the Allocation ACK message. The Allocation Instruction Ack message is used to acknowledge the receipt of and provide status for an Allocation Instruction message.
Q	DontKnowTrade	DontKnowTrade. The Don't Know Trade (DK) message notifies a trading partner that an electronically received execution has been rejected. This message can be thought of as an execution reject message.
R	QuoteRequest	QuoteRequest. In some markets it is the practice to request quotes from brokers prior to placement of an order. The quote request message is used for this purpose. This message is commonly referred to as an Request For Quote (RFQ)
S	Quote	Quote. The Quote message is used as the response to a Quote Request or a Quote Response message in both indicative, tradeable, and restricted tradeable quoting markets.
T	SettlementInstructions	SettlementInstructions. The Settlement Instructions message provides the broker's, the institution's, or the intermediary's instructions for trade settlement. This message has been designed so that it can be sent from the broker to the institution, from the institution to the broker, or from either to an independent "standing instructions" database or matching system or, for CIV, from an intermediary to a fund manager.
V	MarketDataRequest	MarketDataRequest. Some systems allow the transmission of real-time quote, order, trade, trade volume, open interest, and/or other price information on a subscription basis. A MarketDataRequest(35=V) is a general request for market data on specific securities or forex quotes. The values in the fields provided within the request will serve as further filter criteria for the result set.
W	MarketDataSnapshotFullRefresh	MarketDataSnapshotFullRefresh. The Market Data messages are used as the response to a Market Data Request message. In all cases, one Market Data message refers only to one Market Data Request. It can be used to transmit a 2-sided book of orders or list of quotes, a list of trades, index values, opening, closing, settlement, high, low, or VWAP prices, the trade volume or open interest for a security, or any combination of these.

Code	Name	Description
X	MarketDataIncrementalRefresh	MarketDataIncrementalRefresh. The Market Data message for incremental updates may contain any combination of new, changed, or deleted Market Data Entries, for any combination of instruments, with any combination of trades, imbalances, quotes, index values, open, close, settlement, high, low, and VWAP prices, trade volume and open interest so long as the maximum FIX message size is not exceeded. All of these types of Market Data Entries can be changed and deleted.
Y	MarketDataRequestReject	MarketDataRequestReject. The Market Data Request Reject is used when the broker cannot honor the Market Data Request, due to business or technical reasons. Brokers may choose to limit various parameters, such as the size of requests, whether just the top of book or the entire book may be displayed, and whether Full or Incremental updates must be used.
Z	QuoteCancel	QuoteCancel. The Quote Cancel message is used by an originator of quotes to cancel quotes. The Quote Cancel message supports cancellation of: <ul style="list-style-type: none"> <li>• All quotes.</li> <li>• Quotes for a specific symbol or security ID.</li> <li>• All quotes for a security type.</li> <li>• All quotes for an underlying</li> </ul>
a	QuoteStatusRequest	QuoteStatusRequest. The quote status request message is used for the following purposes in markets that employ tradeable or restricted tradeable quotes: <ul style="list-style-type: none"> <li>• For the issuer of a quote in a market to query the status of that quote (using the QuoteID to specify the target quote).</li> <li>• To subscribe and unsubscribe for Quote Status Report messages for one or more securities.</li> </ul>
b	MassQuoteAck	MassQuoteAck. Mass Quote Acknowledgement is used as the application level response to a Mass Quote message.
c	SecurityDefinitionRequest	SecurityDefinitionRequest. The SecurityDefinitionRequest(35=c) message is used for the following: <ol style="list-style-type: none"> <li>1. Request a specific security to be traded with the second party. The requested security can be defined as a multileg security made up of one or more instrument legs.</li> <li>2. Request a set of individual securities for a single market segment.</li> <li>3. Request all securities, independent of market segment.</li> </ol>



Code	Name	Description
d	SecurityDefinition	SecurityDefinition. The SecurityDefinition(35=d) message is used for the following:. 1. Accept the security defined in a SecurityDefinition(35=d) message. 2. Accept the security defined in a SecurityDefinition(35=d) message with changes to the definition and/or identity of the security. 3. Reject the security requested in a SecurityDefinition(35=d) message. 4. Respond to a request for securities within a specified market segment. 5. Convey comprehensive security definition for all market segments that the security participates in. 6. Convey the security's trading rules that differ from default rules for the market segment.
e	SecurityStatusRequest	SecurityStatusRequest. The Security Status Request message provides for the ability to request the status of a security. One or more Security Status messages are returned as a result of a Security Status Request message.
f	SecurityStatus	SecurityStatus. The Security Status message provides for the ability to report changes in status to a security. The Security Status message contains fields to indicate trading status, corporate actions, financial status of the company. The Security Status message is used by one trading entity (for instance an exchange) to report changes in the state of a security.
g	TradingSessionStatusRequest	TradingSessionStatusRequest. The Trading Session Status Request is used to request information on the status of a market. With the move to multiple sessions occurring for a given trading party (morning and evening sessions for instance) there is a need to be able to provide information on what product is trading on what market.
h	TradingSessionStatus	TradingSessionStatus. The Trading Session Status provides information on the status of a market. For markets multiple trading sessions on multiple-markets occurring (morning and evening sessions for instance), this message is able to provide information on what products are trading on what market during what trading session.
i	MassQuote	MassQuote. The Mass Quote message can contain quotes for multiple securities to support applications that allow for the mass quoting of an option series. Two levels of repeating groups have been provided to minimize the amount of data required to submit a set of quotes for a class of options (e.g. all option series for IBM).

Code	Name	Description
j	BusinessMessageReject	BusinessMessageReject. The Business Message Reject message can reject an application-level message which fulfills session-level rules and cannot be rejected via any other means. Note if the message fails a session-level rule (e.g. body length is incorrect), a session-level Reject message should be issued.
k	BidRequest	BidRequest. The BidRequest Message can be used in one of two ways depending on which market conventions are being followed. In the "Non disclosed" convention (e.g. US/European model) the BidRequest message can be used to request a bid based on the sector, country, index and liquidity information contained within the message itself. In the "Non disclosed" convention the entry repeating group is used to define liquidity of the program. See " Program/Basket/List Trading" for an example. In the "Disclosed" convention (e.g. Japanese model) the BidRequest message can be used to request bids based on the ListOrderDetail messages sent in advance of BidRequest message. In the "Disclosed" convention the list repeating group is used to define which ListOrderDetail messages a bid is being sort for and the directions of the required bids.
l	BidResponse	BidResponse. The Bid Response message can be used in one of two ways depending on which market conventions are being followed. In the "Non disclosed" convention the Bid Response message can be used to supply a bid based on the sector, country, index and liquidity information contained within the corresponding bid request message. See "Program/Basket/List Trading" for an example. In the "Disclosed" convention the Bid Response message can be used to supply bids based on the List Order Detail messages sent in advance of the corresponding Bid Request message.
m	ListStrikePrice	ListStrikePrice. The strike price message is used to exchange strike price information for principal trades. It can also be used to exchange reference prices for agency trades.
n	XMLnonFIX	XMLnonFIX.
o	RegistrationInstructions	RegistrationInstructions. The Registration Instructions message type may be used by institutions or retail intermediaries wishing to electronically submit registration information to a broker or fund manager (for CIV) for an order or for an allocation.
p	RegistrationInstructionsResponse	RegistrationInstructionsResponse. The Registration Instructions Response message type may be used by broker or fund manager (for CIV) in response to a Registration Instructions message submitted by an institution or retail intermediary for an order or for an allocation.

Code	Name	Description
q	OrderMassCancelRequest	OrderMassCancelRequest. The order mass cancel request message requests the cancellation of all of the remaining quantity of a group of orders matching criteria specified within the request. NOTE: This message can only be used to cancel order messages (reduce the full quantity).
r	OrderMassCancelReport	OrderMassCancelReport. The Order Mass Cancel Report is used to acknowledge an Order Mass Cancel Request. Note that each affected order that is canceled is acknowledged with a separate Execution Report or Order Cancel Reject message.
s	NewOrderCross	NewOrderCross. Used to submit a cross order into a market. The cross order contains two order sides (a buy and a sell). The cross order is identified by its CrossID.
t	CrossOrderCancelReplaceRequest	CrossOrderCancelReplaceRequest. Used to modify a cross order previously submitted using the New Order - Cross message. See Order Cancel Replace Request for details concerning message usage.
u	CrossOrderCancelRequest	CrossOrderCancelRequest. Used to fully cancel the remaining open quantity of a cross order.
v	SecurityTypeRequest	SecurityTypeRequest. The Security Type Request message is used to return a list of security types available from a counterparty or market.
w	SecurityTypes	SecurityTypes. The Security Type Request message is used to return a list of security types available from a counterparty or market.
x	SecurityListRequest	SecurityListRequest. The Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request
y	SecurityList	SecurityList. The Security List message is used to return a list of securities that matches the criteria specified in a Security List Request.
z	DerivativeSecurityListRequest	DerivativeSecurityListRequest. The Derivative Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request
AA	DerivativeSecurityList	DerivativeSecurityList. The Derivative Security List message is used to return a list of securities that matches the criteria specified in a Derivative Security List Request.
AB	NewOrderMultileg	NewOrderMultileg. The New Order - Multileg is provided to submit orders for securities that are made up of multiple securities, known as legs.

Code	Name	Description
AC	MultilegOrderCancelReplace	MultilegOrderCancelReplace. Used to modify a multileg order previously submitted using the New Order - Multileg message. See Order Cancel Replace Request for details concerning message usage.
AD	TradeCaptureReportRequest	TradeCaptureReportRequest. The Trade Capture Report Request can be used to: <ul style="list-style-type: none"> <li>• Request one or more trade capture reports based upon selection criteria provided on the trade capture report request.</li> <li>• Subscribe for trade capture reports based upon selection criteria provided on the trade capture report request.</li> </ul>
AE	TradeCaptureReport	TradeCaptureReport. The Trade Capture Report message can be: <ul style="list-style-type: none"> <li>- Used to report trades between counterparties.</li> <li>- Used to report trades to a trade matching system.</li> <li>- Sent unsolicited between counterparties.</li> <li>- Sent as a reply to a Trade Capture Report Request.</li> <li>- Used to report unmatched and matched trades.</li> </ul>
AF	OrderMassStatusRequest	OrderMassStatusRequest. The order mass status request message requests the status for orders matching criteria specified within the request.
AG	QuoteRequestReject	QuoteRequestReject. The Quote Request Reject message is used to reject Quote Request messages for all quoting models.
AH	RFQRequest	RFQRequest. In tradeable and restricted tradeable quoting markets – Quote Requests are issued by counterparties interested in ascertaining the market for an instrument. Quote Requests are then distributed by the market to liquidity providers who make markets in the instrument. The RFQ Request is used by liquidity providers to indicate to the market for which instruments they are interested in receiving Quote Requests. It can be used to register interest in receiving quote requests for a single instrument or for multiple instruments
AI	QuoteStatusReport	QuoteStatusReport. The quote status report message is used: <ul style="list-style-type: none"> <li>• as the response to a Quote Status Request message.</li> <li>• as a response to a Quote Cancel message.</li> <li>• as a response to a Quote Response message in a negotiation dialog (see Volume 7 – PRODUCT: FIXED INCOME and USER GROUP: EXCHANGES AND MARKETS)</li> </ul>
AJ	QuoteResponse	QuoteResponse. The QuoteResponse(35=AJ) message is used for the following purposes: <ol style="list-style-type: none"> <li>1. Respond to an IOI(35=6) message.</li> <li>2. Respond to a Quote(35=S) message.</li> <li>3. Counter a Quote.</li> <li>4. End a negotiation dialog.</li> <li>5. Follow-up or end a QuoteRequest(35=R) dialog that did not receive a response.</li> </ol>

Code	Name	Description
AK	Confirmation	Confirmation. The Confirmation messages are used to provide individual trade level confirmations from the sell side to the buy side. In versions of FIX prior to version 4.4, this role was performed by the allocation message. Unlike the allocation message, the confirmation message operates at an allocation account (trade) level rather than block level, allowing for the affirmation or rejection of individual confirmations.
AL	PositionMaintenanceRequest	PositionMaintenanceRequest. The Position Maintenance Request message allows the position owner to submit requests to the holder of a position which will result in a specific action being taken which will affect the position. Generally, the holder of the position is a central counter party or clearing organization but can also be a party providing investment services.
AM	PositionMaintenanceReport	PositionMaintenanceReport. The Position Maintenance Report message is sent by the holder of a position in response to a Position Maintenance Request and is used to confirm that a request has been successfully processed or rejected.
AN	RequestForPositions	RequestForPositions. The Request For Positions message is used by the owner of a position to request a Position Report from the holder of the position, usually the central counter party or clearing organization. The request can be made at several levels of granularity.
AO	RequestForPositionsAck	RequestForPositionsAck. The Request for Positions Ack message is returned by the holder of the position in response to a Request for Positions message. The purpose of the message is to acknowledge that a request has been received and is being processed.
AP	PositionReport	PositionReport. The Position Report message is returned by the holder of a position in response to a Request for Position message. The purpose of the message is to report all aspects of a position and may be provided on a standing basis to report end of day positions to an owner.

Code	Name	Description
AQ	TradeCaptureReportRequestAck	TradeCaptureReportRequestAck. The Trade Capture Request Ack message is used to: - Provide an acknowledgement to a Trade Capture Report Request in the case where the Trade Capture Report Request is used to specify a subscription or delivery of reports via an out-of-band ResponseTransmissionMethod. - Provide an acknowledgement to a Trade Capture Report Request in the case when the return of the Trade Capture Reports matching that request will be delayed or delivered asynchronously. This is useful in distributed trading system environments. - Indicate that no trades were found that matched the selection criteria specified on the Trade Capture Report Request or the Trade Capture Request was invalid for some business reason, such as request is not authorized, invalid or unknown instrument, party, trading session, etc.
AR	TradeCaptureReportAck	TradeCaptureReportAck. The Trade Capture Report Ack message can be: - Used to acknowledge trade capture reports received from a counterparty. - Used to reject a trade capture report received from a counterparty.
AS	AllocationReport	AllocationReport. Sent from sell-side to buy-side, sell-side to 3rd-party or 3rd-party to buy-side, the AllocationReport(35=AS) message (Claim) provides account breakdown of an order or set of orders plus any additional follow-up front-office information developed post-trade during the trade allocation, matching and calculation phase.
AT	AllocationReportAck	AllocationReportAck. The Allocation Report Ack message is used to acknowledge the receipt of and provide status for an Allocation Report message.
AU	ConfirmationAck	ConfirmationAck. The Confirmation Ack (aka Affirmation) message is used to respond to a Confirmation message.
AV	SettlementInstructionRequest	SettlementInstructionRequest. The Settlement Instruction Request message is used to request standing settlement instructions from another party.
AW	AssignmentReport	AssignmentReport. Assignment Reports are sent from a clearing house to counterparties, such as a clearing firm as a result of the assignment process.
AX	CollateralRequest	CollateralRequest. An initiator that requires collateral from a respondent sends a Collateral Request. The initiator can be either counterparty to a trade in a two party model or an intermediary such as an ATS or clearinghouse in a three party model. A Collateral Assignment is expected as a response to a request for collateral.

Code	Name	Description
AY	CollateralAssignment	CollateralAssignment. Used to assign collateral to cover a trading position. This message can be sent unsolicited or in reply to a Collateral Request message.
AZ	CollateralResponse	CollateralResponse. Used to respond to a Collateral Assignment message.
BA	CollateralReport	CollateralReport. Used to report collateral status when responding to a Collateral Inquiry message.
BB	CollateralInquiry	CollateralInquiry. Used to inquire for collateral status.
BC	NetworkCounterpartySystemStatus-Request	NetworkCounterpartySystemStatusRequest. This message is send either immediately after logging on to inform a network (counterparty system) of the type of updates required or to at any other time in the FIX conversation to change the nature of the types of status updates required. It can also be used with a NetworkRequestType of Snapshot to request a one-off report of the status of a network (or counterparty) system. Finally this message can also be used to cancel a request to receive updates into the status of the counterparties on a network by sending a NetworkRequestStatusMessage with a NetworkRequestType of StopSubscribing.
BD	NetworkCounterpartySystemStatus-Response	NetworkCounterpartySystemStatusResponse. This message is sent in response to a Network (Counterparty System) Status Request Message.
BE	UserRequest	UserRequest. This message is used to initiate a user action, logon, logout or password change. It can also be used to request a report on a user's status.
BF	UserResponse	UserResponse. This message is used to respond to a user request message, it reports the status of the user after the completion of any action requested in the user request message.
BG	CollateralInquiryAck	CollateralInquiryAck. Used to respond to a Collateral Inquiry in the following situations: • When the CollateralInquiry will result in an out of band response (such as a file transfer). • When the inquiry is otherwise valid but no collateral is found to match the criteria specified on the Collateral Inquiry message. • When the Collateral Inquiry is invalid based upon the business rules of the counterparty.
BH	ConfirmationRequest	ConfirmationRequest. The Confirmation Request message is used to request a Confirmation message.

Code	Name	Description
BO	ContraryIntentionReport	ContraryIntentionReport. The Contrary Intention Report is used for reporting of contrary expiration quantities for Saturday expiring options. This information is required by options exchanges for regulatory purposes.
BP	SecurityDefinitionUpdateReport	SecurityDefinitionUpdateReport. This message is used for reporting updates to a product security master file. Updates could be the result of corporate actions or other business events. Updates may include additions, modifications or deletions.
BK	SecurityListUpdateReport	SecurityListUpdateReport. The Security List Update Report is used for reporting updates to a Contract Security Masterfile. Updates could be due to Corporate Actions or other business events. Update may include additions, modifications and deletions.
BL	AdjustedPositionReport	AdjustedPositionReport. Used to report changes in position, primarily in equity options, due to modifications to the underlying due to corporate actions
BM	AllocationInstructionAlert	AllocationInstructionAlert. This message is used in a 3-party allocation model (buy-side and sell-side using a central clearing entity) where notification of group creation and group updates to counterparties is needed. The message will also carry trade information that comprised the group to the counterparties.
BN	ExecutionAck	ExecutionAck. The Execution Report Acknowledgement message is an optional message that provides dual functionality to notify a trading partner that an electronically received execution has either been accepted or rejected (DK'd).
BJ	TradingSessionList	TradingSessionList. The Trading Session List message is sent as a response to a Trading Session List Request. The Trading Session List should contain the characteristics of the trading session and the current state of the trading session.
BI	TradingSessionListRequest	TradingSessionListRequest. The Trading Session List Request is used to request a list of trading sessions available in a market place and the state of those trading sessions. A successful request will result in a response from the counterparty of a Trading Session List (MsgType=BJ) message that contains a list of zero or more trading sessions.
BQ	SettlementObligationReport	SettlementObligationReport. The Settlement Obligation Report message provides a central counterparty, institution, or individual counterparty with a capacity for reporting the final details of a currency settlement obligation.



Code	Name	Description
BR	DerivativeSecurityListUpdateReport	DerivativeSecurityListUpdateReport. The Derivative Security List Update Report message is used to send updates to an option family or the strikes that comprise an option family.
BS	TradingSessionListUpdateReport	TradingSessionListUpdateReport. The Trading Session List Update Report is used by marketplaces to provide intra-day updates of trading sessions when there are changes to one or more trading sessions.
BT	MarketDefinitionRequest	MarketDefinitionRequest. The Market Definition Request message is used to request for market structure information from the Respondent that receives this request.
BU	MarketDefinition	MarketDefinition. The MarketDefinition(35=BU) message is used to respond to MarketDefinitionRequest(35=BT). In a subscription, it will be used to provide the initial snapshot of the information requested. Subsequent updates are provided by the MarketDefinitionUpdateReport(35=BV).
BV	MarketDefinitionUpdateReport	MarketDefinitionUpdateReport. In a subscription for market structure information, this message is used once the initial snapshot of the information has been sent using the MarketDefinition(35=BU) message.
BW	ApplicationMessageRequest	ApplicationMessageRequest. This message is used to request a retransmission of a set of one or more messages generated by the application specified in RefApplID (1355).
BX	ApplicationMessageRequestAck	ApplicationMessageRequestAck. This message is used to acknowledge an Application Message Request providing a status on the request (i.e. whether successful or not). This message does not provide the actual content of the messages to be resent.
BY	ApplicationMessageReport	ApplicationMessageReport. This message is used for three difference purposes: to reset the ApplSeqNum (1181) of a specified ApplID (1180). to indicate that the last message has been sent for a particular ApplID, or as a keep-alive mechanism for ApplIDs with infrequent message traffic.
BZ	OrderMassActionReport	OrderMassActionReport. The Order Mass Action Report is used to acknowledge an Order Mass Action Request. Note that each affected order that is suspended or released or canceled is acknowledged with a separate Execution Report for each order.
CA	OrderMassActionRequest	OrderMassActionRequest. The Order Mass Action Request message can be used to request the suspension or release of a group of orders that match the criteria specified within the request. This is equivalent to individual Order Cancel Replace Requests for each order with or without adding "S" to the ExecInst values. It can also be used for mass order cancellation.

Code	Name	Description
CB	UserNotification	UserNotification. The User Notification message is used to notify one or more users of an event or information from the sender of the message. This message is usually sent unsolicited from a marketplace (e.g. Exchange, ECN) to a market participant.
CC	StreamAssignmentRequest	StreamAssignmentRequest. In certain markets where market data aggregators fan out to end clients the pricing streams provided by the price makers, the price maker may assign the clients to certain pricing streams that the price maker publishes via the aggregator. An example of this use is in the FX markets where clients may be assigned to different pricing streams based on volume bands and currency pairs.
CD	StreamAssignmentReport	StreamAssignmentReport. The StreamAssignmentReport(35=CD) message is in response to the StreamAssignmentRequest(35=CC) message. It provides information back to the aggregator as to which clients to assign to receive which price stream based on requested CCY pair. This message can be sent unsolicited to the Aggregator from the Price Maker.
CE	StreamAssignmentReportACK	StreamAssignmentReportACK. This message is used to respond to the Stream Assignment Report, to either accept or reject an unsolicited assingment.
CF	PartyDetailsListRequest	PartyDetailsListRequest. The PartyDetailsListRequest is used to request party detail information.
CG	PartyDetailsListReport	PartyDetailsListReport. The PartyDetailsListReport message is used to disseminate party details between counterparties. PartyDetailsListReport messages may be sent in response to a PartyDetailsListRequest message or sent unsolicited.

Code	Name	Description
CH	MarginRequirementInquiry	MarginRequirementInquiry. The purpose of this message is to initiate a margin requirement inquiry for a margin account. The inquiry may be submitted at the detail level or the summary level. It can also be used to inquire margin excess/deficit or net position information. Margin excess/deficit will provide information about the surplus or shortfall compared to the previous trading day or a more recent margin calculation. An inquiry for net position information will trigger one or more PositionReport messages instead of one or more MarginRequirementReport messages. If the inquiry is made at the detail level, an Instrument block must be provided with the desired level of detail. If the inquiry is made at the summary level, the Instrument block is not provided, implying a summary request is being made. For example, if the inquiring firm specifies the Security Type of "FUT" in the Instrument block, then a detail report will be generated containing the margin requirements for all futures positions for the inquiring account. Similarly, if the inquiry is made at the summary level, the report will contain the total margin requirement aggregated to the margin account level.
CI	MarginRequirementInquiryAck	MarginRequirementInquiryAck. Used to respond to a Margin Requirement Inquiry.
CJ	MarginRequirementReport	MarginRequirementReport. The Margin Requirement Report returns information about margin requirement either as an overview across all margin accounts or on a detailed level due to the inquiry making use of the optional Instrument component block. Application sequencing can be used to re-request a range of reports.
CK	PartyDetailsListUpdateReport	PartyDetailsListUpdateReport. The PartyDetailsListUpdateReport(35=CK) is used to disseminate updates to party detail information.
CL	PartyRiskLimitsRequest	PartyRiskLimitsRequest. The PartyRiskLimitsRequest message is used to request for risk information for specific parties, specific party roles or specific instruments.
CM	PartyRiskLimitsReport	PartyRiskLimitsReport. The PartyRiskLimitsReport message is used to communicate party risk limits. The message can either be sent as a response to the PartyRiskLimitsRequest message or can be published unsolicited.
CN	SecurityMassStatusRequest	SecurityMassStatusRequest.
CO	SecurityMassStatus	SecurityMassStatus.

Code	Name	Description
CQ	AccountSummaryReport	AccountSummaryReport. The AccountSummaryReport is provided by the clearinghouse to its clearing members on a daily basis. It contains margin, settlement, collateral and pay/collect data for each clearing member level account type. Clearing member account types will be described through use of the Parties component and PtysSubGrp sub-component. In certain usages, the clearing members can send the AccountSummaryReport message to the clearinghouse as needed. For example, clearing members can send this message to the clearinghouse to identify the value of collateral for each customer (to satisfy CFTC Legally Segregated Operationally Commingled (LSOC) regulatory reporting obligations). Clearing organizations can also send the AccountSummaryReport message to regulators to meet regulatory reporting obligations. For example, clearing organizations can use this message to submit daily reports for each clearing member ("CM") by house origin and by each customer origin for all futures, options, and swaps positions, and all securities positions held in a segregated account or pursuant to a cross margining agreement, to a regulator (e.g. to the CFTC to meet Part 39, Section 39.19 reporting obligations).
CR	PartyRiskLimitsUpdateReport	PartyRiskLimitsUpdateReport. The PartyRiskLimitsUpdateReport(35=CR) is used to convey incremental changes to risk limits. It is similar to the regular report but uses the PartyRiskLimitsUpdateGrp component instead of the PartyRiskLimitsGrp component to include an update action.
CS	PartyRiskLimitsDefinitionRequest	PartyRiskLimitsDefinitionRequest. PartyRiskLimitDefinitionRequest is used for defining new risk limits.
CT	PartyRiskLimitsDefinitionRequestAck	PartyRiskLimitsDefinitionRequestAck. PartyRiskLimitDefinitionRequestAck is used for accepting (with or without changes) or rejecting the definition of risk limits.
CU	PartyEntitlementsRequest	PartyEntitlementsRequest. The PartyEntitlementsRequest message is used to request for entitlement information for one or more party(-ies), specific party role(s), or specific instruments(s).
CV	PartyEntitlementsReport	PartyEntitlementsReport. The PartyEntitlementsReport is used to report entitlements for one or more parties, party role(s), or specific instrument(s).

Code	Name	Description
CW	QuoteAck	QuoteAck. The QuoteAck(35=CW) message is used to acknowledge a Quote(35=S) submittal or request to cancel an individual quote using the QuoteCancel(35=Z) message during a Quote/Negotiation dialog.
CX	PartyDetailsDefinitionRequest	PartyDetailsDefinitionRequest. The PartyDetailsDefinitionRequest(35=CX) is used for defining new parties and modifying or deleting existing parties information, including the relationships between parties. The recipient of the message responds with a PartyDetailsDefinitionRequestAck(35=CY) to indicate whether the request was accepted or rejected.
CY	PartyDetailsDefinitionRequestAck	PartyDetailsDefinitionRequestAck. The PartyDetailsDefinitionRequestAck(35=CY) is used as a response to the PartyDetailsDefinitionRequest(35=CX) message. The request can be accepted (with or without changes) or rejected.
CZ	PartyEntitlementsUpdateReport	PartyEntitlementsUpdateReport. The PartyEntitlementsUpdateReport(35=CZ) is used to convey incremental changes to party entitlements. It is similar to the PartyEntitlementsReport(35=CV). This message uses the PartyEntitlementsUpdateGrp component which includes the ability to specify an update action using ListUpdateAction(1324).
DA	PartyEntitlementsDefinitionRequest	PartyEntitlementsDefinitionRequest. The PartyEntitlementsDefinitionRequest(35=DA) is used for defining new entitlements, and modifying or deleting existing entitlements for the specified party(-ies).
DB	PartyEntitlementsDefinitionRequestAck	PartyEntitlementsDefinitionRequestAck. The PartyEntitlementsDefinitionRequestAck(35=DB) is used as a response to the PartyEntitlementsDefinitionRequest(35=DA) to accept (with or without changes) or reject the definition of party entitlements.
DC	TradeMatchReport	TradeMatchReport. The TradeMatchReport(35=DC) message is used by exchanges and ECN's to report matched trades to central counterparties (CCPs) as an atomic event. The message is used to express the one-to-one, one-to-many and many-to-many matches as well as implied matches in which more complex instruments can match with simpler instruments.
DD	TradeMatchReportAck	TradeMatchReportAck. The TradeMatchReportAck(35=DD) is used to respond to the TradeMatchReport(35=DC) message. It may be used to report on the status of the request (e.g. accepting the request or rejecting the request).

Code	Name	Description
DE	PartyRiskLimitsReportAck	PartyRiskLimitsReportAck. PartyRiskLimitsReportAck is an optional message used as a response to the PartyRiskLimitReport(35=CM) or PartyRiskLimitUpdateReport(35=CR) messages to acknowledge or reject those messages.
DF	PartyRiskLimitCheckRequest	PartyRiskLimitCheckRequest. PartyRiskLimitCheckRequest is used to request for approval of credit or risk limit amount intended to be used by a party in a transaction from another party that holds the information.
DG	PartyRiskLimitCheckRequestAck	PartyRiskLimitCheckRequestAck. PartyRiskLimitCheckRequestAck is used to acknowledge a PartyRiskLimitCheckRequest(35=DF) message and to respond whether the limit check request was approved or not. When used to accept the PartyRiskLimitCheckRequest(35=DF) message the Respondent may also include the limit amount that was approved.
DH	PartyActionRequest	PartyActionRequest. The PartyActionRequest message is used suspend or halt the specified party from further trading activities at the Respondent. The Respondent must respond with a PartyActionReport(35=DI) message.
DI	PartyActionReport	PartyActionReport. Used to respond to the PartyActionRequest(35=DH) message, indicating whether the request has been received, accepted or rejected. Can also be used in an unsolicited manner to report party actions, e.g. reinstatements after a manual intervention out of band.
DJ	MassOrder	MassOrder. The MassOrder(35=DJ) message can be used to add, modify or delete multiple unrelated orders with a single message. Apart from clearing related attributes, only the key order attributes for high performance trading are available.
DK	MassOrderAck	MassOrderAck. The mass order acknowledgement message is used to acknowledge the receipt of and the status for a MassOrder(35=DJ) message.
DL	PositionTransferInstruction	PositionTransferInstruction. The PositionTransferInstruction(35=DL) is sent by clearing firms to CCPs to initiate position transfers, or to accept or decline position transfers.
DM	PositionTransferInstructionAck	PositionTransferInstructionAck. The PositionTransferInstructionAck(35=DM) is sent by CCPs to clearing firms to acknowledge position transfer instructions, and to report errors processing position transfer instructions.

Code	Name	Description
DN	PositionTransferReport	PositionTransferReport. The PositionTransferReport(35=DN) is sent by CCPs to clearing firms indicating of positions that are to be transferred to the clearing firm, or to report on status of the transfer to the clearing firms involved in the transfer process.
DO	MarketDataStatisticsRequest	MarketDataStatisticsRequest. The MarketDataStatisticsRequest(35=DO) is used to request for statistical data. The simple form is to use an identifier (MDStatisticID(2475)) assigned by the market place which would denote a pre-defined statistical report. Alternatively, or also in addition, the request can define a number of parameters for the desired statistical information.
DP	MarketDataStatisticsReport	MarketDataStatisticsReport. The MarketDataStatisticsReport(35=DP) is used to provide unsolicited statistical information or in response to a specific request. Each report contains a set of statistics for a single entity which could be a market, a market segment, a security list or an instrument.
DQ	CollateralReportAck	CollateralReportAck. CollateralReportAck(35=DQ) is used as a response to the CollateralReport(35=BA). It can be used to reject a CollateralReport(35=BA) when the content of the report is invalid based on the business rules of the receiver. The message may also be used to acknowledge receipt of a valid CollateralReport(35=BA).
DR	MarketDataReport	MarketDataReport. The MarketDataReport(35=DR) message is used to provide delimiting references (e.g. start and end markers in a continuous broadcast) and details about the number of market data messages sent in a given distribution cycle.
DS	CrossRequest	CrossRequest. The CrossRequest(35=DS) message is used to indicate the submission of orders or quotes that may result in a crossed trade.
DT	CrossRequestAck	CrossRequestAck. The CrossRequestAck(35=DT) message is used to confirm the receipt of a CrossRequest(35=DS) message.
DU	AllocationInstructionAlertRequest	AllocationInstructionAlertRequest. This message is used in a clearinghouse 3-party allocation model to request for AllocationInstructionAlert(35=BM) from the clearinghouse. The request may be used to obtain a one-time notification of the status of an allocation group.

Code	Name	Description
DV	AllocationInstructionAlertRequestAck	AllocationInstructionAlertRequestAck. This message is used in a clearinghouse 3-party allocation model to acknowledge a AllocationInstructionAlertRequest(35=DU) message for an AllocationInstructionAlert(35=BM) message from the clearinghouse.
DW	TradeAggregationRequest	TradeAggregationRequest. TradeAggregationRequest(35=DW) is used to request that the identified trades between the initiator and respondent be aggregated together for further processing.
DX	TradeAggregationReport	TradeAggregationReport. TradeAggregationReport(35=DX) is used to respond to the TradeAggregationRequest(35=DW) message. It provides the status of the request (e.g. accepted or rejected) and may also provide additional information supplied by the respondent.
EA	PayManagementReport	PayManagementReport. PayManagementReport(35=EA) may be used to respond to the PayManagementRequest(35=DY) message. It provides the status of the request (e.g. accepted, disputed) and may provide additional information related to the request. PayManagementReport(35=EA) may also be sent unsolicited by the broker to a client. In which case the client may acknowledge and resolve disputes out-of-band or with a simple PayManagementReportAck(35=EB). PayManagementReport(35=EA) may also be sent unsolicited to report the progress status of the payment itself with PayReportTransType(2804)=2 (Status).
EB	PayManagementReportAck	PayManagementReportAck. PayManagementReportAck(35=EB) is used as a response to the PayManagementReport(35=EA) message. It may be used to accept, reject or dispute the details of the PayManagementReport(35=EA) depending on the business rules of the receiver. This message may also be used to acknowledge the receipt of a PayManagementReport(35=EA) message.
DY	PayManagementRequest	PayManagementRequest. PayManagementRequest(35=DY) message is used to communicate a future or expected payment to be made or received related to a trade or contract after its settlement.
DZ	PayManagementRequestAck	PayManagementRequestAck. PayManagementRequestAck(35=DZ) is used to acknowledge the receipt of the PayManagementRequest(35=DY) message (i.e. a technical acknowledgement of receipt). Acceptance or rejection of the request is reported in the corresponding PayManagementReport(35=EA).



Code	Name	Description
EC	SettlementStatusRequest	SettlementStatusRequest. SettlementStatusRequest(35=EC) is used to request for the settlement status of a trade.
ED	SettlementStatusRequestAck	SettlementStatusRequestAck. SettlementStatusRequestAck(35=ED) is used to respond to the SettlementStatusRequest(35=EC) to acknowledge the request and provide status for the request message.
EE	SettlementStatusReport	SettlementStatusReport. SettlementStatusReport(35=EE) is a response to the SettlementStatusRequest(35=EC) to provide settlement status for the requested trade. It may also be sent unsolicited without an explicit request message by the party able to provide the settlement status for the trade identified in the report message.
EF	SettlementStatusReportAck	SettlementStatusReportAck. SettlementStatusReportAck(35=EF) is used to respond to the SettlementStatusReport(35=EE) to acknowledge or reject the report.
EG	SecurityRiskMetricsReport	SecurityRiskMetricsReport. SecurityRiskMetricsReport(35=EG) is used for publishing the risk metrics, valuation metrics or analytics of one or more securities, or for an option series.
EH	AlgoCertificateRequest	AlgoCertificateRequest. AlgoCertificateRequest(35=EH) is used to request algo testing certificate information for one or more algorithms.
EI	AlgoCertificateRequestAck	AlgoCertificateRequestAck. AlgoCertificateRequestAck(35=EI) is used to respond to the AlgoCertificateRequest(35=EH) to acknowledge the request and provide status for the request message.
EJ	AlgoCertificateReport	AlgoCertificateReport. AlgoCertificateReport(35=EJ) is a response to the AlgoCertificateRequest(35=EH) to certify an algo. It may also be sent unsolicited without an explicit request message by the party able to provide certificate information for the algo identified in the report message.
EK	AlgoCertificateReportAck	AlgoCertificateReportAck. AlgoCertificateReportAck(35=EK) is used to respond to the AlgoCertificateReport(35=EJ) to acknowledge or reject the report message.
EL	TestSuiteDefinitionRequest	TestSuiteDefinitionRequest. TestSuiteDefinitionRequest(35=EL) is used to convey to the test system the suite of test scenarios to perform.
EM	TestSuiteDefinitionRequestAck	TestSuiteDefinitionRequestAck. TestSuiteDefinitionRequestAck(35=EM) is used to respond to the TestSuiteDefinitionRequest(35=EL) to acknowledge the request and provide status for the request message.

Code	Name	Description
EN	TestActionRequest	TestActionRequest. TestActionRequest(35=EN) is used to manage test executions or request for testing activity state of the identified test suite.
EO	TestActionRequestAck	TestActionRequestAck. TestActionRequestAck(35=EO) is used to respond to the TestActionRequest(35=EN) to acknowledge the request and provide status for the request message.
EP	TestActionReport	TestActionReport. TestActionReport(35=EP) is used to report the testing results of the identified test suite that has been executed with TestActionRequest(35=EN). In the context of algorithmic trading, the results may be used to create a certificate for the algorithm upon meeting the success criteria.

Used in components: [StandardHeader](#)

### 180.2.2939 MsgTypeGrp

Name	Mult.	Type	Description
NoMsgTypes	[1..1]	NumInGroup	Specifies the number of repeating RefMsgTypes specified
RefMsgType	[0..1]	CodeSet	Specifies a specific, supported MsgType. Required if NoMsgTypes is > 0. Should be specified from the point of view of the sender of the Logon message
MsgDirection	[0..1]	CodeSet	Indicates direction (send vs. receive) of a supported MsgType. Required if NoMsgTypes is > 0. Should be specified from the point of view of the sender of the Logon message
RefApplVerID	[0..1]	CodeSet	Specifies the service pack release being applied to an application message.
RefApplExtID	[0..1]	int	Specified the extension pack being applied to a message.
RefCstmApplVerID	[0..1]	String	Specifies a custom extension to a message being applied at the session level.
DefaultVerIndicator	[0..1]	Boolean	Indicates that this Application Version (RefApplVerID(1130), RefApplExtID(1406),RefCstmApplVerID(1131)) is the default for the RefMsgType(372) field.

Used in messages: [Logon](#)

**180.2.2940 MthToDefault**

The Mth reference obligation to default in a CDS reference basket. When NthToDefault(1942) and MthToDefault(1943) are represented then the CDS payout occurs between the Nth and Mth obligations to default.

Type: **int**

Used in components: **Instrument**

**180.2.2941 MultiAssetSwapIndicator**

Indicates a swap that does not have one easily identifiable primary underlying asset, but instead involves multiple underlying assets within one trade repository's jurisdiction that belong to different asset classes.

Type: **Boolean**

Used in messages: **TradeCaptureReport**

**180.2.2942 MultiJurisdictionReportingIndicator**

Indicate whether a trade is eligible to be reported to more than one regulatory jurisdictions, e.g. due to overlapping reporting rules that require reporting to different jurisdictions.

Type: **int**

Allowed values in MultiJurisdictionReportingIndicatorCodeSet:

Code	Name	Description
0	NotMultiJrsdctnEligible	Trade not eligible for multi-jurisdiction reporting
1	MultiJrsdctnEligible	Trade eligible for multi-jurisdiction reporting

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **TradeCaptureReport**

**180.2.2943 MultilegModel**

Specifies the type of multileg order. Defines whether the security is pre-defined or user-defined. Note that MultilegModel(1377)=2(User-defined, Non-Securitized, Multileg) does not apply for Securities.

Type: **int**

Allowed values in MultilegModelCodeSet:

Code	Name	Description
0	PredefinedMultilegSecurity	Predefined Multileg Security
1	UserDefinedMultilegSecurity	User-defined Multileg Security
2	UserDefined	User-defined, Non-Securitized, Multileg

Used in components: **BaseTradingRules**

Used in messages: **MultilegOrderCancelReplace**, **NewOrderMultileg**

#### **180.2.2944 MultilegPriceMethod**

Code to represent how the multileg price is to be interpreted when applied to the legs.

(See Volume : "Glossary" for further value definitions)

Type: **int**

Allowed values in MultilegPriceMethodCodeSet:

Code	Name	Description
0	NetPrice	Net Price
1	ReversedNetPrice	Reversed Net Price
2	YieldDifference	Yield Difference
3	Individual	Individual
4	ContractWeightedAveragePrice	Contract Weighted Average Price
5	MultipliedPrice	Multiplied Price

Used in components: **BaseTradingRules**

Used in messages: **MultilegOrderCancelReplace**, **NewOrderMultileg**

#### **180.2.2945 MultiLegReportingType**

Used to indicate how the multi-legged security (e.g. option strategies, spreads, etc.) is being reported.

Type: **char**

Allowed values in MultiLegReportingTypeCodeSet:

Code	Name	Description
1	SingleSecurity	Single security (default if not specified)
2	IndividualLegOfAMultiLegSecurity	Individual leg of a multi-leg security
3	MultiLegSecurity	Multi-leg security

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [ExecutionReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#), [TradeCaptureReportRequestAck](#), [TradeMatchReport](#)

### 180.2.2946 MultiLegRptTypeReq

Indicates the method of execution reporting requested by issuer of the order.

Type: [int](#)

Allowed values in MultiLegRptTypeReqCodeSet:

Code	Name	Description
0	ReportByMultilegSecurityOnly	Report by multileg security only (do not report legs)
1	ReportByMultilegSecurityAndInstrumentLegs	Report by multileg security and by instrument legs belonging to the multileg security
2	ReportByInstrumentLegsOnly	Report by instrument legs belonging to the multileg security only (do not report status of multileg security)

Used in messages: [MultilegOrderCancelReplace](#), [NewOrderMultileg](#)

### 180.2.2947 NBBOEntryType

Type of NBBO information.

Type: [int](#)

Allowed values in NBBOEntryTypeCodeSet:

Code	Name	Description
0	Bid	Bid. May apply to price or quantity.
1	Offer	Offer. May apply to price or quantity.
2	MidPrice	Mid-price

Used in groups: **TrdRegTimestamps**

#### **180.2.2948 NBBOPrice**

Price related to NBBO. NBBOEntryType(2831) may be used to indicate entry type, e.g. bid or offer.

Type: **Price**

Used in groups: **TrdRegTimestamps**

#### **180.2.2949 NBBOQty**

Quantity related to NBBO. NBBOEntryType(2831) may be used to indicate entry type, e.g. bid or offer.

Type: **Qty**

Used in groups: **TrdRegTimestamps**

#### **180.2.2950 NBBOSource**

Source of NBBO information.

Type: **int**

Allowed values in NBBOSourceCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Default if not specified. NBBO information is not applicable. NBBOEntryType(2831), NBBOPrice(2832), and NBBOQty(2833) must be omitted.
1	Direct	Direct. Information is retrieved directly from an exchange or other electronic execution venue. There may be a performance advantage compared to retrieving the information from a source consolidating multiple feeds.

Code	Name	Description
2	SIP	Securities Information Processor. The Securities Information Processor (SIP) links the U.S. markets by processing and consolidating all protected bid/ask quotes and trades from every trading venue into a single, easily consumed data feed.
3	Hybrid	Hybrid. A combination of two or more data feeds is used as NBBO source. In the context of US CAT this is used for a combination of direct and SIP feeds.

Used in groups: **TrdRegTimestamps**

### 180.2.2951 NegotiationMethod

Specifies the negotiation method to be used.

Type: **int**

Allowed values in NegotiationMethodCodeSet:

Code	Name	Description
0	AutoSpot	Auto spot. The spot price for the reference or benchmark security is provided automatically.
1	NegotiatedSpot	Negotiated spot. The spot price for the reference or benchmark security is to be negotiated.
2	PhoneSpot	The spot price for the reference or benchmark security is to be negotiated via phone or voice. The spot price for the reference of benchmark security is to be negotiated via phone or voice.

Used in groups: **QuotReqGrp**, **QuotReqRjctGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

### 180.2.2952 Nested2PartyID

PartyID value within a "second instance" Nested repeating group.

Same values as PartyID (448)

Type: **String**

Used in groups: **NestedParties2**

**180.2.2953 Nested2PartyIDSource**

PartyIDSource value within a "second instance" Nested repeating group.

Same values as PartyIDSource (447)

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)



Code	Name	Description
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **NestedParties2**

#### 180.2.2954 Nested2PartyRole

PartyRole value within a "second instance" Nested repeating group.

Same values as PartyRole (452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary

Code	Name	Description
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator

Code	Name	Description
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm

Code	Name	Description
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor

Code	Name	Description
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: [NestedParties2](#)

**180.2.2955 Nested2PartyRoleQualifier**

Used to further qualify the value of Nested2PartyRole(759).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange

Code	Name	Description
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: [NestedParties2](#)

#### 180.2.2956 Nested2PartySubID

PartySubID value within a "second instance" Nested repeating group.

Same values as PartySubID (523)

Type: [String](#)

Used in groups: [NstdPtys2SubGrp](#)



**180.2.2957 Nested2PartySubIDType**

Type of Nested2PartySubID (760) value. Second instance of <NestedParties>.

Same values as PartySubIDType (803)

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type

Code	Name	Description
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.

Code	Name	Description
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **NstdPtys2SubGrp**

**180.2.2958 Nested3PartyID**

PartyID value within a "third instance" Nested repeating group.

Same values as PartyID (448)

Type: **String**

Used in groups: **NestedParties3**

**180.2.2959 Nested3PartyIDSource**

PartyIDSource value within a "third instance" Nested repeating group.

Same values as PartyIDSource (447)

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code

Code	Name	Description
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.



Code	Name	Description
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **NestedParties3**

### 180.2.2960 Nested3PartyRole

PartyRole value within a "third instance" Nested repeating group.

Same values as PartyRole (452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System

Code	Name	Description
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account

Code	Name	Description
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market

Code	Name	Description
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.

Code	Name	Description
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.

Code	Name	Description
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **NestedParties3**

### 180.2.2961 Nested3PartyRoleQualifier

Used to further qualify the value of Nested3PartyRole(951).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.

Code	Name	Description
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.

Code	Name	Description
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **NestedParties3**

#### **180.2.2962 Nested3PartySubID**

PartySubID value within a "third instance" Nested repeating group.

Same values as PartySubID (523)

Type: **String**

Used in groups: **NstdPtys3SubGrp**

#### **180.2.2963 Nested3PartySubIDType**

PartySubIDType value within a "third instance" Nested repeating group.

Same values as PartySubIDType (803)

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm



Code	Name	Description
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)

Code	Name	Description
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier

Code	Name	Description
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C = Credit institution authorized in accordance with Directive 2006/48/EC F = Investment firm in accordance with Directive 2004/39/EC I = Insurance undertaking authorized in accordance with Directive 73/239/EC L = Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O = Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R = Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U = UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N

Code	Name	Description
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.

Code	Name	Description
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI

Code	Name	Description
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **NstdPtys3SubGrp**

#### 180.2.2964 Nested4PartyID

Refer to definition of PartyID(448)

Type: **String**

Used in groups: **NestedParties4**

#### 180.2.2965 Nested4PartyIDSource

Refer to definition of PartyIDSource(447)

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number

Code	Name	Description
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.

Code	Name	Description
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **NestedParties4**

### 180.2.2966 Nested4PartyRole

Refer to definition of PartyRole(452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID



Code	Name	Description
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader

Code	Name	Description
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm

Code	Name	Description
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm

Code	Name	Description
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.

Code	Name	Description
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **NestedParties4**

#### 180.2.2967 Nested4PartyRoleQualifier

Used to further qualify the value of Nested4PartyRole(1417).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.

Code	Name	Description
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: [NestedParties4](#)

#### **180.2.2968 Nested4PartySubID**

Refer to definition of PartySubID(523)

Type: [String](#)

Used in groups: [NstdPtys4SubGrp](#)

#### **180.2.2969 Nested4PartySubIDType**

Refer to definition of PartySubIDType(803)

Type: [int](#)

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier



Code	Name	Description
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account

Code	Name	Description
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **NstdPtys4SubGrp**

**180.2.2970 NestedInstrAttribType**

Code to represent the type of instrument attribute

Type: **int**

Allowed values in InstrAttribTypeCodeSet:

Code	Name	Description
1	Flat	Flat (securities pay interest on a current basis but are traded without interest)
2	ZeroCoupon	Zero coupon
3	InterestBearing	Interest bearing (for Euro commercial paper when not issued at discount)
4	NoPeriodicPayments	No periodic payments
5	VariableRate	Variable rate
6	LessFeeForPut	Less fee for put
7	SteppedCoupon	Stepped coupon
8	CouponPeriod	Coupon period (if not semi-annual). Supply redemption date in the InstrAttribValue(872) field.
9	When	When [and if] issued
10	OriginalIssueDiscount	Original issue discount
11	Callable	Callable, puttable
12	EscrowedToMaturity	Escrowed to Maturity
13	EscrowedToRedemptionDate	Escrowed to redemption date - callable. Supply redemption date in the InstrAttribValue(872) field.
14	PreRefunded	Pre-refunded
15	InDefault	In default
16	Unrated	Unrated
17	Taxable	Taxable
18	Indexed	Indexed
19	SubjectToAlternativeMinimumTax	Subject To Alternative Minimum Tax
20	OriginalIssueDiscountPrice	Original issue discount price. Supply price in the InstrAttribValue(872) field.
21	CallableBelowMaturityValue	Callable below maturity value
22	CallableWithoutNotice	Callable without notice by mail to holder unless registered
23	PriceTickRulesForSecurity	Price tick rules for security
24	TradeTypeEligibilityDetailsForSecurity	Trade type eligibility details for security

Code	Name	Description
25	InstrumentDenominator	Instrument denominator
26	InstrumentNumerator	Instrument numerator
27	InstrumentPricePrecision	Instrument price precision
28	InstrumentStrikePrice	Instrument strike price
29	TradeableIndicator	Tradeable indicator
30	InstrumentEligibleAnonOrders	Instrument is eligible to accept anonymous orders
31	MinGuaranteedFillVolume	Minimum guaranteed fill volume
32	MinGuaranteedFillStatus	Minimum guaranteed fill status
33	TradeAtSettlementEligibility	Trade at settlement (TAS) eligibility
34	TestInstrument	Test instrument. Instrument that is tradable but has no effect on the positions, exchange turnover etc.
35	DummyInstrument	Dummy instrument. Instrument that is normally halted and is only activated for trading under very special conditions (e.g. temporarily assigned for newly listed instrument). Use of a dummy instrument generally applies to systems that are unable to add reference data for new instruments intraday.
36	NegativeSettlementPriceEligibility	Negative settlement price eligibility
37	NegativeStrikePriceEligibility	Negative strike price eligibility
38	USStdContractInd	US standard contract indicator. Indicates through InstrAttribValue(872) - values Y or N - whether the underlying asset in the trade references or is economically related to a contract listed in Appendix B of CFTC Part 43 regulation. See <a href="http://www.ecfr.gov/cgi-bin/text-idx?SID=4b2d1078ad68f6564a89d7ff6c52ec43&amp;node=17:2.0.1.1.3.0.1.8.2&amp;rgn=div">http://www.ecfr.gov/cgi-bin/text-idx?SID=4b2d1078ad68f6564a89d7ff6c52ec43&amp;node=17:2.0.1.1.3.0.1.8.2&amp;rgn=div</a> or refer to Appendix B to Part 43 in the final rule at <a href="http://www.cftc.gov/ucm/groups/public/@lrfederalregister/documents/file/2013-12133a.pdf">http://www.cftc.gov/ucm/groups/public/@lrfederalregister/documents/file/2013-12133a.pdf</a>
39	AdmittedToTradingOnTradingVenue	Admitted to trading on a trading venue
40	AverageDailyNotionalAmount	Average daily notional amount
41	AverageDailyNumberTrades	Average daily number of trades
99	Text	Text. Supply the text value in InstrAttribValue(872).

Used in groups: **NestedInstrumentAttribute**

## 180.2.2971 NestedInstrAttribValue

Attribute value appropriate to the NestedInstrAttribType field

Type: **String**

Used in groups: **NestedInstrumentAttribute**

### 180.2.2972 NestedInstrumentAttribute

Name	Mult.	Type	Description
NoNestedInstrAttrib	[1..1]	NumInGroup	
NestedInstrAttribType	[0..1]	CodeSet	Code to represent the type of instrument attribute
NestedInstrAttribValue	[0..1]	String	Attribute value appropriate to the NestedInstrAttribType field

Used in components: **SecurityTradingRules**

### 180.2.2973 NestedParties2

The NestedParties2 component block is identical to the Parties Block. It is used in other component blocks and repeating groups when nesting will take place resulting in multiple occurrences of the Parties block within a single FIX message. Use of NestedParties2 under these conditions avoids multiple references to the Parties block within the same message which is not allowed in FIX tag/value syntax.

Name	Mult.	Type	Description
NoNested2PartyIDs	[1..1]	NumInGroup	Repeating group below should contain unique combinations of Nested2PartyID, Nested2PartyIDSource, and Nested2PartyRole
Nested2PartyID	[0..1]	String	Used to identify source of Nested2PartyID. Required if Nested2PartyIDSource is specified. Required if NoNested2PartyIDs > 0.
Nested2PartyIDSource	[0..1]	CodeSet	Used to identify class source of Nested2PartyID value (e.g. BIC). Required if Nested2PartyID is specified. Required if NoNested2PartyIDs > 0.
Nested2PartyRole	[0..1]	CodeSet	Identifies the type of Nested2PartyID (e.g. Executing Broker). Required if NoNested2PartyIDs > 0.
Nested2PartyRoleQualifier	[0..1]	CodeSet	
NstdPtys2SubGrp	[0..*]	Group	Repeating group of Nested2Party sub-identifiers.

Used in groups: **LegPreAllocGrp**, **OrdAllocGrp**, **TrdAllocGrp**



**180.2.2974 NestedParties3**

The NestedParties3 component block is identical to the Parties Block. It is used in other component blocks and repeating groups when nesting will take place resulting in multiple occurrences of the Parties block within a single FIX message. Use of NestedParties3 under these conditions avoids multiple references to the Parties block within the same message which is not allowed in FIX tag/value syntax.

Name	Mult.	Type	Description
NoNested3PartyIDs	[1..1]	NumInGroup	Repeating group below should contain unique combinations of Nested3PartyID, Nested3PartyIDSource, and Nested3PartyRole
Nested3PartyID	[0..1]	String	Used to identify source of Nested3PartyID. Required if Nested3PartyIDSource is specified. Required if NoNested3PartyIDs > 0.
Nested3PartyIDSource	[0..1]	CodeSet	Used to identify class source of Nested3PartyID value (e.g. BIC). Required if Nested3PartyID is specified. Required if NoNested3PartyIDs > 0.
Nested3PartyRole	[0..1]	CodeSet	Identifies the type of Nested3PartyID (e.g. Executing Broker). Required if NoNested3PartyIDs > 0.
Nested3PartyRoleQualifier	[0..1]	CodeSet	
NstdPtys3SubGrp	[0..*]	Group	Repeating group of Nested3Party sub-identifiers.

Used in groups: InstrmtLegExecGrp, PreAllocMlegGrp, SideCrossLegGrp, TrdInstrmtLegExecGrp

**180.2.2975 NestedParties4**

The NestedParties4 component block is identical to the Parties Block. It is used in other component blocks and repeating groups when nesting will take place resulting in multiple occurrences of the Parties block within a single FIX message. Use of NestedParties4 under these conditions avoids multiple references to the Parties block within the same message which is not allowed in FIX tag/value syntax.

Name	Mult.	Type	Description
NoNested4PartyIDs	[1..1]	NumInGroup	Repeating group below should contain unique combinations of Nested4PartyID, Nested4PartyIDSource, and Nested4PartyRole.

Name	Mult.	Type	Description
Nested4PartyID	[0..1]	String	Used to identify source of Nested4PartyID. Required if Nested4PartyIDSource is specified. Required if NoNested4PartyIDs > 0.
Nested4PartyIDSource	[0..1]	CodeSet	Used to identify class source of Nested4PartyID value (e.g. BIC). Required if Nested4PartyID is specified. Required if NoNested4PartyIDs > 0.
Nested4PartyRole	[0..1]	CodeSet	Identifies the type of Nested4PartyID (e.g. Executing Broker). Required if NoNested4PartyIDs > 0.
Nested4PartyRoleQualifier	[0..1]	CodeSet	
NstdPtys4SubGrp	[0..*]	Group	

Used in groups: [FillsGrp](#)

### 180.2.2976 NestedParties

The NestedParties component block is identical to the Parties Block. It is used in other component blocks and repeating groups when nesting will take place resulting in multiple occurrences of the Parties block within a single FIX message. Use of NestedParties under these conditions avoids multiple references to the Parties block within the same message which is not allowed in FIX tag/value syntax.

Name	Mult.	Type	Description
NoNestedPartyIDs	[1..1]	NumInGroup	Repeating group below should contain unique combinations of NestedPartyID, NestedPartyIDSource, and NestedPartyRole
NestedPartyID	[0..1]	String	Used to identify source of NestedPartyID. Required if NestedPartyIDSource is specified. Required if NoNestedPartyIDs > 0.
NestedPartyIDSource	[0..1]	CodeSet	Used to identify class source of NestedPartyID value (e.g. BIC). Required if NestedPartyID is specified. Required if NoNestedPartyIDs > 0.
NestedPartyRole	[0..1]	CodeSet	Identifies the type of NestedPartyID (e.g. Executing Broker). Required if NoNestedPartyIDs > 0.
NestedPartyRoleQualifier	[0..1]	CodeSet	
NstdPtysSubGrp	[0..*]	Group	Repeating group of NestedParty sub-identifiers.

Used in components: [MDStatisticParameters](#), [SettlTradeDetails](#)

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [ApplIDRequestAckGrp](#), [ApplIDRequestGrp](#), [LegOrdGrp](#), [LegQuotGrp](#), [LegQuotStatGrp](#), [PositionQty](#), [PreAllocGrp](#), [QuotReqLegsGrp](#), [RgstDtlsGrp](#), [TestScenarioGrp](#), [TrdInstrmtLegGrp](#)

### **180.2.2977 NestedPartyID**

PartyID value within a nested repeating group.

Same values as PartyID (448)

Type: [String](#)

Used in groups: [NestedParties](#)

### **180.2.2978 NestedPartyIDSource**

PartyIDSource value within a nested repeating group.

Same values as PartyIDSource (447)

Type: [char](#)

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number

Code	Name	Description
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.

Code	Name	Description
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **NestedParties**

### 180.2.2979 NestedPartyRole

PartyRole value within a nested repeating group.

Same values as PartyRole (452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)

Code	Name	Description
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number

Code	Name	Description
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator

Code	Name	Description
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.



Code	Name	Description
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.

Code	Name	Description
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **NestedParties**

### 180.2.2980 NestedPartyRoleQualifier

Used to further qualify the value of NestedPartyRole(538).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.

Code	Name	Description
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.

Code	Name	Description
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

---

Used in groups: **NestedParties**

#### **180.2.2981 NestedPartySubID**

PartySubID value within a nested repeating group.

Same values as PartySubID (523)

Type: **String**

Used in groups: **NstdPtysSubGrp**

#### **180.2.2982 NestedPartySubIDType**

Type of NestedPartySubID (545) value.

Same values as PartySubIDType (803)

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)

Code	Name	Description
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier

Code	Name	Description
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C = Credit institution authorized in accordance with Directive 2006/48/EC F = Investment firm in accordance with Directive 2004/39/EC I = Insurance undertaking authorized in accordance with Directive 73/239/EC L = Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O = Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R = Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U = UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N

Code	Name	Description
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.



Code	Name	Description
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI

Code	Name	Description
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: [NstdPtysSubGrp](#)

### 180.2.2983 NetChgPrevDay

Net change from previous day's closing price vs. last traded price.

Type: [PriceOffset](#)

Used in groups: [MDIncGrp](#)

Used in messages: [MarketDataSnapshotFullRefresh](#)

### 180.2.2984 NetGrossInd

Code to represent whether value is net (inclusive of tax) or gross.

Type: [int](#)

Allowed values in NetGrossIndCodeSet:

Code	Name	Description
1	Net	Net
2	Gross	Gross

Used in groups: [BidCompReqGrp](#), [BidCompRspGrp](#), [SettlObligationInstructions](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

**180.2.2985 NetMoney**

Total amount due as the result of the transaction (e.g. for Buy order - principal + commission + fees) reported in currency of execution.

Type: **Amt**

Used in components: **SettlTradeDetails**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **Confirmation**, **ExecutionReport**

**180.2.2986 NetworkRequestID**

Unique identifier for a network resquest.

Type: **String**

Used in messages: **NetworkCounterpartySystemStatusRequest**, **NetworkCounterpartySystemStatus-Response**

**180.2.2987 NetworkRequestType**

Indicates the type and level of details required for a Network Status Request Message

Boolean logic applies EG If you want to subscribe for changes to certain id's then UserRequestType =0 (8+2), Snapshot for certain ID's = 9 (8+1)

Type: **int**

Allowed values in NetworkRequestTypeCodeSet:

Code	Name	Description
1	Snapshot	Snapshot
2	Subscribe	Subscribe
4	StopSubscribing	Stop Subscribing
8	LevelOfDetail	Level of Detail, then NoCompID's becomes required

Used in messages: **NetworkCounterpartySystemStatusRequest**

**180.2.2988 NetworkResponseID**

Unique identifier for a network response.

Type: **String**

Used in messages: **NetworkCounterpartySystemStatusResponse**

**180.2.2989 NetworkStatusResponseType**

Indicates the type of Network Response Message.

Type: **int**

Allowed values in NetworkStatusResponseTypeCodeSet:

Code	Name	Description
1	Full	Full
2	IncrementalUpdate	Incremental Update

Used in messages: **NetworkCounterpartySystemStatusResponse**

**180.2.2990 NewPassword**

New Password or passphrase

Type: **String**

Used in messages: **Logon**, **UserRequest**

**180.2.2991 NewsCategory**

Category of news message.

Type: **int**

Allowed values in NewsCategoryCodeSet:

Code	Name	Description
0	CompanyNews	Company News
1	MarketplaceNews	Marketplace News

Code	Name	Description
2	FinancialMarketNews	Financial Market News
3	TechnicalNews	Technical News
99	OtherNews	Other News

Used in messages: [News](#)

#### **180.2.2992 NewSeqNo**

New sequence number

Type: [SeqNum](#)

Used in messages: [SequenceReset](#)

#### **180.2.2993 NewsID**

Unique identifier for a News message

Type: [String](#)

Used in messages: [News](#)

#### **180.2.2994 NewsRefGrp**

Name	Mult.	Type	Description
<a href="#">NoNewsRefIDs</a>	[1..1]	NumInGroup	Number of news item references
<a href="#">NewsRefID</a>	[0..1]	String	Required if NoNewsRefIDs(2144) > 0. News item being referenced.
<a href="#">NewsRefType</a>	[0..1]	CodeSet	Type of reference.

Used in messages: [News](#)

#### **180.2.2995 NewsRefID**

Reference to another News message identified by NewsID(1474).

Type: **String**

Used in groups: **NewsRefGrp**

### **180.2.2996 NewsRefType**

Type of reference to another News(35=B) message item.

Type: **int**

Allowed values in NewsRefTypeCodeSet:

Code	Name	Description
0	Replacement	Replacement
1	OtherLanguage	Other language
2	Complimentary	Complimentary
3	Withdrawal	Withdrawal. Withdrawal of the referenced news item, e.g. to correct an error.

Used in groups: **NewsRefGrp**

### **180.2.2997 NextAuctionTime**

The time of the next auction.

Type: **UTCTimestamp**

Used in messages: **SecurityStatus**

### **180.2.2998 NextExpectedMsgSeqNum**

Next expected MsgSeqNum value to be received.

Type: **SeqNum**

Used in messages: **Logon**

#### **180.2.2999 NextIndexRollDate**

Next index roll date.

Type: **LocalMktDate**

Used in components: **InstrumentExtension**

#### **180.2.3000 NoAdditionalTermBondRefs**

Number of bonds in the repeating group.

Type: **NumInGroup**

Used in groups: **AdditionalTermBondRefGrp**

#### **180.2.3001 NoAdditionalTerms**

Number of additional terms in the repeating group.

Type: **NumInGroup**

Used in groups: **AdditionalTermGrp**

#### **180.2.3002 NoAffectedMarketSegments**

Number of market segments affected by a mass action.

Type: **NumInGroup**

Used in groups: **AffectedMarketSegmentGrp**

#### **180.2.3003 NoAffectedOrders**

Number of affected orders in the repeating group of order ids.

Type: **NumInGroup**

Used in groups: **AffectedOrdGrp**

#### **180.2.3004 NoAlgoSystemModules**

Number of components making up a system for algorithmic trading.

Type: NumInGroup

Used in groups: AlgoSystemModuleGrp

#### **180.2.3005 NoAllocCommissions**

Number of commissions in the repeating group.

Type: NumInGroup

Used in groups: AllocCommissionDataGrp

#### **180.2.3006 NoAllocGroupSubQtyAttributes**

Indicates number of trade attributes used to define a subgroup in an allocation group.

Type: NumInGroup

Used in groups: AllocGroupSubQtyAttributeGrp

#### **180.2.3007 NoAllocGroupSubQtys**

Indicates number of subgroups in an allocation group.

Type: NumInGroup

Used in groups: AllocGroupSubQtyGrp

#### **180.2.3008 NoAllocRegulatoryTradeIDs**

Number of regulatory IDs in the repeating group.

Type: NumInGroup

Used in groups: AllocRegulatoryTradeIDGrp



### **180.2.3009 NoAllocs**

Number of repeating AllocAccount (79)/AllocPrice (366) entries.

Type: NumInGroup

Used in groups: AllocAckGrp, AllocGrp, PreAllocGrp, PreAllocMlegGrp, TrdAllocGrp

### **180.2.3010 NoAllocTrdRegTimestamps**

Number of allocation timestamps.

Type: NumInGroup

Used in groups: AllocTrdRegTimestamps

### **180.2.3011 NoAltMDSOURCE**

Number of alternative market data sources

Type: NumInGroup

Used in groups: MDRjctGrp

### **180.2.3012 NoApplIDs**

Specifies number of application id occurrences

Type: NumInGroup

Used in groups: ApplIDReportGrp, ApplIDRequestAckGrp, ApplIDRequestGrp

### **180.2.3013 NoAsgnReqs**

Number of assignment requests.

Type: NumInGroup

Used in groups: StrmAsgnReqGrp, StrmAsgnRptGrp

#### **180.2.3014 NoAssetAttributes**

The number of asset attribute entries in the group.

Type: **NumInGroup**

Used in groups: **AssetAttributeGrp**

#### **180.2.3015 NoAttachmentKeywords**

The number of attachment keywords.

Type: **NumInGroup**

Used in groups: **AttachmentKeywordGrp**

#### **180.2.3016 NoAttachments**

The number of attached files.

Type: **NumInGroup**

Used in groups: **AttachmentGrp**

#### **180.2.3017 NoAuctionTypeRules**

Number of auction order types.

Type: **NumInGroup**

Used in groups: **AuctionTypeRuleGrp**

#### **180.2.3018 NoBidComponents**

Indicates the number of list entries.

Type: **NumInGroup**

Used in groups: **BidCompReqGrp**, **BidCompRspGrp**

#### **180.2.3019 NoBidDescriptors**

Number of BidDescriptor (400) entries.

Type: NumInGroup

Used in groups: BidDescReqGrp

#### **180.2.3020 NoBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: BusinessCenterGrp

#### **180.2.3021 NoCapacities**

Number of repeating OrderCapacity entries.

Type: NumInGroup

Used in groups: CpctyConfGrp

#### **180.2.3022 NoCashSettlDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: CashSettlDateBusinessCenterGrp

#### **180.2.3023 NoCashSettlDealers**

Number of dealers in the repeating group.

Type: NumInGroup

Used in groups: CashSettlDealerGrp

#### **180.2.3024 NoCashSettlTerms**

Number of elements in the repeating group.

Type: NumInGroup

Used in groups: CashSettlTermGrp

#### **180.2.3025 NoClearingAccountTypes**

Number of clearing account type entries.

Type: NumInGroup

Used in groups: ClearingAccountTypeGrp

#### **180.2.3026 NoClearingInstructions**

Number of clearing instructions

Type: NumInGroup

Used in groups: ClrInstGrp

#### **180.2.3027 NoClearingPriceParameters**

Number of parameter sets for clearing prices.

Type: NumInGroup

Used in groups: ClearingPriceParametersGrp

#### **180.2.3028 NoCollateralAmounts**

Number of collateral amount entries.

Type: NumInGroup

Used in groups: CollateralAmountGrp

#### **180.2.3029 NoCollateralReinvestments**

Number of instances of CollateralReinvestmentType(2844) in the repeating group.

Type: NumInGroup

Used in groups: CollateralReinvestmentGrp

#### **180.2.3030 NoCollInquiryQualifier**

Number of CollInquiryQualifier entries in a repeating group.

Type: NumInGroup

Used in groups: CollInqQualGrp

#### **180.2.3031 NoCommissions**

Number of commissions in the repeating group.

Type: NumInGroup

Used in groups: CommissionDataGrp

#### **180.2.3032 NoCompIDs**

Number of CompID entries in a repeating group.

Type: NumInGroup

Used in groups: CompIDReqGrp, CompIDStatGrp

#### **180.2.3033 NoComplexEventAveragingObservations**

The number of averaging observations in the repeating group.

Type: NumInGroup

Used in groups: ComplexEventAveragingObservationGrp

#### **180.2.3034 NoComplexEventCreditEventQualifiers**

The number of qualifiers in the repeating group.

Type: NumInGroup

Used in groups: ComplexEventCreditEventQualifierGrp

#### **180.2.3035 NoComplexEventCreditEvents**

The number of credit events specified in the repeating group.

Type: NumInGroup

Used in groups: ComplexEventCreditEventGrp

#### **180.2.3036 NoComplexEventCreditEventSources**

Number of event sources in the repeating group.

Type: NumInGroup

Used in groups: ComplexEventCreditEventSourceGrp

#### **180.2.3037 NoComplexEventDateBusinessCenters**

The number of business centers in the repeating group.

Type: NumInGroup

Used in groups: ComplexEventDateBusinessCenterGrp

#### **180.2.3038 NoComplexEventDates**

Number of complex event date occurrences for a given complex event.

Type: NumInGroup

Used in groups: ComplexEventDates

#### **180.2.3039 NoComplexEventPeriodDateTimes**

The number of entries in the date-time repeating group.

Type: NumInGroup

Used in groups: ComplexEventPeriodDateGrp

#### **180.2.3040 NoComplexEventPeriods**

The number of periods in the repeating group.

Type: NumInGroup

Used in groups: ComplexEventPeriodGrp

#### **180.2.3041 NoComplexEventRateSources**

The number of rate sources in the repeating group.

Type: NumInGroup

Used in groups: ComplexEventRateSourceGrp

#### **180.2.3042 NoComplexEvents**

Number of complex event occurrences.

Type: NumInGroup

Used in groups: ComplexEvents

#### **180.2.3043 NoComplexEventSchedules**

Number of schedules in the repeating group.

Type: NumInGroup

Used in groups: ComplexEventScheduleGrp

#### **180.2.3044 NoComplexEventTimes**

Number of complex event time occurrences for a given complex event date

The default in case of an absence of time fields is 00:00:00-23:59:59.

Type: NumInGroup

Used in groups: ComplexEventTimes

#### **180.2.3045 NoContAmts**

The number of Contract Amount details on an Execution Report message

Type: NumInGroup

Used in groups: ContAmtGrp

#### **180.2.3046 NoContraBrokers**

The number of ContraBroker (375) entries.

Type: NumInGroup

Used in groups: ContraGrp

#### **180.2.3047 NoContractualDefinitions**

Number of financing definitions in the repeating group.

Type: NumInGroup

Used in groups: FinancingContractualDefinitionGrp

#### **180.2.3048 NoContractualMatrices**

Number of contractual matrices in the repeating group.

Type: NumInGroup

Used in groups: FinancingContractualMatrixGrp



#### **180.2.3049 NoCrossLegs**

Number of legs in the side of a cross order.

Type: NumInGroup

Used in groups: SideCrossLegGrp

#### **180.2.3050 NoDates**

Number of Date fields provided in date range

Type: NumInGroup

Used in groups: TrdCapDtGrp

#### **180.2.3051 NoDeliverySchedules**

Number of delivery schedules in the repeating group.

Type: NumInGroup

Used in groups: DeliveryScheduleGrp

#### **180.2.3052 NoDeliveryScheduleSettlDays**

Number of delivery schedules in the repeating group.

Type: NumInGroup

Used in groups: DeliveryScheduleSettlDayGrp

#### **180.2.3053 NoDeliveryScheduleSettlTimes**

Number of hour ranges in the repeating group.

Type: NumInGroup

Used in groups: DeliveryScheduleSettlTimeGrp

#### **180.2.3054 NoDeliveryStreamCommoditySources**

Number of commodity sources in the repeating group.

Type: **NumInGroup**

Used in groups: **DeliveryStreamCommoditySourceGrp**

#### **180.2.3055 NoDeliveryStreamCycles**

Number of delivery cycles in the repeating group.

Type: **NumInGroup**

Used in groups: **DeliveryStreamCycleGrp**

#### **180.2.3056 NoDerivativeEvents**

Number of repeating DerivativeEventType entries.

Type: **NumInGroup**

Used in groups: **DerivativeEventsGrp**

#### **180.2.3057 NoDerivativeInstrAttrib**

Number of instrument attributes.

Type: **NumInGroup**

Used in groups: **DerivativeInstrumentAttribute**

#### **180.2.3058 NoDerivativeInstrumentParties**

Number of repeating derivative instrument party entries.

Type: **NumInGroup**

Used in groups: **DerivativeInstrumentParties**

#### **180.2.3059 NoDerivativeInstrumentPartySubIDs**

Number of derivative instrument party sub IDs.

Type: **NumInGroup**

Used in groups: **DerivativeInstrumentPartySubIDsGrp**

#### **180.2.3060 NoDerivativeSecurityAltID**

Number of alternate derivative security IDs.

Type: **NumInGroup**

Used in groups: **DerivativeSecurityAltIDGrp**

#### **180.2.3061 NoDisclosureInstructions**

Number of disclosure instructions.

Type: **NumInGroup**

Used in groups: **DisclosureInstructionGrp**

#### **180.2.3062 NoDistribInsts**

The number of Distribution Instructions on a Registration Instructions message

Type: **NumInGroup**

Used in groups: **RgstDistInstGrp**

#### **180.2.3063 NoDividendAccrualPaymentDateBusinessCenters**

Number of entries in the DividendAccrualPaymentDateBusinessCenterGrp.

Type: **NumInGroup**

Used in groups: **DividendAccrualPaymentDateBusinessCenterGrp**

#### **180.2.3064 NoDividendFXTriggerDateBusinessCenters**

Number of entries in the DividendFXTriggerDateBusinessCenterGrp.

Type: NumInGroup

Used in groups: DividendFXTriggerDateBusinessCenterGrp

#### **180.2.3065 NoDividendPeriodBusinessCenters**

Number of entries in the DividendPeriodBusinessCenterGrp.

Type: NumInGroup

Used in groups: DividendPeriodBusinessCenterGrp

#### **180.2.3066 NoDividendPeriods**

Number of entries in the DividendPeriodGrp component.

Type: NumInGroup

Used in groups: DividendPeriodGrp

#### **180.2.3067 NoDlvyInst**

Number of delivery instruction fields in repeating group.

Note this field was removed in FIX 4.1 and reinstated in FIX 4.4.

Type: NumInGroup

Used in groups: DlvyInstGrp

#### **180.2.3068 NoEntitlementAttrib**

Number of entitlement attributes.

Type: NumInGroup

Used in groups: EntitlementAttribGrp

#### **180.2.3069 NoEntitlements**

Number of entitlement values.

Type: **NumInGroup**

Used in groups: **EntitlementGrp**

#### **180.2.3070 NoEntitlementTypes**

Number of entitlement types in the repeating group.

Type: **NumInGroup**

Used in groups: **EntitlementTypeGrp**

#### **180.2.3071 NoEvents**

Number of repeating EventType entries.

Type: **NumInGroup**

Used in groups: **EvntGrp**

#### **180.2.3072 NoExecInstRules**

Number of execution instructions

Type: **NumInGroup**

Used in groups: **ExecInstRules**

#### **180.2.3073 NoExecs**

Number of executions or trades.

Type: **NumInGroup**

Used in groups: **ExecAllocGrp**, **ExecCollGrp**, **ExecutionAggregationGrp**

**180.2.3074 NoExpiration**

Number of Expiration Qty entries

Type: NumInGroup

Used in groups: ExpirationQty

**180.2.3075 NoExtraordinaryEvents**

Number of extraordinary events in the repeating group.

Type: NumInGroup

Used in groups: ExtraordinaryEventGrp

**180.2.3076 NoFills**

Type: NumInGroup

Used in groups: FillsGrp

**180.2.3077 NoFinancingTermSupplements**

Number of financing terms supplements in the repeating group.

Type: NumInGroup

Used in groups: FinancingTermSupplementGrp

**180.2.3078 NoFlexProductEligibilities**

Number of eligibility indicators for the creation of flexible securities.

Type: NumInGroup

Used in groups: FlexProductEligibilityGrp

**180.2.3079 NoFundingSources**

Number of instances of FundingSource(2846) in the repeating group.

Type: NumInGroup

Used in groups: FundingSourceGrp

### **180.2.3080 NoHops**

Number of HopCompID entries in repeating group.

Type: NumInGroup

Used in groups: HopGrp

### **180.2.3081 NoIndexRollMonths**

Number of instances of the index roll month.

Type: NumInGroup

Used in groups: IndexRollMonthGrp

### **180.2.3082 NoInstrAttrib**

Number of repeating InstrAttribType entries.

Type: NumInGroup

Used in groups: AttribGrp

### **180.2.3083 NoInstrmtMatchSides**

Number of instrument match sides.

Type: NumInGroup

Used in groups: InstrmtMatchSideGrp

### **180.2.3084 NoInstrumentParties**

Identifies the number of parties identified with an instrument

Type: NumInGroup

Used in groups: InstrumentParties

#### **180.2.3085 NoInstrumentPartySubIDs**

Number of InstrumentPartySubID (1053) and InstrumentPartySubIDType (1054) entries

Type: NumInGroup

Used in groups: InstrumentPtysSubGrp

#### **180.2.3086 NoInstrumentScopes**

Number of instrument scopes.

Type: NumInGroup

Used in groups: InstrumentScopeGrp

#### **180.2.3087 NoInstrumentScopeSecurityAltID**

Number of alternate security identifier for the specified InstrumentScopeSecurityID(1538).

Type: NumInGroup

Used in groups: InstrumentScopeSecurityAltIDGrp

#### **180.2.3088 NoIOIQualifiers**

Number of repeating groups of IOIQualifiers (04).

Type: NumInGroup

Used in groups: IOIQualGrp

#### **180.2.3089 NoLegAdditionalTermBondRefs**

Number of bonds in the repeating group.

Type: NumInGroup

Used in groups: LegAdditionalTermBondRefGrp



#### **180.2.3090 NoLegAdditionalTerms**

Number of additional terms in the repeating group.

Type: NumInGroup

Used in groups: LegAdditionalTermGrp

#### **180.2.3091 NoLegAllocs**

Number of Allocations for the leg

Type: NumInGroup

Used in groups: LegPreAllocGrp

#### **180.2.3092 NoLegAssetAttributes**

Number of asset attribute entries in the group.

Type: NumInGroup

Used in groups: LegAssetAttributeGrp

#### **180.2.3093 NoLegBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegBusinessCenterGrp

#### **180.2.3094 NoLegCashSettlDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegCashSettlDateBusinessCenterGrp

#### **180.2.3095 NoLegCashSettlDealers**

Number of dealers in the repeating group.

Type: NumInGroup

Used in groups: LegCashSettlDealerGrp

#### **180.2.3096 NoLegCashSettlTerms**

Number of elements in the repeating group.

Type: NumInGroup

Used in groups: LegCashSettlTermGrp

#### **180.2.3097 NoLegComplexEventAveragingObservations**

The number of averaging observations in the repeating group.

Type: NumInGroup

Used in groups: LegComplexEventAveragingObservationGrp

#### **180.2.3098 NoLegComplexEventCreditEventQualifiers**

Number of qualifiers in the repeating group.

Type: NumInGroup

Used in groups: LegComplexEventCreditEventQualifierGrp

#### **180.2.3099 NoLegComplexEventCreditEvents**

The number of credit events specified in the repeating group.

Type: NumInGroup

Used in groups: LegComplexEventCreditEventGrp

#### **180.2.3100 NoLegComplexEventCreditEventSources**

Number of event sources in the repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEventCreditEventSourceGrp**

#### **180.2.3101 NoLegComplexEventDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEventDateBusinessCenterGrp**

#### **180.2.3102 NoLegComplexEventDates**

Number of complex event dates in the repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEventDates**

#### **180.2.3103 NoLegComplexEventPeriodDateTimes**

Number of entries in the date-time repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEventPeriodDateGrp**

#### **180.2.3104 NoLegComplexEventPeriods**

Number of periods in the repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEventPeriodGrp**

#### **180.2.3105 NoLegComplexEventRateSources**

Number of rate sources in the repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEventRateSourceGrp**

#### **180.2.3106 NoLegComplexEvents**

Number of complex events in the repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEvents**

#### **180.2.3107 NoLegComplexEventSchedules**

Number of schedules in the repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEventScheduleGrp**

#### **180.2.3108 NoLegComplexEventTimes**

Number of complex event times in the repeating group.

Type: **NumInGroup**

Used in groups: **LegComplexEventTimes**

#### **180.2.3109 NoLegContractualDefinitions**

Number of financing definitions in the repeating group.

Type: **NumInGroup**

Used in groups: **LegFinancingContractualDefinitionsGrp**

#### **180.2.3110 NoLegContractualMatrices**

Number of contractual matrices in the repeating group.

Type: **NumInGroup**

Used in groups: **LegFinancingContractualMatrixGrp**

#### **180.2.3111 NoLegDeliverySchedules**

Number of delivery schedules in the repeating group.

Type: **NumInGroup**

Used in groups: **LegDeliveryScheduleGrp**

#### **180.2.3112 NoLegDeliveryScheduleSettlDays**

Number of delivery schedules in the repeating group.

Type: **NumInGroup**

Used in groups: **LegDeliveryScheduleSettlDayGrp**

#### **180.2.3113 NoLegDeliveryScheduleSettlTimes**

Number of hour ranges in the repeating group.

Type: **NumInGroup**

Used in groups: **LegDeliveryScheduleSettlTimeGrp**

#### **180.2.3114 NoLegDeliveryStreamCommoditySources**

Number of commodity sources in the repeating group.

Type: **NumInGroup**

Used in groups: **LegDeliveryStreamCommoditySourceGrp**

#### **180.2.3115 NoLegDeliveryStreamCycles**

Number of commodity sources in the repeating group.

Type: **NumInGroup**

Used in groups: **LegDeliveryStreamCycleGrp**

#### **180.2.3116 NoLegDividendAccrualPaymentDateBusinessCenters**

Number of entries in the LegDividendAccrualPaymentDateBusinessCenterGrp.

Type: **NumInGroup**

Used in groups: **LegDividendAccrualPaymentDateBusinessCenterGrp**

#### **180.2.3117 NoLegDividendFXTriggerDateBusinessCenters**

Number of entries in the LegDividendFXTriggerDateBusinessCenterGrp.

Type: **NumInGroup**

Used in groups: **LegDividendFXTriggerDateBusinessCenterGrp**

#### **180.2.3118 NoLegDividendPeriodBusinessCenters**

The number of entries in the LegDividendPeriodBusinessCentersGrp component.

Type: **NumInGroup**

Used in groups: **LegDividendPeriodBusinessCenterGrp**

#### **180.2.3119 NoLegDividendPeriods**

Number of entries in the LegDividendPeriodGrp component.

Type: **NumInGroup**

Used in groups: **LegDividendPeriodGrp**

#### **180.2.3120 NoLegEvents**

Number of events in the repeating group

Type: NumInGroup

Used in groups: LegEvtGrp

#### **180.2.3121 NoLegExecs**

Number of instrument leg executions.

Type: NumInGroup

Used in groups: TrdInstrmtLegExecGrp

#### **180.2.3122 NoLegExtraordinaryEvents**

Number of extraordinary events in the repeating group.

Type: NumInGroup

Used in groups: LegExtraordinaryEventGrp

#### **180.2.3123 NoLegFinancingTermSupplements**

Number of financing terms supplements in the repeating group.

Type: NumInGroup

Used in groups: LegFinancingTermSupplementGrp

#### **180.2.3124 NoLegInstrumentParties**

Number of parties in the repeating group.

Type: NumInGroup

Used in groups: LegInstrumentParties

#### **180.2.3125 NoLegInstrumentPartySubIDs**

Number of parties sub-IDs in the repeating group.

Type: **NumInGroup**

Used in groups: **LegInstrumentPtysSubGrp**

#### **180.2.3126 NoLegMarketDisruptionEvents**

Number of disruption events in the repeating group.

Type: **NumInGroup**

Used in groups: **LegMarketDisruptionEventGrp**

#### **180.2.3127 NoLegMarketDisruptionFallbackReferencePrices**

Number of fallback reference securities in the repeating group.

Type: **NumInGroup**

Used in groups: **LegMarketDisruptionFallbackReferencePriceGrp**

#### **180.2.3128 NoLegMarketDisruptionFallbacks**

Number of fallbacks in the repeating group.

Type: **NumInGroup**

Used in groups: **LegMarketDisruptionFallbackGrp**

#### **180.2.3129 NoLegNonDeliverableFixingDates**

Number of fixing dates in the repeating group.

Type: **NumInGroup**

Used in groups: **LegPaymentStreamNonDeliverableFixingDateGrp**



#### **180.2.3130 NoLegOptionExerciseBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegOptionExerciseBusinessCenterGrp

#### **180.2.3131 NoLegOptionExerciseDates**

Number of dates in the repeating group.

Type: NumInGroup

Used in groups: LegOptionExerciseDateGrp

#### **180.2.3132 NoLegOptionExerciseExpirationDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegOptionExerciseExpirationDateBusinessCenterGrp

#### **180.2.3133 NoLegOptionExerciseExpirationDates**

Number of fixed exercise expiration dates in the repeating group.

Type: NumInGroup

Used in groups: LegOptionExerciseExpirationDateGrp

#### **180.2.3134 NoLegPaymentScheduleFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentScheduleFixingDateBusinessCenterGrp

#### **180.2.3135 NoLegPaymentScheduleFixingDays**

Number of fixing days in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentScheduleFixingDayGrp

#### **180.2.3136 NoLegPaymentScheduleInterimExchangeDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentScheduleInterimExchangeDateBusinessCenterGrp

#### **180.2.3137 NoLegPaymentScheduleRateSources**

Number of rate sources in the repeating group

Type: NumInGroup

Used in groups: LegPaymentScheduleRateSourceGrp

#### **180.2.3138 NoLegPaymentSchedules**

Number of swap schedules in the repeating group

Type: NumInGroup

Used in groups: LegPaymentScheduleGrp

#### **180.2.3139 NoLegPaymentStreamCompoundingDates**

Number of dates in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamCompoundingDateGrp

#### **180.2.3140 NoLegPaymentStreamCompoundingDatesBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamCompoundingDatesBusinessCenterGrp

#### **180.2.3141 NoLegPaymentStreamFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamFixingDateBusinessCenterGrp

#### **180.2.3142 NoLegPaymentStreamFixingDates**

Number of fixing dates in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamFixingDateGrp

#### **180.2.3143 NoLegPaymentStreamFormulas**

Number of formulas in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamFormulaMathGrp

#### **180.2.3144 NoLegPaymentStreamInitialFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamInitialFixingDateBusinessCenterGrp

#### **180.2.3145 NoLegPaymentStreamNonDeliverableFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp

#### **180.2.3146 NoLegPaymentStreamPaymentDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamPaymentDateBusinessCenterGrp

#### **180.2.3147 NoLegPaymentStreamPaymentDates**

Number of payment dates in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamPaymentDateGrp

#### **180.2.3148 NoLegPaymentStreamPricingBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamPricingBusinessCenterGrp

#### **180.2.3149 NoLegPaymentStreamPricingDates**

Number of pricing dates in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamPricingDateGrp

**180.2.3150 NoLegPaymentStreamPricingDays**

Number of pricing days in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamPricingDayGrp

**180.2.3151 NoLegPaymentStreamResetDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStreamResetDateBusinessCenterGrp

**180.2.3152 NoLegPaymentStubEndDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStubEndDateBusinessCenterGrp

**180.2.3153 NoLegPaymentStubs**

Number of stubs in the repeating group

Type: NumInGroup

Used in groups: LegPaymentStubGrp

**180.2.3154 NoLegPaymentStubStartDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegPaymentStubStartDateBusinessCenterGrp

#### **180.2.3155 NoLegPhysicalSettlDeliverableObligations**

Number of entries in the repeating group.

Type: **NumInGroup**

Used in groups: **LegPhysicalSettlDeliverableObligationGrp**

#### **180.2.3156 NoLegPhysicalSettlTerms**

Number of entries in the repeating group.

Type: **NumInGroup**

Used in groups: **LegPhysicalSettlTermGrp**

#### **180.2.3157 NoLegPosAmt**

Number of TrdInstrmtLegPosAmt values.

Type: **NumInGroup**

Used in groups: **LegPositionAmountData**

#### **180.2.3158 NoLegPricingDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegPricingDateBusinessCenterGrp**

#### **180.2.3159 NoLegProtectionTermEventNewsSources**

Number of event sources in the repeating group.

Type: **NumInGroup**

Used in groups: **LegProtectionTermEventNewsSourceGrp**

#### **180.2.3160 NoLegProtectionTermEventQualifiers**

Number of qualifiers in the repeating group.

Type: NumInGroup

Used in groups: LegProtectionTermEventQualifierGrp

#### **180.2.3161 NoLegProtectionTermEvents**

Number of protection term events in the repeating group.

Type: NumInGroup

Used in groups: LegProtectionTermEventGrp

#### **180.2.3162 NoLegProtectionTermObligations**

Number of obligations in the repeating group.

Type: NumInGroup

Used in groups: LegProtectionTermObligationGrp

#### **180.2.3163 NoLegProtectionTerms**

Number of protection terms in the repeating group.

Type: NumInGroup

Used in groups: LegProtectionTermGrp

#### **180.2.3164 NoLegProvisionCashSettlPaymentDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegProvisionCashSettlPaymentDateBusinessCenterGrp

**180.2.3165 NoLegProvisionCashSettlPaymentDates**

Number of provision cash settlement payment dates in the repeating group.

Type: **NumInGroup**

Used in groups: **LegProvisionCashSettlPaymentFixedDateGrp**

**180.2.3166 NoLegProvisionCashSettlValueDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegProvisionCashSettlValueDateBusinessCenterGrp**

**180.2.3167 NoLegProvisionDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegProvisionDateBusinessCenterGrp**

**180.2.3168 NoLegProvisionOptionExerciseBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegProvisionOptionExerciseBusinessCenterGrp**

**180.2.3169 NoLegProvisionOptionExerciseFixedDates**

Number of provision option exercise fixed dates in the repeating group.

Type: **NumInGroup**

Used in groups: **LegProvisionOptionExerciseFixedDateGrp**



#### **180.2.3170 NoLegProvisionOptionExpirationDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegProvisionOptionExpirationDateBusinessCenterGrp

#### **180.2.3171 NoLegProvisionOptionRelevantUnderlyingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegProvisionOptionRelevantUnderlyingDateBusinessCenterGrp

#### **180.2.3172 NoLegProvisionPartyIDs**

Number of parties identified in the contract provision.

Type: NumInGroup

Used in groups: LegProvisionParties

#### **180.2.3173 NoLegProvisionPartySubIDs**

Number of sub-party IDs to be reported for the party.

Type: NumInGroup

Used in groups: LegProvisionPtysSubGrp

#### **180.2.3174 NoLegProvisions**

Number of provisions in the repeating group.

Type: NumInGroup

Used in groups: LegProvisionGrp

#### **180.2.3175 NoLegReturnRateDates**

Number of iterations in the return rate date repeating group.

Type: NumInGroup

Used in groups: LegReturnRateDateGrp

#### **180.2.3176 NoLegReturnRateFXConversions**

Number of iterations in the return rate FX conversion repeating group.

Type: NumInGroup

Used in groups: LegReturnRateFXConversionGrp

#### **180.2.3177 NoLegReturnRateInformationSources**

Number of iterations in the return rate information source repeating group.

Type: NumInGroup

Used in groups: LegReturnRateInformationSourceGrp

#### **180.2.3178 NoLegReturnRatePrices**

Number of iterations in the return rate price repeating group.

Type: NumInGroup

Used in groups: LegReturnRatePriceGrp

#### **180.2.3179 NoLegReturnRates**

Number of iterations in the return rate repeating group.

Type: NumInGroup

Used in groups: LegReturnRateGrp

**180.2.3180 NoLegReturnRateValuationDateBusinessCenters**

Number of iterations in the return rate valuation date business center repeating group.

Type: NumInGroup

Used in groups: LegReturnRateValuationDateBusinessCenterGrp

**180.2.3181 NoLegReturnRateValuationDates**

Number of iterations in the return rate valuation date repeating group.

Type: NumInGroup

Used in groups: LegReturnRateValuationDateGrp

**180.2.3182 NoLegs**

Number of InstrumentLeg repeating group instances.

Type: NumInGroup

Used in groups: InstrmtLegExecGrp, InstrmtLegGrp, InstrmtLegIOIGrp, InstrmtLegSecListGrp, LegOrdGrp, LegQuotGrp, LegQuotStatGrp, QuotReqLegsGrp, SecLstUpdRelSymsLegGrp, TrdInstrmtLegGrp

**180.2.3183 NoLegSecondaryAssetClasses**

Number of secondary asset classes in the repeating group.

Type: NumInGroup

Used in groups: LegSecondaryAssetGrp

**180.2.3184 NoLegSecurityAltID**

Multileg instrument's individual security's NoSecurityAltID.

See NoSecurityAltID (454) field for description

Type: NumInGroup

Used in groups: LegSecAltIDGrp

#### **180.2.3185 NoLegSettlMethodElectionDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegSettlMethodElectionDateBusinessCenterGrp**

#### **180.2.3186 NoLegSettlRateFallbacks**

Number of settlement rate fallbacks in the repeating group

Type: **NumInGroup**

Used in groups: **LegSettlRateDisruptionFallbackGrp**

#### **180.2.3187 NoLegStipulations**

Number of leg stipulation entries

Type: **NumInGroup**

Used in groups: **LegStipulations**

#### **180.2.3188 NoLegStreamAssetAttributes**

Number of asset attribute entries in the group.

Type: **NumInGroup**

Used in groups: **LegStreamAssetAttributeGrp**

#### **180.2.3189 NoLegStreamCalculationPeriodBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegStreamCalculationPeriodBusinessCenterGrp**

#### **180.2.3190 NoLegStreamCalculationPeriodDates**

Number of calculation period dates in the repeating group.

Type: NumInGroup

Used in groups: LegStreamCalculationPeriodDateGrp

#### **180.2.3191 NoLegStreamCommodityAltIDs**

Number of alternate security identifiers.

Type: NumInGroup

Used in groups: LegStreamCommodityAltIDGrp

#### **180.2.3192 NoLegStreamCommodityDataSources**

Number of data sources in the repeating group. The order of entry determines priority – first is the main source, second is fallback, third is second fallback.

Type: NumInGroup

Used in groups: LegStreamCommodityDataSourceGrp

#### **180.2.3193 NoLegStreamCommoditySettlBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: LegStreamCommoditySettlBusinessCenterGrp

#### **180.2.3194 NoLegStreamCommoditySettlDays**

Number of days in the repeating group.

Type: NumInGroup

Used in groups: LegStreamCommoditySettlDayGrp

#### **180.2.3195 NoLegStreamCommoditySettlPeriods**

Number of commodity settlement periods in the repeating group.

Type: **NumInGroup**

Used in groups: **LegStreamCommoditySettlPeriodGrp**

#### **180.2.3196 NoLegStreamCommoditySettlTimes**

Number of hour ranges in the repeating group.

Type: **NumInGroup**

Used in groups: **LegStreamCommoditySettlTimeGrp**

#### **180.2.3197 NoLegStreamEffectiveDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegStreamEffectiveDateBusinessCenterGrp**

#### **180.2.3198 NoLegStreamFirstPeriodStartDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegStreamFirstPeriodStartDateBusinessCenterGrp**

#### **180.2.3199 NoLegStreams**

Number of swap streams in the repeating group.

Type: **NumInGroup**

Used in groups: **LegStreamGrp**

### **180.2.3200 NoLegStreamTerminationDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **LegStreamTerminationDateBusinessCenterGrp**

### **180.2.3201 NoLimitAmts**

The number of limit amount entries.

Type: **NumInGroup**

Used in groups: **LimitAmts**

### **180.2.3202 NoLinesOfText**

Identifies number of lines of text body

Type: **NumInGroup**

Used in groups: **LinesOfTextGrp**

### **180.2.3203 NoLotTypeRules**

Number of Lot Type Rules

Type: **NumInGroup**

Used in groups: **LotTypeRules**

### **180.2.3204 NoMandatoryClearingJurisdictions**

Number of mandatory clearing jurisdictions.

Type: **NumInGroup**

Used in groups: **MandatoryClearingJurisdictionGrp**

#### **180.2.3205 NoMarginAmt**

Number of margin requirement amounts.

Type: NumInGroup

Used in groups: MarginAmount

#### **180.2.3206 NoMarginReqmtInqQualifier**

Number of margin requirement inquiry qualifiers.

Type: NumInGroup

Used in groups: MarginReqmtInqQualGrp

#### **180.2.3207 NoMarketDisruptionEvents**

Number of disruption events in the repeating group.

Type: NumInGroup

Used in groups: MarketDisruptionEventGrp

#### **180.2.3208 NoMarketDisruptionFallbackReferencePrices**

Number of fallback reference securities in the repeating group.

Type: NumInGroup

Used in groups: MarketDisruptionFallbackReferencePriceGrp

#### **180.2.3209 NoMarketDisruptionFallbacks**

Number of fallbacks in the repeating group.

Type: NumInGroup

Used in groups: MarketDisruptionFallbackGrp



#### **180.2.3210 NoMarketSegments**

Number of Market Segments on which a security may trade.

Type: **NumInGroup**

Used in groups: **MarketSegmentGrp**, **MarketSegmentScopeGrp**

#### **180.2.3211 NoMatchExceptions**

Number of match exceptions in the repeating group.

Type: **NumInGroup**

Used in groups: **MatchExceptionGrp**

#### **180.2.3212 NoMatchingDataPoints**

Number of matching data points in the repeating group.

Type: **NumInGroup**

Used in groups: **MatchingDataPointGrp**

#### **180.2.3213 NoMatchInst**

Number of Instructions in the <MatchingInstructions> repeating group.

Type: **NumInGroup**

Used in groups: **MatchingInstructions**

#### **180.2.3214 NoMatchRules**

Number of Match Rules

Type: **NumInGroup**

Used in groups: **MatchRules**

#### **180.2.3215 NoMaturityRules**

Number of maturity rules in MarurityRules component block

Type: **NumInGroup**

Used in groups: **MaturityRules**

#### **180.2.3216 NoMDEntries**

Number of entries in Market Data message.

Type: **NumInGroup**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.3217 NoMDEntryTypes**

Number of MDEntryType (269) fields requested.

Type: **NumInGroup**

Used in groups: **MDReqGrp**

#### **180.2.3218 NoMDFeedTypes**

The number of feed types and corresponding book depths associated with a security

Type: **NumInGroup**

Used in groups: **MarketDataFeedTypes**

#### **180.2.3219 NoMDStatistics**

Number of market data statistics.

Type: **NumInGroup**

Used in groups: **MDStatisticReqGrp**, **MDStatisticRptGrp**

**180.2.3220 NoMiscFees**

Number of repeating groups of miscellaneous fees

Type: **NumInGroup**

Used in groups: **MiscFeesGrp**

**180.2.3221 NoMiscFeeSubTypes**

Specifies the number of miscellaneous fee sub-types.

Type: **NumInGroup**

Used in groups: **MiscFeesSubGrp**

**180.2.3222 NoMsgTypes**

Number of MsgTypes (35) in repeating group.

Type: **NumInGroup**

Used in groups: **MsgTypeGrp**

**180.2.3223 NonCashDividendTreatment**

Defines the treatment of non-cash dividends.

Type: **int**

Allowed values in NonCashDividendTreatmentCodeSet:

Code	Name	Description
0	PotentialAdjustment	Potential adjustment event. The treatment of any non-cash dividend shall be determined in accordance with the potential adjustment event provisions.
1	CashEquivalent	Cash equivalent. Any non-cash dividend shall be treated as a declared cash equivalent dividend.

Used in components: **DividendConditions**

**180.2.3224 NonDeliverableFixingDate**

Non-deliverable fixing date unadjusted or adjusted depending on NonDeliverableFixingDateType(40827).

Type: **LocalMktDate**

Used in groups: **PaymentStreamNonDeliverableFixingDateGrp**

**180.2.3225 NonDeliverableFixingDateType**

Specifies the type of date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **PaymentStreamNonDeliverableFixingDateGrp**

**180.2.3226 NoNested2PartyIDs**

Number of Nested2PartyID (757), Nested2PartyIDSource (758), and Nested2PartyRole (759) entries

Type: **NumInGroup**

Used in groups: **NestedParties2**

**180.2.3227 NoNested2PartySubIDs**

Number of Nested2PartySubID (760) and Nested2PartySubIDType (807) entries. Second instance of <NestedParties>.

Type: **NumInGroup**

Used in groups: **NstdPtys2SubGrp**

**180.2.3228 NoNested3PartyIDs**

Number of Nested3PartyID (949), Nested3PartyIDSource (950), and Nested3PartyRole (95) entries

Type: NumInGroup

Used in groups: NestedParties3

**180.2.3229 NoNested3PartySubIDs**

Number of Nested3PartySubIDs (953) entries

Type: NumInGroup

Used in groups: NstdPtys3SubGrp

**180.2.3230 NoNested4PartyIDs**

Refer to definition of NoPartyIDs(453)

Type: NumInGroup

Used in groups: NestedParties4

**180.2.3231 NoNested4PartySubIDs**

Refer to definition of NoPartySubIDs(802)

Type: NumInGroup

Used in groups: NstdPtys4SubGrp

**180.2.3232 NoNestedInstrAttrib**

Type: NumInGroup

Used in groups: NestedInstrumentAttribute

**180.2.3233 NoNestedPartyIDs**

Number of NestedPartyID (524), NestedPartyIDSource (525), and NestedPartyRole (538) entries

Type: NumInGroup

Used in groups: NestedParties

#### **180.2.3234 NoNestedPartySubIDs**

Number of NestedPartySubID (545) and NestedPartySubIDType (805) entries

Type: NumInGroup

Used in groups: NstdPtysSubGrp

#### **180.2.3235 NoNewsRefIDs**

Number of News reference items

Type: NumInGroup

Used in groups: NewsRefGrp

#### **180.2.3236 NoNonDeliverableFixingDates**

Number of Fixing dates in the repeating group

Type: NumInGroup

Used in groups: PaymentStreamNonDeliverableFixingDateGrp

#### **180.2.3237 NoNotAffectedMarketSegments**

Number of market segments left unaffected by a mass action.

Type: NumInGroup

Used in groups: NotAffectedMarketSegmentGrp

#### **180.2.3238 NoNotAffectedOrders**

Number of not affected orders in the repeating group of order ids.

Type: NumInGroup

Used in groups: NotAffectedOrdGrp

### **180.2.3239 NoOfLegUnderlyings**

Number of Underlyings, Identifies the Underlying of the Leg

Type: **NumInGroup**

Used in groups: **TradeCapLegUnderlyingsGrp**

### **180.2.3240 NoOfSecSizes**

The number of secondary sizes specifies in this entry

Type: **NumInGroup**

Used in groups: **SecSizesGrp**

### **180.2.3241 NoOptionExerciseBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **OptionExerciseBusinessCenterGrp**

### **180.2.3242 NoOptionExerciseDates**

Number of dates in the repeating group.

Type: **NumInGroup**

Used in groups: **OptionExerciseDateGrp**

### **180.2.3243 NoOptionExerciseExpirationDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **OptionExerciseExpirationDateBusinessCenterGrp**

#### **180.2.3244 NoOptionExerciseExpirationDates**

Number of fixed exercise expiration dates in the repeating group.

Type: NumInGroup

Used in groups: OptionExerciseExpirationDateGrp

#### **180.2.3245 NoOrderAttributes**

Number of order attribute entries.

Type: NumInGroup

Used in groups: OrderAttributeGrp

#### **180.2.3246 NoOrderEntries**

Number of order entries.

Type: NumInGroup

Used in groups: OrderEntryAckGrp, OrderEntryGrp

#### **180.2.3247 NoOrderEvents**

Number of order events.

Type: NumInGroup

Used in groups: OrderEventGrp

#### **180.2.3248 NoOrders**

Indicates number of orders to be combined for average pricing and allocation.

Type: NumInGroup

Used in groups: ListOrdGrp, OrdAllocGrp, OrdListStatGrp, OrderAggregationGrp, RelatedOrderGrp



#### **180.2.3249 NoOrdTypeRules**

Number of order types

Type: NumInGroup

Used in groups: OrdTypeRules

#### **180.2.3250 NoPartyDetailAltID**

Number of party alternative identifiers.

Type: NumInGroup

Used in groups: PartyDetailAltIDGrp

#### **180.2.3251 NoPartyDetailAltSubIDs**

Number of party detail alternate sub-identifiers.

Type: NumInGroup

Used in groups: PartyDetailAltSubGrp

#### **180.2.3252 NoPartyDetails**

Number of party details.

Type: NumInGroup

Used in groups: PartyDetailGrp

#### **180.2.3253 NoPartyDetailSubIDs**

Number of party detail sub-identifiers.

Type: NumInGroup

Used in groups: PartyDetailSubGrp

#### **180.2.3254 NoPartyEntitlements**

Number of party entitlement values.

Type: **NumInGroup**

Used in groups: **PartyEntitlementAckGrp, PartyEntitlementGrp, PartyEntitlementUpdateGrp**

#### **180.2.3255 NoPartyIDs**

Number of PartyID (448), PartyIDSource (447), and PartyRole (452) entries

Type: **NumInGroup**

Used in groups: **Parties**

#### **180.2.3256 NoPartyRelationships**

Number of party relationships.

Type: **NumInGroup**

Used in groups: **PartyRelationshipGrp**

#### **180.2.3257 NoPartyRiskLimits**

Number of party risk limits.

Type: **NumInGroup**

Used in groups: **PartyRiskLimitsAckGrp, PartyRiskLimitsGrp, PartyRiskLimitsUpdateGrp**

#### **180.2.3258 NoPartySubIDs**

Number of PartySubID (523) and PartySubIDType (803) entries

Type: **NumInGroup**

Used in groups: **PtysSubGrp**

**180.2.3259 NoPartyUpdates**

Number of party updates.

Type: NumInGroup

Used in groups: PartyDetailAckGrp, PartyDetailsUpdateGrp

**180.2.3260 NoPayCollects**

Number of pay collect entries.

Type: NumInGroup

Used in groups: PayCollectGrp

**180.2.3261 NoPaymentBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentBusinessCenterGrp

**180.2.3262 NoPayments**

Number of additional settlement or bullet payments.

Type: NumInGroup

Used in groups: PaymentGrp

**180.2.3263 NoPaymentScheduleFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentScheduleFixingDateBusinessCenterGrp

#### **180.2.3264 NoPaymentScheduleFixingDays**

Number of fixing days in the repeating group.

Type: NumInGroup

Used in groups: PaymentScheduleFixingDayGrp

#### **180.2.3265 NoPaymentScheduleInterimExchangeDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentScheduleInterimExchangeDateBusinessCenterGrp

#### **180.2.3266 NoPaymentScheduleRateSources**

Number of swap schedule rate sources.

Type: NumInGroup

Used in groups: PaymentScheduleRateSourceGrp

#### **180.2.3267 NoPaymentSchedules**

Number of swap schedules in the repeating group

Type: NumInGroup

Used in groups: PaymentScheduleGrp

#### **180.2.3268 NoPaymentSettlPartyIDs**

Number of parties identified in the additional settlement or bullet payment.

Type: NumInGroup

Used in groups: PaymentSettlParties

#### **180.2.3269 NoPaymentSettlPartySubIDs**

Number of sub-party IDs to be reported for the party.

Type: NumInGroup

Used in groups: PaymentSettlPtysSubGrp

#### **180.2.3270 NoPaymentSettls**

Number of additional settlements or bullet payments.

Type: NumInGroup

Used in groups: PaymentSettlGrp

#### **180.2.3271 NoPaymentStreamCompoundingDates**

Number of dates in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamCompoundingDateGrp

#### **180.2.3272 NoPaymentStreamCompoundingDatesBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamCompoundingDatesBusinessCenterGrp

#### **180.2.3273 NoPaymentStreamFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamFixingDateBusinessCenterGrp

#### **180.2.3274 NoPaymentStreamFixingDates**

Number of fixing dates in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamFixingDateGrp

#### **180.2.3275 NoPaymentStreamFormulas**

Number of formulas in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamFormulaMathGrp

#### **180.2.3276 NoPaymentStreamInitialFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamInitialFixingDateBusinessCenterGrp

#### **180.2.3277 NoPaymentStreamNonDeliverableFixingDatesBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamNonDeliverableFixingDatesBusinessCenterGrp

#### **180.2.3278 NoPaymentStreamPaymentDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamPaymentDateBusinessCenterGrp

**180.2.3279 NoPaymentStreamPaymentDates**

Number of payment dates in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamPaymentDateGrp

**180.2.3280 NoPaymentStreamPricingBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamPricingBusinessCenterGrp

**180.2.3281 NoPaymentStreamPricingDates**

Number of pricing dates in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamPricingDateGrp

**180.2.3282 NoPaymentStreamPricingDays**

Number of pricing days in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamPricingDayGrp

**180.2.3283 NoPaymentStreamResetDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStreamResetDateBusinessCenterGrp

**180.2.3284 NoPaymentStubEndDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStubEndDateBusinessCenterGrp

**180.2.3285 NoPaymentStubs**

Number of stubs in the repeating group

Type: NumInGroup

Used in groups: PaymentStubGrp

**180.2.3286 NoPaymentStubStartDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PaymentStubStartDateBusinessCenterGrp

**180.2.3287 NoPhysicalSettlDeliverableObligations**

Number of entries in the repeating group.

Type: NumInGroup

Used in groups: PhysicalSettlDeliverableObligationGrp

**180.2.3288 NoPhysicalSettlTerms**

Number of entries in the repeating group.

Type: NumInGroup

Used in groups: PhysicalSettlTermGrp



#### **180.2.3289 NoPosAmt**

Number of position amount entries.

Type: **NumInGroup**

Used in groups: **PositionAmountData**

#### **180.2.3290 NoPositions**

Number of position entries.

Type: **NumInGroup**

Used in groups: **PositionQty, TradePositionQty**

#### **180.2.3291 NoPriceMovements**

Number of price movement entries.

Type: **NumInGroup**

Used in groups: **PriceMovementGrp**

#### **180.2.3292 NoPriceMovementValues**

Number of price movement value entries.

Type: **NumInGroup**

Used in groups: **PriceMovementValueGrp**

#### **180.2.3293 NoPriceQualifiers**

Number of price qualifiers in the repeating group.

Type: **NumInGroup**

Used in groups: **PriceQualifierGrp**

#### **180.2.3294 NoPriceRangeRules**

Number of rules related to price ranges.

Type: NumInGroup

Used in groups: PriceRangeRuleGrp

#### **180.2.3295 NoPricingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: PricingDateBusinessCenterGrp

#### **180.2.3296 NoProtectionTermEventNewsSources**

Number of event news sources in the repeating group.

Type: NumInGroup

Used in groups: ProtectionTermEventNewsSourceGrp

#### **180.2.3297 NoProtectionTermEventQualifiers**

Number of qualifiers in the repeating group.

Type: NumInGroup

Used in groups: ProtectionTermEventQualifierGrp

#### **180.2.3298 NoProtectionTermEvents**

Number of protection term events in the repeating group.

Type: NumInGroup

Used in groups: ProtectionTermEventGrp

#### **180.2.3299 NoProtectionTermObligations**

Number of obligations in the repeating group.

Type: NumInGroup

Used in groups: ProtectionTermObligationGrp

#### **180.2.3300 NoProtectionTerms**

Number of protection terms in the repeating group.

Type: NumInGroup

Used in groups: ProtectionTermGrp

#### **180.2.3301 NoProvisionCashSettlPaymentDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: ProvisionCashSettlPaymentDateBusinessCenterGrp

#### **180.2.3302 NoProvisionCashSettlPaymentDates**

Number of provision cash settlement payment dates in the repeating group.

Type: NumInGroup

Used in groups: ProvisionCashSettlPaymentFixedDateGrp

#### **180.2.3303 NoProvisionCashSettlValueDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: ProvisionCashSettlValueDateBusinessCenterGrp

#### **180.2.3304 NoProvisionDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: ProvisionDateBusinessCenterGrp

#### **180.2.3305 NoProvisionOptionExerciseBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: ProvisionOptionExerciseBusinessCenterGrp

#### **180.2.3306 NoProvisionOptionExerciseFixedDates**

Number of provision option exercise fixed dates in the repeating group.

Type: NumInGroup

Used in groups: ProvisionOptionExerciseFixedDateGrp

#### **180.2.3307 NoProvisionOptionExpirationDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: ProvisionOptionExpirationDateBusinessCenterGrp

#### **180.2.3308 NoProvisionOptionRelevantUnderlyingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: ProvisionOptionRelevantUnderlyingDateBusinessCenterGrp

#### **180.2.3309 NoProvisionPartyIDs**

Number of parties identified in the contract provision.

Type: **NumInGroup**

Used in groups: **ProvisionParties**

#### **180.2.3310 NoProvisionPartySubIDs**

Number of sub-party IDs to be reported for the party.

Type: **NumInGroup**

Used in groups: **ProvisionPtysSubGrp**

#### **180.2.3311 NoProvisions**

Number of provisions in the repeating group.

Type: **NumInGroup**

Used in groups: **ProvisionGrp**

#### **180.2.3312 NoQuoteAttributes**

Number of quote attributes entries.

Type: **NumInGroup**

Used in groups: **QuoteAttributeGrp**

#### **180.2.3313 NoQuoteEntries**

The number of quote entries for a QuoteSet.

Type: **NumInGroup**

Used in groups: **QuotCxlEntriesGrp**, **QuotEntryAckGrp**, **QuotEntryGrp**

#### **180.2.3314 NoQuoteQualifiers**

Number of repeating groups of QuoteQualifiers (695).

Type: NumInGroup

Used in groups: QuotQualGrp

#### **180.2.3315 NoQuoteSets**

The number of sets of quotes in the message.

Type: NumInGroup

Used in groups: QuotSetAckGrp, QuotSetGrp

#### **180.2.3316 NoQuoteSizeRules**

Number of rules related to quote sizes.

Type: NumInGroup

Used in groups: QuoteSizeRuleGrp

#### **180.2.3317 NoRateSources**

Number of rate sources being specified.

Type: NumInGroup

Used in groups: RateSource

#### **180.2.3318 NoReferenceDataDates**

Number of instances of reference data dates.

Type: NumInGroup

Used in groups: ReferenceDataDateGrp

#### **180.2.3319 NoRegistDtls**

The number of registration details on a Registration Instructions message

Type: NumInGroup

Used in groups: RgstDtlsGrp

#### **180.2.3320 NoRegulatoryTradeIDs**

Number of regulatory IDs in the repeating group.

Type: NumInGroup

Used in groups: RegulatoryTradeIDGrp

#### **180.2.3321 NoRelatedInstruments**

Number of related instruments

Type: NumInGroup

Used in groups: RelatedInstrumentGrp

#### **180.2.3322 NoRelatedMarketSegments**

Number of related market segments.

Type: NumInGroup

Used in groups: RelatedMarketSegmentGrp

#### **180.2.3323 NoRelatedPartyDetailAltID**

Number of related party detail alternate identifiers.

Type: NumInGroup

Used in groups: RelatedPartyDetailAltIDGrp

#### **180.2.3324 NoRelatedPartyDetailAltSubIDs**

Number of related party detail alternate sub-identifiers.

Type: NumInGroup

Used in groups: RelatedPartyDetailAltSubGrp

#### **180.2.3325 NoRelatedPartyDetailID**

Number of related party detail identifiers.

Type: NumInGroup

Used in groups: RelatedPartyDetailGrp

#### **180.2.3326 NoRelatedPartyDetailSubIDs**

Number of related party detail sub-identifiers.

Type: NumInGroup

Used in groups: RelatedPartyDetailSubGrp

#### **180.2.3327 NoRelatedPositions**

Number of related positions.

Type: NumInGroup

Used in groups: RelatedPositionGrp

#### **180.2.3328 NoRelatedSym**

Specifies the number of repeating symbols specified.

Type: NumInGroup

Used in groups: InstrmtGrp, InstrmtMDReqGrp, QuotReqGrp, QuotReqRjctGrp, RFQReqGrp, RelSymDerivSecGrp, RelSymDerivSecUpdGrp, SecListGrp, SecLstUpdRelSymGrp, SecMassStatGrp, StrmAsgnReqInstrmtGrp, StrmAsgnRptInstrmtGrp



#### **180.2.3329 NoRelatedTrades**

Number of related trades.

Type: NumInGroup

Used in groups: RelatedTradeGrp

#### **180.2.3330 NoRelativeValues**

Number of relative value metrics entries in the repeating group.

Type: NumInGroup

Used in groups: RelativeValueGrp

#### **180.2.3331 NoRequestedPartyRoles**

Number of requested party roles.

Type: NumInGroup

Used in groups: RequestedPartyRoleGrp

#### **180.2.3332 NoRequestedRiskLimitType**

Number of risk limit types requested.

Type: NumInGroup

Used in groups: RequestedRiskLimitTypesGrp

#### **180.2.3333 NoRequestingPartyIDs**

Number of requesting party identifiers.

Type: NumInGroup

Used in groups: RequestingPartyGrp

#### **180.2.3334 NoRequestingPartySubIDs**

Number of requesting party sub-identifiers.

Type: NumInGroup

Used in groups: RequestingPartySubGrp

#### **180.2.3335 NoReturnRateDates**

Number of iterations in the return rate date repeating group.

Type: NumInGroup

Used in groups: ReturnRateDateGrp

#### **180.2.3336 NoReturnRateFXConversions**

Number of iterations in the return rate FX conversion repeating group.

Type: NumInGroup

Used in groups: ReturnRateFXConversionGrp

#### **180.2.3337 NoReturnRateInformationSources**

Number of iterations in the return rate information source repeating group.

Type: NumInGroup

Used in groups: ReturnRateInformationSourceGrp

#### **180.2.3338 NoReturnRatePrices**

Number of iterations in the return rate price repeating group.

Type: NumInGroup

Used in groups: ReturnRatePriceGrp

#### **180.2.3339 NoReturnRates**

Number of iterations in the return rate repeating group.

Type: NumInGroup

Used in groups: ReturnRateGrp

#### **180.2.3340 NoReturnRateValuationDateBusinessCenters**

Number of iterations in the return rate valuation date business center repeating group.

Type: NumInGroup

Used in groups: ReturnRateValuationDateBusinessCenterGrp

#### **180.2.3341 NoReturnRateValuationDates**

Number of iterations in the return rate valuation date repeating group.

Type: NumInGroup

Used in groups: ReturnRateValuationDateGrp

#### **180.2.3342 NoRiskInstrumentScopes**

Number of risk instrument scopes.

Type: NumInGroup

Used in groups: RiskInstrumentScopeGrp

#### **180.2.3343 NoRiskLimits**

Number of risk limits for different instrument scopes.

Type: NumInGroup

Used in groups: RiskLimitsGrp

#### **180.2.3344 NoRiskLimitTypes**

Number of risk limits with associated warning levels.

Type: **NumInGroup**

Used in groups: **RiskLimitTypesGrp**

#### **180.2.3345 NoRiskWarningLevels**

Number of risk warning levels.

Type: **NumInGroup**

Used in groups: **RiskWarningLevelGrp**

#### **180.2.3346 NoRootPartyIDs**

Number of RootPartyID (1117), RootPartyIDSource (1118), and RootPartyRole (1119) entries

Type: **NumInGroup**

Used in groups: **RootParties**

#### **180.2.3347 NoRootPartySubIDs**

Number of RootPartySubID (1121) and RootPartySubIDType (1122) entries

Type: **NumInGroup**

Used in groups: **RootSubParties**

#### **180.2.3348 NoRoutingIDs**

Number of repeating groups of RoutingID (217) and RoutingType (216) values.

See Volume 3: "Pre-Trade Message Targeting/Routing"

Type: **NumInGroup**

Used in groups: **RoutingGrp**

#### **180.2.3349 NoRpts**

Total number of reports within series.

Type: **int**

Used in messages: **ListStatus**

#### **180.2.3350 NoSecondaryAssetClasses**

Number of secondary asset classes in the repeating group.

Type: **NumInGroup**

Used in groups: **SecondaryAssetGrp**

#### **180.2.3351 NoSecurityAltID**

Number of SecurityAltID (455) entries.

Type: **NumInGroup**

Used in groups: **SecAltIDGrp**

#### **180.2.3352 NoSecurityClassifications**

Number of Security Classifications.

Type: **NumInGroup**

Used in groups: **SecurityClassificationGrp**

#### **180.2.3353 NoSecurityRiskMetrics**

Number of instruments with security risk metrics data.

Type: **NumInGroup**

Used in groups: **SecurityRiskMetricGrp**

#### **180.2.3354 NoSecurityTypes**

Number of Security Type repeating group instances.

Type: NumInGroup

Used in groups: SecTypesGrp

#### **180.2.3355 NoSettlDetails**

Used to group Each Settlement Party

Type: NumInGroup

Used in groups: SettlDetails

#### **180.2.3356 NoSettlementAmounts**

Number of settlement amount entries.

Type: NumInGroup

Used in groups: SettlementAmountGrp

#### **180.2.3357 NoSettlInst**

Number of settlement instructions within repeating group.

Type: NumInGroup

Used in groups: SettlInstGrp

#### **180.2.3358 NoSettlMethodElectionDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: SettlMethodElectionDateBusinessCenterGrp

#### **180.2.3359 NoSettlOblig**

Number of settlement obligations

Type: **NumInGroup**

Used in groups: **SettlObligationInstructions**

#### **180.2.3360 NoSettlPartyIDs**

Number of SettlPartyID (782), SettlPartyIDSource (783), and SettlPartyRole (784) entries

Type: **NumInGroup**

Used in groups: **SettlParties**

#### **180.2.3361 NoSettlPartySubIDs**

Number of SettlPartySubID (785) and SettlPartySubIDType (786) entries

Type: **NumInGroup**

Used in groups: **SettlPtysSubGrp**

#### **180.2.3362 NoSettlRateFallbacks**

Number of settlement rate fallbacks in the repeating group

Type: **NumInGroup**

Used in groups: **SettlRateDisruptionFallbackGrp**

#### **180.2.3363 NoSideCollateralAmounts**

Number of side collateral amount entries.

Type: **NumInGroup**

Used in groups: **SideCollateralAmountGrp**

**180.2.3364 NoSideCollateralReinvestments**

Number of instances of SideCollateralReinvestmentType(2867) in the repeating group.

Type: NumInGroup

Used in groups: SideCollateralReinvestmentGrp

**180.2.3365 NoSideRegulatoryTradeIDs**

Number of regulatory IDs in the repeating group.

Type: NumInGroup

Used in groups: SideRegulatoryTradeIDGrp

**180.2.3366 NoSides**

Number of Side repeating group instances.

Type: NumInGroup

Allowed values in NoSidesCodeSet:

Code	Name	Description
1	OneSide	One Side
2	BothSides	Both Sides

Used in groups: SideCrossOrdCxlGrp, SideCrossOrdModGrp, TrdCapRptAckSideGrp, TrdCapRptSideGrp

**180.2.3367 NoSideTrdRegTS**

Number of timestamp entries.

Type: NumInGroup

Used in groups: SideTrdRegTS



#### **180.2.3368 NoStatsIndicators**

Number of statistics indicator repeating group entries

Type: NumInGroup

Used in groups: StatsIndGrp

#### **180.2.3369 NoStipulations**

Number of stipulation entries

(Note tag # was reserved in FIX 4.1, added in FIX 4.3).

Type: NumInGroup

Used in groups: Stipulations

#### **180.2.3370 NoStrategyParameters**

Indicates number of strategy parameters

Type: NumInGroup

Used in groups: StrategyParametersGrp

#### **180.2.3371 NoStreamAssetAttributes**

Number of asset attribute entries in the group.

Type: NumInGroup

Used in groups: StreamAssetAttributeGrp

#### **180.2.3372 NoStreamCalculationPeriodBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: StreamCalculationPeriodBusinessCenterGrp

#### **180.2.3373 NoStreamCalculationPeriodDates**

Number of calculation period dates in the repeating group.

Type: NumInGroup

Used in groups: StreamCalculationPeriodDateGrp

#### **180.2.3374 NoStreamCommodityAltIDs**

Number of alternate security identifiers.

Type: NumInGroup

Used in groups: StreamCommodityAltIDGrp

#### **180.2.3375 NoStreamCommodityDataSources**

Number of data sources in the repeating group. The order of entry determines priority – first is the main source, second is fallback, third is second fallback.

Type: NumInGroup

Used in groups: StreamCommodityDataSourceGrp

#### **180.2.3376 NoStreamCommoditySettlBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: StreamCommoditySettlBusinessCenterGrp

#### **180.2.3377 NoStreamCommoditySettlDays**

Number of days in the repeating group.

Type: NumInGroup

Used in groups: StreamCommoditySettlDayGrp

#### **180.2.3378 NoStreamCommoditySettlPeriods**

Number of commodity settlement periods in the repeating group.

Type: **NumInGroup**

Used in groups: **StreamCommoditySettlPeriodGrp**

#### **180.2.3379 NoStreamCommoditySettlTimes**

Number of hour ranges in the repeating group.

Type: **NumInGroup**

Used in groups: **StreamCommoditySettlTimeGrp**

#### **180.2.3380 NoStreamEffectiveDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **StreamEffectiveDateBusinessCenterGrp**

#### **180.2.3381 NoStreamFirstPeriodStartDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **StreamFirstPeriodStartDateBusinessCenterGrp**

#### **180.2.3382 NoStreams**

Number of swap streams in the repeating group.

Type: **NumInGroup**

Used in groups: **StreamGrp**

**180.2.3383 NoStreamTerminationDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **StreamTerminationDateBusinessCenterGrp**

**180.2.3384 NoStrikeRules**

Number of strike rule entries. This block specifies the rules for determining how new strikes should be listed within the stated price range of the underlying instrument

Type: **NumInGroup**

Used in groups: **StrikeRules**

**180.2.3385 NoStrikes**

Number of list strike price entries.

Type: **NumInGroup**

Used in groups: **InstrmtStrkPxGrp**

**180.2.3386 NotAffectedMarketSegmentGrp**

List of market segments that were not affected by a mass action.

Name	Mult.	Type	Description
<b>NoNotAffectedMarketSegments</b>	[1..1]	NumInGroup	
<b>NotAffectedMarketSegmentID</b>	[0..1]	String	Required when NoNotAffectedMarketSegments(1793) > 0.

Used in messages: **OrderMassActionReport**

**180.2.3387 NotAffectedMarketSegmentID**

Market segment within an unaffected market repeating segment group.

Type: **String**

Used in groups: **NotAffectedMarketSegmentGrp**

**180.2.3388 NotAffectedOrderID**

OrderID(37) of an order not affected by a mass cancel or mass action request.

Type: **String**

Used in groups: **NotAffectedOrdGrp**

**180.2.3389 NotAffectedOrdGrp**

Name	Mult.	Type	Description
NoNotAffectedOrders	[1..1]	NumInGroup	
NotAffOrigCLOrdID	[0..1]	String	Required if NoNotAffectedOrders(1370) > 0 and must be the first repeating field in the group. Indicates the client order identifier of an order not affected by the request. If order(s) were manually delivered (or otherwise not delivered over FIX and not assigned a CLOrdID(11)) this field should contain string "MANUAL".
NotAffectedOrderID	[0..1]	String	Contains the OrderID(37) assigned by the counterparty of an unaffected order. Not required as part of the repeating group if NotAffOrigCLOrdID(1372) has a value other than "MANUAL".
NotAffSecondaryOrderID	[0..1]	String	Contains the SecondaryOrderID(198) assigned by the counterparty of an unaffected order. Not required as part of the repeating group.
NotAffectedReason	[0..1]	CodeSet	Can be used to provide a reason for excluding this order from the scope of the mass action.

Used in messages: **OrderMassActionReport**, **OrderMassCancelReport**

**180.2.3390 NotAffectedReason**

Reason for order being unaffected by mass action even though it belongs to the orders covered by MassActionScope(1374).

Type: **int**

Allowed values in NotAffectedReasonCodeSet:

Code	Name	Description
0	OrderSuspended	Order suspended
1	InstrumentSuspended	Instrument suspended

Used in groups: **NotAffectedOrdGrp**

#### **180.2.3391 NotAffOrigClOrdID**

ClOrdID(11) of an order not affected by a mass cancel or mass action request.

Type: **String**

Used in groups: **NotAffectedOrdGrp**

#### **180.2.3392 NotAffSecondaryOrderID**

SecondaryOrderID (198) of an order not affected by a mass cancel or mass action request.

Type: **String**

Used in groups: **NotAffectedOrdGrp**

#### **180.2.3393 NoTargetMarketSegments**

Number of market segments upon which a mass action is to be taken.

Type: **NumInGroup**

Used in groups: **TargetMarketSegmentGrp**

#### **180.2.3394 NoTargetPartyIDs**

Identifies the number of target parties identified in a mass action.

Type: **NumInGroup**

Used in groups: **TargetParties**

#### **180.2.3395 NoTargetPartySubIDs**

Number of target party sub IDs in the repeating group.

Type: NumInGroup

Used in groups: TargetPtysSubGrp

#### **180.2.3396 NoTestGatewayDetails**

Number of test gateway details.

Type: NumInGroup

Used in groups: TestGatewayDetailGrp

#### **180.2.3397 NoTestMeasures**

Number of results for a test scenario.

Type: NumInGroup

Used in groups: TestMeasureGrp

#### **180.2.3398 NoTestOrders**

Number of orders for testing.

Type: NumInGroup

Used in groups: TestOrderGrp

#### **180.2.3399 NoTestScenarios**

Number of test scenarios for an algorithmic trading system.

Type: NumInGroup

Used in groups: TestScenarioGrp

#### **180.2.3400 NoTestStepParameters**

Number of test step parameters.

Type: NumInGroup

Used in groups: TestStepParameterGrp

#### **180.2.3401 NoTestSteps**

Number of test steps.

Type: NumInGroup

Used in groups: TestStepGrp

#### **180.2.3402 NoTestSystemModules**

Number of components making up a testing system.

Type: NumInGroup

Used in groups: TestSystemModuleGrp

#### **180.2.3403 NoThrottleMsgType**

Number of ThrottleMsgType fields.

Type: NumInGroup

Used in groups: ThrottleMsgTypeGrp

#### **180.2.3404 NoThrottles**

Indicates number of repeating groups to follow.

Type: NumInGroup

Used in groups: ThrottleParamsGrp



**180.2.3405 NoTickRules**

Number of tick rules. This block specifies the rules for determining how a security ticks, i.e. the price increments at which it can be quoted and traded, depending on the current price of the security

Type: **NumInGroup**

Used in groups: **TickRules**

**180.2.3406 NotifyBrokerOfCredit**

Indicates whether or not details should be communicated to BrokerOfCredit (i.e. step-in broker).

Type: **Boolean**

Allowed values in NotifyBrokerOfCreditCodeSet:

Code	Name	Description
N	DetailsShouldNotBeCommunicated	Details should not be communicated
Y	DetailsShouldBeCommunicated	Details should be communicated

Used in groups: **AllocGrp**

**180.2.3407 NoTimeInForceRules**

Number of time in force techniques

Type: **NumInGroup**

Used in groups: **TimeInForceRules**

**180.2.3408 NotionalPercentageOutstanding**

Indicates the notional percentage of the deal that is still outstanding based on the remaining components of the index.

Used to calculate the true value of a CDS trade or position.

Type: **Percentage**

Used in components: **Instrument**

#### **180.2.3409 NoTradeAllocAmts**

Number of trade allocation amount entries.

Type: NumInGroup

Used in groups: TradeAllocAmtGrp

#### **180.2.3410 NoTradePriceConditions**

Number of trade price conditions.

Type: NumInGroup

Used in groups: TradePriceConditionGrp

#### **180.2.3411 NoTradeQtys**

Number of trade quantities.

Type: NumInGroup

Used in groups: TradeQtyGrp

#### **180.2.3412 NoTrades**

Number of trades in repeating group.

Type: NumInGroup

Used in groups: TrdCollGrp

#### **180.2.3413 NoTradeTypes**

Number of trade types in repeating group.

Type: NumInGroup

Used in groups: TradeTypeGrp

#### **180.2.3414 NoTradingSessionRules**

Allows trading rules to be expressed by trading session

Type: **NumInGroup**

Used in groups: **TradingSessionRulesGrp**

#### **180.2.3415 NoTradingSessions**

Number of TradingSessionIDs (336) in repeating group.

Type: **NumInGroup**

Used in groups: **TrdSessLstGrp**, **TrdgSesGrp**

#### **180.2.3416 NoTransactionAttributes**

Number of instances of TransactionAttributeType(2872) in the repeating group.

Type: **NumInGroup**

Used in groups: **TransactionAttributeGrp**

#### **180.2.3417 NoTrdMatchSides**

Number of trade match sides.

Type: **NumInGroup**

Used in groups: **TrdMatchSideGrp**

#### **180.2.3418 NoTrdRegPublications**

Number of regulatory publication rules in repeating group.

Type: **NumInGroup**

Used in groups: **TrdRegPublicationGrp**

#### **180.2.3419 NoTrdRegTimestamps**

Number of timestamp entries.

Type: **NumInGroup**

Used in groups: **TrdRegTimestamps**

#### **180.2.3420 NoTrdRepIndicators**

Number of trade reporting indicators

Type: **NumInGroup**

Used in groups: **TrdRepIndicatorsGrp**

#### **180.2.3421 NoUnderlyingAdditionalTermBondRefs**

Number of bonds in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingAdditionalTermBondRefGrp**

#### **180.2.3422 NoUnderlyingAdditionalTerms**

Number of additional terms in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingAdditionalTermGrp**

#### **180.2.3423 NoUnderlyingAmounts**

Total number of occurrences of Amount to pay in order to receive the underlying instrument

Type: **NumInGroup**

Used in groups: **UnderlyingAmount**

**180.2.3424 NoUnderlyingAssetAttributes**

Number of asset attribute entries in the group.

Type: **NumInGroup**

Used in groups: **UnderlyingAssetAttributeGrp**

**180.2.3425 NoUnderlyingBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingBusinessCenterGrp**

**180.2.3426 NoUnderlyingCashSettlDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingCashSettlDateBusinessCenterGrp**

**180.2.3427 NoUnderlyingCashSettlDealers**

Number of dealers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingCashSettlDealerGrp**

**180.2.3428 NoUnderlyingCashSettlTerms**

Number of elements in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingCashSettlTermGrp**

#### **180.2.3429 NoUnderlyingComplexEventAveragingObservations**

The number of averaging observations in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventAveragingObservationGrp

#### **180.2.3430 NoUnderlyingComplexEventCreditEventQualifiers**

Number of qualifiers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventCreditEventQualifierGrp

#### **180.2.3431 NoUnderlyingComplexEventCreditEvents**

The number of credit events specified in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventCreditEventGrp

#### **180.2.3432 NoUnderlyingComplexEventCreditEventSources**

Number of event sources in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventCreditEventSourceGrp

#### **180.2.3433 NoUnderlyingComplexEventDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventDateBusinessCenterGrp

#### **180.2.3434 NoUnderlyingComplexEventDates**

Number of underlying complex event dates in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventDates

#### **180.2.3435 NoUnderlyingComplexEventPeriodDateTimes**

Number of entries in the date-time repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventPeriodDateGrp

#### **180.2.3436 NoUnderlyingComplexEventPeriods**

Number of periods in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventPeriodGrp

#### **180.2.3437 NoUnderlyingComplexEventRateSources**

Number of rate sources in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEventRateSourceGrp

#### **180.2.3438 NoUnderlyingComplexEvents**

Number of complex events in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingComplexEvents

#### **180.2.3439 NoUnderlyingComplexEventSchedules**

Number of schedules in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingComplexEventScheduleGrp**

#### **180.2.3440 NoUnderlyingComplexEventTimes**

Number of complex event times in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingComplexEventTimes**

#### **180.2.3441 NoUnderlyingDeliverySchedules**

Number of delivery schedules in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingDeliveryScheduleGrp**

#### **180.2.3442 NoUnderlyingDeliveryScheduleSettlDays**

Number of delivery schedules in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingDeliveryScheduleSettlDayGrp**

#### **180.2.3443 NoUnderlyingDeliveryScheduleSettlTimes**

Number of hour ranges in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingDeliveryScheduleSettlTimeGrp**



#### **180.2.3444 NoUnderlyingDeliveryStreamCommoditySources**

Number of commodity sources in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingDeliveryStreamCommoditySourceGrp**

#### **180.2.3445 NoUnderlyingDeliveryStreamCycles**

Number of delivery cycles in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingDeliveryStreamCycleGrp**

#### **180.2.3446 NoUnderlyingDividendAccrualPaymentDateBusinessCenters**

Number of entries in the UnderlyingDividendAccrualPaymentDateBusinessCenterGrp.

Type: **NumInGroup**

Used in groups: **UnderlyingDividendAccrualPaymentDateBusinessCenterGrp**

#### **180.2.3447 NoUnderlyingDividendFXTriggerDateBusinessCenters**

Number of entries in the UnderlyingDividendFXTriggerDateBusinessCenterGrp.

Type: **NumInGroup**

Used in groups: **UnderlyingDividendFXTriggerDateBusinessCenterGrp**

#### **180.2.3448 NoUnderlyingDividendPayments**

Number of entries in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingDividendPaymentGrp**

#### **180.2.3449 NoUnderlyingDividendPeriodBusinessCenters**

Number of entries in UnderlyingDividendPeriodBusinessCenterGrp.

Type: NumInGroup

Used in groups: UnderlyingDividendPeriodBusinessCenterGrp

#### **180.2.3450 NoUnderlyingDividendPeriods**

Number of entries in the UnderlyingDividendPeriodGrp component.

Type: NumInGroup

Used in groups: UnderlyingDividendPeriodGrp

#### **180.2.3451 NoUnderlyingEvents**

Number of events in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingEvntGrp

#### **180.2.3452 NoUnderlyingExtraordinaryEvents**

Number of extraordinary events in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingExtraordinaryEventGrp

#### **180.2.3453 NoUnderlyingLegSecurityAltID**

Refer to definition for NoSecurityAltID(454)

Type: NumInGroup

Used in groups: UnderlyingLegSecurityAltIDGrp

#### **180.2.3454 NoUnderlyingMarketDisruptionEvents**

Number of disruption events in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingMarketDisruptionEventGrp

#### **180.2.3455 NoUnderlyingMarketDisruptionFallbackReferencePrices**

Number of fallback reference securities in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingMarketDisruptionFallbackReferencePriceGrp

#### **180.2.3456 NoUnderlyingMarketDisruptionFallbacks**

Number of fallbacks in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingMarketDisruptionFallbackGrp

#### **180.2.3457 NoUnderlyingNonDeliverableFixingDates**

Number of Fixing dates in the repeating group

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamNonDeliverableFixingDateGrp

#### **180.2.3458 NoUnderlyingOptionExerciseBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingOptionExerciseBusinessCenterGrp

**180.2.3459 NoUnderlyingOptionExerciseDates**

Number of dates in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingOptionExerciseDateGrp

**180.2.3460 NoUnderlyingOptionExerciseExpirationDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingOptionExerciseExpirationDateBusinessCenterGrp

**180.2.3461 NoUnderlyingOptionExerciseExpirationDates**

Number of fixed exercise expiration dates in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingOptionExerciseExpirationDateGrp

**180.2.3462 NoUnderlyingPaymentScheduleFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentScheduleFixingDateBusinessCenterGrp

**180.2.3463 NoUnderlyingPaymentScheduleFixingDays**

Number of fixing days in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentScheduleFixingDayGrp

#### **180.2.3464 NoUnderlyingPaymentScheduleInterimExchangeDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingPaymentScheduleInterimExchangeDateBusinessCenterGrp**

#### **180.2.3465 NoUnderlyingPaymentScheduleRateSources**

Number of rate sources in the repeating group

Type: **NumInGroup**

Used in groups: **UnderlyingPaymentScheduleRateSourceGrp**

#### **180.2.3466 NoUnderlyingPaymentSchedules**

Number of swap schedules in the repeating group

Type: **NumInGroup**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.3467 NoUnderlyingPaymentStreamCompoundingDates**

Number of dates in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingPaymentStreamCompoundingDateGrp**

#### **180.2.3468 NoUnderlyingPaymentStreamCompoundingDatesBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingPaymentStreamCompoundingDatesBusinessCenterGrp**

#### **180.2.3469 NoUnderlyingPaymentStreamFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamFixingDateBusinessCenterGrp

#### **180.2.3470 NoUnderlyingPaymentStreamFixingDates**

Number of fixing dates in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamFixingDateGrp

#### **180.2.3471 NoUnderlyingPaymentStreamFormulas**

Number of formulas in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamFormulaMathGrp

#### **180.2.3472 NoUnderlyingPaymentStreamInitialFixingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamInitialFixingDateBusinessCenterGrp

#### **180.2.3473 NoUnderlyingPaymentStreamNonDeliverableFixingDatesBizCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp

**180.2.3474 NoUnderlyingPaymentStreamPaymentDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamPaymentDateBusinessCenterGrp

**180.2.3475 NoUnderlyingPaymentStreamPaymentDates**

Number of payment dates in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamPaymentDateGrp

**180.2.3476 NoUnderlyingPaymentStreamPricingBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamPricingBusinessCenterGrp

**180.2.3477 NoUnderlyingPaymentStreamPricingDates**

Number of pricing dates in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamPricingDateGrp

**180.2.3478 NoUnderlyingPaymentStreamPricingDays**

Number of pricing days in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamPricingDayGrp

**180.2.3479 NoUnderlyingPaymentStreamResetDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStreamResetDateBusinessCenterGrp

**180.2.3480 NoUnderlyingPaymentStubEndDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStubEndDateBusinessCenterGrp

**180.2.3481 NoUnderlyingPaymentStubs**

Number of stubs in the repeating group

Type: NumInGroup

Used in groups: UnderlyingPaymentStubGrp

**180.2.3482 NoUnderlyingPaymentStubStartDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPaymentStubStartDateBusinessCenterGrp

**180.2.3483 NoUnderlyingPhysicalSettlDeliverableObligations**

Number of entries in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPhysicalSettlDeliverableObligationGrp



#### **180.2.3484 NoUnderlyingPhysicalSettlTerms**

Number of entries in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPhysicalSettlTermGrp

#### **180.2.3485 NoUnderlyingPricingDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingPricingDateBusinessCenterGrp

#### **180.2.3486 NoUnderlyingProtectionTermEventNewsSources**

Number of event news sources in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProtectionTermEventNewsSourceGrp

#### **180.2.3487 NoUnderlyingProtectionTermEventQualifiers**

Number of qualifiers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProtectionTermEventQualifierGrp

#### **180.2.3488 NoUnderlyingProtectionTermEvents**

Number of protection term events in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProtectionTermEventGrp

#### **180.2.3489 NoUnderlyingProtectionTermObligations**

Number of obligations in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProtectionTermObligationGrp

#### **180.2.3490 NoUnderlyingProtectionTerms**

Number of protection terms in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProtectionTermGrp

#### **180.2.3491 NoUnderlyingProvisionCashSettlPaymentDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProvisionCashSettlPaymentDateBusinessCenterGrp

#### **180.2.3492 NoUnderlyingProvisionCashSettlPaymentDates**

Number of UnderlyingProvision cash settlement payment dates in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProvisionCashSettlPaymentFixedDateGrp

#### **180.2.3493 NoUnderlyingProvisionCashSettlValueDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProvisionCashSettlValueDateBusinessCenterGrp

**180.2.3494 NoUnderlyingProvisionDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingProvisionDateBusinessCenterGrp**

**180.2.3495 NoUnderlyingProvisionOptionExerciseBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingProvisionOptionExerciseBusinessCenterGrp**

**180.2.3496 NoUnderlyingProvisionOptionExerciseFixedDates**

Number of UnderlyingProvision option exercise fixed dates in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingProvisionOptionExerciseFixedDateGrp**

**180.2.3497 NoUnderlyingProvisionOptionExpirationDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingProvisionOptionExpirationDateBusinessCenterGrp**

**180.2.3498 NoUnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenterGrp**

#### **180.2.3499 NoUnderlyingProvisionPartyIDs**

Number of parties identified in the contract provision.

Type: NumInGroup

Used in groups: UnderlyingProvisionParties

#### **180.2.3500 NoUnderlyingProvisionPartySubIDs**

Number of sub-party IDs to be reported for the party.

Type: NumInGroup

Used in groups: UnderlyingProvisionPtysSubGrp

#### **180.2.3501 NoUnderlyingProvisions**

Number of provisions in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingProvisionGrp

#### **180.2.3502 NoUnderlyingRateSpreadSteps**

Number of entries in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingRateSpreadStepGrp

#### **180.2.3503 NoUnderlyingReturnRateDates**

Number of iterations in the return rate date repeating group.

Type: NumInGroup

Used in groups: UnderlyingReturnRateDateGrp

#### **180.2.3504 NoUnderlyingReturnRateFXConversions**

Number of iterations in the return rate FX conversion repeating group.

Type: NumInGroup

Used in groups: UnderlyingReturnRateFXConversionGrp

#### **180.2.3505 NoUnderlyingReturnRateInformationSources**

Number of iterations in the return rate information source repeating group.

Type: NumInGroup

Used in groups: UnderlyingReturnRateInformationSourceGrp

#### **180.2.3506 NoUnderlyingReturnRatePrices**

Number of iterations in the return rate price repeating group.

Type: NumInGroup

Used in groups: UnderlyingReturnRatePriceGrp

#### **180.2.3507 NoUnderlyingReturnRates**

Number of iterations in the return rate repeating group.

Type: NumInGroup

Used in groups: UnderlyingReturnRateGrp

#### **180.2.3508 NoUnderlyingReturnRateValuationDateBusinessCenters**

Number of iterations in the return rate valuation date business center repeating group.

Type: NumInGroup

Used in groups: UnderlyingReturnRateValuationDateBusinessCenterGrp

#### **180.2.3509 NoUnderlyingReturnRateValuationDates**

Number of iterations in the return rate valuation date repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingReturnRateValuationDateGrp**

#### **180.2.3510 NoUnderlyings**

Number of underlying legs that make up the security.

Type: **NumInGroup**

Used in groups: **PosUndInstrmtGrp**, **UndInstrmtCollGrp**, **UndInstrmtGrp**

#### **180.2.3511 NoUnderlyingSecondaryAssetClasses**

Number of secondary asset classes in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingSecondaryAssetGrp**

#### **180.2.3512 NoUnderlyingSecurityAltID**

Number of UnderlyingSecurityAltID (458) entries.

Type: **NumInGroup**

Used in groups: **UndSecAltIDGrp**

#### **180.2.3513 NoUnderlyingSettlMethodElectionDateBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingSettlMethodElectionDateBusinessCenterGrp**

#### **180.2.3514 NoUnderlyingSettlRateFallbacks**

Number of settlement rate fallbacks in the repeating group

Type: **NumInGroup**

Used in groups: **UnderlyingSettlRateDisruptionFallbackGrp**

#### **180.2.3515 NoUnderlyingStips**

Number of underlying stipulation entries

Type: **NumInGroup**

Used in groups: **UnderlyingStipulations**

#### **180.2.3516 NoUnderlyingStreamAssetAttributes**

Number of asset attribute entries in the group.

Type: **NumInGroup**

Used in groups: **UnderlyingStreamAssetAttributeGrp**

#### **180.2.3517 NoUnderlyingStreamCalculationPeriodBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingStreamCalculationPeriodBusinessCenterGrp**

#### **180.2.3518 NoUnderlyingStreamCalculationPeriodDates**

Number of calculation period dates in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingStreamCalculationPeriodDateGrp**

**180.2.3519 NoUnderlyingStreamCommodityAltIDs**

Number of alternate security identifiers.

Type: **NumInGroup**

Used in groups: **UnderlyingStreamCommodityAltIDGrp**

**180.2.3520 NoUnderlyingStreamCommodityDataSources**

Number of commodity data sources in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingStreamCommodityDataSourceGrp**

**180.2.3521 NoUnderlyingStreamCommoditySettlBusinessCenters**

Number of business centers in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingStreamCommoditySettlBusinessCenterGrp**

**180.2.3522 NoUnderlyingStreamCommoditySettlDays**

Number of days in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingStreamCommoditySettlDayGrp**

**180.2.3523 NoUnderlyingStreamCommoditySettlPeriods**

Number of commodity settlement periods in the repeating group.

Type: **NumInGroup**

Used in groups: **UnderlyingStreamCommoditySettlPeriodGrp**



**180.2.3524 NoUnderlyingStreamCommoditySettlTimes**

Number of hour ranges in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingStreamCommoditySettlTimeGrp

**180.2.3525 NoUnderlyingStreamEffectiveDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingStreamEffectiveDateBusinessCenterGrp

**180.2.3526 NoUnderlyingStreamFirstPeriodStartDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingStreamFirstPeriodStartDateBusinessCenterGrp

**180.2.3527 NoUnderlyingStreams**

Number of swap streams in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingStreamGrp

**180.2.3528 NoUnderlyingStreamTerminationDateBusinessCenters**

Number of business centers in the repeating group.

Type: NumInGroup

Used in groups: UnderlyingStreamTerminationDateBusinessCenterGrp

**180.2.3529 NoUndlyInstrumentParties**

Identifies the number of parties identified with an underlying instrument

Type: NumInGroup

Used in groups: UndlyInstrumentParties

**180.2.3530 NoUndlyInstrumentPartySubIDs**

Number of Underlying InstrumentPartySubID (1053) and InstrumentPartySubIDType (1054) entries

Type: NumInGroup

Used in groups: UndlyInstrumentPtysSubGrp

**180.2.3531 NoUsernames**

Number of Usernames to which this this response is directed

Type: NumInGroup

Used in groups: UsernameGrp

**180.2.3532 NoValueChecks**

Number of value check entries.

Type: NumInGroup

Used in groups: ValueChecksGrp

**180.2.3533 NstdPtys2SubGrp**

---

Name	Mult.	Type	Description
NoNested2PartySubIDs	[1..1]	NumInGroup	
Nested2PartySubID	[0..1]	String	
Nested2PartySubIDType	[0..1]	CodeSet	

---

Used in groups: NestedParties2

**180.2.3534 NstdPtys3SubGrp**

Name	Mult.	Type	Description
NoNested3PartySubIDs	[1..1]	NumInGroup	
Nested3PartySubID	[0..1]	String	
Nested3PartySubIDType	[0..1]	CodeSet	

Used in groups: **NestedParties3**

**180.2.3535 NstdPtys4SubGrp**

Name	Mult.	Type	Description
NoNested4PartySubIDs	[1..1]	NumInGroup	
Nested4PartySubID	[0..1]	String	
Nested4PartySubIDType	[0..1]	CodeSet	

Used in groups: **NestedParties4**

**180.2.3536 NstdPtysSubGrp**

Name	Mult.	Type	Description
NoNestedPartySubIDs	[1..1]	NumInGroup	
NestedPartySubID	[0..1]	String	
NestedPartySubIDType	[0..1]	CodeSet	

Used in groups: **NestedParties**

**180.2.3537 NthToDefault**

The Nth reference obligation to default in a CDS reference basket. If specified without MthToDefault(1943) the default will trigger a CDS payout. If MthToDefault(1943) is also present then payout occurs between the Nth and Mth obligations to default.

Type: **int**

Used in components: **Instrument**

#### **180.2.3538 NTPositionLimit**

Position Limit in the near-term contract for a given exchange-traded product.

Type: **int**

Used in components: **Instrument**

#### **180.2.3539 NumberOfBuyOrders**

Number of buy orders involved in a trade.

Type: **int**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.3540 NumberOfOrders**

Number of orders in the market.

Type: **int**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.3541 NumberOfSellOrders**

Number of sell orders involved in a trade.

Type: **int**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.3542 NumBidders**

Indicates the total number of bidders on the list

Type: **int**

Used in messages: **BidRequest**

**180.2.3543 NumDaysInterest**

Number of Days of Interest for convertible bonds and fixed income. Note value may be negative.

Type: **int**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **Confirmation**, **ExecutionReport**

**180.2.3544 NumOfCompetitors**

The number of competing Respondents (e.g. dealers) to receive a quote request (either via the QuoteRequest(35=R) or via other means).

Type: **int**

Used in groups: **QuotReqGrp**

**180.2.3545 NumOfComplexInstruments**

Represents the total number of multileg securities or user defined securities that make up the security.

Type: **int**

Used in messages: **SecurityDefinition**, **SecurityDefinitionUpdateReport**

**180.2.3546 NumOfSimpleInstruments**

Represents the total number of simple instruments that make up a multi-legged security. Complex spread instruments may be constructed of legs which themselves are multi-leg instruments.

Type: **int**

Used in groups: **RelSymDerivSecGrp**, **SecListGrp**

Used in messages: **SecurityDefinition**, **SecurityDefinitionUpdateReport**

**180.2.3547 NumTickets**

Total number of tickets.

Type: **int**

Used in messages: **BidRequest**

**180.2.3548 ObligationType**

Type of reference obligation for credit derivatives contracts.

Type: **String**

Allowed values in ObligationTypeCodeSet:

Code	Name	Description
0	Bond	Bond
1	ConvertBond	Convertible bond
2	Mortgage	Mortgage
3	Loan	Loan

Used in components: **Instrument**

**180.2.3549 OddLot**

This trade is to be treated as an odd lot

If this field is not specified, the default will be "N"

Type: **Boolean**

Allowed values in OddLotCodeSet:

Code	Name	Description
N	TreatAsRoundLot	Treat as round lot (default)
Y	TreatAsOddLot	Treat as odd lot

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

**180.2.3550 OfferForwardPoints**

Offer F/X forward points added to spot rate. May be a negative value.

Type: **PriceOffset**

Used in groups: **QuotEntryAckGrp**, **QuotEntryGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

**180.2.3551 OfferForwardPoints2**

Offer F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value.

Type: **PriceOffset**

Used in groups: **QuotEntryAckGrp**, **QuotEntryGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

**180.2.3552 OfferID**

Unique identifier for the ask side of the quote assigned by the quote issuer.

Type: **String**

Used in messages: **Quote**, **QuoteStatusReport**

**180.2.3553 OfferMDEntryID**

The market data entry identifier of the offer side of a quote.

Type: **String**

Used in messages: **QuoteStatusReport**

**180.2.3554 OfferPx**

Offer price/rate

Type: **Price**

Used in groups: **QuotEntryAckGrp**, **QuotEntryGrp**, **SecurityRiskMetricGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

**180.2.3555 OfferQuoteID**

Marketplace assigned quote identifier for the offer side. Can be used to indicate priority.

Type: **String**

Used in messages: **QuoteStatusReport**

**180.2.3556 OfferSize**

Quantity of offer

(Prior to FIX 4.2 this field was of type int)

Type: **Qty**

Used in groups: **QuotEntryAckGrp, QuotEntryGrp**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

**180.2.3557 OfferSpotRate**

Offer F/X spot rate.

Type: **Price**

Used in groups: **QuotEntryAckGrp, QuotEntryGrp**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

**180.2.3558 OfferSpread**

Basis points relative to a benchmark curve on the offer side, such as LIBOR, or a known security, such as 10Y US Treasury bond. The benchmark security or curve name is specified in the SpreadOrBenchmarkCurveData component.

Type: **float**

Used in messages: **Quote**

**180.2.3559 OfferSwapPoints**

The offer FX Swap points for an FX Swap. It is the "far offer forward points - near bid forward points". Value can be negative. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199



Type: **PriceOffset**

Used in messages: **Quote**

### **180.2.3560 OfferVolatility**

Volatility based on offer prices.

Type: **float**

Used in groups: **SecurityRiskMetricGrp**

### **180.2.3561 OfferYield**

Offer yield

Type: **Percentage**

Used in groups: **QuotEntryAckGrp**, **QuotEntryGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

### **180.2.3562 OffMarketPriceIndicator**

An indication that the price is off-market.

Type: **Boolean**

Used in messages: **TradeCaptureReport**

### **180.2.3563 OffsetInstruction**

Indicates the trade is a result of an offset or onset.

Type: **int**

Allowed values in OffsetInstructionCodeSet:

---

Code	Name	Description
0	Offset	Offset. A type of transaction where an executing firm gives up a trade as a result of an allocation. Or, in the case of a reversal of an allocation, the take-up (claiming) firm's transaction.

---

Code	Name	Description
1	Onset	Onset. A type of transaction where a take-up (claiming) firm takes up a trade as a result of an allocation. Or, in the case of a reversal of an allocation, the executing firm's transaction.

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#)

### 180.2.3564 OffshoreIndicator

Indicates the type of the currency rate being used. This is relevant for currencies that have offshore rate that different from onshore rate.

Type: [int](#)

Allowed values in OffshoreIndicatorCodeSet:

Code	Name	Description
0	Regular	Regular - Default if not specified. The notion of onshore and offshore rates does not apply.
1	Offshore	Offshore. Used to indicate that the rate specified is an offshore rate which differs from its onshore rate.
2	Onshore	Onshore. Used to indicate that the rate specified is an onshore rate which differs from its offshore rate.

Used in messages: [AllocationInstruction](#), [ExecutionReport](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.3565 OnBehalfOfCompID

Assigned value used to identify firm originating message if the message was delivered by a third party i.e. the third party firm identifier would be delivered in the SenderCompID field and the firm originating the message in this field.

Type: [String](#)

Used in components: [StandardHeader](#)

**180.2.3566 OnBehalfOfLocationID**

Assigned value used to identify specific message originator's location (i.e. geographic location and/or desk, trader) if the message was delivered by a third party

Type: **String**

Used in components: **StandardHeader**

**180.2.3567 OnBehalfOfSubID**

Assigned value used to identify specific message originator (i.e. trader) if the message was delivered by a third party

Type: **String**

Used in components: **StandardHeader**

**180.2.3568 OpenCloseSettlFlag**

Flag that identifies a market data entry. (Prior to FIX 4.3 this field was of type char)

Type: **MultipleCharValue**

Allowed values in OpenCloseSettlFlagCodeSet:

Code	Name	Description
0	DailyOpen	Daily Open / Close / Settlement entry
1	SessionOpen	Session Open / Close / Settlement entry
2	DeliverySettlementEntry	Delivery Settlement entry
3	ExpectedEntry	Expected entry
4	EntryFromPreviousBusinessDay	Entry from previous business day
5	TheoreticalPriceValue	Theoretical Price value

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **MarketDataRequest**

**180.2.3569 OpenInterest**

Open interest that was eligible for assignment.

Type: **Amt**

Used in messages: **AssignmentReport**

**180.2.3570 OptAttribute**

Provided to support versioning of option contracts as a result of corporate actions or events. Use of this field is defined by counterparty agreement or market conventions.

Type: **char**

Used in components: **Instrument**

**180.2.3571 OptionExerciseBusinessCenter**

The business center calendar used to adjust the option exercise dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **OptionExerciseBusinessCenterGrp**

**180.2.3572 OptionExerciseBusinessCenterGrp**

The OptionExerciseBusinessCenterGrp is a repeating subcomponent of the OptionExerciseDates component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
<b>NoOptionExerciseBusinessCenters</b>	[1..1]	NumInGroup	
<b>OptionExerciseBusinessCenter</b>	[0..1]	String	Required if NoOptionExerciseBusinessCenters(41116) > 0.

Used in components: **OptionExerciseDates**

**180.2.3573 OptionExerciseBusinessDayConvention**

The business day convention used to adjust the option exercise dates. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **OptionExerciseDates**

**180.2.3574 OptionExercise**

The OptionExercise component is a subcomponent of the Instrument component used to specify option exercise provisions. Its purpose is to identify the opportunities and conditions for exercise, e.g. the schedule of dates on which exercise is allowed. The embedded OptionExerciseExpiration component is used to terminate the opportunity for exercise.

Name	Mult.	Type	Description
<b>ExerciseDesc</b>	[0..1]	String	
<b>EncodedExerciseDescLen</b>	[0..1]	Length	Must be set if EncodedExerciseDesc(41108) field is specified and must immediately precede it.
<b>EncodedExerciseDesc</b>	[0..1]	data	Encoded (non-ASCII characters) representation of the ExerciseDesc(41106) field in the encoded format specified via the MessageEncoding(347) field.
<b>AutomaticExerciseIndicator</b>	[0..1]	Boolean	
<b>AutomaticExerciseThresholdRate</b>	[0..1]	float	

Name	Mult.	Type	Description
ExerciseConfirmationMethod	[0..1]	CodeSet	
ManualNoticeBusinessCenter	[0..1]	String	
FallbackExerciseIndicator	[0..1]	Boolean	
LimitedRightToConfirmIndicator	[0..1]	Boolean	
ExerciseSplitTicketIndicator	[0..1]	Boolean	
SettlMethodElectingPartySide	[0..1]	CodeSet	
SettlMethodElectionDate	[0..1]	Component	
OptionExerciseDates	[0..1]	Component	
OptionExerciseExpiration	[0..1]	Component	
OptionExerciseMakeWholeProvision	[0..1]	Component	

Used in components: **Instrument**

### 180.2.3575 OptionExerciseDate

The option exercise fixed date, unadjusted or adjusted depending on OptionExerciseDateType(41139).

Type: **LocalMktDate**

Used in groups: **OptionExerciseDateGrp**

### 180.2.3576 OptionExerciseDateGrp

The OptionExerciseDateGrp is a repeating subcomponent of the OptionExerciseDates component used to specify fixed dates for exercise.

Name	Mult.	Type	Description
NoOptionExerciseDates	[1..1]	NumInGroup	
OptionExerciseDate	[0..1]	LocalMktDate	Required if NoOptionExerciseDates(41137) > 0.
OptionExerciseDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: **OptionExerciseDates**

**180.2.3577 OptionExerciseDates**

The OptionExerciseDate component is a subcomponent of the OptionExercise component used to specify option exercise dates.

Name	Mult.	Type	Description
OptionExerciseBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of option exercise dates.
OptionExerciseBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of option exercise dates.
OptionExerciseDateGrp	[0..*]	Group	
OptionExerciseEarliestDateOffsetDay- Type	[0..1]	CodeSet	
OptionExerciseEarliestDateOffsetPe- riod	[0..1]	int	Conditionally required when OptionExerciseEarliestDateUnit(41121) is specified.
OptionExerciseEarliestDateOffsetUnit	[0..1]	CodeSet	Conditionally required when OptionExerciseEarliestDatePeriod(41120) is specified.
OptionExerciseFrequencyPeriod	[0..1]	int	Conditionally required when OptionExerciseFrequencyUnit(41123) is specified.
OptionExerciseFrequencyUnit	[0..1]	CodeSet	Conditionally required when OptionExerciseFrequencyPeriod(41122) is specified.
OptionExerciseStartDateUnadjusted	[0..1]	LocalMktDate	
OptionExerciseStartDateRelativeTo	[0..1]	int	
OptionExerciseStartDateOffsetPeriod	[0..1]	int	Conditionally required when OptionExerciseStartDateOffsetUnit(41127) is specified.
OptionExerciseStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when OptionExerciseStartDateOffsetPeriod(41126) is specified.
OptionExerciseStartDateOffsetDay- Type	[0..1]	CodeSet	
OptionExerciseStartDateAdjusted	[0..1]	LocalMktDate	
OptionExerciseSkip	[0..1]	int	

Name	Mult.	Type	Description
OptionExerciseNominationDeadline	[0..1]	LocalMktDate	
OptionExerciseFirstDateUnadjusted	[0..1]	LocalMktDate	
OptionExerciseLastDateUnadjusted	[0..1]	LocalMktDate	
OptionExerciseEarliestTime	[0..1]	LocalMktTime	
OptionExerciseLatestTime	[0..1]	LocalMktTime	
OptionExerciseTimeBusinessCenter	[0..1]	String	

Used in components: [OptionExercise](#)

### 180.2.3578 OptionExerciseDateType

Specifies the type of date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: [int](#)

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [OptionExerciseDateGrp](#)

### 180.2.3579 OptionExerciseEarliestDateOffsetDayType

Specifies the day type of the relative earliest option exercise date offset.

Type: [int](#)

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business



Code	Name	Description
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [OptionExerciseDates](#)

#### **180.2.3580 OptionExerciseEarliestDateOffsetPeriod**

Time unit multiplier for the relative earliest exercise date offset.

Type: [int](#)

Used in components: [OptionExerciseDates](#)

#### **180.2.3581 OptionExerciseEarliestDateOffsetUnit**

Time unit associated with the relative earliest exercise date offset.

Type: [String](#)

Allowed values in ProvisionOptionExerciseEarliestDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [OptionExerciseDates](#)

#### **180.2.3582 OptionExerciseEarliestTime**

The earliest time at which notice of exercise can be given by the buyer to the seller (or seller's agent) (i) on the expiration date, in the case of a European style option, (ii) on each Bermuda option exercise date and the expiration date, in the case of a Bermuda style option, (iii) the commencement date to, and including, the expiration date, in the case of an American option.

Type: **LocalMktTime**

Used in components: **OptionExerciseDates**

### 180.2.3583 OptionExerciseExpiration

The OptionExerciseExpiration component is a subcomponent of the OptionExercise component used to specify option exercise expiration dates and times. The purpose of OptionExercise is to identify the scheduled opportunities for exercise. OptionExerciseExpiration identifies the end of the schedule.

Name	Mult.	Type	Description
OptionExerciseExpirationDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of option exercise expiration dates.
OptionExerciseExpirationDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of option exercise expiration dates.
OptionExerciseExpirationDateGrp	[0..*]	Group	
OptionExerciseExpirationDateRelativeTo	[0..1]	int	
OptionExerciseExpirationDateOffsetPeriod	[0..1]	int	Conditionally required when OptionExerciseExpirationDateOffsetUnit(41145) is specified.
OptionExerciseExpirationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when OptionExerciseExpirationDateOffsetPeriod(41144) is specified.
OptionExerciseExpirationFrequencyPeriod	[0..1]	int	Conditionally required when OptionExerciseExpirationFrequencyUnit(41147) is specified.
OptionExerciseExpirationFrequencyUnit	[0..1]	CodeSet	Conditionally required when OptionExerciseExpirationFrequencyPeriod(41146) is specified.
OptionExerciseExpirationRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the option expiration dates and times.
OptionExerciseExpirationDateOffsetDayType	[0..1]	CodeSet	

Name	Mult.	Type	Description
OptionExerciseExpirationTime	[0..1]	LocalMktTime	
OptionExerciseExpirationTimeBusinessCenter	[0..1]	String	

Used in components: [OptionExercise](#)

### 180.2.3584 OptionExerciseExpirationDate

An adjusted or unadjusted fixed option exercise expiration date.

Type: [LocalMktDate](#)

Used in groups: [OptionExerciseExpirationDateGrp](#)

### 180.2.3585 OptionExerciseExpirationDateBusinessCenter

The business center calendar used to adjust the option exercise expiration dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [OptionExerciseExpirationDateBusinessCenterGrp](#)

### 180.2.3586 OptionExerciseExpirationDateBusinessCenterGrp

The OptionExerciseExpirationDateBusinessCenterGrp is a repeating subcomponent of the OptionExerciseExpiration component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoOptionExerciseExpirationDateBusinessCenters	[1..1]	NumInGroup	
OptionExerciseExpirationDateBusinessCenter	[0..1]	String	Required if NoOptionExerciseExpirationDateBusinessCenters(41140) > 0.

Used in components: [OptionExerciseExpiration](#)

**180.2.3587 OptionExerciseExpirationDateBusinessDayConvention**

The business day convention used to adjust the option exercise expiration dates. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **OptionExerciseExpiration**

**180.2.3588 OptionExerciseExpirationDateGrp**

The OptionExerciseExpirationDateGrp is a repeating subcomponent of the OptionExerciseExpiration component used to specify fixed dates for expiration.

Name	Mult.	Type	Description
<b>NoOptionExerciseExpirationDates</b>	[1..1]	NumInGroup	
<b>OptionExerciseExpirationDate</b>	[0..1]	LocalMktDate	Required if NoOptionExpirationDates(41152) > 0.
<b>OptionExerciseExpirationDateType</b>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: **OptionExerciseExpiration**

**180.2.3589 OptionExerciseExpirationDateOffsetDayType**

Specifies the day type of the relative option exercise expiration date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **OptionExerciseExpiration**

**180.2.3590 OptionExerciseExpirationDateOffsetPeriod**

Time unit multiplier for the relative exercise expiration date offset.

Type: **int**

Used in components: **OptionExerciseExpiration**

**180.2.3591 OptionExerciseExpirationDateOffsetUnit**

Time unit associated with the relative exercise expiration date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **OptionExerciseExpiration**

**180.2.3592 OptionExerciseExpirationDateRelativeTo**

Specifies the anchor date when the option exercise expiration date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **OptionExerciseExpiration**

**180.2.3593 OptionExerciseExpirationDateType**

Specifies the type of option exercise expiration date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **OptionExerciseExpirationDateGrp**

**180.2.3594 OptionExerciseExpirationFrequencyPeriod**

Time unit multiplier for the frequency of exercise expiration dates.

Type: **int**

Used in components: **OptionExerciseExpiration**

**180.2.3595 OptionExerciseExpirationFrequencyUnit**

Time unit associated with the frequency of exercise expiration dates.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [OptionExerciseExpiration](#)

### 180.2.3596 OptionExerciseExpirationRollConvention

The convention for determining the sequence of exercise expiration dates. It is used in conjunction with a specified frequency. Used only to override the roll convention defined in the DateAdjustment component in Instrument.

Type: [String](#)

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month

Code	Name	Description
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighthDay	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday



Used in components: [OptionExerciseExpiration](#)

### **180.2.3597 OptionExerciseExpirationTime**

The option exercise expiration time.

Type: [LocalMktTime](#)

Used in components: [OptionExerciseExpiration](#)

### **180.2.3598 OptionExerciseExpirationTimeBusinessCenter**

The business center used to determine the locale for option exercise expiration time, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in components: [OptionExerciseExpiration](#)

### **180.2.3599 OptionExerciseFirstDateUnadjusted**

The unadjusted first exercise date.

Type: [LocalMktDate](#)

Used in components: [OptionExerciseDates](#)

### **180.2.3600 OptionExerciseFrequencyPeriod**

Time unit multiplier for the frequency of exercise dates.

Type: [int](#)

Used in components: [OptionExerciseDates](#)

### **180.2.3601 OptionExerciseFrequencyUnit**

Time unit associated with the frequency of exercise dates.

Type: [String](#)

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [OptionExerciseDates](#)

### 180.2.3602 OptionExerciseLastDateUnadjusted

The unadjusted last exercise date.

Type: [LocalMktDate](#)

Used in components: [OptionExerciseDates](#)

### 180.2.3603 OptionExerciseLatestTime

The latest exercise time. See also OptionExerciseEarliestTime(41134).

Type: [LocalMktTime](#)

Used in components: [OptionExerciseDates](#)

### 180.2.3604 OptionExerciseMakeWholeProvision

OptionExerciseMakeWholeProvision is a subcomponent of the OptionExercise component used to specify the set of rules of maintaining balance when an option is exercised.

Name	Mult.	Type	Description
<a href="#">MakeWholeDate</a>	[0..1]	LocalMktDate	
<a href="#">MakeWholeAmount</a>	[0..1]	Amt	
<a href="#">MakeWholeBenchmarkCurveName</a>	[0..1]	String	
<a href="#">MakeWholeBenchmarkCurvePoint</a>	[0..1]	String	
<a href="#">MakeWholeRecallSpread</a>	[0..1]	PriceOffset	
<a href="#">MakeWholeBenchmarkQuote</a>	[0..1]	CodeSet	
<a href="#">MakeWholeInterpolationMethod</a>	[0..1]	CodeSet	

Used in components: [OptionExercise](#)

#### **180.2.3605 OptionExerciseNominationDeadline**

Last date (adjusted) for establishing the option exercise terms.

Type: [LocalMktDate](#)

Used in components: [OptionExerciseDates](#)

#### **180.2.3606 OptionExerciseSkip**

The number of periods in the referenced date schedule that are between each date in the relative date schedule. Thus a skip of 2 would mean that dates are relative to every second date in the referenced schedule. If present this should have a value greater than 1.

Type: [int](#)

Used in components: [OptionExerciseDates](#)

#### **180.2.3607 OptionExerciseStartDateAdjusted**

The adjusted start date for calculating periodic exercise dates.

Type: [LocalMktDate](#)

Used in components: [OptionExerciseDates](#)

#### **180.2.3608 OptionExerciseStartDateOffsetDayType**

Specifies the day type of the relative option exercise start date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

---

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business

---

Code	Name	Description
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [OptionExerciseDates](#)

#### **180.2.3609 OptionExerciseStartDateOffsetPeriod**

Time unit multiplier for the relative exercise start date offset.

Type: [int](#)

Used in components: [OptionExerciseDates](#)

#### **180.2.3610 OptionExerciseStartDateOffsetUnit**

Time unit associated with the relative exercise start date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [OptionExerciseDates](#)

#### **180.2.3611 OptionExerciseStartDateRelativeTo**

Specifies the anchor date when the option exercise start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [OptionExerciseDates](#)

#### **180.2.3612 OptionExerciseStartDateUnadjusted**

The unadjusted start date for calculating periodic exercise dates.

Type: **LocalMktDate**

Used in components: **OptionExerciseDates**

#### **180.2.3613 OptionExerciseTimeBusinessCenter**

The business center used to determine the locale for option exercise time, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values

Type: **String**

Used in components: **OptionExerciseDates**

#### **180.2.3614 OptionExpirationDesc**

Description of the option expiration.

Type: **String**

Used in components: **Instrument**

#### **180.2.3615 OptionsExchangeDividendsIndicator**

Indicates whether option exchange dividends are applicable.

Type: **Boolean**

Used in components: **DividendConditions**

#### **180.2.3616 OptPayoutAmount**

Cash amount indicating the pay out associated with an option. For binary options this is a fixed amount.

Type: **Amt**

Used in components: **Instrument**

**180.2.3617 OptPayoutType**

Indicates the type of valuation method or payout trigger for an in-the-money option.

Type: **int**

Allowed values in OptPayoutTypeCodeSet:

Code	Name	Description
1	Vanilla	Vanilla
2	Capped	Capped
3	Binary	Digital (Binary)
4	Asian	Asian
5	Barrier	Barrier
6	DigitalBarrier	Digital Barrier
7	Lookback	Lookback
8	OtherPathDependent	Other path dependent
99	Other	Other

Used in components: **Instrument**

**180.2.3618 OrdAllocGrp**

Name	Mult.	Type	Description
<b>NoOrders</b>	[1..1]	NumInGroup	Indicates number of orders to be combined for allocation. If order(s) were manually delivered set to 1 (one).Required when AllocNoOrdersType = 1
<b>ClOrdID</b>	[0..1]	String	Order identifier assigned by client if order(s) were electronically delivered over FIX (or otherwise assigned a ClOrdID) and executed. If order(s) were manually delivered (or otherwise not delivered over FIX) this field should contain string "MANUAL". Note where an order has undergone one or more cancel/replaces, this should be the ClOrdID of the most recent version of the order. Required when NoOrders(73) > 0 and must be the first repeating field in the group.
<b>OrderID</b>	[0..1]	String	

Name	Mult.	Type	Description
SecondaryOrderID	[0..1]	String	Can be used to provide order id used by exchange or executing system.
SecondaryClOrdID	[0..1]	String	
ListID	[0..1]	String	Required for List Orders.
NestedParties2	[0..*]	Group	Insert here the set of "NestedParties2" fields defined in "Common Components of Application Messages". This is used to identify the executing broker for step in/give in trades
OrderQty	[0..1]	Qty	
OrderAvgPx	[0..1]	Price	Average price for this order. For FX, if specified, expressed in terms of Currency(15).
OrderBookingQty	[0..1]	Qty	Quantity of this order that is being booked out by this message (will be equal to or less than this order's OrderQty). Note that the sum of the OrderBookingQty values in this repeating group must equal the total quantity being allocated (in Quantity (53) field)
OrdType	[0..1]	CodeSet	

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#), [ConfirmationRequest](#)

### 180.2.3619 OrderAggregationGrp

Identifies the orders being aggregated together.

Name	Mult.	Type	Description
NoOrders	[1..1]	NumInGroup	
ClOrdID	[0..1]	String	Required if NoOrders(73) > 0.
OrderID	[0..1]	String	
OrderQty	[0..1]	Qty	Required if NoOrders(73) > 0.
OrderAvgPx	[0..1]	Price	

Used in messages: [TradeAggregationRequest](#)

**180.2.3620 OrderAttributeGrp**

The OrderAttributeGrp component provides additional attributes about the order. Attributes included in this component are primarily "indicators" that may be associated with regulatory requirements and are typically not part of normal trading activities.

Name	Mult.	Type	Description
NoOrderAttributes	[1..1]	NumInGroup	
OrderAttributeType	[0..1]	CodeSet	Required if NoOrderAttributes(2593) > 0.
OrderAttributeValue	[0..1]	String	Required if NoOrderAttributes(2593) > 0.

Used in components: [TradeReportOrderDetail](#)

Used in groups: [ListOrdGrp](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

**180.2.3621 OrderAttributeType**

The type of order attribute.

Type: [int](#)

Allowed values in OrderAttributeTypeCodeSet:

Code	Name	Description
0	AggregatedOrder	Aggregated order. In the context of ESMA RTS 24 Article 2(3), when OrderAttributeValue(2595)=Y, it signifies that the order consists of several orders aggregated together. This maps to ESMA RTS value "AGGR".
1	PendingAllocation	Order pending allocation. In the context of ESMA RTS 24 Article 2(2), when OrderAttributeValue(2595)=Y, it signifies that the order submitter "is authorized under the legislation of a Member State to allocate an order to its client following submission of the order to the trading venue and has not yet allocated the order to its client at the time of the submission of the order". This maps to ESMA RTS value "PNAL".



Code	Name	Description
2	LiquidityProvisionActivityOrder	Liquidity provision activity order. In the context of ESMA RTS 24 Article 3, when OrderAttributeValue(2595)=Y, it signifies that the order was submitted "as part of a market making strategy pursuant to Articles 17 and 18 of Directive 2014/65/EU, or is submitted as part of another activity in accordance with Article 3" (of RTS 24).
3	RiskReductionOrder	Risk reduction order. In the context of ESMA RTS 22 Article 4(2)(i), when OrderAttributeValue(2595)=Y, it signifies that the commodity derivative order is a transaction "to reduce risk in an objectively measurable way in accordance with Article 57 of Directive 2014/65/EU".
4	AlgorithmicOrder	Algorithmic order. When OrderAttributeValue(2595)=Y, it signifies the order submitted to the dealer/investment firm resulted from an algorithm.
5	SystematicInternaliserOrder	Authorised reporter order. When OrderAttributeValue(2595)=Y, it signifies the order is submitted by an authorised reporter who is responsible for reporting trades resulting from the order. This may be a systematic internaliser.
6	AllExecutionsSubmittedToAPA	All executions for the order are to be submitted to an APA. All executions from this order that may need to be trade reported by the order submitter under MiFID II rules will be submitted by the order receiver on the submitter's behalf to the Approved Publication Arrangement (APA) facility specified in OrderAttributeValue(2595). ESMA RTS 1.
7	OrderExecutionInstructedByClient	Order execution instructed by client. In the context of ESMA RTS 22, Annex I, Table 2, Field 59, when OrderAttributeValue(2595)=Y, it signifies that the execution (e.g. the details of the trade including the venue of execution) was instructed by a client or by another person from outside the Investment Firm but within the same group (Field 59 'CLIENT' in ESMA 2016-1452 Guidelines).
8	LargeInScale	Large in scale order. In the context of MiFIR Article 4(1)(c) and Article 9(1)(a), when OrderAttributeValue(2595)=Y, it signifies that the order size is large in scale compared to normal market size.
9	Hidden	Hidden order. In the context of MiFIR Article 4(1)(d) and Article 9(1)(a), when OrderAttributeValue(2595)=Y, it signifies that the order is held in an order management facility of the trading venue pending disclosure.

Code	Name	Description
10	SubjectToEUSTO	Subject to EU share trading obligation (STO). This attribute is mutually exclusive with OrderAttributeType(2594)=14 (Exempt from STO), but not mutually exclusive with OrderAttributeType(2594)=11 (Subject to UK STO). In the context of the trading obligation for shares (STO) under ESMA's Article 23 of MiFIR, it signifies that the order is subject to the rules defined by ESMA.
11	SubjectToUKSTO	Subject to UK share trading obligation (STO). This attribute is mutually exclusive with OrderAttributeType(2594)=14 (Exempt from STO), but not mutually exclusive with OrderAttributeType(2594)=10 (Subject to EU STO). In the context of the trading obligation for shares (STO) under ESMA's Article 23 of MiFIR, it signifies that the order is subject to UK rules defined by the FCA.
12	RepresentativeOrder	Representative order. Order was originated to represent an order received by the broker from a customer/client.
13	LinkageType	Linkage type. Order is subject to regulatory linkage requirements related to customer/client orders. Can be used for US CAT order and trade level linkages between customer/client orders and representative orders.
14	ExemptFromSTO	Exempt from share trading obligation (STO). This attribute is mutually exclusive with OrderAttributeType(2594)=10 = (Subject to EU STO) and OrderAttributeType(2594)=11 = (Subject to UK STO). It can be used to override standing instructions for a trading obligation for shares (STO). It overrides the standing instructions in their entirety. In the context of STO under ESMA's Article 23 of MiFIR, it signifies that the order is exempt from any share trading obligation.

Used in groups: **OrderAttributeGrp**

### **180.2.3622 OrderAttributeValue**

The value associated with the order attribute type specified in OrderAttributeType(2594).

Type: **String**

Used in groups: **OrderAttributeGrp**

**180.2.3623 OrderAvgPx**

Average price for a specific order

Type: Price

Used in groups: OrdAllocGrp, OrderAggregationGrp

**180.2.3624 OrderBookingQty**

Quantity of the order that is being booked out as part of an Allocation Instruction or Allocation Report message

Type: Qty

Used in groups: OrdAllocGrp

**180.2.3625 OrderCapacity**

Designates the capacity of the firm placing the order.

(as of FIX 4.3, this field replaced Rule80A (tag 47) –used in conjunction with OrderRestrictions (529) field)

(see Volume : "Glossary" for value definitions)

Type: char

Allowed values in OrderCapacityCodeSet:

Code	Name	Description
A	Agency	Agency
G	Proprietary	Proprietary
I	Individual	Individual
P	Principal	Principal. For some markets Principal may include Proprietary.
R	RisklessPrincipal	Riskless Principal
W	AgentForOtherMember	Agent for Other Member
M	MixedCapacity	Mixed capacity

Used in components: TradeReportOrderDetail

Used in groups: CpctyConfGrp, ListOrdGrp, MDFullGrp, MDIncGrp, QuotEntryAckGrp, QuotEntryGrp, SideCrossOrdModGrp

Used in messages: [ExecutionReport](#), [MassOrder](#), [MassOrderAck](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [Quote](#), [QuoteRequest](#), [QuoteResponse](#), [QuoteStatusReport](#)

### **180.2.3626 OrderCapacityQty**

Quantity executed under a specific OrderCapacity (e.g. quantity executed as agent, quantity executed as principal)

Type: [Qty](#)

Used in groups: [CpctyConfGrp](#)

### **180.2.3627 OrderCategory**

Defines the type of interest behind a trade (fill or partial fill).

Type: [char](#)

Allowed values in OrderCategoryCodeSet:

Code	Name	Description
1	Order	Order
2	Quote	Quote
3	PrivatelyNegotiatedTrade	Privately Negotiated Trade
4	MultilegOrder	Multileg order
5	LinkedOrder	Linked order
6	QuoteRequest	Quote Request
7	ImpliedOrder	Implied Order
8	CrossOrder	Cross Order
9	StreamingPrice	Streaming price (quote)
A	InternalCrossOrder	Internal Cross Order

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [ExecutionReport](#)

**180.2.3628 OrderDelay**

Time lapsed from order entry until match, based on the unit of time specified in OrderDelayUnit. Default is seconds if OrderDelayUnit is not specified. Value = 0, indicates the aggressor (the initiating side of the trade).

Type: **int**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.3629 OrderDelayUnit**

Time unit in which the OrderDelay(1428) is expressed

Type: **int**

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.3630 OrderEntryAckGrp**

Acknowledgment for a group of order transactions across one or more instruments.

Name	Mult.	Type	Description
NoOrderEntries	[1..1]	NumInGroup	
OrdStatus	[0..1]	CodeSet	Required if NoOrderEntries(2428) > 0.
ExecType	[0..1]	CodeSet	Required if NoOrderEntries(2428) > 0.
ExecTypeReason	[0..1]	CodeSet	
OrderEntryAction	[0..1]	CodeSet	
OrderEntryID	[0..1]	int	Conditionally required when neither ClOrdID(11) nor OrderID(37) is provided.
ClOrdID	[0..1]	String	Conditionally required when neither OrderEntryID(2430) nor OrderID(37) is provided.
OrigClOrdID	[0..1]	String	ClOrdID(11) of the previous non rejected order (NOT the initial order of the day) when canceling or replacing an order. Conditionally required when ClOrdID(11) is provided and message-chaining model is used.
OrderID	[0..1]	String	Conditionally required when neither OrderEntryID(2430) nor ClOrdID(11) is provided.
OrdRejReason	[0..1]	CodeSet	
CumQty	[0..1]	Qty	Use to explicitly provide executed quantity.
LeavesQty	[0..1]	Qty	Use to explicitly provide remaining quantity.
CxlQty	[0..1]	Qty	Use to explicitly provide cancelled quantity.
OrdType	[0..1]	CodeSet	
Price	[0..1]	Price	
Side	[0..1]	CodeSet	
TimeInForce	[0..1]	CodeSet	
OrderQtyData	[0..1]	Component	
Instrument	[0..1]	Component	

Used in messages: **MassOrderAck**

### 180.2.3631 OrderEntryAction

Specifies the action to be taken for the given order.

Type: **char**

Allowed values in OrderEntryActionCodeSet:

Code	Name	Description
1	Add	Add
2	Modify	Modify
3	Delete	Delete / Cancel
4	Suspend	Suspend
5	Release	Release

Used in groups: [OrderEntryAckGrp](#), [OrderEntryGrp](#)

### 180.2.3632 OrderEntryGrp

Group of order transactions across one or more instruments.

Name	Mult.	Type	Description
<a href="#">NoOrderEntries</a>	[1..1]	NumInGroup	
<a href="#">OrderEntryAction</a>	[0..1]	CodeSet	Required if <a href="#">NoOrderEntries</a> (2428) > 0.
<a href="#">OrderEntryID</a>	[0..1]	int	Unique order entry identification across all entries of a single message. Conditionally required when neither <a href="#">ClOrdID</a> (11) nor <a href="#">OrderID</a> (37) is provided.
<a href="#">ClOrdID</a>	[0..1]	String	Conditionally required when neither <a href="#">OrderEntryID</a> (2430) nor <a href="#">OrderID</a> (37) is provided.
<a href="#">OrigClOrdID</a>	[0..1]	String	Conditionally required when <a href="#">OrderEntryAction</a> (2429) is not "1" (Add), <a href="#">ClOrdID</a> (11) was provided in original order, and message-chaining model is used.
<a href="#">OrderID</a>	[0..1]	String	Conditionally required when <a href="#">OrderEntryAction</a> (2429) is not "1" (Add) and neither <a href="#">OrderEntryID</a> (2430) nor <a href="#">ClOrdID</a> (11) is provided.
<a href="#">OrdType</a>	[0..1]	CodeSet	Conditionally required when <a href="#">OrderEntryAction</a> (2429) = 1 (Add) or 2 (Modify). Only a subset of <a href="#">OrdType</a> (40) values permitted that do not require additional pricing fields other than <a href="#">Price</a> (44) field.
<a href="#">Price</a>	[0..1]	Price	Conditionally required when <a href="#">OrdType</a> (40) = 2 (Limit)
<a href="#">Side</a>	[0..1]	CodeSet	Conditionally required when <a href="#">OrderEntryAction</a> (2429) = 1 (Add) or 2 (Modify)

Name	Mult.	Type	Description
TimeInForce	[0..1]	CodeSet	Only subset of values permitted that do not require additional fields
OrderQtyData	[0..1]	Component	Conditionally required when OrderEntryAction(2429) = 1 (Add) or 2 (Modify)
Instrument	[0..1]	Component	Required if NoOrderEntries(2432) > 0.

Used in messages: **MassOrder**

### 180.2.3633 OrderEntryID

Unique identifier for an order within a single MassOrder(35=DJ) message that can be used as a reference in the MassOrderAck(35=DK) message.

Type: **int**

Used in groups: **OrderEntryAckGrp**, **OrderEntryGrp**

### 180.2.3634 OrderEventExecID

Refer to ExecID(17). Used when multiple different events are reported in single Execution Report. ExecID(17) and OrderEventExecID(1797) values should not overlap.

Type: **String**

Used in groups: **OrderEventGrp**

### 180.2.3635 OrderEventGrp

List the different types of events affecting orders. These can include entry, modification and deletion of orders as well as executions (fills). Modifications can be solicited or unsolicited, e.g. triggering of stop orders, replenishment of reserve orders, orders being suspended (locked) or released from suspension.

Name	Mult.	Type	Description
NoOrderEvents	[1..1]	NumInGroup	
OrderEventType	[0..1]	CodeSet	Required when NoOrderEvents(1795) > 0.
OrderEventExecID	[0..1]	String	



Name	Mult.	Type	Description
OrderEventReason	[0..1]	CodeSet	
OrderEventPx	[0..1]	Price	
OrderEventQty	[0..1]	Qty	
OrderEventLiquidityIndicator	[0..1]	CodeSet	
OrderEventText	[0..1]	String	

Used in messages: **ExecutionReport**

### 180.2.3636 OrderEventLiquidityIndicator

Indicator to identify whether this fill was a result of a liquidity provider providing or liquidity taker taking the liquidity. Applicable only for OrderEventType(1796) values of 4(Partially Filled) or 5(Filled).

Type: **int**

Allowed values in LastLiquidityIndCodeSet:

Code	Name	Description
0	NeitherAddedNorRemovedLiquidity	Neither added nor removed liquidity. May be used by venues where market rules do not define "add" or "remove" liquidity. In the context of the SEC amendment of Regulation NMS Rule 606(b), may be used to identify executions that are only reported as part of total shares executed and not as part of shares providing or removing liquidity (see <a href="https://www.sec.gov/rules/final/2018/34-84528.pdf">https://www.sec.gov/rules/final/2018/34-84528.pdf</a> for details).
1	AddedLiquidity	Added Liquidity
2	RemovedLiquidity	Removed Liquidity
3	LiquidityRoutedOut	Liquidity Routed Out
4	Auction	Auction execution
5	TriggeredStopOrder	Triggered stop order. Fill was the result of a stop order being triggered and immediately executed.
6	TriggeredContingencyOrder	Triggered contingency order. Fill was the result of a contingency order (OCO, OTO, OUO) becoming active (after cancelling or updating another order) and being immediately executed.
7	TriggeredMarketOrder	Triggered market order. Fill was the result of a market order being triggered due to an executable orderbook situation.

Code	Name	Description
8	RemovedLiquidityAfterFirmOrder-Commitment	Removed liquidity after firm order commitment. An order that was submitted for continuous trading that required a firm order commit prior to execution. "Conditional order" is an alternate term used for such orders.
9	AuctionExecutionAfterFirmOrder-Commitment	Auction execution after firm order commitment. An order that was submitted for auction trading that required a firm order commit prior to execution. "Conditional order" is an alternate term used for such orders.
10	Unknown	Unknown. The liquidity indicator of the execution cannot be determined or was not provided upon execution.
11	Other	Other. None of the existing liquidity indicators are applicable for the execution (e.g. due to a venue's new order type that does not fit existing values).

Used in groups: **OrderEventGrp**

#### **180.2.3637 OrderEventPx**

Price associated with the event.

Type: **Price**

Used in groups: **OrderEventGrp**

#### **180.2.3638 OrderEventQty**

Quantity associated with the event.

Type: **Qty**

Used in groups: **OrderEventGrp**

#### **180.2.3639 OrderEventReason**

Action that caused the event to occur.

Type: **int**

Allowed values in OrderEventReasonCodeSet:

Code	Name	Description
1	AddOrderRequest	Add order request
2	ModifyOrderRequest	Modify order request
3	DeleteOrderRequest	Delete order request
4	OrderEnteredOOB	Order entered out-of-band
5	OrderModifiedOOB	Order modified out-of-band
6	OrderDeletedOOB	Order deleted out-of-band
7	OrderActivatedOrTriggered	Order activated or triggered
8	OrderExpired	Order expired
9	ReserveOrderRefreshed	Reserve order refreshed
10	AwayMarketBetter	Away market better
11	CorporateAction	Corporate action
12	StartOfDay	Start of day
13	EndOfDay	End of day

Used in groups: **OrderEventGrp**

#### **180.2.3640 OrderEventText**

Additional information about the event.

Type: **String**

Used in groups: **OrderEventGrp**

#### **180.2.3641 OrderEventType**

The type of event affecting an order. The last event type within the OrderEventGrp component indicates the ExecType(150) value resulting from the series of events (ExecType(150) values are shown in brackets).

Type: **int**

Allowed values in OrderEventTypeCodeSet:

Code	Name	Description
1	Added	Added (0=New)

Code	Name	Description
2	Modified	Modified (5=Replaced)
3	Deleted	Deleted (4=Canceled)
4	PartiallyFilled	Partially Filled (F=Trade)
5	Filled	Filled (F=Trade)
6	Suspended	Suspended (9=Suspended)
7	Released	Released (N=Released)
8	Restated	Restated (D=Restated)
9	Locked	Locked (M=Locked)
10	Triggered	Triggered (L=Triggered or Activated by System)
11	Activated	Activated (L=Triggered or Activated by System)

Used in groups: [OrderEventGrp](#)

#### **180.2.3642 OrderHandlingInstSource**

Identifies the class or source of the order handling instruction values. Scope of this will apply to both [CustOrderHandlingInst\(1031\)](#) and [DeskOrderHandlingInst\(1035\)](#).

Conditionally required when [CustOrderHandlingInst\(1031\)](#) or [DeskOrderHandlingInst\(1035\)](#) is specified.

Type: [int](#)

Allowed values in [OrderHandlingInstSourceCodeSet](#):

Code	Name	Description
1	FINRAOATS	FINRA OATS
2	FIAExecutionSourceCode	FIA Execution Source Code

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#), [ExecutionReport](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

**180.2.3643 OrderID**

Unique identifier for Order as assigned by sell-side (broker, exchange, ECN). Uniqueness must be guaranteed within a single trading day. Firms which accept multi-day orders should consider embedding a date within the OrderID field to assure uniqueness across days.

Type: **String**

Used in components: **TradeReportOrderDetail**

Used in groups: **MDFullGrp, MDIncGrp, OrdAllocGrp, OrdListStatGrp, OrderAggregationGrp, OrderEntryAckGrp, OrderEntryGrp**

Used in messages: **CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralRequest, CollateralResponse, CrossOrderCancelReplaceRequest, CrossOrderCancelRequest, DontKnowTrade, Email, ExecutionAck, ExecutionReport, MultilegOrderCancelReplace, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassCancelReport, OrderStatusRequest, TradeCaptureReportRequest**

**180.2.3644 OrderInputDevice**

Specific device number, terminal number or station where order was entered

Type: **String**

Used in components: **TradeReportOrderDetail**

**180.2.3645 OrderOrigination**

Identifies the origin of the order.

Type: **int**

Allowed values in OrderOriginationCodeSet:

Code	Name	Description
1	OrderReceivedFromCustomer	Order received from a customer
2	OrderReceivedFromWithinFirm	Order received from within the firm
3	OrderReceivedFromAnotherBrokerDealer	Order received from another broker-dealer
4	OrderReceivedFromCustomerOrWithFirm	Order received from a customer or originated from within the firm

Code	Name	Description
5	OrderReceivedFromDirectAccessCustomer	Order received from a direct access or sponsored access customer
6	OrderReceivedFromForeignDealerEquivalent	Order received from a foreign dealer equivalent. A foreign dealer equivalent is a person in the business of trading securities in a foreign jurisdiction in a manner analogous to an investment dealer and that is subject to the regulatory jurisdiction of a signatory to the International Organization of Securities Commissions' (IOSCO) Multilateral Memorandum of Understanding in that foreign jurisdiction.
7	OrderReceivedFromExecutionOnly-Service	Order received from an execution-only service. The acceptance and execution of orders from customers for trades that the broker-dealer has not recommended and for which the broker-dealer takes no responsibility as to the appropriateness or suitability of orders accepted or account positions held.

Used in components: [TradeReportOrderDetail](#)

Used in groups: [SideCrossOrdModGrp](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### **180.2.3646 OrderOriginationFirmID**

Identifier for the original owner of an order as part of the RelatedOrderGrp component. Use the Parties component with PartyRole(452) = 13 (Order Origination Firm) to identify the original owner of an individual order.

Type: [String](#)

Used in groups: [RelatedOrderGrp](#)

### **180.2.3647 OrderOwnershipIndicator**

Change of ownership of an order to a specific party.

Type: [int](#)

Allowed values in OrderOwnershipIndicatorCodeSet:

Code	Name	Description
0	NoChange	No change of ownership (default)
1	ExecutingPartyChange	Change of ownership to executing party. Executing party can be given either implicitly via session attributes or explicitly via Parties component. The party taking over ownership must also be the one submitting the request.
2	EnteringPartyChange	Change of ownership to entering party. Entering party can be given either implicitly via session attributes or explicitly via Parties component. The party taking over ownership must also be the one submitting the request.
3	SpecifiedPartyChange	Change of ownership to specified party. Ownership is transferred by a third party from/to the parties specified via Parties component together with PartyRoleQualifier(2376) = Current(18) and New(19).

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [OrderCancelReplaceRequest](#)

#### **180.2.3648 OrderPercent**

For CIV specifies the approximate order quantity desired. For a CIV Sale it specifies percentage of investor's total holding to be sold. For a CIV switch/exchange it specifies percentage of investor's cash realised from sales to be re-invested. The executing broker, intermediary or fund manager is responsible for converting and calculating OrderQty (38) in shares/units for subsequent messages.

Type: [Percentage](#)

Used in components: [OrderQtyData](#)

#### **180.2.3649 OrderPercentOfTotalVolume**

For Percent-of-volume (POV) average pricing this is the target percentage this order quantity represents of the total trading volume of an instrument during the specified time period. This provides the data needed to ensure that the average price is fair based on the total sum of grouped POV trades.

Type: [Percentage](#)

Used in components: [TradeReportOrderDetail](#)

**180.2.3650 OrderQty**

Quantity ordered. This represents the number of shares for equities or par, face or nominal value for FI instruments.

(Prior to FIX 4.2 this field was of type int)

Type: Qty

Used in components: OrderQtyData

Used in groups: OrdAllocGrp, OrderAggregationGrp

Used in messages: CrossRequest, CrossRequestAck

**180.2.3651 OrderQty2**

OrderQty (38) of the future part of a F/X swap order.

Type: Qty

Used in groups: ListOrdGrp, QuotEntryAckGrp, QuotEntryGrp, QuotReqGrp, QuotReqRjctGrp

Used in messages: ExecutionReport, NewOrderSingle, OrderCancelReplaceRequest, Quote, QuoteResponse, QuoteStatusReport

**180.2.3652 OrderQtyData**

The OrderQtyData component block contains the fields commonly used for indicating the amount or quantity of an order. Note that when this component block is marked as "required" in a message either one of these three fields must be used to identify the amount: OrderQty, CashOrderQty or OrderPercent (in the case of CIV).

---

Name	Mult.	Type	Description
OrderQty	[0..1]	Qty	One of CashOrderQty, OrderQty, or (for CIV only) OrderPercent is required. Note that unless otherwise specified, only one of CashOrderQty, OrderQty, or OrderPercent should be specified.

---



Name	Mult.	Type	Description
CashOrderQty	[0..1]	Qty	One of CashOrderQty, OrderQty, or (for CIV only) OrderPercent is required. Note that unless otherwise specified, only one of CashOrderQty, OrderQty, or OrderPercent should be specified. Specifies the approximate "monetary quantity" for the order. Broker is responsible for converting and calculating OrderQty in tradeable units (e.g. shares) for subsequent messages.
OrderPercent	[0..1]	Percentage	For CIV - Optional. One of CashOrderQty, OrderQty or (for CIV only) OrderPercent is required. Note that unless otherwise specified, only one of CashOrderQty, OrderQty, or OrderPercent should be specified.
RoundingDirection	[0..1]	CodeSet	For CIV - Optional
RoundingModulus	[0..1]	float	For CIV - Optional

Used in components: [TradeReportOrderDetail](#)

Used in groups: [ListOrdGrp](#), [OrderEntryAckGrp](#), [OrderEntryGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [SideCrossOrdCxlGrp](#), [SideCrossOrdModGrp](#)

Used in messages: [DontKnowTrade](#), [ExecutionAck](#), [ExecutionReport](#), [IOI](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

### 180.2.3653 OrderRelationship

Describes the type of relationship between the order identified by RelatedOrderID(2887) and the order outside of the RelatedOrderGrp component.

Type: [int](#)

Allowed values in OrderRelationshipCodeSet:

Code	Name	Description
0	NotSpecified	Not specified
1	OrderAggregation	Order aggregation. Order has been subject to a bundling of multiple orders to a single new order identified outside of the component.

Code	Name	Description
2	OrderSplit	Order split. Order has been created as a child order of the order identified outside of the component.

Used in groups: [RelatedOrderGrp](#)

#### **180.2.3654 OrderRequestID**

Unique message identifier for an order request as assigned by the submitter of the request.

Type: [int](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [CrossOrderCancelRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReject](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [SecurityDefinition](#)

#### **180.2.3655 OrderResponseLevel**

The level of response requested from receiver of mass order messages. A default value should be bilaterally agreed.

Type: [int](#)

Allowed values in OrderResponseLevelCodeSet:

Code	Name	Description
0	NoAck	No acknowledgement. Responses are provided through one or more ExecutionReport(35=8) messages.
1	MinimumAck	Minimum acknowledgement. The minimum is any information to explain why the requested transaction was refused or led to additional events, e.g. immediate execution of an order that was entered or modified.
2	AckEach	Acknowledge each order. The number of entries in the response is identical to the number of entries in the request.
3	SummaryAck	Summary acknowledgement. Responses are provided through a single MassOrderAck(35=DK) without entries and one or more ExecutionReport(35=8) messages.

Used in messages: [MassOrder](#), [MassOrderAck](#)

**180.2.3656 OrderRestrictions**

Restrictions associated with an order. If more than one restriction is applicable to an order, this field can contain multiple instructions separated by space.

Type: **MultipleCharValue**

Allowed values in OrderRestrictionsCodeSet:

Code	Name	Description
1	ProgramTrade	Program Trade
2	IndexArbitrage	Index Arbitrage
3	NonIndexArbitrage	Non-Index Arbitrage
4	CompetingMarketMaker	Competing Market Maker
5	ActingAsMarketMakerOrSpecialistIn-Security	Acting as Market Maker or Specialist in the security
6	ActingAsMarketMakerOrSpecialistIn-Underlying	Acting as Market Maker or Specialist in the underlying security of a derivative security
7	ForeignEntity	Foreign Entity (of foreign government or regulatory jurisdiction)
8	ExternalMarketParticipant	External Market Participant
9	ExternalInterConnectedMarketLinkage	External Inter-connected Market Linkage
A	RisklessArbitrage	Riskless Arbitrage
B	IssuerHolding	Issuer Holding
C	IssuePriceStabilization	Issue Price Stabilization
D	NonAlgorithmic	Non-algorithmic
E	Algorithmic	Algorithmic
F	Cross	Cross
G	InsiderAccount	Insider Account
H	SignificantShareholder	Significant Shareholder
I	NormalCourseIssuerBid	Normal Course Issuer Bid (NCIB)

Used in components: **TradeReportOrderDetail**

Used in groups: **CpctyConfGrp, ListOrdGrp, QuotEntryAckGrp, QuotEntryGrp, SideCrossOrdModGrp**

Used in messages: **ExecutionReport, MassOrder, MassOrderAck, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, Quote, QuoteRequest, QuoteResponse, QuoteStatusReport**

**180.2.3657 OrdListStatGrp**

Name	Mult.	Type	Description
NoOrders	[1..1]	NumInGroup	Number of orders statused in this message, i.e. number of repeating groups to follow.
ClOrdID	[0..1]	String	Required when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID.
OrderID	[0..1]	String	
SecondaryClOrdID	[0..1]	String	
CumQty	[1..1]	Qty	
OrdStatus	[1..1]	CodeSet	
WorkingIndicator	[0..1]	CodeSet	For optional use with OrdStatus = 0 (New)
LeavesQty	[1..1]	Qty	Quantity open for further execution. LeavesQty = OrderQty - CumQty.
CxlQty	[1..1]	Qty	
AvgPx	[1..1]	Price	
OrdRejReason	[0..1]	CodeSet	Used if the order is rejected
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: [ListStatus](#)

**180.2.3658 OrdRejReason**

Code to identify reason for order rejection. Note: Values 3, 4, and 5 will be used when rejecting an order due to pre-allocation information errors.

Type: [int](#)

Allowed values in OrdRejReasonCodeSet:

Code	Name	Description
0	BrokerCredit	Broker / Exchange option
1	UnknownSymbol	Unknown symbol. In the context of IA FX Reject codes, Trade Request Rejection Category F, order rejected due to the product not being supported, e.g. by the specific venue, tenor restrictions on the market participant(s) involved.
2	ExchangeClosed	Exchange closed
3	OrderExceedsLimit	Order exceeds limit
4	TooLateToEnter	Too late to enter
5	UnknownOrder	Unknown order
6	DuplicateOrder	Duplicate Order (e.g. dupe ClOrdID)
7	DuplicateOfAVerballyCommunicatedOrder	Duplicate of a verbally communicated order
8	StaleOrder	Stale order
9	TradeAlongRequired	Trade along required
10	InvalidInvestorID	Invalid Investor ID
11	UnsupportedOrderCharacteristic	Unsupported order characteristic
12	SurveillanceOption	Surveillance option
13	IncorrectQuantity	Incorrect quantity
14	IncorrectAllocatedQuantity	Incorrect allocated quantity
15	UnknownAccount	Unknown account(s). In the context of IA FX Reject codes, Trade Request Rejection Category D, order rejected due to static data when the account/fund is not setup or unknown.
16	PriceExceedsCurrentPriceBand	Price exceeds current price band
18	InvalidPriceIncrement	Invalid price increment
19	ReferencePriceNotAvailable	Reference price not available
20	NotionalValueExceedsThreshold	Notional value exceeds threshold
21	AlgorithmRiskThresholdBreached	Algorithm risk threshold breached. A sell-side broker algorithm has detected that a risk limit has been breached which requires further communication with the client. Used in conjunction with Text(58) to convey the details of the specific event.
22	ShortSellNotPermitted	Short sell not permitted
23	ShortSellSecurityPreBorrowRestriction	Short sell rejected due to security pre-borrow restriction
24	ShortSellAccountPreBorrowRestriction	Short sell rejected due to account pre-borrow restriction

Code	Name	Description
25	InsufficientCreditLimit	Insufficient credit limit. In the context of IA FX Reject codes, Trade Request Rejection Category C, order rejected due to credit limit exceeded or not in place.
26	ExceededClipSizeLimit	Exceeded clip size limit
27	ExceededMaxNotionalOrderAmt	Exceeded maximum notional order amount
28	ExceededDV01PV01Limit	Exceeded DV01/PV01 limit
29	ExceededCS01Limit	Exceeded CS01 limit
30	LastLook	Last look. In the context of IA FX Reject codes, Trade Request Rejection Category A-1, order rejected due to a "last look".
31	LastLookLatency	Last look latency. In the context of IA FX Reject codes, Trade Request Rejection Category A-2, order rejected due to "last look latency", therefore price or liquidity is unavailable.
32	UnavailablePriceLiquidity	Unavailable price or liquidity. In the context of IA FX Reject codes, Trade Request Rejection Category B, the order was not subjected to last look but rejected due to pricing or liquidity being no longer available for execution.
33	InvalidMissingEntitlements	Invalid or missing entitlements. In the context of IA FX Reject codes, Trade Request Rejection Category D, order rejected due to static/reference data error where counterparty is not permitted or entitled.
99	Other	Other. In the context of IA FX Reject codes, Trade Request Rejection Category E, order rejected due to other exceptions. Further detail may be provided in RejectText(1328) or Text(58), with preference for RejectText(1328) if field is present in the message.

Used in groups: **OrdListStatGrp**, **OrderEntryAckGrp**

Used in messages: **ExecutionReport**

### 180.2.3659 OrdStatus

Identifies current status of order. \*\*\* SOME VALUES HAVE BEEN REPLACED - See "Replaced Features and Supported Approach" \*\*\* (see Volume : "Glossary" for value definitions)

Type: **char**

Allowed values in OrdStatusCodeSet:

Code	Name	Description
0	New	New
1	PartiallyFilled	Partially filled
2	Filled	Filled
3	DoneForDay	Done for day
4	Canceled	Canceled
5	Replaced	Replaced (No longer used)
6	PendingCancel	Pending Cancel (i.e. result of Order Cancel Request)
7	Stopped	Stopped
8	Rejected	Rejected
9	Suspended	Suspended
A	PendingNew	Pending New
B	Calculated	Calculated
C	Expired	Expired
D	AcceptedForBidding	Accepted for Bidding
E	PendingReplace	Pending Replace (i.e. result of Order Cancel/Replace Request)

Used in components: [TradeReportOrderDetail](#)

Used in groups: [OrdListStatGrp](#), [OrderEntryAckGrp](#)

Used in messages: [ExecutionReport](#), [OrderCancelReject](#)

### **180.2.3660 OrdStatusReqID**

Can be used to uniquely identify a specific Order Status Request message.

Type: [String](#)

Used in messages: [ExecutionReport](#), [OrderStatusRequest](#)

### **180.2.3661 OrdType**

Order type. \*\*\* SOME VALUES ARE NO LONGER USED - See "Deprecated (Phased-out) Features and Supported Approach" \*\*\* (see Volume : "Glossary" for value definitions)

Type: [char](#)

Allowed values in OrdTypeCodeSet:

Code	Name	Description
1	Market	Market
2	Limit	Limit
3	Stop	Stop/Stop Loss. A stop order that is triggered as a result of a trade in the market at which point the stopped order becomes a market order.
4	StopLimit	Stop Limit. A stop limit order that is triggered as a result of a trade in the market at which point the stopped order becomes a limit order.
5	MarketOnClose	Market On Close (No longer used)
6	WithOrWithout	With Or Without
7	LimitOrBetter	Limit Or Better
8	LimitWithOrWithout	Limit With Or Without
9	OnBasis	On Basis
A	OnClose	On Close (No longer used)
B	LimitOnClose	Limit On Close (No longer used)
C	ForexMarket	Forex Market (No longer used)
D	PreviouslyQuoted	Previously Quoted
E	PreviouslyIndicated	Previously Indicated
F	ForexLimit	Forex Limit (No longer used)
G	ForexSwap	Forex Swap
H	ForexPreviouslyQuoted	Forex Previously Quoted (No longer used)
I	Funari	Funari (Limit day order with unexecuted portion handles as Market On Close. E.g. Japan)
J	MarketIfTouched	Market If Touched (MIT)
K	MarketWithLeftOverAsLimit	Market With Left Over as Limit (market order with unexecuted quantity becoming limit order at last price)
L	PreviousFundValuationPoint	Previous Fund Valuation Point (Historic pricing; for CIV)
M	NextFundValuationPoint	Next Fund Valuation Point (Forward pricing; for CIV)
P	Pegged	Pegged
Q	CounterOrderSelection	Counter-order selection
R	StopOnBidOrOffer	Stop on Bid or Offer. A stop order that is triggered by a bid or offer price movement (quote) at which point the stopped order becomes a market order, also known as "stop on quote" in some markets (e.g. US markets). In the US equities market it is common to trigger a stop off the National Best Bid or Offer (NBBO).



Code	Name	Description
S	StopLimitOnBidOrOffer	Stop Limit on Bid or Offer. A stop order that is triggered by a bid or offer price movement (quote) at which point the stopped order becomes a limit order, also known as "stop limit on quote" in some markets (e.g. US markets). In the US equities market it is common to trigger a stop off the National Best Bid or Offer (NBBO).

Used in components: [MDStatisticParameters](#), [TradeReportOrderDetail](#)

Used in groups: [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#), [OrdAllocGrp](#), [OrdTypeRules](#), [OrderEntryAckGrp](#), [OrderEntryGrp](#), [QuotEntryAckGrp](#), [QuotEntryGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

### 180.2.3662 OrdTypeRules

Name	Mult.	Type	Description
<a href="#">NoOrdTypeRules</a>	[1..1]	NumInGroup	Number of order types
<a href="#">OrdType</a>	[0..1]	CodeSet	Indicates order types that are valid for the specified market segment.

Used in components: [TradingSessionRules](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

### 180.2.3663 OrigClOrdID

ClOrdID (11) of the previous order (NOT the initial order of the day) as assigned by the institution, used to identify the previous order in cancel and cancel/replace requests.

Type: [String](#)

Used in groups: [OrderEntryAckGrp](#), [OrderEntryGrp](#), [SideCrossOrdCxlGrp](#), [SideCrossOrdModGrp](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [OrderCancelReject](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#)

**180.2.3664 OrigCrossID**

CrossID of the previous cross order (NOT the initial cross order of the day) as assigned by the institution, used to identify the previous cross order in Cross Cancel and Cross Cancel/Replace Requests.

Type: **String**

Used in messages: **CrossOrderCancelReplaceRequest**, **CrossOrderCancelRequest**, **ExecutionReport**

**180.2.3665 OrigCustOrderCapacity**

The customer capacity for this trade at the time of the order/execution.

Primarily used by futures exchanges to indicate the CTICode (customer type indicator) as required by the US CFTC (Commodity Futures Trading Commission).

Type: **int**

Allowed values in OrigCustOrderCapacityCodeSet:

Code	Name	Description
1	MemberTradingForTheirOwnAccount	Member trading for their own account
2	ClearingFirmTradingForItsProprietaryAccount	Clearing Firm trading for its proprietary account
3	MemberTradingForAnotherMember	Member trading for another member
4	AllOther	All other

Used in components: **TradeReportOrderDetail**

**180.2.3666 OriginalNotionalPercentageOutstanding**

Used to reflect the Original value prior to the application of a credit event. See NotionalPercentageOutstanding(1451).

Type: **Percentage**

Used in components: **Instrument**

**180.2.3667 OriginatingDeptID**

An identifier representing the department or desk within the firm that originated the order.

Type: **String**

Used in groups: **SideCrossOrdModGrp**

Used in messages: **ExecutionReport, NewOrderSingle, OrderCancelReplaceRequest**

**180.2.3668 OrigOrdModTime**

The most recent (or current) modification TransactTime (tag 60) reported on an Execution Report for the order. The OrigOrdModTime is provided as an optional field on Order Cancel Request and Order Cancel Replace Requests to identify that the state of the order has not changed since the request was issued. The use of this approach is not recommended.

Type: **UTCTimestamp**

Used in components: **TradeReportOrderDetail**

Used in groups: **SideCrossOrdCxlGrp, SideCrossOrdModGrp**

Used in messages: **MultilegOrderCancelReplace, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest**

**180.2.3669 OrigPosReqRefID**

Reference to the PosReqID (710) of a previous maintenance request that is being replaced or canceled.

Type: **String**

Used in messages: **PositionMaintenanceReport, PositionMaintenanceRequest**

**180.2.3670 OrigSecondaryTradeID**

Used to preserve original secondary trade id when original trade is being referenced in a subsequent trade transaction such as a transfer

Type: **String**

Used in messages: **TradeCaptureReport, TradeCaptureReportAck**

**180.2.3671 OrigSendingTime**

Original time of message transmission (always expressed in UTC (Universal Time Coordinated, also known as "GMT") when transmitting orders as the result of a resend request.

Type: **UTCTimestamp**

Used in components: **StandardHeader**

**180.2.3672 OrigStrikePrice**

Original exercise price, e.g. after corporate action requiring changes.

Type: **Price**

Used in components: **Instrument**

**180.2.3673 OrigTime**

Time of message origination (always expressed in UTC (Universal Time Coordinated, also known as "GMT"))

Type: **UTCTimestamp**

Used in messages: **Email, News**

**180.2.3674 OrigTradeDate**

Used to preserve original trade date when original trade is being referenced in a subsequent trade transaction such as a transfer

Type: **LocalMktDate**

Used in messages: **TradeCaptureReport, TradeCaptureReportAck**

**180.2.3675 OrigTradeHandlingInstr**

Optionally used with TradeHandlingInstr = 0 to relay the trade handling instruction used when reporting the trade to the marketplace. Same values as TradeHandlingInstr (1123)

Type: **char**

Allowed values in TradeHandlingInstrCodeSet:

Code	Name	Description
0	TradeConfirmation	Trade confirmation
1	TwoPartyReport	Two-party report
2	OnePartyReportForMatching	One-party report for matching
3	OnePartyReportForPassThrough	One-party report for pass through. Can be used when one of the parties to the trade submits a report which then has to be approved or confirmed by the other (counter)party.
4	AutomatedFloorOrderRouting	Automated floor order routing
5	TwoPartyReportForClaim	Two-party report for claim
6	OnePartyReport	One-party report
7	ThirdPtyRptForPassThrough	Third-party report for pass through. Can be used when RootParties component contains a service provider role who submits the trade report and is not necessarily also on one side of the trade.
8	OnePartyReportAutoMatch	One-party report for auto-match. Indicates that the submission is a transfer trade to a firm or account that is part of the same corporate entity and that once validated the transfer should be automatically accepted without confirmation.

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.3676 OrigTradeID**

Used to preserve original trade id when original trade is being referenced in a subsequent trade transaction such as a transfer

Type: [String](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.3677 OutMainCntryUIndex**

Value of stocks in Currency

Type: [Amt](#)

Used in messages: [BidRequest](#)

**180.2.3678 OutsideIndexPct**

Used in EFP trades. Represented as a percentage.

Type: **Percentage**

Used in groups: **BidDescReqGrp**

**180.2.3679 OvernightInterestRate**

Overnight interest rate.

Type: **float**

Used in groups: **ClearingPriceParametersGrp**

**180.2.3680 OwnershipType**

The relationship between Registration parties.

Type: **char**

Allowed values in OwnershipTypeCodeSet:

---

Code	Name	Description
J	JointInvestors	Joint Investors
T	TenantsInCommon	Tenants in Common
2	JointTrustees	Joint Trustees

---

Used in messages: **RegistrationInstructions**

**180.2.3681 OwnerType**

Identifies the type of owner.

Type: **int**

Allowed values in OwnerTypeCodeSet:

Code	Name	Description
1	IndividualInvestor	Individual investor
2	PublicCompany	Public company
3	PrivateCompany	Private company
4	IndividualTrustee	Individual trustee
5	CompanyTrustee	Company trustee
6	PensionPlan	Pension plan
7	CustodianUnderGiftsToMinorsAct	Custodian under Gifts to Minors Act
8	Trusts	Trusts
9	Fiduciaries	Fiduciaries
10	NetworkingSubAccount	Networking sub-account
11	NonProfitOrganization	Non-profit organization
12	CorporateBody	Corporate body
13	Nominee	Nominee
14	InstitutionalCustomer	Institutional customer
15	Combined	Combined. Representing more than one type of beneficial owner account.
16	MemberFirmEmployee	Member firm employee or associated person
17	MarketMakingAccount	Market making account
18	ProprietaryAccount	Proprietary account
19	NonbrokerDealer	Non-broker-dealer
20	UnknownBeneficialOwnerType	Unknown beneficial owner type. In the context of US CAT this is a non-broker-dealer foreign affiliate or non-reporting foreign broker-dealer.
21	FirmsErrorAccount	Error account of firm
22	FirmAgencyAveragePriceAccount	Firm agency average price account

Used in groups: [RgstDtlsGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [Quote](#)

### 180.2.3682 PackageID

Identifier assigned to a collection of trades so that they can be analyzed as one atomic unit for risk assessment and clearing.

Type: **String**

Used in messages: **TradeCaptureReport**

#### **180.2.3683 ParentAllocID**

Contains the IndividualAllocId (tag 467) value of the allocation that is being offset as a result of a new allocation. This would be an optional field that would only be populated in the case of an allocation of an allocation (as well as any subsequent allocations). This wouldn't be populated for an initial allocation since an allocation id is not supplied on default (initial) allocations.

Type: **String**

Used in groups: **AllocAckGrp, AllocGrp, TrdAllocGrp**

#### **180.2.3684 ParentMktSegmID**

Reference to a parent Market Segment. See MarketSegmentID(1300)

Type: **String**

Used in messages: **MarketDefinition, MarketDefinitionRequest, MarketDefinitionUpdateReport**

#### **180.2.3685 ParticipationRate**

For a TargetStrategy=Participate order specifies the target participation rate. For other order types this is a volume limit (i.e. do not be more than this percent of the market volume)

Type: **Percentage**

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest, ExecutionReport, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest**

#### **180.2.3686 Parties**

The Parties component block is used to identify and convey information on the entities both central and peripheral to the financial transaction represented by the FIX message containing the Parties Block. The Parties block allows many different types of entites to be expressed through use of the PartyRole field and identifies the source of the PartyID through the the PartyIDSource.



Name	Mult.	Type	Description
NoPartyIDs	[1..1]	NumInGroup	Repeating group below should contain unique combinations of PartyID, PartyIDSource, and PartyRole
PartyID	[0..1]	String	Required if NoPartyIDs(453) > 0. Identification of the party.
PartyIDSource	[0..1]	CodeSet	Required if NoPartyIDs(453) > 0. Used to identify classification source.
PartyRole	[0..1]	CodeSet	Required if NoPartyIDs(453) > 0. Identifies the type of PartyID(448).
PartyRoleQualifier	[0..1]	CodeSet	
PtysSubGrp	[0..*]	Group	Repeating group of Party sub-identifiers.

Used in groups: ListOrdGrp, MDFullGrp, MDIncGrp, QuotReqGrp, QuotReqRjctGrp, SettlInstGrp, SettlObligationInstructions, SideCrossOrdCxlGrp, SideCrossOrdModGrp, StrmAsgnReqGrp, StrmAsgnRptGrp, TrdCapRptAckSideGrp, TrdCapRptSideGrp, TrdMatchSideGrp

Used in messages: AccountSummaryReport, AdjustedPositionReport, AlgoCertificateReport, AlgoCertificateRequest, AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationInstructionAlertRequest, AllocationReport, AllocationReportAck, ApplicationMessageRequest, ApplicationMessageRequestAck, AssignmentReport, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralReportAck, CollateralRequest, CollateralResponse, Confirmation, ContraryIntentionReport, ExecutionReport, IOI, ListCancelRequest, MarginRequirementInquiry, MarginRequirementInquiryAck, MarginRequirementReport, MarketDataRequest, MarketDataRequestReject, MarketDataStatisticsReport, MarketDataStatisticsRequest, MarketDefinition, MarketDefinitionUpdateReport, MassOrder, MassOrderAck, MassQuote, MassQuoteAck, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderMassStatusRequest, OrderStatusRequest, PartyActionReport, PartyActionRequest, PartyDetailsListRequest, PartyEntitlementsRequest, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PartyRiskLimitsRequest, PayManagementReport, PayManagementRequest, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport, Quote, QuoteAck, QuoteCancel, QuoteResponse, QuoteStatusReport, QuoteStatusRequest, RFQRequest, RegistrationInstructions, RegistrationInstructionsResponse, RequestForPositions, RequestForPositionsAck, SettlementInstructionRequest, SettlementStatusReport, SettlementStatusRequest, TestActionRequest, TestSuiteDefinitionRequest, TradeAggregationRequest, TradeCaptureReportRequest

**180.2.3687 PartyActionRejectReason**

Specifies the reason the PartyActionRequest(35=DH) was rejected.

Type: **int**

Allowed values in PartyActionRejectReasonCodeSet:

Code	Name	Description
0	InvalidParty	Invalid party or parties
1	UnkReqParty	Unknown requesting party
98	NotAuthorized	Not authorized
99	Other	Other

Used in messages: **PartyActionReport**

**180.2.3688 PartyActionReportID**

The unique identifier of the PartyActionReport(35=DI) message as assigned by the message sender.

Type: **String**

Used in messages: **PartyActionReport**

**180.2.3689 PartyActionRequestID**

The unique identifier of the PartyActionRequest(35=DH) message.

Type: **String**

Used in messages: **PartyActionReport, PartyActionRequest**

**180.2.3690 PartyActionResponse**

Specifies the action taken as a result of the PartyActionType(2239) of the PartyActionRequest(35=DH) message.

Type: **int**

Allowed values in PartyActionResponseCodeSet:

Code	Name	Description
0	Accepted	Accepted. The action request is accepted for processing.
1	Completed	Completed. The processing of the requested action has been successfully completed.
2	Rejected	Rejected. The action request was rejected. PartyActionRejectReason(2233) should be used to specify the rejection reason

Used in messages: **PartyActionReport**

### 180.2.3691 PartyActionType

Specifies the type of action to take or was taken for a given party.

Type: **int**

Allowed values in PartyActionCodeSet:

Code	Name	Description
0	Suspend	Suspend
1	HaltTrading	Halt trading
2	Reinstate	Reinstate

Used in messages: **PartyActionReport**, **PartyActionRequest**

### 180.2.3692 PartyDetailAckGrp

The PartyDetailAckGrp component is used in the PartyDetailsDefinitionRequestAck(35=CX) message to provide the status of each action (add, modify or delete) requested by the PartyDetailsDefinitionRequest(35=CX) message. The PartyDetailStatus(1880) field is used to indicate the status. In the case where an add or modify request is accepted with changes, the PartyDetailGrp component is required, with the complete set of party details that have been accepted for the party included.

Name	Mult.	Type	Description
<b>NoPartyUpdates</b>	[1..1]	NumInGroup	
<b>ListUpdateAction</b>	[0..1]	CodeSet	Required if NoPartyUpdates(1676) > 0.

Name	Mult.	Type	Description
PartyDetailDefinitionStatus	[0..1]	CodeSet	Required if NoPartyUpdates(1676) > 0.
PartyDetailDefinitionResult	[0..1]	CodeSet	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
PartyDetailGrp	[0..*]	Group	

Used in messages: **PartyDetailsDefinitionRequestAck**

### 180.2.3693 PartyDetailAltID

An alternate party identifier for the party specified in PartyDetailID(1691)

Type: **String**

Used in groups: **PartyDetailAltIDGrp**

### 180.2.3694 PartyDetailAltIDGrp

Alternative identifiers for a party.

Name	Mult.	Type	Description
NoPartyDetailAltID	[1..1]	NumInGroup	
PartyDetailAltID	[0..1]	String	Required when NoPartyDetailAltID > 0.
PartyDetailAltIDSource	[0..1]	CodeSet	Required when NoPartyDetailAltID > 0.
PartyDetailAltSubGrp	[0..*]	Group	

Used in groups: **PartyDetailGrp**

### 180.2.3695 PartyDetailAltIDSource

Identifies the source of the PartyDetailAltID(1517) value.

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.

Code	Name	Description
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **PartyDetailAltIDGrp**

### 180.2.3696 PartyDetailAltSubGrp

Alternate sub-identifiers for a party.

Name	Mult.	Type	Description
NoPartyDetailAltSubIDs	[1..1]	NumInGroup	
PartyDetailAltSubID	[0..1]	String	Required when NoPartyDetailAltSubIDs > 0.
PartyDetailAltSubIDType	[0..1]	CodeSet	Required when NoPartyDetailAltSubIDs > 0.

Used in groups: **PartyDetailAltIDGrp**

### **180.2.3697 PartyDetailAltSubID**

Sub-identifier for the party specified in PartyDetailAltID(1517).

Type: **String**

Used in groups: **PartyDetailAltSubGrp**

### **180.2.3698 PartyDetailAltSubIDType**

Type of PartyDetailAltSubID(1520) value.

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name

Code	Name	Description
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".



Code	Name	Description
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.

Code	Name	Description
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C = Credit institution authorized in accordance with Directive 2006/48/EC F = Investment firm in accordance with Directive 2004/39/EC I = Insurance undertaking authorized in accordance with Directive 73/239/EC L = Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O = Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R = Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U = UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.

Code	Name	Description
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.

Code	Name	Description
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.

Code	Name	Description
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: [PartyDetailAltSubGrp](#)

### 180.2.3699 PartyDetailDefinitionResult

Result of party detail definition for one party.

Type: [int](#)

Allowed values in PartyDetailRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidParty	Invalid party(-ies)
2	InvalidRelatedParty	Invalid related party(-ies)
3	InvalidPartyStatus	Invalid party status(es)
98	NotAuthorized	Not authorized
99	Other	Other

Used in groups: [PartyDetailAckGrp](#)

### 180.2.3700 PartyDetailDefinitionStatus

Status of party detail definition for one party.

Type: [int](#)

Allowed values in PartyDetailDefinitionStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithChanges	Accepted with changes
2	Rejected	Rejected

Used in groups: **PartyDetailAckGrp**

### 180.2.3701 PartyDetailGrp

Contains details for a party, including related parties and alternative party identifiers.

Name	Mult.	Type	Description
<b>NoPartyDetails</b>	[1..1]	NumInGroup	
<b>PartyDetailID</b>	[0..1]	String	The identification of the party. Required when NoPartyDetails(1671) > 0.
<b>PartyDetailIDSource</b>	[0..1]	CodeSet	Used to identify source of PartyID value (e.g. BIC). Required when NoPartyDetails(1671) > 0.
<b>PartyDetailRole</b>	[0..1]	CodeSet	Identifies the type of PartyID (e.g. Executing Broker). Required when NoPartyDetails(1671) > 0.
<b>PartyDetailRoleQualifier</b>	[0..1]	CodeSet	
<b>PartyDetailSubGrp</b>	[0..*]	Group	
<b>PartyDetailAltIDGrp</b>	[0..*]	Group	Optionally used to specify alternate IDs to identify the party specified.
<b>RelatedPartyDetailGrp</b>	[0..*]	Group	May not be specified in PartyDetailsListUpdateReport(35=CK) if ListUpdateAction(1324) = D(Delete)
<b>PartyDetailStatus</b>	[0..1]	CodeSet	

Used in groups: **PartyDetailAckGrp**, **PartyDetailsUpdateGrp**, **PartyEntitlementAckGrp**, **PartyEntitlementGrp**, **PartyEntitlementUpdateGrp**, **PartyRiskLimitsAckGrp**, **PartyRiskLimitsGrp**, **PartyRiskLimitsUpdateGrp**, **TrdCapRptSideGrp**

Used in messages: **PartyDetailsListReport**

### 180.2.3702 PartyDetailID

Party identifier within Parties Reference Data messages.

Type: **String**

Used in groups: **PartyDetailGrp**

### 180.2.3703 PartyDetailIDSource

Source of the identifier of the PartyDetailID(1691) specified.

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID

Code	Name	Description
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **PartyDetailGrp**



**180.2.3704 PartyDetailRequestResult**

Result party detail definition request.

Type: **int**

Allowed values in PartyDetailRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidParty	Invalid party(-ies)
2	InvalidRelatedParty	Invalid related party(-ies)
3	InvalidPartyStatus	Invalid party status(es)
98	NotAuthorized	Not authorized
99	Other	Other

Used in messages: **PartyDetailsDefinitionRequestAck**

**180.2.3705 PartyDetailRequestStatus**

Status of party details definition request.

Type: **int**

Allowed values in PartyDetailRequestStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithChanges	Accepted with changes
2	Rejected	Rejected
3	AcceptancePending	Acceptance pending

Used in messages: **PartyDetailsDefinitionRequestAck**

**180.2.3706 PartyDetailRole**

Identifies the type or role of PartyDetailID(1691) specified.

Type: **int**

## Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian

Code	Name	Description
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)

Code	Name	Description
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionV- enue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm

Code	Name	Description
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor

Code	Name	Description
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **PartyDetailGrp**

**180.2.3707 PartyDetailRoleQualifier**

Qualifies the value of PartyDetailRole(1693).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange

Code	Name	Description
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **PartyDetailGrp**

### 180.2.3708 PartyDetailsListReportID

Identifier for the PartyDetailsListReport and the PartyDetailsListUpdateReport.

Type: **String**

Used in messages: **PartyDetailsListReport**, **PartyDetailsListUpdateReport**



**180.2.3709 PartyDetailsListRequestID**

Unique identifier for PartyDetailsListRequest.

Type: **String**

Used in messages: **PartyDetailsDefinitionRequest**, **PartyDetailsDefinitionRequestAck**, **PartyDetailsListReport**, **PartyDetailsListRequest**, **PartyDetailsListUpdateReport**

**180.2.3710 PartyDetailStatus**

Indicates the status of the party identified with PartyDetailID(1691).

Type: **int**

Allowed values in PartyDetailStatusCodeSet:

Code	Name	Description
0	Active	Active (default if not specified)
1	Suspended	Suspended
2	Halted	Halted

Used in groups: **PartyDetailGrp**

**180.2.3711 PartyDetailSubGrp**

Additional party sub-identifiers

Name	Mult.	Type	Description
<b>NoPartyDetailSubIDs</b>	[1..1]	NumInGroup	
<b>PartyDetailSubID</b>	[0..1]	String	Required when NoPartyDetailSubIDs > 0.
<b>PartyDetailSubIDType</b>	[0..1]	CodeSet	Required when NoPartyDetailSubIDs > 0.

Used in groups: **PartyDetailGrp**

**180.2.3712 PartyDetailSubID**

Sub-identifier for the party specified in PartyDetailID(1691).

Type: **String**

Used in groups: **PartyDetailSubGrp**

**180.2.3713 PartyDetailSubIDType**

Type of PartyDetailSubID(1695) value.

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number

Code	Name	Description
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.

Code	Name	Description
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **PartyDetailSubGrp**

**180.2.3714 PartyDetailsUpdateGrp**

Party details component that includes an update action.

Name	Mult.	Type	Description
NoPartyUpdates	[1..1]	NumInGroup	
ListUpdateAction	[0..1]	CodeSet	Required if NoPartyUpdates > 0.
PartyDetailGrp	[0..*]	Group	

Used in messages: [PartyDetailsDefinitionRequest](#), [PartyDetailsListUpdateReport](#)

**180.2.3715 PartyEntitlementAckGrp**

The PartyEntitlementAckGrp component is used in the PartyEntitlementsDefinitionRequestAck(35=DB) message to provide the status of each action (add, modify or delete) requested by the PartyEntitlementsDefinitionRequest(35=DA) message.

Name	Mult.	Type	Description
NoPartyEntitlements	[1..1]	NumInGroup	
ListUpdateAction	[0..1]	CodeSet	Required if NoPartyEntitlements(1772).
EntitlementStatus	[0..1]	CodeSet	Required if NoPartyEntitlements(1772).
EntitlementResult	[0..1]	CodeSet	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	
EncodedRejectText	[0..1]	data	
PartyDetailGrp	[0..*]	Group	Optional when ListUpdateAction(1324) = M(Modify) or D>Delete) and EntitlementRefID(1885) is provided.
EntitlementGrp	[0..*]	Group	Optional when ListUpdateAction(1324) = M(Modify) or D>Delete) and EntitlementRefID(1885) is provided.
EntitlementRefID	[0..1]	String	Optional when PartyDetailGrp is provided or ListUpdateAction(1324) = A(Add).

Used in messages: [PartyEntitlementsDefinitionRequestAck](#)



**180.2.3716 PartyEntitlementGrp**

Conveys a list of parties (optionally including related parties) and the entitlements for each.

Name	Mult.	Type	Description
NoPartyEntitlements	[1..1]	NumInGroup	
PartyDetailGrp	[0..*]	Group	Required if NoPartyEntitlements(1772) > 0.
EntitlementStatus	[0..1]	CodeSet	
EntitlementGrp	[0..*]	Group	Required unless omitted to indicate the removal of entitlements for the party(-ies) specified in the PartyDetailGrp component.

Used in messages: **PartyEntitlementsReport**

**180.2.3717 PartyEntitlementUpdateGrp**

The PartyEntitlementUpdateGrp component is used to supply incremental entitlement definitions changes for the party(-ies) specified in the PartyDetailGrp component. The update action type is specified using ListUpdateAction(1324).

Name	Mult.	Type	Description
NoPartyEntitlements	[1..1]	NumInGroup	
ListUpdateAction	[0..1]	CodeSet	Required if NoPartyEntitlements(1772).
PartyDetailGrp	[0..*]	Group	Optional when ListUpdateAction(1324) = M(Modify) or D>Delete) and EntitlementRefID(1885) is provided.
EntitlementStatus	[0..1]	CodeSet	
EntitlementGrp	[0..*]	Group	Optional when ListUpdateAction(1324) = M(Modify) or D>Delete) and EntitlementRefID(1885) is provided.
EntitlementRefID	[0..1]	String	Optional when PartyDetailGrp is provided or ListUpdateAction(1324) = A>Add).

Used in messages: **PartyEntitlementsDefinitionRequest**, **PartyEntitlementsUpdateReport**

**180.2.3718 PartyID**

Party identifier/code. See PartyIDSource (447) and PartyRole (452).

See "Appendix 6-G - Use of <Parties> Component Block"

Type: **String**

Used in groups: **Parties**

### **180.2.3719 PartyIDSource**

Identifies class or source of the PartyID (448) value. Required if PartyID is specified. Note: applicable values depend upon PartyRole (452) specified.

See "Appendix 6-G - Use of <Parties> Component Block"

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number

Code	Name	Description
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **Parties**

### **180.2.3720 PartyRelationship**

Used to specify the type of the party relationship.

Type: **int**

Allowed values in PartyRelationshipCodeSet:

<b>Code</b>	<b>Name</b>	<b>Description</b>
0	IsAlso	Is also
1	ClearsFor	Clears for
2	ClearsThrough	Clears through
3	TradesFor	Trades for
4	TradesThrough	Trades through
5	Sponsors	Sponsors
6	SponsoredThrough	Sponsored through
7	ProvidesGuaranteeFor	Provides guarantee for
8	IsGuaranteedBy	Is guaranteed by
9	MemberOf	Member of
10	HasMembers	Has members
11	ProvidesMarketplaceFor	Provides marketplace for
12	ParticipantOfMarketplace	Participant of marketplace
13	CarriesPositionsFor	Carries positions for
14	PostsTradesTo	Posts trades to
15	EntersTradesFor	Enters trades for
16	EntersTradesThrough	Enters trades through
17	ProvidesQuotesTo	Provides quotes to
18	RequestsQuotesFrom	Requests quotes from
19	InvestsFor	Invests for
20	InvestsThrough	Invests through
21	BrokersTradesFor	Brokers trades for
22	BrokersTradesThrough	Brokers trades through
23	ProvidesTradingServicesFor	Provides trading services for
24	UsesTradingServicesOf	Uses trading services of
25	ApprovesOf	Approves of

Code	Name	Description
26	ApprovedBy	Approved by
27	ParentFirmFor	Parent firm for
28	SubsidiaryOf	Subsidiary of
29	RegulatoryOwnerOf	Regulatory owner of
30	OwnedByRegulatory	Owned by (regulatory)
31	Controls	Controls
32	IsControlledBy	Is controlled by
33	LegalOwnerOf	Legal / titled owner of
34	OwnedByLegal	Owned by (legal / title)
35	BeneficialOwnerOf	Beneficial owner of
36	OwnedByBeneficial	Owned by (beneficial)
37	SettlesFor	Settles for
38	SettlesThrough	Settles through

Used in groups: **PartyRelationshipGrp**

#### 180.2.3721 PartyRelationshipGrp

Repeating group of party relationships.

Name	Mult.	Type	Description
NoPartyRelationships	[1..1]	NumInGroup	
PartyRelationship	[0..1]	CodeSet	Identifies the type of party relationship requested. Required if NoPartyRelationships > 0.

Used in groups: **RelatedPartyDetailGrp**

Used in messages: **PartyDetailsListRequest**

#### 180.2.3722 PartyRiskLimitsAckGrp

This new block is a repeating group based on the existing block <PartyRiskLimitsGrp> with an additional field RiskLimitStatus(1763) to accept (with or without changes) or reject individual risk limits. It is only used in PartyRiskLimitDefinitionRequestAck, the response to the request to define risk limits. An

approval with changes requires to send <RiskLimitsGrp> with the complete set of risk limits that have been accepted for the party defined.

Name	Mult.	Type	Description
NoPartyRiskLimits	[1..1]	NumInGroup	
ListUpdateAction	[0..1]	CodeSet	Required if NoPartyRiskLimits(1677) > 0.
RiskLimitStatus	[0..1]	CodeSet	Required if NoPartyRiskLimits(1677) > 0.
RiskLimitResult	[0..1]	CodeSet	
PartyDetailGrp	[0..*]	Group	Conditionally required when RiskLimitID(1670) is not provided. Changes to party or related party(-ies) defined in the request are not permitted.
RiskLimitsGrp	[0..*]	Group	Conditionally required when RiskLimitStatus(1763) = 1(Accepted with changes) and must then be complete, i.e. omissions compared to the request represent risk limits that were removed, additional risk limits are possible.
RiskLimitID	[0..1]	String	Conditionally required when PartyDetailGrp component is not provided.
RiskLimitCheckModelType	[0..1]	CodeSet	
RejectText	[0..1]	String	
EncodedRejectTextLen	[0..1]	Length	Must be set if EncodedRejectText(1665) field is specified and must immediately precede it.
EncodedRejectText	[0..1]	data	Encoded (non-ASCII characters) representation of the RejectText(1328) field in the encoded format specified via the MessageEncoding(347) field.
PartyRiskLimitStatus	[0..1]	CodeSet	

Used in messages: **PartyRiskLimitsDefinitionRequestAck**

### 180.2.3723 PartyRiskLimitsGrp

Repeating group of parties (specified using PartyDetails) and the risk limits for the party.

Name	Mult.	Type	Description
NoPartyRiskLimits	[1..1]	NumInGroup	
PartyDetailGrp	[0..*]	Group	Required if NoPartyRiskLimits(1677) > 0.

Name	Mult.	Type	Description
<b>RiskLimitsGrp</b>	[0..*]	Group	Required if NoPartyRiskLimits(1677) > 0. Omit to implicitly report removal of risk limits.
<b>RiskLimitID</b>	[0..1]	String	
<b>RiskLimitCheckModelType</b>	[0..1]	CodeSet	
<b>PartyRiskLimitStatus</b>	[0..1]	CodeSet	

Used in messages: **PartyRiskLimitsReport**

### 180.2.3724 PartyRiskLimitStatus

The status of risk limits for a party.

Type: **int**

Allowed values in PartyRiskLimitStatusCodeSet:

Code	Name	Description
0	Disabled	Disabled. Risk limits for party is disabled.
1	Enabled	Enabled. Risk limits for party is enabled.

Used in groups: **PartyRiskLimitsAckGrp**, **PartyRiskLimitsGrp**, **PartyRiskLimitsUpdateGrp**

### 180.2.3725 PartyRiskLimitsUpdateGrp

This new block is a repeating group based on the existing block <PartyRiskLimitsGrp> with an additional field ListUpdateAction(1324) to support incremental changes of risk limit definitions. The group is part of the definition request as well as part of the update report for risk limits.

Name	Mult.	Type	Description
<b>NoPartyRiskLimits</b>	[1..1]	NumInGroup	
<b>ListUpdateAction</b>	[0..1]	CodeSet	Required if NoPartyRiskLimits(1677) > 0.

Name	Mult.	Type	Description
PartyDetailGrp	[0..*]	Group	Conditionally required when ListUpdateAction(1324) = A(Add). Conditionally required when ListUpdateAction(1324) = M(Modify) or D(Delete) and RiskLimitID(1670) is not provided.
RiskLimitsGrp	[0..*]	Group	Conditionally required when ListUpdateAction(1324) = A(Add) or M(Modify).
RiskLimitID	[0..1]	String	Conditionally required when PartyDetailGrp component is not provided.
RiskLimitCheckModelType	[0..1]	CodeSet	
PartyRiskLimitStatus	[0..1]	CodeSet	

Used in messages: **PartyRiskLimitsDefinitionRequest**, **PartyRiskLimitsReportAck**, **PartyRiskLimitsUpdateReport**

### 180.2.3726 PartyRole

Identifies the type or role of the PartyID (448) specified.

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)



Code	Name	Description
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange

Code	Name	Description
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.

Code	Name	Description
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.

Code	Name	Description
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.

Code	Name	Description
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **Parties**

### 180.2.3727 PartyRoleQualifier

Used to further qualify the value of PartyRole(452).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member

Code	Name	Description
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.

Code	Name	Description
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **Parties**

### **180.2.3728 PartySubID**

Sub-identifier (e.g. Clearing Account for PartyRole (452)=Clearing Firm, Locate ID # for PartyRole=Locate/Lending Firm, etc). Not required when using PartyID (448), PartyIDSource (447), and PartyRole.

Type: **String**

Used in groups: **PtysSubGrp**

### **180.2.3729 PartySubIDType**

Type of PartySubID(523) value.

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier



Code	Name	Description
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account

Code	Name	Description
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **PtysSubGrp**

**180.2.3730 Password**

Password or passphrase.

Type: **String**

Used in messages: **Logon**, **UserRequest**

**180.2.3731 PayAmount**

Amount to be paid by the clearinghouse to the clearing firm.

Type: **Amt**

Used in groups: **PayCollectGrp**

**180.2.3732 PayCollectCurrency**

Currency denomination of value in PayAmount(1710) and CollectAmount(1711). If not specified, default to currency specified in SettlementAmountCurrency(1702).

Type: **Currency**

Used in groups: **PayCollectGrp**

**180.2.3733 PayCollectCurrencyCodeSource**

Identifies class or source of the PayCollectCurrency(1709) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **PayCollectGrp**

### **180.2.3734 PayCollectFXRate**

Foreign exchange rate used to compute the PayAmount(1710) or CollectAmount(1711) from the PayCollectCurrency(1709) and the Currency(15).

Type: **float**

Used in groups: **PayCollectGrp**

### **180.2.3735 PayCollectFXRateCalc**

Specifies whether or not PayCollectFXRate(2094) should be multiplied or divided.

Type: **char**

Allowed values in UnderlyingFXRateCalcCodeSet:

Code	Name	Description
D	Divide	Divide
M	Multiply	Multiply

Used in groups: **PayCollectGrp**

### **180.2.3736 PayCollectGrp**

The Pay Collect Group component block is a repeatable block intended to report individual pay/collect items to be considered when calculating net settlement.

Name	Mult.	Type	Description
<b>NoPayCollects</b>	[1..1]	NumInGroup	
<b>PayCollectType</b>	[0..1]	String	Required if NoPayCollects > 0.
<b>PayCollectCurrency</b>	[0..1]	Currency	Can be used to specify the base settlement currency if Currency(15) is not specified.
<b>PayCollectCurrencyCodeSource</b>	[0..1]	CodeSet	
<b>PayCollectFXRate</b>	[0..1]	float	
<b>PayCollectFXRateCalc</b>	[0..1]	CodeSet	

Name	Mult.	Type	Description
PayAmount	[0..1]	Amt	
CollectAmount	[0..1]	Amt	
PayCollectMarketSegmentID	[0..1]	String	
PayCollectMarketID	[0..1]	String	

Used in messages: [AccountSummaryReport](#)

#### **180.2.3737 PayCollectMarketID**

Market associated with the pay collect amount.

Type: [String](#)

Used in groups: [PayCollectGrp](#)

#### **180.2.3738 PayCollectMarketSegmentID**

Market segment associated with the pay collect amount.

Type: [String](#)

Used in groups: [PayCollectGrp](#)

#### **180.2.3739 PayCollectType**

Category describing the reason for funds paid to, or the funds collected from the clearing firm.

Type: [String](#)

Used in groups: [PayCollectGrp](#)

#### **180.2.3740 PayDisputeReason**

Used to provide the reason for disputing a request or report.

See <https://www.fixtrading.org/packages/PayDisputeReason> for the list of applicable values.

Type: [int](#)

Used in messages: [PayManagementReport](#), [PayManagementReportAck](#)



**180.2.3741 PaymentAmount**

The total payment amount.

Type: **Amt**

Used in groups: **PaymentGrp**

**180.2.3742 PaymentAmountDeterminationMethod**

Specifies the method by which a payment amount is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **PaymentGrp**

**180.2.3743 PaymentAmountRelativeTo**

Specifies the reference amount when the payment amount is relative to another amount in the message.

See [http://www.fixtradingcommunity.org/codelists#Payment\\_Amount\\_Relative\\_To](http://www.fixtradingcommunity.org/codelists#Payment_Amount_Relative_To) for code list of relative amounts.

Type: **int**

Used in groups: **PaymentGrp**

**180.2.3744 PaymentBusinessCenter**

The business center calendar used to adjust the payment date, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **PaymentBusinessCenterGrp**

**180.2.3745 PaymentBusinessCenterGrp**

PaymentBusinessCenterGrp is a repeating subcomponent within the PaymentGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoPaymentBusinessCenters	[1..1]	NumInGroup	
PaymentBusinessCenter	[0..1]	String	Required if NoPaymentBusinessCenters(40944) > 0.

Used in groups: **PaymentGrp**

### 180.2.3746 PaymentBusinessDayConvention

The business day convention used to adjust the payment date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: **PaymentGrp**

### 180.2.3747 PaymentCurrency

Specifies the currency in which PaymentAmount(40217) is denominated. Uses ISO 4271 currency codes.

Type: **Currency**

Used in groups: **PaymentGrp**

**180.2.3748 PaymentDate**

The date written on a cheque or date payment should be submitted to the relevant clearing system.

Type: **LocalMktDate**

Used in groups: **SettlInstGrp**

**180.2.3749 PaymentDateAdjusted**

The adjusted payment date.

Type: **LocalMktDate**

Used in groups: **PaymentGrp**

**180.2.3750 PaymentDateOffsetDayType**

Specifies the day type of the relative payment date offset.

Type: **int**

Allowed values in PaymentDateOffsetDayTypeCodeSet:

---

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	Commodity	Commodity business
3	Currency	Currency business
4	Exchange	Exchange business
5	Scheduled	Scheduled trading day

---

Used in groups: **PaymentGrp**

**180.2.3751 PaymentDateOffsetPeriod**

Time unit multiplier for the relative payment date offset.

Type: **int**

Used in groups: **PaymentGrp**

**180.2.3752 PaymentDateOffsetUnit**

Time unit associated with the relative payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **PaymentGrp**

**180.2.3753 PaymentDateRelativeTo**

Specifies the anchor date when the payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **PaymentGrp**

**180.2.3754 PaymentDateUnadjusted**

The unadjusted payment date.

Type: **LocalMktDate**

Used in groups: **PaymentGrp**

**180.2.3755 PaymentDesc**

A short descriptive name given to the payment, e.g. Premium, Upfront, etc. The description has no intrinsic meaning but should be arbitrarily chosen by the remitter as reference.

Type: **String**

Used in groups: **PaymentGrp**

**180.2.3756 PaymentDiscountFactor**

The value representing the discount factor used to calculate the present value of the cash flow.

Type: **float**

Used in groups: **PaymentGrp**

**180.2.3757 PaymentFixedRate**

The rate applicable to the fixed rate payment.

Type: **Percentage**

Used in groups: **PaymentGrp**

**180.2.3758 PaymentFloatingRateIndex**

The payment floating rate index. See SpreadOrBenchmarkCurveData(221) for suggested values.

Type: **String**

Used in groups: **PaymentGrp**

**180.2.3759 PaymentFloatingRateIndexCurvePeriod**

Time unit multiplier for the floating rate index.

Type: **int**

Used in groups: **PaymentGrp**

**180.2.3760 PaymentFloatingRateIndexCurveUnit**

Time unit associated with the floating rate index.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week

---

---

Code	Name	Description
------	------	-------------

---

Mo	Month	Month
----	-------	-------

Yr	Year	Year
----	------	------

---

Used in groups: **PaymentGrp**

### **180.2.3761 PaymentFloatingRateSpread**

Spread from floating rate index.

Type: **PriceOffset**

Used in groups: **PaymentGrp**

### **180.2.3762 PaymentForwardStartType**

Forward start premium type.

Type: **int**

Allowed values in PaymentForwardStartTypeCodeSet:

---

Code	Name	Description
------	------	-------------

---

0	Prepaid	Prepaid
---	---------	---------

1	Postpaid	Post-paid
---	----------	-----------

2	Variable	Variable
---	----------	----------

3	Fixed	Fixed
---	-------	-------

---

Used in groups: **PaymentGrp**

### **180.2.3763 PaymentFrequencyPeriod**

Time unit multiplier for the payment frequency.

Type: **int**

Used in groups: **PaymentGrp**

**180.2.3764 PaymentFrequencyUnit**

Time unit associated with the payment frequency.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **PaymentGrp**

**180.2.3765 PaymentGrp**

The PaymentGrp is a repeating component used to report additional payments or bullet payments.

Name	Mult.	Type	Description
NoPayments	[1..1]	NumInGroup	
PaymentType	[0..1]	CodeSet	Required if NoPayments(40212) > 0.
PaymentSubType	[0..1]	CodeSet	
PaymentPaySide	[0..1]	CodeSet	
PaymentReceiveSide	[0..1]	CodeSet	
PaymentDesc	[0..1]	String	
PaymentCurrency	[0..1]	Currency	
PaymentAmount	[0..1]	Amt	Either PaymentAmount(40217), PaymentFixedRate(43097) or PaymentRFloatingRateIndex(43098) must be specified.
PaymentAmountRelativeTo	[0..1]	int	
PaymentAmountDetermination-Method	[0..1]	String	

Name	Mult.	Type	Description
PaymentFixedRate	[0..1]	Percentage	Either PaymentAmount(40217), PaymentFixedRate(43097) or PaymentFloatingRateIndex(43098) must be specified.
PaymentFloatingRateIndex	[0..1]	String	Either PaymentAmount(40217), PaymentFixedRate(43097) or PaymentFloatingRateIndex(43098) must be specified.
PaymentFloatingRateIndexCurveUnit	[0..1]	CodeSet	Conditionally required when PaymentFloatingRateIndexCurvePeriod(43099) is specified.
PaymentFloatingRateIndexCurvePeriod	[0..1]	int	Conditionally required when PaymentFloatingRateIndexCurveUnit(43100) is specified.
PaymentFloatingRateSpread	[0..1]	PriceOffset	Conditionally required when PaymentFloatingRateIndex(43098) is specified and the spread to the index is not "zero". When the spread to the index is "zero" this may be omitted.
PaymentRateResetFrequencyUnit	[0..1]	CodeSet	Conditionally required when PaymentRateResetFrequencyPeriod(43104) is specified.
PaymentRateResetFrequencyPeriod	[0..1]	int	Conditionally required when PaymentRateResetFrequencyUnit(43105) is specified.
PaymentFrequencyUnit	[0..1]	CodeSet	Conditionally required when PaymentFrequencyPeriod(43102) is specified.
PaymentFrequencyPeriod	[0..1]	int	Conditionally required when PaymentFrequencyUnitPeriod(43103) is specified.
PaymentPrice	[0..1]	Price	
PaymentPriceType	[0..1]	CodeSet	
PaymentUnitOfMeasure	[0..1]	CodeSet	
PaymentDateUnadjusted	[0..1]	LocalMktDate	
PaymentBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the payment information.



Name	Mult.	Type	Description
PaymentBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the payment information.
PaymentDateRelativeTo	[0..1]	int	
PaymentDateOffsetPeriod	[0..1]	int	Conditionally required when PaymentDateOffsetUnit(41158) is specified.
PaymentDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentDateOffsetPeriod(41157) is specified.
PaymentDateOffsetDayType	[0..1]	CodeSet	
PaymentDateAdjusted	[0..1]	LocalMktDate	
PaymentForwardStartType	[0..1]	CodeSet	
PaymentDiscountFactor	[0..1]	float	
PaymentPresentValueAmount	[0..1]	Amt	
PaymentPresentValueCurrency	[0..1]	Currency	
PaymentSettlStyle	[0..1]	CodeSet	
PaymentMethod	[0..1]	CodeSet	
PaymentSettlGrp	[0..*]	Group	
PaymentLegRefID	[0..1]	String	Used to link a payment back to its parent InstrumentLeg by using the same value as the parent's LegID(1788).
PaymentText	[0..1]	String	
EncodedPaymentTextLen	[0..1]	Length	Must be set if EncodedPaymentText(40985) field is specified and must immediately precede it.
EncodedPaymentText	[0..1]	data	Encoded (non-ASCII characters) representation of the PaymentText(40229) field in the encoded format specified via the MessageEncoding(347) field.

Used in messages: **ExecutionReport**, **PositionMaintenanceReport**, **PositionReport**, **TradeCaptureReport**

### 180.2.3766 PaymentLegRefID

Identifies the instrument leg in which this payment applies to by referencing the leg's LegID(1788).

Type: **String**

Used in groups: **PaymentGrp**

### **180.2.3767 PaymentMethod**

Identifies the settlement payment method.

Type: **int**

Allowed values in PaymentMethodCodeSet:

Code	Name	Description
1	CREST	CREST
2	NSCC	NSCC
3	Euroclear	Euroclear
4	Clearstream	Clearstream
5	Cheque	Cheque
6	TelegraphicTransfer	Telegraphic Transfer
7	FedWire	Fed Wire
8	DebitCard	Debit Card
9	DirectDebit	Direct Debit (BECS)
10	DirectCredit	Direct Credit (BECS)
11	CreditCard	Credit Card
12	ACHDebit	ACH Debit
13	ACHCredit	ACH Credit
14	BPAY	BPAY
15	HighValueClearingSystem	High Value Clearing System (HVACS)
16	CHIPS	CHIPS
17	SWIFT	S.W.I.F.T.
18	CHAPS	CHAPS
19	SIC	SIC
20	EuroSIC	euroSIC.
999	Other	Other

Used in groups: **PaymentGrp**, **SettlInstGrp**

**180.2.3768 PaymentPaySide**

The side of the party paying the payment.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **PaymentGrp**

**180.2.3769 PaymentPresentValueAmount**

The amount representing the present value of the forecast payment.

Type: **Amt**

Used in groups: **PaymentGrp**

**180.2.3770 PaymentPresentValueCurrency**

Specifies the currency the PaymentPresentValueAmount(40225) is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **PaymentGrp**

**180.2.3771 PaymentPrice**

The price determining the payment amount expressed in terms specified in PaymentPriceType(40919) and expressed in market format.

Type: **Price**

Used in groups: **PaymentGrp**

**180.2.3772 PaymentPriceType**

Specifies the type of price for PaymentPrice(40218).

Type: **int**

Allowed values in PriceTypeCodeSet:

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
2	PerUnit	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points spread). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	Yield	Yield
10	FixedCabinetTradePrice	Fixed cabinet trade price (primarily for listed futures and options)
11	VariableCabinetTradePrice	Variable cabinet trade price (primarily for listed futures and options)
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example, the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)

Code	Name	Description
22	BasisPoints	Basis points. When the price is not spread based.
23	UpfrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageNotional	Percentage of notional

Used in groups: **PaymentGrp**

### **180.2.3773 PaymentRateResetFrequencyPeriod**

Time unit multiplier for the floating rate reset frequency.

Type: **int**

Used in groups: **PaymentGrp**

### **180.2.3774 PaymentRateResetFrequencyUnit**

Time unit associated with the floating rate reset frequency.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **PaymentGrp**

### **180.2.3775 PaymentReceiveSide**

The side of the party receiving the payment.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **PaymentGrp**

#### **180.2.3776 PaymentRef**

"Settlement Payment Reference" - A free format Payment reference to assist with reconciliation, e.g. a Client and/or Order ID number.

Type: **String**

Used in groups: **SettlInstGrp**

#### **180.2.3777 PaymentRemitterID**

Identifies sender of a payment, e.g. the payment remitter or a customer reference number.

Type: **String**

Used in groups: **SettlInstGrp**

#### **180.2.3778 PaymentScheduleCurrency**

The currency for this step. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3779 PaymentScheduleEndDateUnadjusted**

The unadjusted end date of a cash flow payment.

Type: **LocalMktDate**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3780 PaymentScheduleFixedAmount**

The explicit payment amount for this step schedule.

Type: **Amt**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3781 PaymentScheduleFixedCurrency**

The currency of the fixed amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3782 PaymentScheduleFixingDateAdjusted**

The adjusted fixing date.

Type: **LocalMktDate**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3783 PaymentScheduleFixingDateBusinessCenter**

The business center calendar used to adjust the payment schedule's fixing date, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **PaymentScheduleFixingDateBusinessCenterGrp**

#### **180.2.3784 PaymentScheduleFixingDateBusinessCenterGrp**

**PaymentScheduleFixingDateBusinessCenterGrp** is a repeating subcomponent within the **PaymentScheduleGrp** component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the **DateAdjustment** component in **Instrument**.

Name	Mult.	Type	Description
NoPaymentScheduleFixingDateBusinessCenters	[1..1]	NumInGroup	
PaymentScheduleFixingDateBusinessCenter	[0..1]	String	Required if NoPaymentScheduleFixingDateBusinessCenters(40944) > 0.

Used in groups: **PaymentScheduleGrp**

### 180.2.3785 PaymentScheduleFixingDateBusinessDayConvention

The business day convention used to adjust the payment schedule's fixing date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: **PaymentScheduleGrp**

### 180.2.3786 PaymentScheduleFixingDateOffsetDayType

Specifies the day type of the relative fixing date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:



Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **PaymentScheduleGrp**

#### **180.2.3787 PaymentScheduleFixingDateOffsetPeriod**

Time unit multiplier for the relative fixing date offset.

Type: **int**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3788 PaymentScheduleFixingDateOffsetUnit**

Time unit associated with the relative fixing date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **PaymentScheduleGrp**

#### **180.2.3789 PaymentScheduleFixingDateRelativeTo**

Specifies the anchor date when the fixing date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3790 PaymentScheduleFixingDateUnadjusted**

The unadjusted fixing date.

Type: **LocalMktDate**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3791 PaymentScheduleFixingDayCount**

The number of days over which fixing should take place.

Type: **int**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3792 PaymentScheduleFixingDayDistribution**

The distribution of fixing days.

Type: **int**

Allowed values in PaymentStreamPricingDayDistributionCodeSet:

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
0	All	All
1	First	First
2	Last	Last
3	Penultimate	Penultimate

---

Used in groups: **PaymentScheduleGrp**

**180.2.3793 PaymentScheduleFixingDayGrp**

The PaymentScheduleFixingDayGrp is a repeating subcomponent of the PaymentScheduleGrp component used to detail periodic fixing days.

Name	Mult.	Type	Description
NoPaymentScheduleFixingDays	[1..1]	NumInGroup	
PaymentScheduleFixingDayOfWeek	[0..1]	CodeSet	Required if NoPaymentScheduleFixingDays(41161) > 0.
PaymentScheduleFixingDayNumber	[0..1]	int	

Used in groups: [PaymentScheduleGrp](#)

**180.2.3794 PaymentScheduleFixingDayNumber**

The occurrence of the day of week on which fixing takes place.

Type: [int](#)

Used in groups: [PaymentScheduleFixingDayGrp](#)

**180.2.3795 PaymentScheduleFixingDayOfWeek**

The day of the week on which fixing will take place.

Type: [int](#)

Allowed values in PaymentStreamPricingDayOfWeekCodeSet:

Code	Name	Description
0	EveryDay	Every day (the default if not specified)
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday

Used in groups: **PaymentScheduleFixingDayGrp**

#### **180.2.3796 PaymentScheduleFixingFirstObservationDateOffsetPeriod**

Time unit multiplier for the relative first observation date offset.

Type: **int**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3797 PaymentScheduleFixingFirstObservationDateOffsetUnit**

Time unit associated with the relative first observation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **PaymentScheduleGrp**

#### **180.2.3798 PaymentScheduleFixingLagPeriod**

Time unit multiplier for the fixing lag duration.

Type: **int**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3799 PaymentScheduleFixingLagUnit**

Time unit associated with the fixing lag duration.

Type: **String**

Allowed values in PaymentStreamInflationLagUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in groups: **PaymentScheduleGrp**

#### **180.2.3800 PaymentScheduleFixingTime**

The fixing time associated with the step schedule.

Type: **LocalMktTime**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3801 PaymentScheduleFixingTimeBusinessCenter**

Business center for determining fixing time.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3802 PaymentScheduleGrp**

The PaymentScheduleGrp is a repeating subcomponent of the StreamGrp component used to specify notional and rate steps of the payment stream.

Name	Mult.	Type	Description
<b>NoPaymentSchedules</b>	[1..1]	NumInGroup	
<b>PaymentScheduleType</b>	[0..1]	CodeSet	Required if NoPaymentSchedules(40828) > 0.
<b>PaymentScheduleXID</b>	[0..1]	XID	
<b>PaymentScheduleXIDRef</b>	[0..1]	XIDREF	
<b>PaymentScheduleStubType</b>	[0..1]	CodeSet	

Name	Mult.	Type	Description
PaymentScheduleStartDateUnadjusted	[0..1]	LocalMktDate	
PaymentScheduleEndDateUnadjusted	[0..1]	LocalMktDate	
PaymentSchedulePaySide	[0..1]	CodeSet	
PaymentScheduleReceiveSide	[0..1]	CodeSet	
PaymentScheduleNotional	[0..1]	Amt	
PaymentScheduleCurrency	[0..1]	Currency	
PaymentScheduleRate	[0..1]	Percentage	
PaymentScheduleRateMultiplier	[0..1]	float	
PaymentScheduleRateSpread	[0..1]	PriceOffset	
PaymentScheduleRateCurrency	[0..1]	Currency	
PaymentScheduleRateUnitOfMeasure	[0..1]	CodeSet	
PaymentScheduleRateConversionFactor	[0..1]	float	
PaymentScheduleRateSpreadType	[0..1]	CodeSet	
PaymentScheduleRateSpreadPositionType	[0..1]	CodeSet	
PaymentScheduleRateTreatment	[0..1]	CodeSet	
PaymentScheduleFixedAmount	[0..1]	Amt	
PaymentScheduleFixedCurrency	[0..1]	Currency	
PaymentScheduleSettlPeriodPrice	[0..1]	Price	
PaymentScheduleSettlPeriodPriceCurrency	[0..1]	Currency	
PaymentScheduleSettlPeriodPriceUnitOfMeasure	[0..1]	CodeSet	
PaymentScheduleStepUnitOfMeasure	[0..1]	CodeSet	
PaymentScheduleStepFrequencyPeriod	[0..1]	int	Conditionally required when PaymentScheduleStepFrequencyUnit(40845) is specified.
PaymentScheduleStepFrequencyUnit	[0..1]	CodeSet	Conditionally required when PaymentScheduleStepFrequencyPeriod(40844) is specified.
PaymentScheduleStepOffsetValue	[0..1]	Amt	
PaymentScheduleStepRate	[0..1]	Percentage	
PaymentScheduleStepOffsetRate	[0..1]	Percentage	
PaymentScheduleStepRelativeTo	[0..1]	CodeSet	

Name	Mult.	Type	Description
PaymentScheduleRateSourceGrp	[0..*]	Group	
PaymentScheduleFixingDateUnadjusted	[0..1]	LocalMktDate	
PaymentScheduleWeight	[0..1]	float	
PaymentScheduleFixingDateRelativeTo	[0..1]	int	
PaymentScheduleFixingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the payment schedule.
PaymentScheduleFixingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the payment schedule.
PaymentScheduleFixingDateOffsetPeriod	[0..1]	int	Conditionally required when PaymentScheduleFixingDateOffsetUnit(40856) is specified.
PaymentScheduleFixingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentScheduleFixingDateOffsetPeriod(40855) is specified.
PaymentScheduleFixingDateOffsetDayType	[0..1]	CodeSet	
PaymentScheduleFixingDayDistribution	[0..1]	CodeSet	
PaymentScheduleFixingDayCount	[0..1]	int	
PaymentScheduleFixingDateAdjusted	[0..1]	LocalMktDate	
PaymentScheduleFixingDayGrp	[0..*]	Group	
PaymentScheduleFixingLagPeriod	[0..1]	int	Conditionally required when PaymentScheduleFixingLagUnit(41177) is specified.
PaymentScheduleFixingLagUnit	[0..1]	CodeSet	Conditionally required when PaymentScheduleFixingLagPeriod(41176) is specified.
PaymentScheduleFixingFirstObservationDateOffsetPeriod	[0..1]	int	Conditionally required when PaymentScheduleFixingFirstObservationDateOffsetUnit(41179) is specified.
PaymentScheduleFixingFirstObservationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentScheduleFixingFirstObservationDateOffsetPeriod(41178) is specified.

Name	Mult.	Type	Description
PaymentScheduleFixingTime	[0..1]	LocalMktTime	
PaymentScheduleFixingTimeBusiness-Center	[0..1]	String	
PaymentScheduleInterimExchange-PaymentDateRelativeTo	[0..1]	int	
PaymentScheduleInterimExchange-DatesBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the payment schedule.
PaymentScheduleInterimExchange-DateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the payment schedule.
PaymentScheduleInterimExchange-DatesOffsetPeriod	[0..1]	int	Conditionally required when PaymentScheduleInterimExchangeDatesOffsetUnit(40865) is specified.
PaymentScheduleInterimExchange-DatesOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentScheduleInterimExchangeDatesOffsetPeriod(40864) is specified.
PaymentScheduleInterimExchange-DatesOffsetDayType	[0..1]	CodeSet	
PaymentScheduleInterimExchange-DateAdjusted	[0..1]	LocalMktDate	

Used in groups: **StreamGrp**

#### 180.2.3803 PaymentScheduleInterimExchangeDateAdjusted

The adjusted interim exchange date.

Type: **LocalMktDate**

Used in groups: **PaymentScheduleGrp**

#### 180.2.3804 PaymentScheduleInterimExchangeDateBusinessCenterGrp

PaymentScheduleInterimExchangeDateBusinessCenterGrp is a repeating subcomponent within the PaymentScheduleGrp component. It is used to specify the set of business centers whose calendars



drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoPaymentScheduleInterimExchange- DateBusinessCenters	[1..1]	NumInGroup	
PaymentScheduleInterimExchange- DatesBusinessCenter	[0..1]	String	Required if NoPaymentScheduleInterimExchange- DateBusinessCenters(40945) > 0.

Used in groups: **PaymentScheduleGrp**

#### 180.2.3805 PaymentScheduleInterimExchangeDatesBusinessCenter

The business center calendar used to adjust the payment schedule's interim exchange date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **PaymentScheduleInterimExchangeDateBusinessCenterGrp**

#### 180.2.3806 PaymentScheduleInterimExchangeDatesBusinessDayConvention

The business day convention used to adjust the payment schedule's interim exchange date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.

Code	Name	Description
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: **PaymentScheduleGrp**

#### **180.2.3807 PaymentScheduleInterimExchangeDatesOffsetDayType**

Specifies the day type of the relative interim exchange date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **PaymentScheduleGrp**

#### **180.2.3808 PaymentScheduleInterimExchangeDatesOffsetPeriod**

Time unit multiplier for the relative interim exchange date offset.

Type: **int**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3809 PaymentScheduleInterimExchangeDatesOffsetUnit**

Time unit associated with the relative interim exchange date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **PaymentScheduleGrp**

#### **180.2.3810 PaymentScheduleInterimExchangePaymentDateRelativeTo**

Specifies the anchor date when the interim exchange payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3811 PaymentScheduleNotional**

The notional value for this step, or amount of a cashflow payment.

Type: **Amt**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3812 PaymentSchedulePaySide**

The side of the party paying the step schedule.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **PaymentScheduleGrp**

**180.2.3813 PaymentScheduleRate**

The rate value for this step schedule.

Type: **Percentage**

Used in groups: **PaymentScheduleGrp**

**180.2.3814 PaymentScheduleRateConversionFactor**

The number to be multiplied by the derived floating rate of the payment schedule in order to arrive at the payment rate. If omitted, the schedule rate conversion factor is 1.

Type: **float**

Used in groups: **PaymentScheduleGrp**

**180.2.3815 PaymentScheduleRateCurrency**

The currency of the schedule rate. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **PaymentScheduleGrp**

**180.2.3816 PaymentScheduleRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: **float**

Used in groups: **PaymentScheduleGrp**

**180.2.3817 PaymentScheduleRateSource**

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: [PaymentScheduleRateSourceGrp](#)

### 180.2.3818 PaymentScheduleRateSourceGrp

PaymentScheduleRateSourceGrp is a repeating component within the PaymentScheduleGrp component used to identify primary and secondary rate sources.

Name	Mult.	Type	Description
<a href="#">NoPaymentScheduleRateSources</a>	[1..1]	NumInGroup	
<a href="#">PaymentScheduleRateSource</a>	[0..1]	CodeSet	Required if <a href="#">NoPaymentScheduleRateSources</a> (40868) > 0.
<a href="#">PaymentScheduleRateSourceType</a>	[0..1]	CodeSet	Required if <a href="#">NoPaymentScheduleRateSources</a> (40868) > 0.
<a href="#">PaymentScheduleReferencePage</a>	[0..1]	String	Conditionally required when <a href="#">PaymentScheduleRateSource</a> (40869) = 99 (Other)

Used in groups: [PaymentScheduleGrp](#)

### 180.2.3819 PaymentScheduleRateSourceType

Rate source type.

Type: [int](#)

Allowed values in RateSourceTypeCodeSet:

Code	Name	Description
0	Primary	Primary
1	Secondary	Secondary

Used in groups: [PaymentScheduleRateSourceGrp](#)

#### **180.2.3820 PaymentScheduleRateSpread**

The spread value for this step schedule.

Type: [PriceOffset](#)

Used in groups: [PaymentScheduleGrp](#)

#### **180.2.3821 PaymentScheduleRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: [int](#)

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in groups: [PaymentScheduleGrp](#)

#### **180.2.3822 PaymentScheduleRateSpreadType**

Identifies whether the rate spread is an absolute value to be added to the index rate or a percentage of the index rate.

Type: [int](#)

Allowed values in PaymentStreamRateSpreadTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in groups: **PaymentScheduleGrp**

### 180.2.3823 PaymentScheduleRateTreatment

Specifies the yield calculation treatment for the step schedule.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in groups: **PaymentScheduleGrp**

### 180.2.3824 PaymentScheduleRateUnitOfMeasure

The schedule rate unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels

Code	Name	Description
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters



Code	Name	Description
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot

Code	Name	Description
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: **PaymentScheduleGrp**

#### **180.2.3825 PaymentScheduleReceiveSide**

The side of the party receiving the stepf schedule.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **PaymentScheduleGrp**

#### **180.2.3826 PaymentScheduleReferencePage**

Identifies the reference “page” from the rate source.

For FX, the reference page to the spot rate to be used for the reference FX spot rate.

When RateSource(1446) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in groups: **PaymentScheduleRateSourceGrp**

**180.2.3827 PaymentScheduleSettlPeriodPrice**

The schedule settlement period price.

Type: **Price**

Used in groups: **PaymentScheduleGrp**

**180.2.3828 PaymentScheduleSettlPeriodPriceCurrency**

Specifies the currency of the schedule settlement period price. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **PaymentScheduleGrp**

**180.2.3829 PaymentScheduleSettlPeriodPriceUnitOfMeasure**

The settlement period price unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction

Code	Name	Description
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument

Code	Name	Description
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [PaymentScheduleGrp](#)

#### **180.2.3830 PaymentScheduleStartDateUnadjusted**

The date on which the value is adjusted, or calculated if a future value notional for certain non-deliverable interest rate swaps (e.g. Brazillian Real (BRL) vs. CETIP Interbank Deposit Rate (CDI)), or the start date of a cashflow payment.

Type: [LocalMktDate](#)

Used in groups: [PaymentScheduleGrp](#)

#### **180.2.3831 PaymentScheduleStepFrequencyPeriod**

Time unit multiplier for the step frequency.

Type: [int](#)

Used in groups: [PaymentScheduleGrp](#)

#### **180.2.3832 PaymentScheduleStepFrequencyUnit**

Time unit associated with the step frequency.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

---

Used in groups: [PaymentScheduleGrp](#)

**180.2.3833 PaymentScheduleStepOffsetRate**

The explicit amount that the rate changes on each step date. This can be a positive or negative value.

Type: **Percentage**

Used in groups: **PaymentScheduleGrp**

**180.2.3834 PaymentScheduleStepOffsetValue**

The explicit amount that the notional changes on each step date. This can be a positive or negative amount.

Type: **Amt**

Used in groups: **PaymentScheduleGrp**

**180.2.3835 PaymentScheduleStepRate**

The percentage by which the notional changes on each step date. The percentage is either a percentage applied to the initial notional amount or the previous outstanding notional, depending on the value specified in PaymentScheduleStepRelativeTo(40849). The percentage can be either positive or negative.

Type: **Percentage**

Used in groups: **PaymentScheduleGrp**

**180.2.3836 PaymentScheduleStepRelativeTo**

Specifies whether the PaymentScheduleStepRate(40847) or PaymentScheduleStepOffsetValue(40846) should be applied to the initial notional or the previous notional in order to calculate the notional step change amount.

Type: **int**

Allowed values in PaymentScheduleStepRelativeToCodeSet:

---

Code	Name	Description
0	Initial	Initial
1	Previous	Previous

---

Used in groups: **PaymentScheduleGrp**

**180.2.3837 PaymentScheduleStepUnitOfMeasure**

The schedule step unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams



Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: **PaymentScheduleGrp**

### 180.2.3838 **PaymentScheduleStubType**

Indicates to which stub this schedule applies.

Type: **int**

Allowed values in PaymentStubTypeCodeSet:

Code	Name	Description
0	Initial	Initial
1	Final	Final

Code	Name	Description
2	CompoundingInitial	Compounding initial
3	CompoundingFinal	Compounding final

Used in groups: **PaymentScheduleGrp**

### 180.2.3839 PaymentScheduleType

Type of schedule.

Type: **int**

Allowed values in PaymentScheduleTypeCodeSet:

Code	Name	Description
0	Notional	Notional
1	CashFlow	Cash flow
2	FXLinkedNotional	FX linked notional
3	FixedRate	Fixed rate
4	FutureValueNotional	Future value notional
5	KnownAmount	Known amount
6	FloatingRateMultiplier	Floating rate multiplier
7	Spread	Spread
8	CapRate	Cap rate
9	FloorRate	Floor rate
10	NonDeliverableSettlPaymentDates	Non-deliverable settlement payment dates
11	NonDeliverableSettlCalculation-Dates	Non-deliverable settlement calculation dates
12	NonDeliverableFXFixingDates	Non-deliverable fixing dates.
13	SettlPeriodNotnl	Settlement period notional
14	SettlPeriodPx	Settlement period price
15	CalcPeriod	Calculation period
16	DividendAccrualRateMultiplier	Dividend accrual rate multiplier
17	DividendAccrualRateSpread	Dividend accrual rate spread
18	DividendAccrualCapRate	Dividend accrual cap rate
19	DividendAccrualFloorRate	Dividend accrual floor rate

Code	Name	Description
20	CompoundingRateMultiplier	Compounding rate multiplier
21	CompoundingRateSpread	Compounding rate spread
22	CompoundingCapRate	Compounding cap rate
23	CompoundingFloorRate	Compounding floor rate

Used in groups: **PaymentScheduleGrp**

#### **180.2.3840 PaymentScheduleWeight**

Floating rate observation weight for cashflow payment.

Type: **float**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3841 PaymentScheduleXID**

Identifier of this PaymentSchedule for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3842 PaymentScheduleXIDRef**

Reference to payment schedule elsewhere in the message.

Type: **XIDREF**

Used in groups: **PaymentScheduleGrp**

#### **180.2.3843 PaymentSettlAmount**

The payment settlement amount.

Type: **Amt**

Used in groups: **PaymentSettlGrp**

**180.2.3844 PaymentSettlCurrency**

Specifies the currency the PaymentSettlAmount(40231) is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **PaymentSettlGrp**

**180.2.3845 PaymentSettlGrp**

The PaymentSettlGrp is a repeating subcomponent of the PaymentGrp component used to report payment settlement as a single or split payment.

Name	Mult.	Type	Description
NoPaymentSettls	[1..1]	NumInGroup	
PaymentSettlAmount	[0..1]	Amt	Required if NoPaymentSettls(40230) > 0.
PaymentSettlCurrency	[0..1]	Currency	
PaymentSettlParties	[0..*]	Group	

Used in groups: **PaymentGrp**

**180.2.3846 PaymentSettlParties**

PaymentSettlParties is a repeating subcomponent of the PaymentSettlGrp component used to report payment settlement routing.

Name	Mult.	Type	Description
NoPaymentSettlPartyIDs	[1..1]	NumInGroup	
PaymentSettlPartyID	[0..1]	String	Required if NoPaymentSettlPartyIDs(40233) > 0.
PaymentSettlPartyIDSource	[0..1]	CodeSet	Required if NoPaymentSettlPartyIDs(40233) > 0.
PaymentSettlPartyRole	[0..1]	CodeSet	Required if NoPaymentSettlPartyIDs(40233) > 0.
PaymentSettlPartyRoleQualifier	[0..1]	CodeSet	
PaymentSettlPtysSubGrp	[0..*]	Group	

Used in groups: **PaymentSettlGrp**

**180.2.3847 PaymentSettlPartyID**

The payment settlement party identifier.

Type: **String**

Used in groups: **PaymentSettlParties**

**180.2.3848 PaymentSettlPartyIDSource**

Identifies the class or source of PaymentSettlPartyID(40234) value (e.g. BIC).

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number

Code	Name	Description
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **PaymentSettlParties**

### 180.2.3849 PaymentSettlPartyRole

Identifies the role of PaymentSettlPartyID(40234) (e.g. the beneficiary's bank or depository institution).

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account



Code	Name	Description
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty

Code	Name	Description
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty

Code	Name	Description
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent

Code	Name	Description
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.

Code	Name	Description
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **PaymentSettlParties**

### 180.2.3850 PaymentSettlPartyRoleQualifier

Qualifies the value of PaymentSettlPartyRole(40236).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.

Code	Name	Description
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).

Code	Name	Description
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **PaymentSettlParties**

### **180.2.3851 PaymentSettlPartySubID**

Party sub-identifier, if applicable, for PaymentSettlPartyRole(40236).

Type: **String**

Used in groups: **PaymentSettlPtysSubGrp**

### **180.2.3852 PaymentSettlPartySubIDType**

The type of PaymentSettlPartySubID(40239) value.

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)

Code	Name	Description
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).



Code	Name	Description
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.

Code	Name	Description
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.

Code	Name	Description
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.

Code	Name	Description
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.

Code	Name	Description
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: [PaymentSettlPtysSubGrp](#)

### 180.2.3853 PaymentSettlPtysSubGrp

PaymentSettlSubParties is a repeating component within the PaymentSettlParties component used to extend information to be reported for the party.

Name	Mult.	Type	Description
<a href="#">NoPaymentSettlPartySubIDs</a>	[1..1]	NumInGroup	
<a href="#">PaymentSettlPartySubID</a>	[0..1]	String	Required if <a href="#">NoPaymentSettlPartySubIDs(40238)</a> > 0.
<a href="#">PaymentSettlPartySubIDType</a>	[0..1]	CodeSet	Required if <a href="#">NoPaymentSettlPartySubIDs(40238)</a> > 0.

Used in groups: [PaymentSettlParties](#)

### 180.2.3854 PaymentSettlStyle

Payment settlement style.

Type: [int](#)

Allowed values in [PaymentSettlStyleCodeSet](#):

Code	Name	Description
0	Standard	Standard
1	Net	Net

Code	Name	Description
2	StandardfNet	Standard and net

Used in groups: [PaymentGrp](#)

#### **180.2.3855 PaymentStreamAccrualDays**

The number of days from the adjusted calculation period start date to the adjusted value date, calculated in accordance with the applicable day count fraction.

Type: [int](#)

Used in components: [PaymentStream](#)

#### **180.2.3856 PaymentStreamAveragingMethod**

When rate averaging is applicable, used to specify whether a weighted or unweighted average calculation method is to be used.

Type: [int](#)

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.3857 PaymentStreamBoundsFirstDateUnadjusted**

The unadjusted first date of the compounding schedule. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in components: [PaymentStreamCompoundingDates](#)

**180.2.3858 PaymentStreamBoundsLastDateUnadjusted**

The unadjusted last date of the compounding schedule. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in components: **PaymentStreamCompoundingDates**

**180.2.3859 PaymentStreamCalculationLagPeriod**

Time unit multiplier for the calculation lag duration.

Type: **int**

Used in components: **PaymentStreamFloatingRate**

**180.2.3860 PaymentStreamCalculationLagUnit**

Time unit associated with the calculation lag duration.

Type: **String**

Allowed values in PaymentStreamInflationLagUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamFloatingRate**

**180.2.3861 PaymentStreamCapRate**

The cap rate, if any, which applies to the floating rate. The cap rate (strike) is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in components: **PaymentStreamFloatingRate**

**180.2.3862 PaymentStreamCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **PaymentStreamFloatingRate**

**180.2.3863 PaymentStreamCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **PaymentStreamFloatingRate**

**180.2.3864 PaymentStreamCashSettlIndicator**

Indicates whether cash settlement is applicable.

Type: **Boolean**

Used in components: **PaymentStream**



**180.2.3865 PaymentStream**

The PaymentStream component is a subcomponent of the Stream used to detail the attributes of a payment stream in a swap.

Name	Mult.	Type	Description
PaymentStreamType	[0..1]	CodeSet	
PaymentStreamMarketRate	[0..1]	int	
PaymentStreamDelayIndicator	[0..1]	Boolean	
PaymentStreamCashSettlIndicator	[0..1]	Boolean	
PaymentStreamSettlCurrency	[0..1]	Currency	
PaymentStreamDayCount	[0..1]	CodeSet	
PaymentStreamOtherDayCount	[0..1]	String	May be used to specify a count method not listed in PaymentStreamDayCount(40742).
PaymentStreamAccrualDays	[0..1]	int	
PaymentStreamDiscountType	[0..1]	CodeSet	
PaymentStreamDiscountRate	[0..1]	Percentage	
PaymentStreamDiscountRateDay-Count	[0..1]	CodeSet	
PaymentStreamCompoundingMethod	[0..1]	CodeSet	
PaymentStreamCompoundingXIDRef	[0..1]	XIDREF	Mutually exclusive with PaymentStreamCompoundingFixedRate(42605) or the PaymentStreamCompoundingFloatingRate component.
PaymentStreamCompoundingSpread	[0..1]	PriceOffset	
PaymentStreamInterpolationMethod	[0..1]	CodeSet	
PaymentStreamInterpolationPeriod	[0..1]	CodeSet	
PaymentStreamInitialPrincipalEx-changeIndicator	[0..1]	Boolean	
PaymentStreamInterimPrincipalEx-changeIndicator	[0..1]	Boolean	
PaymentStreamFinalPrincipalEx-changeIndicator	[0..1]	Boolean	
PaymentStreamFlatRateIndicator	[0..1]	Boolean	
PaymentStreamFlatRateAmount	[0..1]	Amt	
PaymentStreamFlatRateCurrency	[0..1]	Currency	
PaymentStreamMaximumPaymentA-mount	[0..1]	Amt	

Name	Mult.	Type	Description
PaymentStreamMaximumPaymentCurrency	[0..1]	Currency	
PaymentStreamMaximumTransactionAmount	[0..1]	Amt	
PaymentStreamMaximumTransactionCurrency	[0..1]	Currency	
PaymentStreamPaymentDates	[0..1]	Component	
PaymentStreamResetDates	[0..1]	Component	
PaymentStreamFixedRate	[0..1]	Component	
PaymentStreamFloatingRate	[0..1]	Component	
PaymentStreamCompoundingFixedRate	[0..1]	float	Mutually exclusive with PaymentStreamCompoundingXIDRef(42601) or the PaymentStreamCompoundingFloatingRate component.
PaymentStreamCompoundingFloatingRate	[0..1]	Component	Mutually exclusive with PaymentStreamCompoundingFixedRate(42605) or the PaymentStreamCompoundingXIDRef(42601).
PaymentStreamCompoundingDates	[0..1]	Component	
PaymentStreamNonDeliverableSettlementTerms	[0..1]	Component	

Used in groups: **StreamGrp**

### 180.2.3866 PaymentStreamCompoundingAveragingMethod

Specifies the averaging method when compounding floating rate averaging is applicable (e.g. weighted or unweighted).

Type: **int**

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3867 PaymentStreamCompoundingCapRate**

The cap rate, if any, which applies to the compounding floating rate. It is only required where the compounding floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3868 PaymentStreamCompoundingCapRateBuySide**

Reference to the buyer of the compounding cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3869 PaymentStreamCompoundingCapRateSellSide**

Reference to the seller of the compounding cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3870 PaymentStreamCompoundingDate**

The compounding date. The type of date is specified in PaymentStreamCompoundingDate-Type(42608).

Type: **LocalMktDate**

Used in groups: **PaymentStreamCompoundingDateGrp**

**180.2.3871 PaymentStreamCompoundingDateGrp**

PaymentStreamCompoundingDateGrp is a subcomponent of the PaymentStreamCompoundingDates component used to specify predetermined compounding dates.

Name	Mult.	Type	Description
<b>NoPaymentStreamCompoundingDates</b>	[1..1]	NumInGroup	
<b>PaymentStreamCompoundingDate</b>	[0..1]	LocalMktDate	Required if NoPaymentStreamCompoundingDates(42606) > 0.
<b>PaymentStreamCompoundingDate-Type</b>	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in components: **PaymentStreamCompoundingDates**

**180.2.3872 PaymentStreamCompoundingDatesBusinessCenter**

The business center calendar used for date adjustment of the payment stream compounding dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **PaymentStreamCompoundingDatesBusinessCenterGrp**

**180.2.3873 PaymentStreamCompoundingDatesBusinessCenterGrp**

PaymentStreamCompoundingDatesBusinessCenterGrp is a repeating subcomponent within the PaymentStreamCompoundingDates component. It is used to specify the set of business centers whose

calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoPaymentStreamCompounding-DatesBusinessCenters	[1..1]	NumInGroup	
PaymentStreamCompoundingDates-BusinessCenter	[0..1]	String	Required if NoPaymentStreamCompounding-DatesBusinessCenters(42620) > 0.

Used in components: **PaymentStreamCompoundingDates**

#### 180.2.3874 PaymentStreamCompoundingDatesBusinessDayConvention

The compounding dates business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **PaymentStreamCompoundingDates**

#### 180.2.3875 PaymentStreamCompoundingDates

PaymentStreamCompoundingDates is a subcomponent of the PaymentStream component used to specify the compounding dates of the stream - either specific, relative or periodic dates.

Name	Mult.	Type	Description
PaymentStreamCompoundingDates-BusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to payment stream compounding dates.
PaymentStreamCompoundingDates-BusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to payment stream compounding dates.
PaymentStreamCompoundingDateGrp	[0..*]	Group	
PaymentStreamCompoundingDates-RelativeTo	[0..1]	int	
PaymentStreamCompoundingDates-OffsetPeriod	[0..1]	int	Conditionally required when PaymentStream-CompoundingDatesOffsetUnit(42612) is specified.
PaymentStreamCompoundingDates-OffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentCompoundingDatesOffsetPeriod(42611) is specified.
PaymentStreamCompoundingDates-OffsetDayType	[0..1]	CodeSet	
PaymentStreamCompoundingPeriod-Skip	[0..1]	int	
PaymentStreamCompoundingStart-Date	[0..1]	Component	
PaymentStreamCompoundingEnd-Date	[0..1]	Component	
PaymentStreamCompoundingFrequencyPeriod	[0..1]	int	Conditionally required when PaymentStream-CompoundingFrequencyUnit(42616) is specified.
PaymentStreamCompoundingFrequencyUnit	[0..1]	CodeSet	Conditionally required when PaymentStream-CompoundingFrequencyPeriod(42615) is specified.
PaymentStreamCompoundingRoll-Convention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the payment stream compounding dates.
PaymentStreamBoundsFirstDateUnadjusted	[0..1]	LocalMktDate	
PaymentStreamBoundsLastDateUnadjusted	[0..1]	LocalMktDate	

Used in components: [PaymentStream](#)

### **180.2.3876 PaymentStreamCompoundingDatesOffsetDayType**

Specifies the day type of the relative compounding date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [PaymentStreamCompoundingDates](#)

### **180.2.3877 PaymentStreamCompoundingDatesOffsetPeriod**

Time unit multiplier for the relative compounding date offset.

Type: [int](#)

Used in components: [PaymentStreamCompoundingDates](#)

### **180.2.3878 PaymentStreamCompoundingDatesOffsetUnit**

Time unit associated with the relative compounding date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week

---

Code	Name	Description
------	------	-------------

---

Mo	Month	Month
----	-------	-------

Yr	Year	Year
----	------	------

---

Used in components: [PaymentStreamCompoundingDates](#)

#### **180.2.3879 PaymentStreamCompoundingDatesRelativeTo**

Specifies the anchor date when the compounding dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [PaymentStreamCompoundingDates](#)

#### **180.2.3880 PaymentStreamCompoundingDateType**

Specifies the type of payment compounding date (e.g. adjusted for holidays).

Type: [int](#)

Allowed values in NonDeliverableFixingDateTypeCodeSet:

---

Code	Name	Description
------	------	-------------

---

0	Unadjusted	Unadjusted
---	------------	------------

1	Adjusted	Adjusted
---	----------	----------

---

Used in groups: [PaymentStreamCompoundingDateGrp](#)

#### **180.2.3881 PaymentStreamCompoundingEndDateAdjusted**

The adjusted compounding end date.

Type: [LocalMktDate](#)

Used in components: [PaymentStreamCompoundingEndDate](#)



**180.2.3882 PaymentStreamCompoundingEndDate**

PaymentStreamCompoundingEndDate is a subcomponent of the PaymentStreamCompoundingDates component used to specify the end date for compounding.

Name	Mult.	Type	Description
PaymentStreamCompoundingEndDateUnadjusted	[0..1]	LocalMktDate	
PaymentStreamCompoundingEndDateRelativeTo	[0..1]	int	
PaymentStreamCompoundingEndDateOffsetPeriod	[0..1]	int	Conditionally required when PaymentStreamCompoundingEndDateOffsetUnit(42625) is specified.
PaymentStreamCompoundingEndDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamCompoundingEndDateOffsetPeriod(42624) is specified.
PaymentStreamCompoundingEndDateOffsetDayType	[0..1]	CodeSet	
PaymentStreamCompoundingEndDateAdjusted	[0..1]	LocalMktDate	

Used in components: [PaymentStreamCompoundingDates](#)

**180.2.3883 PaymentStreamCompoundingEndDateOffsetDayType**

Specifies the day type of the relative compounding end date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [PaymentStreamCompoundingEndDate](#)

**180.2.3884 PaymentStreamCompoundingEndDateOffsetPeriod**

Time unit multiplier for the relative compounding end date offset.

Type: **int**

Used in components: **PaymentStreamCompoundingEndDate**

**180.2.3885 PaymentStreamCompoundingEndDateOffsetUnit**

Time unit associated with the relative compounding end date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamCompoundingEndDate**

**180.2.3886 PaymentStreamCompoundingEndDateRelativeTo**

Specifies the anchor date when the compounding end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamCompoundingEndDate**

**180.2.3887 PaymentStreamCompoundingEndDateUnadjusted**

The unadjusted compounding end date.

Type: **LocalMktDate**

Used in components: **PaymentStreamCompoundingEndDate**

**180.2.3888 PaymentStreamCompoundingFinalRatePrecision**

Specifies the compounding floating rate rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3889 PaymentStreamCompoundingFinalRateRoundingDirection**

Specifies the rounding direction for the compounding floating rate.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3890 PaymentStreamCompoundingFixedRate**

The compounding fixed rate applicable to the payment stream.

Type: **float**

Used in components: **PaymentStream**

**180.2.3891 PaymentStreamCompoundingFloatingRate**

PaymentStreamCompoundingFloatingRate is a subcomponent of the PaymentStream component used to report the parameters for determining the compounding floating rate of the stream.

Name	Mult.	Type	Description
PaymentStreamCompoundingRateIndex	[0..1]	String	
PaymentStreamCompoundingRateIndexCurvePeriod	[0..1]	int	Conditionally required if PaymentStreamCompoundingRateIndexCurveUnit(42630) is specified.
PaymentStreamCompoundingRateIndexCurveUnit	[0..1]	CodeSet	Conditionally required if PaymentStreamCompoundingRateIndexCurvePeriod(42629) is specified.
PaymentStreamCompoundingRateMultiplier	[0..1]	float	
PaymentStreamCompoundingRateSpread	[0..1]	PriceOffset	
PaymentStreamCompoundingRateSpreadPositionType	[0..1]	CodeSet	
PaymentStreamCompoundingRateTreatment	[0..1]	CodeSet	
PaymentStreamCompoundingCapRate	[0..1]	Percentage	
PaymentStreamCompoundingCapRateBuySide	[0..1]	CodeSet	
PaymentStreamCompoundingCapRateSellSide	[0..1]	CodeSet	
PaymentStreamCompoundingFloorRate	[0..1]	Percentage	
PaymentStreamCompoundingFloorRateBuySide	[0..1]	CodeSet	
PaymentStreamCompoundingFloorRateSellSide	[0..1]	CodeSet	
PaymentStreamCompoundingInitialRate	[0..1]	Percentage	
PaymentStreamCompoundingFinalRateRoundingDirection	[0..1]	CodeSet	
PaymentStreamCompoundingFinalRatePrecision	[0..1]	int	
PaymentStreamCompoundingAveragingMethod	[0..1]	CodeSet	
PaymentStreamCompoundingNegativeRateTreatment	[0..1]	CodeSet	

Used in components: **PaymentStream**

**180.2.3892 PaymentStreamCompoundingFloorRate**

The floor rate, if any, which applies to the compounding floating rate. The floor rate (strike) is only required where the compounding floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate. The rate is expressed as a decimal, e.g. 5% is represented as "0.05".

Type: **Percentage**

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3893 PaymentStreamCompoundingFloorRateBuySide**

Reference to the buyer of the compounding floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3894 PaymentStreamCompoundingFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3895 PaymentStreamCompoundingFrequencyPeriod**

Time unit multiplier for the frequency at which compounding dates occur.

Type: **int**

Used in components: **PaymentStreamCompoundingDates**

**180.2.3896 PaymentStreamCompoundingFrequencyUnit**

Time unit associated with the frequency at which compounding dates occur.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: **PaymentStreamCompoundingDates**

**180.2.3897 PaymentStreamCompoundingInitialRate**

The initial compounding floating rate reset agreed between the principal parties involved in the trade. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. The initial rate is expressed in decimal form, e.g. 5% is represented as "0.05".

Type: **Percentage**

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3898 PaymentStreamCompoundingMethod**

Compounding method.

Type: **int**

Allowed values in PaymentStreamCompoundingMethodCodeSet:

Code	Name	Description
0	None	None
1	Flat	Flat
2	Straight	Straight
3	SpreadExclusive	Spread exclusive

Used in components: **PaymentStream**

**180.2.3899 PaymentStreamCompoundingNegativeRateTreatment**

Specifies the method for calculating payment obligations when a compounding floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3900 PaymentStreamCompoundingPeriodSkip**

The number of periods in the "RelativeTo" schedule that are between each date in the compounding schedule. A skip of 2 would mean that compounding dates are relative to every second date in the "RelativeTo" schedule. If present this should have a value greater than 1.

Type: **int**

Used in components: **PaymentStreamCompoundingDates**

**180.2.3901 PaymentStreamCompoundingRateIndex**

The payment stream's compounding floating rate index.

Type: **String**

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3902 PaymentStreamCompoundingRateIndexCurvePeriod**

Time unit multiplier for the payment stream's compounding floating rate index curve period.

Type: **int**

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3903 PaymentStreamCompoundingRateIndexCurveUnit**

Time unit associated with the payment stream's compounding floating rate index curve period.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3904 PaymentStreamCompoundingRateMultiplier**

A rate multiplier to apply to the compounding floating rate. The multiplier can be less than or greater than 1 (one). This should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: **float**

Used in components: **PaymentStreamCompoundingFloatingRate**



**180.2.3905 PaymentStreamCompoundingRateSpread**

The basis points spread from the index specified in PaymentStreamCompoundingRateIndex(42628).

Type: **PriceOffset**

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3906 PaymentStreamCompoundingRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3907 PaymentStreamCompoundingRateTreatment**

Specifies the yield calculation treatment for the index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: **PaymentStreamCompoundingFloatingRate**

**180.2.3908 PaymentStreamCompoundingRollConvention**

The convention for determining the sequence of compounding dates. It is used in conjunction with a specified frequency.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighDa28y	28th day of the month

Code	Name	Description
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [PaymentStreamCompoundingDates](#)

### **180.2.3909 PaymentStreamCompoundingSpread**

The spread to be used for compounding. Used in scenarios where the interest payment is based on a compounding formula that uses a compounding spread in addition to the regular spread.

Type: [PriceOffset](#)

Used in components: [PaymentStream](#)

**180.2.3910 PaymentStreamCompoundingStartDateAdjusted**

The adjusted compounding start date.

Type: [LocalMktDate](#)

Used in components: [PaymentStreamCompoundingStartDate](#)

**180.2.3911 PaymentStreamCompoundingStartDate**

PaymentStreamCompoundingStartDate is a subcomponent of the PaymentStreamCompoundingDates component used to specify the start date for compounding.

Name	Mult.	Type	Description
<a href="#">PaymentStreamCompoundingStartDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">PaymentStreamCompoundingStartDateRelativeTo</a>	[0..1]	int	
<a href="#">PaymentStreamCompoundingStartDateOffsetPeriod</a>	[0..1]	int	Conditionally required when PaymentStreamCompoundingStartDateOffsetUnit(42649) is specified.
<a href="#">PaymentStreamCompoundingStartDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when PaymentStreamCompoundingStartDateOffsetPeriod(42648) is specified.
<a href="#">PaymentStreamCompoundingStartDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">PaymentStreamCompoundingStartDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [PaymentStreamCompoundingDates](#)

**180.2.3912 PaymentStreamCompoundingStartDateOffsetDayType**

Specifies the day type of the relative compounding start date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [PaymentStreamCompoundingStartDate](#)

#### **180.2.3913 PaymentStreamCompoundingStartDateOffsetPeriod**

Time unit multiplier for the relative compounding start date offset.

Type: [int](#)

Used in components: [PaymentStreamCompoundingStartDate](#)

#### **180.2.3914 PaymentStreamCompoundingStartDateOffsetUnit**

Time unit associated with the relative compounding start date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [PaymentStreamCompoundingStartDate](#)

#### **180.2.3915 PaymentStreamCompoundingStartDateRelativeTo**

Specifies the anchor date when the compounding start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamCompoundingStartDate**

#### **180.2.3916 PaymentStreamCompoundingStartDateUnadjusted**

The unadjusted compounding start date.

Type: **LocalMktDate**

Used in components: **PaymentStreamCompoundingStartDate**

#### **180.2.3917 PaymentStreamCompoundingXIDRef**

Reference to the stream which details the compounding fixed or floating rate.

Type: **XIDREF**

Used in components: **PaymentStream**

#### **180.2.3918 PaymentStreamContractPrice**

The price per relevant unit for purposes of the calculation of a fixed amount for a dry voyage charter or time charter commodity swap.

Type: **Price**

Used in components: **PaymentStreamFixedRate**

#### **180.2.3919 PaymentStreamContractPriceCurrency**

Specifies the currency of PaymentStreamContractPrice(41190). Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **PaymentStreamFixedRate**

**180.2.3920 PaymentStreamDayCount**

The day count convention used in the payment stream calculations.

Type: **int**

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.

Code	Name	Description
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.



Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: **PaymentStream**

### 180.2.3921 **PaymentStreamDaysAdjustmentIndicator**

Indicates whether the contract specifies that the notional should be scaled by the number of days in range divided by the estimate trading days or not. The number of "days in range" refers to the number of returns that contribute to the realized volatility.

Type: **Boolean**

Used in components: **PaymentStreamFloatingRate**

#### **180.2.3922 PaymentStreamDelayIndicator**

Applicable to credit default swaps on mortgage backed securities to specify whether payment delays are applicable to the fixed amount.

Residential mortgage backed securities typically have a payment delay of 5 days between the coupon date of the reference obligation and the payment date of the synthetic swap.

Commercial mortgage backed securities do not typically have a payment delay, with both payment dates (the coupon date of the reference obligation and the payment date of the synthetic swap) being on the 25th of each month.

Type: **Boolean**

Used in components: **PaymentStream**

#### **180.2.3923 PaymentStreamDiscountRate**

Discount rate. The rate is expressed in decimal, e.g. 5% is expressed as 0.05.

Type: **Percentage**

Used in components: **PaymentStream**

#### **180.2.3924 PaymentStreamDiscountRateDayCount**

The day count convention applied to the PaymentStreamDiscountRate(40745).

Type: **int**

Allowed values in CouponDayCountCodeSet:

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).

---

Code	Name	Description
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.

Code	Name	Description
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.

Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: **PaymentStream**

### **180.2.3925 PaymentStreamDiscountType**

The method of calculating discounted payment amounts

Type: **int**

Allowed values in PaymentStreamDiscountTypeCodeSet:

Code	Name	Description
0	Standard	Standard
1	FRA	Forward Rate Agreement (FRA)

Used in components: [PaymentStream](#)

### 180.2.3926 PaymentStreamFinalPricePaymentDateAdjusted

The adjusted final price payment date.

Type: [LocalMktDate](#)

Used in components: [PaymentStreamFinalPricePaymentDate](#)

### 180.2.3927 PaymentStreamFinalPricePaymentDate

PaymentStreamFinalPricePaymentDate is a subcomponent of the PaymentStreamPaymentDates component used to specify the final price payment date, e.g. for an equity return swap.

Name	Mult.	Type	Description
<a href="#">PaymentStreamFinalPricePaymentDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">PaymentStreamFinalPricePaymentDateRelativeTo</a>	[0..1]	int	
<a href="#">PaymentStreamFinalPricePaymentDateOffsetPeriod</a>	[0..1]	int	Conditionally required when PaymentStreamFinalPricePaymentDateOffsetUnit(42657) is specified.
<a href="#">PaymentStreamFinalPricePaymentDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when PaymentStreamFinalPricePaymentDateOffsetPeriod(42656) is specified.
<a href="#">PaymentStreamFinalPricePaymentDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">PaymentStreamFinalPricePaymentDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [PaymentStreamPaymentDates](#)

**180.2.3928 PaymentStreamFinalPricePaymentDateOffsetDayType**

Specifies the day type of the relative final price payment date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStreamFinalPricePaymentDate**

**180.2.3929 PaymentStreamFinalPricePaymentDateOffsetPeriod**

Time unit multiplier for the relative final price payment date offset.

Type: **int**

Used in components: **PaymentStreamFinalPricePaymentDate**

**180.2.3930 PaymentStreamFinalPricePaymentDateOffsetUnit**

Time unit associated with the relative final price payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamFinalPricePaymentDate**

**180.2.3931 PaymentStreamFinalPricePaymentDateRelativeTo**

Specifies the anchor date when the final price payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamFinalPricePaymentDate**

**180.2.3932 PaymentStreamFinalPricePaymentDateUnadjusted**

The unadjusted final price payment date.

Type: **LocalMktDate**

Used in components: **PaymentStreamFinalPricePaymentDate**

**180.2.3933 PaymentStreamFinalPrincipalExchangeIndicator**

Indicates whether there is a final exchange of principal on the termination date.

Type: **Boolean**

Used in components: **PaymentStream**

**180.2.3934 PaymentStreamFinalRate**

The floating rate determined at the final reset. The rate is expressed in decimal form, e.g. 5% is represented as 0.05.

Type: **Percentage**

Used in components: **PaymentStreamFloatingRate**

**180.2.3935 PaymentStreamFinalRatePrecision**

Specifies the rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **PaymentStreamFloatingRate**



**180.2.3936 PaymentStreamFinalRateRoundingDirection**

Specifies the rounding direction.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **PaymentStreamFloatingRate**

**180.2.3937 PaymentStreamFirstObservationDateAdjusted**

The adjusted initial price observation date.

Type: **LocalMktDate**

Used in components: **PaymentStreamFloatingRate**

**180.2.3938 PaymentStreamFirstObservationDateOffsetDayType**

Specifies the day type of the initial price observation date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStreamFloatingRate**

**180.2.3939 PaymentStreamFirstObservationDateOffsetPeriod**

Time unit multiplier for the relative first observation date offset.

Type: **int**

Used in components: **PaymentStreamFloatingRate**

**180.2.3940 PaymentStreamFirstObservationDateOffsetUnit**

Time unit associated with the relative first observation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamFloatingRate**

**180.2.3941 PaymentStreamFirstObservationDateRelativeTo**

Specifies the anchor date when the initial price observation date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamFloatingRate**

**180.2.3942 PaymentStreamFirstObservationDateUnadjusted**

The unadjusted initial price observation date.

Type: **LocalMktDate**

Used in components: **PaymentStreamFloatingRate**

**180.2.3943 PaymentStreamFirstPaymentDateUnadjusted**

The unadjusted first payment date.

Type: **LocalMktDate**

Used in components: **PaymentStreamPaymentDates**

**180.2.3944 PaymentStreamFixedAmount**

The payment stream's fixed payment amount. In CDS an alternative to PaymentStreamRate(40784).

Type: **Amt**

Used in components: **PaymentStreamFixedRate**

**180.2.3945 PaymentStreamFixedAmountUnitOfMeasure**

Specifies the fixed payment amount unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction

Code	Name	Description
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument

Code	Name	Description
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [PaymentStreamFixedRate](#)

### 180.2.3946 [PaymentStreamFixedRate](#)

[PaymentStreamFixedRate](#) is a subcomponent of the [PaymentStream](#) component used to report the fixed rate or fixed payment amount of the stream.

Name	Mult.	Type	Description
<a href="#">PaymentStreamRate</a>	[0..1]	Percentage	Mutually exclusive with <a href="#">PaymentStreamFixedAmount</a> (40785).
<a href="#">PaymentStreamFixedAmount</a>	[0..1]	Amt	Mutually exclusive with <a href="#">PaymentStreamRate</a> (40784).
<a href="#">PaymentStreamRateOrAmountCurrency</a>	[0..1]	Currency	
<a href="#">PaymentStreamFixedAmountUnitOfMeasure</a>	[0..1]	CodeSet	
<a href="#">PaymentStreamTotalFixedAmount</a>	[0..1]	Amt	
<a href="#">PaymentStreamFutureValueNotional</a>	[0..1]	Amt	
<a href="#">PaymentStreamFutureValueDateAdjusted</a>	[0..1]	LocalMktDate	
<a href="#">PaymentStreamWorldScaleRate</a>	[0..1]	float	
<a href="#">PaymentStreamContractPrice</a>	[0..1]	Price	
<a href="#">PaymentStreamContractPriceCurrency</a>	[0..1]	Currency	

Used in components: [PaymentStream](#)

### 180.2.3947 [PaymentStreamFixingDate](#)

The fixing date. The type of date is specified in [PaymentStreamFixingDateType](#)(42662).

Type: [LocalMktDate](#)

Used in groups: [PaymentStreamFixingDateGrp](#)

### 180.2.3948 [PaymentStreamFixingDateAdjusted](#)

The adjusted fixing date.

Type: [LocalMktDate](#)

Used in components: [PaymentStreamResetDates](#)

### **180.2.3949 PaymentStreamFixingDateBusinessCenter**

The business center calendar used to adjust the payment stream's fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [PaymentStreamFixingDateBusinessCenterGrp](#)

### **180.2.3950 PaymentStreamFixingDateBusinessCenterGrp**

[PaymentStreamFixingDateBusinessCenterGrp](#) is a repeating subcomponent within the [PaymentStreamResetDates](#) component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the [DateAdjustment](#) component in [Instrument](#).

Name	Mult.	Type	Description
<a href="#">NoPaymentStreamFixingDateBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">PaymentStreamFixingDateBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoPaymentStreamFixingDateBusinessCenters</a> (40950) > 0.

Used in components: [PaymentStreamResetDates](#)

### **180.2.3951 PaymentStreamFixingDateBusinessDayConvention**

The business day convention used to adjust the payment stream's fixing date. Used only to override the business day convention specified in the [DateAdjustment](#) component within the [Instrument](#) component.

Type: [int](#)

Allowed values in [BusinessDayConventionCodeSet](#):

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.

Code	Name	Description
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [PaymentStreamResetDates](#)

### 180.2.3952 PaymentStreamFixingDateGrp

PaymentStreamFixingDateGrp is a subcomponent of the PaymentStreamResetDates component used to specify predetermined fixing dates.

Name	Mult.	Type	Description
<a href="#">NoPaymentStreamFixingDates</a>	[1..1]	NumInGroup	
<a href="#">PaymentStreamFixingDate</a>	[0..1]	LocalMktDate	Required if NoPaymentStreamFixingDates(42660) > 0.
<a href="#">PaymentStreamFixingDateType</a>	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in components: [PaymentStreamResetDates](#)

### 180.2.3953 PaymentStreamFixingDateOffsetDayType

Specifies the day type of the relative fixing date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:



Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [PaymentStreamResetDates](#)

#### **180.2.3954 PaymentStreamFixingDateOffsetPeriod**

Time unit multiplier for the relative fixing date offset.

Type: [int](#)

Used in components: [PaymentStreamResetDates](#)

#### **180.2.3955 PaymentStreamFixingDateOffsetUnit**

Time unit associated with the relative fixing date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [PaymentStreamResetDates](#)

#### **180.2.3956 PaymentStreamFixingDateRelativeTo**

Specifies the anchor date when the fixing date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamResetDates**

### **180.2.3957 PaymentStreamFixingDateType**

Specifies the type of fixing date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **PaymentStreamFixingDateGrp**

### **180.2.3958 PaymentStreamFlatRateAmount**

Specifies the actual monetary value of the flat rate when PaymentStreamFlatRateIndicator(41180) = 'Y'.

Type: **Amt**

Used in components: **PaymentStream**

### **180.2.3959 PaymentStreamFlatRateCurrency**

Specifies the currency of the actual flat rate. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **PaymentStream**

### **180.2.3960 PaymentStreamFlatRateIndicator**

When this element is specified and set to 'Y', the Flat Rate is the New Worldwide Tanker Nominal Freight Scale for the Freight Index Route taken at the Trade Date of the transaction "Fixed". If 'N' it is taken on each Pricing Date "Floating".

Type: **Boolean**

Used in components: **PaymentStream**

### **180.2.3961 PaymentStreamFloatingRate**

PaymentStreamFloatingRate is a subcomponent of the PaymentStream component used to report the floating rate attributes of the stream.

<b>Name</b>	<b>Mult.</b>	<b>Type</b>	<b>Description</b>
PaymentStreamRateIndex	[0..1]	String	
PaymentStreamRateIndexSource	[0..1]	CodeSet	
PaymentStreamRateIndexID	[0..1]	String	Conditionally required when PaymentStreamRateIndexIDSource(43091) is specified.
PaymentStreamRateIndexIDSource	[0..1]	CodeSet	Conditionally required when PaymentStreamRateIndexID(43090) is specified.
PaymentStreamRateIndexCurveUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamRateIndexCurvePeriod(40792) is specified.
PaymentStreamRateIndexCurvePeriod	[0..1]	int	Conditionally required when PaymentStreamRateIndexCurveUnit(40791) is specified.
PaymentStreamRateIndex2	[0..1]	String	
PaymentStreamRateIndex2Source	[0..1]	CodeSet	
PaymentStreamRateIndex2ID	[0..1]	String	Conditionally required when PaymentStreamRateIndex2IDSource(43115) is specified.
PaymentStreamRateIndex2IDSource	[0..1]	CodeSet	Conditionally required when PaymentStreamRateIndex2ID(43114) is specified.
PaymentStreamRateIndex2CurvePeriod	[0..1]	int	Conditionally required when PaymentStreamRateIndex2CurveUnit(41195) is specified.
PaymentStreamRateIndex2CurveUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamRateIndex2CurvePeriod(41194) is specified.
PaymentStreamRateIndexLocation	[0..1]	String	
PaymentStreamRateIndexLevel	[0..1]	Qty	
PaymentStreamRateIndexUnitOfMeasure	[0..1]	CodeSet	

Name	Mult.	Type	Description
PaymentStreamSettlLevel	[0..1]	CodeSet	
PaymentStreamReferenceLevel	[0..1]	Qty	
PaymentStreamReferenceLevelUnitOfMeasure	[0..1]	CodeSet	
PaymentStreamReferenceLevelEqualsZeroIndicator	[0..1]	Boolean	
PaymentStreamRateMultiplier	[0..1]	float	
PaymentStreamRateSpread	[0..1]	PriceOffset	
PaymentStreamRateSpreadCurrency	[0..1]	Currency	
PaymentStreamRateSpreadUnitOfMeasure	[0..1]	CodeSet	
PaymentStreamRateConversionFactor	[0..1]	float	
PaymentStreamRateSpreadType	[0..1]	CodeSet	
PaymentStreamRateSpreadPositionType	[0..1]	CodeSet	
PaymentStreamRateTreatment	[0..1]	CodeSet	
PaymentStreamCapRate	[0..1]	Percentage	
PaymentStreamCapRateBuySide	[0..1]	CodeSet	
PaymentStreamCapRateSellSide	[0..1]	CodeSet	
PaymentStreamFloorRate	[0..1]	Percentage	
PaymentStreamFloorRateBuySide	[0..1]	CodeSet	
PaymentStreamFloorRateSellSide	[0..1]	CodeSet	
PaymentStreamInitialRate	[0..1]	Percentage	
PaymentStreamLastResetRate	[0..1]	Percentage	
PaymentStreamFinalRate	[0..1]	Percentage	
PaymentStreamFinalRateRoundingDirection	[0..1]	CodeSet	
PaymentStreamFinalRatePrecision	[0..1]	int	
PaymentStreamAveragingMethod	[0..1]	CodeSet	
PaymentStreamNegativeRateTreatment	[0..1]	CodeSet	
PaymentStreamCalculationLagPeriod	[0..1]	int	Conditionally required when PaymentStreamCalculationLagUnit(41210) is specified.
PaymentStreamCalculationLagUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamCalculationLagPeriod(41209) is specified.

Name	Mult.	Type	Description
PaymentStreamFirstObservationDate-Unadjusted	[0..1]	LocalMktDate	
PaymentStreamFirstObservationDateRelativeTo	[0..1]	int	
PaymentStreamFirstObservationDateOffsetDayType	[0..1]	CodeSet	
PaymentStreamFirstObservationDateOffsetPeriod	[0..1]	int	Conditionally required when PaymentStreamFirstObservationOffsetUnit(41212) is specified.
PaymentStreamFirstObservationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamFirstObservationOffsetPeriod(41211) is specified.
PaymentStreamFirstObservationDateAdjusted	[0..1]	LocalMktDate	
PaymentStreamPricingDayType	[0..1]	CodeSet	
PaymentStreamPricingDayDistribution	[0..1]	CodeSet	
PaymentStreamPricingDayCount	[0..1]	int	
PaymentStreamPricingBusinessCalendar	[0..1]	String	
PaymentStreamPricingBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of pricing dates.
PaymentStreamPricingBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of pricing dates.
PaymentStreamPricingDayGrp	[0..*]	Group	
PaymentStreamPricingDateGrp	[0..*]	Group	
PaymentStreamInflationLagPeriod	[0..1]	int	Conditionally required when PaymentStreamInflationLagUnit(40809) is specified.
PaymentStreamInflationLagUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamInflationLagPeriod(40808) is specified.
PaymentStreamInflationLagDayType	[0..1]	CodeSet	
PaymentStreamInflationInterpolationMethod	[0..1]	CodeSet	
PaymentStreamInflationIndexSource	[0..1]	CodeSet	
PaymentStreamInflationPublicationSource	[0..1]	String	

Name	Mult.	Type	Description
PaymentStreamInflationInitialIndexLevel	[0..1]	float	
PaymentStreamInflationFallbackBondApplicable	[0..1]	Boolean	
PaymentStreamFRADiscounting	[0..1]	CodeSet	
PaymentStreamUnderlierRefID	[0..1]	String	
PaymentStreamFormula	[0..1]	Component	
DividendConditions	[0..1]	Component	
ReturnRateNotionalReset	[0..1]	Boolean	
ReturnRateGrp	[0..*]	Group	
PaymentStreamLinkInitialLevel	[0..1]	Price	
PaymentStreamLinkClosingLevelIndicator	[0..1]	Boolean	
PaymentStreamLinkExpiringLevelIndicator	[0..1]	Boolean	
PaymentStreamLinkEstimatedTradingDays	[0..1]	int	
PaymentStreamLinkStrikePrice	[0..1]	Price	
PaymentStreamLinkStrikePriceType	[0..1]	CodeSet	
PaymentStreamLinkMaximumBoundary	[0..1]	float	
PaymentStreamLinkMinimumBoundary	[0..1]	float	
PaymentStreamLinkNumberOfDataSeries	[0..1]	int	
PaymentStreamVarianceUnadjustedCap	[0..1]	float	
PaymentStreamRealizedVarianceMethod	[0..1]	CodeSet	
PaymentStreamDaysAdjustmentIndicator	[0..1]	Boolean	
PaymentStreamNearestExchangeContractRefID	[0..1]	String	
PaymentStreamVegaNotionalAmount	[0..1]	float	

Used in components: **PaymentStream**

**180.2.3962 PaymentStreamFloorRate**

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A floor rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in components: **PaymentStreamFloatingRate**

**180.2.3963 PaymentStreamFloorRateBuySide**

Reference to the buyer of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **PaymentStreamFloatingRate**

**180.2.3964 PaymentStreamFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **PaymentStreamFloatingRate**

**180.2.3965 PaymentStreamFormula**

Contains an XML representation of the formula. Defined for flexibility in choice of language (MathML, OpenMath or text).

Type: **XMLData**

Used in groups: **PaymentStreamFormulaMathGrp**

**180.2.3966 PaymentStreamFormula**

PaymentStreamFormula is a subcomponent of the PaymentStreamFloatingRate component used to report the parameters for determining the floating rate of the stream e.g. for equity swaps.

Name	Mult.	Type	Description
<b>PaymentStreamFormulaCurrency</b>	[0..1]	Currency	
<b>PaymentStreamFormulaCurrencyDe-terminationMethod</b>	[0..1]	String	
<b>PaymentStreamFormulaRefer-enceAmount</b>	[0..1]	int	
<b>PaymentStreamFormulaMathGrp</b>	[0..*]	Group	
<b>PaymentStreamFormulaImage</b>	[0..1]	Component	

Used in components: **PaymentStreamFloatingRate**

**180.2.3967 PaymentStreamFormulaCurrency**

The currency in which the formula amount is denominated. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **PaymentStreamFormula**

**180.2.3968 PaymentStreamFormulaCurrencyDeterminationMethod**

Specifies the method according to which the formula amount currency is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in components: **PaymentStreamFormula**



**180.2.3969 PaymentStreamFormulaDesc**

A description of the math formula in PaymentStreamFormula(42684).

Type: **String**

Used in groups: **PaymentStreamFormulaMathGrp**

**180.2.3970 PaymentStreamFormulImage**

Image of the formula image when represented through an encoded clip in base64Binary.

Type: **data**

Used in components: **PaymentStreamFormulImage**

**180.2.3971 PaymentStreamFormulImage**

PaymentStreamFormulImage is a subcomponent of the PaymentStreamFormula component used to include a base64Binary-encoded image clip of the formula.

Name	Mult.	Type	Description
<b>PaymentStreamFormulImageLength</b>	[0..1]	Length	Conditionally required when PaymentStreamFormulImage(42653) is specified.
<b>PaymentStreamFormulImage</b>	[0..1]	data	Conditionally required when PaymentStreamFormulImageLength(42652) is specified.

Used in components: **PaymentStreamFormula**

**180.2.3972 PaymentStreamFormulImageLength**

Length in bytes of the PaymentStreamFormulImage(42563) field.

Type: **Length**

Used in components: **PaymentStreamFormulImage**

**180.2.3973 PaymentStreamFormulaLength**

Byte length of encoded (non-ASCII characters) PaymentStreamFormula(42648) field.

Type: **Length**

Used in groups: **PaymentStreamFormulaMathGrp**

**180.2.3974 PaymentStreamFormulaMathGrp**

PaymentStreamFormulaMathGrp is a repeating subcomponent within the PaymentStreamFormula component. It is used to specify the set of formulas, sub-formulas and descriptions from which the rate is derived.

Name	Mult.	Type	Description
NoPaymentStreamFormulas	[1..1]	NumInGroup	
PaymentStreamFormulaLength	[0..1]	Length	Required if NoPaymentStreamFormulas(42683) > 0.
PaymentStreamFormula	[0..1]	XMLData	Required if NoPaymentStreamFormulas(42683) > 0.
PaymentStreamFormulaDesc	[0..1]	String	

Used in components: **PaymentStreamFormula**

**180.2.3975 PaymentStreamFormulaReferenceAmount**

Specifies the reference amount when this term either corresponds to the standard ISDA Definition (either the 2002 Equity Definition for the Equity Amount, or the 2000 Definition for the Interest Amount), or refers to a term defined elsewhere in the swap document.

See [http://www.fixtradingcommunity.org/codelists#Payment\\_Amount\\_Relative\\_To](http://www.fixtradingcommunity.org/codelists#Payment_Amount_Relative_To) for code list of reference amounts.

Type: **int**

Used in components: **PaymentStreamFormula**

**180.2.3976 PaymentStreamFRADiscounting**

The method of Forward Rate Agreement (FRA) discounting, if any, that will apply.

Type: **int**

Allowed values in PaymentStreamFRADiscountingCodeSet:

Code	Name	Description
0	None	None
1	ISDA	International Swaps and Derivatives Association (ISDA)
2	AFMA	Australian Financial Markets Association (AFMA)

Used in components: **PaymentStreamFloatingRate**

#### **180.2.3977 PaymentStreamFutureValueDateAdjusted**

The adjusted value date of the future value amount.

Type: **LocalMktDate**

Used in components: **PaymentStreamFixedRate**

#### **180.2.3978 PaymentStreamFutureValueNotional**

The future value notional is normally only required for certain non-deliverable interest rate swaps (e.g. Brazilian Real (BRL) vs. CETIP Interbank Deposit Rate (CDI)). The value is calculated as follows:  $\text{Future Value Notional} = \text{Notional Amount} * (1 + \text{Fixed Rate}) ^ (\text{Fixed Rate Day Count Fraction})$ . The currency is the same as the stream notional.

Type: **Amt**

Used in components: **PaymentStreamFixedRate**

#### **180.2.3979 PaymentStreamInflationFallbackBondApplicable**

Indicates whether a fallback bond as defined in the 2006 ISDA Inflation Derivatives Definitions, sections 1.3 and 1.8, is applicable or not. If not specified, the default value is "Y" (True/Yes).

Type: **Boolean**

Used in components: **PaymentStreamFloatingRate**

**180.2.3980 PaymentStreamInflationIndexSource**

The inflation index reference source.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: **PaymentStreamFloatingRate**

**180.2.3981 PaymentStreamInflationInitialIndexLevel**

Initial known index level for the first calculation period.

Type: **float**

Used in components: **PaymentStreamFloatingRate**

**180.2.3982 PaymentStreamInflationInterpolationMethod**

The method used when calculating the Inflation Index Level from multiple points - the most common is Linear.

Type: **int**

Allowed values in PaymentStreamInflationInterpolationMethodCodeSet:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: **PaymentStreamFloatingRate**

**180.2.3983 PaymentStreamInflationLagDayType**

The inflation lag period day type.

Type: **int**

Allowed values in PaymentStreamInflationLagDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStreamFloatingRate**

**180.2.3984 PaymentStreamInflationLagPeriod**

Time unit multiplier for the inflation lag period. The lag period is the offsetting period from the payment date which determines the reference period for which the inflation index is observed.

Type: **int**

Used in components: **PaymentStreamFloatingRate**

**180.2.3985 PaymentStreamInflationLagUnit**

Time unit associated with the inflation lag period.

Type: **String**

Allowed values in PaymentStreamInflationLagUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month

Code	Name	Description
Yr	Year	Year

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.3986 PaymentStreamInflationPublicationSource**

The current main publication source such as relevant web site or a government body.

Type: [String](#)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.3987 PaymentStreamInitialFixingDateAdjusted**

The adjusted initial fixing date.

Type: [LocalMktDate](#)

Used in components: [PaymentStreamResetDates](#)

#### **180.2.3988 PaymentStreamInitialFixingDateBusinessCenter**

The business center calendar used to adjust the payment stream's initial fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [PaymentStreamInitialFixingDateBusinessCenterGrp](#)

#### **180.2.3989 PaymentStreamInitialFixingDateBusinessCenterGrp**

[PaymentStreamInitialFixingDateBusinessCenterGrp](#) is a repeating subcomponent within the [PaymentStreamResetDates](#) component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the [DateAdjustment](#) component in [Instrument](#).

Name	Mult.	Type	Description
NoPaymentStreamInitialFixingDate-BusinessCenters	[1..1]	NumInGroup	
PaymentStreamInitialFixingDateBusinessCenter	[0..1]	String	Required if NoPaymentStreamInitialFixingDate-BusinessCenters(40949) > 0.

Used in components: [PaymentStreamResetDates](#)

### 180.2.3990 PaymentStreamInitialFixingDateBusinessDayConvention

The business day convention used to adjust the payment stream's initial fixing date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [PaymentStreamResetDates](#)

### 180.2.3991 PaymentStreamInitialFixingDateOffsetDayType

Specifies the day type of the relative initial fixing date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [PaymentStreamResetDates](#)

#### **180.2.3992 PaymentStreamInitialFixingDateOffsetPeriod**

Time unit multiplier for the relative initial fixing date offset.

Type: [int](#)

Used in components: [PaymentStreamResetDates](#)

#### **180.2.3993 PaymentStreamInitialFixingDateOffsetUnit**

Time unit associated with the relative initial fixing date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [PaymentStreamResetDates](#)

#### **180.2.3994 PaymentStreamInitialFixingDateRelativeTo**

Specifies the anchor date when the initial fixing date is relative to an anchor date.



See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamResetDates**

#### **180.2.3995 PaymentStreamInitialPrincipalExchangeIndicator**

Indicates whether there is an initial exchange of principal on the effective date.

Type: **Boolean**

Used in components: **PaymentStream**

#### **180.2.3996 PaymentStreamInitialRate**

The initial floating rate reset agreed between the principal parties involved in the trade. This is assumed to be the first required reset rate for the first regular calculation period. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. An initial rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in components: **PaymentStreamFloatingRate**

#### **180.2.3997 PaymentStreamInterimPrincipalExchangeIndicator**

Indicates whether there are intermediate or interim exchanges of principal during the term of the swap.

Type: **Boolean**

Used in components: **PaymentStream**

#### **180.2.3998 PaymentStreamInterpolationMethod**

The method used when calculating the index rate from multiple points on the curve. The most common is linear method.

Type: **int**

Allowed values in **PaymentStreamInflationInterpolationMethodCodeSet**:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: [PaymentStream](#)

### **180.2.3999 PaymentStreamInterpolationPeriod**

Defines applicable periods for interpolation.

Type: [int](#)

Allowed values in PaymentStreamInterpolationPeriodCodeSet:

Code	Name	Description
0	Initial	Initial. Interpolation is applicable to the initial period only.
1	InitialAndFinal	Initial and final. Interpolation is applicable to the initial and final periods only.
2	Final	Final. Interpolation is applicable to the final period only.
3	AnyPeriod	Any period. Interpolation is applicable to any non-standard period.

Used in components: [PaymentStream](#)

### **180.2.4000 PaymentStreamLastRegularPaymentDateUnadjusted**

The unadjusted last regular payment date.

Type: [LocalMktDate](#)

Used in components: [PaymentStreamPaymentDates](#)

### **180.2.4001 PaymentStreamLastResetRate**

The floating rate determined at the most recent reset. The rate is expressed in decimal form, e.g. 5% is represented as 0.05.

Type: [Percentage](#)

Used in components: [PaymentStreamFloatingRate](#)

**180.2.4002 PaymentStreamLinkClosingLevelIndicator**

Indicates whether the correlation or variance swap contract will ("Y") strike off the closing level of the default exchange traded contract or not.

Type: **Boolean**

Used in components: **PaymentStreamFloatingRate**

**180.2.4003 PaymentStreamLinkEstimatedTradingDays**

The expected number of trading days in the variance or correlation swap stream.

Type: **int**

Used in components: **PaymentStreamFloatingRate**

**180.2.4004 PaymentStreamLinkExpiringLevelIndicator**

Indicates whether the correlation or variance swap contract will ("Y") strike off the expiring level of the default exchange traded contract or not.

Type: **Boolean**

Used in components: **PaymentStreamFloatingRate**

**180.2.4005 PaymentStreamLinkInitialLevel**

Price level at which the correlation or variance swap contract will strike.

Type: **Price**

Used in components: **PaymentStreamFloatingRate**

**180.2.4006 PaymentStreamLinkMaximumBoundary**

Specifies the maximum or upper boundary for variance or strike determination.

For a variation swap stream all observations above this price level will be excluded from the variance calculation.

For a correlation swap stream the maximum boundary is a percentage of the strike price.

Type: **float**

Used in components: **PaymentStreamFloatingRate**

**180.2.4007 PaymentStreamLinkMinimumBoundary**

Specifies the minimum or lower boundary for variance or strike determination.

For a variation swap stream all observations below this price level will be excluded from the variance calculation.

For a correlation swap stream the minimum boundary is a percentage of the strike price.

Type: **float**

Used in components: **PaymentStreamFloatingRate**

**180.2.4008 PaymentStreamLinkNumberOfDataSeries**

Number of data series for a correlation swap. Normal market practice is that correlation data sets are drawn from geographic market areas, such as America, Europe and Asia Pacific. Each of these geographic areas will have its own data series to avoid contagion.

Type: **int**

Used in components: **PaymentStreamFloatingRate**

**180.2.4009 PaymentStreamLinkStrikePrice**

The strike price of a correlation or variance swap stream.

Type: **Price**

Used in components: **PaymentStreamFloatingRate**

**180.2.4010 PaymentStreamLinkStrikePriceType**

For a variance swap specifies how PaymentStreamLinkStrikePrice(42673) is expressed.

Type: **int**

Allowed values in PaymentStreamLinkStrikePriceTypeCodeSet:

---

Code	Name	Description
0	Volatility	Volatility
1	Variance	Variance

---

Used in components: **PaymentStreamFloatingRate**

**180.2.4011 PaymentStreamMarketRate**

Used only for credit index trade. This contains the credit spread ("fair value") at which the trade was executed. The market rate varies over the life of the index depending on market conditions. This is the price of the index as quoted by trading desks.

Type: **int**

Used in components: **PaymentStream**

**180.2.4012 PaymentStreamMasterAgreementPaymentDatesIndicator**

When set to 'Y', it indicates that payment dates are specified in the relevant master agreement.

Type: **Boolean**

Used in components: **PaymentStreamPaymentDates**

**180.2.4013 PaymentStreamMaximumPaymentAmount**

Specifies the limit on the total payment amount.

Type: **Amt**

Used in components: **PaymentStream**

**180.2.4014 PaymentStreamMaximumPaymentCurrency**

Specifies the currency of total payment amount limit. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **PaymentStream**

**180.2.4015 PaymentStreamMaximumTransactionAmount**

Specifies the limit on the payment amount that goes out in any particular calculation period.

Type: **Amt**

Used in components: **PaymentStream**

**180.2.4016 PaymentStreamMaximumTransactionCurrency**

Specifies the currency of the period payment amount limit. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **PaymentStream**

**180.2.4017 PaymentStreamNearestExchangeContractRefID**

References a contract listed on an exchange through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in components: **PaymentStreamFloatingRate**

**180.2.4018 PaymentStreamNegativeRateTreatment**

The specification of any provisions for calculating payment obligations when a floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: **PaymentStreamFloatingRate**

**180.2.4019 PaymentStreamNonDeliverableFixingDateGrp**

PaymentStreamNonDeliverableFixingDate is a subcomponent of the PaymentStreamNonDeliverable-SettlTerms component used to specify predetermined fixing dates.

Name	Mult.	Type	Description
NoNonDeliverableFixingDates	[1..1]	NumInGroup	
NonDeliverableFixingDate	[0..1]	LocalMktDate	Required if NoNonDeliverableFixingDates(40825) > 0.
NonDeliverableFixingDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [PaymentStreamNonDeliverableSettlTerms](#)

#### 180.2.4020 PaymentStreamNonDeliverableFixingDatesBusinessCenter

The business center calendar used to adjust the payment stream's fixing date for the non-deliverable terms, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [PaymentStreamNonDeliverableFixingDatesBusinessCenterGrp](#)

#### 180.2.4021 PaymentStreamNonDeliverableFixingDatesBusinessCenterGrp

PaymentStreamNonDeliverableFixingDatesBusinessCenterGrp is a repeating subcomponent within the PaymentStreamNonDeliverableSettlTerms component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoPaymentStreamNonDeliverableFixingDatesBusinessCenters	[1..1]	NumInGroup	
PaymentStreamNonDeliverableFixingDatesBusinessCenter	[0..1]	String	Required if NoPaymentStreamNonDeliverableFixingDatesBusinessCenters(40946) > 0.

Used in components: [PaymentStreamNonDeliverableSettlTerms](#)

**180.2.4022 PaymentStreamNonDeliverableFixingDatesBusinessDayConvention**

The business day convention used to adjust the payment stream's fixing date for the non-deliverable settlement terms. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **PaymentStreamNonDeliverableSettlTerms**

**180.2.4023 PaymentStreamNonDeliverableFixingDatesOffsetDayType**

Specifies the day type of the relative non-deliverable fixing date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStreamNonDeliverableSettlTerms**



**180.2.4024 PaymentStreamNonDeliverableFixingDatesOffsetPeriod**

Time unit multiplier for the relative non-deliverable fixing date offset.

Type: **int**

Used in components: **PaymentStreamNonDeliverableSettlTerms**

**180.2.4025 PaymentStreamNonDeliverableFixingDatesOffsetUnit**

Time unit associated with the relative non-deliverable fixing date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamNonDeliverableSettlTerms**

**180.2.4026 PaymentStreamNonDeliverableFixingDatesRelativeTo**

Specifies the anchor date when the non-deliverable fixing dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamNonDeliverableSettlTerms**

**180.2.4027 PaymentStreamNonDeliverableRefCurrency**

The non-deliverable settlement reference currency. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **PaymentStreamNonDeliverableSettlTerms**

**180.2.4028 PaymentStreamNonDeliverableSettlRateSource**

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in components: **PaymentStreamNonDeliverableSettlRateSource**

**180.2.4029 PaymentStreamNonDeliverableSettlRateSource**

PaymentStreamNonDeliverableSettlRateSource is a subcomponent of the PaymentStreamNonDeliverableSettlTerms component used to specify the rate source in the event of payment non-delivery.

Name	Mult.	Type	Description
<b>PaymentStreamNonDeliverableSettlRateSource</b>	[0..1]	CodeSet	
<b>PaymentStreamNonDeliverableSettlReferencePage</b>	[0..1]	String	Conditionally required when PaymentStreamNonDeliverableSettlRateSource(40371) = 3 (ISDA Settlement Rate Option) or 99 (Other).

Used in components: **PaymentStreamNonDeliverableSettlTerms**

**180.2.4030 PaymentStreamNonDeliverableSettlReferencePage**

Identifies the reference "page" from the rate source.

When `PaymentStreamNonDeliverableSettlRateSource(40371) = 3` (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in components: **PaymentStreamNonDeliverableSettlRateSource**

### 180.2.4031 **PaymentStreamNonDeliverableSettlTerms**

`PaymentStreamNonDeliverableSettlTerms` is a subcomponent of the `PaymentStream` component used to specify the non-deliverable settlement terms of the payment stream.

Name	Mult.	Type	Description
<code>PaymentStreamNonDeliverableRefCurrency</code>	[0..1]	Currency	
<code>PaymentStreamNonDeliverableFixing-DatesBusinessDayConvention</code>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the <code>DateAdjustment</code> component in <code>Instrument</code> . The specified value would be specific to this instance of the payment stream's non-deliverable fixing dates.
<code>PaymentStreamNonDeliverableFixing-DatesBusinessCenterGrp</code>	[0..*]	Group	When specified, this overrides the business centers defined in the <code>DateAdjustment</code> component in <code>Instrument</code> . The specified values would be specific to this instance of the payment stream's non-deliverable fixing dates.
<code>PaymentStreamNonDeliverableFixing-DatesRelativeTo</code>	[0..1]	int	
<code>PaymentStreamNonDeliverableFixing-DatesOffsetPeriod</code>	[0..1]	int	Conditionally required when <code>PaymentStreamNonDeliverableFixingDatesOffsetUnit(40822)</code> is specified.
<code>PaymentStreamNonDeliverableFixing-DatesOffsetUnit</code>	[0..1]	CodeSet	Conditionally required when <code>PaymentStreamNonDeliverableFixingDatesOffsetPeriod(40821)</code> is specified.
<code>PaymentStreamNonDeliverableFixing-DatesOffsetDayType</code>	[0..1]	CodeSet	
<code>PaymentStreamNonDeliverableSettlRateSource</code>	[0..1]	Component	
<code>PaymentStreamNonDeliverableFixing-DateGrp</code>	[0..*]	Group	
<code>SettlRateDisruptionFallbackGrp</code>	[0..*]	Group	

Used in components: [PaymentStream](#)

#### **180.2.4032 PaymentStreamOtherDayCount**

The industry name of the day count convention not listed in [PaymentStreamDayCount\(40742\)](#).

Type: [String](#)

Used in components: [PaymentStream](#)

#### **180.2.4033 PaymentStreamPaymentDate**

The adjusted or unadjusted fixed stream payment date.

Type: [LocalMktDate](#)

Used in groups: [PaymentStreamPaymentDateGrp](#)

#### **180.2.4034 PaymentStreamPaymentDateBusinessCenter**

The business center calendar used to adjust the payment stream's payment date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [PaymentStreamPaymentDateBusinessCenterGrp](#)

#### **180.2.4035 PaymentStreamPaymentDateBusinessCenterGrp**

[PaymentStreamPaymentDateBusinessCenterGrp](#) is a repeating subcomponent within the [PaymentStreamPaymentDates](#) component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the [DateAdjustment](#) component in [Instrument](#).

Name	Mult.	Type	Description
<a href="#">NoPaymentStreamPaymentDateBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">PaymentStreamPaymentDateBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoPaymentStreamPaymentDateBusinessCenters(40947)</a> > 0.

Used in components: [PaymentStreamPaymentDates](#)

**180.2.4036 PaymentStreamPaymentDateBusinessDayConvention**

The business day convention used to adjust the payment stream's payment date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **PaymentStreamPaymentDates**

**180.2.4037 PaymentStreamPaymentDateGrp**

The PaymentStreamPaymentDateGrp is a repeating subcomponent of the PaymentStreamPaymentDates component used to detail fixed dates for swap stream payments.

Name	Mult.	Type	Description
<b>NoPaymentStreamPaymentDates</b>	[1..1]	NumInGroup	
<b>PaymentStreamPaymentDate</b>	[0..1]	LocalMktDate	Required if NoPaymentStreamPaymentDates(41220) > 0.
<b>PaymentStreamPaymentDateType</b>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: **PaymentStreamPaymentDates**

**180.2.4038 PaymentStreamPaymentDateOffsetDayType**

Specifies the day type of the relative payment date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStreamPaymentDates**

**180.2.4039 PaymentStreamPaymentDateOffsetPeriod**

Time unit multiplier for the relative payment date offset.

Type: **int**

Used in components: **PaymentStreamPaymentDates**

**180.2.4040 PaymentStreamPaymentDateOffsetUnit**

Time unit multiplier for the relative initial fixing date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamPaymentDates**

**180.2.4041 PaymentStreamPaymentDateRelativeTo**

Specifies the anchor date when payment dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamPaymentDates**

**180.2.4042 PaymentStreamPaymentDates**

PaymentStreamPaymentDates is a subcomponent of the PaymentStream component used to specify the payment dates of the stream.

Name	Mult.	Type	Description
PaymentStreamPaymentDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the payment stream's payment dates.
PaymentStreamPaymentDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the payment stream's payment dates.
PaymentStreamPaymentDateGrp	[0..*]	Group	
PaymentStreamPaymentFrequencyPeriod	[0..1]	int	Conditionally required when PaymentStreamPaymentFrequencyUnit(40754) is specified.
PaymentStreamPaymentFrequencyUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamPaymentFrequencyPeriod(40753) is specified.
PaymentStreamPaymentRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the stream payment dates
PaymentStreamFirstPaymentDateUnadjusted	[0..1]	LocalMktDate	
PaymentStreamLastRegularPaymentDateUnadjusted	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
PaymentStreamPaymentDateRelativeTo	[0..1]	int	
PaymentStreamPaymentDateOffsetPeriod	[0..1]	int	Conditionally required when PaymentStreamPaymentDateOffsetUnit(40760) is specified.
PaymentStreamPaymentDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamPaymentDateOffsetPeriod(40759) is specified.
PaymentStreamPaymentDateOffsetDayType	[0..1]	CodeSet	
PaymentStreamMasterAgreementPaymentDatesIndicator	[0..1]	Boolean	
PaymentStreamFinalPricePaymentDate	[0..1]	Component	

Used in components: **PaymentStream**

#### 180.2.4043 PaymentStreamPaymentDateType

Specifies the type of payment date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **PaymentStreamPaymentDateGrp**

#### 180.2.4044 PaymentStreamPaymentFrequencyPeriod

Time unit multiplier for the frequency of payments.

Type: **int**

Used in components: **PaymentStreamPaymentDates**



**180.2.4045 PaymentStreamPaymentFrequencyUnit**

Time unit associated with the frequency of payments.

Type: **String**

Allowed values in PaymentStreamPaymentFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
T	Term	Term

Used in components: **PaymentStreamPaymentDates**

**180.2.4046 PaymentStreamPaymentRollConvention**

The convention for determining the sequence of end dates. It is used in conjunction with a specified frequency. Used only to override the roll convention specified in the DateAdjustment component within the Instrument component.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month

Code	Name	Description
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEigthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday

Code	Name	Description
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [PaymentStreamPaymentDates](#)

#### **180.2.4047 PaymentStreamPricingBusinessCalendar**

Specifies the business calendar to use for pricing.

See <http://www.fpml.org/coding-scheme/commodity-business-calendar> for values.

Type: [String](#)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4048 PaymentStreamPricingBusinessCenter**

The business center calendar used to adjust the payment stream's pricing dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [PaymentStreamPricingBusinessCenterGrp](#)

#### **180.2.4049 PaymentStreamPricingBusinessCenterGrp**

The `PaymentStreamPricingBusinessCenterGrp` is a repeating subcomponent of the `PaymentStreamFloatingRate` component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the `DateAdjustment` component in `Instrument`.

Name	Mult.	Type	Description
NoPaymentStreamPricingBusinessCenters	[1..1]	NumInGroup	
PaymentStreamPricingBusinessCenter	[0..1]	String	Required if NoPaymentStreamPricingBusinessCenters(41192) > 0.

Used in components: [PaymentStreamFloatingRate](#)

### 180.2.4050 PaymentStreamPricingBusinessDayConvention

The business day convention used to adjust the payment stream's pricing dates. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [PaymentStreamFloatingRate](#)

### 180.2.4051 PaymentStreamPricingDate

The adjusted or unadjusted fixed stream pricing date.

Type: [LocalMktDate](#)

Used in groups: [PaymentStreamPricingDateGrp](#)

**180.2.4052 PaymentStreamPricingDateGrp**

The PaymentStreamPricingDateGrp is a repeating subcomponent of the PaymentStreamFloatingRate component used to detail fixed pricing dates.

Name	Mult.	Type	Description
NoPaymentStreamPricingDates	[1..1]	NumInGroup	
PaymentStreamPricingDate	[0..1]	LocalMktDate	Required if NoPaymentStreamPricingDates(41224) > 0.
PaymentStreamPricingDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [PaymentStreamFloatingRate](#)

**180.2.4053 PaymentStreamPricingDateType**

Specifies the type of pricing date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: [int](#)

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [PaymentStreamPricingDateGrp](#)

**180.2.4054 PaymentStreamPricingDayCount**

The number of days over which pricing should take place.

Type: [int](#)

Used in components: [PaymentStreamFloatingRate](#)

**180.2.4055 PaymentStreamPricingDayDistribution**

The distribution of pricing days.

Type: **int**

Allowed values in PaymentStreamPricingDayDistributionCodeSet:

Code	Name	Description
0	All	All
1	First	First
2	Last	Last
3	Penultimate	Penultimate

Used in components: **PaymentStreamFloatingRate**

**180.2.4056 PaymentStreamPricingDayGrp**

The PaymentStreamPricingDayGrp is a repeating subcomponent of the PaymentStreamFloatingRate component used to detail periodic pricing days.

Name	Mult.	Type	Description
<b>NoPaymentStreamPricingDays</b>	[1..1]	NumInGroup	
<b>PaymentStreamPricingDayOfWeek</b>	[0..1]	CodeSet	Required if NoPaymentStreamPricingDays(41227) > 0.
<b>PaymentStreamPricingDayNumber</b>	[0..1]	int	

Used in components: **PaymentStreamFloatingRate**

**180.2.4057 PaymentStreamPricingDayNumber**

The occurrence of the day of week on which pricing takes place.

Type: **int**

Used in groups: **PaymentStreamPricingDayGrp**

**180.2.4058 PaymentStreamPricingDayOfWeek**

The day of the week on which pricing takes place.

Type: **int**

Allowed values in PaymentStreamPricingDayOfWeekCodeSet:

Code	Name	Description
0	EveryDay	Every day (the default if not specified)
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday

Used in groups: **PaymentStreamPricingDayGrp**

**180.2.4059 PaymentStreamPricingDayType**

Specifies the commodity pricing day type.

Type: **int**

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStreamFloatingRate**

**180.2.4060 PaymentStreamRate**

The rate applicable to the fixed rate payment stream.

Type: **Percentage**

Used in components: **PaymentStreamFixedRate**

**180.2.4061 PaymentStreamRateConversionFactor**

The number to be multiplied by the derived floating rate of the payment stream in order to arrive at the payment rate. If omitted, the floating rate conversion factor is 1.

Type: **float**

Used in components: **PaymentStreamFloatingRate**

**180.2.4062 PaymentStreamRateCutoffDateOffsetDayType**

Specifies the day type of the relative rate cut-off date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStreamResetDates**

**180.2.4063 PaymentStreamRateCutoffDateOffsetPeriod**

Time unit multiplier for the relative rate cut-off date offset.

Type: **int**

Used in components: **PaymentStreamResetDates**



**180.2.4064 PaymentStreamRateCutoffDateOffsetUnit**

Time unit associated with the relative rate cut-off date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamResetDates**

**180.2.4065 PaymentStreamRateIndex**

The payment stream floating rate index.

Type: **String**

Used in components: **PaymentStreamFloatingRate**

**180.2.4066 PaymentStreamRateIndex2**

The payment stream's second floating rate index.

Type: **String**

Used in components: **PaymentStreamFloatingRate**

**180.2.4067 PaymentStreamRateIndex2CurvePeriod**

Secondary time unit multiplier for the payment stream's floating rate index curve.

Type: **int**

Used in components: **PaymentStreamFloatingRate**

**180.2.4068 PaymentStreamRateIndex2CurveUnit**

Secondary time unit associated with the payment stream's floating rate index curve.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamFloatingRate**

**180.2.4069 PaymentStreamRateIndex2ID**

Security identifier of the second floating rate index.

Type: **String**

Used in components: **PaymentStreamFloatingRate**

**180.2.4070 PaymentStreamRateIndex2IDSource**

Source for the second floating rate index identified in PaymentStreamRateIndex2ID(43114).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)

Code	Name	Description
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **PaymentStreamFloatingRate**

**180.2.4071 PaymentStreamRateIndex2Source**

The source of the payment stream's second floating rate index.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: **PaymentStreamFloatingRate**

**180.2.4072 PaymentStreamRateIndexCurvePeriod**

Time unit multiplier for the floating rate index.

Type: **int**

Used in components: **PaymentStreamFloatingRate**

**180.2.4073 PaymentStreamRateIndexCurveUnit**

Time unit associated with the floating rate index.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStreamFloatingRate**

**180.2.4074 PaymentStreamRateIndexID**

Security identifier of the floating rate index.

Type: **String**

Used in components: **PaymentStreamFloatingRate**

**180.2.4075 PaymentStreamRateIndexIDSource**

Source for the floating rate index identified in PaymentStreamRateIndexID(43090).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit

Code	Name	Description
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4076 PaymentStreamRateIndexLevel**

This is the weather Cooling Degree Days (CDD), Heating Degree Days (HDD) or HDD index level specified as the number of (amount of) weather index units specified by the parties in the related confirmation.

Type: [Qty](#)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4077 PaymentStreamRateIndexLocation**

Specifies the location of the floating rate index.

Type: [String](#)

Used in components: [PaymentStreamFloatingRate](#)

**180.2.4078 PaymentStreamRateIndexSource**

The source of the payment stream floating rate index.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: **PaymentStreamFloatingRate**

**180.2.4079 PaymentStreamRateIndexUnitOfMeasure**

The unit of measure (UOM) of the rate index level.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)



Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter

Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4080 PaymentStreamRateMultiplier**

A rate multiplier to apply to the floating rate. A multiplier schedule is expressed as explicit multipliers and dates. In the case of a schedule, the step dates may be subject to adjustment in accordance with any adjustments specified in the calculationPeriodDatesAdjustments. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: [float](#)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4081 PaymentStreamRateOrAmountCurrency**

Specifies the currency in which PaymentStreamFixedAmount(40785) or PaymentStreamRate(40784) is denominated. Uses ISO 4271 currency codes.

Type: [Currency](#)

Used in components: [PaymentStreamFixedRate](#)

#### **180.2.4082 PaymentStreamRateSpread**

Spread from floating rate index.

Type: [PriceOffset](#)

Used in components: [PaymentStreamFloatingRate](#)

**180.2.4083 PaymentStreamRateSpreadCurrency**

Specifies the currency of the floating rate spread. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **PaymentStreamFloatingRate**

**180.2.4084 PaymentStreamRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: **PaymentStreamFloatingRate**

**180.2.4085 PaymentStreamRateSpreadType**

Identifies whether the rate spread is an absolute value to be added to the index rate or a percentage of the index rate.

Type: **int**

Allowed values in PaymentStreamRateSpreadTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in components: **PaymentStreamFloatingRate**

**180.2.4086 PaymentStreamRateSpreadUnitOfMeasure**

Species the unit of measure (UOM) of the floating rate spread.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [PaymentStreamFloatingRate](#)

#### 180.2.4087 PaymentStreamRateTreatment

Specifies the yield calculation treatment for the index.

Type: [int](#)

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4088 PaymentStreamRealizedVarianceMethod**

Indicates which price to use to satisfy the boundary condition.

Type: [int](#)

Allowed values in PaymentStreamRealizedVarianceMethodCodeSet:

Code	Name	Description
0	Previous	Previous. For a return on day T, the observed price on T-1 must be in range.
1	Last	Last. For a return on day T, the observed price on T must be in range.
2	Both	Both. For a return on day T, the observed prices on both T and T-1 must be in range.

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4089 PaymentStreamReferenceLevel**

This is the weather Cooling Degree Days (CDD), Heating Degree Days (HDD) or HDD reference level specified as the number of (amount of) weather index units specified by the parties in the related confirmation.

Type: [Qty](#)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4090 PaymentStreamReferenceLevelEqualsZeroIndicator**

When set to 'Y', it indicates the weather reference level equals zero.

Type: [Boolean](#)

Used in components: [PaymentStreamFloatingRate](#)

**180.2.4091 PaymentStreamReferenceLevelUnitOfMeasure**

The unit of measure (UOM) of the rate reference level.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams



Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4092 PaymentStreamResetDateBusinessCenter**

The business center calendar used to adjust the payment stream's reset date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [PaymentStreamResetDateBusinessCenterGrp](#)

**180.2.4093 PaymentStreamResetDateBusinessCenterGrp**

PaymentStreamResetDateBusinessCenterGrp is a repeating subcomponent within the PaymentStreamResetDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoPaymentStreamResetDateBusinessCenters	[1..1]	NumInGroup	
PaymentStreamResetDateBusinessCenter	[0..1]	String	Required if NoPaymentStreamResetDateBusinessCenters(40948) > 0.

Used in components: [PaymentStreamResetDates](#)

**180.2.4094 PaymentStreamResetDateBusinessDayConvention**

The business day convention used to adjust the payment stream's reset date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [PaymentStreamResetDates](#)

**180.2.4095 PaymentStreamResetDateRelativeTo**

Specifies the anchor date when the reset dates are relative to an anchor date.

If the reset frequency is specified as daily this element must not be included.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStreamResetDates**

**180.2.4096 PaymentStreamResetDates**

PaymentStreamResetDates is a subcomponent of the PaymentStream component used to specify the floating rate reset dates of the stream.

Name	Mult.	Type	Description
<b>PaymentStreamResetDateRelativeTo</b>	[0..1]	int	
<b>PaymentStreamResetDateBusiness-DayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the payment stream's reset dates.
<b>PaymentStreamResetDateBusiness-CenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the payment stream's reset dates.
<b>PaymentStreamResetFrequencyPeriod</b>	[0..1]	int	Conditionally required when PaymentStreamResetFrequencyUnit(40765) is specified.
<b>PaymentStreamResetFrequencyUnit</b>	[0..1]	CodeSet	Conditionally required when PaymentStreamResetFrequencyPeriod(40764) is specified.
<b>PaymentStreamResetWeeklyRollConvention</b>	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the stream floating rate reset dates.
<b>PaymentStreamInitialFixingDateRelativeTo</b>	[0..1]	int	

Name	Mult.	Type	Description
PaymentStreamInitialFixingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the payment stream's reset dates.
PaymentStreamInitialFixingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the payment stream's reset dates.
PaymentStreamInitialFixingDateOffsetPeriod	[0..1]	int	Conditionally required when PaymentStreamInitialFixingDateOffsetUnit(40771) is specified.
PaymentStreamInitialFixingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamInitialFixingDateOffsetPeriod(40770) is specified.
PaymentStreamInitialFixingDateOffsetDayType	[0..1]	CodeSet	
PaymentStreamInitialFixingDateAdjusted	[0..1]	LocalMktDate	
PaymentStreamFixingDateRelativeTo	[0..1]	int	
PaymentStreamFixingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the payment stream's reset dates.
PaymentStreamFixingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the payment stream's reset dates.
PaymentStreamFixingDateOffsetPeriod	[0..1]	int	Conditionally required when PaymentStreamFixingDateOffsetUnit(40778) is specified.
PaymentStreamFixingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamFixingDateOffsetPeriod(40777) is specified.
PaymentStreamFixingDateOffsetDayType	[0..1]	CodeSet	
PaymentStreamFixingDateAdjusted	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
PaymentStreamRateCutoffDateOffset-Period	[0..1]	int	Conditionally required when PaymentStreamRateCutoffDateOffsetUnit(40782) is specified.
PaymentStreamRateCutoffDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentStreamRateCutoffDateOffsetPeriod(40783) is specified.
PaymentStreamRateCutoffDateOffset-DayType	[0..1]	CodeSet	
PaymentStreamFixingDateGrp	[0..*]	Group	

Used in components: [PaymentStream](#)

### 180.2.4097 PaymentStreamResetFrequencyPeriod

Time unit multiplier for the frequency of resets.

Type: [int](#)

Used in components: [PaymentStreamResetDates](#)

### 180.2.4098 PaymentStreamResetFrequencyUnit

Time unit associated with the frequency of resets.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: [PaymentStreamResetDates](#)

**180.2.4099 PaymentStreamResetWeeklyRollConvention**

Used to specify the day of the week in which the reset occurs for payments that reset on a weekly basis.

Type: **String**

Allowed values in PaymentStreamResetWeeklyRollConventionCodeSet:

Code	Name	Description
MON	Monday	Monday
TUE	Tuesday	Tuesday
WED	Wednesday	Wednesday
THU	Thursday	Thursday
FRI	Friday	Friday
SAT	Saturday	Saturday
SUN	Sunday	Sunday

Used in components: **PaymentStreamResetDates**

**180.2.4100 PaymentStreamSettlCurrency**

Specifies the currency that the stream settles in (to support swaps that settle in a currency different from the notional currency). Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **PaymentStream**

**180.2.4101 PaymentStreamSettlLevel**

Specifies how weather index units are to be calculated.

Type: **int**

Allowed values in PaymentStreamSettlLevelCodeSet:

Code	Name	Description
0	Average	Average. The cumulative number of weather index units for each day in the calculation period divided by the number of days in the calculation period.
1	Maximum	Maximum. The maximum number of weather index units for any day in the calculation period.
2	Minimum	Minimum. The minimum number of weather index units for any day in the calculation period.
3	Cumulative	Cumulative. The cumulative number of weather index units for each day in the calculation period.

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4102 PaymentStreamTotalFixedAmount**

Specifies the total fixed payment amount.

Type: [Amt](#)

Used in components: [PaymentStreamFixedRate](#)

#### **180.2.4103 PaymentStreamType**

Identifies the type of payment stream associated with the swap.

Type: [int](#)

Allowed values in PaymentStreamTypeCodeSet:

Code	Name	Description
0	Periodic	Periodic (default)
1	Initial	Initial
2	Single	Single
3	Dividend	Dividend
4	Interest	Interest
5	DividendReturn	Dividend return
6	PriceReturn	Price return
7	TotalReturn	Total return



Code	Name	Description
8	Variance	Variance
9	Correlation	Correlation

Used in components: [PaymentStream](#)

#### **180.2.4104 PaymentStreamUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: [String](#)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4105 PaymentStreamVarianceUnadjustedCap**

Indicates the scaling factor to be multiplied by the variance strike price thereby making variance cap applicable.

Type: [float](#)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4106 PaymentStreamVegaNotionalAmount**

"Vega Notional" represents the approximate gain/loss at maturity for a 1% difference between RVol (realised volatility) and KVol (strike volatility). It does not necessarily represent the Vega risk of the trade.

Type: [float](#)

Used in components: [PaymentStreamFloatingRate](#)

#### **180.2.4107 PaymentStreamWorldScaleRate**

The number of Worldscales points for purposes of the calculation of a fixed amount for a wet voyage charter commodity swap.

Type: [float](#)

Used in components: [PaymentStreamFixedRate](#)

**180.2.4108 PaymentStubEndDateAdjusted**

The adjusted stub end date.

Type: **LocalMktDate**

Used in components: **PaymentStubEndDate**

**180.2.4109 PaymentStubEndDateBusinessCenter**

The business center calendar used for date adjustment of the payment stub end date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **PaymentStubEndDateBusinessCenterGrp**

**180.2.4110 PaymentStubEndDateBusinessCenterGrp**

PaymentStubEndDateBusinessCenterGrp is a repeating subcomponent within the PaymentStubEndDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
<b>NoPaymentStubEndDateBusinessCenters</b>	[1..1]	NumInGroup	
<b>PaymentStubEndDateBusinessCenter</b>	[0..1]	String	Required if NoPaymentStubEndDateBusinessCenters(42696) > 0.

Used in components: **PaymentStubEndDate**

**180.2.4111 PaymentStubEndDateBusinessDayConvention**

The stub end date business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [PaymentStubEndDate](#)

### 180.2.4112 PaymentStubEndDate

PaymentStubEndDate is a subcomponent of the PaymentStubGrp component used to specify the end date of the payment stub.

Name	Mult.	Type	Description
<a href="#">PaymentStubEndDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">PaymentStubEndDateBusinessDay-Convention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this payment stub instance.
<a href="#">PaymentStubEndDateBusinessCenter-Grp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this payment stub instance.
<a href="#">PaymentStubEndDateRelativeTo</a>	[0..1]	int	
<a href="#">PaymentStubEndDateOffsetPeriod</a>	[0..1]	int	Conditionally required when PaymentStubEndDateOffsetUnit(42693) is specified.
<a href="#">PaymentStubEndDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when PaymentStubEndDateOffsetPeriod(42692) is specified.
<a href="#">PaymentStubEndDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">PaymentStubEndDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: **PaymentStubGrp**

#### **180.2.4113 PaymentStubEndDateOffsetDayType**

Specifies the day type of the relative stub end date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStubEndDate**

#### **180.2.4114 PaymentStubEndDateOffsetPeriod**

Time unit multiplier for the relative stub end date offset.

Type: **int**

Used in components: **PaymentStubEndDate**

#### **180.2.4115 PaymentStubEndDateOffsetUnit**

Time unit associated with the relative stub end date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week

Code	Name	Description
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStubEndDate**

#### **180.2.4116 PaymentStubEndDateRelativeTo**

Specifies the anchor date when the stub end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStubEndDate**

#### **180.2.4117 PaymentStubEndDateUnadjusted**

The unadjusted stub end date.

Type: **LocalMktDate**

Used in components: **PaymentStubEndDate**

#### **180.2.4118 PaymentStubFixedAmount**

A fixed payment amount for the stub.

Type: **Amt**

Used in groups: **PaymentStubGrp**

#### **180.2.4119 PaymentStubFixedCurrency**

The currency of the fixed payment amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **PaymentStubGrp**

**180.2.4120 PaymentStubGrp**

The PaymentStubGrp is a repeating subcomponent of the StreamGrp component used to specify front and back stubs of the payment stream.

Name	Mult.	Type	Description
NoPaymentStubs	[1..1]	NumInGroup	
PaymentStubType	[0..1]	CodeSet	Required if NoPaymentStubs(40872) > 0.
PaymentStubLength	[0..1]	CodeSet	
PaymentStubStartDate	[0..1]	Component	
PaymentStubEndDate	[0..1]	Component	
PaymentStubRate	[0..1]	Percentage	
PaymentStubFixedAmount	[0..1]	Amt	
PaymentStubFixedCurrency	[0..1]	Currency	
PaymentStubIndex	[0..1]	String	
PaymentStubIndexSource	[0..1]	CodeSet	
PaymentStubIndexCurvePeriod	[0..1]	int	Conditionally required when PaymentStubIndexCurveUnit(40881) is specified.
PaymentStubIndexCurveUnit	[0..1]	CodeSet	Conditionally required when PaymentStubIndexCurvePeriod(40880) is specified.
PaymentStubIndexRateMultiplier	[0..1]	float	
PaymentStubIndexRateSpread	[0..1]	PriceOffset	
PaymentStubIndexRateSpreadPositionType	[0..1]	CodeSet	
PaymentStubIndexRateTreatment	[0..1]	CodeSet	
PaymentStubIndexCapRate	[0..1]	Percentage	
PaymentStubIndexCapRateBuySide	[0..1]	CodeSet	
PaymentStubIndexCapRateSellSide	[0..1]	CodeSet	
PaymentStubIndexFloorRate	[0..1]	Percentage	
PaymentStubIndexFloorRateBuySide	[0..1]	CodeSet	
PaymentStubIndexFloorRateSellSide	[0..1]	CodeSet	
PaymentStubIndex2	[0..1]	String	
PaymentStubIndex2Source	[0..1]	CodeSet	
PaymentStubIndex2CurvePeriod	[0..1]	int	Conditionally required when PaymentStubIndex2CurveUnit(40895) is specified.

Name	Mult.	Type	Description
PaymentStubIndex2CurveUnit	[0..1]	CodeSet	Conditionally required when PaymentStubIndex2CurvePeriod(40894) is specified.
PaymentStubIndex2RateMultiplier	[0..1]	float	
PaymentStubIndex2RateSpread	[0..1]	PriceOffset	
PaymentStubIndex2RateSpreadPositionType	[0..1]	CodeSet	
PaymentStubIndex2RateTreatment	[0..1]	CodeSet	
PaymentStubIndex2CapRate	[0..1]	Percentage	
PaymentStubIndex2FloorRate	[0..1]	Percentage	

Used in groups: **StreamGrp**

#### **180.2.4121 PaymentStubIndex**

The stub floating rate index.

Type: **String**

Used in groups: **PaymentStubGrp**

#### **180.2.4122 PaymentStubIndex2**

The second stub floating rate index.

Type: **String**

Used in groups: **PaymentStubGrp**

#### **180.2.4123 PaymentStubIndex2CapRate**

The cap rate, if any, which applies to the second floating rate. The cap rate (strike) is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **PaymentStubGrp**

**180.2.4124 PaymentStubIndex2CurvePeriod**

Secondary time unit multiplier for the stub floating rate index curve.

Type: **int**

Used in groups: **PaymentStubGrp**

**180.2.4125 PaymentStubIndex2CurveUnit**

Secondary time unit associated with the stub floating rate index curve.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **PaymentStubGrp**

**180.2.4126 PaymentStubIndex2FloorRate**

The floor rate, if any, which applies to the second floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A floor rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **PaymentStubGrp**

**180.2.4127 PaymentStubIndex2RateMultiplier**

A rate multiplier to apply to the second floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.



Type: **float**

Used in groups: **PaymentStubGrp**

#### **180.2.4128 PaymentStubIndex2RateSpread**

Spread from the second floating rate index.

Type: **PriceOffset**

Used in groups: **PaymentStubGrp**

#### **180.2.4129 PaymentStubIndex2RateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in groups: **PaymentStubGrp**

#### **180.2.4130 PaymentStubIndex2RateTreatment**

Specifies the yield calculation treatment for the second stub index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in groups: **PaymentStubGrp**

**180.2.4131 PaymentStubIndex2Source**

The source of the second stub floating rate index.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in groups: **PaymentStubGrp**

**180.2.4132 PaymentStubIndexCapRate**

The cap rate, if any, which applies to the floating rate. The cap rate (strike) is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **PaymentStubGrp**

**180.2.4133 PaymentStubIndexCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **PaymentStubGrp**

**180.2.4134 PaymentStubIndexCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **PaymentStubGrp**

**180.2.4135 PaymentStubIndexCurvePeriod**

Time unit multiplier for the stub floating rate index.

Type: **int**

Used in groups: **PaymentStubGrp**

**180.2.4136 PaymentStubIndexCurveUnit**

Time unit associated with the stub floating rate index.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **PaymentStubGrp**

**180.2.4137 PaymentStubIndexFloorRate**

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A floor rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **PaymentStubGrp**

**180.2.4138 PaymentStubIndexFloorRateBuySide**

Reference to the buyer of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **PaymentStubGrp**

**180.2.4139 PaymentStubIndexFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **PaymentStubGrp**

**180.2.4140 PaymentStubIndexRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: **float**

Used in groups: **PaymentStubGrp**

**180.2.4141 PaymentStubIndexRateSpread**

Spread from floating rate index.

Type: **PriceOffset**

Used in groups: **PaymentStubGrp**

**180.2.4142 PaymentStubIndexRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in groups: **PaymentStubGrp**

**180.2.4143 PaymentStubIndexRateTreatment**

Specifies the yield calculation treatment for the payment stub index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

---

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

---

Used in groups: **PaymentStubGrp**

#### **180.2.4144 PaymentStubIndexSource**

The source of the stub floating rate index.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

---

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

---

Used in groups: **PaymentStubGrp**

#### **180.2.4145 PaymentStubLength**

Optional indication whether stub is shorter or longer than the regular swap period.

Type: **int**

Allowed values in PaymentStubLengthCodeSet:

---

Code	Name	Description
0	Short	Short
1	Long	Long

---

Used in groups: **PaymentStubGrp**

**180.2.4146 PaymentStubRate**

The agreed upon fixed rate for this stub.

Type: **Percentage**

Used in groups: **PaymentStubGrp**

**180.2.4147 PaymentStubStartDateAdjusted**

The adjusted stub start date.

Type: **LocalMktDate**

Used in components: **PaymentStubStartDate**

**180.2.4148 PaymentStubStartDateBusinessCenter**

The business center calendar used for date adjustment of the payment stub start date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **PaymentStubStartDateBusinessCenterGrp**

**180.2.4149 PaymentStubStartDateBusinessCenterGrp**

PaymentStubStartDateBusinessCenterGrp is a repeating subcomponent within the PaymentStubStartDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoPaymentStubStartDateBusinessCenters	[1..1]	NumInGroup	
PaymentStubStartDateBusinessCenter	[0..1]	String	Required if NoPaymentStubStartDateBusinessCenters(42705) > 0.

Used in components: **PaymentStubStartDate**

**180.2.4150 PaymentStubStartDateBusinessDayConvention**

The stub start date business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **PaymentStubStartDate**

**180.2.4151 PaymentStubStartDate**

PaymentStubStartDate is a subcomponent of the PaymentStubGrp component used to specify the start date of the payment stub.

Name	Mult.	Type	Description
<b>PaymentStubStartDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>PaymentStubStartDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this payment stub instance.
<b>PaymentStubStartDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this payment stub instance.
<b>PaymentStubStartDateRelativeTo</b>	[0..1]	int	
<b>PaymentStubStartDateOffsetPeriod</b>	[0..1]	int	Conditionally required when PaymentStubStartDateOffsetUnit(42702) is specified.



Name	Mult.	Type	Description
PaymentStubStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when PaymentStubStartDateOffsetPeriod(42701) is specified.
PaymentStubStartDateOffsetDayType	[0..1]	CodeSet	
PaymentStubStartDateAdjusted	[0..1]	LocalMktDate	

Used in groups: **PaymentStubGrp**

#### 180.2.4152 PaymentStubStartDateOffsetDayType

Specifies the day type of the relative stub start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **PaymentStubStartDate**

#### 180.2.4153 PaymentStubStartDateOffsetPeriod

Time unit multiplier for the relative stub start date offset.

Type: **int**

Used in components: **PaymentStubStartDate**

**180.2.4154 PaymentStubStartDateOffsetUnit**

Time unit associated with the relative stub start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **PaymentStubStartDate**

**180.2.4155 PaymentStubStartDateRelativeTo**

Specifies the anchor date when the stub start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **PaymentStubStartDate**

**180.2.4156 PaymentStubStartDateUnadjusted**

The unadjusted stub start date.

Type: **LocalMktDate**

Used in components: **PaymentStubStartDate**

**180.2.4157 PaymentStubType**

Stub type.

Type: **int**

Allowed values in PaymentStubTypeCodeSet:

Code	Name	Description
0	Initial	Initial
1	Final	Final
2	CompoundingInitial	Compounding initial
3	CompoundingFinal	Compounding final

Used in groups: **PaymentStubGrp**

### 180.2.4158 PaymentSubType

Used to further clarify the value of PaymentType(40213).

Type: **int**

Allowed values in PaymentSubTypeCodeSet:

Code	Name	Description
0	Initial	Initial (principal exchange)
1	Intermediate	Intermediate (principal exchange)
2	Final	Final (principal exchange)
3	Prepaid	Prepaid (premium forward)
4	Postpaid	Postpaid (premium forward)
5	Variable	Variable (premium forward)
6	Fixed	Fixed (premium forward)
7	Swap	Swap (premium). Indicates that the premium is to be paid in the style of payments under an IRS contract.
8	Conditional	Conditional (principal exchange on exercise)
9	FixedRate	Fixed rate. Applicable to PaymentType(40213)=14 (Rebate) for which PaymentFixedRate(43097) and its qualifiers supersede PaymentAmount(40217).
10	FloatingRate	Floating rate. Applicable to PaymentType(40213)=14 (Rebate) for which PaymentFloatingRateIndex(43098) and its qualifiers supersede PaymentAmount(40217).

Used in groups: **PaymentGrp**

**180.2.4159 PaymentText**

Free form text to specify additional information or enumeration description when a standard value does not apply. Identifies the payment type when PaymentType(40213) = 99 (Other).

Type: **String**

Used in groups: **PaymentGrp**

**180.2.4160 PaymentType**

Type of payment.

Type: **int**

Allowed values in PaymentTypeCodeSet:

Code	Name	Description
0	Brokerage	Brokerage
1	UpfrontFee	Upfront fee
2	IndependentAmountCollateral	Independent amount / collateral
3	PrincipalExchange	Principal exchange
4	NovationTermination	Novation / termination
5	EarlyTerminationProvision	Early termination provision
6	CancelableProvision	Cancelable provision
7	ExtendibleProvision	Extendible provision
8	CapRateProvision	Cap rate provision
9	FloorRateProvision	Floor rate provision
10	OptionPremium	Option premium
11	SettlementPayment	Settlement payment
12	CashSettl	Cash settlement
13	SecurityLending	Security lending. Fee that the borrower of the security or commodity pays to the lender. The basis rate is specified in PaymentFixedRate(43097). A security lending fee payment may be periodic, in which case specify PaymentFrequencyPeriod(43102) and PaymentFrequencyUnit(43103).

Code	Name	Description
14	Rebate	Rebate. For contracts calling for rebate payment(s), e.g. Securities Lending, normally specified as a fixed or floating rate rather than a fixed amount. A rebate payment may be periodic, in which case specify PaymentFrequencyPeriod(43102) and PaymentFrequencyUnit(43103).
99	Other	Other

Used in groups: **PaymentGrp**

### 180.2.4161 PaymentUnitOfMeasure

Used to express the unit of measure (UOM) of the payment amount if not in the currency of the trade.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day

Code	Name	Description
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs

Code	Name	Description
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: **PaymentGrp**

**180.2.4162 PayReportID**

Unique ID of the PayManagementReport(35=EA) message.

Type: **String**

Used in messages: **PayManagementReport**, **PayManagementReportAck**

**180.2.4163 PayReportRefID**

Reference identifier of the PayManagementReport(35=EA). To be used with PayReportTransType(2804)=1 (Replace).

Type: **String**

Used in messages: **PayManagementReport**

**180.2.4164 PayReportStatus**

Identifies status of the payment report.

Type: **int**

Allowed values in PayReportStatusCodeSet:

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected
3	Disputed	Disputed. Used when there is some type of mismatch that can be resolved.

Used in messages: **PayManagementReportAck**

**180.2.4165 PayReportTransType**

Identifies the message transaction type.

Type: **int**

Allowed values in PayReportTransTypeCodeSet:



Code	Name	Description
0	New	New
1	Replace	Replace
2	Status	Status. An unsolicited message reporting the current progress status of the payment.

---

Used in messages: [PayManagementReport](#)

#### **180.2.4166 PayRequestID**

Unique ID of the PayManagementRequest(35=DY) message.

Type: [String](#)

Used in messages: [PayManagementReport](#), [PayManagementRequest](#), [PayManagementRequestAck](#)

#### **180.2.4167 PayRequestRefID**

Reference identifier of the PayManagementRequest(35=DY). To be used with PayRequest-TransType(2811)=1 (Cancel).

Type: [String](#)

Used in messages: [PayManagementRequest](#)

#### **180.2.4168 PayRequestStatus**

Identifies status of the request being responded to.

Type: [int](#)

Allowed values in PayRequestStatusCodeSet:

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected
3	Disputed	Disputed. Used when there is some type of mismatch that can be resolved.

---

Used in messages: [PayManagementReport](#), [PayManagementRequestAck](#)

#### **180.2.4169 PayRequestTransType**

Identifies the message transaction type.

Type: [int](#)

Allowed values in PayRequestTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Cancel	Cancel

Used in messages: [PayManagementRequest](#)

#### **180.2.4170 PctAtRisk**

Percent at risk due to lowest possible call.

Type: [Percentage](#)

Used in components: [InstrumentExtension](#)

#### **180.2.4171 PeggedPrice**

The price the order is currently pegged at

Type: [Price](#)

Used in messages: [ExecutionReport](#)

#### **180.2.4172 PeggedRefPrice**

The value of the reference price that the order is pegged to.  $\text{PeggedRefPrice} + \text{PegOffsetValue} (211) = \text{PeggedPrice} (839)$  unless the limit price (44, Price) is breached. The values may not be exact due to rounding.

Type: [Price](#)

Used in messages: [ExecutionReport](#)

### 180.2.4173 PegInstructions

The Peg Instructions component block is used to tie the price of a security to a market event such as opening price, mid-price, best price. The Peg Instructions block may also be used to tie the price to the behavior of a related security.

Name	Mult.	Type	Description
PegOffsetValue	[0..1]	float	Amount (signed) added to the peg for a pegged order in the context of the PegOffsetType
PegPriceType	[0..1]	CodeSet	Defines the type of peg.
PegMoveType	[0..1]	CodeSet	Describes whether peg is static/fixed or floats
PegOffsetType	[0..1]	CodeSet	Type of Peg Offset (e.g. price offset, tick offset etc)
PegLimitType	[0..1]	CodeSet	Specifies nature of resulting pegged price (e.g. or better limit, strict limit etc)
PegRoundDirection	[0..1]	CodeSet	If the calculated peg price is not a valid tick price, specifies how to round the price (e.g. be more or less aggressive)
PegScope	[0..1]	CodeSet	The scope of the "related to" price of the peg (e.g. local, global etc)
PegSecurityIDSource	[0..1]	CodeSet	Required if PegSecurityID is specified.
PegSecurityID	[0..1]	String	Requires PegSecurityIDSource if specified.
PegSymbol	[0..1]	String	
PegSecurityDesc	[0..1]	String	

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.4174 PegLimitType

Type of Peg Limit

Type: [int](#)

Allowed values in PegLimitTypeCodeSet:

Code	Name	Description
0	OrBetter	Or better (default) - price improvement allowed
1	Strict	Strict - limit is a strict limit
2	OrWorse	Or worse - for a buy the peg limit is a minimum and for a sell the peg limit is a maximum (for use for orders which have a price range)

Used in components: [PegInstructions](#)

#### 180.2.4175 PegMoveType

Describes whether peg is static or floats

Type: [int](#)

Allowed values in PegMoveTypeCodeSet:

Code	Name	Description
0	Floating	Floating (default)
1	Fixed	Fixed

Used in components: [PegInstructions](#)

#### 180.2.4176 PegOffsetType

Type of Peg Offset value

Type: [int](#)

Allowed values in PegOffsetTypeCodeSet:

Code	Name	Description
0	Price	Price (default)
1	BasisPoints	Basis Points
2	Ticks	Ticks
3	PriceTier	Price Tier / Level
4	Percentage	Percentage

Used in components: [PegInstructions](#)

#### **180.2.4177 PegOffsetValue**

Amount (signed) added to the peg for a pegged order in the context of the PegOffsetType (836)  
(Prior to FIX 4.4 this field was of type PriceOffset)

Type: [float](#)

Used in components: [PegInstructions](#)

#### **180.2.4178 PegPriceType**

Defines the type of peg.

Type: [int](#)

Allowed values in PegPriceTypeCodeSet:

Code	Name	Description
1	LastPeg	Last peg (last sale)
2	MidPricePeg	Mid-price peg (midprice of inside quote)
3	OpeningPeg	Opening peg
4	MarketPeg	Market peg
5	PrimaryPeg	Primary peg (primary market - buy at bid or sell at offer)
7	PegToVWAP	Peg to VWAP
8	TrailingStopPeg	Trailing Stop Peg
9	PegToLimitPrice	Peg to Limit Price
10	ShortSaleMinPricePeg	Short sale minimum price Peg. Short sale minimum price Peg (published price that a short sell order must meet in order to comply with regulatory requirements, e.g. SEC uptick rules).

Used in components: [PegInstructions](#)

#### **180.2.4179 PegRoundDirection**

If the calculated peg price is not a valid tick price, specifies whether to round the price to be more or less aggressive

Type: **int**

Allowed values in PegRoundDirectionCodeSet:

Code	Name	Description
1	MoreAggressive	More aggressive - on a buy order round the price up to the nearest tick; on a sell order round down to the nearest tick
2	MorePassive	More passive - on a buy order round down to the nearest tick; on a sell order round up to the nearest tick

Used in components: **PegInstructions**

#### **180.2.4180 PegScope**

The scope of the peg

Type: **int**

Allowed values in PegScopeCodeSet:

Code	Name	Description
1	Local	Local (Exchange, ECN, ATS)
2	National	National
3	Global	Global
4	NationalExcludingLocal	National excluding local

Used in components: **PegInstructions**

#### **180.2.4181 PegSecurityDesc**

Security description of the security off whose prices the order will Peg.

Type: **String**

Used in components: **PegInstructions**

**180.2.4182 PegSecurityID**

Defines the identity of the security off whose prices the order will peg.

Type: **String**

Used in components: **PegInstructions**

**180.2.4183 PegSecurityIDSource**

Defines the identity of the security off whose prices the order will peg. Same values as SecurityIDSource (22)

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))

Code	Name	Description
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDASCommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [PegInstructions](#)

#### 180.2.4184 PegSymbol

Defines the common, 'human understood' representation of the security off whose prices the order will Peg.

Type: [String](#)

Used in components: [PegInstructions](#)

#### 180.2.4185 PhysicalSettlBusinessDays

The number of business days used in the determination of physical settlement. Its precise meaning depends on the context in which this element is used.

Type: [int](#)

Used in groups: [PhysicalSettlTermGrp](#)



**180.2.4186 PhysicalSettlCurrency**

Specifies the currency of physical settlement. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **PhysicalSettlTermGrp**

**180.2.4187 PhysicalSettlDeliverableObligationGrp**

The PhysicalSettlDeliverableObligationGrp is a repeating component within the PhysicalSettlTermGrp component used to report CDS physical settlement delivery obligations.

Name	Mult.	Type	Description
NoPhysicalSettlDeliverableObligations	[1..1]	NumInGroup	
PhysicalSettlDeliverableObligation-Type	[0..1]	String	Required if NoPhysicalSettlDeliverableObligations (40209) > 0.
PhysicalSettlDeliverableObligationValue	[0..1]	String	

Used in groups: **PhysicalSettlTermGrp**

**180.2.4188 PhysicalSettlDeliverableObligationType**

Specifies the type of deliverable obligation applicable for physical settlement. See <http://www.fixtradingcommunity.org> for code list for applicable deliverable obligation types.

Type: **String**

Used in groups: **PhysicalSettlDeliverableObligationGrp**

**180.2.4189 PhysicalSettlDeliverableObligationValue**

Physical settlement deliverable obligation value appropriate to PhysicalSettlDeliverableObligationType(40210). See [http://www.fixtradingcommunity.org/codelists#Deliverable\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Deliverable_Obligation_Types) for applicable obligation type values.

Type: **String**

Used in groups: **PhysicalSettlDeliverableObligationGrp**

**180.2.4190 PhysicalSettlMaximumBusinessDays**

A maximum number of business days. Its precise meaning depends on the context in which this element is used. Intended to be used to limit a particular ISDA fallback provision.

Type: **int**

Used in groups: **PhysicalSettlTermGrp**

**180.2.4191 PhysicalSettlTermGrp**

The PhysicalSettlTermGrp is a repeating component within the Instrument component used to report physical settlement terms referenced from UnderlyingInstrument component.

Name	Mult.	Type	Description
NoPhysicalSettlTerms	[1..1]	NumInGroup	
PhysicalSettlDeliverableObligationGrp	[0..*]	Group	Required if NoPhysicalSettlTerms(40204) > 0.
PhysicalSettlCurrency	[0..1]	Currency	
PhysicalSettlBusinessDays	[0..1]	int	
PhysicalSettlMaximumBusinessDays	[0..1]	int	
PhysicalSettlTermXID	[0..1]	XID	

Used in components: **Instrument**

**180.2.4192 PhysicalSettlTermXID**

A named string value referenced by UnderlyingSettlTermXIDRef(41315).

Type: **XID**

Used in groups: **PhysicalSettlTermGrp**

**180.2.4193 Pool**

For Fixed Income, identifies MBS / ABS pool.

Type: **String**

Used in components: **Instrument**

**180.2.4194 PosAmt**

Position amount

Type: **Amt**

Used in groups: **PositionAmountData**

**180.2.4195 PosAmtMarketID**

Market associated with the position amount.

Type: **String**

Used in groups: **PositionAmountData**

**180.2.4196 PosAmtMarketSegmentID**

Market segment associated with the position amount.

Type: **String**

Used in groups: **PositionAmountData**

**180.2.4197 PosAmtPrice**

The price used to calculate the PosAmt(708).

Type: **Price**

Used in groups: **PositionAmountData**

**180.2.4198 PosAmtPriceType**

Specifies the type of price for PosAmtPrice(2876).

Type: **int**

Allowed values in PriceTypeCodeSet:

---

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)

---

Code	Name	Description
2	PerUnit	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points spread). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	Yield	Yield
10	FixedCabinetTradePrice	Fixed cabinet trade price (primarily for listed futures and options)
11	VariableCabinetTradePrice	Variable cabinet trade price (primarily for listed futures and options)
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example, the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)
22	BasisPoints	Basis points. When the price is not spread based.
23	UpfrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageNotional	Percentage of notional

Used in groups: **PositionAmountData**

**180.2.4199 PosAmtReason**

Specifies the reason for an amount type when reported on a position. Useful when multiple instances of the same amount type are reported.

Type: **int**

Allowed values in PosAmtReasonCodeSet:

Code	Name	Description
0	OptionsSettlement	Options settlement
1	PendingErosionAdjustment	Pending erosion adjustment
2	FinalErosionAdjustment	Final erosion adjustment
3	TearUpCouponAmount	Tear-up coupon amount
4	PriceAlignmentInterest	Price alignment interest. To minimize the impact of daily cash variation margin payments on the pricing of interest rate swaps, the Clearing House will charge interest on cumulative variation margin received and pay interest on cumulative variation margin paid in respect of these instruments. This interest element is known as price alignment interest.
5	DeliveryInvoiceCharges	Delivery invoice charges
6	DeliveryStorageCharges	Delivery storage charges

Used in groups: **PositionAmountData**

**180.2.4200 PosAmtStreamDesc**

Corresponds to the value in StreamDesc(40051) in the StreamGrp component.

Type: **String**

Used in groups: **PositionAmountData**

**180.2.4201 PosAmtType**

Type of Position amount

Type: **String**

Allowed values in PosAmtTypeCodeSet:

Code	Name	Description
CASH	CashAmount	Cash amount (corporate event)
CRES	CashResidualAmount	Cash residual amount
FMTM	FinalMarkToMarketAmount	Final mark-to-market amount
IMTM	IncrementalMarkToMarketAmount	Incremental mark-to-market
PREM	PremiumAmount	Premium amount
SMTM	StartOfDayMarkToMarketAmount	Start of day mark-to-market
TVAR	TradeVariationAmount	Trade variation amount
VADJ	ValueAdjustedAmount	Value adjusted amount
SETL	SettlementValue	Settlement value
ICPN	InitialTradeCouponAmount	Initial trade coupon amount
ACPN	AccruedCouponAmount	Accrued coupon amount
CPN	CouponAmount	Coupon amount
IACPN	IncrementalAccruedCoupon	Incremental accrued coupon
CMTM	CollateralizedMarkToMarket	Collateralized mark-to-market
ICMTM	IncrementalCollateralizedMark-ToMarket	Incremental collateralized mark-to-market
DLV	CompensationAmount	Compensation amount
BANK	TotalBankedAmount	Total banked amount
COLAT	TotalCollateralizedAmount	Total collateralized amount
LSNV	LongPairedSwapNotionalValue	Long paired swap or swaption notional value
SSNV	ShortPairedSwapNotionalValue	Short paired swap or swaption notional value
SACPN	StartOfDayAccruedCoupon	Start-of-day accrued coupon
NPV	NetPresentValue	Net present value
SNPV	StartOfDayNetPresentValue	Start-of-day net present value
NCF	NetCashFlow	Net cash flow
PVFEEs	PresentValueOfFees	Present value of all fees
PV01	PresentValueOneBasisPoints	Present value of one basis points. Change in value if yield curve shifts 0.01%.
5YREN	FiveYearEquivalentNotional	The five year equivalent notional amount
UMTM	UndiscountedMarkToMarket	Undiscounted mark-to-market
MTD	MarkToModel	Mark-to-model
VMTM	MarkToMarketVariance	Mark-to-market variance
VMTD	MarkToModelVariance	Mark-to-model variance
UPFRNT	UpfrontPayment	Upfront payment

Code	Name	Description
ENDV	EndVale	End value. Principal amount of a securities financing transaction on maturity date.
MGNLN	OutstandingMarginLoan	Outstanding margin loan. The amount of the outstanding margin loan. In the event that the loan has a short market value, PosAmt(708) would be a negative value.
LNVL	LoanValue	Loan value. The amount of the loan.

Used in groups: **PositionAmountData**

### 180.2.4202 PositionAmountData

The PositionAmountData component block is used to report netted amounts associated with position quantities. In the listed derivatives market the amount is generally expressing a type of futures variation or option premium. In the equities market this may be the net pay or collect on a given position.

Name	Mult.	Type	Description
NoPosAmt	[1..1]	NumInGroup	Number of Position Amount entries
PosAmtType	[0..1]	CodeSet	
PosAmt	[0..1]	Amt	
PosAmtStreamDesc	[0..1]	String	Used when the PosAmt(708) value corresponds to a specific stream in of a swap.
PositionCurrency	[0..1]	String	
PositionCurrencyCodeSource	[0..1]	CodeSet	
PositionFXRate	[0..1]	float	
PositionFXRateCalc	[0..1]	CodeSet	
PosAmtReason	[0..1]	CodeSet	
PosAmtMarketSegmentID	[0..1]	String	
PosAmtMarketID	[0..1]	String	
PosAmtPrice	[0..1]	Price	
PosAmtPriceType	[0..1]	CodeSet	

Used in messages: **AccountSummaryReport**, **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **AssignmentReport**, **PositionMaintenanceReport**, **PositionMaintenanceRequest**, **PositionReport**, **PositionTransferInstruction**, **PositionTransferReport**, **TradeCaptureReport**, **TradeCaptureReportAck**

**180.2.4203 PositionCapacity**

Used to describe the ownership of the position.

Type: **int**

Allowed values in PositionCapacityCodeSet:

Code	Name	Description
0	Principal	Principal
1	Agent	Agent
2	Customer	Customer
3	Counterparty	Counterparty

Used in messages: **PositionMaintenanceReport**, **PositionReport**

**180.2.4204 PositionContingentPrice**

Risk adjusted price used to calculate variation margin on a position.

Type: **Price**

Used in messages: **AssignmentReport**, **PositionReport**

**180.2.4205 PositionCurrency**

The Currency in which the position Amount is denominated

Type: **String**

Used in groups: **PositionAmountData**

**180.2.4206 PositionCurrencyCodeSource**

Identifies class or source of the PositionCurrency(1055) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:



Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **PositionAmountData**

#### 180.2.4207 PositionEffect

Indicates whether the resulting position after a trade should be an opening position or closing position. Used for omnibus accounting - where accounts are held on a gross basis instead of being netted together.

Type: **char**

Allowed values in PositionEffectCodeSet:

Code	Name	Description
C	Close	Close
F	FIFO	FIFO
O	Open	Open
R	Rolled	Rolled
N	CloseButNotifyOnOpen	Close but notify on open
D	Default	Default

Used in groups: **ListOrdGrp**, **SideCrossOrdModGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.4208 PositionFXRate**

Foreign exchange rate used to compute the PosAmt(708) from the PositionCurrency(1055) and the Currency (15).

Type: **float**

Used in groups: **PositionAmountData**

**180.2.4209 PositionFXRateCalc**

Specifies whether or not PositionFXRate(2097) should be multiplied or divided.

Type: **char**

Allowed values in UnderlyingFXRateCalcCodeSet:

Code	Name	Description
D	Divide	Divide
M	Multiply	Multiply

Used in groups: **PositionAmountData**

**180.2.4210 PositionID**

Unique identifier for a position entity. Refer to PosMaintRptID(721) for a unique identifier of a position report message.

Type: **String**

Used in messages: **PositionMaintenanceReport**, **PositionReport**

**180.2.4211 PositionLimit**

Position Limit for a given exchange-traded product.

Type: **int**

Used in components: **Instrument**

**180.2.4212 PositionQty**

The PositionQty component block specifies the various types of position quantity in the position life-cycle including start-of-day, intraday, trade, adjustments, and end-of-day position quantities. Quantities are expressed in terms of long and short quantities.

Name	Mult.	Type	Description
NoPositions	[1..1]	NumInGroup	
PosType	[0..1]	CodeSet	Required if NoPositions > 1
LongQty	[0..1]	Qty	
ShortQty	[0..1]	Qty	
CoveredQty	[0..1]	Qty	Short quantity that is considered covered, e.g. used for short option position
PosQtyStatus	[0..1]	CodeSet	
QuantityDate	[0..1]	LocalMktDate	Date associated with the quantity being reported
PosQtyUnitOfMeasure	[0..1]	CodeSet	
PosQtyUnitOfMeasureCurrency	[0..1]	Currency	
PosQtyUnitOfMeasureCurrencyCodeSource	[0..1]	CodeSet	
NestedParties	[0..*]	Group	Optional repeating group - used to associate or distribute position to a specific party other than the party that currently owns the position.

Used in messages: [AdjustedPositionReport](#), [AssignmentReport](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [PositionReport](#), [PositionTransferInstruction](#), [PositionTransferReport](#)

**180.2.4213 PosMaintAction**

Maintenance Action to be performed.

Type: [int](#)

Allowed values in PosMaintActionCodeSet:

Code	Name	Description
1	New	New. Used to increment the overall transaction quantity.
2	Replace	Replace. Used to override the overall transaction quantity or specific add messages based on the reference ID.

Code	Name	Description
3	Cancel	Cancel. Used to remove the overall transaction quantity or specific add messages based on the reference ID.
4	Reverse	Reverse. Used to completely back-out the transaction such that the transaction never existed.

Used in messages: [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#)

#### **180.2.4214 PosMaintResult**

Result of Position Maintenance Request.

Type: [int](#)

Allowed values in PosMaintResultCodeSet:

Code	Name	Description
0	SuccessfulCompletion	Successful Completion - no warnings or errors
1	Rejected	Rejected
99	Other	Other

Used in messages: [PositionMaintenanceReport](#)

#### **180.2.4215 PosMaintRptID**

Unique identifier for this position report

Type: [String](#)

Used in messages: [AdjustedPositionReport](#), [PositionMaintenanceReport](#), [PositionReport](#), [RequestFor-PositionsAck](#)

#### **180.2.4216 PosMaintRptRefID**

Reference to a PosMaintRptID (721) from a previous Position Maintenance Report that is being replaced or canceled.

Type: [String](#)

Used in messages: [AdjustedPositionReport](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#)

#### **180.2.4217 PosMaintStatus**

Status of Position Maintenance Request

Type: [int](#)

Allowed values in PosMaintStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithWarnings	Accepted With Warnings
2	Rejected	Rejected
3	Completed	Completed
4	CompletedWithWarnings	Completed With Warnings

Used in messages: [PositionMaintenanceReport](#)

#### **180.2.4218 PosQtyStatus**

Status of this position.

Type: [int](#)

Allowed values in PosQtyStatusCodeSet:

Code	Name	Description
0	Submitted	Submitted
1	Accepted	Accepted
2	Rejected	Rejected

Used in groups: [PositionQty](#), [TradePositionQty](#)

**180.2.4219 PosQtyUnitOfMeasure**

Indicates the unit of measure of the position quantity when not expressed in contracts.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: **PositionQty**

#### **180.2.4220 PosQtyUnitOfMeasureCurrency**

Indicates the currency of the unit of measure if position quantity is expressed in valuation rather than contracts. Conditionally required when PosQtyUnitOfMeasure(1836)=Ccy.

Type: **Currency**

Used in groups: **PositionQty**

#### **180.2.4221 PosQtyUnitOfMeasureCurrencyCodeSource**

Identifies class or source of the PosQtyUnitOfMeasureCurrency(1835) value.



Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **PositionQty**

#### **180.2.4222 PosReportAction**

Indicates action that triggered the Position Report.

Type: **int**

Allowed values in PosMaintActionCodeSet:

Code	Name	Description
1	New	New. Used to increment the overall transaction quantity.
2	Replace	Replace. Used to override the overall transaction quantity or specific add messages based on the reference ID.
3	Cancel	Cancel. Used to remove the overall transaction quantity or specific add messages based on the reference ID.
4	Reverse	Reverse. Used to completely back-out the transaction such that the transaction never existed.

Used in messages: **PositionReport**

#### **180.2.4223 PosReqID**

Unique identifier for the position maintenance request as assigned by the submitter

Type: **String**

Used in messages: **AssignmentReport**, **PositionMaintenanceReport**, **PositionMaintenanceRequest**, **PositionReport**, **RequestForPositions**, **RequestForPositionsAck**

### **180.2.4224 PosReqResult**

Result of Request for Positions.

Type: **int**

Allowed values in PosReqResultCodeSet:

Code	Name	Description
0	ValidRequest	Valid request
1	InvalidOrUnsupportedRequest	Invalid or unsupported request
2	NoPositionsFoundThatMatchCriteria	No positions found that match criteria
3	NotAuthorizedToRequestPositions	Not authorized to request positions
4	RequestForPositionNotSupported	Request for position not supported
99	Other	Other. Use Text(58) for further explanation.

Used in messages: **PositionReport**, **RequestForPositionsAck**

### **180.2.4225 PosReqStatus**

Status of Request for Positions

Type: **int**

Allowed values in PosReqStatusCodeSet:

Code	Name	Description
0	Completed	Completed
1	CompletedWithWarnings	Completed With Warnings
2	Rejected	Rejected

Used in messages: **RequestForPositionsAck**

**180.2.4226 PosReqType**

Used to specify the type of position request being made.

Type: **int**

Allowed values in PosReqTypeCodeSet:

Code	Name	Description
0	Positions	Positions
1	Trades	Trades
2	Exercises	Exercises
3	Assignments	Assignments
4	SettlementActivity	Settlement Activity
5	BackoutMessage	Backout Message
6	DeltaPositions	Delta Positions
7	NetPosition	Net Position
8	LargePositionsReporting	Large Positions Reporting
9	ExercisePositionReportingSubmission	Exercise Position Reporting Submission
10	PositionLimitReportingSubmitting	Position Limit Reporting Submission

Used in messages: **AdjustedPositionReport**, **PositionReport**, **RequestForPositions**, **RequestForPositionsAck**

**180.2.4227 PossDupFlag**

Indicates possible retransmission of message with this sequence number

Type: **Boolean**

Allowed values in PossDupFlagCodeSet:

Code	Name	Description
N	OriginalTransmission	Original transmission
Y	PossibleDuplicate	Possible duplicate

Used in components: **StandardHeader**

**180.2.4228 PossResend**

Indicates that message may contain information that has been sent under another sequence number.

Type: **Boolean**

Allowed values in PossResendCodeSet:

Code	Name	Description
N	OriginalTransmission	Original Transmission
Y	PossibleResend	Possible Resend

Used in components: **StandardHeader**

**180.2.4229 PosTransType**

Identifies the type of position transaction.

Type: **int**

Allowed values in PosTransTypeCodeSet:

Code	Name	Description
1	Exercise	Exercise
2	DoNotExercise	Do not exercise
3	PositionAdjustment	Position adjustment
4	PositionChangeSubmission	Position change submission / margin disposition
5	Pledge	Pledge
6	LargeTraderSubmission	Large trader submission
7	LargePositionsReportingSubmission	Large positions reporting submission
8	LongHoldings	Long holdings
9	InternalTransfer	Internal transfer. Changes due to transfer of positions within a firm.
10	TransferOfFirm	Transfer of firm. Changes due to transfer of all positions of a firm.
11	ExternalTransfer	External transfer. Changes due to transfer of positions between firms.
12	CorporateAction	Corporate action

Code	Name	Description
13	Notification	Notification. Information about a position that has been chosen for assignment.
14	PositionCreation	Position creation. Changes due to an option exercise causing a new futures position to be created.
15	Closeout	Close out. Information about a position that has been closed out.
16	Reopen	Reopen. Information about a position that has been reopened, i.e. reversal of a close out.

Used in messages: [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#)

#### **180.2.4230 PostTradePaymentAccount**

The cash account on the books of the receiver of the request or the sender of the report to be debited or credited.

Type: [String](#)

Used in components: [PostTradePayment](#)

#### **180.2.4231 PostTradePaymentAmount**

The payment amount for the specified PostTradePaymentType(2824).

Type: [Amt](#)

Used in components: [PostTradePayment](#)

#### **180.2.4232 PostTradePaymentCalculationDate**

The (actual) date the periodic payments calculations are made.

Type: [LocalMktDate](#)

Used in components: [PostTradePayment](#)

#### **180.2.4233 PostTradePayment**

This component specifies the details of a payment between the parties involved.

Name	Mult.	Type	Description
PostTradePaymentType	[1..1]	String	
PostTradePaymentAmount	[1..1]	Amt	
PostTradePaymentCurrency	[0..1]	Currency	
PostTradePaymentCurrencyCodeSource	[0..1]	CodeSet	
PostTradePaymentCalculationDate	[1..1]	LocalMktDate	The date payment calculations are made. This may be earlier than the date in ClearingBusinessDate(715). When the report is sent unsolicited, this is the payment calculation date as determined by report sender.
PostTradePaymentValueDate	[1..1]	LocalMktDate	The date the payment is legally confirmed to settle.
PostTradePaymentFinalValueDate	[0..1]	LocalMktDate	The actual payment date in the event it differs from the date specified in PostTradePaymentValueDate(2826).
PostTradePaymentDebitOrCredit	[1..1]	CodeSet	
PostTradePaymentAccount	[1..1]	String	
PostTradePaymentID	[0..1]	String	
PostTradePaymentDesc	[0..1]	String	
EncodedPostTradePaymentDescLen	[0..1]	Length	Must be set if EncodedPostTradePaymentDesc(2814) field is specified and must immediately precede it.
EncodedPostTradePaymentDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the PostTradePaymentDesc(2820) field in the encoded format specified via the MessageEncoding(347) field.
PostTradePaymentLinkID	[0..1]	String	
PostTradePaymentStatus	[0..1]	CodeSet	Used when PayReportTransType(2804)=2 (Status) to report actual payment status from payment service (i.e. after payment or remittance instruction with payment service).

Used in messages: [PayManagementReport](#), [PayManagementRequest](#)

### 180.2.4234 PostTradePaymentCurrency

Specifies the currency in which PostTradePaymentAmount(2817) is denominated.

PostTradePaymentCurrencyCodeSource(2956) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in components: **PostTradePayment**

#### **180.2.4235 PostTradePaymentCurrencyCodeSource**

Identifies class or source of the PostTradePaymentCurrency(2818) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **PostTradePayment**

#### **180.2.4236 PostTradePaymentDebitOrCredit**

Payment side of this individual payment from the requesting firm's perspective.

Type: **int**

Allowed values in PostTradePaymentDebitOrCreditCodeSet:

Code	Name	Description
0	DebitPay	Debit / Pay
1	CreditReceive	Credit / Receive

Used in components: **PostTradePayment**

**180.2.4237 PostTradePaymentDesc**

A short descriptive name given to the payment, e.g. Premium, Upfront, etc. The description may be used as reference.

Type: **String**

Used in components: **PostTradePayment**

**180.2.4238 PostTradePaymentFinalValueDate**

The actual or final payment date on which the payment was made.

Type: **LocalMktDate**

Used in components: **PostTradePayment**

**180.2.4239 PostTradePaymentID**

The identifier for the individual payment.

Type: **String**

Used in components: **PostTradePayment**

**180.2.4240 PostTradePaymentLinkID**

Used to link a group of payments together, e.g. cross-currency payments associated with a swap.

Type: **String**

Used in components: **PostTradePayment**

**180.2.4241 PostTradePaymentStatus**

Used to indicate the status of a post-trade payment.

Type: **int**

Allowed values in PostTradePaymentStatusCodeSet:



Code	Name	Description
0	New	New. Payment is awaiting confirmation from the recipient.
1	Initiated	Initiated. Payment is confirmed by the recipient and has been scheduled.
2	Pending	Pending. Payment has been instructed to the payment service but status is unknown.
3	Confirmed	Confirmed. Payment is complete and confirmed by the payment service.
4	Rejected	Rejected. Payment was rejected by the payment service.

Used in components: **PostTradePayment**

#### **180.2.4242 PostTradePaymentType**

Type of post-trade payment.

See ISITC "Payments Cash Purpose Codes" for list of payment type codes to use available at <https://isitc.org/market-practices/reference-data-and-standards-market-practice> and select "ISITC Classification Code List".

Type: **String**

Used in components: **PostTradePayment**

#### **180.2.4243 PostTradePaymentValueDate**

The adjusted (for holidays and other non-business days) payment date on which the payment is expected to settle.

Type: **LocalMktDate**

Used in components: **PostTradePayment**

#### **180.2.4244 PosType**

Used to identify the type of quantity that is being returned.

Type: **String**

Allowed values in PosTypeCodeSet:

Code	Name	Description
ALC	AllocationTradeQty	Allocation Trade Qty
AS	OptionAssignment	Option Assignment
ASF	AsOfTradeQty	As-of Trade Qty
DLV	DeliveryQty	Delivery Qty
ETR	ElectronicTradeQty	Electronic Trade Qty
EX	OptionExerciseQty	Option Exercise Qty
FIN	EndOfDayQty	End-of-Day Qty
IAS	IntraSpreadQty	Intra-spread Qty
IES	InterSpreadQty	Inter-spread Qty
PA	AdjustmentQty	Adjustment Qty
PIT	PitTradeQty	Pit Trade Qty
SOD	StartOfDayQty	Start-of-Day Qty
SPL	IntegralSplit	Integral Split
TA	TransactionFromAssignment	Transaction from Assignment
TOT	TotalTransactionQty	Total Transaction Qty
TQ	TransactionQuantity	Transaction Quantity
TRF	TransferTradeQty	Transfer Trade Qty
TX	TransactionFromExercise	Transaction from Exercise
XM	CrossMarginQty	Cross Margin Qty
RCV	ReceiveQuantity	Receive Quantity
CAA	CorporateActionAdjustment	Corporate Action Adjustment
DN	DeliveryNoticeQty	Delivery Notice Qty
EP	ExchangeForPhysicalQty	Exchange for Physical Qty
PNTN	PrivatelyNegotiatedTradeQty	Privately negotiated Trade Qty (Non-regulated)
CEA	CreditEventAdjustment	Credit Event Adjustment
DLT	NetDeltaQty	Net Delta Qty
SEA	SuccessionEventAdjustment	Succession Event Adjustment
NET	NetQty	Net Qty
GRS	GrossQty	Gross Qty
ITD	IntradayQty	Intraday Qty
NDAS	GrossLongNonDeltaAdjustedSwap- tionPosition	Gross non-delta-adjusted swaption position
DAS	LongDeltaAdjustedPairedSwaption- Position	Delta-adjusted paired swaption position

Code	Name	Description
EXP	ExpiringQuantity	Expiring quantity. The position quantity on expiration day after the application of trade and post trade activity, but prior to the application of exercises and assignments.
UNEX	QuantityNotExercised	Quantity not exercised. The exercise quantity requested that was not allowed, e.g., the exercise quantity requested that exceeded the final long position.
REQ	RequestedExerciseQuantity	Requested exercise quantity. The exercise quantity requested. It may differ from the exercise quantity if it exceeds the final long position.
CFE	CashFuturesEquivalentQuantity	Cash futures equivalent quantity
SECLN	LoanOrBorrowedQuantity	Loan or borrowed quantity. The number of shares, par value of bonds or commodity contracts on loan or borrowed.

Used in groups: [PositionQty](#), [TradePositionQty](#)

#### 180.2.4245 PosUndInstrmtGrp

Name	Mult.	Type	Description
<a href="#">NoUnderlyings</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingInstrument</a>	[0..1]	Component	Insert here the set of "Underlying Instrument" (underlying symbology) fields defined in "Common Components of Application Messages". Required if NoUnderlyings > 0
<a href="#">UnderlyingSettlPrice</a>	[0..1]	Price	
<a href="#">UnderlyingSettlPriceType</a>	[0..1]	CodeSet	Values = Final, Theoretical
<a href="#">UnderlyingDeliveryAmount</a>	[0..1]	Amt	
<a href="#">UnderlyingAmount</a>	[0..*]	Group	Insert here the set of "Underlying Amount" fields defined in "Common Components of Application Messages"

Used in messages: [PositionReport](#)

#### 180.2.4246 PreAllocGrp

Name	Mult.	Type	Description
NoAllocs	[1..1]	NumInGroup	Number of repeating groups for pre-trade allocation
AllocAccount	[0..1]	String	Required if NoAllocs > 0. Must be first field in repeating group.
AllocAcctIDSource	[0..1]	CodeSet	
AllocSettlCurrency	[0..1]	Currency	
AllocSettlCurrencyCodeSource	[0..1]	CodeSet	
IndividualAllocID	[0..1]	String	
AllocLegRefID	[0..1]	String	The field may not be used in NewOrderSingle(35=D), OrderCancelReplaceRequest(35=G), NewOrderList(35=E) or any other message where there are no legs.
NestedParties	[0..*]	Group	Insert here the set of "Nested Parties" (firm identification "nested" within additional repeating group) fields defined in "Common Components of Application Messages". Used for NestedPartyRole=Clearing Firm
AllocHandlInst	[0..1]	CodeSet	
AllocQty	[0..1]	Qty	
CustodialLotID	[0..1]	String	Only used for specific lot trades.
VersusPurchaseDate	[0..1]	LocalMktDate	Only used for specific lot trades. If this field is used, either VersusPurchasePrice(1754) or CurrentCostBasis(1755) should be specified.
VersusPurchasePrice	[0..1]	Price	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified.
CurrentCostBasis	[0..1]	Amt	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified

Used in groups: ListOrdGrp, SideCrossOrdModGrp

Used in messages: ExecutionReport, NewOrderSingle, OrderCancelReplaceRequest

### 180.2.4247 PreallocMethod

Indicates the method of preallocation.

Type: **char**

Allowed values in PreallocMethodCodeSet:

Code	Name	Description
0	ProRata	Pro rata
1	DoNotProRata	Do not pro-rata - discuss first

Used in groups: **ListOrdGrp**, **SideCrossOrdModGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

#### 180.2.4248 PreAllocMlegGrp

Name	Mult.	Type	Description
<b>NoAllocs</b>	[1..1]	NumInGroup	Number of repeating groups for pre-trade allocation
<b>AllocAccount</b>	[0..1]	String	Required if NoAllocs > 0. Must be first field in repeating group.
<b>AllocAcctIDSource</b>	[0..1]	CodeSet	
<b>AllocSettlCurrency</b>	[0..1]	Currency	
<b>AllocSettlCurrencyCodeSource</b>	[0..1]	CodeSet	
<b>IndividualAllocID</b>	[0..1]	String	
<b>AllocLegRefID</b>	[0..1]	String	
<b>NestedParties3</b>	[0..*]	Group	Insert here the set of "NestedParties3" (firm identification "nested" within additional repeating group) fields defined in "Common Components of Application Messages"
<b>AllocQty</b>	[0..1]	Qty	
<b>CustodialLotID</b>	[0..1]	String	Only used for specific lot trades.
<b>VersusPurchaseDate</b>	[0..1]	LocalMktDate	Only used for specific lot trades. If this field is used, either VersusPurchasePrice(1754) or CurrentCostBasis(1755) should be specified.
<b>VersusPurchasePrice</b>	[0..1]	Price	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified.

Name	Mult.	Type	Description
CurrentCostBasis	[0..1]	Amt	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified

Used in messages: MultilegOrderCancelReplace, NewOrderMultileg

#### 180.2.4249 PreTradeAnonymity

Allows trader to explicitly request anonymity or disclosure in pre-trade market data feeds. Anonymity is relevant in markets where counterparties are regularly disclosed in order depth feeds. Disclosure is relevant when counterparties are not normally visible.

Type: Boolean

Used in components: TradeReportOrderDetail

Used in groups: ListOrdGrp, SideCrossOrdModGrp

Used in messages: ExecutionReport, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, QuoteRequest, QuoteRequestReject, QuoteResponse

#### 180.2.4250 PrevClosePx

Previous closing price of security.

Type: Price

Used in groups: InstrmtStrkPxGrp, ListOrdGrp, QuotReqGrp, QuotReqRjctGrp, RFQReqGrp

Used in messages: CrossOrderCancelReplaceRequest, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle

#### 180.2.4251 PreviousAdjustedOpenInterest

Previous day's adjusted open interest.

Type: Amt

Used in messages: SecurityDefinition, SecurityDefinitionUpdateReport

**180.2.4252 PreviousAllocGroupID**

When reporting a group change by the central counterparty to allocations of trades for the same instrument traded at the same price this identifies the previous group identifier.

Type: **String**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationReport**

**180.2.4253 PreviousClearingBusinessDate**

The date of the previous clearing business day.

Type: **LocalMktDate**

Used in messages: **PositionMaintenanceReport**, **PositionReport**

**180.2.4254 PreviouslyReported**

Indicates if the transaction was previously reported to the counterparty or market.

Type: **Boolean**

Allowed values in PreviouslyReportedCodeSet:

Code	Name	Description
N	NotReportedToCounterparty	Not reported to counterparty or market. In the context of RTS 13 Article 16 when a trade is reported to more than one "approved publication arrangement" (APA) the original report can be flagged as "original". This is the ESMA "ORGN" flag.
Y	PreviouslyReportedToCounterparty	Previously reported to counterparty or market. In the context of RTS 13 Article 16 when a trade is reported to more than one "approved publication arrangement" (APA) the additional reports need to be flagged as "duplicative" and this flag needs to be present on any occurrence (even when publishing to the market). This is also used for reporting directly to ESMA when the trade has been previously reported. This is the ESMA "DUPL" flag.

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **ExecutionReport**, **TradeCaptureReport**, **TradeCaptureReportAck**

**180.2.4255 PreviousUnadjustedOpenInterest**

Previous day's unadjusted open interest.

Type: **Amt**

Used in messages: **SecurityDefinition**, **SecurityDefinitionUpdateReport**

**180.2.4256 Price**

Price per unit of quantity (e.g. per share)

Type: **Price**

Used in components: **TradeReportOrderDetail**

Used in groups: **BidCompRspGrp**, **InstrmtStrkPxGrp**, **ListOrdGrp**, **OrderEntryAckGrp**, **OrderEntryGrp**, **QuotReqGrp**, **QuotReqRjctGrp**, **SecurityRiskMetricGrp**

Used in messages: **Advertisement**, **CollateralAssignment**, **CollateralInquiry**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**, **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **IOI**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **OrderMassActionReport**, **OrderMassActionRequest**, **QuoteResponse**, **QuoteStatusReport**

**180.2.4257 Price2**

Price of the future part of a F/X swap order.

See Price (44) for description.

Type: **Price**

Used in groups: **ListOrdGrp**, **QuotReqGrp**, **QuotReqRjctGrp**

Used in messages: **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.4258 PriceDelta**

The rate of change in the price of a derivative with respect to the movement in the price of the underlying instrument(s) upon which the derivative instrument price is based.

This value is normally between -1.0 and 1.0.

Type: **float**

Used in groups: **MDFullGrp**, **MDIncGrp**, **SecurityRiskMetricGrp**



Used in messages: [ExecutionReport](#), [PositionReport](#), [TradeCaptureReport](#)

### 180.2.4259 PriceImprovement

Amount of price improvement.

Type: [PriceOffset](#)

Used in messages: [ExecutionReport](#)

### 180.2.4260 PriceLimits

Name	Mult.	Type	Description
<a href="#">PriceLimitType</a>	[0..1]	CodeSet	Describes the how the price limits are expressed
<a href="#">LowLimitPrice</a>	[0..1]	Price	Allowable low limit price for the trading day. A key parameter in validating order price. Used as the lower band for validating order prices. Orders submitted with prices below the lower limit will be rejected
<a href="#">HighLimitPrice</a>	[0..1]	Price	Allowable high limit price for the trading day. A key parameter in validating order price. Used as the upper band for validating order prices. Orders submitted with prices above the upper limit will be rejected
<a href="#">TradingReferencePrice</a>	[0..1]	Price	Reference price for the current trading price range usually representing the mid price between the HighLimitPrice and LowLimitPrice. The value may be the settlement price or closing price of the prior trading day.

Used in components: [BaseTradingRules](#)

Used in groups: [MDFullGrp](#), [MDIncGrp](#)

### 180.2.4261 PriceLimitType

Describes the how the price limits are expressed.

Type: [int](#)

Allowed values in PriceLimitTypeCodeSet:

Code	Name	Description
0	Price	Price (default)
1	Ticks	Ticks
2	Percentage	Percentage

Used in components: [PriceLimits](#)

### 180.2.4262 PriceMarkup

Price offset of the markup denominated in the price type of the trade.

Type: [PriceOffset](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.4263 PriceMovementGrp

The PriceMovementGrp component is a repeatable block intended to contain theoretical profit and loss data at various price movement points account type(s) for which the price movement may apply to.

Name	Mult.	Type	Description
<a href="#">NoPriceMovements</a>	[1..1]	NumInGroup	
<a href="#">PriceMovementValueGrp</a>	[0..*]	Group	Required if <a href="#">NoPriceMovements</a> (1919) > 0.
<a href="#">ClearingAccountTypeGrp</a>	[0..*]	Group	

Used in groups: [SecListGrp](#)

### 180.2.4264 PriceMovementPoint

Price movement point up (positive integer) or down (negative integer) relative to the underlying price of the instrument.

Type: [int](#)

Used in groups: [PriceMovementValueGrp](#)

**180.2.4265 PriceMovementType**

Describes the format of the PriceMovementValue(1921).

Type: **int**

Allowed values in PriceMovementTypeCodeSet:

Code	Name	Description
0	Amount	Amount
1	Percentage	Percentage

Used in groups: **PriceMovementValueGrp**

**180.2.4266 PriceMovementValue**

Value at specific price movement point.

Type: **float**

Used in groups: **PriceMovementValueGrp**

**180.2.4267 PriceMovementValueGrp**

This PriceMovementValueGrp component is a repeatable block that will be utilized to represent a value relative to a specific price movement point.

Name	Mult.	Type	Description
NoPriceMovementValues	[1..1]	NumInGroup	
PriceMovementValue	[0..1]	float	Required if NoPriceMovementValues(1919) > 0.
PriceMovementPoint	[0..1]	int	
PriceMovementType	[0..1]	CodeSet	

Used in groups: **PriceMovementGrp**

**180.2.4268 PricePrecision**

Specifies the price decimal precision of the instrument.

Type: **int**

Used in messages: **TradeAggregationRequest**, **TradeCaptureReport**

**180.2.4269 PriceProtectionScope**

Defines the type of price protection the customer requires on their order.

Type: **char**

Allowed values in PriceProtectionScopeCodeSet:

Code	Name	Description
0	None	None
1	Local	Local (Exchange, ECN, ATS)
2	National	National (Across all national markets)
3	Global	Global (Across all markets)

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**

**180.2.4270 PriceQualifier**

Qualifier for price. May be used when the price needs to be explicitly qualified.

Type: **int**

Allowed values in PriceQualifierCodeSet:

Code	Name	Description
0	AccruedInterestIsFactored	Accrued interest (if any) is factored into the price. The price is either "dirty" or the security is in default or soon to be defaulted. I.e. on fill there will be no separate accrued interest amount. This is often called a "flat" price.

Code	Name	Description
1	TaxIsFactored	Tax is factored into the price. The security's price includes applicable taxes, e.g. Japanese government bonds.
2	BondAmortizationIsFactored	The effect of bond amortization or the floating rate index offset is factored into the price. The security's price includes the effect of bond amortization or a floating rate index. For example this qualifier would apply to the normal pricing of index-linked UK gilt bonds but not to US or EU index-linked bonds.

Used in groups: [PriceQualifierGrp](#)

### 180.2.4271 PriceQualifierGrp

The PriceQualifierGrp component clarifies the composition of the price when standard market practice for the security calls for a price that is atypical when traded in other markets, or when a price can be expressed in more than one way.

Name	Mult.	Type	Description
<a href="#">NoPriceQualifiers</a>	[1..1]	NumInGroup	
<a href="#">PriceQualifier</a>	[0..1]	CodeSet	Required if NoPriceQualifiers(2709) > 0.

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#), [ExecutionAck](#), [ExecutionReport](#), [IOI](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.4272 PriceQuoteCurrency

Default currency in which the price is quoted. Defined at the instrument level. Used in place of Currency (tag 15) to express the currency of a product when the former is implemented as the FX dealt currency.

Type: [Currency](#)

Used in components: [Instrument](#)

**180.2.4273 PriceQuoteCurrencyCodeSource**

Identifies class or source of the PriceQuoteCurrency(1524) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **Instrument**

**180.2.4274 PriceQuoteMethod**

Method for price quotation

Type: **String**

Allowed values in PriceQuoteMethodCodeSet:

Code	Name	Description
STD	Standard	Standard, money per unit of a physical
INX	Index	Index
INT	InterestRateIndex	Interest rate Index
PCTPAR	PercentOfPar	Percent of Par

Used in components: **Instrument**

**180.2.4275 PriceRangePercentage**

Maximum range expressed as percentage.

Type: **Percentage**

Used in groups: **PriceRangeRuleGrp**

### **180.2.4276 PriceRangeProductComplex**

Identifies an entire suite of products in the context of trading rules related to price ranges.

Type: **String**

Used in groups: **PriceRangeRuleGrp**

### **180.2.4277 PriceRangeRuleGrp**

The PriceRangeRulesGrp component is used to specify the price range rules for a given product group or complex.

<b>Name</b>	<b>Mult.</b>	<b>Type</b>	<b>Description</b>
NoPriceRangeRules	[1..1]	NumInGroup	
StartPriceRange	[0..1]	Price	Required if NoPriceRangeRules(2550) > 0.
EndPriceRange	[0..1]	Price	
PriceRangeValue	[0..1]	Price	Mutually exclusive with PriceRangePercentage(2554).
PriceRangePercentage	[0..1]	Percentage	Mutually exclusive with PriceRangeValue(2553).
PriceRangeRuleID	[0..1]	String	Can be used to provide an identifier so that the rule can be reference via the ID elsewhere.
PriceRangeProductComplex	[0..1]	String	Can be used to limit price range to specific product suite.

Used in components: **BaseTradingRules**

### **180.2.4278 PriceRangeRuleID**

Identifier for a price range rule.

Type: **String**

Used in groups: **PriceRangeRuleGrp**

**180.2.4279 PriceRangeValue**

Maximum range expressed as absolute value.

Type: **Price**

Used in groups: **PriceRangeRuleGrp**

**180.2.4280 PriceType**

Code to represent the price type.

Type: **int**

Allowed values in PriceTypeCodeSet:

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
2	PerUnit	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points spread). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	Yield	Yield
10	FixedCabinetTradePrice	Fixed cabinet trade price (primarily for listed futures and options)
11	VariableCabinetTradePrice	Variable cabinet trade price (primarily for listed futures and options)
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example, the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths



Code	Name	Description
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)
22	BasisPoints	Basis points. When the price is not spread based.
23	UpfrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageNotional	Percentage of notional

Used in components: [BaseTradingRules](#), [SettlTradeDetails](#)

Used in groups: [BidCompRspGrp](#), [InstrmtMatchSideGrp](#), [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [Confirmation](#), [CrossOrderCancelReplaceRequest](#), [ExecutionAck](#), [ExecutionReport](#), [IOI](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [PositionReport](#), [PositionTransferInstruction](#), [PositionTransferReport](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### 180.2.4281 PriceUnitOfMeasure

Used to express the UOM of the price if different from the contract. In futures, this can be different for cross-rate products in which the price is quoted in units differently from the contract

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet

Code	Name	Description
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)

Code	Name	Description
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint

Code	Name	Description
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
Sqcm	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
Sqkm	SquareKilometer	Square kilometer
Sqm	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
Sqmm	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: **Instrument**

#### 180.2.4282 PriceUnitOfMeasureCurrency

Indicates the currency of the price unit of measure. Conditionally required when PriceUnitOfMeasure(1191) = Ccy

Type: **Currency**

Used in components: **Instrument**

#### 180.2.4283 PriceUnitOfMeasureCurrencyCodeSource

Identifies class or source of the PriceUnitOfMeasureCurrency(1717) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP

Code	Name	Description
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **Instrument**

#### **180.2.4284 PriceUnitOfMeasureQty**

Used to express the UOM Quantity of the price if different from the contract. In futures, this can be different for physically delivered products in which price is quoted in a unit size different from the contract, i.e. a Cattle Future contract has a UOMQty of 40,000 and a PriceUOMQty of 100.

Type: **Qty**

Used in components: **Instrument**

#### **180.2.4285 PricingDateAdjusted**

The adjusted pricing or fixing date.

Type: **LocalMktDate**

Used in components: **PricingDateTime**

#### **180.2.4286 PricingDateBusinessCenter**

The business center calendar used to adjust pricing or fixing dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **PricingDateBusinessCenterGrp**

**180.2.4287 PricingDateBusinessCenterGrp**

PricingDateBusinessCenterGrp is a repeating subcomponent of the PricingDateTime component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoPricingDateBusinessCenters	[1..1]	NumInGroup	
PricingDateBusinessCenter	[0..1]	String	Required if NoPricingDateBusinessCenters(41230) > 0.

Used in components: [PricingDateTime](#)

**180.2.4288 PricingDateBusinessDayConvention**

The business day convention used to adjust pricing or fixing dates. Used only to override the business day convention defined in the DateAdjustment component within the Instrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [PricingDateTime](#)

**180.2.4289 PricingDateTime**

The PricingDateTime component is a subcomponent of Instrument used to specify an adjusted or unadjusted pricing or fixing date and optionally the time, e.g. for a commodity or FX forward trade.

Name	Mult.	Type	Description
PricingDateUnadjusted	[0..1]	LocalMktDate	
PricingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of pricing dates.
PricingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of pricing dates.
PricingDateAdjusted	[0..1]	LocalMktDate	
PricingTime	[0..1]	LocalMktTime	
PricingTimeBusinessCenter	[0..1]	String	

Used in components: **Instrument**

#### **180.2.4290 PricingDateUnadjusted**

The unadjusted pricing or fixing date.

Type: **LocalMktDate**

Used in components: **PricingDateTime**

#### **180.2.4291 PricingTime**

Specifies the local market time of the pricing or fixing.

Type: **LocalMktTime**

Used in components: **PricingDateTime**

#### **180.2.4292 PricingTimeBusinessCenter**

Specifies the business center for determining the pricing or fixing time. See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **PricingDateTime**

**180.2.4293 PrimaryServiceLocationID**

Primary service location identifier.

Type: **String**

Used in groups: **MarketDataFeedTypes**

**180.2.4294 PriorityIndicator**

Indicates if a Cancel/Replace has caused an order to lose book priority.

Type: **int**

Allowed values in PriorityIndicatorCodeSet:

Code	Name	Description
0	PriorityUnchanged	Priority unchanged
1	LostPriorityAsResultOfOrderChange	Lost Priority as result of order change

Used in messages: **ExecutionReport**

**180.2.4295 PriorSettlPrice**

Previous settlement price

Type: **Price**

Used in messages: **AdjustedPositionReport**, **AssignmentReport**, **PositionReport**, **SecurityDefinition**, **SecurityDefinitionUpdateReport**

**180.2.4296 PriorSpreadIndicator**

Indicates if requesting a rollover of prior day's spread submissions.

Type: **Boolean**

Used in messages: **PositionMaintenanceReport**, **PositionMaintenanceRequest**



**180.2.4297 PrivateQuote**

Specifies whether a quote is public, i.e. available to the market, or private, i.e. available to a specified counterparty only.

Type: **Boolean**

Allowed values in PrivateQuoteCodeSet:

Code	Name	Description
Y	PrivateQuote	Private Quote
N	PublicQuote	Public Quote

Used in messages: **Quote**, **QuoteRequest**, **QuoteRequestReject**, **RFQRequest**

**180.2.4298 ProcessCode**

Processing code for sub-account. Absence of this field in AllocAccount (79) / AllocPrice (366) /AllocQty (80) / ProcessCode instance indicates regular trade.

Type: **char**

Allowed values in ProcessCodeCodeSet:

Code	Name	Description
0	Regular	Regular
1	SoftDollar	Soft Dollar
2	StepIn	Step-In
3	StepOut	Step-Out
4	SoftDollarStepIn	Soft-dollar Step-In
5	SoftDollarStepOut	Soft-dollar Step-Out
6	PlanSponsor	Plan Sponsor

Used in groups: **AllocGrp**, **ListOrdGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **Confirmation**, **CrossOrderCancelReplaceRequest**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**

**180.2.4299 Product**

Indicates the type of product the security is associated with. See also the CFICode (461) and Security-Type (167) fields.

Type: **int**

Allowed values in ProductCodeSet:

Code	Name	Description
1	AGENCY	AGENCY
2	COMMODITY	COMMODITY
3	CORPORATE	CORPORATE
4	CURRENCY	CURRENCY
5	EQUITY	EQUITY
6	GOVERNMENT	GOVERNMENT
7	INDEX	INDEX
8	LOAN	LOAN
9	MONEYMARKET	MONEYMARKET
10	MORTGAGE	MORTGAGE
11	MUNICIPAL	MUNICIPAL
12	OTHER	OTHER
13	FINANCING	FINANCING

Used in components: **Instrument**

Used in groups: **SecTypesGrp**, **SettlInstGrp**

Used in messages: **SecurityTypeRequest**, **SettlementInstructionRequest**

**180.2.4300 ProductComplex**

Identifies an entire suite of products for a given market. In Futures this may be "interest rates", "agricultural", "equity indexes", etc.

Type: **String**

Used in components: **Instrument**

**180.2.4301 ProgPeriodInterval**

Time in minutes between each ListStatus report sent by SellSide. Zero means don't send status.

Type: **int**

Used in messages: **BidRequest**, **NewOrderList**

**180.2.4302 ProgRptReqs**

Code to identify the desired frequency of progress reports.

Type: **int**

Allowed values in ProgRptReqsCodeSet:

Code	Name	Description
1	BuySideRequests	Buy-side explicitly requests status using Statue Request (default), the sell-side firm can, however, send a DONE status List SStatus Response in an unsolicited fashion
2	SellSideSends	Sell-side periodically sends status using List Status. Period optionally specified in ProgressPeriod.
3	RealTimeExecutionReports	Real-time execution reports (to be discourage)

Used in messages: **BidRequest**, **NewOrderList**

**180.2.4303 ProtectionTermBuyerNotifies**

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring.

ProtectionTermBuyerNotifies(40185)=Y indicates that the buyer notifies.

Type: **Boolean**

Used in groups: **ProtectionTermGrp**

**180.2.4304 ProtectionTermCurrency**

The currency of ProtectionTermNotional(40182). Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **ProtectionTermGrp**

#### **180.2.4305 ProtectionTermEventBusinessCenter**

When used, the business center indicates the local time of the business center that replaces the Greenwich Mean Time in Section 3.3 of the 2003 ISDA Credit Derivatives Definitions. See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ProtectionTermGrp**

#### **180.2.4306 ProtectionTermEventCurrency**

Applicable currency if ProtectionTermEventValue(40193) is an amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **ProtectionTermEventGrp**

#### **180.2.4307 ProtectionTermEventDayType**

Day type for events that specify a period and unit.

Type: **int**

Allowed values in ProtectionTermEventDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **ProtectionTermEventGrp**

**180.2.4308 ProtectionTermEventGrp**

The ProtectionTermEventGrp is a repeating component within the ProtectionTermGrp component used to report applicable CDS credit events.

Name	Mult.	Type	Description
NoProtectionTermEvents	[1..1]	NumInGroup	
ProtectionTermEventType	[0..1]	String	Required if NoProtectionTermEvents(40191) > 0.
ProtectionTermEventValue	[0..1]	String	
ProtectionTermEventCurrency	[0..1]	Currency	
ProtectionTermEventPeriod	[0..1]	int	Conditionally required when ProtectionTermEventUnit(40196) is specified.
ProtectionTermEventUnit	[0..1]	CodeSet	Conditionally required when ProtectionTermEventPeriod(40195) is specified.
ProtectionTermEventDayType	[0..1]	CodeSet	
ProtectionTermEventRateSource	[0..1]	String	
ProtectionTermEventQualifierGrp	[0..*]	Group	

Used in groups: [ProtectionTermGrp](#)

**180.2.4309 ProtectionTermEventMinimumSources**

The minimum number of the specified public information sources that must publish information that reasonably confirms that a credit event has occurred. The market convention is two.

Type: [int](#)

Used in groups: [ProtectionTermGrp](#)

**180.2.4310 ProtectionTermEventNewsSource**

Newspaper or electronic news service or source that may publish relevant information used in the determination of whether or not a credit event has occurred.

Type: [String](#)

Used in groups: [ProtectionTermEventNewsSourceGrp](#)

**180.2.4311 ProtectionTermEventNewsSourceGrp**

ProtectionTermEventNewsSourceGrp is a repeating subcomponent within the ProtectionTermGrp component. It is used to specify the particular newspapers or electronic news services and sources that may publish relevant information used in the determination of whether or not a credit event has occurred.

Name	Mult.	Type	Description
NoProtectionTermEventNewsSources	[1..1]	NumInGroup	
ProtectionTermEventNewsSource	[0..1]	String	Required if NoProtectionTermEventNewsSources(40951) > 0.

Used in groups: [ProtectionTermGrp](#)

**180.2.4312 ProtectionTermEventPeriod**

Time unit multiplier for protection term events.

Type: [int](#)

Used in groups: [ProtectionTermEventGrp](#)

**180.2.4313 ProtectionTermEventQualifier**

Protection term event qualifier. Used to further qualify ProtectionTermEventType(40192).

Type: [char](#)

Allowed values in ProtectionTermEventQualifierCodeSet:

Code	Name	Description
H	RestructuringMultipleHoldingObligations	Retructuring - multiple holding obligations. In relation to a restructuring credit event, unless multiple holder obligation is not specified restructurings are limited to multiple holder obligations. A multiple holder obligation means an obligation that is held by more than three holders that are not affiliates of each other and where at least two thirds of the holders must agree to the event that constitutes the restructuring credit event. ISDA 2003 Term: Multiple Holder Obligation.

Code	Name	Description
E	RestructuringMultipleCreditEvent-Notices	Restructuring - multiple credit event notices. Presence of this element and value set to 'true' indicates that Section 3.9 of the 2003 Credit Derivatives Definitions shall apply. Absence of this element indicates that Section 3.9 shall not apply. NOTE: Not allowed under ISDA Credit 1999.
C	FloatingRateInterestShortfall	Floating rate interest shortfall. Indicates compounding.

Used in groups: [ProtectionTermEventQualifierGrp](#)

#### 180.2.4314 ProtectionTermEventQualifierGrp

The ProtectionTermEventQualifierGrp is a repeating component within the ProtectionTermEventGrp component used to specify qualifying attributes to the event.

Name	Mult.	Type	Description
<a href="#">NoProtectionTermEventQualifiers</a>	[1..1]	NumInGroup	
<a href="#">ProtectionTermEventQualifier</a>	[0..1]	CodeSet	Required if <a href="#">NoProtectionTermEventQualifiers(40199)</a> > 0.

Used in groups: [ProtectionTermEventGrp](#)

#### 180.2.4315 ProtectionTermEventRateSource

Rate source for events that specify a rate source, e.g. Floating rate interest shortfall.

Type: [String](#)

Used in groups: [ProtectionTermEventGrp](#)

#### 180.2.4316 ProtectionTermEventType

Specifies the type of credit event applicable to the protection terms.

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Event_Types) for code list of applicable event types.

Type: [String](#)

Used in groups: [ProtectionTermEventGrp](#)

**180.2.4317 ProtectionTermEventUnit**

Time unit associated with protection term events.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **ProtectionTermEventGrp**

**180.2.4318 ProtectionTermEventValue**

Protection term event value appropriate to ProtectionTermEventType(40192).

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Event_Types) for applicable event type values.

Type: **String**

Used in groups: **ProtectionTermEventGrp**

**180.2.4319 ProtectionTermGrp**

The ProtectionTermGrp is a repeating component within the Instrument component used to report protection term details referenced from UnderlyingInstrument component.

Name	Mult.	Type	Description
NoProtectionTerms	[1..1]	NumInGroup	
ProtectionTermNotional	[0..1]	Amt	Required if NoProtectionTerms(40181) > 0.
ProtectionTermCurrency	[0..1]	Currency	
ProtectionTermSellerNotifies	[0..1]	Boolean	
ProtectionTermBuyerNotifies	[0..1]	Boolean	
ProtectionTermEventBusinessCenter	[0..1]	String	



Name	Mult.	Type	Description
ProtectionTermStandardSources	[0..1]	Boolean	
ProtectionTermEventMinimumSources	[0..1]	int	
ProtectionTermEventNewsSourceGrp	[0..*]	Group	
ProtectionTermEventGrp	[0..*]	Group	
ProtectionTermObligationGrp	[0..*]	Group	
ProtectionTermXID	[0..1]	XID	

Used in components: **Instrument**

#### 180.2.4320 ProtectionTermNotional

The notional amount of protection coverage.

Type: **Amt**

Used in groups: **ProtectionTermGrp**

#### 180.2.4321 ProtectionTermObligationGrp

The ProtectionTermObligationGrp is a repeating component within the ProtectionTermGrp component used to report applicable CDS obligations.

Name	Mult.	Type	Description
NoProtectionTermObligations	[1..1]	NumInGroup	
ProtectionTermObligationType	[0..1]	String	Required if NoProtectionTermObligations(40201) > 0.
ProtectionTermObligationValue	[0..1]	String	

Used in groups: **ProtectionTermGrp**

#### 180.2.4322 ProtectionTermObligationType

Specifies the type of obligation applicable to the protection terms.

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Obligation_Types) for code list of applicable obligation types.

Type: **String**

Used in groups: **ProtectionTermObligationGrp**

#### **180.2.4323 ProtectionTermObligationValue**

Protection term obligation value appropriate to ProtectionTermObligationType(40202).

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Obligation_Types) for applicable obligation type values.

Type: **String**

Used in groups: **ProtectionTermObligationGrp**

#### **180.2.4324 ProtectionTermSellerNotifies**

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring.

ProtectionTermSellerNotifies(40184)=Y indicates that the seller notifies.

Type: **Boolean**

Used in groups: **ProtectionTermGrp**

#### **180.2.4325 ProtectionTermStandardSources**

Indicates whether ISDA defined Standard Public Sources are applicable (ProtectionTermStandardSources(40187)=Y) or not.

Type: **Boolean**

Used in groups: **ProtectionTermGrp**

#### **180.2.4326 ProtectionTermXID**

A named string value referenced by UnderlyingProtectionTermXIDRef(41314).

Type: **XID**

Used in groups: **ProtectionTermGrp**

**180.2.4327 ProvisionBreakFeeElection**

Type of fee elected for the break provision.

Type: **int**

Allowed values in ProvisionBreakFeeElectionCodeSet:

Code	Name	Description
0	FlatFee	Flat fee
1	AmortizedFee	Amortized fee
2	FundingFee	Funding fee
3	FlatAndFundingFee	Flat fee and funding fee
4	AmortizedAndFundingFee	Amortized fee and funding fee

Used in groups: **ProvisionGrp**

**180.2.4328 ProvisionBreakFeeRate**

Break fee election rate when the break fee is proportional to the notional. A fee rate of 5% would be represented as "0.05".

Type: **Percentage**

Used in groups: **ProvisionGrp**

**180.2.4329 ProvisionCalculationAgent**

Used to identify the calculation agent. The calculation agent may be identified in ProvisionCalculation-Agent(40098) or in the ProvisionParties component.

Type: **int**

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreement	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

---

Code	Name	Description
------	------	-------------

---

Used in groups: [ProvisionGrp](#)

#### **180.2.4330 ProvisionCashSettlCurrency**

Specifies the currency of settlement. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [ProvisionGrp](#)

#### **180.2.4331 ProvisionCashSettlCurrency2**

Specifies the currency of settlement for a cross-currency provision. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [ProvisionGrp](#)

#### **180.2.4332 ProvisionCashSettlMethod**

An ISDA defined cash settlement method used for the determination of the applicable cash settlement amount. The method is defined in the 2006 ISDA Definitions, Section 18.3. Cash Settlement Methods, paragraph (e).

Type: [int](#)

Allowed values in ProvisionCashSettlMethodCodeSet:

---

Code	Name	Description
0	CashPrice	Cash price
1	CashPriceAlternate	Cash price alternate
2	ParYieldCurveAdjusted	Par yield curve adjusted
3	ZeroCouponYieldCurveAdjusted	Zero coupon yield curve adjusted
4	ParYieldCurveUnadjusted	Par yield curve unadjusted
5	CrossCurrency	Cross currency
6	CollateralizedPrice	Collateralized price

---

Used in groups: [ProvisionGrp](#)

**180.2.4333 ProvisionCashSettlPaymentDate**

The cash settlement payment date, unadjusted or adjusted depending on ProvisionCashSettlPaymentDateType(40173).

Type: **LocalMktDate**

Used in groups: **ProvisionCashSettlPaymentFixedDateGrp**

**180.2.4334 ProvisionCashSettlPaymentDateBusinessCenter**

The business center calendar used to adjust the provisional cash settlement payment's termination or relative termination date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ProvisionCashSettlPaymentDateBusinessCenterGrp**

**180.2.4335 ProvisionCashSettlPaymentDateBusinessCenterGrp**

ProvisionCashSettlPaymentDateBusinessCenterGrp is a repeating subcomponent within the ProvisionCashSettlPaymentDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoProvisionCashSettlPaymentDateBusinessCenters	[1..1]	NumInGroup	
ProvisionCashSettlPaymentDateBusinessCenter	[0..1]	String	Required if NoProvisionCashSettlPaymentDateBusinessCenters(40952) > 0.

Used in components: **ProvisionCashSettlPaymentDates**

**180.2.4336 ProvisionCashSettlPaymentDateBusinessDayConvention**

The business day convention used to adjust the provisional cash settlement payment's termination or relative termination date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **ProvisionCashSettlPaymentDates**

#### **180.2.4337 ProvisionCashSettlPaymentDateOffsetDayType**

Specifies the day type of the provision's relative cash settlement payment date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **ProvisionCashSettlPaymentDates**

#### **180.2.4338 ProvisionCashSettlPaymentDateOffsetPeriod**

Time unit multiplier for the relative cash settlement payment date offset.

Type: **int**

Used in components: **ProvisionCashSettlPaymentDates**

#### **180.2.4339 ProvisionCashSettlPaymentDateOffsetUnit**

Time unit associated with the relative cash settlement payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **ProvisionCashSettlPaymentDates**

#### **180.2.4340 ProvisionCashSettlPaymentDateRangeFirst**

First date in range when a settlement date range is provided.

Type: **LocalMktDate**

Used in components: **ProvisionCashSettlPaymentDates**

#### **180.2.4341 ProvisionCashSettlPaymentDateRangeLast**

The last date in range when a settlement date range is provided.

Type: **LocalMktDate**

Used in components: **ProvisionCashSettlPaymentDates**

#### **180.2.4342 ProvisionCashSettlPaymentDateRelativeTo**

Specifies the anchor date when the cash settlement payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **ProvisionCashSettlPaymentDates**

### 180.2.4343 ProvisionCashSettlPaymentDates

The ProvisionCashSettlPaymentDates component is a sub-component within the ProvisionGrp component used to report the cash settlement payment dates defined in the provision.

Name	Mult.	Type	Description
ProvisionCashSettlPaymentDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the provisional cash settlement payment dates.
ProvisionCashSettlPaymentDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the provisional cash settlement payment dates.
ProvisionCashSettlPaymentDateRelativeTo	[0..1]	int	
ProvisionCashSettlPaymentDateOffsetPeriod	[0..1]	int	Conditionally required when ProvisionCashSettlPaymentDateOffsetUnit(40167) is specified.
ProvisionCashSettlPaymentDateOffsetUnit	[0..1]	CodeSet	Conditionally required when ProvisionCashSettlPaymentDateOffsetPeriod(40166) is specified.
ProvisionCashSettlPaymentDateOffsetDayType	[0..1]	CodeSet	
ProvisionCashSettlPaymentDateRangeFirst	[0..1]	LocalMktDate	
ProvisionCashSettlPaymentDateRangeLast	[0..1]	LocalMktDate	
ProvisionCashSettlPaymentFixedDateGrp	[0..*]	Group	

Used in groups: **ProvisionGrp**

### 180.2.4344 ProvisionCashSettlPaymentDateType

Specifies the type of date (e.g. adjusted for holidays).



Type: **int**

Allowed values in ProvisionCashSettlPaymentDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **ProvisionCashSettlPaymentFixedDateGrp**

#### **180.2.4345 ProvisionCashSettlPaymentFixedDateGrp**

The ProvisionCashSettlPaymentFixedDateGrp is a repeating component within the ProvisionCashSettlPaymentDates component used to report fixed cash settlement payment dates defined in the provision.

Name	Mult.	Type	Description
<b>NoProvisionCashSettlPaymentDates</b>	[1..1]	NumInGroup	
<b>ProvisionCashSettlPaymentDate</b>	[0..1]	LocalMktDate	Required if NoProvisionCashSettlPaymentDates (40171) > 0.
<b>ProvisionCashSettlPaymentDateType</b>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: **ProvisionCashSettlPaymentDates**

#### **180.2.4346 ProvisionCashSettlQuoteReferencePage**

Identifies the reference "page" from the quote source.

Type: **String**

Used in components: **ProvisionCashSettlQuoteSource**

#### **180.2.4347 ProvisionCashSettlQuoteSource**

Identifies the source of quote information.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: **ProvisionCashSettlQuoteSource**

#### **180.2.4348 ProvisionCashSettlQuoteSource**

The ProvisionCashSettlQuoteSource is a subcomponent of the ProvisionGrp component used to specify the reference source for currency or rate quote for cash settlement purposes.

Name	Mult.	Type	Description
<b>ProvisionCashSettlQuoteSource</b>	[0..1]	CodeSet	
<b>ProvisionCashSettlQuoteReferencePage</b>	[0..1]	String	

Used in groups: **ProvisionGrp**

#### **180.2.4349 ProvisionCashSettlQuoteType**

Identifies the type of quote to be used.

Type: **int**

Allowed values in ProvisionCashSettlQuoteTypeCodeSet:

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer

Code	Name	Description
3	ExercisingPartyPays	Exercising party pays. See 2000 ISDA Definitions, Section 17.2, Certain Definitions Relating to Cash Settlement, paragraph (j) for definition of "exercising party pays".

Used in groups: **ProvisionGrp**

#### 180.2.4350 ProvisionCashSettlValueDateAdjusted

The adjusted cash settlement value date.

Type: **LocalMktDate**

Used in components: **ProvisionCashSettlValueDates**

#### 180.2.4351 ProvisionCashSettlValueDateBusinessCenter

The business center calendar used to adjust the provision's cash settlement valuation date, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ProvisionCashSettlValueDateBusinessCenterGrp**

#### 180.2.4352 ProvisionCashSettlValueDateBusinessCenterGrp

ProvisionCashSettlValueDateBusinessCenterGrp is a repeating subcomponent within the ProvisionCashSettlValueDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoProvisionCashSettlValueDateBusinessCenters	[1..1]	NumInGroup	
ProvisionCashSettlValueDateBusinessCenter	[0..1]	String	Required if NoProvisionCashSettlValueDateBusinessCenters(40953) > 0.

Used in components: **ProvisionCashSettlValueDates**

**180.2.4353 ProvisionCashSettlValueDateBusinessDayConvention**

The cash settlement valuation date adjustment business day convention. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **ProvisionCashSettlValueDates**

**180.2.4354 ProvisionCashSettlValueDateOffsetDayType**

Specifies the day type of the provision's relative cash settlement value date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **ProvisionCashSettlValueDates**

**180.2.4355 ProvisionCashSettlValueDateOffsetPeriod**

Time unit multiplier for the relative cash settlement value date offset.

Type: **int**

Used in components: **ProvisionCashSettlValueDates**

**180.2.4356 ProvisionCashSettlValueDateOffsetUnit**

Time unit associated with the relative cash settlement value date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **ProvisionCashSettlValueDates**

**180.2.4357 ProvisionCashSettlValueDateRelativeTo**

Specifies the anchor date when the cash settlement value date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values

Type: **int**

Used in components: **ProvisionCashSettlValueDates**

**180.2.4358 ProvisionCashSettlValueDates**

The ProvisionCashSettlValueDates component is a subcomponent within the ProvisionGrp component used to report the cash settlement value date and time defined in the provision.

Name	Mult.	Type	Description
ProvisionCashSettlValueTime	[0..1]	LocalMktTime	
ProvisionCashSettlValueTimeBusinessCenter	[0..1]	String	
ProvisionCashSettlValueDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the provisional cash settlement value date.
ProvisionCashSettlValueDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the provisional cash settlement value date.
ProvisionCashSettlValueDateRelativeTo	[0..1]	int	
ProvisionCashSettlValueDateOffsetPeriod	[0..1]	int	Conditionally required when ProvisionCashSettlValueDateOffsetUnit(40120) is specified.
ProvisionCashSettlValueDateOffsetUnit	[0..1]	CodeSet	Conditionally required when ProvisionCashSettlValueDateOffsetPeriod(40119) is specified.
ProvisionCashSettlValueDateOffsetDayType	[0..1]	CodeSet	
ProvisionCashSettlValueDateAdjusted	[0..1]	LocalMktDate	

Used in groups: **ProvisionGrp**

### 180.2.4359 ProvisionCashSettlValueTime

A time specified in 24-hour format, e.g. 11am would be represented as 11:00:00. The time of the cash settlement valuation date when the cash settlement amount will be determined according to the cash settlement method if the parties have not otherwise been able to agree to the cash settlement amount.

Type: **LocalMktTime**

Used in components: **ProvisionCashSettlValueDates**

**180.2.4360 ProvisionCashSettlValueTimeBusinessCenter**

Identifies the business center calendar used with the provision's cash settlement valuation time. See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **ProvisionCashSettlValueDates**

**180.2.4361 ProvisionDateAdjusted**

The adjusted date of the provision.

Type: **LocalMktDate**

Used in groups: **ProvisionGrp**

**180.2.4362 ProvisionDateBusinessCenter**

The business center calendar used to adjust the instrument's provision's dates, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ProvisionDateBusinessCenterGrp**

**180.2.4363 ProvisionDateBusinessCenterGrp**

ProvisionDateBusinessCenterGrp is a repeating subcomponent within the ProvisionGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
<b>NoProvisionDateBusinessCenters</b>	[1..1]	NumInGroup	
<b>ProvisionDateBusinessCenter</b>	[0..1]	String	Required if NoProvisionDateBusinessCenters(40957) > 0.

Used in groups: **ProvisionGrp**

**180.2.4364 ProvisionDateBusinessDayConvention**

The business day convention used to adjust the instrument's provision's dates. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: **ProvisionGrp**

**180.2.4365 ProvisionDateTenorPeriod**

Time unit multiplier for the provision's tenor period.

Type: **int**

Used in groups: **ProvisionGrp**

**180.2.4366 ProvisionDateTenorUnit**

Time unit associated with the provision's tenor period.

Type: **String**

Allowed values in ProvisionDateTenorUnitCodeSet:



Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **ProvisionGrp**

### 180.2.4367 ProvisionDateUnadjusted

The unadjusted date of the provision.

Type: **LocalMktDate**

Used in groups: **ProvisionGrp**

### 180.2.4368 ProvisionGrp

The ProvisionGrp is a repeating subcomponent of the Instrument component used to detail the additional terms and conditions associated with the instrument.

Name	Mult.	Type	Description
<b>NoProvisions</b>	[1..1]	NumInGroup	
<b>ProvisionType</b>	[0..1]	CodeSet	Required if NoProvisions(40090) > 0.
<b>ProvisionDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>ProvisionDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the instrument provisions.
<b>ProvisionDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the instrument provisions.
<b>ProvisionDateAdjusted</b>	[0..1]	LocalMktDate	
<b>ProvisionDateTenorPeriod</b>	[0..1]	int	Conditionally required when ProvisionDateTenorUnit(40097) is specified.

Name	Mult.	Type	Description
ProvisionDateTenorUnit	[0..1]	CodeSet	Conditionally required when ProvisionDateTenorPeriod(40096) is specified.
ProvisionBreakFeeElection	[0..1]	CodeSet	
ProvisionBreakFeeRate	[0..1]	Percentage	
ProvisionCalculationAgent	[0..1]	CodeSet	
ProvisionOptionSinglePartyBuyerSide	[0..1]	CodeSet	
ProvisionOptionSinglePartySellerSide	[0..1]	CodeSet	
ProvisionCashSettlValueDates	[0..1]	Component	
ProvisionOptionExerciseDates	[0..1]	Component	
ProvisionOptionExpirationDate	[0..1]	Component	
ProvisionOptionRelevantUnderlying-Date	[0..1]	Component	
ProvisionOptionExerciseStyle	[0..1]	CodeSet	
ProvisionOptionExerciseMultipleNo-tional	[0..1]	Amt	
ProvisionOptionExerciseMinimumNo-tional	[0..1]	Amt	
ProvisionOptionExerciseMaximumNo-tional	[0..1]	Amt	
ProvisionOptionMinimumNumber	[0..1]	int	
ProvisionOptionMaximumNumber	[0..1]	int	
ProvisionOptionExerciseConfirmation	[0..1]	Boolean	
ProvisionCashSettlPaymentDates	[0..1]	Component	
ProvisionCashSettlMethod	[0..1]	CodeSet	
ProvisionCashSettlCurrency	[0..1]	Currency	
ProvisionCashSettlCurrency2	[0..1]	Currency	
ProvisionCashSettlQuoteType	[0..1]	CodeSet	
ProvisionCashSettlQuoteSource	[0..1]	Component	
ProvisionText	[0..1]	String	
EncodedProvisionTextLen	[0..1]	Length	Must be set if EncodedProvisionText(40987) field is specified and must immediately precede it.
EncodedProvisionText	[0..1]	data	Encoded (non-ASCII characters) representation of the ProvisionText(40113) field in the encoded format specified via the MessageEncoding(347) field.
ProvisionParties	[0..*]	Group	

Used in components: **Instrument**

#### **180.2.4369 ProvisionOptionExerciseBoundsFirstDateUnadjusted**

The unadjusted first date of a schedule. This can be used to restrict the range of exercise dates when they are relative.

Type: **LocalMktDate**

Used in components: **ProvisionOptionExerciseDates**

#### **180.2.4370 ProvisionOptionExerciseBoundsLastDateUnadjusted**

The unadjusted last date of a schedule. This can be used to restrict the range of exercise dates when they are relative.

Type: **LocalMktDate**

Used in components: **ProvisionOptionExerciseDates**

#### **180.2.4371 ProvisionOptionExerciseBusinessCenter**

The business center calendar used to adjust the instrument's provision's option exercise date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ProvisionOptionExerciseBusinessCenterGrp**

#### **180.2.4372 ProvisionOptionExerciseBusinessCenterGrp**

ProvisionOptionExerciseBusinessCenterGrp is a repeating subcomponent within the ProvisionOptionExerciseDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

---

Name	Mult.	Type	Description
NoProvisionOptionExerciseBusinessCenters	[1..1]	NumInGroup	

---

Name	Mult.	Type	Description
<b>ProvisionOptionExerciseBusinessCenter</b>	[0..1]	String	Required if NoProvisionOptionExerciseBusinessCenters(40954) > 0.

Used in components: **ProvisionOptionExerciseDates**

### 180.2.4373 **ProvisionOptionExerciseBusinessDayConvention**

The business day convention used to adjust the instrument's provision's option exercise date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **ProvisionOptionExerciseDates**

### 180.2.4374 **ProvisionOptionExerciseConfirmation**

Used to indicate whether follow-up confirmation of exercise (written or electronic) is required following telephonic notice by the buyer to the seller or seller's agent.

Type: **Boolean**

Used in groups: **ProvisionGrp**

## 180.2.4375 ProvisionOptionExerciseDates

The ProvisionOptionExerciseDates is a subcomponent within the ProvisionGrp component used to report the option exercise dates and times defined in the provision.

Name	Mult.	Type	Description
ProvisionOptionExerciseBusinessDay-Convention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the provisional option exercise dates.
ProvisionOptionExerciseBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the provisional option exercise dates.
ProvisionOptionExerciseFixedDateGrp	[0..*]	Group	
ProvisionOptionExerciseEarliestDate-OffsetPeriod	[0..1]	int	Conditionally required when ProvisionOptionExerciseEarliestDateUnit(40126) is specified.
ProvisionOptionExerciseEarliestDate-OffsetUnit	[0..1]	CodeSet	Conditionally required when ProvisionOptionExerciseEarliestDatePeriod(40125) is specified.
ProvisionOptionExerciseFrequencyPeriod	[0..1]	int	Conditionally required when ProvisionOptionExerciseFrequencyUnit(40128) is specified.
ProvisionOptionExerciseFrequencyUnit	[0..1]	CodeSet	Conditionally required when ProvisionOptionExerciseFrequencyPeriod(40127) is specified.
ProvisionOptionExerciseStartDateUnadjusted	[0..1]	LocalMktDate	
ProvisionOptionExerciseStartDateRelativeTo	[0..1]	int	
ProvisionOptionExerciseStartDateOffsetPeriod	[0..1]	int	Conditionally required when ProvisionOptionExerciseStartDateOffsetUnit(40132) is specified.
ProvisionOptionExerciseStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when ProvisionOptionExerciseStartDateOffsetPeriod(40131) is specified.
ProvisionOptionExerciseStartDateOffsetDayType	[0..1]	CodeSet	
ProvisionOptionExerciseStartDateAdjusted	[0..1]	LocalMktDate	
ProvisionOptionExercisePeriodSkip	[0..1]	int	

Name	Mult.	Type	Description
ProvisionOptionExerciseBoundsFirst-DateUnadjusted	[0..1]	LocalMktDate	
ProvisionOptionExerciseBoundsLast-DateUnadjusted	[0..1]	LocalMktDate	
ProvisionOptionExerciseEarliestTime	[0..1]	LocalMktTime	
ProvisionOptionExerciseEarliestTime-BusinessCenter	[0..1]	String	
ProvisionOptionExerciseLatestTime	[0..1]	LocalMktTime	
ProvisionOptionExerciseLatestTime-BusinessCenter	[0..1]	String	

Used in groups: [ProvisionGrp](#)

#### 180.2.4376 ProvisionOptionExerciseEarliestDateOffsetPeriod

Time unit multiplier for the interval to the first (and possibly only) exercise date in the exercise period.

Type: [int](#)

Used in components: [ProvisionOptionExerciseDates](#)

#### 180.2.4377 ProvisionOptionExerciseEarliestDateOffsetUnit

Time unit associated with the interval to the first (and possibly only) exercise date in the exercise period.

Type: [String](#)

Allowed values in ProvisionOptionExerciseEarliestDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [ProvisionOptionExerciseDates](#)

**180.2.4378 ProvisionOptionExerciseEarliestTime**

The earliest time at which notice of exercise can be given by the buyer to the seller (or seller's agent) i) on the expiration date, in the case of a European style option, (ii) on each bermuda option exercise date and the expiration date, in the case of a Bermuda style option the commencement date to, and including, the expiration date, in the case of an American option.

Type: **LocalMktTime**

Used in components: **ProvisionOptionExerciseDates**

**180.2.4379 ProvisionOptionExerciseEarliestTimeBusinessCenter**

Identifies the business center calendar used with the provision's earliest time for notice of exercise.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **ProvisionOptionExerciseDates**

**180.2.4380 ProvisionOptionExerciseFixedDate**

A predetermined option exercise date, unadjusted or adjusted depending on ProvisionOptionExerciseFixedDateType(40144).

Type: **LocalMktDate**

Used in groups: **ProvisionOptionExerciseFixedDateGrp**

**180.2.4381 ProvisionOptionExerciseFixedDateGrp**

The ProvisionOptionExerciseFixedDateGrp is a repeating component within the ProvisionOptionExerciseDates component used to report an array of unadjusted or adjusted fixed exercise dates.

Name	Mult.	Type	Description
<b>NoProvisionOptionExerciseFixedDates</b>	[1..1]	NumInGroup	
<b>ProvisionOptionExerciseFixedDate</b>	[0..1]	LocalMktDate	Required if NoProvisionOptionExerciseFixedDates (40142) > 0.
<b>ProvisionOptionExerciseFixedDate-Type</b>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [ProvisionOptionExerciseDates](#)

#### **180.2.4382 ProvisionOptionExerciseFixedDateType**

Specifies the type of date (e.g. adjusted for holidays).

Type: [int](#)

Allowed values in ProvisionOptionExerciseFixedDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [ProvisionOptionExerciseFixedDateGrp](#)

#### **180.2.4383 ProvisionOptionExerciseFrequencyPeriod**

Time unit multiplier for the frequency of subsequent exercise dates in the exercise period following the earliest exercise date. An interval of 1 day should be used to indicate an American style exercise period.

Type: [int](#)

Used in components: [ProvisionOptionExerciseDates](#)

#### **180.2.4384 ProvisionOptionExerciseFrequencyUnit**

Time unit associated with the frequency of subsequent exercise dates in the exercise period following the earliest exercise date.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month



Code	Name	Description
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: **ProvisionOptionExerciseDates**

#### **180.2.4385 ProvisionOptionExerciseLatestTime**

For a Bermuda or American style option, the latest time on an exercise business day (excluding the expiration date) within the exercise period that notice can be given by the buyer to the seller or seller's agent. Notice of exercise given after this time will be deemed to have been given on the next exercise business day.

Type: **LocalMktTime**

Used in components: **ProvisionOptionExerciseDates**

#### **180.2.4386 ProvisionOptionExerciseLatestTimeBusinessCenter**

Identifies the business center calendar used with the provision's latest time for notice of exercise.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **ProvisionOptionExerciseDates**

#### **180.2.4387 ProvisionOptionExerciseMaximumNotional**

The maximum notional amount that can be exercised on a given exercise date.

Type: **Amt**

Used in groups: **ProvisionGrp**

**180.2.4388 ProvisionOptionExerciseMinimumNotional**

The minimum notional amount that can be exercised on a given exercise date.

Type: **Amt**

Used in groups: **ProvisionGrp**

**180.2.4389 ProvisionOptionExerciseMultipleNotional**

A notional amount which restricts the amount of notional that can be exercised when partial exercise or multiple exercise is applicable. The integral multiple amount defines a lower limit of notional that can be exercised and also defines a unit multiple of notional that can be exercised, i.e. only integer multiples of this amount can be exercised.

Type: **Amt**

Used in groups: **ProvisionGrp**

**180.2.4390 ProvisionOptionExercisePeriodSkip**

The number of periods in the referenced date schedule that are between each date in the relative date schedule. Thus a skip of 2 would mean that dates are relative to every second date in the referenced schedule. If present this should have a value greater than 1.

Type: **int**

Used in components: **ProvisionOptionExerciseDates**

**180.2.4391 ProvisionOptionExerciseStartDateAdjusted**

The adjusted first day of the exercise period for an American style option.

Type: **LocalMktDate**

Used in components: **ProvisionOptionExerciseDates**

**180.2.4392 ProvisionOptionExerciseStartDateOffsetDayType**

Specifies the day type of the provision's relative option exercise start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [ProvisionOptionExerciseDates](#)

#### **180.2.4393 ProvisionOptionExerciseStartDateOffsetPeriod**

Time unit multiplier for the relative option exercise start date offset.

Type: [int](#)

Used in components: [ProvisionOptionExerciseDates](#)

#### **180.2.4394 ProvisionOptionExerciseStartDateOffsetUnit**

Time unit associated with the relative option exercise start date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [ProvisionOptionExerciseDates](#)

**180.2.4395 ProvisionOptionExerciseStartDateRelativeTo**

Specifies the anchor date when the option exercise start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **ProvisionOptionExerciseDates**

**180.2.4396 ProvisionOptionExerciseStartDateUnadjusted**

The unadjusted first day of the exercise period for an American style option.

Type: **LocalMktDate**

Used in components: **ProvisionOptionExerciseDates**

**180.2.4397 ProvisionOptionExerciseStyle**

The instrument provision option's exercise style.

Type: **int**

Allowed values in ExerciseStyleCodeSet:

Code	Name	Description
0	European	European
1	American	American
2	Bermuda	Bermuda
99	Other	Other

Used in groups: **ProvisionGrp**

**180.2.4398 ProvisionOptionExpirationDateAdjusted**

The adjusted last date within an exercise period for an American style option. For a European style option it is the only date within the exercise period.

Type: **LocalMktDate**

Used in components: **ProvisionOptionExpirationDate**

**180.2.4399 ProvisionOptionExpirationDateBusinessCenter**

The business center calendar used to adjust the instrument's provision's option expiration date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ProvisionOptionExpirationDateBusinessCenterGrp**

**180.2.4400 ProvisionOptionExpirationDateBusinessCenterGrp**

ProvisionOptionExpirationDateBusinessCenterGrp is a repeating subcomponent within the ProvisionOptionExpirationDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoProvisionOptionExpirationDateBusinessCenters	[1..1]	NumInGroup	
ProvisionOptionExpirationDateBusinessCenter	[0..1]	String	Required if NoProvisionOptionExpirationDateBusinessCenters(40955) > 0.

Used in components: **ProvisionOptionExpirationDate**

**180.2.4401 ProvisionOptionExpirationDateBusinessDayConvention**

The business day convention used to adjust the instrument's provision's option expiration date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)

Code	Name	Description
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [ProvisionOptionExpirationDate](#)

### 180.2.4402 ProvisionOptionExpirationDate

The ProvisionOptionExerciseDate is a subcomponent within the ProvisionGrp component used to report the option expiration date and times defined in the provision.

Name	Mult.	Type	Description
<a href="#">ProvisionOptionExpirationDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">ProvisionOptionExpirationDateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the provisional option expiration date.
<a href="#">ProvisionOptionExpirationDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the provisional option expiration date.
<a href="#">ProvisionOptionExpirationDateRelativeTo</a>	[0..1]	int	
<a href="#">ProvisionOptionExpirationDateOffsetPeriod</a>	[0..1]	int	Conditionally required when ProvisionOptionExpirationDateOffsetUnit(40150) is specified.
<a href="#">ProvisionOptionExpirationDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when ProvisionOptionExpirationDateOffsetPeriod(40149) is specified.
<a href="#">ProvisionOptionExpirationDateOffsetDayType</a>	[0..1]	CodeSet	

Name	Mult.	Type	Description
ProvisionOptionExpirationDateAdjusted	[0..1]	LocalMktDate	
ProvisionOptionExpirationTime	[0..1]	LocalMktTime	
ProvisionOptionExpirationTimeBusinessCenter	[0..1]	String	

Used in groups: **ProvisionGrp**

#### 180.2.4403 ProvisionOptionExpirationDateOffsetDayType

Specifies the day type of the provision's relative option expiration date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **ProvisionOptionExpirationDate**

#### 180.2.4404 ProvisionOptionExpirationDateOffsetPeriod

Time unit multiplier for the relative option expiration date offset.

Type: **int**

Used in components: **ProvisionOptionExpirationDate**

**180.2.4405 ProvisionOptionExpirationDateOffsetUnit**

Time unit associated with the relative option expiration date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **ProvisionOptionExpirationDate**

**180.2.4406 ProvisionOptionExpirationDateRelativeTo**

Specifies the anchor date when the option expiration date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **ProvisionOptionExpirationDate**

**180.2.4407 ProvisionOptionExpirationDateUnadjusted**

The unadjusted last day within an exercise period for an American style option. For a European style option it is the only day within the exercise period.

Type: **LocalMktDate**

Used in components: **ProvisionOptionExpirationDate**

**180.2.4408 ProvisionOptionExpirationTime**

The latest time for exercise on the expiration date.

Type: **LocalMktTime**

Used in components: **ProvisionOptionExpirationDate**



**180.2.4409 ProvisionOptionExpirationTimeBusinessCenter**

Identifies the business center calendar used with the provision's latest exercise time on expiration date.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **ProvisionOptionExpirationDate**

**180.2.4410 ProvisionOptionMaximumNumber**

The maximum number of options that can be exercised on a given exercise date. If the number is not specified, it means that the maximum number of options corresponds to the remaining unexercised options.

Type: **int**

Used in groups: **ProvisionGrp**

**180.2.4411 ProvisionOptionMinimumNumber**

The minimum number of options that can be exercised on a given exercise date.

Type: **int**

Used in groups: **ProvisionGrp**

**180.2.4412 ProvisionOptionRelevantUnderlyingDateAdjusted**

The adjusted date on the underlying set by the exercise of an option. What this date is depends on the option (e.g. in a swaption it is the swap effective date, in an extendible/cancelable provision it is the swap termination date).

Type: **LocalMktDate**

Used in components: **ProvisionOptionRelevantUnderlyingDate**

**180.2.4413 ProvisionOptionRelevantUnderlyingDateBusinessCenter**

The business center calendar used to adjust the instrument's provision's option underlying date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ProvisionOptionRelevantUnderlyingDateBusinessCenterGrp**

#### 180.2.4414 **ProvisionOptionRelevantUnderlyingDateBusinessCenterGrp**

ProvisionOptionRelevantUnderlyingDateBusinessCenterGrp is a repeating subcomponent within the ProvisionOptionRelevantUnderlyingDate component. It is used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoProvisionOptionRelevantUnderlyingDateBusinessCenters	[1..1]	NumInGroup	
ProvisionOptionRelevantUnderlyingDateBusinessCenter	[0..1]	String	Required if NoProvisionOptionRelevantUnderlyingDateBusinessCenters(40956) > 0.

Used in components: **ProvisionOptionRelevantUnderlyingDate**

#### 180.2.4415 **ProvisionOptionRelevantUnderlyingDateBusinessDayConvention**

The business day convention used to adjust the instrument's provision's option underlying date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.

Code	Name	Description
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [ProvisionOptionRelevantUnderlyingDate](#)

### 180.2.4416 ProvisionOptionRelevantUnderlyingDate

The ProvisionOptionRelevantUnderlyingDate is a subcomponent within the ProvisionGrp component used to report the option relevant underlying date defined in the provision.

Name	Mult.	Type	Description
<a href="#">ProvisionOptionRelevantUnderlying-DateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">ProvisionOptionRelevantUnderlying-DateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the provisional option relevant underlying date.
<a href="#">ProvisionOptionRelevantUnderlying-DateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the provisional option relevant underlying date.
<a href="#">ProvisionOptionRelevantUnderlying-DateRelativeTo</a>	[0..1]	int	
<a href="#">ProvisionOptionRelevantUnderlying-DateOffsetPeriod</a>	[0..1]	int	Conditionally required when ProvisionOptionRelevantUnderlyingDateOffsetUnit(40160) is specified.
<a href="#">ProvisionOptionRelevantUnderlying-DateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when ProvisionOptionRelevantUnderlyingDateOffsetPeriod(40159) is specified.
<a href="#">ProvisionOptionRelevantUnderlying-DateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">ProvisionOptionRelevantUnderlying-DateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [ProvisionGrp](#)

**180.2.4417 ProvisionOptionRelevantUnderlyingDateOffsetDayType**

Specifies the day type of the provision's relative option relevant underlying date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **ProvisionOptionRelevantUnderlyingDate**

**180.2.4418 ProvisionOptionRelevantUnderlyingDateOffsetPeriod**

Time unit multiplier for the relative option relevant underlying date offset.

Type: **int**

Used in components: **ProvisionOptionRelevantUnderlyingDate**

**180.2.4419 ProvisionOptionRelevantUnderlyingDateOffsetUnit**

Time unit associated with the relative option relevant underlying date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **ProvisionOptionRelevantUnderlyingDate**

**180.2.4420 ProvisionOptionRelevantUnderlyingDateRelativeTo**

Specifies the anchor date when the date relevant to the underlying trade on exercise is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **ProvisionOptionRelevantUnderlyingDate**

**180.2.4421 ProvisionOptionRelevantUnderlyingDateUnadjusted**

The unadjusted date on the underlying set by the exercise of an option. What this date is depends on the option (e.g. in a swaption it is the swap effective date, in an extendible/cancelable provision it is the swap termination date).

Type: **LocalMktDate**

Used in components: **ProvisionOptionRelevantUnderlyingDate**

**180.2.4422 ProvisionOptionSinglePartyBuyerSide**

If optional early termination is not available to both parties then this component identifies the buyer of the option through its side of the trade.

Type: **int**

Allowed values in ProvisionOptionSinglePartyBuyerSideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **ProvisionGrp**

**180.2.4423 ProvisionOptionSinglePartySellerSide**

If optional early termination is not available to both parties then this component identifies the seller of the option through its side of the trade.

Type: **int**

Allowed values in ProvisionOptionSinglePartyBuyerSideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **ProvisionGrp**

#### **180.2.4424 ProvisionParties**

ProvisionParties is a repeating component within the Provision component used to report the parties identified in the contract provision.

Name	Mult.	Type	Description
NoProvisionPartyIDs	[1..1]	NumInGroup	
ProvisionPartyID	[0..1]	String	Required if NoProvisionPartyIDs(40174) > 0.
ProvisionPartyIDSource	[0..1]	CodeSet	Required if NoProvisionPartyIDs(40174) > 0.
ProvisionPartyRole	[0..1]	CodeSet	Required if NoProvisionPartyIDs(40174) > 0.
ProvisionPartyRoleQualifier	[0..1]	CodeSet	
ProvisionPtysSubGrp	[0..*]	Group	

Used in groups: **ProvisionGrp**

#### **180.2.4425 ProvisionPartyID**

The party identifier/code for the payment settlement party.

Type: **String**

Used in groups: **ProvisionParties**

#### **180.2.4426 ProvisionPartyIDSource**

Identifies class or source of the ProvisionPartyID(40175) value.

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.

Code	Name	Description
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **ProvisionParties**

### 180.2.4427 ProvisionPartyRole

Identifies the type or role of ProvisionPartyID(40175) specified.

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)



Code	Name	Description
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party

Code	Name	Description
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)

Code	Name	Description
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionV- enue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm

Code	Name	Description
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor

Code	Name	Description
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **ProvisionParties**

**180.2.4428 ProvisionPartyRoleQualifier**

Used to further qualify the value of ProvisionPartyRole(40177).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange

Code	Name	Description
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **ProvisionParties**

#### 180.2.4429 ProvisionPartySubID

Party sub-identifier, if applicable, for ProvisionPartyID(40175).

Type: **String**

Used in groups: **ProvisionPtysSubGrp**

**180.2.4430 ProvisionPartySubIDType**

The type of ProvisionPartySubID(40179).

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker



Code	Name	Description
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.

Code	Name	Description
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **ProvisionPtysSubGrp**

**180.2.4431 ProvisionPtysSubGrp**

ProvisionPtysSubGrp is a repeating component within the ProvisionParties component used to extend information to be reported for the party.

Name	Mult.	Type	Description
NoProvisionPartySubIDs	[1..1]	NumInGroup	
ProvisionPartySubID	[0..1]	String	Required if NoProvisionPartySubIDs(40178) > 0.
ProvisionPartySubIDType	[0..1]	CodeSet	Required if NoProvisionPartySubIDs(40178) > 0.

Used in groups: [ProvisionParties](#)

**180.2.4432 ProvisionText**

Free form text to specify additional information or enumeration description when a standard value does not apply.

Type: [String](#)

Used in groups: [ProvisionGrp](#)

**180.2.4433 ProvisionType**

Type of provisions.

Type: [int](#)

Allowed values in ProvisionTypeCodeSet:

Code	Name	Description
0	MandatoryEarlyTermination	Mandatory early termination
1	OptionalEarlyTermination	Optional early termination
2	Cancelable	Cancelable
3	Extendable	Extendable. The contract can be extended by either party usually with a specific time notice prior to the expiry date. In the context of EU SFTR reporting this corresponds to "termination optionality" code "ETSB".
4	MutualEarlyTermination	Mutual early termination

Code	Name	Description
5	Evergreen	Evergreen. The contract automatically renews after the expiry date until one party gives the other notice to terminate. In the context of EU SFTR reporting this corresponds to "termination optionality" code "EGRN".
6	Callable	Callable. Contract is callable.
7	Puttable	Puttable. Contract is puttable.

Used in groups: [ProvisionGrp](#)

#### 180.2.4434 PtysSubGrp

Name	Mult.	Type	Description
<a href="#">NoPartySubIDs</a>	[1..1]	NumInGroup	
<a href="#">PartySubID</a>	[0..1]	String	
<a href="#">PartySubIDType</a>	[0..1]	CodeSet	

Used in groups: [Parties](#)

#### 180.2.4435 PublishTrdIndicator

Indicates if a trade should be reported via a market reporting service.

Type: [Boolean](#)

Allowed values in PublishTrdIndicatorCodeSet:

Code	Name	Description
N	DoNotReportTrade	Do Not Report Trade
Y	ReportTrade	Report Trade

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

**180.2.4436 PutOrCall**

Indicates whether an option contract is a put, call, chooser or undetermined.

Type: **int**

Allowed values in PutOrCallCodeSet:

Code	Name	Description
0	Put	Put. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate receiver or into a CDS contract as a seller of protection or for the case of a Floor.
1	Call	Call. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate payer or into a CDS contract as a buyer of protection or for the case of a Cap.
2	Other	Other. In the context of ESMA RTS 22 reporting, this value may be used when, at the time of execution, the option right cannot be determined.
3	Chooser	Chooser. Indicates that the option buyer may choose to buy or sell the underlying security on exercise or if a Swaption to pay or receive the underlying IRS cash flow stream or to buy or sell CDS protection.

Used in components: **Instrument**

**180.2.4437 QtyType**

Type of quantity specified in quantity field. ContractMultiplier (tag 231) is required when QtyType = 1 (Contracts). UnitOfMeasure (tag 996) and TimeUnit (tag 997) are required when QtyType = 2 (Units of Measure per Time Unit).

Type: **int**

Allowed values in QtyTypeCodeSet:

Code	Name	Description
0	Units	Units (shares, par, currency)
1	Contracts	Contracts
2	UnitsOfMeasurePerTimeUnit	Unit of Measure per Time Unit



Used in components: [SettlTradeDetails](#)

Used in groups: [InstrmtMatchSideGrp](#), [ListOrdGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [SideCrossOrdModGrp](#)

Used in messages: [Advertisement](#), [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [Confirmation](#), [ExecutionReport](#), [IOI](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### **180.2.4438 Quantity**

Overall/total quantity (e.g. number of shares)

(Prior to FIX 4.2 this field was of type int)

Type: [Qty](#)

Used in groups: [InstrmtMatchSideGrp](#)

Used in messages: [Advertisement](#), [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AllocationReportAck](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#)

### **180.2.4439 QuantityDate**

Date associated to the quantity that is being reported for the position.

Type: [LocalMktDate](#)

Used in groups: [PositionQty](#), [TradePositionQty](#)

### **180.2.4440 QuotCxlEntriesGrp**

Name	Mult.	Type	Description
<a href="#">NoQuoteEntries</a>	[1..1]	NumInGroup	The number of securities (instruments) whose quotes are to be canceled. Not required when cancelling all quotes.
<a href="#">Instrument</a>	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"

Name	Mult.	Type	Description
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	
InstrmtLegGrp	[0..*]	Group	

Used in messages: [QuoteCancel](#)

#### 180.2.4441 QuoteAckStatus

Acknowledgement status of a Quote(35=S) or QuoteCancel(35=Z) message submission.

Type: [int](#)

Allowed values in QuoteAckStatusCodeSet:

Code	Name	Description
0	ReceivedNotYetProcessed	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected

Used in messages: [QuoteAck](#)

#### 180.2.4442 QuoteAttributeGrp

The QuoteAttributeGrp component provides additional attributes about the quote. Attributes included in this component are primarily "indicators" that may be associated with regulatory requirements and are typically not part of normal trading activities.

Name	Mult.	Type	Description
NoQuoteAttributes	[1..1]	NumInGroup	
QuoteAttributeType	[0..1]	CodeSet	Required if NoQuoteAttributes(2706) > 0.
QuoteAttributeValue	[0..1]	String	Required if NoQuoteAttributes(2706) > 0.

Used in messages: [Quote](#), [QuoteAck](#), [QuoteStatusReport](#)

**180.2.4443 QuoteAttributeType**

The type of attribute for the quote.

Type: **int**

Allowed values in QuoteAttributeTypeCodeSet:

Code	Name	Description
0	QuoteAboveStandardMarketSize	Quote is above standard market size. In the context of ESMA pre-trade transparency under MiFIR to make prices public, the quote size is above standard market size, therefore the price is not made public. Applicable for cash equities instruments.
1	QuoteAboveSpecificInstrumentSize	Quote is above size specific to the instrument. In the context of ESMA pre-trade transparency under MiFID to make public prices, the quote size is above the size specific to the instrument, therefore the price is not or will not be made public. Applicable for non-cash equities instruments.
2	QuoteApplicableForLiquidityProvisionActivity	Quote applicable for liquidity provision activity. In the context of ESMA RTS 24 Article 3, when QuoteAttributeValue(2708)=Y, it signifies that the quote was submitted "as part of a market making strategy pursuant to Articles 17 and 18 of Directive 2014/65/EU, or is submitted as part of another activity in accordance with Article 3" (of RTS 24).
3	QuoteIssuerStatus	Quote issuer status. Indicate whether quote issuer is available or not. Can be used in the context of US CAT to indicate if a market maker's quote is open (O) or closed (C) whenever the quote is sent to an inter-dealer quotation system.
4	BidOrAskRequest	Bid or ask request. Indicate explicitly whether a request for a quote is a request for a bid or an ask.

Used in groups: **QuoteAttributeGrp**

**180.2.4444 QuoteAttributeValue**

The value associated with the quote attribute type specified in QuoteAttributeType(2707).

Type: **String**

Used in groups: **QuoteAttributeGrp**

**180.2.4445 QuoteCancelType**

Identifies the type of quote cancel.

Type: **int**

Allowed values in QuoteCancelTypeCodeSet:

Code	Name	Description
1	CancelForOneOrMoreSecurities	Cancel quotes for one or more securities
2	CancelForSecurityType	Cancel quotes for security type(s)
3	CancelForUnderlyingSecurity	Cancel quotes for underlying security
4	CancelAllQuotes	Cancel all quotes
5	CancelSpecifiedSingleQuote	Cancel specified single quote. Cancel single quote specified in QuoteID(117) or SecondaryQuoteID(1751)
6	CancelByTypeOfQuote	Cancel by type of quote. Cancel quotes by type of quote specified in QuoteType(537)
7	CancelForSecurityIssuer	Cancel quotes for an issuer
8	CancelForIssuerOfUnderlyingSecurity	Cancel quotes for an issuer of underlying security

Used in messages: **MassQuoteAck**, **QuoteAck**, **QuoteCancel**, **QuoteStatusReport**

**180.2.4446 QuoteCondition**

Space-delimited list of conditions describing a quote.

Type: **MultipleStringValue**

Allowed values in QuoteConditionCodeSet:

Code	Name	Description
A	Open	Open/Active
B	Closed	Closed/Inactive
C	ExchangeBest	Exchange Best
D	ConsolidatedBest	Consolidated Best
E	Locked	Locked
F	Crossed	Crossed
G	Depth	Depth

Code	Name	Description
H	FastTrading	Fast Trading
I	NonFirm	Non-Firm
L	Manual	Manual/Slow Quote
J	OutrightPrice	Outright Price
K	ImpliedPrice	Implied Price
M	DepthOnOffer	Depth on Offer
N	DepthOnBid	Depth on Bid
O	Closing	Closing
P	NewsDissemination	News Dissemination
Q	TradingRange	Trading Range
R	OrderInflux	Order Influx
S	DueToRelated	Due to Related
T	NewsPending	News Pending
U	AdditionalInfo	Additional Info
V	AdditionalInfoDueToRelated	Additional Info due to related
W	Resume	Resume
X	ViewOfCommon	View of Common
Y	VolumeAlert	Volume Alert
Z	OrderImbalance	Order Imbalance
a	EquipmentChangeover	Equipment Changeover
b	NoOpen	No Open / No Resume
c	RegularETH	Regular ETH
d	AutomaticExecution	Automatic Execution
e	AutomaticExecutionETH	Automatic Execution ETH
f	FastMarketETH	Fast Market ETH
g	InactiveETH	Inactive ETH
h	Rotation	Rotation
i	RotationETH	Rotation ETH
j	Halt	Halt
k	HaltETH	Halt ETH
l	DueToNewsDissemination	Due to News Dissemination
m	DueToNewsPending	Due to News Pending
n	TradingResume	Trading Resume
o	OutOfSequence	Out of Sequence

Code	Name	Description
p	BidSpecialist	Bid Specialist
q	OfferSpecialist	Offer Specialist
r	BidOfferSpecialist	Bid Offer Specialist
s	EndOfDaySAM	End of Day SAM
t	ForbiddenSAM	Forbidden SAM
u	FrozenSAM	Frozen SAM
v	PreOpeningSAM	PreOpening SAM
w	OpeningSAM	Opening SAM
x	OpenSAM	Open SAM
y	SurveillanceSAM	Surveillance SAM
z	SuspendedSAM	Suspended SAM
0	ReservedSAM	Reserved SAM
1	NoActiveSAM	No Active SAM
2	Restricted	Restricted
3	RestOfBookVWAP	Rest of Book VWAP
4	BetterPricesInConditionalOrders	Better Prices in Conditional Orders
5	MedianPrice	Median Price
6	FullCurve	Full Curve
7	FlatCurve	Flat Curve

Used in components: **MDStatisticParameters**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.4447 QuoteDisplayTime**

Time by which the quote will be displayed.

Type: **UTCTimestamp**

Used in groups: **QuotReqGrp**

#### **180.2.4448 QuoteEntryID**

Unique identifier for a quote. The QuoteEntryID stays with the quote as a static identifier even if the quote is updated.

Type: **String**

Used in groups: **MDFullGrp**, **MDIncGrp**, **QuotEntryAckGrp**, **QuotEntryGrp**

### 180.2.4449 QuoteEntryRejectReason

Reason Quote Entry was rejected:

Type: **int**

Allowed values in QuoteRejectReasonCodeSet:

Code	Name	Description
1	UnknownSymbol	Unknown symbol (security). In the context of IA FX Reject codes, Trade Request Rejection Category F, this may be used with QuoteStatus(297)=5 (Rejected) to indicate product is not supported, e.g. by the specific venue, tenor restrictions on the market participant(s) involved.
2	Exchange	Exchange (security) closed
3	QuoteRequestExceedsLimit	Quote Request exceeds limit
4	TooLateToEnter	Too late to enter
5	UnknownQuote	Unknown quote
6	DuplicateQuote	Duplicate quote
7	InvalidBid	Invalid bid/ask spread
8	InvalidPrice	Invalid price. In the context of IA FX Reject codes, Trade Request Rejection Category A-2, this may be used with QuoteStatus(297)=5 (Rejected) to indicate price is not valid due to "last look latency".
9	NotAuthorizedToQuoteSecurity	Not authorized to quote security
10	PriceExceedsCurrentPriceBand	Price exceeds current price band
11	QuoteLocked	Quote locked - unable to update/cancel
12	InvalidOrUnknownSecurityIssuer	Invalid or unknown security issuer
13	InvalidOrUnknownIssuerOfUnderlyingSecurity	Invalid or unknown issuer of underlying security
14	NotionalValueExceedsThreshold	Notional value exceeds threshold
15	PriceExceedsCurrentPriceBandDepr	Price exceeds current price band
16	ReferencePriceNotAvailable	Reference price not available

Code	Name	Description
17	InsufficientCreditLimit	Insufficient credit limit. In the context of IA FX Reject codes, Trade Request Rejection Category C, this may be used with QuoteStatus(297)=5 (Rejected) to indicate credit limit is exceeded or not in place.
18	ExceededClipSizeLimit	Exceeded clip size limit
19	ExceededMaxNotionalOrderAmt	Exceeded maximum notional order amount
20	ExceededDV01PV01Limit	Exceeded DV01/PV01 limit
21	ExceededCS01Limit	Exceeded CS01 limit
22	UnavailablePriceLiquidity	Unavailable price or liquidity. In the context of IA FX Reject codes, Trade Request Rejection Category B, this may be used with QuoteStatus(297)=5 (Rejected) to indicate the "Hit/lift" was not subjected to last look but pricing or liquidity is no longer available for execution.
23	InvalidMissingEntitlements	Invalid or missing entitlements. In the context of IA FX Reject codes, Trade Request Rejection Category D, this may be used with QuoteStatus(297)=5 (Rejected) to indicate the counterparty is not authorized or has missing entitlements.
24	UnknownAccounts	Unknown account(s). In the context of IA FX Reject codes, Trade Request Rejection Category D, this may be used with QuoteStatus(297)=5 (Rejected) to indicate the account/fund is unknown or not setup.
99	Other	Other. In the context of IA FX Reject codes, Trade Request Rejection Category E, order rejected due to other exceptions. Further detail may be provided in RejectText(1328) or Text(58), with preference for RejectText(1328) if field is present in the message.

Used in groups: [QuotEntryAckGrp](#)

### 180.2.4450 QuoteEntryStatus

Identifies the status of an individual quote. See also QuoteStatus(297) which is used for single Quotes.

Type: [int](#)

Allowed values in QuoteEntryStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted



Code	Name	Description
5	Rejected	Rejected
6	RemovedFromMarket	Removed from Market
7	Expired	Expired
12	LockedMarketWarning	Locked Market Warning
13	CrossMarketWarning	Cross Market Warning
14	CanceledDueToLockMarket	Canceled due to Lock Market
15	CanceledDueToCrossMarket	Canceled due to Cross Market
16	Active	Active

Used in groups: [QuotEntryAckGrp](#)

#### **180.2.4451 QuoteID**

Unique identifier for quote

Type: [String](#)

Used in groups: [ListOrdGrp](#), [QuotReqGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [MassQuote](#), [MassQuoteAck](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [Quote](#), [QuoteAck](#), [QuoteCancel](#), [QuoteResponse](#), [QuoteStatusReport](#), [QuoteStatusRequest](#)

#### **180.2.4452 QuoteModelType**

Quote model type

Type: [int](#)

Allowed values in QuoteModelTypeCodeSet:

Code	Name	Description
1	QuoteEntry	Quote entry. New quote is entered or previously submitted quote is updated in full without regard to amount executed when a subsequent quote (e.g. with the same QuoteID reference) is received by the Recipient of the quote message.

Code	Name	Description
2	QuoteModification	Quote modification. Previously submitted quote must be present and is updated, taking into consideration the amount already executed when a subsequent quote (e.g. with the same QuoteID reference) is received by the Recipient of the quote message.

Used in messages: [MassQuote](#), [Quote](#)

### 180.2.4453 QuoteMsgID

Unique identifier for a quote message.

Type: [String](#)

Used in messages: [ExecutionReport](#), [Quote](#), [QuoteAck](#), [QuoteCancel](#), [QuoteResponse](#), [QuoteStatusReport](#)

### 180.2.4454 QuotEntryAckGrp

Name	Mult.	Type	Description
<a href="#">NoQuoteEntries</a>	[1..1]	NumInGroup	The number of quotes for this Symbol (QuoteSet) that follow in this message.
<a href="#">QuoteEntryID</a>	[0..1]	String	Uniquely identifies the quote across the complete set of all quotes for a given quote provider. First field in repeating group. Required if NoQuoteEntries > 0.
<a href="#">Instrument</a>	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
<a href="#">InstrmtLegGrp</a>	[0..*]	Group	
<a href="#">BidPx</a>	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
<a href="#">OfferPx</a>	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
<a href="#">BidSize</a>	[0..1]	Qty	

Name	Mult.	Type	Description
OfferSize	[0..1]	Qty	
ValidUntilTime	[0..1]	UTCTimestamp	
BidSpotRate	[0..1]	Price	May be applicable for F/X quotes
OfferSpotRate	[0..1]	Price	May be applicable for F/X quotes
BidForwardPoints	[0..1]	PriceOffset	May be applicable for F/X quotes
OfferForwardPoints	[0..1]	PriceOffset	May be applicable for F/X quotes
MidPx	[0..1]	Price	
BidYield	[0..1]	Percentage	
MidYield	[0..1]	Percentage	
OfferYield	[0..1]	Percentage	
TransactTime	[0..1]	UTCTimestamp	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Can be used with forex quotes to specify a specific "value date"
OrdType	[0..1]	CodeSet	Can be used to specify the type of order the quote is for
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
BidForwardPoints2	[0..1]	PriceOffset	Bid F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
OfferForwardPoints2	[0..1]	PriceOffset	Offer F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
Currency	[0..1]	Currency	Can be used to specify the currency of the quoted price.
CurrencyCodeSource	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	
QuoteEntryStatus	[0..1]	CodeSet	

QuoteEntryRejectReason	[0..1]	CodeSet	Reason Quote Entry was rejected.
------------------------	--------	---------	----------------------------------

Used in groups: [QuotSetAckGrp](#)

## 180.2.4455 QuotEntryGrp

Name	Mult.	Type	Description
NoQuoteEntries	[1..1]	NumInGroup	The number of quotes for this Symbol (instrument) (QuoteSet) that follow in this message.
QuoteEntryID	[1..1]	String	Uniquely identifies the quote across the complete set of all quotes for a given quote provider.
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
InstrmtLegGrp	[0..*]	Group	
BidPx	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
OfferPx	[0..1]	Price	If F/X quote, should be the "all-in" rate (spot rate adjusted for forward points). Note that either BidPx, OfferPx or both must be specified.
TotalBidSize	[0..1]	Qty	
TotalOfferSize	[0..1]	Qty	
BidSize	[0..1]	Qty	
OfferSize	[0..1]	Qty	
ValidUntilTime	[0..1]	UTCTimestamp	
BidSpotRate	[0..1]	Price	May be applicable for F/X quotes
OfferSpotRate	[0..1]	Price	May be applicable for F/X quotes
BidForwardPoints	[0..1]	PriceOffset	May be applicable for F/X quotes
OfferForwardPoints	[0..1]	PriceOffset	May be applicable for F/X quotes
MidPx	[0..1]	Price	
BidYield	[0..1]	Percentage	
MidYield	[0..1]	Percentage	
OfferYield	[0..1]	Percentage	
TransactTime	[0..1]	UTCTimestamp	
TradingSessionID	[0..1]	CodeSet	

Name	Mult.	Type	Description
TradingSessionSubID	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Can be used with forex quotes to specify a specific "value date"
OrdType	[0..1]	CodeSet	Can be used to specify the type of order the quote is for
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
BidForwardPoints2	[0..1]	PriceOffset	Bid F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
OfferForwardPoints2	[0..1]	PriceOffset	Offer F/X forward points of the future portion of a F/X swap quote added to spot rate. May be a negative value
Currency	[0..1]	Currency	Can be used to specify the currency of the quoted price.
CurrencyCodeSource	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	

Used in groups: **QuotSetGrp**

### 180.2.4456 QuotePriceType

Code to represent price type requested in Quote.

If the Quote Request is for a Swap, values 1-8 apply to all legs.

Type: **int**

Allowed values in QuotePriceTypeCodeSet:

Code	Name	Description
1	Percent	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
2	PerShare	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed Amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points relative to benchmark). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	YieldSpread	Yield Spread (swaps)
10	Yield	Yield
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example: the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools.
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)
22	BasisPoints	Basis points. When the price is not spread based
23	UpFrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageOfNotional	Percentage of notional

Used in groups: [QuotReqGrp](#), [QuotReqRjctGrp](#)

**180.2.4457 QuoteQualifier**

Code to qualify Quote use and other aspects of price negotiation.

Type: **char**

Allowed values in IOIQualifierCodeSet:

Code	Name	Description
A	AllOrNone	All or None (AON)
B	MarketOnClose	Market On Close (MOC) (held to close)
C	AtTheClose	At the close (around/not held to close)
D	VWAP	VWAP (Volume Weighted Average Price)
E	Axe	Axe. Indicates that a quote is an Axe, without specifying a side preference. Mutually exclusive with F(Axe on bid) and G(Axe on offer).
F	AxeOnBid	Axe on bid. Indicates that a quote is an Axe, with a preference to execute on the bid side. Mutually exclusive with E(Axe) and G (Axe on offer)
G	AxeOnOffer	Axe on offer. Indicates that a quote is an Axe, with a preference to execute on the offer side. Mutually exclusive with E(Axe) and F (Axe on bid)
H	ClientNaturalWorking	Client natural working. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type C2 – Client Natural (Working). A client should be able to seek verification (from IOI publisher's management/compliance) that, for any C2 IOIs received, there was a corresponding live client order for at least the advertised size prior to the IOI being generated. Resulting trades are expected to be of a riskless nature.
I	InTouchWith	In touch with. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type P1 - Potential. Post-execution, a client should be able to seek verification (from IOI publisher's management/ compliance) that, for any P1 IOIs received and executed against, there was by time of the execution, an opposing specific client order. Resulting trades are expected to be of a riskless nature. If the anticipated client order does not materialise, and the broker elects to commit capital, this must be disclosed prior to execution.

Code	Name	Description
J	PositionWanted	Position wanted. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type H2 – Position Wanted. Brokers will be likely be sourcing liquidity and therefore may advertise the size of IOI they wish; however, clients can expect the broker to honour the size of IOI shown. The presumption is that there is no intent to immediately unwind the position without notification, however, brokers may provide additional granularity to the category and may offer bilateral post trade commitments. Brokers will also offer clients a feedback mechanism.
K	MarketMaking	Market making. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type H3 – Market Making, no enforcement is required.
L	Limit	Limit
M	MoreBehind	More Behind
N	ClientNaturalBlock	Client natural block. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type C1 - Client Natural (Block). A client should be able to seek verification (from IOI publisher's management/compliance) that, for any C1 IOIs received, there was a corresponding live client order for at least the advertised size prior to the IOI being generated. Resulting trades are expected to be of a riskless nature.
O	AtTheOpen	At the Open
P	TakingAPosition	Taking a Position
Q	AtTheMarket	At the Market (previously called Current Quote)
R	ReadyToTrade	Ready to Trade
S	PortfolioShown	Inventory or Portfolio Shown
T	ThroughTheDay	Through the Day
U	Unwind	Unwind. With reference to the AFME/IA Framework for Indications of Interest, this is to be used to denote IOIs of type H1 - Unwind. Brokers will be responsible for ensuring that the size of the IOI reflects the actual house position in the relevant business unit and should not inflate the size of the IOI. The presumption is that there is no intent to immediately replace the position without notification, however, brokers may provide additional granularity to the category and may offer bilateral post trade commitments. Brokers will also offer clients a feedback mechanism.
V	Versus	Versus



Code	Name	Description
W	Indication	Indication - Working Away
X	CrossingOpportunity	Crossing Opportunity
Y	AtTheMidpoint	At the Midpoint
Z	PreOpen	Pre-open
1	QuantityNegotiable	Quantity is negotiable. When specified, the dealer may counter with a reduced quantity in its Quotes in response to QuoteRequest(35=R). All-or-none if omitted.
2	AllowLateBids	Allow late bids. When specified in QuoteRequest(35=R) the dealer may submit quotes after curtain time has elapsed.
3	ImmediateOrCounter	Immediate or counter. When specified, the buy-side customer is permitted to counter a firm quote during wiretime.
4	AutoTrade	Auto trade. Trade is in an auto-trading mode whereby the best quote that satisfies user criteria as determined by the trading platform will be accepted automatically.
a	AutomaticSpot	Automatic spot. At completion of price negotiation based on spread the trading platform will propose a benchmark spot price which may be filled immediately by the dealer or countered.
b	PlatformCalculatedSpot	Platform calculated spot. At completion of price negotiation based on spread the trading platform will supply a benchmark spot price and immediately complete the trade reporting fill. There is no dealer last look.
c	OutsideSpread	Outside spread. The IOI is identifiable outside the current bid/offer.
d	DeferredSpot	Deferred spot. At a future time after completion of price negotiation based on spread and reported in StrikeTime(443) the trading platform will propose a benchmark spot price which may be filled immediately by the dealer or countered.
n	NegotiatedSpot	Negotiated spot. Once price negotiation based on spread is completed negotiation of the benchmark spot price proceeds immediately.

Used in groups: **QuotQualGrp**

#### 180.2.4458 QuoteRejectReason

Reason quote was rejected.

Type: **int**

## Allowed values in QuoteRejectReasonCodeSet:

Code	Name	Description
1	UnknownSymbol	Unknown symbol (security). In the context of IA FX Reject codes, Trade Request Rejection Category F, this may be used with QuoteStatus(297)=5 (Rejected) to indicate product is not supported, e.g. by the specific venue, tenor restrictions on the market participant(s) involved.
2	Exchange	Exchange (security) closed
3	QuoteRequestExceedsLimit	Quote Request exceeds limit
4	TooLateToEnter	Too late to enter
5	UnknownQuote	Unknown quote
6	DuplicateQuote	Duplicate quote
7	InvalidBid	Invalid bid/ask spread
8	InvalidPrice	Invalid price. In the context of IA FX Reject codes, Trade Request Rejection Category A-2, this may be used with QuoteStatus(297)=5 (Rejected) to indicate price is not valid due to "last look latency".
9	NotAuthorizedToQuoteSecurity	Not authorized to quote security
10	PriceExceedsCurrentPriceBand	Price exceeds current price band
11	QuoteLocked	Quote locked - unable to update/cancel
12	InvalidOrUnknownSecurityIssuer	Invalid or unknown security issuer
13	InvalidOrUnknownIssuerOfUnderlyingSecurity	Invalid or unknown issuer of underlying security
14	NotionalValueExceedsThreshold	Notional value exceeds threshold
15	PriceExceedsCurrentPriceBandDepr	Price exceeds current price band
16	ReferencePriceNotAvailable	Reference price not available
17	InsufficientCreditLimit	Insufficient credit limit. In the context of IA FX Reject codes, Trade Request Rejection Category C, this may be used with QuoteStatus(297)=5 (Rejected) to indicate credit limit is exceeded or not in place.
18	ExceededClipSizeLimit	Exceeded clip size limit
19	ExceededMaxNotionalOrderAmt	Exceeded maximum notional order amount
20	ExceededDV01PV01Limit	Exceeded DV01/PV01 limit
21	ExceededCS01Limit	Exceeded CS01 limit

Code	Name	Description
22	UnavailablePriceLiquidity	Unavailable price or liquidity. In the context of IA FX Reject codes, Trade Request Rejection Category B, this may be used with QuoteStatus(297)=5 (Rejected) to indicate the "Hit/lift" was not subjected to last look but pricing or liquidity is no longer available for execution.
23	InvalidMissingEntitlements	Invalid or missing entitlements. In the context of IA FX Reject codes, Trade Request Rejection Category D, this may be used with QuoteStatus(297)=5 (Rejected) to indicate the counterparty is not authorized or has missing entitlements.
24	UnknownAccounts	Unknown account(s). In the context of IA FX Reject codes, Trade Request Rejection Category D, this may be used with QuoteStatus(297)=5 (Rejected) to indicate the account/fund is unknown or not setup.
99	Other	Other. In the context of IA FX Reject codes, Trade Request Rejection Category E, order rejected due to other exceptions. Further detail may be provided in RejectText(1328) or Text(58), with preference for RejectText(1328) if field is present in the message.

Used in messages: [MassQuoteAck](#), [QuoteAck](#), [QuoteStatusReport](#)

#### **180.2.4459 QuoteReqID**

Unique identifier for a QuoteRequest(35=R).

Type: [String](#)

Used in messages: [MassQuote](#), [MassQuoteAck](#), [Quote](#), [QuoteAck](#), [QuoteCancel](#), [QuoteRequest](#), [QuoteRequestReject](#), [QuoteResponse](#), [QuoteStatusReport](#)

#### **180.2.4460 QuoteRequestRejectReason**

Reason quote request was rejected.

Type: [int](#)

Allowed values in QuoteRequestRejectReasonCodeSet:

Code	Name	Description
1	UnknownSymbol	Unknown Symbol (Security). In the context of IA FX Reject codes, Quote Rejection Category F, the RFQ is rejected due to unknown or unsupported product, e.g. by the specific venue, tenor restrictions on the market participant(s) involved.
2	Exchange	Exchange (Security) Closed
3	QuoteRequestExceedsLimit	Quote Request Exceeds Limit. In the context of IA FX Reject codes, Quote Rejection Category D, the RFQ is rejected due to risk limit exceeded or not in place.
4	TooLateToEnter	Too Late to enter
5	InvalidPrice	Invalid Price
6	NotAuthorizedToRequestQuote	Not Authorized To Request Quote
7	NoMatchForInquiry	No Match For Inquiry
8	NoMarketForInstrument	No Market For Instrument. In the context of IA FX Reject codes, Quote Rejection Category F, the RFQ is rejected due to unknown or unsupported product.
9	NoInventory	No Inventory
10	Pass	Pass
11	InsufficientCredit	Insufficient credit. In the context of IA FX Reject codes, Quote Rejection Category A, the RFQ is rejected due to credit limit exceeded or not in place.
12	ExceededClipSizeLimit	Exceeded clip size limit
13	ExceededMaxNotionalOrderAmt	Exceeded maximum notional order amount
14	ExceededDV01PV01Limit	Exceeded DV01/PV01 limit
15	ExceededCS01Limit	Exceeded CS01 limit
16	UnavailablePriceLiquidity	Unavailable price or liquidity. In the context of IA FX Reject codes, Quote Rejection Category A, the RFQ is rejected due to unavailable price information.
17	UnmetRegulatoryRequirement	Unmet regulatory requirement. In the context of IA FX Reject codes, Quote Rejection Category B, the RFQ is rejected due to regulatory requirements not being met. For example, a RFQ is submitted into a SEF by a non-SEF participant, or an NDF was submitted into the trading platform.
18	UnknownAccounts	Unknown account(s). In the context of IA FX Reject codes, Quote Rejection Category F, the RFQ is rejected due to static data when the account/fund is not setup or unknown.
19	InvalidMissingEntitlements	Invalid or missing entitlements. In the context of IA FX Reject codes, Quote Rejection Category F, the RFQ is rejected due to static data when the counterparty is not authorized or has missing entitlements.

Code	Name	Description
99	Other	Other. In the context of IA FX Reject codes, Quote Rejection Category E, the RFQ is rejected due to other exceptions. Further detail may be provided in RejectText(1328) or Text(58), with preference for RejectText(1328) if field is present in the message.

Used in messages: [QuoteRequestReject](#)

### 180.2.4461 QuoteRequestType

Indicates the type of Quote Request being generated

Type: [int](#)

Allowed values in QuoteRequestTypeCodeSet:

Code	Name	Description
1	Manual	Manual
2	Automatic	Automatic
3	ConfirmQuote	Confirm quote

Used in groups: [QuotReqGrp](#), [QuotReqRjctGrp](#), [RFQReqGrp](#)

### 180.2.4462 QuoteRespID

Message reference for Quote Response

Type: [String](#)

Used in messages: [ExecutionReport](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

### 180.2.4463 QuoteResponseLevel

Level of Response requested from receiver of quote messages. A default value should be bilaterally agreed.

Type: [int](#)

Allowed values in QuoteResponseLevelCodeSet:

Code	Name	Description
0	NoAcknowledgement	No Acknowledgement
1	AcknowledgeOnlyNegativeOrErroneousQuotes	Acknowledge only negative or erroneous quotes
2	AcknowledgeEachQuoteMessage	Acknowledge each quote message
3	SummaryAcknowledgement	Summary Acknowledgement

Used in messages: [MassQuote](#), [MassQuoteAck](#), [Quote](#), [QuoteCancel](#)

### 180.2.4464 QuoteRespType

Identifies the type of Quote Response.

Type: [int](#)

Allowed values in QuoteRespTypeCodeSet:

Code	Name	Description
1	Hit	Hit/Lift
2	Counter	Counter
3	Expired	Expired
4	Cover	Cover. Trade was done with another quote provider. Quote provider's original quoted price was the best price not traded (i.e. the cover price).
5	DoneAway	Done away. Trade was done with another quote provider.
6	Pass	Pass
7	EndTrade	End trade. Indicates an end to the trade negotiation.
8	TimedOut	Timed out
9	Tied	Tied. Trade was done with another quote provider. Quote provider's original quoted price was the same as the traded price.
10	TiedCover	Tied cover. Trade was done with another quote provider. Quote provider's original quoted price was the best price not traded. There were other quote provider(s) at the same price.
11	Accept	Accept. Used in a response to acknowledge an action communicated by the counterparty.

Code	Name	Description
12	TerminateContract	Terminate contract. Used to communicate the termination of an existing contract.

Used in messages: [QuoteResponse](#)

#### **180.2.4465 QuoteSetID**

Unique id for the Quote Set.

Type: [String](#)

Used in groups: [QuotSetAckGrp](#), [QuotSetGrp](#)

#### **180.2.4466 QuoteSetValidUntilTime**

Indicates expiration time of this particular QuoteSet (always expressed in UTC (Universal Time Coordinated, also known as "GMT"))

Type: [UTCTimestamp](#)

Used in groups: [QuotSetAckGrp](#), [QuotSetGrp](#)

#### **180.2.4467 QuoteSideIndicator**

Indicates whether single sided quotes are allowed.

Type: [Boolean](#)

Allowed values in QuoteSideIndicatorCodeSet:

Code	Name	Description
N	No	Single sided quotes are not allowed.
Y	Yes	Single sided quotes are allowed.

Used in components: [BaseTradingRules](#)

**180.2.4468 QuoteSizeRuleGrp**

Rules for minimum bid and offer sizes of quotes.

Name	Mult.	Type	Description
NoQuoteSizeRules	[1..1]	NumInGroup	Number of quote size rules.
MinBidSize	[0..1]	Qty	Required if NoQuoteSizeRules(2558) > 0.
MinOfferSize	[0..1]	Qty	Required if NoQuoteSizeRules(2558) > 0.
FastMarketIndicator	[0..1]	Boolean	Used to define the sizes applicable for fast market conditions.

Used in components: **BaseTradingRules**

**180.2.4469 QuoteStatus**

Identifies the status of the quote acknowledgement.

Type: **int**

Allowed values in QuoteStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	CancelForSymbol	Canceled for specific securities
2	CanceledForSecurityType	Canceled for specific SecurityTypes(167)
3	CanceledForUnderlying	Canceled for underlying
4	CanceledAll	Canceled all
5	Rejected	Rejected
6	RemovedFromMarket	Removed from market
7	Expired	Expired. In the context of IA FX Reject codes, Trade Request Rejection Category A-2, this may be used to indicate price or liquidity is unavailable due to "last look latency".
8	Query	Query
9	QuoteNotFound	Quote not found
10	Pending	Pending
11	Pass	Pass. In the context of IA FX Reject codes, Trade Request Rejection Category A-1, this is used by price maker to pass due to a "last look".



Code	Name	Description
12	LockedMarketWarning	Locked market warning
13	CrossMarketWarning	Crossed market warning
14	CanceledDueToLockMarket	Canceled due to locked market
15	CanceledDueToCrossMarket	Canceled due to crossed market
16	Active	Active
17	Canceled	Canceled
18	UnsolicitedQuoteReplenishment	Unsolicited quote replenishment
19	PendingEndTrade	Pending end trade
20	TooLateToEnd	Too late to end
21	Traded	Traded
22	TradedAndRemoved	Traded and removed
23	ContractTerminates	Contract terminated. Indicates a contract has been or is being terminated.

Used in messages: [MassQuoteAck](#), [QuoteStatusReport](#)

#### **180.2.4470 QuoteStatusReqID**

Unique identifier for Quote Status Request.

Type: [String](#)

Used in messages: [QuoteStatusReport](#), [QuoteStatusRequest](#)

#### **180.2.4471 QuoteType**

Identifies the type of quote.

An indicative quote is used to inform a counterparty of a market. An indicative quote does not result directly in a trade.

A tradeable quote is submitted to a market and will result directly in a trade against other orders and quotes in a market.

A restricted tradeable quote is submitted to a market and within a certain restriction (possibly based upon price or quantity) will automatically trade against orders. Order that do not comply with restrictions are sent to the quote issuer who can choose to accept or decline the order.

A counter quote is used in the negotiation model. See Volume 7 - Product: Fixed Income for example usage.

Type: **int**

Allowed values in QuoteTypeCodeSet:

Code	Name	Description
0	Indicative	Indicative
1	Tradeable	Tradeable
2	RestrictedTradeable	Restricted tradeable
3	Counter	Counter (tradeable)
4	InitiallyTradeable	Initially tradeable

Used in groups: **InstrmtMDReqGrp**, **QuotReqGrp**, **QuotReqRjctGrp**, **RFQReqGrp**

Used in messages: **MassQuote**, **MassQuoteAck**, **Quote**, **QuoteAck**, **QuoteCancel**, **QuoteResponse**, **QuoteStatusReport**

#### 180.2.4472 QuotQualGrp

Name	Mult.	Type	Description
<b>NoQuoteQualifiers</b>	[1..1]	NumInGroup	
<b>QuoteQualifier</b>	[0..1]	CodeSet	Required if NoQuoteQualifiers > 1

Used in groups: **QuotReqGrp**, **QuotReqRjctGrp**

Used in messages: **Quote**, **QuoteResponse**, **QuoteStatusReport**

#### 180.2.4473 QuotReqGrp

Name	Mult.	Type	Description
<b>NoRelatedSym</b>	[1..1]	NumInGroup	Number of related symbols (instruments) in Request
<b>Instrument</b>	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"

Name	Mult.	Type	Description
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	
PrevClosePx	[0..1]	Price	Useful for verifying security identification
QuoteRequestType	[0..1]	CodeSet	Indicates the type of Quote Request (e.g. Manual vs. Automatic) being generated.
QuoteID	[0..1]	String	Can be used when QuoteRequestType(303) = 3(Confirm Quote).
SecondaryQuoteID	[0..1]	String	Can be used when QuoteRequestType(303) = 3(Confirm Quote).
QuoteType	[0..1]	CodeSet	Type of quote being requested from counterparty or market (e.g. Indicative, Firm, or Restricted Tradeable). Valid values used by FX in the request: 0 = Indicative, 1 = Tradeable; Absence implies a request for an indicative quote.
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
TradeOriginationDate	[0..1]	LocalMktDate	
NumOfCompetitors	[0..1]	int	
Side	[0..1]	CodeSet	If OrdType = "Forex - Swap", should be the side of the future portion of a F/X swap. The absence of a side implies that a two-sided quote is being requested. For single instrument use. FX values, 1 = Buy, 2 = Sell; This is from the perspective of the Initiator. If absent then a two-sided quote is being requested for spot or forward.
QtyType	[0..1]	CodeSet	Type of quantity specified in a quantity field. For FX, if used, should be "0".
OrderQtyData	[0..1]	Component	Conditionally required for single instrument quoting when applicable for the type of instrument.
MinQty	[0..1]	Qty	
SettlType	[0..1]	CodeSet	For NDFs either SettlType (specifying the tenor) or SettlDate must be specified.
SettlDate	[0..1]	LocalMktDate	Can be used (e.g. with forex quotes) to specify the desired "value date". For NDFs either SettlType (specifying the tenor) or SettlDate must be specified.

Name	Mult.	Type	Description
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
Currency	[0..1]	Currency	Can be used to specify the desired currency of the quoted price. May differ from the 'normal' trading currency of the instrument being quote requested.
CurrencyCodeSource	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	Required for NDFs to specify the settlement currency (fixing currency).
SettlCurrencyCodeSource	[0..1]	CodeSet	
RateSource	[0..*]	Group	
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" (repeating group of Fixed Income stipulations) fields defined in "Common Components of Application Messages"
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
QuotReqLegsGrp	[0..*]	Group	
QuotQualGrp	[0..*]	Group	
TrdType	[0..1]	CodeSet	May be used by SEFs (Swap Execution Facilities) to indicate a block swap transaction.
RegulatoryTransactionType	[0..1]	CodeSet	
RegulatoryTradeIDGrp	[0..*]	Group	
NegotiationMethod	[0..1]	CodeSet	
QuotePriceType	[0..1]	CodeSet	Initiator can specify the price type the quote needs to be quoted at. If not specified, the Respondent has option to specify how quote is quoted.
PriceQualifierGrp	[0..*]	Group	
OrdType	[0..1]	CodeSet	Can be used to specify the type of order the quote request is for
ValidUntilTime	[0..1]	UTCTimestamp	Used by the quote initiator to indicate the period of time the resulting Quote must be valid until
ExpireTime	[0..1]	UTCTimestamp	The time when the request for quote or negotiation dialog will expire.

Name	Mult.	Type	Description
ResponseTime	[0..1]	UTCTimestamp	
QuoteDisplayTime	[0..1]	UTCTimestamp	
ExposureDuration	[0..1]	int	The (minimum or suggested) period of time a quote price is tradable before it becomes indicative (i.e. off-the-wire).
ExposureDurationUnit	[0..1]	CodeSet	
TransactTime	[0..1]	UTCTimestamp	Time transaction was entered
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" (Fixed Income spread or benchmark curve) fields defined in "Common Components of Application Messages"
PriceType	[0..1]	CodeSet	
Price	[0..1]	Price	Quoted or target price
MidPx	[0..1]	Price	For OTC swaps, may be used to provide the estimated mid-market-mark.
Price2	[0..1]	Price	Can be used with OrdType = "Forex - Swap" to specify the Quoted or target price for the future portion of a F/X swap.
YieldData	[0..1]	Component	Insert here the set of "YieldData" (yield-related) fields defined in "Common Components of Application Messages"
Parties	[0..*]	Group	
TradeContinuation	[0..1]	CodeSet	Maybe used to indicate quote/negotiation is for the specified post-execution trade continuation or lifecycle event.
TradeContinuationText	[0..1]	String	
EncodedTradeContinuationTextLen	[0..1]	Length	Must be set if EncodedTradeContinuationText(2371) field is specified and must immediately precede it.
EncodedTradeContinuationText	[0..1]	data	Encoded (non-ASCII characters) representation of the TradeContinuationText(2374) field in the encoded format specified via the MessageEncoding(347) field.
StrikeTime	[0..1]	UTCTimestamp	Conditionally required when QuoteQual(695) = d (Deferred spot) is specified.

Used in messages: **QuoteRequest**

**180.2.4474 QuotReqLegsGrp**

Name	Mult.	Type	Description
NoLegs	[1..1]	NumInGroup	
InstrumentLeg	[0..1]	Component	Required if NoLegs(555) > 0.
LegOrderQty	[0..1]	Qty	
LegQty	[0..1]	Qty	The LegQty(687) field is deprecated. The use of LegOrderQty(685) is recommended instead.
LegMidPx	[0..1]	Price	For OTC swaps, may be used to provide the estimated mid-market mark.
LegSwapType	[0..1]	CodeSet	
LegSettlType	[0..1]	CodeSet	
LegSettlDate	[0..1]	LocalMktDate	
LegStipulations	[0..*]	Group	
NestedParties	[0..*]	Group	
LegBenchmarkCurveData	[0..1]	Component	
LegRefID	[0..1]	String	Use of LegRefID(654) in this component is deprecated. Recommend the use of LegID(1788) in the InstrumentLeg component.

Used in groups: [QuotReqGrp](#), [QuotReqRjctGrp](#)

**180.2.4475 QuotReqRjctGrp**

Name	Mult.	Type	Description
NoRelatedSym	[1..1]	NumInGroup	Number of related symbols (instruments) in Request
Instrument	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" (symbology) fields defined in "Common Components of Application Messages"
UndInstrmtGrp	[0..*]	Group	
PrevClosePx	[0..1]	Price	Useful for verifying security identification

Name	Mult.	Type	Description
QuoteRequestType	[0..1]	CodeSet	Indicates the type of Quote Request (e.g. Manual vs. Automatic) being generated.
QuoteType	[0..1]	CodeSet	Type of quote being requested from counterparty or market (e.g. Indicative, Firm, or Restricted Tradeable)
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
TradeOriginationDate	[0..1]	LocalMktDate	
Side	[0..1]	CodeSet	If OrdType = "Forex - Swap", should be the side of the future portion of a F/X swap. The absence of a side implies that a two-sided quote is being requested. Required if specified in Quote Request message.
QtyType	[0..1]	CodeSet	
OrderQtyData	[0..1]	Component	Insert here the set of "OrderQtyData" fields defined in "Common Components of Application Messages". Required if component is specified in Quote Request message.
SettlType	[0..1]	CodeSet	
SettlDate	[0..1]	LocalMktDate	Can be used (e.g. with forex quotes) to specify the desired "value date"
SettlDate2	[0..1]	LocalMktDate	Can be used with OrdType = "Forex - Swap" to specify the "value date" for the future portion of a F/X swap.
OrderQty2	[0..1]	Qty	Can be used with OrdType = "Forex - Swap" to specify the order quantity for the future portion of a F/X swap.
Currency	[0..1]	Currency	Can be used to specify the desired currency of the quoted price. May differ from the 'normal' trading currency of the instrument being quote requested.
CurrencyCodeSource	[0..1]	CodeSet	
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" (repeating group of Fixed Income stipulations) fields defined in "Common Components of Application Messages"
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
QuotReqLegsGrp	[0..*]	Group	

Name	Mult.	Type	Description
QuotQualGrp	[0..*]	Group	
NegotiationMethod	[0..1]	CodeSet	
QuotePriceType	[0..1]	CodeSet	Initiator can specify the price type the quote needs to be quoted at. If not specified, the Respondent has option to specify how quote is quoted.
PriceQualifierGrp	[0..*]	Group	
OrdType	[0..1]	CodeSet	Can be used to specify the type of order the quote request is for
ExpireTime	[0..1]	UTCTimestamp	The time when Quote Request will expire.
TransactTime	[0..1]	UTCTimestamp	Time transaction was entered
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" (Fixed Income spread or benchmark curve) fields defined in "Common Components of Application Messages"
PriceType	[0..1]	CodeSet	
Price	[0..1]	Price	Quoted or target price
Price2	[0..1]	Price	Can be used with OrdType = "Forex - Swap" to specify the Quoted or target price for the future portion of a F/X swap.
YieldData	[0..1]	Component	Insert here the set of "YieldData" (yield-related) fields defined in "Common Components of Application Messages"
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
StrikeTime	[0..1]	UTCTimestamp	Conditionally required when QuoteQual(695) = d (Deferred spot) is specified.

Used in messages: [QuoteRequestReject](#)

#### 180.2.4476 QuotSetAckGrp

Name	Mult.	Type	Description
NoQuoteSets	[1..1]	NumInGroup	The number of sets of quotes in the message
QuoteSetID	[0..1]	String	First field in repeating group. Required if NoQuoteSets > 0



Name	Mult.	Type	Description
UnderlyingInstrument	[0..1]	Component	Insert here the set of "UnderlyingInstrument" (underlying symbology) fields defined in "Common Components of Application Messages". Required if NoQuoteSets > 0
QuoteSetValidUntilTime	[0..1]	UTCTimestamp	
TotNoQuoteEntries	[0..1]	int	Total number of quotes for the quote set across all messages. Should be the sum of all NoQuoteEntries in each message that has repeating quotes that are part of the same quote set. Required if NoQuoteEntries > 0
TotNoCxlDQuotes	[0..1]	int	Total number of quotes canceled for the quote set across all messages.
TotNoAccQuotes	[0..1]	int	Total number of quotes accepted for the quote set across all messages.
TotNoRejQuotes	[0..1]	int	Total number of quotes rejected for the quote set across all messages.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
QuotEntryAckGrp	[0..*]	Group	

Used in messages: **MassQuoteAck**

#### 180.2.4477 QuotSetGrp

Name	Mult.	Type	Description
NoQuoteSets	[1..1]	NumInGroup	The number of sets of quotes in the message
QuoteSetID	[1..1]	String	Sequential number for the Quote Set. For a given QuoteID - assumed to start at 1. Must be the first field in the repeating group.
UnderlyingInstrument	[0..1]	Component	Insert here the set of "UnderlyingInstrument" (underlying symbology) fields defined in "Common Components of Application Messages"
QuoteSetValidUntilTime	[0..1]	UTCTimestamp	

Name	Mult.	Type	Description
TotNoQuoteEntries	[1..1]	int	Total number of quotes for the quote set across all messages. Should be the sum of all NoQuoteEntries in each message that has repeating quotes that are part of the same quote set.
LastFragment	[0..1]	CodeSet	Indicates whether this is the last fragment in a sequence of message fragments. Only required where message has been fragmented.
QuotEntryGrp	[1..*]	Group	

Used in messages: **MassQuote**

### 180.2.4478 RateSource

Identifies the source of rate information.

For FX, the reference source to be used for the FX spot rate.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: **RateSource**

### 180.2.4479 RateSource

The RateSource component is used to identify the source for the rate information as required by the trade for pricing reasons.

Name	Mult.	Type	Description
NoRateSources	[1..1]	NumInGroup	
RateSource	[0..1]	CodeSet	Required if NoRateSource(1445) > 0
RateSourceType	[0..1]	CodeSet	Required if NoRateSources(1445) > 0
ReferencePage	[0..1]	String	May be used when RateSource(1446)=99 (Other)
RateSourceReferencePageHeading	[0..1]	String	
FXBenchmarkRateFix	[0..1]	String	
RateSourceSymbol	[0..1]	String	
FXBenchmark	[0..1]	CodeSet	
FXBenchmarkDate	[0..1]	LocalMktDate	Conditionally required when FXBenchmarkTime(3075) or FXBenchmarkBusinessCenter(3076) is specified.
FXBenchmarkTime	[0..1]	LocalMktTime	Conditionally required when FXBenchmarkDate(3074) or FXBenchmarkBusinessCenter(3076) is specified.
FXBenchmarkBusinessCenter	[0..1]	String	Conditionally required when FXBenchmarkDate(3074) or FXBenchmarkTime(3075) is specified.

Used in groups: MDFullGrp, MDIncGrp, QuotReqGrp

Used in messages: AllocationInstruction, AllocationReport, ExecutionReport, NewOrderSingle, Order-CancelReplaceRequest, Quote, TradeCaptureReport

#### 180.2.4480 RateSourceReferencePageHeading

Identifies the page heading from the rate source.

Type: String

Used in groups: RateSource

#### 180.2.4481 RateSourceSymbol

Identifies the currency pair/symbol that the instance of the rate source information is applicable for the fixing.

Type: String

Used in groups: RateSource

**180.2.4482 RateSourceType**

Indicates whether the rate source specified is a primary or secondary source.

Type: **int**

Allowed values in RateSourceTypeCodeSet:

Code	Name	Description
0	Primary	Primary
1	Secondary	Secondary

Used in groups: **RateSource**

**180.2.4483 RawData**

Unformatted raw data, can include bitmaps, word processor documents, etc.

Type: **data**

Used in messages: **Email, Logon, News, UserRequest**

**180.2.4484 RawDataLength**

Number of bytes in raw data field.

Type: **Length**

Used in messages: **Email, Logon, News, UserRequest**

**180.2.4485 RealizedVariance**

Actual or realized variance of an instrument used to calculate settlement prices, e.g. for variance futures.

Type: **float**

Used in groups: **ClearingPriceParametersGrp**

#### **180.2.4486 ReceivedDeptID**

Identifies the broker-dealer department that first took the order.

Type: **String**

Used in messages: **ExecutionReport**, **NewOrderSingle**, **OrderCancelReplaceRequest**

#### **180.2.4487 ReceivingDeptID**

An identifier representing the department or desk within the firm that received the order.

Type: **String**

Used in groups: **SideCrossOrdModGrp**

Used in messages: **ExecutionReport**, **NewOrderSingle**, **OrderCancelReplaceRequest**

#### **180.2.4488 RedemptionDate**

Return of investor's principal in a security. Bond redemption can occur before maturity date.(Note tag # was reserved in FIX 4.1, added in FIX 4.3) (prior to FIX 4.4 field was of type UTCDate)

Type: **LocalMktDate**

Used in components: **Instrument**

#### **180.2.4489 RefAllocID**

Reference identifier to be used with AllocTransType (71) = Replace or Cancel.

(Prior to FIX 4.1 this field was of type int)

Type: **String**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**

#### **180.2.4490 RefApplExtID**

The extension pack number associated with an application message.

Type: **int**

Used in groups: **MsgTypeGrp**

Used in messages: **BusinessMessageReject**, **Reject**

**180.2.4491 RefApplID**

Reference to the unique application identifier which corresponds to ApplID(1180) from the Application Sequence Group component

Type: **String**

Used in groups: **ApplIDReportGrp, ApplIDRequestAckGrp, ApplIDRequestGrp**

**180.2.4492 RefApplLastSeqNum**

Application sequence number of last message in transmission.

Type: **SeqNum**

Used in groups: **ApplIDReportGrp, ApplIDRequestAckGrp**

**180.2.4493 RefApplReqID**

Used to reference a previously submitted ApplReqID (1346) from within a subsequent ApplicationMessageRequest(MsgType=BW)

Type: **String**

Used in groups: **ApplIDRequestAckGrp, ApplIDRequestGrp**

**180.2.4494 RefApplVerID**

Specifies the service pack release being applied to a message at the session level. Enumerated field with values assigned at time of service pack release. Uses same values as ApplVerID

Type: **String**

Allowed values in ApplVerIDCodeSet:

Code	Name	Description
0	FIX27	FIX27
1	FIX30	FIX30
2	FIX40	FIX40
3	FIX41	FIX41
4	FIX42	FIX42

Code	Name	Description
5	FIX43	FIX43
6	FIX44	FIX44
7	FIX50	FIX50
8	FIX50SP1	FIX50SP1
9	FIX50SP2	FIX50SP2
10	FIXLatest	FIXLatest

Used in groups: [MsgTypeGrp](#)

Used in messages: [BusinessMessageReject](#), [Reject](#)

#### **180.2.4495 RefClOrdID**

Used to reference an order via ClOrdID(11).

Type: [String](#)

Used in messages: [ExecutionReport](#), [NewOrderMultileg](#), [NewOrderSingle](#)

#### **180.2.4496 RefCompID**

Assigned value used to identify a firm.

Type: [String](#)

Used in groups: [CompIDReqGrp](#), [CompIDStatGrp](#)

#### **180.2.4497 RefCstmApplVerID**

Specifies a custom extension to a message being applied at the session level.

Type: [String](#)

Used in groups: [MsgTypeGrp](#)

Used in messages: [BusinessMessageReject](#), [Reject](#)

**180.2.4498 ReferenceDataDate**

Reference data entry's date-time of the type specified in ReferenceDataDateType(2748).

Type: **UTCTimestamp**

Used in groups: **ReferenceDataDateGrp**

**180.2.4499 ReferenceDataDateGrp**

Used to carry the different date-time stamps related to the reference data entry.

Name	Mult.	Type	Description
NoReferenceDataDates	[1..1]	NumInGroup	
ReferenceDataDate	[0..1]	UTCTimestamp	Required if NoReferenceDataDates(2746) > 0.
ReferenceDataDateType	[0..1]	CodeSet	

Used in components: **InstrumentExtension**

**180.2.4500 ReferenceDataDateType**

Reference data entry's date-time type.

Type: **int**

Allowed values in ReferenceDataDateTypeCodeSet:

Code	Name	Description
0	AdmitToTradeRequestDate	Date of request for admission to trading. In the context of MiFID II ESMA RTS 23 this is defined as "Date and time the issuer has approved admission to trading or trading in its financial instruments on a trading venue." (Reference: Annex I Table 3 Field 9)
1	AdmitToTradeApprovalDate	Date of approval of admission to trading. In the context of MiFID II ESMA RTS 23 this is defined as "Date and time of the request for admission to trading on the trading venue." (Reference: Annex I Table 3 Field 10)



Code	Name	Description
2	AdmitToTradeOrFirstTradeDate	Date of admission to trading or date of first trade. In the context of MiFID II ESMA RTS 23 this is defined as "Date and time of the admission to trading on the trading venue or the date and time when the instrument was first traded or an order or quote was first received by the trading venue." (Reference: Annex I Table 3 Field 11)
3	TerminationDate	Termination date. In the context of MiFID II ESMA RTS 23 this is defined as "Where available, the date and time when the financial instrument ceases to be traded or to be admitted to trading on the trading venue." (Reference: Annex I Table 3 Field 12)

Used in groups: [ReferenceDataDateGrp](#)

### 180.2.4501 ReferenceEntityType

Specifies the type of reference entity for first-to-default CDS basket contracts.

Type: [int](#)

Allowed values in ReferenceEntityTypeCodeSet:

Code	Name	Description
1	Asian	Asian
2	AustralianNewZealand	Australian and New Zealand
3	EuropeanEmergingMarkets	European emerging markets
4	Japanese	Japanese
5	NorthAmericanHighYield	North American high yield
6	NorthAmericanInsurance	North American insurance
7	NorthAmericanInvestmentGrade	North American investment grade
8	Singaporean	Singaporean
9	WesternEuropean	Western European
10	WesternEuropeanInsurance	Western European insurance

Used in components: [Instrument](#)

**180.2.4502 ReferencePage**

Identifies the reference "page" from the rate source.

For FX, the reference page to the spot rate to be used for the reference FX spot rate.

When RateSource(1446) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in groups: **RateSource**

**180.2.4503 RefMsgType**

The MsgType (35) of the FIX message being referenced.

Type: **String**

Allowed values in MsgTypeCodeSet:

Code	Name	Description
0	Heartbeat	Heartbeat. The Heartbeat monitors the status of the communication link and identifies when the last of a string of messages was not received.
1	TestRequest	TestRequest. The test request message forces a heartbeat from the opposing application. The test request message checks sequence numbers or verifies communication line status. The opposite application responds to the Test Request with a Heartbeat containing the TestReqID.
2	ResendRequest	ResendRequest. The resend request is sent by the receiving application to initiate the retransmission of messages. This function is utilized if a sequence number gap is detected, if the receiving application lost a message, or as a function of the initialization process.
3	Reject	Reject. The reject message should be issued when a message is received but cannot be properly processed due to a session-level rule violation. An example of when a reject may be appropriate would be the receipt of a message with invalid basic data which successfully passes de-encryption, CheckSum and BodyLength checks.

Code	Name	Description
4	SequenceReset	SequenceReset. The sequence reset message is used by the sending application to reset the incoming sequence number on the opposing side.
5	Logout	Logout. The logout message initiates or confirms the termination of a FIX session. Disconnection without the exchange of logout messages should be interpreted as an abnormal condition.
6	IOI	IOI. Indication of interest messages are used to market merchandise which the broker is buying or selling in either a proprietary or agency capacity. The indications can be time bound with a specific expiration value. Indications are distributed with the understanding that other firms may react to the message first and that the merchandise may no longer be available due to prior trade. Indication messages can be transmitted in various transaction types; NEW, CANCEL, and REPLACE. All message types other than NEW modify the state of the message identified in IOIRefID.
7	Advertisement	Advertisement. Advertisement messages are used to announce completed transactions. The advertisement message can be transmitted in various transaction types; NEW, CANCEL and REPLACE. All message types other than NEW modify the state of a previously transmitted advertisement identified in AdvRefID.
8	ExecutionReport	ExecutionReport. The execution report message is used to: 1. confirm the receipt of an order. 2. confirm changes to an existing order (i.e. accept cancel and replace requests). 3. relay order status information. 4. relay fill information on working orders. 5. relay fill information on tradeable or restricted tradeable quotes. 6. reject orders. 7. report post-trade fees calculations associated with a trade
9	OrderCancelReject	OrderCancelReject. The order cancel reject message is issued by the broker upon receipt of a cancel request or cancel/replace request message which cannot be honored.
A	Logon	Logon. The logon message authenticates a user establishing a connection to a remote system. The logon message must be the first message sent by the application requesting to initiate a FIX session.
B	News	News. The news message is a general free format message between the broker and institution. The message contains flags to identify the news item's urgency and to allow sorting by subject company (symbol). The News message can be originated at either the broker or institution side, or exchanges and other marketplace venues.

Code	Name	Description
C	Email	Email. The email message is similar to the format and purpose of the News message, however, it is intended for private use between two parties.
D	NewOrderSingle	NewOrderSingle. The new order message type is used by institutions wishing to electronically submit securities and forex orders to a broker for execution. The New Order message type may also be used by institutions or retail intermediaries wishing to electronically submit Collective Investment Vehicle (CIV) orders to a broker or fund manager for execution.
E	NewOrderList	NewOrderList. The NewOrderList Message can be used in one of two ways depending on which market conventions are being followed.
F	OrderCancelRequest	OrderCancelRequest. The order cancel request message requests the cancellation of all of the remaining quantity of an existing order. Note that the Order Cancel/Replace Request should be used to partially cancel (reduce) an order).
G	OrderCancelReplaceRequest	OrderCancelReplaceRequest. The order cancel/replace request is used to change the parameters of an existing order. Do not use this message to cancel the remaining quantity of an outstanding order, use the Order Cancel Request message for this purpose.
H	OrderStatusRequest	OrderStatusRequest. The order status request message is used by the institution to generate an order status message back from the broker.
J	AllocationInstruction	AllocationInstruction. The AllocationInstruction(35=J) message provides the ability to specify how an order or set of orders should be subdivided amongst one or more accounts.
K	ListCancelRequest	ListCancelRequest. The List Cancel Request message type is used by institutions wishing to cancel previously submitted lists either before or during execution.
L	ListExecute	ListExecute. The List Execute message type is used by institutions to instruct the broker to begin execution of a previously submitted list. This message may or may not be used, as it may be mirroring a phone conversation.
M	ListStatusRequest	ListStatusRequest. The list status request message type is used by institutions to instruct the broker to generate status messages for a list.

Code	Name	Description
N	ListStatus	ListStatus. The list status message is issued as the response to a List Status Request message sent in an unsolicited fashion by the sell-side. It indicates the current state of the orders within the list as they exist at the broker's site. This message may also be used to respond to the List Cancel Request.
P	AllocationInstructionAck	AllocationInstructionAck. In versions of FIX prior to version 4.4, this message was known as the Allocation ACK message. The Allocation Instruction Ack message is used to acknowledge the receipt of and provide status for an Allocation Instruction message.
Q	DontKnowTrade	DontKnowTrade. The Don't Know Trade (DK) message notifies a trading partner that an electronically received execution has been rejected. This message can be thought of as an execution reject message.
R	QuoteRequest	QuoteRequest. In some markets it is the practice to request quotes from brokers prior to placement of an order. The quote request message is used for this purpose. This message is commonly referred to as an Request For Quote (RFQ)
S	Quote	Quote. The Quote message is used as the response to a Quote Request or a Quote Response message in both indicative, tradeable, and restricted tradeable quoting markets.
T	SettlementInstructions	SettlementInstructions. The Settlement Instructions message provides the broker's, the institution's, or the intermediary's instructions for trade settlement. This message has been designed so that it can be sent from the broker to the institution, from the institution to the broker, or from either to an independent "standing instructions" database or matching system or, for CIV, from an intermediary to a fund manager.
V	MarketDataRequest	MarketDataRequest. Some systems allow the transmission of real-time quote, order, trade, trade volume, open interest, and/or other price information on a subscription basis. A MarketDataRequest(35=V) is a general request for market data on specific securities or forex quotes. The values in the fields provided within the request will serve as further filter criteria for the result set.
W	MarketDataSnapshotFullRefresh	MarketDataSnapshotFullRefresh. The Market Data messages are used as the response to a Market Data Request message. In all cases, one Market Data message refers only to one Market Data Request. It can be used to transmit a 2-sided book of orders or list of quotes, a list of trades, index values, opening, closing, settlement, high, low, or VWAP prices, the trade volume or open interest for a security, or any combination of these.

Code	Name	Description
X	MarketDataIncrementalRefresh	MarketDataIncrementalRefresh. The Market Data message for incremental updates may contain any combination of new, changed, or deleted Market Data Entries, for any combination of instruments, with any combination of trades, imbalances, quotes, index values, open, close, settlement, high, low, and VWAP prices, trade volume and open interest so long as the maximum FIX message size is not exceeded. All of these types of Market Data Entries can be changed and deleted.
Y	MarketDataRequestReject	MarketDataRequestReject. The Market Data Request Reject is used when the broker cannot honor the Market Data Request, due to business or technical reasons. Brokers may choose to limit various parameters, such as the size of requests, whether just the top of book or the entire book may be displayed, and whether Full or Incremental updates must be used.
Z	QuoteCancel	QuoteCancel. The Quote Cancel message is used by an originator of quotes to cancel quotes. The Quote Cancel message supports cancellation of: <ul style="list-style-type: none"> <li>• All quotes.</li> <li>• Quotes for a specific symbol or security ID.</li> <li>• All quotes for a security type.</li> <li>• All quotes for an underlying</li> </ul>
a	QuoteStatusRequest	QuoteStatusRequest. The quote status request message is used for the following purposes in markets that employ tradeable or restricted tradeable quotes: <ul style="list-style-type: none"> <li>• For the issuer of a quote in a market to query the status of that quote (using the QuoteID to specify the target quote).</li> <li>• To subscribe and unsubscribe for Quote Status Report messages for one or more securities.</li> </ul>
b	MassQuoteAck	MassQuoteAck. Mass Quote Acknowledgement is used as the application level response to a Mass Quote message.
c	SecurityDefinitionRequest	SecurityDefinitionRequest. The SecurityDefinitionRequest(35=c) message is used for the following: <ol style="list-style-type: none"> <li>1. Request a specific security to be traded with the second party. The requested security can be defined as a multileg security made up of one or more instrument legs.</li> <li>2. Request a set of individual securities for a single market segment.</li> <li>3. Request all securities, independent of market segment.</li> </ol>

Code	Name	Description
d	SecurityDefinition	SecurityDefinition. The SecurityDefinition(35=d) message is used for the following:. 1. Accept the security defined in a SecurityDefinition(35=d) message. 2. Accept the security defined in a SecurityDefinition(35=d) message with changes to the definition and/or identity of the security. 3. Reject the security requested in a SecurityDefinition(35=d) message. 4. Respond to a request for securities within a specified market segment. 5. Convey comprehensive security definition for all market segments that the security participates in. 6. Convey the security's trading rules that differ from default rules for the market segment.
e	SecurityStatusRequest	SecurityStatusRequest. The Security Status Request message provides for the ability to request the status of a security. One or more Security Status messages are returned as a result of a Security Status Request message.
f	SecurityStatus	SecurityStatus. The Security Status message provides for the ability to report changes in status to a security. The Security Status message contains fields to indicate trading status, corporate actions, financial status of the company. The Security Status message is used by one trading entity (for instance an exchange) to report changes in the state of a security.
g	TradingSessionStatusRequest	TradingSessionStatusRequest. The Trading Session Status Request is used to request information on the status of a market. With the move to multiple sessions occurring for a given trading party (morning and evening sessions for instance) there is a need to be able to provide information on what product is trading on what market.
h	TradingSessionStatus	TradingSessionStatus. The Trading Session Status provides information on the status of a market. For markets multiple trading sessions on multiple-markets occurring (morning and evening sessions for instance), this message is able to provide information on what products are trading on what market during what trading session.
i	MassQuote	MassQuote. The Mass Quote message can contain quotes for multiple securities to support applications that allow for the mass quoting of an option series. Two levels of repeating groups have been provided to minimize the amount of data required to submit a set of quotes for a class of options (e.g. all option series for IBM).

Code	Name	Description
j	BusinessMessageReject	BusinessMessageReject. The Business Message Reject message can reject an application-level message which fulfills session-level rules and cannot be rejected via any other means. Note if the message fails a session-level rule (e.g. body length is incorrect), a session-level Reject message should be issued.
k	BidRequest	BidRequest. The BidRequest Message can be used in one of two ways depending on which market conventions are being followed. In the "Non disclosed" convention (e.g. US/European model) the BidRequest message can be used to request a bid based on the sector, country, index and liquidity information contained within the message itself. In the "Non disclosed" convention the entry repeating group is used to define liquidity of the program. See " Program/Basket/List Trading" for an example. In the "Disclosed" convention (e.g. Japanese model) the BidRequest message can be used to request bids based on the ListOrderDetail messages sent in advance of BidRequest message. In the "Disclosed" convention the list repeating group is used to define which ListOrderDetail messages a bid is being sort for and the directions of the required bids.
l	BidResponse	BidResponse. The Bid Response message can be used in one of two ways depending on which market conventions are being followed. In the "Non disclosed" convention the Bid Response message can be used to supply a bid based on the sector, country, index and liquidity information contained within the corresponding bid request message. See "Program/Basket/List Trading" for an example. In the "Disclosed" convention the Bid Response message can be used to supply bids based on the List Order Detail messages sent in advance of the corresponding Bid Request message.
m	ListStrikePrice	ListStrikePrice. The strike price message is used to exchange strike price information for principal trades. It can also be used to exchange reference prices for agency trades.
n	XMLnonFIX	XMLnonFIX.
o	RegistrationInstructions	RegistrationInstructions. The Registration Instructions message type may be used by institutions or retail intermediaries wishing to electronically submit registration information to a broker or fund manager (for CIV) for an order or for an allocation.
p	RegistrationInstructionsResponse	RegistrationInstructionsResponse. The Registration Instructions Response message type may be used by broker or fund manager (for CIV) in response to a Registration Instructions message submitted by an institution or retail intermediary for an order or for an allocation.



Code	Name	Description
q	OrderMassCancelRequest	OrderMassCancelRequest. The order mass cancel request message requests the cancellation of all of the remaining quantity of a group of orders matching criteria specified within the request. NOTE: This message can only be used to cancel order messages (reduce the full quantity).
r	OrderMassCancelReport	OrderMassCancelReport. The Order Mass Cancel Report is used to acknowledge an Order Mass Cancel Request. Note that each affected order that is canceled is acknowledged with a separate Execution Report or Order Cancel Reject message.
s	NewOrderCross	NewOrderCross. Used to submit a cross order into a market. The cross order contains two order sides (a buy and a sell). The cross order is identified by its CrossID.
t	CrossOrderCancelReplaceRequest	CrossOrderCancelReplaceRequest. Used to modify a cross order previously submitted using the New Order - Cross message. See Order Cancel Replace Request for details concerning message usage.
u	CrossOrderCancelRequest	CrossOrderCancelRequest. Used to fully cancel the remaining open quantity of a cross order.
v	SecurityTypeRequest	SecurityTypeRequest. The Security Type Request message is used to return a list of security types available from a counterparty or market.
w	SecurityTypes	SecurityTypes. The Security Type Request message is used to return a list of security types available from a counterparty or market.
x	SecurityListRequest	SecurityListRequest. The Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request
y	SecurityList	SecurityList. The Security List message is used to return a list of securities that matches the criteria specified in a Security List Request.
z	DerivativeSecurityListRequest	DerivativeSecurityListRequest. The Derivative Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request
AA	DerivativeSecurityList	DerivativeSecurityList. The Derivative Security List message is used to return a list of securities that matches the criteria specified in a Derivative Security List Request.
AB	NewOrderMultileg	NewOrderMultileg. The New Order - Multileg is provided to submit orders for securities that are made up of multiple securities, known as legs.

Code	Name	Description
AC	MultilegOrderCancelReplace	MultilegOrderCancelReplace. Used to modify a multileg order previously submitted using the New Order - Multileg message. See Order Cancel Replace Request for details concerning message usage.
AD	TradeCaptureReportRequest	TradeCaptureReportRequest. The Trade Capture Report Request can be used to: <ul style="list-style-type: none"> <li>• Request one or more trade capture reports based upon selection criteria provided on the trade capture report request.</li> <li>• Subscribe for trade capture reports based upon selection criteria provided on the trade capture report request.</li> </ul>
AE	TradeCaptureReport	TradeCaptureReport. The Trade Capture Report message can be: <ul style="list-style-type: none"> <li>- Used to report trades between counterparties.</li> <li>- Used to report trades to a trade matching system.</li> <li>- Sent unsolicited between counterparties.</li> <li>- Sent as a reply to a Trade Capture Report Request.</li> <li>- Used to report unmatched and matched trades.</li> </ul>
AF	OrderMassStatusRequest	OrderMassStatusRequest. The order mass status request message requests the status for orders matching criteria specified within the request.
AG	QuoteRequestReject	QuoteRequestReject. The Quote Request Reject message is used to reject Quote Request messages for all quoting models.
AH	RFQRequest	RFQRequest. In tradeable and restricted tradeable quoting markets – Quote Requests are issued by counterparties interested in ascertaining the market for an instrument. Quote Requests are then distributed by the market to liquidity providers who make markets in the instrument. The RFQ Request is used by liquidity providers to indicate to the market for which instruments they are interested in receiving Quote Requests. It can be used to register interest in receiving quote requests for a single instrument or for multiple instruments
AI	QuoteStatusReport	QuoteStatusReport. The quote status report message is used: <ul style="list-style-type: none"> <li>• as the response to a Quote Status Request message.</li> <li>• as a response to a Quote Cancel message.</li> <li>• as a response to a Quote Response message in a negotiation dialog (see Volume 7 – PRODUCT: FIXED INCOME and USER GROUP: EXCHANGES AND MARKETS)</li> </ul>
AJ	QuoteResponse	QuoteResponse. The QuoteResponse(35=AJ) message is used for the following purposes: <ol style="list-style-type: none"> <li>1. Respond to an IOI(35=6) message.</li> <li>2. Respond to a Quote(35=S) message.</li> <li>3. Counter a Quote.</li> <li>4. End a negotiation dialog.</li> <li>5. Follow-up or end a QuoteRequest(35=R) dialog that did not receive a response.</li> </ol>

Code	Name	Description
AK	Confirmation	Confirmation. The Confirmation messages are used to provide individual trade level confirmations from the sell side to the buy side. In versions of FIX prior to version 4.4, this role was performed by the allocation message. Unlike the allocation message, the confirmation message operates at an allocation account (trade) level rather than block level, allowing for the affirmation or rejection of individual confirmations.
AL	PositionMaintenanceRequest	PositionMaintenanceRequest. The Position Maintenance Request message allows the position owner to submit requests to the holder of a position which will result in a specific action being taken which will affect the position. Generally, the holder of the position is a central counter party or clearing organization but can also be a party providing investment services.
AM	PositionMaintenanceReport	PositionMaintenanceReport. The Position Maintenance Report message is sent by the holder of a position in response to a Position Maintenance Request and is used to confirm that a request has been successfully processed or rejected.
AN	RequestForPositions	RequestForPositions. The Request For Positions message is used by the owner of a position to request a Position Report from the holder of the position, usually the central counter party or clearing organization. The request can be made at several levels of granularity.
AO	RequestForPositionsAck	RequestForPositionsAck. The Request for Positions Ack message is returned by the holder of the position in response to a Request for Positions message. The purpose of the message is to acknowledge that a request has been received and is being processed.
AP	PositionReport	PositionReport. The Position Report message is returned by the holder of a position in response to a Request for Position message. The purpose of the message is to report all aspects of a position and may be provided on a standing basis to report end of day positions to an owner.

Code	Name	Description
AQ	TradeCaptureReportRequestAck	TradeCaptureReportRequestAck. The Trade Capture Request Ack message is used to: - Provide an acknowledgement to a Trade Capture Report Request in the case where the Trade Capture Report Request is used to specify a subscription or delivery of reports via an out-of-band ResponseTransmissionMethod. - Provide an acknowledgement to a Trade Capture Report Request in the case when the return of the Trade Capture Reports matching that request will be delayed or delivered asynchronously. This is useful in distributed trading system environments. - Indicate that no trades were found that matched the selection criteria specified on the Trade Capture Report Request or the Trade Capture Request was invalid for some business reason, such as request is not authorized, invalid or unknown instrument, party, trading session, etc.
AR	TradeCaptureReportAck	TradeCaptureReportAck. The Trade Capture Report Ack message can be: - Used to acknowledge trade capture reports received from a counterparty. - Used to reject a trade capture report received from a counterparty.
AS	AllocationReport	AllocationReport. Sent from sell-side to buy-side, sell-side to 3rd-party or 3rd-party to buy-side, the AllocationReport(35=AS) message (Claim) provides account breakdown of an order or set of orders plus any additional follow-up front-office information developed post-trade during the trade allocation, matching and calculation phase.
AT	AllocationReportAck	AllocationReportAck. The Allocation Report Ack message is used to acknowledge the receipt of and provide status for an Allocation Report message.
AU	ConfirmationAck	ConfirmationAck. The Confirmation Ack (aka Affirmation) message is used to respond to a Confirmation message.
AV	SettlementInstructionRequest	SettlementInstructionRequest. The Settlement Instruction Request message is used to request standing settlement instructions from another party.
AW	AssignmentReport	AssignmentReport. Assignment Reports are sent from a clearing house to counterparties, such as a clearing firm as a result of the assignment process.
AX	CollateralRequest	CollateralRequest. An initiator that requires collateral from a respondent sends a Collateral Request. The initiator can be either counterparty to a trade in a two party model or an intermediary such as an ATS or clearinghouse in a three party model. A Collateral Assignment is expected as a response to a request for collateral.

Code	Name	Description
AY	CollateralAssignment	CollateralAssignment. Used to assign collateral to cover a trading position. This message can be sent unsolicited or in reply to a Collateral Request message.
AZ	CollateralResponse	CollateralResponse. Used to respond to a Collateral Assignment message.
BA	CollateralReport	CollateralReport. Used to report collateral status when responding to a Collateral Inquiry message.
BB	CollateralInquiry	CollateralInquiry. Used to inquire for collateral status.
BC	NetworkCounterpartySystemStatus-Request	NetworkCounterpartySystemStatusRequest. This message is send either immediately after logging on to inform a network (counterparty system) of the type of updates required or to at any other time in the FIX conversation to change the nature of the types of status updates required. It can also be used with a NetworkRequestType of Snapshot to request a one-off report of the status of a network (or counterparty) system. Finally this message can also be used to cancel a request to receive updates into the status of the counterparties on a network by sending a NetworkRequestStatusMessage with a NetworkRequestType of StopSubscribing.
BD	NetworkCounterpartySystemStatus-Response	NetworkCounterpartySystemStatusResponse. This message is sent in response to a Network (Counterparty System) Status Request Message.
BE	UserRequest	UserRequest. This message is used to initiate a user action, logon, logout or password change. It can also be used to request a report on a user's status.
BF	UserResponse	UserResponse. This message is used to respond to a user request message, it reports the status of the user after the completion of any action requested in the user request message.
BG	CollateralInquiryAck	CollateralInquiryAck. Used to respond to a Collateral Inquiry in the following situations:. • When the CollateralInquiry will result in an out of band response (such as a file transfer). • When the inquiry is otherwise valid but no collateral is found to match the criteria specified on the Collateral Inquiry message. • When the Collateral Inquiry is invalid based upon the business rules of the counterparty.
BH	ConfirmationRequest	ConfirmationRequest. The Confirmation Request message is used to request a Confirmation message.

Code	Name	Description
BO	ContraryIntentionReport	ContraryIntentionReport. The Contrary Intention Report is used for reporting of contrary expiration quantities for Saturday expiring options. This information is required by options exchanges for regulatory purposes.
BP	SecurityDefinitionUpdateReport	SecurityDefinitionUpdateReport. This message is used for reporting updates to a product security master file. Updates could be the result of corporate actions or other business events. Updates may include additions, modifications or deletions.
BK	SecurityListUpdateReport	SecurityListUpdateReport. The Security List Update Report is used for reporting updates to a Contract Security Masterfile. Updates could be due to Corporate Actions or other business events. Update may include additions, modifications and deletions.
BL	AdjustedPositionReport	AdjustedPositionReport. Used to report changes in position, primarily in equity options, due to modifications to the underlying due to corporate actions
BM	AllocationInstructionAlert	AllocationInstructionAlert. This message is used in a 3-party allocation model (buy-side and sell-side using a central clearing entity) where notification of group creation and group updates to counterparties is needed. The message will also carry trade information that comprised the group to the counterparties.
BN	ExecutionAck	ExecutionAck. The Execution Report Acknowledgement message is an optional message that provides dual functionality to notify a trading partner that an electronically received execution has either been accepted or rejected (DK'd).
BJ	TradingSessionList	TradingSessionList. The Trading Session List message is sent as a response to a Trading Session List Request. The Trading Session List should contain the characteristics of the trading session and the current state of the trading session.
BI	TradingSessionListRequest	TradingSessionListRequest. The Trading Session List Request is used to request a list of trading sessions available in a market place and the state of those trading sessions. A successful request will result in a response from the counterparty of a Trading Session List (MsgType=BJ) message that contains a list of zero or more trading sessions.
BQ	SettlementObligationReport	SettlementObligationReport. The Settlement Obligation Report message provides a central counterparty, institution, or individual counterparty with a capacity for reporting the final details of a currency settlement obligation.

Code	Name	Description
BR	DerivativeSecurityListUpdateReport	DerivativeSecurityListUpdateReport. The Derivative Security List Update Report message is used to send updates to an option family or the strikes that comprise an option family.
BS	TradingSessionListUpdateReport	TradingSessionListUpdateReport. The Trading Session List Update Report is used by marketplaces to provide intra-day updates of trading sessions when there are changes to one or more trading sessions.
BT	MarketDefinitionRequest	MarketDefinitionRequest. The Market Definition Request message is used to request for market structure information from the Respondent that receives this request.
BU	MarketDefinition	MarketDefinition. The MarketDefinition(35=BU) message is used to respond to MarketDefinitionRequest(35=BT). In a subscription, it will be used to provide the initial snapshot of the information requested. Subsequent updates are provided by the MarketDefinitionUpdateReport(35=BV).
BV	MarketDefinitionUpdateReport	MarketDefinitionUpdateReport. In a subscription for market structure information, this message is used once the initial snapshot of the information has been sent using the MarketDefinition(35=BU) message.
BW	ApplicationMessageRequest	ApplicationMessageRequest. This message is used to request a retransmission of a set of one or more messages generated by the application specified in RefApplID (1355).
BX	ApplicationMessageRequestAck	ApplicationMessageRequestAck. This message is used to acknowledge an Application Message Request providing a status on the request (i.e. whether successful or not). This message does not provide the actual content of the messages to be resent.
BY	ApplicationMessageReport	ApplicationMessageReport. This message is used for three difference purposes: to reset the ApplSeqNum (1181) of a specified ApplID (1180). to indicate that the last message has been sent for a particular ApplID, or as a keep-alive mechanism for ApplIDs with infrequent message traffic.
BZ	OrderMassActionReport	OrderMassActionReport. The Order Mass Action Report is used to acknowledge an Order Mass Action Request. Note that each affected order that is suspended or released or canceled is acknowledged with a separate Execution Report for each order.
CA	OrderMassActionRequest	OrderMassActionRequest. The Order Mass Action Request message can be used to request the suspension or release of a group of orders that match the criteria specified within the request. This is equivalent to individual Order Cancel Replace Requests for each order with or without adding "S" to the ExecInst values. It can also be used for mass order cancellation.

Code	Name	Description
CB	UserNotification	UserNotification. The User Notification message is used to notify one or more users of an event or information from the sender of the message. This message is usually sent unsolicited from a marketplace (e.g. Exchange, ECN) to a market participant.
CC	StreamAssignmentRequest	StreamAssignmentRequest. In certain markets where market data aggregators fan out to end clients the pricing streams provided by the price makers, the price maker may assign the clients to certain pricing streams that the price maker publishes via the aggregator. An example of this use is in the FX markets where clients may be assigned to different pricing streams based on volume bands and currency pairs.
CD	StreamAssignmentReport	StreamAssignmentReport. The StreamAssignmentReport(35=CD) message is in response to the StreamAssignmentRequest(35=CC) message. It provides information back to the aggregator as to which clients to assign to receive which price stream based on requested CCY pair. This message can be sent unsolicited to the Aggregator from the Price Maker.
CE	StreamAssignmentReportACK	StreamAssignmentReportACK. This message is used to respond to the Stream Assignment Report, to either accept or reject an unsolicited assigningment.
CF	PartyDetailsListRequest	PartyDetailsListRequest. The PartyDetailsListRequest is used to request party detail information.
CG	PartyDetailsListReport	PartyDetailsListReport. The PartyDetailsListReport message is used to disseminate party details between counterparties. PartyDetailsListReport messages may be sent in response to a PartyDetailsListRequest message or sent unsolicited.



Code	Name	Description
CH	MarginRequirementInquiry	MarginRequirementInquiry. The purpose of this message is to initiate a margin requirement inquiry for a margin account. The inquiry may be submitted at the detail level or the summary level. It can also be used to inquire margin excess/deficit or net position information. Margin excess/deficit will provide information about the surplus or shortfall compared to the previous trading day or a more recent margin calculation. An inquiry for net position information will trigger one or more PositionReport messages instead of one or more MarginRequirementReport messages. If the inquiry is made at the detail level, an Instrument block must be provided with the desired level of detail. If the inquiry is made at the summary level, the Instrument block is not provided, implying a summary request is being made. For example, if the inquiring firm specifies the Security Type of "FUT" in the Instrument block, then a detail report will be generated containing the margin requirements for all futures positions for the inquiring account. Similarly, if the inquiry is made at the summary level, the report will contain the total margin requirement aggregated to the margin account level.
CI	MarginRequirementInquiryAck	MarginRequirementInquiryAck. Used to respond to a Margin Requirement Inquiry.
CJ	MarginRequirementReport	MarginRequirementReport. The Margin Requirement Report returns information about margin requirement either as an overview across all margin accounts or on a detailed level due to the inquiry making use of the optional Instrument component block. Application sequencing can be used to re-request a range of reports.
CK	PartyDetailsListUpdateReport	PartyDetailsListUpdateReport. The PartyDetailsListUpdateReport(35=CK) is used to disseminate updates to party detail information.
CL	PartyRiskLimitsRequest	PartyRiskLimitsRequest. The PartyRiskLimitsRequest message is used to request for risk information for specific parties, specific party roles or specific instruments.
CM	PartyRiskLimitsReport	PartyRiskLimitsReport. The PartyRiskLimitsReport message is used to communicate party risk limits. The message can either be sent as a response to the PartyRiskLimitsRequest message or can be published unsolicited.
CN	SecurityMassStatusRequest	SecurityMassStatusRequest.
CO	SecurityMassStatus	SecurityMassStatus.

Code	Name	Description
CQ	AccountSummaryReport	AccountSummaryReport. The AccountSummaryReport is provided by the clearinghouse to its clearing members on a daily basis. It contains margin, settlement, collateral and pay/collect data for each clearing member level account type. Clearing member account types will be described through use of the Parties component and PtysSubGrp sub-component. In certain usages, the clearing members can send the AccountSummaryReport message to the clearinghouse as needed. For example, clearing members can send this message to the clearinghouse to identify the value of collateral for each customer (to satisfy CFTC Legally Segregated Operationally Commingled (LSOC) regulatory reporting obligations). Clearing organizations can also send the AccountSummaryReport message to regulators to meet regulatory reporting obligations. For example, clearing organizations can use this message to submit daily reports for each clearing member ("CM") by house origin and by each customer origin for all futures, options, and swaps positions, and all securities positions held in a segregated account or pursuant to a cross margining agreement, to a regulator (e.g. to the CFTC to meet Part 39, Section 39.19 reporting obligations).
CR	PartyRiskLimitsUpdateReport	PartyRiskLimitsUpdateReport. The PartyRiskLimitsUpdateReport(35=CR) is used to convey incremental changes to risk limits. It is similar to the regular report but uses the PartyRiskLimitsUpdateGrp component instead of the PartyRiskLimitsGrp component to include an update action.
CS	PartyRiskLimitsDefinitionRequest	PartyRiskLimitsDefinitionRequest. PartyRiskLimitDefinitionRequest is used for defining new risk limits.
CT	PartyRiskLimitsDefinitionRequestAck	PartyRiskLimitsDefinitionRequestAck. PartyRiskLimitDefinitionRequestAck is used for accepting (with or without changes) or rejecting the definition of risk limits.
CU	PartyEntitlementsRequest	PartyEntitlementsRequest. The PartyEntitlementsRequest message is used to request for entitlement information for one or more party(-ies), specific party role(s), or specific instruments(s).
CV	PartyEntitlementsReport	PartyEntitlementsReport. The PartyEntitlementsReport is used to report entitlements for one or more parties, party role(s), or specific instrument(s).

Code	Name	Description
CW	QuoteAck	QuoteAck. The QuoteAck(35=CW) message is used to acknowledge a Quote(35=S) submittal or request to cancel an individual quote using the QuoteCancel(35=Z) message during a Quote/Negotiation dialog.
CX	PartyDetailsDefinitionRequest	PartyDetailsDefinitionRequest. The PartyDetailsDefinitionRequest(35=CX) is used for defining new parties and modifying or deleting existing parties information, including the relationships between parties. The recipient of the message responds with a PartyDetailsDefinitionRequestAck(35=CY) to indicate whether the request was accepted or rejected.
CY	PartyDetailsDefinitionRequestAck	PartyDetailsDefinitionRequestAck. The PartyDetailsDefinitionRequestAck(35=CY) is used as a response to the PartyDetailsDefinitionRequest(35=CX) message. The request can be accepted (with or without changes) or rejected.
CZ	PartyEntitlementsUpdateReport	PartyEntitlementsUpdateReport. The PartyEntitlementsUpdateReport(35=CZ) is used to convey incremental changes to party entitlements. It is similar to the PartyEntitlementsReport(35=CV). This message uses the PartyEntitlementsUpdateGrp component which includes the ability to specify an update action using ListUpdateAction(1324).
DA	PartyEntitlementsDefinitionRequest	PartyEntitlementsDefinitionRequest. The PartyEntitlementsDefinitionRequest(35=DA) is used for defining new entitlements, and modifying or deleting existing entitlements for the specified party(-ies).
DB	PartyEntitlementsDefinitionRequestAck	PartyEntitlementsDefinitionRequestAck. The PartyEntitlementsDefinitionRequestAck(35=DB) is used as a response to the PartyEntitlementsDefinitionRequest(35=DA) to accept (with or without changes) or reject the definition of party entitlements.
DC	TradeMatchReport	TradeMatchReport. The TradeMatchReport(35=DC) message is used by exchanges and ECN's to report matched trades to central counterparties (CCPs) as an atomic event. The message is used to express the one-to-one, one-to-many and many-to-many matches as well as implied matches in which more complex instruments can match with simpler instruments.
DD	TradeMatchReportAck	TradeMatchReportAck. The TradeMatchReportAck(35=DD) is used to respond to the TradeMatchReport(35=DC) message. It may be used to report on the status of the request (e.g. accepting the request or rejecting the request).

Code	Name	Description
DE	PartyRiskLimitsReportAck	PartyRiskLimitsReportAck. PartyRiskLimitsReportAck is an optional message used as a response to the PartyRiskLimitReport(35=CM) or PartyRiskLimitUpdateReport(35=CR) messages to acknowledge or reject those messages.
DF	PartyRiskLimitCheckRequest	PartyRiskLimitCheckRequest. PartyRiskLimitCheckRequest is used to request for approval of credit or risk limit amount intended to be used by a party in a transaction from another party that holds the information.
DG	PartyRiskLimitCheckRequestAck	PartyRiskLimitCheckRequestAck. PartyRiskLimitCheckRequestAck is used to acknowledge a PartyRiskLimitCheckRequest(35=DF) message and to respond whether the limit check request was approved or not. When used to accept the PartyRiskLimitCheckRequest(35=DF) message the Respondent may also include the limit amount that was approved.
DH	PartyActionRequest	PartyActionRequest. The PartyActionRequest message is used suspend or halt the specified party from further trading activities at the Respondent. The Respondent must respond with a PartyActionReport(35=DI) message.
DI	PartyActionReport	PartyActionReport. Used to respond to the PartyActionRequest(35=DH) message, indicating whether the request has been received, accepted or rejected. Can also be used in an unsolicited manner to report party actions, e.g. reinstatements after a manual intervention out of band.
DJ	MassOrder	MassOrder. The MassOrder(35=DJ) message can be used to add, modify or delete multiple unrelated orders with a single message. Apart from clearing related attributes, only the key order attributes for high performance trading are available.
DK	MassOrderAck	MassOrderAck. The mass order acknowledgement message is used to acknowledge the receipt of and the status for a MassOrder(35=DJ) message.
DL	PositionTransferInstruction	PositionTransferInstruction. The PositionTransferInstruction(35=DL) is sent by clearing firms to CCPs to initiate position transfers, or to accept or decline position transfers.
DM	PositionTransferInstructionAck	PositionTransferInstructionAck. The PositionTransferInstructionAck(35=DM) is sent by CCPs to clearing firms to acknowledge position transfer instructions, and to report errors processing position transfer instructions.

Code	Name	Description
DN	PositionTransferReport	PositionTransferReport. The PositionTransferReport(35=DN) is sent by CCPs to clearing firms indicating of positions that are to be transferred to the clearing firm, or to report on status of the transfer to the clearing firms involved in the transfer process.
DO	MarketDataStatisticsRequest	MarketDataStatisticsRequest. The MarketDataStatisticsRequest(35=DO) is used to request for statistical data. The simple form is to use an identifier (MDStatisticID(2475)) assigned by the market place which would denote a pre-defined statistical report. Alternatively, or also in addition, the request can define a number of parameters for the desired statistical information.
DP	MarketDataStatisticsReport	MarketDataStatisticsReport. The MarketDataStatisticsReport(35=DP) is used to provide unsolicited statistical information or in response to a specific request. Each report contains a set of statistics for a single entity which could be a market, a market segment, a security list or an instrument.
DQ	CollateralReportAck	CollateralReportAck. CollateralReportAck(35=DQ) is used as a response to the CollateralReport(35=BA). It can be used to reject a CollateralReport(35=BA) when the content of the report is invalid based on the business rules of the receiver. The message may also be used to acknowledge receipt of a valid CollateralReport(35=BA).
DR	MarketDataReport	MarketDataReport. The MarketDataReport(35=DR) message is used to provide delimiting references (e.g. start and end markers in a continuous broadcast) and details about the number of market data messages sent in a given distribution cycle.
DS	CrossRequest	CrossRequest. The CrossRequest(35=DS) message is used to indicate the submission of orders or quotes that may result in a crossed trade.
DT	CrossRequestAck	CrossRequestAck. The CrossRequestAck(35=DT) message is used to confirm the receipt of a CrossRequest(35=DS) message.
DU	AllocationInstructionAlertRequest	AllocationInstructionAlertRequest. This message is used in a clearinghouse 3-party allocation model to request for AllocationInstructionAlert(35=BM) from the clearinghouse. The request may be used to obtain a one-time notification of the status of an allocation group.

Code	Name	Description
DV	AllocationInstructionAlertRequestAck	AllocationInstructionAlertRequestAck. This message is used in a clearinghouse 3-party allocation model to acknowledge a AllocationInstructionAlertRequest(35=DU) message for an AllocationInstructionAlert(35=BM) message from the clearinghouse.
DW	TradeAggregationRequest	TradeAggregationRequest. TradeAggregationRequest(35=DW) is used to request that the identified trades between the initiator and respondent be aggregated together for further processing.
DX	TradeAggregationReport	TradeAggregationReport. TradeAggregationReport(35=DX) is used to respond to the TradeAggregationRequest(35=DW) message. It provides the status of the request (e.g. accepted or rejected) and may also provide additional information supplied by the respondent.
EA	PayManagementReport	PayManagementReport. PayManagementReport(35=EA) may be used to respond to the PayManagementRequest(35=DY) message. It provides the status of the request (e.g. accepted, disputed) and may provide additional information related to the request. PayManagementReport(35=EA) may also be sent unsolicited by the broker to a client. In which case the client may acknowledge and resolve disputes out-of-band or with a simple PayManagementReportAck(35=EB). PayManagementReport(35=EA) may also be sent unsolicited to report the progress status of the payment itself with PayReportTransType(2804)=2 (Status).
EB	PayManagementReportAck	PayManagementReportAck. PayManagementReportAck(35=EB) is used as a response to the PayManagementReport(35=EA) message. It may be used to accept, reject or dispute the details of the PayManagementReport(35=EA) depending on the business rules of the receiver. This message may also be used to acknowledge the receipt of a PayManagementReport(35=EA) message.
DY	PayManagementRequest	PayManagementRequest. PayManagementRequest(35=DY) message is used to communicate a future or expected payment to be made or received related to a trade or contract after its settlement.
DZ	PayManagementRequestAck	PayManagementRequestAck. PayManagementRequestAck(35=DZ) is used to acknowledge the receipt of the PayManagementRequest(35=DY) message (i.e. a technical acknowledgement of receipt). Acceptance or rejection of the request is reported in the corresponding PayManagementReport(35=EA).

Code	Name	Description
EC	SettlementStatusRequest	SettlementStatusRequest. SettlementStatusRequest(35=EC) is used to request for the settlement status of a trade.
ED	SettlementStatusRequestAck	SettlementStatusRequestAck. SettlementStatusRequestAck(35=ED) is used to respond to the SettlementStatusRequest(35=EC) to acknowledge the request and provide status for the request message.
EE	SettlementStatusReport	SettlementStatusReport. SettlementStatusReport(35=EE) is a response to the SettlementStatusRequest(35=EC) to provide settlement status for the requested trade. It may also be sent unsolicited without an explicit request message by the party able to provide the settlement status for the trade identified in the report message.
EF	SettlementStatusReportAck	SettlementStatusReportAck. SettlementStatusReportAck(35=EF) is used to respond to the SettlementStatusReport(35=EE) to acknowledge or reject the report.
EG	SecurityRiskMetricsReport	SecurityRiskMetricsReport. SecurityRiskMetricsReport(35=EG) is used for publishing the risk metrics, valuation metrics or analytics of one or more securities, or for an option series.
EH	AlgoCertificateRequest	AlgoCertificateRequest. AlgoCertificateRequest(35=EH) is used to request algo testing certificate information for one or more algorithms.
EI	AlgoCertificateRequestAck	AlgoCertificateRequestAck. AlgoCertificateRequestAck(35=EI) is used to respond to the AlgoCertificateRequest(35=EH) to acknowledge the request and provide status for the request message.
EJ	AlgoCertificateReport	AlgoCertificateReport. AlgoCertificateReport(35=EJ) is a response to the AlgoCertificateRequest(35=EH) to certify an algo. It may also be sent unsolicited without an explicit request message by the party able to provide certificate information for the algo identified in the report message.
EK	AlgoCertificateReportAck	AlgoCertificateReportAck. AlgoCertificateReportAck(35=EK) is used to respond to the AlgoCertificateReport(35=EJ) to acknowledge or reject the report message.
EL	TestSuiteDefinitionRequest	TestSuiteDefinitionRequest. TestSuiteDefinitionRequest(35=EL) is used to convey to the test system the suite of test scenarios to perform.
EM	TestSuiteDefinitionRequestAck	TestSuiteDefinitionRequestAck. TestSuiteDefinitionRequestAck(35=EM) is used to respond to the TestSuiteDefinitionRequest(35=EL) to acknowledge the request and provide status for the request message.

Code	Name	Description
EN	TestActionRequest	TestActionRequest. TestActionRequest(35=EN) is used to manage test executions or request for testing activity state of the identified test suite.
EO	TestActionRequestAck	TestActionRequestAck. TestActionRequestAck(35=EO) is used to respond to the TestActionRequest(35=EN) to acknowledge the request and provide status for the request message.
EP	TestActionReport	TestActionReport. TestActionReport(35=EP) is used to report the testing results of the identified test suite that has been executed with TestActionRequest(35=EN). In the context of algorithmic trading, the results may be used to create a certificate for the algorithm upon meeting the success criteria.

Used in groups: **MsgTypeGrp**

Used in messages: **BusinessMessageReject, Reject**

#### **180.2.4504 RefOrderID**

The ID reference to the order being hit or taken.

For pre-trade credit/risk limit check process, this is the reference to the placed order, quote request or quote for the credit/risk limit check.

Type: **String**

Used in components: **TradeReportOrderDetail**

Used in groups: **ListOrdGrp**

Used in messages: **ExecutionReport, NewOrderMultileg, NewOrderSingle, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, Quote**

#### **180.2.4505 RefOrderIDSource**

Used to specify the source for the identifier in RefOrderID(1080). This can be an identifier provided in order depth market data when hitting (taking) a specific order or to identify what type of order or quote reference is being provided when seeking credit limit check. In the context of US CAT this can be used to identify related orders and quotes which are parent, previous, or manual orders or quotes. Previous relates to orders changing their unique system assigned order identifier.

Type: **char**



Allowed values in RefOrderIDSourceCodeSet:

Code	Name	Description
0	SecondaryOrderID	Secondary order ID. Can be used to refer to an additional order identifier assigned by the party accepting an order, e.g. SecondaryOrderID(198).
1	OrderID	Order ID. Can be used to refer to an order identifier assigned by the party accepting an order, e.g. OrderID(37).
2	MDEntryID	Market data entry ID. Can be used to refer to a market data entry identifier provided with market data, e.g. MDEntryID(278).
3	QuoteEntryID	Quote entry ID. Can be used to refer to a quote identifier provided with market data or quote, e.g. QuoteEntryID(299).
4	OriginalOrderID	Original order ID. Can be used to refer to an initial order identifier assigned by the party accepting an order, e.g. OrderID(37) that changed.
5	QuoteID	Quote ID. Can be used to refer to a quote identifier assigned by the party issuing the quote, e.g. QuoteID(117).
6	QuoteReqID	Quote request ID. Can be used to refer to a quote identifier or quote request identifier assigned by the party issuing the request, e.g. QuoteReqID(131).
7	PreviousOrderIdentifier	Previous order identifier. Can be used when previously assigned (unique) system order identifier has changed.
8	PreviousQuoteIdentifier	Previous quote identifier. Can be used when previously assigned (unique) quote identifier has changed.
9	ParentOrderIdentifier	Parent order identifier. Can be used where orders are split into child orders and need to refer back to their parent order.
A	ManualOrderIdentifier	Manual order identifier. Can be used to refer to a manually received order that is being replaced by an electronically received order.

Used in components: [TradeReportOrderDetail](#)

Used in groups: [ListOrdGrp](#)

Used in messages: [ExecutionReport](#), [NewOrderMultileg](#), [NewOrderSingle](#), [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#), [Quote](#)

#### **180.2.4506 RefOrdIDReason**

The reason for updating the RefOrdID

Type: **int**

Allowed values in RefOrdIDReasonCodeSet:

Code	Name	Description
0	GTCFromPreviousDay	GTC from previous day
1	PartialFillRemaining	Partial Fill Remaining
2	OrderChanged	Order Changed

Used in components: **TradeReportOrderDetail**

#### **180.2.4507 RefreshIndicator**

Set by the sender to tell the receiver to perform an immediate refresh of the book due to disruptions in the accompanying real-time feed

'Y' - Mandatory refresh by all participants

'N' - Process as required

Type: **Boolean**

Used in messages: **MarketDataSnapshotFullRefresh**

#### **180.2.4508 RefreshQty**

Defines the quantity used to refresh DisplayQty.

Type: **Qty**

Used in components: **DisplayInstruction**

#### **180.2.4509 RefRiskLimitCheckID**

The reference identifier of the PartyRiskLimitCheckRequest(35=DF) message, or a similar out of band message, that contained the approval for the risk/credit limit check request.

Type: **String**

Used in groups: **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationReport**, **ExecutionReport**

**180.2.4510 RefRiskLimitCheckIDType**

Specifies which type of identifier is specified in RefRiskLimitCheckID(2334) field.

Type: **int**

Allowed values in RefRiskLimitCheckIDTypeCodeSet:

Code	Name	Description
0	RiskLimitRequestID	RiskLimitRequestID(1666)
1	RiskLimitCheckID	RiskLimitCheckID(2319)
3	OutOfBandID	Out of band identifier

Used in groups: **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationReport**, **ExecutionReport**

**180.2.4511 RefSeqNum**

Reference message sequence number

Type: **SeqNum**

Used in messages: **BusinessMessageReject**, **Reject**

**180.2.4512 RefSubID**

Assigned value used to identify specific elements within a firm.

Type: **String**

Used in groups: **CompIDReqGrp**, **CompIDStatGrp**

**180.2.4513 RefTagID**

The tag number of the FIX field being referenced.

Type: **int**

Used in messages: **Reject**

#### **180.2.4514 RefTickTableID**

Spread table code referred by the security or symbol.

Type: **int**

Used in components: **Instrument**

#### **180.2.4515 RegistAcctType**

For CIV - a fund manager-defined code identifying which of the fund manager's account types is required.

Type: **String**

Used in messages: **RegistrationInstructions**

#### **180.2.4516 RegistDtls**

Set of Registration name and address details, possibly including phone, fax etc.

Type: **String**

Used in groups: **RgstDtlsGrp**

#### **180.2.4517 RegistEmail**

Email address relating to Registration name and address details

Type: **String**

Used in groups: **RgstDtlsGrp**

#### **180.2.4518 RegistID**

Unique identifier of the registration details as assigned by institution or intermediary.

Type: **String**

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderList**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **RegistrationInstructions**, **RegistrationInstructionsResponse**

**180.2.4519 RegistRefID**

Reference identifier for the RegistID(513) with Cancel and Replace RegistTransType(514) transaction types.

Type: **String**

Used in messages: **RegistrationInstructions**, **RegistrationInstructionsResponse**

**180.2.4520 RegistRejReasonCode**

Reason(s) why Registration Instructions has been rejected.

The reason may be further amplified in the RegistRejReasonCode field.

Possible values of reason code include:

Type: **int**

Allowed values in RegistRejReasonCodeCodeSet:

Code	Name	Description
1	InvalidAccountType	Invalid/unacceptable Account Type
2	InvalidTaxExemptType	Invalid/unacceptable Tax Exempt Type
3	InvalidOwnershipType	Invalid/unacceptable Ownership Type
4	NoRegDetails	Invalid/unacceptable No Reg Details
5	InvalidRegSeqNo	Invalid/unacceptable Reg Seq No
6	InvalidRegDetails	Invalid/unacceptable Reg Details
7	InvalidMailingDetails	Invalid/unacceptable Mailing Details
8	InvalidMailingInstructions	Invalid/unacceptable Mailing Instructions
9	InvalidInvestorID	Invalid/unacceptable Investor ID
10	InvalidInvestorIDSource	Invalid/unacceptable Investor ID Source
11	InvalidDateOfBirth	Invalid/unacceptable Date Of Birth
12	InvalidCountry	Invalid/unacceptable Investor Country Of Residence
13	InvalidDistribInstns	Invalid/unacceptable No Distrib Instns
14	InvalidPercentage	Invalid/unacceptable Distrib Percentage
15	InvalidPaymentMethod	Invalid/unacceptable Distrib Payment Method
16	InvalidAccountName	Invalid/unacceptable Cash Distrib Agent Acct Name
17	InvalidAgentCode	Invalid/unacceptable Cash Distrib Agent Code
18	InvalidAccountNum	Invalid/unacceptable Cash Distrib Agent Acct Num

Code	Name	Description
99	Other	Other

Used in messages: [RegistrationInstructionsResponse](#)

#### **180.2.4521 RegistRejReasonText**

Text indicating reason(s) why a Registration Instruction has been rejected.

Type: [String](#)

Used in messages: [RegistrationInstructionsResponse](#)

#### **180.2.4522 RegistStatus**

Registration status as returned by the broker or (for CIV) the fund manager:

Type: [char](#)

Allowed values in RegistStatusCodeSet:

Code	Name	Description
A	Accepted	Accepted
R	Rejected	Rejected
H	Held	Held
N	Reminder	Reminder - i.e. Registration Instructions are still outstanding

Used in messages: [PositionReport](#), [RegistrationInstructionsResponse](#)

#### **180.2.4523 RegistTransType**

Identifies Registration Instructions transaction type

Type: [char](#)

Allowed values in RegistTransTypeCodeSet:

Code	Name	Description
0	New	New
2	Cancel	Cancel
1	Replace	Replace

Used in messages: [RegistrationInstructions](#), [RegistrationInstructionsResponse](#)

### 180.2.4524 RegulatoryLegRefID

Identifies the leg of the trade the entry applies to by referencing the leg's LegID(1788).

Type: [String](#)

Used in groups: [RegulatoryTradeIDGrp](#)

### 180.2.4525 RegulatoryReportType

Type of regulatory report.

Type: [int](#)

Allowed values in RegulatoryReportTypeCodeSet:

Code	Name	Description
0	RT	Real-time (RT). Report of data relating to a regulated transaction including price and volume that is to be disseminated publically. If dissemination is to be suppressed due to an end user exception or to local regulatory rules that allow suppression of certain types of transactions use TradePublishIndicator(1390)=0.
1	PET	Primary economic terms (PET). Report to regulators of the full terms of a regulated transaction included in the legal confirmation.
2	Snapshot	Snapshot. Periodic report of full primary economic terms data throughout the life cycle of a regulated transaction.
3	Confirmation	Confirmation. Report from a clearing organization of a cleared regulated transaction.
4	RTPET	Combination of RT and PET. A single report combining the requirements of both real-time and full primary economy terms of a regulated transaction.

Code	Name	Description
5	PETConfirmation	Combination of PET and confirmation. A single report combining the requirements of both full primary economic terms of a regulated transaction report and confirmation.
6	RTPETConfirmation	Combination of RT, PET and confirmation. A single report combining the requirements of real-time and full primary economic terms of a regulated transaction report, and confirmation.
7	PostTrade	Post-trade valuation. Periodic report of the ongoing mark-to-market value of a regulated transaction.
8	Verification	Verification. Used by the trading counterparty to report its full primary economic terms of a regulated transaction separately to the repository.
9	PstTrdEvnt	Post-trade event. Report of a regulated transaction continuation event that does not fall within the requirements for real-time reporting.
10	PstTrdEvntRTReportable	Post trade event RT reportable. Report of a regulated transaction continuation event that falls within the requirements for real-time reporting and public dissemination. If dissemination is to be suppressed due to an end user exception or to local regulatory rules that allow suppression of certain types of transactions, use TradePublishIndicator(1390) = 0 (Do not publish trade).
11	LMTF	Limited Details Trade. Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(a)(i) for immediate publication of all details except the quantity. This is ESMA RTS 2 deferral flag "LMTF".
12	DATF	Daily Aggregated Trade. Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(a)(ii) for aggregated publication of at least 5 transactions before 9:00 a.m. local time next day. This is ESMA RTS 2 deferral flag "DATF".
13	VOLO	Volume Omission Trade. Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(b) for immediate publication of all details except the quantity. This is ESMA RTS 2 deferral flag "VOLO".
14	FWAF	Four Weeks Aggregation Trade. Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(c) (non-sovereign debt only) for aggregated publication of transactions executed over the course of one calendar week before 9:00 a.m. local time following Tuesday. This is ESMA RTS 2 deferral flag "FWAF".



Code	Name	Description
15	IDAF	Indefinite Aggregation Trade. Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(d) (sovereign debt only) for aggregated publication of transactions executed over the course of one calendar week before 9:00 a.m. local time following Tuesday. This is ESMA RTS 2 deferral flag "IDAF".
16	VOLW	Volume Omission Trade Eligible for Subsequent Aggregated Enrichment. Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(b) and (d) consecutively (sovereign debt only) for immediate publication of all details except the quantity. This is ESMA RTS 2 deferral flag "VOLW".
17	FULF	Full Details Trade of "Limited Details Trade". Full details of a previously reported "limited details trade (LMTF)". Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(a)(i) which is a follow-up publication of all details before 7pm local time on the second day after initial publication. This is ESMA RTS deferral flag "FULF".
18	FULA	Full Details of "Daily Aggregated Trade". Full details of a previously reported "daily aggregated trade (DATF)". Designates a trade in instruments specified in RTS 2 Article 11 (1)(a)(ii) which is a follow-up publication of the individual transaction with full details before 7pm local time on the second day after initial publication. This is ESMA RTS 2 deferral flag "FULA".
19	FULV	Full Details of "Volume Omission Trade". Full details of a previously reported "volume omission trade (VOLO)". Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(b) which is a follow-up publication of all details before 9 am local time four weeks after initial publication. This is ESMA RTS 2 deferral flag "FULV".
20	FULJ	Full Details of "Four Weeks Aggregation Trade". Full details of a previously reported "four weeks aggregation trade (FWAF)". Designates a trade in instruments specified in ESMA RTS 2 Article 11 (1)(c) (non-sovereign debt only) which is a follow-up publication of the individual transaction with full details before 9 am local time four weeks after initial publication. This is ESMA RTS 2 deferral flag "FULJ".

Code	Name	Description
21	COAF	Full Details in Aggregated Form of "Volume Omission Trade Eligible for Subsequent Aggregated Enrichment". Full details of a previously reported "volume omission trade eligible for subsequent aggregated enrichment (VOLW)". Designates a trade report in instruments specified in ESMA RTS 2 Article 11(1)(b) and (d) consecutively which is an aggregated publication of transactions executed over the course of one calendar week before 9:00 a.m. CET local time the following Tuesday four weeks after initial publication. This is ESMA RTS 2 deferral flag "COAF".
22	Order	Order. Report for order handling events to enter, change or delete orders. In the context of US CAT this is used for the event types MENO, MEOM, MEOJ, and MEOC.
23	ChildOrder	Child order. Report for child order handling events to enter, change or delete child orders. Child orders are created when a (parent) order is split into multiple (child) orders. In the context of US CAT this is used for the event types MECO, MECOM, and MECOC.
24	OrderRoute	Order route. Reported when an order is routed between market participants and/or execution venues such as an exchange. In the context of US CAT this is used for the event types MEOR, MEOA and MEIR.
25	Trade	Trade. Report for trade handling events to enter, change or delete trades. In the context of US CAT this is used for the event types MEOT, MEOF and MEFA.
26	Quote	Quote. Report for quote handling events to enter, change or delete quotes. In the context of US CAT this is used for the event types MENQ, MEQR, and MEQC.
27	Supplement	Supplement. Reported when an order, quote or trade report is split across multiple messages. The recipient must be able to create the full report by combining the initial and supplement reports. In the context of US CAT this is used for the event types MENOS, MEOMS and MEOTS.
28	NewTransaction	New transaction. In the context of EU SFTR reporting this corresponds to "action type" "NEW".
29	TransactionCorrection	Transaction correction. In the context of EU SFTR reporting this corresponds to "action type" "CORR".
30	TransactionModification	Transaction modification. In the context of EU SFTR reporting this corresponds to "action type" "MODI".

Code	Name	Description
31	CollateralUpdate	Collateral update. In the context of EU SFTR reporting this corresponds to "action type" "COLU" if CollStatus(910)=3 (Assigned (Accepted)), or "REUU" if CollStatus(910)=5 (Reused).
32	MarginUpdate	Margin update. In the context of EU SFTR reporting this corresponds to "action type" "MARU".
33	TransactionReportedInError	Transaction reported in error. In the context of EU SFTR reporting this corresponds to "action type" "EROR".
34	TerminationEarlyTermination	Termination / Early termination. In the context of EU SFTR reporting this corresponds to "action type" "ETRM".

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **CollateralReport**, **ExecutionReport**, **MarginRequirementReport**, **NewOrderSingle**, **PositionReport**, **Quote**, **QuoteStatusReport**, **TradeCaptureReport**

#### 180.2.4526 RegulatoryReportTypeBusinessDate

The business date on which the event identified in RegulatoryReportType(1934) took place.

Type: **LocalMktDate**

Used in messages: **CollateralReport**, **MarginRequirementReport**, **PositionReport**, **TradeCaptureReport**

#### 180.2.4527 RegulatoryTradeID

Trade identifier required by government regulators or other regulatory organizations for regulatory reporting purposes. For example, unique swap identifier (USI) as required by the U.S. Commodity Futures Trading Commission.

Type: **String**

Used in groups: **RegulatoryTradeIDGrp**

#### 180.2.4528 RegulatoryTradeIDEvent

Identifies the event which caused origination of the identifier in RegulatoryTradeID(1903). When more than one event is the cause, use the higher enumeration value. For example, if the identifier is

originated due to an allocated trade which was cleared and reported, use the enumeration value 2 (Clearing).

Type: **int**

Allowed values in RegulatoryTradeIDEventCodeSet:

Code	Name	Description
0	InitialBlockTrade	Initial block trade.
1	Allocation	Allocation. Determination that the block trade will not be further allocated.
2	Clearing	Clearing
3	Compression	Compression
4	Novation	Novation
5	Termination	Termination
6	PostTrdVal	Post-trade valuation

Used in groups: **RegulatoryTradeIDGrp**

### 180.2.4529 RegulatoryTradeIDGrp

The RegulatoryTradeIDGrp is a repeating component within the TradeCaptureReport message used to report the source, value and relationship of multiple identifiers for the same trade or position.

This component can be used to meet regulatory trade reporting requirements where identifiers such as the Unique Swaps Identifier (USI) in the US or the Unique Trade Identifier (UTI) in Europe and Canada are required to be reported, showing the chaining of these identifiers as needed.

Name	Mult.	Type	Description
NoRegulatoryTradeIDs	[1..1]	NumInGroup	
RegulatoryTradeID	[0..1]	String	Required if NoRegulatoryTradeIDs(1907) > 0.
RegulatoryTradeIDSource	[0..1]	CodeSet	
RegulatoryTradeIDEvent	[0..1]	CodeSet	
RegulatoryTradeIDType	[0..1]	CodeSet	
RegulatoryLegRefID	[0..1]	String	This field may be used for multi-leg trades sent as a single message to indicate that the entry applies only to a specific leg.
RegulatoryTradeIDScope	[0..1]	CodeSet	

Used in groups: [QuotReqGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAck](#), [AllocationReport](#), [AllocationReportAck](#), [CollateralReport](#), [Confirmation](#), [ConfirmationAck](#), [ExecutionAck](#), [ExecutionReport](#), [PositionMaintenanceReport](#), [PositionReport](#), [SettlementStatusReport](#), [SettlementStatusRequest](#), [TradeCaptureReport](#)

### **180.2.4530 RegulatoryTradeIDScope**

Specifies the scope to which the RegulatoryTradeID(1903) applies. Used when a trade must be assigned more than one identifier, e.g. one for the clearing member and another for the client on a cleared trade as with the principal model in Europe.

Type: [int](#)

Allowed values in RegulatoryTradeIDScopeCodeSet:

Code	Name	Description
1	ClearingMember	Clearing member
2	Client	Client

Used in groups: [RegulatoryTradeIDGrp](#)

### **180.2.4531 RegulatoryTradeIDSource**

Identifies the reporting entity that originated the value in RegulatoryTradeID(1903). The reporting entity identifier may be assigned by a regulator or from a supported standard identifier source scheme.

Type: [String](#)

Allowed values in RegulatoryTradeIDSourceCodeSet:

Code	Name	Description
1	UniqueTransactionIdentifier	Unique Transaction Identifier (ISO 23897)

Used in groups: [RegulatoryTradeIDGrp](#)

**180.2.4532 RegulatoryTradeIDType**

Specifies the type of trade identifier provided in RegulatoryTradeID(1903).

Contextual hierarchy of events for the same trade or transaction maybe captured through use of the different RegulatoryTradeIDType(1906) values using multiple instances of the repeating group as needed for regulatory reporting.

Type: **int**

Allowed values in RegulatoryTradeIDTypeCodeSet:

Code	Name	Description
0	Current	Current. The default if not specified.
1	Previous	Previous. The previous trade's identifier when reporting a cleared trade or novation of a previous trade.
2	Block	Block. The block trade's identifier when reporting an allocated subtrade.
3	Related	Related. The related trade identifier when reporting a mixed swap.
4	ClearedBlockTrade	Cleared block trade. Assigned by the CCP to a bunched order/trade when it needs to be cleared with the standby clearing firm prior to post-trade allocation.
5	TradingVenueTransactionIdentifier	Trading venue transaction identifier. Assigned by the trading venue to a transaction. In the context of ESMA RTS 22 and RTS 24, this is an unique transaction identification "number generated by trading venues and disseminated to both the buying and selling parties in accordance with Article 12 of [RTS 24 on the maintenance of relevant data relating to orders in financial instruments under Article 25 of Regulation 600/2014 EU]." (quoted text from RTS 22). "Uniqueness" may be defined per relevant regulations.
6	ReportTrackingNumber	Report tracking number. In the context of EMIR Refit this is a "unique code assigned to the execution of an order and common for a group of reports related to the same execution" (see Q28 in <a href="https://www.esma.europa.eu/sites/default/files/library/esma74-362-2281_final_report_guidelines_emir_refit.pdf">https://www.esma.europa.eu/sites/default/files/library/esma74-362-2281_final_report_guidelines_emir_refit.pdf</a> ). Also referred to as the RTN.

Used in groups: **RegulatoryTradeIDGrp**

**180.2.4533 RegulatoryTransactionType**

Specifies the regulatory mandate or rule that the transaction complies with.

Type: **int**

Allowed values in RegulatoryTransactionTypeCodeSet:

Code	Name	Description
0	None	None (default if not specified). The transaction does not fall under any special regulatory rule or mandate.
1	SEFRequiredTransaction	Swap Execution Facility (SEF) required transaction. The transaction is a "Required" transaction under Dodd-Frank Act SEF Rules. "Required" transactions are subject to the trade execution mandate under section 2(h)(8) of the CEA and are not block trades.
2	SEFPermittedTransaction	Swap Execution Facility (SEF) permitted transaction. The transaction is a "Permitted" transaction under Dodd-Frank Act SEF Rules. "Permitted" transactions are not subject to the clearing and trade execution mandates, illiquid or bespoke swaps, or block trades.

Used in groups: **QuotReqGrp**

Used in messages: **ExecutionReport, QuoteResponse, TradeCaptureReport**

**180.2.4534 RejectText**

Identifies the reason for rejection.

Type: **String**

Used in groups: **PartyDetailAckGrp, PartyEntitlementAckGrp, PartyRiskLimitsAckGrp**

Used in messages: **AlgoCertificateReportAck, AlgoCertificateRequestAck, AllocationInstructionAck, AllocationInstructionAlertRequestAck, AllocationReportAck, CollateralReportAck, CollateralResponse, ExecutionReport, MassOrderAck, OrderCancelReject, PartyActionReport, PartyDetailsListReport, PartyEntitlementsReport, PartyRiskLimitCheckRequestAck, PartyRiskLimitsReport, PartyRiskLimitsReportAck, PayManagementReport, PayManagementReportAck, PositionMaintenanceReport, PositionTransferInstructionAck, PositionTransferReport, QuoteAck, QuoteStatusReport, SettlementStatusReportAck, SettlementStatusRequestAck, TestActionRequestAck, TestSuiteDefinitionRequestAck, TradeAggregationReport, TradeCaptureReport, TradeCaptureReportAck, TradeMatchReportAck**

**180.2.4535 RelatedClosePrice**

Closing price of the underlying required to calculate the RealizedVariance(2587).

Type: **Price**

Used in groups: **ClearingPriceParametersGrp**

**180.2.4536 RelatedHighPrice**

Upper boundary for the price of a related entity, e.g. price of the underlying instrument in an Underlying Price Contingency (UPC) order.

Type: **Price**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**

**180.2.4537 RelatedInstrumentGrp**

The RelatedInstrumentGrp is a repeating component at the same hierarchical level as the Instrument component, describing relationships and linkages between the Instrument, UnderlyingInstrument and InstrumentLeg entries. If all instances of the UnderlyingInstrument in the message are true underliers of the Instrument then the RelatedInstrumentGrp component is not needed. If any instance of the UnderlyingInstrument has a different relationship, e.g. underlier of an InstrumentLeg, stream, equity equivalent or nearest exchange-traded contract or there are multiple instances of InstrumentLeg, then an entry for every relationship should be included in this component. When the RelatedInstrumentGrp appears within a repeating group, each entry only apply to the Instrument component at the same hierarchical level.

In messages, such as Email(35=C) and News(35=B), where Instrument and the InstrumentLeg are within their repeating groups, the RelatedInstrumentGrp component may be used to link legs and underliers to their appropriate base Instrument.

Name	Mult.	Type	Description
<b>NoRelatedInstruments</b>	[1..1]	NumInGroup	
<b>RelatedInstrumentType</b>	[0..1]	CodeSet	Conditionally required when NoRelatedInstruments > 0



Name	Mult.	Type	Description
RelatedSymbol	[0..1]	String	Either RelatedSymbol(1649) or RelatedSecurityID(1650) must be specified. For RelatedInstrumentType(1648)=1 ("hedges for" instrument) this would be the instrument being used to offset the option Instrument. If one of the "related to" fields is specified, this is the UnderlyingSymbol(311) of an underlying instrument defining the related security in the current message.
RelatedSecurityID	[0..1]	String	Either RelatedSymbol(1649) or RelatedSecurityID(1650) must be specified. If one of the "related to" fields is specified, this is the UnderlyingSecurityID(309) of an underlying instrument defining the related security in the current message.
RelatedSecurityIDSource	[0..1]	CodeSet	Conditionally required when RelatedSecurityID(1650) is specified.
RelatedSecurityType	[0..1]	CodeSet	May be omitted if RelatedSecurityID(1650) or RelatedSymbol(1649) refers to an underlying instrument in the current message.
RelatedMaturityMonthYear	[0..1]	MonthYear	May be omitted if RelatedSecurityID(1650) or RelatedSymbol(1649) refers to an underlying instrument in the current message.
RelatedToSecurityID	[0..1]	String	Mutually exclusive with RelatedToStreamXIDRef(2415) and RelatedToDividendPeriodXIDRef(2417). If correlation is with the security in Instrument component then all "related to" fields may be omitted.
RelatedToSecurityIDSource	[0..1]	CodeSet	Conditionally required when RelatedToSecurityID(2413) is specified.
RelatedToStreamXIDRef	[0..1]	XIDREF	Mutually exclusive with RelatedToSecurityID(2413) and RelatedToDividendPeriodXIDRef(2417). If correlation is with the security in Instrument component then all "related to" fields may be omitted.
RelatedToDividendPeriodXIDRef	[0..1]	XIDREF	Mutually exclusive with RelatedToSecurityID(2413) and RelatedToStreamXIDRef(2415). If correlation is with the security in Instrument component then all "related to" fields may be omitted.

Used in groups: **InstrmtGrp**, **InstrmtMDReqGrp**, **MDIncGrp**, **SecListGrp**, **SecLstUpdRelSymGrp**, **SecMassStatGrp**

Used in messages: **Advertisement**, **IOI**, **MarketDataSnapshotFullRefresh**, **MarketDataStatisticsReport**, **MarketDataStatisticsRequest**, **PositionMaintenanceReport**, **PositionMaintenanceRequest**, **PositionReport**, **SecurityDefinition**, **SecurityDefinitionRequest**, **SecurityDefinitionUpdateReport**, **SecurityListRequest**, **SecurityStatus**, **SecurityStatusRequest**, **TradeCaptureReport**

### **180.2.4538 RelatedInstrumentType**

The type of instrument relationship

Type: **int**

Allowed values in RelatedInstrumentTypeCodeSet:

Code	Name	Description
1	HedgesForInstrument	"hedges for" instrument
2	Underlier	Underlier
3	EquityEquivalent	Equity equivalent
4	NearestExchangeTradedContract	Nearest exchange traded contract
5	RetailEquivalent	Retail equivalent of wholesale instrument.
6	Leg	Leg. Used to associate or link InstrumentLeg to Instrument in messages where there can be multiple instruments, such as in Email(35=C) and News(35=B) messages.

Used in groups: **RelatedInstrumentGrp**

### **180.2.4539 RelatedLowPrice**

Lower boundary for the price of a related entity, e.g. price of the underlying instrument in an Underlying Price Contingency (UPC) order.

Type: **Price**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**

### **180.2.4540 RelatedMarketSegmentGrp**

This component is used to identify market segments that are related to each other for a business purpose. This component should not be used in lieu of available explicit FIX fields that denote specific

relationships (e.g. ParentMktSegmID(1325) for parent market segments), but rather should be used when no such fields exist.

Name	Mult.	Type	Description
NoRelatedMarketSegments	[1..1]	NumInGroup	Number of market segments.
RelatedMarketSegmentID	[0..1]	String	Required if NoRelatedMarketSegments (2545) > 0.
MarketSegmentRelationship	[0..1]	CodeSet	

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

#### 180.2.4541 RelatedMarketSegmentID

Identifies a related market segment.

Type: [String](#)

Used in groups: [RelatedMarketSegmentGrp](#)

#### 180.2.4542 RelatedMaturityMonthYear

Expiration date for the related instrument contract.

Type: [MonthYear](#)

Used in groups: [RelatedInstrumentGrp](#)

#### 180.2.4543 RelatedOrderGrp

This component is used to identify orders that are related to the order identified outside of this component for a business purpose. For example, the bundling of multiple orders into a single order. This component should not be used in lieu of explicit FIX fields that denote specific semantic relationships, but rather should be used when no such fields exist.

Name	Mult.	Type	Description
NoOrders	[1..1]	NumInGroup	
RelatedOrderID	[0..1]	String	Required if NoOrders(73) > 0.
RelatedOrderIDSource	[0..1]	CodeSet	The same value must be used for all orders having the same OrderRelationship(2890) value.

Name	Mult.	Type	Description
RelatedOrderTime	[0..1]	UTCTimestamp	
RelatedOrderQty	[0..1]	Qty	
OrderRelationship	[0..1]	CodeSet	May be used to explicitly express the type of relationship or to provide orders having different relationships.
OrderOriginationFirmID	[0..1]	String	May be used when aggregating orders that were originally submitted by different firms, e.g. due to a merger or acquisition.

Used in components: [TradeReportOrderDetail](#)

Used in messages: [ExecutionReport](#)

#### 180.2.4544 RelatedOrderID

Identifier of a related order.

Type: [String](#)

Used in groups: [RelatedOrderGrp](#)

#### 180.2.4545 RelatedOrderIDSource

Describes the source of the identifier that RelatedOrderID(2887) represents.

Type: [int](#)

Allowed values in RelatedOrderIDSourceCodeSet:

Code	Name	Description
0	NonFIXSource	Non-FIX Source
1	SystemOrderIdentifier	Order identifier. Can be used to refer to an order identifier assigned by the party accepting the order, e.g. OrderID(37).
2	ClientOrderIdentifier	Client order identifier. Can be used to refer to an order identifier assigned by the party initiating the order, e.g. CIOrdID(11).
3	SecondaryOrderIdentifier	Secondary order identifier. Can be used to refer to an additional order identifier assigned by the party accepting the order, e.g. SecondaryOrderID(198).

Code	Name	Description
4	SecondaryClientOrderIdentifier	Secondary client order identifier. Can be used to refer to an additional order identifier assigned by the party initiating the order, e.g. SecondaryCOrdID(526).

Used in groups: [RelatedOrderGrp](#)

#### **180.2.4546 RelatedOrderQty**

Quantity of the related order which can be less than its total quantity. For example, when only parts of an order contribute to an aggregated order.

Type: [Qty](#)

Used in groups: [RelatedOrderGrp](#)

#### **180.2.4547 RelatedOrderTime**

Timestamp for the assignment of a (unique) identifier to an order.

Type: [UTCTimestamp](#)

Used in groups: [RelatedOrderGrp](#)

#### **180.2.4548 RelatedPartyDetailAltID**

An alternate party identifier for the party specified in RelatedPartyID(1563).

Type: [String](#)

Used in groups: [RelatedPartyDetailAltIDGrp](#)

#### **180.2.4549 RelatedPartyDetailAltIDGrp**

Alternative identifiers for parties related to the party specified in the PartyDetailGrp.

Name	Mult.	Type	Description
<a href="#">NoRelatedPartyDetailAltID</a>	[1..1]	NumInGroup	
<a href="#">RelatedPartyDetailAltID</a>	[0..1]	String	Required when NoRelatedPartyDetailAltID > 0.

Name	Mult.	Type	Description
RelatedPartyDetailAltIDSource	[0..1]	CodeSet	Required when NoRelatedPartyDetailAltID > 0.
RelatedPartyDetailAltSubGrp	[0..*]	Group	

Used in groups: **RelatedPartyDetailGrp**

### 180.2.4550 RelatedPartyDetailAltIDSource

Identifies the source of the RelatedPartyDetailAltID(1570) value.

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number

Code	Name	Description
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: [RelatedPartyDetailAltIDGrp](#)

### 180.2.4551 RelatedPartyDetailAltSubGrp

Sub identifiers for related parties alternate identifiers.

Name	Mult.	Type	Description
NoRelatedPartyDetailAltSubIDs	[1..1]	NumInGroup	
RelatedPartyDetailAltSubID	[0..1]	String	Required when NoRelatedPartyDetailAltSubIDs > 0.
RelatedPartyDetailAltSubIDType	[0..1]	CodeSet	Required when NoRelatedPartyDetailAltSubIDs > 0.

Used in groups: [RelatedPartyDetailAltIDGrp](#)

### 180.2.4552 RelatedPartyDetailAltSubID

Sub-identifier for the party specified in RelatedPartyDetailAltID(1570).

Type: [String](#)

Used in groups: [RelatedPartyDetailAltSubGrp](#)

### 180.2.4553 RelatedPartyDetailAltSubIDType

Type of RelatedPartyDetailAltSubID(1573) value.

Type: [int](#)

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address



Code	Name	Description
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code

Code	Name	Description
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier

Code	Name	Description
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C = Credit institution authorized in accordance with Directive 2006/48/EC F = Investment firm in accordance with Directive 2004/39/EC I = Insurance undertaking authorized in accordance with Directive 73/239/EC L = Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O = Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R = Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U = UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N

Code	Name	Description
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.

Code	Name	Description
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI

Code	Name	Description
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: [RelatedPartyDetailAltSubGrp](#)

## 180.2.4554 RelatedPartyDetailGrp

Party details for parties related to the Party specified in the PartyDetailGrp.

Name	Mult.	Type	Description
<a href="#">NoRelatedPartyDetailID</a>	[1..1]	NumInGroup	
<a href="#">RelatedPartyDetailID</a>	[0..1]	String	Required if NoRelatedPartyDetails > 0.
<a href="#">RelatedPartyDetailIDSource</a>	[0..1]	CodeSet	Required if NoRelatedPartyDetails > 0.
<a href="#">RelatedPartyDetailRole</a>	[0..1]	CodeSet	Required if NoRelatedPartyDetails > 0.
<a href="#">RelatedPartyDetailRoleQualifier</a>	[0..1]	CodeSet	
<a href="#">RelatedPartyDetailSubGrp</a>	[0..*]	Group	
<a href="#">RelatedPartyDetailAltIDGrp</a>	[0..*]	Group	
<a href="#">PartyRelationshipGrp</a>	[0..*]	Group	

Used in groups: [PartyDetailGrp](#)

Used in messages: [PartyActionReport](#), [PartyActionRequest](#), [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#)

**180.2.4555 RelatedPartyDetailID**

Party identifier for the party related to the party specified in PartyDetailID(1691).

Type: **String**

Used in groups: **RelatedPartyDetailGrp**

**180.2.4556 RelatedPartyDetailIDSource**

Identifies the source of the RelatedPartyDetailID(1563).

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number

Code	Name	Description
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".



Used in groups: **RelatedPartyDetailGrp**

### **180.2.4557 RelatedPartyDetailRole**

Identifies the type or role of the RelatedPartyDetailID(1563) specified.

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization

Code	Name	Description
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty

Code	Name	Description
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank

Code	Name	Description
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent

Code	Name	Description
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.

Code	Name	Description
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: [RelatedPartyDetailGrp](#)

### 180.2.4558 RelatedPartyDetailRoleQualifier

Qualifies the value of RelatedPartyRole(1565)

Type: [int](#)

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.

Code	Name	Description
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).

Code	Name	Description
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: [RelatedPartyDetailGrp](#)

### 180.2.4559 RelatedPartyDetailSubGrp

PartySubGrp for related parties.

Name	Mult.	Type	Description
<a href="#">NoRelatedPartyDetailSubIDs</a>	[1..1]	NumInGroup	
<a href="#">RelatedPartyDetailSubID</a>	[0..1]	String	Required when NoRelatedPartyDetailSubIDs > 0.
<a href="#">RelatedPartyDetailSubIDType</a>	[0..1]	CodeSet	Required when NoRelatedPartyDetailSubIDs > 0.

Used in groups: [RelatedPartyDetailGrp](#)

### 180.2.4560 RelatedPartyDetailSubID

Sub-identifier for the party specified in RelatedPartyID(1563).

Type: [String](#)

Used in groups: [RelatedPartyDetailSubGrp](#)

### 180.2.4561 RelatedPartyDetailSubIDType

Type of RelatedPartyDetailSubID(1567) value.

Type: [int](#)

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System



Code	Name	Description
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code

Code	Name	Description
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.

Code	Name	Description
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a0 of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N

Code	Name	Description
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.

Code	Name	Description
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."

Code	Name	Description
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: [RelatedPartyDetailSubGrp](#)

#### 180.2.4562 RelatedPositionDate

Used to help identify the position when RelatedPositionID(1862) is not unique across multiple days. This date is generally the creation date of the identifier.

Type: [LocalMktDate](#)

Used in groups: [RelatedPositionGrp](#)

#### 180.2.4563 RelatedPositionGrp

This component is used to identify positions that are related to each other or to other trades. This should not be used in lieu of explicit FIX fields that denote specific semantic relationships, but rather should be used when no such fields exist.

Name	Mult.	Type	Description
NoRelatedPositions	[1..1]	NumInGroup	
RelatedPositionID	[0..1]	String	Required if NoRelatedPositions(1861) > 0.
RelatedPositionIDSource	[0..1]	CodeSet	
RelatedPositionDate	[0..1]	LocalMktDate	

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

#### 180.2.4564 RelatedPositionID

Identifier of a related position.

Type: [String](#)

Used in groups: [RelatedPositionGrp](#)

#### 180.2.4565 RelatedPositionIDSource

Describes the source of the identifier that RelatedPositionID(1862) represents.

Type: [int](#)

Allowed values in RelatedPositionIDSourceCodeSet:

Code	Name	Description
1	PosMaintRptID	Position maintenance report ID - PosMaintRptID(721)
2	TransferID	Position transfer ID - TransferID(2437)
3	PositionEntityID	Position entity ID - PositionID(2618)

Used in groups: [RelatedPositionGrp](#)

#### 180.2.4566 RelatedPriceSource

Source for the price of a related entity, e.g. price of the underlying instrument in an Underlying Price Contingency (UPC) order. Can be used together with RelatedHighPrice (1819) and/or RelatedLowPrice (1820).

Type: [int](#)

Allowed values in RelatedPriceSourceCodeSet:

Code	Name	Description
1	NBBid	NBB (National Best Bid)
2	NBOffer	NBO (National Best Offer)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#)

#### **180.2.4567 RelatedRegulatoryTradeIDSource**

Specifies the identifier of the reporting entity as assigned by regulatory agency.

Type: [String](#)

Used in groups: [RelatedTradeGrp](#)

#### **180.2.4568 RelatedSecurityID**

Related security identifier value of RelatedSecurityIDSource(1651) type.

Type: [String](#)

Used in groups: [RelatedInstrumentGrp](#)

#### **180.2.4569 RelatedSecurityIDSource**

Identifies class or source of the RelatedSecurityID (1650) value.

Type: [String](#)

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)



Code	Name	Description
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **RelatedInstrumentGrp**

**180.2.4570 RelatedSecurityType**

Security type of the related instrument.

Type: **String**

Allowed values in SecurityTypeCodeSet:

Code	Name	Description
ABS	AssetBackedSecurities	Asset-backed Securities
AN	OtherAnticipationNotes	Other Anticipation Notes (BAN, GAN, etc.)
BA	BankersAcceptance	Bankers Acceptance
BRADY	BradyBond	Brady Bond
CORP	CorporateBond	Corporate Bond
CS	CommonStock	Common Stock
EUSUPRA	EuroSupranationalCoupons	Euro Supranational Coupons. Identify the issuer name in Issuer(106).
FOR	ForeignExchangeContract	Foreign Exchange Contract
MF	MutualFund	Mutual Fund
REPO	Repurchase	Repurchase
TERM	TermLoan	Term Loan
BDN	BankDepositoryNote	Bank Depository Note
CAN	CanadianTreasuryNotes	Canadian Treasury Notes
CAP	Cap	Cap. In an interest rate cap, the buyer receives payments at the end of each period in which the rate indec exceeds the agreed strike rate.
CMB	CanadianMortgageBonds	Canadian Mortgage Bonds
COFO	CertificateOfObligation	Certificate Of Obligation
CPP	CorporatePrivatePlacement	Corporate Private Placement
FAC	FederalAgencyCoupon	Federal Agency Coupon
FORWARD	Forward	Forward
FXNDF	NonDeliverableForward	Non-deliverable forward
MLEG	MultilegInstrument	Multileg Instrument
PS	PreferredStock	Preferred Stock
RVLV	RevolverLoan	Revolver Loan
BN	BankNotes	Bank Notes
BUYSELL	BuySellback	Buy Sellback
CB	ConvertibleBond	Convertible Bond

Code	Name	Description
CDS	CreditDefaultSwap	Credit Default Swap
CMBS	Corp	Corp. Mortgage-backed Securities
COFP	CertificateOfParticipation	Certificate Of Participation
CTB	CanadianTreasuryBills	Canadian Treasury Bills
DR	DepositoryReceipts	Depository Receipts
FADN	FederalAgencyDiscountNote	Federal Agency Discount Note
FXSPOT	FXSpot	FX Spot
NONE	NoSecurityType	No Security Type
RVLVTRM	Revolver	Revolver/Term Loan
BOX	BillOfExchanges	Bill Of Exchanges
BRIDGE	BridgeLoan	Bridge Loan
CLLR	Collar	Collar. In an interest rate collar, this is a combination of a cap and a floor.
CMO	CollateralizedMortgageObligation	Collateralized Mortgage Obligation
DUAL	DualCurrency	Dual Currency
EUSOV	EuroSovereigns	Euro Sovereigns. Identify the issuer name in Issuer(106).
FXFWD	FXForward	FX Forward
GO	GeneralObligationBonds	General Obligation Bonds
PEF	PrivateExportFunding	Private Export Funding. Identify the issuer name in Issuer(106).
SECLOAN	SecuritiesLoan	Securities Loan
UST	USTreasuryNoteOld	US Treasury Note (Deprecated Value Use TNOTE)
CAMM	CanadianMoneyMarkets	Canadian Money Markets
CMDTYSWAP	CommoditySwap	Commodity swap
EUCORP	EuroCorporateBond	Euro Corporate Bond
FXSWAP	FXSwap	FX Swap
IET	IOETTEMortgage	IOETTE Mortgage
LOFC	LetterOfCredit	Letter Of Credit
MT	MandatoryTender	Mandatory Tender
PROV	CanadianProvincialBonds	Canadian Provincial Bonds
SECPLEDGE	SecuritiesPledge	Securities Pledge
SUPRA	USDSupranationalCoupons	USD Supranational Coupons. Identify the issuer name in Issuer(106).
USTB	USTreasuryBillOld	US Treasury Bill (Deprecated Value Use TBILL)
?	Wildcard	Wildcard entry for use on Security Definition Request
CD	CertificateOfDeposit	Certificate Of Deposit

Code	Name	Description
DVPLDG	DeliveryVersusPledge	Delivery versus pledge
EUFRN	EuroCorporateFloatingRateNotes	Euro Corporate Floating Rate Notes
EXOTIC	Exotic	Exotic
FXNDS	NonDeliverableSwap	Non-deliverable Swap
MBS	MortgageBackedSecurities	Mortgage-backed Securities
RAN	RevenueAnticipationNote	Revenue Anticipation Note
SWING	SwingLineFacility	Swing Line Facility
TB	TreasuryBill	Treasury Bill - non US
CASH	Cash	Cash
CL	CallLoans	Call Loans
COLLBSKT	CollateralBasket	Collateral basket. A collection of securities held as collateral in the customer's collateral fund. The collateral fund is usually managed by a custodian.
DINP	DebtorInPossession	Debtor In Possession
FLR	Floor	Floor. In an interest rate floor, the buyer receives payments at the end of each period in which the rate index is below the agreed strike rate.
FRN	USCorporateFloatingRateNotes	US Corporate Floating Rate Notes
FXBN	FXBankNote	FX Bank Note
MIO	MortgageInterestOnly	Mortgage Interest Only
OOCC	OptionsOnCombo	Options on Combo
REV	RevenueBonds	Revenue Bonds
TBOND	USTreasuryBond	US Treasury Bond
CP	CommercialPaper	Commercial Paper
DEFLTED	Defaulted	Defaulted
FRA	FRA	Forward Rate Agreement
FXDN	ForeignCurrencyDiscountNote	Foreign Currency Discount Note. Discount notes issued in foreign currency by Fannie Mae.
MPO	MortgagePrincipalOnly	Mortgage Principal Only
Other	Other	Other
SFP	StructuredFinanceProduct	Structured finance product
SPCLA	SpecialAssessment	Special Assessment
TINT	InterestStripFromAnyBondOrNote	Interest Strip From Any Bond Or Note
XLINKD	IndexedLinked	Indexed Linked
DN	DepositNotes	Deposit Notes

Code	Name	Description
ETN	ExchangeTradedNote	Exchange traded note
FUT	Future	Future
MPP	MortgagePrivatePlacement	Mortgage Private Placement
SPCLO	SpecialObligation	Special Obligation
STRUCT	StructuredNotes	Structured Notes
TBILL	USTreasuryBill	US Treasury Bill
TIPS	TreasuryInflationProtectedSecurities	Treasury Inflation Protected Securities
WITHDRN	Withdrawn	Withdrawn
EUCD	EuroCertificateOfDeposit	Euro Certificate Of Deposit
FWD	DerivativeForward	Derivative forward
MPT	MiscellaneousPassThrough	Miscellaneous Pass-through
MRGNLOAN	MarginLoan	Margin loan
REPLACD	Replaced	Replaced
SPCLT	SpecialTax	Special Tax
TCAL	PrincipalStripOfACallableBondOrNote	Principal Strip Of A Callable Bond Or Note
YANK	YankeeCorporateBond	Yankee Corporate Bond
DIMSUMCORP	OffshoreIssuedChineseYuanCorporateBond	Offshore issued Chinese Yuan (CNY) denominated corporate bond
EUCP	EuroCommercialPaper	Euro Commercial Paper
IRS	InterestRateSwap	Interest Rate Swap
MATURED	Matured	Matured
PFAND	Pfandbrief	Pfandbrief. Identify the issuer name in Issuer(106).
SECDERIV	SecuritizedDerivative	Securitized derivative
TAN	TaxAnticipationNote	Tax Anticipation Note
TPRN	PrincipalStripFromANonCallableBondOrNote	Principal Strip From A Non-Callable Bond Or Note
TRS	TotalReturnSwap	Total return swap
AMENDED	Amended	Amended and restated
ETF	ExchangeTradedFund	Exchange Traded Fund
LOANLEASE	LoanLease	Loan/lease
LQN	LiquidityNote	Liquidity Note
PRCORP	PreferredCorporateBond	Preferred Corporate Bond
TAXA	TaxAllocation	Tax Allocation
TBA	ToBeAnnounced	To Be Announced

Code	Name	Description
TNOTE	USTreasuryNote	US Treasury Note
DIGITAL	DigitalAsset	Digital Asset. Asset that exists only in digital form or which is the digital representation of another asset (Source: ISO 24165 - Terms and Definitions).
DIMSUMSOV	OffshoreIssuedChineseYuanSovereignBond	Offshore issued Chinese Yuan (CNY) denominated sovereign bond
MTN	MediumTermNotes	Medium Term Notes
RETIRED	Retired	Retired
TECP	TaxExemptCommercialPaper	Tax Exempt Commercial Paper
ONITE	Overnight	Overnight
OOF	OptionsOnFutures	Options on Futures
SOV	SovereignBond	Sovereign Bond. Sovereign or government bond other than Euro and US issuer. Specify sovereign issuer in Issuer(106).
TMCP	TaxableMunicipalCP	Taxable Municipal CP
OOP	OptionsOnPhysical	Options on Physical - use not recommended
PN	PromissoryNote	Promissory Note
STN	ShortTermLoanNote	Short Term Loan Note
TFRN	USTreasuryFloatingRateNote	US Treasury Floating Rate Note
TRAN	TaxRevenueAnticipationNote	Tax Revenue Anticipation Note
OPT	Option	Option
PZFJ	PlazosFijos	Plazos Fijos
VRDN	VariableRateDemandNote	Variable Rate Demand Note
SLQN	SecuredLiquidityNote	Secured Liquidity Note
SPOTFWD	SpotForward	Spot forward
WAR	Warrant	Warrant
MCPIB	MunicipalInterestBearingCommercialPaper	Municipal Interest Bearing Commercial Paper
SWAPTION	SwapOption	Swap option
TD	TimeDeposit	Time Deposit
TMB	TaxableMunicipalBond	Taxable Municipal Bond
XMISSION	Transmission	Transmission
INDEX	Index	General type for a contract based on an established index
TLQN	TermLiquidityNote	Term Liquidity Note
VRDO	VariableRateDemandObligation	Variable Rate Demand Obligation
BDBSKT	BondBasket	Bond basket

Code	Name	Description
XCN	ExtendedCommNote	Extended Comm Note
CFD	ContractForDifference	Contract for difference
YCD	YankeeCertificateOfDeposit	Yankee Certificate Of Deposit
BAB	BankAcceptedBill	Bank Accepted Bill. Also known as Bank Bill.
CRLNSWAP	CorrelationSwap	Correlation swap
BNST	ShortTermBankNote	Short Term Bank Note
DVDNSWAP	DividendSwap	Dividend swap
CLCP	CallableCommercialPaper	Callable Commercial Paper
EQBSKT	EquityBasket	Equity basket
CN	CommercialNote	Commercial Note
EQFWD	EquityForward	Equity forward
CPIB	InterestBearingCommercialPaper	Interest Bearing Commercial Paper
RTRNSWAP	ReturnSwap	Return swap
EUMTN	EuroMediumTermNote	Euro Medium Term Note
VARSWAP	VarianceSwap	Variance swap
EUNCP	EuroNegotiableCommercialPaper	Euro Negotiable Commercial Paper
PRTFLIOSWAP	PortfolioSwaps	Portfolio swap
EUSTLQN	EuroStructuredLiquidityNote	Euro Structured Liquidity Note
FUTSWAP	FuturesOnASwap	Futures on a Swap
EUTD	EuroTimeDeposit	Euro Time Deposit
FWDSWAP	ForwardsOnASwap	Forwards on a Swap
FWDFRTAGMT	ForwardFreightAgreement	Forward Freight Agreement
JCD	JumboCertificateOfDeposit	Jumbo Certificate of Deposit
MMF	MoneyMarketFund	Money Market Fund
SPREADBET	SpreadBetting	Spread Betting
ETC	ExchangeTradedCommodity	Exchange traded commodity
MN	MasterNote	Master Note. Short term notes issued by Federal Farm Credit Banks Funding Corporation to provide loans and funding under Federal Farm Credit System (FFCS).
NCD	NegotiableCertificateOfDeposit	Negotiable Certificate of Deposit
NCP	NegotiableCommercialPaper	Negotiable Commercial Paper
RCD	RetailCertificateOfDeposit	Retail Certificate of Deposit
TDR	TermDepositReceipt	Term Deposit Receipt

Used in groups: [RelatedInstrumentGrp](#)

#### **180.2.4571 RelatedSymbol**

Ticker symbol of the related security. Common "human understood" representation of the security.

Type: [String](#)

Used in groups: [RelatedInstrumentGrp](#)

#### **180.2.4572 RelatedToDividendPeriodXIDRef**

The DividendPeriodXID(42293) of the stream dividend period with which the related instrument has correlation.

Type: [XIDREF](#)

Used in groups: [RelatedInstrumentGrp](#)

#### **180.2.4573 RelatedToSecurityID**

The security identifier of the instrument, instrument leg or underlying instrument with which the related instrument has correlation.

Type: [String](#)

Used in groups: [RelatedInstrumentGrp](#)

#### **180.2.4574 RelatedToSecurityIDSource**

Identifies class or source of the RelatedToSecurityID(2413) value.

Type: [String](#)

Allowed values in SecurityIDSourceCodeSet:

---

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN

---



Code	Name	Description
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [RelatedInstrumentGrp](#)

#### **180.2.4575 RelatedToStreamXIDRef**

StreamXID(41303), LegStreamXID(41700) or UnderlyingStreamXID(42016) of the stream with which the related instrument has correlation.

Type: [XIDREF](#)

Used in groups: [RelatedInstrumentGrp](#)

#### **180.2.4576 RelatedTradeDate**

Date of a related trade.

Type: [LocalMktDate](#)

Used in groups: [RelatedTradeGrp](#)

#### **180.2.4577 RelatedTradeGrp**

This component is used to identify trades that are related to each other for a business purpose, such as netting of forwards. This component should not be used in lieu of explicit FIX fields that denote specific semantic relationships, but rather should be used when no such fields exist.

Name	Mult.	Type	Description
<a href="#">NoRelatedTrades</a>	[1..1]	NumInGroup	
<a href="#">RelatedTradeID</a>	[0..1]	String	Required if <a href="#">NoRelatedTrades</a> (1855) > 0.
<a href="#">RelatedTradeIDSource</a>	[0..1]	CodeSet	
<a href="#">RelatedRegulatoryTradeIDSource</a>	[0..1]	String	Optionally used for <a href="#">RelatedTradeIDSource</a> (1857)=6(Regulatory trade ID) when <a href="#">RelatedTradeID</a> (1856) is not unique across multiple reporting entities.
<a href="#">RelatedTradeDate</a>	[0..1]	LocalMktDate	Optionally used to help identify the trade when <a href="#">RelatedTradeID</a> (1856) is not unique across multiple days.
<a href="#">RelatedTradeMarketID</a>	[0..1]	Exchange	Optionally used to help identify the trade when <a href="#">RelatedTradeID</a> (1856) is not unique across multiple markets.
<a href="#">RelatedTradeQuantity</a>	[0..1]	Qty	

Used in groups: **MDFullGrp**, **MDIncGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **PayManagementReport**, **PayManagementRequest**, **PositionMaintenanceReport**, **PositionReport**

#### **180.2.4578 RelatedTradeID**

Identifier of a related trade.

Type: **String**

Used in groups: **RelatedTradeGrp**

#### **180.2.4579 RelatedTradeIDSource**

Describes the source of the identifier that RelatedTradeID(1856) represents.

Type: **int**

Allowed values in RelatedTradeIDSourceCodeSet:

Code	Name	Description
0	NonFIXSource	Non-FIX source
1	TradeID	Trade ID
2	SecondaryTradeID	Secondary trade ID
3	TradeReportID	Trade report ID
4	FirmTradeID	Firm trade ID
5	SecondaryFirmTradeID	Secondary firm Trade ID
6	RegulatoryTradeID	Regulatory trade ID

Used in groups: **RelatedTradeGrp**

#### **180.2.4580 RelatedTradeMarketID**

Market of execution of related trade.

Type: **Exchange**

Used in groups: **RelatedTradeGrp**

**180.2.4581 RelatedTradeQuantity**

Quantity of the related trade which can be less than or equal to the actual quantity of the related trade. For example, when one trade offsets another across asset classes.

Type: Qty

Used in groups: RelatedTradeGrp

**180.2.4582 RelativeValue**

The valuation of an instrument relative to a base measurement specified in RelativeValueType(2530). This value can be negative.

Type: float

Used in groups: RelativeValueGrp

**180.2.4583 RelativeValueGrp**

The RelativeValueGrp component is used to convey relative valuation metrics or analytics for a given instrument.

Name	Mult.	Type	Description
NoRelativeValues	[1..1]	NumInGroup	
RelativeValueType	[0..1]	CodeSet	Required if NoRelativeValues(2529) > 0.
RelativeValue	[0..1]	float	Required if NoRelativeValues(2529) > 0.
RelativeValueSide	[0..1]	CodeSet	
RelativeValueTimestamp	[0..1]	UTCTimestamp	

Used in groups: SecurityRiskMetricGrp

Used in messages: ExecutionReport, IOI, Quote

**180.2.4584 RelativeValueSide**

Specifies the side of the relative value.

Type: int

Allowed values in RelativeValueSideCodeSet:

Code	Name	Description
1	Bid	Bid
2	Mid	Mid
3	Offer	Offer

Used in groups: [RelativeValueGrp](#)

### 180.2.4585 RelativeValueTimestamp

Timestamp at which the relative valuation metric or analytic is calculated or captured.

Type: [UTCTimestamp](#)

Used in groups: [RelativeValueGrp](#)

### 180.2.4586 RelativeValueType

Indicates the type of relative value measurement being specified.

Type: [int](#)

Allowed values in RelativeValueTypeCodeSet:

Code	Name	Description
1	ASWSpread	Asset Swap Spread. ASW Spread. The asset swap spread is the difference in the bond's yield (yield to maturity) and a floating interest rate (usually LIBOR), expressed in basis points.
2	OIS	Overnight Indexed Swap Spread. OIS Spread. The overnight indexed swap spread is the spread, expressed in basis points, between the bond yield (the fixed rate) and an overnight indexed rate (e.g. Fed Funds rate, EONIA, SONIA, etc.) (the floating rate).
3	ZSpread	Zero Volatility Spread. Z-Spread. The zero coupon spread is the constant spread added to the reference zero coupon yield curve (usually Treasury spot rate curve), expressed in basis points, to derive the adjusted yield curve used to determine the present value of the cash flows so that it equals the dirty price of the bond (i.e. accrued interest factored in).

Code	Name	Description
4	DiscountMargin	Discount Margin. The DM is the spread, expressed in basis points, added to the bond's reference rate that will equate the bond's cash flows to its current price.
5	ISpread	Interpolated Spread. I-Spread or I-Curve spread. The spread, expressed in basis points, added to an interpolated point on the reference yield curve.
6	OAS	Option Adjusted Spread. OAS or OA-spread. Used to evaluate bonds with embedded (callable or put-able) options. The option adjusted spread is a constant spread, expressed in basis points, applied to each point on the spot rate curve (usually Treasury spot rate curve) where the bond's cash flow is received, such that the price of the bond is the same as the present value of its cash flows.
7	GSpread	G-Spread. The spread difference between the bond's yield and the interpolated yield from the government reference yield curve, expressed in basis points. It represents the curve adjusted value of the bond by accounting for the difference between the bond's benchmark yield and the interpolated government reference yield at the same point on the curve that matches the bond's remaining life.
8	CDSBasis	CDS Basis. Also referred to as CDS Bond Basis. The CDS basis is the spread difference between the CDS spread or premium for the obligor and the Z-Spread or the ASW spread of the same reference or obligor bond, expressed in basis points.
9	CDSInterpolatedBasis	CDS Interpolated Basis. Also referred to as CDS Bond Interpolated Basis. The CDS interpolated basis is the difference between the reference or obligor bond's Z Spread or ASW spread and an interpolated point on CDS curve that matches the maturity of the reference bond, expressed in basis points.
10	DV01	DV01. The currency value change in response to a move of one basis point in the yield of the instrument. Typically used as a measure of interest rate risk of a single bond. Also known as "basis point value" or BPV.
11	PV01	PV01. The present value change in response to a move of one basis point all along the yield curve used for the instrument. In certain cases the DV01 and PV01 values may be the same.
12	CS01	CS01. Credit spread sensitivity. Represents the change in value of a (CDS) transaction for a one basis point change in the credit spread.

Used in groups: **RelativeValueGrp**

**180.2.4587 ReleaseInstruction**

Instruction to define conditions under which to release a locked order or parts of it.

Type: **int**

Allowed values in ReleaseInstructionCodeSet:

Code	Name	Description
1	ISO	Intermarket Sweep Order (ISO)
2	NoAwayMarketBetterCheck	No Away Market Better check

Used in messages: **ExecutionReport**, **OrderCancelReplaceRequest**

**180.2.4588 ReleaseQty**

Quantity to be made available, i.e. released from a lock.

Type: **Qty**

Used in messages: **ExecutionReport**, **OrderCancelReplaceRequest**

**180.2.4589 RelSymDerivSecGrp**

Name	Mult.	Type	Description
<b>NoRelatedSym</b>	[1..1]	NumInGroup	Specifies the number of repeating symbols (instruments) specified
<b>Instrument</b>	[0..1]	Component	
<b>SecondaryPriceLimits</b>	[0..1]	Component	Secondary price limit rules
<b>Currency</b>	[0..1]	Currency	
<b>CurrencyCodeSource</b>	[0..1]	CodeSet	
<b>CorporateAction</b>	[0..1]	CodeSet	Identifies the type of Corporate Action
<b>InstrumentExtension</b>	[0..1]	Component	
<b>InstrmtLegGrp</b>	[0..*]	Group	
<b>RelSymTransactTime</b>	[0..1]	UTCTimestamp	
<b>NumOfSimpleInstruments</b>	[0..1]	int	Number of simple instruments.
<b>Text</b>	[0..1]	String	Comment, instructions, or other identifying information.

Name	Mult.	Type	Description
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: [DerivativeSecurityList](#)

### 180.2.4590 RelSymDerivSecUpdGrp

Name	Mult.	Type	Description
NoRelatedSym	[1..1]	NumInGroup	
ListUpdateAction	[0..1]	CodeSet	If provided, then Instrument occurrence has explicitly changed
CorporateAction	[0..1]	CodeSet	
Instrument	[0..1]	Component	
InstrumentExtension	[0..1]	Component	
SecondaryPriceLimits	[0..1]	Component	Secondary price limit rules
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
InstrmtLegGrp	[0..*]	Group	
RelSymTransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	Comment, instructions, or other identifying information.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: [DerivativeSecurityListUpdateReport](#)

### 180.2.4591 RelSymTransactTime

See TransactTime(60)



Type: **UTCTimestamp**

Used in groups: **RelSymDerivSecGrp**, **RelSymDerivSecUpdGrp**, **SecListGrp**, **SecLstUpdRelSymGrp**

#### **180.2.4592 RemunerationIndicator**

Indicates whether the trade price was adjusted for compensation (i.e. includes a mark-up, mark-down or commission) in the price paid.

Type: **int**

Allowed values in RemunerationIndicatorCodeSet:

Code	Name	Description
0	NoRemunerationPaid	No remuneration paid
1	RemunerationPaid	Remuneration paid

Used in groups: **TrdCapRptSideGrp**

#### **180.2.4593 ReplaceText**

Identifies the reason for amendment.

Type: **String**

Used in messages: **PayManagementReport**

#### **180.2.4594 RepoCollateralSecurityType**

Identifies the collateral used in the transaction.

Valid values: see SecurityType (167) field (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **String**

Used in components: **Instrument**

#### **180.2.4595 ReportedPx**

Reported price (used to differentiate from AvgPx on a confirmation of a marked-up or marked-down principal trade)

Type: **Price**

Used in messages: **Confirmation**

#### **180.2.4596 ReportedPxDiff**

Indicates that the reported price that is different from the market price. The price difference should be stated by using field 828 TrdType and, if required, field 829 TrdSubType

Type: **Boolean**

Used in messages: **TradeCaptureReport**

#### **180.2.4597 ReportingPx**

Represents the reportable price on fill when an instance of the Parties component with PartyRole(452) = 73 (Execution Venue) is present to prevent having to compute running totals.

Type: **Price**

Used in messages: **ExecutionReport**

#### **180.2.4598 ReportingQty**

Represents the reportable quantity on fill when an instance of the Parties component with PartyRole(452) = 73 (Execution Venue) is present to prevent having to compute running totals.

Type: **Qty**

Used in messages: **ExecutionReport**

#### **180.2.4599 ReportToExch**

Identifies party of trade responsible for exchange reporting.

Type: **Boolean**

Allowed values in ReportToExchCodeSet:

---

Code	Name	Description
N	SenderReports	Indicates the party sending message will report trade
Y	ReceiverReports	Indicates the party receiving message must report trade

---

Used in messages: **ExecutionReport**

#### **180.2.4600 RepurchaseRate**

Percent of par at which a Repo will be repaid. Represented as a percent, e.g. .9525 represents 95-/4 percent of par. (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **Percentage**

Used in components: **Instrument**

#### **180.2.4601 RepurchaseTerm**

Number of business days before repurchase of a repo. (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **int**

Used in components: **Instrument**

#### **180.2.4602 RequestedPartyRole**

Identifies the type or role of party that has been requested.

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)

Code	Name	Description
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account

Code	Name	Description
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)

Code	Name	Description
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm

Code	Name	Description
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)

Code	Name	Description
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **RequestedPartyRoleGrp**

### 180.2.4603 RequestedPartyRoleGrp

Used to specify one or more PartyRoles as part of a request.

Name	Mult.	Type	Description
NoRequestedPartyRoles	[1..1]	NumInGroup	
RequestedPartyRole	[0..1]	CodeSet	Identifies the type of party role requested. Required if NoRequestedPartyRoles > 0.
RequestedPartyRoleQualifier	[0..1]	CodeSet	



Used in messages: [PartyDetailsListRequest](#), [PartyEntitlementsRequest](#), [PartyRiskLimitsRequest](#)

#### 180.2.4604 RequestedPartyRoleQualifier

Used to further qualify the value of RequestedPartyRole(1509).

Type: [int](#)

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.

Code	Name	Description
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **RequestedPartyRoleGrp**

#### 180.2.4605 RequestedRiskLimitTypesGrp

List of risk limit types being requested.

Name	Mult.	Type	Description
NoRequestedRiskLimitType	[1..1]	NumInGroup	
RiskLimitType	[0..1]	CodeSet	Required if NoRequestedRiskLimitType > 0.

Used in messages: **PartyRiskLimitsRequest**

### 180.2.4606 RequestingPartyGrp

Identifies the party making the request.

Name	Mult.	Type	Description
NoRequestingPartyIDs	[1..1]	NumInGroup	
RequestingPartyID	[0..1]	String	Required when NoRequestingPartyIDs > 0.
RequestingPartyIDSource	[0..1]	CodeSet	Required when NoRequestingPartyIDs > 0.
RequestingPartyRole	[0..1]	CodeSet	Required when NoRequestingPartyIDs > 0.
RequestingPartyRoleQualifier	[0..1]	CodeSet	
RequestingPartySubGrp	[0..*]	Group	

Used in messages: **PartyActionReport**, **PartyActionRequest**, **PartyDetailsDefinitionRequest**, **PartyDetailsDefinitionRequestAck**, **PartyDetailsListRequest**, **PartyDetailsListUpdateReport**, **PartyEntitlementsDefinitionRequest**, **PartyEntitlementsDefinitionRequestAck**, **PartyEntitlementsRequest**, **PartyEntitlementsUpdateReport**, **PartyRiskLimitCheckRequest**, **PartyRiskLimitCheckRequestAck**, **PartyRiskLimitsDefinitionRequest**, **PartyRiskLimitsDefinitionRequestAck**, **PartyRiskLimitsRequest**, **PartyRiskLimitsUpdateReport**

### 180.2.4607 RequestingPartyID

Party identifier for the requesting party.

Type: **String**

Used in groups: **RequestingPartyGrp**

### 180.2.4608 RequestingPartyIDSource

Identifies the source of the RequestingPartyID(1658) value.

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI

Code	Name	Description
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **RequestingPartyGrp**

### 180.2.4609 RequestingPartyRole

Identifies the type or role of the RequestingPartyID(1658) specified.

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party

Code	Name	Description
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)

Code	Name	Description
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionV- enue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm



Code	Name	Description
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor

Code	Name	Description
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **RequestingPartyGrp**

**180.2.4610 RequestingPartyRoleQualifier**

Qualifies the value of RequestingPartyRole(1660).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange

Code	Name	Description
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **RequestingPartyGrp**

#### 180.2.4611 RequestingPartySubGrp

Sub identifiers for the requesting party.

Name	Mult.	Type	Description
NoRequestingPartySubIDs	[1..1]	NumInGroup	

Name	Mult.	Type	Description
RequestingPartySubID	[0..1]	String	Required when NoRequestingPartySubIDs > 0.
RequestingPartySubIDType	[0..1]	CodeSet	Required when NoRequestingPartySubIDs > 0.

Used in groups: [RequestingPartyGrp](#)

### 180.2.4612 RequestingPartySubID

Sub-identifier for the party specified in RequestingPartyID(1658).

Type: [String](#)

Used in groups: [RequestingPartySubGrp](#)

### 180.2.4613 RequestingPartySubIDType

Type of RequestingPartySubID(1662) value.

Type: [int](#)

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)

Code	Name	Description
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).

Code	Name	Description
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.

Code	Name	Description
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.



Code	Name	Description
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.

Code	Name	Description
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.

Code	Name	Description
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **RequestingPartySubGrp**

### 180.2.4614 RequestResult

Result of a request as identified by the appropriate request ID field

Type: **int**

Allowed values in RequestResultCodeSet:

Code	Name	Description
0	ValidRequest	Valid request
1	InvalidOrUnsupportedRequest	Invalid or unsupported request
2	NoDataFound	No data found that match selection criteria
3	NotAuthorized	Not authorized to retrieve data
4	DataTemporarilyUnavailable	Data temporarily unavailable
5	RequestForDataNotSupported	Request for data not supported
99	Other	Other (further information in RejectText (1328) field)

Used in messages: **PartyDetailsListReport**, **PartyEntitlementsReport**, **PartyRiskLimitsReport**

### 180.2.4615 ResetSeqNumFlag

Indicates that both sides of the FIX session should reset sequence numbers.

Type: **Boolean**

Allowed values in ResetSeqNumFlagCodeSet:

Code	Name	Description
N	No	No
Y	Yes	Yes, reset sequence numbers

Used in messages: [Logon](#)

### 180.2.4616 RespondentType

Specifies the type of respondents requested.

Type: [int](#)

Allowed values in RespondentTypeCodeSet:

Code	Name	Description
1	AllMarketParticipants	All market participants
2	SpecifiedMarketParticipants	Specified market participants
3	AllMarketMakers	All Market Makers
4	PrimaryMarketMaker	Primary Market Maker(s)

Used in messages: [QuoteRequest](#), [QuoteRequestReject](#)

### 180.2.4617 ResponseDestination

URI (Uniform Resource Identifier) for details or other pre-arranged value. Used in conjunction with ResponseTransportType (725) value of Out-of-Band to identify the out-of-band destination.

See Appendix 6-B FIX Fields Based Upon Other Standards

Type: [String](#)

Used in messages: [CollateralInquiry](#), [CollateralInquiryAck](#), [MarginRequirementInquiry](#), [MarginRequirementInquiryAck](#), [RequestForPositions](#), [RequestForPositionsAck](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#), [TradeCaptureReportRequestAck](#)

### 180.2.4618 ResponseTime

The time by which a meaningful response should arrive back (always expressed in UTC (Universal Time Coordinated, also known as "GMT")).

Type: [UTCTimestamp](#)

Used in groups: [QuotReqGrp](#)

### 180.2.4619 ResponseTransportType

Identifies how the response to the request should be transmitted.

Type: [int](#)

Allowed values in ResponseTransportTypeCodeSet:

Code	Name	Description
0	Inband	In-band (default). Transport of the request was sent over in-band.
1	OutOfBand	Out of band. Pre-arranged out-of-band delivery mechanism (e.g. FTP, HTTP, NDM, etc.) between counterparties. Details specified via ResponseDestination(726).

Used in messages: [CollateralInquiry](#), [CollateralInquiryAck](#), [MarginRequirementInquiry](#), [MarginRequirementInquiryAck](#), [RequestForPositions](#), [RequestForPositionsAck](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#), [TradeCaptureReportRequestAck](#)

### 180.2.4620 RestructuringType

A category of CDS credit event in which the underlying bond experiences a restructuring.

Used to define a CDS instrument.

Type: [String](#)

Allowed values in RestructuringTypeCodeSet:

Code	Name	Description
FR	FullRestructuring	Full Restructuring
MR	ModifiedRestructuring	Modified Restructuring
MM	ModifiedModRestructuring	Modified Mod Restructuring
XR	NoRestructuringSpecified	No Restructuring specified

Used in components: [Instrument](#)

**180.2.4621 ReturnRateAmountRelativeTo**

Specifies the reference amount when the return rate amount is relative to another amount in the trade.

See [http://www.fixtradingcommunity.org/codelists#Payment\\_Amount\\_Relative\\_To](http://www.fixtradingcommunity.org/codelists#Payment_Amount_Relative_To) for code list of relative amounts.

Type: **int**

Used in groups: **ReturnRateGrp**

**180.2.4622 ReturnRateCashFlowType**

Specifies the type of cash flows, e.g. coupon payment, premium fee, settlement fee, etc.

See <http://www.fpml.org/coding-scheme/cashflow-type> for values.

Type: **String**

Used in groups: **ReturnRateGrp**

**180.2.4623 ReturnRateCommissionAmount**

The commission amount.

Type: **Amt**

Used in groups: **ReturnRateGrp**

**180.2.4624 ReturnRateCommissionBasis**

Specifies the basis or unit used to calculate the commission.

Type: **char**

Allowed values in CommTypeCodeSet:

---

Code	Name	Description
1	PerUnit	Amount per unit. Implying shares, par, currency, physical unit etc. Use CommissionUnitOfMeasure(1238) to clarify for commodities.
2	Percent	Percent

---

Code	Name	Description
3	Absolute	Absolute. Total monetary amount.
4	PercentageWaivedCashDiscount	Percentage waived, cash discount basis. For use with CIV buy orders.
5	PercentageWaivedEnhancedUnits	Percentage waived, enhanced units basis. For use with CIV buy orders.
6	PointsPerBondOrContract	Points per bond or contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention, e.g. 1000 par for bonds.
7	BasisPoints	Basis points. The commission is expressed in basis points in reference to the gross price of the reference asset.
8	AmountPerContract	Amount per contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention.

Used in groups: **ReturnRateGrp**

#### 180.2.4625 ReturnRateCommissionCurrency

Specifies the currency the commission amount is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **ReturnRateGrp**

#### 180.2.4626 ReturnRateDateGrp

ReturnRateDateGrp is a repeating subcomponent within the ReturnRateGrp component. It is used to specify the equity and dividend valuation dates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoReturnRateDates	[1..1]	NumInGroup	
ReturnRateDateMode	[0..1]	CodeSet	Required if NoReturnRateDates(42709) > 0.
ReturnRateValuationDateGrp	[0..*]	Group	
ReturnRateValuationDateRelativeTo	[0..1]	int	
ReturnRateValuationDateOffsetPeriod	[0..1]	int	Conditionally required when ReturnRateValuationDateOffsetUnit(42713) is specified.

Name	Mult.	Type	Description
ReturnRateValuationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when ReturnRateValuationDateOffsetPeriod(42712) is specified.
ReturnRateValuationDateOffsetDay-Type	[0..1]	CodeSet	
ReturnRateValuationStartDateUnadjusted	[0..1]	LocalMktDate	
ReturnRateValuationStartDateRelativeTo	[0..1]	int	
ReturnRateValuationStartDateOffsetPeriod	[0..1]	int	Conditionally required when ReturnRateValuationStartDateOffsetUnit(42718) is specified.
ReturnRateValuationStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when ReturnRateValuationStartDateOffsetPeriod(42717) is specified.
ReturnRateValuationStartDateOffsetDayType	[0..1]	CodeSet	
ReturnRateValuationStartDateAdjusted	[0..1]	LocalMktDate	
ReturnRateValuationEndDateUnadjusted	[0..1]	LocalMktDate	
ReturnRateValuationEndDateRelativeTo	[0..1]	int	
ReturnRateValuationEndDateOffsetPeriod	[0..1]	int	Conditionally required when ReturnRateValuationEndDateOffsetUnit(42724) is specified.
ReturnRateValuationEndDateOffsetUnit	[0..1]	CodeSet	Conditionally required when ReturnRateValuationEndDateOffsetPeriod(42723) is specified.
ReturnRateValuationEndDateOffsetDayType	[0..1]	CodeSet	
ReturnRateValuationEndDateAdjusted	[0..1]	LocalMktDate	
ReturnRateValuationFrequencyPeriod	[0..1]	int	Conditionally required when ReturnRateValuationFrequencyUnit(42728) is specified.
ReturnRateValuationFrequencyUnit	[0..1]	CodeSet	Conditionally required when ReturnRateValuationFrequencyPeriod(42727) is specified.



Name	Mult.	Type	Description
<b>ReturnRateValuationFrequencyRoll-Convention</b>	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the payment stream return rate valuation dates.
<b>ReturnRateValuationDateBusinessDay-Convention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to payment stream return rate valuation dates.
<b>ReturnRateValuationDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified values would be specific to payment stream return rate valuation dates.

Used in groups: **ReturnRateGrp**

#### 180.2.4627 ReturnRateDateMode

Specifies the valuation type applicable to the return rate date.

Type: **int**

Allowed values in ReturnRateDateModeCodeSet:

Code	Name	Description
0	PriceValuation	Price valuation
1	DividendValuation	Dividend valuation

Used in groups: **ReturnRateDateGrp**

#### 180.2.4628 ReturnRateDeterminationMethod

Specifies the method by which the underlier prices are determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **ReturnRateGrp**

**180.2.4629 ReturnRateFinalPriceFallback**

Specifies the fallback provision for the hedging party in the determination of the final price.

Type: **int**

Allowed values in ComplexEventPVFinalPriceElectionFallbackCodeSet:

Code	Name	Description
0	Close	Close. In respect of the "early final valuation date", the provisions for "future present value close" shall apply.
1	HedgeElection	Hedge election. In respect of the "early final valuation date", the provisions for "future present value hedge execution" shall apply.

Used in groups: **ReturnRateGrp**

**180.2.4630 ReturnRateFXConversionGrp**

ReturnRateFXConversionGrp is a repeating subcomponent within the ReturnRateGrp component. It is used to specify the FX conversion rates for an equity return swap payment stream.

Name	Mult.	Type	Description
<b>NoReturnRateFXConversions</b>	[1..1]	NumInGroup	
<b>ReturnRateFXCurrencySymbol</b>	[0..1]	String	Required if NoReturnRateFXConversions(42731) > 0.
<b>ReturnRateFXRate</b>	[0..1]	float	Required if NoReturnRateFXConversions(42731) > 0.
<b>ReturnRateFXRateCalc</b>	[0..1]	CodeSet	

Used in groups: **ReturnRateGrp**

**180.2.4631 ReturnRateFXCurrencySymbol**

Specifies the currency pair for the FX conversion expressed using the CCY1/CCY2 convention. Uses ISO 4217 currency codes.

Type: **String**

Used in groups: **ReturnRateFXConversionGrp**

**180.2.4632 ReturnRateFXRate**

The rate of exchange between the two currencies specified in ReturnRateFXCurrencySymbol(42732).

Type: **float**

Used in groups: **ReturnRateFXConversionGrp**

**180.2.4633 ReturnRateFXRateCalc**

Specifies whether ReturnRateFXRate(42733) should be multiplied or divided.

Type: **char**

Allowed values in SettlCurrFxRateCalcCodeSet:

Code	Name	Description
M	Multiply	Multiply
D	Divide	Divide

Used in groups: **ReturnRateFXConversionGrp**

**180.2.4634 ReturnRateGrp**

ReturnRateGrp is a repeating subcomponent within the PaymentStreamFloatingRate component. It is used to specify the multiple return rates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoReturnRates	[1..1]	NumInGroup	
ReturnRatePriceSequence	[0..1]	CodeSet	Required if NoReturnRates(42735) > 0.
ReturnRateCommissionBasis	[0..1]	CodeSet	
ReturnRateCommissionAmount	[0..1]	Amt	
ReturnRateCommissionCurrency	[0..1]	Currency	If not specified, this is defaulted to the reporting currency.
ReturnRateTotalCommissionPerTrade	[0..1]	Amt	
ReturnRateDeterminationMethod	[0..1]	String	
ReturnRatePriceGrp	[0..*]	Group	
ReturnRateFXConversionGrp	[0..*]	Group	

Name	Mult.	Type	Description
ReturnRateAmountRelativeTo	[0..1]	int	
ReturnRateQuoteMeasureType	[0..1]	String	
ReturnRateQuoteUnits	[0..1]	String	
ReturnRateQuoteMethod	[0..1]	CodeSet	
ReturnRateQuoteCurrency	[0..1]	Currency	
ReturnRateQuoteCurrencyType	[0..1]	String	
ReturnRateQuoteTimeType	[0..1]	CodeSet	Mutually exclusive with ReturnRateQuoteTime(42749).
ReturnRateQuoteTime	[0..1]	LocalMktTime	Mutually exclusive with ReturnRateQuoteTimeType(42748).
ReturnRateQuoteDate	[0..1]	LocalMktDate	
ReturnRateQuoteExpirationTime	[0..1]	LocalMktTime	
ReturnRateQuoteBusinessCenter	[0..1]	String	
ReturnRateQuoteExchange	[0..1]	Exchange	
ReturnRateInformationSourceGrp	[0..*]	Group	
ReturnRateQuotePricingModel	[0..1]	String	
ReturnRateCashFlowType	[0..1]	String	
ReturnRateDateGrp	[0..*]	Group	
ReturnRateValuationTimeType	[0..1]	CodeSet	Mutually exclusive with ReturnRateValuationTime(42757).
ReturnRateValuationTime	[0..1]	LocalMktTime	Mutually exclusive with ReturnRateValuationTimeType(42756).
ReturnRateValuationTimeBusiness-Center	[0..1]	String	
ReturnRateValuationPriceOption	[0..1]	CodeSet	
ReturnRateFinalPriceFallback	[0..1]	CodeSet	

Used in components: **PaymentStreamFloatingRate**

### 180.2.4635 ReturnRateInformationSource

Identifies the source of rate information. For FX the references source to be used for the FX spot rate.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: [ReturnRateInformationSourceGrp](#)

### 180.2.4636 ReturnRateInformationSourceGrp

ReturnRateInformationSourceGrp is a repeating subcomponent within the ReturnRateGrp component. It is used to specify the information sources for equity prices and FX rates for an equity return swap payment stream.

Name	Mult.	Type	Description
<a href="#">NoReturnRateInformationSources</a>	[1..1]	NumInGroup	
<a href="#">ReturnRateInformationSource</a>	[0..1]	CodeSet	Required if <a href="#">NoReturnRateInformationSources</a> (42761) > 0.
<a href="#">ReturnRateReferencePage</a>	[0..1]	String	
<a href="#">ReturnRateReferencePageHeading</a>	[0..1]	String	

Used in groups: [ReturnRateGrp](#)

### 180.2.4637 ReturnRateNotionalReset

Indicates whether the term "Equity Notional Reset" as defined in the ISDA 2002 Equity Derivatives Definitions is applicable ("Y") or not.

Type: [Boolean](#)

Used in components: [PaymentStreamFloatingRate](#)

**180.2.4638 ReturnRatePrice**

Specifies the price of the underlying swap asset.

Type: **Price**

Used in groups: **ReturnRatePriceGrp**

**180.2.4639 ReturnRatePriceBasis**

The basis of the return price.

Type: **int**

Allowed values in ReturnRatePriceBasisCodeSet:

Code	Name	Description
0	Gross	Gross.
1	Net	Net
2	Accrued	Accrued
3	CleanNet	Clean net

Used in groups: **ReturnRatePriceGrp**

**180.2.4640 ReturnRatePriceCurrency**

Specifies the currency of the price of the underlying swap asset. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **ReturnRatePriceGrp**

**180.2.4641 ReturnRatePriceGrp**

ReturnRatePriceGrp is a repeating subcomponent within the ReturnRateGrp component. It is used to specify the return rate prices for an equity return swap payment stream.

Name	Mult.	Type	Description
<b>NoReturnRatePrices</b>	[1..1]	NumInGroup	

Name	Mult.	Type	Description
ReturnRatePriceBasis	[0..1]	CodeSet	Required if NoReturnRatePrices(42765) > 0.
ReturnRatePrice	[0..1]	Price	
ReturnRatePriceCurrency	[0..1]	Currency	
ReturnRatePriceType	[0..1]	CodeSet	

Used in groups: **ReturnRateGrp**

### 180.2.4642 ReturnRatePriceSequence

Specifies the type of price sequence of the return rate.

Type: **int**

Allowed values in ReturnRatePriceSequenceCodeSet:

Code	Name	Description
0	Initial	Initial
1	Interim	Interim
2	Final	Final

Used in groups: **ReturnRateGrp**

### 180.2.4643 ReturnRatePriceType

Specifies whether the ReturnRatePrice(42767) is expressed in absolute or relative terms.

Type: **int**

Allowed values in ReturnRatePriceTypeCodeSet:

Code	Name	Description
0	AbsoluteTerms	Absolute terms
1	PercentageOfNotional	Percentage of notional

Used in groups: **ReturnRatePriceGrp**

**180.2.4644 ReturnRateQuoteBusinessCenter**

The business center calendar used for adjustments associated with ReturnRateQuoteTimeType(42748) or ReturnRateQuoteTime(42749) and ReturnRateQuoteDate(42750), e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ReturnRateGrp**

**180.2.4645 ReturnRateQuoteCurrency**

Specifies the currency the return rate quote is denominated in. Uses ISO 4217 Currency Code.

Type: **Currency**

Used in groups: **ReturnRateGrp**

**180.2.4646 ReturnRateQuoteCurrencyType**

Specifies the type of currency, e.g. settlement currency, base currency, etc., that the quote is reported in.

See <http://www.fpml.org/coding-scheme/reporting-currency-type> for values.

Type: **String**

Used in groups: **ReturnRateGrp**

**180.2.4647 ReturnRateQuoteDate**

The date when the quote is to be generated.

Type: **LocalMktDate**

Used in groups: **ReturnRateGrp**

**180.2.4648 ReturnRateQuoteExchange**

Specifies the exchange (e.g. stock or listed futures/options exchange) from which the quote is obtained.

Type: **Exchange**

Used in groups: **ReturnRateGrp**



**180.2.4649 ReturnRateQuoteExpirationTime**

The time when the quote ceases to be valid.

Type: **LocalMktTime**

Used in groups: **ReturnRateGrp**

**180.2.4650 ReturnRateQuoteMeasureType**

Specifies the type of the measure applied to the return rate's asset, e.g. valuation, sensitivity risk. This could be an NPV, a cash flow, a clean price, etc.

See <http://www.fpml.org/coding-scheme/asset-measure> for values.

Type: **String**

Used in groups: **ReturnRateGrp**

**180.2.4651 ReturnRateQuoteMethod**

Specifies the type of quote used to determine the return rate of the swap.

Type: **int**

Allowed values in CashSettlQuoteMethodCodeSet:

---

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer

---

Used in groups: **ReturnRateGrp**

**180.2.4652 ReturnRateQuotePricingModel**

Specifies the pricing model used to evaluate the underlying asset price.

See <http://www.fpml.org/coding-scheme/pricing-model> for values.

Type: **String**

Used in groups: **ReturnRateGrp**

**180.2.4653 ReturnRateQuoteTime**

The time when the quote is to be generated.

Type: **LocalMktTime**

Used in groups: **ReturnRateGrp**

**180.2.4654 ReturnRateQuoteTimeType**

Specifies how or the timing when the quote is to be obtained.

Type: **int**

Allowed values in ReturnRateQuoteTimeTypeCodeSet:

Code	Name	Description
0	Open	Open. The official opening time of the exchange on valuation date.
1	OfficialSettlPx	Official settlement price time. The time at which the official settlement price is determined.
2	Xetra	XETRA. The time at which the official settlement price (following the auction by the exchange) is determined by the exchange.
3	Close	Close. The official closing time of the exchange on valuation date.
4	DerivativesClose	Derivatives close. The official closing time for derivative trading of the exchange on valuation date.
5	High	High. The high price for the day.
6	Low	Low. The low price for the day.
7	AsSpecifiedInMasterConfirmation	As specified in the master confirmation

Used in groups: **ReturnRateGrp**

**180.2.4655 ReturnRateQuoteUnits**

Specifies the units that the measure is expressed in. If not specified, the default is a price/value in currency units.

See <http://www.fpml.org/coding-scheme/price-quote-units> for values.

Type: **String**

Used in groups: **ReturnRateGrp**

**180.2.4656 ReturnRateReferencePage**

Identifies the reference "page" from the rate source.

For FX, the reference page to the spot rate to be used for the reference FX spot rate.

When ReturnRateInformationSource(42762) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions.

See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in groups: **ReturnRateInformationSourceGrp**

**180.2.4657 ReturnRateReferencePageHeading**

Identifies the page heading from the rate source.

Type: **String**

Used in groups: **ReturnRateInformationSourceGrp**

**180.2.4658 ReturnRateTotalCommissionPerTrade**

The total commission per trade.

Type: **Amt**

Used in groups: **ReturnRateGrp**

**180.2.4659 ReturnRateValuationDate**

The return rate valuation date. Type of date is specified in ReturnRateValuationDateType(42774).

Type: **LocalMktDate**

Used in groups: **ReturnRateValuationDateGrp**

**180.2.4660 ReturnRateValuationDateBusinessCenter**

The business center calendar used for date adjustment of the return rate valuation unadjusted or relative dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ReturnRateValuationDateBusinessCenterGrp**

### 180.2.4661 ReturnRateValuationDateBusinessCenterGrp

ReturnRateValuationDateBusinessCenterGrp is a repeating subcomponent within the ReturnRateValuationDateGrp component. It is used to specify the valuation date business center adjustments for an equity return swap payment stream.

Name	Mult.	Type	Description
NoReturnRateValuationDateBusinessCenters	[1..1]	NumInGroup	
ReturnRateValuationDateBusinessCenter	[0..1]	String	Required if NoReturnRateValuationDateBusinessCenters(42770) > 0.

Used in groups: **ReturnRateDateGrp**

### 180.2.4662 ReturnRateValuationDateBusinessDayConvention

The return rate valuation dates business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: **ReturnRateDateGrp**

**180.2.4663 ReturnRateValuationDateGrp**

ReturnRateValuationDateGrp is a repeating subcomponent within the ReturnRateDateGrp component. It is used to specify the fixed valuation dates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoReturnRateValuationDates	[1..1]	NumInGroup	
ReturnRateValuationDate	[0..1]	LocalMktDate	Required if NoReturnRateValuationDates(42772) > 0.
ReturnRateValuationDateType	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in groups: [ReturnRateDateGrp](#)

**180.2.4664 ReturnRateValuationDateOffsetDayType**

Specifies the day type of the relative return rate valuation date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [ReturnRateDateGrp](#)

**180.2.4665 ReturnRateValuationDateOffsetPeriod**

Time unit multiplier for the relative return rate valuation date offset.

Type: **int**

Used in groups: **ReturnRateDateGrp**

#### **180.2.4666 ReturnRateValuationDateOffsetUnit**

Time unit associated with the relative return rate valuation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **ReturnRateDateGrp**

#### **180.2.4667 ReturnRateValuationDateRelativeTo**

Specifies the anchor date when the return rate valuation dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **ReturnRateDateGrp**

#### **180.2.4668 ReturnRateValuationDateType**

Specifies the type of return rate valuation date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted

Code	Name	Description
1	Adjusted	Adjusted

Used in groups: [ReturnRateValuationDateGrp](#)

#### **180.2.4669 ReturnRateValuationEndDateAdjusted**

The adjusted end date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in groups: [ReturnRateDateGrp](#)

#### **180.2.4670 ReturnRateValuationEndDateOffsetDayType**

Specifies the day type of the relative return rate valuation end date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [ReturnRateDateGrp](#)

#### **180.2.4671 ReturnRateValuationEndDateOffsetPeriod**

Time unit multiplier for the relative return rate valuation end date offset.

Type: [int](#)

Used in groups: [ReturnRateDateGrp](#)

**180.2.4672 ReturnRateValuationEndDateOffsetUnit**

Time unit associated with the relative return rate valuation end date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **ReturnRateDateGrp**

**180.2.4673 ReturnRateValuationEndDateRelativeTo**

Specifies the anchor date when the return rate valuation end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **ReturnRateDateGrp**

**180.2.4674 ReturnRateValuationEndDateUnadjusted**

The unadjusted end date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in groups: **ReturnRateDateGrp**

**180.2.4675 ReturnRateValuationFrequencyPeriod**

Time unit multiplier for the frequency at which return rate valuation dates occur.

Type: **int**

Used in groups: **ReturnRateDateGrp**



**180.2.4676 ReturnRateValuationFrequencyRollConvention**

The convention for determining the sequence of return rate valuation dates. It is used in conjunction with a specified frequency.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighDa28y	28th day of the month

Code	Name	Description
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in groups: [ReturnRateDateGrp](#)

### 180.2.4677 ReturnRateValuationFrequencyUnit

Time unit associated with the frequency at which return rate valuation dates occur.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day

Code	Name	Description
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in groups: [ReturnRateDateGrp](#)

#### **180.2.4678 ReturnRateValuationPriceOption**

Indicates whether an ISDA price option applies, and if applicable which type of price.

Type: [int](#)

Allowed values in ReturnRateValuationPriceOptionCodeSet:

Code	Name	Description
0	None	None (the default)
1	FuturesPrice	Futures price. The official settlement price as announced by the related futures exchange is applicable.
2	OptionsPrice	Options price. The official settlement price as announced by the related options exchange is applicable.

Used in groups: [ReturnRateGrp](#)

#### **180.2.4679 ReturnRateValuationStartDateAdjusted**

The adjusted start date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in groups: [ReturnRateDateGrp](#)

**180.2.4680 ReturnRateValuationStartDateOffsetDayType**

Specifies the day type of the relative return rate valuation start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **ReturnRateDateGrp**

**180.2.4681 ReturnRateValuationStartDateOffsetPeriod**

Time unit multiplier for the relative return rate valuation start date offset.

Type: **int**

Used in groups: **ReturnRateDateGrp**

**180.2.4682 ReturnRateValuationStartDateOffsetUnit**

Time unit associated with the relative return rate valuation start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **ReturnRateDateGrp**

**180.2.4683 ReturnRateValuationStartDateRelativeTo**

Specifies the anchor date when the return rate valuation start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **ReturnRateDateGrp**

**180.2.4684 ReturnRateValuationStartDateUnadjusted**

The unadjusted start date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in groups: **ReturnRateDateGrp**

**180.2.4685 ReturnRateValuationTime**

The time at which the calculation agent values the underlying asset.

Type: **LocalMktTime**

Used in groups: **ReturnRateGrp**

**180.2.4686 ReturnRateValuationTimeBusinessCenter**

The business center calendar used for adjustments associated with ReturnRateValuationTimeType(42756) or ReturnRateValuationTime(42757), e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **ReturnRateGrp**

**180.2.4687 ReturnRateValuationTimeType**

Specifies the timing at which the calculation agent values the underlying.

Type: **int**

Allowed values in ReturnRateQuoteTimeTypeCodeSet:

Code	Name	Description
0	Open	Open. The official opening time of the exchange on valuation date.
1	OfficialSettlPx	Official settlement price time. The time at which the official settlement price is determined.
2	Xetra	XETRA. The time at which the official settlement price (following the auction by the exchange) is determined by the exchange.
3	Close	Close. The official closing time of the exchange on valuation date.
4	DerivativesClose	Derivatives close. The official closing time for derivative trading of the exchange on valuation date.
5	High	High. The high price for the day.
6	Low	Low. The low price for the day.
7	AsSpecifiedInMasterConfirmation	As specified in the master confirmation

Used in groups: **ReturnRateGrp**

## 180.2.4688 ReturnTrigger

Indicates the type of return or payout trigger for the swap or forward.

Type: **int**

Allowed values in ReturnTriggerCodeSet:

Code	Name	Description
1	Dividend	Dividend
2	Variance	Variance
3	Volatility	Volatility
4	TotalReturn	Total return
5	ContractForDifference	Contract for difference
6	CreditDefault	Credit default
7	SpreadBet	Spread bet
8	Price	Price
9	ForwardPriceUnderlyingInstrument	Forward price of underlying instrument
99	Other	Other

Used in components: **Instrument**

**180.2.4689 ReversalIndicator**

Indicates a trade that reverses a previous trade.

Type: **Boolean**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**

**180.2.4690 RFQReqGrp**

Name	Mult.	Type	Description
<b>NoRelatedSym</b>	[1..1]	NumInGroup	Number of related symbols (instruments) in Request
<b>Instrument</b>	[1..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages"
<b>UndInstrmtGrp</b>	[0..*]	Group	
<b>InstrmtLegGrp</b>	[0..*]	Group	
<b>PrevClosePx</b>	[0..1]	Price	Useful for verifying security identification
<b>QuoteRequestType</b>	[0..1]	CodeSet	Indicates the type of Quote Request (e.g. Manual vs. Automatic) being generated.
<b>QuoteType</b>	[0..1]	CodeSet	Type of quote being requested from counterparty or market (e.g. Indicative, Firm, or Restricted Tradeable)
<b>TradingSessionID</b>	[0..1]	CodeSet	
<b>TradingSessionSubID</b>	[0..1]	CodeSet	

Used in messages: **RFQRequest**

**180.2.4691 RFQReqID**

RFQ Request ID - used to identify an RFQ Request.

Type: **String**

Used in messages: **QuoteRequest**, **QuoteRequestReject**, **RFQRequest**

**180.2.4692 RgstDistInstGrp**

Name	Mult.	Type	Description
NoDistribInsts	[1..1]	NumInGroup	Number of Distribution instructions in this message (number of repeating groups to follow)
DistribPaymentMethod	[0..1]	CodeSet	Must be first field in the repeating group if NoDistribInsts > 0.
DistribPercentage	[0..1]	Percentage	
CashDistribCurr	[0..1]	Currency	
CashDistribAgentName	[0..1]	String	
CashDistribAgentCode	[0..1]	String	
CashDistribAgentAcctNumber	[0..1]	String	
CashDistribPayRef	[0..1]	String	
CashDistribAgentAcctName	[0..1]	String	

Used in messages: [RegistrationInstructions](#)

**180.2.4693 RgstDtlsGrp**

Name	Mult.	Type	Description
NoRegistDtls	[1..1]	NumInGroup	Number of registration details in this message (number of repeating groups to follow)
RegistDtls	[0..1]	String	Must be first field in the repeating group
RegistEmail	[0..1]	String	
MailingDtls	[0..1]	String	
MailingInst	[0..1]	String	
NestedParties	[0..*]	Group	Insert here the set of "Nested Parties" (firm identification "nested" within additional repeating group) fields defined in "Common Components of Application Messages". Used for NestedPartyRole=InvestorID
OwnerType	[0..1]	CodeSet	
DateOfBirth	[0..1]	LocalMktDate	
InvestorCountryOfResidence	[0..1]	Country	

Used in messages: [RegistrationInstructions](#)



**180.2.4694 Rho**

The security's value rate of change in response to a 1% change in (risk-free) interest rate. Measures the security's sensitivity to interest rate change.

Type: **float**

Used in groups: **SecurityRiskMetricGrp**

**180.2.4695 RiskFreeRate**

Interest rate. Usually some form of short term rate.

Type: **float**

Used in groups: **ClearingPriceParametersGrp**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **SecurityRiskMetricsReport**, **TradeCaptureReport**

**180.2.4696 RiskInstrumentMultiplier**

Multiplier applied to the transaction amount for comparison with risk limits. Default if not specified is 1.0.

Type: **float**

Used in groups: **RiskInstrumentScopeGrp**

**180.2.4697 RiskInstrumentScopeGrp**

Repeating group of InstrumentScope Components. Used to specify the instruments to which a request applies.

Name	Mult.	Type	Description
<b>NoRiskInstrumentScopes</b>	[1..1]	NumInGroup	
<b>InstrumentScopeOperator</b>	[0..1]	CodeSet	Required when NoRiskInstrumentScopes > 0.
<b>InstrumentScope</b>	[0..1]	Component	
<b>RiskInstrumentMultiplier</b>	[0..1]	float	

Used in groups: **RiskLimitsGrp**

Used in messages: **PartyRiskLimitsRequest**

**180.2.4698 RiskLimitAction**

Identifies the action to take or risk model to assume should risk limit be exceeded or breached for the specified party.

Type: **int**

Allowed values in RiskLimitActionCodeSet:

Code	Name	Description
0	QueueInbound	Queue inbound
1	QueueOutbound	Queue outbound
2	Reject	Reject
3	Disconnect	Disconnect
4	Warning	Warning
5	PingCreditCheckWithRevalidation	Ping credit check model with revalidation. Each subsequent order, quote request or quote submission by the Credit. User must obtain pre-approval. Any open orders, quote requests or quotes are to be cancelled.
6	PingCreditCheckNoRevalidation	Ping credit check model without revalidation. Each subsequent order, quote request or quote submission by the Credit. User must obtain pre-approval. Any open orders, quote requests or quotes will remain active.
7	PushCreditCheckWithRevalidation	Push credit check model with revalidation. Each subsequent order, quote request or quote submission by the Credit. User must be checked against the limit amounts pushed to the trading platform. Any open orders, quote requests or quotes are. to be cancelled.
8	PushCreditCheckNoRevalidation	Push credit check model without revalidation. Each subsequent order, quote request or quote submission by the Credit. User must be checked against the limit amounts pushed to the trading platform. Any open orders, quote requests or quotes will. remain active.
9	Suspend	Suspend. Suspend the Credit User from trading once limit(s) is breached. This is. considered a "soft" stop.
10	HaltTrading	Halt trading. Halt or stop the Credit User from trading once limit(s) is breached. This is considered a "hard" stop and may require more involved actions to reinstate the Credit User's ability. to trade.

Used in groups: **RiskLimitTypesGrp**

#### **180.2.4699 RiskLimitAmount**

Specifies the risk limit amount.

Type: **Amt**

Used in groups: **RiskLimitTypesGrp**

#### **180.2.4700 RiskLimitApprovedAmount**

The credit/risk limit amount approved.

Type: **Amt**

Used in messages: **PartyRiskLimitCheckRequestAck**

#### **180.2.4701 RiskLimitCheckAmount**

Specifies the amount being requested for approval.

Type: **Amt**

Used in messages: **PartyRiskLimitCheckRequest**, **PartyRiskLimitCheckRequestAck**

#### **180.2.4702 RiskLimitCheckID**

The unique and static identifier, at the business entity level, of a risk limit check request.

Type: **String**

Used in messages: **PartyRiskLimitCheckRequest**, **PartyRiskLimitCheckRequestAck**

#### **180.2.4703 RiskLimitCheckModelType**

Specifies the type of credit limit check model workflow to apply for the specified party

Type: **int**

Allowed values in RiskLimitCheckModelTypeCodeSet:

Code	Name	Description
0	None	None (default if not specified). No specified limit check model is defined. Limit checks for the party will be based on parameters defined.
1	PlusOneModel	PlusOne model. A pre-trade credit limit check model which allows trades to occur until it is determined by the clearinghouse or other designated limit checker that the party's limit(s) was breached by the most recent trade executed.
2	PingModel	Ping model. A pre-trade credit limit check model which requires the execution venue to obtain limit approval from the Credit Provider for every transaction about to be conducted by the Credit User.
3	PushModel	Push model. A pre-trade credit limit check model in which the Credit Provider "pushes" to the execution venue the credit limit information allocated to each of the Credit Provider's counterparty or customer.

Used in groups: [PartyRiskLimitsAckGrp](#), [PartyRiskLimitsGrp](#), [PartyRiskLimitsUpdateGrp](#)

#### **180.2.4704 RiskLimitCheckRequestID**

The unique identifier of the PartyRiskLimitCheckRequest(35=DF) message.

Type: [String](#)

Used in messages: [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#)

#### **180.2.4705 RiskLimitCheckRequestRefID**

Specifies the message reference identifier of the risk limit check request message.

Type: [int](#)

Used in messages: [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#)

#### **180.2.4706 RiskLimitCheckRequestResult**

Result of the credit limit check request.

Type: [int](#)

Allowed values in RiskLimitCheckRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidParty	Invalid party
2	ReqExceedsCreditLimit	Requested amount exceeds credit limit
3	ReqExceedsClipSizeLimit	Requested amount exceeds clip size limit
4	ReqExceedsMaxNotional	Request exceeds maximum notional order amount
99	Other	Other

Used in messages: [PartyRiskLimitCheckRequestAck](#)

### **180.2.4707 RiskLimitCheckRequestStatus**

Indicates the status of the risk limit check request.

Type: [int](#)

Allowed values in RiskLimitCheckRequestStatusCodeSet:

Code	Name	Description
0	Approved	Approved. Request has been accepted and processed. The credit amount requested has been reserved for the transaction.
1	PartiallyApproved	Partially approved. Only a partial amount of the credit amount requested has been approved and has been reserved for the transaction.
2	Rejected	Rejected
3	ApprovalPending	Approval pending
4	Cancelled	Cancelled

Used in messages: [PartyRiskLimitCheckRequestAck](#)

### **180.2.4708 RiskLimitCheckRequestType**

Specifies the type of limit amount check being requested.

Type: [int](#)

Allowed values in RiskLimitCheckRequestTypeCodeSet:

Code	Name	Description
0	AllOrNone	All or none (default if not specified). The limit check request is for the full amount requested or none at all. Request can only be responded to with a full approval of the amount requested or a rejection of the request.
1	Partial	Partial. The requester will accept a partial approval of the requested credit limit amount.

Used in messages: **PartyRiskLimitCheckRequest**

### 180.2.4709 RiskLimitCheckStatus

Indicates the status of the risk limit check performed on a trade.

Type: **int**

Allowed values in RiskLimitCheckStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted. For use when none of the more specific status enumerations apply.
1	Rejected	Rejected. For use when none of the more specific status enumerations apply.
2	ClaimRequired	Claim required. Indicates that the clearing firm is required to accept or decline the trade.
3	PreDefinedLimitCheckSucceeded	Pre-defined limit check succeeded. Indicates a check enforced automatically by the clearing house.
4	PreDefinedLimitCheckFailed	Pre-defined limit check failed. Indicates a check enforced automatically by the clearing house.
5	PreDefinedAutoAcceptRuleInvoked	Pre-defined auto-accept rule invoked. Indicates that the clearing firm is required to accept or decline the trade because no limit or rule applies.
6	PreDefinedAutoRejectRuleInvoked	Pre-defined auto-reject rule invoked. Indicates a check enforced automatically by the clearing house. Note that clearing house rules of engagement may still require a clearing firm accept or reject the trade.
7	AcceptedByClearingFirm	Accepted by clearing firm. Indicates that explicit action by the clearing firm, and not an automatic check by the clearing house, was the basis for accepting the trade.

Code	Name	Description
8	RejectedByClearingFirm	Rejected by clearing firm. Indicates that explicit action by the clearing firm, and not an automatic check by the clearing house, was the basis for rejecting the trade.
9	Pending	Pending. Indicates that one or more side level risk checks are in progress.
10	AcceptedByCreditHub	Accepted by credit hub. Indicates that a credit hub accepted the trade. An identifier assigned by the credit hub may appear in the appropriate RefRiskLimitCheckID(2334) field.
11	RejectedByCreditHub	Rejected by credit hub. Indicates that a credit hub rejected the trade.
12	PendingCreditHubCheck	Pending credit hub check. Indicates that a check is pending at a credit hub.
13	AcceptedByExecVenue	Accepted by execution venue. Indicates acceptance by an execution venue, such as a SEF.
14	RejectedByExecVenue	Rejected by execution venue. Indicates that the trade was rejected by an execution venue, such as a SEF.

Used in messages: [AllocationInstruction](#), [AllocationReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.4710 RiskLimitCheckTransType

Specifies the transaction type of the risk limit check request.

Type: [int](#)

Allowed values in RiskLimitCheckTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Cancel	Cancel
2	Replace	Replace

Used in messages: [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#)

### 180.2.4711 RiskLimitCheckType

Specifies the type of limit check message.

Type: **int**

Allowed values in RiskLimitCheckTypeCodeSet:

Code	Name	Description
0	Submit	Submit. Indicates a submission for a limit check. The RiskLimitCheckTransType(2320) indicates whether the submission is a new request, a cancel or replace/amend of a prior submission.
1	LimitConsumed	Limit consumed. Indicates that the limit reserved by a prior request has been used or consumed by a transaction that occurred.

Used in messages: **PartyRiskLimitCheckRequest**, **PartyRiskLimitCheckRequestAck**

#### **180.2.4712 RiskLimitCurrency**

Used to specify the currency of the risk limit amount.

Type: **Currency**

Used in groups: **RiskLimitTypesGrp**

#### **180.2.4713 RiskLimitCurrencyCodeSource**

Identifies class or source of the RiskLimitCurrency(1532) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)



Used in groups: [RiskLimitTypesGrp](#)

#### **180.2.4714 RiskLimitID**

Unique reference identifier for a specific risk limit defined for the specified party.

Type: [String](#)

Used in groups: [PartyRiskLimitsAckGrp](#), [PartyRiskLimitsGrp](#), [PartyRiskLimitsUpdateGrp](#)

Used in messages: [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#)

#### **180.2.4715 RiskLimitPlatform**

The area to which risk limit is applicable. This can be a trading platform or an offering.

Type: [String](#)

Used in groups: [RiskLimitTypesGrp](#)

Used in messages: [PartyRiskLimitsRequest](#)

#### **180.2.4716 RiskLimitReportID**

Identifier for the PartyRiskLimitsReport

Type: [String](#)

Used in messages: [PartyRiskLimitsReport](#), [PartyRiskLimitsReportAck](#), [PartyRiskLimitsUpdateReport](#)

#### **180.2.4717 RiskLimitReportRejectReason**

The reason for rejecting the PartyRiskLimitsReport(35=CM) or PartyRiskLimitsUpdateReport(35=CR).

Type: [int](#)

Allowed values in RiskLimitReportRejectReasonCodeSet:

Code	Name	Description
0	UnkRiskLmtRprtID	Unknown RiskLimitReportID(1667)
1	UnkPty	Unknown party
99	Other	Other

Used in messages: [PartyRiskLimitsReportAck](#)

**180.2.4718 RiskLimitReportStatus**

Status of risk limit report.

Type: **int**

Allowed values in RiskLimitReportStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	Rejected	Rejected

Used in messages: **PartyRiskLimitsReportAck**

**180.2.4719 RiskLimitRequestID**

Unique identifier for the PartyRiskLimitsRequest

Type: **String**

Used in messages: **PartyRiskLimitsDefinitionRequest**, **PartyRiskLimitsDefinitionRequestAck**, **PartyRiskLimitsReport**, **PartyRiskLimitsReportAck**, **PartyRiskLimitsRequest**, **PartyRiskLimitsUpdateReport**

**180.2.4720 RiskLimitRequestResult**

Result of risk limit definition request.

Type: **int**

Allowed values in RiskLimitRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidParty	Invalid party(-ies)
2	InvalidRelatedParty	Invalid related party(-ies)
3	InvalidRiskLimitType	Invalid risk limit type(s)
4	InvalidRiskLimitID	Invalid risk limit ID(s)
5	InvalidRiskLimitAmount	Invalid risk limit amount(s)

Code	Name	Description
6	InvalidRiskWarningLevelAction	Invalid risk/warning level action(s)
7	InvalidRiskInstrumentScope	Invalid risk instrument scope(s)
8	RiskLimitActionsNotSupported	Risk limit actions not supported
9	WarningLevelsNotSupported	Warning levels not supported
10	WarningLevelActionsNotSupported	Warning level actions not supported
11	RiskInstrumentScopeNotSupported	Risk instrument scope not supported
12	RiskLimitNotApprovedForParty	Risk limit not approved for party(-ies)
13	RiskLimitAlreadyDefinedForParty	Risk limit already defined for party(-ies)
14	InstrumentNotApprovedForParty	Instrument not approved for party(-ies)
98	NotAuthorized	Not authorized
99	Other	Other

Used in messages: [PartyRiskLimitsDefinitionRequestAck](#)

#### **180.2.4721 RiskLimitRequestStatus**

Status of risk limit definition request.

Type: [int](#)

Allowed values in PartyDetailRequestStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithChanges	Accepted with changes
2	Rejected	Rejected
3	AcceptancePending	Acceptance pending

Used in messages: [PartyRiskLimitsDefinitionRequestAck](#)

#### **180.2.4722 RiskLimitRequestType**

Type of risk limit information.

Type: [int](#)

Allowed values in RiskLimitRequestTypeCodeSet:

Code	Name	Description
1	Definitions	Definitions(Default)
2	Utilization	Utilization
3	DefinitionsAndUtilizations	Definitions and utilization

Used in messages: [PartyRiskLimitsReport](#), [PartyRiskLimitsRequest](#), [PartyRiskLimitsUpdateReport](#)

### 180.2.4723 RiskLimitResult

Result of risk limit definition for one party.

Type: [int](#)

Allowed values in RiskLimitRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidParty	Invalid party(-ies)
2	InvalidRelatedParty	Invalid related party(-ies)
3	InvalidRiskLimitType	Invalid risk limit type(s)
4	InvalidRiskLimitID	Invalid risk limit ID(s)
5	InvalidRiskLimitAmount	Invalid risk limit amount(s)
6	InvalidRiskWarningLevelAction	Invalid risk/warning level action(s)
7	InvalidRiskInstrumentScope	Invalid risk instrument scope(s)
8	RiskLimitActionsNotSupported	Risk limit actions not supported
9	WarningLevelsNotSupported	Warning levels not supported
10	WarningLevelActionsNotSupported	Warning level actions not supported
11	RiskInstrumentScopeNotSupported	Risk instrument scope not supported
12	RiskLimitNotApprovedForParty	Risk limit not approved for party(-ies)
13	RiskLimitAlreadyDefinedForParty	Risk limit already defined for party(-ies)
14	InstrumentNotApprovedForParty	Instrument not approved for party(-ies)
98	NotAuthorized	Not authorized
99	Other	Other

Used in groups: [PartyRiskLimitsAckGrp](#)

**180.2.4724 RiskLimitsGrp**

Repeating group of risk limits.

Name	Mult.	Type	Description
NoRiskLimits	[1..1]	NumInGroup	
RiskLimitTypesGrp	[0..*]	Group	Required if NoRiskLimits(1669) > 0.
RiskInstrumentScopeGrp	[0..*]	Group	

Used in groups: [PartyRiskLimitsAckGrp](#), [PartyRiskLimitsGrp](#), [PartyRiskLimitsUpdateGrp](#)

**180.2.4725 RiskLimitStatus**

Status of risk limit definition for one party.

Type: [int](#)

Allowed values in PartyDetailDefinitionStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	AcceptedWithChanges	Accepted with changes
2	Rejected	Rejected

Used in groups: [PartyRiskLimitsAckGrp](#)

**180.2.4726 RiskLimitType**

Used to specify the type of risk limit amount or position limit quantity or margin requirement amounts.

Type: [int](#)

Allowed values in RiskLimitTypeCodeSet:

Code	Name	Description
0	CreditLimit	Credit limit. The credit limit provided by one party to another for trading.
1	GrossLimit	Gross limit
2	NetLimit	Net limit
3	Exposure	Exposure
4	LongLimit	Long limit
5	ShortLimit	Short limit
6	CashMargin	Cash margin
7	AdditionalMargin	Additional margin
8	TotalMargin	Total margin
9	LimitConsumed	Limit consumed. The limit used in the recent transaction.
10	ClipSize	Clip size/notional limit per time period. The total notional amount limit allowed to be executed within a defined period of time or velocity. The defined period of time may be specified by the RiskLimitVelocityPeriod(2336) and RiskLimitVelocityUnit(2337).
11	MaxNotionalOrderSize	Maximum notional order size
12	DV01PV01Limit	DV01/PV01 limit. The maximum dollar value change resulting from a move of 1 basis point in the yield curve. This limits the interest rate risk exposure. Also known as "basis point value" or BPV.
13	CS01Limit	CS01 limit. Credit spread sensitivity. Represents the change in market value of a CDS for a one basis point change in the credit spread. This limits the credit risk exposure of a CDS. Also known as "risky-DV01".
14	VolumeLimitPerTimePeriod	Volume limit per time period. The total number of shares, bonds or contracts allowed to be executed within a defined period of time or velocity. The defined period of time may be specified by the RiskLimitVelocityPeriod(2336) and RiskLimitVelocityUnit(2337).
15	VolFilledPctOrdVolTmPeriod	Volume filled as percent of ordered volume per time period. The total number of shares, bonds or contracts executed as a percentage of the total ordered shares, contracts or notional amount for a specified security, instrument, symbol, or underlying, over a defined period of time or velocity. The defined period of time may be specified by the RiskLimitVelocityPeriod(2336) and RiskLimitVelocityUnit(2337).

Code	Name	Description
16	NotlFilledPctNotlTmPeriod	Notional filled as percent of notional per time period. The total notional amount executed as a percentage of the total ordered shares, contracts or notional amount for a specified security, instrument, symbol, or underlying, over a defined period of time or velocity. The defined period of time may be specified by the RiskLimitVelocityPeriod(2336) and RiskLimitVelocityUnit(2337).
17	TransactionExecutionLimitPer-TimePeriod	Transaction/execution limit per time period. The total number of transactions or execution fills allowed within a defined period of time or velocity. The defined period of time may be specified by the RiskLimitVelocityPeriod(2336) and RiskLimitVelocityUnit(2337).

Used in groups: [RequestedRiskLimitTypesGrp](#), [RiskLimitTypesGrp](#)

### 180.2.4727 RiskLimitTypesGrp

Repeating group of risk limit types and values.

Name	Mult.	Type	Description
<a href="#">NoRiskLimitTypes</a>	[1..1]	NumInGroup	
<a href="#">RiskLimitType</a>	[0..1]	CodeSet	Required if NoRiskLimitTypes(1529) > 0.
<a href="#">RiskLimitAmount</a>	[0..1]	Amt	
<a href="#">RiskLimitAction</a>	[0..1]	CodeSet	
<a href="#">RiskLimitUtilizationAmount</a>	[0..1]	Amt	Not applicable in a request.
<a href="#">RiskLimitUtilizationPercent</a>	[0..1]	Percentage	Not applicable in a request.
<a href="#">RiskLimitCurrency</a>	[0..1]	Currency	
<a href="#">RiskLimitCurrencyCodeSource</a>	[0..1]	CodeSet	
<a href="#">RiskLimitPlatform</a>	[0..1]	String	
<a href="#">RiskLimitVelocityPeriod</a>	[0..1]	int	Conditionally required when RiskLimitType(1530) = 10 (Clip size)
<a href="#">RiskLimitVelocityUnit</a>	[0..1]	CodeSet	
<a href="#">RiskWarningLevelGrp</a>	[0..*]	Group	

Used in groups: [RiskLimitsGrp](#)

**180.2.4728 RiskLimitUtilizationAmount**

Absolute amount of utilization of a party's set risk limit.

Type: **Amt**

Used in groups: **RiskLimitTypesGrp**

**180.2.4729 RiskLimitUtilizationPercent**

Percentage of utilization of a party's set risk limit.

Type: **Percentage**

Used in groups: **RiskLimitTypesGrp**

**180.2.4730 RiskLimitVelocityPeriod**

The time interval for which the clip size limit applies. The velocity time unit is expressed in RiskLimitVelocityUnit(2337).

Type: **int**

Used in groups: **RiskLimitTypesGrp**

**180.2.4731 RiskLimitVelocityUnit**

Unit of time in which RiskLimitVelocityPeriod(2336) is expressed.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter



Code	Name	Description
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in groups: [RiskLimitTypesGrp](#)

#### **180.2.4732 RiskMetricsSecurityGroup**

Describes a group of related instruments for which risk metrics are provided.

Type: [String](#)

Used in messages: [SecurityRiskMetricsReport](#)

#### **180.2.4733 RiskMetricsSecuritySubGroup**

Describes a sub-group of a group identified by RiskMetricsSecurityGroup(2989).

Type: [String](#)

Used in messages: [SecurityRiskMetricsReport](#)

#### **180.2.4734 RiskWarningLevelAction**

Action to take should warning level be exceeded.

Type: [int](#)

Allowed values in RiskLimitActionCodeSet:

Code	Name	Description
0	QueueInbound	Queue inbound
1	QueueOutbound	Queue outbound
2	Reject	Reject
3	Disconnect	Disconnect
4	Warning	Warning

Code	Name	Description
5	PingCreditCheckWithRevalidation	Ping credit check model with revalidation. Each subsequent order, quote request or quote submission by the Credit. User must obtain pre-approval. Any open orders, quote requests or quotes are to be cancelled.
6	PingCreditCheckNoRevalidation	Ping credit check model without revalidation. Each subsequent order, quote request or quote submission by the Credit. User must obtain pre-approval. Any open orders, quote requests or quotes will remain active.
7	PushCreditCheckWithRevalidation	Push credit check model with revalidation. Each subsequent order, quote request or quote submission by the Credit. User must be checked against the limit amounts pushed to the trading platform. Any open orders, quote requests or quotes are. to be cancelled.
8	PushCreditCheckNoRevalidation	Push credit check model without revalidation. Each subsequent order, quote request or quote submission by the Credit. User must be checked against the limit amounts pushed to the trading platform. Any open orders, quote requests or quotes will. remain active.
9	Suspend	Suspend. Suspend the Credit User from trading once limit(s) is breached. This is. considered a "soft" stop.
10	HaltTrading	Halt trading. Halt or stop the Credit User from trading once limit(s) is breached. This is considered a "hard" stop and may require more involved actions to reinstate the Credit User's ability. to trade.

Used in groups: **RiskWarningLevelGrp**

#### **180.2.4735 RiskWarningLevelAmount**

Amount at which a warning is issued.

Type: **int**

Used in groups: **RiskWarningLevelGrp**

#### **180.2.4736 RiskWarningLevelGrp**

Risk warning levels.

Name	Mult.	Type	Description
NoRiskWarningLevels	[1..1]	NumInGroup	
RiskWarningLevelAction	[0..1]	CodeSet	Required if NoRiskWarningLevels(1559) > 0.
RiskWarningLevelPercent	[0..1]	Percentage	Conditionally required when RiskWarningLevelAmount(1768) is not provided.
RiskWarningLevelAmount	[0..1]	int	Conditionally required when RiskWarningLevelPercent(1560) is not provided.
RiskWarningLevelName	[0..1]	String	

Used in groups: [RiskLimitTypesGrp](#)

#### **180.2.4737 RiskWarningLevelName**

Name or error message associated with the risk warning level.

Type: [String](#)

Used in groups: [RiskWarningLevelGrp](#)

#### **180.2.4738 RiskWarningLevelPercent**

Percent of risk limit at which a warning is issued.

Type: [Percentage](#)

Used in groups: [RiskWarningLevelGrp](#)

#### **180.2.4739 RndPx**

Specifies average price rounded to quoted precision.

Type: [Price](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.4740 RootParties**

The RootParties component block is a version of the Parties component block used to provide root information regarding the owning and entering parties of a transaction.

Name	Mult.	Type	Description
NoRootPartyIDs	[1..1]	NumInGroup	Repeating group below should contain unique combinations of RootPartyID, RootPartyIDSource, and RootPartyRole
RootPartyID	[0..1]	String	Required if NoRootPartyIDs(1116) > 0. Identification of the party.
RootPartyIDSource	[0..1]	CodeSet	Required if NoRootPartyIDs(1116) > 0. Used to identify class source of the RootPartyID(1117) value (e.g. BIC).
RootPartyRole	[0..1]	CodeSet	Required if NoRootPartyIDs(1116) > 0. Identifies the role of the RootPartyID(1117) (e.g. Executing Broker).
RootPartyRoleQualifier	[0..1]	CodeSet	
RootSubParties	[0..*]	Group	Repeating group of RootParty sub-identifiers.

Used in messages: [CrossOrderCancelReplaceRequest](#), [CrossOrderCancelRequest](#), [NewOrderCross](#), [NewOrderList](#), [QuoteRequest](#), [QuoteRequestReject](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### 180.2.4741 RootPartyID

PartyID value within a root parties component. Same values as PartyID (448)

Type: [String](#)

Used in groups: [RootParties](#)

#### 180.2.4742 RootPartyIDSource

PartyIDSource value within a root parties component. Same values as PartyIDSource (447)

Type: [char](#)

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.

Code	Name	Description
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.

Code	Name	Description
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **RootParties**

### 180.2.4743 RootPartyRole

PartyRole value within a root parties component. Same values as PartyRole (452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID

Code	Name	Description
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader

Code	Name	Description
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm



Code	Name	Description
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm

Code	Name	Description
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.

Code	Name	Description
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **RootParties**

#### 180.2.4744 RootPartyRoleQualifier

Used to further qualify the value of RootPartyRole(1119).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.

Code	Name	Description
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **RootParties**

#### **180.2.4745 RootPartySubID**

PartySubID value within a root parties component. Same values as PartySubID (523)

Type: **String**

Used in groups: **RootSubParties**

#### **180.2.4746 RootPartySubIDType**

Type of RootPartySubID (1121) value. Same values as PartySubIDType (803)

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier

Code	Name	Description
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account

Code	Name	Description
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.



Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **RootSubParties**

**180.2.4747 RootSubParties**

Name	Mult.	Type	Description
NoRootPartySubIDs	[1..1]	NumInGroup	Repeating group of RootParty sub-identifiers.
RootPartySubID	[0..1]	String	Sub-identifier (e.g. Clearing Acct for PartyID=Clearing Firm) if applicable. Required if. NoRootPartySubIDs > 0.
RootPartySubIDType	[0..1]	CodeSet	Type of Sub-identifier. Required if NoRootPartySubIDs > 0.

Used in groups: **RootParties**

**180.2.4748 RoundingDirection**

Specifies which direction to round For CIV - indicates whether or not the quantity of shares/units is to be rounded and in which direction where CashOrdQty (152) or (for CIV only) OrderPercent (516) are specified on an order.

The default is for rounding to be at the discretion of the executing broker or fund manager.

e.g. for an order specifying CashOrdQty or OrderPercent if the calculated number of shares/units was 325.76 and RoundingModulus (469) was 0 - "round down" would give 320 units, 1 - "round up" would give 330 units and "round to nearest" would give 320 units.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **OrderQtyData**

**180.2.4749 RoundingModulus**

For CIV - a float value indicating the value to which rounding is required.

i.e. 0 means round to a multiple of 0 units/shares; 0.5 means round to a multiple of 0.5 units/shares.

The default, if RoundingDirection (468) is specified without RoundingModulus, is to round to a whole unit/share.

Type: **float**

Used in components: **OrderQtyData**

### **180.2.4750 RoundLot**

The trading lot size of a security

Type: **Qty**

Used in components: **BaseTradingRules**

### **180.2.4751 RoutingArrangementIndicator**

Indicates whether a routing arrangement is in place, e.g. between two brokers. May be used together with OrderOrigination(1724) to further describe the origin of an order.

Type: **int**

Allowed values in RoutingArrangementIndicatorCodeSet:

Code	Name	Description
0	NoRoutingArrangementInPlace	No routing arrangement in place
1	RoutingArrangementInPlace	Routing arrangement in place

Used in groups: **SideCrossOrdModGrp**

Used in messages: **ExecutionReport**, **NewOrderSingle**, **OrderCancelReplaceRequest**

### **180.2.4752 RoutingGrp**

The RoutingGrp is used to allow the application message sender to instruct the intermediary distributing the message who to further send the application message to. The original sender may also instruct who is not allowed to receive the message. When provided, the routing instructions provided in this component are effective on a message by message basis.

Name	Mult.	Type	Description
NoRoutingIDs	[1..1]	NumInGroup	
RoutingType	[0..1]	CodeSet	Indicates type of RoutingID. Required if NoRoutingIDs is > 0.
RoutingID	[0..1]	String	Identifies routing destination. Required if NoRoutingIDs is > 0.

Used in messages: [Advertisement](#), [Email](#), [IOI](#), [MarketDataIncrementalRefresh](#), [MarketDataSnapshot-FullRefresh](#), [News](#), [Quote](#)

### 180.2.4753 RoutingID

Assigned value used to identify a specific routing destination.

Type: [String](#)

Used in groups: [RoutingGrp](#)

### 180.2.4754 RoutingType

Indicates the type of RoutingID (217) specified.

Type: [int](#)

Allowed values in RoutingTypeCodeSet:

Code	Name	Description
1	TargetFirm	Target Firm
2	TargetList	Target List
3	BlockFirm	Block Firm
4	BlockList	Block List
5	TargetPerson	Target Person
6	BlockPerson	Block Person

Used in groups: [RoutingGrp](#)

**180.2.4755 RptSeq**

Sequence number of message within report series. Used to carry reporting sequence number of the fill as represented on the Trade Report Side.

Type: **int**

Used in groups: **MDFullGrp**, **MDIncGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **ListStatus**

**180.2.4756 RptSys**

Indicates the system or medium on which the report has been published

Type: **String**

Used in messages: **TradeCaptureReportAck**

**180.2.4757 Scope**

Specifies the market scope of the market data.

Type: **MultipleCharValue**

Allowed values in ScopeCodeSet:

Code	Name	Description
1	LocalMarket	Local Market (Exchange, ECN, ATS)
2	National	National
3	Global	Global

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **MarketDataRequest**

**180.2.4758 SecAltIDGrp**

Name	Mult.	Type	Description
<b>NoSecurityAltID</b>	[1..1]	NumInGroup	

Name	Mult.	Type	Description
SecurityAltID	[0..1]	String	
SecurityAltIDSource	[0..1]	CodeSet	
SymbolPositionNumber	[0..1]	int	

Used in components: **Instrument**

### 180.2.4759 SecListGrp

Name	Mult.	Type	Description
NoRelatedSym	[1..1]	NumInGroup	Specifies the number of repeating symbols (instruments) specified
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". of the requested Security
InstrumentExtension	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "Common Components of Application Messages"
SecurityClassificationGrp	[0..*]	Group	Used to specify forms of product classifications
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "Common Components of Application Messages"
SecurityTradingRules	[0..1]	Component	Used to provide listing rules
StrikeRules	[0..*]	Group	Used to provide listing rules
UndInstrmtGrp	[0..*]	Group	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
Stipulations	[0..*]	Group	Insert here the set of "Stipulations" fields defined in "Common Components of Application Messages"
InstrmtLegSecListGrp	[0..*]	Group	
RelatedInstrumentGrp	[0..*]	Group	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of "SpreadOrBenchmarkCurveData" fields defined in "Common Components of Application Messages"
YieldData	[0..1]	Component	Insert here the set of "YieldData" fields defined in "Common Components of Application Messages"



Name	Mult.	Type	Description
PriceMovementGrp	[0..*]	Group	
RelSymTransactTime	[0..1]	UTCTimestamp	
NumOfSimpleInstruments	[0..1]	int	Number of simple instruments.
Text	[0..1]	String	Comment, instructions, or other identifying information.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: [SecurityList](#)

#### 180.2.4760 SecLstUpdRelSymGrp

Name	Mult.	Type	Description
NoRelatedSym	[1..1]	NumInGroup	Specifies the number of repeating symbols (instruments) specified
ListUpdateAction	[0..1]	CodeSet	
Instrument	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "common components of application messages" of the requested Security
InstrumentExtension	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "COMMON COMPONENTS OF APPLICATION MESSAGES"
FinancingDetails	[0..1]	Component	Insert here the set of "FinancingDetails" fields defined in "COMMON COMPONENTS OF APPLICATION MESSAGES"
SecurityTradingRules	[0..1]	Component	
StrikeRules	[0..*]	Group	
UndInstrmtGrp	[0..*]	Group	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
Stipulations	[0..*]	Group	
SecLstUpdRelSymsLegGrp	[0..*]	Group	

Name	Mult.	Type	Description
RelatedInstrumentGrp	[0..*]	Group	
SpreadOrBenchmarkCurveData	[0..1]	Component	Insert here the set of " SpreadOrBenchmarkCurveData " fields defined in " COMMON COMPONENTS OF APPLICATION MESSAGES "
YieldData	[0..1]	Component	Insert here the set of " YieldData " fields defined in " COMMON COMPONENTS OF APPLICATION MESSAGES "
RelSymTransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	Comment, instructions, or other identifying information.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: [SecurityListUpdateReport](#)

#### 180.2.4761 SecLstUpdRelSymsLegGrp

Name	Mult.	Type	Description
NoLegs	[1..1]	NumInGroup	Number of legs that make up the Security
InstrumentLeg	[0..1]	Component	Insert here the set of "Instrument Legs" (leg symbology) fields defined in "common components of application messages" Required if NoLegs > 0
LegSwapType	[0..1]	CodeSet	
LegSettlType	[0..1]	CodeSet	
LegStipulations	[0..*]	Group	Insert here the set of "LegStipulations" (leg symbology) fields defined in "common components of application messages" Required if NoLegs > 0
LegBenchmarkCurveData	[0..1]	Component	Insert here the set of "LegBenchmarkCurveData" (leg symbology) fields defined in "common components of application messages" Required if NoLegs > 0

Used in groups: [SecLstUpdRelSymGrp](#)

### 180.2.4762 SecMassStatGrp

Name	Mult.	Type	Description
<a href="#">NoRelatedSym</a>	[1..1]	NumInGroup	Number of exceptions with a trading status different from SecurityMassTradingStatus (1679).
<a href="#">Instrument</a>	[0..1]	Component	Insert here the set of "Instrument" (symbology) fields defined in "Common Components of Application Messages". Conditionally required if NoRelatedSym > 0.
<a href="#">InstrumentExtension</a>	[0..1]	Component	Insert here the set of "InstrumentExtension" fields defined in "Common Components of Application Messages".
<a href="#">FinancingDetails</a>	[0..1]	Component	
<a href="#">UndInstrmtGrp</a>	[0..*]	Group	
<a href="#">InstrmtLegGrp</a>	[0..*]	Group	
<a href="#">RelatedInstrumentGrp</a>	[0..*]	Group	
<a href="#">SecurityTradingStatus</a>	[0..1]	CodeSet	Conditionally required if NoRelatedSym > 0.
<a href="#">SecurityTradingEvent</a>	[0..1]	CodeSet	
<a href="#">HaltReason</a>	[0..1]	CodeSet	
<a href="#">FinancialStatus</a>	[0..1]	CodeSet	
<a href="#">CorporateAction</a>	[0..1]	CodeSet	
<a href="#">Text</a>	[0..1]	String	Comment, instructions, or other identifying information.
<a href="#">EncodedTextLen</a>	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
<a href="#">EncodedText</a>	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: [SecurityMassStatus](#)

### 180.2.4763 SecondaryAllocID

Secondary allocation identifier. Unlike the AllocID (70), this can be shared across a number of allocation instruction or allocation report messages, thereby making it possible to pass an identifier for an original

allocation message on multiple messages (e.g. from one party to a second to a third, across cancel and replace messages etc.).

Type: **String**

Used in components: **SettlTradeDetails**

Used in messages: **AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationReport, AllocationReportAck, Confirmation, ConfirmationRequest**

### **180.2.4764 SecondaryAssetClass**

The broad asset category for assessing risk exposure for a multi-asset trade.

Type: **int**

Allowed values in AssetClassCodeSet:

Code	Name	Description
1	InterestRate	Interest rate
2	Currency	Currency
3	Credit	Credit
4	Equity	Equity
5	Commodity	Commodity
6	Other	Other
7	Cash	Cash
8	Debt	Debt
9	Fund	Fund. Such as mutual fund, collective investment vehicle, investment program, specialized account program.
10	LoanFacility	Loan facility
11	Index	Index. A main index identified as a security type, for example under EU SFTR reporting.

Used in groups: **SecondaryAssetGrp**

### **180.2.4765 SecondaryAssetGrp**

SecondaryAssetGrp is a repeating subcomponent of the Instrument component used to specify secondary assets of a multi-asset swap.

Name	Mult.	Type	Description
NoSecondaryAssetClasses	[1..1]	NumInGroup	
SecondaryAssetClass	[0..1]	CodeSet	Required if NoSecondaryAssetClasses(1976) > 0.
SecondaryAssetSubClass	[0..1]	CodeSet	Required if SecondaryAssetType(1979) is specified.
SecondaryAssetType	[0..1]	String	Required if SecondaryAssetSubType(2741) is specified.
SecondaryAssetSubType	[0..1]	String	

Used in components: **Instrument**

### 180.2.4766 SecondaryAssetSubClass

An indication of the general description of the asset class.

Type: **int**

Allowed values in AssetSubClassCodeSet:

Code	Name	Description
1	SingleCurrency	Single currency
2	CrossCurrency	Cross currency
3	Basket	Basket [for multi-currency]
4	SingleName	Single name
5	CreditIndex	Credit index
6	IndexTranche	Index tranche
7	CreditBasket	Credit basket
8	Exotic	Exotic
9	Common	Common
10	Preferred	Preferred
11	EquityIndex	Equity index
12	EquityBasket	Equity basket
13	Metals	Metals
14	Bullion	Bullion
15	Energy	Energy
16	CommodityIndex	Commodity index

Code	Name	Description
17	Agricultural	Agricultural
18	Environmental	Environmental
19	Freight	Freight
20	Government	Government
21	Agency	Agency
22	Corporate	Corporate
23	Financing	Financing
24	MoneyMarket	Money market
25	Mortgage	Mortgage
26	Municipal	Municipal
27	MutualFund	Mutual fund
28	CollectiveInvestmentVehicle	Collective investment vehicle
29	InvestmentProgram	Investment program. A generalized fund for major investors.
30	SpecializedAccountProgram	Specialized account program. A specialized fund setup for a particular account or group of accounts.
31	TermLoan	Term loan
32	BridgeLoan	Bridge loan
33	LetterOfCredit	Letter of credit
34	DividendIndex	Dividend index
35	StockDividend	Stock dividend
36	ExchangeTradedFund	Exchange traded fund
37	VolatilityIndex	Volatility index
38	FXCrossRates	FX cross rates
39	FXEmergingMarkets	FX emerging markets
40	FXMajors	FX Majors
41	Fertilizer	Fertilizer
42	IndustrialProduct	Industrial product
43	Inflation	Inflation
44	Paper	Paper
45	Polypropylene	Polypropylene
46	OfficialEconomicStatistics	Official economic statistics

Code	Name	Description
47	OtherC10	Other C10. Defined under MiFID II (Directive 2014/65/EU) Section C(10) of Annex I and paraphrased in ESMA RTS 2 Annex III Section 10, "Other C10" is a financial instrument "which is not a 'Freight derivative', any of the following interest rate derivatives sub-asset classes: 'Inflation multi-currency swap or cross-currency swap', a 'Future/forward on inflation multi-currency swaps or cross-currency swaps', an 'Inflation single currency swap', a 'Future/forward on inflation single currency swap' and any of the following equity derivatives sub-asset classes: a 'Volatility index option', a 'Volatility index future/forward', a swap with parameter return variance, a swap with parameter return volatility, a portfolio swap with parameter return variance, a portfolio swap with parameter return volatility".
48	Other	Other. May be used with any AssetClass(1938) values.

Used in groups: **SecondaryAssetGrp**

#### 180.2.4767 SecondaryAssetSubType

Used to provide a more specific description of the asset specified in SecondaryAssetType(1979).

See <https://www.fixtrading.org/codelists/AssetSubType> for code list of applicable values.

Type: **String**

Used in groups: **SecondaryAssetGrp**

#### 180.2.4768 SecondaryAssetType

Used to provide more specific description of the asset specified in SecondaryAssetSubClass(1978).

See <https://www.fixtrading.org/codelists/AssetType> for code list of applicable values. ISO 4721 Currency Code values are to be used when specific currency as an asset type is to be expressed.

Other values may be used by mutual agreement of the counterparties.

Type: **String**

Used in groups: **SecondaryAssetGrp**

**180.2.4769 SecondaryClOrdID**

Assigned by the party which originates the order. Can be used to provide the ClOrdID (11) used by an exchange or executing system.

Type: **String**

Used in components: **TradeReportOrderDetail**

Used in groups: **InstrmtStrkPxGrp, ListOrdGrp, OrdAllocGrp, OrdListStatGrp, SideCrossOrdCxlGrp, SideCrossOrdModGrp**

Used in messages: **CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralRequest, CollateralResponse, ExecutionReport, MultilegOrderCancelReplace, NewOrder-Multileg, NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderStatusRequest**

**180.2.4770 SecondaryDisplayQty**

Used for reserve orders when DisplayQty applies to the primary execution market (e.g. an ECN) and another quantity is to be shown at other markets (e.g. the exchange). On orders specifies the qty to be displayed, on execution reports the currently displayed quantity.

Type: **Qty**

Used in components: **DisplayInstruction**

**180.2.4771 SecondaryExecID**

Assigned by the party which accepts the order. Can be used to provide the ExecID (17) used by an exchange or executing system.

Type: **String**

Used in groups: **ExecAllocGrp**

Used in messages: **ExecutionReport, TradeCaptureReport, TradeCaptureReportAck, TradeCaptureReportRequest**

**180.2.4772 SecondaryFirmTradeID**

Used to carry an internal firm assigned ID which may or may not be reported to the exchange or central counterparty



Type: **String**

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**, **TradeCaptureReportRequestAck**

#### **180.2.4773 SecondaryHighLimitPrice**

Refer to definition of HighLimitPrice(1149)

Type: **Price**

Used in components: **SecondaryPriceLimits**

#### **180.2.4774 SecondaryIndividualAllocID**

Will allow the intermediary to specify an allocation ID generated by their system.

Type: **String**

Used in groups: **AllocAckGrp**, **AllocGrp**, **TrdAllocGrp**

#### **180.2.4775 SecondaryLockedQty**

Locked order quantity in addition to LockedQty (1808), e.g. to distinguish total locked quantity from currently locked quantity.

Type: **Qty**

Used in messages: **ExecutionReport**

#### **180.2.4776 SecondaryLowLimitPrice**

Refer to definition of LowLimitPrice(1148)

Type: **Price**

Used in components: **SecondaryPriceLimits**

#### **180.2.4777 SecondaryOrderID**

Assigned by the party which accepts the order. Can be used to provide the OrderID (37) used by an exchange or executing system.

Type: **String**

Used in components: **TradeReportOrderDetail**

Used in groups: **MDFullGrp**, **MDIncGrp**, **OrdAllocGrp**

Used in messages: **CollateralAssignment**, **CollateralInquiry**, **CollateralInquiryAck**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**, **DontKnowTrade**, **ExecutionAck**, **ExecutionReport**, **OrderCancelReject**, **OrderMassCancelReport**

### **180.2.4778 SecondaryPriceLimits**

<b>Name</b>	<b>Mult.</b>	<b>Type</b>	<b>Description</b>
<b>SecondaryPriceLimitType</b>	[0..1]	CodeSet	
<b>SecondaryLowLimitPrice</b>	[0..1]	Price	
<b>SecondaryHighLimitPrice</b>	[0..1]	Price	
<b>SecondaryTradingReferencePrice</b>	[0..1]	Price	

Used in groups: **RelSymDerivSecGrp**, **RelSymDerivSecUpdGrp**

### **180.2.4779 SecondaryPriceLimitType**

Describes the how the price limits are expressed

Type: **int**

Allowed values in PriceLimitTypeCodeSet:

<b>Code</b>	<b>Name</b>	<b>Description</b>
0	Price	Price (default)
1	Ticks	Ticks
2	Percentage	Percentage

Used in components: **SecondaryPriceLimits**

**180.2.4780 SecondaryQuoteID**

Assigned by the party which accepts the quote. Can be used to provide the quote identifier assigned by an exchange, marketplace or executing system.

Type: **String**

Used in groups: **QuotReqGrp**

Used in messages: **Quote**, **QuoteAck**, **QuoteCancel**, **QuoteStatusReport**

**180.2.4781 SecondaryServiceLocationID**

Secondary or alternate service location identifier.

Type: **String**

Used in groups: **MarketDataFeedTypes**

**180.2.4782 SecondaryTradeID**

Used to carry an internal trade entity ID which may or may not be reported to the firm

Type: **String**

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**, **TradeCaptureReportRequestAck**

**180.2.4783 SecondaryTradeReportID**

Secondary trade report identifier - can be used to associate an additional identifier with a trade.

Type: **String**

Used in groups: **TrdCollGrp**

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**

**180.2.4784 SecondaryTradeReportRefID**

Used to refer to a previous SecondaryTradeReportRefID when amending the transaction (cancel, replace, release, or reversal).

Type: **String**

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**

**180.2.4785 SecondaryTradingReferencePrice**

Refer to definition for TradingReferencePrice(1150)

Type: **Price**

Used in components: **SecondaryPriceLimits**

**180.2.4786 SecondaryTrdType**

Type of trade assigned to a trade. Used in addition to TrdType(828). Must not be used when only one trade type needs to be assigned.

Type: **int**

Allowed values in TrdTypeCodeSet:

Code	Name	Description
0	RegularTrade	Regular trade
1	BlockTrade	Block trade
2	EFP	Exchange for physical (EFP)
3	Transfer	Transfer
4	LateTrade	Late trade
5	TTrade	T trade
6	WeightedAveragePriceTrade	Weighted average price trade
7	BunchedTrade	Bunched trade
8	LateBunchedTrade	Late bunched trade
9	PriorReferencePriceTrade	Prior reference price trade
10	AfterHoursTrade	After hours trade
11	ExchangeForRisk	Exchange for risk (EFR)
12	ExchangeForSwap	Exchange for swap (EFS)
13	ExchangeOfFuturesFor	Exchange of futures for in market futures (EFM). For example full sized for mini.
14	ExchangeOfOptionsForOptions	Exchange of options for options (EOO)
15	TradingAtSettlement	Trading at settlement
16	AllOrNone	All or none
17	FuturesLargeOrderExecution	Futures large order execution
18	ExchangeOfFuturesForFutures	Exchange of futures for external market futures (EFF)
19	OptionInterimTrade	Option interim trade

Code	Name	Description
20	OptionCabinetTrade	Option cabinet trade
22	PrivatelyNegotiatedTrades	Privately negotiated trade
23	SubstitutionOfFuturesForForwards	Substitution of futures for forwards
24	ErrorTrade	Error trade
25	SpecialCumDividend	Special cum dividend (CD)
26	SpecialExDividend	Special ex dividend (XD)
27	SpecialCumCoupon	Special cum coupon (CC)
28	SpecialExCoupon	Special ex coupon (XC)
29	CashSettlement	Cash settlement (CS)
30	SpecialPrice	Special price (SP). Usually net or all-in price.
31	GuaranteedDelivery	Guaranteed delivery (GD)
32	SpecialCumRights	Special cum rights (CR)
33	SpecialExRights	Special ex rights (XR)
34	SpecialCumCapitalRepayments	Special cum capital repayments (CP)
35	SpecialExCapitalRepayments	Special ex capital repayments (XP)
36	SpecialCumBonus	Special cum bonus (CB)
37	SpecialExBonus	Special ex bonus (XB)
38	LargeTrade	Block trade. The same as large trade.
39	WorkedPrincipalTrade	Worked principal trade
40	BlockTrades	Block trades
41	NameChange	Name change
42	PortfolioTransfer	Portfolio transfer
43	ProrogationBuy	Prorogation buy. Used by Euronext Paris only. Is used to defer settlement under French SRD (deferred settlement system). Trades must be reported as crosses at zero price.
44	ProrogationSell	Prorogation sell. See prorogation buy.
45	OptionExercise	Option exercise
46	DeltaNeutralTransaction	Delta neutral transaction
47	FinancingTransaction	Financing transaction
48	NonStandardSettlement	Non-standard settlement
49	DerivativeRelatedTransaction	Derivative related transaction

Code	Name	Description
50	PortfolioTrade	Portfolio trade. Identifies a collection/basket of trades. In the context of bonds (e.g. corporate bonds) these are transacted as a single trade at an aggregate price for the entire portfolio and may be traded all-or-none or most-or-none depending on bilateral agreement. In the context of ESMA RTS 1 Article 2(b), may be used to refer to portfolio trades to distinguish between addressable and non-addressable volume. In the context of Market Model Typology (MMT), use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
51	VolumeWeightedAverageTrade	Volume weighted average trade
52	ExchangeGrantedTrade	Exchange granted trade
53	RepurchaseAgreement	Repurchase agreement
54	OTC	OTC. Trade executed off-market. In the context of CFTC regulatory reporting for swaps, it is a large notional off-facility swap. In the context of MiFID transparency reporting rules this is used to report, into an exchange, deals made outside exchange rules.
55	ExchangeBasisFacility	Exchange basis facility (EBF)
56	OpeningTrade	Opening trade. Identifies a trade that resulted from the opening of a market. In the context of IIROC, this indicates a trade that occurred at the opening or the first trade of the day for a security.
57	NettedTrade	Netted trade
58	BlockSwapTrade	Block swap trade. Block trade executed off-market or on a registered market. In the context of CFTC regulatory reporting for swaps, it is a swap executed according to SEF or DCM rules.
59	CreditEventTrade	Credit event trade
60	SuccessionEventTrade	Succession event trade
61	GiveUpGiveInTrade	Give-up Give-in trade
62	DarkTrade	Dark trade. In the context of Market Model Typology (MMT), a dark trade might also come from a lit/hybrid book (e.g. when an aggressive lit order hits a resting dark order). The use of this value applies to TrdType(828), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
63	TechnicalTrade	Technical trade

Code	Name	Description
64	Benchmark	Benchmark. In the context of ESMA RTS 1 Article 2(a), may be used to refer to benchmark trades. In the context of Market Model Typology (MMT), the "benchmark" price depends on a benchmark which has no current price but was derived from a time series such as a VWAP. The use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
65	PackageTrade	Package trade. May be used to identify the pseudo-trade of a stream or collection of trades to be transacted, cleared and be reported as an atomic unit. In the context of MiFIR RTS 1, this is the "CONT" flag. In the context of MiFIR RTS 2 Article 1(1)(b), may be used to refer to package transactions (excluding exchange for physicals). In the context of Market Model Typology (MMT), use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
66	RollTrade	Roll trade. Trade is a roll from one contract that is about to expire to a new contract.
67	ClosingPriceTrade	Closing price trade. Identifies a trade that uses the closing price of a market without resulting from the closing of this market. In the context of FCA policy statement PS23/4, this indicates a benchmark transaction executed using the market closing price and is the "CLSE" flag.
68	InterFundTransferTrade	Inter-fund transfer trade. Administrative trade (non price-forming) related to the transfer of ownership between funds.
69	NetAssetValueCalculatedTrade	Net asset value calculated trade. Trade of a fund priced at the net asset value of its constituents. In the context of MiFIR RTS 1, this may be used for ETFs when the NAV price becomes available.

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **Confirmation**, **ExecutionReport**, **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**

## 180.2.4787 SecSizesGrp

Name	Mult.	Type	Description
NoOfSecSizes	[1..1]	NumInGroup	Number of entries following. Conditionally required when MDUpdateAction = New(0) and MDEntryType = Bid(0) or Offer(1).
MDSecSizeType	[0..1]	CodeSet	Defines the type of secondary size specified in MDSecSize(1179). Must be first field in this repeating group
MDSecSize	[0..1]	Qty	

Used in groups: **MDFullGrp**, **MDIncGrp**

### 180.2.4788 SecTypesGrp

Name	Mult.	Type	Description
NoSecurityTypes	[1..1]	NumInGroup	
SecurityType	[0..1]	CodeSet	Required if NoSecurityTypes > 0
SecuritySubType	[0..1]	String	
Product	[0..1]	CodeSet	
CFICode	[0..1]	String	
UPICode	[0..1]	String	
TransactTime	[0..1]	UTCTimestamp	

Used in messages: **SecurityTypes**

### 180.2.4789 SecureData

Actual encrypted data stream

Type: **data**

Used in components: **StandardHeader**

### 180.2.4790 SecureDataLen

Length of encrypted message

Type: **Length**



Used in components: **StandardHeader**

### **180.2.4791 SecurityAltID**

Alternate Security identifier value for this security of SecurityAltIDSource (456) type (e.g. CUSIP, SEDOL, ISIN, etc). Requires SecurityAltIDSource.

Type: **String**

Used in groups: **SecAltIDGrp**

### **180.2.4792 SecurityAltIDSource**

Identifies class or source of the SecurityAltID(455) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))

Code	Name	Description
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [SecAltIDGrp](#)

### 180.2.4793 SecurityClassificationGrp

Name	Mult.	Type	Description
<a href="#">NoSecurityClassifications</a>	[1..1]	NumInGroup	
<a href="#">SecurityClassificationReason</a>	[0..1]	CodeSet	Conditionally required if NoSecurityClassifications > 0.
<a href="#">SecurityClassificationValue</a>	[0..1]	String	

Used in components: [DerivativeSecurityDefinition](#)

Used in groups: [SecListGrp](#)

Used in messages: [SecurityDefinition](#)

**180.2.4794 SecurityClassificationReason**

Allows classification of instruments according to a set of high level reasons. Classification reasons describe the classes in which the instrument participates.

Type: **int**

Allowed values in SecurityClassificationReasonCodeSet:

Code	Name	Description
0	Fee	Fee
1	CreditControls	Credit Controls
2	Margin	Margin
3	EntitlementOrEligibility	Entitlement / Eligibility
4	MarketData	Market Data
5	AccountSelection	Account Selection
6	DeliveryProcess	Delivery Process
7	Sector	Sector

Used in groups: **SecurityClassificationGrp**

**180.2.4795 SecurityClassificationValue**

Specifies the product classification value which further details the manner in which the instrument participates in the class.

Type: **String**

Used in groups: **SecurityClassificationGrp**

**180.2.4796 SecurityDesc**

Can be used by the venue or one of the trading parties to provide a non-normative textual description for the financial instrument.

Type: **String**

Used in components: **Instrument**

**180.2.4797 SecurityExchange**

Market used to help identify a security.

Valid values:

See "Appendix 6-C"

Type: **Exchange**

Used in components: **Instrument**

Used in groups: **TrdSessLstGrp**

Used in messages: **TradingSessionListRequest**, **TradingSessionStatusRequest**

**180.2.4798 SecurityGroup**

An exchange specific name assigned to a group of related securities which may be concurrently affected by market events and actions.

Type: **String**

Used in components: **Instrument**

**180.2.4799 SecurityID**

Security identifier value of SecurityIDSource (22) type (e.g. CUSIP, SEDOL, ISIN, etc). Requires SecurityIDSource.

Type: **String**

Used in components: **Instrument**

**180.2.4800 SecurityIDSource**

Identifies class or source of the SecurityID(48) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

---

Code	Name	Description
1	CUSIP	CUSIP

---

Code	Name	Description
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".

Code	Name	Description
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **Instrument**

#### **180.2.4801 SecurityListDesc**

Specifies a description or name of a Security List.

Type: **String**

Used in messages: **SecurityList**, **SecurityListUpdateReport**

#### **180.2.4802 SecurityListID**

Specifies an identifier for a Security List

Type: **String**

Used in messages: **MarketDataStatisticsReport**, **MarketDataStatisticsRequest**, **SecurityList**, **SecurityListRequest**, **SecurityListUpdateReport**, **SecurityMassStatus**, **SecurityMassStatusRequest**

#### **180.2.4803 SecurityListRefID**

Specifies a reference from one Security List to another. Used to support a hierarchy of Security Lists.

Type: **String**

Used in messages: **SecurityList**, **SecurityListUpdateReport**

#### **180.2.4804 SecurityListRequestType**

Identifies the type/criteria of Security List Request

Type: **int**

Allowed values in SecurityListRequestTypeCodeSet:

Code	Name	Description
0	Symbol	Symbol
1	SecurityTypeAnd	SecurityType and/or CFICode
2	Product	Product
3	TradingSessionID	TradingSessionID
4	AllSecurities	All Securities
5	MarketIDOrMarketID	MarketID or MarketID + MarketSegmentID

Used in messages: [DerivativeSecurityListRequest](#), [SecurityListRequest](#)

### 180.2.4805 SecurityListType

Specifies a type of Security List.

Type: [int](#)

Allowed values in SecurityListTypeCodeSet:

Code	Name	Description
1	IndustryClassification	Industry Classification
2	TradingList	Trading List
3	Market	Market / Market Segment List
4	NewspaperList	Newspaper List

Used in messages: [SecurityList](#), [SecurityListRequest](#), [SecurityListUpdateReport](#)

### 180.2.4806 SecurityListTypeSource

Specifies a specific source for a SecurityListType. Relevant when a certain type can be provided from various sources.

Type: [int](#)

Allowed values in SecurityListTypeSourceCodeSet:

Code	Name	Description
1	ICB	ICB (Industry Classification Benchmark) published by Dow Jones and FTSE - <a href="http://www.icbenchmark.com">www.icbenchmark.com</a>
2	NAICS	NAICS (North American Industry Classification System). Replaced SIC (Standard Industry Classification) <a href="http://www.census.gov/naics">www.census.gov/naics</a> or <a href="http://www.naics.com">www.naics.com</a> .
3	GICS	GICS (Global Industry Classification Standard) published by Standards & Poor

Used in messages: [SecurityList](#), [SecurityListRequest](#), [SecurityListUpdateReport](#)

### 180.2.4807 SecurityMassTradingEvent

Identifies an event related to the mass trading status.

Type: [int](#)

Allowed values in SecurityTradingEventCodeSet:

Code	Name	Description
1	OrderImbalance	Order imbalance, auction is extended
2	TradingResumes	Trading resumes (after Halt)
3	PriceVolatilityInterruption	Price Volatility Interruption
4	ChangeOfTradingSession	Change of Trading Session
5	ChangeOfTradingSubsession	Change of Trading Subsession
6	ChangeOfSecurityTradingStatus	Change of Security Trading Status
7	ChangeOfBookType	Change of Book Type
8	ChangeOfMarketDepth	Change of Market Depth
9	CorporateAction	Corporate action

Used in messages: [SecurityMassStatus](#)

### 180.2.4808 SecurityMassTradingStatus

Identifies the trading status applicable to a group of instruments.

Type: [int](#)



Allowed values in SecurityTradingStatusCodeSet:

Code	Name	Description
1	OpeningDelay	Opening delay
2	TradingHalt	Trading halt
3	Resume	Resume
4	NoOpen	No Open / No Resume
5	PriceIndication	Price indication
6	TradingRangeIndication	Trading Range Indication
7	MarketImbalanceBuy	Market Imbalance Buy
8	MarketImbalanceSell	Market Imbalance Sell
9	MarketOnCloseImbalanceBuy	Market on Close Imbalance Buy
10	MarketOnCloseImbalanceSell	Market on Close Imbalance Sell
12	NoMarketImbalance	No Market Imbalance
13	NoMarketOnCloseImbalance	No Market on Close Imbalance
14	ITSPreOpening	ITS Pre-opening
15	NewPriceIndication	New Price Indication
16	TradeDisseminationTime	Trade Dissemination Time
17	ReadyToTrade	Ready to trade (start of session)
18	NotAvailableForTrading	Not available for trading (end of session)
19	NotTradedOnThisMarket	Not traded on this market
20	UnknownOrInvalid	Unknown or Invalid
21	PreOpen	Pre-open
22	OpeningRotation	Opening Rotation
23	FastMarket	Fast Market
24	PreCross	Pre-Cross - system is in a pre-cross state allowing market to respond to either side of cross
25	Cross	Cross - system has crossed a percentage of the orders and allows market to respond prior to crossing remaining portion
26	PostClose	Post-close
27	NoCancel	No-cancel

Used in messages: **SecurityMassStatus**

**180.2.4809 SecurityReferenceDataSupplement**

May be used to generically assist in disambiguating an instrument where the security identifier and core reference data attributes are not sufficient to uniquely identify the instrument. The values used are bilaterally agreed.

Type: **String**

Used in components: **Instrument**

**180.2.4810 SecurityRejectReason**

Identifies the reason a security definition request is being rejected.

Type: **int**

Allowed values in SecurityRejectReasonCodeSet:

Code	Name	Description
1	InvalidInstrumentRequested	Invalid instrument requested
2	InstrumentAlreadyExists	Instrument already exists
3	RequestTypeNotSupported	Request type not supported
4	SystemUnavailableForInstrumentCreation	System unavailable for instrument creation
5	IneligibleInstrumentGroup	Ineligible instrument group
6	InstrumentIDUnavailable	Instrument ID unavailable
7	InvalidOrMissingDataOnOptionLeg	Invalid or missing data on option leg
8	InvalidOrMissingDataOnFutureLeg	Invalid or missing data on future leg
10	InvalidOrMissingDataOnFXLeg	Invalid or missing data on FX leg
11	InvalidLegPriceSpecified	Invalid leg price specified
12	InvalidInstrumentStructureSpecified	Invalid instrument structure specified

Used in messages: **DerivativeSecurityList**, **SecurityDefinition**, **SecurityList**

**180.2.4811 SecurityReportID**

Identifies a Security List message.

Type: **int**

Used in messages: [DerivativeSecurityList](#), [SecurityDefinition](#), [SecurityDefinitionUpdateReport](#), [SecurityList](#), [SecurityListUpdateReport](#)

### **180.2.4812 SecurityReqID**

Unique ID of a Security Definition Request.

Type: [String](#)

Used in messages: [DerivativeSecurityList](#), [DerivativeSecurityListRequest](#), [DerivativeSecurityListUpdateReport](#), [SecurityDefinition](#), [SecurityDefinitionRequest](#), [SecurityDefinitionUpdateReport](#), [SecurityList](#), [SecurityListRequest](#), [SecurityListUpdateReport](#), [SecurityTypeRequest](#), [SecurityTypes](#)

### **180.2.4813 SecurityRequestResult**

The results returned to a Security Request message

Type: [int](#)

Allowed values in SecurityRequestResultCodeSet:

Code	Name	Description
0	ValidRequest	Valid request
1	InvalidOrUnsupportedRequest	Invalid or unsupported request
2	NoInstrumentsFound	No instruments found that match selection criteria
3	NotAuthorizedToRetrieveInstrumentData	Not authorized to retrieve instrument data
4	InstrumentDataTemporarilyUnavailable	Instrument data temporarily unavailable
5	RequestForInstrumentDataNotSupported	Request for instrument data not supported

Used in messages: [DerivativeSecurityList](#), [DerivativeSecurityListUpdateReport](#), [SecurityDefinition](#), [SecurityList](#), [SecurityListUpdateReport](#)

### **180.2.4814 SecurityRequestType**

Type of Security Definition Request.

Type: [int](#)

Allowed values in SecurityRequestTypeCodeSet:

Code	Name	Description
0	RequestSecurityIdentityAndSpecifications	Request Security identity and specifications
1	RequestSecurityIdentityForSpecifications	Request Security identity for the specifications provided (name of the security is not supplied)
2	RequestListSecurityTypes	Request List Security Types
3	RequestListSecurities	Request List Securities (can be qualified with Symbol, SecurityType, TradingSessionID, SecurityExchange. If provided then only list Securities for the specific type.)
4	Symbol	Symbol
5	SecurityTypeAndOrCFIcode	SecurityType and or CFIcode
6	Product	Product
7	TradingSessionID	TradingSessionID
8	AllSecurities	All Securities
9	MarketIDOrMarketID	MarketID or MarketID + MarketSegmentID

Used in messages: [SecurityDefinitionRequest](#)

#### **180.2.4815 SecurityResponseID**

Unique ID of a Security Definition message.

Type: [String](#)

Used in messages: [DerivativeSecurityList](#), [DerivativeSecurityListUpdateReport](#), [SecurityDefinition](#), [SecurityDefinitionUpdateReport](#), [SecurityList](#), [SecurityListUpdateReport](#), [SecurityTypes](#)

#### **180.2.4816 SecurityResponseType**

Type of Security Definition message response.

Type: [int](#)

Allowed values in SecurityResponseTypeCodeSet:

Code	Name	Description
1	AcceptAsIs	Accept security proposal as-is
2	AcceptWithRevisions	Accept security proposal with revisions as indicated in the message
5	RejectSecurityProposal	Reject security proposal
6	CannotMatchSelectionCriteria	Cannot match selection criteria

Used in messages: [SecurityDefinition](#), [SecurityDefinitionUpdateReport](#), [SecurityTypes](#)

### 180.2.4817 SecurityRiskMetricGrp

List of option securities on an underlying with related calculations (e.g. theoretical valuations, implied volatilities, and other hedge statistics).

Name	Mult.	Type	Description
<a href="#">NoSecurityRiskMetrics</a>	[1..1]	NumInGroup	
<a href="#">Instrument</a>	[0..1]	Component	Required when NoSecurityRiskMetrics(2995) > 0.
<a href="#">PriceDelta</a>	[0..1]	float	
<a href="#">Gamma</a>	[0..1]	float	
<a href="#">Rho</a>	[0..1]	float	
<a href="#">Theta</a>	[0..1]	float	
<a href="#">Vega</a>	[0..1]	float	
<a href="#">Price</a>	[0..1]	Price	May be used for the theoretical (e.g. option) price of the security.
<a href="#">BidPx</a>	[0..1]	Price	May be used to specify the security's top of book bid price, if available, used in the metric calculation.
<a href="#">OfferPx</a>	[0..1]	Price	May be used to specify the security's top of book offer price, if available, used in the metric calculation.
<a href="#">VolatilityTime</a>	[0..1]	UTCTimestamp	
<a href="#">Volatility</a>	[0..1]	float	
<a href="#">BidVolatility</a>	[0..1]	float	
<a href="#">OfferVolatility</a>	[0..1]	float	
<a href="#">MidVolatility</a>	[0..1]	float	

Name	Mult.	Type	Description
RelativeValueGrp	[0..*]	Group	May be used for other types of valuation metrics or analytics.

Used in messages: [SecurityRiskMetricsReport](#)

#### 180.2.4818 SecurityRiskMetricsReportID

Unique identifier for the SecurityRiskMetricsReport(35=EG) message.

Type: [String](#)

Used in messages: [SecurityRiskMetricsReport](#)

#### 180.2.4819 SecurityStatus

Indicates the current state of the instrument.

Type: [String](#)

Allowed values in SecurityStatusCodeSet:

Code	Name	Description
1	Active	Active. Instrument is active, i.e. trading is possible.
2	Inactive	Inactive. Instrument has previously been active and is now no longer traded but has not expired yet. The instrument may become active again.
3	ActiveClosingOrdersOnly	Active, closing orders only. Instrument is active but only orders closing positions (reducing risk) are allowed.
4	Expired	Expired. Instrument has expired. E.g. An instrument may expire due to reaching maturity or expired based on contract definitions or exchange rules.
5	Delisted	Delisted. Instrument has been removed from securities reference data. Delisting rules varies from exchange to exchange, which may include non-compliance of capitalization, revenue, consecutive minimum closing price. The instrument may become listed again once the instrument is back in compliance. A delisted instrument would not trade on the exchange but it may still be traded over-the-counter (e.g. OTCBB) or on Pink Sheets, or other similar trading service.

Code	Name	Description
6	KnockedOut	Knocked-out. Instrument has breached a pre-defined price threshold.
7	KnockOutRevoked	Knock-out revoked. Instrument reinstated, i.e. threshold has not been breached.
8	PendingExpiry	Pending Expiry. Instrument is currently still active but will expire after the current business day. For example, a contract that expires intra-day (e.g. at noon time) and is no longer tradeable but will still show up in the current day's order book with related statistics.
9	Suspended	Suspended. Instrument has been temporarily disabled for trading (i.e. halted).
10	Published	Published. Instrument information is provided prior to its first activation.
11	PendingDeletion	Pending Deletion. Instrument is awaiting deletion from security reference data.

---

Used in components: **Instrument**

#### **180.2.4820 SecurityStatusReqID**

Unique ID of a Security Status Request or a Security Mass Status Request message.

Type: **String**

Used in messages: **SecurityMassStatus**, **SecurityMassStatusRequest**, **SecurityStatus**, **SecurityStatusRequest**

#### **180.2.4821 SecuritySubType**

Sub-type qualification/identification of the SecurityType. As an example for SecurityType(167)="REPO", the SecuritySubType="General Collateral" can be used to further specify the type of REPO.

If SecuritySubType is used, then SecurityType is required.

For SecurityType="MLEG" a name of the option or futures strategy name can be specified, such as "Calendar", "Vertical", "Butterfly".

For SecurityType(167)="OPT" the subclassification can be specified, such as "Asian".

For SecurityType(167)="SWAPTION" a value of "Straddle" is used to identify a straddle swaption.

In the context of EU SFTR reporting use the appropriate 4-character code noted in the regulations - "GENE" for general collateral or "SPEC" for specific collateral (without quote marks).

Type: **String**

Used in components: **Instrument**

Used in groups: **SecTypesGrp**

Used in messages: **DerivativeSecurityListRequest**, **SecurityTypeRequest**

### **180.2.4822 SecurityTradingEvent**

Identifies an event related to a SecurityTradingStatus(326). An event occurs and is gone, it is not a state that applies for a period of time.

Type: **int**

Allowed values in SecurityTradingEventCodeSet:

Code	Name	Description
1	OrderImbalance	Order imbalance, auction is extended
2	TradingResumes	Trading resumes (after Halt)
3	PriceVolatilityInterruption	Price Volatility Interruption
4	ChangeOfTradingSession	Change of Trading Session
5	ChangeOfTradingSubsession	Change of Trading Subsession
6	ChangeOfSecurityTradingStatus	Change of Security Trading Status
7	ChangeOfBookType	Change of Book Type
8	ChangeOfMarketDepth	Change of Market Depth
9	CorporateAction	Corporate action

Used in groups: **SecMassStatGrp**

Used in messages: **SecurityStatus**

### **180.2.4823 SecurityTradingRules**

This SecurityTradingRules component block is used as part of security definition to specify the specific security's standard trading parameters such as trading session eligibility and other attributes of the security.



Name	Mult.	Type	Description
BaseTradingRules	[0..1]	Component	This block contains the base trading rules
TradingSessionRulesGrp	[0..*]	Group	This block contains the trading rules specific to a trading session
NestedInstrumentAttribute	[0..*]	Group	

Used in groups: **MarketSegmentGrp**, **SecListGrp**, **SecLstUpdRelSymGrp**

### 180.2.4824 SecurityTradingStatus

Identifies the trading status applicable to the transaction.

Type: **int**

Allowed values in SecurityTradingStatusCodeSet:

Code	Name	Description
1	OpeningDelay	Opening delay
2	TradingHalt	Trading halt
3	Resume	Resume
4	NoOpen	No Open / No Resume
5	PriceIndication	Price indication
6	TradingRangeIndication	Trading Range Indication
7	MarketImbalanceBuy	Market Imbalance Buy
8	MarketImbalanceSell	Market Imbalance Sell
9	MarketOnCloseImbalanceBuy	Market on Close Imbalance Buy
10	MarketOnCloseImbalanceSell	Market on Close Imbalance Sell
12	NoMarketImbalance	No Market Imbalance
13	NoMarketOnCloseImbalance	No Market on Close Imbalance
14	ITSPreOpening	ITS Pre-opening
15	NewPriceIndication	New Price Indication
16	TradeDisseminationTime	Trade Dissemination Time
17	ReadyToTrade	Ready to trade (start of session)
18	NotAvailableForTrading	Not available for trading (end of session)
19	NotTradedOnThisMarket	Not traded on this market
20	UnknownOrInvalid	Unknown or Invalid

Code	Name	Description
21	PreOpen	Pre-open
22	OpeningRotation	Opening Rotation
23	FastMarket	Fast Market
24	PreCross	Pre-Cross - system is in a pre-cross state allowing market to respond to either side of cross
25	Cross	Cross - system has crossed a percentage of the orders and allows market to respond prior to crossing remaining portion
26	PostClose	Post-close
27	NoCancel	No-cancel

Used in groups: [MDFullGrp](#), [MDIncGrp](#), [SecMassStatGrp](#)

Used in messages: [SecurityStatus](#)

### 180.2.4825 SecurityType

Indicates type of security. Security type enumerations are grouped by Product(460) field value. NOTE: Additional values may be used by mutual agreement of the counterparties.

Type: [String](#)

Allowed values in SecurityTypeCodeSet:

Code	Name	Description
ABS	AssetBackedSecurities	Asset-backed Securities
AN	OtherAnticipationNotes	Other Anticipation Notes (BAN, GAN, etc.)
BA	BankersAcceptance	Bankers Acceptance
BRADY	BradyBond	Brady Bond
CORP	CorporateBond	Corporate Bond
CS	CommonStock	Common Stock
EUSUPRA	EuroSupranationalCoupons	Euro Supranational Coupons. Identify the issuer name in Issuer(106).
FOR	ForeignExchangeContract	Foreign Exchange Contract
MF	MutualFund	Mutual Fund
REPO	Repurchase	Repurchase
TERM	TermLoan	Term Loan

Code	Name	Description
BDN	BankDepositoryNote	Bank Depository Note
CAN	CanadianTreasuryNotes	Canadian Treasury Notes
CAP	Cap	Cap. In an interest rate cap, the buyer receives payments at the end of each period in which the rate indec exceeds the agreed strike rate.
CMB	CanadianMortgageBonds	Canadian Mortgage Bonds
COFO	CertificateOfObligation	Certificate Of Obligation
CPP	CorporatePrivatePlacement	Corporate Private Placement
FAC	FederalAgencyCoupon	Federal Agency Coupon
FORWARD	Forward	Forward
FXNDF	NonDeliverableForward	Non-deliverable forward
MLEG	MultilegInstrument	Multileg Instrument
PS	PreferredStock	Preferred Stock
RVLV	RevolverLoan	Revolver Loan
BN	BankNotes	Bank Notes
BUYSELL	BuySellback	Buy Sellback
CB	ConvertibleBond	Convertible Bond
CDS	CreditDefaultSwap	Credit Default Swap
CMBS	Corp	Corp. Mortgage-backed Securities
COFP	CertificateOfParticipation	Certificate Of Participation
CTB	CanadianTreasuryBills	Canadian Treasury Bills
DR	DepositoryReceipts	Depository Receipts
FADN	FederalAgencyDiscountNote	Federal Agency Discount Note
FXSPOT	FXSpot	FX Spot
NONE	NoSecurityType	No Security Type
RVLVTRM	Revolver	Revolver/Term Loan
BOX	BillOfExchanges	Bill Of Exchanges
BRIDGE	BridgeLoan	Bridge Loan
CLLR	Collar	Collar. In an interest rate collar, this is a combination of a cap and a floor.
CMO	CollateralizedMortgageObligation	Collateralized Mortgage Obligation
DUAL	DualCurrency	Dual Currency
EUSOV	EuroSovereigns	Euro Sovereigns. Identify the issuer name in Issuer(106).
FXFWD	FXForward	FX Forward
GO	GeneralObligationBonds	General Obligation Bonds

Code	Name	Description
PEF	PrivateExportFunding	Private Export Funding. Identify the issuer name in Issuer(106).
SECLOAN	SecuritiesLoan	Securities Loan
UST	USTreasuryNoteOld	US Treasury Note (Deprecated Value Use TNOTE)
CAMM	CanadianMoneyMarkets	Canadian Money Markets
CMDTYSWAP	CommoditySwap	Commodity swap
EUCORP	EuroCorporateBond	Euro Corporate Bond
FXSWAP	FXSwap	FX Swap
IET	IOETTEMortgage	IOETTE Mortgage
LOFC	LetterOfCredit	Letter Of Credit
MT	MandatoryTender	Mandatory Tender
PROV	CanadianProvincialBonds	Canadian Provincial Bonds
SECPLEDGE	SecuritiesPledge	Securities Pledge
SUPRA	USDSupranationalCoupons	USD Supranational Coupons. Identify the issuer name in Issuer(106).
USTB	USTreasuryBillOld	US Treasury Bill (Deprecated Value Use TBILL)
?	Wildcard	Wildcard entry for use on Security Definition Request
CD	CertificateOfDeposit	Certificate Of Deposit
DVPLDG	DeliveryVersusPledge	Delivery versus pledge
EUFRN	EuroCorporateFloatingRateNotes	Euro Corporate Floating Rate Notes
EXOTIC	Exotic	Exotic
FXNDS	NonDeliverableSwap	Non-deliverable Swap
MBS	MortgageBackedSecurities	Mortgage-backed Securities
RAN	RevenueAnticipationNote	Revenue Anticipation Note
SWING	SwingLineFacility	Swing Line Facility
TB	TreasuryBill	Treasury Bill - non US
CASH	Cash	Cash
CL	CallLoans	Call Loans
COLLBSKT	CollateralBasket	Collateral basket. A collection of securities held as collateral in the customer's collateral fund. The collateral fund is usually managed by a custodian.
DINP	DebtorInPossession	Debtor In Possession
FLR	Floor	Floor. In an interest rate floor, the buyer receives payments at the end of each period in which the rate index is below the agreed strike rate.
FRN	USCorporateFloatingRateNotes	US Corporate Floating Rate Notes

Code	Name	Description
FXBN	FXBankNote	FX Bank Note
MIO	MortgageInterestOnly	Mortgage Interest Only
OOC	OptionsOnCombo	Options on Combo
REV	RevenueBonds	Revenue Bonds
TBOND	USTreasuryBond	US Treasury Bond
CP	CommercialPaper	Commercial Paper
DEFLTED	Defaulted	Defaulted
FRA	FRA	Forward Rate Agreement
FXDN	ForeignCurrencyDiscountNote	Foreign Currency Discount Note. Discount notes issued in foreign currency by Fannie Mae.
MPO	MortgagePrincipalOnly	Mortgage Principal Only
Other	Other	Other
SFP	StructuredFinanceProduct	Structured finance product
SPCLA	SpecialAssessment	Special Assessment
TINT	InterestStripFromAnyBondOrNote	Interest Strip From Any Bond Or Note
XLINKD	IndexedLinked	Indexed Linked
DN	DepositNotes	Deposit Notes
ETN	ExchangeTradedNote	Exchange traded note
FUT	Future	Future
MPP	MortgagePrivatePlacement	Mortgage Private Placement
SPCLO	SpecialObligation	Special Obligation
STRUCT	StructuredNotes	Structured Notes
TBILL	USTreasuryBill	US Treasury Bill
TIPS	TreasuryInflationProtectedSecurities	Treasury Inflation Protected Securities
WITHDRN	Withdrawn	Withdrawn
EUCD	EuroCertificateOfDeposit	Euro Certificate Of Deposit
FWD	DerivativeForward	Derivative forward
MPT	MiscellaneousPassThrough	Miscellaneous Pass-through
MGRNLOAN	MarginLoan	Margin loan
REPLACD	Replaced	Replaced
SPCLT	SpecialTax	Special Tax
TCAL	PrincipalStripOfACallableBondOrNote	Principal Strip Of A Callable Bond Or Note
YANK	YankeeCorporateBond	Yankee Corporate Bond

Code	Name	Description
DIMSUMCORP	OffshoreIssuedChineseYuanCorpo- rateBond	Offshore issued Chinese Yuan (CNY) denominated corporate bond
EUCP	EuroCommercialPaper	Euro Commercial Paper
IRS	InterestRateSwap	Interest Rate Swap
MATURED	Matured	Matured
PFAND	Pfandbrief	Pfandbrief. Identify the issuer name in Issuer(106).
SECDERIV	SecuritizedDerivative	Securitized derivative
TAN	TaxAnticipationNote	Tax Anticipation Note
TPRN	PrincipalStripFromANonCallable- BondOrNote	Principal Strip From A Non-Callable Bond Or Note
TRS	TotalReturnSwap	Total return swap
AMENDED	Amended	Amended and restated
ETF	ExchangeTradedFund	Exchange Traded Fund
LOANLEASE	LoanLease	Loan/lease
LQN	LiquidityNote	Liquidity Note
PRCORP	PreferredCorporateBond	Preferred Corporate Bond
TAXA	TaxAllocation	Tax Allocation
TBA	ToBeAnnounced	To Be Announced
TNOTE	USTreasuryNote	US Treasury Note
DIGITAL	DigitalAsset	Digital Asset. Asset that exists only in digital form or which is the digital representation of another asset (Source: ISO 24165 - Terms and Definitions).
DIMSUMSOV	OffshoreIssuedChine- seYuanSovereignBond	Offshore issued Chinese Yuan (CNY) denominated sovereign bond
MTN	MediumTermNotes	Medium Term Notes
RETIRED	Retired	Retired
TECP	TaxExemptCommercialPaper	Tax Exempt Commercial Paper
ONITE	Overnight	Overnight
OOF	OptionsOnFutures	Options on Futures
SOV	SovereignBond	Sovereign Bond. Sovereign or government bond other than Euro and US issuer. Specify sovereign issuer in Issuer(106).
TMCP	TaxableMunicipalCP	Taxable Municipal CP
OOP	OptionsOnPhysical	Options on Physical - use not recommended
PN	PromissoryNote	Promissory Note
STN	ShortTermLoanNote	Short Term Loan Note
TFRN	USTreasuryFloatingRateNote	US Treasury Floating Rate Note

Code	Name	Description
TRAN	TaxRevenueAnticipationNote	Tax Revenue Anticipation Note
OPT	Option	Option
PZFJ	PlazosFijos	Plazos Fijos
VRDN	VariableRateDemandNote	Variable Rate Demand Note
SLQN	SecuredLiquidityNote	Secured Liquidity Note
SPOTFWD	SpotForward	Spot forward
WAR	Warrant	Warrant
MCPIB	MunicipalInterestBearingCommercialPaper	Municipal Interest Bearing Commercial Paper
SWAPTION	SwapOption	Swap option
TD	TimeDeposit	Time Deposit
TMB	TaxableMunicipalBond	Taxable Municipal Bond
XMISSION	Transmission	Transmission
INDEX	Index	General type for a contract based on an established index
TLQN	TermLiquidityNote	Term Liquidity Note
VRDO	VariableRateDemandObligation	Variable Rate Demand Obligation
BDBSKT	BondBasket	Bond basket
XCN	ExtendedCommNote	Extended Comm Note
CFD	ContractForDifference	Contract for difference
YCD	YankeeCertificateOfDeposit	Yankee Certificate Of Deposit
BAB	BankAcceptedBill	Bank Accepted Bill. Also known as Bank Bill.
CRLNSWAP	CorrelationSwap	Correlation swap
BNST	ShortTermBankNote	Short Term Bank Note
DVDNDSWAP	DividendSwap	Dividend swap
CLCP	CallableCommercialPaper	Callable Commercial Paper
EQBSKT	EquityBasket	Equity basket
CN	CommercialNote	Commercial Note
EQFWD	EquityForward	Equity forward
CPIB	InterestBearingCommercialPaper	Interest Bearing Commercial Paper
RTRNSWAP	ReturnSwap	Return swap
EUMTN	EuroMediumTermNote	Euro Medium Term Note
VARSWAP	VarianceSwap	Variance swap
EUNCP	EuroNegotiableCommercialPaper	Euro Negotiable Commercial Paper
PRTFLIOSWAP	PortfolioSwaps	Portfolio swap

Code	Name	Description
EUSTLQN	EuroStructuredLiquidityNote	Euro Structured Liquidity Note
FUTSWAP	FuturesOnASwap	Futures on a Swap
EUTD	EuroTimeDeposit	Euro Time Deposit
FWDSWAP	ForwardsOnASwap	Forwards on a Swap
FWDFRTAGMT	ForwardFreightAgreement	Forward Freight Agreement
JCD	JumboCertificateOfDeposit	Jumbo Certificate of Deposit
MMF	MoneyMarketFund	Money Market Fund
SPREADBET	SpreadBetting	Spread Betting
ETC	ExchangeTradedCommodity	Exchange traded commodity
MN	MasterNote	Master Note. Short term notes issued by Federal Farm Credit Banks Funding Corporation to provide loans and funding under Federal Farm Credit System (FFCS).
NCD	NegotiableCertificateOfDeposit	Negotiable Certificate of Deposit
NCP	NegotiableCommercialPaper	Negotiable Commercial Paper
RCD	RetailCertificateOfDeposit	Retail Certificate of Deposit
TDR	TermDepositReceipt	Term Deposit Receipt

Used in components: **Instrument**

Used in groups: **SecTypesGrp**, **SettlInstGrp**

Used in messages: **SecurityTypeRequest**, **SettlementInstructionRequest**

## 180.2.4826 SecurityUpdateAction

Specifies the action taken or to be taken for the specified instrument or list of instruments.

Type: **char**

Allowed values in SecurityUpdateActionCodeSet:

Code	Name	Description
A	Add	Add
D	Delete	Delete
M	Modify	Modify

Used in messages: **DerivativeSecurityListUpdateReport**, **SecurityDefinitionUpdateReport**, **SecurityListUpdateReport**



**180.2.4827 SecurityXML**

XML definition for the security.

Type: **XMLData**

Used in components: **SecurityXML**

**180.2.4828 SecurityXML**

The SecurityXML component is used to provide a definition in an XML format for the instrument.

Name	Mult.	Type	Description
<b>SecurityXMLLen</b>	[0..1]	Length	Must be provided if SecurityXML(1185) field is specified and must immediately precede it.
<b>SecurityXML</b>	[0..1]	XMLData	
<b>SecurityXMLSchema</b>	[0..1]	String	

Used in components: **Instrument**

**180.2.4829 SecurityXMLLen**

The length of the SecurityXML(1185) data block.

Type: **Length**

Used in components: **SecurityXML**

**180.2.4830 SecurityXMLSchema**

The schema used to validate the contents of SecurityXML(1185).

Type: **String**

Used in components: **SecurityXML**

**180.2.4831 SelfMatchPreventionID**

Identifies an order or trade that should not be matched to an opposite order or trade if both buy and sell orders for the same asset contain the same SelfMatchPreventionID(2362) and submitted by the same firm.

Type: **String**

Used in components: **TradeReportOrderDetail**

Used in messages: **ExecutionReport**, **MassQuote**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **Quote**

#### **180.2.4832 SelfMatchPreventionInstruction**

Indicate the instruction for self-match prevention when the incoming (aggressive) order has the same SelfMatchPreventionID(2362) as a resting (passive) order.

Type: **int**

Allowed values in SelfMatchPreventionInstructionCodeSet:

Code	Name	Description
1	CancelAggressive	Cancel aggressive. Cancel incoming order.
2	CancelPassive	Cancel passive. Cancel resting order with the same SelfMatchPreventionID(2362).
3	CancelAggressivePassive	Cancel aggressive and passive. Cancel both incoming and resting order with the same SelfMatchPreventionID(2362).

Used in components: **TradeReportOrderDetail**

Used in messages: **ExecutionReport**, **MassQuote**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **Quote**

#### **180.2.4833 SellerDays**

Specifies the number of days that may elapse before delivery of the security

Type: **int**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.4834 SellVolume**

Quantity sold.

Type: **Qty**

Used in messages: **SecurityStatus**

#### **180.2.4835 SenderCompID**

Assigned value used to identify firm sending message.

Type: **String**

Used in components: **StandardHeader**

#### **180.2.4836 SenderLocationID**

Assigned value used to identify specific message originator's location (i.e. geographic location and/or desk, trader)

Type: **String**

Used in components: **StandardHeader**

#### **180.2.4837 SenderSubID**

Assigned value used to identify specific message originator (desk, trader, etc.)

Type: **String**

Used in components: **StandardHeader**

#### **180.2.4838 SendingTime**

Time of message transmission (always expressed in UTC (Universal Time Coordinated, also known as "GMT"))

Type: **UTCTimestamp**

Used in components: **StandardHeader**

#### **180.2.4839 Seniority**

Specifies which issue (underlying bond) will receive payment priority in the event of a default.

Used to define a CDS instrument.

Type: **String**

Allowed values in SeniorityCodeSet:

Code	Name	Description
SD	SeniorSecured	Senior Secured
SR	Senior	Senior
SB	Subordinated	Subordinated
JR	Junior	Junior. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
MZ	Mezzanine	Mezzanine. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
SN	SeniorNonPreferred	Senior Non-Preferred. For CDS reference obligations of non-preferred senior debt issued by European Financials that constitute a layer of debt ranking between the bank's normal senior debt but above the bank's normal tier 2 subordinated debt (reference: ISDA Credit Market Infrastructure Group).

Used in components: **Instrument**

### 180.2.4840 SessionRejectReason

Code to identify reason for a session-level Reject message.

Type: **int**

Allowed values in SessionRejectReasonCodeSet:

Code	Name	Description
0	InvalidTagNumber	Invalid Tag Number
1	RequiredTagMissing	Required Tag Missing
2	TagNotDefinedForThisMessageType	Tag not defined for this message type
3	UndefinedTag	Undefined tag
4	TagSpecifiedWithoutAValue	Tag specified without a value
5	ValueIsIncorrect	Value is incorrect (out of range) for this tag
6	IncorrectDataFormatForValue	Incorrect data format for value
7	DecryptionProblem	Decryption problem
8	SignatureProblem	Signature problem
9	CompIDProblem	CompID problem
10	SendingTimeAccuracyProblem	SendingTime Accuracy Problem
11	InvalidMsgType	Invalid MsgType

Code	Name	Description
12	XMLValidationError	XML Validation Error
13	TagAppearsMoreThanOnce	Tag appears more than once
14	TagSpecifiedOutOfRequiredOrder	Tag specified out of required order
15	RepeatingGroupFieldsOutOfOrder	Repeating group fields out of order
16	IncorrectNumInGroupCountForRepeatingGroup	Incorrect NumInGroup count for repeating group
17	NonDataValueIncludesFieldDelimiter	Non "Data" value includes field delimiter (<SOH> character)
18	InvalidUnsupportedApplVer	Invalid/Unsupported Application Version
99	Other	Other

Used in messages: **Reject**

### 180.2.4841 SessionStatus

Status of a FIX session

Type: **int**

Allowed values in SessionStatusCodeSet:

Code	Name	Description
0	SessionActive	Session active
1	SessionPasswordChanged	Session password changed
2	SessionPasswordDueToExpire	Session password due to expire
3	NewSessionPasswordDoesNotComplyWithPolicy	New session password does not comply with policy
4	SessionLogoutComplete	Session logout complete
5	InvalidUsernameOrPassword	Invalid username or password
6	AccountLocked	Account locked
7	LogonsAreNotAllowedAtThisTime	Logons are not allowed at this time
8	PasswordExpired	Password expired
9	ReceivedMsgSeqNumTooLow	Received MsgSeqNum(34) is too low.
10	ReceivedNextExpectedMsgSeqNumTooHigh	Received NextExpectedMsgSeqNum(789) is too high.

Used in messages: **Logon**, **Logout**

**180.2.4842 SettlCurrAmt**

Total amount due expressed in settlement currency (includes the effect of the forex transaction)

Type: **Amt**

Used in components: **SettlTradeDetails**

Used in groups: **AllocGrp, SettlObligationInstructions, TrdCapRptAckSideGrp, TrdCapRptSideGrp**

Used in messages: **Confirmation, ExecutionReport**

**180.2.4843 SettlCurrBidFxRate**

Foreign exchange rate used to compute the bid "SettlCurrAmt" (119) from Currency (15) to SettlCurrency (120)

Type: **float**

Used in messages: **Quote, QuoteResponse, QuoteStatusReport**

**180.2.4844 SettlCurrency**

Currency code of settlement denomination.

Type: **Currency**

Used in components: **SettlTradeDetails**

Used in groups: **AllocGrp, InstrmtMatchSideGrp, ListOrdGrp, MDFullGrp, MDIncGrp, QuotReqGrp, SettlInstGrp, SettlObligationInstructions, SideCrossOrdModGrp**

Used in messages: **Confirmation, ExecutionReport, MultilegOrderCancelReplace, NewOrder-Multileg, NewOrderSingle, OrderCancelReplaceRequest, PositionMaintenanceReport, Position-MaintenanceRequest, PositionReport, Quote, RequestForPositions, RequestForPositionsAck, SettlementInstructionRequest, TradeCaptureReport, TradeCaptureReportAck**

**180.2.4845 SettlCurrencyCodeSource**

Identifies class or source of the SettlCurrency(120) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [SettlTradeDetails](#)

Used in groups: [InstrmtMatchSideGrp](#), [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#), [QuotReqGrp](#), [SettlInstGrp](#), [SettlObligationInstructions](#), [SideCrossOrdModGrp](#)

Used in messages: [Confirmation](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrder-Multileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [PositionMaintenanceReport](#), [Position-MaintenanceRequest](#), [PositionReport](#), [Quote](#), [RequestForPositions](#), [RequestForPositionsAck](#), [SettlementInstructionRequest](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### 180.2.4846 SettlCurrFxRate

Foreign exchange rate used to compute SettlCurrAmt(119) from Currency(15) to SettlCurrency(120).

Type: [float](#)

Used in groups: [AllocGrp](#), [SettlObligationInstructions](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [Confirmation](#), [ExecutionReport](#)

#### 180.2.4847 SettlCurrFxRateCalc

Specifies whether or not SettlCurrFxRate (155) should be multiplied or divided.

Type: [char](#)

Allowed values in SettlCurrFxRateCalcCodeSet:

Code	Name	Description
M	Multiply	Multiply

Code	Name	Description
D	Divide	Divide

Used in groups: [AllocGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [Confirmation](#), [ExecutionReport](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

#### **180.2.4848 SettlCurrOfferFxRate**

Foreign exchange rate used to compute the offer "SettlCurrAmt" (119) from Currency (15) to SettlCurrency (120)

Type: [float](#)

Used in messages: [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

#### **180.2.4849 SettlDate**

Specific date of trade settlement (SettlementDate) in YYYYMMDD format.

If present, this field overrides SettlType (63). This field is required if the value of SettlType (63) is 6 (Future) or 8 (Sellers Option). This field must be omitted if the value of SettlType (63) is 7 (When and If Issued)

(expressed in local time at place of settlement)

Type: [LocalMktDate](#)

Used in components: [SettlTradeDetails](#)

Used in groups: [BidCompReqGrp](#), [BidCompRspGrp](#), [InstrmtMDReqGrp](#), [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#), [QuotEntryAckGrp](#), [QuotEntryGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [SettlObligationInstructions](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [Confirmation](#), [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [PositionReport](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [RequestForPositions](#), [TradeAggregationReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)



**180.2.4850 SettlDate2**

SettlDate (64) of the future part of a F/X swap order.

Type: **LocalMktDate**

Used in groups: **ListOrdGrp**, **QuotEntryAckGrp**, **QuotEntryGrp**, **QuotReqGrp**, **QuotReqRjctGrp**

Used in messages: **ExecutionReport**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **Quote**, **QuoteResponse**, **QuoteStatusReport**

**180.2.4851 SettlDeliveryType**

Identifies type of settlement

Type: **int**

Allowed values in SettlDeliveryTypeCodeSet:

Code	Name	Description
0	Versus	"Versus. Payment": Deliver (if Sell) or Receive (if Buy) vs. (Against) Payment
1	Free	"Free": Deliver (if Sell) or Receive (if Buy) Free
2	TriParty	Tri-Party
3	HoldInCustody	Hold In Custody

Used in components: **SettlInstructionsData**

**180.2.4852 SettlDetails**

Name	Mult.	Type	Description
<b>NoSettlDetails</b>	[1..1]	NumInGroup	Number of settlement parties
<b>SettlObligSource</b>	[0..1]	CodeSet	Indicates the Source of the Settlement Instructions
<b>StandInstDbType</b>	[0..1]	CodeSet	
<b>StandInstDbName</b>	[0..1]	String	
<b>StandInstDbID</b>	[0..1]	String	
<b>SettlParties</b>	[0..*]	Group	Carries settlement account information

Used in groups: **SettlObligationInstructions**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: [PayManagementReport](#), [PayManagementRequest](#)

#### **180.2.4853 SettlDisruptionProvision**

Specifies the consequences of bullion settlement disruption events.

Type: [int](#)

Allowed values in SettlDisruptionProvisionCodeSet:

Code	Name	Description
1	Negotiation	Negotiation
2	Cancellation	Cancellation and payment

Used in components: [Instrument](#)

#### **180.2.4854 SettledEntityMatrixPublicationDate**

The publication date of the applicable version of the matrix. If not specified, the Standard Terms Supplement defines rules for which version of the matrix is applicable.

Type: [LocalMktDate](#)

Used in components: [Instrument](#)

#### **180.2.4855 SettledEntityMatrixSource**

Relevant settled entity matrix source.

Type: [String](#)

Used in components: [Instrument](#)

#### **180.2.4856 SettlementAmount**

The amount of settlement.

Type: [Amt](#)

Used in groups: [SettlementAmountGrp](#)

**180.2.4857 SettlementAmountCurrency**

The currency of the reported settlement amount.

Type: **Currency**

Used in groups: **SettlementAmountGrp**

**180.2.4858 SettlementAmountCurrencyCodeSource**

Identifies class or source of the SettlementAmountCurrency(1702) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **SettlementAmountGrp**

**180.2.4859 SettlementAmountGrp**

The Settlement Amount Group component block is a repeating group of settlement amounts for an account

Name	Mult.	Type	Description
<b>NoSettlementAmounts</b>	[1..1]	NumInGroup	
<b>SettlementAmount</b>	[0..1]	Amt	Required if NoSettlementAmounts > 0.
<b>SettlementAmountCurrency</b>	[0..1]	Currency	
<b>SettlementAmountCurrencyCodeSource</b>	[0..1]	CodeSet	

Used in messages: [AccountSummaryReport](#)

#### **180.2.4860 SettlementCycleNo**

Settlement cycle in which the settlement obligation was generated

Type: [int](#)

Used in messages: [SettlementObligationReport](#)

#### **180.2.4861 SettleOnOpenFlag**

Indicator to determine if instrument is settle on open

Type: [String](#)

Used in components: [Instrument](#)

#### **180.2.4862 SettlForwardPoints**

FX forward points added to SettlPrice(730). The value is expressed in decimal form and may be a negative.

Type: [PriceOffset](#)

Used in messages: [PositionReport](#)

#### **180.2.4863 SettlInstGrp**

Name	Mult.	Type	Description
<a href="#">NoSettlInst</a>	[1..1]	NumInGroup	Required except where SettlInstMode is 5=Reject SSI request
<a href="#">SettlInstID</a>	[0..1]	String	Unique ID for this settlement instruction. Required except where SettlInstMode is 5=Reject SSI request
<a href="#">SettlInstTransType</a>	[0..1]	CodeSet	New, Replace, Cancel or Restate. Required except where SettlInstMode is 5=Reject SSI request
<a href="#">SettlInstRefID</a>	[0..1]	String	Required where SettlInstTransType is Cancel or Replace

Name	Mult.	Type	Description
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages". Used here for settlement location. Also used for executing broker for CIV settlement instructions
Side	[0..1]	CodeSet	Can be used for SettleInstMode 1 if SSIs are being provided for a particular side.
Product	[0..1]	CodeSet	Can be used for SettleInstMode 1 if SSIs are being provided for a particular product.
SecurityType	[0..1]	CodeSet	Can be used for SettleInstMode 1 if SSIs are being provided for a particular security type (as alternative to CFICode).
CFICode	[0..1]	String	Can be used for SettleInstMode 1 if SSIs are being provided for a particular CFI (as identified by CFI code).
UPICode	[0..1]	String	Can be used for SettleInstMode 1 if SSIs are being provided for a particular UPI (as identified by UPI code).
SettlCurrency	[0..1]	Currency	Can be used for SettleInstMode 1 if SSIs are being provided for a particular settlement currency
SettlCurrencyCodeSource	[0..1]	CodeSet	
EffectiveTime	[0..1]	UTCTimestamp	Effective (start) date/time for this settlement instruction. Required except where SettleInstMode is 5=Reject SSI request
ExpireTime	[0..1]	UTCTimestamp	Termination date/time for this settlement instruction.
LastUpdateTime	[0..1]	UTCTimestamp	Date/time this settlement instruction was last updated (or created if not updated since creation). Required except where SettleInstMode is 5=Reject SSI request
SettleInstructionsData	[0..1]	Component	Insert here the set of "SettleInstructionsData" fields defined in "Common Components of Application Messages"
PaymentMethod	[0..1]	CodeSet	For use with CIV settlement instructions
PaymentRef	[0..1]	String	For use with CIV settlement instructions
CardHolderName	[0..1]	String	For use with CIV settlement instructions
CardNumber	[0..1]	String	For use with CIV settlement instructions
CardStartDate	[0..1]	LocalMktDate	For use with CIV settlement instructions
CardExpDate	[0..1]	LocalMktDate	For use with CIV settlement instructions

Name	Mult.	Type	Description
CardIssNum	[0..1]	String	For use with CIV settlement instructions
PaymentDate	[0..1]	LocalMktDate	For use with CIV settlement instructions
PaymentRemitterID	[0..1]	String	For use with CIV settlement instructions

Used in messages: [SettlementInstructions](#)

### 180.2.4864 SettlInstID

Unique identifier for Settlement Instruction.

Type: [String](#)

Used in groups: [SettlInstGrp](#)

### 180.2.4865 SettlInstMode

Indicates mode used for Settlement Instructions message. \*\*\* SOME VALUES HAVE BEEN REPLACED - See "Replaced Features and Supported Approach" \*\*\*

Type: [char](#)

Allowed values in SettlInstModeCodeSet:

Code	Name	Description
0	Default	Default (Replaced)
1	StandingInstructionsProvided	Standing Instructions Provided
2	SpecificAllocationAccountOverriding	Specific Allocation Account Overriding (Replaced)
3	SpecificAllocationAccountStanding	Specific Allocation Account Standing (Replaced)
4	SpecificOrderForASingleAccount	Specific Order for a single account (for CIV)
5	RequestReject	Request reject

Used in groups: [ListOrdGrp](#)

Used in messages: [SettlementInstructions](#)

**180.2.4866 SettlInstMsgID**

Unique identifier for Settlement Instruction message.

Type: **String**

Used in messages: **SettlementInstructions**

**180.2.4867 SettlInstRefID**

Reference identifier for the SettlInstID (162) with Cancel and Replace SettlInstTransType (163) transaction types.

Type: **String**

Used in groups: **SettlInstGrp**

**180.2.4868 SettlInstReqID**

Unique ID of settlement instruction request message

Type: **String**

Used in messages: **SettlementInstructionRequest**, **SettlementInstructions**

**180.2.4869 SettlInstReqRejCode**

Identifies reason for rejection (of a settlement instruction request message).

Type: **int**

Allowed values in SettlInstReqRejCodeCodeSet:

Code	Name	Description
0	UnableToProcessRequest	Unable to process request
1	UnknownAccount	Unknown account
2	NoMatchingSettlementInstructions-Found	No matching settlement instructions found
99	Other	Other

Used in messages: **SettlementInstructions**

**180.2.4870 SettlInstructionsData**

The SettlInstructionsData component block is used to convey key information regarding standing settlement and delivery instructions. It also provides a reference to standing settlement details regarding the source, delivery instructions, and settlement parties

Name	Mult.	Type	Description
SettlDeliveryType	[0..1]	CodeSet	Required if AllocSettlInstType = 1 or 2
StandInstDbType	[0..1]	CodeSet	Required if AllocSettlInstType = 3 (should not be populated otherwise)
StandInstDbName	[0..1]	String	Required if AllocSettlInstType = 3 (should not be populated otherwise)
StandInstDbID	[0..1]	String	Identifier used within the StandInstDbType. Required if AllocSettlInstType = 3 (should not be populated otherwise)
DlvInstGrp	[0..*]	Group	Required (and must be > 0) if AllocSettlInstType = 2 (should not be populated otherwise)

Used in components: [SettlTradeDetails](#)

Used in groups: [AllocGrp](#), [SettlInstGrp](#)

Used in messages: [CollateralAssignment](#), [CollateralInquiry](#), [CollateralReport](#), [Confirmation](#)

**180.2.4871 SettlInstSource**

Indicates source of Settlement Instructions

Type: [char](#)

Allowed values in SettlInstSourceCodeSet:

Code	Name	Description
1	BrokerCredit	Broker's Instructions
2	Institution	Institution's Instructions
3	Investor	Investor (e.g. CIV use)

Used in groups: [DlvInstGrp](#)



**180.2.4872 SettlInstTransType**

Settlement Instructions message transaction type

Type: **char**

Allowed values in SettlInstTransTypeCodeSet:

Code	Name	Description
N	New	New
C	Cancel	Cancel
R	Replace	Replace
T	Restate	Restate

Used in groups: **SettlInstGrp**

**180.2.4873 SettlMethod**

Settlement method for a contract or instrument. Additional values may be used with bilateral agreement.

Type: **String**

Allowed values in SettlMethodCodeSet:

Code	Name	Description
C	CashSettlementRequired	Cash settlement required
P	PhysicalSettlementRequired	Physical settlement required
E	Election	Election at exercise. The settlement method will be elected at the time of contract exercise.

Used in components: **Instrument**

**180.2.4874 SettlMethodElectingPartySide**

Side value of the party electing the settlement method.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in components: [OptionExercise](#)

### 180.2.4875 **SettlMethodElectionDateAdjusted**

The adjusted settlement method election date.

Type: [LocalMktDate](#)

Used in components: [SettlMethodElectionDate](#)

### 180.2.4876 **SettlMethodElectionDateBusinessCenter**

The business center calendar used for date adjustment of the settlement method election unadjusted or relative date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [SettlMethodElectionDateBusinessCenterGrp](#)

### 180.2.4877 **SettlMethodElectionDateBusinessCenterGrp**

SettlMethodElectionDateBusinessCenterGrp is a repeating subcomponent within the SettlMethodElectionDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
<a href="#">NoSettlMethodElectionDateBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">SettlMethodElectionDateBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoSettlMethodElectionDateBusinessCenters</a> (42775) > 0.

Used in components: [SettlMethodElectionDate](#)

**180.2.4878 SettlMethodElectionDateBusinessDayConvention**

The settlement method election date adjustment business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **SettlMethodElectionDate**

**180.2.4879 SettlMethodElectionDate**

The SettlMethodElectionDate component is a subcomponent within the OptionExercise component used to report the settlement method election date.

Name	Mult.	Type	Description
<b>SettlMethodElectionDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>SettlMethodElectionDateBusinessDay-Convention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to OptionExercise.
<b>SettlMethodElectionDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to OptionExercise.
<b>SettlMethodElectionDateRelativeTo</b>	[0..1]	int	
<b>SettlMethodElectionDateOffsetPeriod</b>	[0..1]	int	Conditionally required when SettlMethodElectionDateOffsetUnit(42781) is specified.

Name	Mult.	Type	Description
SettlMethodElectionDateOffsetUnit	[0..1]	CodeSet	Conditionally required when SettlMethodElectionDateOffsetPeriod(42780) is specified.
SettlMethodElectionDateOffsetDay-Type	[0..1]	CodeSet	
SettlMethodElectionDateAdjusted	[0..1]	LocalMktDate	

Used in components: [OptionExercise](#)

### 180.2.4880 SettlMethodElectionDateOffsetDayType

Specifies the day type of the relative settlement method election date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [SettlMethodElectionDate](#)

### 180.2.4881 SettlMethodElectionDateOffsetPeriod

Time unit multiplier for the relative settlement method election date offset.

Type: [int](#)

Used in components: [SettlMethodElectionDate](#)

**180.2.4882 SettlMethodElectionDateOffsetUnit**

Time unit associated with the relative settlement method election date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **SettlMethodElectionDate**

**180.2.4883 SettlMethodElectionDateRelativeTo**

Specifies the anchor date when the settlement method election date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **SettlMethodElectionDate**

**180.2.4884 SettlMethodElectionDateUnadjusted**

The unadjusted settlement method election date.

Type: **LocalMktDate**

Used in components: **SettlMethodElectionDate**

**180.2.4885 SettlObligationInstructions**

Name	Mult.	Type	Description
<b>NoSettlOblig</b>	[1..1]	NumInGroup	Number of Settlement Obligations
<b>NetGrossInd</b>	[0..1]	CodeSet	

Name	Mult.	Type	Description
SettlObligID	[0..1]	String	Unique ID for this settlement instruction
SettlObligTransType	[0..1]	CodeSet	New, Replace, Cancel, or Restate
SettlObligRefID	[0..1]	String	Required where SettlObligTransType(1162) is Cancel or Replace. The SettlObligID(1161) of the settlement obligation being canceled or replaced.
CcyAmt	[0..1]	Amt	Net flow of currency 1
SettlCurrAmt	[0..1]	Amt	Net flow of currency 2
Currency	[0..1]	Currency	Currency 1 in the stated currency pair, the dealt currency
CurrencyCodeSource	[0..1]	CodeSet	
SettlCurrency	[0..1]	Currency	Currency 2 in the stated currency pair, the contra currency
SettlCurrencyCodeSource	[0..1]	CodeSet	
SettlCurrFxRate	[0..1]	float	Derived rate of Ccy2 per Ccy1 based on netting
SettlDate	[0..1]	LocalMktDate	Value Date
Instrument	[0..1]	Component	Used to express the instrument in which settlement is taking place
Parties	[0..*]	Group	
EffectiveTime	[0..1]	UTCTimestamp	Effective (start) date/time for this settlement instruction
ExpireTime	[0..1]	UTCTimestamp	Termination date/time for this settlement instruction.
LastUpdateTime	[0..1]	UTCTimestamp	Date/time this settlement instruction was last updated (or created if not updated since creation).
SettlDetails	[0..*]	Group	Conveys settlement account details reported as part of obligation

Used in messages: **SettlementObligationReport**

### 180.2.4886 SettlObligID

Unique ID for this settlement instruction.

Type: **String**

Used in groups: **SettlObligationInstructions**

**180.2.4887 SettlObligMode**

Used to identify the reporting mode of the settlement obligation which is either preliminary or final

Type: **int**

Allowed values in SettlObligModeCodeSet:

Code	Name	Description
1	Preliminary	Preliminary
2	Final	Final

Used in messages: **SettlementObligationReport**

**180.2.4888 SettlObligMsgID**

Message identifier for Settlement Obligation Report

Type: **String**

Used in messages: **SettlementObligationReport**

**180.2.4889 SettlObligRefID**

Required where SettlInstTransType is Cancel or Replace

Type: **String**

Used in groups: **SettlObligationInstructions**

**180.2.4890 SettlObligSource**

Used to identify whether these delivery instructions are for the buyside or the sellside.

Type: **char**

Allowed values in SettlObligSourceCodeSet:

Code	Name	Description
1	InstructionsOfBroker	Instructions of Broker
2	InstructionsForInstitution	Instructions for Institution

Code	Name	Description
3	Investor	Investor
4	BuyersSettlementInstructions	Buyer's settlement instructions
5	SellersSettlementInstructions	Seller's settlement instructions

Used in groups: [SettlDetails](#)

### 180.2.4891 SettlObligTransType

Transaction Type - required except where SettlInstMode is 5=Reject SSI request

Type: [char](#)

Allowed values in SettlObligTransTypeCodeSet:

Code	Name	Description
C	Cancel	Cancel
N	New	New
R	Replace	Replace
T	Restate	Restate

Used in groups: [SettlObligationInstructions](#)

### 180.2.4892 SettlParties

The SettlParties component block is used in a similar manner as Parties Block within the context of settlement instruction messages to distinguish between parties involved in the settlement and parties who are expected to execute the settlement process.

Name	Mult.	Type	Description
<a href="#">NoSettlPartyIDs</a>	[1..1]	NumInGroup	Repeating group below should contain unique combinations of SettlPartyID, SettlPartyIDSource, and SettlPartyRole
<a href="#">SettlPartyID</a>	[0..1]	String	Used to identify source of SettlPartyID. Required if SettlPartyIDSource is specified. Required if NoSettlPartyIDs > 0.



Name	Mult.	Type	Description
SettlPartyIDSource	[0..1]	CodeSet	Used to identify class source of SettlPartyID value (e.g. BIC). Required if SettlPartyID is specified. Required if NoSettlPartyIDs > 0.
SettlPartyRole	[0..1]	CodeSet	Identifies the type of SettlPartyID (e.g. Executing Broker). Required if NoSettlPartyIDs > 0.
SettlPartyRoleQualifier	[0..1]	CodeSet	
SettlPtysSubGrp	[0..*]	Group	Repeating group of SettlParty sub-identifiers.

Used in groups: [DlvInstGrp](#), [SettlDetails](#)

### 180.2.4893 SettlPartyID

PartyID value within a settlement parties component. Nested repeating group.

Same values as PartyID (448)

Type: [String](#)

Used in groups: [SettlParties](#)

### 180.2.4894 SettlPartyIDSource

PartyIDSource value within a settlement parties component.

Same values as PartyIDSource (447)

Type: [char](#)

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")

Code	Name	Description
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".

Code	Name	Description
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **SettlParties**

### 180.2.4895 SettlPartyRole

PartyRole value within a settlement parties component.

Same values as PartyRole (452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm

Code	Name	Description
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.

Code	Name	Description
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)

Code	Name	Description
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm

Code	Name	Description
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)

Code	Name	Description
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **SettlParties**

### 180.2.4896 SettlPartyRoleQualifier

Used to further qualify the value of SettlPartyRole(784).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal



Code	Name	Description
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.

Code	Name	Description
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **SettlParties**

#### **180.2.4897 SettlPartySubID**

PartySubID value within a settlement parties component.

Same values as PartySubID (523)

Type: **String**

Used in groups: **SettlPtysSubGrp**

#### **180.2.4898 SettlPartySubIDType**

Type of SettlPartySubID (785) value.

Same values as PartySubIDType (803)

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier

Code	Name	Description
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account

Code	Name	Description
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **SettlPtysSubGrp**



**180.2.4899 SettlPrice**

Settlement price

Type: **Price**

Used in messages: **AdjustedPositionReport**, **AssignmentReport**, **PositionReport**, **SecurityStatus**

**180.2.4900 SettlPriceDeterminationMethod**

Calculation method used to determine settlement price.

Type: **int**

Allowed values in SettlPriceDeterminationMethodCodeSet:

Code	Name	Description
0	Unknown	Unknown
1	LastTradePrice	Last trade price
2	LastBidPrice	Last bid price
3	LastOfferPrice	Last offer price
4	MidPrice	Mid price. The price at the mid-point between last bid and last offer price.
5	AverageLastTradePrice	Average last trade price. The average price across a bi-laterally agreed number of trades, e.g. last five trades.
6	AverageLastTradePeriod	Average last trade period. Average price across bi-laterally agreed time period, e.g. last minute of trading.
7	UnderlyingPrice	Underlying price. Based on price of underlying instrument.
8	CalculatedPrice	Calculated price. Other calculation method, e.g. theoretical price.
9	ManualPrice	Manual price. Manually entered price.

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **SecurityStatus**

**180.2.4901 SettlPriceFxRateCalc**

Specifies whether LastPx(31) **TradeCaptureReport** or SettlPrice(730) **PositionReport** should be multiplied or divided.

Type: **char**

Allowed values in SettlCurrFxRateCalcCodeSet:

Code	Name	Description
M	Multiply	Multiply
D	Divide	Divide

Used in messages: **PositionReport**, **TradeCaptureReport**

#### **180.2.4902 SettlPriceIncrement**

Settlement price increment for stated price range.

Type: **Price**

Used in groups: **TickRules**

#### **180.2.4903 SettlPriceSecondaryIncrement**

Secondary settlement price increment for stated price range. The meaning of secondary is left to bilateral agreement, e.g. it may refer to final settlement for a contract.

Type: **Price**

Used in groups: **TickRules**

#### **180.2.4904 SettlPriceType**

Type of settlement price

Type: **int**

Allowed values in SettlPriceTypeCodeSet:

Code	Name	Description
1	Final	Final
2	Theoretical	Theoretical

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **AssignmentReport**, **PositionReport**, **SecurityStatus**

**180.2.4905 SettlPriceUnitOfMeasure**

Used to express the unit of measure of the settlement price if different from the contract.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in messages: **PositionReport**

#### **180.2.4906 SettlPriceUnitOfMeasureCurrency**

Indicates the currency of the settlement price unit of measure if expressed in another currency than the base currency.

Conditionally required when SettlPriceUnitOfMeasure(1886)=Ccy.

Type: **Currency**

Used in messages: **PositionReport**

**180.2.4907 SettlPriceUnitOfMeasureCurrencyCodeSource**

Identifies the class or source of the SettlPriceUnitOfMeasureCurrency(1887) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in messages: **PositionReport**

**180.2.4908 SettlPtysSubGrp**

Name	Mult.	Type	Description
NoSettlPartySubIDs	[1..1]	NumInGroup	
SettlPartySubID	[0..1]	String	
SettlPartySubIDType	[0..1]	CodeSet	

Used in groups: **SettlParties**

**180.2.4909 SettlRateDisruptionFallbackGrp**

The SettlRateDisruptionsFallbackGrp is a repeating subcomponent of the PaymentStreamNonDeliverableSettlTermGrp component used to specify the method, prioritized by the order it is listed, to get a replacement rate for a disrupted settlement rate option for a non-deliverable settlement currency.

Name	Mult.	Type	Description
NoSettlRateFallbacks	[1..1]	NumInGroup	
SettlRatePostponementMaximumDays	[0..1]	int	Required if NoSettlRateFallbacks(40085) > 0.
SettlRateFallbackRateSource	[0..1]	Component	
SettlRatePostponementSurvey	[0..1]	Boolean	
SettlRatePostponementCalculationAgent	[0..1]	CodeSet	

Used in components: **PaymentStreamNonDeliverableSettlTerms**

### 180.2.4910 SettlRateFallbackRateSource

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in components: **SettlRateFallbackRateSource**

### 180.2.4911 SettlRateFallbackRateSource

SettlRateFallbackRateSource is a subcomponent of the SettlRateDisruptionFallbackGrp component used to specify the rate source in the event of rate disruption fallback.

Name	Mult.	Type	Description
SettlRateFallbackRateSource	[0..1]	CodeSet	
SettlRateFallbackReferencePage	[0..1]	String	Conditionally required when SettlRateFallbackRateSource(40373) = 3 (ISDA Settlement Rate Option) or 99 (Other).

Used in groups: **SettlRateDisruptionFallbackGrp**

#### **180.2.4912 SettlRateFallbackReferencePage**

Identifies the reference "page" from the rate source.

When SettlRateFallbackRateSource(40373) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in components: **SettlRateFallbackRateSource**

#### **180.2.4913 SettlRateIndex**

In an outright or forward commodity trade that is cash settled this is the index used to determine the cash payment.

Type: **String**

Used in components: **Instrument**

#### **180.2.4914 SettlRateIndexLocation**

This is an optional qualifying attribute of SettlRateIndex(1577) such as the delivery zone for an electricity contract.

Type: **String**

Used in components: **Instrument**



**180.2.4915 SettlRatePostponementCalculationAgent**

Used to identify the settlement rate postponement calculation agent.

Type: **int**

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreement	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

Used in groups: **SettlRateDisruptionFallbackGrp**

**180.2.4916 SettlRatePostponementMaximumDays**

The maximum number of days to wait for a quote from the disrupted settlement rate option before proceeding to this method.

Type: **int**

Used in groups: **SettlRateDisruptionFallbackGrp**

**180.2.4917 SettlRatePostponementSurvey**

Indicates whether to request a settlement rate quote from the market.

Type: **Boolean**

Used in groups: **SettlRateDisruptionFallbackGrp**

**180.2.4918 SettlSessID**

Identifies a specific settlement session

Type: **String**

Allowed values in SettlSessIDCodeSet:

Code	Name	Description
ITD	Intraday	Intraday
RTH	RegularTradingHours	Regular Trading Hours
ETH	ElectronicTradingHours	Electronic Trading Hours
EOD	EndOfDay	End Of Day

Used in messages: [AccountSummaryReport](#), [AdjustedPositionReport](#), [AssignmentReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [MarginRequirementInquiry](#), [MarginRequirementInquiryAck](#), [MarginRequirementReport](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [PositionReport](#), [RequestForPositions](#), [RequestForPositionsAck](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.4919 SettlSessSubID**

SubID value associated with SettlSessID(716)

Type: [String](#)

Used in messages: [AccountSummaryReport](#), [AssignmentReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [MarginRequirementInquiry](#), [MarginRequirementInquiryAck](#), [MarginRequirementReport](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [PositionReport](#), [RequestForPositions](#), [RequestForPositionsAck](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.4920 SettlStatus**

The settlement status of the identified trade.

Type: [String](#)

Used in messages: [SettlementStatusReport](#)

#### **180.2.4921 SettlStatusReason**

Used to provide additional reason or qualify the reason for the settlement status specified in SettlStatus(2968).

Type: [String](#)

Used in messages: [SettlementStatusReport](#)

**180.2.4922 SettlStatusReasonText**

Text description associated with SettlStatusReason(2969).

Type: **String**

Used in messages: **SettlementStatusReport**

**180.2.4923 SettlStatusReportID**

Unique identifier of the SettlementStatusReport(35=EE).

Type: **String**

Used in messages: **SettlementStatusReport**, **SettlementStatusReportAck**

**180.2.4924 SettlStatusReportStatus**

Status of the report being responded to.

Type: **int**

Allowed values in SettlStatusReportStatusCodeSet:

---

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected. Rejection reason provided in RejectText(1328).

---

Used in messages: **SettlementStatusReportAck**

**180.2.4925 SettlStatusRequestID**

Unique identifier of the SettlementStatusRequest(35=EC).

Type: **String**

Used in messages: **SettlementStatusReport**, **SettlementStatusRequest**, **SettlementStatusRequestAck**

**180.2.4926 SettlStatusRequestStatus**

Status of the SettlementStatusRequest(35=EC) message being responded to.

Type: **int**

Allowed values in SettlStatusRequestStatusCodeSet:

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected. Rejection reason provided in RejectText(1328).

Used in messages: **SettlementStatusRequestAck**

**180.2.4927 SettlSubMethod**

Specifies a suitable settlement sub-method for a given settlement method.

Type: **int**

Allowed values in SettlSubMethodCodeSet:

Code	Name	Description
1	Shares	Shares.
2	Derivatives	Derivatives.
3	PaymentVsPayment	Payment vs payment.
4	Notional	Notional.
5	Cascade	Cascade.
6	Repurchase	Repurchase.
99	Other	Other.

Used in components: **Instrument**

**180.2.4928 SettlTradeDetails**

SettlTradeDetails component is used to provide the details which can be used to look up a single trade.

Name	Mult.	Type	Description
ConfirmID	[0..1]	String	May be used to identify the trade via the known Confirmation(35=AK) message.
AllocID	[0..1]	String	May be used to identify the trade via the known AllocationInstruction(35=J) message.
IndividualAllocID	[0..1]	String	May be used to identify the trade via a specific allocated account instance of an AllocationInstruction(35=J) this IndividualAllocID(467) is part of. If specified AllocID(70) should be specified.
SecondaryAllocID	[0..1]	String	May be used to identify the trade via a specific allocated account instance of an AllocationInstruction(35=J) this SecondaryAllocID(793) is part of. If specified AllocID(70) should be specified.
AllocAccount	[0..1]	String	
TradeDate	[0..1]	LocalMktDate	
Instrument	[0..1]	Component	
AllocQty	[0..1]	Qty	
Side	[0..1]	CodeSet	
AvgPx	[0..1]	Price	
PriceType	[0..1]	CodeSet	
AvgParPx	[0..1]	Price	
GrossTradeAmt	[0..1]	Amt	
NetMoney	[0..1]	Amt	
Currency	[0..1]	Currency	
CurrencyCodeSource	[0..1]	CodeSet	
QtyType	[0..1]	CodeSet	
NestedParties	[0..*]	Group	
SettlDate	[0..1]	LocalMktDate	
SettlCurrAmt	[0..1]	Amt	
SettlCurrency	[0..1]	Currency	
SettlCurrencyCodeSource	[0..1]	CodeSet	
SettlInstructionsData	[0..1]	Component	

Used in messages: [SettlementStatusReport](#), [SettlementStatusRequest](#)

**180.2.4929 SettlType**

Indicates order settlement period. If present, SettlDate (64) overrides this field. If both SettlType (63) and SettlDate (64) are omitted, the default for SettlType (63) is 0 (Regular)

Regular is defined as the default settlement period for the particular security on the exchange of execution.

In Fixed Income the contents of this field may influence the instrument definition if the SecurityID (48) is ambiguous. In the US an active Treasury offering may be re-opened, and for a time one CUSIP will apply to both the current and "when-issued" securities. Supplying a value of "7" clarifies the instrument description; any other value or the absence of this field should cause the respondent to default to the active issue.

Additionally the following patterns may be used as well as enum values

Dx = FX tenor expression for "days", e.g. "D5", where "x" is any integer > 0

Mx = FX tenor expression for "months", e.g. "M3", where "x" is any integer > 0

Wx = FX tenor expression for "weeks", e.g. "W13", where "x" is any integer > 0

Yx = FX tenor expression for "years", e.g. "Y1", where "x" is any integer > 0

Noted that for FX the tenors expressed using Dx, Mx, Wx, and Yx values do not denote business days, but calendar days.

Type: **String**

Allowed values in SettlTypeCodeSet:

Code	Name	Description
0	Regular	Regular / FX Spot settlement (T+1 or T+2 depending on currency)
1	Cash	Cash (TOD / T+0)
2	NextDay	Next Day (TOM / T+1)
3	TPlus2	T+2
4	TPlus3	T+3
5	TPlus4	T+4
6	Future	Future
7	WhenAndIfIssued	When And If Issued
8	SellersOption	Sellers Option
9	TPlus5	T+5

Code	Name	Description
B	BrokenDate	Broken date. Use within FX to specify a non-standard tenor. The use of SettlDate(64) is required to specify the actual settlement date when SettlType(63) = B (Broken date).
C	FXSpotNextSettlement	FX Spot Next settlement (Spot+1, aka next day)

Used in groups: [BidCompReqGrp](#), [BidCompRspGrp](#), [InstrmtMDReqGrp](#), [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [StrmAsgnReqInstrmtGrp](#), [StrmAsgnRptInstrmtGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#), [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.4930 SharedCommission**

Commission to be shared with a third party, e.g. as part of a directed brokerage commission sharing arrangement.

Type: [Amt](#)

Used in messages: [Confirmation](#)

#### **180.2.4931 ShortMarkingExemptIndicator**

Indicates whether the originating account is exempt (Y) from marking orders as short or not (N). This designation may be used on both buy and sell orders.

Type: [Boolean](#)

Used in groups: [ListOrdGrp](#), [SideCrossOrdModGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

#### **180.2.4932 ShortQty**

Short quantity.

Type: [Qty](#)

Used in groups: [PositionQty](#), [TradePositionQty](#)

**180.2.4933 ShortSaleExemptionReason**

Indicates the reason a short sale order is exempted from applicable regulation (e.g. Reg SHO addendum (b)(1) in the U.S.).

Type: **int**

Allowed values in ShortSaleExemptionReasonCodeSet:

Code	Name	Description
0	ExemptionReasonUnknown	Exemption reason unknown. An exemption reason not provided or received.
1	IncomingSSE	Income sell short exempt. Agency broker has the customer's exemption reason, which is not explicitly provided to executing broker.
2	AboveNationalBestBid	Above national best bid (broker/dealer provision). Broker / dealer responsible for enforcing exemption rule has determined that the order is priced one or more ticks above the nation best bid of the security to be traded.
3	DelayedDelivery	Delayed delivery. The broker-dealer has a reasonable basis to believe the seller owns the covered security (pursuant to Rule 200 in the U.S.), but is subject to restrictions on delivery, provided that the seller intends to deliver the security as soon as all restrictions on delivery have been removed.
4	OddLot	Odd lot. The broker-dealer has a reasonable basis to believe the sale is by a market maker to offset customer odd-lot orders or to liquidate an odd-lot position that changes such broker's or dealer's position by no more than a unit of trading.
5	DomesticArbitrage	Domestic arbitrage. The sale is connected to a bona-fide domestic arbitrage transaction.
6	InternationalArbitrage	International arbitrage. The sale is connected to an international arbitrage transaction.
7	UnderwriterOrSyndicateDistribution	Underwriter or syndicate distribution. The short sale is (i) by an underwriter or member of a syndicate or group participating in the distribution of a security in connection with an over-allotment of securities; or (ii) is for purposes of a lay-off sale by an underwriter or member of a syndicate or group in connection with a distribution of securities through a rights or standby underwriting commitment.
8	RisklessPrincipal	Riskless principal. The short sale is by a broker or dealer effecting the execution of a customer purchase or the execution of a customer "long" sale on a riskless principal basis.



Code	Name	Description
9	VWAP	VWAP. The short sale order is for the sale of a covered security at the volume weighted average price (VWAP) meeting certain criteria.

Used in groups: [ListOrdGrp](#)

Used in messages: [ExecutionReport](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.4934 ShortSaleReason

Reason for short sale.

Type: [int](#)

Allowed values in ShortSaleReasonCodeSet:

Code	Name	Description
0	DealerSoldShort	Dealer Sold Short
1	DealerSoldShortExempt	Dealer Sold Short Exempt
2	SellingCustomerSoldShort	Selling Customer Sold Short
3	SellingCustomerSoldShortExempt	Selling Customer Sold Short Exempt
4	QualifiedServiceRepresentative	Qualified Service Representative (QSR) or Automatic Give-up (AGU) Contra Side Sold Short
5	QSRorAGUContraSideSoldShortExempt	QSR or AGU Contra Side Sold Short Exempt

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.4935 ShortSaleRestriction

Indicates whether a restriction applies to short selling a security.

Type: [int](#)

Allowed values in ShortSaleRestrictionCodeSet:

Code	Name	Description
0	NoRestrictions	No restrictions
1	SecurityNotShortable	Security is not shortable
2	SecurityNotShortableAtOrBelowBestBid	Security not shortable at or below the best bid
3	SecurityNotShortableWithoutPre-Borrow	Security is not shortable without pre-borrow

Used in components: **Instrument**

### 180.2.4936 Side

Side of order (see Volume : "Glossary" for value definitions)

Type: **char**

Allowed values in SideCodeSet:

Code	Name	Description
1	Buy	Buy. For Securities Financing indicates the receipt of securities or collateral.
2	Sell	Sell. For Securities Financing indicates the delivery of securities or collateral.
3	BuyMinus	Buy minus
4	SellPlus	Sell plus
5	SellShort	Sell short
6	SellShortExempt	Sell short exempt
7	Undisclosed	Undisclosed
8	Cross	Cross (orders where counterparty is an exchange, valid for all messages except IOIs)
9	CrossShort	Cross short
A	CrossShortExempt	Cross short exempt
B	AsDefined	"As Defined" (for use with multileg instruments)
C	Opposite	"Opposite" (for use with multileg instruments)
D	Subscribe	Subscribe (e.g. CIV)
E	Redeem	Redeem (e.g. CIV)
F	Lend	Lend (FINANCING - identifies direction of collateral)

Code	Name	Description
G	Borrow	Borrow (FINANCING - identifies direction of collateral)
H	SellUndisclosed	Sell undisclosed. In the context of ESMA RTS 22, this allows for reporting of transactions where the investment firm (broker) is not able to determine whether the sell is a short sale transaction. Corresponds to RTS 22 "short selling indicator" value of 'UNDI'.

Used in components: [MDStatisticParameters](#), [SettlTradeDetails](#)

Used in groups: [BidCompReqGrp](#), [BidCompRspGrp](#), [InstrmtStrkPxGrp](#), [ListOrdGrp](#), [OrderEntryAckGrp](#), [OrderEntryGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [SettlInstGrp](#), [SideCrossOrdCxlGrp](#), [SideCrossOrdModGrp](#), [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [Confirmation](#), [DontKnowTrade](#), [ExecutionAck](#), [ExecutionReport](#), [IOI](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [OrderMassActionReport](#), [OrderMassActionRequest](#), [OrderMassCancelReport](#), [OrderMassCancelRequest](#), [OrderMassStatusRequest](#), [OrderStatusRequest](#), [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [SettlementInstructionRequest](#), [TradeAggregationReport](#), [TradeAggregationRequest](#), [TradeCaptureReportRequest](#)

### 180.2.4937 SideAvgPx

Calculated average price for this side of the trade.

Type: [Price](#)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

### 180.2.4938 SideAvgPxGroupID

The identifier for the average price group for the trade side. See also [AvgPxGroupID\(1731\)](#).

Type: [String](#)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

**180.2.4939 SideAvgPxIndicator**

Used to indicate whether a trade or a sub-allocation should be allocated at the trade price (e.g. no average pricing), or whether it should be grouped with other trades/sub-allocations and allocated at the average price of the group.

Type: **int**

Allowed values in AvgPxIndicatorCodeSet:

Code	Name	Description
0	NoAveragePricing	No average pricing
1	Trade	Trade is part of an average price group identified by the AvgPxGroupID(1731)
2	LastTrade	Last trade of the average price group identified by the AvgPxGroupID(1731)
3	NotionalValueAveragePxGroupTrade	Trade is part of a notional value average price group. A notional value average price (NVAP) group is effectively closed and available for allocation as long as the NVAP of the group is non-zero.
4	AveragePricedTrade	Trade is average priced

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

**180.2.4940 SideClearingTradePrice**

Alternate clearing price for the side being reported.

Type: **Price**

Used in groups: **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.4941 SideClearingTradePriceType**

Indicates to recipient whether trade is clearing at execution prices LastPx(tag 31) or alternate clearing prices SideClearingTradePrice(tag 1597).

Type: **int**

Allowed values in SideClearingTradePriceTypeCodeSet:

Code	Name	Description
0	TradeClearingAtExecutionPrice	Trade Clearing at Execution Price
1	TradeClearingAtAlternateClearing- Price	Trade Clearing at Alternate Clearing Price

Used in groups: [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

### 180.2.4942 SideCollateralAmountGrp

The SideCollateralAmountGrp component block is a repeating group that provides the current value of the collateral type on deposit for a side of the trade report. The currency of the collateral value may be optionally included.

Name	Mult.	Type	Description
<a href="#">NoSideCollateralAmounts</a>	[1..1]	NumInGroup	
<a href="#">SideCurrentCollateralAmount</a>	[0..1]	Amt	Required if NoSideCollateralAmounts(2691) > 0.
<a href="#">SideCollateralCurrency</a>	[0..1]	Currency	Can be used to specify the currency of SideCollateralAmount(2702) if Currency(15) is not specified or is not the same.
<a href="#">SideCollateralCurrencyCodeSource</a>	[0..1]	CodeSet	
<a href="#">SideCollateralAmountType</a>	[0..1]	CodeSet	
<a href="#">SideCollateralFXRate</a>	[0..1]	float	
<a href="#">SideCollateralFXRateCalc</a>	[0..1]	CodeSet	
<a href="#">SideCollateralType</a>	[0..1]	String	
<a href="#">SideCollateralAmountMarketSegmentID</a>	[0..1]	String	
<a href="#">SideCollateralAmountMarketID</a>	[0..1]	String	
<a href="#">SideHaircutIndicator</a>	[0..1]	Boolean	
<a href="#">SideCollateralPortfolioID</a>	[0..1]	String	
<a href="#">SideCollateralPercentOverage</a>	[0..1]	Percentage	
<a href="#">SideCollateralMarketPrice</a>	[0..1]	Price	
<a href="#">SideCollateralReinvestmentRate</a>	[0..1]	Percentage	When multiple instances of the SideCollateralReinvestmentGrp component are present this field specifies the average reinvestment rate.
<a href="#">SideCollateralReinvestmentGrp</a>	[0..*]	Group	

Name	Mult.	Type	Description
SideUnderlyingRefID	[0..1]	String	May be used to indicate that this entry applies to the underlying collateral instrument being referenced by the value in UnderlyingID(2874).

Used in groups: TrdCapRptSideGrp

#### 180.2.4943 SideCollateralAmountMarketID

Market associated with the collateral amount.

Type: String

Used in groups: SideCollateralAmountGrp

#### 180.2.4944 SideCollateralAmountMarketSegmentID

Market segment associated with the collateral amount.

Type: String

Used in groups: SideCollateralAmountGrp

#### 180.2.4945 SideCollateralAmountType

The type of value in CurrentCollateralAmount(1704).

Type: int

Allowed values in CollateralAmountTypeCodeSet:

Code	Name	Description
0	MarketValuation	Market valuation (the default)
1	PortfolioValue	Portfolio value before processing pledge request
2	ValueConfirmed	Value confirmed as "locked-up" for processing a pledge request
3	CollateralCreditValue	Credit value of collateral at CCP processing a pledge request
4	AdditionalCollateralValue	Additional collateral value. Additional collateral deposited by the collateral provider at trade or post-trade. CollateralPercentOverage(2690) gives the overage percent

Code	Name	Description
5	EstimatedMarketValuation	Estimated market valuation. Estimated market valuation of collateral. In the context of EU SFTR this may be used for value of re-use of collateral.

Used in groups: [SideCollateralAmountGrp](#)

#### 180.2.4946 SideCollateralCurrency

Specifies the currency of the collateral; optional, defaults to settlement currency if not specified.

SideCollateralCurrencyCodeSource(2930) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: [Currency](#)

Used in groups: [SideCollateralAmountGrp](#)

#### 180.2.4947 SideCollateralCurrencyCodeSource

Identifies class or source of the SideCollateralCurrency(2695) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [SideCollateralAmountGrp](#)

**180.2.4948 SideCollateralFXRate**

Foreign exchange rate used to compute the SideCurrentCollateralAmount(2702) from the SideCollateralCurrency(2695) and the Currency(15).

Type: **float**

Used in groups: **SideCollateralAmountGrp**

**180.2.4949 SideCollateralFXRateCalc**

Specifies whether or not SideCollateralFXRate(2696) should be multiplied or divided.

Type: **char**

Allowed values in UnderlyingFXRateCalcCodeSet:

Code	Name	Description
D	Divide	Divide
M	Multiply	Multiply

Used in groups: **SideCollateralAmountGrp**

**180.2.4950 SideCollateralMarketPrice**

Market price of the collateral, either from market sources or pre-agreed by the counterparties.

Type: **Price**

Used in groups: **SideCollateralAmountGrp**

**180.2.4951 SideCollateralPercentOverage**

Percentage of over-collateralization particularly when SideCollateralAmountType(2694) = 4 (Additional collateral value).

Type: **Percentage**

Used in groups: **SideCollateralAmountGrp**



**180.2.4952 SideCollateralPortfolioID**

Identifier of the collateral portfolio when reporting on a portfolio basis.

Type: **String**

Used in groups: **SideCollateralAmountGrp**

**180.2.4953 SideCollateralReinvestmentAmount**

The cash amount of the specified re-investment type.

Type: **Amt**

Used in groups: **SideCollateralReinvestmentGrp**

**180.2.4954 SideCollateralReinvestmentCurrency**

The currency denomination of the re-invested cash amount.

SideCollateralReinvestmentCurrencyCodeSource(2932) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **SideCollateralReinvestmentGrp**

**180.2.4955 SideCollateralReinvestmentCurrencyCodeSource**

Identifies class or source of the SideCollateralReinvestmentCurrency(2866) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".

Code	Name	Description
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [SideCollateralReinvestmentGrp](#)

### 180.2.4956 SideCollateralReinvestmentGrp

The SideCollateralReinvestmentGrp component block is a repeating group that may be used to provide a breakdown of the cash collateral's reinvestment types and amounts (e.g. SideCollateralType(2701)="CASH").

Name	Mult.	Type	Description
<a href="#">NoSideCollateralReinvestments</a>	[1..1]	NumInGroup	
<a href="#">SideCollateralReinvestmentType</a>	[0..1]	CodeSet	Required if NoSideCollateralReinvestments(2864) > 0.
<a href="#">SideCollateralReinvestmentAmount</a>	[0..1]	Amt	
<a href="#">SideCollateralReinvestmentCurrency</a>	[0..1]	Currency	
<a href="#">SideCollateralReinvestmentCurrency-CodeSource</a>	[0..1]	CodeSet	

Used in groups: [SideCollateralAmountGrp](#)

### 180.2.4957 SideCollateralReinvestmentRate

Interest rate received for collateral reinvestment.

Type: [Percentage](#)

Used in groups: [SideCollateralAmountGrp](#)

### 180.2.4958 SideCollateralReinvestmentType

Indicates the type of investment the cash collateral is re-invested in.

Type: [int](#)

Allowed values in CollateralReinvestmentTypeCodeSet:

Code	Name	Description
0	MoneyMarketFund	Money market fund. Registered money market fund. In the context of EU SFTR reporting this corresponds to code "MMFT".
1	OtherComingledPool	Other comingled pool. Any commingled pool other than money market fund. In the context of EU SFTR reporting this corresponds to code "OCMP".
2	RepoMarket	Repo market. The repurchase agreement market. In the context of EU SFTR reporting this corresponds to code "REPM".
3	DirectPurchaseOfSecurities	Direct purchase of securities. In the context of EU SFTR reporting this corresponds to code "SDPU".
4	OtherInvestments	Other investments. In the context of EU SFTR reporting this corresponds to code "OTHR".

---

Used in groups: [SideCollateralReinvestmentGrp](#)

#### **180.2.4959 SideCollateralType**

Type of collateral on deposit being reported.

Type: [String](#)

Used in groups: [SideCollateralAmountGrp](#)

#### **180.2.4960 SideComplianceID**

ID within repeating group of sides which is used to represent this transaction for compliance purposes (e.g. OATS reporting).

Type: [String](#)

Used in groups: [SideCrossOrdModGrp](#)

#### **180.2.4961 SideCrossLegGrp**

Repeating group that is similar to LegOrdGrp component in order to support leg level information per side of cross orders and is part of SideCrossOrdModGrp component. LegOrdGrp component cannot be re-used for this purpose as it contains the component blocks InstrumentLeg component and NestedParties component which are already part of the cross messages. The difference to LegOrdGrp component is that SideCrossLegGrp component does not have an InstrumentLeg component to

describe the legs, it only has a single reference field to identify the leg which can be defined by the InstrumentLeg component which is present on a higher level of the message and outside of the side group.

Name	Mult.	Type	Description
NoCrossLegs	[1..1]	NumInGroup	
LegRefID	[0..1]	String	Required if NoCrossLegs(1829) > 0.
LegOrderQty	[0..1]	Qty	Quantity ordered for this leg as provided during order entry.
LegSwapType	[0..1]	CodeSet	
LegStipulations	[0..*]	Group	
LegAllocID	[0..1]	String	
LegPreAllocGrp	[0..*]	Group	
LegClearingAccountType	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in ClearingAccountType(1816) in the Instrument component.
LegPositionEffect	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in PositionEffect(77) in the Instrument component.
LegCoveredOrUncovered	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in CoveredOrUncovered(203) in the Instrument component.
NestedParties3	[0..*]	Group	
LegSettlType	[0..1]	CodeSet	
LegSettlDate	[0..1]	LocalMktDate	
LegSettlCurrency	[0..1]	Currency	
LegSettlCurrencyCodeSource	[0..1]	CodeSet	
LegVolatility	[0..1]	float	
LegDividendYield	[0..1]	Percentage	
LegCurrencyRatio	[0..1]	float	
LegExecInst	[0..1]	CodeSet	
LegShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when LegSide(624) = 6(Sell short exempt) in InstrumentLeg component.

Used in groups: SideCrossOrdModGrp

**180.2.4962 SideCrossOrdCxlGrp**

Name	Mult.	Type	Description
NoSides	[1..1]	CodeSet	Must be 1 or 2
Side	[1..1]	CodeSet	
OrigClOrdID	[0..1]	String	Required when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID(11).
ClOrdID	[1..1]	String	Unique identifier of the order as assigned by institution or by the intermediary with closest association with the investor.
SecondaryClOrdID	[0..1]	String	
ClOrdLinkID	[0..1]	String	
OrigOrdModTime	[0..1]	UTCTimestamp	
Parties	[0..*]	Group	Insert here the set of "Parties" (firm identification) fields defined in "Common Components of Application Messages"
TradeOriginationDate	[0..1]	LocalMktDate	
TradeDate	[0..1]	LocalMktDate	
OrderQtyData	[1..1]	Component	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: **CrossOrderCancelRequest**

**180.2.4963 SideCrossOrdModGrp**

Name	Mult.	Type	Description
NoSides	[1..1]	CodeSet	Must be 1 or 2 if CrossType(549)=1(All-or-none Cross), 2 otherwise.
Side	[1..1]	CodeSet	Required if NoSides(552) > 0.
ShortMarkingExemptIndicator	[0..1]	Boolean	
OrigClOrdID	[0..1]	String	Required when referring to orders that were electronically submitted over FIX or otherwise assigned a ClOrdID(11)
ClOrdID	[1..1]	String	Unique identifier of the order as assigned by institution or by the intermediary with closest association with the investor.
SecondaryClOrdID	[0..1]	String	
ClOrdLinkID	[0..1]	String	
OrigOrdModTime	[0..1]	UTCTimestamp	
Parties	[0..*]	Group	
SideCrossLegGrp	[0..*]	Group	
SideShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when Side(54) = 6 (Sell short exempt).
TradeOriginationDate	[0..1]	LocalMktDate	
TradeDate	[0..1]	LocalMktDate	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
DayBookingInst	[0..1]	CodeSet	
BookingUnit	[0..1]	CodeSet	
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	Use to assign an identifier to the block of preallocations
PreAllocGrp	[0..*]	Group	
QtyType	[0..1]	CodeSet	
OrderQtyData	[1..1]	Component	
CommissionData	[0..1]	Component	
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData if multiple commissions or enhanced attributes are needed.
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	

Name	Mult.	Type	Description
OrderOrigination	[0..1]	CodeSet	
OriginatingDeptID	[0..1]	String	
ReceivingDeptID	[0..1]	String	
RoutingArrangementIndicator	[0..1]	CodeSet	
PreTradeAnonymity	[0..1]	Boolean	
CustOrderCapacity	[0..1]	CodeSet	
ForexReq	[0..1]	CodeSet	Indicates that broker is requested to execute a Forex accommodation trade in conjunction with the security trade.
SettlCurrency	[0..1]	Currency	Conditionally required when ForexReq(121) = "Y".
SettlCurrencyCodeSource	[0..1]	CodeSet	
BookingType	[0..1]	CodeSet	Method for booking out this order. Used when notifying a broker that an order to be settled by that broker is to be booked out as an OTC derivative (e.g. CFD or similar). Absence of this field implies regular booking.
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.
ClearingAccountType	[0..1]	CodeSet	
PositionEffect	[0..1]	CodeSet	For use in derivatives omnibus accounting
CoveredOrUncovered	[0..1]	CodeSet	For use with derivatives, such as options
CashMargin	[0..1]	CodeSet	
ClearingFeeIndicator	[0..1]	CodeSet	
SolicitedFlag	[0..1]	CodeSet	
SideComplianceID	[0..1]	String	
SideTimeInForce	[0..1]	UTCTimestamp	Specifies how long the order as specified in the side stays in effect. Absence of this field indicates Day order.

Used in messages: [CrossOrderCancelReplaceRequest](#), [NewOrderCross](#)

**180.2.4964 SideCurrency**

Used to identify the trading currency on the Trade Capture Report Side

Type: **Currency**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.4965 SideCurrencyCodeSource**

Identifies class or source of the SideCurrency(1154) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.4966 SideCurrentCollateralAmount**

Currency value currently attributed to the collateral.

Type: **Amt**

Used in groups: **SideCollateralAmountGrp**

**180.2.4967 SideExecID**

When reporting trades, used to reference the identifier of the execution (ExecID) being reported if different ExecIDs were assigned to each side of the trade.



Type: **String**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

#### **180.2.4968 SideExecRefID**

Used to reference the value from SideExecID(1427).

Type: **String**

Used in groups: **TrdMatchSideGrp**

#### **180.2.4969 SideFillStationCd**

Used on a multi-sided trade to convey order routing information

Type: **String**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

#### **180.2.4970 SideGrossTradeAmt**

The gross trade amount for this side of the trade. See also GrossTradeAmt (381) for additional definition.

Type: **Amt**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

#### **180.2.4971 SideHaircutIndicator**

Indicates, if "Y", that a stated valuation includes a haircut, e.g. that the stated value reflects the subtraction of the haircut. Note that a value of "N" does not imply a haircut is not applicable, only that the haircut (if any) is not reflected in the stated valuation.

Type: **Boolean**

Used in groups: **SideCollateralAmountGrp**

**180.2.4972 SideLastQty**

Used to indicate the quantity on one side of a multi-sided trade.

Type: Qty

Used in groups: TrdCapRptAckSideGrp, TrdCapRptSideGrp, TrdMatchSideGrp

**180.2.4973 SideLiquidityInd**

Indicator to identify whether this fill was a result of a liquidity provider providing or liquidity taker taking the liquidity. Applicable only for OrdStatus of Partial or Filled.

Type: int

Allowed values in LastLiquidityIndCodeSet:

Code	Name	Description
0	NeitherAddedNorRemovedLiquidity	Neither added nor removed liquidity. May be used by venues where market rules do not define "add" or "remove" liquidity. In the context of the SEC amendment of Regulation NMS Rule 606(b), may be used to identify executions that are only reported as part of total shares executed and not as part of shares providing or removing liquidity (see <a href="https://www.sec.gov/rules/final/2018/34-84528.pdf">https://www.sec.gov/rules/final/2018/34-84528.pdf</a> for details).
1	AddedLiquidity	Added Liquidity
2	RemovedLiquidity	Removed Liquidity
3	LiquidityRoutedOut	Liquidity Routed Out
4	Auction	Auction execution
5	TriggeredStopOrder	Triggered stop order. Fill was the result of a stop order being triggered and immediately executed.
6	TriggeredContingencyOrder	Triggered contingency order. Fill was the result of a contingency order (OCO, OTO, OUO) becoming active (after cancelling or updating another order) and being immediately executed.
7	TriggeredMarketOrder	Triggered market order. Fill was the result of a market order being triggered due to an executable orderbook situation.
8	RemovedLiquidityAfterFirmOrder-Commitment	Removed liquidity after firm order commitment. An order that was submitted for continuous trading that required a firm order commit prior to execution. "Conditional order" is an alternate term used for such orders.

Code	Name	Description
9	AuctionExecutionAfterFirmOrder-Commitment	Auction execution after firm order commitment. An order that was submitted for auction trading that required a firm order commit prior to execution. "Conditional order" is an alternate term used for such orders.
10	Unknown	Unknown. The liquidity indicator of the execution cannot be determined or was not provided upon execution.
11	Other	Other. None of the existing liquidity indicators are applicable for the execution (e.g. due to a venue's new order type that does not fit existing values).

Used in groups: [TrdCapRptSideGrp](#)

#### 180.2.4974 SideMarketSegmentID

Identifies the market segment of the side.

Type: [String](#)

Used in groups: [TrdMatchSideGrp](#)

#### 180.2.4975 SideMultiLegReportingType

Used to indicate if the side being reported on Trade Capture Report represents a leg of a multileg instrument or a single security.

Type: [int](#)

Allowed values in SideMultiLegReportingTypeCodeSet:

Code	Name	Description
1	SingleSecurity	Single Security (default if not specified)
2	IndividualLegOfAMultilegSecurity	Individual leg of a multileg security
3	MultilegSecurity	Multileg Security

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

**180.2.4976 SideOrigTradeID**

Used to capture the original trade id for each side of a trade undergoing novation to a standardized model.

Type: **String**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

**180.2.4977 SidePriceDifferential**

Price Differential between the front and back leg of a spread or complex instrument.

Type: **Price**

Used in groups: **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.4978 SideReasonCd**

Used on a multi-sided trade to convey reason for execution

Type: **String**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

**180.2.4979 SideRegulatoryLegRefID**

Identifies the leg of the trade the entry applies to by referencing the leg's LegID(1788).

Type: **String**

Used in groups: **SideRegulatoryTradeIDGrp**

**180.2.4980 SideRegulatoryTradeID**

Trade identifier required by government regulators or other regulatory organizations for regulatory reporting purposes. For example, unique swap identifier (USI) as required by the U.S. Commodity Futures Trading Commission.

Type: **String**

Used in groups: **SideRegulatoryTradeIDGrp**

**180.2.4981 SideRegulatoryTradeIDEvent**

Identifies the event which caused origination of the identifier in SideRegulatoryTradeID(1972). When more than one event is the cause, use the higher enumeration value. For example, if the identifier is originated due to an allocated trade which was cleared and reported, use the enumeration value 2 (Clearing).

Type: **int**

Allowed values in RegulatoryTradeIDEventCodeSet:

Code	Name	Description
0	InitialBlockTrade	Initial block trade.
1	Allocation	Allocation. Determination that the block trade will not be further allocated.
2	Clearing	Clearing
3	Compression	Compression
4	Novation	Novation
5	Termination	Termination
6	PostTrdVal	Post-trade valuation

Used in groups: **SideRegulatoryTradeIDGrp**

**180.2.4982 SideRegulatoryTradeIDGrp**

The SideRegulatoryTradeIDGrp is a repeating component within the TrdCapRptSideGrp component used to report the source, value and relationship of multiple trade identifiers for the same trade side.

This component can be used to meet regulatory trade reporting requirements where identifiers such as the Unique Swaps Identifier (USI) are required to be reported, showing the chaining of these identifiers as needed.

Name	Mult.	Type	Description
NoSideRegulatoryTradeIDs	[1..1]	NumInGroup	
SideRegulatoryTradeID	[0..1]	String	Required if NoSideRegulatoryTradeIDs(1971) > 0.
SideRegulatoryTradeIDSource	[0..1]	CodeSet	
SideRegulatoryTradeIDEvent	[0..1]	CodeSet	
SideRegulatoryTradeIDType	[0..1]	CodeSet	

Name	Mult.	Type	Description
SideRegulatoryLegRefID	[0..1]	String	This field may be used for multi-leg trades sent as a single message to indicate that the entry applies only to a specific leg.
SideRegulatoryTradeIDScope	[0..1]	CodeSet	

Used in groups: [TrdCapRptSideGrp](#)

### 180.2.4983 SideRegulatoryTradeIDScope

Specifies the scope to which the SideRegulatoryTradeID(1972) applies. Used when a trade must be assigned more than one identifier, e.g. one for the clearing member and another for the client on a cleared trade as with the principal model in Europe.

Type: [int](#)

Allowed values in RegulatoryTradeIDScopeCodeSet:

Code	Name	Description
1	ClearingMember	Clearing member
2	Client	Client

Used in groups: [SideRegulatoryTradeIDGrp](#)

### 180.2.4984 SideRegulatoryTradeIDSource

Identifies the reporting entity that originated the value in RegulatoryTradeID(1903). The reporting entity identifier may be assigned by a regulator or from a supported standard identifier source scheme.

Type: [String](#)

Allowed values in RegulatoryTradeIDSourceCodeSet:

Code	Name	Description
1	UniqueTransactionIdentifier	Unique Transaction Identifier (ISO 23897)

Used in groups: [SideRegulatoryTradeIDGrp](#)

**180.2.4985 SideRegulatoryTradeIDType**

Specifies the type of trade identifier provided in SideRegulatoryTradeID(1972), within the context of the hierarchy of trade events.

Type: **int**

Allowed values in RegulatoryTradeIDTypeCodeSet:

Code	Name	Description
0	Current	Current. The default if not specified.
1	Previous	Previous. The previous trade's identifier when reporting a cleared trade or novation of a previous trade.
2	Block	Block. The block trade's identifier when reporting an allocated subtrade.
3	Related	Related. The related trade identifier when reporting a mixed swap.
4	ClearedBlockTrade	Cleared block trade. Assigned by the CCP to a bunched order/trade when it needs to be cleared with the standby clearing firm prior to post-trade allocation.
5	TradingVenueTransactionIdentifier	Trading venue transaction identifier. Assigned by the trading venue to a transaction. In the context of ESMA RTS 22 and RTS 24, this is a unique transaction identification "number generated by trading venues and disseminated to both the buying and selling parties in accordance with Article 12 of [RTS 24 on the maintenance of relevant data relating to orders in financial instruments under Article 25 of Regulation 600/2014 EU]." (quoted text from RTS 22). "Uniqueness" may be defined per relevant regulations.
6	ReportTrackingNumber	Report tracking number. In the context of EMIR Refit this is a "unique code assigned to the execution of an order and common for a group of reports related to the same execution" (see Q28 in <a href="https://www.esma.europa.eu/sites/default/files/library/esma74-362-2281_final_report_guidelines_emir_refit.pdf">https://www.esma.europa.eu/sites/default/files/library/esma74-362-2281_final_report_guidelines_emir_refit.pdf</a> ). Also referred to as the RTN.

Used in groups: **SideRegulatoryTradeIDGrp**

**180.2.4986 SideRiskLimitCheckStatus**

Indicates the status of the risk limit check performed on the side of a trade.

Type: **int**

Allowed values in RiskLimitCheckStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted. For use when none of the more specific status enumerations apply.
1	Rejected	Rejected. For use when none of the more specific status enumerations apply.
2	ClaimRequired	Claim required. Indicates that the clearing firm is required to accept or decline the trade.
3	PreDefinedLimitCheckSucceeded	Pre-defined limit check succeeded. Indicates a check enforced automatically by the clearing house.
4	PreDefinedLimitCheckFailed	Pre-defined limit check failed. Indicates a check enforced automatically by the clearing house.
5	PreDefinedAutoAcceptRuleInvoked	Pre-defined auto-accept rule invoked. Indicates that the clearing firm is required to accept or decline the trade because no limit or rule applies.
6	PreDefinedAutoRejectRuleInvoked	Pre-defined auto-reject rule invoked. Indicates a check enforced automatically by the clearing house. Note that clearing house rules of engagement may still require a clearing firm accept or reject the trade.
7	AcceptedByClearingFirm	Accepted by clearing firm. Indicates that explicit action by the clearing firm, and not an automatic check by the clearing house, was the basis for accepting the trade.
8	RejectedByClearingFirm	Rejected by clearing firm. Indicates that explicit action by the clearing firm, and not an automatic check by the clearing house, was the basis for rejecting the trade.
9	Pending	Pending. Indicates that one or more side level risk checks are in progress.
10	AcceptedByCreditHub	Accepted by credit hub. Indicates that a credit hub accepted the trade. An identifier assigned by the credit hub may appear in the appropriate RefRiskLimitCheckID(2334) field.
11	RejectedByCreditHub	Rejected by credit hub. Indicates that a credit hub rejected the trade.
12	PendingCreditHubCheck	Pending credit hub check. Indicates that a check is pending at a credit hub.
13	AcceptedByExecVenue	Accepted by execution venue. Indicates acceptance by an execution venue, such as a SEF.
14	RejectedByExecVenue	Rejected by execution venue. Indicates that the trade was rejected by an execution venue, such as a SEF.



Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

### **180.2.4987 SideSettlCurrency**

Used to identify the settlement currency on the Trade Capture Report Side

Type: [Currency](#)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

### **180.2.4988 SideSettlCurrencyCodeSource**

Identifies class or source of the SideSettlCurrency(1155) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

### **180.2.4989 SideShortSaleExemptionReason**

Indicates the reason a short sale is exempted from applicable regulation (e.g. Reg SHO addendum (b)(1) in the U.S.)

Type: [int](#)

Allowed values in ShortSaleExemptionReasonCodeSet:

Code	Name	Description
0	ExemptionReasonUnknown	Exemption reason unknown. An exemption reason not provided or received.
1	IncomingSSE	Income sell short exempt. Agency broker has the customer's exemption reason, which is not explicitly provided to executing broker.
2	AboveNationalBestBid	Above national best bid (broker/dealer provision). Broker / dealer responsible for enforcing exemption rule has determined that the order is priced one or more ticks above the nation best bid of the security to be traded.
3	DelayedDelivery	Delayed delivery. The broker-dealer has a reasonable basis to believe the seller owns the covered security (pursuant to Rule 200 in the U.S.), but is subject to restrictions on delivery, provided that the seller intends to deliver the security as soon as all restrictions on delivery have been removed.
4	OddLot	Odd lot. The broker-dealer has a reasonable basis to believe the sale is by a market maker to offset customer odd-lot orders or to liquidate an odd-lot position that changes such broker's or dealer's position by no more than a unit of trading.
5	DomesticArbitrage	Domestic arbitrage. The sale is connected to a bona-fide domestic arbitrage transaction.
6	InternationalArbitrage	International arbitrage. The sale is connected to an international arbitrage transaction.
7	UnderwriterOrSyndicateDistribution	Underwriter or syndicate distribution. The short sale is (i) by an underwriter or member of a syndicate or group participating in the distribution of a security in connection with an over-allotment of securities; or (ii) is for purposes of a lay-off sale by an underwriter or member of a syndicate or group in connection with a distribution of securities through a rights or standby underwriting commitment.
8	RisklessPrincipal	Riskless principal. The short sale is by a broker or dealer effecting the execution of a customer purchase or the execution of a customer "long" sale on a riskless principal basis.
9	VWAP	VWAP. The short sale order is for the sale of a covered security at the volume weighted average price (VWAP) meeting certain criteria.

Used in groups: [SideCrossOrdModGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

**180.2.4990 SideTimeInForce**

Indicates how long the order as specified in the side stays in effect. SideTimeInForce allows a two-sided cross order to specify order behavior separately for each side. Absence of this field indicates that TimeInForce should be referenced. SideTimeInForce will override TimeInForce if both are provided.

Type: **UTCTimestamp**

Used in groups: **SideCrossOrdModGrp**

**180.2.4991 SideTradeID**

Used to represent the trade ID for each side of the trade assigned by an intermediary.

Type: **String**

Used in groups: **TrdCapRptAckSideGrp, TrdCapRptSideGrp, TrdMatchSideGrp**

**180.2.4992 SideTradeReportID**

Used on a multi-sided trade to designate the ReportID

Type: **String**

Used in groups: **TrdCapRptAckSideGrp, TrdCapRptSideGrp, TrdMatchSideGrp**

**180.2.4993 SideTradeReportingIndicator**

Used between parties to convey trade reporting status.

Type: **int**

Allowed values in TradeReportingIndicatorCodeSet:

Code	Name	Description
0	NotReported	Trade has not (yet) been reported. Depending on the regulatory regime the trade is reportable and the recipient may be responsible for reporting.
1	OnBook	Trade has been or will be reported by a trading venue as an "on-book" trade
2	SISeller	Trade has or will be reported as a seller trade by the authorised reporter

Code	Name	Description
3	SIBuyer	Trade has or will be reported as a buyer trade by the authorised reporter
4	NonSISeller	Trade has or will be reported as a seller trade by an entity other than the authorised reporter
5	SubDelegationByFirm	Trade has been or will be reported under a sub-delegation arrangement by an investment firm to a reporting facility (e.g. APA) on behalf of another investment firm
6	Reportable	Trade has been or will be reported. Depending on the regulatory regime the recipient is not responsible for reporting.
7	NonSIBuyer	Trade has been or will be reported as a buyer trade by an entity other than the authorised reporter
8	OffBook	Trade has been or will be reported by a trading venue as an "off-book" trade
9	NotReportable	Trade is not reportable. The (non-equity) instrument does not need to be reported by any party, e.g. because it is not deemed to have been traded on a trading venue.

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

#### **180.2.4994 SideTrdRegTimestamp**

Same as TrdRegTimestamp(769). Used in a multi-sided message to indicate relevant trade-side timestamp.

Type: [UTCTimestamp](#)

Used in groups: [SideTrdRegTS](#)

#### **180.2.4995 SideTrdRegTimestampSrc**

Same as TrdRegTimestampOrigin(771). Used in a multi-sided message to indicate relevant trade-side origin or source of timestamp.

Type: [String](#)

Used in groups: [SideTrdRegTS](#)

**180.2.4996 SideTrdRegTimestampType**

Same as TrdRegTimeStampType(770). Used in a multi-sided message to indicate relevant trade-side timestamp type.

Type: **int**

Allowed values in TrdRegTimestampTypeCodeSet:

Code	Name	Description
1	ExecutionTime	Execution time. Timestamp for the order execution. In the context of US futures markets (CFTC regulated) this is the non-qualified reporting time of order execution.
2	TimeIn	Time in. Timestamp for receiving an order, quote or trade. In the context of US futures markets (CFTC) this is the timestamp of when the order was received on the trading floor (booth).
3	TimeOut	Time out. Timestamp for sending an order, quote or trade. In the context of US futures markets (CFTC) this is the timestamp when the trade was received from the pit.
4	BrokerReceipt	Broker receipt. Timestamp for a broker receiving an order, quote or trade. In the context of US futures markets (CFTC) this is the time at which the broker received the order.
5	BrokerExecution	Broker execution. Timestamp for the broker executing an order. In the context of US futures markets (CFTC regulated) this is the time at which a broker executed the order for another broker.
6	DeskReceipt	Desk receipt. Timestamp for the transmission of an order to an internal desk or department on the same day the firm received the order.
7	SubmissionToClearing	Submission to clearing. The timestamp when the trade was officially acknowledged by the Clearing House.
8	TimePriority	Time priority. A timestamp (manually or electronically) assigned by a market to specify time priority for an order or quote.
9	OrderbookEntryTime	Orderbook entry time. Timestamp for an order representing the time it was entered in the orderbook of the execution venue. The orderbook entry time cannot change during the lifetime of the order.
10	OrderSubmissionTime	Order submission time. Time the order was sent by the submitter.
11	PubliclyReported	Publicly reported. In the context of MiFID II, this is used to identify the time at which the transaction was first published to the market.

Code	Name	Description
12	PublicReportUpdated	Public report updated. In the context of MiFID II, this is used to identify the time at which the transaction's publication to the market was last updated
13	NonPubliclyReported	Non-publicly reported
14	NonPublicReportUpdated	Non-public report updated
15	SubmittedForConfirmation	Submitted for confirmation
16	UpdatedForConfirmation	Updated for confirmation
17	Confirmed	Confirmed
18	UpdatedForClearing	Updated for clearing
19	Cleared	Cleared
20	AllocationsSubmitted	Allocations submitted
21	AllocationsUpdated	Allocations updated
22	AllocationsCompleted	Allocations completed
23	SubmittedToRepository	Submitted to repository
24	PostTrdContntnEvt	Post-trade continuation event
25	PostTradeValuation	Post-trade valuation
26	PreviousTimePriority	Previous time priority. Can be used in conjunction with TrdRegTimestampType(770) = 8 (Time priority) to provide the current and last priority timestamp in a single message.
27	IdentifierAssigned	Identifier assigned. Timestamp for the assignment of a (unique) identifier to an entity (e.g. order, quote, trade).
28	PreviousIdentifierAssigned	Previous identifier assigned. Timestamp of previous assignment of a (unique) identifier to an entity (e.g. order, quote, trade).
29	OrderCancellationTime	Order cancellation time. Timestamp for the cancellation of an order or quote.
30	OrderModificationTime	Order modification time. Timestamp for the modification of an order or quote.
31	OrderRoutingTime	Order routing time. Timestamp for the routing of an order to another broker or electronic execution venue.
32	TradeCancellationTime	Trade cancellation time. Timestamp for the cancellation of an execution (ExecType(150) = H (Trade Cancel)) or trade (TradeReportType(856) = 6 (Trade Report Cancel)).
33	TradeModificationTime	Trade modification time. Timestamp for the modification of an execution (ExecType(150) = G (Trade Correct)) or trade (TradeReportType(856) = 5 (No/Was)).
34	ReferenceTimeForNBBO	Reference time for NBBO. Timestamp for an NBBO reference price.

Code	Name	Description
35	Affirmed	Affirmed

Used in groups: [SideTrdRegTS](#)

### 180.2.4997 SideTrdRegTS

The SideTrdRegTS component block is used to convey trading or regulatory timestamps associated with one side of a multi-sided trade event.

Name	Mult.	Type	Description
<a href="#">NoSideTrdRegTS</a>	[1..1]	NumInGroup	
<a href="#">SideTrdRegTimestamp</a>	[0..1]	UTCTimestamp	
<a href="#">SideTrdRegTimestampType</a>	[0..1]	CodeSet	
<a href="#">SideTrdRegTimestampSrc</a>	[0..1]	String	

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

### 180.2.4998 SideTrdSubType

Used on a multi-sided trade to specify the type of trade for a given side. Same values as TrdSubType (829).

Type: [int](#)

Allowed values in TrdSubTypeCodeSet:

Code	Name	Description
0	CMTA	CMTA
1	InternalTransferOrAdjustment	Internal transfer or adjustment
2	ExternalTransferOrTransferOfAccount	External transfer or transfer of account
3	RejectForSubmittingSide	Reject for submitting side
4	AdvisoryForContraSide	Advisory for contra side
5	OffsetDueToAnAllocation	Offset due to an allocation
6	OnsetDueToAnAllocation	Onset due to an allocation

Code	Name	Description
7	DifferentialSpread	Differential spread
8	ImpliedSpreadLegExecutedAgainstAnOutright	Implied spread leg executed against an outright
9	TransactionFromExercise	Transaction from exercise
10	TransactionFromAssignment	Transaction from assignment
11	ACATS	ACATS
14	AI	AI (Automated input facility disabled in response to an exchange request.)
15	B	B (Transaction between two member firms where neither member firm is registered as a market maker in the security in question and neither is a designated fund manager. Also used by broker dealers when dealing with another broker which is not a member firm. Non-order book securities only.)
16	K	K (Transaction using block trade facility.)
17	LC	LC (Correction submitted more than three days after publication of the original trade report.)
18	M	M (Transaction, other than a transaction resulting from a stock swap or stock switch, between two market makers registered in that security including IDB or a public display system trades. Non-order book securities only.)
19	N	N (Non-protected portfolio transaction or a fully disclosed portfolio transaction)
20	NM	NM ( i) transaction where Exchange has granted permission for non-publication. ii)IDB is reporting as seller. iii) submitting a transaction report to the Exchange, where the transaction report is not also a trade report.)
21	NR	NR (Non-risk transaction in a SEATS security other than an AIM security)
22	P	P (Protected portfolio transaction or a worked principal agreement to effect a portfolio transaction which includes order book securities)
23	PA	PA (Protected transaction notification)
24	PC	PC (Contra trade for transaction which took place on a previous day and which was automatically executed on the Exchange trading system)
25	PN	PN (Worked principal notification for a portfolio transaction which includes order book securities)



Code	Name	Description
26	R	R ( (i) riskless principal transaction between non-members where the buying and selling transactions are executed at different prices or on different terms (requires a trade report with trade type indicator R for each transaction). (ii) market maker is reporting all the legs of a riskless principal transaction where the buying and selling transactions are executed at different prices (requires a trade report with trade type indicator R for each transaction) or. (iii) market maker is reporting the onward leg of a riskless principal transaction where the legs are executed at different prices, and another market maker has submitted a trade report using trade type indicator M for the first leg (this requires a single trade report with trade type indicator R).)
27	RO	RO (Transaction which resulted from the exercise of a traditional option or a stock-settled covered warrant)
28	RT	RT (Risk transaction in a SEATS security, (excluding AIM security) reported by a market maker registered in that security)
29	SW	SW (Transactions resulting from stock swap or a stock switch (one report is required for each line of stock))
30	T	T (If reporting a single protected transaction)
31	WN	WN (Worked principal notification for a single order book security)
32	WT	WT (Worked principal transaction (other than a portfolio transaction))
33	OffHoursTrade	Off Hours Trade
34	OnHoursTrade	On Hours Trade
35	OTCQuote	OTC Quote
36	ConvertedSWAP	Converted SWAP
37	CrossedTrade	Crossed Trade (X)
38	InterimProtectedTrade	Interim Protected Trade (I)
39	LargeInScale	Large in Scale (L)
40	WashTrade	Wash Trade
41	TradeAtSettlement	Trade at Settlement (TAS). Identifies a trade that will be priced using the settlement price.
42	AuctionTrade	Auction Trade. Mutually exclusive with TrdSubType(829) = 50 (Balancing).

Code	Name	Description
43	TradeAtMarker	Trade at Marker (TAM). Posted at a specific time each day and used to price the consummated trade for the product/month/strip executed (+/- and differentials). Closely related to TAS trades in function and trade practice.
44	CreditDefault	Default (Credit Event)
45	CreditRestructuring	Restructuring (credit event)
46	Merger	Merger (succession event)
47	SpinOff	Spin-off (succession event)
48	MultilateralCompression	Multilateral compression. Used to identify a special case of compression between multiple parties, e.g. for netted or portfolio trades.
50	Balancing	Balancing. Identifies an additional trade distributed to auction participants meant to resolve an imbalance between bids and offers. Mutually exclusive with TrdSubType(829) = 42 =(Auction).
51	BasisTradeIndexClose	Basis Trade index Close (BTIC). The marketplace name given to Trade at Marker (TAM) transactions in equity index futures.
52	TradeAtCashOpen	Trade At Cash Open (TACO). The marketplace name given to trading futures based on an opening quote of the underlying cash market.
53	TrdSubmitVenueClrSettl	Trade submitted to venue for clearing and settlement. Identifies trades brought on a trading venue purely for clearing and settlement purposes.
54	BilateralCompression	Bilateral compression. Used to identify a special case of compression between two parties, e.g. for netted or portfolio trades.

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

### 180.2.4999 SideUnderlyingRefID

Identifies the underlying instrument the entity applies to by referencing the underlying instrument's UnderlyingID(2874).

Type: [String](#)

Used in groups: [SideCollateralAmountGrp](#)

**180.2.5000 SideValue1**

Amounts in currency

Type: **Amt**

Used in messages: **BidRequest**

**180.2.5001 SideValue2**

Amounts in currency

Type: **Amt**

Used in messages: **BidRequest**

**180.2.5002 SideValueInd**

Code to identify which "SideValue" the value refers to. SideValue1 and SideValue2 are used as opposed to Buy or Sell so that the basket can be quoted either way as Buy or Sell.

Type: **int**

Allowed values in SideValueIndCodeSet:

Code	Name	Description
1	SideValue1	Side Value 1
2	SideValue2	Side Value 2

Used in groups: **BidDescReqGrp**, **ListOrdGrp**

**180.2.5003 SideVenueType**

Identifies the type of venue where the trade was executed for the side.

Type: **char**

Allowed values in VenueTypeCodeSet:

Code	Name	Description
E	Electronic	Electronic exchange

Code	Name	Description
P	Pit	Pit
X	ExPit	Ex-pit
C	ClearingHouse	Clearinghouse
R	RegisteredMarket	Registered market. Markets registered with regulators such as exchange, multilateral trading facility (MTF), swap execution facility (SEF). In the context of regulatory reporting (e.g. CFTC reporting), this is used for regulated markets, e.g. swap markets.
O	OffMarket	Off-market. Off-book, off-facility. In the context of regulatory reporting (e.g. CFTC reporting) this identifies trades conducted away from a regulated market.
B	CentralLimitOrderBook	Central limit order book
Q	QuoteDrivenMarket	Quote driven market
D	DarkOrderBook	Dark order book
A	AuctionDrivenMarket	Auction driven market. Markets where matching occurs only in scheduled auctions.
N	QuoteNegotiation	Quote negotiation. Discretionary quoting on request or "request for quote" market.
V	VoiceNegotiation	Voice negotiation. A trading system where transactions between members are arranged through voice negotiation.
H	HybridMarket	Hybrid market. A hybrid system falling into two or more types of trading systems. In the context of ESMA reporting, this is for "Hybrid system." In the context of FCA reporting, this is for "Any other, including hybrid."
z	OtherMarket	Other market (lowercase "z"). A market that does not fall under any of the market types defined for VenueType(1430). In the context of ESMA reporting, this is for "Any other, excluding hybrid."

Used in groups: **TrdMatchSideGrp**

#### 180.2.5004 Signature

Electronic signature

Type: **data**

Used in components: **StandardTrailer**

**180.2.5005 SignatureLength**

Number of bytes in signature field

Type: **Length**

Used in components: **StandardTrailer**

**180.2.5006 SingleQuoteIndicator**

Used to indicate whether the quoting system allows only one quote to be active at a time for the quote issuer or market maker.

Type: **Boolean**

Allowed values in SingleQuoteIndicatorCodeSet:

Code	Name	Description
N	MultipleQuotesAllowed	Multiple quotes allowed
Y	OnlyOneQuoteAllowed	Only one quote allowed

Used in messages: **Quote**

**180.2.5007 SolicitedFlag**

Indicates whether or not the order was solicited.

Type: **Boolean**

Allowed values in SolicitedFlagCodeSet:

Code	Name	Description
N	WasNotSolicited	Was not solicited
Y	WasSolicited	Was solicited

Used in groups: **ListOrdGrp**, **SideCrossOrdModGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **Trd-MatchSideGrp**

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **Quote**

**180.2.5008 SpecialDividendsIndicator**

Indicates whether special dividends are applicable.

Type: **Boolean**

Used in components: **DividendConditions**

**180.2.5009 Spread**

For Fixed Income. Either Swap Spread or Spread to Benchmark depending upon the order type.

Spread to Benchmark: Basis points relative to a benchmark. To be expressed as count of basis points (vs. an absolute value). E.g. High Grade Corporate Bonds may express price as basis points relative to benchmark (the BenchmarkCurveName(221) field). Note: Basis points can be negative.

Swap Spread: Target spread for a swap.

Type: **PriceOffset**

Used in components: **SpreadOrBenchmarkCurveData**

**180.2.5010 SpreadOrBenchmarkCurveData**

The SpreadOrBenchmarkCurveData component block is primarily used for Fixed Income to convey spread to a benchmark security or curve.

Name	Mult.	Type	Description
<b>Spread</b>	[0..1]	PriceOffset	For Fixed Income
<b>BenchmarkCurveCurrency</b>	[0..1]	Currency	
<b>BenchmarkCurveCurrencyCodeSource</b>	[0..1]	CodeSet	
<b>BenchmarkCurveName</b>	[0..1]	CodeSet	
<b>BenchmarkCurvePoint</b>	[0..1]	String	
<b>BenchmarkPrice</b>	[0..1]	Price	
<b>BenchmarkPriceType</b>	[0..1]	CodeSet	Must be present if BenchmarkPrice is used.
<b>BenchmarkSecurityID</b>	[0..1]	String	The identifier of the benchmark security, e.g. Treasury against Corporate bond.
<b>BenchmarkSecurityIDSource</b>	[0..1]	CodeSet	Source of BenchmarkSecurityID. If not specified, then ID Source is understood to be the same as that in the Instrument block.

Used in groups: InstrmtMDReqGrp, ListOrdGrp, MDFullGrp, MDIncGrp, QuotReqGrp, QuotReqRjctGrp, SecListGrp, SecLstUpdRelSymGrp

Used in messages: AllocationInstruction, AllocationInstructionAlert, AllocationReport, CollateralAssignment, CollateralInquiry, CollateralReport, CollateralRequest, CollateralResponse, Confirmation, CrossOrderCancelReplaceRequest, ExecutionReport, IOI, NewOrderCross, NewOrderSingle, OrderCancelReplaceRequest, Quote, QuoteResponse, QuoteStatusReport, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, TradeCaptureReport

### 180.2.5011 StandardHeader

The standard FIX message header

Name	Mult.	Type	Description
BeginString	[1..1]	CodeSet	FIXT.1.1 (Always unencrypted, must be first field in message)
BodyLength	[1..1]	Length	(Always unencrypted, must be second field in message)
MsgType	[1..1]	CodeSet	(Always unencrypted, must be third field in message)
ApplVerID	[0..1]	CodeSet	Indicates application version using a service pack identifier. The ApplVerID applies to a specific message occurrence.
ApplExtID	[0..1]	int	
CstmApplVerID	[0..1]	String	Used to support bilaterally agreed custom functionality
SenderCompID	[1..1]	String	(Always unencrypted)
TargetCompID	[1..1]	String	(Always unencrypted)
OnBehalfOfCompID	[0..1]	String	Trading partner company ID used when sending messages via a third party (Can be embedded within encrypted data section.)
DeliverToCompID	[0..1]	String	Trading partner company ID used when sending messages via a third party (Can be embedded within encrypted data section.)
SecureDataLen	[0..1]	Length	Required to identify length of encrypted section of message. (Always unencrypted)
SecureData	[0..1]	data	Required when message body is encrypted. Always immediately follows SecureDataLen field.
MsgSeqNum	[1..1]	SeqNum	(Can be embedded within encrypted data section.)

Name	Mult.	Type	Description
SenderSubID	[0..1]	String	(Can be embedded within encrypted data section.)
SenderLocationID	[0..1]	String	Sender's LocationID (i.e. geographic location and/or desk) (Can be embedded within encrypted data section.)
TargetSubID	[0..1]	String	"ADMIN" reserved for administrative messages not intended for a specific user. (Can be embedded within encrypted data section.)
TargetLocationID	[0..1]	String	Trading partner LocationID (i.e. geographic location and/or desk) (Can be embedded within encrypted data section.)
OnBehalfOfSubID	[0..1]	String	Trading partner SubID used when delivering messages via a third party. (Can be embedded within encrypted data section.)
OnBehalfOfLocationID	[0..1]	String	Trading partner LocationID (i.e. geographic location and/or desk) used when delivering messages via a third party. (Can be embedded within encrypted data section.)
DeliverToSubID	[0..1]	String	Trading partner SubID used when delivering messages via a third party. (Can be embedded within encrypted data section.)
DeliverToLocationID	[0..1]	String	Trading partner LocationID (i.e. geographic location and/or desk) used when delivering messages via a third party. (Can be embedded within encrypted data section.)
PossDupFlag	[0..1]	CodeSet	Always required for retransmitted messages, whether prompted by the sending system or as the result of a resend request. (Can be embedded within encrypted data section.)
PossResend	[0..1]	CodeSet	Required when message may be duplicate of another message sent under a different sequence number. (Can be embedded within encrypted data section.)
SendingTime	[1..1]	UTCTimestamp	(Can be embedded within encrypted data section.)
OrigSendingTime	[0..1]	UTCTimestamp	Required for message resent as a result of a ResendRequest. If data is not available set to same value as SendingTime (Can be embedded within encrypted data section.)
XmlDataLen	[0..1]	Length	Required when specifying XmlData to identify the length of a XmlData message block. (Can be embedded within encrypted data section.)



Name	Mult.	Type	Description
XmlData	[0..1]	XMLData	Can contain a XML formatted message block (e.g. FIXML). Always immediately follows XmlDataLen field. (Can be embedded within encrypted data section.). See Volume 1: FIXML Support
MessageEncoding	[0..1]	String	Type of message encoding (non-ASCII characters) used in a message's "Encoded" fields. Required if any "Encoding" fields are used.
LastMsgSeqNumProcessed	[0..1]	SeqNum	The last MsgSeqNum value received by the FIX engine and processed by downstream application, such as trading system or order routing system. Can be specified on every message sent. Useful for detecting a backlog with a counterparty.
HopGrp	[0..*]	Group	Number of repeating groups of historical "hop" information. Only applicable if OnBehalfOfCompID is used, however, its use is optional. Note that some market regulations or counterparties may require tracking of message hops.

Used in messages: AccountSummaryReport, AdjustedPositionReport, Advertisement, AlgoCertificateReport, AlgoCertificateReportAck, AlgoCertificateRequest, AlgoCertificateRequestAck, AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationInstructionAlertRequest, AllocationInstructionAlertRequestAck, AllocationReport, AllocationReportAck, ApplicationMessageReport, ApplicationMessageRequest, ApplicationMessageRequestAck, AssignmentReport, BidRequest, BidResponse, BusinessMessageReject, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralReportAck, CollateralRequest, CollateralResponse, Confirmation, ConfirmationAck, ConfirmationRequest, ContraryIntentionReport, CrossOrderCancelReplaceRequest, CrossOrderCancelRequest, CrossRequest, CrossRequestAck, DerivativeSecurityList, DerivativeSecurityListRequest, DerivativeSecurityListUpdateReport, DontKnowTrade, Email, ExecutionAck, ExecutionReport, Heartbeat, IOI, ListCancelRequest, ListExecute, ListStatus, ListStatusRequest, ListStrikePrice, Logon, Logout, MarginRequirementInquiry, MarginRequirementInquiryAck, MarginRequirementReport, MarketDataIncrementalRefresh, MarketDataReport, MarketDataRequest, MarketDataRequestReject, MarketDataSnapshotFullRefresh, MarketDataStatisticsReport, MarketDataStatisticsRequest, MarketDefinition, MarketDefinitionRequest, MarketDefinitionUpdateReport, MassOrder, MassOrderAck, MassQuote, MassQuoteAck, MultilegOrderCancelReplace, NetworkCounterpartySystemStatusRequest, NetworkCounterpartySystemStatusResponse, NewOrderCross, NewOrderList, NewOrderMultileg, NewOrderSingle, News, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, Order-

MassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderMassStatusRequest, OrderStatusRequest, PartyActionReport, PartyActionRequest, PartyDetailsDefinitionRequest, PartyDetailsDefinitionRequestAck, PartyDetailsListReport, PartyDetailsListRequest, PartyDetailsListUpdateReport, PartyEntitlementsDefinitionRequest, PartyEntitlementsDefinitionRequestAck, PartyEntitlementsReport, PartyEntitlementsRequest, PartyEntitlementsUpdateReport, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PartyRiskLimitsDefinitionRequest, PartyRiskLimitsDefinitionRequestAck, PartyRiskLimitsReport, PartyRiskLimitsReportAck, PartyRiskLimitsRequest, PartyRiskLimitsUpdateReport, PayManagementReport, PayManagementReportAck, PayManagementRequest, PayManagementRequestAck, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport, Quote, QuoteAck, QuoteCancel, QuoteRequest, QuoteRequestReject, QuoteResponse, QuoteStatusReport, QuoteStatusRequest, RFQRequest, RegistrationInstructions, RegistrationInstructionsResponse, Reject, RequestForPositions, RequestForPositionsAck, ResendRequest, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityList, SecurityListRequest, SecurityListUpdateReport, SecurityMassStatus, SecurityMassStatusRequest, SecurityRiskMetricsReport, SecurityStatus, SecurityStatusRequest, SecurityTypeRequest, SecurityTypes, SequenceReset, SettlementInstructionRequest, SettlementInstructions, SettlementObligationReport, SettlementStatusReport, SettlementStatusReportAck, SettlementStatusRequest, SettlementStatusRequestAck, StreamAssignmentReport, StreamAssignmentReportACK, StreamAssignmentRequest, TestActionReport, TestActionRequest, TestActionRequestAck, TestRequest, TestSuiteDefinitionRequest, TestSuiteDefinitionRequestAck, TradeAggregationReport, TradeAggregationRequest, TradeCaptureReport, TradeCaptureReportAck, TradeCaptureReportRequest, TradeCaptureReportRequestAck, TradeMatchReport, TradeMatchReportAck, TradingSessionList, TradingSessionListRequest, TradingSessionListUpdateReport, TradingSessionStatus, TradingSessionStatusRequest, UserNotification, UserRequest, UserResponse, XMLnonFIX

### 180.2.5012 StandardTrailer

The standard FIX message trailer

Name	Mult.	Type	Description
SignatureLength	[0..1]	Length	Required when trailer contains signature. Note: Not to be included within SecureData field
Signature	[0..1]	data	Note: Not to be included within SecureData field
Checksum	[1..1]	String	(Always unencrypted, always last field in message)

Used in messages: AccountSummaryReport, AdjustedPositionReport, Advertisement, AlgoCertifi-

cateReport, AlgoCertificateReportAck, AlgoCertificateRequest, AlgoCertificateRequestAck, AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationInstructionAlertRequest, AllocationInstructionAlertRequestAck, AllocationReport, AllocationReportAck, ApplicationMessageReport, ApplicationMessageRequest, ApplicationMessageRequestAck, AssignmentReport, BidRequest, BidResponse, BusinessMessageReject, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralReportAck, CollateralRequest, CollateralResponse, Confirmation, ConfirmationAck, ConfirmationRequest, ContraryIntentionReport, CrossOrderCancelReplaceRequest, CrossOrderCancelRequest, CrossRequest, CrossRequestAck, DerivativeSecurityList, DerivativeSecurityListRequest, DerivativeSecurityListUpdateReport, DontKnowTrade, Email, ExecutionAck, ExecutionReport, Heartbeat, IOI, ListCancelRequest, ListExecute, ListStatus, ListStatusRequest, ListStrikePrice, Logon, Logout, MarginRequirementInquiry, MarginRequirementInquiryAck, MarginRequirementReport, MarketDataIncrementalRefresh, MarketDataReport, MarketDataRequest, MarketDataRequestReject, MarketDataSnapshotFullRefresh, MarketDataStatisticsReport, MarketDataStatisticsRequest, MarketDefinition, MarketDefinitionRequest, MarketDefinitionUpdateReport, MassOrder, MassOrderAck, MassQuote, MassQuoteAck, MultilegOrderCancelReplace, NetworkCounterpartySystemStatusRequest, NetworkCounterpartySystemStatusResponse, NewOrderCross, NewOrderList, NewOrderMultileg, NewOrderSingle, News, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderMassStatusRequest, OrderStatusRequest, PartyActionReport, PartyActionRequest, PartyDetailsDefinitionRequest, PartyDetailsDefinitionRequestAck, PartyDetailsListReport, PartyDetailsListRequest, PartyDetailsListUpdateReport, PartyEntitlementsDefinitionRequest, PartyEntitlementsDefinitionRequestAck, PartyEntitlementsReport, PartyEntitlementsRequest, PartyEntitlementsUpdateReport, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PartyRiskLimitsDefinitionRequest, PartyRiskLimitsDefinitionRequestAck, PartyRiskLimitsReport, PartyRiskLimitsReportAck, PartyRiskLimitsRequest, PartyRiskLimitsUpdateReport, PayManagementReport, PayManagementReportAck, PayManagementRequest, PayManagementRequestAck, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport, Quote, QuoteAck, QuoteCancel, QuoteRequest, QuoteRequestReject, QuoteResponse, QuoteStatusReport, QuoteStatusRequest, RFQRequest, RegistrationInstructions, RegistrationInstructionsResponse, Reject, RequestForPositions, RequestForPositionsAck, ResendRequest, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityList, SecurityListRequest, SecurityListUpdateReport, SecurityMassStatus, SecurityMassStatusRequest, SecurityRiskMetricsReport, SecurityStatus, SecurityStatusRequest, SecurityTypeRequest, SecurityTypes, SequenceReset, SettlementInstructionRequest, SettlementInstructions, SettlementObligationReport, SettlementStatusReport, SettlementStatusReportAck, SettlementStatusRequest, SettlementStatusRequestAck, StreamAssignmentReport, StreamAssignmentReportACK, StreamAssignmentRequest, TestActionReport, TestActionRequest, TestActionRequestAck, TestRequest, TestSuiteDefinitionRequest, TestSuiteDefinitionRequestAck, TradeAggregationReport, TradeAggregationRequest, TradeCaptur-

eReport, TradeCaptureReportAck, TradeCaptureReportRequest, TradeCaptureReportRequestAck, TradeMatchReport, TradeMatchReportAck, TradingSessionList, TradingSessionListRequest, TradingSessionListUpdateReport, TradingSessionStatus, TradingSessionStatusRequest, UserNotification, UserRequest, UserResponse, XMLnonFIX

#### **180.2.5013 StandardVariance**

Standard variance (over the lifetime of an instrument) or initial variance used to calculate settlement prices, e.g. for variance futures.

Type: **float**

Used in groups: **ClearingPriceParametersGrp**

#### **180.2.5014 StandInstDbID**

Unique identifier used on the Standing Instructions database for the Standing Instructions to be referenced.

Type: **String**

Used in components: **SettlInstructionsData**

Used in groups: **SettlDetails**

Used in messages: **SettlementInstructionRequest**

#### **180.2.5015 StandInstDbName**

Name of the Standing Instruction database represented with StandInstDbType (169) (i.e. the Global Custodian's name).

Type: **String**

Used in components: **SettlInstructionsData**

Used in groups: **SettlDetails**

Used in messages: **SettlementInstructionRequest**

#### **180.2.5016 StandInstDbType**

Identifies the Standing Instruction database used

Type: **int**

Allowed values in StandInstDbTypeCodeSet:

Code	Name	Description
0	Other	Other
1	DTCSID	DTC SID
2	ThomsonALERT	Thomson ALERT
3	AGlobalCustodian	A Global Custodian (StandInstDBName (70) must be provided)
4	AccountNet	AccountNet

Used in components: **SettlInstructionsData**

Used in groups: **SettlDetails**

Used in messages: **SettlementInstructionRequest**

#### **180.2.5017 StartCash**

Starting dirty cash consideration of a financing deal, i.e. paid to the seller on the Start Date.

Type: **Amt**

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **CollateralAssignment**, **CollateralInquiry**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**, **Confirmation**, **ExecutionReport**

#### **180.2.5018 StartDate**

Start date of a financing deal, i.e. the date the buyer pays the seller cash and takes control of the collateral

Type: **LocalMktDate**

Used in components: **FinancingDetails**

#### **180.2.5019 StartMaturityMonthYear**

Starting maturity month year for an option class

Type: **MonthYear**

Used in groups: **MaturityRules**

#### **180.2.5020 StartPriceRange**

Lower boundary for price range.

Type: **Price**

Used in groups: **PriceRangeRuleGrp**

#### **180.2.5021 StartStrikePxRange**

Starting price for the range to which the StrikeIncrement applies. Price refers to the price of the underlying

Type: **Price**

Used in groups: **StrikeRules**

#### **180.2.5022 StartTickPriceRange**

Starting price range for specified tick increment

Type: **Price**

Used in groups: **TickRules**

#### **180.2.5023 StateOrProvinceOfIssue**

A two-character state or province abbreviation.

Type: **String**

Used in components: **Instrument**

#### **180.2.5024 StatsIndGrp**

---

Name	Mult.	Type	Description
<b>NoStatsIndicators</b>	[1..1]	NumInGroup	Number of statistics indicators

---

Name	Mult.	Type	Description
StatsType	[0..1]	CodeSet	Indicates that the MD Entry is eligible for inclusion in the type of statistic specified by the StatsType. Must be provided if NoStatsIndicators greater than 0.

Used in groups: MDIncGrp

### 180.2.5025 StatsType

Type of statistics

Type: int

Allowed values in StatsTypeCodeSet:

Code	Name	Description
1	ExchangeLast	Exchange Last
2	High	High / Low Price
3	AveragePrice	Average Price (VWAP, TWAP .. )
4	Turnover	Turnover (Price * Qty)

Used in groups: StatsIndGrp

### 180.2.5026 StatusText

A text description associated with a network status.

Type: String

Used in groups: ComplIDStatGrp

### 180.2.5027 StatusValue

Indicates the status of a network connection

Type: int

Allowed values in StatusValueCodeSet:

Code	Name	Description
1	Connected	Connected
2	NotConnectedUnexpected	Not Connected - down expected up
3	NotConnectedExpected	Not Connected - down expected down
4	InProcess	In Process

Used in groups: [CompIDStatGrp](#)

### 180.2.5028 Stipulations

The Stipulations component block is used in Fixed Income to provide additional information on a given security. These additional information are usually not considered static data information.

Name	Mult.	Type	Description
<a href="#">NoStipulations</a>	[1..1]	NumInGroup	
<a href="#">StipulationType</a>	[0..1]	CodeSet	Required if NoStipulations >0
<a href="#">StipulationValue</a>	[0..1]	String	

Used in groups: [ListOrdGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [SecListGrp](#), [SecLstUpdRelSymGrp](#), [Trd-CapRptAckSideGrp](#), [TrdCapRptSideGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [Confirmation](#), [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [IOI](#), [NewOrderCross](#), [NewOrderSingle](#), [Order-CancelReplaceRequest](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [SecurityDefinition](#), [SecurityDefinitionRequest](#), [SecurityDefinitionUpdateReport](#)

### 180.2.5029 StipulationType

For Fixed Income.

Type of Stipulation.

Other types may be used by mutual agreement of the counterparties.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: [String](#)



## Allowed values in StipulationTypeCodeSet:

Code	Name	Description
ABS	AbsolutePrepaymentSpeed	Absolute Prepayment Speed
AMT	AlternativeMinimumTax	Alternative Minimum Tax (Y/N)
INCURRCVY	IncurredRecovery	Incurred recovery (Y/N). Specifies whether incurred recovery is applicable (Y) or not (N). Outstanding Swap Notional Amount is defined at any time on any day, as the greater of: (a) Zero; If Incurred Recovery Amount Applicable: (b) The Original Swap Notional Amount minus the sum of all Incurred Loss Amounts and all Incurred Recovery Amounts (if any) determined under this Confirmation at or prior to such time. Incurred Recovery Amount not populated: (b) The Original Swap Notional Amount minus the sum of all Incurred Loss Amounts determined under this Confirmation at or prior to such time. 2009 CDX Tranche Terms.
ADDTRM	AdditionalTerm	Additional term. Used for representing information contained in the Additional Terms field of the 2003 Master Credit Derivatives confirm.
AUTOREINV	AutoReinvestment	Auto Reinvestment at <rate> or better
CPP	ConstantPrepaymentPenalty	Constant Prepayment Penalty
BANKQUAL	BankQualified	Bank qualified (Y/N)
CPR	ConstantPrepaymentRate	Constant Prepayment Rate
MODEQTYDLVY	ModifiedEquityDelivery	Modified equity delivery. Indicates whether delivery of selected obligations having an amount greater than the reference entity notional amount is allowed (Y) or (N). 2005 iTraxx tranching Transactions Standard Terms Supplement.
BGNCON	BargainConditions	Bargain conditions (see StipulationValue (234) for values)
CPY	ConstantPrepaymentYield	Constant Prepayment Yield
NOREFOBLIG	NoReferenceObligation	No reference obligation (Y/N). When specified as "Y" this indicates that there is no Reference Obligation associated with this Credit Default Swap and that there will never be one. 2003 ISDA Credit Derivatives Definitions.
COUPON	CouponRange	Coupon range
HEP	FinalCPR of Home Equity Prepayment Curve	final CPR of Home Equity Prepayment Curve

Code	Name	Description
UNKREFOBLIG	UnknownReferenceObligation	Unknown reference obligation (Y/N). When specified as "Y" this indicates that the Reference obligation associated with the Credit Default Swap is currently not known. This is not valid for Legal Confirmation purposes, but is valid for earlier stages in the trade life cycle (e.g. Broker Confirmation). 2003 FpML-CD-4.0.
ALLGUARANTEES	AllGuarantees	All guarantees (Y/N). Indicates whether an obligation of the Reference Entity, guaranteed by the Reference Entity on behalf of a non-Affiliate, is to be considered an Obligation for the purpose of the transaction (Y) or (N). ISDA 2003 Term: All Guarantees.
CURRENCY	ISOCurrencyCode	ISO Currency Code
MHP	PercentOfManufacturedHousingPrepaymentCurve	Percent of Manufactured Housing Prepayment Curve
CUSTOMDATE	CustomStart	Custom start/end date
MPR	MonthlyPrepaymentRate	Monthly Prepayment Rate
REFPX	ReferencePrice	Reference price (Y/N). Specifies the reference price expressed as a percentage between 0 and 1 (e.g. 0.05 is 5%). The reference price is used to determine (a) for physically settled trades, the Physical Settlement Amount, which equals the Floating Rate Payer Calculation Amount times the Reference Price and (b) for cash settled trades, the Cash Settlement Amount, which equals the greater of (i) the difference between the Reference Price and the Final Price and (ii) zero. ISDA 2003 Term: Reference Price.
GEOG	Geographics	Geographics and % range (ex. 234=CA 0-80 [minimum of 80% California assets])
PPC	PercentOfProspectusPrepaymentCurve	Percent of Prospectus Prepayment Curve

Code	Name	Description
REFPOLICY	ReferencePolicy	Reference policy (Y/N). Indicates whether the reference obligation is guaranteed (Y), or not (N), under a reference policy. If the Reference Obligation is guaranteed under a Reference Policy, and such Reference Policy by its terms excludes any component of the Expected Principal Amount for purposes of determining the liability of the relevant Insurer, or the Insurer is otherwise not required to pay any such amounts under the terms of the Reference Policy, the relevant component or amount shall also be excluded for purposes of determining the Expected Principal Amount with respect to any determination of Principal Shortfall hereunder. 2006 ISDA CDS on MBS Terms.
HAIRCUT	ValuationDiscount	Valuation Discount
PSA	PercentOfBMAPrepaymentCurve	Percent of BMA Prepayment Curve
SECRDLIST	SecuredList	Secured list (Y/N). Specifies whether a list of Syndicated Secured Obligations (also known as the Relevant Secured List) exists (Y), or not (N), for the Reference Entity. With respect to any day, the list of Syndicated Secured Obligations of the Designated Priority of the Reference Entity published by Markit Group Limited or any successor thereto appointed by the Specified Dealers (the "Secured List Publisher") on or most recently before such day, which list is currently available at [ <a href="http://www.markit.com">http://www.markit.com</a> ]. ISDA 2003 Term: Relevant Secured List.
INSURED	Insured	Insured (Y/N)
SMM	SingleMonthlyMortality	Single Monthly Mortality
ISSUE	IssueDate	Year Or Year/Month of Issue (ex. 234=2002/09)
ISSUER	Issuer	Issuer's ticker
ISSUESIZE	IssueSizeRange	issue size range
LOOKBACK	LookbackDays	Lookback Days
LOT	ExplicitLotIdentifier	Explicit lot identifier
LOTVAR	LotVariance	Lot Variance (value in percent maximum over- or under-allocation allowed)
MAT	MaturityYearAndMonth	Maturity Year And Month
MATURITY	MaturityRange	Maturity range
MAXSUBS	MaximumSubstitutions	Maximum substitutions (Repo)
MINDNOM	MinimumDenomination	Minimum denomination
MININCR	MinimumIncrement	Minimum increment

Code	Name	Description
MINQTY	MinimumQuantity	Minimum quantity
PAYFREQ	PaymentFrequency	Payment frequency, calendar
PIECES	NumberOfPieces	Number Of Pieces
PMAX	PoolsMaximum	Pools Maximum
PPL	PoolsPerLot	Pools per Lot
PPM	PoolsPerMillion	Pools per Million
PPT	PoolsPerTrade	Pools per Trade
PRICE	PriceRange	Price Range
PRICEFREQ	PricingFrequency	Pricing frequency
PROD	ProductionYear	Production Year
PROTECT	CallProtection	Call protection
PURPOSE	Purpose	Purpose
PXSOURCE	BenchmarkPriceSource	Benchmark price source
RATING	RatingSourceAndRange	Rating source and range
REDEMPTION	TypeOfRedemption	Type Of Redemption - values are: NonCallable, Prefunded, EscrowedToMaturity, Putable, Convertible
RESTRICTED	Restricted	Restricted (Y/N)
SECTOR	MarketSector	Market Sector
SECTYPE	SecurityTypeIncludedOrExcluded	Security Type included or excluded
STRUCT	Structure	Structure
SUBSFREQ	SubstitutionsFrequency	Substitutions frequency (Repo)
SUBSLEFT	SubstitutionsLeft	Substitutions left (Repo)
TEXT	FreeformText	Freeform Text
TRDVAR	TradeVariance	Trade Variance (value in percent maximum over- or under-allocation allowed)
WAC	WeightedAverageCoupon	Weighted Average Coupon - value in percent (exact or range) plus "Gross" or "Net" of servicing spread (the default) (ex. 234=6.5-Net [minimum of 6.5% net of servicing fee])
WAL	WeightedAverageLifeCoupon	Weighted Average Life Coupon - value in percent (exact or range)
WALA	WeightedAverageLoanAge	Weighted Average Loan Age - value in months (exact or range)
WAM	WeightedAverageMaturity	Weighted Average Maturity - value in months (exact or range)

Code	Name	Description
WHOLE	WholePool	Whole Pool (Y/N)
YIELD	YieldRange	Yield Range
AVFICO	AverageFICOScore	Average FICO Score
ORIGAMT	OriginalAmount	Original amount. The original issued amount of a mortgage backed security or other loan/asset backed security.
AVSIZE	AverageLoanSize	Average Loan Size
POOLEFFDT	PoolEffectiveDate	Pool effective date
MAXBAL	MaximumLoanBalance	Maximum Loan Balance
POOLINITFCTR	PoolInitialFactor	Pool initial factor. For mortgage backed securities, the part of the mortgage that is outstanding on trade inception, i.e. has not been repaid yet as principal. It is expressed as a multiplier factor to the mortgage: where 1 means that the whole mortgage amount is outstanding, 0.8 means that 80% remains to be repaid and 20% has been repaid.
POOL	PoolIdentifier	Pool Identifier
TRANCHE	Tranche	Tranche identifier. Identifies the tranche of a mortgage backed security, loan, collateralized mortgage obligation or similar securities that can be split into different risk or maturity (for example) classes.
ROLLTYPE	TypeOfRollTrade	Type of Roll trade
SUBSTITUTION	Substitution	Substitution (Y/N). Indicates whether substitution is applicable (Y) or (N).
MULTEXCHFLLBCK	MULTEXCHFLLBCK	Multiple exchange fallback (Y/N). For an index option transaction, indicates whether a relevant "Multiple Exchange Index Annex" is applicable (Y) to the transaction or not (N). This annex defines additional provisions which are applicable where an index is comprised of component securities that are traded on multiple exchanges.
REFTRADE	ReferenceToRollingOrClosing-Trade	Reference to rolling or closing trade
COMPSECFLBCK	COMPSECFLBCK	Component security fallback (Y/N). For an index option transaction, indicates whether a relevant "Component Security Index Annex" is applicable (Y) to the transaction or not (N).
REFPRIN	PrincipalOfRollingOrClosing-Trade	Principal to rolling or closing trade

Code	Name	Description
LOCLJRSRCTN	LOCLJRSRCTN	Local jurisdiction (Y/N). "Local Jurisdiction" is used in the AEJ Master Confirmation to determine applicability (Y), or not (N), of local taxes (including taxes, duties, and similar charges) imposed by the taxing authority of the local jurisdiction.
REFINT	InterestOfRollingOrClosingTrade	Interest of rolling or closing trade
AVAILQTY	AvailableOfferQuantity-ToBeShownToTheStreet	Available offer quantity to be shown to the street
RELJRSRCTN	RELJRSRCTN	Relevant jurisdiction (Y/N). "Relevant Jurisdiction" is used in the AEJ Master Confirmation to determine applicability (Y), or not (N), of local taxes (including taxes, duties and similar charges) that would be imposed by the taxing authority of the "country of underlier" on a "hypothetical broker dealer" assuming that the applicable hedge positions are held by its office in the Relevant Jurisdiction.
BROKERCREDIT	BrokerCredit	Broker's sales credit
INTERNALPX	OfferPriceToBeShownToInternalBrokers	Offer price to be shown to internal brokers
INTERNALQTY	OfferQuantityToBeShownToInternalBrokers	Offer quantity to be shown to internal brokers
LEAVEQTY	TheMinimumResidualOffer-Quantity	The minimum residual offer quantity
MAXORDQTY	MaximumOrderSize	Maximum order size
ORDRINCR	OrderQuantityIncrement	Order quantity increment
PRIMARY	PrimaryOrSecondaryMarketIndicator	Primary or Secondary market indicator
SALESCREDITOVR	BrokerSalesCreditOverride	Broker sales credit override
TRADERCREDIT	TraderCredit	Trader's credit
DISCOUNT	DiscountRate	Discount Rate (when price is denominated in percent of par)
YTM	YieldToMaturity	Yield to Maturity (when YieldType(235) and Yield(236) show a different yield)
PAYOFF	InterestPayoffOfRollingOrAmendingTrade	Interest payoff of rolling or amending trade

Used in groups: **Stipulations**

**180.2.5030 StipulationValue**

For Fixed Income. Value of stipulation.

The expression can be an absolute single value or a combination of values and logical operators:

< value

> value

<= value

>= value

value

value - value2

value OR value2

value AND value2

YES

NO

Bargain conditions recognized by the London Stock Exchange - to be used when StipulationType is "BGNCON".

CD = Special cum Dividend

XD = Special ex Dividend

CC = Special cum Coupon

XC = Special ex Coupon

CB = Special cum Bonus

XB = Special ex Bonus

CR = Special cum Rights

XR = Special ex Rights

CP = Special cum Capital Repayments

XP = Special ex Capital Repayments

CS = Cash Settlement

SP = Special Price

TR = Report for European Equity Market Securities in accordance with Chapter 8 of the Rules.

GD = Guaranteed Delivery

Values for StipulationType = "PXSOURCE":

BB GENERIC

BB FAIRVALUE

BROKERTEC

ESPEED

GOVPX

HILLIARD FARBER

ICAP

TRADEWEB

TULLETT LIBERTY

If a particular side of the market is wanted append /BID /OFFER or /MID.

plus appropriate combinations of the above and other expressions by mutual agreement of the counterparties.

Examples: ">=60", ".25", "ORANGE OR CONTRACOSTA", etc.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **String**

Used in groups: **Stipulations**

### **180.2.5031 StopPx**

Price per unit of quantity (e.g. per share)

Type: **Price**

Used in components: **TradeReportOrderDetail**

Used in groups: **ListOrdGrp**

Used in messages: **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**



**180.2.5032 StrategyLinkID**

Identifies the multileg strategy (e.g. spread) to which the trade belongs. This links together trade legs executed as part of a strategy during a single match event.

Type: **String**

Used in groups: **MDFullGrp**, **MDIncGrp**, **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**

**180.2.5033 StrategyParameterName**

Name of parameter

Type: **String**

Used in groups: **StrategyParametersGrp**

**180.2.5034 StrategyParametersGrp**

Name	Mult.	Type	Description
<b>NoStrategyParameters</b>	[1..1]	NumInGroup	Indicates number of strategy parameters
<b>StrategyParameterName</b>	[0..1]	String	Name of parameter
<b>StrategyParameterType</b>	[0..1]	CodeSet	Datatype of the parameter.
<b>StrategyParameterValue</b>	[0..1]	String	Value of the parameter

Used in groups: **ListOrdGrp**

Used in messages: **AlgoCertificateReport**, **CrossOrderCancelReplaceRequest**, **ExecutionReport**, **Multi-legOrderCancelReplace**, **NewOrderCross**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **TestActionReport**, **TestSuiteDefinitionRequest**

**180.2.5035 StrategyParameterType**

Datatype of the parameter

Type: **int**

Allowed values in StrategyParameterTypeCodeSet:

Code	Name	Description
1	Int	Int
2	Length	Length
3	NumInGroup	NumInGroup
4	SeqNum	SeqNum
5	TagNum	TagNum
6	Float	float
7	Qty	Qty
8	Price	Price
9	PriceOffset	PriceOffset
10	Amt	Amt
11	Percentage	Percentage
12	Char	Char
13	Boolean	Boolean
14	String	String
15	MultipleCharValue	MultipleCharValue
16	Currency	Currency
17	Exchange	Exchange
18	MonthYear	MonthYear
19	UTCTimestamp	UTCTimestamp
20	UTCTimeOnly	UTCTimeOnly
21	LocalMktDate	LocalMktDate
22	UTCDateOnly	UTCDateOnly
23	Data	data
24	MultipleStringValue	MultipleStringValue
25	Country	Country
26	Language	Language
27	TZTimeOnly	TZTimeOnly
28	TZTimestamp	TZTimestamp
29	Tenor	Tenor

Used in groups: [StrategyParametersGrp](#)

**180.2.5036 StrategyParameterValue**

Value of the parameter

Type: **String**

Used in groups: **StrategyParametersGrp**

**180.2.5037 StrategyType**

Specifies the type of trade strategy.

Type: **String**

Allowed values in StrategyTypeCodeSet:

Code	Name	Description
STD	Straddle	Straddle
STG	Strangle	Strangle
BF	Butterfly	Butterfly
CNDR	Condor	Condor
CISN	CallableInversibleSnowball	Callable inversible snowball
OTHER	Other	Other

Used in components: **Instrument**

**180.2.5038 StreamAsgnAckType**

Type of acknowledgement.

Type: **int**

Allowed values in StreamAsgnAckTypeCodeSet:

Code	Name	Description
0	AssignmentAccepted	Assignment Accepted
1	AssignmentRejected	Assignment Rejected

Used in messages: **StreamAssignmentReportACK**

**180.2.5039 StreamAsgnRejReason**

Reason code for stream assignment request reject.

Type: **int**

Allowed values in StreamAsgnRejReasonCodeSet:

Code	Name	Description
0	UnknownClient	Unknown client
1	ExceedsMaximumSize	Exceeds maximum size
2	UnknownOrInvalidCurrencyPair	Unknown or Invalid currency pair
3	NoAvailableStream	No available stream
99	Other	Other

Used in groups: **StrmAsgnRptInstrmtGrp**

Used in messages: **StreamAssignmentReportACK**

**180.2.5040 StreamAsgnReqID**

Unique identifier for the stream assignment request provided by the requester.

Type: **String**

Used in messages: **StreamAssignmentReport, StreamAssignmentRequest**

**180.2.5041 StreamAsgnReqType**

Type of stream assignment request.

Type: **int**

Allowed values in StreamAsgnReqTypeCodeSet:

Code	Name	Description
1	StreamAssignmentForNewCustomer	Stream assignment for new customer(s)
2	StreamAssignmentForExistingCustomer	Stream assignment for existing customer(s)

Used in messages: **StreamAssignmentReport, StreamAssignmentRequest**

**180.2.5042 StreamAsgnRptID**

Unique identifier of the stream assignment report provided by the respondent.

Type: **String**

Used in messages: **StreamAssignmentReport**, **StreamAssignmentReportACK**

**180.2.5043 StreamAsgnType**

The type of assignment being affected in the Stream Assignment Report.

Type: **int**

Allowed values in StreamAsgnTypeCodeSet:

Code	Name	Description
1	Assignment	Assignment
2	Rejected	Rejected
3	Terminate	Terminate/Unassign

Used in groups: **StrmAsgnRptInstrmtGrp**

**180.2.5044 StreamAssetAttributeGrp**

The StreamAssetAttributeGrp is a repeating subcomponent of the StreamCommodity component used to detail commodity attributes, quality standards and reject limits.

Name	Mult.	Type	Description
<b>NoStreamAssetAttributes</b>	[1..1]	NumInGroup	
<b>StreamAssetAttributeType</b>	[0..1]	String	Required if NoStreamAssetAttributes(41237) > 0.
<b>StreamAssetAttributeValue</b>	[0..1]	String	
<b>StreamAssetAttributeLimit</b>	[0..1]	String	

Used in components: **StreamCommodity**

#### **180.2.5045 StreamAssetAttributeLimit**

Limit or lower acceptable value of the attribute.

Type: **String**

Used in groups: **StreamAssetAttributeGrp**

#### **180.2.5046 StreamAssetAttributeType**

Specifies the name of the attribute.

See [http://www.fixtradingcommunity.org/codelists#Asset\\_Attribute\\_Types](http://www.fixtradingcommunity.org/codelists#Asset_Attribute_Types) for code list of applicable asset attribute types.

Type: **String**

Used in groups: **StreamAssetAttributeGrp**

#### **180.2.5047 StreamAssetAttributeValue**

Specifies the value of the attribute.

Type: **String**

Used in groups: **StreamAssetAttributeGrp**

#### **180.2.5048 StreamCalculationBalanceOfFirstPeriod**

When specified and set to 'Y', it indicates that the first calculation period should run from the effective date to the end of the calendar period in which the effective date falls (e.g. Jan 15 - Jan 31 if the calculation periods are one month long and effective date is Jan 15.). If 'N' or not specified, it indicates that the first calculation period should run from the effective date for one whole period (e.g. Jan 15 to Feb 14 if the calculation periods are one month long and the effective date is Jan 15.).

Type: **Boolean**

Used in components: **StreamCalculationPeriodDates**

#### **180.2.5049 StreamCalculationCorrectionPeriod**

Time unit multiplier for the length of time after the publication of the data when corrections can be made.

Type: **int**

Used in components: **StreamCalculationPeriodDates**

#### **180.2.5050 StreamCalculationCorrectionUnit**

Time unit associated with the length of time after the publication of the data when corrections can be made.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **StreamCalculationPeriodDates**

#### **180.2.5051 StreamCalculationFrequencyPeriod**

Time unit multiplier for the frequency at which calculation period end dates occur.

Type: **int**

Used in components: **StreamCalculationPeriodDates**

#### **180.2.5052 StreamCalculationFrequencyUnit**

Time unit associated with the frequency at which calculation period end dates occur.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week

Code	Name	Description
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: [StreamCalculationPeriodDates](#)

### 180.2.5053 StreamCalculationPeriodBusinessCenter

The business center calendar used to adjust calculation periods, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [StreamCalculationPeriodBusinessCenterGrp](#)

### 180.2.5054 StreamCalculationPeriodBusinessCenterGrp

StreamCalculationPeriodBusinessCenterGrp is a repeating subcomponent within the StreamCalculationPeriodDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
<a href="#">NoStreamCalculationPeriodBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">StreamCalculationPeriodBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoStreamCalculationPeriodBusinessCenters</a> (40958) > 0.

Used in components: [StreamCalculationPeriodDates](#)



**180.2.5055 StreamCalculationPeriodBusinessDayConvention**

The business day convention used to adjust calculation periods. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **StreamCalculationPeriodDates**

**180.2.5056 StreamCalculationPeriodDate**

The adjusted or unadjusted fixed calculation period date.

Type: **LocalMktDate**

Used in groups: **StreamCalculationPeriodDateGrp**

**180.2.5057 StreamCalculationPeriodDateGrp**

The StreamCalculationPeriodDateGrp is a repeating subcomponent of the StreamCalculationPeriodDates component used to detail fixed dates for the swap stream.

Name	Mult.	Type	Description
<b>NoStreamCalculationPeriodDates</b>	[1..1]	NumInGroup	
<b>StreamCalculationPeriodDate</b>	[0..1]	LocalMktDate	Required if NoStreamCalculationPeriodDates(41241) > 0.

Name	Mult.	Type	Description
<a href="#">StreamCalculationPeriodDateType</a>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [StreamCalculationPeriodDates](#)

### 180.2.5058 [StreamCalculationPeriodDates](#)

[StreamCalculationPeriodDates](#) is a subcomponent of the [StreamGrp](#) component used to specify the calculation period dates of the stream.

Name	Mult.	Type	Description
<a href="#">StreamCalculationPeriodDatesXID</a>	[0..1]	XID	
<a href="#">StreamCalculationPeriodDatesXIDRef</a>	[0..1]	XIDREF	
<a href="#">StreamCalculationPeriodBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the <a href="#">DateAdjustment</a> component in <a href="#">Instrument</a> . The specified value would be specific to this instance of the calculation period dates of the stream.
<a href="#">StreamCalculationPeriodBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the <a href="#">DateAdjustment</a> component in <a href="#">Instrument</a> . The specified values would be specific to this instance of the calculation period dates of the stream.
<a href="#">StreamCalculationPeriodDateGrp</a>	[0..*]	Group	
<a href="#">StreamFirstPeriodStartDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">StreamFirstPeriodStartDateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the <a href="#">DateAdjustment</a> component in <a href="#">Instrument</a> . The specified value would be specific to this instance of the calculation period dates of the stream.
<a href="#">StreamFirstPeriodStartDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the <a href="#">DateAdjustment</a> component in <a href="#">Instrument</a> . The specified values would be specific to this instance of the calculation period dates of the stream.
<a href="#">StreamFirstPeriodStartDateAdjusted</a>	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
StreamFirstRegularPeriodStartDateUnadjusted	[0..1]	LocalMktDate	
StreamFirstCompoundingPeriodEndDateUnadjusted	[0..1]	LocalMktDate	
StreamLastRegularPeriodEndDateUnadjusted	[0..1]	LocalMktDate	
StreamCalculationFrequencyPeriod	[0..1]	int	Conditionally required when StreamCalculationFrequencyUnit(40083) is specified.
StreamCalculationFrequencyUnit	[0..1]	CodeSet	Conditionally required when StreamCalculationFrequencyPeriod(40082) is specified.
StreamCalculationRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the stream calculation dates.
StreamCalculationBalanceOfFirstPeriod	[0..1]	Boolean	
StreamCalculationCorrectionPeriod	[0..1]	int	Conditionally required when StreamCalculationCorrectionUnit(41248) is specified.
StreamCalculationCorrectionUnit	[0..1]	CodeSet	Conditionally required when StreamCalculationCorrectionPeriod(41247) is specified.

Used in groups: [StreamGrp](#)

#### 180.2.5059 StreamCalculationPeriodDatesXID

Identifier of this calculation period for cross referencing elsewhere in the message.

Type: [XID](#)

Used in components: [StreamCalculationPeriodDates](#)

#### 180.2.5060 StreamCalculationPeriodDatesXIDRef

Cross reference to another calculation period for duplicating its properties.

Type: **XIDREF**

Used in components: **StreamCalculationPeriodDates**

#### **180.2.5061 StreamCalculationPeriodDateType**

Specifies the type of fixed calculation period date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **StreamCalculationPeriodDateGrp**

#### **180.2.5062 StreamCalculationRollConvention**

The convention for determining the sequence of end dates. It is used in conjunction with a specified frequency. Used only to override the roll convention specified in the DateAdjustment component within the Instrument component.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month

Code	Name	Description
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEigthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.

Code	Name	Description
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [StreamCalculationPeriodDates](#)

#### **180.2.5063 StreamCommodityAltID**

Alternate security identifier value for the commodity.

Type: [String](#)

Used in groups: [StreamCommodityAltIDGrp](#)

#### **180.2.5064 StreamCommodityAltIDGrp**

StreamCommodityAltIDGrp is a subcomponent of the StreamCommodity component used to specify alternate identifiers.

Name	Mult.	Type	Description
<a href="#">NoStreamCommodityAltIDs</a>	[1..1]	NumInGroup	
<a href="#">StreamCommodityAltID</a>	[0..1]	String	Required if NoStreamCommodityAltIDs(41277) > 0.
<a href="#">StreamCommodityAltIDSource</a>	[0..1]	String	Required if NoStreamCommodityAltIDs(41277) > 0.

Used in components: [StreamCommodity](#)

#### **180.2.5065 StreamCommodityAltIDSource**

Identifies the class or source of the alternate commodity security identifier.

Type: [String](#)

Used in groups: [StreamCommodityAltIDGrp](#)

**180.2.5066 StreamCommodityBase**

Specifies the general base type of the commodity traded. Where possible, this should follow the naming convention used in the 2005 ISDA Commodity Definitions.

Type: **String**

Used in components: **StreamCommodity**

**180.2.5067 StreamCommodity**

StreamCommodity is a subcomponent of the Stream component used to identify and describe the underlying commodity.

Name	Mult.	Type	Description
StreamCommodityBase	[0..1]	String	
StreamCommodityType	[0..1]	String	
StreamCommoditySecurityID	[0..1]	String	Conditionally required when StreamCommoditySecurityIDSource(41254) is specified.
StreamCommoditySecurityIDSource	[0..1]	CodeSet	Conditionally required when StreamCommoditySecurityID(41253) is specified.
StreamCommodityAltIDGrp	[0..*]	Group	
StreamCommodityDesc	[0..1]	String	
EncodedStreamCommodityDescLen	[0..1]	Length	Must be set if EncodedCommodityDesc(41257) field is specified and must immediately precede it.
EncodedStreamCommodityDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the StreamCommodityDesc(41255) field in the encoded format specified via the MessageEncoding(347) field.
StreamCommodityDeliveryPricingRegion	[0..1]	String	May be used to specify the delivery or pricing region of a non-standard commodity swap contract (e.g. when InstrAttribType(871)=38 (US standard contract indicator) and InstrAttribValue(872)=N).
StreamAssetAttributeGrp	[0..*]	Group	
StreamCommodityUnitOfMeasure	[0..1]	CodeSet	
StreamCommodityCurrency	[0..1]	Currency	
StreamCommodityExchange	[0..1]	Exchange	
StreamCommodityRateSource	[0..1]	int	

Name	Mult.	Type	Description
StreamCommodityRateReferencePage	[0..1]	String	
StreamCommodityRateReferencePageHeading	[0..1]	String	
StreamDataProvider	[0..1]	String	
StreamCommodityDataSourceGrp	[0..*]	Group	
StreamCommodityPricingType	[0..1]	String	
StreamCommodityNearbySettlDayPeriod	[0..1]	int	Conditionally required when StreamCommodityNearbySettlDayUnit(41267) is specified.
StreamCommodityNearbySettlDayUnit	[0..1]	CodeSet	Conditionally required when StreamCommodityNearbySettlDayPeriod(41266) is specified.
StreamCommoditySettlDateUnadjusted	[0..1]	LocalMktDate	
StreamCommoditySettlDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of settlement dates.
StreamCommoditySettlBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of settlement dates.
StreamCommoditySettlDateAdjusted	[0..1]	LocalMktDate	
StreamCommoditySettlMonth	[0..1]	int	
StreamCommoditySettlDateRollPeriod	[0..1]	int	Conditionally required when StreamCommoditySettlDateRollUnit(41273) is specified.
StreamCommoditySettlDateRollUnit	[0..1]	CodeSet	Conditionally required when StreamCommoditySettlDateRollPeriod(41272) is specified.
StreamCommoditySettlDayType	[0..1]	CodeSet	
StreamCommoditySettlPeriodGrp	[0..*]	Group	
StreamCommodityXID	[0..1]	XID	
StreamCommodityXIDRef	[0..1]	XIDREF	

Used in groups: **StreamGrp**



**180.2.5068 StreamCommodityCurrency**

Identifies the currency of the commodity asset. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **StreamCommodity**

**180.2.5069 StreamCommodityDataSourceGrp**

StreamCommodityDataSourceGrp is a subcomponent of the StreamCommodity component used to specify sources of data, e.g. weather stations. The order of entry determines priority – first is the main source, second is fallback, third is second fallback.

Name	Mult.	Type	Description
NoStreamCommodityDataSources	[1..1]	NumInGroup	
StreamCommodityDataSourceID	[0..1]	String	Required if NoStreamCommodityDataSources(41280) > 0.
StreamCommodityDataSourceIDType	[0..1]	CodeSet	Required if NoStreamCommodityDataSources(41280) > 0.

Used in components: **StreamCommodity**

**180.2.5070 StreamCommodityDataSourceID**

Data source identifier.

Type: **String**

Used in groups: **StreamCommodityDataSourceGrp**

**180.2.5071 StreamCommodityDataSourceIDType**

Type of data source identifier.

Type: **int**

Allowed values in StreamCommodityDataSourceIDTypeCodeSet:

Code	Name	Description
0	City	City (4 character business center code)
1	Airport	Airport (IATA standard)
2	WeatherStation	Weather station WBAN (Weather Bureau Army Navy)
3	WeatherIndex	Weather index WMO (World Meteorological Organization)

Used in groups: [StreamCommodityDataSourceGrp](#)

#### **180.2.5072 StreamCommodityDeliveryPricingRegion**

The delivery or pricing region associated with the commodity swap. See [http://www.ecfr.gov/cgi-bin/text-idx?SID=660d6a40f836aa6ddf213cba080c5b22&node=ap17.2.43\\_17.e&rgn=div9](http://www.ecfr.gov/cgi-bin/text-idx?SID=660d6a40f836aa6ddf213cba080c5b22&node=ap17.2.43_17.e&rgn=div9) for the external code list.

Type: [String](#)

Used in components: [StreamCommodity](#)

#### **180.2.5073 StreamCommodityDesc**

Description of the commodity asset.

Type: [String](#)

Used in components: [StreamCommodity](#)

#### **180.2.5074 StreamCommodityExchange**

Identifies the exchange where the commodity is traded.

Type: [Exchange](#)

Used in components: [StreamCommodity](#)

#### **180.2.5075 StreamCommodityNearbySettlDayPeriod**

Time unit multiplier for the nearby settlement day.

Type: [int](#)

Used in components: [StreamCommodity](#)

**180.2.5076 StreamCommodityNearbySettlDayUnit**

Time unit associated with the nearby settlement day.

Type: **String**

Allowed values in StreamCommodityNearbySettlDayUnitCodeSet:

Code	Name	Description
Wk	Week	Week
Mo	Month	Month

Used in components: **StreamCommodity**

**180.2.5077 StreamCommodityPricingType**

Specifies how the pricing or rate setting of the trade is to be determined or based upon.

See [http://www.fixtradingcommunity.org/codelists#Commodity\\_Rate\\_Pricing\\_Type](http://www.fixtradingcommunity.org/codelists#Commodity_Rate_Pricing_Type) for code list of applicable commodity pricing types.

Type: **String**

Used in components: **StreamCommodity**

**180.2.5078 StreamCommodityRateReferencePage**

Identifies the reference "page" from the rate source.

Type: **String**

Used in components: **StreamCommodity**

**180.2.5079 StreamCommodityRateReferencePageHeading**

Identifies the page heading from the rate source.

Type: **String**

Used in components: **StreamCommodity**

**180.2.5080 StreamCommodityRateSource**

Identifies the source of rate information used for commodities.

See [http://www.fixtradingcommunity.org/codelists#Commodity\\_Rate\\_Source](http://www.fixtradingcommunity.org/codelists#Commodity_Rate_Source) for code list of applicable sources.

Type: **int**

Used in components: **StreamCommodity**

**180.2.5081 StreamCommoditySecurityID**

Specifies the market identifier for the commodity.

Type: **String**

Used in components: **StreamCommodity**

**180.2.5082 StreamCommoditySecurityIDSource**

Identifies the class or source of the StreamCommoditySecurityIDSource(41253) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch

Code	Name	Description
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **StreamCommodity**

### 180.2.5083 StreamCommoditySettlBusinessCenter

The business center calendar used to adjust the commodity delivery date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **StreamCommoditySettlBusinessCenterGrp**

**180.2.5084 StreamCommoditySettlBusinessCenterGrp**

StreamCommoditySettlBusinessCenterGrp is a repeating subcomponent of the StreamCommodity component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoStreamCommoditySettlBusinessCenters	[1..1]	NumInGroup	
StreamCommoditySettlBusinessCenter	[0..1]	String	Required if NoStreamCommoditySettlBusinessCenters(41249) > 0.

Used in components: [StreamCommodity](#)

**180.2.5085 StreamCommoditySettlCountry**

Specifies the country where delivery takes place. Uses ISO 3166 2-character country code.

Type: [Country](#)

Used in groups: [StreamCommoditySettlPeriodGrp](#)

**180.2.5086 StreamCommoditySettlDateAdjusted**

The adjusted commodity delivery date.

Type: [LocalMktDate](#)

Used in components: [StreamCommodity](#)

**180.2.5087 StreamCommoditySettlDateBusinessDayConvention**

The business day convention used to adjust the commodity delivery date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [StreamCommodity](#)

#### **180.2.5088 StreamCommoditySettlDateRollPeriod**

Time unit multiplier for the commodity delivery date roll.

Type: [int](#)

Used in components: [StreamCommodity](#)

#### **180.2.5089 StreamCommoditySettlDateRollUnit**

Time unit associated with the commodity delivery date roll.

Type: [String](#)

Allowed values in StreamCommoditySettlDateRollUnitCodeSet:

Code	Name	Description
D	Day	Day

Used in components: [StreamCommodity](#)

#### **180.2.5090 StreamCommoditySettlDateUnadjusted**

The unadjusted commodity delivery date.

Type: [LocalMktDate](#)

Used in components: [StreamCommodity](#)

**180.2.5091 StreamCommoditySettlDay**

Specifies the day or group of days for delivery.

Type: **int**

Allowed values in DeliveryScheduleSettlDayCodeSet:

Code	Name	Description
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday
8	AllWeekdays	All weekdays
9	AllDays	All days
10	AllWeekends	All weekends

Used in groups: **StreamCommoditySettlDayGrp**

**180.2.5092 StreamCommoditySettlDayGrp**

The StreamCommoditySettlDayGrp is a repeating subcomponent of the StreamCommoditySettlPeriodGrp component used to define the settlement days associated with the commodity contract.

Name	Mult.	Type	Description
<b>NoStreamCommoditySettlDays</b>	[1..1]	NumInGroup	
<b>StreamCommoditySettlDay</b>	[0..1]	CodeSet	Required if NoStreamCommoditySettlDays(41283) > 0.
<b>StreamCommoditySettlTotalHours</b>	[0..1]	int	
<b>StreamCommoditySettlTimeGrp</b>	[0..*]	Group	

Used in groups: **StreamCommoditySettlPeriodGrp**



**180.2.5093 StreamCommoditySettlDayType**

Specifies the commodity delivery roll day type.

Type: **int**

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **StreamCommodity**

**180.2.5094 StreamCommoditySettlEnd**

The end time for commodities settlement where delivery occurs over time. The time format is specified by the settlement time type.

Type: **String**

Used in groups: **StreamCommoditySettlTimeGrp**

**180.2.5095 StreamCommoditySettlFlowType**

Specifies the commodity delivery flow type.

Type: **int**

Allowed values in DeliveryScheduleSettlFlowTypeCodeSet:

Code	Name	Description
0	AllTimes	All times
1	OnPeak	On peak
2	OffPeak	Off peak

Code	Name	Description
3	Base	Base
4	BlockHours	Block hours
5	Other	Other

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### **180.2.5096 StreamCommoditySettlHolidaysProcessingInstruction**

Indicates whether holidays are included in the settlement periods. Required for electricity contracts.

Type: [int](#)

Allowed values in DeliveryScheduleSettlHolidaysProcessingInstructionCodeSet:

Code	Name	Description
0	DoNotIncludeHolidays	Do not include holidays
1	IncludeHolidays	Include holidays

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### **180.2.5097 StreamCommoditySettlMonth**

Specifies a fixed single month for commodity delivery.

Type: [int](#)

Used in components: [StreamCommodity](#)

#### **180.2.5098 StreamCommoditySettlPeriodFrequencyPeriod**

Time unit multiplier for the settlement period frequency.

Type: [int](#)

Used in groups: [StreamCommoditySettlPeriodGrp](#)

**180.2.5099 StreamCommoditySettlPeriodFrequencyUnit**

Time unit associated with the settlement period frequency.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **StreamCommoditySettlPeriodGrp**

**180.2.5100 StreamCommoditySettlPeriodGrp**

The StreamCommoditySettlPeriodGrp is a repeating subcomponent of the StreamCommodity component used to define the settlement period details associated with the commodity contract.

Name	Mult.	Type	Description
NoStreamCommoditySettlPeriods	[1..1]	NumInGroup	
StreamCommoditySettlCountry	[0..1]	Country	Required if NoStreamCommoditySettlPeriods(41289) > 0.
StreamCommoditySettlTimeZone	[0..1]	String	
StreamCommoditySettlFlowType	[0..1]	CodeSet	
StreamCommoditySettlPeriodNotional	[0..1]	Qty	
StreamCommoditySettlPeriodNotionalUnitOfMeasure	[0..1]	CodeSet	
StreamCommoditySettlPeriodFrequencyPeriod	[0..1]	int	Conditionally required when StreamCommoditySettlFrequencyUnit(41296) is specified.
StreamCommoditySettlPeriodFrequencyUnit	[0..1]	CodeSet	Conditionally required when StreamCommoditySettlFrequencyPeriod(41295) is specified.
StreamCommoditySettlPeriodPrice	[0..1]	Price	

Name	Mult.	Type	Description
StreamCommoditySettlPeriodPriceUnitOfMeasure	[0..1]	CodeSet	
StreamCommoditySettlPeriodPriceCurrency	[0..1]	Currency	
StreamCommoditySettlHolidaysProcessingInstruction	[0..1]	CodeSet	
StreamCommoditySettlDayGrp	[0..*]	Group	
StreamCommoditySettlPeriodXID	[0..1]	XID	
StreamCommoditySettlPeriodXIDRef	[0..1]	XIDREF	

Used in components: [StreamCommodity](#)

#### 180.2.5101 StreamCommoditySettlPeriodNotional

Specifies the delivery quantity associated with this settlement period.

Type: [Qty](#)

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### 180.2.5102 StreamCommoditySettlPeriodNotionalUnitOfMeasure

Specifies the unit of measure (UOM) of the delivery quantity associated with this settlement period.

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels

Code	Name	Description
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters

Code	Name	Description
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot

Code	Name	Description
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### **180.2.5103 StreamCommoditySettlPeriodPrice**

The settlement period price.

Type: [Price](#)

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### **180.2.5104 StreamCommoditySettlPeriodPriceCurrency**

The currency of the settlement period price. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### **180.2.5105 StreamCommoditySettlPeriodPriceUnitOfMeasure**

Specifies the settlement period price unit of measure (UOM).

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms



Code	Name	Description
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce

Code	Name	Description
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### **180.2.5106 StreamCommoditySettlPeriodXID**

Identifier of this settlement period for cross referencing elsewhere in the message.

Type: [XID](#)

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### **180.2.5107 StreamCommoditySettlPeriodXIDRef**

Cross reference to another settlement period for duplicating its properties.

Type: [XIDREF](#)

Used in groups: [StreamCommoditySettlPeriodGrp](#)

**180.2.5108 StreamCommoditySettlStart**

The start time for commodities settlement where delivery occurs over time. The time format is specified by the settlement time type.

Type: **String**

Used in groups: **StreamCommoditySettlTimeGrp**

**180.2.5109 StreamCommoditySettlTimeGrp**

The StreamCommoditySettlTimeGrp is a repeating subcomponent of the StreamCommoditySettlDayGrp component used to define the settlement time periods associated with the commodity contract.

Name	Mult.	Type	Description
<b>NoStreamCommoditySettlTimes</b>	[1..1]	NumInGroup	
<b>StreamCommoditySettlStart</b>	[0..1]	String	Required if NoStreamCommoditySettlTimes(41286) > 0.
<b>StreamCommoditySettlEnd</b>	[0..1]	String	Required if NoStreamCommoditySettlTimes(41286) > 0.
<b>StreamCommoditySettlTimeType</b>	[0..1]	CodeSet	May be defaulted to market convention or bilaterally agreed if not specified.

Used in groups: **StreamCommoditySettlDayGrp**

**180.2.5110 StreamCommoditySettlTimeType**

Specifies the format of the commodities settlement start and end times.

Type: **int**

Allowed values in DeliveryScheduleSettlTimeTypeCodeSet:

Code	Name	Description
0	Hour	Hour of the day. Applicable for electricity contracts. Time value is expressed as an integer hour of the day (1-24). The delivery start/end hour is specified as the end of the included hour. For example, a start hour of "4" begins at 3 a.m.; an end hour of "20" ends at 8 p.m.; a start hour of "1" and end hour of "24" indicates midnight to midnight delivery.

Code	Name	Description
1	Timestamp	HH:MM time format. Applicable for gas contracts. Time value is expressed using a 24-hour time format. For example, a time value of "13:30" is 1:30 p.m.

Used in groups: [StreamCommoditySettlTimeGrp](#)

#### **180.2.5111 StreamCommoditySettlTimeZone**

Commodity delivery timezone specified as "prevailing" rather than "standard" or "daylight".

See [http://www.fixtradingcommunity.org/codelists#Prevailing\\_Timezones](http://www.fixtradingcommunity.org/codelists#Prevailing_Timezones) for code list of applicable prevailing timezones.

Type: [String](#)

Used in groups: [StreamCommoditySettlPeriodGrp](#)

#### **180.2.5112 StreamCommoditySettlTotalHours**

Sum of the hours specified in [StreamCommoditySettlTimeGrp](#).

Type: [int](#)

Used in groups: [StreamCommoditySettlDayGrp](#)

#### **180.2.5113 StreamCommodityType**

Specifies the type of commodity product.

For coal see <http://www.fpml.org/coding-scheme/commodity-coal-product-type> for values.

For metals see <http://www.fpml.org/coding-scheme/commodity-metal-product-type> for values.

For bullion see [http://www.fixtradingcommunity.org/codelists#Bullion\\_Types](http://www.fixtradingcommunity.org/codelists#Bullion_Types) for the external code list of bullion types.

Type: [String](#)

Used in components: [StreamCommodity](#)

**180.2.5114 StreamCommodityUnitOfMeasure**

The unit of measure (UOM) of the commodity asset.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [StreamCommodity](#)

#### **180.2.5115 StreamCommodityXID**

Identifier of this stream commodity for cross referencing elsewhere in the message.

Type: [XID](#)

Used in components: [StreamCommodity](#)

#### **180.2.5116 StreamCommodityXIDRef**

Reference to a stream commodity elsewhere in the message.

Type: **XIDREF**

Used in components: **StreamCommodity**

#### **180.2.5117 StreamCurrency**

Specifies the currency the StreamNotional(40054) is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **StreamGrp**

#### **180.2.5118 StreamDataProvider**

Specifies the commodity data or information provider.

See <http://www.fpml.org/coding-scheme/commodity-information-provider> for values.

Type: **String**

Used in components: **StreamCommodity**

#### **180.2.5119 StreamDesc**

A short descriptive name given to the payment stream. Eg. CDS, Fixed, Float, Float2, GBP. The description has no intrinsic meaning but should be arbitrarily chosen by the remitter as reference.

Type: **String**

Used in groups: **StreamGrp**

#### **180.2.5120 StreamEffectiveDateAdjusted**

The adjusted effective date.

Type: **LocalMktDate**

Used in components: **StreamEffectiveDate**



**180.2.5121 StreamEffectiveDateBusinessCenter**

The business center calendar used to adjust the instrument's stream's effective, or relative effective, date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **StreamEffectiveDateBusinessCenterGrp**

**180.2.5122 StreamEffectiveDateBusinessCenterGrp**

StreamEffectiveDateBusinessCenterGrp is a repeating subcomponent of the StreamEffectiveDate component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
<b>NoStreamEffectiveDateBusinessCenters</b>	[1..1]	NumInGroup	
<b>StreamEffectiveDateBusinessCenter</b>	[0..1]	String	Required if NoStreamEffectiveDateBusinessCenters(40960) > 0.

Used in components: **StreamEffectiveDate**

**180.2.5123 StreamEffectiveDateBusinessDayConvention**

The business day convention used to adjust the instrument's stream's effective, or relative effective, date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.

Code	Name	Description
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [StreamEffectiveDate](#)

### 180.2.5124 StreamEffectiveDate

StreamEffectiveDate is a subcomponent of the StreamGrp component used to specify the effective date of the stream.

Name	Mult.	Type	Description
<a href="#">StreamEffectiveDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">StreamEffectiveDateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the effective date of the stream.
<a href="#">StreamEffectiveDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the effective date of the stream.
<a href="#">StreamEffectiveDateRelativeTo</a>	[0..1]	int	
<a href="#">StreamEffectiveDateOffsetPeriod</a>	[0..1]	int	Conditionally required when StreamEffectiveDateOffsetUnit(40912) is specified.
<a href="#">StreamEffectiveDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when StreamEffectiveDateOffsetPeriod(40911) is specified.
<a href="#">StreamEffectiveDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">StreamEffectiveDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [StreamGrp](#)

**180.2.5125 StreamEffectiveDateOffsetDayType**

Specifies the day type of the relative effective date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **StreamEffectiveDate**

**180.2.5126 StreamEffectiveDateOffsetPeriod**

Time unit multiplier for the relative effective date offset.

Type: **int**

Used in components: **StreamEffectiveDate**

**180.2.5127 StreamEffectiveDateOffsetUnit**

Time unit associated with the relative effective date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **StreamEffectiveDate**

**180.2.5128 StreamEffectiveDateRelativeTo**

Specifies the anchor date when the effective date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **StreamEffectiveDate**

**180.2.5129 StreamEffectiveDateUnadjusted**

The unadjusted effective date.

Type: **LocalMktDate**

Used in components: **StreamEffectiveDate**

**180.2.5130 StreamFirstCompoundingPeriodEndDateUnadjusted**

The unadjusted end date of the initial compounding period.

Type: **LocalMktDate**

Used in components: **StreamCalculationPeriodDates**

**180.2.5131 StreamFirstPeriodStartDateAdjusted**

The adjusted first calculation period start date, if it is before the effective date.

Type: **LocalMktDate**

Used in components: **StreamCalculationPeriodDates**

**180.2.5132 StreamFirstPeriodStartDateBusinessCenter**

The business center calendar used to adjust the instrument's stream's first calculation period start date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **StreamFirstPeriodStartDateBusinessCenterGrp**

**180.2.5133 StreamFirstPeriodStartDateBusinessCenterGrp**

StreamFirstPeriodStartDateBusinessCenterGrp is a repeating subcomponent within the StreamCalculationPeriodDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
NoStreamFirstPeriodStartDateBusinessCenters	[1..1]	NumInGroup	
StreamFirstPeriodStartDateBusinessCenter	[0..1]	String	Required if NoStreamFirstPeriodStartDateBusinessCenters(40959) > 0.

Used in components: [StreamCalculationPeriodDates](#)

**180.2.5134 StreamFirstPeriodStartDateBusinessDayConvention**

The business day convention used to adjust the instrument's stream's first calculation period start date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [StreamCalculationPeriodDates](#)

**180.2.5135 StreamFirstPeriodStartDateUnadjusted**

The unadjusted first calculation period start date if before the effective date.

Type: [LocalMktDate](#)

Used in components: [StreamCalculationPeriodDates](#)

**180.2.5136 StreamFirstRegularPeriodStartDateUnadjusted**

The unadjusted first start date of the regular calculation period, if there is an initial stub period.

Type: [LocalMktDate](#)

Used in components: [StreamCalculationPeriodDates](#)

**180.2.5137 StreamGrp**

The StreamGrp is a repeating subcomponent of the Instrument component used to detail the swap streams associated with the instrument.

Name	Mult.	Type	Description
<a href="#">NoStreams</a>	[1..1]	NumInGroup	
<a href="#">StreamType</a>	[0..1]	CodeSet	Required if NoStreams(40049) > 0.
<a href="#">StreamXID</a>	[0..1]	XID	
<a href="#">StreamDesc</a>	[0..1]	String	
<a href="#">StreamVersion</a>	[0..1]	String	
<a href="#">StreamVersionEffectiveDate</a>	[0..1]	LocalMktDate	
<a href="#">StreamPaySide</a>	[0..1]	CodeSet	
<a href="#">StreamReceiveSide</a>	[0..1]	CodeSet	
<a href="#">StreamNotionalXIDRef</a>	[0..1]	XIDREF	
<a href="#">StreamNotional</a>	[0..1]	Amt	
<a href="#">StreamCurrency</a>	[0..1]	Currency	
<a href="#">StreamNotionalDeterminationMethod</a>	[0..1]	String	
<a href="#">StreamNotionalAdjustments</a>	[0..1]	CodeSet	
<a href="#">StreamNotionalFrequencyPeriod</a>	[0..1]	int	Conditionally required when StreamNotionalFrequencyUnit(41307) is specified.
<a href="#">StreamNotionalFrequencyUnit</a>	[0..1]	CodeSet	Conditionally required when StreamNotionalFrequencyPeriod(41306) is specified.

Name	Mult.	Type	Description
StreamNotionalCommodityFrequency	[0..1]	CodeSet	
StreamNotionalUnitOfMeasure	[0..1]	CodeSet	
StreamTotalNotional	[0..1]	Qty	
StreamTotalNotionalUnitOfMeasure	[0..1]	CodeSet	
StreamCommodity	[0..1]	Component	
StreamEffectiveDate	[0..1]	Component	
StreamTerminationDate	[0..1]	Component	
StreamCalculationPeriodDates	[0..1]	Component	
PaymentStream	[0..1]	Component	
PaymentScheduleGrp	[0..*]	Group	
PaymentStubGrp	[0..*]	Group	
DeliveryStream	[0..1]	Component	
DeliveryScheduleGrp	[0..*]	Group	
StreamText	[0..1]	String	
EncodedStreamTextLen	[0..1]	Length	Must be set if EncodedStreamText(40983) field is specified and must immediately precede it.
EncodedStreamText	[0..1]	data	Encoded (non-ASCII characters) representation of the StreamText(40056) field in the encoded format specified via the MessageEncoding(347) field.

Used in components: **Instrument**

#### 180.2.5138 StreamLastRegularPeriodEndDateUnadjusted

The unadjusted last regular period end date if there is a final stub period.

Type: **LocalMktDate**

Used in components: **StreamCalculationPeriodDates**

#### 180.2.5139 StreamNotional

Notional, or initial notional value for the payment stream. Use the PaymentScheduleGrp component to specify the rate steps.

Type: **Amt**

Used in groups: **StreamGrp**

**180.2.5140 StreamNotionalAdjustments**

For equity swaps this specifies the conditions that govern the adjustment to the number of units of the swap.

Type: **int**

Allowed values in StreamNotionalAdjustmentsCodeSet:

Code	Name	Description
0	Execution	Execution. The adjustments to the number of units are governed by an execution clause.
1	PortfolioRebalancing	Portfolio rebalancing. The adjustments to the number of units are governed by a portfolio rebalancing clause.
2	Standard	Standard. The adjustments to the number of units are not governed by any specific clause.

Used in groups: **StreamGrp**

**180.2.5141 StreamNotionalCommodityFrequency**

The commodity's notional or quantity delivery frequency.

Type: **int**

Allowed values in StreamNotionalCommodityFrequencyCodeSet:

Code	Name	Description
0	Term	Term
1	PerBusinessDay	Per business day
2	PerCalculationPeriod	Per calculation period
3	PerSettlPeriod	Per settlement period
4	PerCalendarDay	Per calendar day
5	PerHour	Per hour
6	PerMonth	Per month

Used in groups: **StreamGrp**



**180.2.5142 StreamNotionalDeterminationMethod**

Specifies the method for determining the floating notional value for equity swaps.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **StreamGrp**

**180.2.5143 StreamNotionalFrequencyPeriod**

Time unit multiplier for the swap stream's notional frequency.

Type: **int**

Used in groups: **StreamGrp**

**180.2.5144 StreamNotionalFrequencyUnit**

Time unit associated with the swap stream's notional frequency.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in groups: **StreamGrp**

**180.2.5145 StreamNotionalUnitOfMeasure**

Specifies the delivery stream quantity unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: **StreamGrp**

#### **180.2.5146 StreamNotionalXIDRef**

Cross reference to another Stream notional for duplicating its properties.

Type: **XIDREF**

Used in groups: **StreamGrp**

#### **180.2.5147 StreamPaySide**

The side of the party paying the stream.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **StreamGrp**

#### **180.2.5148 StreamReceiveSide**

The side of the party receiving the stream.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **StreamGrp**

#### **180.2.5149 StreamTerminationDateAdjusted**

The adjusted termination date.

Type: **LocalMktDate**

Used in components: **StreamTerminationDate**

#### **180.2.5150 StreamTerminationDateBusinessCenter**

The business center calendar used to adjust the instrument's stream's termination, or relative termination, date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **StreamTerminationDateBusinessCenterGrp**

**180.2.5151 StreamTerminationDateBusinessCenterGrp**

StreamTerminationDateBusinessCenterGrp is a repeating subcomponent within the StreamTerminationDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in the Instrument component.

Name	Mult.	Type	Description
NoStreamTerminationDateBusinessCenters	[1..1]	NumInGroup	
StreamTerminationDateBusinessCenter	[0..1]	String	Required if NoStreamTerminationDateBusinessCenters(40961) > 0.

Used in components: [StreamTerminationDate](#)

**180.2.5152 StreamTerminationDateBusinessDayConvention**

The business day convention used to adjust the instrument's stream's termination, or relative termination, date. Used only to override the business day convention specified in the DateAdjustment component within the Instrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [StreamTerminationDate](#)

**180.2.5153 StreamTerminationDate**

StreamTerminationDate is a subcomponent of the StreamGrp component used to specify the termination date of the stream.

Name	Mult.	Type	Description
StreamTerminationDateUnadjusted	[0..1]	LocalMktDate	
StreamTerminationDateBusinessDay-Convention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in Instrument. The specified value would be specific to this instance of the termination date of the stream.
StreamTerminationDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in Instrument. The specified values would be specific to this instance of the termination date of the stream.
StreamTerminationDateRelativeTo	[0..1]	int	
StreamTerminationDateOffsetPeriod	[0..1]	int	Conditionally required when StreamTerminationDateOffsetUnit(40070) is specified.
StreamTerminationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when StreamTerminationDateOffsetPeriod(40069) is specified.
StreamTerminationDateOffsetDayType	[0..1]	CodeSet	
StreamTerminationDateAdjusted	[0..1]	LocalMktDate	

Used in groups: **StreamGrp**

**180.2.5154 StreamTerminationDateOffsetDayType**

Specifies the day type of the relative termination date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar

Code	Name	Description
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [StreamTerminationDate](#)

#### **180.2.5155 StreamTerminationDateOffsetPeriod**

Time unit multiplier for the relative termination date offset.

Type: [int](#)

Used in components: [StreamTerminationDate](#)

#### **180.2.5156 StreamTerminationDateOffsetUnit**

Time unit associated with the relative termination date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [StreamTerminationDate](#)

#### **180.2.5157 StreamTerminationDateRelativeTo**

Specifies the anchor date when the termination date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [StreamTerminationDate](#)



**180.2.5158 StreamTerminationDateUnadjusted**

The unadjusted termination date.

Type: **LocalMktDate**

Used in components: **StreamTerminationDate**

**180.2.5159 StreamText**

Free form text to specify additional information or enumeration description when a standard value does not apply.

Type: **String**

Used in groups: **StreamGrp**

**180.2.5160 StreamTotalNotional**

Total notional or delivery quantity over the term of the contract.

Type: **Qty**

Used in groups: **StreamGrp**

**180.2.5161 StreamTotalNotionalUnitOfMeasure**

Specifies the unit of measure (UOM) for the total notional or delivery quantity over the term of the contract.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

---

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels

---

Code	Name	Description
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters

Code	Name	Description
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot

Code	Name	Description
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: **StreamGrp**

#### 180.2.5162 StreamType

Type of swap stream.

Type: **int**

Allowed values in StreamTypeCodeSet:

Code	Name	Description
0	PaymentCashSettlement	Payment / cash settlement
1	PhysicalDelivery	Physical delivery

Used in groups: **StreamGrp**

#### 180.2.5163 StreamVersion

The stream version identifier when there have been modifications to the contract over time. Helps signal when there are embedded changes.

Type: **String**

Used in groups: **StreamGrp**

**180.2.5164 StreamVersionEffectiveDate**

The effective date of the StreamVersion(42784).

Type: **LocalMktDate**

Used in groups: **StreamGrp**

**180.2.5165 StreamXID**

Identifier of this Stream for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **StreamGrp**

**180.2.5166 StrikeCurrency**

Currency in which the StrikePrice is denominated.

Type: **Currency**

Used in components: **Instrument**

**180.2.5167 StrikeCurrencyCodeSource**

Identifies class or source of the StrikeCurrency(947) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **Instrument**

**180.2.5168 StrikeExerciseStyle**

Expiration Style for an option class:

Type: **int**

Allowed values in ExerciseStyleCodeSet:

Code	Name	Description
0	European	European
1	American	American
2	Bermuda	Bermuda
99	Other	Other

Used in groups: **StrikeRules**

**180.2.5169 StrikeIncrement**

Value by which strike price should be incremented within the specified price range.

Type: **float**

Used in groups: **StrikeRules**

**180.2.5170 StrikeIndex**

Specifies the index used to calculate the strike price.

Type: **String**

Used in components: **Instrument**

**180.2.5171 StrikeIndexCurvePoint**

The point on the floating rate index curve. Sample values:

M = combination of a number between 1-12 and an "M" for month, e.g. 3M

Y = combination of number between 1-100 and a "Y" for year, e.g. 10Y

10Y-OLD = see above, then add "-OLD" when appropriate

INTERPOLATED = the point is mathematically derived

2/2031 5 3/8 = the point is stated via a combination of maturity month / year and coupon.

Type: **String**

Used in components: **Instrument**

#### **180.2.5172 StrikeIndexQuote**

The quote side from which the index price is to be determined.

Type: **int**

Allowed values in StrikeIndexQuoteCodeSet:

Code	Name	Description
0	Bid	Bid.
1	Mid	Mid
2	Offer	Offer

Used in components: **Instrument**

#### **180.2.5173 StrikeIndexSpread**

Specifies the strike price offset from the named index.

Type: **PriceOffset**

Used in components: **Instrument**

#### **180.2.5174 StrikeMultiplier**

Used for derivatives. Multiplier applied to the strike price for the purpose of calculating the settlement value.

Type: **float**

Used in components: **Instrument**

**180.2.5175 StrikePrice**

Strike Price for an Option.

Type: **Price**

Used in components: **Instrument**

**180.2.5176 StrikePriceBoundaryMethod**

Specifies the boundary condition to be used for the strike price relative to the underlying price at the point of option exercise.

Type: **int**

Allowed values in StrikePriceBoundaryMethodCodeSet:

Code	Name	Description
1	LessThan	Less than underlying price is in-the-money (ITM)
2	LessThanOrEqual	Less than or equal to the underlying price is in-the-money(ITM)
3	Equal	Equal to the underlying price is in-the-money(ITM)
4	GreaterThanOrEqual	Greater than or equal to underlying price is in-the-money(ITM)
5	GreaterThan	Greater than underlying is in-the-money(ITM)

Used in components: **Instrument**

**180.2.5177 StrikePriceBoundaryPrecision**

Used in combination with StrikePriceBoundaryMethod to specify the percentage of the strike price in relation to the underlying price. The percentage is generally 100 or greater for puts and 100 or less for calls.

Type: **Percentage**

Used in components: **Instrument**

**180.2.5178 StrikePriceDeterminationMethod**

Specifies how the strike price is determined at the point of option exercise. The strike may be fixed throughout the life of the option, set at expiration to the value of the underlying, set to the average value of the underlying , or set to the optimal value of the underlying.



Type: **int**

Allowed values in StrikePriceDeterminationMethodCodeSet:

Code	Name	Description
1	FixedStrike	Fixed strike (default if not specified)
2	StrikeSetAtExpiration	Strike set at expiration to underlying or other value (lookback floating)
3	StrikeSetToAverageAcrossLife	Strike set to average of underlying settlement price across the life of the option
4	StrikeSetToOptimalValue	Strike set to optimal value

Used in components: **Instrument**

#### **180.2.5179 StrikePricePrecision**

Specifies the number of decimal places for exercise price.

Type: **int**

Used in components: **Instrument**

#### **180.2.5180 StrikeRuleID**

Allows strike rule to be referenced via an identifier so that rules do not need to be explicitly enumerated

Type: **String**

Used in groups: **StrikeRules**

#### **180.2.5181 StrikeRules**

Name	Mult.	Type	Description
NoStrikeRules	[1..1]	NumInGroup	Number of strike rule entries. This block specifies the rules for determining how new strikes should be listed within the stated price range of the underlying instrument

Name	Mult.	Type	Description
StrikeRuleID	[0..1]	String	Allows strike rule to be referenced via an identifier so that rules do not need to be explicitly enumerated
StartStrikePxRange	[0..1]	Price	Starting price for the range to which the StrikeIncrement applies. Price refers to the price of the underlying
EndStrikePxRange	[0..1]	Price	Ending price of the range to which the StrikeIncrement applies. Price refers to the price of the underlying
StrikeIncrement	[0..1]	float	Value by which strike price should be incremented within the specified price
StrikeExerciseStyle	[0..1]	CodeSet	Enumeration that represents the exercise style for a class of options. Same values as ExerciseStyle
MaturityRules	[0..*]	Group	Describes the maturity rules for a given set of strikes as defined by StrikeRules

Used in groups: [MarketSegmentGrp](#), [SecListGrp](#), [SecLstUpdRelSymGrp](#)

#### 180.2.5182 StrikeTime

The time at which current market prices are used to determine the value of a basket.

In negotiation workflows where a spread-to-benchmark price is negotiated, this is the pre-determined time at which the benchmark is to be spotted.

Type: [UTCTimestamp](#)

Used in groups: [QuotReqGrp](#), [QuotReqRjctGrp](#)

Used in messages: [BidRequest](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

#### 180.2.5183 StrikeUnitOfMeasure

Used to express the unit of measure (UOM) of the price if different from the contract.

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms

Code	Name	Description
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce

Code	Name	Description
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: **Instrument**

### 180.2.5184 StrikeValue

Used for derivatives. The number of shares/units for the financial instrument involved in the option trade.

Type: **float**

Used in components: **Instrument**

### 180.2.5185 StrmAsgnReqGrp

Name	Mult.	Type	Description
NoAsgnReqs	[1..1]	NumInGroup	Stream Assignment Requests.
Parties	[0..*]	Group	
StrmAsgnReqInstrmtGrp	[0..*]	Group	

Used in messages: [StreamAssignmentRequest](#)

**180.2.5186 StrmAsgnReqInstrmtGrp**

Name	Mult.	Type	Description
<a href="#">NoRelatedSym</a>	[1..1]	NumInGroup	
<a href="#">Instrument</a>	[0..1]	Component	
<a href="#">SettlType</a>	[0..1]	CodeSet	
<a href="#">MDEntrySize</a>	[0..1]	Qty	
<a href="#">MDStreamID</a>	[0..1]	String	

Used in groups: [StrmAsgnReqGrp](#)

**180.2.5187 StrmAsgnRptGrp**

Name	Mult.	Type	Description
<a href="#">NoAsgnReqs</a>	[1..1]	NumInGroup	Stream Assignment Reports.
<a href="#">Parties</a>	[0..*]	Group	
<a href="#">StrmAsgnRptInstrmtGrp</a>	[0..*]	Group	

Used in messages: [StreamAssignmentReport](#)

**180.2.5188 StrmAsgnRptInstrmtGrp**

Name	Mult.	Type	Description
<a href="#">NoRelatedSym</a>	[1..1]	NumInGroup	
<a href="#">Instrument</a>	[0..1]	Component	
<a href="#">SettlType</a>	[0..1]	CodeSet	
<a href="#">StreamAsgnType</a>	[0..1]	CodeSet	
<a href="#">MDStreamID</a>	[0..1]	String	
<a href="#">StreamAsgnRejReason</a>	[0..1]	CodeSet	
<a href="#">Text</a>	[0..1]	String	

Name	Mult.	Type	Description
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	

Used in groups: **StrmAsgnRptGrp**

### 180.2.5189 Subject

The subject of an Email message

Type: **String**

Used in messages: **Email**

### 180.2.5190 SubscriptionRequestType

Subscription Request Type

Type: **char**

Allowed values in SubscriptionRequestTypeCodeSet:

Code	Name	Description
0	Snapshot	Snapshot
1	SnapshotAndUpdates	Snapshot + Updates (Subscribe)
2	DisablePreviousSnapshot	Disable previous Snapshot + Update Request (Unsubscribe)

Used in messages: **CollateralInquiry**, **DerivativeSecurityListRequest**, **MarginRequirementInquiry**, **MarginRequirementInquiryAck**, **MarketDataRequest**, **MarketDataStatisticsRequest**, **MarketDefinitionRequest**, **PartyDetailsListRequest**, **PartyEntitlementsRequest**, **PartyRiskLimitsRequest**, **PositionReport**, **QuoteStatusRequest**, **RFQRequest**, **RequestForPositions**, **RequestForPositionsAck**, **SecurityDefinitionRequest**, **SecurityListRequest**, **SecurityMassStatusRequest**, **SecurityStatusRequest**, **SecurityTypes**, **SettlementStatusRequest**, **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**, **TradeCaptureReportRequestAck**, **TradingSessionListRequest**, **TradingSessionStatusRequest**

**180.2.5191 SwapClass**

The classification or type of swap. Additional values may be used by mutual agreement of the counter-parties.

Type: **String**

Allowed values in SwapClassCodeSet:

Code	Name	Description
BS	BasisSwap	Basis swap
IX	IndexSwap	Index swap
BB	BroadBasedSecuritySwap	Broad-based security swap
SK	BasketSwap	Basket swap

Used in components: **Instrument**

**180.2.5192 SwapPoints**

For FX Swap, this is used to express the differential between the far leg's bid/offer and the near leg's bid/offer. Value can be negative. Expressed in decimal form. For example, 61.99 points is expressed and sent as 0.006199

Type: **PriceOffset**

Used in messages: **MultilegOrderCancelReplace**, **NewOrderMultileg**

**180.2.5193 SwapSubClass**

The sub-classification or notional schedule type of the swap.

Type: **String**

Allowed values in SwapSubClassCodeSet:

Code	Name	Description
AMTZ	Amortizing	Amortizing notional schedule
COMP	Compounding	Compounding
CNST	ConstantNotionalSchedule	Constant notional schedule
ACRT	AccretingNotionalSchedule	Accreting notional schedule



Code	Name	Description
CUST	CustomNotionalSchedule	Custom notional schedule

Used in components: **Instrument**

### 180.2.5194 Symbol

Ticker symbol. Common, "human understood" representation of the security. SecurityID (48) value can be specified if no symbol exists (e.g. non-exchange traded Collective Investment Vehicles)

Use "[N/A]" for products which do not have a symbol.

Type: **String**

Used in components: **Instrument**

### 180.2.5195 SymbolPositionNumber

Reference to the first or second currency or digital asset in Symbol(55) for FX-style trading.

Conditionally required when one or both symbols in Symbol(55) represent a digital asset.

Type: **int**

Used in groups: **SecAltIDGrp**

### 180.2.5196 SymbolSfx

Additional information about the security (e.g. preferred, warrants, etc.). Note also see SecurityType (167).

As defined in the NYSE Stock and bond Symbol Directory and in the AMEX Fitch Directory.

Type: **String**

Allowed values in SymbolSfxCodeSet:

Code	Name	Description
CD	EUCPWithLumpSumInterest	EUCP with lump-sum interest rather than discount price
WI	WhenIssued	"When Issued" for a security to be reissued under an old CUSIP or ISIN

Used in components: [Instrument](#)

#### **180.2.5197 TargetCompID**

Assigned value used to identify receiving firm.

Type: [String](#)

Used in components: [StandardHeader](#)

#### **180.2.5198 TargetLocationID**

Assigned value used to identify specific message destination's location (i.e. geographic location and/or desk, trader)

Type: [String](#)

Used in components: [StandardHeader](#)

#### **180.2.5199 TargetMarketSegmentGrp**

Convey a list of market segments upon which an action is to be taken.

Name	Mult.	Type	Description
<a href="#">NoTargetMarketSegments</a>	[1..1]	NumInGroup	
<a href="#">TargetMarketSegmentID</a>	[0..1]	String	Required when NoTargetMarketSegments(1789) > 0.

Used in messages: [OrderMassActionReport](#), [OrderMassActionRequest](#)

#### **180.2.5200 TargetMarketSegmentID**

Market segment within a target market segment repeating group.

Type: [String](#)

Used in groups: [TargetMarketSegmentGrp](#)

**180.2.5201 TargetParties**

Name	Mult.	Type	Description
NoTargetPartyIDs	[1..1]	NumInGroup	Repeating group below should contain unique combinations of TargetPartyID, TargetPartyIDSource, and TargetPartyRole.
TargetPartyID	[0..1]	String	Required if NoTargetPartyIDs(1461) > 0. Used to identify the party targeted for the action specified in the message.
TargetPartyIDSource	[0..1]	CodeSet	Used to identify source of target party identifier.
TargetPartyRole	[0..1]	CodeSet	Used to identify the role of source party identifier.
TargetPartyRoleQualifier	[0..1]	CodeSet	Used to further qualify the role of the target party role.
TargetPtysSubGrp	[0..*]	Group	Repeating group of target party sub-identifiers.

Used in messages: AlgoCertificateRequest, ExecutionReport, MassQuoteAck, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReplaceRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderMassStatusRequest, PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport, QuoteCancel, QuoteStatusReport, QuoteStatusRequest

**180.2.5202 TargetPartyID**

PartyID value within an target party repeating group.

Type: String

Used in groups: TargetParties

**180.2.5203 TargetPartyIDSource**

PartyIDSource value within an target party repeating group.

Same values as PartyIDSource (447)

Type: char

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.

Code	Name	Description
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **TargetParties**

#### 180.2.5204 TargetPartyRole

PartyRole value within an target party repeating group.

Same values as PartyRole (452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party

Code	Name	Description
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)

Code	Name	Description
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionV- enue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm



Code	Name	Description
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor

Code	Name	Description
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **TargetParties**

**180.2.5205 TargetPartyRoleQualifier**

Qualifies the value of TargetPartyRole (1464).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange

Code	Name	Description
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **TargetParties**

#### 180.2.5206 TargetPartySubID

Party sub-identifier value within a target party repeating group.

Type: **String**

Used in groups: **TargetPtysSubGrp**

**180.2.5207 TargetPartySubIDType**

Type of TargetPartySubID(2434) value.

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker

Code	Name	Description
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.

Code	Name	Description
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.



Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **TargetPtysSubGrp**

**180.2.5208 TargetPtysSubGrp**

Repeating group of target party sub-identifiers.

Name	Mult.	Type	Description
NoTargetPartySubIDs	[1..1]	NumInGroup	
TargetPartySubID	[0..1]	String	Required when NoTargetPartySubIDs(2433) > 0.
TargetPartySubIDType	[0..1]	CodeSet	Required when NoTargetPartySubIDs(2433) > 0.

Used in groups: [TargetParties](#)

**180.2.5209 TargetStrategy**

The target strategy of the order

1000+ = Reserved and available for bi-laterally agreed upon user defined values

Type: [int](#)

Allowed values in TargetStrategyCodeSet:

Code	Name	Description
1	VWAP	VWAP
2	Participate	Participate (i.e. aim to be x percent of the market volume)
3	MinimizeMarketImpact	Minimize market impact

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

**180.2.5210 TargetStrategyParameters**

Field to allow further specification of the TargetStrategy - usage to be agreed between counterparties

Type: [String](#)

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

**180.2.5211 TargetStrategyPerformance**

For communication of the performance of the order versus the target strategy

Type: **float**

Used in messages: **ExecutionReport**

**180.2.5212 TargetSubID**

Assigned value used to identify specific individual or unit intended to receive message. "ADMIN" reserved for administrative messages not intended for a specific user.

Type: **String**

Used in components: **StandardHeader**

**180.2.5213 TaxAdvantageType**

Identifies the type of tax exempt account in which purchases shares/units are to be held. Used for CIV.

Type: **int**

Allowed values in TaxAdvantageTypeCodeSet:

Code	Name	Description
0	None	None/Not Applicable (default)
1	MaxiISA	Maxi ISA (UK)
2	TESSA	TESSA (UK)
3	MiniCashISA	Mini Cash ISA (UK)
4	MiniStocksAndSharesISA	Mini Stocks And Shares ISA (UK)
5	MiniInsuranceISA	Mini Insurance ISA (UK)
6	CurrentYearPayment	Current Year Payment (US)
7	PriorYearPayment	Prior Year Payment (US)
8	AssetTransfer	Asset Transfer (US)
9	EmployeePriorYear	Employee - prior year (US)
10	EmployeeCurrentYear	Employee - current year (US)
11	EmployerPriorYear	Employer - prior year (US)
12	EmployerCurrentYear	Employer - current year (US)

Code	Name	Description
13	NonFundPrototypeIRA	Non-fund prototype IRA (US)
14	NonFundQualifiedPlan	Non-fund qualified plan (US)
15	DefinedContributionPlan	Defined contribution plan (US)
16	IRA	Individual Retirement Account (US)
17	IRARollover	Individual Retirement Account - Rollover (US)
18	KEOGH	KEOGH (US)
19	ProfitSharingPlan	Profit Sharing Plan (US)
20	US401K	401(k) (US)
21	SelfDirectedIRA	Self-directed IRA (US)
22	US403b	403(b) (US)
23	US457	457 (US)
24	RothIRAPrototype	Roth IRA (Fund Prototype) (US)
25	RothIRANonPrototype	Roth IRA (Non-prototype) (US)
26	RothConversionIRAPrototype	Roth Conversion IRA (Fund Prototype) (US)
27	RothConversionIRANonPrototype	Roth Conversion IRA (Non-prototype) (US)
28	EducationIRAPrototype	Education IRA (Fund Prototype) (US)
29	EducationIRANonPrototype	Education IRA (Non-prototype) (US)
999	Other	Other

Used in messages: [RegistrationInstructions](#)

### 180.2.5214 TaxonomyType

The type of identification taxonomy used to identify the security.

Type: **char**

Allowed values in TaxonomyTypeCodeSet:

Code	Name	Description
I	ISINOrAltInstrmtID	ISIN or Alternate instrument identifier plus CFI. Identified through use of SecurityID(48) and SecurityIDSource(22) of ISIN or another standard source plus CFICode(461).

Code	Name	Description
E	InterimTaxonomy	Interim Taxonomy. Identified through use of AssetClass(1938) plus either Symbol(55) or SecurityID(48) and SecurityIDSource(22), and/or other additional instrument attributes.

Used in messages: [PositionReport](#), [TradeCaptureReport](#)

#### 180.2.5215 TerminatedIndicator

Indicates if the position has been terminated.

Type: [Boolean](#)

Used in messages: [PositionMaintenanceReport](#), [PositionReport](#)

#### 180.2.5216 TerminationDate

The date of a contract's early termination or other post-trade event when the event is prior to the contract natural end or maturity not defined as part of the security's reference data or contractual terms/agreement.

Type: [LocalMktDate](#)

Used in messages: [PositionReport](#), [QuoteResponse](#), [QuoteStatusReport](#), [TradeCaptureReport](#)

#### 180.2.5217 TerminationType

Type of financing termination.

Type: [int](#)

Allowed values in TerminationTypeCodeSet:

Code	Name	Description
1	Overnight	Overnight
2	Term	Term
3	Flexible	Flexible
4	Open	Open

Used in components: [FinancingDetails](#)

**180.2.5218 TertiaryTrdType**

Type of trade assigned to a trade. Used in addition to TrdType(828) and SecondaryTrdType(855). Must not be used when only one additional trade type needs to be assigned.

Type: **int**

Allowed values in TrdTypeCodeSet:

Code	Name	Description
0	RegularTrade	Regular trade
1	BlockTrade	Block trade
2	EFP	Exchange for physical (EFP)
3	Transfer	Transfer
4	LateTrade	Late trade
5	TTrade	T trade
6	WeightedAveragePriceTrade	Weighted average price trade
7	BunchedTrade	Bunched trade
8	LateBunchedTrade	Late bunched trade
9	PriorReferencePriceTrade	Prior reference price trade
10	AfterHoursTrade	After hours trade
11	ExchangeForRisk	Exchange for risk (EFR)
12	ExchangeForSwap	Exchange for swap (EFS)
13	ExchangeOfFuturesFor	Exchange of futures for in market futures (EFM). For example full sized for mini.
14	ExchangeOfOptionsForOptions	Exchange of options for options (EOO)
15	TradingAtSettlement	Trading at settlement
16	AllOrNone	All or none
17	FuturesLargeOrderExecution	Futures large order execution
18	ExchangeOfFuturesForFutures	Exchange of futures for external market futures (EFF)
19	OptionInterimTrade	Option interim trade
20	OptionCabinetTrade	Option cabinet trade
22	PrivatelyNegotiatedTrades	Privately negotiated trade
23	SubstitutionOfFuturesForForwards	Substitution of futures for forwards
24	ErrorTrade	Error trade
25	SpecialCumDividend	Special cum dividend (CD)
26	SpecialExDividend	Special ex dividend (XD)
27	SpecialCumCoupon	Special cum coupon (CC)

Code	Name	Description
28	SpecialExCoupon	Special ex coupon (XC)
29	CashSettlement	Cash settlement (CS)
30	SpecialPrice	Special price (SP). Usually net or all-in price.
31	GuaranteedDelivery	Guaranteed delivery (GD)
32	SpecialCumRights	Special cum rights (CR)
33	SpecialExRights	Special ex rights (XR)
34	SpecialCumCapitalRepayments	Special cum capital repayments (CP)
35	SpecialExCapitalRepayments	Special ex capital repayments (XP)
36	SpecialCumBonus	Special cum bonus (CB)
37	SpecialExBonus	Special ex bonus (XB)
38	LargeTrade	Block trade. The same as large trade.
39	WorkedPrincipalTrade	Worked principal trade
40	BlockTrades	Block trades
41	NameChange	Name change
42	PortfolioTransfer	Portfolio transfer
43	ProrogationBuy	Prorogation buy. Used by Euronext Paris only. Is used to defer settlement under French SRD (deferred settlement system). Trades must be reported as crosses at zero price.
44	ProrogationSell	Prorogation sell. See prorogation buy.
45	OptionExercise	Option exercise
46	DeltaNeutralTransaction	Delta neutral transaction
47	FinancingTransaction	Financing transaction
48	NonStandardSettlement	Non-standard settlement
49	DerivativeRelatedTransaction	Derivative related transaction
50	PortfolioTrade	Portfolio trade. Identifies a collection/basket of trades. In the context of bonds (e.g. corporate bonds) these are transacted as a single trade at an aggregate price for the entire portfolio and may be traded all-or-none or most-or-none depending on bilateral agreement. In the context of ESMA RTS 1 Article 2(b), may be used to refer to portfolio trades to distinguish between addressable and non-addressable volume. In the context of Market Model Typology (MMT), use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
51	VolumeWeightedAverageTrade	Volume weighted average trade
52	ExchangeGrantedTrade	Exchange granted trade



Code	Name	Description
53	RepurchaseAgreement	Repurchase agreement
54	OTC	OTC. Trade executed off-market. In the context of CFTC regulatory reporting for swaps, it is a large notional off-facility swap. In the context of MiFID transparency reporting rules this is used to report, into an exchange, deals made outside exchange rules.
55	ExchangeBasisFacility	Exchange basis facility (EBF)
56	OpeningTrade	Opening trade. Identifies a trade that resulted from the opening of a market. In the context of IIROC, this indicates a trade that occurred at the opening or the first trade of the day for a security.
57	NettedTrade	Netted trade
58	BlockSwapTrade	Block swap trade. Block trade executed off-market or on a registered market. In the context of CFTC regulatory reporting for swaps, it is a swap executed according to SEF or DCM rules.
59	CreditEventTrade	Credit event trade
60	SuccessionEventTrade	Succession event trade
61	GiveUpGiveInTrade	Give-up Give-in trade
62	DarkTrade	Dark trade. In the context of Market Model Typology (MMT), a dark trade might also come from a lit/hybrid book (e.g. when an aggressive lit order hits a resting dark order). The use of this value applies to TrdType(828), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
63	TechnicalTrade	Technical trade
64	Benchmark	Benchmark. In the context of ESMA RTS 1 Article 2(a), may be used to refer to benchmark trades. In the context of Market Model Typology (MMT), the "benchmark" price depends on a benchmark which has no current price but was derived from a time series such as a VWAP. The use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).

Code	Name	Description
65	PackageTrade	Package trade. May be used to identify the pseudo-trade of a stream or collection of trades to be transacted, cleared and be reported as an atomic unit. In the context of MiFIR RTS 1, this is the "CONT" flag. In the context of MiFIR RTS 2 Article 1(1)(b), may be used to refer to package transactions (excluding exchange for physicals). In the context of Market Model Typology (MMT), use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
66	RollTrade	Roll trade. Trade is a roll from one contract that is about to expire to a new contract.
67	ClosingPriceTrade	Closing price trade. Identifies a trade that uses the closing price of a market without resulting from the closing of this market. In the context of FCA policy statement PS23/4, this indicates a benchmark transaction executed using the market closing price and is the "CLSE" flag.
68	InterFundTransferTrade	Inter-fund transfer trade. Administrative trade (non price-forming) related to the transfer of ownership between funds.
69	NetAssetValueCalculatedTrade	Net asset value calculated trade. Trade of a fund priced at the net asset value of its constituents. In the context of MiFIR RTS 1, this may be used for ETFs when the NAV price becomes available.

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **ExecutionReport**, **TradeCaptureReport**

### 180.2.5219 TestActionReportID

Identifier of the test action report.

Type: **String**

Used in messages: **TestActionReport**

### 180.2.5220 TestActionRequestID

Unique identifier of the TestActionRequest(35=EN).

Type: **String**

Used in messages: **TestActionRequest**, **TestActionRequestAck**

#### **180.2.5221 TestActionRequestStatus**

Status of the TestActionRequest(35=EN) message being responded to.

Type: **int**

Allowed values in TestActionRequestStatusCodeSet:

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected. Rejection reason provided in RejectText(1328).

Used in messages: **TestActionRequestAck**

#### **180.2.5222 TestActionType**

Specifies the type of action to take or that was taken for a given test suite.

Type: **int**

Allowed values in TestActionTypeCodeSet:

Code	Name	Description
0	Start	Start
1	Stop	Stop
2	State	State

Used in messages: **TestActionRequest**

#### **180.2.5223 TestFailLevelValue**

Value of the measure upon which the test is considered to have failed.

Type: **float**

Used in groups: **TestMeasureGrp**

**180.2.5224 TestGatewayDetailGrp**

Provides information about gateways for testing applications, e.g. for order entry or market data.

Name	Mult.	Type	Description
NoTestGatewayDetails	[1..1]	NumInGroup	
TestGatewayDetailName	[0..1]	String	Required if NoTestGatewayDetails(3092)>0.
TestGatewayDetailType	[0..1]	CodeSet	Required if NoTestGatewayDetails(3092)>0.
TestGatewayDetailValue	[0..1]	String	Required if NoTestGatewayDetails(3092)>0.
TestGatewayMarketID	[0..1]	Exchange	

Used in messages: [TestSuiteDefinitionRequestAck](#)

**180.2.5225 TestGatewayDetailName**

Name of test gateway information.

Type: [String](#)

Used in groups: [TestGatewayDetailGrp](#)

**180.2.5226 TestGatewayDetailType**

Type of test gateway information.

Type: [int](#)

Allowed values in TestGatewayDetailTypeCodeSet:

Code	Name	Description
0	MarketDataGatewayIPAddress	Market data gateway IP address. IP address of the market data gateway of a venue.
1	MarketDataGatewayPortNumber	Market data gateway port number. Port for the IP address of the market data gateway of a venue.
2	MarketDataGatewayDataFormat	Market data gateway data format. Data format for market data.
3	MarketDataGatewayFormatVersion	Market data gateway format version. Version of the data format for market data.

Code	Name	Description
4	MarketDataGatewayRoutingIPAd- dress	Market data gateway routing IP address. Intermediate gateway that is needed to setup the IP route to the actual market data gateway.
5	OrderEntryGatewayIPAddress	Order entry gateway IP address. IP address of the order entry gateway of a venue.
6	OrderEntryGatewayPortNumber	Order entry gateway port number. Port for the IP address of the order entry gateway of a venue.
7	OrderEntryGatewaydataFormat	Order entry gateway data format. Data format for order entry.
8	OrderEntryGatewayFormatVersion	Order entry gateway format version. Version of the data format for order entry.
9	OrderEntryGatewayRoutingIPAd- dress	Order entry gateway routing IP address. Intermediate gateway that is needed to setup the IP route to the actual order entry gateway.

Used in groups: **TestGatewayDetailGrp**

#### **180.2.5227 TestGatewayDetailValue**

Value of test gateway information.

Type: **String**

Used in groups: **TestGatewayDetailGrp**

#### **180.2.5228 TestGatewayMarketID**

Execution venue of test system.

Type: **Exchange**

Used in groups: **TestGatewayDetailGrp**

#### **180.2.5229 TestMeasureDesc**

Description of a test measure.

Type: **String**

Used in groups: **TestMeasureGrp**

**180.2.5230 TestMeasureGrp**

Provides details for a collection of test measures or criteria that a test case/scenario is assessed against.

Name	Mult.	Type	Description
NoTestMeasures	[1..1]	NumInGroup	
TestMeasureName	[0..1]	String	Required if NoTestMeasures(3052)>0.
TestMeasureDesc	[0..1]	String	
TestMeasureType	[0..1]	CodeSet	Required if NoTestMeasures(3052)>0.
TestMeasurePrecision	[0..1]	int	
TestMeasureResult	[0..1]	CodeSet	Required if NoTestMeasures(3052)>0.
TestThresholdType	[0..1]	CodeSet	Required if NoTestMeasures(3052)>0.
TestWarningLevelValue	[0..1]	float	
TestFailLevelValue	[0..1]	float	Required if NoTestMeasures(3052)>0.
TestPeakLevelValue	[0..1]	float	

Used in groups: **TestScenarioGrp**

**180.2.5231 TestMeasureName**

Name of a test measure.

Type: **String**

Used in groups: **TestMeasureGrp**

**180.2.5232 TestMeasurePrecision**

Number of decimal places for TestMeasureType(3055).

Type: **int**

Used in groups: **TestMeasureGrp**

**180.2.5233 TestMeasureResult**

Identifies the result of an individual test based on a measure.

Type: **int**

Allowed values in TestSuiteStatusCodeSet:

Code	Name	Description
0	Undefined	Undefined
1	Pass	Pass
2	Fail	Fail
3	Warning	Warning

Used in groups: **TestMeasureGrp**

### **180.2.5234 TestMeasureType**

Datatype of the metric being used for a test.

Type: **int**

Allowed values in StrategyParameterTypeCodeSet:

Code	Name	Description
1	Int	Int
2	Length	Length
3	NumInGroup	NumInGroup
4	SeqNum	SeqNum
5	TagNum	TagNum
6	Float	float
7	Qty	Qty
8	Price	Price
9	PriceOffset	PriceOffset
10	Amt	Amt
11	Percentage	Percentage
12	Char	Char
13	Boolean	Boolean
14	String	String
15	MultipleCharValue	MultipleCharValue
16	Currency	Currency

Code	Name	Description
17	Exchange	Exchange
18	MonthYear	MonthYear
19	UTCTimestamp	UTCTimestamp
20	UTCTimeOnly	UTCTimeOnly
21	LocalMktDate	LocalMktDate
22	UTCDateOnly	UTCDateOnly
23	Data	data
24	MultipleStringValue	MultipleStringValue
25	Country	Country
26	Language	Language
27	TZTimeOnly	TZTimeOnly
28	TZTimestamp	TZTimestamp
29	Tenor	Tenor

Used in groups: **TestMeasureGrp**

#### **180.2.5235 TestMessageIndicator**

Indicates whether or not this FIX Session is a "test" vs. "production" connection. Useful for preventing "accidents".

Type: **Boolean**

Allowed values in TestMessageIndicatorCodeSet:

Code	Name	Description
N	False	False (production)
Y	True	True (test)

Used in messages: **Logon**

#### **180.2.5236 TestOrderGrp**

Provides list of orders for the execution of test scenarios.



Name	Mult.	Type	Description
NoTestOrders	[1..1]	NumInGroup	
TestOrderID	[0..1]	String	Required if NoTestOrders(3082)>0.
TestOrderSymbol	[0..1]	String	
TestOrderSecurityID	[0..1]	String	
TestOrderSecurityIDSource	[0..1]	String	
TestOrderPrice	[0..1]	Price	
TestOrderPriceType	[0..1]	CodeSet	
TestOrderQty	[0..1]	Qty	
TestOrderOffsetPeriod	[0..1]	int	Use for an effective time relative to the overall starting time defined by TestScenarioStartTime(3031). Required when TestOrderOffsetUnit(3091) is specified.
TestOrderOffsetUnit	[0..1]	CodeSet	Use for an effective time relative to the overall starting time defined by TestScenarioStartTime(3031). Required when TestOrderOffsetPeriod(3090) is specified.

Used in groups: [TestScenarioGrp](#)

#### 180.2.5237 TestOrderID

Identifier of a test order.

Type: [String](#)

Used in groups: [TestOrderGrp](#)

#### 180.2.5238 TestOrderOffsetPeriod

Time unit multiplier for the effective time of an order relative to the starting time of a test scenario.

Type: [int](#)

Used in groups: [TestOrderGrp](#)

#### 180.2.5239 TestOrderOffsetUnit

Time unit associated with the effective time of an order relative to the starting time of a test scenario.

Type: **int**

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in groups: **TestOrderGrp**

#### **180.2.5240 TestOrderPrice**

Used for the price of a test order.

See Price(44) field for description.

Type: **Price**

Used in groups: **TestOrderGrp**

#### **180.2.5241 TestOrderPriceType**

Type of price of TestOrderPrice(3087).

Type: **int**

Allowed values in PriceTypeCodeSet:

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
2	PerUnit	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points spread). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	Yield	Yield
10	FixedCabinetTradePrice	Fixed cabinet trade price (primarily for listed futures and options)
11	VariableCabinetTradePrice	Variable cabinet trade price (primarily for listed futures and options)
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example, the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)
22	BasisPoints	Basis points. When the price is not spread based.
23	UpfrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageNotional	Percentage of notional

Used in groups: [TestOrderGrp](#)

#### **180.2.5242 TestOrderQty**

Used for the quantity of a test order.

See OrderQty(80) field for description.

Type: [Qty](#)

Used in groups: [TestOrderGrp](#)

#### **180.2.5243 TestOrderSecurityID**

Used for the security identifier of a test order.

See Security(48) field for description.

Type: [String](#)

Used in groups: [TestOrderGrp](#)

#### **180.2.5244 TestOrderSecurityIDSource**

Used for the source of the security identifier of a test order.

See SecurityIDSource(22) field for description.

Type: [String](#)

Used in groups: [TestOrderGrp](#)

#### **180.2.5245 TestOrderSymbol**

Used for the security symbol of a test order.

See Symbol(55) field for description.

Type: [String](#)

Used in groups: [TestOrderGrp](#)

**180.2.5246 TestPeakLevelValue**

Peak value of the measure achieved in testing.

Type: **float**

Used in groups: **TestMeasureGrp**

**180.2.5247 TestReqID**

Identifier included in Test Request message to be returned in resulting Heartbeat

Type: **String**

Used in messages: **Heartbeat**, **TestRequest**

**180.2.5248 TestScenarioEndTime**

Ending date and time of test scenario execution for a software system.

Type: **UTCTimestamp**

Used in groups: **TestScenarioGrp**

**180.2.5249 TestScenarioGroupID**

Unique identifier for the group of test scenarios constituting a test suite.

Type: **String**

Used in messages: **AlgoCertificateRequest**, **TestSuiteDefinitionRequest**

**180.2.5250 TestScenarioGrp**

TestScenarioGrp provides details for a collection of test cases/scenarios that makes up a test suite.

Name	Mult.	Type	Description
<b>NoTestScenarios</b>	[1..1]	NumInGroup	
<b>TestScenarioID</b>	[0..1]	String	Required if NoTestScenarios(3028)>0.
<b>TestScenarioStatus</b>	[0..1]	CodeSet	Required if NoTestScenarios(3028)>0.
<b>TestScenarioStartTime</b>	[0..1]	UTCTimestamp	Overall starting time of this test scenario.

Name	Mult.	Type	Description
TestScenarioEndTime	[0..1]	UTCTimestamp	Overall ending time of this test scenario.
NestedParties	[0..*]	Group	May be used to identify one or more execution venues.
InstrumentScopeGrp	[0..*]	Group	InstrumentScopeSecurityGroup(1545) may be used to reference a list of securities provided with the SecurityList(35=y) message.
MDOriOriginType	[0..1]	CodeSet	
MDOriOriginDesc	[0..1]	String	
MDOriOriginTime	[0..1]	UTCTimestamp	
TestStepGroupID	[0..1]	String	May be used to define a shortcut for TestStepGrp.
TestStepGrp	[0..*]	Group	
TestSystemModuleGrp	[0..*]	Group	
TestMeasureGrp	[0..*]	Group	Use to provide the metrics and thresholds for the scenario identified by TestScenarioID(3029). Required unless TestSuiteStatus(3070)=0 (Undefined).
TestOrderGrp	[0..*]	Group	Use to provide a list of orders to be used for testing the scenario.

Used in messages: AlgoCertificateReport, AlgoCertificateRequest, TestActionReport, TestActionRequest, TestSuiteDefinitionRequest

#### 180.2.5251 TestScenarioID

Unique identifier of a test scenario for a software system.

Type: String

Used in groups: TestScenarioGrp

#### 180.2.5252 TestScenarioStartTime

Starting date and time of test scenario execution for a software system.

Type: UTCTimestamp

Used in groups: TestScenarioGrp

**180.2.5253 TestScenarioStatus**

Identifies the overall result of a test scenario identified by TestScenarioID(3029).

Type: **int**

Allowed values in TestSuiteStatusCodeSet:

Code	Name	Description
0	Undefined	Undefined
1	Pass	Pass
2	Fail	Fail
3	Warning	Warning

Used in groups: **TestScenarioGrp**

**180.2.5254 TestStepDesc**

Description of a test step.

Type: **String**

Used in groups: **TestStepGrp**

**180.2.5255 TestStepEndOffsetPeriod**

Time unit multiplier for the ending time of a test step relative to the starting time of a test scenario.

Type: **int**

Used in groups: **TestStepGrp**

**180.2.5256 TestStepEndOffsetUnit**

Time unit associated with the starting time of a test step relative to the ending time of a test scenario.

Type: **int**

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in groups: **TestStepGrp**

#### **180.2.5257 TestStepEndTime**

Ending time of a test step.

Type: **UTCTimestamp**

Used in groups: **TestStepGrp**

#### **180.2.5258 TestStepGroupID**

Unique identifier for the group of test steps constituting a test scenario.

Type: **String**

Used in groups: **TestScenarioGrp**

#### **180.2.5259 TestStepGrp**

TestStepGrp is a repeating group used to provide information regarding the steps of a test case/scenario for a testing system.



Name	Mult.	Type	Description
NoTestSteps	[1..1]	NumInGroup	
TestStepID	[0..1]	String	Required if NoTestSteps(3036)>0.
TestStepDesc	[0..1]	String	
TestStepStartTime	[0..1]	UTCTimestamp	Use for an absolute starting time. Mutually exclusive with TestStepStartOffsetUnit(3041) and TestStepStartOffsetPeriod(3040).
TestStepStartOffsetPeriod	[0..1]	int	Use for a starting time relative to the overall starting time defined by TestScenarioStartTime(3031). Required when TestStepStartOffsetUnit(3041) is specified.
TestStepStartOffsetUnit	[0..1]	CodeSet	Use for a starting time relative to the overall starting time defined by TestScenarioStartTime(3031). Required when TestStepStartOffsetPeriod(3040) is specified.
TestStepEndTime	[0..1]	UTCTimestamp	Use for an absolute ending time. Mutually exclusive with TestStepEndOffsetUnit(3044) and TestStepEndOffsetPeriod(3043).
TestStepEndOffsetPeriod	[0..1]	int	Use for an ending time relative to the starting time of the step defined by TestStepStartTime(3039). Required when TestStepEndOffsetUnit(3044) is specified.
TestStepEndOffsetUnit	[0..1]	CodeSet	Use for an ending time relative to the starting time of the step defined by TestStepStartTime(3039). Required when TestStepEndOffsetPeriod(3043) is specified.
TestStepParameterGrp	[0..*]	Group	

Used in groups: **TestScenarioGrp**

### 180.2.5260 TestStepID

Unique identifier of a test step.

Type: **String**

Used in groups: **TestStepGrp**

**180.2.5261 TestStepParameterGrp**

TestStepParameterGrp is a repeating group used to provide information regarding the input parameters of a test step for testing.

Name	Mult.	Type	Description
NoTestStepParameters	[1..1]	NumInGroup	
TestStepParameterName	[0..1]	String	Required if NoTestStepParameters(3045)>0.
TestStepParameterType	[0..1]	CodeSet	Required if NoTestStepParameters(3045)>0.
TestStepParameterValue	[0..1]	String	Required if NoTestStepParameters(3045)>0.

Used in groups: [TestStepGrp](#)

**180.2.5262 TestStepParameterName**

Name of the test step parameter.

Type: [String](#)

Used in groups: [TestStepParameterGrp](#)

**180.2.5263 TestStepParameterType**

Datatype of the test step parameter.

Type: [int](#)

Allowed values in StrategyParameterTypeCodeSet:

Code	Name	Description
1	Int	Int
2	Length	Length
3	NumInGroup	NumInGroup
4	SeqNum	SeqNum
5	TagNum	TagNum
6	Float	float
7	Qty	Qty
8	Price	Price

Code	Name	Description
9	PriceOffset	PriceOffset
10	Amt	Amt
11	Percentage	Percentage
12	Char	Char
13	Boolean	Boolean
14	String	String
15	MultipleCharValue	MultipleCharValue
16	Currency	Currency
17	Exchange	Exchange
18	MonthYear	MonthYear
19	UTCTimestamp	UTCTimestamp
20	UTCTimeOnly	UTCTimeOnly
21	LocalMktDate	LocalMktDate
22	UTCDateOnly	UTCDateOnly
23	Data	data
24	MultipleStringValue	MultipleStringValue
25	Country	Country
26	Language	Language
27	TZTimeOnly	TZTimeOnly
28	TZTimestamp	TZTimestamp
29	Tenor	Tenor

Used in groups: **TestStepParameterGrp**

#### **180.2.5264 TestStepParameterValue**

Value of the test step parameter.

Type: **String**

Used in groups: **TestStepParameterGrp**

#### **180.2.5265 TestStepStartOffsetPeriod**

Time unit multiplier for the starting time of a test step relative to the starting time of a test scenario.

Type: **int**

Used in groups: **TestStepGrp**

### **180.2.5266 TestStepStartOffsetUnit**

Time unit associated with the starting time of a test step relative to the starting time of a test scenario.

Type: **int**

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in groups: **TestStepGrp**

### **180.2.5267 TestStepStartTime**

Starting time of a test step.

Type: **UTCTimestamp**

Used in groups: **TestStepGrp**

### **180.2.5268 TestSuiteActivityState**

Specifies the activity state the test suite is in.

Type: **int**

Allowed values in TestSuiteActivityStateCodeSet:

Code	Name	Description
0	Scheduled	Scheduled. Test suite is planned for execution but has not started yet.
1	Running	Running. Test suite is currently being executed.
2	Completed	Completed. Test suite has run to completion and test status information is available.
3	Cancelled	Cancelled. Test suite has not run to completion due to a cancellation by the user or an abnormal termination by the test system. Test suite status information is undefined.

Used in messages: **TestActionRequestAck**

#### **180.2.5269 TestSuiteRequestID**

Unique identifier of the TestSuiteDefinitionRequest(35=EL).

Type: **String**

Used in messages: **TestActionReport**, **TestActionRequest**, **TestActionRequestAck**, **TestSuiteDefinitionRequest**, **TestSuiteDefinitionRequestAck**

#### **180.2.5270 TestSuiteRequestRefID**

Reference identifier of the TestSuiteDefinitionRequest(35=EL).

Type: **String**

Used in messages: **TestSuiteDefinitionRequest**

#### **180.2.5271 TestSuiteRequestStatus**

Status of the TestSuiteDefinitionRequest(35=EL) message being responded to.

Type: **int**

Allowed values in TestSuiteRequestStatusCodeSet:

Code	Name	Description
0	Received	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected. Rejection reason provided in RejectText(1328).

Used in messages: [TestSuiteDefinitionRequestAck](#)

### 180.2.5272 TestSuiteRequestTransType

Identifies the message transaction type.

Type: [int](#)

Allowed values in TestSuiteRequestTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Cancel	Cancel

Used in messages: [TestSuiteDefinitionRequest](#)

### 180.2.5273 TestSuiteStatus

Identifies the overall test result of a group of individual test scenarios.

Type: [int](#)

Allowed values in TestSuiteStatusCodeSet:

Code	Name	Description
0	Undefined	Undefined
1	Pass	Pass
2	Fail	Fail
3	Warning	Warning

Used in messages: [AlgoCertificateReport](#), [TestActionReport](#)

**180.2.5274 TestSystemModuleGrp**

TestSystemModuleGrp is a repeating group used to provide information regarding the software components of a testing system.

Name	Mult.	Type	Description
NoTestSystemModules	[1..1]	NumInGroup	
TestSystemModuleName	[0..1]	String	Required if NoTestSystemModules(3049)>0.
TestSystemModuleVersion	[0..1]	String	Required if NoTestSystemModules(3049)>0.
TestSystemModuleLastUpdateTime	[0..1]	UTCTimestamp	

Used in groups: [TestScenarioGrp](#)

**180.2.5275 TestSystemModuleLastUpdateTime**

Support Timestamp of last update to Algo Test System Module.

Type: [UTCTimestamp](#)

Used in groups: [TestSystemModuleGrp](#)

**180.2.5276 TestSystemModuleName**

Name of the component of a testing system.

Type: [String](#)

Used in groups: [TestSystemModuleGrp](#)

**180.2.5277 TestSystemModuleVersion**

Version (e.g. build or commit number) of the component of a testing system.

Type: [String](#)

Used in groups: [TestSystemModuleGrp](#)

**180.2.5278 TestThresholdType**

Identifies whether the value of a measure needs to be over or under a specific threshold to be successful.

Type: **int**

Allowed values in TestThresholdTypeCodeSet:

Code	Name	Description
0	Under	Under
1	Over	Over

Used in groups: **TestMeasureGrp**

**180.2.5279 TestWarningLevelValue**

Value of the measure upon which a warning is issued for the test.

Type: **float**

Used in groups: **TestMeasureGrp**

**180.2.5280 Text**

Free format text string

(Note: this field does not have a specified maximum length)

Type: **String**

Used in groups: **BidCompRspGrp, InstrmtStrkPxGrp, LinesOfTextGrp, ListOrdGrp, MDFullGrp, MDIncGrp, OrdListStatGrp, RelSymDerivSecGrp, RelSymDerivSecUpdGrp, SecListGrp, SecLstUpdRelSymGrp, SecMassStatGrp, SideCrossOrdCxlGrp, SideCrossOrdModGrp, StrmAsgnRptInstrmtGrp, TrdCapRptSideGrp, TrdMatchSideGrp, TrdSessLstGrp**

Used in messages: **Advertisement, AlgoCertificateReport, AlgoCertificateRequest, AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationReport, AllocationReportAck, ApplicationMessageReport, ApplicationMessageRequest, ApplicationMessageRequestAck, AssignmentReport, BidRequest, BusinessMessageReject, CollateralAssignment, CollateralInquiry, CollateralInquiryAck,**



CollateralReport, CollateralReportAck, CollateralRequest, CollateralResponse, Confirmation, ConfirmationAck, ConfirmationRequest, ContraryIntentionReport, DerivativeSecurityListRequest, DontKnowTrade, ExecutionAck, ExecutionReport, IOI, ListCancelRequest, ListExecute, ListStatusRequest, Logon, Logout, MarginRequirementInquiry, MarginRequirementInquiryAck, MarginRequirementReport, MarketDataRequestReject, MarketDataStatisticsReport, MarketDataStatisticsRequest, MarketDefinition, MarketDefinitionUpdateReport, MassOrder, MassOrderAck, MassQuoteAck, MultilegOrderCancelReplace, NewOrderMultileg, NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, PartyActionReport, PartyActionRequest, PartyDetailsDefinitionRequest, PartyDetailsDefinitionRequestAck, PartyDetailsListReport, PartyDetailsListRequest, PartyDetailsListUpdateReport, PartyEntitlementsDefinitionRequest, PartyEntitlementsDefinitionRequestAck, PartyEntitlementsReport, PartyEntitlementsRequest, PartyEntitlementsUpdateReport, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PartyRiskLimitsDefinitionRequest, PartyRiskLimitsDefinitionRequestAck, PartyRiskLimitsReport, PartyRiskLimitsReportAck, PartyRiskLimitsRequest, PartyRiskLimitsUpdateReport, PayManagementReport, PayManagementRequest, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport, Quote, QuoteAck, QuoteRequest, QuoteRequestReject, QuoteResponse, QuoteStatusReport, Reject, RequestForPositions, RequestForPositionsAck, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, SecurityListRequest, SecurityStatus, SecurityTypeRequest, SecurityTypes, SettlementInstructions, SettlementObligationReport, SettlementStatusReport, SettlementStatusRequest, StreamAssignmentReportACK, TestActionReport, TestActionRequest, TestSuiteDefinitionRequest, TradeCaptureReportAck, TradeCaptureReportRequest, TradeCaptureReportRequestAck, TradeMatchReportAck, TradingSessionStatus, UserNotification

### **180.2.5281 Theta**

The security's price rate of change in relation to passage of time. Also known as "time decay".

Type: **float**

Used in groups: **SecurityRiskMetricGrp**

### **180.2.5282 ThresholdAmount**

Amount that a position has to be in the money before it is exercised.

Type: **PriceOffset**

Used in messages: **AssignmentReport, PositionMaintenanceReport, PositionMaintenanceRequest**

**180.2.5283 ThrottleAction**

Action to take should throttle limit be exceeded.

Type: **int**

Allowed values in ThrottleActionCodeSet:

Code	Name	Description
0	QueueInbound	Queue inbound
1	QueueOutbound	Queue outbound
2	Reject	Reject
3	Disconnect	Disconnect
4	Warning	Warning

Used in groups: **ThrottleParamsGrp**

**180.2.5284 ThrottleCountIndicator**

Indicates whether a message decrements the number of outstanding requests, e.g. one where ThrottleType = Outstanding Requests.

Type: **int**

Allowed values in ThrottleCountIndicatorCodeSet:

Code	Name	Description
0	OutstandingRequestsUnchanged	Outstanding requests unchanged
1	OutstandingRequestsDecreased	Outstanding requests decreased

Used in components: **ThrottleResponse**

**180.2.5285 ThrottleInst**

Describes action recipient should take if a throttle limit were exceeded.

Type: **int**

Allowed values in ThrottleInstCodeSet:

Code	Name	Description
0	RejectIfThrottleLimitExceeded	Reject if throttle limit exceeded
1	QueueIfThrottleLimitExceeded	Queue if throttle limit exceeded

Used in components: [ThrottleResponse](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [MassOrder](#), [MassQuote](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderList](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [Quote](#)

### 180.2.5286 ThrottleMsgType

The MsgType (35) of the FIX message being referenced.

Type: [String](#)

Allowed values in MsgTypeCodeSet:

Code	Name	Description
0	Heartbeat	Heartbeat. The Heartbeat monitors the status of the communication link and identifies when the last of a string of messages was not received.
1	TestRequest	TestRequest. The test request message forces a heartbeat from the opposing application. The test request message checks sequence numbers or verifies communication line status. The opposite application responds to the Test Request with a Heartbeat containing the TestReqID.
2	ResendRequest	ResendRequest. The resend request is sent by the receiving application to initiate the retransmission of messages. This function is utilized if a sequence number gap is detected, if the receiving application lost a message, or as a function of the initialization process.
3	Reject	Reject. The reject message should be issued when a message is received but cannot be properly processed due to a session-level rule violation. An example of when a reject may be appropriate would be the receipt of a message with invalid basic data which successfully passes de-encryption, CheckSum and BodyLength checks.
4	SequenceReset	SequenceReset. The sequence reset message is used by the sending application to reset the incoming sequence number on the opposing side.

Code	Name	Description
5	Logout	Logout. The logout message initiates or confirms the termination of a FIX session. Disconnection without the exchange of logout messages should be interpreted as an abnormal condition.
6	IOI	IOI. Indication of interest messages are used to market merchandise which the broker is buying or selling in either a proprietary or agency capacity. The indications can be time bound with a specific expiration value. Indications are distributed with the understanding that other firms may react to the message first and that the merchandise may no longer be available due to prior trade. Indication messages can be transmitted in various transaction types; NEW, CANCEL, and REPLACE. All message types other than NEW modify the state of the message identified in IOIRefID.
7	Advertisement	Advertisement. Advertisement messages are used to announce completed transactions. The advertisement message can be transmitted in various transaction types; NEW, CANCEL and REPLACE. All message types other than NEW modify the state of a previously transmitted advertisement identified in AdvRefID.
8	ExecutionReport	ExecutionReport. The execution report message is used to: 1. confirm the receipt of an order. 2. confirm changes to an existing order (i.e. accept cancel and replace requests). 3. relay order status information. 4. relay fill information on working orders. 5. relay fill information on tradeable or restricted tradeable quotes. 6. reject orders. 7. report post-trade fees calculations associated with a trade
9	OrderCancelReject	OrderCancelReject. The order cancel reject message is issued by the broker upon receipt of a cancel request or cancel/replace request message which cannot be honored.
A	Logon	Logon. The logon message authenticates a user establishing a connection to a remote system. The logon message must be the first message sent by the application requesting to initiate a FIX session.
B	News	News. The news message is a general free format message between the broker and institution. The message contains flags to identify the news item's urgency and to allow sorting by subject company (symbol). The News message can be originated at either the broker or institution side, or exchanges and other marketplace venues.
C	Email	Email. The email message is similar to the format and purpose of the News message, however, it is intended for private use between two parties.

Code	Name	Description
D	NewOrderSingle	NewOrderSingle. The new order message type is used by institutions wishing to electronically submit securities and forex orders to a broker for execution. The New Order message type may also be used by institutions or retail intermediaries wishing to electronically submit Collective Investment Vehicle (CIV) orders to a broker or fund manager for execution.
E	NewOrderList	NewOrderList. The NewOrderList Message can be used in one of two ways depending on which market conventions are being followed.
F	OrderCancelRequest	OrderCancelRequest. The order cancel request message requests the cancellation of all of the remaining quantity of an existing order. Note that the Order Cancel/Replace Request should be used to partially cancel (reduce) an order).
G	OrderCancelReplaceRequest	OrderCancelReplaceRequest. The order cancel/replace request is used to change the parameters of an existing order. Do not use this message to cancel the remaining quantity of an outstanding order, use the Order Cancel Request message for this purpose.
H	OrderStatusRequest	OrderStatusRequest. The order status request message is used by the institution to generate an order status message back from the broker.
J	AllocationInstruction	AllocationInstruction. The AllocationInstruction(35=J) message provides the ability to specify how an order or set of orders should be subdivided amongst one or more accounts.
K	ListCancelRequest	ListCancelRequest. The List Cancel Request message type is used by institutions wishing to cancel previously submitted lists either before or during execution.
L	ListExecute	ListExecute. The List Execute message type is used by institutions to instruct the broker to begin execution of a previously submitted list. This message may or may not be used, as it may be mirroring a phone conversation.
M	ListStatusRequest	ListStatusRequest. The list status request message type is used by institutions to instruct the broker to generate status messages for a list.
N	ListStatus	ListStatus. The list status message is issued as the response to a List Status Request message sent in an unsolicited fashion by the sell-side. It indicates the current state of the orders within the list as they exist at the broker's site. This message may also be used to respond to the List Cancel Request.

Code	Name	Description
P	AllocationInstructionAck	AllocationInstructionAck. In versions of FIX prior to version 4.4, this message was known as the Allocation ACK message. The Allocation Instruction Ack message is used to acknowledge the receipt of and provide status for an Allocation Instruction message.
Q	DontKnowTrade	DontKnowTrade. The Don't Know Trade (DK) message notifies a trading partner that an electronically received execution has been rejected. This message can be thought of as an execution reject message.
R	QuoteRequest	QuoteRequest. In some markets it is the practice to request quotes from brokers prior to placement of an order. The quote request message is used for this purpose. This message is commonly referred to as an Request For Quote (RFQ)
S	Quote	Quote. The Quote message is used as the response to a Quote Request or a Quote Response message in both indicative, tradeable, and restricted tradeable quoting markets.
T	SettlementInstructions	SettlementInstructions. The Settlement Instructions message provides the broker's, the institution's, or the intermediary's instructions for trade settlement. This message has been designed so that it can be sent from the broker to the institution, from the institution to the broker, or from either to an independent "standing instructions" database or matching system or, for CIV, from an intermediary to a fund manager.
V	MarketDataRequest	MarketDataRequest. Some systems allow the transmission of real-time quote, order, trade, trade volume, open interest, and/or other price information on a subscription basis. A MarketDataRequest(35=V) is a general request for market data on specific securities or forex quotes. The values in the fields provided within the request will serve as further filter criteria for the result set.
W	MarketDataSnapshotFullRefresh	MarketDataSnapshotFullRefresh. The Market Data messages are used as the response to a Market Data Request message. In all cases, one Market Data message refers only to one Market Data Request. It can be used to transmit a 2-sided book of orders or list of quotes, a list of trades, index values, opening, closing, settlement, high, low, or VWAP prices, the trade volume or open interest for a security, or any combination of these.

Code	Name	Description
X	MarketDataIncrementalRefresh	MarketDataIncrementalRefresh. The Market Data message for incremental updates may contain any combination of new, changed, or deleted Market Data Entries, for any combination of instruments, with any combination of trades, imbalances, quotes, index values, open, close, settlement, high, low, and VWAP prices, trade volume and open interest so long as the maximum FIX message size is not exceeded. All of these types of Market Data Entries can be changed and deleted.
Y	MarketDataRequestReject	MarketDataRequestReject. The Market Data Request Reject is used when the broker cannot honor the Market Data Request, due to business or technical reasons. Brokers may choose to limit various parameters, such as the size of requests, whether just the top of book or the entire book may be displayed, and whether Full or Incremental updates must be used.
Z	QuoteCancel	QuoteCancel. The Quote Cancel message is used by an originator of quotes to cancel quotes. The Quote Cancel message supports cancellation of: <ul style="list-style-type: none"> <li>• All quotes.</li> <li>• Quotes for a specific symbol or security ID.</li> <li>• All quotes for a security type.</li> <li>• All quotes for an underlying</li> </ul>
a	QuoteStatusRequest	QuoteStatusRequest. The quote status request message is used for the following purposes in markets that employ tradeable or restricted tradeable quotes: <ul style="list-style-type: none"> <li>• For the issuer of a quote in a market to query the status of that quote (using the QuoteID to specify the target quote).</li> <li>• To subscribe and unsubscribe for Quote Status Report messages for one or more securities.</li> </ul>
b	MassQuoteAck	MassQuoteAck. Mass Quote Acknowledgement is used as the application level response to a Mass Quote message.
c	SecurityDefinitionRequest	SecurityDefinitionRequest. The SecurityDefinitionRequest(35=c) message is used for the following: <ol style="list-style-type: none"> <li>1. Request a specific security to be traded with the second party. The requested security can be defined as a multileg security made up of one or more instrument legs.</li> <li>2. Request a set of individual securities for a single market segment.</li> <li>3. Request all securities, independent of market segment.</li> </ol>

Code	Name	Description
d	SecurityDefinition	SecurityDefinition. The SecurityDefinition(35=d) message is used for the following:. 1. Accept the security defined in a SecurityDefinition(35=d) message. 2. Accept the security defined in a SecurityDefinition(35=d) message with changes to the definition and/or identity of the security. 3. Reject the security requested in a SecurityDefinition(35=d) message. 4. Respond to a request for securities within a specified market segment. 5. Convey comprehensive security definition for all market segments that the security participates in. 6. Convey the security's trading rules that differ from default rules for the market segment.
e	SecurityStatusRequest	SecurityStatusRequest. The Security Status Request message provides for the ability to request the status of a security. One or more Security Status messages are returned as a result of a Security Status Request message.
f	SecurityStatus	SecurityStatus. The Security Status message provides for the ability to report changes in status to a security. The Security Status message contains fields to indicate trading status, corporate actions, financial status of the company. The Security Status message is used by one trading entity (for instance an exchange) to report changes in the state of a security.
g	TradingSessionStatusRequest	TradingSessionStatusRequest. The Trading Session Status Request is used to request information on the status of a market. With the move to multiple sessions occurring for a given trading party (morning and evening sessions for instance) there is a need to be able to provide information on what product is trading on what market.
h	TradingSessionStatus	TradingSessionStatus. The Trading Session Status provides information on the status of a market. For markets multiple trading sessions on multiple-markets occurring (morning and evening sessions for instance), this message is able to provide information on what products are trading on what market during what trading session.
i	MassQuote	MassQuote. The Mass Quote message can contain quotes for multiple securities to support applications that allow for the mass quoting of an option series. Two levels of repeating groups have been provided to minimize the amount of data required to submit a set of quotes for a class of options (e.g. all option series for IBM).



Code	Name	Description
j	BusinessMessageReject	BusinessMessageReject. The Business Message Reject message can reject an application-level message which fulfills session-level rules and cannot be rejected via any other means. Note if the message fails a session-level rule (e.g. body length is incorrect), a session-level Reject message should be issued.
k	BidRequest	BidRequest. The BidRequest Message can be used in one of two ways depending on which market conventions are being followed. In the "Non disclosed" convention (e.g. US/European model) the BidRequest message can be used to request a bid based on the sector, country, index and liquidity information contained within the message itself. In the "Non disclosed" convention the entry repeating group is used to define liquidity of the program. See " Program/Basket/List Trading" for an example. In the "Disclosed" convention (e.g. Japanese model) the BidRequest message can be used to request bids based on the ListOrderDetail messages sent in advance of BidRequest message. In the "Disclosed" convention the list repeating group is used to define which ListOrderDetail messages a bid is being sort for and the directions of the required bids.
l	BidResponse	BidResponse. The Bid Response message can be used in one of two ways depending on which market conventions are being followed. In the "Non disclosed" convention the Bid Response message can be used to supply a bid based on the sector, country, index and liquidity information contained within the corresponding bid request message. See "Program/Basket/List Trading" for an example. In the "Disclosed" convention the Bid Response message can be used to supply bids based on the List Order Detail messages sent in advance of the corresponding Bid Request message.
m	ListStrikePrice	ListStrikePrice. The strike price message is used to exchange strike price information for principal trades. It can also be used to exchange reference prices for agency trades.
n	XMLnonFIX	XMLnonFIX.
o	RegistrationInstructions	RegistrationInstructions. The Registration Instructions message type may be used by institutions or retail intermediaries wishing to electronically submit registration information to a broker or fund manager (for CIV) for an order or for an allocation.
p	RegistrationInstructionsResponse	RegistrationInstructionsResponse. The Registration Instructions Response message type may be used by broker or fund manager (for CIV) in response to a Registration Instructions message submitted by an institution or retail intermediary for an order or for an allocation.

Code	Name	Description
q	OrderMassCancelRequest	OrderMassCancelRequest. The order mass cancel request message requests the cancellation of all of the remaining quantity of a group of orders matching criteria specified within the request. NOTE: This message can only be used to cancel order messages (reduce the full quantity).
r	OrderMassCancelReport	OrderMassCancelReport. The Order Mass Cancel Report is used to acknowledge an Order Mass Cancel Request. Note that each affected order that is canceled is acknowledged with a separate Execution Report or Order Cancel Reject message.
s	NewOrderCross	NewOrderCross. Used to submit a cross order into a market. The cross order contains two order sides (a buy and a sell). The cross order is identified by its CrossID.
t	CrossOrderCancelReplaceRequest	CrossOrderCancelReplaceRequest. Used to modify a cross order previously submitted using the New Order - Cross message. See Order Cancel Replace Request for details concerning message usage.
u	CrossOrderCancelRequest	CrossOrderCancelRequest. Used to fully cancel the remaining open quantity of a cross order.
v	SecurityTypeRequest	SecurityTypeRequest. The Security Type Request message is used to return a list of security types available from a counterparty or market.
w	SecurityTypes	SecurityTypes. The Security Type Request message is used to return a list of security types available from a counterparty or market.
x	SecurityListRequest	SecurityListRequest. The Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request
y	SecurityList	SecurityList. The Security List message is used to return a list of securities that matches the criteria specified in a Security List Request.
z	DerivativeSecurityListRequest	DerivativeSecurityListRequest. The Derivative Security List Request message is used to return a list of securities from the counterparty that match criteria provided on the request
AA	DerivativeSecurityList	DerivativeSecurityList. The Derivative Security List message is used to return a list of securities that matches the criteria specified in a Derivative Security List Request.
AB	NewOrderMultileg	NewOrderMultileg. The New Order - Multileg is provided to submit orders for securities that are made up of multiple securities, known as legs.

Code	Name	Description
AC	MultilegOrderCancelReplace	MultilegOrderCancelReplace. Used to modify a multileg order previously submitted using the New Order - Multileg message. See Order Cancel Replace Request for details concerning message usage.
AD	TradeCaptureReportRequest	TradeCaptureReportRequest. The Trade Capture Report Request can be used to: <ul style="list-style-type: none"> <li>• Request one or more trade capture reports based upon selection criteria provided on the trade capture report request.</li> <li>• Subscribe for trade capture reports based upon selection criteria provided on the trade capture report request.</li> </ul>
AE	TradeCaptureReport	TradeCaptureReport. The Trade Capture Report message can be: <ul style="list-style-type: none"> <li>- Used to report trades between counterparties.</li> <li>- Used to report trades to a trade matching system.</li> <li>- Sent unsolicited between counterparties.</li> <li>- Sent as a reply to a Trade Capture Report Request.</li> <li>- Used to report unmatched and matched trades.</li> </ul>
AF	OrderMassStatusRequest	OrderMassStatusRequest. The order mass status request message requests the status for orders matching criteria specified within the request.
AG	QuoteRequestReject	QuoteRequestReject. The Quote Request Reject message is used to reject Quote Request messages for all quoting models.
AH	RFQRequest	RFQRequest. In tradeable and restricted tradeable quoting markets – Quote Requests are issued by counterparties interested in ascertaining the market for an instrument. Quote Requests are then distributed by the market to liquidity providers who make markets in the instrument. The RFQ Request is used by liquidity providers to indicate to the market for which instruments they are interested in receiving Quote Requests. It can be used to register interest in receiving quote requests for a single instrument or for multiple instruments
AI	QuoteStatusReport	QuoteStatusReport. The quote status report message is used: <ul style="list-style-type: none"> <li>• as the response to a Quote Status Request message.</li> <li>• as a response to a Quote Cancel message.</li> <li>• as a response to a Quote Response message in a negotiation dialog (see Volume 7 – PRODUCT: FIXED INCOME and USER GROUP: EXCHANGES AND MARKETS)</li> </ul>
AJ	QuoteResponse	QuoteResponse. The QuoteResponse(35=AJ) message is used for the following purposes: <ol style="list-style-type: none"> <li>1. Respond to an IOI(35=6) message.</li> <li>2. Respond to a Quote(35=S) message.</li> <li>3. Counter a Quote.</li> <li>4. End a negotiation dialog.</li> <li>5. Follow-up or end a QuoteRequest(35=R) dialog that did not receive a response.</li> </ol>

Code	Name	Description
AK	Confirmation	Confirmation. The Confirmation messages are used to provide individual trade level confirmations from the sell side to the buy side. In versions of FIX prior to version 4.4, this role was performed by the allocation message. Unlike the allocation message, the confirmation message operates at an allocation account (trade) level rather than block level, allowing for the affirmation or rejection of individual confirmations.
AL	PositionMaintenanceRequest	PositionMaintenanceRequest. The Position Maintenance Request message allows the position owner to submit requests to the holder of a position which will result in a specific action being taken which will affect the position. Generally, the holder of the position is a central counter party or clearing organization but can also be a party providing investment services.
AM	PositionMaintenanceReport	PositionMaintenanceReport. The Position Maintenance Report message is sent by the holder of a position in response to a Position Maintenance Request and is used to confirm that a request has been successfully processed or rejected.
AN	RequestForPositions	RequestForPositions. The Request For Positions message is used by the owner of a position to request a Position Report from the holder of the position, usually the central counter party or clearing organization. The request can be made at several levels of granularity.
AO	RequestForPositionsAck	RequestForPositionsAck. The Request for Positions Ack message is returned by the holder of the position in response to a Request for Positions message. The purpose of the message is to acknowledge that a request has been received and is being processed.
AP	PositionReport	PositionReport. The Position Report message is returned by the holder of a position in response to a Request for Position message. The purpose of the message is to report all aspects of a position and may be provided on a standing basis to report end of day positions to an owner.

Code	Name	Description
AQ	TradeCaptureReportRequestAck	TradeCaptureReportRequestAck. The Trade Capture Request Ack message is used to: - Provide an acknowledgement to a Trade Capture Report Request in the case where the Trade Capture Report Request is used to specify a subscription or delivery of reports via an out-of-band ResponseTransmissionMethod. - Provide an acknowledgement to a Trade Capture Report Request in the case when the return of the Trade Capture Reports matching that request will be delayed or delivered asynchronously. This is useful in distributed trading system environments. - Indicate that no trades were found that matched the selection criteria specified on the Trade Capture Report Request or the Trade Capture Request was invalid for some business reason, such as request is not authorized, invalid or unknown instrument, party, trading session, etc.
AR	TradeCaptureReportAck	TradeCaptureReportAck. The Trade Capture Report Ack message can be: - Used to acknowledge trade capture reports received from a counterparty. - Used to reject a trade capture report received from a counterparty.
AS	AllocationReport	AllocationReport. Sent from sell-side to buy-side, sell-side to 3rd-party or 3rd-party to buy-side, the AllocationReport(35=AS) message (Claim) provides account breakdown of an order or set of orders plus any additional follow-up front-office information developed post-trade during the trade allocation, matching and calculation phase.
AT	AllocationReportAck	AllocationReportAck. The Allocation Report Ack message is used to acknowledge the receipt of and provide status for an Allocation Report message.
AU	ConfirmationAck	ConfirmationAck. The Confirmation Ack (aka Affirmation) message is used to respond to a Confirmation message.
AV	SettlementInstructionRequest	SettlementInstructionRequest. The Settlement Instruction Request message is used to request standing settlement instructions from another party.
AW	AssignmentReport	AssignmentReport. Assignment Reports are sent from a clearing house to counterparties, such as a clearing firm as a result of the assignment process.
AX	CollateralRequest	CollateralRequest. An initiator that requires collateral from a respondent sends a Collateral Request. The initiator can be either counterparty to a trade in a two party model or an intermediary such as an ATS or clearinghouse in a three party model. A Collateral Assignment is expected as a response to a request for collateral.

Code	Name	Description
AY	CollateralAssignment	CollateralAssignment. Used to assign collateral to cover a trading position. This message can be sent unsolicited or in reply to a Collateral Request message.
AZ	CollateralResponse	CollateralResponse. Used to respond to a Collateral Assignment message.
BA	CollateralReport	CollateralReport. Used to report collateral status when responding to a Collateral Inquiry message.
BB	CollateralInquiry	CollateralInquiry. Used to inquire for collateral status.
BC	NetworkCounterpartySystemStatus-Request	NetworkCounterpartySystemStatusRequest. This message is send either immediately after logging on to inform a network (counterparty system) of the type of updates required or to at any other time in the FIX conversation to change the nature of the types of status updates required. It can also be used with a NetworkRequestType of Snapshot to request a one-off report of the status of a network (or counterparty) system. Finally this message can also be used to cancel a request to receive updates into the status of the counterparties on a network by sending a NetworkRequestStatusMessage with a NetworkRequestType of StopSubscribing.
BD	NetworkCounterpartySystemStatus-Response	NetworkCounterpartySystemStatusResponse. This message is sent in response to a Network (Counterparty System) Status Request Message.
BE	UserRequest	UserRequest. This message is used to initiate a user action, logon, logout or password change. It can also be used to request a report on a user's status.
BF	UserResponse	UserResponse. This message is used to respond to a user request message, it reports the status of the user after the completion of any action requested in the user request message.
BG	CollateralInquiryAck	CollateralInquiryAck. Used to respond to a Collateral Inquiry in the following situations: • When the CollateralInquiry will result in an out of band response (such as a file transfer). • When the inquiry is otherwise valid but no collateral is found to match the criteria specified on the Collateral Inquiry message. • When the Collateral Inquiry is invalid based upon the business rules of the counterparty.
BH	ConfirmationRequest	ConfirmationRequest. The Confirmation Request message is used to request a Confirmation message.

Code	Name	Description
BO	ContraryIntentionReport	ContraryIntentionReport. The Contrary Intention Report is used for reporting of contrary expiration quantities for Saturday expiring options. This information is required by options exchanges for regulatory purposes.
BP	SecurityDefinitionUpdateReport	SecurityDefinitionUpdateReport. This message is used for reporting updates to a product security master file. Updates could be the result of corporate actions or other business events. Updates may include additions, modifications or deletions.
BK	SecurityListUpdateReport	SecurityListUpdateReport. The Security List Update Report is used for reporting updates to a Contract Security Masterfile. Updates could be due to Corporate Actions or other business events. Update may include additions, modifications and deletions.
BL	AdjustedPositionReport	AdjustedPositionReport. Used to report changes in position, primarily in equity options, due to modifications to the underlying due to corporate actions
BM	AllocationInstructionAlert	AllocationInstructionAlert. This message is used in a 3-party allocation model (buy-side and sell-side using a central clearing entity) where notification of group creation and group updates to counterparties is needed. The message will also carry trade information that comprised the group to the counterparties.
BN	ExecutionAck	ExecutionAck. The Execution Report Acknowledgement message is an optional message that provides dual functionality to notify a trading partner that an electronically received execution has either been accepted or rejected (DK'd).
BJ	TradingSessionList	TradingSessionList. The Trading Session List message is sent as a response to a Trading Session List Request. The Trading Session List should contain the characteristics of the trading session and the current state of the trading session.
BI	TradingSessionListRequest	TradingSessionListRequest. The Trading Session List Request is used to request a list of trading sessions available in a market place and the state of those trading sessions. A successful request will result in a response from the counterparty of a Trading Session List (MsgType=BJ) message that contains a list of zero or more trading sessions.
BQ	SettlementObligationReport	SettlementObligationReport. The Settlement Obligation Report message provides a central counterparty, institution, or individual counterparty with a capacity for reporting the final details of a currency settlement obligation.

Code	Name	Description
BR	DerivativeSecurityListUpdateReport	DerivativeSecurityListUpdateReport. The Derivative Security List Update Report message is used to send updates to an option family or the strikes that comprise an option family.
BS	TradingSessionListUpdateReport	TradingSessionListUpdateReport. The Trading Session List Update Report is used by marketplaces to provide intra-day updates of trading sessions when there are changes to one or more trading sessions.
BT	MarketDefinitionRequest	MarketDefinitionRequest. The Market Definition Request message is used to request for market structure information from the Respondent that receives this request.
BU	MarketDefinition	MarketDefinition. The MarketDefinition(35=BU) message is used to respond to MarketDefinitionRequest(35=BT). In a subscription, it will be used to provide the initial snapshot of the information requested. Subsequent updates are provided by the MarketDefinitionUpdateReport(35=BV).
BV	MarketDefinitionUpdateReport	MarketDefinitionUpdateReport. In a subscription for market structure information, this message is used once the initial snapshot of the information has been sent using the MarketDefinition(35=BU) message.
BW	ApplicationMessageRequest	ApplicationMessageRequest. This message is used to request a retransmission of a set of one or more messages generated by the application specified in RefApplID (1355).
BX	ApplicationMessageRequestAck	ApplicationMessageRequestAck. This message is used to acknowledge an Application Message Request providing a status on the request (i.e. whether successful or not). This message does not provide the actual content of the messages to be resent.
BY	ApplicationMessageReport	ApplicationMessageReport. This message is used for three difference purposes: to reset the ApplSeqNum (1181) of a specified ApplID (1180). to indicate that the last message has been sent for a particular ApplID, or as a keep-alive mechanism for ApplIDs with infrequent message traffic.
BZ	OrderMassActionReport	OrderMassActionReport. The Order Mass Action Report is used to acknowledge an Order Mass Action Request. Note that each affected order that is suspended or released or canceled is acknowledged with a separate Execution Report for each order.
CA	OrderMassActionRequest	OrderMassActionRequest. The Order Mass Action Request message can be used to request the suspension or release of a group of orders that match the criteria specified within the request. This is equivalent to individual Order Cancel Replace Requests for each order with or without adding "S" to the ExecInst values. It can also be used for mass order cancellation.



Code	Name	Description
CB	UserNotification	UserNotification. The User Notification message is used to notify one or more users of an event or information from the sender of the message. This message is usually sent unsolicited from a marketplace (e.g. Exchange, ECN) to a market participant.
CC	StreamAssignmentRequest	StreamAssignmentRequest. In certain markets where market data aggregators fan out to end clients the pricing streams provided by the price makers, the price maker may assign the clients to certain pricing streams that the price maker publishes via the aggregator. An example of this use is in the FX markets where clients may be assigned to different pricing streams based on volume bands and currency pairs.
CD	StreamAssignmentReport	StreamAssignmentReport. The StreamAssignmentReport(35=CD) message is in response to the StreamAssignmentRequest(35=CC) message. It provides information back to the aggregator as to which clients to assign to receive which price stream based on requested CCY pair. This message can be sent unsolicited to the Aggregator from the Price Maker.
CE	StreamAssignmentReportACK	StreamAssignmentReportACK. This message is used to respond to the Stream Assignment Report, to either accept or reject an unsolicited assigningment.
CF	PartyDetailsListRequest	PartyDetailsListRequest. The PartyDetailsListRequest is used to request party detail information.
CG	PartyDetailsListReport	PartyDetailsListReport. The PartyDetailsListReport message is used to disseminate party details between counterparties. PartyDetailsListReport messages may be sent in response to a PartyDetailsListRequest message or sent unsolicited.

Code	Name	Description
CH	MarginRequirementInquiry	MarginRequirementInquiry. The purpose of this message is to initiate a margin requirement inquiry for a margin account. The inquiry may be submitted at the detail level or the summary level. It can also be used to inquire margin excess/deficit or net position information. Margin excess/deficit will provide information about the surplus or shortfall compared to the previous trading day or a more recent margin calculation. An inquiry for net position information will trigger one or more PositionReport messages instead of one or more MarginRequirementReport messages. If the inquiry is made at the detail level, an Instrument block must be provided with the desired level of detail. If the inquiry is made at the summary level, the Instrument block is not provided, implying a summary request is being made. For example, if the inquiring firm specifies the Security Type of "FUT" in the Instrument block, then a detail report will be generated containing the margin requirements for all futures positions for the inquiring account. Similarly, if the inquiry is made at the summary level, the report will contain the total margin requirement aggregated to the margin account level.
CI	MarginRequirementInquiryAck	MarginRequirementInquiryAck. Used to respond to a Margin Requirement Inquiry.
CJ	MarginRequirementReport	MarginRequirementReport. The Margin Requirement Report returns information about margin requirement either as an overview across all margin accounts or on a detailed level due to the inquiry making use of the optional Instrument component block. Application sequencing can be used to re-request a range of reports.
CK	PartyDetailsListUpdateReport	PartyDetailsListUpdateReport. The PartyDetailsListUpdateReport(35=CK) is used to disseminate updates to party detail information.
CL	PartyRiskLimitsRequest	PartyRiskLimitsRequest. The PartyRiskLimitsRequest message is used to request for risk information for specific parties, specific party roles or specific instruments.
CM	PartyRiskLimitsReport	PartyRiskLimitsReport. The PartyRiskLimitsReport message is used to communicate party risk limits. The message can either be sent as a response to the PartyRiskLimitsRequest message or can be published unsolicited.
CN	SecurityMassStatusRequest	SecurityMassStatusRequest.
CO	SecurityMassStatus	SecurityMassStatus.

Code	Name	Description
CQ	AccountSummaryReport	AccountSummaryReport. The AccountSummaryReport is provided by the clearinghouse to its clearing members on a daily basis. It contains margin, settlement, collateral and pay/collect data for each clearing member level account type. Clearing member account types will be described through use of the Parties component and PtysSubGrp sub-component. In certain usages, the clearing members can send the AccountSummaryReport message to the clearinghouse as needed. For example, clearing members can send this message to the clearinghouse to identify the value of collateral for each customer (to satisfy CFTC Legally Segregated Operationally Commingled (LSOC) regulatory reporting obligations). Clearing organizations can also send the AccountSummaryReport message to regulators to meet regulatory reporting obligations. For example, clearing organizations can use this message to submit daily reports for each clearing member ("CM") by house origin and by each customer origin for all futures, options, and swaps positions, and all securities positions held in a segregated account or pursuant to a cross margining agreement, to a regulator (e.g. to the CFTC to meet Part 39, Section 39.19 reporting obligations).
CR	PartyRiskLimitsUpdateReport	PartyRiskLimitsUpdateReport. The PartyRiskLimitsUpdateReport(35=CR) is used to convey incremental changes to risk limits. It is similar to the regular report but uses the PartyRiskLimitsUpdateGrp component instead of the PartyRiskLimitsGrp component to include an update action.
CS	PartyRiskLimitsDefinitionRequest	PartyRiskLimitsDefinitionRequest. PartyRiskLimitDefinitionRequest is used for defining new risk limits.
CT	PartyRiskLimitsDefinitionRequestAck	PartyRiskLimitsDefinitionRequestAck. PartyRiskLimitDefinitionRequestAck is used for accepting (with or without changes) or rejecting the definition of risk limits.
CU	PartyEntitlementsRequest	PartyEntitlementsRequest. The PartyEntitlementsRequest message is used to request for entitlement information for one or more party(-ies), specific party role(s), or specific instruments(s).
CV	PartyEntitlementsReport	PartyEntitlementsReport. The PartyEntitlementsReport is used to report entitlements for one or more parties, party role(s), or specific instrument(s).

Code	Name	Description
CW	QuoteAck	QuoteAck. The QuoteAck(35=CW) message is used to acknowledge a Quote(35=S) submittal or request to cancel an individual quote using the QuoteCancel(35=Z) message during a Quote/Negotiation dialog.
CX	PartyDetailsDefinitionRequest	PartyDetailsDefinitionRequest. The PartyDetailsDefinitionRequest(35=CX) is used for defining new parties and modifying or deleting existing parties information, including the relationships between parties. The recipient of the message responds with a PartyDetailsDefinitionRequestAck(35=CY) to indicate whether the request was accepted or rejected.
CY	PartyDetailsDefinitionRequestAck	PartyDetailsDefinitionRequestAck. The PartyDetailsDefinitionRequestAck(35=CY) is used as a response to the PartyDetailsDefinitionRequest(35=CX) message. The request can be accepted (with or without changes) or rejected.
CZ	PartyEntitlementsUpdateReport	PartyEntitlementsUpdateReport. The PartyEntitlementsUpdateReport(35=CZ) is used to convey incremental changes to party entitlements. It is similar to the PartyEntitlementsReport(35=CV). This message uses the PartyEntitlementsUpdateGrp component which includes the ability to specify an update action using ListUpdateAction(1324).
DA	PartyEntitlementsDefinitionRequest	PartyEntitlementsDefinitionRequest. The PartyEntitlementsDefinitionRequest(35=DA) is used for defining new entitlements, and modifying or deleting existing entitlements for the specified party(-ies).
DB	PartyEntitlementsDefinitionRequestAck	PartyEntitlementsDefinitionRequestAck. The PartyEntitlementsDefinitionRequestAck(35=DB) is used as a response to the PartyEntitlementsDefinitionRequest(35=DA) to accept (with or without changes) or reject the definition of party entitlements.
DC	TradeMatchReport	TradeMatchReport. The TradeMatchReport(35=DC) message is used by exchanges and ECN's to report matched trades to central counterparties (CCPs) as an atomic event. The message is used to express the one-to-one, one-to-many and many-to-many matches as well as implied matches in which more complex instruments can match with simpler instruments.
DD	TradeMatchReportAck	TradeMatchReportAck. The TradeMatchReportAck(35=DD) is used to respond to the TradeMatchReport(35=DC) message. It may be used to report on the status of the request (e.g. accepting the request or rejecting the request).

Code	Name	Description
DE	PartyRiskLimitsReportAck	PartyRiskLimitsReportAck. PartyRiskLimitsReportAck is an optional message used as a response to the PartyRiskLimitReport(35=CM) or PartyRiskLimitUpdateReport(35=CR) messages to acknowledge or reject those messages.
DF	PartyRiskLimitCheckRequest	PartyRiskLimitCheckRequest. PartyRiskLimitCheckRequest is used to request for approval of credit or risk limit amount intended to be used by a party in a transaction from another party that holds the information.
DG	PartyRiskLimitCheckRequestAck	PartyRiskLimitCheckRequestAck. PartyRiskLimitCheckRequestAck is used to acknowledge a PartyRiskLimitCheckRequest(35=DF) message and to respond whether the limit check request was approved or not. When used to accept the PartyRiskLimitCheckRequest(35=DF) message the Respondent may also include the limit amount that was approved.
DH	PartyActionRequest	PartyActionRequest. The PartyActionRequest message is used suspend or halt the specified party from further trading activities at the Respondent. The Respondent must respond with a PartyActionReport(35=DI) message.
DI	PartyActionReport	PartyActionReport. Used to respond to the PartyActionRequest(35=DH) message, indicating whether the request has been received, accepted or rejected. Can also be used in an unsolicited manner to report party actions, e.g. reinstatements after a manual intervention out of band.
DJ	MassOrder	MassOrder. The MassOrder(35=DJ) message can be used to add, modify or delete multiple unrelated orders with a single message. Apart from clearing related attributes, only the key order attributes for high performance trading are available.
DK	MassOrderAck	MassOrderAck. The mass order acknowledgement message is used to acknowledge the receipt of and the status for a MassOrder(35=DJ) message.
DL	PositionTransferInstruction	PositionTransferInstruction. The PositionTransferInstruction(35=DL) is sent by clearing firms to CCPs to initiate position transfers, or to accept or decline position transfers.
DM	PositionTransferInstructionAck	PositionTransferInstructionAck. The PositionTransferInstructionAck(35=DM) is sent by CCPs to clearing firms to acknowledge position transfer instructions, and to report errors processing position transfer instructions.

Code	Name	Description
DN	PositionTransferReport	PositionTransferReport. The PositionTransferReport(35=DN) is sent by CCPs to clearing firms indicating of positions that are to be transferred to the clearing firm, or to report on status of the transfer to the clearing firms involved in the transfer process.
DO	MarketDataStatisticsRequest	MarketDataStatisticsRequest. The MarketDataStatisticsRequest(35=DO) is used to request for statistical data. The simple form is to use an identifier (MDStatisticID(2475)) assigned by the market place which would denote a pre-defined statistical report. Alternatively, or also in addition, the request can define a number of parameters for the desired statistical information.
DP	MarketDataStatisticsReport	MarketDataStatisticsReport. The MarketDataStatisticsReport(35=DP) is used to provide unsolicited statistical information or in response to a specific request. Each report contains a set of statistics for a single entity which could be a market, a market segment, a security list or an instrument.
DQ	CollateralReportAck	CollateralReportAck. CollateralReportAck(35=DQ) is used as a response to the CollateralReport(35=BA). It can be used to reject a CollateralReport(35=BA) when the content of the report is invalid based on the business rules of the receiver. The message may also be used to acknowledge receipt of a valid CollateralReport(35=BA).
DR	MarketDataReport	MarketDataReport. The MarketDataReport(35=DR) message is used to provide delimiting references (e.g. start and end markers in a continuous broadcast) and details about the number of market data messages sent in a given distribution cycle.
DS	CrossRequest	CrossRequest. The CrossRequest(35=DS) message is used to indicate the submission of orders or quotes that may result in a crossed trade.
DT	CrossRequestAck	CrossRequestAck. The CrossRequestAck(35=DT) message is used to confirm the receipt of a CrossRequest(35=DS) message.
DU	AllocationInstructionAlertRequest	AllocationInstructionAlertRequest. This message is used in a clearinghouse 3-party allocation model to request for AllocationInstructionAlert(35=BM) from the clearinghouse. The request may be used to obtain a one-time notification of the status of an allocation group.

Code	Name	Description
DV	AllocationInstructionAlertRequestAck	AllocationInstructionAlertRequestAck. This message is used in a clearinghouse 3-party allocation model to acknowledge a AllocationInstructionAlertRequest(35=DU) message for an AllocationInstructionAlert(35=BM) message from the clearinghouse.
DW	TradeAggregationRequest	TradeAggregationRequest. TradeAggregationRequest(35=DW) is used to request that the identified trades between the initiator and respondent be aggregated together for further processing.
DX	TradeAggregationReport	TradeAggregationReport. TradeAggregationReport(35=DX) is used to respond to the TradeAggregationRequest(35=DW) message. It provides the status of the request (e.g. accepted or rejected) and may also provide additional information supplied by the respondent.
EA	PayManagementReport	PayManagementReport. PayManagementReport(35=EA) may be used to respond to the PayManagementRequest(35=DY) message. It provides the status of the request (e.g. accepted, disputed) and may provide additional information related to the request. PayManagementReport(35=EA) may also be sent unsolicited by the broker to a client. In which case the client may acknowledge and resolve disputes out-of-band or with a simple PayManagementReportAck(35=EB). PayManagementReport(35=EA) may also be sent unsolicited to report the progress status of the payment itself with PayReportTransType(2804)=2 (Status).
EB	PayManagementReportAck	PayManagementReportAck. PayManagementReportAck(35=EB) is used as a response to the PayManagementReport(35=EA) message. It may be used to accept, reject or dispute the details of the PayManagementReport(35=EA) depending on the business rules of the receiver. This message may also be used to acknowledge the receipt of a PayManagementReport(35=EA) message.
DY	PayManagementRequest	PayManagementRequest. PayManagementRequest(35=DY) message is used to communicate a future or expected payment to be made or received related to a trade or contract after its settlement.
DZ	PayManagementRequestAck	PayManagementRequestAck. PayManagementRequestAck(35=DZ) is used to acknowledge the receipt of the PayManagementRequest(35=DY) message (i.e. a technical acknowledgement of receipt). Acceptance or rejection of the request is reported in the corresponding PayManagementReport(35=EA).

Code	Name	Description
EC	SettlementStatusRequest	SettlementStatusRequest. SettlementStatusRequest(35=EC) is used to request for the settlement status of a trade.
ED	SettlementStatusRequestAck	SettlementStatusRequestAck. SettlementStatusRequestAck(35=ED) is used to respond to the SettlementStatusRequest(35=EC) to acknowledge the request and provide status for the request message.
EE	SettlementStatusReport	SettlementStatusReport. SettlementStatusReport(35=EE) is a response to the SettlementStatusRequest(35=EC) to provide settlement status for the requested trade. It may also be sent unsolicited without an explicit request message by the party able to provide the settlement status for the trade identified in the report message.
EF	SettlementStatusReportAck	SettlementStatusReportAck. SettlementStatusReportAck(35=EF) is used to respond to the SettlementStatusReport(35=EE) to acknowledge or reject the report.
EG	SecurityRiskMetricsReport	SecurityRiskMetricsReport. SecurityRiskMetricsReport(35=EG) is used for publishing the risk metrics, valuation metrics or analytics of one or more securities, or for an option series.
EH	AlgoCertificateRequest	AlgoCertificateRequest. AlgoCertificateRequest(35=EH) is used to request algo testing certificate information for one or more algorithms.
EI	AlgoCertificateRequestAck	AlgoCertificateRequestAck. AlgoCertificateRequestAck(35=EI) is used to respond to the AlgoCertificateRequest(35=EH) to acknowledge the request and provide status for the request message.
EJ	AlgoCertificateReport	AlgoCertificateReport. AlgoCertificateReport(35=EJ) is a response to the AlgoCertificateRequest(35=EH) to certify an algo. It may also be sent unsolicited without an explicit request message by the party able to provide certificate information for the algo identified in the report message.
EK	AlgoCertificateReportAck	AlgoCertificateReportAck. AlgoCertificateReportAck(35=EK) is used to respond to the AlgoCertificateReport(35=EJ) to acknowledge or reject the report message.
EL	TestSuiteDefinitionRequest	TestSuiteDefinitionRequest. TestSuiteDefinitionRequest(35=EL) is used to convey to the test system the suite of test scenarios to perform.
EM	TestSuiteDefinitionRequestAck	TestSuiteDefinitionRequestAck. TestSuiteDefinitionRequestAck(35=EM) is used to respond to the TestSuiteDefinitionRequest(35=EL) to acknowledge the request and provide status for the request message.



Code	Name	Description
EN	TestActionRequest	TestActionRequest. TestActionRequest(35=EN) is used to manage test executions or request for testing activity state of the identified test suite.
EO	TestActionRequestAck	TestActionRequestAck. TestActionRequestAck(35=EO) is used to respond to the TestActionRequest(35=EN) to acknowledge the request and provide status for the request message.
EP	TestActionReport	TestActionReport. TestActionReport(35=EP) is used to report the testing results of the identified test suite that has been executed with TestActionRequest(35=EN). In the context of algorithmic trading, the results may be used to create a certificate for the algorithm upon meeting the success criteria.

Used in groups: [ThrottleMsgTypeGrp](#)

#### 180.2.5287 ThrottleMsgTypeGrp

Name	Mult.	Type	Description
NoThrottleMsgType	[1..1]	NumInGroup	
ThrottleMsgType	[0..1]	CodeSet	Required when NoThrottleMsgType > 0.

Used in groups: [ThrottleParamsGrp](#)

#### 180.2.5288 ThrottleNoMsgs

Maximum number of messages allowed by the throttle. May be a rate limit or a limit on the number of outstanding requests.

Type: [int](#)

Used in groups: [ThrottleParamsGrp](#)

#### 180.2.5289 ThrottleParamsGrp

Name	Mult.	Type	Description
NoThrottles	[1..1]	NumInGroup	Indicates number of throttles to follow.
ThrottleAction	[0..1]	CodeSet	Required when NoThrottles > 0.
ThrottleType	[0..1]	CodeSet	Required when NoThrottles > 0.
ThrottleNoMsgs	[0..1]	int	Number of messages per time interval, or number of outstanding requests. Required when NoThrottles > 0.
ThrottleTimeInterval	[0..1]	int	Can be used only when ThrottleType = Inbound Rate. Indicates, along with ThrottleTimeUnit, the interval of time in which ThrottleNoMsgs may be sent. Default is 1.
ThrottleTimeUnit	[0..1]	CodeSet	Can be used only when ThrottleType = Inbound Rate. Indicates, along with ThrottleTimeUnit, the interval of time in which ThrottleNoMsgs may be sent. Default is Seconds.
ThrottleMsgTypeGrp	[0..*]	Group	Indicates MsgType values that this throttle counts. If not specified, the definition is implicit based upon bilateral agreement.

Used in messages: [UserNotification](#), [UserResponse](#)

### 180.2.5290 ThrottleResponse

Name	Mult.	Type	Description
ThrottleInst	[0..1]	CodeSet	
ThrottleStatus	[0..1]	CodeSet	
ThrottleCountIndicator	[0..1]	CodeSet	

Used in messages: [ExecutionReport](#), [MassOrderAck](#), [MassQuoteAck](#), [QuoteStatusReport](#)

### 180.2.5291 ThrottleStatus

Indicates whether a message was queued as a result of throttling.

Type: [int](#)

Allowed values in ThrottleStatusCodeSet:

Code	Name	Description
0	ThrottleLimitNotExceeded-NotQueued	Throttle limit not exceeded, not queued
1	QueuedDueToThrottleLimitExceeded	Queued due to throttle limit exceeded

Used in components: [ThrottleResponse](#)

### 180.2.5292 ThrottleTimeInterval

Value of the time interval in which the rate throttle is applied.

Type: [int](#)

Used in groups: [ThrottleParamsGrp](#)

### 180.2.5293 ThrottleTimeUnit

Units in which ThrottleTimeInterval is expressed. Uses same enumerations as OrderDelayUnit(1429).

Type: [int](#)

Allowed values in OrderDelayUnitCodeSet:

Code	Name	Description
0	Seconds	Seconds (default if not specified)
1	TenthsOfASecond	Tenths of a second
2	HundredthsOfASecond	Hundredths of a second
3	Milliseconds	milliseconds
4	Microseconds	microseconds
5	Nanoseconds	nanoseconds
10	Minutes	minutes
11	Hours	hours
12	Days	days
13	Weeks	weeks
14	Months	months
15	Years	years

Used in groups: [ThrottleParamsGrp](#)

**180.2.5294 ThrottleType**

Type of throttle.

Type: **int**

Allowed values in ThrottleTypeCodeSet:

Code	Name	Description
0	InboundRate	Inbound Rate
1	OutstandingRequests	Outstanding Requests

Used in groups: **ThrottleParamsGrp**

**180.2.5295 TickDirection**

Direction of the "tick".

Type: **char**

Allowed values in TickDirectionCodeSet:

Code	Name	Description
0	PlusTick	Plus Tick
1	ZeroPlusTick	Zero-Plus Tick
2	MinusTick	Minus Tick
3	ZeroMinusTick	Zero-Minus Tick

Used in groups: **MDFullGrp**, **MDIncGrp**

**180.2.5296 TickIncrement**

Tick increment for stated price range. Specifies the valid price increments at which a security can be quoted and traded

Type: **Price**

Used in groups: **TickRules**

**180.2.5297 TickRuleProductComplex**

Identifies an entire suite of products for which the price tick rule applies.

Type: **String**

Used in groups: **TickRules**

**180.2.5298 TickRules**

The TickRules component specifies the rules for determining how a security ticks, i.e. the price increments which it can be quoted, traded, and for certain cases settled, depending on the current price of the security.

Name	Mult.	Type	Description
NoTickRules	[1..1]	NumInGroup	
StartTickPriceRange	[0..1]	Price	Required if NoTickRules(1205) > 0.
EndTickPriceRange	[0..1]	Price	
TickIncrement	[0..1]	Price	
TickRuleType	[0..1]	CodeSet	
TickRuleProductComplex	[0..1]	String	Can be used to limit tick rule to specific product suite.
SettlPriceIncrement	[0..1]	Price	
SettlPriceSecondaryIncrement	[0..1]	Price	

Used in components: **BaseTradingRules**

**180.2.5299 TickRuleType**

Specifies the type of tick rule which is being described

Type: **int**

Allowed values in TickRuleTypeCodeSet:

Code	Name	Description
0	RegularTrading	Regular trading
1	VariableCabinet	Variable cabinet

Code	Name	Description
2	FixedCabinet	Fixed cabinet
3	TradedAsASpreadLeg	Traded as a spread leg
4	SettledAsASpreadLeg	Settled as a spread leg
5	TradedAsSpread	Traded as spread. Basis points spread

Used in groups: [TickRules](#)

### **180.2.5300 TierCode**

The Tier the trade was matched by the clearing system.

Type: [String](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### **180.2.5301 TimeBracket**

A code that represents a time interval in which a fill or trade occurred.

Required for US futures markets.

Type: [String](#)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [ExecutionReport](#), [TradeCaptureReportRequest](#)

### **180.2.5302 TimeInForce**

Specifies how long the order remains in effect. Absence of this field is interpreted as DAY. NOTE not applicable to CIV Orders.

Type: [char](#)

Allowed values in TimeInForceCodeSet:

Code	Name	Description
0	Day	Day (or session). A buy or sell order that, if not executed expires at the end of the trading day on which it was entered.

Code	Name	Description
1	GoodTillCancel	Good Till Cancel (GTC). An order to buy or sell that remains in effect until it is either executed or canceled; sometimes called an "open order".
2	AtTheOpening	At the Opening (OPG). A market or limit-price order to be executed at the opening of the stock or not at all; all or part of any order not executed at the opening is treated as canceled.
3	ImmediateOrCancel	Immediate Or Cancel (IOC). A market or limit-price order that is to be executed in whole or in part as soon as it is available in the market; any portion not so executed is to be canceled.
4	FillOrKill	Fill Or Kill (FOK). A market or limit-price order that is to be executed in its entirety as soon as it is available in the market; if not so executed, the order is to be canceled.
5	GoodTillCrossing	Good Till Crossing (GTX). An order to buy or sell that is canceled prior to the market entering into an auction or crossing phase.
6	GoodTillDate	Good Till Date (GTD). An order to buy or sell that remains in effect until it expires, defined by ExpireDate(432) or ExpireTime(126).
7	AtTheClose	At the Close. Indicated price is to be around the closing price, however, not held to the closing price.
8	GoodThroughCrossing	Good Through Crossing. An order that is valid up till and including a crossing phase.]
9	AtCrossing	At Crossing. An order that is valid only during crossing (auction) phases. The order is valid during the day or up to and including a specified trading (sub) session.
A	GoodForTime	Good for Time (GFT). An order that is valid for a pre-defined time period expressed with ExposureDuration(1629) and (optionally) ExposureDurationUnit(1916).
B	GoodForAuction	Good for Auction (GFA). An order that is valid for an auction initiated by a trading firm (see AuctionType(1803) for examples.
C	GoodForMonth	Good for this Month (GFM). An order that is valid until the end of the current month, i.e. from the time of order submission until the end of the last trading day of the current month.

Used in components: [MDStatisticParameters](#), [TradeReportOrderDetail](#)

Used in groups: [ListOrdGrp](#), [MDFullGrp](#), [MDIncGrp](#), [OrderEntryAckGrp](#), [OrderEntryGrp](#), [TimeIn-ForceRules](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

**180.2.5303 TimeInForceRules**

Name	Mult.	Type	Description
NoTimeInForceRules	[1..1]	NumInGroup	Number of time in force techniques
TimeInForce	[0..1]	CodeSet	Indicates time in force techniques that are valid for the specified market segment

Used in components: [TradingSessionRules](#)

Used in messages: [MarketDefinition](#), [MarketDefinitionUpdateReport](#)

**180.2.5304 TimeToExpiration**

Time to expiration in years calculated as the number of days remaining to expiration divided by 365 days per year.

Type: [float](#)

Used in messages: [ExecutionReport](#), [TradeCaptureReport](#)

**180.2.5305 TimeUnit**

Unit of time associated with the contract.

NOTE: Additional values may be used by mutual agreement of the counterparties.

Type: [String](#)

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter



Code	Name	Description
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in components: **Instrument**

#### **180.2.5306 TotalAccruedInterestAmt**

Total Amount of Accrued Interest for convertible bonds and fixed income

Type: **Amt**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**

#### **180.2.5307 TotalAffectedOrders**

Total number of orders affected by either the OrderMassActionRequest(MsgType=CA) or OrderMassCancelRequest(MsgType=Q).

Type: **int**

Used in messages: **OrderMassActionReport**, **OrderMassCancelReport**

#### **180.2.5308 TotalBidSize**

Specifies the total bid size.

Type: **Qty**

Used in groups: **QuotEntryGrp**

Used in messages: **Quote**, **QuoteStatusReport**

#### **180.2.5309 TotalGrossTradeAmt**

Expresses the full total monetary value of the traded contract. The value is the product of LastPx(31) and TotalTradeQty(2367) or TotalTradeMultipliedQty(2370), if priced in units instead of contracts.

Type: **Amt**

Used in messages: **TradeCaptureReport**

**180.2.5310 TotalIssuedAmount**

Specifies the total amount of the issue. Corresponds to the par value multiplied by the number of issued securities.

Type: **Amt**

Used in components: **Instrument**

**180.2.5311 TotalNetValue**

TotalNetValue is determined as follows:

At the initial collateral assignment TotalNetValue is the sum of  $(\text{UnderlyingStartValue} * (1 - \text{haircut}))$ .

In a collateral substitution TotalNetValue is the sum of  $(\text{UnderlyingCurrentValue} * (1 - \text{haircut}))$ .

For listed derivatives clearing margin management, this is the collateral value which equals  $(\text{Market value} * \text{haircut})$

Type: **Amt**

Used in messages: **AccountSummaryReport**, **CollateralAssignment**, **CollateralInquiry**, **CollateralReport**, **CollateralRequest**, **CollateralResponse**

**180.2.5312 TotalNotAffectedOrders**

Total number of orders unaffected by either the OrderMassActionRequest(35=CA) or OrderMassCancel-Request(35=Q).

Type: **int**

Used in messages: **OrderMassActionReport**

**180.2.5313 TotalNumPosReports**

Total number of Position Reports being returned.

Type: **int**

Used in messages: **PositionReport**, **RequestForPositionsAck**

**180.2.5314 TotalOfferSize**

Specifies the total offer size.

Type: Qty

Used in groups: QuotEntryGrp

Used in messages: Quote, QuoteStatusReport

**180.2.5315 TotalTakedown**

The price at which the securities are distributed to the different members of an underwriting group for the primary market in Municipals, total gross underwriter's spread.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: Amt

Used in groups: TrdCapRptAckSideGrp, TrdCapRptSideGrp

Used in messages: AllocationInstruction, AllocationInstructionAlert, AllocationReport, Confirmation, ExecutionReport

**180.2.5316 TotalTradeMultipliedQty**

Expresses the total trade quantity in units where ContractMultiplier(231) is not 1. The value is the product of TotalTradeQty(2367) and ContractMultiplier(231).

Type: Qty

Used in messages: TradeCaptureReport

**180.2.5317 TotalTradeQty**

Expresses the total quantity traded over the life of the contract when LastQty(32) is repeated periodically over the term of the contract. The value is the product of LastQty(32) and TradingUnitPeriodMultiplier(2353).

Type: Qty

Used in messages: TradeCaptureReport

**180.2.5318 TotalTradingBusinessDays**

Number of trading business days over the lifetime of an instrument.

Type: **int**

Used in groups: **ClearingPriceParametersGrp**

**180.2.5319 TotalVolumeTraded**

Total volume (quantity) traded.

Type: **Qty**

Used in groups: **TrdSessLstGrp**

Used in messages: **TradingSessionStatus**

**180.2.5320 TotNoAccQuotes**

Specifies the number of accepted quotes

Type: **int**

Used in groups: **QuotSetAckGrp**

**180.2.5321 TotNoAllocs**

Total number of NoAlloc entries across all messages. Should be the sum of all NoAllocs in each message that has repeating NoAlloc entries related to the same AllocID or AllocReportID. Used to support fragmentation.

Type: **int**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**

**180.2.5322 TotNoCxlQuotes**

Specifies the number of canceled quotes

Type: **int**

Used in groups: **QuotSetAckGrp**

#### **180.2.5323 TotNoEntitlementReports**

Total number of reports related to party entitlement information.

Type: **int**

Used in messages: **MarketDataReport**

#### **180.2.5324 TotNoFills**

Total number of fill entries across all messages. Should be the sum of all NoFills(1362) in each message that has repeating list of fill entries related to the same ExecID(17). Used to support fragmentation.

Type: **int**

Used in messages: **ExecutionReport**

#### **180.2.5325 TotNoInstrumentReports**

Total number of reports related to instruments.

Type: **int**

Used in messages: **MarketDataReport**

#### **180.2.5326 TotNoMarketSegmentReports**

Total number of reports related to market segments.

Type: **int**

Used in messages: **MarketDataReport**

#### **180.2.5327 TotNoOrderEntries**

Totals number of orders for a mass order or its acknowledgment being fragmented across multiple messages.

Type: **int**

Used in messages: **MassOrder, MassOrderAck**

**180.2.5328 TotNoOrders**

Total number of list order entries across all messages. Should be the sum of all NoOrders (73) in each message that has repeating list order entries related to the same ListID (66). Used to support fragmentation.

(Prior to FIX 4.2 this field was named "ListNoOrds")

Type: **int**

Used in messages: **ListStatus**, **NewOrderList**

**180.2.5329 TotNoParties**

Total number of PartyListGrp returned.

Type: **int**

Used in messages: **PartyDetailsListReport**, **PartyDetailsListUpdateReport**, **PartyEntitlementsReport**, **PartyEntitlementsUpdateReport**, **PartyRiskLimitsReport**, **PartyRiskLimitsUpdateReport**

**180.2.5330 TotNoPartyDetailReports**

Total number of reports related to party detail information.

Type: **int**

Used in messages: **MarketDataReport**

**180.2.5331 TotNoQuoteEntries**

Total number of quotes for the quote set.

Type: **int**

Used in groups: **QuotSetAckGrp**, **QuotSetGrp**

**180.2.5332 TotNoRejQuotes**

Specifies the number of rejected quotes

Type: **int**

Used in groups: **QuotSetAckGrp**

#### **180.2.5333 TotNoRelatedSym**

Total number of securities.

(Prior to FIX 4.4 this field was named TotalNumSecurities)

Type: **int**

Used in messages: **BidRequest**, **DerivativeSecurityList**, **DerivativeSecurityListUpdateReport**, **SecurityList**, **SecurityListUpdateReport**

#### **180.2.5334 TotNoRiskLimitReports**

Total number of reports related to party risk limit information.

Type: **int**

Used in messages: **MarketDataReport**

#### **180.2.5335 TotNoSecurityTypes**

Used to support fragmentation. Indicates total number of security types when multiple Security Type messages are used to return results.

Type: **int**

Used in messages: **SecurityTypes**

#### **180.2.5336 TotNoStrikes**

Total number of strike price entries across all messages. Should be the sum of all NoStrikes (428) in each message that has repeating strike price entries related to the same ListID (66). Used to support fragmentation.

Type: **int**

Used in messages: **ListStrikePrice**

#### **180.2.5337 TotNumAssignmentReports**

Total Number of Assignment Reports being returned to a firm

Type: **int**

Used in messages: **AssignmentReport**

**180.2.5338 TotNumCollateralRequests**

Total number of request messages within a set or group of requests.

Type: **int**

Used in messages: **CollateralAssignment**, **CollateralResponse**

**180.2.5339 TotNumReports**

Total number of reports returned in response to a request.

Type: **int**

Used in messages: **CollateralInquiryAck**, **CollateralReport**, **ExecutionReport**, **MarginRequirementInquiryAck**, **MarginRequirementReport**, **MarketDataReport**, **MarketDataSnapshotFullRefresh**, **PositionReport**, **RequestForPositionsAck**

**180.2.5340 TotNumTradeReports**

Total number of trade reports returned.

Type: **int**

Used in messages: **TradeCaptureReport**, **TradeCaptureReportRequestAck**

**180.2.5341 TradeAggregationRejectReason**

Reason for trade aggregation request being rejected.

Type: **int**

Allowed values in TradeAggregationRejectReasonCodeSet:

Code	Name	Description
0	UnknownOrders	Unknown order(s)
1	UnknownExecutionFills	Unknown execution/fill(s)
99	Other	Other

Used in messages: **TradeAggregationReport**



**180.2.5342 TradeAggregationReportID**

Unique identifier for the TradeAggregationReport(35=DX).

Type: **String**

Used in messages: **TradeAggregationReport**

**180.2.5343 TradeAggregationRequestID**

The message identifier for the trade aggregation request.

Type: **String**

Used in messages: **TradeAggregationReport**, **TradeAggregationRequest**

**180.2.5344 TradeAggregationRequestRefID**

Reference identifier to a previously sent trade aggregation message being cancelled or replaced.

Type: **String**

Used in messages: **TradeAggregationRequest**

**180.2.5345 TradeAggregationRequestStatus**

Status of the trade aggregation request.

Type: **int**

Allowed values in TradeAggregationRequestStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	Rejected	Rejected

Used in messages: **TradeAggregationReport**

**180.2.5346 TradeAggregationTransType**

Identifies the trade aggregation transaction type.

Type: **int**

Allowed values in TradeAggregationTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Cancel	Cancel
2	Replace	Replace

Used in messages: **TradeAggregationRequest**

**180.2.5347 TradeAllocAmt**

The amount associated with a trade allocation.

Type: **Amt**

Used in groups: **TradeAllocAmtGrp**

**180.2.5348 TradeAllocAmtGrp**

The TradeAllocAmtGrp component is used to communicate the monetary amounts associated with allocated positions. This is the per-allocation portion of the per-trade amount specified in Position-AmountData component.

Name	Mult.	Type	Description
<b>NoTradeAllocAmts</b>	[1..1]	NumInGroup	
<b>TradeAllocAmtType</b>	[0..1]	CodeSet	Required if NoTradeAllocAmts(1844) > 0.
<b>TradeAllocAmt</b>	[0..1]	Amt	Required if NoTradeAllocAmts(1844) > 0.
<b>TradeAllocCurrency</b>	[0..1]	Currency	
<b>TradeAllocCurrencyCodeSource</b>	[0..1]	CodeSet	
<b>TradeAllocAmtReason</b>	[0..1]	CodeSet	

Used in groups: **AllocGrp**, **TrdAllocGrp**

**180.2.5349 TradeAllocAmtReason**

Specifies the reason for an amount type when reported on an allocation. Useful when multiple instances of the same amount type are reported.

Type: **int**

Allowed values in PosAmtReasonCodeSet:

Code	Name	Description
0	OptionsSettlement	Options settlement
1	PendingErosionAdjustment	Pending erosion adjustment
2	FinalErosionAdjustment	Final erosion adjustment
3	TearUpCouponAmount	Tear-up coupon amount
4	PriceAlignmentInterest	Price alignment interest. To minimize the impact of daily cash variation margin payments on the pricing of interest rate swaps, the Clearing House will charge interest on cumulative variation margin received and pay interest on cumulative variation margin paid in respect of these instruments. This interest element is known as price alignment interest.
5	DeliveryInvoiceCharges	Delivery invoice charges
6	DeliveryStorageCharges	Delivery storage charges

Used in groups: **TradeAllocAmtGrp**

**180.2.5350 TradeAllocAmtType**

Type of the amount associated with a trade allocation.

Type: **String**

Allowed values in PosAmtTypeCodeSet:

Code	Name	Description
CASH	CashAmount	Cash amount (corporate event)
CRES	CashResidualAmount	Cash residual amount
FMTM	FinalMarkToMarketAmount	Final mark-to-market amount
IMTM	IncrementalMarkToMarketAmount	Incremental mark-to-market
PREM	PremiumAmount	Premium amount

Code	Name	Description
SMTM	StartOfDayMarkToMarketAmount	Start of day mark-to-market
TVAR	TradeVariationAmount	Trade variation amount
VADJ	ValueAdjustedAmount	Value adjusted amount
SETL	SettlementValue	Settlement value
ICPN	InitialTradeCouponAmount	Initial trade coupon amount
ACPN	AccruedCouponAmount	Accrued coupon amount
CPN	CouponAmount	Coupon amount
IACPN	IncrementalAccruedCoupon	Incremental accrued coupon
CMTM	CollateralizedMarkToMarket	Collateralized mark-to-market
ICMTM	IncrementalCollateralizedMark-ToMarket	Incremental collateralized mark-to-market
DLV	CompensationAmount	Compensation amount
BANK	TotalBankedAmount	Total banked amount
COLAT	TotalCollateralizedAmount	Total collateralized amount
LSNV	LongPairedSwapNotionalValue	Long paired swap or swaption notional value
SSNV	ShortPairedSwapNotionalValue	Short paired swap or swaption notional value
SACPN	StartOfDayAccruedCoupon	Start-of-day accrued coupon
NPV	NetPresentValue	Net present value
SNPV	StartOfDayNetPresentValue	Start-of-day net present value
NCF	NetCashFlow	Net cash flow
PVFEEs	PresentValueOfFees	Present value of all fees
PV01	PresentValueOneBasisPoints	Present value of one basis points. Change in value if yield curve shifts 0.01%.
5YREN	FiveYearEquivalentNotional	The five year equivalent notional amount
UMTM	UndiscountedMarkToMarket	Undiscounted mark-to-market
MTD	MarkToModel	Mark-to-model
VMTM	MarkToMarketVariance	Mark-to-market variance
VMTD	MarkToModelVariance	Mark-to-model variance
UPFRNT	UpfrontPayment	Upfront payment
ENDV	EndVale	End value. Principal amount of a securities financing transaction on maturity date.
MGNLN	OutstandingMarginLoan	Outstanding margin loan. The amount of the outstanding margin loan. In the event that the loan has a short market value, PosAmt(708) would be a negative value.
LNVL	LoanValue	Loan value. The amount of the loan.

Used in groups: **TradeAllocAmtGrp**

#### **180.2.5351 TradeAllocCurrency**

Currency denomination of the trade allocation amount.

Type: **Currency**

Used in groups: **TradeAllocAmtGrp**

#### **180.2.5352 TradeAllocCurrencyCodeSource**

Identifies class or source of the TradeAllocCurrency(1847) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **TradeAllocAmtGrp**

#### **180.2.5353 TradeAllocGroupInstruction**

Instruction on how to add a trade to an allocation group when it is being given-up.

Type: **int**

Allowed values in TradeAllocGroupInstructionCodeSet:

Code	Name	Description
0	Add	Add to an existing allocation group if one exists.
1	DoNotAdd	Do not add the trade to an allocation group.

Used in groups: [TrdCapRptSideGrp](#)

### 180.2.5354 TradeAllocIndicator

Identifies if, and how, the trade is to be allocated or split.

Type: [int](#)

Allowed values in TradeAllocIndicatorCodeSet:

Code	Name	Description
0	AllocationNotRequired	Allocation not required
1	AllocationRequired	Allocation required (give-up trade) allocation information not provided (incomplete)
2	UseAllocationProvidedWithTheTrade	Use allocation provided with the trade
3	AllocationGiveUpExecutor	Allocation give-up executor
4	AllocationFromExecutor	Allocation from executor
5	AllocationToClaimAccount	Allocation to claim account
6	TradeSplit	Trade split

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

### 180.2.5355 TradeAllocStatus

Identifies the status of an allocation when using a pre-clear workflow.

Type: [int](#)

Allowed values in TradeAllocStatusCodeSet:

Code	Name	Description
0	PendingClear	Pending clear
1	Claimed	Claimed

Code	Name	Description
2	Cleared	Cleared
3	Rejected	Rejected

Used in groups: **TrdAllocGrp**

### 180.2.5356 TradeCapLegUnderlyingsGrp

Name	Mult.	Type	Description
NoOfLegUnderlyings	[1..1]	NumInGroup	Number of legs for the underlying instrument
UnderlyingLegInstrument	[0..1]	Component	

Used in groups: **TrdInstrmtLegGrp**

### 180.2.5357 TradeClearingInstruction

Specifies the eligibility of this trade for clearing and central counterparty processing.

Type: **int**

Allowed values in ClearingInstructionCodeSet:

Code	Name	Description
0	ProcessNormally	Process normally
1	ExcludeFromAllNetting	Exclude from all netting
2	BilateralNettingOnly	Bilateral netting only
3	ExClearing	Ex clearing
4	SpecialTrade	Special trade
5	MultilateralNetting	Multilateral netting
6	ClearAgainstCentralCounterparty	Clear against central counterparty
7	ExcludeFromCentralCounterparty	Exclude from central counterparty
8	ManualMode	Manual mode (pre-posting and/or pre-giveup)
9	AutomaticPostingMode	Automatic posting mode (trade posting to the position account number specified)

Code	Name	Description
10	AutomaticGiveUpMode	Automatic give-up mode (trade give-up to the give-up destination number specified)
11	QualifiedServiceRepresentativeQSR	Qualified Service Representative QSR
12	CustomerTrade	Customer trade
13	SelfClearing	Self clearing
14	BuyIn	Buy-in

Used in messages: [TradeCaptureReport](#)

### 180.2.5358 TradeCollateralization

Specifies how the trade is collateralized.

Type: [int](#)

Allowed values in TradeCollateralizationCodeSet:

Code	Name	Description
0	Uncollateralized	Uncollateralized
1	PartiallyCollateralized	Partially collateralized
2	OneWayCollaterallization	One-way collaterallization
3	FullyCollateralized	Fully collateralized
4	NetExposure	Net exposure. Indication of whether the collateral has been provided for a net exposure, rather than for a single transaction.

Used in messages: [CollateralReport](#), [PositionReport](#), [TradeCaptureReport](#)

### 180.2.5359 TradeCondition

Type of market data entry.

Type: [MultipleStringValue](#)

Allowed values in TradeConditionCodeSet:



Code	Name	Description
A	Cash	Cash (only) Market
B	AveragePriceTrade	Average Price Trade
C	CashTrade	Cash Trade (same day clearing)
D	NextDay	Next Day (only)Market
E	Opening	Opening/Reopening Trade Detail
F	IntradayTradeDetail	Intraday Trade Detail
G	Rule127Trade	Rule 127 Trade (NYSE)
H	Rule155Trade	Rule 155 Trade (AMEX)
I	SoldLast	Sold Last (late reporting)
J	NextDayTrade	Next Day Trade (next day clearing)
K	Opened	Opened (late report of opened trade)
L	Seller	Seller
M	Sold	Sold (out of sequence)
N	StoppedStock	Stopped Stock (guarantee of price but does not execute the order)
P	ImbalanceMoreBuyers	Imbalance More Buyers (cannot be used in combination with Q)
Q	ImbalanceMoreSellers	Imbalance More Sellers (cannot be used in combination with P)
R	OpeningPrice	Opening Price
S	BargainCondition	Bargain Condition (LSE)
T	ConvertedPriceIndicator	Converted Price Indicator
U	ExchangeLast	Exchange Last
V	FinalPriceOfSession	Final Price of Session
W	ExPit	Ex-pit
X	Crossed	Crossed
Y	TradesResultingFromManual	Trades resulting from manual/slow quote
Z	TradesResultingFromIntermarketSweep	Trades resulting from intermarket sweep
a	VolumeOnly	Volume Only
b	DirectPlus	Direct Plus
c	Acquisition	Acquisition
d	Bunched	Bunched
e	Distribution	Distribution
f	BunchedSale	Bunched Sale
g	SplitTrade	Split Trade
h	CancelStopped	Cancel Stopped

Code	Name	Description
i	CancelETH	Cancel ETH
j	CancelStoppedETH	Cancel Stopped ETH
k	OutOfSequenceETH	Out of Sequence ETH
l	CancelLastETH	Cancel Last ETH
m	SoldLastSaleETH	Sold Last Sale ETH
n	CancelLast	Cancel Last
o	SoldLastSale	Sold Last Sale
p	CancelOpen	Cancel Open
q	CancelOpenETH	Cancel Open ETH
r	OpenedSaleETH	Opened Sale ETH
s	CancelOnly	Cancel Only
t	CancelOnlyETH	Cancel Only ETH
u	LateOpenETH	Late Open ETH
v	AutoExecutionETH	Auto Execution ETH
w	Reopen	Reopen
x	ReopenETH	Reopen ETH
y	Adjusted	Adjusted
z	AdjustedETH	Adjusted ETH
AA	Spread	Spread
AB	SpreadETH	Spread ETH
AC	Straddle	Straddle
AD	StraddleETH	Straddle ETH
AE	Stopped	Stopped
AF	StoppedETH	Stopped ETH
AG	RegularETH	Regular ETH
AH	Combo	Combo
AI	ComboETH	Combo ETH
AJ	OfficialClosingPrice	Official Closing Price
AK	PriorReferencePrice	Prior Reference Price
AL	StoppedSoldLast	Stopped Sold Last
AM	StoppedOutOfSequence	Stopped Out of Sequence
AN	OfficialClosingPriceDup	Official Closing Price (duplicate enumeration - use 'AJ' instead)
AO	CrossedOld	Crossed (duplicate enumeration - use 'X' instead)
AP	FastMarket	Fast Market

Code	Name	Description
AQ	AutomaticExecution	Automatic Execution
AR	FormT	Form T
AS	BasketIndex	Basket Index
AT	BurstBasket	Burst Basket
AU	TradeThroughExempt	Trade through exempt. Trade ignored prices on away markets.
AV	QuoteSpread	Quote spread
AW	LastAuctionPrice	Last auction price. Trade represents outcome of last auction
AX	HighPrice	High price. Trade establishes new high price for the session
AY	LowPrice	Low price. Trade establishes new low price for the session
AZ	SystematicInternaliser	Systematic Internaliser (SI). Trade conducted by Systematic Internaliser (SI).
BA	AwayMarket	Away market. Trade conducted on away market
BB	MidpointPrice	Mid-point price. Trade represents current midpoint price
BC	TradedBeforeIssueDate	Traded before issue date. Trade conducted during subscription phase of new issue
BD	PreviousClosingPrice	Previous closing price. Trade represents closing price of previous business day
BE	NationalBestBidOffer	National Best Bid and Offer. Trade price within National Best Bid and Offer (NBBO)
0	Cancel	Cancel
1	ImpliedTrade	Implied Trade
2	MarketplaceEnteredTrade	Marketplace entered trade
3	MultiAssetClassMultilegTrade	Multi-asset class multileg trade
4	MultilegToMultilegTrade	Multileg-to-Multileg Trade
5	ShortSaleMinPrice	Short Sale Minimum Price
6	Benchmark	Benchmark. Market Model Typology (MMT) terminology: The "benchmark" price depends on a benchmark which has no current price but derived from a time series such as a VWAP.

Used in components: **MDStatisticParameters**

Used in groups: **MDFullGrp**, **MDIncGrp**

### 180.2.5360 TradeConfirmationReferenceID

A reference or control identifier or number used as a trade confirmation key.

Type: **String**

Used in messages: **Confirmation**, **ConfirmationAck**

### 180.2.5361 TradeContingency

Indicates the contingency attribute for a trade in an asset class that may be contingent on the clearing of a corresponding paired trade (for example Exchange for Physical (EFP), Exchange for Swap (EFS), Exchange for Related (EFR) or Exchange for Option (EFO), collectively called EFRPs). Once the paired trade clears or fails to clear, the related trade (the trade which carries this attribute) ceases to exist.

Type: **int**

Allowed values in TradeContingencyCodeSet:

Code	Name	Description
0	DoesNotApply	Does not apply (default if not specified). The trade is for an asset class that is not traded with contingency.
1	ContingentTrade	Contingent trade. The trade is terminated as soon as its paired trade is cleared or denied clearing.
2	NonContingentTrade	Non-contingent trade. Identifies a trade that is not contingent but is for an asset class that may be contingent.

Used in messages: **TradeCaptureReport**

### 180.2.5362 TradeContinuation

Specifies the post-execution trade continuation or lifecycle event. Additional values may be used by mutual agreement of the counterparties.

Type: **int**

Allowed values in TradeContinuationCodeSet:

Code	Name	Description
0	Novation	Novation
1	PartialNovation	Partial novation
2	TradeUnwind	Trade unwind. "Trade" includes "Swaps".
3	PartialTradeUnwind	Partial trade unwind. "Trade" includes "Swaps".

Code	Name	Description
4	Exercise	Exercise
5	Netting	Compression/Netting. Compression (used for OTC derivative trades) and Netting (used for Futures trades) are essentially the same business process, i.e. rolling up closely related contracts into a single trade or position.
6	FullNetting	Full netting
7	PartialNetting	Partial netting
8	Amendment	Amendment. Based on mutual agreement between the counterparties, used to change the original or previously amended contract terms reported to a trade repository.
9	Increase	Increase
10	CreditEvent	Credit event
11	StrategicRestructuring	Strategic restructuring
12	SuccessionEventReorganization	Succession event reorganization
13	SuccessionEventRenaming	Succession event renaming
14	Porting	Porting
15	Withdrawal	Withdrawal. One party withdrew from the trade prior to confirmation or clearing. Can be used with TradeReportTransType(487)=1 (Cancel).
16	Void	Void. Trade is to be ended after clearing. Can be used with TradeReportTransType(487)=1 (Cancel).
17	AccountTransfer	Account transfer
18	GiveUp	Give up
19	TakeUp	TakeUp
20	AveragePricing	Average pricing
21	Reversal	Reversal
22	AllocTrdPosting	Allocation/Trade posting
23	Cascade	Cascade. The breakdown of a contract position to a more granular level, e.g. from a yearly position to monthly positions.
24	Delivery	Delivery
25	OptionAsgn	Option assignment
26	Expiration	Expiration
27	Maturity	Maturity
28	EqualPosAdj	Equal position adjustment
29	UnequalPosAdj	Unequal position adjustment. An adjustment to either the long or short position quantity but not both.

Code	Name	Description
30	Correction	Correction. Used to correct an error in the contract terms of a previously submitted report to a trade repository.
31	EarlyTermination	Early termination. The transaction/contract has closed before its natural end (maturity date or end date).
32	Rerate	Rerate. Change in the repo rate of an open repo contract due to shift in the market conditions.
99	Other	Other price-forming continuation data. Other price-forming continuation data or lifecycle event. Include description of type in TradeContinuationText(2374).

Used in groups: [QuotReqGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationReport](#), [Confirmation](#), [ExecutionReport](#), [Position-Report](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [TradeCaptureReport](#)

#### 180.2.5363 TradeContinuationText

Free form text to specify additional trade continuation information or data.

Type: [String](#)

Used in groups: [QuotReqGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationReport](#), [Confirmation](#), [ExecutionReport](#), [Position-Report](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [TradeCaptureReport](#)

#### 180.2.5364 TradeDate

Indicates date of trading day. Absence of this field indicates current day (expressed in local time at place of trade).

Type: [LocalMktDate](#)

Used in components: [SettlTradeDetails](#)

Used in groups: [ListOrdGrp](#), [SideCrossOrdCxlGrp](#), [SideCrossOrdModGrp](#), [TrdCapDtGrp](#)

Used in messages: [Advertisement](#), [AllocationInstruction](#), [AllocationInstructionAck](#), [AllocationInstructionAlert](#), [AllocationInstructionAlertRequest](#), [AllocationReport](#), [AllocationReportAck](#), [BidRequest](#), [CollateralAssignment](#), [CollateralReport](#), [CollateralResponse](#), [Confirmation](#), [ConfirmationAck](#), [ExecutionReport](#), [ListCancelRequest](#), [MarketDataIncrementalRefresh](#), [MarketDataSnapshotFullRefresh](#), [MarketDataStatisticsReport](#), [MarketDataStatisticsRequest](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#),

NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, PositionTransferInstruction, PositionTransferReport, SecurityMassStatus, SecurityStatus, TradeCaptureReport, TradeCaptureReportAck, TradeMatchReport, TradingSessionStatus

### 180.2.5365 TradedFlatSwitch

Driver and part of trade in the event that the Security Master file was wrong at the point of entry(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **Boolean**

Allowed values in TradedFlatSwitchCodeSet:

Code	Name	Description
N	NotTradedFlat	Not Traded Flat
Y	TradedFlat	Traded Flat

Used in messages: **ExecutionReport**

### 180.2.5366 TradeHandlingInstr

Specified how the TradeCaptureReport(35=AE) should be handled by the respondent.

Type: **char**

Allowed values in TradeHandlingInstrCodeSet:

Code	Name	Description
0	TradeConfirmation	Trade confirmation
1	TwoPartyReport	Two-party report
2	OnePartyReportForMatching	One-party report for matching
3	OnePartyReportForPassThrough	One-party report for pass through. Can be used when one of the parties to the trade submits a report which then has to be approved or confirmed by the other (counter)party.
4	AutomatedFloorOrderRouting	Automated floor order routing
5	TwoPartyReportForClaim	Two-party report for claim
6	OnePartyReport	One-party report

Code	Name	Description
7	ThirdPtyRptForPassThrough	Third-party report for pass through. Can be used when RootParties component contains a service provider role who submits the trade report and is not necessarily also on one side of the trade.
8	OnePartyReportAutoMatch	One-party report for auto-match. Indicates that the submission is a transfer trade to a firm or account that is part of the same corporate entity and that once validated the transfer should be automatically accepted without confirmation.

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#)

### **180.2.5367 TradeID**

The unique ID assigned to the trade entity once it is received or matched by the exchange or central counterparty.

Type: [String](#)

Used in groups: [ExecAllocGrp](#), [ExecutionAggregationGrp](#), [MDFullGrp](#), [MDIncGrp](#)

Used in messages: [TradeAggregationReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#), [TradeCaptureReportRequestAck](#)

### **180.2.5368 TradeInputDevice**

Specific device number, terminal number or station where trade was entered

Type: [String](#)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

Used in messages: [AllocationReport](#), [TradeCaptureReportRequest](#)

### **180.2.5369 TradeInputSource**

Type of input device or system from which the trade was entered.

Type: [String](#)

Used in components: [MDStatisticParameters](#)

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)



Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [TradeCaptureReportRequest](#)

#### **180.2.5370 TradeLegRefID**

Reference to the leg of a multileg instrument to which this trade refers

Type: [String](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.5371 TradeLinkID**

Used to link a group of trades together.

Type: [String](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#)

#### **180.2.5372 TradeMatchAckStatus**

Used to indicate the status of the trade match report submission.

Type: [int](#)

Allowed values in TradeMatchAckStatusCodeSet:

Code	Name	Description
0	ReceivedNotProcessed	Received, not yet processed
1	Accepted	Accepted
2	Rejected	Rejected

Used in messages: [TradeMatchReportAck](#)

#### **180.2.5373 TradeMatchRejectReason**

Reason the trade match report submission was rejected.

Type: [int](#)

Allowed values in TradeMatchRejectReasonCodeSet:

Code	Name	Description
0	Successful	Successful
1	InvalidPartyInformation	Invalid party information
2	UnknownInstrument	Unknown instrument
3	Unauthorized	Not authorized to report trades
4	InvalidTradeType	Invalid trade type
99	Other	Other

Used in messages: [TradeMatchReportAck](#)

#### **180.2.5374 TradeMatchTimestamp**

Timestamp of the match event. For off-exchange trades the time at which the deal was matched by the exchange.

This timestamp will be the same on all the trades and will not change when a trade is modified.

Type: [UTCTimestamp](#)

Used in messages: [TradeMatchReport](#)

#### **180.2.5375 TradeNumber**

Ordinal number of the trade within a series of related trades.

Type: [int](#)

Used in messages: [TradeCaptureReport](#)

#### **180.2.5376 TradeOriginationDate**

Used with Fixed Income for Municipal New Issue Market. Agreement in principal between counter-parties prior to actual trade date.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCDate)

Type: [LocalMktDate](#)

Used in groups: [ListOrdGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [SideCrossOrdCxlGrp](#), [SideCrossOrdModGrp](#)

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [ExecutionReport](#), [ListCancelRequest](#), [MultilegOrderCancelReplace](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReject](#), [OrderCancelReplaceRequest](#)

### 180.2.5377 TradePositionQty

The TradePositionQty component block specifies, for a single trade side, the various types of position quantity in the position life-cycle including start-of-day, intraday, trade, adjustments, and end-of-day position quantities.

Name	Mult.	Type	Description
<a href="#">NoPositions</a>	[1..1]	NumInGroup	
<a href="#">PosType</a>	[0..1]	CodeSet	Required if NoPositions > 0.
<a href="#">LongQty</a>	[0..1]	Qty	
<a href="#">ShortQty</a>	[0..1]	Qty	
<a href="#">CoveredQty</a>	[0..1]	Qty	
<a href="#">PosQtyStatus</a>	[0..1]	CodeSet	
<a href="#">QuantityDate</a>	[0..1]	LocalMktDate	

Used in groups: [TrdCapRptSideGrp](#)

### 180.2.5378 TradePriceCondition

Price conditions in effect at the time of the trade. Multiple price conditions can be in effect at the same time. Price conditions are usually required to be reported in markets that have regulations on price execution at a market or national best bid or offer, and the trade price differs from the best bid or offer.

Type: [int](#)

Allowed values in TradePriceConditionCodeSet:

Code	Name	Description
0	SpecialCumDividend	Special cum dividend (CD)
1	SpecialCumRights	Special cum rights (CR)
2	SpecialExDividend	Special ex dividend (XD)
3	SpecialExRights	Special ex rights (XR)

Code	Name	Description
4	SpecialCumCoupon	Special cum coupon (CC)
5	SpecialCumCapitalRepayments	Special cum capital repayments (CP)
6	SpecialExCoupon	Special ex coupon (XC)
7	SpecialExCapitalRepayments	Special ex capital repayments (XP)
8	CashSettlement	Cash settlement (CS)
9	SpecialCumBonus	Special cum bonus (CB)
10	SpecialPrice	Special price (SP). Usually net or all-in price.
11	SpecialExBonus	Special ex bonus (XB)
12	GuaranteedDelivery	Guaranteed delivery (GD)
13	SpecialDividend	Special dividend. Deviation from regular ex/cum treatment (without further specification) leading to price modification. To be used only if it is not clear whether it is a special cum or special ex dividend. For ESMA RTS 1, this is the "SDIV" flag.
14	PriceImprovement	Price improvement. The price is better than a reference price. For example, this may be due to an offer by a systematic internaliser to always quote better prices than a public reference price. For ESMA RTS 1, this is the "RPRI" flag.
15	NonPriceFormingTrade	Non-price forming trade. In the context of MiFID II, these are transactions which are exempted from the trading obligation (i.e. permitted to be transacted as an OTC transaction) and are deemed not to be contributing to the price discovery process. However, these transactions are not exempted from post trade transparency reporting and are required to be published by MiFID venues and "approved publication arrangement" (APAs) for market transparency purposes. The price from exempted transactions should be disregarded for the purposes of price discovery. For ESMA RTS 1 and RTS 2, this is the "NPFT" flag.
16	TradeExemptedFromTradingObligation	Trade exempted from trading obligation. Per MiFIR Article 23, these types of trades are not exempted from post-trade transparency if reported to a trading venue under MiFID II and deemed on exchange, however, they are ignored for price formation despite published by venue. For the UK implementation of MiFIR RTS 1, this is the "TNCP" flag.
17	PricePending	Price or strike price is pending. In the context of MiFIR RTS 1, RTS 2, and RTS 22, this is the "PNDG" flag.
18	PriceNotApplicable	Price is not applicable. In the context of MiFIR RTS 1, RTS 2, and RTS 22, this is the "NOAP" flag.

Used in groups: **TradePriceConditionGrp**

**180.2.5379 TradePriceConditionGrp**

Price conditions associated with a trade that impact trade price.

Name	Mult.	Type	Description
NoTradePriceConditions	[1..1]	NumInGroup	
TradePriceCondition	[0..1]	CodeSet	Required if NoTradePriceConditions(1838) > 0.

Used in groups: ExecAllocGrp, MDFullGrp, MDIncGrp

Used in messages: ExecutionReport, TradeCaptureReport

**180.2.5380 TradePriceNegotiationMethod**

Method used for negotiation of contract price.

Type: int

Allowed values in TradePriceNegotiationMethodCodeSet:

Code	Name	Description
0	PercentPar	Percent of par
1	DealSpread	Deal spread
2	UpfrontPnts	Upfront points
3	UpfrontAmt	Upfront amount
4	ParUpfrontAmt	Percent of par and upfront amount
5	SpreadUpfrontAmt	Deal spread and upfront amount
6	UpfrontPntsAmt	Upfront points and upfront amount

Used in messages: ExecutionReport, NewOrderMultileg, NewOrderSingle, TradeCaptureReport

**180.2.5381 TradePublishIndicator**

Indicates if a trade should be or has been published via a market publication service. The indicator governs all publication services of the recipient. Replaces PublishTrdIndicator(852).

Type: int

Allowed values in TradePublishIndicatorCodeSet:

Code	Name	Description
0	DoNotPublishTrade	Do Not Publish Trade
1	PublishTrade	Publish Trade
2	DeferredPublication	Deferred Publication
3	Published	Published. Indicates that the transaction has been published to the market.

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: **AllocationInstruction**, **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **TradeCaptureReport**, **TradeCaptureReportAck**

### **180.2.5382 TradeQty**

Trade quantity.

Type: **Qty**

Used in groups: **TradeQtyGrp**

### **180.2.5383 TradeQtyGrp**

Quantities of the trade that have been processed and the type of processing that has occurred for that trade quantity.

Name	Mult.	Type	Description
<b>NoTradeQty</b>	[1..1]	NumInGroup	
<b>TradeQtyType</b>	[0..1]	CodeSet	Required if NoTradeQty(1841) > 0.
<b>TradeQty</b>	[0..1]	Qty	Required if NoTradeQty(1841) > 0.

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**

### **180.2.5384 TradeQtyType**

Indicates the type of trade quantity in TradeQty(1843).

Type: **int**

Allowed values in TradeQtyTypeCodeSet:

Code	Name	Description
0	ClearedQuantity	Cleared quantity
1	LongSideClaimedQuantity	Long side claimed quantity
2	ShortSideClaimedQuantity	Short side claimed quantity
3	LongSideRejectedQuantity	Long side rejected quantity
4	ShortSideRejectedQuantity	Short side rejected quantity
5	PendingQuantity	Pending quantity
6	TransactionQuantity	Transaction quantity
7	RemainingQuantity	Remaining trade quantity. Used to indicate the remaining quantity of a trade after a give-up or posting action.
8	PreviousRemainingQuantity	Previous remaining trade quantity. Used to indicate the remaining quantity of a trade prior to a give-up or posting action.

Used in groups: **TradeQtyGrp**

#### **180.2.5385 TradeReportID**

Unique identifier of trade capture report

Type: **String**

Used in groups: **TrdCollGrp**

Used in messages: **TradeCaptureReport, TradeCaptureReportAck, TradeCaptureReportRequest**

#### **180.2.5386 TradeReportingIndicator**

Used between parties to convey trade reporting status.

Type: **int**

Allowed values in TradeReportingIndicatorCodeSet:

Code	Name	Description
0	NotReported	Trade has not (yet) been reported. Depending on the regulatory regime the trade is reportable and the recipient may be responsible for reporting.
1	OnBook	Trade has been or will be reported by a trading venue as an "on-book" trade
2	SISeller	Trade has or will be reported as a seller trade by the authorised reporter
3	SIBuyer	Trade has or will be reported as a buyer trade by the authorised reporter
4	NonSISeller	Trade has or will be reported as a seller trade by an entity other than the authorised reporter
5	SubDelegationByFirm	Trade has been or will be reported under a sub-delegation arrangement by an investment firm to a reporting facility (e.g. APA) on behalf of another investment firm
6	Reportable	Trade has been or will be reported. Depending on the regulatory regime the recipient is not responsible for reporting.
7	NonSIBuyer	Trade has been or will be reported as a buyer trade by an entity other than the authorised reporter
8	OffBook	Trade has been or will be reported by a trading venue as an "off-book" trade
9	NotReportable	Trade is not reportable. The (non-equity) instrument does not need to be reported by any party, e.g. because it is not deemed to have been traded on a trading venue.

Used in groups: [ExecAllocGrp](#)

Used in messages: [ExecutionReport](#), [NewOrderSingle](#), [TradeCaptureReport](#)

### 180.2.5387 TradeReportOrderDetail

Name	Mult.	Type	Description
<a href="#">OrderID</a>	[0..1]	String	
<a href="#">SecondaryOrderID</a>	[0..1]	String	
<a href="#">ClOrdID</a>	[0..1]	String	In the case of quotes can be mapped to QuoteMsgID(1166) of a single Quote(MsgType=S) or QuoteID(117) of a MassQuote(MsgType=i).



Name	Mult.	Type	Description
SecondaryClOrdID	[0..1]	String	In the case of quotes can be mapped to QuoteID(117) of a single Quote(MsgType=S) or QuoteEntryID(299) of a MassQuote(MsgType=i).
ListID	[0..1]	String	
RefOrderID	[0..1]	String	Some hosts assign an order a new order id under special circumstances. The RefOrdID field will connect the same underlying order across changing OrderIDs.
RefOrderIDSource	[0..1]	CodeSet	
RefOrdIDReason	[0..1]	CodeSet	The reason for updating the RefOrdID
RelatedOrderGrp	[0..*]	Group	
PreTradeAnonymity	[0..1]	Boolean	
OrdType	[0..1]	CodeSet	Order type from the order associated with the trade
Price	[0..1]	Price	Order price at time of trade
StopPx	[0..1]	Price	Stop/Limit order price
ExecInst	[0..1]	CodeSet	Execution Instruction from the order associated with the trade
OrdStatus	[0..1]	CodeSet	Status of order as of this trade report
OrderQtyData	[0..1]	Component	Order quantity at time of trade
LeavesQty	[0..1]	Qty	
CumQty	[0..1]	Qty	
TimeInForce	[0..1]	CodeSet	
ExpireTime	[0..1]	UTCTimestamp	The order expiration date/time in UTC
MatchingInstructions	[0..*]	Group	
SelfMatchPreventionID	[0..1]	String	May be used as an alternative to MatchingInstructions when the identifier does not appear in another field.
SelfMatchPreventionInstruction	[0..1]	CodeSet	
ExposureDuration	[0..1]	int	The (minimum or suggested) period of time a quoted price is to be tradable before it becomes indicative. (i.e. quoted price becomes off-the-wire).
ExposureDurationUnit	[0..1]	CodeSet	
DisplayInstruction	[0..1]	Component	
OrderCapacity	[0..1]	CodeSet	
OrderRestrictions	[0..1]	CodeSet	

Name	Mult.	Type	Description
BookingType	[0..1]	CodeSet	
OrigCustOrderCapacity	[0..1]	CodeSet	
OrderOrigination	[0..1]	CodeSet	
OrderAttributeGrp	[0..*]	Group	
ExDestinationType	[0..1]	CodeSet	
OrderInputDevice	[0..1]	String	
LotType	[0..1]	CodeSet	
TransBkdTime	[0..1]	UTCTimestamp	
OrigOrdModTime	[0..1]	UTCTimestamp	
OrderPercentOfTotalVolume	[0..1]	Percentage	

Used in groups: **TrdCapRptAckSideGrp**, **TrdCapRptSideGrp**, **TrdMatchSideGrp**

### 180.2.5388 TradeReportRefID

Reference identifier used with CANCEL and REPLACE transaction types.

Type: **String**

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**

### 180.2.5389 TradeReportRejectReason

Reason Trade Capture Request was rejected.

100+ Reserved and available for bi-laterally agreed upon user-defined values.

Type: **int**

Allowed values in TradeReportRejectReasonCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidPartyInformation	Invalid party information
2	UnknownInstrument	Unknown instrument
3	UnauthorizedToReportTrades	Unauthorized to report trades
4	InvalidTradeType	Invalid trade type

Code	Name	Description
5	PriceExceedsCurrentPriceBand	Price exceeds current price band
6	ReferencePriceNotAvailable	Reference price not available
7	NotionalValueExceedsThreshold	Notional value exceeds threshold
99	Other	Other

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.5390 TradeReportTransType

Identifies Trade Report message transaction type

(Prior to FIX 4.4 this field was of type char)

Type: [int](#)

Allowed values in TradeReportTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Cancel	Cancel
2	Replace	Replace
3	Release	Release
4	Reverse	Reverse
5	CancelDueToBackOutOfTrade	Cancel Due To Back Out of Trade

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.5391 TradeReportType

Type of Trade Report

Type: [int](#)

Allowed values in TradeReportTypeCodeSet:

Code	Name	Description
0	Submit	Submit
1	Alleged	Alleged
2	Accept	Accept
3	Decline	Decline
4	Addendum	Addendum. Used to provide material supplemental data to a previously submitted trade.
5	No	No/Was. Used to report a full replacement of a previously submitted trade.
6	TradeReportCancel	Trade Report Cancel
7	LockedIn	(Locked-In) Trade Break
8	Defaulted	Defaulted
9	InvalidCMTA	Invalid CMTA
10	Pended	Pended
11	AllegedNew	Alleged New
12	AllegedAddendum	Alleged Addendum
13	AllegedNo	Alleged No/Was
14	AllegedTradeReportCancel	Alleged Trade Report Cancel
15	AllegedTradeBreak	Alleged (Locked-In) Trade Break
16	Verify	Verify. Used in reports from a trading party to the SDR to confirm trade details. Omit RegulatoryReportType(1934).
17	Dispute	Dispute. Used in reports from a trading party to the SDR to dispute trade details. Omit RegulatoryReportType(1934).
18	NonMaterialUpdate	Non-material Update. Used to provide non-material supplemental data to a previously submitted trade.

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeMatchReport](#)

### **180.2.5392 TradeRequestID**

Trade Capture Report Request ID

Type: [String](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportRequest](#), [TradeCaptureReportRequestAck](#)

**180.2.5393 TradeRequestResult**

Result of Trade Request

Type: **int**

Allowed values in TradeRequestResultCodeSet:

Code	Name	Description
0	Successful	Successful (default)
1	InvalidOrUnknownInstrument	Invalid or unknown instrument
2	InvalidTypeOfTradeRequested	Invalid type of trade requested
3	InvalidParties	Invalid parties
4	InvalidTransportTypeRequested	Invalid transport type requested
5	InvalidDestinationRequested	Invalid destination requested
8	TradeRequestTypeNotSupported	TradeRequestType not supported
9	NotAuthorized	Not authorized
99	Other	Other

Used in messages: **TradeCaptureReportRequestAck**

**180.2.5394 TradeRequestStatus**

Status of Trade Request.

Type: **int**

Allowed values in TradeRequestStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	Completed	Completed
2	Rejected	Rejected

Used in messages: **TradeCaptureReportRequestAck**

**180.2.5395 TradeRequestType**

Type of Trade Capture Report.

Type: **int**

Allowed values in TradeRequestTypeCodeSet:

Code	Name	Description
0	AllTrades	All Trades
1	MatchedTradesMatchingCriteria	Matched trades matching criteria provided on request (Parties, ExecID, TradeID, OrderID, Instrument, InputSource, etc.)
2	UnmatchedTradesThatMatchCriteria	Unmatched trades that match criteria
3	UnreportedTradesThatMatchCriteria	Unreported trades that match criteria
4	AdvisoriesThatMatchCriteria	Advisories that match criteria

Used in messages: **TradeCaptureReportRequest**, **TradeCaptureReportRequestAck**

**180.2.5396 TradeSubType**

Further qualification to the trade type defined in TradeType(3006).

Type: **int**

Allowed values in TrdSubTypeCodeSet:

Code	Name	Description
0	CMTA	CMTA
1	InternalTransferOrAdjustment	Internal transfer or adjustment
2	ExternalTransferOrTransferOfAccount	External transfer or transfer of account
3	RejectForSubmittingSide	Reject for submitting side
4	AdvisoryForContraSide	Advisory for contra side
5	OffsetDueToAnAllocation	Offset due to an allocation
6	OnsetDueToAnAllocation	Onset due to an allocation
7	DifferentialSpread	Differential spread
8	ImpliedSpreadLegExecutedAgainstAnOutright	Implied spread leg executed against an outright
9	TransactionFromExercise	Transaction from exercise

Code	Name	Description
10	TransactionFromAssignment	Transaction from assignment
11	ACATS	ACATS
14	AI	AI (Automated input facility disabled in response to an exchange request.)
15	B	B (Transaction between two member firms where neither member firm is registered as a market maker in the security in question and neither is a designated fund manager. Also used by broker dealers when dealing with another broker which is not a member firm. Non-order book securities only.)
16	K	K (Transaction using block trade facility.)
17	LC	LC (Correction submitted more than three days after publication of the original trade report.)
18	M	M (Transaction, other than a transaction resulting from a stock swap or stock switch, between two market makers registered in that security including IDB or a public display system trades. Non-order book securities only.)
19	N	N (Non-protected portfolio transaction or a fully disclosed portfolio transaction)
20	NM	NM ( i) transaction where Exchange has granted permission for non-publication. ii)IDB is reporting as seller. iii) submitting a transaction report to the Exchange, where the transaction report is not also a trade report.)
21	NR	NR (Non-risk transaction in a SEATS security other than an AIM security)
22	P	P (Protected portfolio transaction or a worked principal agreement to effect a portfolio transaction which includes order book securities)
23	PA	PA (Protected transaction notification)
24	PC	PC (Contra trade for transaction which took place on a previous day and which was automatically executed on the Exchange trading system)
25	PN	PN (Worked principal notification for a portfolio transaction which includes order book securities)

Code	Name	Description
26	R	R ( (i) riskless principal transaction between non-members where the buying and selling transactions are executed at different prices or on different terms (requires a trade report with trade type indicator R for each transaction). (ii) market maker is reporting all the legs of a riskless principal transaction where the buying and selling transactions are executed at different prices (requires a trade report with trade type indicator R for each transaction) or. (iii) market maker is reporting the onward leg of a riskless principal transaction where the legs are executed at different prices, and another market maker has submitted a trade report using trade type indicator M for the first leg (this requires a single trade report with trade type indicator R).)
27	RO	RO (Transaction which resulted from the exercise of a traditional option or a stock-settled covered warrant)
28	RT	RT (Risk transaction in a SEATS security, (excluding AIM security) reported by a market maker registered in that security)
29	SW	SW (Transactions resulting from stock swap or a stock switch (one report is required for each line of stock))
30	T	T (If reporting a single protected transaction)
31	WN	WN (Worked principal notification for a single order book security)
32	WT	WT (Worked principal transaction (other than a portfolio transaction))
33	OffHoursTrade	Off Hours Trade
34	OnHoursTrade	On Hours Trade
35	OTCQuote	OTC Quote
36	ConvertedSWAP	Converted SWAP
37	CrossedTrade	Crossed Trade (X)
38	InterimProtectedTrade	Interim Protected Trade (I)
39	LargeInScale	Large in Scale (L)
40	WashTrade	Wash Trade
41	TradeAtSettlement	Trade at Settlement (TAS). Identifies a trade that will be priced using the settlement price.
42	AuctionTrade	Auction Trade. Mutually exclusive with TrdSubType(829) = 50 (Balancing).



Code	Name	Description
43	TradeAtMarker	Trade at Marker (TAM). Posted at a specific time each day and used to price the consummated trade for the product/month/strip executed (+/- and differentials). Closely related to TAS trades in function and trade practice.
44	CreditDefault	Default (Credit Event)
45	CreditRestructuring	Restructuring (credit event)
46	Merger	Merger (succession event)
47	SpinOff	Spin-off (succession event)
48	MultilateralCompression	Multilateral compression. Used to identify a special case of compression between multiple parties, e.g. for netted or portfolio trades.
50	Balancing	Balancing. Identifies an additional trade distributed to auction participants meant to resolve an imbalance between bids and offers. Mutually exclusive with TrdSubType(829) = 42 =(Auction).
51	BasisTradeIndexClose	Basis Trade index Close (BTIC). The marketplace name given to Trade at Marker (TAM) transactions in equity index futures.
52	TradeAtCashOpen	Trade At Cash Open (TACO). The marketplace name given to trading futures based on an opening quote of the underlying cash market.
53	TrdSubmitVenueClrSettl	Trade submitted to venue for clearing and settlement. Identifies trades brought on a trading venue purely for clearing and settlement purposes.
54	BilateralCompression	Bilateral compression. Used to identify a special case of compression between two parties, e.g. for netted or portfolio trades.

Used in groups: **TradeTypeGrp**

### 180.2.5397 TradeType

Type of trade assigned to a trade.

Type: **int**

Allowed values in TrdTypeCodeSet:

Code	Name	Description
0	RegularTrade	Regular trade

Code	Name	Description
1	BlockTrade	Block trade
2	EFP	Exchange for physical (EFP)
3	Transfer	Transfer
4	LateTrade	Late trade
5	TTrade	T trade
6	WeightedAveragePriceTrade	Weighted average price trade
7	BunchedTrade	Bunched trade
8	LateBunchedTrade	Late bunched trade
9	PriorReferencePriceTrade	Prior reference price trade
10	AfterHoursTrade	After hours trade
11	ExchangeForRisk	Exchange for risk (EFR)
12	ExchangeForSwap	Exchange for swap (EFS)
13	ExchangeOfFuturesFor	Exchange of futures for in market futures (EFM). For example full sized for mini.
14	ExchangeOfOptionsForOptions	Exchange of options for options (EOO)
15	TradingAtSettlement	Trading at settlement
16	AllOrNone	All or none
17	FuturesLargeOrderExecution	Futures large order execution
18	ExchangeOfFuturesForFutures	Exchange of futures for external market futures (EFF)
19	OptionInterimTrade	Option interim trade
20	OptionCabinetTrade	Option cabinet trade
22	PrivatelyNegotiatedTrades	Privately negotiated trade
23	SubstitutionOfFuturesForForwards	Substitution of futures for forwards
24	ErrorTrade	Error trade
25	SpecialCumDividend	Special cum dividend (CD)
26	SpecialExDividend	Special ex dividend (XD)
27	SpecialCumCoupon	Special cum coupon (CC)
28	SpecialExCoupon	Special ex coupon (XC)
29	CashSettlement	Cash settlement (CS)
30	SpecialPrice	Special price (SP). Usually net or all-in price.
31	GuaranteedDelivery	Guaranteed delivery (GD)
32	SpecialCumRights	Special cum rights (CR)
33	SpecialExRights	Special ex rights (XR)
34	SpecialCumCapitalRepayments	Special cum capital repayments (CP)

Code	Name	Description
35	SpecialExCapitalRepayments	Special ex capital repayments (XP)
36	SpecialCumBonus	Special cum bonus (CB)
37	SpecialExBonus	Special ex bonus (XB)
38	LargeTrade	Block trade. The same as large trade.
39	WorkedPrincipalTrade	Worked principal trade
40	BlockTrades	Block trades
41	NameChange	Name change
42	PortfolioTransfer	Portfolio transfer
43	ProrogationBuy	Prorogation buy. Used by Euronext Paris only. Is used to defer settlement under French SRD (deferred settlement system). Trades must be reported as crosses at zero price.
44	ProrogationSell	Prorogation sell. See prorogation buy.
45	OptionExercise	Option exercise
46	DeltaNeutralTransaction	Delta neutral transaction
47	FinancingTransaction	Financing transaction
48	NonStandardSettlement	Non-standard settlement
49	DerivativeRelatedTransaction	Derivative related transaction
50	PortfolioTrade	Portfolio trade. Identifies a collection/basket of trades. In the context of bonds (e.g. corporate bonds) these are transacted as a single trade at an aggregate price for the entire portfolio and may be traded all-or-none or most-or-none depending on bilateral agreement. In the context of ESMA RTS 1 Article 2(b), may be used to refer to portfolio trades to distinguish between addressable and non-addressable volume. In the context of Market Model Typology (MMT), use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
51	VolumeWeightedAverageTrade	Volume weighted average trade
52	ExchangeGrantedTrade	Exchange granted trade
53	RepurchaseAgreement	Repurchase agreement
54	OTC	OTC. Trade executed off-market. In the context of CFTC regulatory reporting for swaps, it is a large notional off-facility swap. In the context of MiFID transparency reporting rules this is used to report, into an exchange, deals made outside exchange rules.
55	ExchangeBasisFacility	Exchange basis facility (EBF)

Code	Name	Description
56	OpeningTrade	Opening trade. Identifies a trade that resulted from the opening of a market. In the context of IIROC, this indicates a trade that occurred at the opening or the first trade of the day for a security.
57	NettedTrade	Netted trade
58	BlockSwapTrade	Block swap trade. Block trade executed off-market or on a registered market. In the context of CFTC regulatory reporting for swaps, it is a swap executed according to SEF or DCM rules.
59	CreditEventTrade	Credit event trade
60	SuccessionEventTrade	Succession event trade
61	GiveUpGiveInTrade	Give-up Give-in trade
62	DarkTrade	Dark trade. In the context of Market Model Typology (MMT), a dark trade might also come from a lit/hybrid book (e.g. when an aggressive lit order hits a resting dark order). The use of this value applies to TrdType(828), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
63	TechnicalTrade	Technical trade
64	Benchmark	Benchmark. In the context of ESMA RTS 1 Article 2(a), may be used to refer to benchmark trades. In the context of Market Model Typology (MMT), the "benchmark" price depends on a benchmark which has no current price but was derived from a time series such as a VWAP. The use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
65	PackageTrade	Package trade. May be used to identify the pseudo-trade of a stream or collection of trades to be transacted, cleared and be reported as an atomic unit. In the context of MiFIR RTS 1, this is the "CONT" flag. In the context of MiFIR RTS 2 Article 1(1)(b), may be used to refer to package transactions (excluding exchange for physicals). In the context of Market Model Typology (MMT), use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
66	RollTrade	Roll trade. Trade is a roll from one contract that is about to expire to a new contract.

Code	Name	Description
67	ClosingPriceTrade	Closing price trade. Identifies a trade that uses the closing price of a market without resulting from the closing of this market. In the context of FCA policy statement PS23/4, this indicates a benchmark transaction executed using the market closing price and is the "CLSE" flag.
68	InterFundTransferTrade	Inter-fund transfer trade. Administrative trade (non price-forming) related to the transfer of ownership between funds.
69	NetAssetValueCalculatedTrade	Net asset value calculated trade. Trade of a fund priced at the net asset value of its constituents. In the context of MiFIR RTS 1, this may be used for ETFs when the NAV price becomes available.

Used in groups: [TradeTypeGrp](#)

### 180.2.5398 TradeTypeGrp

The TradeTypeGrp component is used to express multiple trade types on the same message and can be used as an alternative to the fields TrdType(828), SecondaryTrdType(855), and TertiaryTrdType(2896) when three or fewer trade types are needed.

Name	Mult.	Type	Description
<a href="#">NoTradeTypes</a>	[1..1]	NumInGroup	
<a href="#">TradeType</a>	[0..1]	CodeSet	Required if NoTradeTypes(3005) > 0.
<a href="#">TradeSubType</a>	[0..1]	CodeSet	

Used in groups: [MDFullGrp](#), [MDIncGrp](#)

Used in messages: [ExecutionReport](#), [TradeCaptureReport](#)

### 180.2.5399 TradeVersion

Specifies the version of a trade or contract. This is used by systems or trading platforms in conjunction with TradeID(1003) to uniquely identify the version of a trade or contract. If used the conditions for a change of version are subject to bilateral agreement. It is recommended to change the version only for significant updates to the business entity rather than for minor changes to trade details or systematic

distribution of reports. Examples where the version would change are trade quantity modification, customer account assignment or trade novation.

Type: **String**

Used in messages: **TradeCaptureReport**

#### **180.2.5400 TradeVolType**

Define the type of trade volume applicable for the MinTradeVol(562) and MaxTradeVol(1140)

Type: **int**

Allowed values in TradeVolTypeCodeSet:

Code	Name	Description
0	NumberOfUnits	Number of units (e.g. share, par, currency, contracts) (default)
1	NumberOfRoundLots	Number of round lots

Used in components: **BaseTradingRules**

#### **180.2.5401 TradeVolume**

Used to report volume with a trade

Type: **Qty**

Used in groups: **MDFullGrp**, **MDIncGrp**

#### **180.2.5402 TradingBusinessDays**

Number of actual trading business days of an instrument.

Type: **int**

Used in groups: **ClearingPriceParametersGrp**

#### **180.2.5403 TradingCapacity**

Designates the capacity in which the order is submitted for trading by the market participant.

Type: **int**

Allowed values in TradingCapacityCodeSet:

Code	Name	Description
1	Customer	Customer
2	CustomerProfessional	Customer professional
3	BrokerDealer	Broker-dealer
4	CustomerBrokerDealer	Customer broker-dealer
5	Principal	Principal
6	MarketMaker	Market maker
7	AwayMarketMaker	Away market maker
8	SystematicInternaliser	Systematic internaliser

Used in components: [MDStatisticParameters](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MassOrder](#), [MassOrderAck](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

#### **180.2.5404 TradingCurrency**

Used when the trading currency can differ from the price currency

Type: [Currency](#)

Used in components: [BaseTradingRules](#)

#### **180.2.5405 TradingCurrencyCodeSource**

Identifies class or source of the TradingCurrency(1245) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [BaseTradingRules](#)

#### **180.2.5406 TradingReferencePrice**

Reference price for the current trading price range usually representing the mid price between the HighLimitPrice and LowLimitPrice. The value may be the settlement price or closing price of the prior trading day.

Type: [Price](#)

Used in components: [PriceLimits](#)

#### **180.2.5407 TradingSessionDesc**

Trading Session description

Type: [String](#)

Used in groups: [TrdSessLstGrp](#)

#### **180.2.5408 TradingSessionID**

Identifier for a trading session.

A trading session spans an extended period of time that can also be expressed informally in terms of the trading day. Usage is determined by market or counterparties.

To specify good for session where session spans more than one calendar day, use TimeInForce = 0 (Day) in conjunction with TradingSessionID(336).

Bilaterally agreed values of data type "String" that start with a character can be used for backward compatibility.

Type: [String](#)

Allowed values in TradingSessionIDCodeSet:



Code	Name	Description
1	Day	Day
2	HalfDay	HalfDay
3	Morning	Morning
4	Afternoon	Afternoon
5	Evening	Evening
6	AfterHours	After-hours
7	Holiday	Holiday

Used in components: **MDStatisticParameters**

Used in groups: **BidCompReqGrp, BidCompRspGrp, MDFullGrp, MDIncGrp, QuotEntryAckGrp, QuotEntryGrp, QuotReqGrp, QuotReqRjctGrp, RFQReqGrp, TradingSessionRulesGrp, TrdCapRptAckSideGrp, TrdCapRptSideGrp, TrdSessLstGrp, TrdgSesGrp**

Used in messages: **Advertisement, AllocationInstruction, AllocationInstructionAlert, AllocationReport, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralRequest, DerivativeSecurityListRequest, ExecutionReport, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderMassStatusRequest, Quote, QuoteCancel, QuoteResponse, QuoteStatusReport, QuoteStatusRequest, SecurityDefinitionRequest, SecurityListRequest, SecurityMassStatus, SecurityMassStatusRequest, SecurityStatus, SecurityStatusRequest, SecurityTypeRequest, SecurityTypes, TradeCaptureReportRequest, TradeMatchReport, TradingSessionListRequest, TradingSessionStatus, TradingSessionStatusRequest**

### 180.2.5409 TradingSessionRules

Name	Mult.	Type	Description
<b>OrdTypeRules</b>	[0..*]	Group	Specifies the order types that are valid for trading. The scope of the rule is determined by the context in which the component is used. In this case, the scope is trading session.
<b>TimeInForceRules</b>	[0..*]	Group	Specifies the time in force rules that are valid for trading. The scope of the rule is determined by the context in which the component is used. In this case, the scope is trading session.

Name	Mult.	Type	Description
<a href="#">ExecInstRules</a>	[0..*]	Group	Specifies the execution instructions that are valid for trading. The scope of the rule is determined by the context in which the component is used. In this case, the scope is trading session.
<a href="#">AuctionTypeRuleGrp</a>	[0..*]	Group	Specifies the auction order types that are valid for trading on the identified. The scope of the rule is determined by the context in which the component is used. In this case, the scope is trading session.
<a href="#">MatchRules</a>	[0..*]	Group	Specifies the matching rules that are valid for trading. The scope of the rule is determined by the context in which the component is used. In this case, the scope is trading session.
<a href="#">MarketDataFeedTypes</a>	[0..*]	Group	Specifies the market data feed types that are valid for trading. The scope of the rule is determined by the context in which the component is used. In this case, the scope is trading session.

Used in groups: [TradingSessionRulesGrp](#), [TrdSessLstGrp](#)

### 180.2.5410 TradingSessionRulesGrp

Name	Mult.	Type	Description
<a href="#">NoTradingSessionRules</a>	[1..1]	NumInGroup	Allows trading rules to be expressed by trading session
<a href="#">TradingSessionID</a>	[0..1]	CodeSet	Identifier for the trading session. Must be provided if NoTradingSessions > 0. Set to [N/A] if values are not specific to trading session
<a href="#">TradingSessionSubID</a>	[0..1]	CodeSet	Identifier for the trading session. Set to [N/A] if values are not specific to trading session sub id
<a href="#">TradingSessionRules</a>	[0..1]	Component	Contains trading rules specified at the trading session level

Used in components: [SecurityTradingRules](#)

**180.2.5411 TradingSessionSubID**

Optional market assigned sub identifier for a trading phase within a trading session. Usage is determined by market or counterparties. Used by US based futures markets to identify exchange specific execution time bracket codes as required by US market regulations. Bilaterally agreed values of data type "String" that start with a character can be used for backward compatibility

Type: **String**

Allowed values in TradingSessionSubIDCodeSet:

Code	Name	Description
1	PreTrading	Pre-Trading
2	OpeningOrOpeningAuction	Opening or opening auction
3	Continuous	(Continuous) Trading
4	ClosingOrClosingAuction	Closing or closing auction
5	PostTrading	Post-Trading
6	ScheduledIntradayAuction	Scheduled intraday auction
7	Quiescent	Quiescent
8	AnyAuction	Any auction
9	UnscheduledIntradayAuction	Unscheduled intraday auction. An unscheduled intraday auction might be triggered by a circuit breaker.
10	OutOfMainSessionTrading	Out of main session trading. In the context of Market Model Typology "Out of main session trading" refers to both before and after session, neither auction nor continuous trading.
11	PrivateAuction	Private auction. An auction phase where only two parties participate.
12	PublicAuction	Public auction. An auction phase where all trading parties participate.
13	GroupAuction	Group auction. An auction phase limited to specific parties (e.g. parties that have resting orders in the order book).
14	OrderInitiatedAuction	Order initiated auction. Auction automatically triggered by an order, e.g. an incoming order or a resting order that can be matched based on an incoming order. Use 9="Unscheduled intraday auction" for any other auctions that are not scheduled. In the context of Market Model Topology, this can be used for an on demand auction (a.k.a. frequent batched auction).

Used in components: **MDStatisticParameters**

Used in groups: BidCompReqGrp, BidCompRspGrp, MDFullGrp, MDIncGrp, QuotEntryAckGrp, QuotEntryGrp, QuotReqGrp, QuotReqRjctGrp, RFQReqGrp, TradingSessionRulesGrp, TrdCapRptAckSideGrp, TrdCapRptSideGrp, TrdSessLstGrp, TrdgSesGrp

Used in messages: Advertisement, AllocationInstruction, AllocationInstructionAlert, AllocationReport, CollateralAssignment, CollateralInquiry, CollateralInquiryAck, CollateralReport, CollateralRequest, DerivativeSecurityListRequest, ExecutionReport, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderMassStatusRequest, Quote, QuoteCancel, QuoteResponse, QuoteStatusReport, QuoteStatusRequest, SecurityDefinitionRequest, SecurityListRequest, SecurityMassStatus, SecurityMassStatusRequest, SecurityStatus, SecurityStatusRequest, SecurityTypeRequest, SecurityTypes, TradeCaptureReportRequest, TradeMatchReport, TradingSessionListRequest, TradingSessionStatus, TradingSessionStatusRequest

#### **180.2.5412 TradingUnitPeriodMultiplier**

Indicates the number of contract periods associated with the minimum trading unit for a given contract duration resulting in the number of total traded contracts.

Type: **int**

Used in components: **Instrument**

#### **180.2.5413 TradSesCloseTime**

Closing time of the trading session

Type: **UTCTimestamp**

Used in groups: **TrdSessLstGrp**

Used in messages: **TradingSessionStatus**

#### **180.2.5414 TradSesControl**

Indicates how control of trading session and subsession transitions are performed.

Type: **int**

Allowed values in TradSesControlCodeSet:

Code	Name	Description
0	Automatic	Automatic (Default)
1	Manual	Manual

Used in messages: [TradingSessionStatus](#)

#### **180.2.5415 TradSesEndTime**

End time of the trading session

Type: [UTCTimestamp](#)

Used in groups: [TrdSessLstGrp](#)

Used in messages: [TradingSessionStatus](#)

#### **180.2.5416 TradSesEvent**

Identifies an event related to a TradSesStatus(340). An event occurs and is gone, it is not a state that applies for a period of time.

Type: [int](#)

Allowed values in TradSesEventCodeSet:

Code	Name	Description
0	TradingResumes	Trading resumes (after Halt)
1	ChangeOfTradingSession	Change of Trading Session
2	ChangeOfTradingSubsession	Change of Trading Subsession
3	ChangeOfTradingStatus	Change of Trading Status

Used in messages: [TradingSessionStatus](#)

#### **180.2.5417 TradSesMethod**

Method of trading

Type: [int](#)

Allowed values in TradSesMethodCodeSet:

Code	Name	Description
1	Electronic	Electronic
2	OpenOutcry	Open Outcry
3	TwoParty	Two Party
4	Voice	Voice

Used in components: [MDStatisticParameters](#)

Used in groups: [TrdSessLstGrp](#)

Used in messages: [TradingSessionListRequest](#), [TradingSessionStatus](#), [TradingSessionStatusRequest](#)

#### **180.2.5418 TradSesMode**

Trading Session Mode

Type: [int](#)

Allowed values in TradSesModeCodeSet:

Code	Name	Description
1	Testing	Testing
2	Simulated	Simulated
3	Production	Production

Used in groups: [TrdSessLstGrp](#)

Used in messages: [TradingSessionListRequest](#), [TradingSessionStatus](#), [TradingSessionStatusRequest](#)

#### **180.2.5419 TradSesOpenTime**

Time of the opening of the trading session

Type: [UTCTimestamp](#)

Used in groups: [TrdSessLstGrp](#)

Used in messages: [TradingSessionStatus](#)

**180.2.5420 TradSesPreCloseTime**

Time of the pre-closed of the trading session

Type: **UTCTimestamp**

Used in groups: **TrdSessLstGrp**

Used in messages: **TradingSessionStatus**

**180.2.5421 TradSesReqID**

Unique ID of a Trading Session Status message.

Type: **String**

Used in messages: **TradingSessionList**, **TradingSessionListRequest**, **TradingSessionListUpdateReport**, **TradingSessionStatus**, **TradingSessionStatusRequest**

**180.2.5422 TradSesStartTime**

Starting time of the trading session

Type: **UTCTimestamp**

Used in groups: **TrdSessLstGrp**

Used in messages: **TradingSessionStatus**

**180.2.5423 TradSesStatus**

State of the trading session.

Type: **int**

Allowed values in TradSesStatusCodeSet:

Code	Name	Description
0	Unknown	Unknown
1	Halted	Halted
2	Open	Open
3	Closed	Closed
4	PreOpen	Pre-Open

Code	Name	Description
5	PreClose	Pre-Close
6	RequestRejected	Request Rejected

Used in groups: [TrdSessLstGrp](#)

Used in messages: [TradingSessionStatus](#)

#### **180.2.5424 TradSesStatusRejReason**

Indicates the reason a Trading Session Status Request was rejected.

Type: [int](#)

Allowed values in TradSesStatusRejReasonCodeSet:

Code	Name	Description
1	UnknownOrInvalidTradingSessionID	Unknown or invalid TradingSessionID
99	Other	Other

Used in groups: [TrdSessLstGrp](#)

Used in messages: [TradingSessionStatus](#)

#### **180.2.5425 TradSesUpdateAction**

Specifies the action taken for the specified trading sessions.

Type: [char](#)

Allowed values in SecurityUpdateActionCodeSet:

Code	Name	Description
A	Add	Add
D	Delete	Delete
M	Modify	Modify

Used in groups: [TrdSessLstGrp](#)



**180.2.5426 TransactionAttributeGrp**

The TransactionAttributeGrp component block is a repeating group that may be used to provide additional transaction attributes for the trade and other post-trade events.

Name	Mult.	Type	Description
NoTransactionAttributes	[1..1]	NumInGroup	
TransactionAttributeType	[0..1]	CodeSet	Required if NoTransactionAttributes(2871) > 0.
TransactionAttributeValue	[0..1]	String	

Used in messages: [CollateralReport](#), [PositionReport](#), [TradeCaptureReport](#)

**180.2.5427 TransactionAttributeType**

Type of attribute(s) or characteristic(s) associated with the transaction.

Type: [int](#)

Allowed values in TransactionAttributeTypeCodeSet:

Code	Name	Description
0	ExclusiveArrangement	Exclusive arrangement. In the context of securities borrowing and lending transaction, an indication of whether the borrower has exclusive access to borrow from the lender's securities portfolio. Not applicable to commodities. TransactionAttributeValue(2873) takes Y or N value.
1	CollateralReuse	Collateral reuse. Indication of whether the collateral taker can reuse the securities provided as collateral for the transaction. TransactionAttributeValue(tbd2873) takes Y or N value.
2	CollateralArrangementType	Collateral arrangement type. In the context of securities financing transactions, indicates the type of collateral arrangement. For EU SFTR reporting, TransactionAttributeValue(2873) may take ESMA assigned values "TTCA" (title transfer), "SICA" (securities financial interest), or "SIUR" (securities financial interest with right of use).

Used in groups: [TransactionAttributeGrp](#)

**180.2.5428 TransactionAttributeValue**

Value associated with the specified TransactionAttributeType(2872).

Type: **String**

Used in groups: **TransactionAttributeGrp**

**180.2.5429 TransactionID**

The unique transaction entity identifier.

Type: **String**

Used in messages: **CollateralAssignment, CollateralReport, CollateralResponse**

**180.2.5430 TransactTime**

Timestamp when the business transaction represented by the message occurred.

Type: **UTCTimestamp**

Used in groups: **ListOrdGrp, MDIncGrp, QuotEntryAckGrp, QuotEntryGrp, QuotReqGrp, QuotReqRjctGrp, SecTypesGrp, TrdCapDtGrp, TrdSessLstGrp**

Used in messages: **AccountSummaryReport, Advertisement, AlgoCertificateReport, AlgoCertificateRequest, AllocationInstruction, AllocationInstructionAck, AllocationInstructionAlert, AllocationReport, AllocationReportAck, CollateralAssignment, CollateralReport, CollateralReportAck, CollateralRequest, CollateralResponse, Confirmation, ConfirmationAck, ConfirmationRequest, ContraryIntentionReport, CrossOrderCancelReplaceRequest, CrossOrderCancelRequest, DerivativeSecurityList, DerivativeSecurityListUpdateReport, ExecutionReport, IOI, ListCancelRequest, ListExecute, ListStatus, MarginRequirementInquiry, MarginRequirementInquiryAck, MarginRequirementReport, MarketDataReport, MarketDataStatisticsReport, MarketDataStatisticsRequest, MarketDefinition, MarketDefinitionUpdateReport, MassOrder, MassOrderAck, MultilegOrderCancelReplace, NewOrderCross, NewOrderMultileg, NewOrderSingle, OrderCancelReject, OrderCancelReplaceRequest, OrderCancelRequest, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, PartyActionReport, PartyActionRequest, PartyDetailsListReport, PartyDetailsListUpdateReport, PartyEntitlementsReport, PartyEntitlementsUpdateReport, PartyRiskLimitCheckRequest, PartyRiskLimitCheckRequestAck, PartyRiskLimitsReport, PartyRiskLimitsReportAck, PartyRiskLimitsUpdateReport, PayManagementReport, PayManagementRequest, PositionMaintenanceReport, PositionMaintenanceRequest, PositionReport, PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport, Quote, QuoteResponse, QuoteStatusReport, RequestForPositions,**

SecurityDefinition, SecurityDefinitionUpdateReport, SecurityList, SecurityListUpdateReport, SecurityMassStatus, SecurityRiskMetricsReport, SecurityStatus, SettlementInstructionRequest, SettlementInstructions, SettlementObligationReport, SettlementStatusReport, SettlementStatusRequest, TestActionRequest, TestSuiteDefinitionRequest, TradeCaptureReport, TradeCaptureReportAck, TradeMatchReport, TradingSessionStatus

#### **180.2.5431 TransBkdTime**

For CIV A date and time stamp to indicate the time a CIV order was booked by the fund manager.

For derivatives a date and time stamp to indicate when this order was booked with the agent prior to submission to the VMU. Indicates the time at which the order was finalized between the buyer and seller prior to submission.

Type: **UTCTimestamp**

Used in components: **TradeReportOrderDetail**

Used in groups: **MDIncGrp**

Used in messages: **CrossOrderCancelReplaceRequest, ExecutionReport, NewOrderCross**

#### **180.2.5432 TransferID**

The unique identifier assigned to the transfer entity once it is received, for example, by the CCP or the party governing the transfer process. Generally this same identifier for the transfer is used by all parties involved.

Type: **String**

Used in messages: **PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport**

#### **180.2.5433 TransferInstructionID**

Unique identifier for the transfer instruction assigned by the submitter.

Type: **String**

Used in messages: **PositionTransferInstruction, PositionTransferInstructionAck, PositionTransferReport**

**180.2.5434 TransferReason**

Reason trade is being transferred

Type: **String**

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**

**180.2.5435 TransferRejectReason**

Reason the transfer instruction was rejected.

Type: **int**

Allowed values in TransferRejectReasonCodeSet:

Code	Name	Description
0	Success	Success
1	InvalidParty	Invalid party
2	UnknownInstrument	Unknown instrument
3	UnauthorizedToSubmitXfer	Not authorized to submit transfers
4	UnknownPosition	Unknown position
99	Other	Other

Used in messages: **PositionTransferInstructionAck**, **PositionTransferReport**

**180.2.5436 TransferReportID**

Unique identifier for the transfer report message.

Type: **String**

Used in messages: **PositionTransferReport**

**180.2.5437 TransferReportType**

Indicates the type of transfer report.

Type: **int**

Allowed values in TransferReportTypeCodeSet:

---

Code	Name	Description
------	------	-------------

---

0	Submit	Submit
---	--------	--------

1	Alleged	Alleged
---	---------	---------

---

Used in messages: [PositionTransferReport](#)

### 180.2.5438 TransferScope

Indicates the type of transfer.

Type: [int](#)

Allowed values in TransferScopeCodeSet:

---

Code	Name	Description
------	------	-------------

---

0	InterFirmTransfer	Inter-firm transfer
---	-------------------	---------------------

1	IntraFirmTransfer	Intra-firm transfer
---	-------------------	---------------------

2	CMTA	Clearing Member Trade Assignment
---	------	----------------------------------

---

Used in messages: [PositionTransferInstruction](#), [PositionTransferInstructionAck](#), [PositionTransferReport](#)

### 180.2.5439 TransferStatus

Status of the transfer.

Type: [int](#)

Allowed values in TransferStatusCodeSet:

---

Code	Name	Description
------	------	-------------

---

0	Received	Received
---	----------	----------

1	RejectedByIntermediary	Rejected by intermediary
---	------------------------	--------------------------

2	AcceptPending	Accept pending
---	---------------	----------------

3	Accepted	Accepted
---	----------	----------

4	Declined	Declined
---	----------	----------

5	Cancelled	Cancelled
---	-----------	-----------

---

Used in messages: [PositionTransferInstructionAck](#), [PositionTransferReport](#)

#### **180.2.5440 TransferTransType**

Indicates the type of transfer transaction.

Type: [int](#)

Allowed values in TransferTransTypeCodeSet:

Code	Name	Description
0	New	New
1	Replace	Replace
2	Cancel	Cancel

Used in messages: [PositionTransferInstruction](#), [PositionTransferInstructionAck](#), [PositionTransferReport](#)

#### **180.2.5441 TransferType**

Indicates the type of transfer request.

Type: [int](#)

Allowed values in TransferTypeCodeSet:

Code	Name	Description
0	RequestTransfer	Request transfer
1	AcceptTransfer	Accept transfer
2	DeclineTransfer	Decline transfer

Used in messages: [PositionTransferInstruction](#), [PositionTransferInstructionAck](#)

#### **180.2.5442 TrdAckStatus**

Used to indicate the status of the trade submission (not the trade report)

Type: [int](#)

Allowed values in TrdAckStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	Rejected	Rejected
2	Received	Received

Used in messages: [TradeCaptureReportAck](#)

### 180.2.5443 TrdAllocGrp

Name	Mult.	Type	Description
NoAllocs	[1..1]	NumInGroup	
AllocAccount	[0..1]	String	Required if NoAllocs(78) > 0.
AllocAcctIDSource	[0..1]	CodeSet	
AllocSettlCurrency	[0..1]	Currency	
AllocSettlCurrencyCodeSource	[0..1]	CodeSet	
IndividualAllocID	[0..1]	String	
ParentAllocID	[0..1]	String	
AllocLegRefID	[0..1]	String	The field may not be used in any message where there are no legs.
AllocRegulatoryTradeIDGrp	[0..*]	Group	
FirmMnemonic	[0..1]	String	
NestedParties2	[0..*]	Group	
AllocHandlInst	[0..1]	CodeSet	
AllocQty	[0..1]	Qty	
AllocCalculatedCcyQty	[0..1]	Qty	
CustodialLotID	[0..1]	String	Only used for specific lot trades.
VersusPurchaseDate	[0..1]	LocalMktDate	Only used for specific lot trades. If this field is used, either VersusPurchasePrice(1754) or CurrentCostBasis(1755) should be specified.
VersusPurchasePrice	[0..1]	Price	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified.

Name	Mult.	Type	Description
CurrentCostBasis	[0..1]	Amt	Only used for specific lot trades. If this field is used, VersusPurchaseDate(1753) should be specified
AllocCustomerCapacity	[0..1]	String	Can be used for granular reporting of separate allocation detail within a single trade report or allocation message.
AllocMethod	[0..1]	CodeSet	
SecondaryIndividualAllocID	[0..1]	String	
AllocClearingFeeIndicator	[0..1]	String	
TradeAllocAmtGrp	[0..*]	Group	
TradeAllocStatus	[0..1]	CodeSet	
AllocationRollupInstruction	[0..1]	CodeSet	
AllocText	[0..1]	String	
EncodedAllocTextLen	[0..1]	Length	
EncodedAllocText	[0..1]	data	
FirmAllocText	[0..1]	String	
EncodedFirmAllocTextLen	[0..1]	Length	
EncodedFirmAllocText	[0..1]	data	
AllocRefRiskLimitCheckID	[0..1]	String	
AllocRefRiskLimitCheckIDType	[0..1]	CodeSet	
AllocCommissionDataGrp	[0..*]	Group	

Used in groups: [TrdCapRptAckSideGrp](#), [TrdCapRptSideGrp](#), [TrdMatchSideGrp](#)

#### 180.2.5444 TrdCapDtGrp

Name	Mult.	Type	Description
NoDates	[1..1]	NumInGroup	Number of date ranges provided (must be 1 or 2 if specified)
TradeDate	[0..1]	LocalMktDate	Used when reporting other than current day trades. Conditionally required if NoDates > 0
LastUpdateTime	[0..1]	UTCTimestamp	
TransactTime	[0..1]	UTCTimestamp	To request trades for a specific time.

Used in messages: [TradeCaptureReportRequest](#)



**180.2.5445 TrdCapRptAckSideGrp**

Name	Mult.	Type	Description
NoSides	[1..1]	CodeSet	
Side	[1..1]	CodeSet	Required when NoSides(552) > 0.
SideExecID	[0..1]	String	
SideTradeID	[0..1]	String	
SideOrigTradeID	[0..1]	String	
OrderDelay	[0..1]	int	
OrderDelayUnit	[0..1]	CodeSet	
Parties	[0..*]	Group	
Account	[0..1]	String	
AcctIDSource	[0..1]	CodeSet	
AccountType	[0..1]	CodeSet	
LimitAmts	[0..*]	Group	Insert here the set of "LimitAmts" field defined in "Common Components"
ProcessCode	[0..1]	CodeSet	
OddLot	[0..1]	CodeSet	
ClrInstGrp	[0..*]	Group	
SideTradeReportingIndicator	[0..1]	CodeSet	
TradeInputSource	[0..1]	String	
TradeInputDevice	[0..1]	String	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
CustOrderCapacity	[0..1]	CodeSet	
TradingSessionID	[0..1]	CodeSet	
TradingSessionSubID	[0..1]	CodeSet	
TimeBracket	[0..1]	String	
NetGrossInd	[0..1]	CodeSet	

Name	Mult.	Type	Description
SideCurrency	[0..1]	Currency	
SideCurrencyCodeSource	[0..1]	CodeSet	
SideSettlCurrency	[0..1]	Currency	
SideSettlCurrencyCodeSource	[0..1]	CodeSet	
CommissionData	[0..1]	Component	
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData if multiple commissions or enhanced attributes are needed.
NumDaysInterest	[0..1]	int	
ExDate	[0..1]	LocalMktDate	
AccruedInterestRate	[0..1]	Percentage	
AccruedInterestAmt	[0..1]	Amt	
InterestAtMaturity	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	
StartCash	[0..1]	Amt	
EndCash	[0..1]	Amt	
Concession	[0..1]	Amt	
TotalTakedown	[0..1]	Amt	
NetMoney	[0..1]	Amt	
SettlCurrAmt	[0..1]	Amt	
SettlCurrFxRate	[0..1]	float	
SettlCurrFxRateCalc	[0..1]	CodeSet	
PositionEffect	[0..1]	CodeSet	
SideMultiLegReportingType	[0..1]	CodeSet	
ContAmtGrp	[0..*]	Group	
Stipulations	[0..*]	Group	
MiscFeesGrp	[0..*]	Group	
ExchangeRule	[0..1]	String	
SettlDetails	[0..*]	Group	Conveys settlement account details reported as part of obligation.
TradeAllocIndicator	[0..1]	CodeSet	
AllocGroupID	[0..1]	String	
PreviousAllocGroupID	[0..1]	String	Identifies the previous AllocGroupID(1730) being changed when AllocGroupStatus(2767)=3 (Changed).

Name	Mult.	Type	Description
GroupAmount	[0..1]	Amt	
AllocGroupStatus	[0..1]	CodeSet	
SideAvgPxIndicator	[0..1]	CodeSet	
SideAvgPxGroupID	[0..1]	String	
SideAvgPx	[0..1]	Price	
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	
TrdAllocGrp	[0..*]	Group	
SideGrossTradeAmt	[0..1]	Amt	
AggressorIndicator	[0..1]	CodeSet	
SideLastQty	[0..1]	Qty	
SideTradeReportID	[0..1]	String	
SideFillStationCd	[0..1]	String	
SideReasonCd	[0..1]	String	
RptSeq	[0..1]	int	
SideTrdSubType	[0..1]	CodeSet	
OrderCategory	[0..1]	CodeSet	
StrategyLinkID	[0..1]	String	
TradeReportOrderDetail	[0..1]	Component	Details of the order associated with this side of the trade.
SideTrdRegTS	[0..*]	Group	
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
RelatedTradeGrp	[0..*]	Group	
RelatedPositionGrp	[0..*]	Group	
SideRiskLimitCheckStatus	[0..1]	CodeSet	

Used in messages: [TradeCaptureReportAck](#)

#### 180.2.5446 TrdCapRptSideGrp

Name	Mult.	Type	Description
NoSides	[1..1]	CodeSet	

Name	Mult.	Type	Description
Side	[1..1]	CodeSet	Required when NoSides(552) > 0.
ShortMarkingExemptIndicator	[0..1]	Boolean	
SideExecID	[0..1]	String	
OrderDelay	[0..1]	int	
OrderDelayUnit	[0..1]	CodeSet	
SideLastQty	[0..1]	Qty	
SideClearingTradePrice	[0..1]	Price	Used to indicate a side specific alternate clearing price.
SidePriceDifferential	[0..1]	Price	Used to indicate the Price Differential between the first and second leg of a complex instrument.
SideClearingTradePriceType	[0..1]	CodeSet	Used to indicate whether the trade is clearing using execution price (LastPx) or alternate clearing price (ClrTrdPx)
SideTradeReportID	[0..1]	String	
SideTradeID	[0..1]	String	
SideOrigTradeID	[0..1]	String	
SideFillStationCd	[0..1]	String	
SideReasonCd	[0..1]	String	
RptSeq	[0..1]	int	
SideTrdSubType	[0..1]	CodeSet	
NetGrossInd	[0..1]	CodeSet	
SideCurrency	[0..1]	Currency	
SideCurrencyCodeSource	[0..1]	CodeSet	
SideSettlCurrency	[0..1]	Currency	
SideSettlCurrencyCodeSource	[0..1]	CodeSet	
Parties	[0..*]	Group	
PartyDetailGrp	[0..*]	Group	PartyDetailID(1619) must reference an existing entry in Parties component or a previous entry in RelatedPartyDetailGrp. The instance must have the same role as the referenced entry. The embedded RelatedPartyDetailID(1563) should introduce a new party identifier not previously reported.
Account	[0..1]	String	Required for executions against electronically submitted orders which were assigned an account by the institution or intermediary.
AcctIDSource	[0..1]	CodeSet	

Name	Mult.	Type	Description
AccountType	[0..1]	CodeSet	
OwnerType	[0..1]	CodeSet	
LimitAmts	[0..*]	Group	Insert here the set of "LimitAmts" fields defined in "Common Components"
ProcessCode	[0..1]	CodeSet	Used to specify Step-out trades.
OddLot	[0..1]	CodeSet	
ClrInstGrp	[0..*]	Group	
ClearingFeeIndicator	[0..1]	CodeSet	
SideRegulatoryTradeIDGrp	[0..*]	Group	
SideTradeReportingIndicator	[0..1]	CodeSet	May be used to bilaterally inform counterparty of trade reporting status for this side of the trade.
FirmTradeEventID	[0..1]	String	
TradeInputSource	[0..1]	String	
TradeInputDevice	[0..1]	String	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
CustOrderCapacity	[0..1]	CodeSet	The customer capacity for this trade
TradingSessionID	[0..1]	CodeSet	Usually the same for all sides of a trade, if reported only on the first side the same TradingSessionID(336) then applies to all sides of the trade.
TradingSessionSubID	[0..1]	CodeSet	Usually the same for all sides of a trade, if reported only on the first side the same TradingSessionSubID(625) then applies to all sides of the trade.
TimeBracket	[0..1]	String	
RemunerationIndicator	[0..1]	CodeSet	
CommissionData	[0..1]	Component	

Name	Mult.	Type	Description
CommissionDataGrp	[0..*]	Group	Use as an alternative to CommissionData if multiple commissions or enhanced attributes are needed.
NumDaysInterest	[0..1]	int	
ExDate	[0..1]	LocalMktDate	
AccruedInterestRate	[0..1]	Percentage	
AccruedInterestAmt	[0..1]	Amt	
InterestAtMaturity	[0..1]	Amt	
EndAccruedInterestAmt	[0..1]	Amt	For repurchase agreements the accrued interest on termination.
StartCash	[0..1]	Amt	For repurchase agreements the start (dirty) cash consideration.
EndCash	[0..1]	Amt	For repurchase agreements the end (dirty) cash consideration.
Concession	[0..1]	Amt	
TotalTakedown	[0..1]	Amt	
NetMoney	[0..1]	Amt	Value expressed in the currency reflected by the Currency(15) field.
SettlCurrAmt	[0..1]	Amt	
SettlCurrFxRate	[0..1]	float	
SettlCurrFxRateCalc	[0..1]	CodeSet	
PositionEffect	[0..1]	CodeSet	Can be used for derivatives omnibus accounting.
Text	[0..1]	String	Can be used by the executing market to record any execution details that are particular to that market.
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	
SideMultiLegReportingType	[0..1]	CodeSet	Can be used to support the scenario where a single leg instrument trades against an individual leg of a multileg instrument.
ContAmtGrp	[0..*]	Group	
Stipulations	[0..*]	Group	
MiscFeesGrp	[0..*]	Group	
ExchangeRule	[0..1]	String	
TradeAllocIndicator	[0..1]	CodeSet	
TradeAllocGroupInstruction	[0..1]	CodeSet	

Name	Mult.	Type	Description
AllocGroupID	[0..1]	String	
PreviousAllocGroupID	[0..1]	String	Identifies the previous AllocGroupID(1730) being changed by this message when AllocGroupStatus(2767)=3 (Changed).
GroupAmount	[0..1]	Amt	
AllocGroupStatus	[0..1]	CodeSet	
SideAvgPxIndicator	[0..1]	CodeSet	
SideAvgPxGroupID	[0..1]	String	
SideAvgPx	[0..1]	Price	
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	Used to assign an ID to the block of preallocations.
TrdAllocGrp	[0..*]	Group	
SideTrdRegTS	[0..*]	Group	
SettlDetails	[0..*]	Group	Conveys settlement account details reported as part of obligation.
SideGrossTradeAmt	[0..1]	Amt	
AggressorIndicator	[0..1]	CodeSet	
ExchangeSpecialInstructions	[0..1]	String	
SideShortSaleExemptionReason	[0..1]	CodeSet	Optional when Side (54) = 6 (Sell short exempt)
OrderCategory	[0..1]	CodeSet	
SideLiquidityInd	[0..1]	CodeSet	
StrategyLinkID	[0..1]	String	
TradeReportOrderDetail	[0..1]	Component	Order details for the order associated with this side of the trade.
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
TradePositionQty	[0..*]	Group	
RelatedTradeGrp	[0..*]	Group	
RelatedPositionGrp	[0..*]	Group	
BlockTrdAllocIndicator	[0..1]	CodeSet	
SideRiskLimitCheckStatus	[0..1]	CodeSet	
LastCapacity	[0..1]	CodeSet	In the context of regulatory trade reporting, this specifies the trading capacity of the reporting party.
RefRiskLimitCheckID	[0..1]	String	
RefRiskLimitCheckIDType	[0..1]	CodeSet	

Name	Mult.	Type	Description
CompressionGroupID	[0..1]	String	
SideCollateralAmountGrp	[0..*]	Group	

Used in messages: [TradeCaptureReport](#)

#### 180.2.5447 TrdCollGrp

Name	Mult.	Type	Description
NoTrades	[1..1]	NumInGroup	Trades for which collateral is required
TradeReportID	[0..1]	String	Required if NoTrades > 0
SecondaryTradeReportID	[0..1]	String	

Used in messages: [CollateralAssignment](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#)

#### 180.2.5448 TrdgSesGrp

Name	Mult.	Type	Description
NoTradingSessions	[1..1]	NumInGroup	Specifies the number of repeating TradingSessionIDs
TradingSessionID	[0..1]	CodeSet	Required if NoTradingSessions is > 0.
TradingSessionSubID	[0..1]	CodeSet	

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [MarketDataRequest](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [RequestForPositions](#)

#### 180.2.5449 TrdInstrmtLegExecGrp

The TrdInstrmtLegExecGrp component comprises individual executions for legs of the trade side of a trade match report for a specific instrument.



Name	Mult.	Type	Description
NoLegExecs	[1..1]	NumInGroup	
LegRefID	[0..1]	String	Required if NoLegExecs(1892) > 0.
LegExecID	[0..1]	String	
LegExecRefID	[0..1]	String	
LegTradeID	[0..1]	String	
LegTradeReportID	[0..1]	String	
LegOrderQty	[0..1]	Qty	
LegPositionEffect	[0..1]	CodeSet	Can be used to specify the position effect for the leg if it is different from the position effect of the overall multileg security.
LegCoveredOrUncovered	[0..1]	CodeSet	Can be used to specify whether the option is a cover, if it is different from the overall multileg security.
NestedParties3	[0..*]	Group	
LegLastPx	[0..1]	Price	
LegPriceType	[0..1]	CodeSet	
LegSettlCurrency	[0..1]	Currency	
LegSettlCurrencyCodeSource	[0..1]	CodeSet	
LegShortSaleExemptionReason	[0..1]	CodeSet	
LegLastQty	[0..1]	Qty	
LegQtyType	[0..1]	CodeSet	

Used in groups: **TrdMatchSideGrp**

### 180.2.5450 TrdInstrmtLegGrp

Name	Mult.	Type	Description
NoLegs	[1..1]	NumInGroup	
InstrumentLeg	[0..1]	Component	Required if NoLegs(555) > 0.
LegFinancingDetails	[0..1]	Component	
LegPositionAmountData	[0..*]	Group	
LegOrderQty	[0..1]	Qty	Quantity ordered for this leg as provided during order entry.

Name	Mult.	Type	Description
LegQty	[0..1]	Qty	The LegQty(687) field is deprecated. The use of LegOrderQty(685) is recommended instead.
LegMidPx	[0..1]	Price	
LegSwapType	[0..1]	CodeSet	Instead of LegOrderQty(685) requests that the sellside calculate LegOrderQty(685) based on opposite Leg.
LegReportID	[0..1]	String	Additional attribute to store the trade or trade report identifier of the leg.
LegNumber	[0..1]	int	Allow sequencing of legs for a strategy to be captured.
LegStipulations	[0..*]	Group	
LegAccount	[0..1]	String	
LegClearingAccountType	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in ClearingAccountType(1816) in the Instrument component.
LegPositionEffect	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in PositionEffect(77) in the Instrument component.
LegCoveredOrUncovered	[0..1]	CodeSet	Provide if different from the value specified for the overall multileg security in CoveredOrUncovered(203) in the Instrument component.
NestedParties	[0..*]	Group	
LegRefID	[0..1]	String	Use of LegRefID(654) in this component is deprecated. Recommend the use of LegID(1788) in the InstrumentLeg component.
LegSettlType	[0..1]	CodeSet	
LegSettlDate	[0..1]	LocalMktDate	Takes precedence over a calculated LegSettlType(587) when specified regardless of LegSettlType(587) value. Conditionally required when LegSettlType(587) = B(Broken date).
LegLastPx	[0..1]	Price	Used to report the execution price assigned to the leg of the multileg instrument.
LegPriceType	[0..1]	CodeSet	Indicates the price type provided with each leg of a multi-leg trade
LegSettlCurrency	[0..1]	Currency	
LegSettlCurrencyCodeSource	[0..1]	CodeSet	
LegLastForwardPoints	[0..1]	PriceOffset	

Name	Mult.	Type	Description
LegCalculatedCcyLastQty	[0..1]	Qty	
LegGrossTradeAmt	[0..1]	Amt	For FX Futures can be used to express the notional value of a trade when LegLastQty(1418) and other quantity fields are expressed in terms of number of contracts - LegContractMultiplier(231) is required in this case.
LegShortSaleExemptionReason	[0..1]	CodeSet	Available for optional use when LegSide(624) = 6 (Sell short exempt) in InstrumentLeg component.
LegVolatility	[0..1]	float	
LegDividendYield	[0..1]	Percentage	
LegCurrencyRatio	[0..1]	float	
LegExecInst	[0..1]	CodeSet	
LegLastQty	[0..1]	Qty	Quantity executed for this leg.
LegQtyType	[0..1]	CodeSet	Leg quantity type to be specified at the leg level. Can be different for each leg.
LegLastMultipliedQty	[0..1]	Qty	
LegTotalTradeQty	[0..1]	Qty	
LegTotalTradeMultipliedQty	[0..1]	Qty	
LegTotalGrossTradeAmt	[0..1]	Amt	
TradeCapLegUnderlyingsGrp	[0..*]	Group	
LegDifferentialPrice	[0..1]	PriceOffset	

Used in messages: TradeCaptureReport, TradeCaptureReportAck

### 180.2.5451 TrdMatchID

Identifier assigned by a matching system to a match event that results in multiple executions or trades.

Type: String

Used in groups: ExecAllocGrp

Used in messages: ExecutionReport, TradeCaptureReport, TradeCaptureReportAck, TradeCaptureReportRequest, TradeMatchReport, TradeMatchReportAck

**180.2.5452 TrdMatchSideGrp**

The TrdMatchSideGrp component conveys all trade sides for a single instance of the InstrmtMatchSideGrp component.

Name	Mult.	Type	Description
NoTrdMatchSides	[1..1]	NumInGroup	
Side	[0..1]	CodeSet	Required if NoTrdMatchSides(1890) > 0.
SideExecID	[0..1]	String	
SideExecRefID	[0..1]	String	
SideTradeID	[0..1]	String	
SideTradeReportID	[0..1]	String	
OrderDelay	[0..1]	int	
OrderDelayUnit	[0..1]	CodeSet	
SideLastQty	[0..1]	Qty	Required if NoTrdMatchSides(1890) > 0. Used to indicate the matched quantity for this trade side as a result of the match event.
SideClearingTradePrice	[0..1]	Price	
SidePriceDifferential	[0..1]	Price	
SideClearingTradePriceType	[0..1]	CodeSet	
SideFillStationCd	[0..1]	String	
SideReasonCd	[0..1]	String	
SideTrdSubType	[0..1]	CodeSet	
NetGrossInd	[0..1]	CodeSet	
SideCurrency	[0..1]	Currency	
SideCurrencyCodeSource	[0..1]	CodeSet	
SideSettlCurrency	[0..1]	Currency	
SideSettlCurrencyCodeSource	[0..1]	CodeSet	
Parties	[0..*]	Group	Required if NoTrdMatchSides(1890) > 0.
TradeInputSource	[0..1]	String	
TradeInputDevice	[0..1]	String	
ComplianceID	[0..1]	String	
ComplianceText	[0..1]	String	
EncodedComplianceTextLen	[0..1]	Length	Must be set if EncodedComplianceText(2352) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedComplianceText	[0..1]	data	Encoded (non-ASCII characters) representation of the ComplianceText(2404) field in the encoded format specified via the MessageEncoding(347) field.
SolicitedFlag	[0..1]	CodeSet	
CustOrderCapacity	[0..1]	CodeSet	
TimeBracket	[0..1]	String	
PositionEffect	[0..1]	CodeSet	For use in derivatives omnibus accounting.
ExchangeRule	[0..1]	String	
TradeAllocIndicator	[0..1]	CodeSet	
PreallocMethod	[0..1]	CodeSet	
AllocID	[0..1]	String	
TrdAllocGrp	[0..*]	Group	
SideGrossTradeAmt	[0..1]	Amt	
AggressorIndicator	[0..1]	CodeSet	
ExchangeSpecialInstructions	[0..1]	String	
SideShortSaleExemptionReason	[0..1]	CodeSet	
OrderCategory	[0..1]	CodeSet	
AvgPxIndicator	[0..1]	CodeSet	
AvgPxGroupID	[0..1]	String	
SideMarketSegmentID	[0..1]	String	Can be used if the match event results in matches across different market segments for this side.
SideVenueType	[0..1]	CodeSet	Can be used if the match event results in matches across different venue types for this side.
ClearingFeeIndicator	[0..1]	CodeSet	
TradeReportOrderDetail	[0..1]	Component	
TrdInstrmtLegExecGrp	[0..*]	Group	
CustOrderHandlingInst	[0..1]	CodeSet	
OrderHandlingInstSource	[0..1]	CodeSet	
Text	[0..1]	String	Can be used to include text included in the order submission.
EncodedTextLen	[0..1]	Length	
EncodedText	[0..1]	data	

Used in groups: InstrmtMatchSideGrp

**180.2.5453 TrdMatchSubID**

Used to identify each price level, step or clip within a match event.

Type: **String**

Used in groups: **InstrmtMatchSideGrp**

Used in messages: **ExecutionReport**

**180.2.5454 TrdRegPublicationGrp**

The TrdRegPublicationGrp component is used to express trade publication reasons that are required by regulatory agencies. Reasons may include deferrals, exemptions, waivers, etc.

Name	Mult.	Type	Description
NoTrdRegPublications	[1..1]	NumInGroup	
TrdRegPublicationType	[0..1]	CodeSet	Required if NoTrdRegPublications(2668) > 0.
TrdRegPublicationReason	[0..1]	CodeSet	

Used in groups: **ExecAllocGrp**, **MDFullGrp**, **MDIncGrp**

Used in messages: **ExecutionReport**, **NewOrderSingle**, **TradeCaptureReport**

**180.2.5455 TrdRegPublicationReason**

Additional reason for trade publication type specified in TrdRegPublicationType(2669).

Reasons may be specific to regulatory trade publication rules.

Type: **int**

Allowed values in TrdRegPublicationReasonCodeSet:

Code	Name	Description
0	NoBookOrderDueToAverageSpread-Price	No preceding order in book as transaction price set within average spread of a liquid instrument. Per MiFIR Article 4(1)(b)(i) the obligation to place a public order can be waived for transactions of liquid instruments on "systems that formalise negotiated transactions which are made within the current volume weighted spread reflected on the order book or the quotes of the market makers of the trading venue operating that system, subject to the conditions set out in Article 5" of MiFIR on volume caps. "Liquid markets" as per MiFIR Article 2(17)(b) are assessed by the regulator for the purposes of MiFIR Articles 4, 5 and 14. For ESMA RTS 1, RTS 6 and RTS 22 this is the waiver "NLIQ" flag.
1	NoBookOrderDueToRefPrice	No preceding order in book as transaction price depends on system-set reference price for an illiquid instrument. Per MiFIR Article 4(1)(b)(ii) the obligation to place a public order can be waived for "negotiated transactions which are in an illiquid share, depositary receipt, ETF, certificate or other similar financial instrument that does not fall within the meaning of a liquid market, and are dealt within a percentage of a suitable reference price, being a percentage and a reference price set in advance by the system operator." For ESMA RTS 1, this is the "OILQ" flag.
2	NoBookOrderDueToOtherConditions	No preceding order in book as transaction price is for transaction subject to conditions other than current market price. Per MiFIR Article 4(1)(b)(iii), the obligation to place a public order can be waived in "systems that formalise negotiated transactions which are subject to conditions other than the current market price of that financial instrument." For ESMA RTS1, RTS 6 and RTS 22 this is the waiver flag "PRIC".
3	NoPublicPriceDueToRefPrice	No public price for preceding order as public reference price was used for matching orders. Per MiFIR Article 4(1)(a) the obligation to place a public order can be waived for "systems matching orders based on a trading methodology by which the price of the financial instrument is derived from the trading venue where that financial instrument was first admitted to trading or the most relevant market in terms of liquidity, where that reference price is widely published and is regarded by market participants as a reliable reference price." For ESMA RTS 1, RTS 6 and RTS 22 this is the waiver flag "RFPT".

Code	Name	Description
4	NoPublicPriceDueToIlliquid	No public price quoted as instrument is illiquid. According to MiFIR Article 4(1)(b)(ii) and Article 14(1) the obligation to publish the quote prior to closing the trade may be waived if it was made in an illiquid instrument. However, according to MiFIR Article 14(1) and Article 18(2), systematic internalisers shall still disclose quotes to their clients upon request. This obligation may also be waived in case of bonds, structured finance products, emission allowances and derivatives. For ESMA RTS 1, RTS 2, RTS 6 and RTS 22 this is the waiver flag "ILQD".
5	NoPublicPriceDueToOrderSize	No public price quoted due to "Size". In the context of ESMA, as per MiFIR Article 4(1)(c) and Article 14(2), the systematic internaliser was not obliged to quote prior to closing the trade as the trade was above the standard market size. In accordance to MiFIR Article 9(1)(b) and Article 18(10), market operators, investment firms and systematic internalisers may be waived, in accordance to guidance from the Competent Authorities, from making public prices for derivative instruments which are above a size specific to the instrument. For ESMA RTS 1, RTS 2, RTS 6 and RTS 22 this is the waiver flag "SIZE".
6	DeferralDueToLargeInScale	Deferral due to "Large in Scale". Per MiFID Article 14, publication deferral is permitted if the transaction is large in scale compared to a standard market size, as set in RTS 1/Annex II (thresholds for "large in scale") and RTS 2/Annex III ("LIS and SSTI thresholds"). For ESMA RTS 1 and RTS 2, this is the "LRGS" flag.
7	DeferralDueToIlliquid	Deferral due to "Illiquid Instrument". Publication deferral is permitted if the transaction's instrument is illiquid, as defined by regulator's stipulation. For ESMA RTS 2, this is the "ILQD" flag.
8	DeferralDueToSizeSpecific	Deferral due to "Size Specific". Per MiFIR Article 11, publication deferral is permitted if the transaction is greater than the stipulated 'Size Specific to the financial instrument' threshold. For ESMA RTS 2, this is the "SIZE" flag.
9	NoPublicPriceDueToLargeInScale	No public price and/or size quoted as transaction is "large in scale". In the context of ESMA, as per MiFIR Article 4(1)(c) and Article 9(1)(a), the trading venue was not obliged to quote prior to closing the trade as the order size was above normal market size.



Code	Name	Description
10	NoPublicPriceSizeDueToOrderHidden	No public price and/or size quoted due to order being hidden. In the context of ESMA, as per MiFIR Article 4(1)(d) and Article 9(1)(a), a transaction arising from an order that was not fully pre-trade transparent due to all or part of it being held in a trading venue order management facility, such as a reserve order.
11	ExemptedDueToSecuritiesFinancing-Transaction	Exempted due to securities financing transaction. Per ESMA RTS 22, Annex I, Table 2, Field 65: a transaction which "falls within the scope of activity but is exempted from reporting under Securities Financing Transaction Regulation".
12	ExemptedDueToESCBPolicyTransaction	Exempted due to European System of Central Banks (ESCB) policy transaction. Per ESMA RTS2, Article 14(1), and Article 15(1): "A transaction shall be considered to be entered into by a member of the European System of Central Banks (ESCB) in performance of monetary, foreign exchange and financial stability policy [is exempted from publication] ... [The regulation] shall not apply to the following types of transaction entered into by a member of the ESCB for the performance of one of the tasks referred to in Article 14: transaction entered into for the management of its own funds; transaction entered into for administrative purposes or for the staff of the member of the ESCB which include transactions conducted in the capacity as administrator of a pension scheme for its staff; transactions entered into for its investment portfolio pursuant to obligations under national law."
13	ExceptionDueToReportByPaper	Exception due to report by paper. Incomplete report due to submission by paper (form). In the context of US CAT this is Form T pursuant to FINRA Trade Reporting Rules.
14	ExceptionDueToTradeExecutedWith-NonReportingParty	Exception due to trade with non-reporting party. Incomplete report due to counterparty of the reporting party being absent. In the context of US CAT this is when a trade was executed by a non-FINRA member and reported to the TRF by the FINRA member counterparty.
15	ExceptionDueToIntraFirmOrder	Exception due to intra-firm order. Incomplete report due to intra-firm order filled from firm's proprietary account.

Code	Name	Description
16	ReportedOutsideReportingHours	Reported outside of reporting hours. In the context of ESMA, trades published after the trade reporting facility being used (e.g. APA for trades brought onto a trading venue) closes, will be reported the following business day and not flagged as deferred (as the MiFID deferral regime is not applicable). This value distinguishes these types of trades from trades executed (and published) on the same business day. It is recommended that this value be set by the trade reporting facility, e.g. APAs, (as opposed to publishing investment firms) to ensure the most accurate use of this value.
17	NoPublicPxDueToPreTradeWaiver	No public price quoted due to usage of a pre-trade transparency waiver. Per FCA policy statement PS23/4, this is the "NETW" flag for negotiated trades in accordance to MiFIR Article 4(1)(b).

Used in groups: **TrdRegPublicationGrp**

## 180.2.5456 TrdRegPublicationType

Specifies the type of regulatory trade publication.

Additional reasons for the publication type may be specified in TrdRegPublicationReason(2670).

Type: **int**

Allowed values in TrdRegPublicationTypeCodeSet:

Code	Name	Description
0	PreTradeTransparencyWaiver	Pre-trade transparency waiver. There are allowable waivers from the obligation to make public current bid/offer prices and trading depth. In the context of MiFIR, see Article 3 and Article 4.
1	PostTradeDeferral	Post-trade deferral. There are allowable deferrals for the post-trade publication of trade transactions. In the context of MiFIR, see Article 7(1).
2	ExemptFromPublication	Exempt from publication. There are allowable exemptions for the post-trade publication of trade transactions. In the context of ESMA exemptions are specified in RTS 22 Annex I, Table 2, Field 65 and RTS 2 Article 14(1) and Article 15(1).

Code	Name	Description
3	OrderLevelPublicationToSubscribers	Order level publication to subscribers. Individual orders are displayed outside of the execution venue but only to subscribers. In the context of US CAT this can be used by Alternative Trading Systems (ATs) to provide additional information related to price distribution.
4	PriceLevelPublicationToSubscribers	Price level publication to subscribers. Aggregated orders are displayed outside of the execution venue but only to subscribers. In the context of US CAT this can be used by Alternative Trading Systems (ATs) to provide additional information related to price distribution.
5	OrderLevelPublicationToThePublic	Order level publication to the public. Individual orders are displayed outside of the execution venue via public quotation. In the context of US CAT this can be used by Alternative Trading Systems (ATs) to provide additional information related to price distribution.
6	PublicationInternalToExecutionVenue	Publication internal to execution venue. Orders are not displayed outside of the execution venue. In the context of US CAT this can be used by Alternative Trading Systems (ATs) to provide additional information related to price distribution.

Used in groups: **TrdRegPublicationGrp**

#### **180.2.5457 TrdRegTimestamp**

Traded / Regulatory timestamp value.

Type: **UTCTimestamp**

Used in groups: **TrdRegTimestamps**

#### **180.2.5458 TrdRegTimestampManualIndicator**

Indicates whether a given timestamp was manually captured.

Type: **Boolean**

Allowed values in TrdRegTimestampManualIndicatorCodeSet:

Code	Name	Description
N	NotManuallyCaptured	Not manually captured
Y	ManuallyCaptured	Manually captured

Used in groups: **TrdRegTimestamps**

### 180.2.5459 TrdRegTimestampOrigin

Text which identifies the "origin" (i.e. system which was used to generate the timestamp) for the Traded / Regulatory timestamp value.

Type: **String**

Used in groups: **TrdRegTimestamps**

### 180.2.5460 TrdRegTimestamps

The TrdRegTimestamps component block is used to express timestamps for an order or trade that are required by regulatory agencies. These timestamps are used to identify the timeframes for when an order or trade is received on the floor, received and executed by the broker, etc.

Name	Mult.	Type	Description
NoTrdRegTimestamps	[1..1]	NumInGroup	
TrdRegTimestamp	[0..1]	UTCTimestamp	Required if NoTrdRegTimestamps(768) > 0.
TrdRegTimestampType	[0..1]	CodeSet	Required if NoTrdRegTimestamps(768) > 0.
TrdRegTimestampOrigin	[0..1]	String	
TrdRegTimestampManualIndicator	[0..1]	CodeSet	
DeskType	[0..1]	CodeSet	
DeskTypeSource	[0..1]	CodeSet	
DeskOrderHandlingInst	[0..1]	CodeSet	
InformationBarrierID	[0..1]	String	
NBBOEntryType	[0..1]	CodeSet	May be used with TrdRegTimestampType(770)=34 (Reference time for NBBO).
NBBOPrice	[0..1]	Price	May be used with TrdRegTimestampType(770)=34 (Reference time for NBBO).
NBBOQty	[0..1]	Qty	May be used with TrdRegTimestampType(770)=34 (Reference time for NBBO).

Name	Mult.	Type	Description
NBBOSource	[0..1]	CodeSet	May be used with TrdRegTimestampType(770)=34 (Reference time for NBBO).

Used in messages: [AllocationInstruction](#), [AllocationReport](#), [CollateralAssignment](#), [CollateralInquiry](#), [CollateralReport](#), [CollateralRequest](#), [CollateralResponse](#), [Confirmation](#), [ExecutionReport](#), [MarginRequirementReport](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#), [PositionReport](#), [Quote](#), [QuoteStatusReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.5461 TrdRegTimestampType

Trading / Regulatory timestamp type.

Type: [int](#)

Allowed values in TrdRegTimestampTypeCodeSet:

Code	Name	Description
1	ExecutionTime	Execution time. Timestamp for the order execution. In the context of US futures markets (CFTC regulated) this is the non-qualified reporting time of order execution.
2	TimeIn	Time in. Timestamp for receiving an order, quote or trade. In the context of US futures markets (CFTC) this is the timestamp of when the order was received on the trading floor (booth).
3	TimeOut	Time out. Timestamp for sending an order, quote or trade. In the context of US futures markets (CFTC) this is the timestamp when the trade was received from the pit.
4	BrokerReceipt	Broker receipt. Timestamp for a broker receiving an order, quote or trade. In the context of US futures markets (CFTC) this is the time at which the broker received the order.
5	BrokerExecution	Broker execution. Timestamp for the broker executing an order. In the context of US futures markets (CFTC regulated) this is the time at which a broker executed the order for another broker.
6	DeskReceipt	Desk receipt. Timestamp for the transmission of an order to an internal desk or department on the same day the firm received the order.
7	SubmissionToClearing	Submission to clearing. The timestamp when the trade was officially acknowledged by the Clearing House.

Code	Name	Description
8	TimePriority	Time priority. A timestamp (manually or electronically) assigned by a market to specify time priority for an order or quote.
9	OrderbookEntryTime	Orderbook entry time. Timestamp for an order representing the time it was entered in the orderbook of the execution venue. The orderbook entry time cannot change during the lifetime of the order.
10	OrderSubmissionTime	Order submission time. Time the order was sent by the submitter.
11	PubliclyReported	Publicly reported. In the context of MiFID II, this is used to identify the time at which the transaction was first published to the market.
12	PublicReportUpdated	Public report updated. In the context of MiFID II, this is used to identify the time at which the transaction's publication to the market was last updated
13	NonPubliclyReported	Non-publicly reported
14	NonPublicReportUpdated	Non-public report updated
15	SubmittedForConfirmation	Submitted for confirmation
16	UpdatedForConfirmation	Updated for confirmation
17	Confirmed	Confirmed
18	UpdatedForClearing	Updated for clearing
19	Cleared	Cleared
20	AllocationsSubmitted	Allocations submitted
21	AllocationsUpdated	Allocations updated
22	AllocationsCompleted	Allocations completed
23	SubmittedToRepository	Submitted to repository
24	PostTrdContntnEvnt	Post-trade continuation event
25	PostTradeValuation	Post-trade valuation
26	PreviousTimePriority	Previous time priority. Can be used in conjunction with TrdRegTimestampType(770) = 8 (Time priority) to provide the current and last priority timestamp in a single message.
27	IdentifierAssigned	Identifier assigned. Timestamp for the assignment of a (unique) identifier to an entity (e.g. order, quote, trade).
28	PreviousIdentifierAssigned	Previous identifier assigned. Timestamp of previous assignment of a (unique) identifier to an entity (e.g. order, quote, trade).
29	OrderCancellationTime	Order cancellation time. Timestamp for the cancellation of an order or quote.

Code	Name	Description
30	OrderModificationTime	Order modification time. Timestamp for the modification of an order or quote.
31	OrderRoutingTime	Order routing time. Timestamp for the routing of an order to another broker or electronic execution venue.
32	TradeCancellationTime	Trade cancellation time. Timestamp for the cancellation of an execution (ExecType(150) = H (Trade Cancel)) or trade (TradeReportType(856) = 6 (Trade Report Cancel)).
33	TradeModificationTime	Trade modification time. Timestamp for the modification of an execution (ExecType(150) = G (Trade Correct)) or trade (TradeReportType(856) = 5 (No/Was)).
34	ReferenceTimeForNBBO	Reference time for NBBO. Timestamp for an NBBO reference price.
35	Affirmed	Affirmed

Used in groups: **TrdRegTimestamps**

#### 180.2.5462 TrdRepIndicator

Specifies whether the trade should be reported (or not) to parties of the provided TrdRepPartyRole(1388). Used to override standard reporting behavior by the receiver of the trade report and thereby complements the PublTrdIndicator( tag1390).

Type: **Boolean**

Used in groups: **TrdRepIndicatorsGrp**

#### 180.2.5463 TrdRepIndicatorsGrp

Name	Mult.	Type	Description
NoTrdRepIndicators	[1..1]	NumInGroup	Number of trade publication indicators following
TrdRepPartyRole	[0..1]	CodeSet	
TrdRepIndicator	[0..1]	Boolean	

Used in messages: **TradeCaptureReport**, **TradeCaptureReportAck**

**180.2.5464 TrdRepPartyRole**

Identifies the type of party for trade reporting. Same values as PartyRole(452).

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)



Code	Name	Description
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit

Code	Name	Description
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity

Code	Name	Description
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower

Code	Name	Description
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: [TrdRepIndicatorsGrp](#)

### 180.2.5465 TrdRptStatus

Trade Report Status

Type: [int](#)

Allowed values in TrdRptStatusCodeSet:

Code	Name	Description
0	Accepted	Accepted
1	Rejected	Rejected
2	Cancelled	Cancelled
3	AcceptedWithErrors	Accepted with errors
4	PendingNew	Pending New
5	PendingCancel	Pending Cancel
6	PendingReplace	Pending Replace
7	Terminated	Terminated
8	PendingVerification	Pending verification. Used in reports from the SDR to the regulator and to trading parties to indicate that the trade details have not been verified by one or both parties.
9	DeemedVerified	Deemed verified. Used in reports from the SDR to the regulator and to trading parties to indicate that the trade details are deemed verified by the SDR but have not been confirmed by the trading parties.
10	Verified	Verified. Used in reports from the SDR to the regulator and to trading parties to indicate that the trade details have been confirmed by the trading parties.
11	Disputed	Disputed. Used in reports from the SDR to the regulator and to trading parties to indicate that the trade details have been disputed by a trading party.

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

### 180.2.5466 TrdSessLstGrp

Name	Mult.	Type	Description
NoTradingSessions	[1..1]	NumInGroup	
TradingSessionID	[1..1]	CodeSet	Identifier for Trading Session
TradingSessionSubID	[0..1]	CodeSet	
TradSesUpdateAction	[0..1]	CodeSet	
SecurityExchange	[0..1]	Exchange	
MarketID	[0..1]	Exchange	Market for which Trading Session applies
MarketSegmentID	[0..1]	String	Market Segment for which Trading Session applies
TradingSessionDesc	[0..1]	String	
TradSesMethod	[0..1]	CodeSet	Method of Trading
TradSesMode	[0..1]	CodeSet	Trading Session Mode
UnsolicitedIndicator	[0..1]	CodeSet	"Y" if message is sent unsolicited as a result of a previous subscription request.
TradSesStatus	[1..1]	CodeSet	State of trading session.
TradSesStatusRejReason	[0..1]	CodeSet	Used with TradSesStatus = "Request Rejected"
TradSesStartTime	[0..1]	UTCTimestamp	Starting time of trading session
TradSesOpenTime	[0..1]	UTCTimestamp	Time of the opening of the trading session
TradSesPreCloseTime	[0..1]	UTCTimestamp	Time of pre-close of trading session
TradSesCloseTime	[0..1]	UTCTimestamp	Closing time of trading session
TradSesEndTime	[0..1]	UTCTimestamp	End time of trading session
TotalVolumeTraded	[0..1]	Qty	
TradingSessionRules	[0..1]	Component	Insert here the set of "TradingSessionRules" fields defined in "common components of application messages"
TransactTime	[0..1]	UTCTimestamp	
Text	[0..1]	String	
EncodedTextLen	[0..1]	Length	Must be set if EncodedText field is specified and must immediately precede it.
EncodedText	[0..1]	data	Encoded (non-ASCII characters) representation of the Text field in the encoded format specified via the MessageEncoding field.

Used in messages: [TradingSessionList](#), [TradingSessionListUpdateReport](#)

**180.2.5467 TrdSubType**

Further qualification to the trade type defined in TrdType(828).

Type: **int**

Allowed values in TrdSubTypeCodeSet:

Code	Name	Description
0	CMTA	CMTA
1	InternalTransferOrAdjustment	Internal transfer or adjustment
2	ExternalTransferOrTransferOfAccount	External transfer or transfer of account
3	RejectForSubmittingSide	Reject for submitting side
4	AdvisoryForContraSide	Advisory for contra side
5	OffsetDueToAnAllocation	Offset due to an allocation
6	OnsetDueToAnAllocation	Onset due to an allocation
7	DifferentialSpread	Differential spread
8	ImpliedSpreadLegExecutedAgainstAnOutright	Implied spread leg executed against an outright
9	TransactionFromExercise	Transaction from exercise
10	TransactionFromAssignment	Transaction from assignment
11	ACATS	ACATS
14	AI	AI (Automated input facility disabled in response to an exchange request.)
15	B	B (Transaction between two member firms where neither member firm is registered as a market maker in the security in question and neither is a designated fund manager. Also used by broker dealers when dealing with another broker which is not a member firm. Non-order book securities only.)
16	K	K (Transaction using block trade facility.)
17	LC	LC (Correction submitted more than three days after publication of the original trade report.)
18	M	M (Transaction, other than a transaction resulting from a stock swap or stock switch, between two market makers registered in that security including IDB or a public display system trades. Non-order book securities only.)
19	N	N (Non-protected portfolio transaction or a fully disclosed portfolio transaction)

Code	Name	Description
20	NM	NM ( i) transaction where Exchange has granted permission for non-publication. ii)IDB is reporting as seller. iii) submitting a transaction report to the Exchange, where the transaction report is not also a trade report.)
21	NR	NR (Non-risk transaction in a SEATS security other than an AIM security)
22	P	P (Protected portfolio transaction or a worked principal agreement to effect a portfolio transaction which includes order book securities)
23	PA	PA (Protected transaction notification)
24	PC	PC (Contra trade for transaction which took place on a previous day and which was automatically executed on the Exchange trading system)
25	PN	PN (Worked principal notification for a portfolio transaction which includes order book securities)
26	R	R ( (i) riskless principal transaction between non-members where the buying and selling transactions are executed at different prices or on different terms (requires a trade report with trade type indicator R for each transaction). (ii) market maker is reporting all the legs of a riskless principal transaction where the buying and selling transactions are executed at different prices (requires a trade report with trade type indicator R for each transaction)or. (iii) market maker is reporting the onward leg of a riskless principal transaction where the legs are executed at different prices, and another market maker has submitted a trade report using trade type indicator M for the first leg (this requires a single trade report with trade type indicator R).)
27	RO	RO (Transaction which resulted from the exercise of a traditional option or a stock-settled covered warrant)
28	RT	RT (Risk transaction in a SEATS security, (excluding AIM security) reported by a market maker registered in that security)
29	SW	SW (Transactions resulting from stock swap or a stock switch (one report is required for each line of stock))
30	T	T (If reporting a single protected transaction)
31	WN	WN (Worked principal notification for a single order book security)
32	WT	WT (Worked principal transaction (other than a portfolio transaction))
33	OffHoursTrade	Off Hours Trade



Code	Name	Description
34	OnHoursTrade	On Hours Trade
35	OTCQuote	OTC Quote
36	ConvertedSWAP	Converted SWAP
37	CrossedTrade	Crossed Trade (X)
38	InterimProtectedTrade	Interim Protected Trade (I)
39	LargeInScale	Large in Scale (L)
40	WashTrade	Wash Trade
41	TradeAtSettlement	Trade at Settlement (TAS). Identifies a trade that will be priced using the settlement price.
42	AuctionTrade	Auction Trade. Mutually exclusive with TrdSubType(829) = 50 (Balancing).
43	TradeAtMarker	Trade at Marker (TAM). Posted at a specific time each day and used to price the consummated trade for the product/month/strip executed (+/- and differentials). Closely related to TAS trades in function and trade practice.
44	CreditDefault	Default (Credit Event)
45	CreditRestructuring	Restructuring (credit event)
46	Merger	Merger (succession event)
47	SpinOff	Spin-off (succession event)
48	MultilateralCompression	Multilateral compression. Used to identify a special case of compression between multiple parties, e.g. for netted or portfolio trades.
50	Balancing	Balancing. Identifies an additional trade distributed to auction participants meant to resolve an imbalance between bids and offers. Mutually exclusive with TrdSubType(829) = 42 =(Auction).
51	BasisTradeIndexClose	Basis Trade index Close (BTIC). The marketplace name given to Trade at Marker (TAM) transactions in equity index futures.
52	TradeAtCashOpen	Trade At Cash Open (TACO). The marketplace name given to trading futures based on an opening quote of the underlying cash market.
53	TrdSubmitVenueClrSettl	Trade submitted to venue for clearing and settlement. Identifies trades brought on a trading venue purely for clearing and settlement purposes.
54	BilateralCompression	Bilateral compression. Used to identify a special case of compression between two parties, e.g. for netted or portfolio trades.

Used in groups: **MDFullGrp**, **MDIncGrp**

Used in messages: [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [Confirmation](#), [ExecutionReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#), [TradeMatchReport](#)

### 180.2.5468 TrdType

Type of trade assigned to a trade. SecondaryTrdType(855) and TertiaryTrdType(2896) may be used in addition to TrdType(828) to assign up to three different trade types to a single trade.

Type: [int](#)

Allowed values in TrdTypeCodeSet:

Code	Name	Description
0	RegularTrade	Regular trade
1	BlockTrade	Block trade
2	EFP	Exchange for physical (EFP)
3	Transfer	Transfer
4	LateTrade	Late trade
5	TTrade	T trade
6	WeightedAveragePriceTrade	Weighted average price trade
7	BunchedTrade	Bunched trade
8	LateBunchedTrade	Late bunched trade
9	PriorReferencePriceTrade	Prior reference price trade
10	AfterHoursTrade	After hours trade
11	ExchangeForRisk	Exchange for risk (EFR)
12	ExchangeForSwap	Exchange for swap (EFS)
13	ExchangeOfFuturesFor	Exchange of futures for in market futures (EFM). For example full sized for mini.
14	ExchangeOfOptionsForOptions	Exchange of options for options (EOO)
15	TradingAtSettlement	Trading at settlement
16	AllOrNone	All or none
17	FuturesLargeOrderExecution	Futures large order execution
18	ExchangeOfFuturesForFutures	Exchange of futures for external market futures (EFF)
19	OptionInterimTrade	Option interim trade
20	OptionCabinetTrade	Option cabinet trade
22	PrivatelyNegotiatedTrades	Privately negotiated trade

Code	Name	Description
23	SubstitutionOfFuturesForForwards	Substitution of futures for forwards
24	ErrorTrade	Error trade
25	SpecialCumDividend	Special cum dividend (CD)
26	SpecialExDividend	Special ex dividend (XD)
27	SpecialCumCoupon	Special cum coupon (CC)
28	SpecialExCoupon	Special ex coupon (XC)
29	CashSettlement	Cash settlement (CS)
30	SpecialPrice	Special price (SP). Usually net or all-in price.
31	GuaranteedDelivery	Guaranteed delivery (GD)
32	SpecialCumRights	Special cum rights (CR)
33	SpecialExRights	Special ex rights (XR)
34	SpecialCumCapitalRepayments	Special cum capital repayments (CP)
35	SpecialExCapitalRepayments	Special ex capital repayments (XP)
36	SpecialCumBonus	Special cum bonus (CB)
37	SpecialExBonus	Special ex bonus (XB)
38	LargeTrade	Block trade. The same as large trade.
39	WorkedPrincipalTrade	Worked principal trade
40	BlockTrades	Block trades
41	NameChange	Name change
42	PortfolioTransfer	Portfolio transfer
43	ProrogationBuy	Prorogation buy. Used by Euronext Paris only. Is used to defer settlement under French SRD (deferred settlement system). Trades must be reported as crosses at zero price.
44	ProrogationSell	Prorogation sell. See prorogation buy.
45	OptionExercise	Option exercise
46	DeltaNeutralTransaction	Delta neutral transaction
47	FinancingTransaction	Financing transaction
48	NonStandardSettlement	Non-standard settlement
49	DerivativeRelatedTransaction	Derivative related transaction

Code	Name	Description
50	PortfolioTrade	Portfolio trade. Identifies a collection/basket of trades. In the context of bonds (e.g. corporate bonds) these are transacted as a single trade at an aggregate price for the entire portfolio and may be traded all-or-none or most-or-none depending on bilateral agreement. In the context of ESMA RTS 1 Article 2(b), may be used to refer to portfolio trades to distinguish between addressable and non-addressable volume. In the context of Market Model Typology (MMT), use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
51	VolumeWeightedAverageTrade	Volume weighted average trade
52	ExchangeGrantedTrade	Exchange granted trade
53	RepurchaseAgreement	Repurchase agreement
54	OTC	OTC. Trade executed off-market. In the context of CFTC regulatory reporting for swaps, it is a large notional off-facility swap. In the context of MiFID transparency reporting rules this is used to report, into an exchange, deals made outside exchange rules.
55	ExchangeBasisFacility	Exchange basis facility (EBF)
56	OpeningTrade	Opening trade. Identifies a trade that resulted from the opening of a market. In the context of IIROC, this indicates a trade that occurred at the opening or the first trade of the day for a security.
57	NettedTrade	Netted trade
58	BlockSwapTrade	Block swap trade. Block trade executed off-market or on a registered market. In the context of CFTC regulatory reporting for swaps, it is a swap executed according to SEF or DCM rules.
59	CreditEventTrade	Credit event trade
60	SuccessionEventTrade	Succession event trade
61	GiveUpGiveInTrade	Give-up Give-in trade
62	DarkTrade	Dark trade. In the context of Market Model Typology (MMT), a dark trade might also come from a lit/hybrid book (e.g. when an aggressive lit order hits a resting dark order). The use of this value applies to TrdType(828), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
63	TechnicalTrade	Technical trade

Code	Name	Description
64	Benchmark	Benchmark. In the context of ESMA RTS 1 Article 2(a), may be used to refer to benchmark trades. In the context of Market Model Typology (MMT), the "benchmark" price depends on a benchmark which has no current price but was derived from a time series such as a VWAP. The use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
65	PackageTrade	Package trade. May be used to identify the pseudo-trade of a stream or collection of trades to be transacted, cleared and be reported as an atomic unit. In the context of MiFIR RTS 1, this is the "CONT" flag. In the context of MiFIR RTS 2 Article 1(1)(b), may be used to refer to package transactions (excluding exchange for physicals). In the context of Market Model Typology (MMT), use of this value applies to SecondaryTrdType(855) or TertiaryTrdType(2896), and when used for MMT market data publication requires MDEntryType(269) = 2 (Trade).
66	RollTrade	Roll trade. Trade is a roll from one contract that is about to expire to a new contract.
67	ClosingPriceTrade	Closing price trade. Identifies a trade that uses the closing price of a market without resulting from the closing of this market. In the context of FCA policy statement PS23/4, this indicates a benchmark transaction executed using the market closing price and is the "CLSE" flag.
68	InterFundTransferTrade	Inter-fund transfer trade. Administrative trade (non price-forming) related to the transfer of ownership between funds.
69	NetAssetValueCalculatedTrade	Net asset value calculated trade. Trade of a fund priced at the net asset value of its constituents. In the context of MiFIR RTS 1, this may be used for ETFs when the NAV price becomes available.

Used in groups: **MDFullGrp**, **MDIncGrp**, **QuotReqGrp**

Used in messages: **AllocationInstruction**, **AllocationInstructionAlert**, **AllocationReport**, **Confirmation**, **ExecutionReport**, **Quote**, **QuoteResponse**, **TradeCaptureReport**, **TradeCaptureReportAck**, **TradeCaptureReportRequest**, **TradeMatchReport**

**180.2.5469 TriggerAction**

Defines the type of action to take when the trigger hits.

Type: **char**

Allowed values in TriggerActionCodeSet:

Code	Name	Description
1	Activate	Activate
2	Modify	Modify
3	Cancel	Cancel

Used in components: **TriggeringInstruction**

**180.2.5470 Triggered**

Indicates whether order has been triggered during its lifetime. Applies to cases where original information, e.g. OrdType(40), is modified when the order is triggered.

Type: **int**

Allowed values in TriggeredCodeSet:

Code	Name	Description
0	NotTriggered	Not triggered (default)
1	Triggered	Triggered
2	StopOrderTriggered	Stop order triggered
3	OCOOrderTriggered	One Cancels the Other (OCO) order triggered
4	OTOOrderTriggered	One Triggers the Other (OTO) order triggered
5	OUOOrderTriggered	One Updates the Other (OUO) order triggered

Used in messages: **ExecutionReport**

**180.2.5471 TriggeringInstruction**

The TriggeringInstruction component block specifies the conditions under which an order will be triggered by related market events as well as the behavior of the order in the market once it is triggered.

Name	Mult.	Type	Description
TriggerType	[0..1]	CodeSet	Required if any other Triggering tags are specified.
TriggerAction	[0..1]	CodeSet	
TriggerScope	[0..1]	CodeSet	Conditionally required when TriggerAction(1101)=3 (Cancel).
TriggerPrice	[0..1]	Price	Only relevant and required for TriggerAction = 1
TriggerSymbol	[0..1]	String	Only relevant and required for TriggerAction = 1
TriggerSecurityID	[0..1]	String	Requires TriggerSecurityIDSource if specified. Only relevant and required for TriggerAction = 1
TriggerSecurityIDSource	[0..1]	CodeSet	Requires TriggerSecurityIDSource if specified. Only relevant and required for TriggerAction = 1
TriggerSecurityDesc	[0..1]	String	
TriggerPriceType	[0..1]	CodeSet	Only relevant for TriggerAction = 1
TriggerPriceTypeScope	[0..1]	CodeSet	Only relevant for TriggerAction = 1
TriggerPriceDirection	[0..1]	CodeSet	Only relevant for TriggerAction = 1
TriggerNewPrice	[0..1]	Price	Should be specified if the order changes Price.
TriggerOrderType	[0..1]	CodeSet	Should be specified if the order changes type.
TriggerNewQty	[0..1]	Qty	Required if the order should change quantity
TriggerTradingSessionID	[0..1]	CodeSet	Only relevant and required for TriggerType = 2.
TriggerTradingSessionSubID	[0..1]	CodeSet	Requires TriggerTradingSessionID if specified. Relevant for TriggerType = 2 only.

Used in groups: [ListOrdGrp](#)

Used in messages: [CrossOrderCancelReplaceRequest](#), [ExecutionReport](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [OrderCancelReplaceRequest](#)

### 180.2.5472 TriggerNewPrice

The Price that the order should have after the trigger has hit. Could be applicable for any trigger type, but must be specified for Trigger Type 1.

Type: [Price](#)

Used in components: [TriggeringInstruction](#)

### 180.2.5473 TriggerNewQty

The Quantity the order should have after the trigger has hit.

Type: Qty

Used in components: TriggeringInstruction

#### 180.2.5474 TriggerOrderType

The OrdType the order should have after the trigger has hit. Required to express orders that change from Limit to Market. Other values from OrdType (40) may be used if appropriate and bilaterally agreed upon.

Type: char

Allowed values in TriggerOrderTypeCodeSet:

Code	Name	Description
1	Market	Market
2	Limit	Limit

Used in components: TriggeringInstruction

#### 180.2.5475 TriggerPrice

The price at which the trigger should hit.

Type: Price

Used in components: TriggeringInstruction

#### 180.2.5476 TriggerPriceDirection

The side from which the trigger price is reached.

Type: char

Allowed values in TriggerPriceDirectionCodeSet:

Code	Name	Description
U	Up	Trigger if the price of the specified type goes UP to or through the specified Trigger Price.



Code	Name	Description
D	Down	Trigger if the price of the specified type goes DOWN to or through the specified Trigger Price.

Used in components: [TriggeringInstruction](#)

### 180.2.5477 TriggerPriceType

The type of price that the trigger is compared to.

Type: [char](#)

Allowed values in TriggerPriceTypeCodeSet:

Code	Name	Description
1	BestOffer	Best Offer
2	LastTrade	Last Trade
3	BestBid	Best Bid
4	BestBidOrLastTrade	Best Bid or Last Trade
5	BestOfferOrLastTrade	Best Offer or Last Trade
6	BestMid	Best Mid

Used in components: [TriggeringInstruction](#)

### 180.2.5478 TriggerPriceTypeScope

Defines the type of price protection the customer requires on their order.

Type: [char](#)

Allowed values in TriggerPriceTypeScopeCodeSet:

Code	Name	Description
0	None	None
1	Local	Local (Exchange, ECN, ATS)
2	National	National (Across all national markets)
3	Global	Global (Across all markets)

Used in components: [TriggeringInstruction](#)

### **180.2.5479 TriggerScope**

Defines the scope of TriggerAction(1101) when it is set to "cancel" (3).

Type: [int](#)

Allowed values in TriggerScopeCodeSet:

Code	Name	Description
0	ThisOrder	This order (default)
1	OtherOrder	Other order (use RefID)
2	AllOtherOrdersForGivenSecurity	All other orders for the given security
3	AllOtherOrdersForGivenSecurityAnd-Price	All other orders for the given security and price
4	AllOtherOrdersForGivenSecurityAnd-Side	All other orders for the given security and side
5	AllOtherOrdersForGivenSecurityPriceAndSide	All other orders for the given security, price and side

Used in components: [TriggeringInstruction](#)

### **180.2.5480 TriggerSecurityDesc**

Defines the security description of the security whose prices will be tracked by the trigger logic.

Type: [String](#)

Used in components: [TriggeringInstruction](#)

### **180.2.5481 TriggerSecurityID**

Defines the identity of the security whose prices will be tracked by the trigger logic.

Type: [String](#)

Used in components: [TriggeringInstruction](#)

**180.2.5482 TriggerSecurityIDSource**

Defines the identity of the security whose prices will be tracked by the trigger logic. Same values as SecurityIDSource (22).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [TriggeringInstruction](#)

### 180.2.5483 TriggerSymbol

Defines the common, 'human understood' representation of the security whose prices will be tracked by the trigger logic.

Type: [String](#)

Used in components: [TriggeringInstruction](#)

### 180.2.5484 TriggerTradingSessionID

Defines the trading session at which the order will be activated.

Type: [String](#)

Allowed values in TradingSessionIDCodeSet:

Code	Name	Description
1	Day	Day
2	HalfDay	HalfDay
3	Morning	Morning
4	Afternoon	Afternoon

Code	Name	Description
5	Evening	Evening
6	AfterHours	After-hours
7	Holiday	Holiday

Used in components: **TriggeringInstruction**

### 180.2.5485 TriggerTradingSessionSubID

Defines the subordinate trading session at which the order will be activated.

Type: **String**

Allowed values in TradingSessionSubIDCodeSet:

Code	Name	Description
1	PreTrading	Pre-Trading
2	OpeningOrOpeningAuction	Opening or opening auction
3	Continuous	(Continuous) Trading
4	ClosingOrClosingAuction	Closing or closing auction
5	PostTrading	Post-Trading
6	ScheduledIntradayAuction	Scheduled intraday auction
7	Quiescent	Quiescent
8	AnyAuction	Any auction
9	UnscheduledIntradayAuction	Unscheduled intraday auction. An unscheduled intraday auction might be triggered by a circuit breaker.
10	OutOfMainSessionTrading	Out of main session trading. In the context of Market Model Typology "Out of main session trading" refers to both before and after session, neither auction nor continuous trading.
11	PrivateAuction	Private auction. An auction phase where only two parties participate.
12	PublicAuction	Public auction. An auction phase where all trading parties participate.
13	GroupAuction	Group auction. An auction phase limited to specific parties (e.g. parties that have resting orders in the order book).

Code	Name	Description
14	OrderInitiatedAuction	Order initiated auction. Auction automatically triggered by an order, e.g. an incoming order or a resting order that can be matched based on an incoming order. Use 9="Unscheduled intraday auction" for any other auctions that are not scheduled. In the context of Market Model Topology, this can be used for an on demand auction (a.k.a. frequent batched auction).

Used in components: [TriggeringInstruction](#)

### 180.2.5486 TriggerType

Defines when the trigger will hit, i.e. the action specified by the trigger instructions will come into effect.

Type: [char](#)

Allowed values in TriggerTypeCodeSet:

Code	Name	Description
1	PartialExecution	Partial Execution
2	SpecifiedTradingSession	Specified Trading Session
3	NextAuction	Next Auction
4	PriceMovement	Price Movement
5	OnOrderEntryOrModification	On Order Entry or order modification entry

Used in components: [TriggeringInstruction](#)

### 180.2.5487 TZTransactTime

Transact time in the local date-time stamp with a TZ offset to UTC identified

Type: [TZTimestamp](#)

Used in messages: [TradeCaptureReport](#)

**180.2.5488 UnderlyingAccruedInterestAmt**

Amount of accrued interest of underlying security.

Type: **Amt**

Used in components: **UnderlyingInstrument**

**180.2.5489 UnderlyingAdditionalDividendsIndicator**

Indicates whether additional dividends are applicable.

Type: **Boolean**

Used in components: **UnderlyingDividendConditions**

**180.2.5490 UnderlyingAdditionalTermBondCouponFrequencyPeriod**

Time unit multiplier for the frequency of the bond's coupon payment.

Type: **int**

Used in groups: **UnderlyingAdditionalTermBondRefGrp**

**180.2.5491 UnderlyingAdditionalTermBondCouponFrequencyUnit**

Time unit associated with the frequency of the bond's coupon payment.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

---

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### **180.2.5492 UnderlyingAdditionalTermBondCouponRate**

Coupon rate of the bond. See also [CouponRate\(223\)](#).

Type: [Percentage](#)

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### **180.2.5493 UnderlyingAdditionalTermBondCouponType**

Coupon type of the bond.

Type: [int](#)

Allowed values in [CouponTypeCodeSet](#):

Code	Name	Description
0	Zero	Zero
1	FixedRate	Fixed rate
2	FloatingRate	Floating rate
3	Structured	Structured

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### **180.2.5494 UnderlyingAdditionalTermBondCurrency**

Specifies the currency the bond value is denominated in. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### **180.2.5495 UnderlyingAdditionalTermBondCurrentTotalIssuedAmount**

Total issued amount of the bond.

Type: [Amt](#)

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)



**180.2.5496 UnderlyingAdditionalTermBondDayCount**

The day count convention used in interest calculations for a bond or an interest bearing security.

Type: **int**

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.

Code	Name	Description
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.

Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### 180.2.5497 UnderlyingAdditionalTermBondDesc

Description of the bond.

Type: [String](#)

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

**180.2.5498 UnderlyingAdditionalTermBondIssuer**

Issuer of the bond.

Type: **String**

Used in groups: **UnderlyingAdditionalTermBondRefGrp**

**180.2.5499 UnderlyingAdditionalTermBondMaturityDate**

The maturity date of the bond.

Type: **LocalMktDate**

Used in groups: **UnderlyingAdditionalTermBondRefGrp**

**180.2.5500 UnderlyingAdditionalTermBondParValue**

The par value of the bond.

Type: **Amt**

Used in groups: **UnderlyingAdditionalTermBondRefGrp**

**180.2.5501 UnderlyingAdditionalTermBondRefGrp**

The UnderlyingAdditionalTermBondRefGrp is a repeating group subcomponent of the UnderlyingAdditionalTermGrp component used to identify an underlying reference bond for a swap.

Name	Mult.	Type	Description
NoUnderlyingAdditionalTermBondRefs	[1..1]	NumInGroup	
UnderlyingAdditionalTermBondSecurityID	[0..1]	String	Required if NoUnderlyingAdditionalTermBondRefs(41340) > 0.
UnderlyingAdditionalTermBondSecurityIDSource	[0..1]	CodeSet	Conditionally required when UnderlyingAdditionalTermBondSecurityID(41341) is specified.
UnderlyingAdditionalTermBondDesc	[0..1]	String	
EncodedUnderlyingAdditionalTermBondDescLen	[0..1]	Length	Must be set if EncodedUnderlyingAdditionalTermBondDesc(41709) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedUnderlyingAdditionalTermBondDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingAdditionalTermBondDesc(41709) field in the encoded format specified via the MessageEncoding(347) field.
UnderlyingAdditionalTermBondCurrency	[0..1]	Currency	
UnderlyingAdditionalTermBondIssuer	[0..1]	String	
EncodedUnderlyingAdditionalTermBondIssuerLen	[0..1]	Length	Must be set if EncodedUnderlyingAdditionalTermBondIssuer(42017) field is specified and must immediately precede it.
EncodedUnderlyingAdditionalTermBondIssuer	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingAdditionalTermBondIssuer(42017) field in the encoded format specified via the MessageEncoding(347) field.
UnderlyingAdditionalTermBondSeniority	[0..1]	CodeSet	
UnderlyingAdditionalTermBondCouponType	[0..1]	CodeSet	
UnderlyingAdditionalTermBondCouponRate	[0..1]	Percentage	
UnderlyingAdditionalTermBondMaturityDate	[0..1]	LocalMktDate	
UnderlyingAdditionalTermBondParValue	[0..1]	Amt	
UnderlyingAdditionalTermBondCurrentTotalIssuedAmount	[0..1]	Amt	
UnderlyingAdditionalTermBondCouponFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingAdditionalTermBondCouponFrequencyUnit(42034) is specified.
UnderlyingAdditionalTermBondCouponFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingAdditionalTermBondCouponFrequencyPeriod(42033) is specified.
UnderlyingAdditionalTermBondDayCount	[0..1]	CodeSet	

Used in groups: UnderlyingAdditionalTermGrp

**180.2.5502 UnderlyingAdditionalTermBondSecurityID**

Security identifier of the bond.

Type: **String**

Used in groups: **UnderlyingAdditionalTermBondRefGrp**

**180.2.5503 UnderlyingAdditionalTermBondSecurityIDSource**

Identifies the source scheme of the UnderlyingAdditionalTermBondSecurityID(41341) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit

Code	Name	Description
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **UnderlyingAdditionalTermBondRefGrp**

#### 180.2.5504 UnderlyingAdditionalTermBondSeniority

Specifies the bond's payment priority in the event of a default.

Type: **String**

Allowed values in SeniorityCodeSet:

Code	Name	Description
SD	SeniorSecured	Senior Secured
SR	Senior	Senior
SB	Subordinated	Subordinated
JR	Junior	Junior. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
MZ	Mezzanine	Mezzanine. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".

Code	Name	Description
SN	SeniorNonPreferred	Senior Non-Preferred. For CDS reference obligations of non-preferred senior debt issued by European Financials that constitute a layer of debt ranking between the bank's normal senior debt but above the bank's normal tier 2 subordinated debt (reference: ISDA Credit Market Infrastructure Group).

Used in groups: [UnderlyingAdditionalTermBondRefGrp](#)

#### 180.2.5505 UnderlyingAdditionalTermConditionPrecedentBondIndicator

Indicates whether the condition precedent bond is applicable. The swap contract is only valid if the bond is issued and if there is any dispute over the terms of fixed stream then the bond terms would be used.

Type: [Boolean](#)

Used in groups: [UnderlyingAdditionalTermGrp](#)

#### 180.2.5506 UnderlyingAdditionalTermDiscrepancyClauseIndicator

Indicates whether the discrepancy clause is applicable.

Type: [Boolean](#)

Used in groups: [UnderlyingAdditionalTermGrp](#)

#### 180.2.5507 UnderlyingAdditionalTermGrp

The UnderlyingAdditionalTermGrp is a repeating subcomponent of the UnderlyingInstrument component used to report additional contract terms.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingAdditionalTerms</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingAdditionalTermCondition-PrecedentBondIndicator</a>	[0..1]	Boolean	Required if NoUnderlyingAdditionalTerms(42036) > 0.
<a href="#">UnderlyingAdditionalTermDiscrepancyClauseIndicator</a>	[0..1]	Boolean	
<a href="#">UnderlyingAdditionalTermBondRefGrp</a>	[0..*]	Group	



---

Name	Mult.	Type	Description
------	-------	------	-------------

---

Used in components: [UnderlyingInstrument](#)

#### **180.2.5508 UnderlyingAdjustedQuantity**

Unit amount of the underlying security (shares) adjusted for pending corporate action not yet allocated.

Type: [Qty](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5509 UnderlyingAllDividendsIndicator**

Represents the European Master Confirmation value of 'All Dividends' which, when applicable, signifies that, for a given Ex-Date, the daily observed share price for that day is adjusted (reduced) by the cash dividend and/or the cash value of any non-cash dividend per share (including extraordinary dividends) declared by the issuer.

Type: [Boolean](#)

Used in components: [UnderlyingDividendConditions](#)

#### **180.2.5510 UnderlyingAllocationPercent**

Percent of the Strike Price that this underlying represents.

Type: [Percentage](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5511 UnderlyingAmount**

The UnderlyingAmount component block is used to supply the underlying amounts, dates, settlement status and method for derivative positions.

Name	Mult.	Type	Description
NoUnderlyingAmounts	[1..1]	NumInGroup	
UnderlyingPayAmount	[0..1]	Amt	Amount to pay in order to receive the underlying instrument.
UnderlyingCollectAmount	[0..1]	Amt	Amount to collect in order to deliver the underlying instrument.
UnderlyingSettlementDate	[0..1]	LocalMktDate	Date the underlying instrument will settle. Used for derivatives that deliver into more than one underlying instrument. Settlement dates can vary across underlying instruments.
UnderlyingSettlementStatus	[0..1]	String	Settlement status of the underlying instrument. Used for derivatives that deliver into more than one underlying instrument. Settlement can be delayed for an underlying instrument.

Used in groups: **PosUndInstrmtGrp**

### 180.2.5512 UnderlyingAssetAttributeGrp

The UnderlyingAssetAttributeGrp is a repeating subcomponent of the UnderlyingInstrument component used to detail attributes of the instrument asset.

Name	Mult.	Type	Description
NoUnderlyingAssetAttributes	[1..1]	NumInGroup	
UnderlyingAssetAttributeType	[0..1]	String	Required if NoUnderlyingAssetAttributes(2312) > 0.
UnderlyingAssetAttributeValue	[0..1]	String	
UnderlyingAssetAttributeLimit	[0..1]	String	

Used in components: **UnderlyingInstrument**

### 180.2.5513 UnderlyingAssetAttributeLimit

Limit or lower acceptable value of the attribute.

Type: **String**

Used in groups: **UnderlyingAssetAttributeGrp**

**180.2.5514 UnderlyingAssetAttributeType**

Specifies the name of the attribute.

See [http://www.fixtradingcommunity.org/codelists#Asset\\_Attribute\\_Types](http://www.fixtradingcommunity.org/codelists#Asset_Attribute_Types) for code list of applicable asset attribute types.

Type: **String**

Used in groups: **UnderlyingAssetAttributeGrp**

**180.2.5515 UnderlyingAssetAttributeValue**

Specifies the value of the attribute.

Type: **String**

Used in groups: **UnderlyingAssetAttributeGrp**

**180.2.5516 UnderlyingAssetClass**

The broad asset category for assessing risk exposure.

Type: **int**

Allowed values in AssetClassCodeSet:

Code	Name	Description
1	InterestRate	Interest rate
2	Currency	Currency
3	Credit	Credit
4	Equity	Equity
5	Commodity	Commodity
6	Other	Other
7	Cash	Cash
8	Debt	Debt
9	Fund	Fund. Such as mutual fund, collective investment vehicle, investment program, specialized account program.
10	LoanFacility	Loan facility
11	Index	Index. A main index identified as a security type, for example under EU SFTR reporting.

Used in components: [UnderlyingInstrument](#)

### 180.2.5517 UnderlyingAssetGroup

Indicates the broad product or asset classification. May be used to provide grouping for the product taxonomy (Product(460), SecurityType(167), etc.) and/or the risk taxonomy (AssetClass(1938), AssetSubClass(1939), AssetType(1940), etc.).

Type: [int](#)

Allowed values in AssetGroupCodeSet:

Code	Name	Description
1	Financials	Financials. A categorization which usually includes rates, foreign exchange, credit, bonds and equity products or assets.
2	Commodities	Commodities. A categorization which usually includes hard commodities such as agricultural, metals, freight, energy products or assets.
3	AlternativeInvestments	Alternative investments. A categorization which usually includes weather, housing, and commodity indices products or assets.

Used in components: [UnderlyingInstrument](#)

### 180.2.5518 UnderlyingAssetSubClass

An indication of the general description of the asset class.

Type: [int](#)

Allowed values in AssetSubClassCodeSet:

Code	Name	Description
1	SingleCurrency	Single currency
2	CrossCurrency	Cross currency
3	Basket	Basket [for multi-currency]
4	SingleName	Single name
5	CreditIndex	Credit index
6	IndexTranche	Index tranche

Code	Name	Description
7	CreditBasket	Credit basket
8	Exotic	Exotic
9	Common	Common
10	Preferred	Preferred
11	EquityIndex	Equity index
12	EquityBasket	Equity basket
13	Metals	Metals
14	Bullion	Bullion
15	Energy	Energy
16	CommodityIndex	Commodity index
17	Agricultural	Agricultural
18	Environmental	Environmental
19	Freight	Freight
20	Government	Government
21	Agency	Agency
22	Corporate	Corporate
23	Financing	Financing
24	MoneyMarket	Money market
25	Mortgage	Mortgage
26	Municipal	Municipal
27	MutualFund	Mutual fund
28	CollectiveInvestmentVehicle	Collective investment vehicle
29	InvestmentProgram	Investment program. A generalized fund for major investors.
30	SpecializedAccountProgram	Specialized account program. A specialized fund setup for a particular account or group of accounts.
31	TermLoan	Term loan
32	BridgeLoan	Bridge loan
33	LetterOfCredit	Letter of credit
34	DividendIndex	Dividend index
35	StockDividend	Stock dividend
36	ExchangeTradedFund	Exchange traded fund
37	VolatilityIndex	Volatility index
38	FXCrossRates	FX cross rates
39	FXEmergingMarkets	FX emerging markets

Code	Name	Description
40	FXMajors	FX Majors
41	Fertilizer	Fertilizer
42	IndustrialProduct	Industrial product
43	Inflation	Inflation
44	Paper	Paper
45	Polypropylene	Polypropylene
46	OfficialEconomicStatistics	Official economic statistics
47	OtherC10	Other C10. Defined under MiFID II (Directive 2014/65/EU) Section C(10) of Annex I and paraphrased in ESMA RTS 2 Annex III Section 10, "Other C10" is a financial instrument "which is not a 'Freight derivative', any of the following interest rate derivatives sub-asset classes: 'Inflation multi-currency swap or cross-currency swap', a 'Future/forward on inflation multi-currency swaps or cross-currency swaps', an 'Inflation single currency swap', a 'Future/forward on inflation single currency swap' and any of the following equity derivatives sub-asset classes: a 'Volatility index option', a 'Volatility index future/forward', a swap with parameter return variance, a swap with parameter return volatility, a portfolio swap with parameter return variance, a portfolio swap with parameter return volatility".
48	Other	Other. May be used with any AssetClass(1938) values.

Used in components: **UnderlyingInstrument**

#### 180.2.5519 UnderlyingAssetSubType

Used to provide a more specific description of the asset specified in UnderlyingAssetType(2015).

See <https://www.fixtrading.org/codelists/AssetSubType> for code list of applicable values.

Type: **String**

Used in components: **UnderlyingInstrument**

#### 180.2.5520 UnderlyingAssetType

Used to provide more specific description of the asset specified in UnderlyingAssetSubClass(2082).

See <https://www.fixtrading.org/codelists/AssetType> for code list of applicable values. ISO 4721 Currency Code values are to be used when specific currency as an asset type is to be expressed.

Other values may be used by mutual agreement of the counterparties.

Type: **String**

Used in components: **UnderlyingInstrument**

### **180.2.5521 UnderlyingAssignmentMethod**

Method under which assignment was conducted

Type: **char**

Allowed values in InstrmtAssignmentMethodCodeSet:

Code	Name	Description
P	ProRata	Pro rata
R	Random	Random

Used in components: **UnderlyingInstrument**

### **180.2.5522 UnderlyingAttachmentPoint**

See AttachmentPoint(1457).

Type: **Percentage**

Used in components: **UnderlyingInstrument**

### **180.2.5523 UnderlyingAutomaticExerciseIndicator**

Indicates (when 'Y') that exercise is automatic when the strike price is crossed or the underlying trade is in the money.

Type: **Boolean**

Used in components: **UnderlyingOptionExercise**

**180.2.5524 UnderlyingAutomaticExerciseThresholdRate**

The threshold rate for triggering automatic exercise.

Type: **float**

Used in components: **UnderlyingOptionExercise**

**180.2.5525 UnderlyingAverageVolumeLimitationPercentage**

The limit of average percentage of individual securities traded in a day or a number of days.

Type: **Amt**

Used in components: **UnderlyingInstrument**

**180.2.5526 UnderlyingAverageVolumeLimitationPeriodDays**

Specifies the limitation period for average daily trading volume in number of days.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.5527 UnderlyingBasketDivisor**

Specifies the basket divisor amount. This value is normally used to adjust the constituent weight for pricing or to adjust for dividends, or other corporate actions.

Type: **float**

Used in components: **UnderlyingInstrument**

**180.2.5528 UnderlyingBidPx**

Bid price of the underlying instrument.

Type: **Price**

Used in messages: **SecurityRiskMetricsReport**



**180.2.5529 UnderlyingBusinessCenter**

A business center whose calendar is used for date adjustment, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingBusinessCenterGrp**

**180.2.5530 UnderlyingBusinessCenterGrp**

UnderlyingBusinessCenterGrp is a repeating subcomponent within the UnderlyingDateAdjustment component. It is used to specify the set of business centers whose calendars drive the date adjustment. The business centers defined here apply to all adjustable dates in the instrument unless specifically overridden.

Name	Mult.	Type	Description
<b>NoUnderlyingBusinessCenters</b>	[1..1]	NumInGroup	
<b>UnderlyingBusinessCenter</b>	[0..1]	String	Required if NoUnderlyingBusinessCenters(40962) > 0.

Used in components: **UnderlyingDateAdjustment**

**180.2.5531 UnderlyingBusinessDayConvention**

The business day convention used for adjusting dates. The value defined here applies to all adjustable dates in the underlying instrument unless specifically overridden.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.

Code	Name	Description
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingDateAdjustment](#)

### **180.2.5532 UnderlyingCapPrice**

Used to express the ceiling price of a capped call.

Type: [Price](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.5533 UnderlyingCapValue**

Maximum notional value for a capped financial instrument

Type: [Amt](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.5534 UnderlyingCashAmount**

Cash amount associated with the underlying component.

Type: [Amt](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.5535 UnderlyingCashSettlAccruedInterestIndicator**

Indicates whether accrued interest is included or not in the value provided in UnderlyingCashSettlAmount(42054).

For cash settlement this specifies whether quotations should be obtained inclusive or not of accrued interest.

For physical settlement this specifies whether the buyer should deliver the obligation with an outstanding principal balance that includes or excludes accrued interest.

Type: **Boolean**

Used in groups: **UnderlyingCashSettlTermGrp**

#### **180.2.5536 UnderlyingCashSettlAmount**

The amount paid between the trade parties, seller to the buyer, for cash settlement on the cash settlement date.

Type: **Amt**

Used in groups: **UnderlyingCashSettlTermGrp**

#### **180.2.5537 UnderlyingCashSettlBusinessCenter**

Identifies the business center calendar used at valuation time for cash settlement purposes e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingCashSettlTermGrp**

#### **180.2.5538 UnderlyingCashSettlBusinessDays**

The number of business days used in the determination of the cash settlement payment date.

Type: **int**

Used in groups: **UnderlyingCashSettlTermGrp**

#### **180.2.5539 UnderlyingCashSettlCurrency**

Specifies the currency the UnderlyingCashSettlAmount(42054) is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5540 UnderlyingCashSettlDateAdjusted**

The adjusted cash settlement date.

Type: **LocalMktDate**

Used in components: **UnderlyingCashSettlDate**

**180.2.5541 UnderlyingCashSettlDateBusinessCenter**

The business center calendar used for date adjustment of the cash settlement unadjusted or relative date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingCashSettlDateBusinessCenterGrp**

**180.2.5542 UnderlyingCashSettlDateBusinessCenterGrp**

UnderlyingCashSettlDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingCashSettlDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the DateAdjustment component in Instrument.

Name	Mult.	Type	Description
<b>NoUnderlyingCashSettlDateBusinessCenters</b>	[1..1]	NumInGroup	
<b>UnderlyingCashSettlDateBusinessCenter</b>	[0..1]	String	Required if NoUnderlyingCashSettlDateBusinessCenters(42788) > 0.

Used in components: **UnderlyingCashSettlDate**

**180.2.5543 UnderlyingCashSettlDateBusinessDayConvention**

The business day convention used to adjust the cash settlement provision's date. Used only to override the business day convention defined in the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingCashSettlDate](#)

### 180.2.5544 UnderlyingCashSettlDate

The UnderlyingCashSettlDate component is a subcomponent within the UnderlyingCashSettlTermGrp component used to report the cash settlement date defined in the settlement provision.

Name	Mult.	Type	Description
<a href="#">UnderlyingCashSettlDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingCashSettlDateBusinessDay-Convention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the DateAdjustment component in the Instrument component. The specified value would be specific to this instance of the cash settlement provision.
<a href="#">UnderlyingCashSettlDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the DateAdjustment component in the Instrument component. The specified values would be specific to this instance of the cash settlement provision.
<a href="#">UnderlyingCashSettlDateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingCashSettlDateOffsetPeriod</a>	[0..1]	int	Conditionally required when UnderlyingCashSettlDateOffsetUnit(42794) is specified.
<a href="#">UnderlyingCashSettlDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when UnderlyingCashSettlDateOffsetPeriod(42793) is specified.

Name	Mult.	Type	Description
<a href="#">UnderlyingCashSettlDateOffsetDay-Type</a>	[0..1]	CodeSet	
<a href="#">UnderlyingCashSettlDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [UnderlyingCashSettlTermGrp](#)

#### **180.2.5545 UnderlyingCashSettlDateOffsetDayType**

Specifies the day type of the relative cash settlement date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingCashSettlDate](#)

#### **180.2.5546 UnderlyingCashSettlDateOffsetPeriod**

Time unit multiplier for the relative cash settlement date offset.

Type: [int](#)

Used in components: [UnderlyingCashSettlDate](#)

#### **180.2.5547 UnderlyingCashSettlDateOffsetUnit**

Time unit associated with the relative cash settlement date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingCashSettlDate](#)

#### **180.2.5548 UnderlyingCashSettlDateRelativeTo**

Specifies the anchor date when the cash settlement date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [UnderlyingCashSettlDate](#)

#### **180.2.5549 UnderlyingCashSettlDateUnadjusted**

The unadjusted cash settlement date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingCashSettlDate](#)

#### **180.2.5550 UnderlyingCashSettlDealer**

Identifies the dealer from whom price quotations for the reference obligation are obtained for the purpose of cash settlement valuation calculation.

Type: [String](#)

Used in groups: [UnderlyingCashSettlDealerGrp](#)

**180.2.5551 UnderlyingCashSettlDealerGrp**

UnderlyingCashSettlDealerGrp is a repeating subcomponent within the UnderlyingCashSettlTermGrp component. It is used to specify the dealers from whom price quotations for the reference obligation are obtained for the purpose of cash settlement valuation.

Name	Mult.	Type	Description
NoUnderlyingCashSettlDealers	[1..1]	NumInGroup	
UnderlyingCashSettlDealer	[0..1]	String	Required if NoUnderlyingCashSettlDealers(42039) > 0.

Used in groups: [UnderlyingCashSettlTermGrp](#)

**180.2.5552 UnderlyingCashSettlFixedTermIndicator**

Indicates whether fixed settlement is applicable or not applicable in a recovery lock.

Type: [Boolean](#)

Used in groups: [UnderlyingCashSettlTermGrp](#)

**180.2.5553 UnderlyingCashSettlMinimumQuoteAmount**

When determining the cash settlement amount, if weighted average price quotes are to be obtained for the reference obligation, this is the minimum intended threshold amount of outstanding principal balance of the reference obligation for which the quote should be obtained. If not specified, the ISDA definitions provide for a fallback amount of the lower of either USD1,000,000 (or its equivalent in the relevant obligation currency) or the (minimum) quoted amount.

Type: [Amt](#)

Used in groups: [UnderlyingCashSettlTermGrp](#)

**180.2.5554 UnderlyingCashSettlMinimumQuoteCurrency**

Specifies the currency the UnderlyingCashSettlQuoteAmount(42049) is denominated in. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingCashSettlTermGrp](#)



**180.2.5555 UnderlyingCashSettlNumOfValuationDates**

Where multiple valuation dates are specified as being applicable for cash settlement, this element specifies the number of applicable valuation dates.

Type: **int**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5556 UnderlyingCashSettlPriceDefault**

The default election for determining settlement price.

Type: **int**

Allowed values in CashSettlPriceDefaultCodeSet:

Code	Name	Description
0	Close	Close. Official closing price.
1	Hedge	Hedge. Determined by the hedging party.

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5557 UnderlyingCashSettlPriceSource**

The source from which the settlement price is to be obtained.

See <http://www.fpml.org/coding-scheme/settlement-price-source> for values.

Type: **String**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5558 UnderlyingCashSettlQuoteAmount**

When determining the cash settlement amount, if weighted average price quotes are to be obtained for the reference obligation, this is the upper limit to the outstanding principal balance of the reference obligation for which the quote should be obtained. If not specified, the ISDA definitions provide for a fallback amount equal to floating rate payer calculation amount.

Type: **Amt**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5559 UnderlyingCashSettlQuoteCurrency**

Specifies the currency the UnderlyingCashSettlQuoteAmount(42049) is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5560 UnderlyingCashSettlQuoteMethod**

The type of quote used to determine the cash settlement price.

Type: **int**

Allowed values in CashSettlQuoteMethodCodeSet:

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5561 UnderlyingCashSettlRecoveryFactor**

Used for fixed recovery, this specifies the recovery level as determined at contract inception, to be applied in the event of a default. The factor is used to calculate the amount paid by the seller to the buyer for cash settlement on the cash settlement date. The amount is calculated is  $(1 - \text{UnderlyingCashSettlRecoveryFactor}(42055)) \times \text{floating rate payer calculation amount}$ . The currency is derived from the floating rate payer calculation amount.

Type: **float**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5562 UnderlyingCashSettlTermGrp**

The UnderlyingCashSettlTermGrp is a repeating component within the UnderlyingInstrument component used to report cash settlement terms.

Name	Mult.	Type	Description
NoUnderlyingCashSettlTerms	[1..1]	NumInGroup	
UnderlyingCashSettlCurrency	[0..1]	Currency	Required if NoUnderlyingCashSettlTerms(42041) > 0.
UnderlyingCashSettlValuationFirst-BusinessDayOffset	[0..1]	int	
UnderlyingCashSettlValuationSubsequentBusinessDaysOffset	[0..1]	int	
UnderlyingCashSettlNumOfValuation-Dates	[0..1]	int	
UnderlyingCashSettlValuationTime	[0..1]	LocalMktTime	
UnderlyingCashSettlBusinessCenter	[0..1]	String	
UnderlyingCashSettlQuoteMethod	[0..1]	CodeSet	
UnderlyingCashSettlQuoteAmount	[0..1]	Amt	
UnderlyingCashSettlQuoteCurrency	[0..1]	Currency	
UnderlyingCashSettlMini-mumQuoteAmount	[0..1]	Amt	
UnderlyingCashSettlMinimumQuote-Currency	[0..1]	Currency	
UnderlyingCashSettlDealerGrp	[0..*]	Group	
UnderlyingCashSettlPriceSource	[0..1]	String	
UnderlyingCashSettlPriceDefault	[0..1]	CodeSet	
UnderlyingCashSettlBusinessDays	[0..1]	int	
UnderlyingCashSettlAmount	[0..1]	Amt	
UnderlyingCashSettlDate	[0..1]	Component	
UnderlyingCashSettlRecoveryFactor	[0..1]	float	
UnderlyingCashSettlFixedTermIndica-tor	[0..1]	Boolean	
UnderlyingCashSettlAccruedInter-estIndicator	[0..1]	Boolean	
UnderlyingCashSettlValuationMethod	[0..1]	CodeSet	
UnderlyingCashSettlTermXID	[0..1]	XID	

Used in components: **UnderlyingInstrument**

**180.2.5563 UnderlyingCashSettlTermXID**

Name referenced from UnderlyingSettlementTermXIDRef(41315).

Type: **XID**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5564 UnderlyingCashSettlValuationFirstBusinessDayOffset**

The number of business days after settlement conditions have been satisfied, when the calculation agent is to obtain a price quotation on the reference obligation for purposes of cash settlement.

Type: **int**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5565 UnderlyingCashSettlValuationMethod**

The ISDA defined methodology for determining the final price of the reference obligation for purposes of cash settlement.

Type: **int**

Allowed values in CashSettlValuationMethodCodeSet:

Code	Name	Description
0	Market	Market
1	Highest	Highest
2	AverageMarket	Average market
3	AverageHighest	Average highest
4	BlendedMarket	Blended market
5	BlendedHighest	Blended highest
6	AverageBlendedMarket	Average blended market
7	AverageBlendedHighest	Average blended highest

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5566 UnderlyingCashSettlValuationSubsequentBusinessDaysOffset**

The number of business days between successive valuation dates when multiple valuation dates are applicable for cash settlement.

Type: **int**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5567 UnderlyingCashSettlValuationTime**

Time of valuation.

Type: **LocalMktTime**

Used in groups: **UnderlyingCashSettlTermGrp**

**180.2.5568 UnderlyingCashType**

Used for derivatives that deliver into cash underlying.

Type: **String**

Allowed values in UnderlyingCashTypeCodeSet:

Code	Name	Description
FIXED	FIXED	FIXED
DIFF	DIFF	DIFF

Used in components: **UnderlyingInstrument**

**180.2.5569 UnderlyingCFIcode**

Underlying security's CFIcode.

Valid values: see CFIcode (461) field

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5570 UnderlyingCollectAmount**

Amount to collect in order to deliver the underlying instrument

Type: **Amt**

Used in groups: **UnderlyingAmount**

**180.2.5571 UnderlyingCommonPricingIndicator**

When this element is specified and set to 'Y', it indicates that common pricing applies. Common pricing may be relevant for a transaction that references more than one commodity reference price.

Type: **Boolean**

Used in components: **UnderlyingInstrument**

**180.2.5572 UnderlyingComplexEventAveragingObservationGrp**

UnderlyingComplexEventAveragingObservationGrp is an optional subcomponent of UnderlyingComplexEventPeriodGrp for specifying the weight of each of the dated observations.

Name	Mult.	Type	Description
NoUnderlyingComplexEventAveragingObservations	[1..1]	NumInGroup	
UnderlyingComplexEventAveragingObservationNumber	[0..1]	int	Required if NoUnderlyingComplexEventAveragingObservations(41713) > 0.
UnderlyingComplexEventAveragingWeight	[0..1]	float	

Used in groups: **UnderlyingComplexEventPeriodGrp**

**180.2.5573 UnderlyingComplexEventAveragingObservationNumber**

Cross reference to the ordinal observation as specified either in the UnderlyingComplexEventScheduleGrp or UnderlyingComplexEventPeriodDateGrp components.

Type: **int**

Used in groups: **UnderlyingComplexEventAveragingObservationGrp**

**180.2.5574 UnderlyingComplexEventAveragingWeight**

The weight factor to be applied to the observation.

Type: **float**

Used in groups: **UnderlyingComplexEventAveragingObservationGrp**

**180.2.5575 UnderlyingComplexEventBusinessCenter**

The business center for adjusting dates and times in the schedule or date-time group.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingComplexEventPeriodGrp**

**180.2.5576 UnderlyingComplexEventCalculationAgent**

Used to identify the calculation agent.

Type: **int**

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreeent	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

Used in groups: **UnderlyingComplexEvents**

**180.2.5577 UnderlyingComplexEventCondition**

Specifies the condition between complex events when more than one event is specified.

Multiple barrier events would use an "or" condition since only one can be effective at a given time. A set of digital range events would use an "and" condition since both conditions must be in effect for a payout to result.

Type: **int**

Allowed values in ComplexEventConditionCodeSet:

Code	Name	Description
1	And	And
2	Or	Or

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5578 UnderlyingComplexEventCreditEventBusinessCenter**

Specifies the local business center for which the credit event is to be determined. The inclusion of this business center implies that Greenwich Mean Time in Section 3.3 of the 2003 ISDA Credit Derivatives Definitions is replaced by the local time of the specified business center.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5579 UnderlyingComplexEventCreditEventCurrency**

Specifies the applicable currency when UnderlyingComplexEventCreditEventValue(41718) is an amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingComplexEventCreditEventGrp**

#### **180.2.5580 UnderlyingComplexEventCreditEventDayType**

Specifies the day type for the complex credit events.

Type: **int**

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:



Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [UnderlyingComplexEventCreditEventGrp](#)

### 180.2.5581 UnderlyingComplexEventCreditEventGrp

The UnderlyingComplexEventCreditEventGrp is a repeating component within the UnderlyingComplexEventGrp component used to report applicable option credit events.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingComplexEventCreditEvents</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingComplexEventCreditEventType</a>	[0..1]	String	Required if <a href="#">NoUnderlyingComplexEventCreditEvents(41716)</a> > 0.
<a href="#">UnderlyingComplexEventCreditEventValue</a>	[0..1]	String	
<a href="#">UnderlyingComplexEventCreditEventCurrency</a>	[0..1]	Currency	
<a href="#">UnderlyingComplexEventCreditEventPeriod</a>	[0..1]	int	Conditionally required when <a href="#">UnderlyingComplexEventCreditEventUnit(41721)</a> is specified.
<a href="#">UnderlyingComplexEventCreditEventUnit</a>	[0..1]	CodeSet	Conditionally required when <a href="#">UnderlyingComplexEventCreditEventPeriod(41720)</a> is specified.
<a href="#">UnderlyingComplexEventCreditEventDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingComplexEventCreditEventRateSource</a>	[0..1]	int	
<a href="#">UnderlyingComplexEventCreditEventQualifierGrp</a>	[0..*]	Group	

Used in groups: [UnderlyingComplexEvents](#)

**180.2.5582 UnderlyingComplexEventCreditEventMinimumSources**

The minimum number of the specified public information sources that must publish information that reasonably confirms that a credit event has occurred. The market convention is two.

Type: **int**

Used in groups: **UnderlyingComplexEvents**

**180.2.5583 UnderlyingComplexEventCreditEventNotifyingParty**

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring.

Type: **int**

Allowed values in ComplexEventCreditEventNotifyingPartyCodeSet:

Code	Name	Description
0	SellerNotifies	Seller notifies
1	BuyerNotifies	Buyer notifies
2	SellerOrBuyerNotifies	Seller or buyer notifies

Used in groups: **UnderlyingComplexEvents**

**180.2.5584 UnderlyingComplexEventCreditEventPeriod**

Time unit multiplier for complex credit events.

Type: **int**

Used in groups: **UnderlyingComplexEventCreditEventGrp**

**180.2.5585 UnderlyingComplexEventCreditEventQualifier**

Specifies a complex event qualifier. Used to further qualify UnderlyingComplexEventCreditEvent-Type(41717).

Type: **char**

Allowed values in ProtectionTermEventQualifierCodeSet:

Code	Name	Description
H	RestructuringMultipleHoldingObligations	Restructuring - multiple holding obligations. In relation to a restructuring credit event, unless multiple holder obligation is not specified restructurings are limited to multiple holder obligations. A multiple holder obligation means an obligation that is held by more than three holders that are not affiliates of each other and where at least two thirds of the holders must agree to the event that constitutes the restructuring credit event. ISDA 2003 Term: Multiple Holder Obligation.
E	RestructuringMultipleCreditEventNotices	Restructuring - multiple credit event notices. Presence of this element and value set to 'true' indicates that Section 3.9 of the 2003 Credit Derivatives Definitions shall apply. Absence of this element indicates that Section 3.9 shall not apply. NOTE: Not allowed under ISDA Credit 1999.
C	FloatingRateInterestShortfall	Floating rate interest shortfall. Indicates compounding.

Used in groups: [UnderlyingComplexEventCreditEventQualifierGrp](#)

### 180.2.5586 UnderlyingComplexEventCreditEventQualifierGrp

The UnderlyingComplexEventCreditEventQualifierGrp is a repeating component within the UnderlyingComplexEventCreditEventGrp component used to specify qualifying attributes to an event.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingComplexEventCreditEventQualifiers</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingComplexEventCreditEventQualifier</a>	[0..1]	CodeSet	Required if <a href="#">NoUnderlyingComplexEventCreditEventQualifiers</a> (41724) > 0.

Used in groups: [UnderlyingComplexEventCreditEventGrp](#)

### 180.2.5587 UnderlyingComplexEventCreditEventRateSource

Identifies the source of rate information used for credit events.

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Rate\\_Source](http://www.fixtradingcommunity.org/codelists#Credit_Event_Rate_Source) for code list of applicable sources.

Type: **int**

Used in groups: **UnderlyingComplexEventCreditEventGrp**

#### **180.2.5588 UnderlyingComplexEventCreditEventSource**

A newspaper or electronic news service that may publish relevant information used in the determination of whether or not a credit event has occurred.

Type: **String**

Used in groups: **UnderlyingComplexEventCreditEventSourceGrp**

#### **180.2.5589 UnderlyingComplexEventCreditEventSourceGrp**

UnderlyingComplexEventCreditEventSourceGrp is a repeating subcomponent of the UnderlyingComplexEvents component used to specify the particular newspapers or electronic news services that may publish relevant information used in the determination of whether or not a credit event has occurred.

Name	Mult.	Type	Description
<b>NoUnderlyingComplexEventCreditEventSources</b>	[1..1]	NumInGroup	
<b>UnderlyingComplexEventCreditEventSource</b>	[0..1]	String	Required if NoUnderlyingCreditEventCreditEventSources(41748) > 0.

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5590 UnderlyingComplexEventCreditEventStandardSources**

When this element is specified and set to 'Y', indicates that ISDA defined Standard Public Sources are applicable.

Type: **Boolean**

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5591 UnderlyingComplexEventCreditEventsXIDRef**

Reference to credit event table elsewhere in the message.

Type: **XIDREF**

Used in groups: **UnderlyingComplexEvents**

### **180.2.5592 UnderlyingComplexEventCreditEventType**

Specifies the type of credit event.

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Credit_Event_Types) for code list of applicable event types.

Type: **String**

Used in groups: **UnderlyingComplexEventCreditEventGrp**

### **180.2.5593 UnderlyingComplexEventCreditEventUnit**

Time unit associated with complex credit events.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **UnderlyingComplexEventCreditEventGrp**

### **180.2.5594 UnderlyingComplexEventCreditEventValue**

The credit event value appropriate to UnderlyingComplexEventCreditEventType(41717).

See [http://www.fixtradingcommunity.org/codelists#Credit\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Credit_Event_Types) for applicable event type values.

Type: **String**

Used in groups: **UnderlyingComplexEventCreditEventGrp**

**180.2.5595 UnderlyingComplexEventCurrencyOne**

Specifies the first or only reference currency of the trade.

UnderlyingComplexEventCurrencyOneCodeSource(2948) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **UnderlyingComplexEvents**

**180.2.5596 UnderlyingComplexEventCurrencyOneCodeSource**

Identifies class or source of the UnderlyingComplexEventCurrencyOne(2268) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **UnderlyingComplexEvents**

**180.2.5597 UnderlyingComplexEventCurrencyTwo**

Specifies the second reference currency of the trade.

UnderlyingComplexEventCurrencyTwoCodeSource(2949) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **UnderlyingComplexEvents**

**180.2.5598 UnderlyingComplexEventCurrencyTwoCodeSource**

Identifies class or source of the UnderlyingComplexEventCurrencyTwo(2269) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **UnderlyingComplexEvents**

**180.2.5599 UnderlyingComplexEventDateAdjusted**

The adjusted complex event date.

Type: **LocalMktDate**

Used in components: **UnderlyingComplexEventRelativeDate**

**180.2.5600 UnderlyingComplexEventDateBusinessCenter**

The business center calendar is used to adjust the event date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingComplexEventDateBusinessCenterGrp**

**180.2.5601 UnderlyingComplexEventDateBusinessCenterGrp**

UnderlyingComplexEventDateBusinessCenterGrp is a repeating subcomponent of the UnderlyingComplexEventRelativeDate component used to specify the set of business centers whose calendars drive

date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingComplexEventDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingComplexEventDateBusinessCenter	[0..1]	String	Required if NoUnderlyingComplexEventDateBusinessCenters(41737) > 0.

Used in components: [UnderlyingComplexEventRelativeDate](#)

### 180.2.5602 UnderlyingComplexEventDateBusinessDayConvention

The business day convention used to adjust the event date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingComplexEventRelativeDate](#)

### 180.2.5603 UnderlyingComplexEventDateOffsetDayType

Specifies the day type of the relative date offset.

Type: [int](#)



Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingComplexEventRelativeDate](#)

#### **180.2.5604 UnderlyingComplexEventDateOffsetPeriod**

Time unit multiplier for the relative date offset.

Type: [int](#)

Used in components: [UnderlyingComplexEventRelativeDate](#)

#### **180.2.5605 UnderlyingComplexEventDateOffsetUnit**

Time unit associated with the relative date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingComplexEventRelativeDate](#)

**180.2.5606 UnderlyingComplexEventDateRelativeTo**

Specifies the anchor date when the complex event date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingComplexEventRelativeDate**

**180.2.5607 UnderlyingComplexEventDates**

The UnderlyingComplexEventDates and subcomponent UnderlyingComplexEventTimes components are used to constrain a complex event to a specific date range, and optional time range. If specified the event is only effective on or within the specified dates and times.

Name	Mult.	Type	Description
NoUnderlyingComplexEventDates	[1..1]	NumInGroup	
UnderlyingComplexEventStartDate	[0..1]	UTCDateOnly	Required if NoUnderlyingComplexEventDates(2054) > 0.
UnderlyingComplexEventEndDate	[0..1]	UTCDateOnly	Required if NoUnderlyingComplexEventDates(2054) > 0.
UnderlyingComplexEventTimes	[0..*]	Group	

Used in groups: **UnderlyingComplexEvents**

**180.2.5608 UnderlyingComplexEventDateUnadjusted**

The unadjusted complex event date.

Type: **LocalMktDate**

Used in components: **UnderlyingComplexEventRelativeDate**

**180.2.5609 UnderlyingComplexEventDeterminationMethod**

Specifies the method according to which an amount or a date is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **UnderlyingComplexEvents**

**180.2.5610 UnderlyingComplexEventEndDate**

The end date of the date range on which a complex event is effective. The start date will be set equal to the end date for single day events such as Bermuda options.

UnderlyingComplexEventEndDate(2056) must always be greater than or equal to UnderlyingComplexEventStartDate(2055).

Type: **UTCDateOnly**

Used in groups: **UnderlyingComplexEventDates**

**180.2.5611 UnderlyingComplexEventEndTime**

The end time of the time range on which a complex event date is effective.

UnderlyingComplexEventEndTime(2058) must always be greater than or equal to UnderlyingComplexEventStartTime(2057).

Type: **UTCTimeOnly**

Used in groups: **UnderlyingComplexEventTimes**

**180.2.5612 UnderlyingComplexEventFixedFXRate**

Specifies the fixed FX rate alternative for FX Quanto options.

Type: **float**

Used in groups: **UnderlyingComplexEvents**

**180.2.5613 UnderlyingComplexEventFixingTime**

The local market fixing time.

Type: **LocalMktTime**

Used in components: **UnderlyingComplexEventRelativeDate**

**180.2.5614 UnderlyingComplexEventFixingTimeBusinessCenter**

The business center for determining the actual fixing times.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **UnderlyingComplexEventRelativeDate**

#### **180.2.5615 UnderlyingComplexEventForwardPoints**

FX forward points added to spot rate. May be a negative value.

Type: **PriceOffset**

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5616 UnderlyingComplexEventFuturesPriceValuation**

Indicates whether the official settlement price as announced by the related exchange is applicable, in accordance with the ISDA 2002 definitions. Applicable only to futures contracts.

Type: **Boolean**

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5617 UnderlyingComplexEventOptionsPriceValuation**

Indicates whether the official settlement price as announced by the related exchange is applicable, in accordance with the ISDA 2002 definitions. Applicable only to options contracts.

Type: **Boolean**

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5618 UnderlyingComplexEventPeriodDate**

The averaging date for an Asian option.

The trigger date for a Barrier or Knock option.

Type: **LocalMktDate**

Used in groups: **UnderlyingComplexEventPeriodDateGrp**

**180.2.5619 UnderlyingComplexEventPeriodDateGrp**

UnderlyingComplexEventPeriodDateGrp is a subcomponent of UnderlyingComplexEventPeriodGrp for specifying fixed period dates and times for an Asian or Strike Schedule option or trigger dates for a Barrier or Knock option.

Name	Mult.	Type	Description
NoUnderlyingComplexEventPeriod- DateTimes	[1..1]	NumInGroup	
UnderlyingComplexEventPeriodDate	[0..1]	LocalMktDate	Required if NoUnderlyingComplexEventPeriod- DateTimes(41726) > 0.
UnderlyingComplexEventPeriodTime	[0..1]	LocalMktTime	

Used in groups: [UnderlyingComplexEventPeriodGrp](#)

**180.2.5620 UnderlyingComplexEventPeriodGrp**

UnderlyingComplexEventPeriodGrp is a subcomponent of UnderlyingComplexEvents for specifying the periods for an Asian, Barrier, Knock or Strike Schedule option feature.

Name	Mult.	Type	Description
NoUnderlyingComplexEventPeriods	[1..1]	NumInGroup	
UnderlyingComplexEventPeriodType	[0..1]	CodeSet	Required if NoUnderlyingComplexEventPeriods(41729) > 0.
UnderlyingComplexEventBusiness- Center	[0..1]	String	
UnderlyingComplexEventScheduleGrp	[0..*]	Group	
UnderlyingComplexEventPeriodDate- Grp	[0..*]	Group	
UnderlyingComplexEventAveragin- gObservationGrp	[0..*]	Group	

Used in groups: [UnderlyingComplexEvents](#)

**180.2.5621 UnderlyingComplexEventPeriodTime**

The averaging time for an Asian option.

Type: **LocalMktTime**

Used in groups: **UnderlyingComplexEventPeriodDateGrp**

### **180.2.5622 UnderlyingComplexEventPeriodType**

Specifies the period type.

Type: **int**

Allowed values in ComplexEventPeriodTypeCodeSet:

Code	Name	Description
0	AsianOut	Asian Out
1	AsianIn	Asian In
2	BarrierCap	Barrier Cap
3	BarrierFloor	Barrier Floor
4	KnockOut	Knock Out
5	KnockIn	Knock In

Used in groups: **UnderlyingComplexEventPeriodGrp**

### **180.2.5623 UnderlyingComplexEventPrice**

Specifies the price at which the complex event takes effect. Impact of the event price is determined by the UnderlyingComplexEventType(2046).

Type: **Price**

Used in groups: **UnderlyingComplexEvents**

### **180.2.5624 UnderlyingComplexEventPriceBoundaryMethod**

Specifies the boundary condition to be used for the event price relative to the UnderlyingComplexEventPrice(2048) at the point the complex event outcome takes effect as determined by the UnderlyingComplexEventPriceTimeType(2051).

Type: **int**

Allowed values in ComplexEventPriceBoundaryMethodCodeSet:

Code	Name	Description
1	LessThanComplexEventPrice	Less than ComplexEventPrice(1486)
2	LessThanOrEqualToComplexEvent- Price	Less than or equal to ComplexEventPrice(1486)
3	EqualToComplexEventPrice	Equal to ComplexEventPrice(1486)
4	GreaterThanOrEqualToComplex- EventPrice	Greater than or equal to ComplexEventPrice(1486)
5	GreaterThanComplexEventPrice	Greater than ComplexEventPrice(1486)

Used in groups: [UnderlyingComplexEvents](#)

#### **180.2.5625 UnderlyingComplexEventPriceBoundaryPrecision**

Used in combination with UnderlyingComplexEventPriceBoundaryMethod(2049) to specify the percentage of the strike price in relation to the underlying price. The percentage is generally 100 or greater for puts and 100 or less for calls.

Type: [Percentage](#)

Used in groups: [UnderlyingComplexEvents](#)

#### **180.2.5626 UnderlyingComplexEventPricePercentage**

Specifies the price percentage at which the complex event takes effect. Impact of the event price is determined by the UnderlyingComplexEventType(2046).

Type: [Percentage](#)

Used in groups: [UnderlyingComplexEvents](#)

#### **180.2.5627 UnderlyingComplexEventPriceTimeType**

Specifies when the complex event outcome takes effect. The outcome of a complex event is a payout or barrier action as specified by the UnderlyingComplexEventType(2046).

Type: [int](#)

Allowed values in ComplexEventPriceTimeTypeCodeSet:

Code	Name	Description
1	Expiration	Expiration
2	Immediate	Immediate (At Any Time)
3	SpecifiedDate	Specified Date/Time
4	Close	Close. Official closing time of the exchange on valuation date.
5	Open	Open. Official opening time of the exchange on valuation date.
6	OfficialSettlPrice	Official settlement price. Official settlement price determination time.
7	DerivativesClose	Derivatives close. Official closing time of the derivatives exchange.
8	AsSpecifiedMasterConfirmation	As specified in Master Confirmation

Used in groups: **UnderlyingComplexEvents**

#### 180.2.5628 UnderlyingComplexEventPVFinalPriceElectionFallback

Specifies the fallback provisions for the hedging party in the determination of the final settlement price

Type: **int**

Allowed values in ComplexEventPVFinalPriceElectionFallbackCodeSet:

Code	Name	Description
0	Close	Close. In respect of the "early final valuation date", the provisions for "future present value close" shall apply.
1	HedgeElection	Hedge election. In respect of the "early final valuation date", the provisions for "future present value hedge execution" shall apply.

Used in groups: **UnderlyingComplexEvents**

#### 180.2.5629 UnderlyingComplexEventQuoteBasis

Specifies the currency pairing for the quote.

Type: **int**



Allowed values in ComplexEventQuoteBasisCodeSet:

Code	Name	Description
0	Currency1PerCurrency2	Currency 1 per currency 2
1	Currency2PerCurrency1	Currency 2 per currency 1

Used in groups: **UnderlyingComplexEvents**

### 180.2.5630 UnderlyingComplexEventRateSource

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: **UnderlyingComplexEventRateSourceGrp**

### 180.2.5631 UnderlyingComplexEventRateSourceGrp

UnderlyingComplexEventRateSourceGrp is a subcomponent of UnderlyingComplexEvents for specifying primary and secondary rate sources.

Name	Mult.	Type	Description
<b>NoUnderlyingComplexEventRateSources</b>	[1..1]	NumInGroup	

Name	Mult.	Type	Description
<a href="#">UnderlyingComplexEventRateSource</a>	[0..1]	CodeSet	Required if NoUnderlyingComplexEventRateSources(41732) > 0.
<a href="#">UnderlyingComplexEventRateSource-Type</a>	[0..1]	CodeSet	Required if NoUnderlyingComplexEventRateSources(41732) > 0.
<a href="#">UnderlyingComplexEventReferencePage</a>	[0..1]	String	Conditionally required when ComplexEventRateSource(41014) = 99 (Other).
<a href="#">UnderlyingComplexEventReferencePageHeading</a>	[0..1]	String	

Used in groups: [UnderlyingComplexEvents](#)

### 180.2.5632 UnderlyingComplexEventRateSourceType

Indicates whether the rate source specified is a primary or secondary source.

Type: [int](#)

Allowed values in RateSourceTypeCodeSet:

Code	Name	Description
0	Primary	Primary
1	Secondary	Secondary

Used in groups: [UnderlyingComplexEventRateSourceGrp](#)

### 180.2.5633 UnderlyingComplexEventReferencePage

Identifies the reference page from the rate source.

For FX, the reference page to the spot rate is to be used for the reference FX spot rate.

When UnderlyingComplexEventRateSource(41733) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>.

Type: [String](#)

Used in groups: [UnderlyingComplexEventRateSourceGrp](#)

**180.2.5634 UnderlyingComplexEventReferencePageHeading**

Identifies the reference page heading from the rate source.

Type: **String**

Used in groups: **UnderlyingComplexEventRateSourceGrp**

**180.2.5635 UnderlyingComplexEventRelativeDate**

UnderlyingComplexEventRelativeDate is a subcomponent of UnderlyingComplexEvents for specifying the event date and time for an FX or Calendar Spread option or the payout date for a Barrier or Knock option.

Name	Mult.	Type	Description
UnderlyingComplexEventDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingComplexEventDateRelativeTo	[0..1]	int	
UnderlyingComplexEventDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingComplexEventDateOffsetUnit(41742) is specified.
UnderlyingComplexEventDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingComplexEventDateOffsetPeriod(41741) is specified.
UnderlyingComplexEventDateOffsetDayType	[0..1]	CodeSet	
UnderlyingComplexEventDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to the underlying complex event dates.
UnderlyingComplexEventDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to the underlying complex event dates.
UnderlyingComplexEventDateAdjusted	[0..1]	LocalMktDate	
UnderlyingComplexEventFixingTime	[0..1]	LocalMktTime	
UnderlyingComplexEventFixingTimeBusinessCenter	[0..1]	String	

Used in groups: [UnderlyingComplexEvents](#)

#### **180.2.5636 UnderlyingComplexEventScheduleEndDate**

The end date of the schedule.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingComplexEventScheduleGrp](#)

#### **180.2.5637 UnderlyingComplexEventScheduleFrequencyPeriod**

Time unit multiplier for the schedule date frequency.

Type: [int](#)

Used in groups: [UnderlyingComplexEventScheduleGrp](#)

#### **180.2.5638 UnderlyingComplexEventScheduleFrequencyUnit**

Time unit associated with the schedule date frequency.

Type: [String](#)

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [UnderlyingComplexEventScheduleGrp](#)

#### **180.2.5639 UnderlyingComplexEventScheduleGrp**

[UnderlyingComplexEventScheduleGrp](#) is a subcomponent of [UnderlyingComplexEventPeriodGrp](#) for specifying a periodic schedule for an Asian, Barrier or Strike Schedule option feature.

Name	Mult.	Type	Description
NoUnderlyingComplexEventSchedules	[1..1]	NumInGroup	
UnderlyingComplexEventScheduleStartDate	[0..1]	LocalMktDate	Required if NoUnderlyingComplexEventSchedules(41750) > 0.
UnderlyingComplexEventScheduleEndDate	[0..1]	LocalMktDate	
UnderlyingComplexEventScheduleFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingComplexEventScheduleFrequencyUnit(41754) is specified.
UnderlyingComplexEventScheduleFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingComplexEventScheduleFrequencyPeriod(41753) is specified.
UnderlyingComplexEventScheduleRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the option schedule dates.

Used in groups: **UnderlyingComplexEventPeriodGrp**

#### 180.2.5640 UnderlyingComplexEventScheduleRollConvention

The convention for determining the sequence of dates. It is used in conjunction with a specified frequency. Used only to override the roll convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month

Code	Name	Description
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEigthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.

Code	Name	Description
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in groups: [UnderlyingComplexEventScheduleGrp](#)

#### 180.2.5641 UnderlyingComplexEventScheduleStartDate

The start date of the schedule.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingComplexEventScheduleGrp](#)

#### 180.2.5642 UnderlyingComplexEvents

The UnderlyingComplexEvent Group is a repeating block which allows specifying an unlimited number and types of advanced events, such as observation and pricing in over the lifetime of an option, futures, commodities or equity swap contract. Use UnderlyingEvntGrp to specify more straightforward events.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingComplexEvents</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingComplexEventType</a>	[0..1]	CodeSet	Required if NoUnderlyingComplexEvents(2045) > 0.
<a href="#">UnderlyingComplexOptPayoutPaySide</a>	[0..1]	CodeSet	
<a href="#">UnderlyingComplexOptPayoutReceiveSide</a>	[0..1]	CodeSet	
<a href="#">UnderlyingComplexOptPayoutUnderlier</a>	[0..1]	String	

Name	Mult.	Type	Description
UnderlyingComplexOptPayoutAmount	[0..1]	Amt	
UnderlyingComplexOptPayoutPercentage	[0..1]	Percentage	
UnderlyingComplexOptPayoutTime	[0..1]	CodeSet	
UnderlyingComplexOptPayoutCurrency	[0..1]	Currency	
UnderlyingComplexOptPayoutCurrencyCodeSource	[0..1]	CodeSet	
UnderlyingComplexEventPrice	[0..1]	Price	
UnderlyingComplexEventPricePercentage	[0..1]	Percentage	
UnderlyingComplexEventPriceBoundaryMethod	[0..1]	CodeSet	
UnderlyingComplexEventPriceBoundaryPrecision	[0..1]	Percentage	
UnderlyingComplexEventPriceTimeType	[0..1]	CodeSet	
UnderlyingComplexEventCondition	[0..1]	CodeSet	Conditionally required when there are more than one UnderlyingComplexEvent occurrences. A chain of events must be linked together through use of the UnderlyingComplexEventCondition(2052) in which the relationship between any two events is described. For any two occurrences of events the first occurrence will specify the UnderlyingComplexEventCondition(2052) which links it with the second event.
UnderlyingComplexEventDates	[0..*]	Group	
UnderlyingComplexEventCurrencyOne	[0..1]	Currency	
UnderlyingComplexEventCurrencyOneCodeSource	[0..1]	CodeSet	
UnderlyingComplexEventCurrencyTwo	[0..1]	Currency	
UnderlyingComplexEventCurrencyTwoCodeSource	[0..1]	CodeSet	
UnderlyingComplexEventQuoteBasis	[0..1]	CodeSet	
UnderlyingComplexEventFixedFXRate	[0..1]	float	
UnderlyingComplexEventSpotRate	[0..1]	Price	
UnderlyingComplexEventForwardPoints	[0..1]	PriceOffset	



Name	Mult.	Type	Description
UnderlyingComplexEventDeterminationMethod	[0..1]	String	
UnderlyingComplexEventCalculationAgent	[0..1]	CodeSet	
UnderlyingComplexEventStrikePrice	[0..1]	Price	
UnderlyingComplexEventStrikeFactor	[0..1]	float	
UnderlyingComplexEventStrikeNumberOfOptions	[0..1]	int	
UnderlyingComplexEventRateSourceGrp	[0..*]	Group	
UnderlyingComplexEventRelativeDate	[0..1]	Component	
UnderlyingComplexEventPeriodGrp	[0..*]	Group	
UnderlyingComplexEventCreditEventsXIDRef	[0..1]	XIDREF	
UnderlyingComplexEventCreditEventNotifyingParty	[0..1]	CodeSet	
UnderlyingComplexEventCreditEventBusinessCenter	[0..1]	String	
UnderlyingComplexEventCreditEventStandardSources	[0..1]	Boolean	
UnderlyingComplexEventCreditEventMinimumSources	[0..1]	int	
UnderlyingComplexEventCreditEventSourceGrp	[0..*]	Group	
UnderlyingComplexEventCreditEventGrp	[0..*]	Group	
UnderlyingComplexEventFuturesPriceValuation	[0..1]	Boolean	
UnderlyingComplexEventOptionsPriceValuation	[0..1]	Boolean	
UnderlyingComplexEventPVFinalPriceElectionFallback	[0..1]	CodeSet	
UnderlyingComplexEventXID	[0..1]	XID	
UnderlyingComplexEventXIDRef	[0..1]	XIDREF	

Used in components: [UnderlyingInstrument](#)

**180.2.5643 UnderlyingComplexEventSpotRate**

FX spot rate.

Type: **Price**

Used in groups: **UnderlyingComplexEvents**

**180.2.5644 UnderlyingComplexEventStartDate**

The start date of the date range on which a complex event is effective. The start date will be set equal to the end date for single day events such as Bermuda options.

The start date must always be less than or equal to end date.

Type: **UTCDateOnly**

Used in groups: **UnderlyingComplexEventDates**

**180.2.5645 UnderlyingComplexEventStartTime**

The start time of the time range on which a complex event date is effective.

UnderlyingComplexEventStartTime(2057) must always be less than or equal to UnderlyingComplexEventEndTime(2058).

Type: **UTCTimeOnly**

Used in groups: **UnderlyingComplexEventTimes**

**180.2.5646 UnderlyingComplexEventStrikeFactor**

Strike factor for Asian option feature. Upper strike percentage for a Strike Spread.

Type: **float**

Used in groups: **UnderlyingComplexEvents**

**180.2.5647 UnderlyingComplexEventStrikeNumberOfOptions**

Upper string number of options for a Strike Spread.

Type: **int**

Used in groups: **UnderlyingComplexEvents**

**180.2.5648 UnderlyingComplexEventStrikePrice**

Upper strike price for Asian option feature. Strike percentage for a Strike Spread.

Type: **Price**

Used in groups: **UnderlyingComplexEvents**

**180.2.5649 UnderlyingComplexEventTimes**

The UnderlyingComplexEventTimes is a repeating subcomponent of the UnderlyingComplexEvent-Dates component. It is used to further qualify any dates placed on the event and is used to specify time ranges for which a complex event is effective. It is always provided within the context of start and end dates. The time range is assumed to be in effect for the entirety of the date or date range specified.

Name	Mult.	Type	Description
NoUnderlyingComplexEventTimes	[1..1]	NumInGroup	
UnderlyingComplexEventStartTime	[0..1]	UTCTimeOnly	Required if NoUnderlyingComplexEventTimes(2056) > 0.
UnderlyingComplexEventEndTime	[0..1]	UTCTimeOnly	Required if NoUnderlyingComplexEventTimes(2056) > 0.

Used in groups: **UnderlyingComplexEventDates**

**180.2.5650 UnderlyingComplexEventType**

Identifies the type of complex event.

Type: **int**

Allowed values in ComplexEventTypeCodeSet:

Code	Name	Description
1	Capped	Capped
2	Trigger	Trigger
3	KnockInUp	Knock-in up
4	KnockInDown	Knock-in down
5	KnockOutUp	Knock-out up
6	KnockOutDown	Knock-out down

Code	Name	Description
7	Underlying	Underlying
8	ResetBarrier	Reset Barrier
9	RollingBarrier	Rolling Barrier
10	OneTouch	One-touch
11	NoTouch	No-touch
12	DblOneTouch	Double one-touch
13	DblNoTouch	Double no-touch
14	FXComposite	Foreign exchange composite
15	FXQuanto	Foreign exchange Quanto
16	FXCrssCcy	Foreign exchange cross currency
17	StrkSpread	Strike spread
18	ClndrSpread	Calendar spread
19	PxObsvtn	Price observation (Asian or Lookback)
20	PassThrough	Pass-through
21	StrkSched	Strike schedule
22	EquityValuation	Equity valuation
23	DividendValuation	Dividend valuation

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5651 UnderlyingComplexEventXID**

Identifier of this complex event for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **UnderlyingComplexEvents**

#### **180.2.5652 UnderlyingComplexEventXIDRef**

Reference to a complex event elsewhere in the message.

Type: **XIDREF**

Used in groups: **UnderlyingComplexEvents**

**180.2.5653 UnderlyingComplexOptPayoutAmount**

Cash amount indicating the pay out associated with an event. For binary options this is a fixed amount.

Type: **Amt**

Used in groups: **UnderlyingComplexEvents**

**180.2.5654 UnderlyingComplexOptPayoutCurrency**

Specifies the currency of the payout amount.

UnderlyingComplexOptPayoutCurrencyCodeSource(2947) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in groups: **UnderlyingComplexEvents**

**180.2.5655 UnderlyingComplexOptPayoutCurrencyCodeSource**

Identifies class or source of the UnderlyingComplexOptPayoutCurrency(2266) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **UnderlyingComplexEvents**

**180.2.5656 UnderlyingComplexOptPayoutPaySide**

Trade side of payout payer.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **UnderlyingComplexEvents**

**180.2.5657 UnderlyingComplexOptPayoutPercentage**

Percentage of observed price for calculating the payout associated with the event.

Type: **Percentage**

Used in groups: **UnderlyingComplexEvents**

**180.2.5658 UnderlyingComplexOptPayoutReceiveSide**

Trade side of payout receiver.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **UnderlyingComplexEvents**

**180.2.5659 UnderlyingComplexOptPayoutTime**

The time when the payout is to occur.

Type: **int**

Allowed values in ComplexOptPayoutTimeCodeSet:

Code	Name	Description
0	Close	Close
1	Open	Open
2	OfficialSettl	Official settlement
3	ValuationTime	Valuation time
4	ExchagneSettlTime	Exchange settlement time
5	DerivativesClose	Derivatives close
6	AsSpecified	As specified in master confirmation

Used in groups: **UnderlyingComplexEvents**

**180.2.5660 UnderlyingComplexOptPayoutUnderlier**

Reference to the underlier whose payments are being passed through.

Type: **String**

Used in groups: **UnderlyingComplexEvents**

**180.2.5661 UnderlyingConstituentWeight**

For a basket, or pool, describes the weight of each of the constituents within the basket. If not provided, it is assumed to be equal weighted.

Type: **float**

Used in components: **UnderlyingInstrument**

**180.2.5662 UnderlyingContractMultiplier**

Underlying security's ContractMultiplier.

See ContractMultiplier (231) field for description

Type: **float**

Used in components: **UnderlyingInstrument**

#### **180.2.5663 UnderlyingContractMultiplierUnit**

Indicates the type of multiplier being applied to the contract.

Type: **int**

Allowed values in ContractMultiplierUnitCodeSet:

Code	Name	Description
0	Shares	Shares
1	Hours	Hours
2	Days	Days

Used in components: **UnderlyingInstrument**

#### **180.2.5664 UnderlyingContractPriceRefMonth**

Reference month if there is no applicable UnderlyingMaturityMonth(313) value for the contract or security.

Type: **MonthYear**

Used in components: **UnderlyingInstrument**

#### **180.2.5665 UnderlyingContractSettlMonth**

Specifies when the contract (i.e. MBS/TBA) will settle. Must be present for MBS/TBA.

Type: **MonthYear**

Used in components: **UnderlyingInstrument**

#### **180.2.5666 UnderlyingContraryInstructionEligibilityIndicator**

Identifies whether the option instrument is eligible for contrary instructions at the time of exercise. The contrariness of an instruction will be determined in the context of UnderlyingInTheMoneyCondition(2683). When not specified, the eligibility is undefined or not applicable.



Type: **Boolean**

Used in components: **UnderlyingInstrument**

### **180.2.5667 UnderlyingCountryOfIssue**

Underlying security's CountryOfIssue.

See CountryOfIssue (470) field for description

Type: **Country**

Used in components: **UnderlyingInstrument**

### **180.2.5668 UnderlyingCouponDayCount**

The day count convention used in interest calculations for a bond or an interest bearing security.

Type: **int**

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.

Code	Name	Description
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.

Code	Name	Description
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.

Code	Name	Description
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: [UnderlyingInstrument](#)

### 180.2.5669 UnderlyingCouponFrequencyPeriod

Time unit multiplier for the frequency of the bond's coupon payment.

Type: [int](#)

Used in components: [UnderlyingInstrument](#)

### 180.2.5670 UnderlyingCouponFrequencyUnit

Time unit associated with the frequency of the bond's coupon payment.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second

Code	Name	Description
T	Term	Term

Used in components: [UnderlyingInstrument](#)

#### **180.2.5671 UnderlyingCouponOtherDayCount**

The industry name of the day count convention not listed in UnderlyingCouponDayCount(1993).

Type: [String](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5672 UnderlyingCouponPaymentDate**

Underlying security's CouponPaymentDate.

See CouponPaymentDate (224) field for description

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCTDate)

Type: [LocalMktDate](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5673 UnderlyingCouponRate**

Underlying security's CouponRate.

See CouponRate (223) field for description

Type: [Percentage](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5674 UnderlyingCouponType**

Specifies the coupon type of the underlying bond.

Type: [int](#)

Allowed values in CouponTypeCodeSet:

Code	Name	Description
0	Zero	Zero
1	FixedRate	Fixed rate
2	FloatingRate	Floating rate
3	Structured	Structured

Used in components: [UnderlyingInstrument](#)

### 180.2.5675 UnderlyingCPPProgram

The program under which the underlying commercial paper is issued

Type: [int](#)

Allowed values in CPPProgramCodeSet:

Code	Name	Description
1	Program3a3	3(a)(3). Arising out of a current transaction with a maturity less than 9 months.
2	Program42	4(2). Issued not involving any public offering.
3	Program3a2	3(a)(2). Issued or guaranteed by the US, state or territorial government.
4	Program3a3And3c7	3(a)(3) & 3(c)(7). Combination of 3(a)(3) and 3(c)(7).
5	Program3a4	3(a)(4). Religious, education, benevolent, fraternal, charitable or reformatory purposes.
6	Program3a5	3(a)(5). Issued by an institution supervised by state or federal authority or by an exempt farmer's cooperative.
7	Program3a7	3(a)(7). Issued by a receiver or trustee in bankruptcy.
8	Program3c7	3(c)(7). Qualified hedge-fund under the Investment Company Act of 1940.
99	Other	Other

Used in components: [UnderlyingInstrument](#)

**180.2.5676 UnderlyingCPRegType**

The registration type of the underlying commercial paper issuance

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5677 UnderlyingCreditRating**

Underlying security's CreditRating.

See CreditRating (255) field for description

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5678 UnderlyingCurrency**

Underlying security's currency.

Type: **Currency**

Used in components: **UnderlyingInstrument**

**180.2.5679 UnderlyingCurrencyCodeSource**

Identifies class or source of the UnderlyingCurrency(318) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5680 UnderlyingCurrentValue**

Currency value currently attributed to this collateral

Type: [Amt](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5681 UnderlyingDateAdjustment**

UnderlyingDateAdjustment is a subcomponent within the UnderlyingInstrument component. It is used to specify date adjustment parameters and rules. The date adjustments specified here applies to all adjustable dates for the underlying instrument, unless specifically overridden in the respective specified components further within the UnderlyingInstrument component.

Name	Mult.	Type	Description
<a href="#">UnderlyingBusinessDayConvention</a>	[0..1]	CodeSet	
<a href="#">UnderlyingBusinessCenterGrp</a>	[0..*]	Group	
<a href="#">UnderlyingDateRollConvention</a>	[0..1]	CodeSet	

Used in components: [UnderlyingInstrument](#)

#### **180.2.5682 UnderlyingDatedDate**

If different from IssueDate()

Type: [LocalMktDate](#)

Used in components: [UnderlyingInstrument](#)



**180.2.5683 UnderlyingDateRollConvention**

The convention for determining a sequence of dates. It is used in conjunction with a specified frequency. The value defined here applies to all adjustable dates in the underlying instrument unless specifically overridden.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month

Code	Name	Description
28	TwentyEighthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [UnderlyingDateAdjustment](#)

### 180.2.5684 UnderlyingDeliveryAmount

Indicates the underlying position amount to be delivered

Type: [Amt](#)

Used in groups: [PosUndInstrmtGrp](#)

**180.2.5685 UnderlyingDeliveryRouteOrCharter**

Specific delivery route or time charter average. Applicable to commodity freight contracts.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5686 UnderlyingDeliveryScheduleGrp**

The UnderlyingDeliveryScheduleGrp is a repeating subcomponent of the UnderlyingStream component used to detail step schedules associated with a delivery stream.

Name	Mult.	Type	Description
NoUnderlyingDeliverySchedules	[1..1]	NumInGroup	
UnderlyingDeliveryScheduleType	[0..1]	CodeSet	Required if NoUnderlyingDeliverySchedules(41756) > 0.
UnderlyingDeliveryScheduleXID	[0..1]	XID	
UnderlyingDeliveryScheduleNotional	[0..1]	Qty	
UnderlyingDeliveryScheduleNotionalUnitOfMeasure	[0..1]	CodeSet	
UnderlyingDeliveryScheduleNotionalCommodityFrequency	[0..1]	CodeSet	
UnderlyingDeliveryScheduleNegativeTolerance	[0..1]	float	
UnderlyingDeliverySchedulePositiveTolerance	[0..1]	float	
UnderlyingDeliveryScheduleToleranceUnitOfMeasure	[0..1]	CodeSet	
UnderlyingDeliveryScheduleToleranceType	[0..1]	CodeSet	Conditionally required when UnderlyingDeliveryScheduleNegativeTolerance(41762) or UnderlyingDeliverySchedulePositiveTolerance(41763) is specified.
UnderlyingDeliveryScheduleSettlCountry	[0..1]	Country	
UnderlyingDeliveryScheduleSettlTimeZone	[0..1]	String	
UnderlyingDeliveryScheduleSettlFlowType	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingDeliveryScheduleSettlHolidaysProcessingInstruction	[0..1]	CodeSet	
UnderlyingDeliveryScheduleSettlDayGrp	[0..*]	Group	

Used in groups: [UnderlyingStreamGrp](#)

### 180.2.5687 UnderlyingDeliveryScheduleNegativeTolerance

Specifies the negative tolerance value. The value may be an absolute quantity or a percentage, as specified in UnderlyingDeliveryScheduleToleranceType(41765). Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: [float](#)

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

### 180.2.5688 UnderlyingDeliveryScheduleNotional

Physical delivery quantity.

Type: [Qty](#)

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

### 180.2.5689 UnderlyingDeliveryScheduleNotionalCommodityFrequency

The frequency of notional delivery.

Type: [int](#)

Allowed values in StreamNotionalCommodityFrequencyCodeSet:

Code	Name	Description
0	Term	Term
1	PerBusinessDay	Per business day
2	PerCalculationPeriod	Per calculation period
3	PerSettlPeriod	Per settlement period

Code	Name	Description
4	PerCalendarDay	Per calendar day
5	PerHour	Per hour
6	PerMonth	Per month

Used in groups: **UnderlyingDeliveryScheduleGrp**

### 180.2.5690 UnderlyingDeliveryScheduleNotionalUnitOfMeasure

Specifies the delivery quantity unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU

Code	Name	Description
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter

Code	Name	Description
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

**180.2.5691 UnderlyingDeliverySchedulePositiveTolerance**

Specifies the positive tolerance value. The value may be an absolute quantity or a percentage, as specified in UnderlyingDeliveryScheduleToleranceType(41765). Value may exceed agreed upon value. Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **float**

Used in groups: **UnderlyingDeliveryScheduleGrp**

**180.2.5692 UnderlyingDeliveryScheduleSettlCountry**

Specifies the country where delivery takes place. Uses ISO 3166 2-character country code.

Type: **Country**

Used in groups: **UnderlyingDeliveryScheduleGrp**

**180.2.5693 UnderlyingDeliveryScheduleSettlDay**

Specifies the day or group of days for delivery.

Type: **int**

Allowed values in DeliveryScheduleSettlDayCodeSet:

Code	Name	Description
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday
8	AllWeekdays	All weekdays
9	AllDays	All days
10	AllWeekends	All weekends

Used in groups: **UnderlyingDeliveryScheduleSettlDayGrp**



**180.2.5694 UnderlyingDeliveryScheduleSettlDayGrp**

The UnderlyingDeliveryScheduleSettlDayGrp is a repeating subcomponent of the UnderlyingDeliveryScheduleGrp component used to detail commodity delivery days.

Name	Mult.	Type	Description
NoUnderlyingDeliveryScheduleSettlDays	[1..1]	NumInGroup	
UnderlyingDeliveryScheduleSettlDay	[0..1]	CodeSet	Required if NoUnderlyingDeliveryScheduleSettlDays(41770) > 0.
UnderlyingDeliveryScheduleSettlTotalHours	[0..1]	int	
UnderlyingDeliveryScheduleSettlTimeGrp	[0..*]	Group	

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

**180.2.5695 UnderlyingDeliveryScheduleSettlEnd**

The scheduled end time for the delivery of the commodity where delivery occurs over specified times. The format of the time value is specified in UnderlyingDeliveryScheduleSettlTimeType(41776).

Type: [String](#)

Used in groups: [UnderlyingDeliveryScheduleSettlTimeGrp](#)

**180.2.5696 UnderlyingDeliveryScheduleSettlFlowType**

Specifies the delivery flow type.

Type: [int](#)

Allowed values in DeliveryScheduleSettlFlowTypeCodeSet:

Code	Name	Description
0	AllTimes	All times
1	OnPeak	On peak
2	OffPeak	Off peak

Code	Name	Description
3	Base	Base
4	BlockHours	Block hours
5	Other	Other

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

#### **180.2.5697 UnderlyingDeliveryScheduleSettlHolidaysProcessingInstruction**

Indicates whether holidays are included in the settlement periods. Required for electricity contracts.

Type: [int](#)

Allowed values in DeliveryScheduleSettlHolidaysProcessingInstructionCodeSet:

Code	Name	Description
0	DoNotIncludeHolidays	Do not include holidays
1	IncludeHolidays	Include holidays

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

#### **180.2.5698 UnderlyingDeliveryScheduleSettlStart**

The scheduled start time for the delivery of the commodity where delivery occurs over specified times. The format of the time value is specified in UnderlyingDeliveryScheduleSettlTimeType(41776).

Type: [String](#)

Used in groups: [UnderlyingDeliveryScheduleSettlTimeGrp](#)

#### **180.2.5699 UnderlyingDeliveryScheduleSettlTimeGrp**

The UnderlyingDeliveryScheduleSettlTimeGrp is a repeating subcomponent of the UnderlyingDeliveryScheduleSettlDayGrp component used to detail commodity delivery time periods.

Name	Mult.	Type	Description
NoUnderlyingDeliveryScheduleSettlTimes	[1..1]	NumInGroup	
UnderlyingDeliveryScheduleSettlStart	[0..1]	String	Required if NoUnderlyingDeliveryScheduleSettlTimes(41773) > 0.
UnderlyingDeliveryScheduleSettlEnd	[0..1]	String	Required if NoUnderlyingDeliveryScheduleSettlTimes(41773) > 0.
UnderlyingDeliveryScheduleSettlTimeType	[0..1]	CodeSet	May be defaulted to market convention or bilaterally agreed if not specified.

Used in groups: **UnderlyingDeliveryScheduleSettlDayGrp**

### 180.2.5700 UnderlyingDeliveryScheduleSettlTimeType

Specifies the format of the delivery start and end time values.

Type: **int**

Allowed values in DeliveryScheduleSettlTimeTypeCodeSet:

Code	Name	Description
0	Hour	Hour of the day. Applicable for electricity contracts. Time value is expressed as an integer hour of the day (1-24). The delivery start/end hour is specified as the end of the included hour. For example, a start hour of "4" begins at 3 a.m.; an end hour of "20" ends at 8 p.m.; a start hour of "1" and end hour of "24" indicates midnight to midnight delivery.
1	Timestamp	HH:MM time format. Applicable for gas contracts. Time value is expressed using a 24-hour time format. For example, a time value of "13:30" is 1:30 p.m.

Used in groups: **UnderlyingDeliveryScheduleSettlTimeGrp**

### 180.2.5701 UnderlyingDeliveryScheduleSettlTimeZone

Delivery timezone specified as "prevailing" rather than "standard" or "daylight".

See [http://www.fixtradingcommunity.org/codelists#Prevailing\\_Timezones](http://www.fixtradingcommunity.org/codelists#Prevailing_Timezones) for code list of applicable prevailing timezones.

Type: **String**

Used in groups: **UnderlyingDeliveryScheduleGrp**

### **180.2.5702 UnderlyingDeliveryScheduleSettlTotalHours**

The sum of the total hours specified in the UnderlyingDeliveryScheduleSettlTimeGrp component.

Type: **int**

Used in groups: **UnderlyingDeliveryScheduleSettlDayGrp**

### **180.2.5703 UnderlyingDeliveryScheduleToleranceType**

Specifies the tolerance value type.

Type: **int**

Allowed values in DeliveryScheduleToleranceTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in groups: **UnderlyingDeliveryScheduleGrp**

### **180.2.5704 UnderlyingDeliveryScheduleToleranceUnitOfMeasure**

Specifies the tolerance value's unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches

Code	Name	Description
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)

Code	Name	Description
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart

Code	Name	Description
Sqcm	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
Sqkm	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

---

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

#### **180.2.5705 UnderlyingDeliveryScheduleType**

Specifies the type of delivery schedule.

Type: [int](#)

Allowed values in DeliveryScheduleTypeCodeSet:

Code	Name	Description
0	Notional	Notional
1	Delivery	Delivery
2	PhysicalSettlPeriods	Physical settlement period

---

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

#### **180.2.5706 UnderlyingDeliveryScheduleXID**

Identifier for this instance of delivery schedule for cross referencing elsewhere in the message.

Type: [XID](#)

Used in groups: [UnderlyingDeliveryScheduleGrp](#)

**180.2.5707 UnderlyingDeliveryStreamCommoditySource**

The SCoTA coal cargo origin, mining region, mine(s), mining complex(es), loadout(s) or river dock(s) or other point(s) of origin that seller and buyer agree are acceptable origins for the coal product. For international coal transactions, this is the origin of the coal product.

See <http://www.fpml.org/coding-scheme/commodity-coal-product-source> for values.

Type: **String**

Used in groups: **UnderlyingDeliveryStreamCommoditySourceGrp**

**180.2.5708 UnderlyingDeliveryStreamCommoditySourceGrp**

The UnderlyingDeliveryStreamCommoditySourceGrp is a repeating subcomponent of the UnderlyingDeliveryStream component used to detail the origins or sources of the commodity.

Name	Mult.	Type	Description
<b>NoUnderlyingDeliveryStreamCommoditySources</b>	[1..1]	NumInGroup	
<b>UnderlyingDeliveryStreamCommoditySource</b>	[0..1]	String	Required if NoUnderlyingDeliveryStreamCommoditySources(41808) > 0.

Used in components: **UnderlyingDeliveryStream**

**180.2.5709 UnderlyingDeliveryStream**

The UnderlyingDeliveryStream component is a subcomponent of the UnderlyingStream used to detail the attributes of a physical delivery stream in a swap.

Name	Mult.	Type	Description
<b>UnderlyingDeliveryStreamType</b>	[0..1]	CodeSet	
<b>UnderlyingDeliveryStreamCommoditySourceGrp</b>	[0..*]	Group	
<b>UnderlyingDeliveryStreamPipeline</b>	[0..1]	String	
<b>UnderlyingDeliveryStreamEntryPoint</b>	[0..1]	String	
<b>UnderlyingDeliveryStreamWithdrawalPoint</b>	[0..1]	String	



Name	Mult.	Type	Description
UnderlyingDeliveryStreamDelivery-Point	[0..1]	String	
UnderlyingDeliveryStreamDelivery-PointSource	[0..1]	CodeSet	
UnderlyingDeliveryStreamDelivery-PointDesc	[0..1]	String	
UnderlyingDeliveryStreamDeliveryRe- striction	[0..1]	CodeSet	
UnderlyingDeliveryStreamDeliv- eryContingency	[0..1]	String	
UnderlyingDeliveryStreamDeliv- eryContingentPartySide	[0..1]	CodeSet	
UnderlyingDeliveryStreamDeliverAt- SourceIndicator	[0..1]	Boolean	
UnderlyingDeliveryStreamRiskAppor- tionment	[0..1]	String	
UnderlyingDeliveryStreamRiskAppor- tionmentSource	[0..1]	String	
UnderlyingDeliveryStreamCycleGrp	[0..*]	Group	
UnderlyingDeliveryStreamTitleTrans- ferLocation	[0..1]	String	
UnderlyingDeliveryStreamTitleTrans- ferCondition	[0..1]	CodeSet	
UnderlyingDeliveryStreamIm- porterOfRecord	[0..1]	String	
UnderlyingDeliveryStreamNegativeTol- erance	[0..1]	float	
UnderlyingDeliveryStreamPositiveTol- erance	[0..1]	float	
UnderlyingDeliveryStreamToleranceU- nitOfMeasure	[0..1]	CodeSet	
UnderlyingDeliveryStreamTolerance- Type	[0..1]	CodeSet	
UnderlyingDeliveryStreamToler- anceOptionSide	[0..1]	CodeSet	
UnderlyingDeliveryStreamTotalPosi- tiveTolerance	[0..1]	Percentage	
UnderlyingDeliveryStreamTotalNega- tiveTolerance	[0..1]	Percentage	

Name	Mult.	Type	Description
UnderlyingDeliveryStreamNotional-ConversionFactor	[0..1]	float	
UnderlyingDeliveryStreamTransportEquipment	[0..1]	String	
UnderlyingDeliveryStreamElectingPartySide	[0..1]	CodeSet	
UnderlyingDeliveryStreamRouteOrCharter	[0..1]	String	

Used in groups: [UnderlyingStreamGrp](#)

### 180.2.5710 UnderlyingDeliveryStreamCycleDesc

The delivery cycles during which the oil product will be transported in the pipeline.

Type: [String](#)

Used in groups: [UnderlyingDeliveryStreamCycleGrp](#)

### 180.2.5711 UnderlyingDeliveryStreamCycleGrp

The UnderlyingDeliveryStreamCycleGrp is a repeating subcomponent of the UnderlyingDeliveryStream component used to detail delivery cycles during which the oil product will be transported in the pipeline.

Name	Mult.	Type	Description
NoUnderlyingDeliveryStreamCycles	[1..1]	NumInGroup	
UnderlyingDeliveryStreamCycleDesc	[0..1]	String	Required if NoUnderlyingDeliveryStreamCycles(41804) > 0.
EncodedUnderlyingDeliveryStreamCycleDescLen	[0..1]	Length	Must be set if EncodedUnderlyingDeliveryStreamCycleDesc(41807) field is specified and must immediately precede it.
EncodedUnderlyingDeliveryStreamCycleDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingDeliveryStreamCycleDesc(41805) field in the encoded format specified via the MessageEncoding(347) field.

Used in components: [UnderlyingDeliveryStream](#)

**180.2.5712 UnderlyingDeliveryStreamDeliverAtSourceIndicator**

When this element is specified and set to 'Y', delivery of the coal product is to be at its source.

Type: **Boolean**

Used in components: **UnderlyingDeliveryStream**

**180.2.5713 UnderlyingDeliveryStreamDeliveryContingency**

Specifies the electricity delivery contingency.

See <http://www.fpml.org/coding-scheme/electricity-transmission-contingency> for values.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5714 UnderlyingDeliveryStreamDeliveryContingentPartySide**

The trade side value of the party responsible for electricity delivery contingency.

Type: **int**

Allowed values in DeliveryStreamElectingPartySideCodeSet:

Code	Name	Description
0	Buyer	Buyer
1	Seller	Seller

Used in components: **UnderlyingDeliveryStream**

**180.2.5715 UnderlyingDeliveryStreamDeliveryPoint**

The point at which the commodity product will be delivered and received. Value specified should follow market convention appropriate for the commodity product.

For bullion see <http://www.fpml.org/coding-scheme/bullion-delivery-location> for values.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5716 UnderlyingDeliveryStreamDeliveryPointDesc**

Description of the delivery point identified in UnderlyingDeliveryStreamDeliveryPoint(41781).

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5717 UnderlyingDeliveryStreamDeliveryPointSource**

Identifies the class or source of UnderlyingDeliveryStreamDeliveryPoint(41781).

Type: **int**

Allowed values in DeliveryStreamDeliveryPointSourceCodeSet:

Code	Name	Description
0	Proprietary	Proprietary
1	EIC	Energy Identification Code (EIC). Energy Identification Code specifies the location or connection point codes of energy delivery. See <a href="http://www.entsog.eu/eic-codes/eic-location-codes-v">http://www.entsog.eu/eic-codes/eic-location-codes-v</a> or <a href="http://www.eiccodes.eu">http://www.eiccodes.eu</a> for more information and allocated values to use in DeliveryStreamDeliveryPoint(41062).

Used in components: **UnderlyingDeliveryStream**

**180.2.5718 UnderlyingDeliveryStreamDeliveryRestriction**

Specifies under what conditions the buyer and seller should be excused of their delivery obligations.

Type: **int**

Allowed values in DeliveryStreamDeliveryRestrictionCodeSet:

Code	Name	Description
1	Firm	Firm. Never excused of delivery obligations.
2	NonFirm	Interruptable or non-firm. Excused when interrupted for any reason or for no reason without liability.
3	ForceMajeure	Force majeure. Excused when prevented by force majeure.

Code	Name	Description
4	SystemFirm	System firm. Must be supplied from the owned or controlled generation of pre-existing purchased power assets of the system specified.
5	UnitFirm	Unit firm. Must be supplied from the generation asset specified.

Used in components: [UnderlyingDeliveryStream](#)

### 180.2.5719 UnderlyingDeliveryStreamElectingPartySide

A reference to the party able to choose whether the gas is delivered for a particular period e.g. a swing or interruptible contract.

Type: [int](#)

Allowed values in DeliveryStreamElectingPartySideCodeSet:

Code	Name	Description
0	Buyer	Buyer
1	Seller	Seller

Used in components: [UnderlyingDeliveryStream](#)

### 180.2.5720 UnderlyingDeliveryStreamEntryPoint

The point at which the commodity will enter the delivery mechanism or pipeline.

Type: [String](#)

Used in components: [UnderlyingDeliveryStream](#)

### 180.2.5721 UnderlyingDeliveryStreamImporterOfRecord

A party, not necessarily of the trade, who is the Importer of Record for the purposes of paying customs duties and applicable taxes or costs related to importation.

Type: [String](#)

Used in components: [UnderlyingDeliveryStream](#)

**180.2.5722 UnderlyingDeliveryStreamNegativeTolerance**

Specifies the negative tolerance value. The value may be an absolute quantity or a percentage, as specified in UnderlyingDeliveryStreamToleranceType(41793). Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **float**

Used in components: **UnderlyingDeliveryStream**

**180.2.5723 UnderlyingDeliveryStreamNotionalConversionFactor**

If the notional quantity is specified in a unit that does not match the unit in which the commodity reference price is quoted, the scaling or conversion factor used to convert the commodity reference price unit into the notional quantity unit should be stated here. If there is no conversion, this field is not intended to be used.

Type: **float**

Used in components: **UnderlyingDeliveryStream**

**180.2.5724 UnderlyingDeliveryStreamPipeline**

The name of the oil delivery pipeline.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5725 UnderlyingDeliveryStreamPositiveTolerance**

Specifies the positive tolerance value. The value may be an absolute quantity or a percentage, as specified in UnderlyingDeliveryStreamToleranceType(41793). Value may exceed agreed upon value. Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **float**

Used in components: **UnderlyingDeliveryStream**

**180.2.5726 UnderlyingDeliveryStreamRiskApportionment**

Specifies how the parties to the trade apportion responsibility for the delivery of the commodity product.

See [http://www.fixtradingcommunity.org/codelists#Risk\\_Apportionment](http://www.fixtradingcommunity.org/codelists#Risk_Apportionment) for the details of the external code list.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5727 UnderlyingDeliveryStreamRiskApportionmentSource**

Specifies the source or legal framework for the risk apportionment.

See [http://www.fixtradingcommunity.org/codelists#Risk\\_Apportionment\\_Source](http://www.fixtradingcommunity.org/codelists#Risk_Apportionment_Source) for the details of the external code list.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5728 UnderlyingDeliveryStreamRouteOrCharter**

Specific delivery route or time charter average. Applicable to commodity freight swaps.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5729 UnderlyingDeliveryStreamTitleTransferCondition**

Specifies the title transfer condition.

Type: **int**

Allowed values in DeliveryStreamTitleTransferConditionCodeSet:

---

Code	Name	Description
0	Transfers	Transfers with risk of loss
1	DoesNotTransfer	Does not transfer with risk of loss

---

Used in components: **UnderlyingDeliveryStream**

**180.2.5730 UnderlyingDeliveryStreamTitleTransferLocation**

Specifies the title transfer location.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5731 UnderlyingDeliveryStreamToleranceOptionSide**

Indicates whether the tolerance is at the seller's or buyer's option.

Type: **int**

Allowed values in DeliveryStreamToleranceOptionSideCodeSet:

Code	Name	Description
1	Buyer	Buyer
2	Seller	Seller

Used in components: **UnderlyingDeliveryStream**

**180.2.5732 UnderlyingDeliveryStreamToleranceType**

Specifies the tolerance value type.

Type: **int**

Allowed values in DeliveryScheduleToleranceTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in components: **UnderlyingDeliveryStream**



**180.2.5733 UnderlyingDeliveryStreamToleranceUnitOfMeasure**

Specifies the tolerance value's unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [UnderlyingDeliveryStream](#)

#### **180.2.5734 UnderlyingDeliveryStreamTotalNegativeTolerance**

The negative percent tolerance which applies to the total quantity delivered over all shipment periods.

Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: [Percentage](#)

Used in components: [UnderlyingDeliveryStream](#)

**180.2.5735 UnderlyingDeliveryStreamTotalPositiveTolerance**

The positive percent tolerance which applies to the total quantity delivered over all shipment periods.

Percentage value is to be expressed relative to "1.0" representing 100% (e.g. a value of "0.0575" represents 5.75%).

Type: **Percentage**

Used in components: **UnderlyingDeliveryStream**

**180.2.5736 UnderlyingDeliveryStreamTransportEquipment**

The transportation equipment with which the commodity product will be delivered and received.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

**180.2.5737 UnderlyingDeliveryStreamType**

Specifies the type of delivery stream.

Type: **int**

Allowed values in DeliveryStreamTypeCodeSet:

Code	Name	Description
0	Periodic	Periodic (default if not specified)
1	Initial	Initial
2	Single	Single

Used in components: **UnderlyingDeliveryStream**

**180.2.5738 UnderlyingDeliveryStreamWithdrawalPoint**

The point at which the commodity product will be withdrawn prior to delivery.

Type: **String**

Used in components: **UnderlyingDeliveryStream**

### **180.2.5739 UnderlyingDepositoryReceiptIndicator**

Indicates whether the underlier is a depository receipt.

Type: **Boolean**

Used in components: **UnderlyingInstrument**

### **180.2.5740 UnderlyingDetachmentPoint**

See DetachmentPoint(1458).

Type: **Percentage**

Used in components: **UnderlyingInstrument**

### **180.2.5741 UnderlyingDirtyPrice**

Price (percent-of-par or per unit) of the underlying security or basket. "Dirty" means it includes accrued interest

Type: **Price**

Used in components: **UnderlyingInstrument**

### **180.2.5742 UnderlyingDividendAccrualFixedRate**

The dividend accrual fixed rate per annum expressed as a decimal.

A value of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **UnderlyingDividendConditions**

### **180.2.5743 UnderlyingDividendAccrualFloatingRate**

The UnderlyingDividendAccrualFloatingRate component is a subcomponent of UnderlyingDividendConditions used to define the dividend accrual floating rate attributes of dividend payment conditions.

Name	Mult.	Type	Description
UnderlyingDividendFloatingRateIndex	[0..1]	String	
UnderlyingDividendFloatingRateIndex-CurvePeriod	[0..1]	int	Conditionally required when UnderlyingDividendFloatingRateIndexCurveUnit(42803) is specified.
UnderlyingDividendFloatingRateIndex-CurveUnit	[0..1]	CodeSet	Conditionally required when UnderlyingDividendFloatingRateIndexCurvePeriod(42802) is specified.
UnderlyingDividendFloatingRateMultiplier	[0..1]	float	
UnderlyingDividendFloatingRate-Spread	[0..1]	PriceOffset	
UnderlyingDividendFloatingRate-SpreadPositionType	[0..1]	CodeSet	
UnderlyingDividendFloatingRateTreatment	[0..1]	CodeSet	
UnderlyingDividendCapRate	[0..1]	Percentage	
UnderlyingDividendCapRateBuySide	[0..1]	CodeSet	
UnderlyingDividendCapRateSellSide	[0..1]	CodeSet	
UnderlyingDividendFloorRate	[0..1]	Percentage	
UnderlyingDividendFloorRateBuySide	[0..1]	CodeSet	
UnderlyingDividendFloorRateSellSide	[0..1]	CodeSet	
UnderlyingDividendInitialRate	[0..1]	Percentage	
UnderlyingDividendFinalRateRoundingDirection	[0..1]	CodeSet	
UnderlyingDividendFinalRatePrecision	[0..1]	int	
UnderlyingDividendAveragingMethod	[0..1]	CodeSet	
UnderlyingDividendNegativeRate-Treatment	[0..1]	CodeSet	

Used in components: [UnderlyingDividendConditions](#)

#### 180.2.5744 UnderlyingDividendAccrualPaymentDateAdjusted

The adjusted accrual payment date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingDividendAccrualPaymentDate](#)

**180.2.5745 UnderlyingDividendAccrualPaymentDateBusinessCenter**

The business center calendar used for date adjustment of the instrument's dividend accrual payment date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingDividendAccrualPaymentDateBusinessCenterGrp**

**180.2.5746 UnderlyingDividendAccrualPaymentDateBusinessCenterGrp**

UnderlyingDividendAccrualPaymentDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingDividendAccrualPaymentDate component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
NoUnderlyingDividendAccrualPaymentDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingDividendAccrualPaymentDateBusinessCenter	[0..1]	String	Required if NoUnderlyingDividendAccrualPaymentDateBusinessCenters(42799) > 0.

Used in components: **UnderlyingDividendAccrualPaymentDate**

**180.2.5747 UnderlyingDividendAccrualPaymentDateBusinessDayConvention**

Accrual payment date adjustment business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.

Code	Name	Description
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingDividendAccrualPaymentDate](#)

### 180.2.5748 UnderlyingDividendAccrualPaymentDate

The UnderlyingDividendAccrualPaymentDate component is a subcomponent of UnderlyingDividendConditions used to report the dividend accrual payment date.

Name	Mult.	Type	Description
<a href="#">UnderlyingDividendAccrualPayment-DateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingDividendAccrualPayment-DateOffsetPeriod</a>	[0..1]	int	Conditionally required when UnderlyingDividendAccrualPaymentDateOffsetUnit(42821) is specified.
<a href="#">UnderlyingDividendAccrualPayment-DateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when UnderlyingDividendAccrualPaymentDateOffsetPeriod(42820) is specified.
<a href="#">UnderlyingDividendAccrualPayment-DateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingDividendAccrualPayment-DateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingDividendAccrualPayment-DateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The value would be specific to this instance of UnderlyingDividendAccrualPaymentDate.
<a href="#">UnderlyingDividendAccrualPayment-DateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The values would be specific to this instance of UnderlyingDividendAccrualPaymentDate.
<a href="#">UnderlyingDividendAccrualPayment-DateAdjusted</a>	[0..1]	LocalMktDate	



Used in components: [UnderlyingDividendConditions](#)

#### **180.2.5749 UnderlyingDividendAccrualPaymentDateOffsetDayType**

Specifies the day type of the relative accrual payment date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingDividendAccrualPaymentDate](#)

#### **180.2.5750 UnderlyingDividendAccrualPaymentDateOffsetPeriod**

Time unit multiplier for the relative accrual payment date offset.

Type: [int](#)

Used in components: [UnderlyingDividendAccrualPaymentDate](#)

#### **180.2.5751 UnderlyingDividendAccrualPaymentDateOffsetUnit**

Time unit associated with the relative accrual payment date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week

Code	Name	Description
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingDividendAccrualPaymentDate](#)

#### **180.2.5752 UnderlyingDividendAccrualPaymentDateRelativeTo**

Specifies the anchor date when the accrual payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [UnderlyingDividendAccrualPaymentDate](#)

#### **180.2.5753 UnderlyingDividendAccrualPaymentDateUnadjusted**

The unadjusted accrual payment date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingDividendAccrualPaymentDate](#)

#### **180.2.5754 UnderlyingDividendAccruedInterest**

Accrued interest on the dividend or coupon payment.

Type: [Amt](#)

Used in groups: [UnderlyingDividendPaymentGrp](#)

#### **180.2.5755 UnderlyingDividendAmountType**

Indicates how the gross cash dividend amount per share is determined.

Type: [int](#)

Allowed values in DividendAmountTypeCodeSet:

Code	Name	Description
0	RecordAmount	Record amount. 100% of the gross cash dividend per share paid over record date during relevant dividend period.
1	ExAmount	Ex amount. 100% of gross cash dividend per share paid after the ex-dividend date during relevant dividend period.
2	PaidAmount	Paid amount. 100% of gross cash dividend per share paid during relevant dividend period.
3	PerMasterConfirm	As specified in master confirmation. The amount is determined as provided in the relevant master confirmation.

Used in components: [UnderlyingDividendConditions](#)

### 180.2.5756 UnderlyingDividendAveragingMethod

When averaging is applicable, used to specify whether a weighted or unweighted average method of calculation is to be used.

Type: [int](#)

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### 180.2.5757 UnderlyingDividendCapRate

The cap rate, if any, which applies to the floating rate. It is only required where the floating rate is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as "0.05".

Type: [Percentage](#)

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

**180.2.5758 UnderlyingDividendCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingDividendAccrualFloatingRate**

**180.2.5759 UnderlyingDividendCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingDividendAccrualFloatingRate**

**180.2.5760 UnderlyingDividendCashEquivalentPercentage**

Declared cash-equivalent dividend percentage. A value of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **UnderlyingDividendConditions**

**180.2.5761 UnderlyingDividendCashPercentage**

Declared cash dividend percentage.

A value of 5% would be represented as "0.05".

Type: **Percentage**

Used in components: **UnderlyingDividendConditions**

**180.2.5762 UnderlyingDividendComposition**

Defines how the composition of dividends is to be determined.

Type: **int**

Allowed values in DividendCompositionCodeSet:

Code	Name	Description
0	EquityAmountReceiver	Equity amount receiver election. The equity amount receiver determines the composition of dividends (subject to conditions).
1	CalculationAgent	Calculation agent election. The calculation agent determines the composition of dividends (subject to conditions).

Used in components: **UnderlyingDividendConditions**

**180.2.5763 UnderlyingDividendCompoundingMethod**

The compounding method to be used when more than one dividend period contributes to a single payment.

Type: **int**

Allowed values in PaymentStreamCompoundingMethodCodeSet:

Code	Name	Description
0	None	None
1	Flat	Flat
2	Straight	Straight
3	SpreadExclusive	Spread exclusive

Used in components: [UnderlyingDividendConditions](#)

### 180.2.5764 UnderlyingDividendConditions

The UnderlyingDividendConditions component is a subcomponent of UnderlyingPaymentStream used to specify the conditions' valuations and dates governing the payment of dividends.

Name	Mult.	Type	Description
<a href="#">UnderlyingDividendReinvestmentIndicator</a>	[0..1]	Boolean	
<a href="#">UnderlyingDividendEntitlementEvent</a>	[0..1]	CodeSet	
<a href="#">UnderlyingDividendAmountType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingDividendUnderlierRefID</a>	[0..1]	String	
<a href="#">UnderlyingDividendPeriodGrp</a>	[0..*]	Group	
<a href="#">UnderlyingExtraordinaryDividendPartySide</a>	[0..1]	CodeSet	
<a href="#">UnderlyingExtraordinaryDividendAmountType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingExtraordinaryDividendCurrency</a>	[0..1]	Currency	
<a href="#">UnderlyingExtraordinaryDividendTerminationMethod</a>	[0..1]	String	
<a href="#">UnderlyingDividendFXTriggerDate</a>	[0..1]	Component	
<a href="#">UnderlyingDividendAccrualFloatingRate</a>	[0..1]	Component	
<a href="#">UnderlyingDividendAccrualFixedRate</a>	[0..1]	Percentage	
<a href="#">UnderlyingDividendAccrualPaymentDate</a>	[0..1]	Component	
<a href="#">UnderlyingDividendCompoundingMethod</a>	[0..1]	CodeSet	
<a href="#">UnderlyingDividendNumOfIndexUnits</a>	[0..1]	int	
<a href="#">UnderlyingDividendCashPercentage</a>	[0..1]	Percentage	
<a href="#">UnderlyingDividendCashEquivalentPercentage</a>	[0..1]	Percentage	
<a href="#">UnderlyingNonCashDividendTreatment</a>	[0..1]	CodeSet	
<a href="#">UnderlyingDividendComposition</a>	[0..1]	CodeSet	
<a href="#">UnderlyingSpecialDividendsIndicator</a>	[0..1]	Boolean	

Name	Mult.	Type	Description
<a href="#">UnderlyingMaterialDividendsIndicator</a>	[0..1]	Boolean	
<a href="#">UnderlyingOptionsExchangeDividendsIndicator</a>	[0..1]	Boolean	
<a href="#">UnderlyingAdditionalDividendsIndicator</a>	[0..1]	Boolean	
<a href="#">UnderlyingAllDividendsIndicator</a>	[0..1]	Boolean	

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### 180.2.5765 UnderlyingDividendEntitlementEvent

Defines the contract event which the receiver of the derivative is entitled to the dividend.

Type: [int](#)

Allowed values in DividendEntitlementEventCodeSet:

Code	Name	Description
0	ExDate	Ex-date. Dividend entitlement is on the dividend ex-date.
1	RecordDate	Record date. Dividend entitlement is on the dividend record date.

Used in components: [UnderlyingDividendConditions](#)

### 180.2.5766 UnderlyingDividendFinalRatePrecision

Specifies the rounding precision of the final rate in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: [int](#)

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### 180.2.5767 UnderlyingDividendFinalRateRoundingDirection

Specifies the rounding direction of the final rate.

Type: [char](#)

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### **180.2.5768 UnderlyingDividendFloatingRateIndex**

The dividend accrual floating rate index.

Type: [String](#)

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### **180.2.5769 UnderlyingDividendFloatingRateIndexCurvePeriod**

Time unit multiplier for the dividend accrual floating rate index curve.

Type: [int](#)

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### **180.2.5770 UnderlyingDividendFloatingRateIndexCurveUnit**

Time unit associated with the dividend accrual floating rate index curve period.

Type: [String](#)

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingDividendAccrualFloatingRate](#)



**180.2.5771 UnderlyingDividendFloatingRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This should only be included if the multiplier is not equal to 1 (one) for the term of the contract.

Type: **float**

Used in components: **UnderlyingDividendAccrualFloatingRate**

**180.2.5772 UnderlyingDividendFloatingRateSpread**

The basis points spread from the index specified in UnderlyingDividendFloatingRateIndex(42801).

Type: **PriceOffset**

Used in components: **UnderlyingDividendAccrualFloatingRate**

**180.2.5773 UnderlyingDividendFloatingRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: **UnderlyingDividendAccrualFloatingRate**

**180.2.5774 UnderlyingDividendFloatingRateTreatment**

Specifies the yield calculation treatment for the index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### 180.2.5775 UnderlyingDividendFloorRate

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate. The rate is expressed as a decimal, e.g. 5% is represented as "0.05".

Type: [Percentage](#)

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### 180.2.5776 UnderlyingDividendFloorRateBuySide

Reference to the buyer of the floor rate option through its trade side.

Type: [int](#)

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### 180.2.5777 UnderlyingDividendFloorRateSellSide

Reference to the seller of the floor rate option through its trade side.

Type: [int](#)

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [UnderlyingDividendAccrualFloatingRate](#)

### 180.2.5778 UnderlyingDividendFXTriggerDateAdjusted

The adjusted FX trigger date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingDividendFXTriggerDate](#)

### 180.2.5779 UnderlyingDividendFXTriggerDateBusinessCenter

The business center calendar used for date adjustment of the instrument's FX trigger date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingDividendFXTriggerDateBusinessCenterGrp](#)

### 180.2.5780 UnderlyingDividendFXTriggerDateBusinessCenterGrp

[UnderlyingDividendFXTriggerDateBusinessCenterGrp](#) is a repeating subcomponent within the [UnderlyingDividendFXTriggerDate](#) component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingDividendFXTriggerDate-BusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingDividendFXTriggerDate-BusinessCenter</a>	[0..1]	String	Required if <a href="#">NoUnderlyingDividendFXTriggerDate-BusinessCenters</a> (42853) > 0.

Used in components: [UnderlyingDividendFXTriggerDate](#)

**180.2.5781 UnderlyingDividendFXTriggerDateBusinessDayConvention**

The business day convention used for the FX trigger date adjustment.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **UnderlyingDividendFXTriggerDate**

**180.2.5782 UnderlyingDividendFXTriggerDate**

The UnderlyingDividendFXTriggerDate component is a subcomponent of UnderlyingDividendConditions used to report the dividend date when a foreign exchange trade is triggered.

Name	Mult.	Type	Description
<b>UnderlyingDividendFXTriggerDateRelativeTo</b>	[0..1]	int	
<b>UnderlyingDividendFXTriggerDateOffsetPeriod</b>	[0..1]	int	Conditionally required when UnderlyingDividendFXTriggerDateOffsetUnit(42848) is specified.
<b>UnderlyingDividendFXTriggerDateOffsetUnit</b>	[0..1]	CodeSet	Conditionally required when UnderlyingDividendFXTriggerDateOffsetPeriod(42847) is specified.
<b>UnderlyingDividendFXTriggerDateOffsetDayType</b>	[0..1]	CodeSet	
<b>UnderlyingDividendFXTriggerDateUnadjusted</b>	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
<a href="#">UnderlyingDividendFXTriggerDate-BusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The value would be specific to this instance of UnderlyingDividendFXTriggerDate.
<a href="#">UnderlyingDividendFXTriggerDate-BusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The values would be specific to this instance of UnderlyingDividendFXTriggerDate.
<a href="#">UnderlyingDividendFXTriggerDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [UnderlyingDividendConditions](#)

### 180.2.5783 UnderlyingDividendFXTriggerDateOffsetDayType

Specifies the day type of the relative FX trigger date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingDividendFXTriggerDate](#)

### 180.2.5784 UnderlyingDividendFXTriggerDateOffsetPeriod

Time unit multiplier for the relative FX trigger date offset.

Type: **int**

Used in components: **UnderlyingDividendFXTriggerDate**

#### **180.2.5785 UnderlyingDividendFXTriggerDateOffsetUnit**

Time unit associated with the relative FX trigger date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingDividendFXTriggerDate**

#### **180.2.5786 UnderlyingDividendFXTriggerDateRelativeTo**

Specifies the anchor date when the FX trigger date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingDividendFXTriggerDate**

#### **180.2.5787 UnderlyingDividendFXTriggerDateUnadjusted**

The unadjusted FX trigger date.

Type: **LocalMktDate**

Used in components: **UnderlyingDividendFXTriggerDate**

**180.2.5788 UnderlyingDividendInitialRate**

The initial floating rate reset agreed between the principal parties involved in the trade. This is assumed to be the first required reset rate for the first regular calculation period. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. The initial rate is expressed in decimal form, e.g. 5% is represented as "0.05".

Type: **Percentage**

Used in components: **UnderlyingDividendAccrualFloatingRate**

**180.2.5789 UnderlyingDividendNegativeRateTreatment**

The specification of any provisions for calculating payment obligations when a floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: **UnderlyingDividendAccrualFloatingRate**

**180.2.5790 UnderlyingDividendNumOfIndexUnits**

The number of index units applicable to dividends.

Type: **int**

Used in components: **UnderlyingDividendConditions**

**180.2.5791 UnderlyingDividendPaymentAmount**

The amount of the dividend or coupon payment.

Type: **Amt**

Used in groups: **UnderlyingDividendPaymentGrp**

**180.2.5792 UnderlyingDividendPaymentCurrency**

Specifies the currency the UnderlyingDividendPaymentAmount(42857) is denominated in. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingDividendPaymentGrp**

**180.2.5793 UnderlyingDividendPaymentDate**

Specifies the date that the dividend or coupon payment is due.

Type: **LocalMktDate**

Used in groups: **UnderlyingDividendPaymentGrp**

**180.2.5794 UnderlyingDividendPaymentGrp**

UnderlyingDividendPaymentGrp is a repeating subcomponent of UnderlyingDividendPayout used to specify the anticipated dividend or coupon payment dates and amounts of an equity or bond underlier.

Name	Mult.	Type	Description
NoUnderlyingDividendPayments	[1..1]	NumInGroup	
UnderlyingDividendPaymentDate	[0..1]	LocalMktDate	Required if NoUnderlyingDividendPayments (42855) > 0.
UnderlyingDividendPaymentAmount	[0..1]	Amt	Required if NoUnderlyingDividendPayments (42855) > 0.
UnderlyingDividendPaymentCurrency	[0..1]	Currency	
UnderlyingDividendAccruedInterest	[0..1]	Amt	

Used in components: **UnderlyingDividendPayout**

**180.2.5795 UnderlyingDividendPayout**

UnderlyingDividendPayout is a subcomponent of UnderlyingInstrument used to specify the dividend or coupon payout parameters of an equity or bond underlier.



Name	Mult.	Type	Description
UnderlyingDividendPayoutRatio	[0..1]	float	
UnderlyingDividendPayoutConditions	[0..1]	String	
UnderlyingDividendPaymentGrp	[0..*]	Group	

Used in components: [UnderlyingInstrument](#)

#### **180.2.5796 UnderlyingDividendPayoutConditions**

Specifies the dividend payout conditions that will be applied in the case where the actual ratio is not known, typically because of regulatory or legal uncertainties.

Type: [String](#)

Used in components: [UnderlyingDividendPayout](#)

#### **180.2.5797 UnderlyingDividendPayoutRatio**

Specifies the actual dividend payout ratio associated with the equity or bond underlier.

Type: [float](#)

Used in components: [UnderlyingDividendPayout](#)

#### **180.2.5798 UnderlyingDividendPeriodBusinessCenter**

The business center calendar used for date adjustment of the instrument's dividend period date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingDividendPeriodBusinessCenterGrp](#)

#### **180.2.5799 UnderlyingDividendPeriodBusinessCenterGrp**

UnderlyingDividendPeriodBusinessCenterGrp is a repeating subcomponent within the UnderlyingDividendPeriodGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment.

Name	Mult.	Type	Description
NoUnderlyingDividendPeriodBusinessCenters	[1..1]	NumInGroup	
UnderlyingDividendPeriodBusinessCenter	[0..1]	String	Required if NoUnderlyingDividendPeriodBusinessCenters(42882) > 0.

Used in groups: [UnderlyingDividendPeriodGrp](#)

### 180.2.5800 UnderlyingDividendPeriodBusinessDayConvention

The dividend period dates business day convention.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [UnderlyingDividendPeriodGrp](#)

### 180.2.5801 UnderlyingDividendPeriodEndDateUnadjusted

The unadjusted date on which the dividend period will end.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingDividendPeriodGrp](#)

## 180.2.5802 UnderlyingDividendPeriodGrp

UnderlyingDividendPeriodGrp is a repeating subcomponent within the UnderlyingDividendConditions component. It is used to specify the valuation and payments dates of the dividend leg of a dividend swap.

Name	Mult.	Type	Description
NoUnderlyingDividendPeriods	[1..1]	NumInGroup	
UnderlyingDividendPeriodSequence	[0..1]	int	Required if NoUnderlyingDividendPeriods(42862) > 0.
UnderlyingDividendPeriodStartDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingDividendPeriodEndDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingDividendPeriodUnderlierRefID	[0..1]	String	When specified, this overrides UnderlyingDividendUnderlierRefID(42829). The specified value would be specific to this dividend period instance.
UnderlyingDividendPeriodStrikePrice	[0..1]	Price	
UnderlyingDividendPeriodBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this dividend period instance.
UnderlyingDividendPeriodBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this dividend period instance.
UnderlyingDividendPeriodValuationDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingDividendPeriodValuationDateRelativeTo	[0..1]	int	
UnderlyingDividendPeriodValuationDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingDividendPeriodValuationDateOffsetUnit(42872) is specified.
UnderlyingDividendPeriodValuationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingDividendPeriodValuationDateOffsetPeriod(42871) is specified.
UnderlyingDividendPeriodValuationDateOffsetDayType	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingDividendPeriodValuation-DateAdjusted	[0..1]	LocalMktDate	
UnderlyingDividendPeriodPaymentDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingDividendPeriodPaymentDateRelativeTo	[0..1]	int	
UnderlyingDividendPeriodPaymentDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingDividend-PeriodPaymentDateOffsetUnit(42878) is specified.
UnderlyingDividendPeriodPaymentDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingDividend-PeriodPaymentDateOffsetPeriod(42877) is specified.
UnderlyingDividendPeriodPaymentDateOffsetDayType	[0..1]	CodeSet	
UnderlyingDividendPeriodPaymentDateAdjusted	[0..1]	LocalMktDate	
UnderlyingDividendPeriodXID	[0..1]	XID	

Used in components: [UnderlyingDividendConditions](#)

### 180.2.5803 UnderlyingDividendPeriodPaymentDateAdjusted

The adjusted dividend period payment date.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingDividendPeriodGrp](#)

### 180.2.5804 UnderlyingDividendPeriodPaymentDateOffsetDayType

Specifies the day type of the relative dividend period payment date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar

Code	Name	Description
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [UnderlyingDividendPeriodGrp](#)

#### **180.2.5805 UnderlyingDividendPeriodPaymentDateOffsetPeriod**

Time unit multiplier for the relative dividend period payment date offset.

Type: [int](#)

Used in groups: [UnderlyingDividendPeriodGrp](#)

#### **180.2.5806 UnderlyingDividendPeriodPaymentDateOffsetUnit**

Time unit associated with the relative dividend period payment date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [UnderlyingDividendPeriodGrp](#)

#### **180.2.5807 UnderlyingDividendPeriodPaymentDateRelativeTo**

Specifies the anchor date when the dividend period payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in groups: [UnderlyingDividendPeriodGrp](#)

#### **180.2.5808 UnderlyingDividendPeriodPaymentDateUnadjusted**

The unadjusted dividend period payment date.

Type: **LocalMktDate**

Used in groups: **UnderlyingDividendPeriodGrp**

#### **180.2.5809 UnderlyingDividendPeriodSequence**

Defines the ordinal dividend period. E.g. 1 = First period, 2 = Second period, etc.

Type: **int**

Used in groups: **UnderlyingDividendPeriodGrp**

#### **180.2.5810 UnderlyingDividendPeriodStartDateUnadjusted**

The unadjusted date on which the dividend period will begin.

Type: **LocalMktDate**

Used in groups: **UnderlyingDividendPeriodGrp**

#### **180.2.5811 UnderlyingDividendPeriodStrikePrice**

Specifies the fixed strike price of the dividend period.

Type: **Price**

Used in groups: **UnderlyingDividendPeriodGrp**

#### **180.2.5812 UnderlyingDividendPeriodUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in groups: **UnderlyingDividendPeriodGrp**

**180.2.5813 UnderlyingDividendPeriodValuationDateAdjusted**

The adjusted dividend period valuation date.

Type: **LocalMktDate**

Used in groups: **UnderlyingDividendPeriodGrp**

**180.2.5814 UnderlyingDividendPeriodValuationDateOffsetDayType**

Specifies the day type of the relative dividend period valuation date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **UnderlyingDividendPeriodGrp**

**180.2.5815 UnderlyingDividendPeriodValuationDateOffsetPeriod**

Time unit multiplier for the relative dividend period valuation date offset.

Type: **int**

Used in groups: **UnderlyingDividendPeriodGrp**

**180.2.5816 UnderlyingDividendPeriodValuationDateOffsetUnit**

Time unit associated with the relative dividend period valuation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in groups: [UnderlyingDividendPeriodGrp](#)

#### **180.2.5817 UnderlyingDividendPeriodValuationDateRelativeTo**

Specifies the anchor date when the dividend period valuation date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in groups: [UnderlyingDividendPeriodGrp](#)

#### **180.2.5818 UnderlyingDividendPeriodValuationDateUnadjusted**

The unadjusted dividend period valuation date.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingDividendPeriodGrp](#)

#### **180.2.5819 UnderlyingDividendPeriodXID**

Identifier for linking this stream dividend period to an underlier through an instance of RelatedInstrumentGrp.

Type: [XID](#)

Used in groups: [UnderlyingDividendPeriodGrp](#)

#### **180.2.5820 UnderlyingDividendReinvestmentIndicator**

Indicates whether the dividend will be reinvested.

Type: [Boolean](#)

Used in components: [UnderlyingDividendConditions](#)



**180.2.5821 UnderlyingDividendUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in a separate instance of the UnderlyingInstrument component.

Type: **String**

Used in components: **UnderlyingDividendConditions**

**180.2.5822 UnderlyingEndPrice**

Price (percent-of-par or per unit) of the underlying security or basket at the end of the agreement.

Type: **Price**

Used in components: **UnderlyingInstrument**

**180.2.5823 UnderlyingEndValue**

Currency value attributed to this collateral at the end of the agreement

Type: **Amt**

Used in components: **UnderlyingInstrument**

**180.2.5824 UnderlyingEquityID**

Specifies the equity in which a convertible bond can be converted.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5825 UnderlyingEquityIDSource**

Identifies the source of the UnderlyingEquityID(1996).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)

Code	Name	Description
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5826 UnderlyingEventDate**

The date of the event.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingEvntGrp](#)

#### **180.2.5827 UnderlyingEventMonthYear**

Used with derivatives when an event is express as a month-year with optional day or month or week of month.

Format:

YYYYMM (e.g. 199903)

YYYYMMDD (e.g. 20030323)

YYYYMMwN (e.g. 200303w2) for week

A specific date can be appended to the month-year. For instance, if multiple event types exist in the same Year and Month, but actually at a different time, a value can be appended, such as "w" or "w2" to indicate week. Likewise, the day of monty (0-31) can be appended to indicate a specific event date.

Type: [MonthYear](#)

Used in groups: [UnderlyingEvntGrp](#)

#### **180.2.5828 UnderlyingEventPx**

Predetermined price of issue at event, if applicable.

Type: [Price](#)

Used in groups: [UnderlyingEvntGrp](#)

**180.2.5829 UnderlyingEventText**

Free form text to specify comments related to the event.

Type: **String**

Used in groups: **UnderlyingEvntGrp**

**180.2.5830 UnderlyingEventTime**

The time of the event. To be used in combination with UnderlyingEventDate(1983).

Type: **UTCTimestamp**

Used in groups: **UnderlyingEvntGrp**

**180.2.5831 UnderlyingEventTimePeriod**

Time unit multiplier for the event.

Type: **int**

Used in groups: **UnderlyingEvntGrp**

**180.2.5832 UnderlyingEventTimeUnit**

Time unit associated with the event.

Type: **String**

Used in groups: **UnderlyingEvntGrp**

**180.2.5833 UnderlyingEventType**

Code to represent the type of event.

Type: **int**

Allowed values in EventTypeCodeSet:

---

Code	Name	Description
1	Put	Put
2	Call	Call

---

Code	Name	Description
3	Tender	Tender
4	SinkingFundCall	Sinking fund call
5	Activation	Activation
6	Inactivation	Inactivation
7	LastEligibleTradeDate	Last eligible trade date
8	SwapStartDate	Swap start date
9	SwapEndDate	Swap end date
10	SwapRollDate	Swap roll date
11	SwapNextStartDate	Swap next start date
12	SwapNextRollDate	Swap next roll date
13	FirstDeliveryDate	First delivery date
14	LastDeliveryDate	Last delivery date
15	InitialInventoryDueDate	Initial inventory due date
16	FinalInventoryDueDate	Final inventory due date
17	FirstIntentDate	First intent date
18	LastIntentDate	Last intent date
19	PositionRemovalDate	Position removal date
20	MinimumNotice	Minimum notice
21	DeliveryStartTime	Delivery start time
22	DeliveryEndTime	Delivery end time
23	FirstNoticeDate	First notice date. The first day that a notice of intent to deliver a commodity can be made by a clearing house to a buyer in fulfillment of a given month's futures contract.
24	LastNoticeDate	Last notice date. The last day on which a clearing house may inform an investor that a seller intends to make delivery of a commodity that the investor previously bought in a futures contract. The date is governed by the rules of different exchanges and clearing houses, but may also be stated in the futures contract itself.
25	FirstExerciseDate	First exercise date
26	RedemptionDate	Redemption date
27	TrdCntntnEfctvDt	Trade continuation effective date
99	Other	Other

Used in groups: **UnderlyingEvntGrp**

### 180.2.5834 UnderlyingEvtGrp

The UnderlyingEvtGrp is a repeating subcomponent of the UnderlyingInstrument component used to specify straightforward events associated with the instrument. Examples include put and call dates for bonds and options; first exercise date for options; inventory and delivery dates for commodities; start, end and roll dates for swaps. Use UnderlyingComplexEvents for more advanced dates such as option, futures, commodities and equity swap observation and pricing events.

Name	Mult.	Type	Description
NoUnderlyingEvents	[1..1]	NumInGroup	
UnderlyingEventType	[0..1]	CodeSet	Required if NoUnderlyingEvents(1982) > 0.
UnderlyingEventDate	[0..1]	LocalMktDate	Conditionally required when UnderlyingEventTime(1984) is specified.
UnderlyingEventTime	[0..1]	UTCTimestamp	
UnderlyingEventTimeUnit	[0..1]	String	Conditionally required when UnderlyingEventTimePeriod(1986) is specified.
UnderlyingEventTimePeriod	[0..1]	int	Conditionally required when UnderlyingEventTimeUnit(1985) is specified.
UnderlyingEventMonthYear	[0..1]	MonthYear	
UnderlyingEventPx	[0..1]	Price	
UnderlyingEventText	[0..1]	String	
EncodedUnderlyingEventTextLen	[0..1]	Length	Must be set if EncodedUnderlyingEventText(2073) field is specified and must immediately precede it.
EncodedUnderlyingEventText	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingEventText(2071) field in the encoded format specified via the MessageEncoding(347) field.

Used in components: [UnderlyingInstrument](#)

### 180.2.5835 UnderlyingExchangeLookAlike

For a share option trade, indicates whether the instrument is to be treated as an 'exchange look-alike'.

Type: [Boolean](#)

Used in components: [UnderlyingInstrument](#)

**180.2.5836 UnderlyingExerciseConfirmationMethod**

Indicates whether follow-up confirmation of exercise (written or electronic) is required following telephonic notice by the buyer to the seller or seller's agent.

Type: **int**

Allowed values in ExerciseConfirmationMethodCodeSet:

Code	Name	Description
0	NotRequired	Not required
1	NonElectronic	Non-electronic
2	Electronic	Electronic
3	Unknown	Unknown at time of report

Used in components: **UnderlyingOptionExercise**

**180.2.5837 UnderlyingExerciseDesc**

A description of the option exercise.

Type: **String**

Used in components: **UnderlyingOptionExercise**

**180.2.5838 UnderlyingExerciseSplitTicketIndicator**

Indicates in physical settlement of bond and convertible bond options whether the party required to deliver the bonds will divide those to be delivered as notifying party desires to facilitate delivery obligations.

Type: **Boolean**

Used in components: **UnderlyingOptionExercise**

**180.2.5839 UnderlyingExerciseStyle**

Type of exercise of a derivatives security

Type: **int**

Allowed values in ExerciseStyleCodeSet:

Code	Name	Description
0	European	European
1	American	American
2	Bermuda	Bermuda
99	Other	Other

Used in components: [UnderlyingInstrument](#)

### 180.2.5840 UnderlyingExtraordinaryDividendAmountType

Indicates how the extraordinary gross cash dividend per share is determined.

Type: [int](#)

Allowed values in DividendAmountTypeCodeSet:

Code	Name	Description
0	RecordAmount	Record amount. 100% of the gross cash dividend per share paid over record date during relevant dividend period.
1	ExAmount	Ex amount. 100% of gross cash dividend per share paid after the ex-dividend date during relevant dividend period.
2	PaidAmount	Paid amount. 100% of gross cash dividend per share paid during relevant dividend period.
3	PerMasterConfirm	As specified in master confirmation. The amount is determined as provided in the relevant master confirmation.

Used in components: [UnderlyingDividendConditions](#)

### 180.2.5841 UnderlyingExtraordinaryDividendCurrency

The currency in which the excess dividend is denominated. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in components: [UnderlyingDividendConditions](#)



**180.2.5842 UnderlyingExtraordinaryDividendDeterminationMethod**

Specifies the method in which the excess amount is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in components: **UnderlyingDividendConditions**

**180.2.5843 UnderlyingExtraordinaryDividendPartySide**

Reference to the party through its side in the trade who makes the determination whether dividends are extraordinary in relation to normal levels.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingDividendConditions**

**180.2.5844 UnderlyingExtraordinaryEventAdjustmentMethod**

Defines how adjustments will be made to the contract should one or more of the extraordinary events occur.

Type: **int**

Allowed values in ExtraordinaryEventAdjustmentMethodCodeSet:

Code	Name	Description
0	CalculationAgent	Calculation agent. The Calculation Agent has the right to adjust the terms of the trade following a corporate action.
1	OptionsExchange	Options exchange. The trade will be adjusted in accordance with any adjustment made by the exchange on which options on the underlying are listed.

Used in components: **UnderlyingInstrument**

**180.2.5845 UnderlyingExtraordinaryEventGrp**

The UnderlyingExtraordinaryEventGrp is a repeating component within the UnderlyingInstrument component. It is used to report extraordinary and disruptive events applicable to the reference entity that affects the contract.

Name	Mult.	Type	Description
NoUnderlyingExtraordinaryEvents	[1..1]	NumInGroup	
UnderlyingExtraordinaryEventType	[0..1]	String	Required if NoUnderlyingExtraordinaryEvents(42884) > 0.
UnderlyingExtraordinaryEventValue	[0..1]	String	Required if NoUnderlyingExtraordinaryEvents(42884) > 0.

Used in components: [UnderlyingInstrument](#)

**180.2.5846 UnderlyingExtraordinaryEventType**

Identifies the type of extraordinary or disruptive event applicable to UnderlyingExtraordinaryEventType(42885).

See [http://www.fixtradingcommunity.org/codelists#Extraordinary\\_Event\\_Type](http://www.fixtradingcommunity.org/codelists#Extraordinary_Event_Type) for code list of extraordinary event types and values.

Type: [String](#)

Used in groups: [UnderlyingExtraordinaryEventGrp](#)

**180.2.5847 UnderlyingExtraordinaryEventValue**

The extraordinary or disruptive event value appropriate to UnderlyingExtraordinaryEventType(42885).

See [http://www.fixtradingcommunity.org/codelists#Extraordinary\\_Event\\_Type](http://www.fixtradingcommunity.org/codelists#Extraordinary_Event_Type) for code list of extraordinary event types and values.

Type: [String](#)

Used in groups: [UnderlyingExtraordinaryEventGrp](#)

#### **180.2.5848 UnderlyingFactor**

Underlying security's Factor.

See Factor (228) field for description

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **float**

Used in components: **UnderlyingInstrument**

#### **180.2.5849 UnderlyingFallbackExerciseIndicator**

Indicates whether the notional amount of the underlying swap, not previously exercised under the option, will be automatically exercised at the expiration time on the expiration date if at such time the buyer is in-the-money, provided that the difference between the settlement rate and the fixed rate under the relevant underlying swap is not less than one tenth of a percentage point (0.10% or 0.001).

Type: **Boolean**

Used in components: **UnderlyingOptionExercise**

#### **180.2.5850 UnderlyingFinancialInstrumentFullName**

The full normative name of the underlying financial instrument.

Type: **String**

Used in components: **UnderlyingInstrument**

#### **180.2.5851 UnderlyingFinancialInstrumentShortName**

Short name of the financial instrument. Uses ISO 18774 (FINS) values.

Type: **String**

Used in components: **UnderlyingInstrument**

#### **180.2.5852 UnderlyingFlexibleIndicator**

Used to indicate if a security has been defined as flexible according to "non-standard" means. Analog to CFICode Standard/Non-standard indicator.

Type: **Boolean**

Used in components: **UnderlyingInstrument**

### **180.2.5853 UnderlyingFlexProductEligibilityIndicator**

Used to indicate if a product or group of product supports the creation of flexible securities.

Type: **Boolean**

Used in components: **UnderlyingInstrument**

### **180.2.5854 UnderlyingFloorPrice**

Used to express the floor price of a capped put.

Type: **Price**

Used in components: **UnderlyingInstrument**

### **180.2.5855 UnderlyingFlowScheduleType**

The industry standard flow schedule by which electricity or natural gas is traded. Schedules exist by regions and on-peak and off-peak status, such as "Western Peak".

Type: **int**

Allowed values in FlowScheduleTypeCodeSet:

Code	Name	Description
0	NERCEasternOffPeak	NERC Eastern Off-Peak
1	NERCWesternOffPeak	NERC Western Off-Peak
2	NERCCalendarAllDaysInMonth	NERC Calendar-All Days in month
3	NERCEasternPeak	NERC Eastern Peak
4	NERCWesternPeak	NERC Western Peak
5	AllTimes	All times
6	OnPeak	On peak
7	OffPeak	Off peak
8	Base	Base
9	Block	Block

Code	Name	Description
99	Other	Other

Used in components: [UnderlyingInstrument](#)

### 180.2.5856 UnderlyingFutureID

In the case of an index underlier specifies the unique identifier for the referenced futures contract.

Type: [String](#)

Used in components: [UnderlyingInstrument](#)

### 180.2.5857 UnderlyingFutureIDSource

Identifies the source of the UnderlyingFutureID(2620).

Type: [String](#)

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam

Code	Name	Description
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **UnderlyingInstrument**

### 180.2.5858 UnderlyingFXRate

Foreign exchange rate used to compute UnderlyingCurrentValue(885) (or market value) from UnderlyingCurrency(318) to Currency(15).

Type: **float**

Used in components: **UnderlyingInstrument**

**180.2.5859 UnderlyingFXRateCalc**

Specifies whether the UnderlyingFxRate(1045) should be multiplied or divided.

Type: **char**

Allowed values in UnderlyingFXRateCalcCodeSet:

Code	Name	Description
D	Divide	Divide
M	Multiply	Multiply

Used in components: **UnderlyingInstrument**

**180.2.5860 UnderlyingID**

Unique identifier for the underlying instrument within the context of a message.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5861 UnderlyingIndexAnnexDate**

The date of a credit default swap index series annex.

Type: **LocalMktDate**

Used in components: **UnderlyingInstrument**

**180.2.5862 UnderlyingIndexAnnexSource**

The source of a credit default swap index series annex.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5863 UnderlyingIndexAnnexVersion**

The version identifier of a credit default swap index annex.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.5864 UnderlyingIndexCurvePeriod**

Curve time multiplier for the underlying index.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.5865 UnderlyingIndexCurveUnit**

Curve time unit associated with the underlying index.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in components: **UnderlyingInstrument**

**180.2.5866 UnderlyingIndexSeries**

The series identifier of a credit default swap index.

Type: **int**

Used in components: **UnderlyingInstrument**



**180.2.5867 UnderlyingInstrRegistry**

Underlying security's InstrRegistry.

See InstrRegistry (543) field for description

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5868 UnderlyingInstrument**

The UnderlyingInstrument component block, like the Instrument component block, contains all the fields commonly used to describe a security or instrument. In the case of the UnderlyingInstrument component block it describes an instrument which underlies the primary instrument. Refer to the Instrument component block comments as this component block mirrors Instrument, except for the noted fields.

Name	Mult.	Type	Description
<b>UnderlyingSymbol</b>	[0..1]	String	Common, "human understood" representation of the security. SecurityID value can be specified if no symbol exists (e.g. non-exchange traded Collective Investment Vehicles). Use "[N/A]" for products which do not have a symbol. Required if the UnderlyingInstrument component is marked as required where the component is used.
<b>UnderlyingSymbolSfx</b>	[0..1]	CodeSet	
<b>UnderlyingSecurityID</b>	[0..1]	String	
<b>UnderlyingSecurityIDSource</b>	[0..1]	CodeSet	
<b>UndSecAltIDGrp</b>	[0..*]	Group	
<b>UnderlyingID</b>	[0..1]	String	Used for unique identification of the underlying instance that can subsequently be used to serve as input value for fields such as UnderlyingRefID(2841), for example, whenever a simple underlying reference is allowed or needed.
<b>UnderlyingProduct</b>	[0..1]	CodeSet	
<b>UnderlyingSecurityXML</b>	[0..1]	Component	Embedded XML document describing the underlying instrument.
<b>UnderlyingCFICode</b>	[0..1]	String	
<b>UnderlyingUPICode</b>	[0..1]	String	
<b>UnderlyingSecurityType</b>	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingSecuritySubType	[0..1]	String	
UnderlyingMaturityMonthYear	[0..1]	MonthYear	
UnderlyingMaturityDate	[0..1]	LocalMktDate	
UnderlyingMaturityTime	[0..1]	TZTimeOnly	
UnderlyingMaturityFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingMaturityFrequencyPeriod(2985) is specified.
UnderlyingMaturityFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingMaturityFrequencyUnit(2984) is specified and the value is not EOM (End of Month) or F (Flexible).
UnderlyingContractPriceRefMonth	[0..1]	MonthYear	
UnderlyingCouponPaymentDate	[0..1]	LocalMktDate	
UnderlyingRestructuringType	[0..1]	CodeSet	
UnderlyingSeniority	[0..1]	CodeSet	
UnderlyingNotional	[0..1]	Amt	
UnderlyingNotionalCurrency	[0..1]	Currency	
UnderlyingNotionalCurrencyCodeSource	[0..1]	CodeSet	
UnderlyingNotionalDetermination-Method	[0..1]	String	
UnderlyingNotionalAdjustments	[0..1]	CodeSet	
UnderlyingNotionalXIDRef	[0..1]	XIDREF	
UnderlyingNotionalPercentageOutstanding	[0..1]	Percentage	
UnderlyingOriginalNotionalPercentageOutstanding	[0..1]	Percentage	
UnderlyingAttachmentPoint	[0..1]	Percentage	
UnderlyingDetachmentPoint	[0..1]	Percentage	
UnderlyingIssueDate	[0..1]	LocalMktDate	
UnderlyingRepoCollateralSecurityType	[0..1]	String	
UnderlyingRepurchaseTerm	[0..1]	int	
UnderlyingRepurchaseRate	[0..1]	Percentage	
UnderlyingFactor	[0..1]	float	
UnderlyingCreditRating	[0..1]	String	
UnderlyingInstrRegistry	[0..1]	String	

Name	Mult.	Type	Description
UnderlyingCountryOfIssue	[0..1]	Country	
UnderlyingStateOrProvinceOfIssue	[0..1]	String	
UnderlyingLocaleOfIssue	[0..1]	String	
UnderlyingRedemptionDate	[0..1]	LocalMktDate	
UnderlyingStrikePrice	[0..1]	Price	
UnderlyingStrikeCurrency	[0..1]	Currency	
UnderlyingStrikeCurrencyCodeSource	[0..1]	CodeSet	
UnderlyingOptAttribute	[0..1]	char	
UnderlyingContractMultiplier	[0..1]	float	
UnderlyingContractMultiplierUnit	[0..1]	CodeSet	
UnderlyingTradingUnitPeriodMultiplier	[0..1]	int	
UnderlyingFlowScheduleType	[0..1]	CodeSet	
UnderlyingUnitOfMeasure	[0..1]	CodeSet	
UnderlyingUnitOfMeasureQty	[0..1]	Qty	
UnderlyingUnitOfMeasureCurrency	[0..1]	Currency	
UnderlyingUnitOfMeasureCurrencyCodeSource	[0..1]	CodeSet	
UnderlyingPriceUnitOfMeasure	[0..1]	CodeSet	
UnderlyingPriceUnitOfMeasureQty	[0..1]	Qty	
UnderlyingPriceUnitOfMeasureCurrency	[0..1]	Currency	
UnderlyingPriceUnitOfMeasureCurrencyCodeSource	[0..1]	CodeSet	
UnderlyingTimeUnit	[0..1]	CodeSet	Used to indicate a time unit for the contract (e.g., days, weeks, months, etc.)
UnderlyingExerciseStyle	[0..1]	CodeSet	
UnderlyingPriceQuoteCurrency	[0..1]	Currency	
UnderlyingPriceQuoteCurrencyCodeSource	[0..1]	CodeSet	
UnderlyingCouponRate	[0..1]	Percentage	
UnderlyingSecurityExchange	[0..1]	Exchange	
UnderlyingIssuer	[0..1]	String	
EncodedUnderlyingIssuerLen	[0..1]	Length	Must be set if UnderlyingEncodedIssuer(363) field is specified and must immediately precede it.

Name	Mult.	Type	Description
EncodedUnderlyingIssuer	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingIssuer(363) field in the encoded format specified via the MessageEncoding(347) field.
UnderlyingFinancialInstrumentShort-Name	[0..1]	String	
UnderlyingFinancialInstrumentFull-Name	[0..1]	String	
EncodedUnderlyingFinancialInstrumentFullNameLen	[0..1]	Length	Must be set if EncodedUnderlyingFinancialInstrumentFullName(2722) field is specified and must immediately precede it.
EncodedUnderlyingFinancialInstrumentFullName	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingFinancialInstrumentFullName(2720) field in the encoded format specified via the MessageEncoding(347) field.
UnderlyingIndexCurveUnit	[0..1]	CodeSet	Requires UnderlyingSecurityID(305) to identify the index. Requires UnderlyingIndexCurvePeriod(2724).
UnderlyingIndexCurvePeriod	[0..1]	int	Requires UnderlyingSecurityID(305) to identify the index. Requires UnderlyingIndexCurveUnit(2723).
UnderlyingSecurityDesc	[0..1]	String	
EncodedUnderlyingSecurityDescLen	[0..1]	Length	Must be set if UnderlyingEncodedSecurityDesc(307) field is specified and must immediately precede it.
EncodedUnderlyingSecurityDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingSecurityDesc(307) field in the encoded format specified via the MessageEncoding(347) field.
UnderlyingCPPProgram	[0..1]	CodeSet	
UnderlyingCPRegType	[0..1]	String	
UnderlyingAllocationPercent	[0..1]	Percentage	Specific to the < UnderlyingInstrument > Percent of the Strike Price that this underlying represents. Necessary for derivatives that deliver into more than one underlying instrument.
UnderlyingCurrency	[0..1]	Currency	Specific to the <UnderlyingInstrument> (not in <Instrument>)
UnderlyingCurrencyCodeSource	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingQty	[0..1]	Qty	Specific to the <UnderlyingInstrument> (not in <Instrument>). Unit amount of the underlying security (par, shares, currency, etc.)
UnderlyingSettlementType	[0..1]	CodeSet	Specific to the < UnderlyingInstrument > Indicates order settlement period for the underlying deliverable component.
UnderlyingCashAmount	[0..1]	Amt	Specific to the < UnderlyingInstrument > Cash amount associated with the underlying component. Necessary for derivatives that deliver into more than one underlying instrument and one of the underlying's is a fixed cash value.
UnderlyingCashType	[0..1]	CodeSet	Specific to the < UnderlyingInstrument > Used for derivatives that deliver into cash underlying. Indicates that the cash is either fixed or difference value (difference between strike and current underlying price)
UnderlyingPx	[0..1]	Price	Specific to the <UnderlyingInstrument> (not in <Instrument>). In a financing deal clean price (percent-of-par or per unit) of the underlying security or basket.
UnderlyingDirtyPrice	[0..1]	Price	Specific to the <UnderlyingInstrument> (not in <Instrument>). In a financing deal price (percent-of-par or per unit) of the underlying security or basket. "Dirty" means it includes accrued interest
UnderlyingEndPrice	[0..1]	Price	Specific to the <UnderlyingInstrument> (not in <Instrument>). In a financing deal price (percent-of-par or per unit) of the underlying security or basket at the end of the agreement.
UnderlyingStartValue	[0..1]	Amt	Specific to the <UnderlyingInstrument> (not in <Instrument>). Currency value attributed to this collateral at the start of the agreement
UnderlyingCurrentValue	[0..1]	Amt	Specific to the <UnderlyingInstrument> (not in <Instrument>). Currency value currently attributed to this collateral
UnderlyingEndValue	[0..1]	Amt	Specific to the <UnderlyingInstrument> (not in <Instrument>). Currency value attributed to this collateral at the end of the agreement
UnderlyingAccruedInterestAmt	[0..1]	Amt	
UnderlyingNumDaysInterest	[0..1]	int	

Name	Mult.	Type	Description
UnderlyingStipulations	[0..*]	Group	Specific to the <UnderlyingInstrument> (not in <Instrument>). Insert here the contents of the <UnderlyingStipulations> Component Block
UnderlyingAdjustedQuantity	[0..1]	Qty	Specific to the <UnderlyingInstrument> (not in <Instrument>). For listed derivatives margin management, this is the number of shares adjusted for upcoming corporate action. Used only for securities which are optionable and are between ex-date and settlement date (4 days).
UnderlyingFXRate	[0..1]	float	Specific to the <UnderlyingInstrument> (not in <Instrument>). Foreign exchange rate used to compute UnderlyingCurrentValue (885) (or market value) from UnderlyingCurrency (318) to Currency (15).
UnderlyingFXRateCalc	[0..1]	CodeSet	Specific to the <UnderlyingInstrument> (not in <Instrument>). Specified whether UnderlyingFxRate (1045) should be multiplied or divided to derive UnderlyingCurrentValue (885).
UnderlyingCapValue	[0..1]	Amt	
UnderlyingInstrumentParties	[0..*]	Group	
UnderlyingSettlMethod	[0..1]	CodeSet	
UnderlyingPutOrCall	[0..1]	CodeSet	Used to express option right
UnderlyingInTheMoneyCondition	[0..1]	CodeSet	Used to express in-the-moneyness behavior in general terms for the option without the use of UnderlyingStrikePrice(316) and UnderlyingPutOrCall(315).
UnderlyingContraryInstructionEligibilityIndicator	[0..1]	Boolean	
UnderlyingConstituentWeight	[0..1]	float	
UnderlyingCouponType	[0..1]	CodeSet	
UnderlyingTotalIssuedAmount	[0..1]	Amt	
UnderlyingCouponFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingCouponFrequencyUnit(1992) is specified.
UnderlyingCouponFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingCouponFrequencyPeriod(1991) is specified.
UnderlyingCouponDayCount	[0..1]	CodeSet	
UnderlyingCouponOtherDayCount	[0..1]	String	

Name	Mult.	Type	Description
UnderlyingObligationID	[0..1]	String	
UnderlyingObligationIDSource	[0..1]	CodeSet	Conditionally required when UnderlyingObligationID(1994) is specified.
UnderlyingEquityID	[0..1]	String	
UnderlyingEquityIDSource	[0..1]	CodeSet	Conditionally required when UnderlyingEquityID(1996) is specified.
UnderlyingFutureID	[0..1]	String	
UnderlyingFutureIDSource	[0..1]	CodeSet	Required if UnderlyingFutureID(2620) is specified.
UnderlyingEvtGrp	[0..*]	Group	
UnderlyingLienSeniority	[0..1]	CodeSet	
UnderlyingLoanFacility	[0..1]	CodeSet	
UnderlyingReferenceEntityType	[0..1]	CodeSet	
UnderlyingIndexSeries	[0..1]	int	
UnderlyingIndexAnnexVersion	[0..1]	int	
UnderlyingIndexAnnexDate	[0..1]	LocalMktDate	
UnderlyingIndexAnnexSource	[0..1]	String	
UnderlyingSettlRateIndex	[0..1]	String	
UnderlyingSettlRateIndexLocation	[0..1]	String	
UnderlyingOptionExpirationDesc	[0..1]	String	
EncodedUnderlyingOptionExpirationDescLen	[0..1]	Length	Must be set if EncodedUnderlyingOptionExpirationDesc(2288) field is specified and must immediately precede it.
EncodedUnderlyingOptionExpirationDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingOptionExpirationDesc(2286) field in the encoded format specified via the MessageEncoding(347) field.
UnderlyingProductComplex	[0..1]	String	
UnderlyingSecurityGroup	[0..1]	String	
UnderlyingSettleOnOpenFlag	[0..1]	String	
UnderlyingAssignmentMethod	[0..1]	CodeSet	
UnderlyingSecurityStatus	[0..1]	CodeSet	
UnderlyingObligationType	[0..1]	CodeSet	
UnderlyingAssetGroup	[0..1]	CodeSet	
UnderlyingAssetClass	[0..1]	CodeSet	Required if UnderlyingAssetSubClass(2014) is specified.

Name	Mult.	Type	Description
UnderlyingAssetSubClass	[0..1]	CodeSet	Required if UnderlyingAssetType(2015) is specified.
UnderlyingAssetType	[0..1]	String	Required if UnderlyingAssetSubType(2744) is specified.
UnderlyingAssetSubType	[0..1]	String	
UnderlyingSecondaryAssetGrp	[0..*]	Group	
UnderlyingAssetAttributeGrp	[0..*]	Group	
UnderlyingSwapClass	[0..1]	CodeSet	
UnderlyingSwapSubClass	[0..1]	CodeSet	
UnderlyingNthToDefault	[0..1]	int	Conditionally required when UnderlyingMthToDefault(2018) is specified.
UnderlyingMthToDefault	[0..1]	int	
UnderlyingSettledEntityMatrixSource	[0..1]	String	
UnderlyingSettledEntityMatrixPublicationDate	[0..1]	LocalMktDate	
UnderlyingStrikeMultiplier	[0..1]	float	
UnderlyingStrikeValue	[0..1]	float	
UnderlyingStrikeUnitOfMeasure	[0..1]	CodeSet	
UnderlyingStrikeIndexCurvePoint	[0..1]	String	
UnderlyingStrikeIndex	[0..1]	String	
UnderlyingStrikeIndexQuote	[0..1]	CodeSet	
UnderlyingStrikeIndexSpread	[0..1]	PriceOffset	
UnderlyingStrikePriceDetermination-Method	[0..1]	CodeSet	
UnderlyingStrikePriceBoundaryMethod	[0..1]	CodeSet	When specified, UnderlyingPutOrCall(315), UnderlyingStrikePrice(316), and UnderlyingStrikePriceBoundaryPrecision(2025) must also be specified.
UnderlyingStrikePriceBoundaryPrecision	[0..1]	Percentage	
UnderlyingMinPriceIncrement	[0..1]	float	
UnderlyingMinPriceIncrementAmount	[0..1]	Amt	
UnderlyingOptPayoutType	[0..1]	CodeSet	
UnderlyingOptPayoutAmount	[0..1]	Amt	Conditionally required if UnderlyingOptPayoutType(2028) = 3 (Binary).
UnderlyingReturnTrigger	[0..1]	CodeSet	
UnderlyingPriceQuoteMethod	[0..1]	CodeSet	



Name	Mult.	Type	Description
UnderlyingValuationMethod	[0..1]	CodeSet	
UnderlyingValuationSource	[0..1]	String	
UnderlyingValuationReferenceModel	[0..1]	String	
UnderlyingListMethod	[0..1]	CodeSet	
UnderlyingCapPrice	[0..1]	Price	
UnderlyingFloorPrice	[0..1]	Price	
UnderlyingFlexibleIndicator	[0..1]	Boolean	
UnderlyingFlexProductEligibilityIndicator	[0..1]	Boolean	
UnderlyingPositionLimit	[0..1]	int	
UnderlyingNTPositionLimit	[0..1]	int	
UnderlyingPool	[0..1]	String	
UnderlyingContractSettlMonth	[0..1]	MonthYear	
UnderlyingDatedDate	[0..1]	LocalMktDate	
UnderlyingInterestAccrualDate	[0..1]	LocalMktDate	
UnderlyingShortSaleRestriction	[0..1]	CodeSet	
UnderlyingRefTickTableID	[0..1]	int	
UnderlyingProtectionTermXIDRef	[0..1]	XIDREF	
UnderlyingSettlTermXIDRef	[0..1]	XIDREF	
UnderlyingComplexEvents	[0..*]	Group	
UnderlyingStrategyType	[0..1]	CodeSet	
UnderlyingCommonPricingIndicator	[0..1]	Boolean	
UnderlyingSettlDisruptionProvision	[0..1]	CodeSet	
UnderlyingDeliveryRouteOrCharter	[0..1]	String	
UnderlyingInstrumentRoundingDirection	[0..1]	CodeSet	
UnderlyingInstrumentRoundingPrecision	[0..1]	int	
UnderlyingDateAdjustment	[0..1]	Component	
UnderlyingPricingDateTime	[0..1]	Component	
UnderlyingMarketDisruption	[0..1]	Component	
UnderlyingOptionExercise	[0..1]	Component	
UnderlyingStreamGrp	[0..*]	Group	
UnderlyingProvisionGrp	[0..*]	Group	
UnderlyingAdditionalTermGrp	[0..*]	Group	

Name	Mult.	Type	Description
UnderlyingProtectionTermGrp	[0..*]	Group	
UnderlyingCashSettlTermGrp	[0..*]	Group	
UnderlyingPhysicalSettlTermGrp	[0..*]	Group	
UnderlyingRateSpreadSchedule	[0..1]	Component	
UnderlyingDividendPayout	[0..1]	Component	
UnderlyingExtraordinaryEventGrp	[0..*]	Group	
UnderlyingExtraordinaryEventAdjustmentMethod	[0..1]	CodeSet	
UnderlyingExchangeLookAlike	[0..1]	Boolean	
UnderlyingAverageVolumeLimitation-Percentage	[0..1]	Amt	
UnderlyingAverageVolumeLimitation-PeriodDays	[0..1]	int	
UnderlyingDepositoryReceiptIndicator	[0..1]	Boolean	
UnderlyingOpenUnits	[0..1]	Qty	
UnderlyingBasketDivisor	[0..1]	float	
UnderlyingInstrumentXID	[0..1]	XID	

Used in groups: PosUndInstrmtGrp, QuotSetAckGrp, QuotSetGrp, UndInstrmtCollGrp, UndInstrmtGrp

Used in messages: DerivativeSecurityList, DerivativeSecurityListRequest, DerivativeSecurityListUpdateReport, OrderMassActionReport, OrderMassActionRequest, OrderMassCancelReport, OrderMassCancelRequest, OrderMassStatusRequest, SecurityRiskMetricsReport

#### 180.2.5869 UnderlyingInstrumentPartyID

PartyID value within an underlying instrument party repeating group.

Same values as PartyID (448)

Type: String

Used in groups: UndlyInstrumentParties

#### 180.2.5870 UnderlyingInstrumentPartyIDSource

PartyIDSource value within an underlying instrument partyrepeating group.

Same values as PartyIDSource (447)

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier

Code	Name	Description
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **UndlyInstrumentParties**

### 180.2.5871 UnderlyingInstrumentPartyRole

PartyRole value within an underlying instrument party repeating group.

Same values as PartyRole (452)

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party

Code	Name	Description
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)

Code	Name	Description
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionV- enue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm

Code	Name	Description
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor



Code	Name	Description
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **UndlyInstrumentParties**

**180.2.5872 UnderlyingInstrumentPartyRoleQualifier**

Used to further qualify the value of UnderlyingInstrumentPartyRole(1061).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange

Code	Name	Description
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **UndlyInstrumentParties**

### 180.2.5873 UnderlyingInstrumentPartySubID

PartySubID value within an underlying instrument party repeating group.

Same values as PartySubID (523)

Type: **String**

Used in groups: **UndlyInstrumentPtysSubGrp**

**180.2.5874 UnderlyingInstrumentPartySubIDType**

Type of underlying InstrumentPartySubID (1053) value.

Same values as PartySubIDType (803)

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type

Code	Name	Description
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.

Code	Name	Description
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.



Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: **UndlyInstrumentPtysSubGrp**

**180.2.5875 UnderlyingInstrumentRoundingDirection**

Specifies the rounding direction if not overridden elsewhere.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **UnderlyingInstrument**

**180.2.5876 UnderlyingInstrumentRoundingPrecision**

Specifies the rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.5877 UnderlyingInstrumentXID**

Identifier for referencing this UnderlyingInstrument from a parent instrument or a convertible instrument.

Type: **XID**

Used in components: **UnderlyingInstrument**

**180.2.5878 UnderlyingInterestAccrualDate**

If different from IssueDate and DatedDate

Type: **LocalMktDate**

Used in components: **UnderlyingInstrument**

**180.2.5879 UnderlyingInTheMoneyCondition**

Specifies an option instrument's "in the money" condition in general terms.

Type: **int**

Allowed values in InTheMoneyConditionCodeSet:

Code	Name	Description
0	StandardITM	Standard in-the-money. The option's strike price is less than the underlying settlement price for a call or greater than the underlying settlement price for a put.
1	ATMITM	At-the-money is in-the-money. The option's strike price of either the put or call is equal to the underlying settlement price in addition to standard in-the-money behavior.
2	ATMCallITM	At-the-money call is in-the-money. The call option's strike price is equal to the underlying settlement price in addition to standard in-the-money behavior.
3	ATMPutITM	At-the-money put is in-the-money. The put option's strike price is equal to the underlying settlement price in addition to standard in-the-money behavior.

Used in components: **UnderlyingInstrument**

**180.2.5880 UnderlyingIssueDate**

Underlying security's IssueDate.

See IssueDate (225) field for description

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

(prior to FIX 4.4 field was of type UTCTDate)

Type: **LocalMktDate**

Used in components: **UnderlyingInstrument**

**180.2.5881 UnderlyingIssuer**

Underlying security's Issuer.

See Issuer(106) field for description.

Type: **String**

Used in components: **UnderlyingInstrument**

### **180.2.5882 UnderlyingLastPx**

The calculated or traded price for the underlying instrument that corresponds to a derivative. Used for transactions that include the cash instrument and the derivative.

Type: **Price**

Used in messages: **ExecutionReport**

### **180.2.5883 UnderlyingLastQty**

The calculated or traded quantity for the underlying instrument that corresponds to a derivative. Used for transactions that include the cash instrument and the derivative.

Type: **Qty**

Used in messages: **ExecutionReport**

### **180.2.5884 UnderlyingLegCFIcode**

Refer to definition for CFIcode(461)

Type: **String**

Used in components: **UnderlyingLegInstrument**

### **180.2.5885 UnderlyingLegInstrument**

---

<b>Name</b>	<b>Mult.</b>	<b>Type</b>	<b>Description</b>
<b>UnderlyingLegSymbol</b>	[0..1]	String	
<b>UnderlyingLegSymbolSfx</b>	[0..1]	String	
<b>UnderlyingLegSecurityID</b>	[0..1]	String	
<b>UnderlyingLegSecurityIDSource</b>	[0..1]	String	
<b>UnderlyingLegSecurityAltIDGrp</b>	[0..*]	Group	
<b>UnderlyingLegCFIcode</b>	[0..1]	String	
<b>UnderlyingLegSecurityType</b>	[0..1]	String	

---

Name	Mult.	Type	Description
UnderlyingLegSecuritySubType	[0..1]	String	
UnderlyingLegMaturityMonthYear	[0..1]	MonthYear	
UnderlyingLegMaturityDate	[0..1]	LocalMktDate	
UnderlyingLegMaturityTime	[0..1]	TZTimeOnly	
UnderlyingLegStrikePrice	[0..1]	Price	
UnderlyingLegOptAttribute	[0..1]	char	
UnderlyingLegPutOrCall	[0..1]	int	
UnderlyingLegSecurityExchange	[0..1]	String	
UnderlyingLegSecurityDesc	[0..1]	String	

Used in groups: [TradeCapLegUnderlyingsGrp](#)

#### **180.2.5886 UnderlyingLegMaturityDate**

Date of maturity.

Type: [LocalMktDate](#)

Used in components: [UnderlyingLegInstrument](#)

#### **180.2.5887 UnderlyingLegMaturityMonthYear**

Refer to definition for MaturityMonthYear(200)

Type: [MonthYear](#)

Used in components: [UnderlyingLegInstrument](#)

#### **180.2.5888 UnderlyingLegMaturityTime**

Time of security's maturity expressed in local time with offset to UTC specified

Type: [TZTimeOnly](#)

Used in components: [UnderlyingLegInstrument](#)

**180.2.5889 UnderlyingLegOptAttribute**

Refer to definition of OptAttribute(206)

Type: **char**

Used in components: **UnderlyingLegInstrument**

**180.2.5890 UnderlyingLegPutOrCall**

Refer to definition for PutOrCall(201)

Type: **int**

Used in components: **UnderlyingLegInstrument**

**180.2.5891 UnderlyingLegSecurityAltID**

Refer to definition for SecurityAltID(455)

Type: **String**

Used in groups: **UnderlyingLegSecurityAltIDGrp**

**180.2.5892 UnderlyingLegSecurityAltIDGrp**

---

Name	Mult.	Type	Description
NoUnderlyingLegSecurityAltID	[1..1]	NumInGroup	
UnderlyingLegSecurityAltID	[0..1]	String	
UnderlyingLegSecurityAltIDSource	[0..1]	String	

---

Used in components: **UnderlyingLegInstrument**

**180.2.5893 UnderlyingLegSecurityAltIDSource**

Refer to definition for SecurityAltIDSource(456)

Type: **String**

Used in groups: **UnderlyingLegSecurityAltIDGrp**

#### **180.2.5894 UnderlyingLegSecurityDesc**

Refer to definition of SecurityDesc(107)

Type: **String**

Used in components: **UnderlyingLegInstrument**

#### **180.2.5895 UnderlyingLegSecurityExchange**

Refer to definition for SecurityExchange(207)

Type: **String**

Used in components: **UnderlyingLegInstrument**

#### **180.2.5896 UnderlyingLegSecurityID**

Refer to definition for SecurityID(48)

Type: **String**

Used in components: **UnderlyingLegInstrument**

#### **180.2.5897 UnderlyingLegSecurityIDSource**

Refer to definition for SecurityIDSource(22)

Type: **String**

Used in components: **UnderlyingLegInstrument**

#### **180.2.5898 UnderlyingLegSecuritySubType**

Refer to definition for SecuritySubType(762)

Type: **String**

Used in components: **UnderlyingLegInstrument**

**180.2.5899 UnderlyingLegSecurityType**

Refer to definition for SecurityType(167)

Type: **String**

Used in components: **UnderlyingLegInstrument**

**180.2.5900 UnderlyingLegStrikePrice**

Refer to definition for StrikePrice(202)

Type: **Price**

Used in components: **UnderlyingLegInstrument**

**180.2.5901 UnderlyingLegSymbol**

Refer to definition for Symbol(55)

Type: **String**

Used in components: **UnderlyingLegInstrument**

**180.2.5902 UnderlyingLegSymbolSfx**

Refer to definition for SymbolSfx(65)

Type: **String**

Used in components: **UnderlyingLegInstrument**

**180.2.5903 UnderlyingLienSeniority**

Indicates the seniority level of the lien in a loan.

Type: **int**

Allowed values in LienSeniorityCodeSet:

---

Code	Name	Description
0	Unknown	Unknown
1	FirstLien	First lien

---



Code	Name	Description
2	SecondLien	Second lien
3	ThirdLien	Third lien

Used in components: [UnderlyingInstrument](#)

#### **180.2.5904 UnderlyingLimitedRightToConfirmIndicator**

Indicates whether the Seller may request the Buyer to confirm its intent to exercise if not done on or before the expiration time on the Expiration date. If true ("Y") specific rules will apply in relation to the settlement mode.

Type: [Boolean](#)

Used in components: [UnderlyingOptionExercise](#)

#### **180.2.5905 UnderlyingListMethod**

Indicates whether the instruments are pre-listed only or can also be defined via user request.

Type: [int](#)

Allowed values in ListMethodCodeSet:

Code	Name	Description
0	PreListedOnly	pre-listed only
1	UserRequested	user requested

Used in components: [UnderlyingInstrument](#)

#### **180.2.5906 UnderlyingLoanFacility**

Specifies the type of loan when the credit default swap's reference obligation is a loan.

Type: [int](#)

Allowed values in LoanFacilityCodeSet:

Code	Name	Description
0	BridgeLoan	Bridge loan
1	LetterOfCredit	Letter of credit
2	RevolvingLoan	Revolving loan
3	SwinglineFunding	Swingline funding
4	TermLoan	Term loan
5	TradeClaim	Trade claim

Used in components: [UnderlyingInstrument](#)

#### **180.2.5907 UnderlyingLocaleOfIssue**

Underlying security's LocaleOfIssue.

See LocaleOfIssue (472) field for description

Type: [String](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5908 UnderlyingMakeWholeAmount**

Amount to be paid by the buyer of the option if the option is exercised prior to the UnderlyingMakeWholeDate(42888).

Type: [Amt](#)

Used in components: [UnderlyingOptionExerciseMakeWholeProvision](#)

#### **180.2.5909 UnderlyingMakeWholeBenchmarkCurveName**

Identifies the benchmark floating rate index.

Type: [String](#)

Used in components: [UnderlyingOptionExerciseMakeWholeProvision](#)

**180.2.5910 UnderlyingMakeWholeBenchmarkCurvePoint**

The point on the floating rate index curve.

Sample values:

M = combination of a number between 1-12 and an "M" for month, e.g. 3M

Y = combination of number between 1-100 and a "Y" for year, e.g. 10Y

10Y-OLD = see above, then add "-OLD" when appropriate

INTERPOLATED = the point is mathematically derived

2/2031 5 3/8 = the point is stated via a combination of maturity month / year and coupon.

Type: **String**

Used in components: **UnderlyingOptionExerciseMakeWholeProvision**

**180.2.5911 UnderlyingMakeWholeBenchmarkQuote**

The quote side of the benchmark to be used for calculating the "make whole" amount.

Type: **int**

Allowed values in StrikeIndexQuoteCodeSet:

Code	Name	Description
0	Bid	Bid.
1	Mid	Mid
2	Offer	Offer

Used in components: **UnderlyingOptionExerciseMakeWholeProvision**

**180.2.5912 UnderlyingMakeWholeDate**

The date through which the option cannot be exercised without penalty.

Type: **LocalMktDate**

Used in components: **UnderlyingOptionExerciseMakeWholeProvision**

**180.2.5913 UnderlyingMakeWholeInterpolationMethod**

The method used when calculating the "make whole" amount. The most common is linear method.

Type: **int**

Allowed values in PaymentStreamInflationInterpolationMethodCodeSet:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: **UnderlyingOptionExerciseMakeWholeProvision**

**180.2.5914 UnderlyingMakeWholeRecallSpread**

Spread over the floating rate index.

Type: **PriceOffset**

Used in components: **UnderlyingOptionExerciseMakeWholeProvision**

**180.2.5915 UnderlyingManualNoticeBusinessCenter**

Identifies the business center used for adjusting the time for manual exercise notice.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **UnderlyingOptionExercise**

**180.2.5916 UnderlyingMarketDisruption**

The UnderlyingMarketDisruption component is a subcomponent of the UnderlyingInstrument used to specify the market disruption provisions of the swap.

Name	Mult.	Type	Description
<b>UnderlyingMarketDisruptionProvision</b>	[0..1]	CodeSet	
<b>UnderlyingMarketDisruptionEventGrp</b>	[0..*]	Group	

Name	Mult.	Type	Description
UnderlyingMarketDisruptionFallback-Provision	[0..1]	CodeSet	
UnderlyingMarketDisruptionFallback-Grp	[0..*]	Group	
UnderlyingMarketDisruptionFallback-ReferencePriceGrp	[0..*]	Group	
UnderlyingMarketDisruptionMaximumDays	[0..1]	int	
UnderlyingMarketDisruptionMaterialityPercentage	[0..1]	Percentage	If specified, the disruption event should be specified in UnderlyingMarketDisruptionEventGrp.
UnderlyingMarketDisruptionMinimum-FuturesContracts	[0..1]	int	Applicable only when UnderlyingMarketDisruptionEvent(41865)='DeMinimisTrading'.

Used in components: **UnderlyingInstrument**

### 180.2.5917 UnderlyingMarketDisruptionEvent

Specifies the market disruption event.

For commodities see <http://www.fpml.org/coding-scheme/commodity-market-disruption> for values.

For foreign exchange, see [http://www.fixtradingcommunity.org/codelists#Market\\_Disruption\\_Event](http://www.fixtradingcommunity.org/codelists#Market_Disruption_Event) for code list of applicable event types.

Type: **String**

Used in groups: **UnderlyingMarketDisruptionEventGrp**

### 180.2.5918 UnderlyingMarketDisruptionEventGrp

The UnderlyingMarketDisruptionEventGrp is a repeating subcomponent of the UnderlyingMarketDisruption component used to specify the market disruption events.

Name	Mult.	Type	Description
NoUnderlyingMarketDisruptionEvents	[1..1]	NumInGroup	
UnderlyingMarketDisruptionEvent	[0..1]	String	Required if NoUnderlyingMarketDisruptionEvents(41864) > 0.

Name	Mult.	Type	Description
<a href="#">UnderlyingMarketDisruptionValue</a>	[0..1]	String	

Used in components: [UnderlyingMarketDisruption](#)

#### **180.2.5919 UnderlyingMarketDisruptionFallbackBasketCurrency**

Specifies the currency if the underlier is a basket. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingMarketDisruptionFallbackReferencePriceGrp](#)

#### **180.2.5920 UnderlyingMarketDisruptionFallbackBasketDivisor**

Specifies the basket divisor amount. This value is normally used to adjust the constituent weight for pricing or to adjust for dividends, or other corporate actions.

Type: [float](#)

Used in groups: [UnderlyingMarketDisruptionFallbackReferencePriceGrp](#)

#### **180.2.5921 UnderlyingMarketDisruptionFallbackGrp**

The UnderlyingMarketDisruptionFallbackGrp is a repeating subcomponent of the UnderlyingMarketDisruption component used to specify the market disruption fallback provisions.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingMarketDisruptionFallbacks</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingMarketDisruptionFallbackType</a>	[0..1]	String	Required if <a href="#">NoUnderlyingMarketDisruptionFallbacks</a> (41866) > 0. The sequence of entries specifies the order in which the fallback provisions should be applied.
<a href="#">UnderlyingMarketDisruptionFallbackValue</a>	[0..1]	String	

Used in components: [UnderlyingMarketDisruption](#)

**180.2.5922 UnderlyingMarketDisruptionFallbackOpenUnits**

If there are multiple underlying assets, this specifies the number of units (index or securities) that constitute the underlier of the swap. In the case of a basket swap, this is used to reference both the number of basket units, and the number of each asset components of the basket when these are expressed in absolute terms.

Type: **Qty**

Used in groups: **UnderlyingMarketDisruptionFallbackReferencePriceGrp**

**180.2.5923 UnderlyingMarketDisruptionFallbackProvision**

Specifies the location of the fallback provision documentation.

Type: **int**

Allowed values in MarketDisruptionFallbackProvisionCodeSet:

Code	Name	Description
0	MasterAgreement	As specified in master agreement
1	Confirmation	As specified in confirmation

Used in components: **UnderlyingMarketDisruption**

**180.2.5924 UnderlyingMarketDisruptionFallbackReferencePriceGrp**

The UnderlyingMarketDisruptionFallbackReferencePriceGrp is a repeating subcomponent of the UnderlyingMarketDisruption component used to specify the fallback reference price and underlying security provisions

Name	Mult.	Type	Description
<b>NoUnderlyingMarketDisruptionFallbackReferencePrices</b>	[1..1]	NumInGroup	
<b>UnderlyingMarketDisruptionFallbackUnderlierType</b>	[0..1]	CodeSet	Required if NoUnderlyingMarketDisruptionFallbackReferencePrices (41868) > 0.
<b>UnderlyingMarketDisruptionFallbackUnderlierSecurityID</b>	[0..1]	String	Conditionally required when UnderlyingMarketDisruptionFallbackUnderlierSecurityIDSource(41871) is specified.

Name	Mult.	Type	Description
UnderlyingMarketDisruptionFallback-UnderlierSecurityIDSource	[0..1]	CodeSet	Conditionally required when UnderlyingMarketDisruptionFallbackUnderlierSecurityID(41870) is specified.
UnderlyingMarketDisruptionFallback-UnderlierSecurityDesc	[0..1]	String	
EncodedUnderlyingMarketDisruption-FallbackUnderlierSecDescLen	[0..1]	Length	Must be set if EncodedUnderlyingMarketDisruptionFallbackUnderlierSecurityDesc(41874) field is specified and must immediately precede it.
EncodedUnderlyingMarketDisruption-FallbackUnderlierSecurityDesc	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingMarketDisruptionFallbackUnderlierSecurityDesc(41872) field in the encoded format specified via the MessageEncoding(347) field.
UnderlyingMarketDisruptionFallback-OpenUnits	[0..1]	Qty	
UnderlyingMarketDisruptionFallback-BasketCurrency	[0..1]	Currency	
UnderlyingMarketDisruptionFallback-BasketDivisor	[0..1]	float	

Used in components: **UnderlyingMarketDisruption**

### 180.2.5925 UnderlyingMarketDisruptionFallbackType

Specifies the type of disruption fallback.

See <http://www.fpml.org/coding-scheme/commodity-market-disruption-fallback> for values.

Type: **String**

Used in groups: **UnderlyingMarketDisruptionFallbackGrp**

### 180.2.5926 UnderlyingMarketDisruptionFallbackUnderlierSecurityDesc

Specifies the description of underlying security.

Type: **String**

Used in groups: **UnderlyingMarketDisruptionFallbackReferencePriceGrp**



**180.2.5927 UnderlyingMarketDisruptionFallbackUnderlierSecurityID**

Specifies the identifier value of the security.

Type: **String**

Used in groups: **UnderlyingMarketDisruptionFallbackReferencePriceGrp**

**180.2.5928 UnderlyingMarketDisruptionFallbackUnderlierSecurityIDSource**

Specifies the class or source scheme of the security identifier.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit

Code	Name	Description
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **UnderlyingMarketDisruptionFallbackReferencePriceGrp**

### 180.2.5929 UnderlyingMarketDisruptionFallbackUnderlierType

The type of reference price underlier.

Type: **int**

Allowed values in MarketDisruptionFallbackUnderlierTypeCodeSet:

Code	Name	Description
0	Basket	Basket
1	Bond	Bond
2	Cash	Cash
3	Commodity	Commodity
4	ConvertibleBond	Convertible bond
5	Equity	Equity
6	ExchangeTradedFund	Exchange traded fund

Code	Name	Description
7	Future	Future
8	Index	Index
9	Loan	Loan
10	Mortgage	Mortgage
11	MutualFund	Mutual fund

Used in groups: [UnderlyingMarketDisruptionFallbackReferencePriceGrp](#)

#### **180.2.5930 UnderlyingMarketDisruptionFallbackValue**

Applicable value for UnderlyingMarketDisruptionFallbackType(41867).

Type: [String](#)

Used in groups: [UnderlyingMarketDisruptionFallbackGrp](#)

#### **180.2.5931 UnderlyingMarketDisruptionMaterialityPercentage**

Used when a price materiality percentage applies to the price source disruption event and this event has been specified.

Type: [Percentage](#)

Used in components: [UnderlyingMarketDisruption](#)

#### **180.2.5932 UnderlyingMarketDisruptionMaximumDays**

Specifies the maximum number of market disruption days (commodity or bullion business days) in a contract or confirmation. If none are specified, the maximum number of market disruption days is five (5).

Type: [int](#)

Used in components: [UnderlyingMarketDisruption](#)

#### **180.2.5933 UnderlyingMarketDisruptionMinimumFuturesContracts**

Specifies the minimum futures contracts level that dictates whether or not a 'De Minimis Trading' event has occurred.

Type: **int**

Used in components: **UnderlyingMarketDisruption**

#### **180.2.5934 UnderlyingMarketDisruptionProvision**

The consequences of market disruption events.

Type: **int**

Allowed values in MarketDisruptionProvisionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable
1	Applicable	Applicable
2	AsInMasterAgreement	As specified in master agreement
3	AsInConfirmation	As specified in confirmation

Used in components: **UnderlyingMarketDisruption**

#### **180.2.5935 UnderlyingMarketDisruptionValue**

Applicable value for UnderlyingMarketDisruptionEvent(41865).

Type: **String**

Used in groups: **UnderlyingMarketDisruptionEventGrp**

#### **180.2.5936 UnderlyingMaterialDividendsIndicator**

Indicates whether material non-cash dividends are applicable.

Type: **Boolean**

Used in components: **UnderlyingDividendConditions**

#### **180.2.5937 UnderlyingMaturityDate**

Underlying security's maturity date.

See MaturityDate (541) field for description

Type: **LocalMktDate**

Used in components: **UnderlyingInstrument**

### **180.2.5938 UnderlyingMaturityFrequencyPeriod**

Time unit multiplier for the minimum frequency of the instrument maturity intervals.

Type: **int**

Used in components: **UnderlyingInstrument**

### **180.2.5939 UnderlyingMaturityFrequencyUnit**

Time unit associated with the minimum frequency of the instrument maturity intervals.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in components: **UnderlyingInstrument**

### **180.2.5940 UnderlyingMaturityMonthYear**

Underlying security's MaturityMonthYear. Can be used with standardized derivatives vs. the UnderlyingMaturityDate (542) field.

See MaturityMonthYear (200) field for description

Type: **MonthYear**

Used in components: **UnderlyingInstrument**

#### **180.2.5941 UnderlyingMaturityTime**

Time of security's maturity expressed in local time with offset to UTC specified

Type: **TZTimeOnly**

Used in components: **UnderlyingInstrument**

#### **180.2.5942 UnderlyingMinPriceIncrement**

Minimum price increment for the instrument. Could also be used to represent tick value.

Type: **float**

Used in components: **UnderlyingInstrument**

#### **180.2.5943 UnderlyingMinPriceIncrementAmount**

Minimum price increment amount associated with the UnderlyingMinPriceIncrement(2026). For listed derivatives, the value can be calculated by multiplying UnderlyingMinPriceIncrement(2026) by UnderlyingContractMultiplier(436).

Type: **Amt**

Used in components: **UnderlyingInstrument**

#### **180.2.5944 UnderlyingMthToDefault**

The Mth reference obligation to default in a CDS reference basket. When UnderlyingNthToDefault(2017) and UnderlyingMthToDefault(2018) are represented then the CDS payout occurs between the Nth and Mth obligations to default.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.5945 UnderlyingNonCashDividendTreatment**

Defines the treatment of non-cash dividends.

Type: **int**

Allowed values in NonCashDividendTreatmentCodeSet:

Code	Name	Description
0	PotentialAdjustment	Potential adjustment event. The treatment of any non-cash dividend shall be determined in accordance with the potential adjustment event provisions.
1	CashEquivalent	Cash equivalent. Any non-cash dividend shall be treated as a declared cash equivalent dividend.

Used in components: **UnderlyingDividendConditions**

**180.2.5946 UnderlyingNonDeliverableFixingDate**

The non-deliverable fixing date unadjusted or adjusted depending on UnderlyingNonDeliverableFixingDateType(40658).

Type: **LocalMktDate**

Used in groups: **UnderlyingPaymentStreamNonDeliverableFixingDateGrp**

**180.2.5947 UnderlyingNonDeliverableFixingDateType**

Specifies the type of date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **UnderlyingPaymentStreamNonDeliverableFixingDateGrp**

**180.2.5948 UnderlyingNotional**

Notional value for the equity or bond underlier.

Type: **Amt**

Used in components: **UnderlyingInstrument**

**180.2.5949 UnderlyingNotionalAdjustments**

Specifies the conditions that govern the adjustment to the number of units of the return swap.

Type: **int**

Allowed values in UnderlyingNotionalAdjustmentsCodeSet:

Code	Name	Description
0	Execution	Execution. The adjustments to the number of units are governed by an execution clause.
1	PortfolioRebalancing	Portfolio rebalancing. The adjustments to the number of units are governed by a portfolio rebalancing clause.
2	Standard	Standrd. The adjustments to the number of units are not governed by any specific clause.

Used in components: **UnderlyingInstrument**

**180.2.5950 UnderlyingNotionalCurrency**

Specifies the currency denomination of the notional value.

UnderlyingNotionalCurrencyCodeSource(2921) may be used to disambiguate the code source scheme used, and ISO 4217 is the default scheme if absent.

Type: **Currency**

Used in components: **UnderlyingInstrument**

**180.2.5951 UnderlyingNotionalCurrencyCodeSource**

Identifies class or source of the UnderlyingNotionalCurrency(2615) value.

Type: **String**



Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5952 UnderlyingNotionalDeterminationMethod**

Specifies the method of determining the notional amount.

See: <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: [String](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5953 UnderlyingNotionalPercentageOutstanding**

See NotionalPercentageOutstanding(1451)

Type: [Percentage](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.5954 UnderlyingNotionalXIDRef**

Cross reference to another notional amount for duplicating its properties.

Type: [XIDREF](#)

Used in components: [UnderlyingInstrument](#)

**180.2.5955 UnderlyingNthToDefault**

The Nth reference obligation to default in a CDS reference basket. If specified without UnderlyingMthToDefault(2018) the default will trigger a CDS payout. If UnderlyingMthToDefault(2018) is also present then payout occurs between the Nth and Mth obligations to default.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.5956 UnderlyingNTPositionLimit**

Position Limit in the near-term contract for a given exchange-traded product.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.5957 UnderlyingNumDaysInterest**

Number of days of interest for underlying security.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.5958 UnderlyingObligationID**

For a CDS basket or pool identifies the reference obligation.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.5959 UnderlyingObligationIDSource**

Identifies the source scheme of the UnderlyingObligationID(1994).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)

Code	Name	Description
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingInstrument](#)

### 180.2.5960 UnderlyingObligationType

Type of reference obligation for credit derivatives contracts.

Type: [String](#)

Allowed values in UnderlyingObligationTypeCodeSet:

Code	Name	Description
0	Bond	Bond
1	ConvertibleBond	Convertible bond
2	Mortgage	Mortgage
3	Loan	Loan

Used in components: [UnderlyingInstrument](#)

### 180.2.5961 UnderlyingOfferPx

Offer price of the underlying instrument.

Type: [Price](#)

Used in messages: [SecurityRiskMetricsReport](#)

### 180.2.5962 UnderlyingOpenUnits

The number of units (units of the index or number of securities, par amount of a bond) that constitute the underlier. In the case of a basket swap, this is used to reference both the number of basket units, and the number of each asset components of the basket when these are expressed in absolute terms.

Type: **Qty**

Used in components: **UnderlyingInstrument**

### **180.2.5963 UnderlyingOptAttribute**

Underlying security's OptAttribute.

See OptAttribute (206) field for description

Type: **char**

Used in components: **UnderlyingInstrument**

### **180.2.5964 UnderlyingOptionExerciseBusinessCenter**

The business center calendar used to adjust the option exercise dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingOptionExerciseBusinessCenterGrp**

### **180.2.5965 UnderlyingOptionExerciseBusinessCenterGrp**

UnderlyingOptionExerciseBusinessCenterGrp is a repeating subcomponent of the UnderlyingOptionExerciseDates component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingOptionExerciseBusinessCenters	[1..1]	NumInGroup	
UnderlyingOptionExerciseBusinessCenter	[0..1]	String	Required if NoUnderlyingOptionExerciseBusinessCenters(41820) > 0.

Used in components: **UnderlyingOptionExerciseDates**

### 180.2.5966 UnderlyingOptionExerciseBusinessDayConvention

The business day convention used to adjust the option exercise dates. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **UnderlyingOptionExerciseDates**

### 180.2.5967 UnderlyingOptionExercise

The UnderlyingOptionExercise component is a subcomponent of the UnderlyingInstrument component used to specify option exercise provisions. Its purpose is to identify the opportunities and conditions for exercise, e.g. the schedule of dates on which exercise is allowed. The embedded UnderlyingOptionExerciseExpiration component is used to terminate the opportunity for exercise.

Name	Mult.	Type	Description
<b>UnderlyingExerciseDesc</b>	[0..1]	String	
<b>EncodedUnderlyingExerciseDescLen</b>	[0..1]	Length	Must be set if EncodedUnderlyingExerciseDesc(41812) field is specified and must immediately precede it.
<b>EncodedUnderlyingExerciseDesc</b>	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingExerciseDesc(41810) field in the encoded format specified via the MessageEncoding(347) field.

Name	Mult.	Type	Description
UnderlyingAutomaticExerciseIndicator	[0..1]	Boolean	
UnderlyingAutomaticExerciseThresholdRate	[0..1]	float	
UnderlyingExerciseConfirmation-Method	[0..1]	CodeSet	
UnderlyingManualNoticeBusinessCenter	[0..1]	String	
UnderlyingFallbackExerciseIndicator	[0..1]	Boolean	
UnderlyingLimitedRightToConfirmIndicator	[0..1]	Boolean	
UnderlyingExerciseSplitTicketIndicator	[0..1]	Boolean	
UnderlyingSettlMethodElectingParty-Side	[0..1]	CodeSet	
UnderlyingSettlMethodElectionDate	[0..1]	Component	
UnderlyingOptionExerciseDates	[0..1]	Component	
UnderlyingOptionExerciseExpiration	[0..1]	Component	
UnderlyingOptionExerciseMakeWholeProvision	[0..1]	Component	

Used in components: [UnderlyingInstrument](#)

### 180.2.5968 UnderlyingOptionExerciseDate

The adjusted or unadjusted option exercise fixed date.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingOptionExerciseDateGrp](#)

### 180.2.5969 UnderlyingOptionExerciseDateGrp

The UnderlyingOptionExerciseDateGrp is a repeating subcomponent of the UnderlyingOptionExerciseDates component used to specify fixed dates for exercise.

Name	Mult.	Type	Description
NoUnderlyingOptionExerciseDates	[1..1]	NumInGroup	

Name	Mult.	Type	Description
UnderlyingOptionExerciseDate	[0..1]	LocalMktDate	Required if NoUnderlyingOptionExerciseDates(41841) > 0.
UnderlyingOptionExerciseDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [UnderlyingOptionExerciseDates](#)

### 180.2.5970 UnderlyingOptionExerciseDates

The UnderlyingOptionExerciseDate component is a subcomponent of the UnderlyingOptionExercise component used to specify option exercise dates.

Name	Mult.	Type	Description
UnderlyingOptionExerciseBusiness-DayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to the underlying exercise dates.
UnderlyingOptionExerciseBusiness-CenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to the underlying option exercise dates.
UnderlyingOptionExerciseDateGrp	[0..*]	Group	
UnderlyingOptionExerciseEarliestDate-OffsetDayType	[0..1]	CodeSet	
UnderlyingOptionExerciseEarliestDate-OffsetPeriod	[0..1]	int	Conditionally required when UnderlyingOptionExerciseEarliestDateUnit(41825) is specified.
UnderlyingOptionExerciseEarliestDate-OffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingOptionExerciseEarliestDatePeriod(41824) is specified.
UnderlyingOptionExerciseFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingOptionExerciseFrequencyUnit(41827) is specified.
UnderlyingOptionExerciseFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingOptionExerciseFrequencyPeriod(41826) is specified.
UnderlyingOptionExerciseStartDateUnadjusted	[0..1]	LocalMktDate	



Name	Mult.	Type	Description
UnderlyingOptionExerciseStartDateRelativeTo	[0..1]	int	
UnderlyingOptionExerciseStartDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingOptionExerciseStartDateOffsetUnit(41831) is specified.
UnderlyingOptionExerciseStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingOptionExerciseStartDateOffsetPeriod(41830) is specified.
UnderlyingOptionExerciseStartDateOffsetDayType	[0..1]	CodeSet	
UnderlyingOptionExerciseStartDateAdjusted	[0..1]	LocalMktDate	
UnderlyingOptionExerciseSkip	[0..1]	int	
UnderlyingOptionExerciseNominationDeadline	[0..1]	LocalMktDate	
UnderlyingOptionExerciseFirstDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingOptionExerciseLastDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingOptionExerciseEarliestTime	[0..1]	LocalMktTime	
UnderlyingOptionExerciseLatestTime	[0..1]	LocalMktTime	
UnderlyingOptionExerciseTimeBusinessCenter	[0..1]	String	

Used in components: **UnderlyingOptionExercise**

### 180.2.5971 UnderlyingOptionExerciseDateType

Specifies the type of option exercise date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **UnderlyingOptionExerciseDateGrp**

**180.2.5972 UnderlyingOptionExerciseEarliestDateOffsetDayType**

Specifies the day type of the relative earliest exercise date offset.

Type: **int**

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingOptionExerciseDates**

**180.2.5973 UnderlyingOptionExerciseEarliestDateOffsetPeriod**

Time unit multiplier for the relative earliest exercise date offset.

Type: **int**

Used in components: **UnderlyingOptionExerciseDates**

**180.2.5974 UnderlyingOptionExerciseEarliestDateOffsetUnit**

Time unit associated with the relative earliest exercise date offset.

Type: **String**

Allowed values in ProvisionOptionExerciseEarliestDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingOptionExerciseDates**

### 180.2.5975 UnderlyingOptionExerciseEarliestTime

The earliest time at which notice of exercise can be given by the buyer to the seller (or seller's agent) (i) on the expiration date, in the case of a European style option, (ii) on each Bermuda option exercise date and the expiration date, in the case of a Bermuda style option, (iii) the commencement date to, and including, the expiration date, in the case of an American option.

Type: **LocalMktTime**

Used in components: **UnderlyingOptionExerciseDates**

### 180.2.5976 UnderlyingOptionExerciseExpiration

The UnderlyingOptionExerciseExpiration component is a subcomponent of the UnderlyingOptionExercise component used to specify option exercise expiration dates and times. The purpose of UnderlyingOptionExercise is to identify the scheduled opportunities for exercise. UnderlyingOptionExerciseExpiration identifies the end of the schedule.

Name	Mult.	Type	Description
<b>UnderlyingOptionExerciseExpirationDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to the underlying exercise expiration dates.
<b>UnderlyingOptionExerciseExpirationDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to the underlying option exercise expiration dates.
<b>UnderlyingOptionExerciseExpirationDateGrp</b>	[0..*]	Group	
<b>UnderlyingOptionExerciseExpirationDateRelativeTo</b>	[0..1]	int	
<b>UnderlyingOptionExerciseExpirationDateOffsetPeriod</b>	[0..1]	int	Conditionally required when UnderlyingOptionExerciseExpirationDateOffsetUnit(41849) is specified.
<b>UnderlyingOptionExerciseExpirationDateOffsetUnit</b>	[0..1]	CodeSet	Conditionally required when UnderlyingOptionExerciseExpirationDateOffsetPeriod(41848) is specified.
<b>UnderlyingOptionExerciseExpirationFrequencyPeriod</b>	[0..1]	int	Conditionally required when UnderlyingOptionExerciseExpirationFrequencyUnit(41851) is specified.

Name	Mult.	Type	Description
<a href="#">UnderlyingOptionExerciseExpirationFrequencyUnit</a>	[0..1]	CodeSet	Conditionally required when <a href="#">UnderlyingOptionExerciseExpirationFrequencyPeriod(41850)</a> is specified.
<a href="#">UnderlyingOptionExerciseExpirationRollConvention</a>	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the <a href="#">UnderlyingDateAdjustment</a> component in <a href="#">UnderlyingInstrument</a> . The specified values would be specific to this instance of the option exercise dates.
<a href="#">UnderlyingOptionExerciseExpirationDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingOptionExerciseExpirationTime</a>	[0..1]	LocalMktTime	
<a href="#">UnderlyingOptionExerciseExpirationTimeBusinessCenter</a>	[0..1]	String	

Used in components: [UnderlyingOptionExercise](#)

### 180.2.5977 [UnderlyingOptionExerciseExpirationDate](#)

The adjusted or unadjusted option exercise expiration fixed date.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingOptionExerciseExpirationDateGrp](#)

### 180.2.5978 [UnderlyingOptionExerciseExpirationDateBusinessCenter](#)

The business center calendar used to adjust the option exercise expiration dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingOptionExerciseExpirationDateBusinessCenterGrp](#)

### 180.2.5979 [UnderlyingOptionExerciseExpirationDateBusinessCenterGrp](#)

[UnderlyingOptionExerciseExpirationDateBusinessCenterGrp](#) is a repeating subcomponent of the [UnderlyingOptionExerciseExpiration](#) component used to specify the set of business centers whose calendars

drive date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingOptionExerciseExpirationDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingOptionExerciseExpirationDateBusinessCenter	[0..1]	String	Required if NoUnderlyingOptionExerciseExpirationDateBusinessCenters(41844) > 0.

Used in components: [UnderlyingOptionExerciseExpiration](#)

### 180.2.5980 UnderlyingOptionExerciseExpirationDateBusinessDayConvention

The business day convention used to adjust the option exercise expiration dates. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingOptionExerciseExpiration](#)

### 180.2.5981 UnderlyingOptionExerciseExpirationDateGrp

The UnderlyingOptionExerciseExpirationDateGrp is a repeating subcomponent of the UnderlyingOptionExerciseExpiration component used to specify fixed dates for expiration.

Name	Mult.	Type	Description
NoUnderlyingOptionExerciseExpirationDates	[1..1]	NumInGroup	
UnderlyingOptionExerciseExpirationDate	[0..1]	LocalMktDate	Required if NoUnderlyingOptionExpirationDates(41856) > 0.
UnderlyingOptionExerciseExpirationDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [UnderlyingOptionExerciseExpiration](#)

### 180.2.5982 UnderlyingOptionExerciseExpirationDateOffsetDayType

Specifies the day type of the relative option exercise expiration date offset.

Type: [int](#)

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingOptionExerciseExpiration](#)

### 180.2.5983 UnderlyingOptionExerciseExpirationDateOffsetPeriod

Time unit multiplier for the relative exercise expiration date offset.

Type: [int](#)

Used in components: [UnderlyingOptionExerciseExpiration](#)

**180.2.5984 UnderlyingOptionExerciseExpirationDateOffsetUnit**

Time unit associated with the relative exercise expiration date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingOptionExerciseExpiration**

**180.2.5985 UnderlyingOptionExerciseExpirationDateRelativeTo**

Specifies the anchor date when the option exercise expiration date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingOptionExerciseExpiration**

**180.2.5986 UnderlyingOptionExerciseExpirationDateType**

Specifies the type of option exercise expiration date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **UnderlyingOptionExerciseExpirationDateGrp**

**180.2.5987 UnderlyingOptionExerciseExpirationFrequencyPeriod**

Time unit multiplier for the frequency of exercise expiration dates.

Type: **int**

Used in components: **UnderlyingOptionExerciseExpiration**

**180.2.5988 UnderlyingOptionExerciseExpirationFrequencyUnit**

Time unit associated with the frequency of exercise expiration dates.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingOptionExerciseExpiration**

**180.2.5989 UnderlyingOptionExerciseExpirationRollConvention**

The convention for determining the sequence of exercise expiration dates. It is used in conjunction with a specified frequency. Used only to override the roll convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month



Code	Name	Description
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEigthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.

Code	Name	Description
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [UnderlyingOptionExerciseExpiration](#)

#### **180.2.5990 UnderlyingOptionExerciseExpirationTime**

The option exercise expiration time.

Type: [LocalMktTime](#)

Used in components: [UnderlyingOptionExerciseExpiration](#)

#### **180.2.5991 UnderlyingOptionExerciseExpirationTimeBusinessCenter**

The business center used to determine the locale for option exercise expiration time, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in components: [UnderlyingOptionExerciseExpiration](#)

#### **180.2.5992 UnderlyingOptionExerciseFirstDateUnadjusted**

The unadjusted first exercise date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingOptionExerciseDates](#)

**180.2.5993 UnderlyingOptionExerciseFrequencyPeriod**

Time unit multiplier for the frequency of exercise dates.

Type: **int**

Used in components: **UnderlyingOptionExerciseDates**

**180.2.5994 UnderlyingOptionExerciseFrequencyUnit**

Time unit associated with the frequency of exercise dates.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingOptionExerciseDates**

**180.2.5995 UnderlyingOptionExerciseLastDateUnadjusted**

The unadjusted last exercise date.

Type: **LocalMktDate**

Used in components: **UnderlyingOptionExerciseDates**

**180.2.5996 UnderlyingOptionExerciseLatestTime**

Latest exercise time. See also UnderlyingOptionExerciseEarliestTime(41838).

Type: **LocalMktTime**

Used in components: **UnderlyingOptionExerciseDates**

**180.2.5997 UnderlyingOptionExerciseMakeWholeProvision**

UnderlyingOptionExerciseMakeWholeProvision is a subcomponent of the UnderlyingOptionExercise component used to specify the set of rules of maintaining balance when an option is exercised.

Name	Mult.	Type	Description
UnderlyingMakeWholeDate	[0..1]	LocalMktDate	
UnderlyingMakeWholeAmount	[0..1]	Amt	
UnderlyingMakeWholeBenchmarkCurveName	[0..1]	String	
UnderlyingMakeWholeBenchmarkCurvePoint	[0..1]	String	
UnderlyingMakeWholeRecallSpread	[0..1]	PriceOffset	
UnderlyingMakeWholeBenchmarkQuote	[0..1]	CodeSet	
UnderlyingMakeWholeInterpolationMethod	[0..1]	CodeSet	

Used in components: [UnderlyingOptionExercise](#)

**180.2.5998 UnderlyingOptionExerciseNominationDeadline**

The last date (adjusted) for establishing the option exercise terms.

Type: [LocalMktDate](#)

Used in components: [UnderlyingOptionExerciseDates](#)

**180.2.5999 UnderlyingOptionExerciseSkip**

The number of periods in the referenced date schedule that are between each date in the relative date schedule. Thus a skip of 2 would mean that dates are relative to every second date in the referenced schedule. If present this should have a value greater than 1.

Type: [int](#)

Used in components: [UnderlyingOptionExerciseDates](#)

**180.2.6000 UnderlyingOptionExerciseStartDateAdjusted**

The adjusted start date for calculating periodic exercise dates.

Type: **LocalMktDate**

Used in components: **UnderlyingOptionExerciseDates**

**180.2.6001 UnderlyingOptionExerciseStartDateOffsetDayType**

Specifies the day type of the relative option exercise start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingOptionExerciseDates**

**180.2.6002 UnderlyingOptionExerciseStartDateOffsetPeriod**

Time unit multiplier for the relative exercise start date offset.

Type: **int**

Used in components: **UnderlyingOptionExerciseDates**

**180.2.6003 UnderlyingOptionExerciseStartDateOffsetUnit**

Time unit associated with the relative exercise start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingOptionExerciseDates](#)

#### **180.2.6004 UnderlyingOptionExerciseStartDateRelativeTo**

Specifies the anchor date when the option exercise start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [UnderlyingOptionExerciseDates](#)

#### **180.2.6005 UnderlyingOptionExerciseStartDateUnadjusted**

The unadjusted start date for calculating periodic exercise dates.

Type: [LocalMktDate](#)

Used in components: [UnderlyingOptionExerciseDates](#)

#### **180.2.6006 UnderlyingOptionExerciseTimeBusinessCenter**

The business center used to determine the locale for option exercise time, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values

Type: [String](#)

Used in components: [UnderlyingOptionExerciseDates](#)

#### **180.2.6007 UnderlyingOptionExpirationDesc**

Description of the option expiration.

Type: [String](#)

Used in components: [UnderlyingInstrument](#)

**180.2.6008 UnderlyingOptionsExchangeDividendsIndicator**

Indicates whether option exchange dividends are applicable.

Type: **Boolean**

Used in components: **UnderlyingDividendConditions**

**180.2.6009 UnderlyingOptPayoutAmount**

Cash amount indicating the pay out associated with an option. For binary options this is a fixed amount.

Type: **Amt**

Used in components: **UnderlyingInstrument**

**180.2.6010 UnderlyingOptPayoutType**

Indicates the type of valuation method or payout trigger for an in-the-money option.

Type: **int**

Allowed values in OptPayoutTypeCodeSet:

Code	Name	Description
1	Vanilla	Vanilla
2	Capped	Capped
3	Binary	Digital (Binary)
4	Asian	Asian
5	Barrier	Barrier
6	DigitalBarrier	Digital Barrier
7	Lookback	Lookback
8	OtherPathDependent	Other path dependent
99	Other	Other

Used in components: **UnderlyingInstrument**

#### **180.2.6011 UnderlyingOriginalNotionalPercentageOutstanding**

See OriginalNotionalPercentageOutstanding(1452)

Type: **Percentage**

Used in components: **UnderlyingInstrument**

#### **180.2.6012 UnderlyingPayAmount**

Amount to pay in order to receive the underlying instrument

Type: **Amt**

Used in groups: **UnderlyingAmount**

#### **180.2.6013 UnderlyingPaymentScheduleCurrency**

The currency for this step. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6014 UnderlyingPaymentScheduleEndDateUnadjusted**

The unadjusted end date of a cashflow payment.

Type: **LocalMktDate**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6015 UnderlyingPaymentScheduleFixedAmount**

The explicit payment amount for this step.

Type: **Amt**

Used in groups: **UnderlyingPaymentScheduleGrp**



**180.2.6016 UnderlyingPaymentScheduleFixedCurrency**

The currency of the fixed amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6017 UnderlyingPaymentScheduleFixingDateAdjusted**

The adjusted fixing date.

Type: **LocalMktDate**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6018 UnderlyingPaymentScheduleFixingDateBusinessCenter**

The business center calendar used to adjust the payment schedule's fixing date, e.g. "GBLO". See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingPaymentScheduleFixingDateBusinessCenterGrp**

**180.2.6019 UnderlyingPaymentScheduleFixingDateBusinessCenterGrp**

UnderlyingPaymentScheduleFixingDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingPaymentScheduleGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in the UnderlyingInstrument component.

Name	Mult.	Type	Description
NoUnderlyingPaymentScheduleFixing- DateBusinessCenters	[1..1]	NumInGroup	
UnderlyingPaymentScheduleFixing- DateBusinessCenter	[0..1]	String	Required if NoUnderlyingPaymentScheduleFixing- DateBusinessCenters(40966) > 0.

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6020 UnderlyingPaymentScheduleFixingDateBusinessDayCnvt**

The business day convention used to adjust the payment schedule's fixing date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6021 UnderlyingPaymentScheduleFixingDateOffsetDayType**

Specifies the day type of the relative fixing date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6022 UnderlyingPaymentScheduleFixingDateOffsetPeriod**

Time unit multiplier for the relative fixing date offset.

Type: **int**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6023 UnderlyingPaymentScheduleFixingDateOffsetUnit**

Time unit associated with the relative fixing date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6024 UnderlyingPaymentScheduleFixingDateRelativeTo**

Specifies the anchor date when the fixing date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6025 UnderlyingPaymentScheduleFixingDateUnadjusted**

The unadjusted fixing date.

Type: **LocalMktDate**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6026 UnderlyingPaymentScheduleFixingDayCount**

The number of days over which fixing should take place.

Type: **int**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6027 UnderlyingPaymentScheduleFixingDayDistribution**

The distribution of fixing days.

Type: **int**

Allowed values in PaymentStreamPricingDayDistributionCodeSet:

Code	Name	Description
0	All	All
1	First	First
2	Last	Last
3	Penultimate	Penultimate

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6028 UnderlyingPaymentScheduleFixingDayGrp**

The UnderlyingPaymentScheduleFixingDayGrp is a repeating subcomponent of the UnderlyingPaymentScheduleGrp component used to detail periodic fixing days.

Name	Mult.	Type	Description
<b>NoUnderlyingPaymentScheduleFixing-Days</b>	[1..1]	NumInGroup	
<b>UnderlyingPaymentScheduleFixing-DayOfWeek</b>	[0..1]	CodeSet	Required if NoUnderlyingPaymentScheduleFixing-Days(41878) > 0.
<b>UnderlyingPaymentScheduleFixing-DayNumber</b>	[0..1]	int	

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6029 UnderlyingPaymentScheduleFixingDayNumber**

The occurrence of the day of week on which fixing takes place.

Type: **int**

Used in groups: **UnderlyingPaymentScheduleFixingDayGrp**

**180.2.6030 UnderlyingPaymentScheduleFixingDayOfWeek**

The day of the week on which fixing takes place.

Type: **int**

Allowed values in PaymentStreamPricingDayOfWeekCodeSet:

Code	Name	Description
0	EveryDay	Every day (the default if not specified)
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday

Used in groups: **UnderlyingPaymentScheduleFixingDayGrp**

**180.2.6031 UnderlyingPaymentScheduleFixingFirstObservationDateOffsetPeriod**

Time unit multiplier for the relative first observation date offset.

Type: **int**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6032 UnderlyingPaymentScheduleFixingFirstObservationDateOffsetUnit**

Time unit associated with the relative first observation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [UnderlyingPaymentScheduleGrp](#)

### **180.2.6033 UnderlyingPaymentScheduleFixingLagPeriod**

Time unit multiplier for the fixing lag duration.

Type: [int](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

### **180.2.6034 UnderlyingPaymentScheduleFixingLagUnit**

Time unit associated with the fixing lag duration.

Type: [String](#)

Allowed values in PaymentStreamInflationLagUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [UnderlyingPaymentScheduleGrp](#)

### **180.2.6035 UnderlyingPaymentScheduleFixingTime**

The fixing time.

Type: [LocalMktTime](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

**180.2.6036 UnderlyingPaymentScheduleFixingTimeBusinessCenter**

Business center for determining fixing time. See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6037 UnderlyingPaymentScheduleGrp**

The UnderlyingPaymentScheduleGrp is a repeating subcomponent of the UnderlyingPaymentStream component used to specify notional and rate steps in the payment stream.

Name	Mult.	Type	Description
NoUnderlyingPaymentSchedules	[1..1]	NumInGroup	
UnderlyingPaymentScheduleType	[0..1]	CodeSet	Required if NoUnderlyingPaymentSchedules(40664) > 0.
UnderlyingPaymentScheduleXID	[0..1]	XID	
UnderlyingPaymentScheduleXIDRef	[0..1]	XIDREF	
UnderlyingPaymentScheduleStubType	[0..1]	CodeSet	
UnderlyingPaymentScheduleStartDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPaymentScheduleEndDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPaymentSchedulePaySide	[0..1]	CodeSet	
UnderlyingPaymentScheduleReceiveSide	[0..1]	CodeSet	
UnderlyingPaymentScheduleNotional	[0..1]	Amt	
UnderlyingPaymentScheduleCurrency	[0..1]	Currency	
UnderlyingPaymentScheduleRate	[0..1]	Percentage	
UnderlyingPaymentScheduleRateMultiplier	[0..1]	float	
UnderlyingPaymentScheduleRateSpread	[0..1]	PriceOffset	
UnderlyingPaymentScheduleRateCurrency	[0..1]	Currency	
UnderlyingPaymentScheduleRateUnitOfMeasure	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingPaymentScheduleRateConversionFactor	[0..1]	float	
UnderlyingPaymentScheduleRateSpreadType	[0..1]	CodeSet	
UnderlyingPaymentScheduleRateSpreadPositionType	[0..1]	CodeSet	
UnderlyingPaymentScheduleRateTreatment	[0..1]	CodeSet	
UnderlyingPaymentScheduleFixedAmount	[0..1]	Amt	
UnderlyingPaymentScheduleFixedCurrency	[0..1]	Currency	
UnderlyingPaymentScheduleSettlPeriodPrice	[0..1]	Price	
UnderlyingPaymentScheduleSettlPeriodPriceCurrency	[0..1]	Currency	
UnderlyingPaymentScheduleSettlPeriodPriceUnitOfMeasure	[0..1]	CodeSet	
UnderlyingPaymentScheduleStepUnitOfMeasure	[0..1]	CodeSet	
UnderlyingPaymentScheduleStepFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentScheduleStepFrequencyUnit(40681) is specified.
UnderlyingPaymentScheduleStepFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentScheduleStepFrequencyPeriod(40680) is specified.
UnderlyingPaymentScheduleStepOffsetValue	[0..1]	Amt	
UnderlyingPaymentScheduleStepRate	[0..1]	Percentage	
UnderlyingPaymentScheduleStepOffsetRate	[0..1]	Percentage	
UnderlyingPaymentScheduleStepRelativeTo	[0..1]	CodeSet	
UnderlyingPaymentScheduleRateSourceGrp	[0..*]	Group	
UnderlyingPaymentScheduleFixingDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPaymentScheduleWeight	[0..1]	float	



Name	Mult.	Type	Description
UnderlyingPaymentScheduleFixing-DateRelativeTo	[0..1]	int	
UnderlyingPaymentScheduleFixing-DateBusinessDayCnvt	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's payment schedule.
UnderlyingPaymentScheduleFixing-DateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's payment schedule.
UnderlyingPaymentScheduleFixingDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentScheduleFixingDateOffsetUnit(40692) is specified.
UnderlyingPaymentScheduleFixingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentScheduleFixingDateOffsetPeriod(40691) is specified.
UnderlyingPaymentScheduleFixingDateOffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentScheduleFixing-DayDistribution	[0..1]	CodeSet	
UnderlyingPaymentScheduleFixing-DayCount	[0..1]	int	
UnderlyingPaymentScheduleFixingDateAdjusted	[0..1]	LocalMktDate	
UnderlyingPaymentScheduleFixing-DayGrp	[0..*]	Group	
UnderlyingPaymentScheduleFixingLagPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentScheduleFixingLagUnit(41894) is specified.
UnderlyingPaymentScheduleFixingLagUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentScheduleFixingLagPeriod(41893) is specified.
UnderlyingPaymentScheduleFixingFirstObservationDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentScheduleFixingFirstObservationDateOffsetUnit(41896) is specified.
UnderlyingPaymentScheduleFixingFirstObservationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentScheduleFixingFirstObservationDateOffsetPeriod(41895) is specified.

Name	Mult.	Type	Description
UnderlyingPaymentScheduleFixing-Time	[0..1]	LocalMktTime	
UnderlyingPaymentScheduleFixing-TimeBusinessCenter	[0..1]	String	
UnderlyingPaymentScheduleInterimExchangePaymentDateRelativeTo	[0..1]	int	
UnderlyingPaymentScheduleInterimExchangeDatesBizDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's payment schedule.
UnderlyingPaymentScheduleInterimExchangeDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's payment schedule.
UnderlyingPaymentScheduleInterimExchangeDatesOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentScheduleInterimExchangeDatesOffsetUnit(40701) is specified.
UnderlyingPaymentScheduleInterimExchangeDatesOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentScheduleInterimExchangeDatesOffsetPeriod(40700) is specified.
UnderlyingPaymentScheduleInterimExchangeDatesOffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentScheduleInterimExchangeDateAdjusted	[0..1]	LocalMktDate	

Used in groups: [UnderlyingStreamGrp](#)

### 180.2.6038 UnderlyingPaymentScheduleInterimExchangeDateAdjusted

The adjusted interim exchange date.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

**180.2.6039 UnderlyingPaymentScheduleInterimExchangeDateBusinessCenterGrp**

UnderlyingPaymentScheduleInterimExchangeDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingPaymentScheduleGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in the UnderlyingInstrument component.

Name	Mult.	Type	Description
NoUnderlyingPaymentScheduleInterimExchangeDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingPaymentScheduleInterimExchangeDatesBusinessCenter	[0..1]	String	Required if NoUnderlyingPaymentScheduleInterimExchangeDateBusinessCenters(40967) > 0.

Used in groups: [UnderlyingPaymentScheduleGrp](#)

**180.2.6040 UnderlyingPaymentScheduleInterimExchangeDatesBizDayConvention**

The business day convention used to adjust the payment schedule's interim exchange date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [UnderlyingPaymentScheduleGrp](#)

**180.2.6041 UnderlyingPaymentScheduleInterimExchangeDatesBusinessCenter**

The business center calendar used to adjust the payment schedule's interim exchange date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingPaymentScheduleInterimExchangeDateBusinessCenterGrp**

**180.2.6042 UnderlyingPaymentScheduleInterimExchangeDatesOffsetDayType**

Specifies the day type of the relative interim exchange date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6043 UnderlyingPaymentScheduleInterimExchangeDatesOffsetPeriod**

Time unit multiplier for the relative interim exchange date offset.

Type: **int**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6044 UnderlyingPaymentScheduleInterimExchangeDatesOffsetUnit**

Time unit associated with the relative interim exchange date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6045 UnderlyingPaymentScheduleInterimExchangePaymentDateRelativeTo**

Specifies the anchor date when the interim exchange payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6046 UnderlyingPaymentScheduleNotional**

The notional value for this step, or amount of a cashflow payment.

Type: **Amt**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6047 UnderlyingPaymentSchedulePaySide**

The side of the party paying the step schedule.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy

Code	Name	Description
2	Sell	Sell

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6048 UnderlyingPaymentScheduleRate**

The rate value for this step.

Type: [Percentage](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6049 UnderlyingPaymentScheduleRateConversionFactor**

The number to be multiplied by the derived floating rate of the underlying's payment schedule in order to arrive at the payment rate. If omitted, the schedule rate conversion factor is 1.

Type: [float](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6050 UnderlyingPaymentScheduleRateCurrency**

Specifies the currency of the schedule rate. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6051 UnderlyingPaymentScheduleRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: [float](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

**180.2.6052 UnderlyingPaymentScheduleRateSource**

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: **UnderlyingPaymentScheduleRateSourceGrp**

**180.2.6053 UnderlyingPaymentScheduleRateSourceGrp**

UnderlyingPaymentScheduleRateSourceGrp is a repeating component within the UnderlyingPaymentScheduleGrp component used to identify primary and secondary rate sources.

Name	Mult.	Type	Description
<b>NoUnderlyingPaymentScheduleRateSources</b>	[1..1]	NumInGroup	
<b>UnderlyingPaymentScheduleRateSource</b>	[0..1]	CodeSet	Required if NoUnderlyingPaymentScheduleRates(40704) > 0.
<b>UnderlyingPaymentScheduleRateSourceType</b>	[0..1]	CodeSet	Required if NoUnderlyingPaymentScheduleRates(40704) > 0.
<b>UnderlyingPaymentScheduleReferencePage</b>	[0..1]	String	Conditionally required when UnderlyingPaymentScheduleRateSource(40705) = 99 (Other).

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6054 UnderlyingPaymentScheduleRateSourceType**

Rate source type.

Type: **int**

Allowed values in RateSourceTypeCodeSet:

Code	Name	Description
0	Primary	Primary
1	Secondary	Secondary

Used in groups: **UnderlyingPaymentScheduleRateSourceGrp**

**180.2.6055 UnderlyingPaymentScheduleRateSpread**

The spread value for this step.

Type: **PriceOffset**

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6056 UnderlyingPaymentScheduleRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in groups: **UnderlyingPaymentScheduleGrp**



**180.2.6057 UnderlyingPaymentScheduleRateSpreadType**

Specifies whether the rate spread is an absolute value to be added to the index rate or a percentage of the index rate.

Type: **int**

Allowed values in PaymentStreamRateSpreadTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6058 UnderlyingPaymentScheduleRateTreatment**

Specifies the yield calculation treatment for the step schedule.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6059 UnderlyingPaymentScheduleRateUnitOfMeasure**

The schedule rate unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances

Code	Name	Description
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters

Code	Name	Description
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece

Code	Name	Description
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6060 UnderlyingPaymentScheduleReceiveSide**

The side of the party receiving the step schedule.

Type: [int](#)

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6061 UnderlyingPaymentScheduleReferencePage**

Identifies the reference “page” from the rate source.

For FX, the reference page to the spot rate to be used for the reference FX spot rate.

When RateSource(1446) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in groups: **UnderlyingPaymentScheduleRateSourceGrp**

#### **180.2.6062 UnderlyingPaymentScheduleSettlPeriodPrice**

The schedule settlement period price.

Type: **Price**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6063 UnderlyingPaymentScheduleSettlPeriodPriceCurrency**

The currency of the schedule settlement period price. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6064 UnderlyingPaymentScheduleSettlPeriodPriceUnitOfMeasure**

The settlement period price unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels

Code	Name	Description
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters

Code	Name	Description
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot

Code	Name	Description
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6065 UnderlyingPaymentScheduleStartDateUnadjusted**

The unadjusted date on which the value is adjusted, or calculated if a future value notional for certain non-deliverable interest rate swaps (e.g. Brazillian Real (BRL) vs. CETIP Interbank Deposit Rate (CDI)), or the start date of a cashflow payment.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6066 UnderlyingPaymentScheduleStepFrequencyPeriod**

Time unit multiplier for the step frequency.

Type: [int](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6067 UnderlyingPaymentScheduleStepFrequencyUnit**

Time unit associated with the step frequency.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:



Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6068 UnderlyingPaymentScheduleStepOffsetRate**

The explicit amount that the rate changes on each step date. This can be a positive or negative value.

Type: [Percentage](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6069 UnderlyingPaymentScheduleStepOffsetValue**

The explicit amount that the notional changes on each step date. This can be a positive or negative amount.

Type: [Amt](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6070 UnderlyingPaymentScheduleStepRate**

The percentage by which the notional changes on each step date. The percentage is either a percentage applied to the initial notional amount or the previous outstanding notional, depending on the value specified in [UnderlyingPaymentScheduleStepRelativeTo\(40685\)](#). The percentage can be either positive or negative.

Type: [Percentage](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

**180.2.6071 UnderlyingPaymentScheduleStepRelativeTo**

Specifies whether the UnderlyingPaymentScheduleStepRate(40683) or UnderlyingPaymentScheduleStepOffsetValue(40682) should be applied to the initial notional or the previous notional in order to calculate the notional step change amount.

Type: **int**

Allowed values in PaymentScheduleStepRelativeToCodeSet:

Code	Name	Description
0	Initial	Initial
1	Previous	Previous

Used in groups: **UnderlyingPaymentScheduleGrp**

**180.2.6072 UnderlyingPaymentScheduleStepUnitOfMeasure**

The schedule step unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)

Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter

Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [UnderlyingPaymentScheduleGrp](#)

### 180.2.6073 UnderlyingPaymentScheduleStubType

Indicates to which stub this schedule applies.

Type: [int](#)

Allowed values in PaymentStubTypeCodeSet:

Code	Name	Description
0	Initial	Initial
1	Final	Final
2	CompoundingInitial	Compounding initial
3	CompoundingFinal	Compounding final

Used in groups: [UnderlyingPaymentScheduleGrp](#)

### 180.2.6074 UnderlyingPaymentScheduleType

Type of schedule.

Type: [int](#)

Allowed values in PaymentScheduleTypeCodeSet:

Code	Name	Description
0	Notional	Notional
1	CashFlow	Cash flow
2	FXLinkedNotional	FX linked notional
3	FixedRate	Fixed rate

Code	Name	Description
4	FutureValueNotional	Future value notional
5	KnownAmount	Known amount
6	FloatingRateMultiplier	Floating rate multiplier
7	Spread	Spread
8	CapRate	Cap rate
9	FloorRate	Floor rate
10	NonDeliverableSettlPaymentDates	Non-deliverable settlement payment dates
11	NonDeliverableSettlCalculation-Dates	Non-deliverable settlement calculation dates
12	NonDeliverableFXFixingDates	Non-deliverable fixing dates.
13	SettlPeriodNotnl	Settlement period notional
14	SettlPeriodPx	Settlement period price
15	CalcPeriod	Calculation period
16	DividendAccrualRateMultiplier	Dividend accrual rate multiplier
17	DividendAccrualRateSpread	Dividend accrual rate spread
18	DividendAccrualCapRate	Dividend accrual cap rate
19	DividendAccrualFloorRate	Dividend accrual floor rate
20	CompoundingRateMultiplier	Compounding rate multiplier
21	CompoundingRateSpread	Compounding rate spread
22	CompoundingCapRate	Compounding cap rate
23	CompoundingFloorRate	Compounding floor rate

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6075 UnderlyingPaymentScheduleWeight**

Floating rate observation weight for cashflow payment.

Type: [float](#)

Used in groups: [UnderlyingPaymentScheduleGrp](#)

#### **180.2.6076 UnderlyingPaymentScheduleXID**

Identifier of this UnderlyingPaymentSchedule for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6077 UnderlyingPaymentScheduleXIDRef**

Reference to payment schedule elsewhere in the message.

Type: **XIDREF**

Used in groups: **UnderlyingPaymentScheduleGrp**

#### **180.2.6078 UnderlyingPaymentStreamAccrualDays**

The number of days from the adjusted calculation period start date to the adjusted value date, calculated in accordance with the applicable day count fraction.

Type: **int**

Used in components: **UnderlyingPaymentStream**

#### **180.2.6079 UnderlyingPaymentStreamAveragingMethod**

When rate averaging is applicable, used to specify whether a weighted or unweighted average calculation method is to be used.

Type: **int**

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: **UnderlyingPaymentStreamFloatingRate**

#### **180.2.6080 UnderlyingPaymentStreamBoundsFirstDateUnadjusted**

The unadjusted first date of the compounding schedule. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamCompoundingDates**

### **180.2.6081 UnderlyingPaymentStreamBoundsLastDateUnadjusted**

The unadjusted last date of the compounding schedule. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamCompoundingDates**

### **180.2.6082 UnderlyingPaymentStreamCalculationLagPeriod**

Time unit multiplier for the calculation lag duration.

Type: **int**

Used in components: **UnderlyingPaymentStreamFloatingRate**

### **180.2.6083 UnderlyingPaymentStreamCalculationLagUnit**

Time unit associated with the calculation lag duration.

Type: **String**

Allowed values in PaymentStreamInflationLagUnitCodeSet:

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

---

Used in components: **UnderlyingPaymentStreamFloatingRate**



**180.2.6084 UnderlyingPaymentStreamCapRate**

The cap rate, if any, which applies to the floating rate. The cap rate (strike) is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6085 UnderlyingPaymentStreamCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6086 UnderlyingPaymentStreamCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6087 UnderlyingPaymentStreamCashSettlIndicator**

Indicates whether cash settlement is applicable.

Type: **Boolean**

Used in components: **UnderlyingPaymentStream**

**180.2.6088 UnderlyingPaymentStream**

The UnderlyingPaymentStream component is a subcomponent of the UnderlyingStream used to detail the attributes of a payment stream in a swap.

Name	Mult.	Type	Description
UnderlyingPaymentStreamType	[0..1]	CodeSet	
UnderlyingPaymentStreamMarketRate	[0..1]	int	
UnderlyingPaymentStreamDelayIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamCashSettlIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamSettlCurrency	[0..1]	Currency	
UnderlyingPaymentStreamDayCount	[0..1]	CodeSet	
UnderlyingPaymentStreamOtherDayCount	[0..1]	String	May be used to specify a count method not listed in UnderlyingPaymentStreamDayCount(40572).
UnderlyingPaymentStreamAccrualDays	[0..1]	int	
UnderlyingPaymentStreamDiscountType	[0..1]	CodeSet	
UnderlyingPaymentStreamDiscountRate	[0..1]	Percentage	
UnderlyingPaymentStreamDiscountRateDayCount	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingMethod	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingXIDRef	[0..1]	XIDREF	Mutually exclusive with UnderlyingPaymentStreamCompoundingFixedRate(42900) or the UnderlyingPaymentStreamCompoundingFloatingRate component.

Name	Mult.	Type	Description
UnderlyingPaymentStreamCompoundingSpread	[0..1]	PriceOffset	
UnderlyingPaymentStreamInterpolationMethod	[0..1]	CodeSet	
UnderlyingPaymentStreamInterpolationPeriod	[0..1]	CodeSet	
UnderlyingPaymentStreamInitialPrincipalExchangeIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamInterimPrincipalExchangeIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamFinalPrincipalExchangeIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamFlatRateIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamFlatRateAmount	[0..1]	Amt	
UnderlyingPaymentStreamFlatRateCurrency	[0..1]	Currency	
UnderlyingPaymentStreamMaximumPaymentAmount	[0..1]	Amt	
UnderlyingPaymentStreamMaximumPaymentCurrency	[0..1]	Currency	
UnderlyingPaymentStreamMaximumTransactionAmount	[0..1]	Amt	
UnderlyingPaymentStreamMaximumTransactionCurrency	[0..1]	Currency	
UnderlyingPaymentStreamPaymentDates	[0..1]	Component	
UnderlyingPaymentStreamResetDates	[0..1]	Component	
UnderlyingPaymentStreamFixedRate	[0..1]	Component	
UnderlyingPaymentStreamFloatingRate	[0..1]	Component	
UnderlyingPaymentStreamCompoundingFixedRate	[0..1]	float	Mutually exclusive with UnderlyingPaymentStreamCompoundingXIDRef(42896) or the UnderlyingPaymentStreamCompoundingFloatingRate component.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStreamCompoundingFloatingRate</a>	[0..1]	Component	Mutually exclusive with UnderlyingPaymentStreamCompoundingFixedRate(42900) or the UnderlyingPaymentStreamCompoundingXIDRef(42896).
<a href="#">UnderlyingPaymentStreamCompoundingDates</a>	[0..1]	Component	
<a href="#">UnderlyingPaymentStreamNonDeliverableSettlTerms</a>	[0..1]	Component	

Used in groups: [UnderlyingStreamGrp](#)

### 180.2.6089 UnderlyingPaymentStreamCompoundingAveragingMethod

Specifies the averaging method when compounding floating rate averaging is applicable (e.g. weighted or unweighted).

Type: [int](#)

Allowed values in PaymentStreamAveragingMethodCodeSet:

Code	Name	Description
0	Unweighted	Unweighted
1	Weighted	Weighted

Used in components: [UnderlyingPaymentStreamCompoundingFloatingRate](#)

### 180.2.6090 UnderlyingPaymentStreamCompoundingCapRate

The cap rate, if any, which applies to the compounding floating rate. It is only required where the compounding floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as "0.05".

Type: [Percentage](#)

Used in components: [UnderlyingPaymentStreamCompoundingFloatingRate](#)

**180.2.6091 UnderlyingPaymentStreamCompoundingCapRateBuySide**

Reference to the buyer of the compounding cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6092 UnderlyingPaymentStreamCompoundingCapRateSellSide**

Reference to the seller of the compounding cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6093 UnderlyingPaymentStreamCompoundingDate**

The compounding date. Type of date is specified in UnderlyingPaymentStreamCompoundingDate-Type(42903).

Type: **LocalMktDate**

Used in groups: **UnderlyingPaymentStreamCompoundingDateGrp**

**180.2.6094 UnderlyingPaymentStreamCompoundingDateGrp**

UnderlyingPaymentStreamCompoundingDateGrp is a subcomponent of the UnderlyingPaymentStreamCompoundingDates component used to specify predetermined compounding dates.

Name	Mult.	Type	Description
NoUnderlyingPaymentStreamCompoundingDates	[1..1]	NumInGroup	
UnderlyingPaymentStreamCompoundingDate	[0..1]	LocalMktDate	Required if NoUnderlyingPaymentStreamCompoundingDates(42901) > 0.
UnderlyingPaymentStreamCompoundingDateType	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in components: [UnderlyingPaymentStreamCompoundingDates](#)

**180.2.6095 UnderlyingPaymentStreamCompoundingDatesBusinessCenter**

The business center calendar used for date adjustment of the payment stream compounding dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingPaymentStreamCompoundingDatesBusinessCenterGrp](#)

**180.2.6096 UnderlyingPaymentStreamCompoundingDatesBusinessCenterGrp**

UnderlyingPaymentStreamCompoundingDatesBusinessCenterGrp is a repeating subcomponent within the UnderlyingPaymentStreamCompoundingDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingPaymentStreamCompoundingDatesBusinessCenters	[1..1]	NumInGroup	

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStreamCompoundingDatesBusinessCenter</a>	[0..1]	String	Required if NoUnderlyingPaymentStreamCompoundingDatesBusinessCenters(42915) > 0.

Used in components: [UnderlyingPaymentStreamCompoundingDates](#)

### 180.2.6097 UnderlyingPaymentStreamCompoundingDatesBusinessDayConvention

The compounding dates business day convention.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingPaymentStreamCompoundingDates](#)

### 180.2.6098 UnderlyingPaymentStreamCompoundingDates

UnderlyingPaymentStreamCompoundingDates is a subcomponent of the UnderlyingPaymentStream component used to specify the compounding dates of the stream - either specific, relative or periodic dates.

Name	Mult.	Type	Description
UnderlyingPaymentStreamCompoundingDatesBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to payment stream compounding dates.
UnderlyingPaymentStreamCompoundingDatesBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to payment stream compounding dates.
UnderlyingPaymentStreamCompoundingDateGrp	[0..*]	Group	
UnderlyingPaymentStreamCompoundingDatesRelativeTo	[0..1]	int	
UnderlyingPaymentStreamCompoundingDatesOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamCompoundingDatesOffsetUnit(42907) is specified.
UnderlyingPaymentStreamCompoundingDatesOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamCompoundingDatesOffsetPeriod(42906) is specified.
UnderlyingPaymentStreamCompoundingDatesOffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingPeriodSkip	[0..1]	int	
UnderlyingPaymentStreamCompoundingStartDate	[0..1]	Component	
UnderlyingPaymentStreamCompoundingEndDate	[0..1]	Component	
UnderlyingPaymentStreamCompoundingFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamCompoundingFrequencyUnit(42911) is specified.
UnderlyingPaymentStreamCompoundingFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamCompoundingFrequencyPeriod(42910) is specified.
UnderlyingPaymentStreamCompoundingRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the payment stream dates.



Name	Mult.	Type	Description
UnderlyingPaymentStreamBounds-FirstDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPaymentStreamBoundsLastDateUnadjusted	[0..1]	LocalMktDate	

Used in components: [UnderlyingPaymentStream](#)

### 180.2.6099 UnderlyingPaymentStreamCompoundingDatesOffsetDayType

Specifies the day type of the relative compounding date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingPaymentStreamCompoundingDates](#)

### 180.2.6100 UnderlyingPaymentStreamCompoundingDatesOffsetPeriod

Time unit multiplier for the relative compounding date offset.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamCompoundingDates](#)

### 180.2.6101 UnderlyingPaymentStreamCompoundingDatesOffsetUnit

Time unit associated with the relative compounding date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamCompoundingDates**

#### **180.2.6102 UnderlyingPaymentStreamCompoundingDatesRelativeTo**

Specifies the anchor date when the compounding dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamCompoundingDates**

#### **180.2.6103 UnderlyingPaymentStreamCompoundingDateType**

Specifies the type of payment compounding date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **UnderlyingPaymentStreamCompoundingDateGrp**

**180.2.6104 UnderlyingPaymentStreamCompoundingEndDateAdjusted**

The adjusted compounding end date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingPaymentStreamCompoundingEndDate](#)

**180.2.6105 UnderlyingPaymentStreamCompoundingEndDate**

[UnderlyingPaymentStreamCompoundingEndDate](#) is a subcomponent of the [UnderlyingPaymentStreamCompoundingDates](#) component used to specify the end date for compounding.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStreamCompoundingEndDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingPaymentStreamCompoundingEndDateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingPaymentStreamCompoundingEndDateOffsetPeriod</a>	[0..1]	int	Conditionally required when <a href="#">UnderlyingPaymentStreamCompoundingEndDateOffsetUnit(42920)</a> is specified.
<a href="#">UnderlyingPaymentStreamCompoundingEndDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when <a href="#">UnderlyingPaymentStreamCompoundingEndDateOffsetPeriod(42919)</a> is specified.
<a href="#">UnderlyingPaymentStreamCompoundingEndDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingPaymentStreamCompoundingEndDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [UnderlyingPaymentStreamCompoundingDates](#)

**180.2.6106 UnderlyingPaymentStreamCompoundingEndDateOffsetDayType**

Specifies the day type of the relative compounding end date offset.

Type: [int](#)

Allowed values in [PaymentStreamPaymentDateOffsetDayTypeCodeSet](#):

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingPaymentStreamCompoundingEndDate](#)

#### **180.2.6107 UnderlyingPaymentStreamCompoundingEndDateOffsetPeriod**

Time unit multiplier for the relative compounding end date offset.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamCompoundingEndDate](#)

#### **180.2.6108 UnderlyingPaymentStreamCompoundingEndDateOffsetUnit**

Time unit associated with the relative compounding end date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingPaymentStreamCompoundingEndDate](#)

#### **180.2.6109 UnderlyingPaymentStreamCompoundingEndDateRelativeTo**

Specifies the anchor date when the compounding end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamCompoundingEndDate**

#### **180.2.6110 UnderlyingPaymentStreamCompoundingEndDateUnadjusted**

The unadjusted compounding end date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamCompoundingEndDate**

#### **180.2.6111 UnderlyingPaymentStreamCompoundingFinalRatePrecision**

Specifies the compounding floating rate rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

#### **180.2.6112 UnderlyingPaymentStreamCompoundingFinalRateRoundingDirection**

Specifies the rounding direction for the compounding floating rate.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6113 UnderlyingPaymentStreamCompoundingFixedRate**

The compounding fixed rate applicable to the payment stream.

Type: **float**

Used in components: **UnderlyingPaymentStream**

**180.2.6114 UnderlyingPaymentStreamCompoundingFloatingRate**

UnderlyingPaymentStreamCompoundingFloatingRate is a subcomponent of the UnderlyingPaymentStream component used to report the parameters for determining the compounding floating rate of the stream.

Name	Mult.	Type	Description
UnderlyingPaymentStreamCompoundingRateIndex	[0..1]	String	
UnderlyingPaymentStreamCompoundingRateIndexCurvePeriod	[0..1]	int	Conditionally required if UnderlyingPaymentStreamCompoundingRateIndexCurveUnit(42925) is specified.
UnderlyingPaymentStreamCompoundingRateIndexCurveUnit	[0..1]	CodeSet	Conditionally required if UnderlyingPaymentStreamCompoundingRateIndexCurvePeriod(42924) is specified.
UnderlyingPaymentStreamCompoundingRateMultiplier	[0..1]	float	
UnderlyingPaymentStreamCompoundingRateSpread	[0..1]	PriceOffset	
UnderlyingPaymentStreamCompoundingRateSpreadPositionType	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingRateTreatment	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingCapRate	[0..1]	Percentage	
UnderlyingPaymentStreamCompoundingCapRateBuySide	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingCapRateSellSide	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingFloorRate	[0..1]	Percentage	
UnderlyingPaymentStreamCompoundingFloorRateBuySide	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingPaymentStreamCompoundingFloorRateSellSide	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingInitialRate	[0..1]	Percentage	
UnderlyingPaymentStreamCompoundingFinalRateRoundingDirection	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingFinalRatePrecision	[0..1]	int	
UnderlyingPaymentStreamCompoundingAveragingMethod	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingNegativeRateTreatment	[0..1]	CodeSet	

Used in components: [UnderlyingPaymentStream](#)

#### 180.2.6115 UnderlyingPaymentStreamCompoundingFloorRate

The floor rate, if any, which applies to the compounding floating rate. The floor rate (strike) is only required where the compounding floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate. The rate is expressed as a decimal, e.g. 5% is represented as "0.05".

Type: [Percentage](#)

Used in components: [UnderlyingPaymentStreamCompoundingFloatingRate](#)

#### 180.2.6116 UnderlyingPaymentStreamCompoundingFloorRateBuySide

Reference to the buyer of the compounding floor rate option through its trade side.

Type: [int](#)

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: [UnderlyingPaymentStreamCompoundingFloatingRate](#)

**180.2.6117 UnderlyingPaymentStreamCompoundingFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6118 UnderlyingPaymentStreamCompoundingFrequencyPeriod**

Time unit multiplier for the frequency at which compounding dates occur.

Type: **int**

Used in components: **UnderlyingPaymentStreamCompoundingDates**

**180.2.6119 UnderlyingPaymentStreamCompoundingFrequencyUnit**

Time unit associated with the frequency at which compounding dates occur.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: **UnderlyingPaymentStreamCompoundingDates**



**180.2.6120 UnderlyingPaymentStreamCompoundingInitialRate**

The initial compounding floating rate reset agreed between the principal parties involved in the trade. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. The initial rate is expressed in decimal form, e.g. 5% is represented as "0.05".

Type: **Percentage**

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6121 UnderlyingPaymentStreamCompoundingMethod**

Compounding Method.

Type: **int**

Allowed values in PaymentStreamCompoundingMethodCodeSet:

Code	Name	Description
0	None	None
1	Flat	Flat
2	Straight	Straight
3	SpreadExclusive	Spread exclusive

Used in components: **UnderlyingPaymentStream**

**180.2.6122 UnderlyingPaymentStreamCompoundingNegativeRateTreatment**

Specifies the method for calculating payment obligations when a compounding floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6123 UnderlyingPaymentStreamCompoundingPeriodSkip**

The number of periods in the "RelativeTo" schedule that are between each date in the compounding schedule. A skip of 2 would mean that compounding dates are relative to every second date in the "RelativeTo" schedule. If present this should have a value greater than 1.

Type: **int**

Used in components: **UnderlyingPaymentStreamCompoundingDates**

**180.2.6124 UnderlyingPaymentStreamCompoundingRateIndex**

The payment stream's compounding floating rate index.

Type: **String**

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6125 UnderlyingPaymentStreamCompoundingRateIndexCurvePeriod**

Time unit multiplier for the payment stream's compounding floating rate index curve period.

Type: **int**

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6126 UnderlyingPaymentStreamCompoundingRateIndexCurveUnit**

Time unit associated with the payment stream's compounding floating rate index curve period.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6127 UnderlyingPaymentStreamCompoundingRateMultiplier**

A rate multiplier to apply to the compounding floating rate. The multiplier can be less than or greater than 1 (one). This should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: **float**

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6128 UnderlyingPaymentStreamCompoundingRateSpread**

The basis points spread from the index specified in UnderlyingPaymentStreamCompoundingRateIndex(42923).

Type: **PriceOffset**

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6129 UnderlyingPaymentStreamCompoundingRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

**180.2.6130 UnderlyingPaymentStreamCompoundingRateTreatment**

Specifies the yield calculation treatment for the index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: **UnderlyingPaymentStreamCompoundingFloatingRate**

### 180.2.6131 UnderlyingPaymentStreamCompoundingRollConvention

The convention for determining the sequence of compounding dates. It is used in conjunction with a specified frequency.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6th day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelfthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	FourteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month

Code	Name	Description
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighthDay	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [UnderlyingPaymentStreamCompoundingDates](#)

**180.2.6132 UnderlyingPaymentStreamCompoundingSpread**

The spread to be used for compounding. Used in scenarios where the interest payment is based on a compounding formula that uses a compounding spread in addition to the regular spread.

Type: **PriceOffset**

Used in components: **UnderlyingPaymentStream**

**180.2.6133 UnderlyingPaymentStreamCompoundingStartDateAdjusted**

The adjusted compounding start date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamCompoundingStartDate**

**180.2.6134 UnderlyingPaymentStreamCompoundingStartDate**

UnderlyingPaymentStreamCompoundingStartDate is a subcomponent of the UnderlyingPaymentStreamCompoundingDates component used to specify the start date for compounding.

Name	Mult.	Type	Description
UnderlyingPaymentStreamCompoundingStartDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPaymentStreamCompoundingStartDateRelativeTo	[0..1]	int	
UnderlyingPaymentStreamCompoundingStartDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamCompoundingStartDateOffsetUnit(42944) is specified.
UnderlyingPaymentStreamCompoundingStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamCompoundingStartDateOffsetPeriod(42943) is specified.
UnderlyingPaymentStreamCompoundingStartDateOffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentStreamCompoundingStartDateAdjusted	[0..1]	LocalMktDate	

Used in components: **UnderlyingPaymentStreamCompoundingDates**

**180.2.6135 UnderlyingPaymentStreamCompoundingStartDateOffsetDayType**

Specifies the day type of the relative compounding start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingPaymentStreamCompoundingStartDate**

**180.2.6136 UnderlyingPaymentStreamCompoundingStartDateOffsetPeriod**

Time unit multiplier for the relative compounding start date offset.

Type: **int**

Used in components: **UnderlyingPaymentStreamCompoundingStartDate**

**180.2.6137 UnderlyingPaymentStreamCompoundingStartDateOffsetUnit**

Time unit associated with the relative compounding start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamCompoundingStartDate**

**180.2.6138 UnderlyingPaymentStreamCompoundingStartDateRelativeTo**

Specifies the anchor date when the compounding start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamCompoundingStartDate**

**180.2.6139 UnderlyingPaymentStreamCompoundingStartDateUnadjusted**

The unadjusted compounding start date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamCompoundingStartDate**

**180.2.6140 UnderlyingPaymentStreamCompoundingXIDRef**

Reference to the stream which details the compounding fixed or floating rate.

Type: **XIDREF**

Used in components: **UnderlyingPaymentStream**

**180.2.6141 UnderlyingPaymentStreamContractPrice**

The price per relevant unit for purposes of the calculation of a fixed amount for a dry voyage charter or time charter commodity swap.

Type: **Price**

Used in components: **UnderlyingPaymentStreamFixedRate**

**180.2.6142 UnderlyingPaymentStreamContractPriceCurrency**

Specifies the currency of UnderlyingPaymentStreamContractPrice(41907). Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **UnderlyingPaymentStreamFixedRate**



**180.2.6143 UnderlyingPaymentStreamDayCount**

The day count convention used in the payment stream calculations.

Type: **int**

Allowed values in CouponDayCountCodeSet:

Code	Name	Description
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.

Code	Name	Description
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.

Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: **UnderlyingPaymentStream**

#### 180.2.6144 UnderlyingPaymentStreamDaysAdjustmentIndicator

Indicates whether the contract specifies that the notional should be scaled by the number of days in range divided by the estimate trading days or not. The number of "days in range" refers to the number of returns that contribute to the realized volatility.

Type: **Boolean**

Used in components: **UnderlyingPaymentStreamFloatingRate**

#### **180.2.6145 UnderlyingPaymentStreamDelayIndicator**

Applicable to credit default swaps on mortgage backed securities to specify whether payment delays are applicable to the fixed amount.

Residential mortgage backed securities typically have a payment delay of 5 days between the coupon date of the reference obligation and the payment date of the synthetic swap.

Commercial mortgage backed securities do not typically have a payment delay, with both payment dates (the coupon date of the reference obligation and the payment date of the synthetic swap) being on the 25th of each month.

Type: **Boolean**

Used in components: **UnderlyingPaymentStream**

#### **180.2.6146 UnderlyingPaymentStreamDiscountRate**

Discount rate. The rate is expressed in decimal, e.g. 5% is expressed as 0.05.

Type: **Percentage**

Used in components: **UnderlyingPaymentStream**

#### **180.2.6147 UnderlyingPaymentStreamDiscountRateDayCount**

The day count convention applied to the UnderlyingPaymentStreamDiscountRate(40575).

Type: **int**

Allowed values in CouponDayCountCodeSet:

---

<b>Code</b>	<b>Name</b>	<b>Description</b>
0	OneOne	1/1. If parties specify the Day Count Fraction to be 1/1 then in calculating the applicable amount, 1 is simply input into the calculation as the relevant Day Count Fraction. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (a).

---

Code	Name	Description
1	ThirtyThreeSixtyUS	30/360 (30U/360 or Bond Basis). See also ISO 15022 MICO code 'A001'.
2	ThirtyThreeSixtySIA	30/360 (SIA). A variant of "30/360" - when Date1 and Date2 are both Feb. 28th or 29th convert them to 30th using the same logic in the conversion of 31st to 30th.
3	ThirtyThreeSixtyM	30/360M. Commonly used day count convention for US mortgage backed securities. Feb 28th (or 29th in a leap year) is always considered as a 30th for a start date. As a comparison, in the regular 30/360 day count as used by most US agency and corporate bonds, a start date of Feb 28th (or 29th in a leap year) is still considered as the 28th (or 29th) day of a month of 30 days.
4	ThirtyEThreeSixty	30E/360 (Eurobond Basis). See also ISO 15022 MICO code 'A007'.
5	ThirtyEThreeSixtyISDA	30E/360 (ISDA). Date adjustment rules are: (1) if Date1 is the last day of the month, then change Date1 to 30; (2) if D2 is the last day of the month (unless Date2 is the maturity date and Date2 is in February), then change Date2 to 30. See also 2006 ISDA Definitions, Section 4.16. Day Count Fraction, paragraph (h).
6	ActThreeSixty	Act/360. See also ISO 15022 MICO code 'A004'.
7	ActThreeSixtyFiveFixed	Act/365 (FIXED). See also ISO 15022 MICO code 'A005'.
8	ActActAFB	Act/Act (AFB). See also ISO 15022 MICO code 'A010'.
9	ActActICMA	Act/Act (ICMA). See also ISO 15022 MICO code 'A006'.
10	ActActISMAUltimo	Act/Act (ICMA Ultimo). The Act/Act (ICMA Ultimo) differs from Act/Act (ICMA) method only that it assumes that regular coupons always fall on the last day of the month.
11	ActActISDA	Act/Act (ISDA). See also ISO 15022 MICO code 'A008'.
12	BusTwoFiftyTwo	BUS/252. Used for Brazilian Real swaps, which is based on business days instead of calendar days. The number of business days divided by 252.
13	ThirtyEPlusThreeSixty	30E+/360. Variation on 30E/360. Date adjustment rules: (1) If Date1 falls on the 31st, then change it to the 30th; (2) If Date2 falls on the 31st, then change it to 1 and increase Month2 by one, i.e. next month.
14	ActThreeSixtyFiveL	Act/365L. See also ISO 15022 MICO code 'A009'.
15	NLThreeSixtyFive	NL365. See also ISO 15022 MICO code 'A014'.
16	NLThreeSixty	NL360. This is the same as Act/360, with the exception of leap days (29th February) which are ignored.
17	Act364	Act/364. The actual number of days between Date1 and Date2, divided by 364.

Code	Name	Description
18	ThirtyThreeSixtyFive	30/365. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and a 365-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). See also ISO 15022 MICO code 'A002'.
19	ThirtyActual	30/Actual. Interest is calculated based on a 30-day month in a way similar to the 30/360 (basic rule) and the assumed number of days in a year in a way similar to the Actual/Actual (ICMA). Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). The assumed number of days in a year is computed as the actual number of days in the coupon period multiplied by the number of interest payments in the year. See also ISO 15022 MICO code 'A003'.
20	ThirtyThreeSixtyICMA	30/360 (ICMA or basis rule). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30 calendar day of the same month, except for February. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be a 28 (or 29). It is the most commonly used 30/360 method for non-US straight and convertible bonds issued before 1 January 1999. See also ISO 15022 MICO code 'A011'.

Code	Name	Description
21	ThirtyETwoThreeSixty	30E2/360 (Eurobond basis model two). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month, except for the last day of February whose day of the month value shall be adapted to the value of the first day of the interest period if the latter is higher and if the period is one of a regular schedule. This means that a 31 is assumed to be a 30 and the 28 February of a non-leap year is assumed to be equivalent to a 29 February when the first day of the interest period is a 29, or to a 30 February when the first day of the interest period is a 30 or a 31. The 29 February of a leap year is assumed to be equivalent to a 30 February when the first day of the interest period is a 30 or a 31. Similarly, if the coupon period starts on the last day of February, it is assumed to produce only one day of interest in February as if it was starting on a 30 February when the end of the period is a 30 or a 31, or two days of interest in February when the end of the period is a 29, or three days of interest in February when it is the 28 February of a non-leap year and the end of the period is before the 29. See also ISO 15022 MICO code 'A012'.
22	ThirtyEThreeThreeSixty	30E3/360 (Eurobond basis model three). Interest is calculated based on a 30-day month and a 360-day year. Accrued interest to a value date on the last day of a month shall be the same as to the 30th calendar day of the same month. This means that a 31 is assumed to be a 30 and the 28 February (or 29 February for a leap year) is assumed to be equivalent to a 30 February. It is a variation of the 30E/360 (or Eurobond basis) method where the last day of February is always assumed to be a 30, even if it is the last day of the maturity coupon period. See also ISO 15022 MICO code 'A013'.
99	Other	Other. For other day count method. See also ISO 15022 MICO code 'OTHR'.

Used in components: **UnderlyingPaymentStream**

### 180.2.6148 UnderlyingPaymentStreamDiscountType

The method of calculating discounted payment amounts

Type: **int**

Allowed values in PaymentStreamDiscountTypeCodeSet:

Code	Name	Description
0	Standard	Standard
1	FRA	Forward Rate Agreement (FRA)

Used in components: [UnderlyingPaymentStream](#)

### 180.2.6149 UnderlyingPaymentStreamFinalPricePaymentDateAdjusted

The adjusted final price payment date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingPaymentStreamFinalPricePaymentDate](#)

### 180.2.6150 UnderlyingPaymentStreamFinalPricePaymentDate

UnderlyingPaymentStreamFinalPricePaymentDate is a subcomponent of the UnderlyingPaymentStreamPaymentDates component used to specify the final price payment date, e.g. for an equity return swap.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStreamFinalPrice-PaymentDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingPaymentStreamFinalPrice-PaymentDateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingPaymentStreamFinalPrice-PaymentDateOffsetPeriod</a>	[0..1]	int	Conditionally required when UnderlyingPaymentStreamFinalPricePaymentDateOffsetUnit(42952) is specified.
<a href="#">UnderlyingPaymentStreamFinalPrice-PaymentDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamFinalPricePaymentDateOffsetPeriod(42951) is specified.
<a href="#">UnderlyingPaymentStreamFinalPrice-PaymentDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingPaymentStreamFinalPrice-PaymentDateAdjusted</a>	[0..1]	LocalMktDate	

Used in components: [UnderlyingPaymentStreamPaymentDates](#)



**180.2.6151 UnderlyingPaymentStreamFinalPricePaymentDateOffsetDayType**

Specifies the day type of the relative final price payment date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingPaymentStreamFinalPricePaymentDate**

**180.2.6152 UnderlyingPaymentStreamFinalPricePaymentDateOffsetPeriod**

Time unit multiplier for the relative final price payment date offset.

Type: **int**

Used in components: **UnderlyingPaymentStreamFinalPricePaymentDate**

**180.2.6153 UnderlyingPaymentStreamFinalPricePaymentDateOffsetUnit**

Time unit associated with the relative final price payment date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamFinalPricePaymentDate**

**180.2.6154 UnderlyingPaymentStreamFinalPricePaymentDateRelativeTo**

Specifies the anchor date when the final price payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamFinalPricePaymentDate**

**180.2.6155 UnderlyingPaymentStreamFinalPricePaymentDateUnadjusted**

The unadjusted final price payment date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamFinalPricePaymentDate**

**180.2.6156 UnderlyingPaymentStreamFinalPrincipalExchangeIndicator**

Indicates whether there is a final exchange of principal on the termination date.

Type: **Boolean**

Used in components: **UnderlyingPaymentStream**

**180.2.6157 UnderlyingPaymentStreamFinalRate**

The floating rate determined at the final reset. The rate is expressed in decimal form, e.g. 5% is represented as 0.05.

Type: **Percentage**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6158 UnderlyingPaymentStreamFinalRatePrecision**

Specifies the rounding precision in terms of a number of decimal places. Note how a percentage rate rounding of 5 decimal places is expressed as a rounding precision of 7.

Type: **int**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6159 UnderlyingPaymentStreamFinalRateRoundingDirection**

Specifies the rounding direction.

Type: **char**

Allowed values in RoundingDirectionCodeSet:

Code	Name	Description
0	RoundToNearest	Round to nearest
1	RoundDown	Round down
2	RoundUp	Round up

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6160 UnderlyingPaymentStreamFirstObservationDateAdjusted**

The adjusted initial price observation date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6161 UnderlyingPaymentStreamFirstObservationDateOffsetDayType**

Specifies the day type of the initial price observation date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6162 UnderlyingPaymentStreamFirstObservationDateOffsetPeriod**

Time unit multiplier for the relative first observation date offset.

Type: **int**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6163 UnderlyingPaymentStreamFirstObservationDateOffsetUnit**

Time unit associated with the relative first observation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6164 UnderlyingPaymentStreamFirstObservationDateRelativeTo**

Specifies the anchor date when the initial price observation date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6165 UnderlyingPaymentStreamFirstObservationDateUnadjusted**

The unadjusted initial price observation date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6166 UnderlyingPaymentStreamFirstPaymentDateUnadjusted**

The unadjusted first payment date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamPaymentDates**

**180.2.6167 UnderlyingPaymentStreamFixedAmount**

The underlying payment stream's fixed payment amount. In CDS an alternative to UnderlyingPaymentStreamRate(40615).

Type: **Amt**

Used in components: **UnderlyingPaymentStreamFixedRate**

**180.2.6168 UnderlyingPaymentStreamFixedAmountUnitOfMeasure**

Fixed payment amount unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.

Code	Name	Description
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces

Code	Name	Description
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard

Code	Name	Description
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [UnderlyingPaymentStreamFixedRate](#)

### 180.2.6169 UnderlyingPaymentStreamFixedRate

UnderlyingPaymentStreamFixedRate is a subcomponent of the UnderlyingPaymentStream component used to report the fixed rate or fixed payment amount of the stream.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStreamRate</a>	[0..1]	Percentage	Mutually exclusive with UnderlyingPaymentStreamFixedAmount(40616).
<a href="#">UnderlyingPaymentStream-FixedAmount</a>	[0..1]	Amt	Mutually exclusive with UnderlyingPaymentStreamRate(40615).
<a href="#">UnderlyingPaymentStreamRateOrAmountCurrency</a>	[0..1]	Currency	
<a href="#">UnderlyingPaymentStream-FixedAmountUnitOfMeasure</a>	[0..1]	CodeSet	
<a href="#">UnderlyingPaymentStreamTotal-FixedAmount</a>	[0..1]	Amt	
<a href="#">UnderlyingPaymentStreamFutureValueNotional</a>	[0..1]	Amt	
<a href="#">UnderlyingPaymentStreamFutureValueDateAdjusted</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingPaymentStreamWorldScaleRate</a>	[0..1]	float	
<a href="#">UnderlyingPaymentStreamContract-Price</a>	[0..1]	Price	
<a href="#">UnderlyingPaymentStreamContract-PriceCurrency</a>	[0..1]	Currency	

Used in components: [UnderlyingPaymentStream](#)



**180.2.6170 UnderlyingPaymentStreamFixingDate**

The fixing date. Type of date is specified in UnderlyingPaymentStreamFixingDateType(42957).

Type: **LocalMktDate**

Used in groups: **UnderlyingPaymentStreamFixingDateGrp**

**180.2.6171 UnderlyingPaymentStreamFixingDateAdjusted**

The adjusted fixing date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6172 UnderlyingPaymentStreamFixingDateBusinessCenter**

The business center calendar used to adjust the payment stream's fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingPaymentStreamFixingDateBusinessCenterGrp**

**180.2.6173 UnderlyingPaymentStreamFixingDateBusinessCenterGrp**

UnderlyingPaymentStreamFixingDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingPaymentStreamResetDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Name	Mult.	Type	Description
<b>NoUnderlyingPaymentStreamFixing- DateBusinessCenters</b>	[1..1]	NumInGroup	
<b>UnderlyingPaymentStreamFixingDate- BusinessCenter</b>	[0..1]	String	Required if NoUnderlyingPaymentStreamFixing- DateBusinessCenters(40972) > 0.

Used in components: **UnderlyingPaymentStreamResetDates**

### 180.2.6174 UnderlyingPaymentStreamFixingDateBusinessDayConvention

The business day convention used to adjust the payment stream's fixing date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **UnderlyingPaymentStreamResetDates**

### 180.2.6175 UnderlyingPaymentStreamFixingDateGrp

UnderlyingPaymentStreamFixingDateGrp is a subcomponent of the UnderlyingPaymentStreamResetDates component used to specify predetermined fixing dates.

Name	Mult.	Type	Description
<b>NoUnderlyingPaymentStreamFixingDates</b>	[1..1]	NumInGroup	
<b>UnderlyingPaymentStreamFixingDate</b>	[0..1]	LocalMktDate	Required if NoUnderlyingPaymentStreamFixingDates(42955) > 0.
<b>UnderlyingPaymentStreamFixingDate-Type</b>	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6176 UnderlyingPaymentStreamFixingDateOffsetDayType**

Specifies the day type of the relative fixing date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6177 UnderlyingPaymentStreamFixingDateOffsetPeriod**

Time unit multiplier for the relative fixing date offset.

Type: **int**

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6178 UnderlyingPaymentStreamFixingDateOffsetUnit**

Time unit associated with the relative fixing date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6179 UnderlyingPaymentStreamFixingDateRelativeTo**

Specifies the anchor date when the fixing date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6180 UnderlyingPaymentStreamFixingDateType**

Specifies the type of fixing date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **UnderlyingPaymentStreamFixingDateGrp**

**180.2.6181 UnderlyingPaymentStreamFlatRateAmount**

Specifies the actual monetary value of the flat rate when UnderlyingPaymentStreamFlatRateIndicator(41897) = 'Y'.

Type: **Amt**

Used in components: **UnderlyingPaymentStream**

**180.2.6182 UnderlyingPaymentStreamFlatRateCurrency**

Specifies the currency of the actual flat rate. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **UnderlyingPaymentStream**

**180.2.6183 UnderlyingPaymentStreamFlatRateIndicator**

When this element is specified and set to 'Y', the Flat Rate is the New Worldwide Tanker Nominal Freight Scale for the Freight Index Route taken at the Trade Date of the transaction "Fixed". If 'N' it is taken on each Pricing Date "Floating".

Type: **Boolean**

Used in components: **UnderlyingPaymentStream**

**180.2.6184 UnderlyingPaymentStreamFloatingRate**

UnderlyingPaymentStreamFloatingRate is a subcomponent of the UnderlyingPaymentStream component used to report the floating rate attributes of the stream.

Name	Mult.	Type	Description
UnderlyingPaymentStreamRateIndex	[0..1]	String	
UnderlyingPaymentStreamRateIndex-Source	[0..1]	CodeSet	
UnderlyingPaymentStreamRateIndexID	[0..1]	String	Conditionally required when UnderlyingPaymentStreamRateIndexIDSource(43093) is specified.
UnderlyingPaymentStreamRateIndexIDSource	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamRateIndexID(43092) is specified.
UnderlyingPaymentStreamRateIndex-CurveUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamRateIndexCurvePeriod(40623) is specified.
UnderlyingPaymentStreamRateIndex-CurvePeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamRateIndexCurveUnit(40622) is specified.
UnderlyingPaymentStreamRateIndex2	[0..1]	String	
UnderlyingPaymentStreamRateIndex2Source	[0..1]	CodeSet	
UnderlyingPaymentStreamRateIndex2ID	[0..1]	String	Conditionally required when UnderlyingPaymentStreamRateIndex2IDSource(43123) is specified.
UnderlyingPaymentStreamRateIndex2IDSource	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamRateIndex2ID(43122) is specified.

Name	Mult.	Type	Description
UnderlyingPaymentStreamRateIndex2CurveUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamRateIndex2CurvePeriod(41912) is specified.
UnderlyingPaymentStreamRateIndex2CurvePeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamRateIndex2CurveUnit(41911) is specified.
UnderlyingPaymentStreamRateIndexLocation	[0..1]	String	
UnderlyingPaymentStreamRateIndexLevel	[0..1]	Qty	
UnderlyingPaymentStreamRateIndexUnitOfMeasure	[0..1]	CodeSet	
UnderlyingPaymentStreamSettleLevel	[0..1]	CodeSet	
UnderlyingPaymentStreamReferenceLevel	[0..1]	Qty	
UnderlyingPaymentStreamReferenceLevelUnitOfMeasure	[0..1]	CodeSet	
UnderlyingPaymentStreamReferenceLevelEqualsZeroIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamRateMultiplier	[0..1]	float	
UnderlyingPaymentStreamRateSpread	[0..1]	PriceOffset	
UnderlyingPaymentStreamRateSpreadCurrency	[0..1]	Currency	
UnderlyingPaymentStreamRateSpreadUnitOfMeasure	[0..1]	CodeSet	
UnderlyingPaymentStreamRateConversionFactor	[0..1]	float	
UnderlyingPaymentStreamRateSpreadType	[0..1]	CodeSet	
UnderlyingPaymentStreamRateSpreadPositionType	[0..1]	CodeSet	
UnderlyingPaymentStreamRateTreatment	[0..1]	CodeSet	
UnderlyingPaymentStreamCapRate	[0..1]	Percentage	
UnderlyingPaymentStreamCapRateBuySide	[0..1]	CodeSet	
UnderlyingPaymentStreamCapRateSellSide	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingPaymentStreamFloorRate	[0..1]	Percentage	
UnderlyingPaymentStreamFloorRate-BuySide	[0..1]	CodeSet	
UnderlyingPaymentStreamFloorRate-SellSide	[0..1]	CodeSet	
UnderlyingPaymentStreamInitialRate	[0..1]	Percentage	
UnderlyingPaymentStreamLastResetRate	[0..1]	Percentage	
UnderlyingPaymentStreamFinalRate	[0..1]	Percentage	
UnderlyingPaymentStreamFinalRateRoundingDirection	[0..1]	CodeSet	
UnderlyingPaymentStreamFinalRatePrecision	[0..1]	int	
UnderlyingPaymentStreamAveragingMethod	[0..1]	CodeSet	
UnderlyingPaymentStreamNegativeRateTreatment	[0..1]	CodeSet	
UnderlyingPaymentStreamCalculationLagPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamCalculationLagUnit(41927) is specified.
UnderlyingPaymentStreamCalculationLagUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamCalculationLagPeriod(41926) is specified.
UnderlyingPaymentStreamFirstObservationDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPaymentStreamFirstObservationDateRelativeTo	[0..1]	int	
UnderlyingPaymentStreamFirstObservationDateOffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentStreamFirstObservationDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamFirstObservationOffsetUnit(41929) is specified.
UnderlyingPaymentStreamFirstObservationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamFirstObservationOffsetPeriod(41928) is specified.
UnderlyingPaymentStreamFirstObservationDateAdjusted	[0..1]	LocalMktDate	
UnderlyingPaymentStreamPricingDayType	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingPaymentStreamPricingDay-Distribution	[0..1]	CodeSet	
UnderlyingPaymentStreamPricingDay-Count	[0..1]	int	
UnderlyingPaymentStreamPricing-BusinessCalendar	[0..1]	String	
UnderlyingPaymentStreamPricing-BusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of pricing dates.
UnderlyingPaymentStreamPricing-BusinessCenterGrp	[0..*]	Group	
UnderlyingPaymentStreamPricingDay-Grp	[0..*]	Group	
UnderlyingPaymentStreamPricing-DateGrp	[0..*]	Group	
UnderlyingPaymentStreamInflation-LagPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamInflationLagUnit(40640) is specified.
UnderlyingPaymentStreamInflationLagUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamInflationLagPeriod(40639) is specified.
UnderlyingPaymentStreamInflation-LagDayType	[0..1]	CodeSet	
UnderlyingPaymentStreamInflationInterpolationMethod	[0..1]	CodeSet	
UnderlyingPaymentStreamInflationIndexSource	[0..1]	CodeSet	
UnderlyingPaymentStreamInflation-PublicationSource	[0..1]	String	
UnderlyingPaymentStreamInflationInitialIndexLevel	[0..1]	float	
UnderlyingPaymentStreamInflation-FallbackBondApplicable	[0..1]	Boolean	
UnderlyingPaymentStreamFRADiscounting	[0..1]	CodeSet	
UnderlyingPaymentStreamUnderlier-RefID	[0..1]	String	
UnderlyingPaymentStreamFormula	[0..1]	Component	



Name	Mult.	Type	Description
UnderlyingDividendConditions	[0..1]	Component	
UnderlyingReturnRateNotionalReset	[0..1]	Boolean	
UnderlyingReturnRateGrp	[0..*]	Group	
UnderlyingPaymentStreamLinkInitialLevel	[0..1]	Price	
UnderlyingPaymentStreamLinkClosingLevelIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamLinkExpiringLevelIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamLinkEstimatedTradingDays	[0..1]	int	
UnderlyingPaymentStreamLinkStrikePrice	[0..1]	Price	
UnderlyingPaymentStreamLinkStrikePriceType	[0..1]	CodeSet	
UnderlyingPaymentStreamLinkMaximumBoundary	[0..1]	float	
UnderlyingPaymentStreamLinkMinimumBoundary	[0..1]	float	
UnderlyingPaymentStreamLinkNumberOfDataSeries	[0..1]	int	
UnderlyingPaymentStreamVarianceUnadjustedCap	[0..1]	float	
UnderlyingPaymentStreamRealizedVarianceMethod	[0..1]	CodeSet	
UnderlyingPaymentStreamDaysAdjustmentIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamNearestExchangeContractRefID	[0..1]	String	
UnderlyingPaymentStreamVegaNotionalAmount	[0..1]	float	

Used in components: **UnderlyingPaymentStream**

**180.2.6185 UnderlyingPaymentStreamFloorRate**

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A floor rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6186 UnderlyingPaymentStreamFloorRateBuySide**

Reference to the buyer of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6187 UnderlyingPaymentStreamFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6188 UnderlyingPaymentStreamFormula**

Contains an XML representation of the formula. Defined for flexibility in choice of language (MathML, OpenMath or text).

Type: **XMLData**

Used in groups: **UnderlyingPaymentStreamFormulaMathGrp**

**180.2.6189 UnderlyingPaymentStreamFormula**

UnderlyingPaymentStreamFormula is a subcomponent of the UnderlyingPaymentStreamFloatingRate component used to report the parameters for determining the floating rate of the stream e.g. for equity swaps.

Name	Mult.	Type	Description
UnderlyingPaymentStreamFormulaCurrency	[0..1]	Currency	
UnderlyingPaymentStreamFormulaCurrencyDeterminationMethod	[0..1]	String	
UnderlyingPaymentStreamFormulaReferenceAmount	[0..1]	int	
UnderlyingPaymentStreamFormulaMathGrp	[0..*]	Group	
UnderlyingPaymentStreamFormulaImage	[0..1]	Component	

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6190 UnderlyingPaymentStreamFormulaCurrency**

The currency in which the formula amount is denominated. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **UnderlyingPaymentStreamFormula**

**180.2.6191 UnderlyingPaymentStreamFormulaCurrencyDeterminationMethod**

Specifies the method according to which the formula amount currency is determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in components: **UnderlyingPaymentStreamFormula**

#### **180.2.6192 UnderlyingPaymentStreamFormulaDesc**

A description of the math formula in UnderlyingPaymentStreamFormula(42982).

Type: **String**

Used in groups: **UnderlyingPaymentStreamFormulaMathGrp**

#### **180.2.6193 UnderlyingPaymentStreamFormulImage**

Image of the formula image when represented through an encoded clip in base64Binary.

Type: **data**

Used in components: **UnderlyingPaymentStreamFormulImage**

#### **180.2.6194 UnderlyingPaymentStreamFormulImage**

UnderlyingPaymentStreamFormulImage is a subcomponent of the UnderlyingPaymentStreamFormula component used to include a base64Binary-encoded image clip of the formula.

Name	Mult.	Type	Description
<b>UnderlyingPaymentStreamFormulImageLength</b>	[0..1]	Length	Conditionally required when UnderlyingPaymentStreamFormulImage(42948) is specified.
<b>UnderlyingPaymentStreamFormulImage</b>	[0..1]	data	Conditionally required when UnderlyingPaymentStreamFormulImageLength(42947) is specified.

Used in components: **UnderlyingPaymentStreamFormula**

#### **180.2.6195 UnderlyingPaymentStreamFormulImageLength**

Length in bytes of the UnderlyingPaymentStreamFormulImage(42948) field.

Type: **Length**

Used in components: **UnderlyingPaymentStreamFormulaImage**

### **180.2.6196 UnderlyingPaymentStreamFormulaLength**

Byte length of encoded (non-ASCII characters) UnderlyingPaymentStreamFormula(42982) field.

Type: **Length**

Used in groups: **UnderlyingPaymentStreamFormulaMathGrp**

### **180.2.6197 UnderlyingPaymentStreamFormulaMathGrp**

UnderlyingPaymentStreamFormulaMathGrp is a repeating subcomponent within the UnderlyingPaymentStreamFormula component. It is used to specify the set of formulas, sub-formulas and descriptions from which the rate is derived.

Name	Mult.	Type	Description
NoUnderlyingPaymentStreamFormulas	[1..1]	NumInGroup	
UnderlyingPaymentStreamFormulaLength	[0..1]	Length	Required if NoUnderlyingPaymentStreamFormulas(42981) > 0
UnderlyingPaymentStreamFormula	[0..1]	XMLData	Required if NoUnderlyingPaymentStreamFormulas(42981) > 0.
UnderlyingPaymentStreamFormulaDesc	[0..1]	String	

Used in components: **UnderlyingPaymentStreamFormula**

### **180.2.6198 UnderlyingPaymentStreamFormulaReferenceAmount**

Specifies the reference amount when this term either corresponds to the standard ISDA Definition (either the 2002 Equity Definition for the Equity Amount, or the 2000 Definition for the Interest Amount), or refers to a term defined elsewhere in the swap document.

See [http://www.fixtradingcommunity.org/codelists#Payment\\_Amount\\_Relative\\_To](http://www.fixtradingcommunity.org/codelists#Payment_Amount_Relative_To) for code list of reference amounts.

Type: **int**

Used in components: **UnderlyingPaymentStreamFormula**

### **180.2.6199 UnderlyingPaymentStreamFRADiscounting**

The method of Forward Rate Agreement (FRA) discounting, if any, that will apply.

Type: **int**

Allowed values in PaymentStreamFRADiscountingCodeSet:

Code	Name	Description
0	None	None
1	ISDA	International Swaps and Derivatives Association (ISDA)
2	AFMA	Australian Financial Markets Association (AFMA)

Used in components: **UnderlyingPaymentStreamFloatingRate**

### **180.2.6200 UnderlyingPaymentStreamFutureValueDateAdjusted**

The adjusted value date of the future value amount.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamFixedRate**

### **180.2.6201 UnderlyingPaymentStreamFutureValueNotional**

The future value notional is normally only required for certain non-deliverable interest rate swaps (e.g. Brazilian Real (BRL) vs. CETIP Interbank Deposit Rate (CDI)). The value is calculated as follows: Future Value Notional = Notional Amount \* (1 + Fixed Rate) ^ (Fixed Rate Day Count Fraction). The currency is the same as the stream notional.

Type: **Amt**

Used in components: **UnderlyingPaymentStreamFixedRate**

**180.2.6202 UnderlyingPaymentStreamInflationFallbackBondApplicable**

Indicates whether a fallback bond as defined in the 2006 ISDA Inflation Derivatives Definitions, sections 1.3 and 1.8, is applicable or not. If not specified, the default value is "Y" (True/Yes).

Type: **Boolean**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6203 UnderlyingPaymentStreamInflationIndexSource**

The inflation index reference source.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6204 UnderlyingPaymentStreamInflationInitialIndexLevel**

Initial known index level for the first calculation period.

Type: **float**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6205 UnderlyingPaymentStreamInflationInterpolationMethod**

The method used when calculating the Inflation Index Level from multiple points - the most common is Linear.

Type: **int**

Allowed values in PaymentStreamInflationInterpolationMethodCodeSet:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6206 UnderlyingPaymentStreamInflationLagDayType**

The inflation lag period day type.

Type: [int](#)

Allowed values in PaymentStreamInflationLagDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6207 UnderlyingPaymentStreamInflationLagPeriod**

Time unit multiplier for the inflation lag period. The lag period is the offsetting period from the payment date which determines the reference period for which the inflation index is observed.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6208 UnderlyingPaymentStreamInflationLagUnit**

Time unit associated with the inflation lag period.

Type: [String](#)



Allowed values in PaymentStreamInflationLagUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6209 UnderlyingPaymentStreamInflationPublicationSource**

The current main publication source such as relevant web site or a government body.

Type: [String](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6210 UnderlyingPaymentStreamInitialFixingDateAdjusted**

The adjusted initial fixing date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingPaymentStreamResetDates](#)

#### **180.2.6211 UnderlyingPaymentStreamInitialFixingDateBusinessCenter**

The business center calendar used to adjust the payment stream's initial fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingPaymentStreamInitialFixingDateBusinessCenterGrp](#)

#### **180.2.6212 UnderlyingPaymentStreamInitialFixingDateBusinessCenterGrp**

[UnderlyingPaymentStreamInitialFixingDateBusinessCenterGrp](#) is a repeating subcomponent within the [UnderlyingPaymentStreamResetDates](#) component. It is used to specify the set of business centers

whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Name	Mult.	Type	Description
NoUnderlyingPaymentStreamInitialFixingDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingPaymentStreamInitialFixingDateBusinessCenter	[0..1]	String	Required if NoUnderlyingPaymentStreamInitialFixingDateBusinessCenters(40971) > 0.

Used in components: [UnderlyingPaymentStreamResetDates](#)

### 180.2.6213 UnderlyingPaymentStreamInitialFixingDateBusinessDayConvention

The business day convention used to adjust the payment stream's initial fixing date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingPaymentStreamResetDates](#)

### 180.2.6214 UnderlyingPaymentStreamInitialFixingDateOffsetDayType

Specifies the day type of the relative initial fixing date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingPaymentStreamResetDates](#)

#### **180.2.6215 UnderlyingPaymentStreamInitialFixingDateOffsetPeriod**

Time unit multiplier for the relative initial fixing date offset.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamResetDates](#)

#### **180.2.6216 UnderlyingPaymentStreamInitialFixingDateOffsetUnit**

Time unit associated with the relative initial fixing date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingPaymentStreamResetDates](#)

**180.2.6217 UnderlyingPaymentStreamInitialFixingDateRelativeTo**

Specifies the anchor date when the initial fixing date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6218 UnderlyingPaymentStreamInitialPrincipalExchangeIndicator**

Indicates whether there is an initial exchange of principal on the effective date.

Type: **Boolean**

Used in components: **UnderlyingPaymentStream**

**180.2.6219 UnderlyingPaymentStreamInitialRate**

The initial floating rate reset agreed between the principal parties involved in the trade. This is assumed to be the first required reset rate for the first regular calculation period. It should only be included when the rate is not equal to the rate published on the source implied by the floating rate index. An initial rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6220 UnderlyingPaymentStreamInterimPrincipalExchangeIndicator**

Indicates whether there are intermediate or interim exchanges of principal during the term of the swap.

Type: **Boolean**

Used in components: **UnderlyingPaymentStream**

**180.2.6221 UnderlyingPaymentStreamInterpolationMethod**

The method used when calculating the index rate from multiple points on the curve. The most common is linear method.

Type: **int**

Allowed values in PaymentStreamInflationInterpolationMethodCodeSet:

Code	Name	Description
0	None	None
1	LinearZeroYield	Linear zero yield

Used in components: **UnderlyingPaymentStream**

### **180.2.6222 UnderlyingPaymentStreamInterpolationPeriod**

Defines applicable periods for interpolation.

Type: **int**

Allowed values in PaymentStreamInterpolationPeriodCodeSet:

Code	Name	Description
0	Initial	Initial. Interpolation is applicable to the initial period only.
1	InitialAndFinal	Initial and final. Interpolation is applicable to the initial and final periods only.
2	Final	Final. Interpolation is applicable to the final period only.
3	AnyPeriod	Any period. Interpolation is applicable to any non-standard period.

Used in components: **UnderlyingPaymentStream**

### **180.2.6223 UnderlyingPaymentStreamLastRegularPaymentDateUnadjusted**

The unadjusted last regular payment date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStreamPaymentDates**

**180.2.6224 UnderlyingPaymentStreamLastResetRate**

The floating rate determined at the most recent reset. The rate is expressed in decimal form, e.g. 5% is represented as 0.05.

Type: **Percentage**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6225 UnderlyingPaymentStreamLinkClosingLevelIndicator**

Indicates whether the correlation or variance swap contract will ("Y") strike off the closing level of the default exchange traded contract or not.

Type: **Boolean**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6226 UnderlyingPaymentStreamLinkEstimatedTradingDays**

The expected number of trading days in the variance or correlation swap stream.

Type: **int**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6227 UnderlyingPaymentStreamLinkExpiringLevelIndicator**

Indicates whether the correlation or variance swap contract will ("Y") strike off the expiring level of the default exchange traded contract or not.

Type: **Boolean**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6228 UnderlyingPaymentStreamLinkInitialLevel**

Price level at which the correlation or variance swap contract will strike.

Type: **Price**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6229 UnderlyingPaymentStreamLinkMaximumBoundary**

Specifies the maximum or upper boundary for variance or strike determination.

For a variation swap stream all observations above this price level will be excluded from the variance calculation.

For a correlation swap stream the maximum boundary is a percentage of the strike price.

Type: **float**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6230 UnderlyingPaymentStreamLinkMinimumBoundary**

Specifies the minimum or lower boundary for variance or strike determination.

For a variation swap stream all observations below this price level will be excluded from the variance calculation.

For a correlation swap stream the minimum boundary is a percentage of the strike price.

Type: **float**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6231 UnderlyingPaymentStreamLinkNumberOfDataSeries**

Number of data series for a correlation swap. Normal market practice is that correlation data sets are drawn from geographic market areas, such as America, Europe and Asia Pacific. Each of these geographic areas will have its own data series to avoid contagion.

Type: **int**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6232 UnderlyingPaymentStreamLinkStrikePrice**

The strike price of a correlation or variance swap stream.

Type: **Price**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6233 UnderlyingPaymentStreamLinkStrikePriceType**

For a variance swap specifies how UnderlyingPaymentStreamLinkStrikePrice(42968) is expressed.

Type: **int**

Allowed values in PaymentStreamLinkStrikePriceTypeCodeSet:

Code	Name	Description
0	Volatility	Volatility
1	Variance	Variance

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6234 UnderlyingPaymentStreamMarketRate**

Used only for credit index trade. This contains the credit spread ("fair value") at which the trade was executed. The market rate varies over the life of the index depending on market conditions. This is the price of the index as quoted by trading desks.

Type: **int**

Used in components: **UnderlyingPaymentStream**

**180.2.6235 UnderlyingPaymentStreamMasterAgreementPaymentDatesIndicator**

When set to 'Y', it indicates that payment dates are specified in the relevant master agreement.

Type: **Boolean**

Used in components: **UnderlyingPaymentStreamPaymentDates**

**180.2.6236 UnderlyingPaymentStreamMaximumPaymentAmount**

Specifies the limit on the total payment amount.

Type: **Amt**

Used in components: **UnderlyingPaymentStream**



**180.2.6237 UnderlyingPaymentStreamMaximumPaymentCurrency**

Specifies the currency of total payment amount limit. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **UnderlyingPaymentStream**

**180.2.6238 UnderlyingPaymentStreamMaximumTransactionAmount**

Specifies the limit on the payment amount that goes out in any particular calculation period.

Type: **Amt**

Used in components: **UnderlyingPaymentStream**

**180.2.6239 UnderlyingPaymentStreamMaximumTransactionCurrency**

Specifies the currency of the period payment amount limit. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **UnderlyingPaymentStream**

**180.2.6240 UnderlyingPaymentStreamNearestExchangeContractRefID**

References a contract listed on an exchange through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: **String**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6241 UnderlyingPaymentStreamNegativeRateTreatment**

The specification of any provisions for calculating payment obligations when a floating rate is negative (either due to a quoted negative floating rate or by operation of a spread that is subtracted from the floating rate).

Type: **int**

Allowed values in PaymentStreamNegativeRateTreatmentCodeSet:

Code	Name	Description
0	ZeroInterestRateMethod	Zero interest rate method
1	NegativeInterestRateMethod	Negative interest rate method

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### 180.2.6242 UnderlyingPaymentStreamNonDeliverableFixingDateGrp

UnderlyingPaymentStreamNonDeliverableFixingDate is a subcomponent of the UnderlyingPaymentStreamNonDeliverableSettlTerms component used to specify predetermined fixing dates.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingNonDeliverableFixingDates</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingNonDeliverableFixingDate</a>	[0..1]	LocalMktDate	Required if <a href="#">NoUnderlyingNonDeliverableFixingDates(40656)</a> > 0.
<a href="#">UnderlyingNonDeliverableFixingDate-Type</a>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [UnderlyingPaymentStreamNonDeliverableSettlTerms](#)

### 180.2.6243 UnderlyingPaymentStreamNonDeliverableFixingDatesBizDayConvention

The business day convention used to adjust the payment stream's fixing date for the non-deliverable terms. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)

Code	Name	Description
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingPaymentStreamNonDeliverableSettlTerms](#)

#### 180.2.6244 UnderlyingPaymentStreamNonDeliverableFixingDatesBusinessCenter

The business center calendar used to adjust the payment stream's fixing date for the non-deliverable terms, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp](#)

#### 180.2.6245 UnderlyingPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp

[UnderlyingPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp](#) is a repeating subcomponent within the [UnderlyingPaymentStreamNonDeliverableSettlTerms](#) component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the [UnderlyingDateAdjustment](#) component in the [UnderlyingInstrument](#) component.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingPaymentStreamNonDeliverableFixingDatesBizCenters</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingPaymentStreamNonDeliverableFixingDatesBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoUnderlyingPaymentStreamNonDeliverableFixingDatesBizCenters</a> (40968) > 0.

Used in components: [UnderlyingPaymentStreamNonDeliverableSettlTerms](#)

**180.2.6246 UnderlyingPaymentStreamNonDeliverableFixingDatesOffsetDayType**

Specifies the day type of the relative non-deliverable fixing date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingPaymentStreamNonDeliverableSettlTerms**

**180.2.6247 UnderlyingPaymentStreamNonDeliverableFixingDatesOffsetPeriod**

Time unit multiplier for the relative non-deliverable fixing date offset.

Type: **int**

Used in components: **UnderlyingPaymentStreamNonDeliverableSettlTerms**

**180.2.6248 UnderlyingPaymentStreamNonDeliverableFixingDatesOffsetUnit**

Time unit associated with the relative non-deliverable fixing date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamNonDeliverableSettlTerms**

**180.2.6249 UnderlyingPaymentStreamNonDeliverableFixingDatesRelativeTo**

Specifies the anchor date when the non-deliverable fixing dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamNonDeliverableSettlTerms**

**180.2.6250 UnderlyingPaymentStreamNonDeliverableRefCurrency**

The non-deliverable settlement reference currency. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **UnderlyingPaymentStreamNonDeliverableSettlTerms**

**180.2.6251 UnderlyingPaymentStreamNonDeliverableSettlRateSource**

Identifies the source of rate information.

Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in components: **UnderlyingPaymentStreamNonDeliverableSettlRateSource**

**180.2.6252 UnderlyingPaymentStreamNonDeliverableSettlRateSource**

UnderlyingPaymentStreamNonDeliverableSettlRateSource is a subcomponent of the UnderlyingPaymentStreamNonDeliverableSettlTerms component used to specify the rate source in the event of payment non-delivery.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStreamNonDeliverableSettlRateSource</a>	[0..1]	CodeSet	
<a href="#">UnderlyingPaymentStreamNonDeliverableSettlReferencePage</a>	[0..1]	String	Conditionally required when UnderlyingPaymentStreamNonDeliverableSettlRateSource(40661) = 3 (ISDA Settlement Rate Option) or 99 (Other).

Used in components: [UnderlyingPaymentStreamNonDeliverableSettlTerms](#)

### 180.2.6253 UnderlyingPaymentStreamNonDeliverableSettlReferencePage

Identifies the reference "page" from the rate source.

When UnderlyingPaymentStreamNonDeliverableSettlRateSource(40661) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: [String](#)

Used in components: [UnderlyingPaymentStreamNonDeliverableSettlRateSource](#)

### 180.2.6254 UnderlyingPaymentStreamNonDeliverableSettlTerms

UnderlyingPaymentStreamNonDeliverableSettlTerms is a subcomponent of the UnderlyingPaymentStream component used to specify the non-deliverable settlement terms of the stream.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStreamNonDeliverableRefCurrency</a>	[0..1]	Currency	
<a href="#">UnderlyingPaymentStreamNonDeliverableFixingDatesBizDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's non-deliverable settlement terms.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStreamNonDeliverableFixingDatesBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's non-deliverable settlement terms.
<a href="#">UnderlyingPaymentStreamNonDeliverableFixingDatesRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingPaymentStreamNonDeliverableFixingDatesOffsetPeriod</a>	[0..1]	int	Conditionally required when UnderlyingPaymentStreamNonDeliverableFixingDatesOffsetUnit(40653) is specified.
<a href="#">UnderlyingPaymentStreamNonDeliverableFixingDatesOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamNonDeliverableFixingDatesOffsetPeriod(40652) is specified.
<a href="#">UnderlyingPaymentStreamNonDeliverableFixingDatesOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingPaymentStreamNonDeliverableSettlRateSource</a>	[0..1]	Component	
<a href="#">UnderlyingPaymentStreamNonDeliverableFixingDateGrp</a>	[0..*]	Group	
<a href="#">UnderlyingSettlRateDisruptionFallbackGrp</a>	[0..*]	Group	

Used in components: [UnderlyingPaymentStream](#)

### 180.2.6255 UnderlyingPaymentStreamOtherDayCount

The industry name of the day count convention not listed in UnderlyingPaymentStreamDayCount(40572).

Type: [String](#)

Used in components: [UnderlyingPaymentStream](#)

### 180.2.6256 UnderlyingPaymentStreamPaymentDate

The adjusted or unadjusted fixed stream payment date.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingPaymentStreamPaymentDateGrp](#)

**180.2.6257 UnderlyingPaymentStreamPaymentDateBusinessCenter**

The business center calendar used to adjust the payment stream's payment date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingPaymentStreamPaymentDateBusinessCenterGrp**

**180.2.6258 UnderlyingPaymentStreamPaymentDateBusinessCenterGrp**

UnderlyingPaymentStreamPaymentDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingPaymentStreamPaymentDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in the UnderlyingInstrument component.

Name	Mult.	Type	Description
NoUnderlyingPaymentStreamPaymentDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingPaymentStreamPaymentDateBusinessCenter	[0..1]	String	Required if NoUnderlyingPaymentStreamPaymentDateBusinessCenters(40969) > 0.

Used in components: **UnderlyingPaymentStreamPaymentDates**

**180.2.6259 UnderlyingPaymentStreamPaymentDateBusinessDayConvention**

The business day convention used to adjust the payment stream's payment date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.



Code	Name	Description
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingPaymentStreamPaymentDates](#)

### 180.2.6260 UnderlyingPaymentStreamPaymentDateGrp

The UnderlyingPaymentStreamPaymentDateGrp is a repeating subcomponent of the UnderlyingPaymentStreamPaymentDates component used to detail fixed dates for swap stream payments.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingPaymentStreamPaymentDates</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingPaymentStreamPaymentDate</a>	[0..1]	LocalMktDate	Required if <a href="#">NoUnderlyingPaymentStreamPaymentDates</a> (41937) > 0.
<a href="#">UnderlyingPaymentStreamPaymentDateType</a>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [UnderlyingPaymentStreamPaymentDates](#)

### 180.2.6261 UnderlyingPaymentStreamPaymentDateOffsetDayType

Specifies the day type of the relative payment date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar

Code	Name	Description
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingPaymentStreamPaymentDates](#)

#### **180.2.6262 UnderlyingPaymentStreamPaymentDateOffsetPeriod**

Time unit multiplier for the relative payment date offset.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamPaymentDates](#)

#### **180.2.6263 UnderlyingPaymentStreamPaymentDateOffsetUnit**

Time unit associated with the relative payment date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingPaymentStreamPaymentDates](#)

#### **180.2.6264 UnderlyingPaymentStreamPaymentDateRelativeTo**

Specifies the anchor date when payment dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamPaymentDates](#)

## 180.2.6265 UnderlyingPaymentStreamPaymentDates

UnderlyingPaymentStreamPaymentDates is a subcomponent of the UnderlyingPaymentStream component used to specify the payment dates of the stream.

Name	Mult.	Type	Description
UnderlyingPaymentStreamPayment- DateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's payment stream's payment dates.
UnderlyingPaymentStreamPayment- DateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's payment stream's payment dates.
UnderlyingPaymentStreamPayment- DateGrp	[0..*]	Group	
UnderlyingPaymentStreamPayment- FrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamPaymentFrequencyUnit(40584) is specified.
UnderlyingPaymentStreamPayment- FrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamPaymentFrequencyPeriod(40583) is specified.
UnderlyingPaymentStreamPayment- tRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the stream payment dates.
UnderlyingPaymentStreamFirstPay- mentDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPaymentStreamLastRegu- larPaymentDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPaymentStreamPayment- DateRelativeTo	[0..1]	int	
UnderlyingPaymentStreamPayment- DateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamPaymentOffsetUnit(40590) is specified.

Name	Mult.	Type	Description
UnderlyingPaymentStreamPayment-DateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamPaymentOffsetPeriod(40589) is specified.
UnderlyingPaymentStreamPayment-DateOffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentStreamMasterAgreementPaymentDatesIndicator	[0..1]	Boolean	
UnderlyingPaymentStreamFinalPrice-PaymentDate	[0..1]	Component	

Used in components: [UnderlyingPaymentStream](#)

#### 180.2.6266 UnderlyingPaymentStreamPaymentDateType

Specifies the type of payment date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: [int](#)

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [UnderlyingPaymentStreamPaymentDateGrp](#)

#### 180.2.6267 UnderlyingPaymentStreamPaymentFrequencyPeriod

Time unit multiplier for the frequency of payments.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamPaymentDates](#)

**180.2.6268 UnderlyingPaymentStreamPaymentFrequencyUnit**

Time unit associated with the frequency of payments.

Type: **String**

Allowed values in PaymentStreamPaymentFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
T	Term	Term

Used in components: **UnderlyingPaymentStreamPaymentDates**

**180.2.6269 UnderlyingPaymentStreamPaymentRollConvention**

The convention for determining the sequence of end dates. It is used in conjunction with a specified frequency. Used only to override the roll convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month

Code	Name	Description
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEigthDa28y	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday

Code	Name	Description
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [UnderlyingPaymentStreamPaymentDates](#)

#### **180.2.6270 UnderlyingPaymentStreamPricingBusinessCalendar**

Specifies the business calendar to use for pricing.

See <http://www.fpml.org/coding-scheme/commodity-business-calendar> for values.

Type: [String](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6271 UnderlyingPaymentStreamPricingBusinessCenter**

The business center calendar used to adjust the payment stream's pricing dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingPaymentStreamPricingBusinessCenterGrp](#)

#### **180.2.6272 UnderlyingPaymentStreamPricingBusinessCenterGrp**

[UnderlyingPaymentStreamPricingBusinessCenterGrp](#) is a repeating subcomponent of the [UnderlyingPaymentStreamFloatingRate](#) component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the [UnderlyingDateAdjustment](#) component in [UnderlyingInstrument](#).

Name	Mult.	Type	Description
NoUnderlyingPaymentStreamPricing-BusinessCenters	[1..1]	NumInGroup	
UnderlyingPaymentStreamPricing-BusinessCenter	[0..1]	String	Required if NoUnderlyingPaymentStreamPricing-BusinessCenters(41909) > 0.

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### 180.2.6273 UnderlyingPaymentStreamPricingBusinessDayConvention

The business day convention used to adjust the payment stream's pricing dates. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### 180.2.6274 UnderlyingPaymentStreamPricingDate

An adjusted or unadjusted fixed pricing date.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingPaymentStreamPricingDateGrp](#)



**180.2.6275 UnderlyingPaymentStreamPricingDateGrp**

The UnderlyingPaymentStreamPricingDateGrp is a repeating subcomponent of the UnderlyingPaymentStreamFloatingRate component used to detail fixed pricing dates.

Name	Mult.	Type	Description
NoUnderlyingPaymentStreamPricing-Dates	[1..1]	NumInGroup	
UnderlyingPaymentStreamPricingDate	[0..1]	LocalMktDate	Required if NoUnderlyingPaymentStreamPricing-Dates(41941) > 0.
UnderlyingPaymentStreamPricing-DateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

**180.2.6276 UnderlyingPaymentStreamPricingDateType**

Specifies the type of pricing date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: [int](#)

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [UnderlyingPaymentStreamPricingDateGrp](#)

**180.2.6277 UnderlyingPaymentStreamPricingDayCount**

The number of days over which pricing should take place.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

**180.2.6278 UnderlyingPaymentStreamPricingDayDistribution**

The distribution of pricing days.

Type: **int**

Allowed values in PaymentStreamPricingDayDistributionCodeSet:

Code	Name	Description
0	All	All
1	First	First
2	Last	Last
3	Penultimate	Penultimate

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6279 UnderlyingPaymentStreamPricingDayGrp**

The UnderlyingPaymentStreamPricingDayGrp is a repeating subcomponent of the UnderlyingPaymentStreamFloatingRate component used to detail periodic pricing days.

Name	Mult.	Type	Description
<b>NoUnderlyingPaymentStreamPricing-Days</b>	[1..1]	NumInGroup	
<b>UnderlyingPaymentStreamPricingDay-OfWeek</b>	[0..1]	CodeSet	Required if NoUnderlyingPaymentStreamPricingDays(41944) > 0.
<b>UnderlyingPaymentStreamPricing-DayNumber</b>	[0..1]	int	

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6280 UnderlyingPaymentStreamPricingDayNumber**

The occurrence of the day of week on which pricing takes place.

Type: **int**

Used in groups: **UnderlyingPaymentStreamPricingDayGrp**

**180.2.6281 UnderlyingPaymentStreamPricingDayOfWeek**

The day of the week on which pricing takes place.

Type: **int**

Allowed values in PaymentStreamPricingDayOfWeekCodeSet:

Code	Name	Description
0	EveryDay	Every day (the default if not specified)
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday

Used in groups: **UnderlyingPaymentStreamPricingDayGrp**

**180.2.6282 UnderlyingPaymentStreamPricingDayType**

Specifies the commodity pricing day type.

Type: **int**

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6283 UnderlyingPaymentStreamRate**

The rate applicable to the fixed rate payment stream.

Type: **Percentage**

Used in components: **UnderlyingPaymentStreamFixedRate**

**180.2.6284 UnderlyingPaymentStreamRateConversionFactor**

The number to be multiplied by the derived floating rate of the underlying's payment stream in order to arrive at the payment rate. If omitted, the floating rate conversion factor is 1.

Type: **float**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6285 UnderlyingPaymentStreamRateCutoffDateOffsetDayType**

Specifies the day type of the relative rate cut-off date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6286 UnderlyingPaymentStreamRateCutoffDateOffsetPeriod**

Time unit multiplier for the relative rate cut-off date offset.

Type: **int**

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6287 UnderlyingPaymentStreamRateCutoffDateOffsetUnit**

Time unit associated with the relative rate cut-off date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6288 UnderlyingPaymentStreamRateIndex**

The payment stream's floating rate index.

Type: **String**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6289 UnderlyingPaymentStreamRateIndex2**

The payment stream's second floating rate index.

Type: **String**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6290 UnderlyingPaymentStreamRateIndex2CurvePeriod**

Secondary time unit multiplier for the payment stream's floating rate index curve.

Type: **int**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6291 UnderlyingPaymentStreamRateIndex2CurveUnit**

Secondary time unit associated with the payment stream's floating rate index curve.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6292 UnderlyingPaymentStreamRateIndex2ID**

Security identifier of the second floating rate index.

Type: **String**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6293 UnderlyingPaymentStreamRateIndex2IDSource**

Source for the second floating rate index identified in UnderlyingPaymentStreamRateIndex2ID(43122).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC

Code	Name	Description
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6294 UnderlyingPaymentStreamRateIndex2Source**

The source of the payment stream's second floating rate index.

Type: [int](#)

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6295 UnderlyingPaymentStreamRateIndexCurvePeriod**

Time unit multiplier for the underlying instrument's floating rate index.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6296 UnderlyingPaymentStreamRateIndexCurveUnit**

Time unit associated with the underlying instrument's floating rate index.

Type: [String](#)

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingPaymentStreamFloatingRate](#)



**180.2.6297 UnderlyingPaymentStreamRateIndexID**

Security identifier of the floating rate index.

Type: **String**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6298 UnderlyingPaymentStreamRateIndexIDSource**

Source for the floating rate index identified in UnderlyingPaymentStreamRateIndexID(43092).

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit

Code	Name	Description
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6299 UnderlyingPaymentStreamRateIndexLevel**

This is the weather Cooling Degree Days (CDD), Heating Degree Days (HDD) or HDD index level specified as the number of (amount of) weather index units specified by the parties in the related confirmation.

Type: [Qty](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6300 UnderlyingPaymentStreamRateIndexLocation**

Specifies the location of the floating rate index.

Type: [String](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

**180.2.6301 UnderlyingPaymentStreamRateIndexSource**

The source of the payment stream floating rate index.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6302 UnderlyingPaymentStreamRateIndexUnitOfMeasure**

The unit of measure (UOM) of the rate index level.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day

Code	Name	Description
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)

Code	Name	Description
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter

Code	Name	Description
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6303 UnderlyingPaymentStreamRateMultiplier**

A rate multiplier to apply to the floating rate. A multiplier schedule is expressed as explicit multipliers and dates. In the case of a schedule, the step dates may be subject to adjustment in accordance with any adjustments specified in the calculationPeriodDatesAdjustments. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: [float](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6304 UnderlyingPaymentStreamRateOrAmountCurrency**

Specifies the currency in which UnderlyingPaymentStreamFixedAmount(40616) or UnderlyingPaymentStreamRate(40615) is denominated. Users ISO 4271 currency codes.

Type: [Currency](#)

Used in components: [UnderlyingPaymentStreamFixedRate](#)

#### **180.2.6305 UnderlyingPaymentStreamRateSpread**

Spread from floating rate index.

Type: [PriceOffset](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

**180.2.6306 UnderlyingPaymentStreamRateSpreadCurrency**

Specifies the currency of the floating rate spread. Uses ISO 4217 currency codes.

Type: **Currency**

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6307 UnderlyingPaymentStreamRateSpreadPositionType**

Identifies a short or long spread value.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6308 UnderlyingPaymentStreamRateSpreadType**

Identifies whether the rate spread is an absolute value to be added to the index rate or a percentage of the index rate.

Type: **int**

Allowed values in PaymentStreamRateSpreadTypeCodeSet:

Code	Name	Description
0	Absolute	Absolute
1	Percentage	Percentage

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6309 UnderlyingPaymentStreamRateSpreadUnitOfMeasure**

Specifies the unit of measure (UOM) of the floating rate spread.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams



Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### 180.2.6310 UnderlyingPaymentStreamRateTreatment

Specifies the yield calculation treatment for the index.

Type: [int](#)

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### **180.2.6311 UnderlyingPaymentStreamRealizedVarianceMethod**

Indicates which price to use to satisfy the boundary condition.

Type: [int](#)

Allowed values in PaymentStreamRealizedVarianceMethodCodeSet:

Code	Name	Description
0	Previous	Previous. For a return on day T, the observed price on T-1 must be in range.
1	Last	Last. For a return on day T, the observed price on T must be in range.
2	Both	Both. For a return on day T, the observed prices on both T and T-1 must be in range.

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### **180.2.6312 UnderlyingPaymentStreamReferenceLevel**

This is the weather Cooling Degree Days (CDD), Heating Degree Days (HDD) or HDD reference level specified as the number of (amount of) weather index units specified by the parties in the related confirmation.

Type: [Qty](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### **180.2.6313 UnderlyingPaymentStreamReferenceLevelEqualsZeroIndicator**

When set to 'Y', it indicates that the weather reference level equals zero.

Type: [Boolean](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

**180.2.6314 UnderlyingPaymentStreamReferenceLevelUnitOfMeasure**

The unit of measure (UOM) of the rate reference level.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### **180.2.6315 UnderlyingPaymentStreamResetDateBusinessCenter**

The business center calendar used to adjust the payment stream's reset date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingPaymentStreamResetDateBusinessCenterGrp](#)

### 180.2.6316 UnderlyingPaymentStreamResetDateBusinessCenterGrp

UnderlyingPaymentStreamResetDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingPaymentStreamResetDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Name	Mult.	Type	Description
NoUnderlyingPaymentStreamReset- DateBusinessCenters	[1..1]	NumInGroup	
UnderlyingPaymentStreamResetDate- BusinessCenter	[0..1]	String	Required if NoUnderlyingPaymentStreamReset- DateBusinessCenters(40970) > 0.

Used in components: [UnderlyingPaymentStreamResetDates](#)

### 180.2.6317 UnderlyingPaymentStreamResetDateBusinessDayConvention

The business day convention used to adjust the payment stream's reset date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingPaymentStreamResetDates](#)

**180.2.6318 UnderlyingPaymentStreamResetDateRelativeTo**

Specifies the anchor date when the reset dates are relative to an anchor date.

If the reset frequency is specified as daily this element must not be included.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStreamResetDates**

**180.2.6319 UnderlyingPaymentStreamResetDates**

UnderlyingPaymentStreamResetDates is a subcomponent of the UnderlyingPaymentStream component used to specify the floating rate reset dates of the stream.

Name	Mult.	Type	Description
<b>UnderlyingPaymentStreamResetDateRelativeTo</b>	[0..1]	int	
<b>UnderlyingPaymentStreamResetDate-BusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's payment stream's reset dates.
<b>UnderlyingPaymentStreamResetDate-BusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's payment stream's reset dates.
<b>UnderlyingPaymentStreamResetFrequencyPeriod</b>	[0..1]	int	Conditionally required when UnderlyingPaymentStreamResetFrequencyUnit(40596) is specified.
<b>UnderlyingPaymentStreamResetFrequencyUnit</b>	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamResetFrequencyPeriod(40595) is specified.
<b>UnderlyingPaymentStreamResetWeeklyRollConvention</b>	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the reset dates.



Name	Mult.	Type	Description
UnderlyingPaymentStreamInitialFixingDateRelativeTo	[0..1]	int	
UnderlyingPaymentStreamInitialFixingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's payment stream's reset dates.
UnderlyingPaymentStreamInitialFixingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's payment stream's reset dates.
UnderlyingPaymentStreamInitialFixingDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamInitialFixingDateOffsetUnit(40602) is specified.
UnderlyingPaymentStreamInitialFixingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamInitialFixingDateOffsetPeriod(40601) is specified.
UnderlyingPaymentStreamInitialFixingDateOffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentStreamInitialFixingDateAdjusted	[0..1]	LocalMktDate	
UnderlyingPaymentStreamFixingDateRelativeTo	[0..1]	int	
UnderlyingPaymentStreamFixingDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's payment stream's reset dates.
UnderlyingPaymentStreamFixingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's payment stream's reset dates.
UnderlyingPaymentStreamFixingDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamFixingDateOffsetUnit(40609) is specified.

Name	Mult.	Type	Description
UnderlyingPaymentStreamFixingDate-OffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamFixingDateOffsetPeriod(40608) is specified.
UnderlyingPaymentStreamFixingDate-OffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentStreamFixing-DateAdjusted	[0..1]	LocalMktDate	
UnderlyingPaymentStreamRateCutoff-DateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStreamRateCutoffDateOffsetUnit(40613) is specified.
UnderlyingPaymentStreamRateCutoff-DateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStreamRateCutoffDateOffsetPeriod(40612) is specified.
UnderlyingPaymentStreamRateCutoff-DateOffsetDayType	[0..1]	CodeSet	
UnderlyingPaymentStreamFixingDate-Grp	[0..*]	Group	

Used in components: [UnderlyingPaymentStream](#)

### 180.2.6320 UnderlyingPaymentStreamResetFrequencyPeriod

Time unit multiplier for frequency of resets.

Type: [int](#)

Used in components: [UnderlyingPaymentStreamResetDates](#)

### 180.2.6321 UnderlyingPaymentStreamResetFrequencyUnit

Time unit associated with frequency of resets.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week

Code	Name	Description
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: [UnderlyingPaymentStreamResetDates](#)

### 180.2.6322 UnderlyingPaymentStreamResetWeeklyRollConvention

Used to specify the day of the week in which the reset occurs for payments that reset on a weekly basis.

Type: [String](#)

Allowed values in PaymentStreamResetWeeklyRollConventionCodeSet:

Code	Name	Description
MON	Monday	Monday
TUE	Tuesday	Tuesday
WED	Wednesday	Wednesday
THU	Thursday	Thursday
FRI	Friday	Friday
SAT	Saturday	Saturday
SUN	Sunday	Sunday

Used in components: [UnderlyingPaymentStreamResetDates](#)

### 180.2.6323 UnderlyingPaymentStreamSettlCurrency

Specifies the currency that the stream settles in (to support swaps that settle in a currency different from the notional currency). Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in components: [UnderlyingPaymentStream](#)

**180.2.6324 UnderlyingPaymentStreamSettlLevel**

Specifies how weather index units are to be calculated.

Type: **int**

Allowed values in PaymentStreamSettlLevelCodeSet:

Code	Name	Description
0	Average	Average. The cumulative number of weather index units for each day in the calculation period divided by the number of days in the calculation period.
1	Maximum	Maximum. The maximum number of weather index units for any day in the calculation period.
2	Minimum	Minimum. The minimum number of weather index units for any day in the calculation period.
3	Cumulative	Cumulative. The cumulative number of weather index units for each day in the calculation period.

Used in components: **UnderlyingPaymentStreamFloatingRate**

**180.2.6325 UnderlyingPaymentStreamTotalFixedAmount**

Specifies the total fixed payment amount.

Type: **Amt**

Used in components: **UnderlyingPaymentStreamFixedRate**

**180.2.6326 UnderlyingPaymentStreamType**

Identifies the type of payment stream applicable to the swap stream associated with the underlying instrument.

Type: **int**

Allowed values in PaymentStreamTypeCodeSet:

Code	Name	Description
0	Periodic	Periodic (default)
1	Initial	Initial

Code	Name	Description
2	Single	Single
3	Dividend	Dividend
4	Interest	Interest
5	DividendReturn	Dividend return
6	PriceReturn	Price return
7	TotalReturn	Total return
8	Variance	Variance
9	Correlation	Correlation

Used in components: [UnderlyingPaymentStream](#)

#### **180.2.6327 UnderlyingPaymentStreamUnderlierRefID**

References the dividend underlier through the instrument's UnderlyingSecurityID(309) which must be fully specified in an instance of the UnderlyingInstrument component.

Type: [String](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6328 UnderlyingPaymentStreamVarianceUnadjustedCap**

Indicates the scaling factor to be multiplied by the variance strike price thereby making variance cap applicable.

Type: [float](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

#### **180.2.6329 UnderlyingPaymentStreamVegaNotionalAmount**

Vega Notional represents the approximate gain/loss at maturity for a 1% difference between RVol (realised volatility) and KVol (strike volatility). It does not necessarily represent the Vega risk of the trade.

Type: [float](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

**180.2.6330 UnderlyingPaymentStreamWorldScaleRate**

The number of Worldscales points for purposes of the calculation of a fixed amount for a wet voyage charter commodity swap.

Type: **float**

Used in components: **UnderlyingPaymentStreamFixedRate**

**180.2.6331 UnderlyingPaymentStubEndDateAdjusted**

The adjusted stub end date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStubEndDate**

**180.2.6332 UnderlyingPaymentStubEndDateBusinessCenter**

The business center calendar used for date adjustment of the payment stub end date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingPaymentStubEndDateBusinessCenterGrp**

**180.2.6333 UnderlyingPaymentStubEndDateBusinessCenterGrp**

UnderlyingPaymentStubEndDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingPaymentStubEndDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingPaymentStubEndDate-BusinessCenters	[1..1]	NumInGroup	
UnderlyingPaymentStubEndDateBusinessCenter	[0..1]	String	Required if NoUnderlyingPaymentStubEndDate-BusinessCenters(42991) > 0.

Used in components: **UnderlyingPaymentStubEndDate**

**180.2.6334 UnderlyingPaymentStubEndDateBusinessDayConvention**

The stub end date business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **UnderlyingPaymentStubEndDate**

**180.2.6335 UnderlyingPaymentStubEndDate**

UnderlyingPaymentStubEndDate is a subcomponent of the UnderlyingPaymentStubGrp component used to specify the end date of the payment stub.

Name	Mult.	Type	Description
<b>UnderlyingPaymentStubEndDateUnadjusted</b>	[0..1]	LocalMktDate	
<b>UnderlyingPaymentStubEndDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this payment stub instance.
<b>UnderlyingPaymentStubEndDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this payment stub instance.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStubEndDateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingPaymentStubEndDateOffsetPeriod</a>	[0..1]	int	Conditionally required when <a href="#">UnderlyingPaymentStubEndDateOffsetUnit(42988)</a> is specified.
<a href="#">UnderlyingPaymentStubEndDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when <a href="#">UnderlyingPaymentStubEndDateOffsetPeriod(42987)</a> is specified.
<a href="#">UnderlyingPaymentStubEndDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingPaymentStubEndDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [UnderlyingPaymentStubGrp](#)

### 180.2.6336 UnderlyingPaymentStubEndDateOffsetDayType

Specifies the day type of the relative stub end date offset.

Type: [int](#)

Allowed values in [PaymentStreamPaymentDateOffsetDayTypeCodeSet](#):

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingPaymentStubEndDate](#)

### 180.2.6337 UnderlyingPaymentStubEndDateOffsetPeriod

Time unit multiplier for the relative stub end date offset.

Type: [int](#)

Used in components: [UnderlyingPaymentStubEndDate](#)



**180.2.6338 UnderlyingPaymentStubEndDateOffsetUnit**

Time unit associated with the relative stub end date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStubEndDate**

**180.2.6339 UnderlyingPaymentStubEndDateRelativeTo**

Specifies the anchor date when the stub end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStubEndDate**

**180.2.6340 UnderlyingPaymentStubEndDateUnadjusted**

The unadjusted stub end date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStubEndDate**

**180.2.6341 UnderlyingPaymentStubFixedAmount**

A fixed payment amount for the stub.

Type: **Amt**

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6342 UnderlyingPaymentStubFixedCurrency**

The currency of the fixed payment amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6343 UnderlyingPaymentStubGrp**

The UnderlyingPaymentStubGrp is a repeating subcomponent of the UnderlyingPaymentStream component used to specify front and back stubs in the payment stream.

Name	Mult.	Type	Description
NoUnderlyingPaymentStubs	[1..1]	NumInGroup	
UnderlyingPaymentStubType	[0..1]	CodeSet	Required if NoUnderlyingPaymentStubs(40708) > 0.
UnderlyingPaymentStubLength	[0..1]	CodeSet	
UnderlyingPaymentStubStartDate	[0..1]	Component	
UnderlyingPaymentStubEndDate	[0..1]	Component	
UnderlyingPaymentStubRate	[0..1]	Percentage	
UnderlyingPaymentStubFixedAmount	[0..1]	Amt	
UnderlyingPaymentStubFixedCurrency	[0..1]	Currency	
UnderlyingPaymentStubIndex	[0..1]	String	
UnderlyingPaymentStubIndexSource	[0..1]	CodeSet	
UnderlyingPaymentStubIndexCurvePeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStubIndexCurveUnit(40717) is specified.
UnderlyingPaymentStubIndexCurveUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStubIndexCurvePeriod(40716) is specified.
UnderlyingPaymentStubIndexRateMultiplier	[0..1]	float	
UnderlyingPaymentStubIndexRateSpread	[0..1]	PriceOffset	
UnderlyingPaymentStubIndexRateSpreadPositionType	[0..1]	CodeSet	
UnderlyingPaymentStubIndexRateTreatment	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingPaymentStubIndexCapRate	[0..1]	Percentage	
UnderlyingPaymentStubIndex-CapRateBuySide	[0..1]	CodeSet	
UnderlyingPaymentStubIndex-CapRateSellSide	[0..1]	CodeSet	
UnderlyingPaymentStubIndexFloor-Rate	[0..1]	Percentage	
UnderlyingPaymentStubIndexFloor-RateBuySide	[0..1]	CodeSet	
UnderlyingPaymentStubIndexFloor-RateSellSide	[0..1]	CodeSet	
UnderlyingPaymentStubIndex2	[0..1]	String	
UnderlyingPaymentStubIndex2Source	[0..1]	CodeSet	
UnderlyingPaymentStubIndex2CurvePeriod	[0..1]	int	Conditionally required when UnderlyingPaymentStubIndex2CurveUnit(40731) is specified.
UnderlyingPaymentStubIndex2CurveUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStubIndex2CurvePeriod(40730) is specified.
UnderlyingPaymentStubIndex2RateMultiplier	[0..1]	float	
UnderlyingPaymentStubIndex2RateSpread	[0..1]	PriceOffset	
UnderlyingPaymentStubIndex2RateSpreadPositionType	[0..1]	CodeSet	
UnderlyingPaymentStubIndex2RateTreatment	[0..1]	CodeSet	
UnderlyingPaymentStubIndex2CapRate	[0..1]	Percentage	
UnderlyingPaymentStubIndex2FloorRate	[0..1]	Percentage	

Used in groups: **UnderlyingStreamGrp**

#### 180.2.6344 UnderlyingPaymentStubIndex

The stub floating rate index.

Type: **String**

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6345 UnderlyingPaymentStubIndex2**

The second stub floating rate index.

Type: [String](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6346 UnderlyingPaymentStubIndex2CapRate**

The cap rate, if any, which applies to the second floating rate. The cap rate (strike) is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: [Percentage](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6347 UnderlyingPaymentStubIndex2CurvePeriod**

Secondary time unit multiplier for the stub floating rate index curve.

Type: [int](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6348 UnderlyingPaymentStubIndex2CurveUnit**

Secondary time unit associated with the stub floating rate index curve.

Type: [String](#)

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

---

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month

---

Code	Name	Description
Yr	Year	Year

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6349 UnderlyingPaymentStubIndex2FloorRate**

The floor rate, if any, which applies to the second floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A floor rate of 5% would be represented as 0.05.

Type: [Percentage](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6350 UnderlyingPaymentStubIndex2RateMultiplier**

A rate multiplier to apply to the second floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: [float](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6351 UnderlyingPaymentStubIndex2RateSpread**

Spread from the second floating rate index.

Type: [PriceOffset](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6352 UnderlyingPaymentStubIndex2RateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: [int](#)

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in groups: [UnderlyingPaymentStubGrp](#)

### 180.2.6353 UnderlyingPaymentStubIndex2RateTreatment

Specifies the yield calculation treatment for the second stub index.

Type: [int](#)

Allowed values in PaymentStreamRateTreatmentCodeSet:

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

Used in groups: [UnderlyingPaymentStubGrp](#)

### 180.2.6354 UnderlyingPaymentStubIndex2Source

The source of the second stub floating rate index.

Type: [int](#)

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in groups: [UnderlyingPaymentStubGrp](#)

**180.2.6355 UnderlyingPaymentStubIndexCapRate**

The cap rate, if any, which applies to the floating rate. The cap rate (strike) is only required where the floating rate on a swap stream is capped at a certain level. The cap rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A cap rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6356 UnderlyingPaymentStubIndexCapRateBuySide**

Reference to the buyer of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6357 UnderlyingPaymentStubIndexCapRateSellSide**

Reference to the seller of the cap rate option through its trade side.

Type: **int**

Allowed values in PaymentStreamCapRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6358 UnderlyingPaymentStubIndexCurvePeriod**

Time unit multiplier for the underlying payment stub floating rate index.

Type: **int**

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6359 UnderlyingPaymentStubIndexCurveUnit**

Time unit associated with the underlying payment stub floating rate index.

Type: **String**

Allowed values in PaymentStreamRateIndexCurveUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6360 UnderlyingPaymentStubIndexFloorRate**

The floor rate, if any, which applies to the floating rate. The floor rate (strike) is only required where the floating rate on a swap stream is floored at a certain strike level. The floor rate is assumed to be exclusive of any spread and is a per annum rate, expressed as a decimal. A floor rate of 5% would be represented as 0.05.

Type: **Percentage**

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6361 UnderlyingPaymentStubIndexFloorRateBuySide**

Reference to the buyer of the floor rate option through its trade side.

Type: **int**



Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6362 UnderlyingPaymentStubIndexFloorRateSellSide**

Reference to the seller of the floor rate option through its trade side.

Type: [int](#)

Allowed values in PaymentStreamFloorRateBuySideCodeSet:

Code	Name	Description
1	Buyer	Buyer of the trade
2	Seller	Seller of the trade

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6363 UnderlyingPaymentStubIndexRateMultiplier**

A rate multiplier to apply to the floating rate. The multiplier can be less than or greater than 1 (one). This element should only be included if the multiplier is not equal to 1 (one) for the term of the stream.

Type: [float](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6364 UnderlyingPaymentStubIndexRateSpread**

Spread from floating rate index.

Type: [PriceOffset](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

**180.2.6365 UnderlyingPaymentStubIndexRateSpreadPositionType**

Identifies whether the rate spread is applied to a long or short position.

Type: **int**

Allowed values in PaymentStreamRateSpreadPositionTypeCodeSet:

---

Code	Name	Description
0	Short	Short
1	Long	Long

---

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6366 UnderlyingPaymentStubIndexRateTreatment**

Specifies the yield calculation treatment for the stub index.

Type: **int**

Allowed values in PaymentStreamRateTreatmentCodeSet:

---

Code	Name	Description
0	BondEquivalentYield	Bond equivalent yield
1	MoneyMarketYield	Money market yield

---

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6367 UnderlyingPaymentStubIndexSource**

The source for the underlying payment stub floating rate index.

Type: **int**

Allowed values in PaymentStreamRateIndexSourceCodeSet:

---

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters

---

Code	Name	Description
2	Telerate	Telerate
99	Other	Other

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6368 UnderlyingPaymentStubLength**

Optional indication whether stub is shorter or longer than the regular swap period.

Type: [int](#)

Allowed values in PaymentStubLengthCodeSet:

Code	Name	Description
0	Short	Short
1	Long	Long

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6369 UnderlyingPaymentStubRate**

The agreed upon fixed rate for this stub.

Type: [Percentage](#)

Used in groups: [UnderlyingPaymentStubGrp](#)

#### **180.2.6370 UnderlyingPaymentStubStartDateAdjusted**

The adjusted stub start date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingPaymentStubStartDate](#)

**180.2.6371 UnderlyingPaymentStubStartDateBusinessCenter**

The business center calendar used for date adjustment of the payment stub start date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingPaymentStubStartDateBusinessCenterGrp**

**180.2.6372 UnderlyingPaymentStubStartDateBusinessCenterGrp**

UnderlyingPaymentStubStartDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingPaymentStubStartDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingPaymentStubStartDate-BusinessCenters	[1..1]	NumInGroup	
UnderlyingPaymentStubStartDate-BusinessCenter	[0..1]	String	Required if NoUnderlyingPaymentStubStartDate-BusinessCenters(43000) > 0.

Used in components: **UnderlyingPaymentStubStartDate**

**180.2.6373 UnderlyingPaymentStubStartDateBusinessDayConvention**

The stub start date business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.

Code	Name	Description
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingPaymentStubStartDate](#)

### 180.2.6374 UnderlyingPaymentStubStartDate

UnderlyingPaymentStubStartDate is a subcomponent of the UnderlyingPaymentStubGrp component used to specify the start date of the payment stub.

Name	Mult.	Type	Description
<a href="#">UnderlyingPaymentStubStartDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingPaymentStubStartDate-BusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this payment stub instance.
<a href="#">UnderlyingPaymentStubStartDate-BusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this payment stub instance.
<a href="#">UnderlyingPaymentStubStartDateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingPaymentStubStartDateOffsetPeriod</a>	[0..1]	int	Conditionally required when UnderlyingPaymentStubStartDateOffsetUnit(42997) is specified.
<a href="#">UnderlyingPaymentStubStartDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentStubStartDateOffsetPeriod(42996) is specified.
<a href="#">UnderlyingPaymentStubStartDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingPaymentStubStartDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [UnderlyingPaymentStubGrp](#)

**180.2.6375 UnderlyingPaymentStubStartDateOffsetDayType**

Specifies the day type of the relative stub start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingPaymentStubStartDate**

**180.2.6376 UnderlyingPaymentStubStartDateOffsetPeriod**

Time unit multiplier for the relative stub start date offset.

Type: **int**

Used in components: **UnderlyingPaymentStubStartDate**

**180.2.6377 UnderlyingPaymentStubStartDateOffsetUnit**

Time unit associated with the relative stub start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingPaymentStubStartDate**

**180.2.6378 UnderlyingPaymentStubStartDateRelativeTo**

Specifies the anchor date when the stub start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingPaymentStubStartDate**

**180.2.6379 UnderlyingPaymentStubStartDateUnadjusted**

The unadjusted stub start date.

Type: **LocalMktDate**

Used in components: **UnderlyingPaymentStubStartDate**

**180.2.6380 UnderlyingPaymentStubType**

Stub type.

Type: **int**

Allowed values in PaymentStubTypeCodeSet:

Code	Name	Description
0	Initial	Initial
1	Final	Final
2	CompoundingInitial	Compounding initial
3	CompoundingFinal	Compounding final

Used in groups: **UnderlyingPaymentStubGrp**

**180.2.6381 UnderlyingPhysicalSettlBusinessDays**

A number of business days. Its precise meaning is dependent on the context in which this element is used.

Type: **int**

Used in groups: **UnderlyingPhysicalSettlTermGrp**

**180.2.6382 UnderlyingPhysicalSettlCurrency**

Currency of physical settlement. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingPhysicalSettlTermGrp**

**180.2.6383 UnderlyingPhysicalSettlDeliverableObligationGrp**

The UnderlyingPhysicalSettlDeliverableObligationGrp is a repeating component within the UnderlyingPhysicalSettlTermGrp component used to report CDS physical settlement delivery obligations.

Name	Mult.	Type	Description
NoUnderlyingPhysicalSettlDeliverableObligations	[1..1]	NumInGroup	
UnderlyingPhysicalSettlDeliverableObligationType	[0..1]	String	Required if NoUnderlyingPhysicalSettlDeliverableObligations(42065) > 0.
UnderlyingPhysicalSettlDeliverableObligationValue	[0..1]	String	

Used in groups: **UnderlyingPhysicalSettlTermGrp**

**180.2.6384 UnderlyingPhysicalSettlDeliverableObligationType**

Specifies the type of delivery obligation applicable for physical settlement.

See [http://www.fixtradingcommunity.org/codelists#Deliverable\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Deliverable_Obligation_Types) for code list for applicable deliverable obligation types.

Type: **String**

Used in groups: **UnderlyingPhysicalSettlDeliverableObligationGrp**

**180.2.6385 UnderlyingPhysicalSettlDeliverableObligationValue**

Physical settlement delivery obligation value appropriate to UnderlyingPhysicalSettlDeliverableObligationType(42066).

See [http://www.fixtradingcommunity.org/codelists#Deliverable\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Deliverable_Obligation_Types) for applicable obligation type values.



Type: **String**

Used in groups: **UnderlyingPhysicalSettlDeliverableObligationGrp**

### **180.2.6386 UnderlyingPhysicalSettlMaximumBusinessDays**

A maximum number of business days. Its precise meaning is dependent on the context in which this element is used. Intended to be used to limit a particular ISDA fallback provision.

Type: **int**

Used in groups: **UnderlyingPhysicalSettlTermGrp**

### **180.2.6387 UnderlyingPhysicalSettlTermGrp**

The UnderlyingPhysicalSettlTermGrp is a repeating component within the UnderlyingInstrument component used to report physical settlement terms.

<b>Name</b>	<b>Mult.</b>	<b>Type</b>	<b>Description</b>
<b>NoUnderlyingPhysicalSettlTerms</b>	[1..1]	NumInGroup	
<b>UnderlyingPhysicalSettlDeliverableObligationGrp</b>	[0..*]	Group	Required if NoUnderlyingPhysicalSettlTerms(42060) > 0.
<b>UnderlyingPhysicalSettlCurrency</b>	[0..1]	Currency	
<b>UnderlyingPhysicalSettlBusinessDays</b>	[0..1]	int	
<b>UnderlyingPhysicalSettlMaximumBusinessDays</b>	[0..1]	int	
<b>UnderlyingPhysicalSettlTermXID</b>	[0..1]	XID	

Used in components: **UnderlyingInstrument**

### **180.2.6388 UnderlyingPhysicalSettlTermXID**

A named string value referenced by UnderlyingSettlTermXIDRef(41315).

Type: **XID**

Used in groups: **UnderlyingPhysicalSettlTermGrp**

**180.2.6389 UnderlyingPool**

Identifies the mortgage backed security (MBS) / asset backed security (ABS) pool.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.6390 UnderlyingPositionLimit**

Position limit for the instrument.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.6391 UnderlyingPriceDeterminationMethod**

Specifies how the underlying price is determined at the point of option exercise. The underlying price may be set to the current settlement price, set to a special reference, set to the optimal value of the underlying during the defined period ("Look-back") or set to the average value of the underlying during the defined period ("Asian option").

Type: **int**

Allowed values in UnderlyingPriceDeterminationMethodCodeSet:

Code	Name	Description
1	Regular	Regular
2	SpecialReference	Special reference
3	OptimalValue	Optimal value (Lookback)
4	AverageValue	Average value (Asian option)

Used in components: **Instrument**

**180.2.6392 UnderlyingPriceQuoteCurrency**

Default currency in which the price is quoted. Defined at the instrument level. Used in place of Currency (tag 15) to express the currency of a product when the former is implemented as the FX dealt currency.

Type: **Currency**

Used in components: **UnderlyingInstrument**

**180.2.6393 UnderlyingPriceQuoteCurrencyCodeSource**

Identifies class or source of the UnderlyingPriceQuoteCurrency(1526) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **UnderlyingInstrument**

**180.2.6394 UnderlyingPriceQuoteMethod**

Method for price quotation.

Type: **String**

Allowed values in PriceQuoteMethodCodeSet:

Code	Name	Description
STD	Standard	Standard, money per unit of a physical
INX	Index	Index
INT	InterestRateIndex	Interest rate Index
PCTPAR	PercentOfPar	Percent of Par

Used in components: **UnderlyingInstrument**

**180.2.6395 UnderlyingPriceUnitOfMeasure**

Refer to definition for PriceUnitOfMeasure(1191)

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs

Code	Name	Description
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile

Code	Name	Description
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [UnderlyingInstrument](#)

#### 180.2.6396 UnderlyingPriceUnitOfMeasureCurrency

Indicates the currency of the underlying price unit of measure. Conditionally required when UnderlyingPriceUnitOfMeasure(1424) = Ccy

Type: [Currency](#)

Used in components: [UnderlyingInstrument](#)

#### 180.2.6397 UnderlyingPriceUnitOfMeasureCurrencyCodeSource

Identifies class or source of the UnderlyingPriceUnitOfMeasureCurrency(1719) value.

Type: [String](#)

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingInstrument](#)

#### **180.2.6398 UnderlyingPriceUnitOfMeasureQty**

Refer to definition of PriceUnitOfMeasureQty(1192)

Type: [Qty](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.6399 UnderlyingPricingDateAdjusted**

The adjusted pricing or fixing date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingPricingDateTime](#)

#### **180.2.6400 UnderlyingPricingDateBusinessCenter**

The business center calendar used to adjust the pricing or fixing date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingPricingDateBusinessCenterGrp](#)

### 180.2.6401 UnderlyingPricingDateBusinessCenterGrp

UnderlyingPricingDateBusinessCenterGrp is a repeating subcomponent of the UnderlyingPricingDate-Time component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingPricingDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingPricingDateBusinessCenter	[0..1]	String	Required if NoUnderlyingPricingDateBusinessCenters(41947) > 0.

Used in components: [UnderlyingPricingDateTime](#)

### 180.2.6402 UnderlyingPricingDateBusinessDayConvention

The business day convention used to adjust the pricing or fixing date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingPricingDateTime](#)



**180.2.6403 UnderlyingPricingDateTime**

The UnderlyingPricingDateTime component is a subcomponent of UnderlyingInstrument used to specify an adjusted or unadjusted pricing or fixing date and optionally the time, e.g. for a commodity or FX forward trade.

Name	Mult.	Type	Description
UnderlyingPricingDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingPricingDateBusinessDay-Convention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to the underlying complex event dates.
UnderlyingPricingDateBusinessCenter-Grp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to the underlying complex event dates.
UnderlyingPricingDateAdjusted	[0..1]	LocalMktDate	
UnderlyingPricingTime	[0..1]	LocalMktTime	
UnderlyingPricingTimeBusinessCenter	[0..1]	String	

Used in components: **UnderlyingInstrument**

**180.2.6404 UnderlyingPricingDateUnadjusted**

The unadjusted pricing or fixing date.

Type: **LocalMktDate**

Used in components: **UnderlyingPricingDateTime**

**180.2.6405 UnderlyingPricingTime**

The local market pricing or fixing time.

Type: **LocalMktTime**

Used in components: **UnderlyingPricingDateTime**

**180.2.6406 UnderlyingPricingTimeBusinessCenter**

Specifies the business center for determining the pricing or fixing time. See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **UnderlyingPricingDateTime**

**180.2.6407 UnderlyingProduct**

Underlying security's Product.

Valid values: see Product(460) field

Type: **int**

Allowed values in ProductCodeSet:

Code	Name	Description
1	AGENCY	AGENCY
2	COMMODITY	COMMODITY
3	CORPORATE	CORPORATE
4	CURRENCY	CURRENCY
5	EQUITY	EQUITY
6	GOVERNMENT	GOVERNMENT
7	INDEX	INDEX
8	LOAN	LOAN
9	MONEYMARKET	MONEYMARKET
10	MORTGAGE	MORTGAGE
11	MUNICIPAL	MUNICIPAL
12	OTHER	OTHER
13	FINANCING	FINANCING

Used in components: **UnderlyingInstrument**

**180.2.6408 UnderlyingProductComplex**

Identifies an entire suite of products for a given market. In Futures this may be "interest rates", "agricultural", "equity indexes", etc

Type: **String**

Used in components: **UnderlyingInstrument**

#### **180.2.6409 UnderlyingProtectionTermBuyerNotifies**

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring.

UnderlyingProtectionTermBuyerNotifies(42072)=Y indicates that the buyer notifies.

Type: **Boolean**

Used in groups: **UnderlyingProtectionTermGrp**

#### **180.2.6410 UnderlyingProtectionTermCurrency**

The currency of UnderlyingProtectionTermNotional(42069). Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingProtectionTermGrp**

#### **180.2.6411 UnderlyingProtectionTermEventBusinessCenter**

When used, the business center indicates the local time of the business center that replaces the Greenwich Mean Time in Section 3.3 of the 2003 ISDA Credit Derivatives Definitions.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingProtectionTermGrp**

#### **180.2.6412 UnderlyingProtectionTermEventCurrency**

Applicable currency if UnderlyingProtectionTermEventValue(42079) is an amount. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingProtectionTermEventGrp**

**180.2.6413 UnderlyingProtectionTermEventDayType**

Day type for events that specify a period and unit.

Type: **int**

Allowed values in ProtectionTermEventDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **UnderlyingProtectionTermEventGrp**

**180.2.6414 UnderlyingProtectionTermEventGrp**

The UnderlyingProtectionTermEventGrp is a repeating component within the UnderlyingProtectionTermGrp component used to report applicable CDS credit events.

Name	Mult.	Type	Description
NoUnderlyingProtectionTermEvents	[1..1]	NumInGroup	
UnderlyingProtectionTermEventType	[0..1]	String	Required if NoUnderlyingProtectionTermEvents (42078) > 0.
UnderlyingProtectionTermEventValue	[0..1]	String	
UnderlyingProtectionTermEventCurrency	[0..1]	Currency	
UnderlyingProtectionTermEventPeriod	[0..1]	int	Conditionally required when UnderlyingProtectionTermEventUnit(42082) is specified.
UnderlyingProtectionTermEventUnit	[0..1]	CodeSet	Conditionally required when UnderlyingProtectionTermEventPeriod(42081) is specified.
UnderlyingProtectionTermEventDayType	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingProtectionTermEventRate-Source	[0..1]	String	
UnderlyingProtectionTermEventQualifierGrp	[0..*]	Group	

Used in groups: [UnderlyingProtectionTermGrp](#)

### 180.2.6415 UnderlyingProtectionTermEventMinimumSources

The minimum number of the specified public information sources that must publish information that reasonably confirms that a credit event has occurred. The market convention is two.

Type: [int](#)

Used in groups: [UnderlyingProtectionTermGrp](#)

### 180.2.6416 UnderlyingProtectionTermEventNewsSource

Newspaper or electronic news service or source that may publish relevant information used in the determination of whether or not a credit event has occurred.

Type: [String](#)

Used in groups: [UnderlyingProtectionTermEventNewsSourceGrp](#)

### 180.2.6417 UnderlyingProtectionTermEventNewsSourceGrp

UnderlyingProtectionTermEventNewsSourceGrp is a repeating subcomponent within the UnderlyingProtectionTermGrp component. It is used to specify the particular newspapers or electronic news services and sources that may publish relevant information used in the determination of whether or not a credit event has occurred.

Name	Mult.	Type	Description
NoUnderlyingProtectionTermEventNewsSources	[1..1]	NumInGroup	
UnderlyingProtectionTermEventNewsSource	[0..1]	String	Required if NoUnderlyingProtectionTermEventNewsSources(42090) > 0.

Used in groups: [UnderlyingProtectionTermGrp](#)

**180.2.6418 UnderlyingProtectionTermEventPeriod**

Time unit multiplier for protection term events.

Type: **int**

Used in groups: **UnderlyingProtectionTermEventGrp**

**180.2.6419 UnderlyingProtectionTermEventQualifier**

Protection term event qualifier. Used to further qualify UnderlyingProtectionTermEventType(43078).

Type: **char**

Allowed values in ProtectionTermEventQualifierCodeSet:

Code	Name	Description
H	RestructuringMultipleHoldingObligations	Restructuring - multiple holding obligations. In relation to a restructuring credit event, unless multiple holder obligation is not specified restructurings are limited to multiple holder obligations. A multiple holder obligation means an obligation that is held by more than three holders that are not affiliates of each other and where at least two thirds of the holders must agree to the event that constitutes the restructuring credit event. ISDA 2003 Term: Multiple Holder Obligation.
E	RestructuringMultipleCreditEvent-Notices	Restructuring - multiple credit event notices. Presence of this element and value set to 'true' indicates that Section 3.9 of the 2003 Credit Derivatives Definitions shall apply. Absence of this element indicates that Section 3.9 shall not apply. NOTE: Not allowed under ISDA Credit 1999.
C	FloatingRateInterestShortfall	Floating rate interest shortfall. Indicates compounding.

Used in groups: **UnderlyingProtectionTermEventQualifierGrp**

**180.2.6420 UnderlyingProtectionTermEventQualifierGrp**

The UnderlyingProtectionTermEventQualifierGrp is a repeating component within the UnderlyingProtectionTermEventGrp component used to specify qualifying attributes to the event.

Name	Mult.	Type	Description
NoUnderlyingProtectionTermEventQualifiers	[1..1]	NumInGroup	
UnderlyingProtectionTermEventQualifier	[0..1]	CodeSet	Required if NoUnderlyingProtectionTermEventQualifiers(42085) > 0.

Used in groups: [UnderlyingProtectionTermEventGrp](#)

#### 180.2.6421 UnderlyingProtectionTermEventRateSource

Rate source for events that specify a rate source, e.g. Floating rate interest shortfall.

Type: [String](#)

Used in groups: [UnderlyingProtectionTermEventGrp](#)

#### 180.2.6422 UnderlyingProtectionTermEventType

Specifies the type of credit event applicable to the protection terms.

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Event_Types) for code list of applicable event types.

Type: [String](#)

Used in groups: [UnderlyingProtectionTermEventGrp](#)

#### 180.2.6423 UnderlyingProtectionTermEventUnit

Time unit associated with protection term events.

Type: [String](#)

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [UnderlyingProtectionTermEventGrp](#)

#### **180.2.6424 UnderlyingProtectionTermEventValue**

Protection term event value appropriate to UnderlyingProtectionTermEventType(42078).

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Event\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Event_Types) for applicable event type values.

Type: [String](#)

Used in groups: [UnderlyingProtectionTermEventGrp](#)

#### **180.2.6425 UnderlyingProtectionTermGrp**

The UnderlyingProtectionTermGrp is a repeating component within the UnderlyingInstrument component used to report contract protection term details.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingProtectionTerms</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingProtectionTermNotional</a>	[0..1]	Amt	Required if NoUnderlyingProtectionTerms(42068) > 0.
<a href="#">UnderlyingProtectionTermCurrency</a>	[0..1]	Currency	
<a href="#">UnderlyingProtectionTermSellerNotifies</a>	[0..1]	Boolean	
<a href="#">UnderlyingProtectionTermBuyerNotifies</a>	[0..1]	Boolean	
<a href="#">UnderlyingProtectionTermEventBusinessCenter</a>	[0..1]	String	
<a href="#">UnderlyingProtectionTermStandardSources</a>	[0..1]	Boolean	
<a href="#">UnderlyingProtectionTermEventMinimumSources</a>	[0..1]	int	
<a href="#">UnderlyingProtectionTermEventNewsSourceGrp</a>	[0..*]	Group	
<a href="#">UnderlyingProtectionTermEventGrp</a>	[0..*]	Group	
<a href="#">UnderlyingProtectionTermObligationGrp</a>	[0..*]	Group	
<a href="#">UnderlyingProtectionTermXID</a>	[0..1]	XID	



Used in components: [UnderlyingInstrument](#)

### **180.2.6426 UnderlyingProtectionTermNotional**

The notional amount of protection coverage for a floating rate.

Type: [Amt](#)

Used in groups: [UnderlyingProtectionTermGrp](#)

### **180.2.6427 UnderlyingProtectionTermObligationGrp**

The UnderlyingProtectionTermObligationGrp is a repeating component within the UnderlyingProtectionTermGrp component used to report applicable CDS obligations.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingProtectionTermObligations</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingProtectionTermObligation-Type</a>	[0..1]	String	Required if NoUnderlyingProtectionTermObligations(42087) > 0.
<a href="#">UnderlyingProtectionTermObligation-Value</a>	[0..1]	String	

Used in groups: [UnderlyingProtectionTermGrp](#)

### **180.2.6428 UnderlyingProtectionTermObligationType**

Specifies the type of obligation applicable to the protection terms.

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Obligation_Types) for code list of applicable obligation types.

Type: [String](#)

Used in groups: [UnderlyingProtectionTermObligationGrp](#)

**180.2.6429 UnderlyingProtectionTermObligationValue**

Protection term obligation value appropriate to UnderlyingProtectionTermObligationType(42088).

See [http://www.fixtradingcommunity.org/codelists#Protection\\_Term\\_Obligation\\_Types](http://www.fixtradingcommunity.org/codelists#Protection_Term_Obligation_Types) for applicable obligation type values.

Type: **String**

Used in groups: **UnderlyingProtectionTermObligationGrp**

**180.2.6430 UnderlyingProtectionTermSellerNotifies**

The notifying party is the party that notifies the other party when a credit event has occurred by means of a credit event notice. If more than one party is referenced as being the notifying party then either party may notify the other of a credit event occurring.

UnderlyingProtectionTermSellerNotifies(42071)=Y indicates that the seller notifies.

Type: **Boolean**

Used in groups: **UnderlyingProtectionTermGrp**

**180.2.6431 UnderlyingProtectionTermStandardSources**

Indicates whether ISDA defined Standard Public Sources are applicable (UnderlyingProtectionTermStandardSources(42074)=Y) or not.

Type: **Boolean**

Used in groups: **UnderlyingProtectionTermGrp**

**180.2.6432 UnderlyingProtectionTermXID**

A named string value referenced by UnderlyingProtectionTermXIDRef(41314).

Type: **XID**

Used in groups: **UnderlyingProtectionTermGrp**

**180.2.6433 UnderlyingProtectionTermXIDRef**

Reference to the protection terms applicable to this entity or obligation. Contains the same XID named string value of the instance in the ProtectionTerms repeating group that applies to this Underlying.

Type: **XIDREF**

Used in components: **UnderlyingInstrument**

**180.2.6434 UnderlyingProvisionBreakFeeElection**

Type of fee elected for the break provision.

Type: **int**

Allowed values in ProvisionBreakFeeElectionCodeSet:

Code	Name	Description
0	FlatFee	Flat fee
1	AmortizedFee	Amortized fee
2	FundingFee	Funding fee
3	FlatAndFundingFee	Flat fee and funding fee
4	AmortizedAndFundingFee	Amortized fee and funding fee

Used in groups: **UnderlyingProvisionGrp**

**180.2.6435 UnderlyingProvisionBreakFeeRate**

Break fee election rate when the break fee is proportional to the notional. A fee rate of 5% would be represented as "0.05".

Type: **Percentage**

Used in groups: **UnderlyingProvisionGrp**

**180.2.6436 UnderlyingProvisionCalculationAgent**

Used to identify the calculation agent. The calculation agent may be identified in UnderlyingProvisionCalculationAgent(42156) or in the underlying provision parties component.

Type: **int**

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreement	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

Used in groups: [UnderlyingProvisionGrp](#)

#### **180.2.6437 UnderlyingProvisionCashSettlCurrency**

Specifies the currency of settlement. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingProvisionGrp](#)

#### **180.2.6438 UnderlyingProvisionCashSettlCurrency2**

Specifies the currency of settlement for a cross-currency provision. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingProvisionGrp](#)

#### **180.2.6439 UnderlyingProvisionCashSettlMethod**

An ISDA defined cash settlement method used for the determination of the applicable cash settlement amount. The method is defined in the 2006 ISDA Definitions, Section 18.3. Cash Settlement Methods, paragraph (e).

Type: [int](#)

Allowed values in ProvisionCashSettlMethodCodeSet:

Code	Name	Description
0	CashPrice	Cash price
1	CashPriceAlternate	Cash price alternate

Code	Name	Description
2	ParYieldCurveAdjusted	Par yield curve adjusted
3	ZeroCouponYieldCurveAdjusted	Zero coupon yield curve adjusted
4	ParYieldCurveUnadjusted	Par yield curve unadjusted
5	CrossCurrency	Cross currency
6	CollateralizedPrice	Collateralized price

Used in groups: **UnderlyingProvisionGrp**

#### **180.2.6440 UnderlyingProvisionCashSettlPaymentDate**

The cash settlement payment date, unadjusted or adjusted depending on UnderlyingProvisionCashSettlPaymentDateType(42101).

Type: **LocalMktDate**

Used in groups: **UnderlyingProvisionCashSettlPaymentFixedDateGrp**

#### **180.2.6441 UnderlyingProvisionCashSettlPaymentDateBusinessCenter**

The business center calendar used to adjust the provision's cash settlement payment's termination, or relative termination, date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingProvisionCashSettlPaymentDateBusinessCenterGrp**

#### **180.2.6442 UnderlyingProvisionCashSettlPaymentDateBusinessCenterGrp**

UnderlyingProvisionCashSettlPaymentDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingProvisionCashSettlPaymentDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingProvisionCashSettlPaymentDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingProvisionCashSettlPaymentDateBusinessCenter	[0..1]	String	Required if NoUnderlyingProvisionCashSettlPaymentDateBusinessCenters(42180) > 0.

Used in components: [UnderlyingProvisionCashSettlPaymentDates](#)

### 180.2.6443 UnderlyingProvisionCashSettlPaymentDateBusinessDayConvention

The business day convention used to adjust the provisional cash settlement payment's termination, or relative termination, date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingProvisionCashSettlPaymentDates](#)

### 180.2.6444 UnderlyingProvisionCashSettlPaymentDateOffsetDayType

Specifies the day type of the provision's relative cash settlement payment date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingProvisionCashSettlPaymentDates](#)

#### **180.2.6445 UnderlyingProvisionCashSettlPaymentDateOffsetPeriod**

Time unit multiplier for the relative cash settlement payment date offset.

Type: [int](#)

Used in components: [UnderlyingProvisionCashSettlPaymentDates](#)

#### **180.2.6446 UnderlyingProvisionCashSettlPaymentDateOffsetUnit**

Time unit associated with the relative cash settlement payment date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingProvisionCashSettlPaymentDates](#)

#### **180.2.6447 UnderlyingProvisionCashSettlPaymentDateRangeFirst**

First date in range when a settlement date range is provided.

Type: **LocalMktDate**

Used in components: **UnderlyingProvisionCashSettlPaymentDates**

#### **180.2.6448 UnderlyingProvisionCashSettlPaymentDateRangeLast**

Last date in range when a settlement date range is provided.

Type: **LocalMktDate**

Used in components: **UnderlyingProvisionCashSettlPaymentDates**

#### **180.2.6449 UnderlyingProvisionCashSettlPaymentDateRelativeTo**

Specifies the anchor date when the cash settlement payment date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingProvisionCashSettlPaymentDates**

#### **180.2.6450 UnderlyingProvisionCashSettlPaymentDates**

The UnderlyingProvisionCashSettlPaymentDates component is a sub-component within the UnderlyingProvisionGrp component used to report the cash settlement payment dates defined in the provision.

Name	Mult.	Type	Description
<b>UnderlyingProvisionCashSettlPaymentDateBusinessDayConvention</b>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the provisional cash settlement payment date.
<b>UnderlyingProvisionCashSettlPaymentDateBusinessCenterGrp</b>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the provisional cash settlement payment date.
<b>UnderlyingProvisionCashSettlPaymentDateRelativeTo</b>	[0..1]	int	



Name	Mult.	Type	Description
<a href="#">UnderlyingProvisionCashSettlPaymentDateOffsetPeriod</a>	[0..1]	int	Conditionally required when UnderlyingProvisionCashSettlPaymentDateOffsetUnit(42095) is specified.
<a href="#">UnderlyingProvisionCashSettlPaymentDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when UnderlyingProvisionCashSettlPaymentDateOffsetPeriod(42094) is specified.
<a href="#">UnderlyingProvisionCashSettlPaymentDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingProvisionCashSettlPaymentDateRangeFirst</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingProvisionCashSettlPaymentDateRangeLast</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingProvisionCashSettlPaymentFixedDateGrp</a>	[0..*]	Group	

Used in groups: [UnderlyingProvisionGrp](#)

### 180.2.6451 UnderlyingProvisionCashSettlPaymentDateType

Specifies the type of date (e.g. adjusted for holidays).

Type: [int](#)

Allowed values in ProvisionCashSettlPaymentDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [UnderlyingProvisionCashSettlPaymentFixedDateGrp](#)

### 180.2.6452 UnderlyingProvisionCashSettlPaymentFixedDateGrp

The UnderlyingProvisionCashSettlPaymentFixedDateGrp is a repeating component within the UnderlyingProvisionCashSettlPaymentDates component used to report fixed cash settlement payment dates defined in the provision.

Name	Mult.	Type	Description
NoUnderlyingProvisionCashSettlPaymentDates	[1..1]	NumInGroup	
UnderlyingProvisionCashSettlPaymentDate	[0..1]	LocalMktDate	Required if NoUnderlyingProvisionCashSettlPaymentDates (42099) > 0.
UnderlyingProvisionCashSettlPaymentDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [UnderlyingProvisionCashSettlPaymentDates](#)

### 180.2.6453 UnderlyingProvisionCashSettlQuoteReferencePage

Identifies the reference "page" from the quote source.

Type: [String](#)

Used in components: [UnderlyingProvisionCashSettlQuoteSource](#)

### 180.2.6454 UnderlyingProvisionCashSettlQuoteSource

Identifies the source of quote information.

Type: [int](#)

Allowed values in PaymentStreamRateIndexSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
99	Other	Other

Used in components: [UnderlyingProvisionCashSettlQuoteSource](#)

**180.2.6455 UnderlyingProvisionCashSettlQuoteSource**

The UnderlyingProvisionCashSettlQuoteSource is a subcomponent of the UnderlyingProvisionGrp component used to specify the reference source for currency or rate quote for cash settlement purposes.

Name	Mult.	Type	Description
UnderlyingProvisionCashSettlQuote-Source	[0..1]	CodeSet	
UnderlyingProvisionCashSettlQuoteReferencePage	[0..1]	String	

Used in groups: [UnderlyingProvisionGrp](#)

**180.2.6456 UnderlyingProvisionCashSettlQuoteType**

Identifies the type of quote to be used.

Type: [int](#)

Allowed values in ProvisionCashSettlQuoteTypeCodeSet:

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer
3	ExercisingPartyPays	Exercising party pays. See 2000 ISDA Definitions, Section 17.2, Certain Definitions Relating to Cash Settlement, paragraph (j) for definition of "exercising party pays".

Used in groups: [UnderlyingProvisionGrp](#)

**180.2.6457 UnderlyingProvisionCashSettlValueDateAdjusted**

The adjusted cash settlement value date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingProvisionCashSettlValueDates](#)

**180.2.6458 UnderlyingProvisionCashSettlValueDateBusinessCenter**

The business center calendar used to adjust the cash settlement valuation date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingProvisionCashSettlValueDateBusinessCenterGrp**

**180.2.6459 UnderlyingProvisionCashSettlValueDateBusinessCenterGrp**

UnderlyingProvisionCashSettlValueDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingProvisionCashSettlValueDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
<b>NoUnderlyingProvisionCashSettlValueDateBusinessCenters</b>	[1..1]	NumInGroup	
<b>UnderlyingProvisionCashSettlValueDateBusinessCenter</b>	[0..1]	String	Required if NoUnderlyingProvisionCashSettlValueDateBusinessCenters(42182) > 0.

Used in components: **UnderlyingProvisionCashSettlValueDates**

**180.2.6460 UnderlyingProvisionCashSettlValueDateBusinessDayConvention**

The business day convention used to adjust the cash settlement valuation date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.

Code	Name	Description
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingProvisionCashSettlValueDates](#)

#### **180.2.6461 UnderlyingProvisionCashSettlValueDateOffsetDayType**

Specifies the day type of the provision's relative cash settlement value date offset.

Type: [int](#)

Allowed values in [PaymentStreamPaymentDateOffsetDayTypeCodeSet](#):

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingProvisionCashSettlValueDates](#)

#### **180.2.6462 UnderlyingProvisionCashSettlValueDateOffsetPeriod**

Time unit multiplier for the relative cash settlement value date offset.

Type: [int](#)

Used in components: [UnderlyingProvisionCashSettlValueDates](#)

**180.2.6463 UnderlyingProvisionCashSettlValueDateOffsetUnit**

Time unit associated with the relative cash settlement value date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingProvisionCashSettlValueDates**

**180.2.6464 UnderlyingProvisionCashSettlValueDateRelativeTo**

Specifies the anchor date when the cash settlement value date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingProvisionCashSettlValueDates**

**180.2.6465 UnderlyingProvisionCashSettlValueDates**

The UnderlyingProvisionCashSettlValueDates is a subcomponent within the UnderlyingProvisionGrp component used to report the cash settlement value date and time defined in the provision.

Name	Mult.	Type	Description
<b>UnderlyingProvisionCashSettlValue-Time</b>	[0..1]	LocalMktTime	
<b>UnderlyingProvisionCashSettlValue-TimeBusinessCenter</b>	[0..1]	String	

Name	Mult.	Type	Description
<a href="#">UnderlyingProvisionCashSettlValue-DateBusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the provisional cash settlement value date.
<a href="#">UnderlyingProvisionCashSettlValue-DateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the provisional cash settlement value date.
<a href="#">UnderlyingProvisionCashSettlValue-DateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingProvisionCashSettlValueDateOffsetPeriod</a>	[0..1]	int	Conditionally required when UnderlyingProvisionCashSettlValueDateOffsetUnit(42109) is specified.
<a href="#">UnderlyingProvisionCashSettlValueDateOffsetUnit</a>	[0..1]	CodeSet	Conditionally required when UnderlyingProvisionCashSettlValueDateOffsetPeriod(42108) is specified.
<a href="#">UnderlyingProvisionCashSettlValueDateOffsetDayType</a>	[0..1]	CodeSet	
<a href="#">UnderlyingProvisionCashSettlValueDateAdjusted</a>	[0..1]	LocalMktDate	

Used in groups: [UnderlyingProvisionGrp](#)

### 180.2.6466 UnderlyingProvisionCashSettlValueTime

A time specified in 24-hour format, e.g. 11am would be represented as 11:00:00. The time of the cash settlement valuation date when the cash settlement amount will be determined according to the cash settlement method if the parties have not otherwise been able to agree to the cash settlement amount.

Type: [LocalMktTime](#)

Used in components: [UnderlyingProvisionCashSettlValueDates](#)

### 180.2.6467 UnderlyingProvisionCashSettlValueTimeBusinessCenter

Identifies the business center calendar used with the provision's cash settlement valuation time.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **UnderlyingProvisionCashSettlValueDates**

### **180.2.6468 UnderlyingProvisionDateAdjusted**

The adjusted date of the provision.

Type: **LocalMktDate**

Used in groups: **UnderlyingProvisionGrp**

### **180.2.6469 UnderlyingProvisionDateBusinessCenter**

The business center calendar used to adjust the underlying instrument's provision's date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingProvisionDateBusinessCenterGrp**

### **180.2.6470 UnderlyingProvisionDateBusinessCenterGrp**

UnderlyingProvisionDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingProvisionGrp component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
<b>NoUnderlyingProvisionDateBusinessCenters</b>	[1..1]	NumInGroup	
<b>UnderlyingProvisionDateBusinessCenter</b>	[0..1]	String	Required if NoUnderlyingProvisionDateBusinessCenters(42190) > 0.

Used in groups: **UnderlyingProvisionGrp**



**180.2.6471 UnderlyingProvisionDateBusinessDayConvention**

The business day convention used to adjust the underlying instrument's provision's date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: **UnderlyingProvisionGrp**

**180.2.6472 UnderlyingProvisionDateTenorPeriod**

Time unit multiplier for the provision's tenor period.

Type: **int**

Used in groups: **UnderlyingProvisionGrp**

**180.2.6473 UnderlyingProvisionDateTenorUnit**

Time unit associated with the provision's tenor period.

Type: **String**

Allowed values in ProvisionDateTenorUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [UnderlyingProvisionGrp](#)

### 180.2.6474 UnderlyingProvisionDateUnadjusted

The unadjusted date of the provision.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingProvisionGrp](#)

### 180.2.6475 UnderlyingProvisionGrp

The UnderlyingProvisionGrp is a repeating subcomponent of the UnderlyingInstrument component used to detail additional terms and conditions associated with the instrument.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingProvisions</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingProvisionType</a>	[0..1]	CodeSet	Required if <a href="#">NoUnderlyingProvisions</a> (42149) > 0.
<a href="#">UnderlyingProvisionDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingProvisionDateBusinessDay-Convention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the <a href="#">UnderlyingDateAdjustment</a> component in <a href="#">UnderlyingInstrument</a> . The specified value would be specific to this instance of the instrument provisions.
<a href="#">UnderlyingProvisionDateBusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the <a href="#">UnderlyingDateAdjustment</a> component in <a href="#">UnderlyingInstrument</a> . The specified values would be specific to this instance of the instrument provisions.
<a href="#">UnderlyingProvisionDateAdjusted</a>	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
UnderlyingProvisionDateTenorPeriod	[0..1]	int	Conditionally required when UnderlyingProvisionDateTenorUnit(42155) is specified.
UnderlyingProvisionDateTenorUnit	[0..1]	CodeSet	Conditionally required when UnderlyingProvisionDateTenorPeriod(42154) is specified.
UnderlyingProvisionBreakFeeElection	[0..1]	CodeSet	
UnderlyingProvisionBreakFeeRate	[0..1]	Percentage	
UnderlyingProvisionCalculationAgent	[0..1]	CodeSet	
UnderlyingProvisionOptionSinglePartyBuyerSide	[0..1]	CodeSet	
UnderlyingProvisionOptionSinglePartySellerSide	[0..1]	CodeSet	
UnderlyingProvisionCashSettlValue-Dates	[0..1]	Component	
UnderlyingProvisionOptionExercise-Dates	[0..1]	Component	
UnderlyingProvisionOptionExpirationDate	[0..1]	Component	
UnderlyingProvisionOptionRelevantUnderlyingDate	[0..1]	Component	
UnderlyingProvisionOptionExerciseStyle	[0..1]	CodeSet	
UnderlyingProvisionOptionExerciseMultipleNotional	[0..1]	Amt	
UnderlyingProvisionOptionExerciseMinimumNotional	[0..1]	Amt	
UnderlyingProvisionOptionExerciseMaximumNotional	[0..1]	Amt	
UnderlyingProvisionOptionMinimumNumber	[0..1]	int	
UnderlyingProvisionOptionMaximumNumber	[0..1]	int	
UnderlyingProvisionOptionExerciseConfirmation	[0..1]	Boolean	
UnderlyingProvisionCashSettlPaymentDates	[0..1]	Component	
UnderlyingProvisionCashSettlMethod	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingProvisionCashSettlCur- rency	[0..1]	Currency	
UnderlyingProvisionCashSettlCur- rency2	[0..1]	Currency	
UnderlyingProvisionCashSettlQuote- Type	[0..1]	CodeSet	
UnderlyingProvisionCashSettlQuote- Source	[0..1]	Component	
UnderlyingProvisionText	[0..1]	String	
EncodedUnderlyingProvisionTextLen	[0..1]	Length	Must be set if EncodedProvisionText(40987) field is specified and must immediately precede it.
EncodedUnderlyingProvisionText	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingProvisionText(42170) field in the encoded format specified via the MessageEncoding(347) field.
UnderlyingProvisionParties	[0..*]	Group	

Used in components: [UnderlyingInstrument](#)

#### **180.2.6476 UnderlyingProvisionOptionExerciseBoundsFirstDateUnadjusted**

The unadjusted first date of a schedule. This can be used to restrict the range of exercise dates when they are relative.

Type: [LocalMktDate](#)

Used in components: [UnderlyingProvisionOptionExerciseDates](#)

#### **180.2.6477 UnderlyingProvisionOptionExerciseBoundsLastDateUnadjusted**

The unadjusted last date of a schedule. This can be used to restrict the range of exercise dates when they are relative.

Type: [LocalMktDate](#)

Used in components: [UnderlyingProvisionOptionExerciseDates](#)

**180.2.6478 UnderlyingProvisionOptionExerciseBusinessCenter**

The business center calendar used to adjust the underlying instrument's provision's option exercise date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingProvisionOptionExerciseBusinessCenterGrp**

**180.2.6479 UnderlyingProvisionOptionExerciseBusinessCenterGrp**

UnderlyingProvisionOptionExerciseBusinessCenterGrp is a repeating subcomponent within the UnderlyingProvisionOptionExerciseDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingProvisionOptionExerciseBusinessCenters	[1..1]	NumInGroup	
UnderlyingProvisionOptionExerciseBusinessCenter	[0..1]	String	Required if NoUnderlyingProvisionOptionExerciseBusinessCenters(42184) > 0.

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6480 UnderlyingProvisionOptionExerciseBusinessDayConvention**

The business day convention used to adjust the underlying instrument's provision's option exercise date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)

Code	Name	Description
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingProvisionOptionExerciseDates](#)

### 180.2.6481 UnderlyingProvisionOptionExerciseConfirmation

Used to indicate whether follow-up confirmation of exercise (written or electronic) is required following telephonic notice by the buyer to the seller or seller's agent.

Type: [Boolean](#)

Used in groups: [UnderlyingProvisionGrp](#)

### 180.2.6482 UnderlyingProvisionOptionExerciseDates

The UnderlyingProvisionOptionExerciseDates is a subcomponent within the UnderlyingProvisionGrp component used to report the option exercise dates and times defined in the provision.

Name	Mult.	Type	Description
<a href="#">UnderlyingProvisionOptionExercise-BusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the provisional option exercise date.
<a href="#">UnderlyingProvisionOptionExercise-BusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the provisional option exercise date.
<a href="#">UnderlyingProvisionOptionExercise-FixedDateGrp</a>	[0..*]	Group	

Name	Mult.	Type	Description
UnderlyingProvisionOptionExerciseEarliestDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingProvisionOptionExerciseEarliestDateUnit(42117) is specified.
UnderlyingProvisionOptionExerciseEarliestDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingProvisionOptionExerciseEarliestDatePeriod(42116) is specified.
UnderlyingProvisionOptionExerciseFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingProvisionOptionExerciseFrequencyUnit(42119) is specified.
UnderlyingProvisionOptionExerciseFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingProvisionOptionExerciseFrequencyPeriod(42118) is specified.
UnderlyingProvisionOptionExerciseStartDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingProvisionOptionExerciseStartDateRelativeTo	[0..1]	int	
UnderlyingProvisionOptionExerciseStartDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingProvisionOptionExerciseStartDateOffsetUnit(42123) is specified.
UnderlyingProvisionOptionExerciseStartDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingProvisionOptionExerciseStartDateOffsetPeriod(42122) is specified.
UnderlyingProvisionOptionExerciseStartDateOffsetDayType	[0..1]	CodeSet	
UnderlyingProvisionOptionExerciseStartDateAdjusted	[0..1]	LocalMktDate	
UnderlyingProvisionOptionExercisePeriodSkip	[0..1]	int	
UnderlyingProvisionOptionExerciseBoundsFirstDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingProvisionOptionExerciseBoundsLastDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingProvisionOptionExerciseEarliestTime	[0..1]	LocalMktTime	
UnderlyingProvisionOptionExerciseEarliestTimeBusinessCenter	[0..1]	String	
UnderlyingProvisionOptionExerciseLatestTime	[0..1]	LocalMktTime	

<b>UnderlyingProvisionOptionExercise- LatestTimeBusinessCenter</b>	[0..1]	String
--	--------	--------

---

Used in groups: **UnderlyingProvisionGrp**

#### **180.2.6483 UnderlyingProvisionOptionExerciseEarliestDateOffsetPeriod**

Time unit multiplier for the interval to the first (and possibly only) exercise date in the exercise period.

Type: **int**

Used in components: **UnderlyingProvisionOptionExerciseDates**

#### **180.2.6484 UnderlyingProvisionOptionExerciseEarliestDateOffsetUnit**

Time unit associated with the interval to the first (and possibly only) exercise date in the exercise period.

Type: **String**

Allowed values in ProvisionOptionExerciseEarliestDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingProvisionOptionExerciseDates**

#### **180.2.6485 UnderlyingProvisionOptionExerciseEarliestTime**

The earliest time at which notice of exercise can be given by the buyer to the seller (or seller's agent) i) on the expiration date, in the case of a European style option, (ii) on each bermuda option exercise date and the expiration date, in the case of a Bermuda style option the commencement date to, and including, the expiration date, in the case of an American option.

Type: **LocalMktTime**

Used in components: **UnderlyingProvisionOptionExerciseDates**



**180.2.6486 UnderlyingProvisionOptionExerciseEarliestTimeBusinessCenter**

Identifies the business center calendar used with the provision's earliest time for notice of exercise.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6487 UnderlyingProvisionOptionExerciseFixedDate**

A predetermined option exercise date, unadjusted or adjusted depending on UnderlyingProvisionOptionExerciseFixedDateType(42114).

Type: **LocalMktDate**

Used in groups: **UnderlyingProvisionOptionExerciseFixedDateGrp**

**180.2.6488 UnderlyingProvisionOptionExerciseFixedDateGrp**

The UnderlyingProvisionOptionExerciseFixedDateGrp is a repeating component within the UnderlyingProvisionOptionExerciseDates component used to report an array of unadjusted or adjusted fixed exercise dates.

Name	Mult.	Type	Description
NoUnderlyingProvisionOptionExerciseFixedDates	[1..1]	NumInGroup	
UnderlyingProvisionOptionExerciseFixedDate	[0..1]	LocalMktDate	Required if NoUnderlyingProvisionOptionExerciseFixedDates(42112) > 0.
UnderlyingProvisionOptionExerciseFixedDateType	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6489 UnderlyingProvisionOptionExerciseFixedDateType**

Specifies the type of date (e.g. adjusted for holidays).

Type: **int**

Allowed values in ProvisionOptionExerciseFixedDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: [UnderlyingProvisionOptionExerciseFixedDateGrp](#)

### **180.2.6490 UnderlyingProvisionOptionExerciseFrequencyPeriod**

Time unit multiplier for the frequency of subsequent exercise dates in the exercise period following the earliest exercise date. An interval of 1 day should be used to indicate an American style exercise frequency.

Type: [int](#)

Used in components: [UnderlyingProvisionOptionExerciseDates](#)

### **180.2.6491 UnderlyingProvisionOptionExerciseFrequencyUnit**

Time unit associated with the frequency of subsequent exercise dates in the exercise period following the earliest exercise date.

Type: [String](#)

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in components: [UnderlyingProvisionOptionExerciseDates](#)

**180.2.6492 UnderlyingProvisionOptionExerciseLatestTime**

For a Bermuda or American style option, the latest time on an exercise business day (excluding the expiration date) within the exercise period that notice can be given by the buyer to the seller or seller's agent. Notice of exercise given after this time will be deemed to have been given on the next exercise business day.

Type: **LocalMktTime**

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6493 UnderlyingProvisionOptionExerciseLatestTimeBusinessCenter**

Identifies the business center calendar used with the provision's latest time for notice of exercise.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6494 UnderlyingProvisionOptionExerciseMaximumNotional**

The maximum notional amount that can be exercised on a given exercise date.

Type: **Amt**

Used in groups: **UnderlyingProvisionGrp**

**180.2.6495 UnderlyingProvisionOptionExerciseMinimumNotional**

The minimum notional amount that can be exercised on a given exercise date.

Type: **Amt**

Used in groups: **UnderlyingProvisionGrp**

**180.2.6496 UnderlyingProvisionOptionExerciseMultipleNotional**

A notional amount which restricts the amount of notional that can be exercised when partial exercise or multiple exercise is applicable. The integral multiple amount defines a lower limit of notional that can be exercised and also defines a unit multiple of notional that can be exercised, i.e. only integer multiples of this amount can be exercised.

Type: **Amt**

Used in groups: **UnderlyingProvisionGrp**

#### **180.2.6497 UnderlyingProvisionOptionExercisePeriodSkip**

The number of periods in the referenced date schedule that are between each date in the relative date schedule. Thus a skip of 2 would mean that dates are relative to every second date in the referenced schedule. If present this should have a value greater than 1.

Type: **int**

Used in components: **UnderlyingProvisionOptionExerciseDates**

#### **180.2.6498 UnderlyingProvisionOptionExerciseStartDateAdjusted**

The adjusted first day of the exercise period for an American style option.

Type: **LocalMktDate**

Used in components: **UnderlyingProvisionOptionExerciseDates**

#### **180.2.6499 UnderlyingProvisionOptionExerciseStartDateOffsetDayType**

Specifies the day type of the provision's relative option exercise start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6500 UnderlyingProvisionOptionExerciseStartDateOffsetPeriod**

Time unit multiplier for the relative option exercise start date offset.

Type: **int**

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6501 UnderlyingProvisionOptionExerciseStartDateOffsetUnit**

Time unit associated with the relative option exercise start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6502 UnderlyingProvisionOptionExerciseStartDateRelativeTo**

Specifies the anchor date when the option exercise start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6503 UnderlyingProvisionOptionExerciseStartDateUnadjusted**

The unadjusted first day of the exercise period for an American style option.

Type: **LocalMktDate**

Used in components: **UnderlyingProvisionOptionExerciseDates**

**180.2.6504 UnderlyingProvisionOptionExerciseStyle**

The instrument provision's exercise style.

Type: **int**

Allowed values in ExerciseStyleCodeSet:

Code	Name	Description
0	European	European
1	American	American
2	Bermuda	Bermuda
99	Other	Other

Used in groups: **UnderlyingProvisionGrp**

**180.2.6505 UnderlyingProvisionOptionExpirationDateAdjusted**

The adjusted last date within an exercise period for an American style option. For a European style option it is the only date within the exercise period.

Type: **LocalMktDate**

Used in components: **UnderlyingProvisionOptionExpirationDate**

**180.2.6506 UnderlyingProvisionOptionExpirationDateBusinessCenter**

The business center calendar used to adjust the underlying instrument's provision's option expiration date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingProvisionOptionExpirationDateBusinessCenterGrp**

**180.2.6507 UnderlyingProvisionOptionExpirationDateBusinessCenterGrp**

UnderlyingProvisionOptionExpirationDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingProvisionOptionExpirationDate component. It is used to specify the set of business centers

whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingProvisionOptionExpirationDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingProvisionOptionExpirationDateBusinessCenter	[0..1]	String	Required if NoUnderlyingProvisionOptionExpirationDateBusinessCenters(42186) > 0.

Used in components: [UnderlyingProvisionOptionExpirationDate](#)

### 180.2.6508 UnderlyingProvisionOptionExpirationDateBusinessDayConvention

The business day convention used to adjust the underlying instrument's provision's option expiration date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingProvisionOptionExpirationDate](#)

### 180.2.6509 UnderlyingProvisionOptionExpirationDate

The UnderlyingProvisionOptionExerciseDate is a subcomponent within the UnderlyingProvisionGrp component used to report the option expiration date and times defined in the provision.

Name	Mult.	Type	Description
UnderlyingProvisionOptionExpirationDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingProvisionOptionExpirationDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the provisional option expiration date.
UnderlyingProvisionOptionExpirationDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the provisional option expiration date.
UnderlyingProvisionOptionExpirationDateRelativeTo	[0..1]	int	
UnderlyingProvisionOptionExpirationDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingProvisionOptionExpirationDateOffsetUnit(42137) is specified.
UnderlyingProvisionOptionExpirationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingProvisionOptionExpirationDateOffsetPeriod(42136) is specified.
UnderlyingProvisionOptionExpirationDateOffsetDayType	[0..1]	CodeSet	
UnderlyingProvisionOptionExpirationDateAdjusted	[0..1]	LocalMktDate	
UnderlyingProvisionOptionExpirationTime	[0..1]	LocalMktTime	
UnderlyingProvisionOptionExpirationTimeBusinessCenter	[0..1]	String	

Used in groups: **UnderlyingProvisionGrp**

### 180.2.6510 UnderlyingProvisionOptionExpirationDateOffsetDayType

Specifies the day type of the provision's relative option expiration date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:



Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingProvisionOptionExpirationDate](#)

#### **180.2.6511 UnderlyingProvisionOptionExpirationDateOffsetPeriod**

Time unit multiplier for the relative option expiration date offset.

Type: [int](#)

Used in components: [UnderlyingProvisionOptionExpirationDate](#)

#### **180.2.6512 UnderlyingProvisionOptionExpirationDateOffsetUnit**

Time unit associated with the relative option expiration date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingProvisionOptionExpirationDate](#)

#### **180.2.6513 UnderlyingProvisionOptionExpirationDateRelativeTo**

Specifies the anchor date when the option expiration date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingProvisionOptionExpirationDate**

#### **180.2.6514 UnderlyingProvisionOptionExpirationDateUnadjusted**

The unadjusted last day within an exercise period for an American style option. For a European style option it is the only day within the exercise period.

Type: **LocalMktDate**

Used in components: **UnderlyingProvisionOptionExpirationDate**

#### **180.2.6515 UnderlyingProvisionOptionExpirationTime**

The latest time for exercise on the expiration date.

Type: **LocalMktTime**

Used in components: **UnderlyingProvisionOptionExpirationDate**

#### **180.2.6516 UnderlyingProvisionOptionExpirationTimeBusinessCenter**

Identifies the business center calendar used with the provision's latest exercise time on expiration date.

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in components: **UnderlyingProvisionOptionExpirationDate**

#### **180.2.6517 UnderlyingProvisionOptionMaximumNumber**

The maximum number of options that can be exercised on a given exercise date. If the number is not specified, it means that the maximum number of options corresponds to the remaining unexercised options.

Type: **int**

Used in groups: **UnderlyingProvisionGrp**

**180.2.6518 UnderlyingProvisionOptionMinimumNumber**

The minimum number of options that can be exercised on a given exercise date.

Type: **int**

Used in groups: **UnderlyingProvisionGrp**

**180.2.6519 UnderlyingProvisionOptionRelevantUnderlyingDateAdjusted**

The adjusted date on the underlying set by the exercise of an option. What this date is depends on the option (e.g. in a swaption it is the swap effective date, in an extendible/cancelable provision it is the swap termination date).

Type: **LocalMktDate**

Used in components: **UnderlyingProvisionOptionRelevantUnderlyingDate**

**180.2.6520 UnderlyingProvisionOptionRelevantUnderlyingDateBizDayConvention**

The business day convention used to adjust the underlying instrument provision's option underlying date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: **UnderlyingProvisionOptionRelevantUnderlyingDate**

**180.2.6521 UnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenter**

The business center calendar used to adjust the underlying instrument's provision's option underlying date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenterGrp**

**180.2.6522 UnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenterGrp**

UnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingProvisionOptionRelevantUnderlyingDate component. It is used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
NoUnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenter	[0..1]	String	Required if NoUnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenters(42188) > 0.

Used in components: **UnderlyingProvisionOptionRelevantUnderlyingDate**

**180.2.6523 UnderlyingProvisionOptionRelevantUnderlyingDate**

The UnderlyingProvisionOptionRelevantUnderlyingDate is a subcomponent within the UnderlyingProvisionGrp component used to report the option relevant underlying date defined in the provision.

Name	Mult.	Type	Description
UnderlyingProvisionOptionRelevantUnderlyingDateUnadjusted	[0..1]	LocalMktDate	

Name	Mult.	Type	Description
UnderlyingProvisionOptionRelevantUnderlyingDateBizDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the provisional option relevant underlying date.
UnderlyingProvisionOptionRelevantUnderlyingDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the provisional option relevant underlying date.
UnderlyingProvisionOptionRelevantUnderlyingDateRelativeTo	[0..1]	int	
UnderlyingProvisionOptionRelevantUnderlyingDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingProvisionOptionRelevantUnderlyingDateOffsetUnit(42146) is specified.
UnderlyingProvisionOptionRelevantUnderlyingDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingProvisionOptionRelevantUnderlyingDateOffsetPeriod(42145) is specified.
UnderlyingProvisionOptionRelevantUnderlyingDateOffsetDayType	[0..1]	CodeSet	
UnderlyingProvisionOptionRelevantUnderlyingDateAdjusted	[0..1]	LocalMktDate	

Used in groups: **UnderlyingProvisionGrp**

### 180.2.6524 UnderlyingProvisionOptionRelevantUnderlyingDateOffsetDayType

Specifies the day type of the provision's relative option relevant underlying date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business

Code	Name	Description
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingProvisionOptionRelevantUnderlyingDate](#)

#### 180.2.6525 UnderlyingProvisionOptionRelevantUnderlyingDateOffsetPeriod

Time unit multiplier for the relative option relevant underlying date offset.

Type: [int](#)

Used in components: [UnderlyingProvisionOptionRelevantUnderlyingDate](#)

#### 180.2.6526 UnderlyingProvisionOptionRelevantUnderlyingDateOffsetUnit

Time unit associated with the relative option relevant underlying date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingProvisionOptionRelevantUnderlyingDate](#)

#### 180.2.6527 UnderlyingProvisionOptionRelevantUnderlyingDateRelativeTo

Specifies the anchor date when the date relevant to the underlying trade on exercise is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [UnderlyingProvisionOptionRelevantUnderlyingDate](#)

**180.2.6528 UnderlyingProvisionOptionRelevantUnderlyingDateUnadjusted**

The unadjusted date on the underlying set by the exercise of an option. What this date is depends on the option (e.g. in a swaption it is the swap effective date, in an extendible/cancelable provision it is the swap termination date).

Type: **LocalMktDate**

Used in components: **UnderlyingProvisionOptionRelevantUnderlyingDate**

**180.2.6529 UnderlyingProvisionOptionSinglePartyBuyerSide**

If optional early termination is not available to both parties then this component identifies the buyer of the option through its side of the trade.

Type: **int**

Allowed values in ProvisionOptionSinglePartyBuyerSideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **UnderlyingProvisionGrp**

**180.2.6530 UnderlyingProvisionOptionSinglePartySellerSide**

If optional early termination is not available to both parties then this component identifies the seller of the option through its side of the trade.

Type: **int**

Allowed values in ProvisionOptionSinglePartyBuyerSideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **UnderlyingProvisionGrp**

**180.2.6531 UnderlyingProvisionParties**

UnderlyingProvisionParties is a repeating component within the UnderlyingProvisionGrp component used to report the parties identified in the contract provision.

Name	Mult.	Type	Description
NoUnderlyingProvisionPartyIDs	[1..1]	NumInGroup	
UnderlyingProvisionPartyID	[0..1]	String	Required if NoUnderlyingProvisionPartyIDs(42173) > 0.
UnderlyingProvisionPartyIDSource	[0..1]	CodeSet	Required if NoUnderlyingProvisionPartyIDs(42173) > 0.
UnderlyingProvisionPartyRole	[0..1]	CodeSet	Required if NoUnderlyingProvisionPartyIDs(42173) > 0.
UnderlyingProvisionPartyRoleQualifier	[0..1]	CodeSet	
UnderlyingProvisionPtysSubGrp	[0..*]	Group	

Used in groups: **UnderlyingProvisionGrp**

**180.2.6532 UnderlyingProvisionPartyID**

The party identifier for the payment settlement party.

Type: **String**

Used in groups: **UnderlyingProvisionParties**

**180.2.6533 UnderlyingProvisionPartyIDSource**

Identifies the class or source of the UnderlyingProvisionPartyID(42174) value.

Type: **char**

Allowed values in PartyIDSourceCodeSet:

Code	Name	Description
1	KoreanInvestorID	Korean Investor ID. Also known as the Investor Registration Certificate (IRC) issued by Korea's Financial Supervisory Service (FSS), an identifier tied into the depository for settlement and record keeping.



Code	Name	Description
6	UKNationalInsuranceOrPension-Number	UK National Insurance or Pension Number
B	BIC	BIC (Bank Identification Code - SWIFT managed) code (ISO9362 - See "Appendix 6-B")
I	ISITCAcronym	Directed broker three character acronym as defined in ISITC "ETC Best Practice" guidelines document
2	TaiwaneseForeignInvestorID	Taiwanese Qualified Foreign Investor ID QFII/FID
7	USSocialSecurityNumber	US Social Security Number
C	GeneralIdentifier	Generally accepted market participant identifier (e.g. NASD mnemonic)
3	TaiwaneseTradingAcct	Taiwanese Trading Acct
8	USEmployerOrTaxIDNumber	US Employer or Tax ID Number
D	Proprietary	Proprietary / Custom code. Custom ID schema used between counterparties, trading platforms and repositories.
4	MalaysianCentralDepository	Malaysian Central Depository (MCD) number
9	AustralianBusinessNumber	Australian Business Number
E	ISOCountryCode	ISO Country Code
5	ChineseInvestorID	Chinese Investor ID
A	AustralianTaxFileNumber	Australian Tax File Number
F	SettlementEntityLocation	Settlement Entity Location (note if Local Market Settlement use "E=ISO Country Code") (see "Appendix 6-G" for valid values)
G	MIC	Market Identifier Code (ISO 10383) MIC
J	TaxID	Tax ID
H	CSDParticipant	CSD participant/member code (e.g. Euroclear, DTC, CREST or Kassenverein number)
K	AustralianCompanyNumber	Australian Company Number
L	AustralianRegisteredBodyNumber	Australian Registered Body Number
M	CFTCReportingFirmIdentifier	CFTC reporting firm identifier
N	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
O	InterimIdentifier	Interim identifier. An interim entity identifier assigned by a regulatory agency prior to an LEI (ISO 17442) being assigned.
P	ShortCodeIdentifier	Short code identifier. A generic means for trading venues, brokers, investment managers to convey a bilaterally agreed upon "short hand" code for an identifier that is a reference to a mapping between the parties.

Code	Name	Description
Q	NationalIDNaturalPerson	National ID of natural person. An identification number generally assigned by a government authority or agency to a natural person which is unique to the person it is assigned to. Examples include, but not limited to, "social security number", "pension number".
R	IndiaPermanentAccountNumber	India Permanent Account Number. Also referred to as PAN ID. An identifier issued by the Income Tax Department of India.
S	FDID	Firm designated identifier. Also referred to as FDID. A unique identifier required by the SEC for each trading account designated by Industry Members for purposes of reporting to CAT (Consolidated Audit Trail).
T	SPSAID	Special Segregated Account ID. Also referred to as SPSA ID. The Special Segregated Account identifier issued by Hong Kong Exchanges and Clearing.
U	MasterSPSAID	Master Special Segregated Account ID. Also referred to as Master SPSA ID. The master identifier issued by Hong Kong Exchanges and Clearing for the aggregation of SPSA IDs.
V	KoreaShortSellingRegistrationNumber	Korea Short Selling Registration Number. Short selling registration number assigned by Korea's Financial Supervisory Service (FSS) for institutions placing eligible orders under Korea's Financial Services Commission's "Short Sale Reform Measures".

Used in groups: **UnderlyingProvisionParties**

### 180.2.6534 UnderlyingProvisionPartyRole

Identifies the type or role of UnderlyingProvisionPartyID(42174) specified.

Type: **int**

Allowed values in PartyRoleCodeSet:

Code	Name	Description
1	ExecutingFirm	Executing Firm (formerly FIX 4.2 ExecBroker)
2	BrokerOfCredit	Broker of Credit (formerly FIX 4.2 BrokerOfCredit)
3	ClientID	Client ID (formerly FIX 4.2 ClientID)
4	ClearingFirm	Clearing Firm (formerly FIX 4.2 ClearingFirm)
5	InvestorID	Investor ID

Code	Name	Description
6	IntroducingFirm	Introducing Firm
7	EnteringFirm	Entering Firm
8	Locate	Locate / Lending Firm (for short-sales)
9	FundManagerClientID	Fund Manager Client ID (for CIV)
10	SettlementLocation	Settlement Location (formerly FIX 4.2 SettlLocation)
11	OrderOriginationTrader	Order Origination Trader (associated with Order Origination Firm - i.e. trader who initiates/submits the order)
12	ExecutingTrader	Executing Trader (associated with Executing Firm - actually executes)
13	OrderOriginationFirm	Order Origination Firm (e.g. buy-side firm)
14	GiveupClearingFirmDepr	Giveup Clearing Firm (firm to which trade is given up)
15	CorrespondantClearingFirm	Correspondant Clearing Firm
16	ExecutingSystem	Executing System
17	ContraFirm	Contra Firm
18	ContraClearingFirm	Contra Clearing Firm
19	SponsoringFirm	Sponsoring Firm
20	UnderlyingContraFirm	Underlying Contra Firm
21	ClearingOrganization	Clearing Organization
22	Exchange	Exchange. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
24	CustomerAccount	Customer Account
25	CorrespondentClearingOrganization	Correspondent Clearing Organization
26	CorrespondentBroker	Correspondent Broker
27	Buyer	Buyer/Seller (Receiver/Deliverer)
28	Custodian	Custodian
29	Intermediary	Intermediary
30	Agent	Agent
31	SubCustodian	Sub-custodian
32	Beneficiary	Beneficiary
33	InterestedParty	Interested party
34	RegulatoryBody	Regulatory body. In the context of regulatory reporting, this identifies the regulator the trade is being reported to.
35	LiquidityProvider	Liquidity provider
36	EnteringTrader	Entering trader
37	ContraTrader	Contra trader

Code	Name	Description
38	PositionAccount	Position account. The account which positions are maintained. Typically represents the aggregation of one or more customer accounts.
39	ContraInvestorID	Contra Investor ID
40	TransferToFirm	Transfer to Firm
41	ContraPositionAccount	Contra Position Account
42	ContraExchange	Contra Exchange
43	InternalCarryAccount	Internal Carry Account
44	OrderEntryOperatorID	Order Entry Operator ID
45	SecondaryAccountNumber	Secondary Account Number
46	ForeignFirm	Foreign Firm
47	ThirdPartyAllocationFirm	Third Party Allocation Firm
48	ClaimingAccount	Claiming Account
49	AssetManager	Asset Manager
50	PledgorAccount	Pledgor Account
51	PledgeeAccount	Pledgee Account
52	LargeTraderReportableAccount	Large Trader Reportable Account
53	TraderMnemonic	Trader mnemonic
54	SenderLocation	Sender Location
55	SessionID	Session ID
56	AcceptableCounterparty	Acceptable Counterparty
57	UnacceptableCounterparty	Unacceptable Counterparty
58	EnteringUnit	Entering Unit
59	ExecutingUnit	Executing Unit
60	IntroducingBroker	Introducing Broker
61	QuoteOriginator	Quote originator
62	ReportOriginator	Report originator
63	SystematicInternaliser	Systematic internaliser (SI)
64	MultilateralTradingFacility	Multilateral Trading Facility (MTF). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
65	RegulatedMarket	Regulated Market (RM). Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
66	MarketMaker	Market Maker
67	InvestmentFirm	Investment Firm

Code	Name	Description
68	HostCompetentAuthority	Host Competent Authority (Host CA)
69	HomeCompetentAuthority	Home Competent Authority (Home CA)
70	CompetentAuthorityLiquidity	Competent Authority of the most relevant market in terms of liquidity (CAL)
71	CompetentAuthorityTransactionVenue	Competent Authority of the Transaction (Execution) Venue (CATV)
72	ReportingIntermediary	Reporting intermediary. The medium or vendor used to report to a regulator, non-regulatory agency or data repository.
73	ExecutionVenue	Execution Venue. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
74	MarketDataEntryOriginator	Market data entry originator
75	LocationID	Location ID
76	DeskID	Desk ID
77	MarketDataMarket	Market data market
78	AllocationEntity	Allocation Entity
79	PrimeBroker	Prime Broker providing General Trade Services
80	StepOutFirm	Step-Out Firm (Prime Broker)
81	BrokerClearingID	Broker clearing identifier
82	CentralRegistrationDepository	Central Registration Depository (CRD)
83	ClearingAccount	Clearing Account
84	AcceptableSettlingCounterparty	Acceptable Settling Counterparty
85	UnacceptableSettlingCounterparty	Unacceptable Settling Counterparty
86	CLSMemberBank	CLS Member Bank
87	InConcertGroup	In Concert Group
88	InConcertControllingEntity	In Concert Controlling Entity
89	LargePositionsReportingAccount	Large Positions Reporting Account
90	SettlementFirm	Settlement Firm
91	SettlementAccount	Settlement account. The account to which individual payment obligations are aggregated for netting and funds movement. Typically represents the aggregation of many margin (performance bond) accounts.
92	ReportingMarketCenter	Reporting Market Center
93	RelatedReportingMarketCenter	Related Reporting Market Center
94	AwayMarket	Away Market. Identify using PartyIDSource(tag 447) = G (Market Identifier Code) if the MIC exists.
95	GiveupTradingFirm	Give-up (trading) firm

Code	Name	Description
96	TakeupTradingFirm	Take-up (trading) firm
97	GiveupClearingFirm	Give-up clearing firm
98	TakeupClearingFirm	Take-up clearing firm
99	OriginatingMarket	Originating Market. Identifies the Market using PartyIDSource(tag 447) = G (Market Identifier Code) where an order originated in the event that the order is sent to an alternative market for execution. Serves as an inverse of an away market.
100	MarginAccount	Margin account. Also referred to as "performance bond account". The margin account is the calculated margin requirements. Typically represents the aggregation of one or more position accounts.
101	CollateralAssetAccount	Collateral asset account. The account at which individual collateral assets are maintained. Typically, although not always, one-for-one with the settlement account.
102	DataRepository	Data repository. Multiple instances of this PartyRole may appear for reporting purposes.
103	CalculationAgent	Calculation agent
104	ExerciseNoticeSender	Sender of exercise notice
105	ExerciseNoticeReceiver	Receiver of exercise notice
106	RateReferenceBank	Rate reference bank. The bank providing the reference rate. Multiple instance of this PartyRole may appear.
107	Correspondent	Correspondent
109	BeneficiaryBank	Beneficiary's bank or depository institution. The institution in which the beneficiary, a person or an entity, has their account with. The institution may be a bank or non-bank institution.
110	Borrower	Borrower
111	PrimaryObligator	Primary obligator
112	Guarantor	Guarantor
113	ExcludedReferenceEntity	Excluded reference entity
114	DeterminingParty	Determining party
115	HedgingParty	Hedging party
116	ReportingEntity	Reporting entity. The entity that is reporting the information.
117	SalesPerson	Sales person. The person who is involved in the sales activities for their firm.
118	Operator	Operator. The person who has the capabilities and authorization to take certain actions; for example, setting entitlements, etc.

Code	Name	Description
119	CSD	Central Securities Depository (CSD)
120	ICSD	International Central Securities Depository (ICSD)
121	TradingSubAccount	Trading sub-account. Example of sub-accounts include a clearing account that has multiple trading sub-accounts, a trading account that has multiple trading sub-accounts belonging to different trading firms.
122	InvestmentDecisionMaker	Investment decision maker. In the context of ESMA RTS reporting, this is used to specify party responsible for the investment decision. See RTS 24, Annex, Table 2, Field 4.
123	PublishingIntermediary	Publishing intermediary. The medium or vendor used to publish to the market.
124	CSDParticipant	Central Securities Depository (CSD) Participant. In the context of EU SFTR reporting the identifier of the CSD participant or indirect participant of the reporting counterparty. Where both the CSD participant and indirect participant are involved in the transaction this should identify the indirect participant.
125	Issuer	Issuer. The issuer of the security.
126	ContraCustomerAccount	Contra Customer Account. Same as PartyRole(452) = 24 (Customer Account) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
127	ContraInvestmentDecisionMaker	Contra Investment Decision Maker. Same as PartyRole(452) = 122 (Investment Decision Maker) but for the counterparty. Can be used whenever the parties component is not nested in a repeating group representing both sides.
128	AuthorizingPerson	Authorizing person. In the context of MiFIR, this value is used to identify the person authorizing algorithms within a trading firm.

Used in groups: **UnderlyingProvisionParties**

### 180.2.6535 UnderlyingProvisionPartyRoleQualifier

Used to further qualify the value of UnderlyingProvisionPartyRole(42176).

Type: **int**

Allowed values in PartyDetailRoleQualifierCodeSet:

Code	Name	Description
0	Agency	Agency
1	Principal	Principal
2	RisklessPrincipal	Riskless principal
3	GeneralClearingMember	General clearing member
30	ExchangeOrderSubmitter	Exchange order submitter. Used to identify original or initial exchange order submitting broker when party role "1" (Executing Firm) appears more than once.
4	IndividualClearingMember	Individual clearing member
5	PreferredMarketMaker	Preferred market maker. Market maker getting a part of the matched quantity before primary or default market maker.
6	DirectedMarketMaker	Directed market maker. Single market maker to handle the order provided.
7	Bank	Bank
8	Hub	Hub. Indicates that the Intermediary party is a hub system or service provider.
9	PrimaryTrdRepository	Primary trade repository. Used to differentiate the principal trade repository from the Original or Additional trade repositories when there are multiple trade repositories being reported.
10	OrigTrdRepository	Original trade repository. Used to identify the trade repository to which the trade was originally reported if different from the current repository to which the trade is being reported.
11	AddtnlIntlTrdRepository	Additional international trade repository. Used with InternationalSwapIndicator(2526) to identify the trade repository that is in addition to the local swaps data repository as required by U.S. law.
12	AddtnlDomesticTrdRepository	Additional domestic trade repository. Used with MixedSwapIndicator(1929) to identify the trade repository that is in addition to the current trade repository when the assets in the swap are subject to two different domestic regulators.
13	RelatedExchange	Related exchange
14	OptionsExchange	Options exchange
15	SpecifiedExchange	Specified exchange
16	ConstituentExchange	Constituent exchange.
17	ExemptFromTradeReporting	Exempt from trade reporting. In the context of FINRA TRACE reporting requirements, this is used to indicate the ATS has been granted a regulatory exemption from reporting.
18	Current	Current. Can be used to convey an existing party identifier for the same party role in a single message.



Code	Name	Description
19	New	New. Can be used to convey a future party identifier for the same party role in a single message.
20	DesignatedSponsor	Designated sponsor. Market maker jointly providing liquidity for the same security with other market makers.
21	Specialist	Specialist. Market maker being the only one providing liquidity for a security.
22	Algorithm	Algorithm
23	FirmOrLegalEntity	Firm or legal entity
24	NaturalPerson	Natural person
25	RegularTrader	Regular trader. Standard trader profile.
26	HeadTrader	Head trader. Senior trader leading a group of regular traders.
27	Supervisor	Supervisor. Administrative user that has only limited rights for normal trading but possibly special rights for emergency actions.
28	TriParty	Tri-party. In the context of EU SFTR reporting, identifies the third party, not necessarily the custodian, to which the reporting counterparty has outsourced the post-trade processing of an SFT (if applicable).
29	Lender	Lender. In the context of EU SFTR reporting, identifies the agent lender involved in the securities lending transaction.

Used in groups: **UnderlyingProvisionParties**

#### **180.2.6536 UnderlyingProvisionPartySubID**

Underlying provision party sub-identifier, if applicable for UnderlyingProvisionPartyID(42174).

Type: **String**

Used in groups: **UnderlyingProvisionPtysSubGrp**

#### **180.2.6537 UnderlyingProvisionPartySubIDType**

The type of UnderlyingProvisionPartySubID(42178).

Type: **int**

Allowed values in PartySubIDTypeCodeSet:

Code	Name	Description
1	Firm	Firm
2	Person	Person
3	System	System
4	Application	Application
5	FullLegalNameOfFirm	Full legal name of firm
6	PostalAddress	Postal address
7	PhoneNumber	Phone number
8	EmailAddress	Email address
9	ContactName	Contact name
10	SecuritiesAccountNumber	Securities account number (for settlement instructions)
11	RegistrationNumber	Registration number (for settlement instructions and confirmations)
12	RegisteredAddressForConfirmation	Registered address (for confirmation purposes)
13	RegulatoryStatus	Regulatory status (for confirmation purposes)
14	RegistrationName	Registration name (for settlement instructions)
15	CashAccountNumber	Cash account number (for settlement instructions)
16	BIC	BIC
17	CSDParticipantMemberCode	CSD participant member code
18	RegisteredAddress	Registered address
19	FundAccountName	Fund account name
20	TelexNumber	Telex number
21	FaxNumber	Fax number
22	SecuritiesAccountName	Securities account name
23	CashAccountName	Cash account name
24	Department	Department
25	LocationDesk	Location desk
26	PositionAccountType	Position account type
27	SecurityLocateID	Security locate ID
28	MarketMaker	Market maker
29	EligibleCounterparty	Eligible counterparty
30	ProfessionalClient	Professional client
31	Location	Location
32	ExecutionVenue	Execution venue
33	CurrencyDeliveryIdentifier	Currency delivery identifier

Code	Name	Description
34	AddressCity	Address City
35	AddressStateOrProvince	Address State/Province
36	AddressPostalCode	Address Postal Code
37	AddressStreet	Address Street
38	AddressISOCountryCode	Address Country (ISO country code)
39	ISOCountryCode	ISO country code
40	MarketSegment	Market segment
41	CustomerAccountType	Customer account type
42	OmnibusAccount	Omnibus account
43	FundsSegregationType	Funds segregation type
44	GuaranteeFund	Guarantee fund. Identifies a guarantee fund related to an account. Used when one account has multiple funds of collateral, each guaranteeing different positions. Can be used for PartyRole(452) = Customer Account(24).
45	SwapDealer	Swap dealer. The US regulator's defined term for identifying the trade counterparty as "any person who holds itself out as a dealer in swaps, makes a market in swaps, regularly enters into swaps with counterparties as an ordinary course of business for its own account, or engages in activity causing itself to be commonly known in the trade as a dealer or market maker in swaps".
46	MajorParticipant	Major participant. When PartySubID(523)=Y the counterparty is not the swap dealer but is a major swap participant as defined in the regulations.
47	FinancialEntity	Financial entity. When PartySubID(523)=Y the counterparty is neither a swap dealer nor a major swap participant but is a financial entity as defined in the regulations.
48	USPerson	U.S. person. A legal term referring to any U.S. person or legal entity anywhere in the world that should be taxed under U.S. law.
49	ReportingEntityIndicator	Reporting entity indicator. Indicates the entity obligated or delegated to report to their regulator, a non-regulatory agency or data repository. Set PartySubID(523)=Y if true.
50	ElectedClearingRequirementException	Elected clearing requirement exception
51	BusinessCenter	Business center.
52	ReferenceText	Reference text
53	ShortMarkingExemptAccount	Short-marking exempt account

Code	Name	Description
54	ParentFirmIdentifier	Parent firm identifier. Implementation-specific identifier of this party's parent entity.
55	ParentFirmName	Parent firm name. Full name of this party's parent entity.
56	DealIdentifier	Deal identifier. The internal identifier assigned to the trade by this party, particularly by a Clearing Organization.
57	SystemTradeID	System trade identifier
58	SystemTradeSubID	System trade sub-identifier
59	FCMCode	Futures Commission Merchant (FCM) code. The FCM's code or identifier in relation to the PartyRole(452). For example, if PartyRole(452) is the exchange or clearinghouse, the FCM code/ID specified in PartySubID(523) is the FCM's identifier at the exchange or clearinghouse.
60	DlvryTrmlCode	Delivery terminal customer account/code. Usually used for gas delivery to identify whose account the gas is allocated to at the delivery terminal. Often referred to as "HUB" code.
61	VolntyRptEntity	Voluntary reporting entity. The entity voluntarily reporting the trade to the regulator. Set PartySubID(523)=Y if true.
62	RptObligJursdctn	Reporting obligation jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the reporting jurisdiction to which the party is obligated to report.
63	VolntyRptJursdctn	Voluntary reporting jurisdiction. For a trade that falls under multiple jurisdictions this may be used to identify, through PartySubID(523), the regulatory jurisdiction to which the party is submitting a voluntary report.

Code	Name	Description
64	CompanyActivities	Company activities. For regulatory reporting. ID values include: A = Assurance undertaking authorized in accordance with Directive 2002/83/EC C=Credit institution authorized in accordance with Directive 2006/48/EC F=Investment firm in accordance with Directive 2004/39/EC I=Insurance undertaking authorized in accordance with Directive 73/239/EC L=Alternative investment fund managed by AIFMs authorized or registered in accordance with Directive 2011/61/EC O=Institution for occupational retirement provision within the meaning of Article 6(a) of Directive 2003/41/EC R=Reinsurance undertaking authorized in accordance with Directive 2005/68/EC U=UCITS and its management company, authorized in accordance with Directive 2009/65/EC or blank in case of coverage by LEI or in case of non-financial counterparties. In the context of EU SFTR reporting use the appropriate 4- or 1-character code noted in the regulations. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
65	EEAreaDomiciled	European Economic Area domiciled. ID values: Y or N
66	ContractLinked	Contract linked to commercial or treasury financing for this counterparty. ID values: Y or N
67	ContractAbove	Contract above clearing threshold for this counterparty. ID values: Y or N
68	VolntyRptPty	Voluntary reporting party. When PartySubID(523)=Y, identifies that the trading party is reporting voluntarily when VoluntaryRegulatoryReport(1935)=Y.
69	EndUser	End user. When PartySubID(523)=Y, the counterparty is neither the swap dealer, major swap participant nor financial entity as defined in the regulations.
70	LocationOrJurisdiction	Location or jurisdiction. One or more instances may be used in combination with PartySubIDType(803) = 49 (Reporting entity indicator) or 102 (Data repository) to identify the jurisdiction, countries, regions or provinces for which the party is a reporting entity or data repository when that characteristic is ambiguous or where there are multiple locations. The party sub-ID value is either a jurisdiction acronym, a 2-character ISO 3166 country code, or a hyphenated combination of the country code and the standard post-office abbreviation for province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.

Code	Name	Description
71	DerivativesDealer	Derivatives dealer. Indicates whether the party is a derivatives dealer or not (Y/N). The Canadian regulator's defined term for identifying the trade counterparty as "a person or company engaging in or holding himself, herself or itself out as engaging in the business of trading in derivatives in Ontario as principal or agent".
72	Domicile	Domicile. Country and optionally province, state or region of domicile. The party sub-ID value is either a 2-character ISO 3166 country code or a hyphenated combination of the country code and the standard post-office abbreviation of province, state or region if necessary. E.g. "US" for United States or "CA-QC" for Quebec Canada.
73	ExemptFromRecognition	Exempt from recognition. Used with party role 21 "Clearing Organization" to indicate exemption (Y/N). Identifies a clearing agency as exempt from oversight in Ontario, i.e. one that 1) only provides limited services and does not present significant risks or 2) is foreign-based, intends to operate in Ontario but is subject to regulatory oversight in another jurisdiction.
74	Payer	Payer. Identifies the party as the payer of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
75	Receiver	Receiver. Identifies the party as the receiver of a particular payment stream or bullet payment by quoting the stream's StreamDesc(40051) (or LegStreamDesc(40243) or UnderlyingStreamDesc(40542)) or payment's PaymentDesc(43087) in the associated party sub-identifier field.
76	SystematicInternaliser	Systematic Internaliser (SI). In the context of ESMA reporting, this is used to indicate whether the specified party is a Systematic Internaliser or not for the security defined in the Instrument component (Y/N).
77	PublishingEntityIndicator	Publishing entity indicator. Indicates the entity obligated or delegated to publish to the market. Set PartySubID(523)=Y if true.
78	FirstName	First name. The first name(s) of a natural person. If multiple names, separate entries by a comma.
79	Surname	Surname. The surname(s) or lastname(s) of a natural person. If multiple names, separate entries by a comma.

Code	Name	Description
80	DateOfBirth	Date of birth. The date of birth of a natural person in the format YYYYMMDD.
81	OrderTransmittingFirm	Order transmitting firm. Identifies whether the party specified in PartyID(448) is the firm that transmitted the order. In the context of RTS 22 Article 4, when "true" the PartySubID(523)=Y shall be set "by the transmitting firm within the transmitting firm's report where conditions for transmission specified in Article 4 were not satisfied."
82	OrderTransmittingFirmBuyer	Order transmitting firm for buyer. Identifies the firm that transmitted the order for the buyer. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the buyer. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
83	OrderTransmitterSeller	Order transmitter for seller. Identifies the order transmitting firm for the seller. In the context of ESMA RTS 22, PartySubID(523)=Y is used to indicate the firm identified in PartyID(448) is the firm that transmitted the order for the seller. "This shall be populated by the receiving firm within the receiving firm's report with the identification code provided by the transmitting firm."
84	LegalEntityIdentifier	Legal Entity Identifier (ISO 17442) LEI
85	SubSectorClassification	Sub-sector classification. Supplemental to party sub-ID type "64" (Company activities) for regulatory reporting. For EU SFTR reporting use the appropriate 4-character code noted in the regulations applying the conditional association rules. See SFTR ITS "Commission Implementing Regulation (EU) 2019/363" Annexes 1 and 2 for values.
86	PartySide	Party side. May be used, when appropriate, to explicitly indicate the transaction side of the party, e.g. Buyer, Seller, Lender, Borrower, Maker, Taker, etc. in the ID. In the context of EU SFTR reporting, use values as required by SFTR, "GIVE" and "TAKE" in the ID, to identify collateral giver and taker.
87	LegalRegistrationCountry	Legal registration country. ISO Country Code where the registered office of the party is located as specified in the LEI reference data.

Used in groups: [UnderlyingProvisionPtysSubGrp](#)

**180.2.6538 UnderlyingProvisionPtysSubGrp**

UnderlyingProvisionPtysSubGrp is a repeating component within the UnderlyingProvisionParties component used to extend information to be reported for the party.

Name	Mult.	Type	Description
NoUnderlyingProvisionPartySubIDs	[1..1]	NumInGroup	
UnderlyingProvisionPartySubID	[0..1]	String	Required if NoUnderlyingProvisionPartySubIDs(42177) > 0.
UnderlyingProvisionPartySubIDType	[0..1]	CodeSet	Required if NoUnderlyingProvisionPartySubIDs(42177) > 0.

Used in groups: [UnderlyingProvisionParties](#)

**180.2.6539 UnderlyingProvisionText**

Free form text to specify additional information or enumeration description when a standard value does not apply.

Type: [String](#)

Used in groups: [UnderlyingProvisionGrp](#)

**180.2.6540 UnderlyingProvisionType**

Type of provision.

Type: [int](#)

Allowed values in ProvisionTypeCodeSet:

Code	Name	Description
0	MandatoryEarlyTermination	Mandatory early termination
1	OptionalEarlyTermination	Optional early termination
2	Cancelable	Cancelable
3	Extendable	Extendable. The contract can be extended by either party usually with a specific time notice prior to the expiry date. In the context of EU SFTR reporting this corresponds to "termination optionality" code "ETSB".



Code	Name	Description
4	MutualEarlyTermination	Mutual early termination
5	Evergreen	Evergreen. The contract automatically renews after the expiry date until one party gives the other notice to terminate. In the context of EU SFTR reporting this corresponds to "termination optionality" code "EGRN".
6	Callable	Callable. Contract is callable.
7	Puttable	Puttable. Contract is puttable.

Used in groups: [UnderlyingProvisionGrp](#)

### 180.2.6541 UnderlyingPutOrCall

Indicates whether an underlying option contract is a put, call, chooser or undetermined.

Type: [int](#)

Allowed values in PutOrCallCodeSet:

Code	Name	Description
0	Put	Put. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate receiver or into a CDS contract as a seller of protection or for the case of a Floor.
1	Call	Call. Also used for the case in which the buyer of a Swaption has the right to enter into an IRS contract as a fixed-rate payer or into a CDS contract as a buyer of protection or for the case of a Cap.
2	Other	Other. In the context of ESMA RTS 22 reporting, this value may be used when, at the time of execution, the option right cannot be determined.
3	Chooser	Chooser. Indicates that the option buyer may choose to buy or sell the underlying security on exercise or if a Swaption to pay or receive the underlying IRS cash flow stream or to buy or sell CDS protection.

Used in components: [UnderlyingInstrument](#)

**180.2.6542 UnderlyingPx**

Underlying price associate with a derivative instrument.

Type: **Price**

Used in components: **UnderlyingInstrument**

**180.2.6543 UnderlyingQty**

Unit amount of the underlying security (par, shares, currency, etc.)

Type: **Qty**

Used in components: **UnderlyingInstrument**

**180.2.6544 UnderlyingRateSpreadInitialValue**

Specifies the initial rate spread for a basket underlier.

Type: **float**

Used in components: **UnderlyingRateSpreadSchedule**

**180.2.6545 UnderlyingRateSpreadSchedule**

UnderlyingRateSpreadSchedule is a subcomponent of UnderlyingInstrument used to specify the rate spread schedule for a basket underlier.

Name	Mult.	Type	Description
<b>UnderlyingRateSpreadInitialValue</b>	[0..1]	float	
<b>UnderlyingRateSpreadStepGrp</b>	[0..*]	Group	

Used in components: **UnderlyingInstrument**

**180.2.6546 UnderlyingRateSpreadStepDate**

The date that the rate spread step takes affect.

Type: **LocalMktDate**

Used in groups: **UnderlyingRateSpreadStepGrp**

**180.2.6547 UnderlyingRateSpreadStepGrp**

UnderlyingRateSpreadStepGrp is a repeating subcomponent of UnderlyingRateSpreadSchedule used to specify the step dates and amounts of a basket spread schedule.

Name	Mult.	Type	Description
NoUnderlyingRateSpreadSteps	[1..1]	NumInGroup	
UnderlyingRateSpreadStepDate	[0..1]	LocalMktDate	Required if NoUnderlyingRateSpreadSteps(43005) > 0.
UnderlyingRateSpreadStepValue	[0..1]	float	Required if NoUnderlyingRateSpreadSteps(43005) > 0.

Used in components: [UnderlyingRateSpreadSchedule](#)

**180.2.6548 UnderlyingRateSpreadStepValue**

The the value of the new rate spread as of the UnderlyingRateSpreadStepDate(43006).

Type: [float](#)

Used in groups: [UnderlyingRateSpreadStepGrp](#)

**180.2.6549 UnderlyingRedemptionDate**

Underlying security's RedemptionDate. See RedemptionDate (240) field for description (Note tag # was reserved in FIX 4.1, added in FIX 4.3) (prior to FIX 4.4 field was of type UTCDate)

Type: [LocalMktDate](#)

Used in components: [UnderlyingInstrument](#)

**180.2.6550 UnderlyingReferenceEntityType**

Specifies the type of reference entity for first-to-default CDS basket contracts.

Type: [int](#)

Allowed values in ReferenceEntityTypeCodeSet:

Code	Name	Description
1	Asian	Asian
2	AustralianNewZealand	Australian and New Zealand
3	EuropeanEmergingMarkets	European emerging markets
4	Japanese	Japanese
5	NorthAmericanHighYield	North American high yield
6	NorthAmericanInsurance	North American insurance
7	NorthAmericanInvestmentGrade	North American investment grade
8	Singaporean	Singaporean
9	WesternEuropean	Western European
10	WesternEuropeanInsurance	Western European insurance

Used in components: **UnderlyingInstrument**

#### **180.2.6551 UnderlyingRefID**

Identifies the underlying instrument the entity applies to by referencing the underlying instrument's UnderlyingID(2874).

Type: **String**

Used in groups: **CollateralAmountGrp**

#### **180.2.6552 UnderlyingRefTickTableID**

Spread table code referred by the security or symbol.

Type: **int**

Used in components: **UnderlyingInstrument**

#### **180.2.6553 UnderlyingRepoCollateralSecurityType**

Underlying security's RepoCollateralSecurityType. See RepoCollateralSecurityType (239) field for description.(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.6554 UnderlyingRepurchaseRate**

Underlying security's RepurchaseRate. See RepurchaseRate (227) field for description (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **Percentage**

Used in components: **UnderlyingInstrument**

**180.2.6555 UnderlyingRepurchaseTerm**

Underlying security's RepurchaseTerm. See RepurchaseTerm (226) field for description (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.6556 UnderlyingRestructuringType**

See RestructuringType(1449)

Type: **String**

Allowed values in RestructuringTypeCodeSet:

Code	Name	Description
FR	FullRestructuring	Full Restructuring
MR	ModifiedRestructuring	Modified Restructuring
MM	ModifiedModRestructuring	Modified Mod Restructuring
XR	NoRestructuringSpecified	No Restructuring specified

Used in components: **UnderlyingInstrument**

**180.2.6557 UnderlyingReturnRateAmountRelativeTo**

Specifies the reference amount when the return rate amount is relative to another amount in the trade.

See [http://www.fixtradingcommunity.org/codelists#Payment\\_Amount\\_Relative\\_To](http://www.fixtradingcommunity.org/codelists#Payment_Amount_Relative_To) for code list of relative amounts.

Type: **int**

Used in groups: **UnderlyingReturnRateGrp**

### **180.2.6558 UnderlyingReturnRateCashFlowType**

Specifies the type of cash flows, e.g. coupon payment, premium fee, settlement fee, etc.

See <http://www.fpml.org/coding-scheme/cashflow-type> for values.

Type: **String**

Used in groups: **UnderlyingReturnRateGrp**

### **180.2.6559 UnderlyingReturnRateCommissionAmount**

The commission amount.

Type: **Amt**

Used in groups: **UnderlyingReturnRateGrp**

### **180.2.6560 UnderlyingReturnRateCommissionBasis**

Specifies the basis or unit used to calculate the commission.

Type: **char**

Allowed values in CommTypeCodeSet:

Code	Name	Description
1	PerUnit	Amount per unit. Implying shares, par, currency, physical unit etc. Use CommissionUnitOfMeasure(1238) to clarify for commodities.
2	Percent	Percent
3	Absolute	Absolute. Total monetary amount.
4	PercentageWaivedCashDiscount	Percentage waived, cash discount basis. For use with CIV buy orders.
5	PercentageWaivedEnhancedUnits	Percentage waived, enhanced units basis. For use with CIV buy orders.
6	PointsPerBondOrContract	Points per bond or contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention, e.g. 1000 par for bonds.

Code	Name	Description
7	BasisPoints	Basis points. The commission is expressed in basis points in reference to the gross price of the reference asset.
8	AmountPerContract	Amount per contract. Specify ContractMultiplier(231) in the Instrument component if the security is denominated in a size other than the market convention.

Used in groups: [UnderlyingReturnRateGrp](#)

### 180.2.6561 UnderlyingReturnRateCommissionCurrency

Specifies the currency the commission amount is denominated in. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingReturnRateGrp](#)

### 180.2.6562 UnderlyingReturnRateDateGrp

UnderlyingReturnRateDateGrp is a repeating subcomponent within the UnderlyingReturnRateGrp component. It is used to specify the equity and dividend valuation dates for an equity return swap payment stream.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingReturnRateDates</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingReturnRateDateMode</a>	[0..1]	CodeSet	Required if <a href="#">NoUnderlyingReturnRateDates</a> (43008) > 0.
<a href="#">UnderlyingReturnRateValuationDate-Grp</a>	[0..*]	Group	
<a href="#">UnderlyingReturnRateValuation-DateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingReturnRateValuationDate-OffsetPeriod</a>	[0..1]	int	Conditionally required when <a href="#">UnderlyingReturnRateValuationDateOffsetUnit</a> (43012) is specified.
<a href="#">UnderlyingReturnRateValuationDate-OffsetUnit</a>	[0..1]	CodeSet	Conditionally required when <a href="#">UnderlyingReturnRateValuationDateOffsetPeriod</a> (43011) is specified.
<a href="#">UnderlyingReturnRateValuationDate-OffsetDayType</a>	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingReturnRateValuationStart-DateUnadjusted	[0..1]	LocalMktDate	
UnderlyingReturnRateValuationStart-DateRelativeTo	[0..1]	int	
UnderlyingReturnRateValuationStart-DateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingReturnRateValuationStartDateOffsetUnit(43017) is specified.
UnderlyingReturnRateValuationStart-DateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingReturnRateValuationStartDateOffsetPeriod(43016) is specified.
UnderlyingReturnRateValuationStart-DateOffsetDayType	[0..1]	CodeSet	
UnderlyingReturnRateValuationStart-DateAdjusted	[0..1]	LocalMktDate	
UnderlyingReturnRateValuationEnd-DateUnadjusted	[0..1]	LocalMktDate	
UnderlyingReturnRateValuationEnd-DateRelativeTo	[0..1]	int	
UnderlyingReturnRateValuationEnd-DateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingReturnRateValuationEndDateOffsetUnit(43023) is specified.
UnderlyingReturnRateValuationEnd-DateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingReturnRateValuationEndDateOffsetPeriod(43022) is specified.
UnderlyingReturnRateValuationEnd-DateOffsetDayType	[0..1]	CodeSet	
UnderlyingReturnRateValuationEnd-DateAdjusted	[0..1]	LocalMktDate	
UnderlyingReturnRateValuationFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingReturnRateValuationFrequencyUnit(43027) is specified.
UnderlyingReturnRateValuationFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingReturnRateValuationFrequencyPeriod(43026) is specified.
UnderlyingReturnRateValuationFrequencyRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the return rate dates.



Name	Mult.	Type	Description
<a href="#">UnderlyingReturnRateValuationDate-BusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to payment stream return rate valuation dates.
<a href="#">UnderlyingReturnRateValuationDate-BusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to payment stream return rate valuation dates.

Used in groups: [UnderlyingReturnRateGrp](#)

### 180.2.6563 UnderlyingReturnRateDateMode

Specifies the valuation type applicable to the return rate date.

Type: [int](#)

Allowed values in ReturnRateDateModeCodeSet:

Code	Name	Description
0	PriceValuation	Price valuation
1	DividendValuation	Dividend valuation

Used in groups: [UnderlyingReturnRateDateGrp](#)

### 180.2.6564 UnderlyingReturnRateDeterminationMethod

Specifies the method by which the underlier prices are determined.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: [String](#)

Used in groups: [UnderlyingReturnRateGrp](#)

**180.2.6565 UnderlyingReturnRateFinalPriceFallback**

Specifies the fallback provision for the hedging party in the determination of the final price.

Type: **int**

Allowed values in ComplexEventPVFinalPriceElectionFallbackCodeSet:

Code	Name	Description
0	Close	Close. In respect of the "early final valuation date", the provisions for "future present value close" shall apply.
1	HedgeElection	Hedge election. In respect of the "early final valuation date", the provisions for "future present value hedge execution" shall apply.

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6566 UnderlyingReturnRateFXConversionGrp**

UnderlyingReturnRateFXConversionGrp is a repeating subcomponent within the UnderlyingReturnRateGrp component. It is used to specify the FX conversion rates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoUnderlyingReturnRateFXConversions	[1..1]	NumInGroup	
UnderlyingReturnRateFXCurrencySymbol	[0..1]	String	Required if NoUnderlyingReturnRateFXConversions(43030) > 0.
UnderlyingReturnRateFXRate	[0..1]	float	Required if NoUnderlyingReturnRateFXConversions(43030) > 0.
UnderlyingReturnRateFXRateCalc	[0..1]	CodeSet	

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6567 UnderlyingReturnRateFXCurrencySymbol**

Specifies the currency pair for the FX conversion expressed using the CCY1/CCY2 convention. Uses ISO 4217 currency codes.

Type: **String**

Used in groups: **UnderlyingReturnRateFXConversionGrp**

#### **180.2.6568 UnderlyingReturnRateFXRate**

The rate of exchange between the two currencies specified in UnderlyingReturnRateFXCurrencySymbol(43031).

Type: **float**

Used in groups: **UnderlyingReturnRateFXConversionGrp**

#### **180.2.6569 UnderlyingReturnRateFXRateCalc**

Specifies whether UnderlyingReturnRateFXRate(43032) should be multiplied or divided.

Type: **char**

Allowed values in SettlCurrFxRateCalcCodeSet:

Code	Name	Description
M	Multiply	Multiply
D	Divide	Divide

Used in groups: **UnderlyingReturnRateFXConversionGrp**

#### **180.2.6570 UnderlyingReturnRateGrp**

UnderlyingReturnRateGrp is a repeating subcomponent within the UnderlyingPaymentStreamFloatingRate component. It is used to specify the multiple return rates for an equity return swap payment stream.

Name	Mult.	Type	Description
<b>NoUnderlyingReturnRates</b>	[1..1]	NumInGroup	
<b>UnderlyingReturnRatePriceSequence</b>	[0..1]	CodeSet	Required if NoUnderlyingReturnRates(43034) > 0.
<b>UnderlyingReturnRateCommissionBasis</b>	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingReturnRateCommission-Amount	[0..1]	Amt	
UnderlyingReturnRateCommissionCur- rency	[0..1]	Currency	If not specified, this is defaulted to the reporting currency.
UnderlyingReturnRateTotalCommis- sionPerTrade	[0..1]	Amt	
UnderlyingReturnRateDetermination- Method	[0..1]	String	
UnderlyingReturnRatePriceGrp	[0..*]	Group	
UnderlyingReturnRateFXConversion- Grp	[0..*]	Group	
UnderlyingReturnRateAmountRela- tiveTo	[0..1]	int	
UnderlyingReturnRateQuoteMeasure- Type	[0..1]	String	
UnderlyingReturnRateQuoteUnits	[0..1]	String	
UnderlyingReturnRateQuoteMethod	[0..1]	CodeSet	
UnderlyingReturnRateQuoteCurrency	[0..1]	Currency	
UnderlyingReturnRateQuoteCurrency- Type	[0..1]	String	
UnderlyingReturnRateQuoteTimeType	[0..1]	CodeSet	Mutually exclusive with UnderlyingReturnRateQuoteTime(43048).
UnderlyingReturnRateQuoteTime	[0..1]	LocalMktDate	Mutually exclusive with UnderlyingReturnRateQuoteTimeType(43047).
UnderlyingReturnRateQuoteDate	[0..1]	LocalMktDate	
UnderlyingReturnRateQuoteExpira- tionTime	[0..1]	LocalMktTime	
UnderlyingReturnRateQuoteBusiness- Center	[0..1]	String	
UnderlyingReturnRateQuoteExchange	[0..1]	Exchange	
UnderlyingReturnRateInformation- SourceGrp	[0..*]	Group	
UnderlyingReturnRateQuotePricing- Model	[0..1]	String	
UnderlyingReturnRateCashFlowType	[0..1]	String	
UnderlyingReturnRateDateGrp	[0..*]	Group	
UnderlyingReturnRateValuationTime- Type	[0..1]	CodeSet	Mutually exclusive with UnderlyingReturnRateValuationTime(43056)

Name	Mult.	Type	Description
<a href="#">UnderlyingReturnRateValuationTime</a>	[0..1]	LocalMktTime	Mutually exclusive with <a href="#">UnderlyingReturnRateValuationTimeType(43055)</a> .
<a href="#">UnderlyingReturnRateValuationTime-BusinessCenter</a>	[0..1]	String	
<a href="#">UnderlyingReturnRateValuation-PriceOption</a>	[0..1]	CodeSet	
<a href="#">UnderlyingReturnRateFinalPriceFall-back</a>	[0..1]	CodeSet	

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### 180.2.6571 UnderlyingReturnRateInformationSource

Identifies the source of rate information. For FX the references source to be used for the FX spot rate.

Type: [int](#)

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in groups: [UnderlyingReturnRateInformationSourceGrp](#)

### 180.2.6572 UnderlyingReturnRateInformationSourceGrp

[UnderlyingReturnRateInformationSourceGrp](#) is a repeating subcomponent within the [UnderlyingReturnRateGrp](#) component. It is used to specify the information sources for equity prices and FX rates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoUnderlyingReturnRateInformation-Sources	[1..1]	NumInGroup	
UnderlyingReturnRateInformation-Source	[0..1]	CodeSet	Required if NoUnderlyingReturnRateInformation-Sources(43060) > 0.
UnderlyingReturnRateReferencePage	[0..1]	String	
UnderlyingReturnRateReferencePage-Heading	[0..1]	String	

Used in groups: [UnderlyingReturnRateGrp](#)

### 180.2.6573 UnderlyingReturnRateNotionalReset

Indicates whether the term "Equity Notional Reset" as defined in the ISDA 2002 Equity Derivatives Definitions is applicable ("Y") or not.

Type: [Boolean](#)

Used in components: [UnderlyingPaymentStreamFloatingRate](#)

### 180.2.6574 UnderlyingReturnRatePrice

Specifies the price of the underlying swap asset.

Type: [Price](#)

Used in groups: [UnderlyingReturnRatePriceGrp](#)

### 180.2.6575 UnderlyingReturnRatePriceBasis

The basis of the return price.

Type: [int](#)

Allowed values in ReturnRatePriceBasisCodeSet:

Code	Name	Description
0	Gross	Gross.
1	Net	Net

---

Code	Name	Description
------	------	-------------

---

2	Accrued	Accrued
---	---------	---------

3	CleanNet	Clean net
---	----------	-----------

---

Used in groups: [UnderlyingReturnRatePriceGrp](#)

### 180.2.6576 UnderlyingReturnRatePriceCurrency

Specifies the currency of the price of the underlying swap asset. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingReturnRatePriceGrp](#)

### 180.2.6577 UnderlyingReturnRatePriceGrp

UnderlyingReturnRatePriceGrp is a repeating subcomponent within the UnderlyingReturnRateGrp component. It is used to specify the return rate prices for an equity return swap payment stream.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingReturnRatePrices</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingReturnRatePriceBasis</a>	[0..1]	CodeSet	Required if NoUnderlyingReturnRatePrices(43064) > 0.
<a href="#">UnderlyingReturnRatePrice</a>	[0..1]	Price	
<a href="#">UnderlyingReturnRatePriceCurrency</a>	[0..1]	Currency	
<a href="#">UnderlyingReturnRatePriceType</a>	[0..1]	CodeSet	

Used in groups: [UnderlyingReturnRateGrp](#)

### 180.2.6578 UnderlyingReturnRatePriceSequence

Specifies the type of price sequence of the return rate.

Type: [int](#)

Allowed values in ReturnRatePriceSequenceCodeSet:

Code	Name	Description
0	Initial	Initial
1	Interim	Interim
2	Final	Final

Used in groups: **UnderlyingReturnRateGrp**

#### **180.2.6579 UnderlyingReturnRatePriceType**

Specifies whether the UnderlyingReturnRatePrice(43066) is expressed in absolute or relative terms.

Type: **int**

Allowed values in ReturnRatePriceTypeCodeSet:

Code	Name	Description
0	AbsoluteTerms	Absolute terms
1	PercentageOfNotional	Percentage of notional

Used in groups: **UnderlyingReturnRatePriceGrp**

#### **180.2.6580 UnderlyingReturnRateQuoteBusinessCenter**

The business center calendar used for adjustments associated with UnderlyingReturnRateQuoteTimeType(43047) or UnderlyingReturnRateQuoteTime(43048) and UnderlyingReturnRateQuoteDate(43049), e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingReturnRateGrp**

#### **180.2.6581 UnderlyingReturnRateQuoteCurrency**

Specifies the currency the return rate quote is denominated in. Uses ISO 4217 Currency Code.

Type: **Currency**

Used in groups: **UnderlyingReturnRateGrp**



**180.2.6582 UnderlyingReturnRateQuoteCurrencyType**

Specifies the type of currency, e.g. settlement currency, base currency, etc., that the quote is reported in.

See <http://www.fpml.org/coding-scheme/reporting-currency-type> for values.

Type: **String**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6583 UnderlyingReturnRateQuoteDate**

The date when the quote is to be generated.

Type: **LocalMktDate**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6584 UnderlyingReturnRateQuoteExchange**

Specifies the exchange (e.g. stock or listed futures/options exchange) from which the quote is obtained.

Type: **Exchange**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6585 UnderlyingReturnRateQuoteExpirationTime**

The time when the quote ceases to be valid.

Type: **LocalMktTime**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6586 UnderlyingReturnRateQuoteMeasureType**

Specifies the type of the measure applied to the return rate's asset, e.g. valuation, sensitivity risk. This could be an NPV, a cash flow, a clean price, etc.

See <http://www.fpml.org/coding-scheme/asset-measure> for values.

Type: **String**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6587 UnderlyingReturnRateQuoteMethod**

Specifies the type of quote used to determine the return rate of the swap.

Type: **int**

Allowed values in CashSettlQuoteMethodCodeSet:

Code	Name	Description
0	Bid	Bid
1	Mid	Mid
2	Offer	Offer

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6588 UnderlyingReturnRateQuotePricingModel**

Specifies the pricing model used to evaluate the underlying asset price.

See <http://www.fpml.org/coding-scheme/pricing-model> for values.

Type: **String**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6589 UnderlyingReturnRateQuoteTime**

The time when the quote is to be generated.

Type: **LocalMktDate**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6590 UnderlyingReturnRateQuoteTimeType**

Specifies how or the timing when the quote is to be obtained.

Type: **int**

Allowed values in ReturnRateQuoteTimeTypeCodeSet:

Code	Name	Description
0	Open	Open. The official opening time of the exchange on valuation date.
1	OfficialSettlPx	Official settlement price time. The time at which the official settlement price is determined.
2	Xetra	XETRA. The time at which the official settlement price (following the auction by the exchange) is determined by the exchange.
3	Close	Close. The official closing time of the exchange on valuation date.
4	DerivativesClose	Derivatives close. The official closing time for derivative trading of the exchange on valuation date.
5	High	High. The high price for the day.
6	Low	Low. The low price for the day.
7	AsSpecifiedInMasterConfirmation	As specified in the master confirmation

Used in groups: **UnderlyingReturnRateGrp**

#### 180.2.6591 UnderlyingReturnRateQuoteUnits

Specifies the units that the measure is expressed in. If not specified, the default is a price/value in currency units.

See <http://www.fpml.org/coding-scheme/price-quote-units> for values.

Type: **String**

Used in groups: **UnderlyingReturnRateGrp**

#### 180.2.6592 UnderlyingReturnRateReferencePage

Identifies the reference "page" from the rate source.

For FX, the reference page to the spot rate to be used for the reference FX spot rate.

When UnderlyingReturnRateInformationSource(43061) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions.

See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in groups: **UnderlyingReturnRateInformationSourceGrp**

**180.2.6593 UnderlyingReturnRateReferencePageHeading**

Identifies the page heading from the rate source.

Type: **String**

Used in groups: **UnderlyingReturnRateInformationSourceGrp**

**180.2.6594 UnderlyingReturnRateTotalCommissionPerTrade**

The total commission per trade.

Type: **Amt**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6595 UnderlyingReturnRateValuationDate**

The return rate valuation date. Type of date is specified in UnderlyingReturnRateValuationDate-Type(43073).

Type: **LocalMktDate**

Used in groups: **UnderlyingReturnRateValuationDateGrp**

**180.2.6596 UnderlyingReturnRateValuationDateBusinessCenter**

The business center calendar used for date adjustment of the return rate valuation unadjusted or relative dates, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingReturnRateValuationDateBusinessCenterGrp**

**180.2.6597 UnderlyingReturnRateValuationDateBusinessCenterGrp**

UnderlyingReturnRateValuationDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingReturnRateValuationDateGrp component. It is used to specify the valuation date business center adjustments for an equity return swap payment stream.

Name	Mult.	Type	Description
NoUnderlyingReturnRateValuation-DateBusinessCenters	[1..1]	NumInGroup	
UnderlyingReturnRateValuationDate-BusinessCenter	[0..1]	String	Required if NoUnderlyingReturnRateValuation-DateBusinessCenters(43069) > 0.

Used in groups: [UnderlyingReturnRateDateGrp](#)

### 180.2.6598 UnderlyingReturnRateValuationDateBusinessDayConvention

The return rate valuation dates business day convention.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in groups: [UnderlyingReturnRateDateGrp](#)

### 180.2.6599 UnderlyingReturnRateValuationDateGrp

UnderlyingReturnRateValuationDateGrp is a repeating subcomponent within the UnderlyingReturnRateDateGrp component. It is used to specify the fixed valuation dates for an equity return swap payment stream.

Name	Mult.	Type	Description
NoUnderlyingReturnRateValuation-Dates	[1..1]	NumInGroup	
UnderlyingReturnRateValuationDate	[0..1]	LocalMktDate	Required if NoUnderlyingReturnRateValuationDates(43071) > 0.
UnderlyingReturnRateValuationDate-Type	[0..1]	CodeSet	When specified it applies not only to the current date instance but to all subsequent date instances in the group until overridden when a new type is specified.

Used in groups: [UnderlyingReturnRateDateGrp](#)

### 180.2.6600 UnderlyingReturnRateValuationDateOffsetDayType

Specifies the day type of the relative return rate valuation date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: [UnderlyingReturnRateDateGrp](#)

### 180.2.6601 UnderlyingReturnRateValuationDateOffsetPeriod

Time unit multiplier for the relative return rate valuation date offset.

Type: [int](#)

Used in groups: [UnderlyingReturnRateDateGrp](#)

**180.2.6602 UnderlyingReturnRateValuationDateOffsetUnit**

Time unit associated with the relative return rate valuation date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6603 UnderlyingReturnRateValuationDateRelativeTo**

Specifies the anchor date when the return rate valuation dates are relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6604 UnderlyingReturnRateValuationDateType**

Specifies the type of return rate valuation date (e.g. adjusted for holidays).

Type: **int**

Allowed values in NonDeliverableFixingDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **UnderlyingReturnRateValuationDateGrp**

**180.2.6605 UnderlyingReturnRateValuationEndDateAdjusted**

The adjusted end date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6606 UnderlyingReturnRateValuationEndDateOffsetDayType**

Specifies the day type of the relative return rate valuation end date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6607 UnderlyingReturnRateValuationEndDateOffsetPeriod**

Time unit multiplier for the relative return rate valuation end date offset.

Type: **int**

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6608 UnderlyingReturnRateValuationEndDateOffsetUnit**

Time unit associated with the relative return rate valuation end date offset.

Type: **String**



Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [UnderlyingReturnRateDateGrp](#)

#### **180.2.6609 UnderlyingReturnRateValuationEndDateRelativeTo**

Specifies the anchor date when the return rate valuation end date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in groups: [UnderlyingReturnRateDateGrp](#)

#### **180.2.6610 UnderlyingReturnRateValuationEndDateUnadjusted**

The unadjusted end date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingReturnRateDateGrp](#)

#### **180.2.6611 UnderlyingReturnRateValuationFrequencyPeriod**

Time unit multiplier for the frequency at which return rate valuation dates occur.

Type: [int](#)

Used in groups: [UnderlyingReturnRateDateGrp](#)

**180.2.6612 UnderlyingReturnRateValuationFrequencyRollConvention**

The convention for determining the sequence of return rate valuation dates. It is used in conjunction with a specified frequency.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighDa28y	28th day of the month

Code	Name	Description
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in groups: **UnderlyingReturnRateDateGrp**

### 180.2.6613 UnderlyingReturnRateValuationFrequencyUnit

Time unit associated with the frequency at which return rate valuation dates occur.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day

Code	Name	Description
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
T	Term	Term

Used in groups: [UnderlyingReturnRateDateGrp](#)

#### **180.2.6614 UnderlyingReturnRateValuationPriceOption**

Indicates whether an ISDA price option applies, and if applicable which type of price.

Type: [int](#)

Allowed values in ReturnRateValuationPriceOptionCodeSet:

Code	Name	Description
0	None	None (the default)
1	FuturesPrice	Futures price. The official settlement price as announced by the related futures exchange is applicable.
2	OptionsPrice	Options price. The official settlement price as announced by the related options exchange is applicable.

Used in groups: [UnderlyingReturnRateGrp](#)

#### **180.2.6615 UnderlyingReturnRateValuationStartDateAdjusted**

The adjusted start date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingReturnRateDateGrp](#)

**180.2.6616 UnderlyingReturnRateValuationStartDateOffsetDayType**

Specifies the day type of the relative return rate valuation start date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6617 UnderlyingReturnRateValuationStartDateOffsetPeriod**

Time unit multiplier for the relative return rate valuation start date offset.

Type: **int**

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6618 UnderlyingReturnRateValuationStartDateOffsetUnit**

Time unit associated with the relative return rate valuation start date offset.

Type: **String**

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6619 UnderlyingReturnRateValuationStartDateRelativeTo**

Specifies the anchor date when the return rate valuation start date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6620 UnderlyingReturnRateValuationStartDateUnadjusted**

The unadjusted start date for return rate valuation. This can be used to restrict the range of dates when they are relative.

Type: **LocalMktDate**

Used in groups: **UnderlyingReturnRateDateGrp**

**180.2.6621 UnderlyingReturnRateValuationTime**

The time at which the calculation agent values the underlying asset.

Type: **LocalMktTime**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6622 UnderlyingReturnRateValuationTimeBusinessCenter**

The business center calendar used for adjustments associated with UnderlyingReturnRateValuationTimeType(43055) or UnderlyingReturnRateValuationTime(43056) , e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingReturnRateGrp**

**180.2.6623 UnderlyingReturnRateValuationTimeType**

Specifies the timing at which the calculation agent values the underlying.

Type: **int**

Allowed values in ReturnRateQuoteTimeTypeCodeSet:

Code	Name	Description
0	Open	Open. The official opening time of the exchange on valuation date.
1	OfficialSettlPx	Official settlement price time. The time at which the official settlement price is determined.
2	Xetra	XETRA. The time at which the official settlement price (following the auction by the exchange) is determined by the exchange.
3	Close	Close. The official closing time of the exchange on valuation date.
4	DerivativesClose	Derivatives close. The official closing time for derivative trading of the exchange on valuation date.
5	High	High. The high price for the day.
6	Low	Low. The low price for the day.
7	AsSpecifiedInMasterConfirmation	As specified in the master confirmation

Used in groups: [UnderlyingReturnRateGrp](#)

### 180.2.6624 UnderlyingReturnTrigger

Indicates the type of return or payout trigger for the swap or forward.

Type: [int](#)

Allowed values in ReturnTriggerCodeSet:

Code	Name	Description
1	Dividend	Dividend
2	Variance	Variance
3	Volatility	Volatility
4	TotalReturn	Total return
5	ContractForDifference	Contract for difference
6	CreditDefault	Credit default
7	SpreadBet	Spread bet
8	Price	Price
9	ForwardPriceUnderlyingInstrument	Forward price of underlying instrument
99	Other	Other

Used in components: [UnderlyingInstrument](#)

**180.2.6625 UnderlyingSecondaryAssetClass**

The broad asset category for assessing risk exposure for a multi-asset trade.

Type: **int**

Allowed values in AssetClassCodeSet:

Code	Name	Description
1	InterestRate	Interest rate
2	Currency	Currency
3	Credit	Credit
4	Equity	Equity
5	Commodity	Commodity
6	Other	Other
7	Cash	Cash
8	Debt	Debt
9	Fund	Fund. Such as mutual fund, collective investment vehicle, investment program, specialized account program.
10	LoanFacility	Loan facility
11	Index	Index. A main index identified as a security type, for example under EU SFTR reporting.

Used in groups: **UnderlyingSecondaryAssetGrp**

**180.2.6626 UnderlyingSecondaryAssetGrp**

UnderlyingSecondaryAssetGrp is a repeating subcomponent of the UnderlyingInstrument component used to specify secondary assets of a multi-asset swap.

Name	Mult.	Type	Description
<b>NoUnderlyingSecondaryAssetClasses</b>	[1..1]	NumInGroup	
<b>UnderlyingSecondaryAssetClass</b>	[0..1]	CodeSet	Required if NoUnderlyingSecondaryAssetClasses(2080) > 0.
<b>UnderlyingSecondaryAssetSubClass</b>	[0..1]	CodeSet	Required if UnderlyingSecondaryAssetType(2083) is specified.



Name	Mult.	Type	Description
<b>UnderlyingSecondaryAssetType</b>	[0..1]	String	Required if UnderlyingSecondaryAssetSubType(2745) is specified.
<b>UnderlyingSecondaryAssetSubType</b>	[0..1]	String	

Used in components: **UnderlyingInstrument**

### 180.2.6627 UnderlyingSecondaryAssetSubClass

An indication of the general description of the asset class.

Type: **int**

Allowed values in AssetSubClassCodeSet:

Code	Name	Description
1	SingleCurrency	Single currency
2	CrossCurrency	Cross currency
3	Basket	Basket [for multi-currency]
4	SingleName	Single name
5	CreditIndex	Credit index
6	IndexTranche	Index tranche
7	CreditBasket	Credit basket
8	Exotic	Exotic
9	Common	Common
10	Preferred	Preferred
11	EquityIndex	Equity index
12	EquityBasket	Equity basket
13	Metals	Metals
14	Bullion	Bullion
15	Energy	Energy
16	CommodityIndex	Commodity index
17	Agricultural	Agricultural
18	Environmental	Environmental
19	Freight	Freight

Code	Name	Description
20	Government	Government
21	Agency	Agency
22	Corporate	Corporate
23	Financing	Financing
24	MoneyMarket	Money market
25	Mortgage	Mortgage
26	Municipal	Municipal
27	MutualFund	Mutual fund
28	CollectiveInvestmentVehicle	Collective investment vehicle
29	InvestmentProgram	Investment program. A generalized fund for major investors.
30	SpecializedAccountProgram	Specialized account program. A specialized fund setup for a particular account or group of accounts.
31	TermLoan	Term loan
32	BridgeLoan	Bridge loan
33	LetterOfCredit	Letter of credit
34	DividendIndex	Dividend index
35	StockDividend	Stock dividend
36	ExchangeTradedFund	Exchange traded fund
37	VolatilityIndex	Volatility index
38	FXCrossRates	FX cross rates
39	FXEmergingMarkets	FX emerging markets
40	FXMajors	FX Majors
41	Fertilizer	Fertilizer
42	IndustrialProduct	Industrial product
43	Inflation	Inflation
44	Paper	Paper
45	Polypropylene	Polypropylene
46	OfficialEconomicStatistics	Official economic statistics

Code	Name	Description
47	OtherC10	Other C10. Defined under MiFID II (Directive 2014/65/EU) Section C(10) of Annex I and paraphrased in ESMA RTS 2 Annex III Section 10, "Other C10" is a financial instrument "which is not a 'Freight derivative', any of the following interest rate derivatives sub-asset classes: 'Inflation multi-currency swap or cross-currency swap', a 'Future/forward on inflation multi-currency swaps or cross-currency swaps', an 'Inflation single currency swap', a 'Future/forward on inflation single currency swap' and any of the following equity derivatives sub-asset classes: a 'Volatility index option', a 'Volatility index future/forward', a swap with parameter return variance, a swap with parameter return volatility, a portfolio swap with parameter return variance, a portfolio swap with parameter return volatility".
48	Other	Other. May be used with any AssetClass(1938) values.

Used in groups: **UnderlyingSecondaryAssetGrp**

#### 180.2.6628 UnderlyingSecondaryAssetSubType

May be used to provide a more specific description of the asset specified in UnderlyingSecondaryAssetType(2083).

See <https://www.fixtrading.org/codelists/AssetSubType> for code list of applicable values.

Type: **String**

Used in groups: **UnderlyingSecondaryAssetGrp**

#### 180.2.6629 UnderlyingSecondaryAssetType

Used to provide more specific description of the asset specified in UnderlyingSecondaryAssetSubClass(2082).

See <https://www.fixtrading.org/codelists/AssetType> for code list of applicable values. ISO 4721 Currency Code values are to be used when specific currency as an asset type is to be expressed.

Other values may be used by mutual agreement of the counterparties.

Type: **String**

Used in groups: **UnderlyingSecondaryAssetGrp**

**180.2.6630 UnderlyingSecurityAltID**

Alternate Security identifier value for this underlying security of UnderlyingSecurityAltIDSource (459) type (e.g. CUSIP, SEDOL, ISIN, etc). Requires UnderlyingSecurityAltIDSource.

Type: **String**

Used in groups: **UndSecAltIDGrp**

**180.2.6631 UnderlyingSecurityAltIDSource**

Identifies class or source of the UnderlyingSecurityAltID(458) value.

Required if UnderlyingSecurityAltID is specified.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority

Code	Name	Description
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in groups: **UndSecAltIDGrp**

### 180.2.6632 UnderlyingSecurityDesc

Description of the underlying security.

Can be used by the venue or one of the trading parties to provide an optional non-normative textual description of the financial instrument.

Type: **String**

Used in components: **UnderlyingInstrument**

### 180.2.6633 UnderlyingSecurityExchange

Underlying security's SecurityExchange. Can be used to identify the underlying security.

Valid values: see SecurityExchange (207)

Type: **Exchange**

Used in components: **UnderlyingInstrument**

#### **180.2.6634 UnderlyingSecurityGroup**

An exchange specific name assigned to a group of related securities which may be concurrently affected by market events and actions.

Type: **String**

Used in components: **UnderlyingInstrument**

#### **180.2.6635 UnderlyingSecurityID**

Underlying security's SecurityID.

See SecurityID (48) field for description

Type: **String**

Used in components: **UnderlyingInstrument**

#### **180.2.6636 UnderlyingSecurityIDSource**

Identifies class or source of the UnderlyingSecurityID(309) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol

Code	Name	Description
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **UnderlyingInstrument**

**180.2.6637 UnderlyingSecurityStatus**

Indicates the current state of the underlying instrument.

Type: **String**

Allowed values in SecurityStatusCodeSet:

Code	Name	Description
1	Active	Active. Instrument is active, i.e. trading is possible.
2	Inactive	Inactive. Instrument has previously been active and is now no longer traded but has not expired yet. The instrument may become active again.
3	ActiveClosingOrdersOnly	Active, closing orders only. Instrument is active but only orders closing positions (reducing risk) are allowed.
4	Expired	Expired. Instrument has expired. E.g. An instrument may expire due to reaching maturity or expired based on contract definitions or exchange rules.
5	Delisted	Delisted. Instrument has been removed from securities reference data. Delisting rules varies from exchange to exchange, which may include non-compliance of capitalization, revenue, consecutive minimum closing price. The instrument may become listed again once the instrument is back in compliance. A delisted instrument would not trade on the exchange but it may still be traded over-the-counter (e.g. OTCBB) or on Pink Sheets, or other similar trading service.
6	KnockedOut	Knocked-out. Instrument has breached a pre-defined price threshold.
7	KnockOutRevoked	Knock-out revoked. Instrument reinstated, i.e. threshold has not been breached.
8	PendingExpiry	Pending Expiry. Instrument is currently still active but will expire after the current business day. For example, a contract that expires intra-day (e.g. at noon time) and is no longer tradeable but will still show up in the current day's order book with related statistics.
9	Suspended	Suspended. Instrument has been temporarily disabled for trading (i.e. halted).
10	Published	Published. Instrument information is provided prior to its first activation.
11	PendingDeletion	Pending Deletion. Instrument is awaiting deletion from security reference data.



Used in components: [UnderlyingInstrument](#)

### **180.2.6638 UnderlyingSecuritySubType**

Underlying security's SecuritySubType.

See SecuritySubType (762) field for description

Type: [String](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.6639 UnderlyingSecurityType**

Underlying security's SecurityType.

Valid values: see SecurityType (167) field

(see below for details concerning this fields use in conjunction with SecurityType=REPO)

The following applies when used in conjunction with SecurityType=REPO

Represents the general or specific type of security that underlies a financing agreement

Valid values for SecurityType=REPO:

If bonds of a particular issuer or country are wanted in an Order or are in the basket of an Execution and the SecurityType is not granular enough, include the UnderlyingIssuer (306), UnderlyingCountryOfIssue (592), UnderlyingProgram, UnderlyingRegType and/or < UnderlyingStipulations > block e.g.:

Type: [String](#)

Allowed values in SecurityTypeCodeSet:

---

Code	Name	Description
ABS	AssetBackedSecurities	Asset-backed Securities
AN	OtherAnticipationNotes	Other Anticipation Notes (BAN, GAN, etc.)
BA	BankersAcceptance	Bankers Acceptance
BRADY	BradyBond	Brady Bond
CORP	CorporateBond	Corporate Bond
CS	CommonStock	Common Stock
EUSUPRA	EuroSupranationalCoupons	Euro Supranational Coupons. Identify the issuer name in Issuer(106).
FOR	ForeignExchangeContract	Foreign Exchange Contract

---

Code	Name	Description
MF	MutualFund	Mutual Fund
REPO	Repurchase	Repurchase
TERM	TermLoan	Term Loan
BDN	BankDepositoryNote	Bank Depository Note
CAN	CanadianTreasuryNotes	Canadian Treasury Notes
CAP	Cap	Cap. In an interest rate cap, the buyer receives payments at the end of each period in which the rate indec exceeds the agreed strike rate.
CMB	CanadianMortgageBonds	Canadian Mortgage Bonds
COFO	CertificateOfObligation	Certificate Of Obligation
CPP	CorporatePrivatePlacement	Corporate Private Placement
FAC	FederalAgencyCoupon	Federal Agency Coupon
FORWARD	Forward	Forward
FXNDF	NonDeliverableForward	Non-deliverable forward
MLEG	MultilegInstrument	Multileg Instrument
PS	PreferredStock	Preferred Stock
RVLV	RevolverLoan	Revolver Loan
BN	BankNotes	Bank Notes
BUYSELL	BuySellback	Buy Sellback
CB	ConvertibleBond	Convertible Bond
CDS	CreditDefaultSwap	Credit Default Swap
CMBS	Corp	Corp. Mortgage-backed Securities
COFP	CertificateOfParticipation	Certificate Of Participation
CTB	CanadianTreasuryBills	Canadian Treasury Bills
DR	DepositoryReceipts	Depository Receipts
FADN	FederalAgencyDiscountNote	Federal Agency Discount Note
FXSPOT	FXSpot	FX Spot
NONE	NoSecurityType	No Security Type
RVLVTRM	Revolver	Revolver/Term Loan
BOX	BillOfExchanges	Bill Of Exchanges
BRIDGE	BridgeLoan	Bridge Loan
CLLR	Collar	Collar. In an interest rate collar, this is a combination of a cap and a floor.
CMO	CollateralizedMortgageObligation	Collateralized Mortgage Obligation
DUAL	DualCurrency	Dual Currency

Code	Name	Description
EUSOV	EuroSovereigns	Euro Sovereigns. Identify the issuer name in Issuer(106).
FXFWD	FXForward	FX Forward
GO	GeneralObligationBonds	General Obligation Bonds
PEF	PrivateExportFunding	Private Export Funding. Identify the issuer name in Issuer(106).
SECLOAN	SecuritiesLoan	Securities Loan
UST	USTreasuryNoteOld	US Treasury Note (Deprecated Value Use TNOTE)
CAMM	CanadianMoneyMarkets	Canadian Money Markets
CMDTYSWAP	CommoditySwap	Commodity swap
EUCORP	EuroCorporateBond	Euro Corporate Bond
FXSWAP	FXSwap	FX Swap
IET	IOETTEMortgage	IOETTE Mortgage
LOFC	LetterOfCredit	Letter Of Credit
MT	MandatoryTender	Mandatory Tender
PROV	CanadianProvincialBonds	Canadian Provincial Bonds
SECPLEDGE	SecuritiesPledge	Securities Pledge
SUPRA	USDSupranationalCoupons	USD Supranational Coupons. Identify the issuer name in Issuer(106).
USTB	USTreasuryBillOld	US Treasury Bill (Deprecated Value Use TBILL)
?	Wildcard	Wildcard entry for use on Security Definition Request
CD	CertificateOfDeposit	Certificate Of Deposit
DVPLDG	DeliveryVersusPledge	Delivery versus pledge
EUFRN	EuroCorporateFloatingRateNotes	Euro Corporate Floating Rate Notes
EXOTIC	Exotic	Exotic
FXNDS	NonDeliverableSwap	Non-deliverable Swap
MBS	MortgageBackedSecurities	Mortgage-backed Securities
RAN	RevenueAnticipationNote	Revenue Anticipation Note
SWING	SwingLineFacility	Swing Line Facility
TB	TreasuryBill	Treasury Bill - non US
CASH	Cash	Cash
CL	CallLoans	Call Loans
COLLBSKT	CollateralBasket	Collateral basket. A collection of securities held as collateral in the customer's collateral fund. The collateral fund is usually managed by a custodian.
DINP	DebtorInPossession	Debtor In Possession

Code	Name	Description
FLR	Floor	Floor. In an interest rate floor, the buyer receives payments at the end of each period in which the rate index is below the agreed strike rate.
FRN	USCorporateFloatingRateNotes	US Corporate Floating Rate Notes
FXBN	FXBankNote	FX Bank Note
MIO	MortgageInterestOnly	Mortgage Interest Only
OOC	OptionsOnCombo	Options on Combo
REV	RevenueBonds	Revenue Bonds
TBOND	USTreasuryBond	US Treasury Bond
CP	CommercialPaper	Commercial Paper
DEFLTED	Defaulted	Defaulted
FRA	FRA	Forward Rate Agreement
FXDN	ForeignCurrencyDiscountNote	Foreign Currency Discount Note. Discount notes issued in foreign currency by Fannie Mae.
MPO	MortgagePrincipalOnly	Mortgage Principal Only
Other	Other	Other
SFP	StructuredFinanceProduct	Structured finance product
SPCLA	SpecialAssessment	Special Assessment
TINT	InterestStripFromAnyBondOrNote	Interest Strip From Any Bond Or Note
XLINKD	IndexedLinked	Indexed Linked
DN	DepositNotes	Deposit Notes
ETN	ExchangeTradedNote	Exchange traded note
FUT	Future	Future
MPP	MortgagePrivatePlacement	Mortgage Private Placement
SPCLO	SpecialObligation	Special Obligation
STRUCT	StructuredNotes	Structured Notes
TBILL	USTreasuryBill	US Treasury Bill
TIPS	TreasuryInflationProtectedSecurities	Treasury Inflation Protected Securities
WITHDRN	Withdrawn	Withdrawn
EUCD	EuroCertificateOfDeposit	Euro Certificate Of Deposit
FWD	DerivativeForward	Derivative forward
MPT	MiscellaneousPassThrough	Miscellaneous Pass-through
MGRNLOAN	MarginLoan	Margin loan
REPLACD	Replaced	Replaced
SPCLT	SpecialTax	Special Tax

Code	Name	Description
TCAL	PrincipalStripOfACallableBondOrNote	Principal Strip Of A Callable Bond Or Note
YANK	YankeeCorporateBond	Yankee Corporate Bond
DIMSUMCORP	OffshoreIssuedChineseYuanCorporateBond	Offshore issued Chinese Yuan (CNY) denominated corporate bond
EUCP	EuroCommercialPaper	Euro Commercial Paper
IRS	InterestRateSwap	Interest Rate Swap
MATURED	Matured	Matured
PFAND	Pfandbrief	Pfandbrief. Identify the issuer name in Issuer(106).
SECDERIV	SecuritizedDerivative	Securitized derivative
TAN	TaxAnticipationNote	Tax Anticipation Note
TPRN	PrincipalStripFromANonCallableBondOrNote	Principal Strip From A Non-Callable Bond Or Note
TRS	TotalReturnSwap	Total return swap
AMENDED	Amended	Amended and restated
ETF	ExchangeTradedFund	Exchange Traded Fund
LOANLEASE	LoanLease	Loan/lease
LQN	LiquidityNote	Liquidity Note
PRCORP	PreferredCorporateBond	Preferred Corporate Bond
TAXA	TaxAllocation	Tax Allocation
TBA	ToBeAnnounced	To Be Announced
TNOTE	USTreasuryNote	US Treasury Note
DIGITAL	DigitalAsset	Digital Asset. Asset that exists only in digital form or which is the digital representation of another asset (Source: ISO 24165 - Terms and Definitions).
DIMSUMSOV	OffshoreIssuedChineseYuanSovereignBond	Offshore issued Chinese Yuan (CNY) denominated sovereign bond
MTN	MediumTermNotes	Medium Term Notes
RETIRED	Retired	Retired
TECP	TaxExemptCommercialPaper	Tax Exempt Commercial Paper
ONITE	Overnight	Overnight
OOF	OptionsOnFutures	Options on Futures
SOV	SovereignBond	Sovereign Bond. Sovereign or government bond other than Euro and US issuer. Specify sovereign issuer in Issuer(106).
TMCP	TaxableMunicipalCP	Taxable Municipal CP
OOP	OptionsOnPhysical	Options on Physical - use not recommended

Code	Name	Description
PN	PromissoryNote	Promissory Note
STN	ShortTermLoanNote	Short Term Loan Note
TFRN	USTreasuryFloatingRateNote	US Treasury Floating Rate Note
TRAN	TaxRevenueAnticipationNote	Tax Revenue Anticipation Note
OPT	Option	Option
PZFJ	PlazosFijos	Plazos Fijos
VRDN	VariableRateDemandNote	Variable Rate Demand Note
SLQN	SecuredLiquidityNote	Secured Liquidity Note
SPOTFWD	SpotForward	Spot forward
WAR	Warrant	Warrant
MCPIB	MunicipalInterestBearingCommercialPaper	Municipal Interest Bearing Commercial Paper
SWAPTION	SwapOption	Swap option
TD	TimeDeposit	Time Deposit
TMB	TaxableMunicipalBond	Taxable Municipal Bond
XMISSION	Transmission	Transmission
INDEX	Index	General type for a contract based on an established index
TLQN	TermLiquidityNote	Term Liquidity Note
VRDO	VariableRateDemandObligation	Variable Rate Demand Obligation
BDBSKT	BondBasket	Bond basket
XCN	ExtendedCommNote	Extended Comm Note
CFD	ContractForDifference	Contract for difference
YCD	YankeeCertificateOfDeposit	Yankee Certificate Of Deposit
BAB	BankAcceptedBill	Bank Accepted Bill. Also known as Bank Bill.
CRLNSWAP	CorrelationSwap	Correlation swap
BNST	ShortTermBankNote	Short Term Bank Note
DVDNSWAP	DividendSwap	Dividend swap
CLCP	CallableCommercialPaper	Callable Commercial Paper
EQBSKT	EquityBasket	Equity basket
CN	CommercialNote	Commercial Note
EQFWD	EquityForward	Equity forward
CPIB	InterestBearingCommercialPaper	Interest Bearing Commercial Paper
RTRNSWAP	ReturnSwap	Return swap
EUMTN	EuroMediumTermNote	Euro Medium Term Note

Code	Name	Description
VARSWAP	VarianceSwap	Variance swap
EUNCP	EuroNegotiableCommercialPaper	Euro Negotiable Commercial Paper
PRTFLIOSWAP	PortfolioSwaps	Portfolio swap
EUSTLQN	EuroStructuredLiquidityNote	Euro Structured Liquidity Note
FUTSWAP	FuturesOnASwap	Futures on a Swap
EUTD	EuroTimeDeposit	Euro Time Deposit
FWDSWAP	ForwardsOnASwap	Forwards on a Swap
FWDFRTAGMT	ForwardFreightAgreement	Forward Freight Agreement
JCD	JumboCertificateOfDeposit	Jumbo Certificate of Deposit
MMF	MoneyMarketFund	Money Market Fund
SPREADBET	SpreadBetting	Spread Betting
ETC	ExchangeTradedCommodity	Exchange traded commodity
MN	MasterNote	Master Note. Short term notes issued by Federal Farm Credit Banks Funding Corporation to provide loans and funding under Federal Farm Credit System (FFCS).
NCD	NegotiableCertificateOfDeposit	Negotiable Certificate of Deposit
NCP	NegotiableCommercialPaper	Negotiable Commercial Paper
RCD	RetailCertificateOfDeposit	Retail Certificate of Deposit
TDR	TermDepositReceipt	Term Deposit Receipt

Used in components: [UnderlyingInstrument](#)

### 180.2.6640 UnderlyingSecurityXML

XML definition for the underlying security.

Type: [XMLData](#)

Used in components: [UnderlyingSecurityXML](#)

### 180.2.6641 UnderlyingSecurityXML

The UnderlyingSecurityXML component is used to provide a definition in an XML format for the underlying instrument.

Name	Mult.	Type	Description
UnderlyingSecurityXMLLen	[0..1]	Length	Must be provided if UnderlyingSecurityXML(1875) field is specified and must immediately precede it.
UnderlyingSecurityXML	[0..1]	XMLData	
UnderlyingSecurityXMLSchema	[0..1]	String	

Used in components: **UnderlyingInstrument**

### 180.2.6642 UnderlyingSecurityXMLLen

The length of the UnderlyingSecurityXML(1875) data block.

Type: **Length**

Used in components: **UnderlyingSecurityXML**

### 180.2.6643 UnderlyingSecurityXMLSchema

The schema used to validate the contents of UnderlyingSecurityXML(1875).

Type: **String**

Used in components: **UnderlyingSecurityXML**

### 180.2.6644 UnderlyingSeniority

See Seniority(1450)

Type: **String**

Allowed values in SeniorityCodeSet:

Code	Name	Description
SD	SeniorSecured	Senior Secured
SR	Senior	Senior
SB	Subordinated	Subordinated
JR	Junior	Junior. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".



Code	Name	Description
MZ	Mezzanine	Mezzanine. In the context of MiFID II this value is used as identified in RTS 23 Annex I Table 3 Field 23 "Seniority of the bond".
SN	SeniorNonPreferred	Senior Non-Preferred. For CDS reference obligations of non-preferred senior debt issued by European Financials that constitute a layer of debt ranking between the bank's normal senior debt but above the bank's normal tier 2 subordinated debt (reference: ISDA Credit Market Infrastructure Group).

Used in components: [UnderlyingInstrument](#)

#### 180.2.6645 UnderlyingSettlDisruptionProvision

Specifies the consequences of settlement disruption events.

Type: [int](#)

Allowed values in SettlDisruptionProvisionCodeSet:

Code	Name	Description
1	Negotiation	Negotiation
2	Cancellation	Cancellation and payment

Used in components: [UnderlyingInstrument](#)

#### 180.2.6646 UnderlyingSettledEntityMatrixPublicationDate

Specifies the publication date of the applicable version of the matrix. If not specified, the Standard Terms Supplement defines rules for which version of the matrix is applicable.

Type: [LocalMktDate](#)

Used in components: [UnderlyingInstrument](#)

#### 180.2.6647 UnderlyingSettledEntityMatrixSource

Relevant settled entity matrix source.

Type: **String**

Used in components: **UnderlyingInstrument**

#### **180.2.6648 UnderlyingSettlementDate**

Date the underlying instrument will settle. Used for derivatives that deliver into more than one underlying instrument. Settlement dates can vary across underlying instruments.

Type: **LocalMktDate**

Used in groups: **UnderlyingAmount**

Used in messages: **TradeCaptureReport**

#### **180.2.6649 UnderlyingSettlementStatus**

Settlement status of the underlying instrument. Used for derivatives that deliver into more than one underlying instrument. Settlement can be delayed for an underlying instrument.

Type: **String**

Used in groups: **UnderlyingAmount**

#### **180.2.6650 UnderlyingSettlementType**

Indicates order settlement period for the underlying instrument.

Type: **int**

Allowed values in UnderlyingSettlementTypeCodeSet:

Code	Name	Description
2	TPlus1	T+1
4	TPlus3	T+3
5	TPlus4	T+4

Used in components: **UnderlyingInstrument**

**180.2.6651 UnderlyingSettleOnOpenFlag**

Indicator to determine if Instrument is Settle on Open.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.6652 UnderlyingSettlMethod**

Settlement method for a contract or instrument. Additional values may be used with bilateral agreement.

Type: **String**

Allowed values in SettlMethodCodeSet:

Code	Name	Description
C	CashSettlementRequired	Cash settlement required
P	PhysicalSettlementRequired	Physical settlement required
E	Election	Election at exercise. The settlement method will be elected at the time of contract exercise.

Used in components: **UnderlyingInstrument**

**180.2.6653 UnderlyingSettlMethodElectingPartySide**

Side value of the party electing the settlement method.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in components: **UnderlyingOptionExercise**

**180.2.6654 UnderlyingSettlMethodElectionDateAdjusted**

The adjusted settlement method election date.

Type: **LocalMktDate**

Used in components: **UnderlyingSettlMethodElectionDate**

**180.2.6655 UnderlyingSettlMethodElectionDateBusinessCenter**

The business center calendar used for date adjustment of the settlement method election unadjusted or relative date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingSettlMethodElectionDateBusinessCenterGrp**

**180.2.6656 UnderlyingSettlMethodElectionDateBusinessCenterGrp**

UnderlyingSettlMethodElectionDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingSettlMethodElectionDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
<b>NoUnderlyingSettlMethodElectionDateBusinessCenters</b>	[1..1]	NumInGroup	
<b>UnderlyingSettlMethodElectionDateBusinessCenter</b>	[0..1]	String	Required if NoUnderlyingSettlMethodElectionDateBusinessCenters(43074) > 0.

Used in components: **UnderlyingSettlMethodElectionDate**

**180.2.6657 UnderlyingSettlMethodElectionDateBusinessDayConvention**

The settlement method election date adjustment business day convention.

Type: **int**

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingSettlMethodElectionDate](#)

### 180.2.6658 UnderlyingSettlMethodElectionDate

The UnderlyingSettlMethodElectionDate component is a subcomponent within the UnderlyingOptionExercise component used to report the settlement method election date.

Name	Mult.	Type	Description
<a href="#">UnderlyingSettlMethodElectionDateUnadjusted</a>	[0..1]	LocalMktDate	
<a href="#">UnderlyingSettlMethodElectionDate-BusinessDayConvention</a>	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to UnderlyingOptionExercise.
<a href="#">UnderlyingSettlMethodElectionDate-BusinessCenterGrp</a>	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to UnderlyingOptionExercise.
<a href="#">UnderlyingSettlMethodElectionDateRelativeTo</a>	[0..1]	int	
<a href="#">UnderlyingSettlMethodElectionDate-OffsetPeriod</a>	[0..1]	int	Conditionally required when UnderlyingSettlMethodElectionDateOffsetUnit(43080) is specified.
<a href="#">UnderlyingSettlMethodElectionDate-OffsetUnit</a>	[0..1]	CodeSet	Conditionally required when UnderlyingSettlMethodElectionDateOffsetPeriod(43079) is specified.
<a href="#">UnderlyingSettlMethodElectionDate-OffsetDayType</a>	[0..1]	CodeSet	

Name	Mult.	Type	Description
UnderlyingSettlMethodElection- DateAdjusted	[0..1]	LocalMktDate	

Used in components: [UnderlyingOptionExercise](#)

### 180.2.6659 UnderlyingSettlMethodElectionDateOffsetDayType

Specifies the day type of the relative settlement method election date offset.

Type: [int](#)

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingSettlMethodElectionDate](#)

### 180.2.6660 UnderlyingSettlMethodElectionDateOffsetPeriod

Time unit multiplier for the relative settlement method election date offset.

Type: [int](#)

Used in components: [UnderlyingSettlMethodElectionDate](#)

### 180.2.6661 UnderlyingSettlMethodElectionDateOffsetUnit

Time unit associated with the relative settlement method election date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingSettlMethodElectionDate](#)

#### **180.2.6662 UnderlyingSettlMethodElectionDateRelativeTo**

Specifies the anchor date when the settlement method election date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [UnderlyingSettlMethodElectionDate](#)

#### **180.2.6663 UnderlyingSettlMethodElectionDateUnadjusted**

The unadjusted settlement method election date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingSettlMethodElectionDate](#)

#### **180.2.6664 UnderlyingSettlPrice**

Underlying security's SettlPrice.

See SettlPrice (730) field for description

Type: [Price](#)

Used in groups: [PosUndInstrmtGrp](#)

Used in messages: [AssignmentReport](#)

**180.2.6665 UnderlyingSettlPriceType**

Underlying security's SettlPriceType.

See SettlPriceType (731) field for description

Type: **int**

Allowed values in SettlPriceTypeCodeSet:

Code	Name	Description
1	Final	Final
2	Theoretical	Theoretical

Used in groups: **PosUndInstrmtGrp**

**180.2.6666 UnderlyingSettlRateDisruptionFallbackGrp**

The UnderlyingSettlRateDisruptionFallbackGrp is a repeating subcomponent of the UnderlyingPaymentStreamNonDeliverableSettlTermGrp component used to specify the method, prioritized by the order it is listed, to get a replacement rate for a disrupted settlement rate option for a non-deliverable settlement currency.

Name	Mult.	Type	Description
<b>NoUnderlyingSettlRateFallbacks</b>	[1..1]	NumInGroup	
<b>UnderlyingSettlRatePostponement-MaximumDays</b>	[0..1]	int	Required if NoUnderlyingSettlRateFallbacks(40659) > 0.
<b>UnderlyingSettlRateFallbackRate-Source</b>	[0..1]	Component	
<b>UnderlyingSettlRatePostpone-mentSurvey</b>	[0..1]	Boolean	
<b>UnderlyingSettlRatePostponementCal-culationAgent</b>	[0..1]	CodeSet	

Used in components: **UnderlyingPaymentStreamNonDeliverableSettlTerms**

**180.2.6667 UnderlyingSettlRateFallbackRateSource**

Identifies the source of rate information.



Type: **int**

Allowed values in RateSourceCodeSet:

Code	Name	Description
0	Bloomberg	Bloomberg
1	Reuters	Reuters
2	Telerate	Telerate
3	ISDARateOption	ISDA Settlement Rate Option. The source of the currency conversion as specified by the ISDA terms in Annex A to the 1998 FX and Currency Option Definitions. See <a href="http://www.fpml.org/coding-scheme/settlement-rate-option">http://www.fpml.org/coding-scheme/settlement-rate-option</a>
99	Other	Other

Used in components: **UnderlyingSettlRateFallbackRateSource**

#### 180.2.6668 UnderlyingSettlRateFallbackRateSource

UnderlyingSettlRateFallbackRateSource is a subcomponent of the UnderlyingSettlRateDisruptionFallbackGrp component used to specify the rate source in the event of rate disruption fallback.

Name	Mult.	Type	Description
<b>UnderlyingSettlRateFallbackRateSource</b>	[0..1]	CodeSet	
<b>UnderlyingSettlRateFallbackReferencePage</b>	[0..1]	String	Conditionally required when UnderlyingSettlRateFallbackRateSource(40904) = 3 (ISDA Settlement Rate Option) or 99 (Other).

Used in groups: **UnderlyingSettlRateDisruptionFallbackGrp**

#### 180.2.6669 UnderlyingSettlRateFallbackReferencePage

Identifies the reference "page" from the rate source.

When UnderlyingSettlRateFallbackRateSource(40904) = 3 (ISDA Settlement Rate Option) this contains the value from the scheme that reflects the terms of the Annex A to the ISDA 1998 FX and Currency Option Definitions. See: <http://www.fpml.org/coding-scheme/settlement-rate-option>

Type: **String**

Used in components: **UnderlyingSettlRateFallbackRateSource**

**180.2.6670 UnderlyingSettlRateIndex**

In an outright or forward commodity trade that is cash settled this is the index used to determine the cash payment.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.6671 UnderlyingSettlRateIndexLocation**

This is an optional qualifying attribute of UnderlyingSettlementRateIndex(2284) such as the delivery zone for an electricity contract.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.6672 UnderlyingSettlRatePostponementCalculationAgent**

Used to identify the settlement rate postponement calculation agent.

Type: **int**

Allowed values in ProvisionCalculationAgentCodeSet:

Code	Name	Description
0	ExercisingParty	Exercising party
1	NonExercisingParty	Non-exercising party
2	MasterAgreement	As specified in the master agreement
3	Supplement	As specified in the standard terms supplement

Used in groups: **UnderlyingSettlRateDisruptionFallbackGrp**

**180.2.6673 UnderlyingSettlRatePostponementMaximumDays**

The maximum number of days to wait for a quote from the disrupted settlement rate option before proceeding to this method.

Type: **int**

Used in groups: **UnderlyingSettlRateDisruptionFallbackGrp**

**180.2.6674 UnderlyingSettlRatePostponementSurvey**

Indicates whether to request a settlement rate quote from the market.

Type: **Boolean**

Used in groups: **UnderlyingSettlRateDisruptionFallbackGrp**

**180.2.6675 UnderlyingSettlTermXIDRef**

Reference to the cash or physical settlement terms applicable to this entity or obligation. Contains the same XID named string value of the instance in the appropriate repeating group that applies to this Underlying.

Type: **XIDREF**

Used in components: **UnderlyingInstrument**

**180.2.6676 UnderlyingShortSaleRestriction**

Indicates whether a restriction applies to short selling a security.

Type: **int**

Allowed values in ShortSaleRestrictionCodeSet:

Code	Name	Description
0	NoRestrictions	No restrictions
1	SecurityNotShortable	Security is not shortable
2	SecurityNotShortableAtOrBelowBestBid	Security not shortable at or below the best bid
3	SecurityNotShortableWithoutPre-Borrow	Security is not shortable without pre-borrow

Used in components: **UnderlyingInstrument**

**180.2.6677 UnderlyingSpecialDividendsIndicator**

Indicates whether special dividends are applicable.

Type: **Boolean**

Used in components: **UnderlyingDividendConditions**

**180.2.6678 UnderlyingStartValue**

Currency value attributed to this collateral at the start of the agreement

Type: **Amt**

Used in components: **UnderlyingInstrument**

**180.2.6679 UnderlyingStateOrProvinceOfIssue**

Underlying security's StateOrProvinceOfIssue.

See StateOrProvinceOfIssue (471) field for description

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.6680 UnderlyingStipType**

Type of stipulation.

Same values as StipulationType (233)

Type: **String**

Allowed values in StipulationTypeCodeSet:

Code	Name	Description
ABS	AbsolutePrepaymentSpeed	Absolute Prepayment Speed
AMT	AlternativeMinimumTax	Alternative Minimum Tax (Y/N)
INCURRCVY	IncurredRecovery	Incurred recovery (Y/N). Specifies whether incurred recovery is applicable (Y) or not (N). Outstanding Swap Notional Amount is defined at any time on any day, as the greater of: (a) Zero; If Incurred Recovery Amount Applicable: (b) The Original Swap Notional Amount minus the sum of all Incurred Loss Amounts and all Incurred Recovery Amounts (if any) determined under this Confirmation at or prior to such time. Incurred Recovery Amount not populated: (b) The Original Swap Notional Amount minus the sum of all Incurred Loss Amounts determined under this Confirmation at or prior to such time. 2009 CDX Tranche Terms.

Code	Name	Description
ADDTM	AdditionalTerm	Additional term. Used for representing information contained in the Additional Terms field of the 2003 Master Credit Derivatives confirm.
AUTOREINV	AutoReinvestment	Auto Reinvestment at <rate> or better
CPP	ConstantPrepaymentPenalty	Constant Prepayment Penalty
BANKQUAL	BankQualified	Bank qualified (Y/N)
CPR	ConstantPrepaymentRate	Constant Prepayment Rate
MODEQTYDLVY	ModifiedEquityDelivery	Modified equity delivery. Indicates whether delivery of selected obligations having an amount greater than the reference entity notional amount is allowed (Y) or (N). 2005 iTraxx tranching Transactions Standard Terms Supplement.
BGNCON	BargainConditions	Bargain conditions (see StipulationValue (234) for values)
CPY	ConstantPrepaymentYield	Constant Prepayment Yield
NOREFOBLIG	NoReferenceObligation	No reference obligation (Y/N). When specified as "Y" this indicates that there is no Reference Obligation associated with this Credit Default Swap and that there will never be one. 2003 ISDA Credit Derivatives Definitions.
COUPON	CouponRange	Coupon range
HEP	FinalCPROfHomeEquityPrepaymentCurve	final CPR of Home Equity Prepayment Curve
UNKREFOBLIG	UnknownReferenceObligation	Unknown reference obligation (Y/N). When specified as "Y" this indicates that the Reference obligation associated with the Credit Default Swap is currently not known. This is not valid for Legal Confirmation purposes, but is valid for earlier stages in the trade life cycle (e.g. Broker Confirmation). 2003 FpML-CD-4.0.
ALLGUARANTEES	AllGuarantees	All guarantees (Y/N). Indicates whether an obligation of the Reference Entity, guaranteed by the Reference Entity on behalf of a non-Affiliate, is to be considered an Obligation for the purpose of the transaction (Y) or (N). ISDA 2003 Term: All Guarantees.
CURRENCY	ISOCurrencyCode	ISO Currency Code
MHP	PercentOfManufacturedHousingPrepaymentCurve	Percent of Manufactured Housing Prepayment Curve
CUSTOMDATE	CustomStart	Custom start/end date
MPR	MonthlyPrepaymentRate	Monthly Prepayment Rate

Code	Name	Description
REFPX	ReferencePrice	Reference price (Y/N). Specifies the reference price expressed as a percentage between 0 and 1 (e.g. 0.05 is 5%). The reference price is used to determine (a) for physically settled trades, the Physical Settlement Amount, which equals the Floating Rate Payer Calculation Amount times the Reference Price and (b) for cash settled trades, the Cash Settlement Amount, which equals the greater of (i) the difference between the Reference Price and the Final Price and (ii) zero. ISDA 2003 Term: Reference Price.
GEOG	Geographics	Geographics and % range (ex. 234=CA 0-80 [minimum of 80% California assets])
PPC	PercentOfProspectusPrepaymentCurve	Percent of Prospectus Prepayment Curve
REFPOLICY	ReferencePolicy	Reference policy (Y/N). Indicates whether the reference obligation is guaranteed (Y), or not (N), under a reference policy. If the Reference Obligation is guaranteed under a Reference Policy, and such Reference Policy by its terms excludes any component of the Expected Principal Amount for purposes of determining the liability of the relevant Insurer, or the Insurer is otherwise not required to pay any such amounts under the terms of the Reference Policy, the relevant component or amount shall also be excluded for purposes of determining the Expected Principal Amount with respect to any determination of Principal Shortfall hereunder. 2006 ISDA CDS on MBS Terms.
HAIRCUT	ValuationDiscount	Valuation Discount
PSA	PercentOfBMAPrepaymentCurve	Percent of BMA Prepayment Curve
SECRDLIST	SecuredList	Secured list (Y/N). Specifies whether a list of Syndicated Secured Obligations (also known as the Relevant Secured List) exists (Y), or not (N), for the Reference Entity. With respect to any day, the list of Syndicated Secured Obligations of the Designated Priority of the Reference Entity published by Markit Group Limited or any successor thereto appointed by the Specified Dealers (the "Secured List Publisher") on or most recently before such day, which list is currently available at [ <a href="http://www.markit.com">http://www.markit.com</a> ]. ISDA 2003 Term: Relevant Secured List.
INSURED	Insured	Insured (Y/N)
SMM	SingleMonthlyMortality	Single Monthly Mortality

Code	Name	Description
ISSUE	IssueDate	Year Or Year/Month of Issue (ex. 234=2002/09)
ISSUER	Issuer	Issuer's ticker
ISSUESIZE	IssueSizeRange	issue size range
LOOKBACK	LookbackDays	Lookback Days
LOT	ExplicitLotIdentifier	Explicit lot identifier
LOTVAR	LotVariance	Lot Variance (value in percent maximum over- or under-allocation allowed)
MAT	MaturityYearAndMonth	Maturity Year And Month
MATURITY	MaturityRange	Maturity range
MAXSUBS	MaximumSubstitutions	Maximum substitutions (Repo)
MINDNOM	MinimumDenomination	Minimum denomination
MININCR	MinimumIncrement	Minimum increment
MINQTY	MinimumQuantity	Minimum quantity
PAYFREQ	PaymentFrequency	Payment frequency, calendar
PIECES	NumberOfPieces	Number Of Pieces
PMAX	PoolsMaximum	Pools Maximum
PPL	PoolsPerLot	Pools per Lot
PPM	PoolsPerMillion	Pools per Million
PPT	PoolsPerTrade	Pools per Trade
PRICE	PriceRange	Price Range
PRICEFREQ	PricingFrequency	Pricing frequency
PROD	ProductionYear	Production Year
PROTECT	CallProtection	Call protection
PURPOSE	Purpose	Purpose
PXSOURCE	BenchmarkPriceSource	Benchmark price source
RATING	RatingSourceAndRange	Rating source and range
REDEMPTION	TypeOfRedemption	Type Of Redemption - values are: NonCallable, Prefunded, EscrowedToMaturity, Puttable, Convertible
RESTRICTED	Restricted	Restricted (Y/N)
SECTOR	MarketSector	Market Sector
SECTYPE	SecurityTypeIncludedOrExcluded	Security Type included or excluded
STRUCT	Structure	Structure
SUBSFREQ	SubstitutionsFrequency	Substitutions frequency (Repo)
SUBSLEFT	SubstitutionsLeft	Substitutions left (Repo)

Code	Name	Description
TEXT	FreeformText	Freeform Text
TRDVAR	TradeVariance	Trade Variance (value in percent maximum over- or under-allocation allowed)
WAC	WeightedAverageCoupon	Weighted Average Coupon - value in percent (exact or range) plus "Gross" or "Net" of servicing spread (the default) (ex. 234=6.5-Net [minimum of 6.5% net of servicing fee])
WAL	WeightedAverageLifeCoupon	Weighted Average Life Coupon - value in percent (exact or range)
WALA	WeightedAverageLoanAge	Weighted Average Loan Age - value in months (exact or range)
WAM	WeightedAverageMaturity	Weighted Average Maturity - value in months (exact or range)
WHOLE	WholePool	Whole Pool (Y/N)
YIELD	YieldRange	Yield Range
AVFICO	AverageFICOScore	Average FICO Score
ORIGAMT	OriginalAmount	Original amount. The original issued amount of a mortgage backed security or other loan/asset backed security.
AVSIZE	AverageLoanSize	Average Loan Size
POOLEFFDT	PoolEffectiveDate	Pool effective date
MAXBAL	MaximumLoanBalance	Maximum Loan Balance
POOLINITFCTR	PoolInitialFactor	Pool initial factor. For morttgage backed securities, the part of the mortgage that is outstanding on trade inception, i.e. has not been repaid yet as principal. It is expressed as a multiplier factor to the mortgage: where 1 means that the whole mortgage amount is outstanding, 0.8 means that80% remains to be repaid and 20% has been repaid.
POOL	PoolIdentifier	Pool Identifier
TRANCHE	Tranche	Tranche identifier. Identifies the tranche of a mortgage backed security, loan, collateralized mortgage obligation or similar securities that can be split into different risk or maturity (for example) classes.
ROLLTYPE	TypeOfRollTrade	Type of Roll trade
SUBSTITUTION	Substitution	Substitution (Y/N). Indicates whether substitution is applicable (Y) or (N).



Code	Name	Description
MULTEXCHFLLBCK	MULTEXCHFLLBCK	Multiple exchange fallback (Y/N). For an index option transaction, indicates whether a relevant "Multiple Exchange Index Annex" is applicable (Y) to the transaction or not (N). This annex defines additional provisions which are applicable where an index is comprised of component securities that are traded on multiple exchanges.
REFTRADE	ReferenceToRollingOrClosing-Trade	Reference to rolling or closing trade
COMPSECFLBCK	COMPSECFLBCK	Component security fallback (Y/N). For an index option transaction, indicates whether a relevant "Component Security Index Annex" is applicable (Y) to the transaction or not (N).
REFPRIN	PrincipalOfRollingOrClosing-Trade	Principal to rolling or closing trade
LOCLJRSDCTN	LOCLJRSDCTN	Local jurisdiction (Y/N). "Local Jurisdiction" is used in the AEJ Master Confirmation to determine applicability (Y), or not (N), of local taxes (including taxes, duties, and similar charges) imposed by the taxing authority of the local jurisdiction.
REFINT	InterestOfRollingOrClosingTrade	Interest of rolling or closing trade
AVAILQTY	AvailableOfferQuantity-ToBeShownToTheStreet	Available offer quantity to be shown to the street
RELVJRSDCTN	RELVJRSDCTN	Relevant jurisdiction (Y/N). "Relevant Jurisdiction" is used in the AEJ Master Confirmation to determine applicability (Y), or not (N), of local taxes (including taxes, duties and similar charges) that would be imposed by the taxing authority of the "country of underlier" on a "hypothetical broker dealer" assuming that the applicable hedge positions are held by its office in the Relevant Jurisdiction.
BROKERCREDIT	BrokerCredit	Broker's sales credit
INTERNALPX	OfferPriceToBeShownToInternalBrokers	Offer price to be shown to internal brokers
INTERNALQTY	OfferQuantityToBeShownToInternalBrokers	Offer quantity to be shown to internal brokers
LEAVEQTY	TheMinimumResidualOffer-Quantity	The minimum residual offer quantity
MAXORDQTY	MaximumOrderSize	Maximum order size
ORDRINCR	OrderQuantityIncrement	Order quantity increment

Code	Name	Description
PRIMARY	PrimaryOrSecondaryMarketIndicator	Primary or Secondary market indicator
SALESCREDITOVR	BrokerSalesCreditOverride	Broker sales credit override
TRADERCREDIT	TraderCredit	Trader's credit
DISCOUNT	DiscountRate	Discount Rate (when price is denominated in percent of par)
YTM	YieldToMaturity	Yield to Maturity (when YieldType(235) and Yield(236) show a different yield)
PAYOFF	InterestPayoffOfRollingOrAmendingTrade	Interest payoff of rolling or amending trade

Used in groups: [UnderlyingStipulations](#)

### 180.2.6681 UnderlyingStipulations

The UnderlyingStipulations component block has the same usage as the Stipulations component block, but for an underlying security.

Name	Mult.	Type	Description
NoUnderlyingStips	[1..1]	NumInGroup	
UnderlyingStipType	[0..1]	CodeSet	Required if NoUnderlyingStips >0
UnderlyingStipValue	[0..1]	String	

Used in components: [UnderlyingInstrument](#)

### 180.2.6682 UnderlyingStipValue

Value of stipulation.

Same values as StipulationValue (234)

Type: [String](#)

Used in groups: [UnderlyingStipulations](#)

**180.2.6683 UnderlyingStrategyType**

Specifies the type of trade strategy.

Type: **String**

Allowed values in StrategyTypeCodeSet:

Code	Name	Description
STD	Straddle	Straddle
STG	Strangle	Strangle
BF	Butterfly	Butterfly
CNDR	Condor	Condor
CISN	CallableInversibleSnowball	Callable inversible snowball
OTHER	Other	Other

Used in components: **UnderlyingInstrument**

**180.2.6684 UnderlyingStreamAssetAttributeGrp**

The UnderlyingStreamAssetAttributeGrp is a repeating subcomponent of the UnderlyingStreamCommodity component used to detail commodity attributes, quality standards and reject limits.

Name	Mult.	Type	Description
<b>NoUnderlyingStreamAssetAttributes</b>	[1..1]	NumInGroup	
<b>UnderlyingStreamAssetAttributeType</b>	[0..1]	String	Required if NoUnderlyingStreamAssetAttributes(41800) > 0.
<b>UnderlyingStreamAssetAttributeValue</b>	[0..1]	String	
<b>UnderlyingStreamAssetAttributeLimit</b>	[0..1]	String	

Used in components: **UnderlyingStreamCommodity**

**180.2.6685 UnderlyingStreamAssetAttributeLimit**

The limit or lower acceptable value of the attribute.

Type: **String**

Used in groups: **UnderlyingStreamAssetAttributeGrp**

**180.2.6686 UnderlyingStreamAssetAttributeType**

Specifies the name of the attribute.

See [http://www.fixtradingcommunity.org/codelists#Asset\\_Attribute\\_Types](http://www.fixtradingcommunity.org/codelists#Asset_Attribute_Types) for code list of applicable asset attribute types.

Type: **String**

Used in groups: **UnderlyingStreamAssetAttributeGrp**

**180.2.6687 UnderlyingStreamAssetAttributeValue**

Specifies the value of the attribute.

Type: **String**

Used in groups: **UnderlyingStreamAssetAttributeGrp**

**180.2.6688 UnderlyingStreamCalculationBalanceOfFirstPeriod**

When specified and set to 'Y', it indicates that the first calculation period should run from the effective date to the end of the calendar period in which the effective date falls (e.g. Jan 15 - Jan 31 if the calculation periods are one month long and effective date is Jan 15.). If 'N' or not specified, it indicates that the first calculation period should run from the effective date for one whole period (e.g. Jan 15 to Feb 14 if the calculation periods are one month long and the effective date is Jan 15.).

Type: **Boolean**

Used in components: **UnderlyingStreamCalculationPeriodDates**

**180.2.6689 UnderlyingStreamCalculationCorrectionPeriod**

Time unit multiplier for the length of time after the publication of the data when corrections can be made.

Type: **int**

Used in components: **UnderlyingStreamCalculationPeriodDates**

**180.2.6690 UnderlyingStreamCalculationCorrectionUnit**

Time unit associated with the length of time after the publication of the data when corrections can be made.

Type: **String**

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: **UnderlyingStreamCalculationPeriodDates**

**180.2.6691 UnderlyingStreamCalculationFrequencyPeriod**

Time unit multiplier for the frequency at which calculation period end dates occur.

Type: **int**

Used in components: **UnderlyingStreamCalculationPeriodDates**

**180.2.6692 UnderlyingStreamCalculationFrequencyUnit**

Time unit associated with the frequency at which calculation period end dates occur.

Type: **String**

Allowed values in CouponFrequencyUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
H	Hour	Hour
Min	Minute	Minute

Code	Name	Description
S	Second	Second
T	Term	Term

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

### 180.2.6693 UnderlyingStreamCalculationPeriodBusinessCenter

The business center calendar used to adjust the calculation periods, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingStreamCalculationPeriodBusinessCenterGrp](#)

### 180.2.6694 UnderlyingStreamCalculationPeriodBusinessCenterGrp

UnderlyingStreamCalculationPeriodBusinessCenterGrp is a repeating subcomponent within the UnderlyingStreamCalculationPeriodDates component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingStreamCalculationPeriodBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingStreamCalculationPeriodBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoUnderlyingStreamCalculationPeriodBusinessCenters</a> (40973) > 0.

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

### 180.2.6695 UnderlyingStreamCalculationPeriodBusinessDayConvention

The business day convention used to adjust the calculation periods. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

#### 180.2.6696 UnderlyingStreamCalculationPeriodDate

The adjusted or unadjusted fixed calculation period date.

Type: [LocalMktDate](#)

Used in groups: [UnderlyingStreamCalculationPeriodDateGrp](#)

#### 180.2.6697 UnderlyingStreamCalculationPeriodDateGrp

The UnderlyingStreamCalculationPeriodDateGrp is a repeating subcomponent of the UnderlyingStreamCalculationPeriodDates component used to detail fixed dates for the swap stream.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingStreamCalculationPeriodDates</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingStreamCalculationPeriodDate</a>	[0..1]	LocalMktDate	Required if <a href="#">NoUnderlyingStreamCalculationPeriodDates</a> (41954) > 0.
<a href="#">UnderlyingStreamCalculationPeriodDateType</a>	[0..1]	CodeSet	When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

## 180.2.6698 UnderlyingStreamCalculationPeriodDates

UnderlyingStreamCalculationPeriodDates is a subcomponent of the UnderlyingStreamGrp component used to specify the calculation period dates of the stream.

Name	Mult.	Type	Description
UnderlyingStreamCalculationPeriod-DatesXID	[0..1]	XID	
UnderlyingStreamCalculationPeriod-DatesXIDRef	[0..1]	XIDREF	
UnderlyingStreamCalculationPeriod-BusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's calculation period dates.
UnderlyingStreamCalculationPeriod-BusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's calculation period dates.
UnderlyingStreamCalculationPeriod-DateGrp	[0..*]	Group	
UnderlyingStreamFirstPeriodStartDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingStreamFirstPeriodStartDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's calculation period dates.
UnderlyingStreamFirstPeriodStartDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's calculation period dates.
UnderlyingStreamFirstPeriodStartDateAdjusted	[0..1]	LocalMktDate	
UnderlyingStreamFirstRegularPeriodStartDateUnadjusted	[0..1]	LocalMktDate	



Name	Mult.	Type	Description
UnderlyingStreamFirstCompounding-PeriodEndDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingStreamLastRegularPeriodEndDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingStreamCalculationFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingStreamCalculationFrequencyUnit(40566) is specified.
UnderlyingStreamCalculationFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingStreamCalculationFrequencyPeriod(40565) is specified.
UnderlyingStreamCalculationRollConvention	[0..1]	CodeSet	When specified, this overrides the date roll convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the stream payment dates.
UnderlyingStreamCalculationBalance-OfFirstPeriod	[0..1]	Boolean	
UnderlyingStreamCalculationCorrectionPeriod	[0..1]	int	Conditionally required when UnderlyingStreamCalculationCorrectionUnit(41961) is specified.
UnderlyingStreamCalculationCorrectionUnit	[0..1]	CodeSet	Conditionally required when UnderlyingStreamCalculationCorrectionPeriod(41960) is specified.

Used in groups: [UnderlyingStreamGrp](#)

### 180.2.6699 UnderlyingStreamCalculationPeriodDatesXID

Identifier of this calculation period for cross referencing elsewhere in the message.

Type: [XID](#)

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

### 180.2.6700 UnderlyingStreamCalculationPeriodDatesXIDRef

Cross reference to another calculation period for duplicating its properties.

Type: [XIDREF](#)

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

**180.2.6701 UnderlyingStreamCalculationPeriodDateType**

Specifies the type of fixed calculation period date. When specified it applies not only to the current date but to all subsequent dates in the group until overridden with a new type.

Type: **int**

Allowed values in OptionExerciseDateTypeCodeSet:

Code	Name	Description
0	Unadjusted	Unadjusted
1	Adjusted	Adjusted

Used in groups: **UnderlyingStreamCalculationPeriodDateGrp**

**180.2.6702 UnderlyingStreamCalculationRollConvention**

The convention for determining the sequence of end dates. It is used in conjunction with a specified frequency. Used only to override the roll convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: **String**

Allowed values in DateRollConventionCodeSet:

Code	Name	Description
1	FirstDay	1st day of the month
2	SecondDay	2nd day of the month
3	ThirdDay	3rd day of the month
4	FourthDay	4th day of the month
5	FifthDay	5th day of the month
6	SixthDay	6thd day of the month
7	SeventhDay	7th day of the month
8	EighthDay	8th day of the month
9	NinthDay	9th day of the month
10	TenthDay	10th day of the month
11	EleventhDay	11th day of the month
12	TwelvthDay	12th day of the month

Code	Name	Description
13	ThirteenthDay	13th day of the month
14	ForteenthDay	14th day of the month
15	FifteenthDay	15th day of the month
16	SixteenthDay	16th day of the month
17	SeventeenthDay	17th day of the month
18	EighteenthDay	18th day of the month
19	NineteenthDay	19th day of the month
20	TwentiethDay	20th day of the month
21	TwentyFirstDay	21st day of the month
22	TwentySecondDay	22nd day of the month
23	TwentyThirdDay	23rd day of the month
24	TwentyFourthDay	24th day of the month
25	TwentyFifthDay	25th day of the month
26	TwentySixthDay	26th day of the month
27	TwentySeventhDay	27th day of the month
28	TwentyEighthDay	28th day of the month
29	TwentyNinthDay	29th day of the month
30	ThirtiethDay	30th day of the month
EOM	EOM	The end of the month. Use EOM for 31st day of the month.
FRN	FRN	The floating rate note convention or Eurodollar convention.
IMM	IMM	The International Money Market settlement date, i.e. the 3rd Wednesday of the month.
IMMCAD	IMMCAD	The last trading day/expiration day of the Canadian Derivatives Exchange.
IMMAUD	IMMAUD	The last trading day of the Sydney Futures Exchange Australian 90-day bank accepted bill futures contract.
IMMNZD	IMMNZD	The last trading day of the Sydney Futures Exchange New Zealand 90-day bank bill futures contract.
SFE	SFE	The Sydney Futures Exchange 90-day bank accepted bill futures settlement dates.
NONE	NONE	No adjustment
TBILL	TBILL	The 13-week and 26-week U.S. Treasury Bill auction dates.
MON	MON	Monday
TUE	TUE	Tuesday
WED	WED	Wednesday

Code	Name	Description
THU	THU	Thursday
FRI	FRI	Friday
SAT	SAT	Saturday
SUN	SUN	Sunday

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

### 180.2.6703 UnderlyingStreamCommodityAltID

Alternate security identifier value for the commodity.

Type: [String](#)

Used in groups: [UnderlyingStreamCommodityAltIDGrp](#)

### 180.2.6704 UnderlyingStreamCommodityAltIDGrp

UnderlyingStreamCommodityAltIDGrp is a subcomponent of the UnderlyingStreamCommodity component used to specify alternate identifiers.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingStreamCommodityAltIDs</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingStreamCommodityAltID</a>	[0..1]	String	Required if <a href="#">NoUnderlyingStreamCommodityAltIDs</a> (41990) > 0.
<a href="#">UnderlyingStreamCommodityAltID-Source</a>	[0..1]	String	Required if <a href="#">NoUnderlyingStreamCommodityAltIDs</a> (41990) > 0.

Used in components: [UnderlyingStreamCommodity](#)

### 180.2.6705 UnderlyingStreamCommodityAltIDSource

Identifies the class or source of the alternate commodity security identifier.

Type: [String](#)

Used in groups: [UnderlyingStreamCommodityAltIDGrp](#)

**180.2.6706 UnderlyingStreamCommodityBase**

Specifies the general base type of the commodity traded. Where possible, this should follow the naming convention used in the 2005 ISDA Commodity Definitions.

Type: **String**

Used in components: **UnderlyingStreamCommodity**

**180.2.6707 UnderlyingStreamCommodity**

UnderlyingStreamCommodity is a subcomponent of the UnderlyingStream component used to identify and describe the underlying commodity.

Name	Mult.	Type	Description
<b>UnderlyingStreamCommodityBase</b>	[0..1]	String	
<b>UnderlyingStreamCommodityType</b>	[0..1]	String	
<b>UnderlyingStreamCommoditySecurityID</b>	[0..1]	String	Conditionally required when UnderlyingStreamCommoditySecurityIDSource(41967) is specified.
<b>UnderlyingStreamCommoditySecurityIDSource</b>	[0..1]	CodeSet	Conditionally required when UnderlyingStreamCommoditySecurityID(41966) is specified.
<b>UnderlyingStreamCommodityAltIDGrp</b>	[0..*]	Group	
<b>UnderlyingStreamCommodityDesc</b>	[0..1]	String	
<b>EncodedUnderlyingStreamCommodityDescLen</b>	[0..1]	Length	Must be set if EncodedUnderlyingStreamCommodityDesc(41970) field is specified and must immediately precede it.
<b>EncodedUnderlyingStreamCommodityDesc</b>	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingStreamCommodityDesc(41968) field in the encoded format specified via the MessageEncoding(347) field.
<b>UnderlyingStreamCommodityDeliveryPricingRegion</b>	[0..1]	String	May be used to specify the delivery or pricing region of a non-standard commodity swap contract (e.g. when InstrAttribType(871)=38 (US standard contract indicator) and InstrAttribValue(872)=N).
<b>UnderlyingStreamAssetAttributeGrp</b>	[0..*]	Group	
<b>UnderlyingStreamCommodityUnitOfMeasure</b>	[0..1]	CodeSet	
<b>UnderlyingStreamCommodityCurrency</b>	[0..1]	Currency	

Name	Mult.	Type	Description
UnderlyingStreamCommodityExchange	[0..1]	Exchange	
UnderlyingStreamCommodityRateSource	[0..1]	int	
UnderlyingStreamCommodityRateReferencePage	[0..1]	String	
UnderlyingStreamCommodityRateReferencePageHeading	[0..1]	String	
UnderlyingStreamDataProvider	[0..1]	String	
UnderlyingStreamCommodityDataSourceGrp	[0..*]	Group	
UnderlyingStreamCommodityPricingType	[0..1]	String	
UnderlyingStreamCommodityNearbySettlDayPeriod	[0..1]	int	Conditionally required when UnderlyingStreamCommodityNearbySettlDayUnit(41980) is specified.
UnderlyingStreamCommodityNearbySettlDayUnit	[0..1]	CodeSet	Conditionally required when UnderlyingStreamCommodityNearbySettlDayPeriod(41979) is specified.
UnderlyingStreamCommoditySettlDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingStreamCommoditySettlDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to the underlying settlement dates.
UnderlyingStreamCommoditySettlBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to the settlement dates.
UnderlyingStreamCommoditySettlDateAdjusted	[0..1]	LocalMktDate	
UnderlyingStreamCommoditySettlMonth	[0..1]	int	
UnderlyingStreamCommoditySettlDateRollPeriod	[0..1]	int	Conditionally required when UnderlyingStreamCommoditySettlDateRollUnit(41986) is specified.
UnderlyingStreamCommoditySettlDateRollUnit	[0..1]	CodeSet	Conditionally required when UnderlyingStreamCommoditySettlDateRollPeriod(41985) is specified.

Name	Mult.	Type	Description
UnderlyingStreamCommoditySettlDayType	[0..1]	CodeSet	
UnderlyingStreamCommoditySettlPeriodGrp	[0..*]	Group	
UnderlyingStreamCommodityXID	[0..1]	XID	
UnderlyingStreamCommodityXIDRef	[0..1]	XIDREF	

Used in groups: [UnderlyingStreamGrp](#)

### 180.2.6708 UnderlyingStreamCommodityCurrency

Identifies the currency of the commodity asset. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in components: [UnderlyingStreamCommodity](#)

### 180.2.6709 UnderlyingStreamCommodityDataSourceGrp

UnderlyingStreamCommodityDataSourceGrp is a subcomponent of the UnderlyingStreamCommodity component used to specify sources of data, e.g. weather stations. The order of entry determines priority – first is the main source, second is fallback, third is second fallback.

Name	Mult.	Type	Description
NoUnderlyingStreamCommodityDataSources	[1..1]	NumInGroup	
UnderlyingStreamCommodityDataSourceID	[0..1]	String	Required if NoUnderlyingStreamCommodityDataSources(41993) > 0.
UnderlyingStreamCommodityDataSourceIDType	[0..1]	CodeSet	Required if NoUnderlyingStreamCommodityDataSources(41993) > 0.

Used in components: [UnderlyingStreamCommodity](#)

### 180.2.6710 UnderlyingStreamCommodityDataSourceID

Data source identifier.

Type: **String**

Used in groups: **UnderlyingStreamCommodityDataSourceGrp**

### **180.2.6711 UnderlyingStreamCommodityDataSourceIDType**

Specifies the type of data source identifier.

Type: **int**

Allowed values in StreamCommodityDataSourceIDTypeCodeSet:

Code	Name	Description
0	City	City (4 character business center code)
1	Airport	Airport (IATA standard)
2	WeatherStation	Weather station WBAN (Weather Bureau Army Navy)
3	WeatherIndex	Weather index WMO (World Meteorological Organization)

Used in groups: **UnderlyingStreamCommodityDataSourceGrp**

### **180.2.6712 UnderlyingStreamCommodityDeliveryPricingRegion**

The delivery or pricing region associated with the commodity swap. See [http://www.ecfr.gov/cgi-bin/text-idx?SID=660d6a40f836aa6ddf213cba080c5b22&node=ap17.2.43\\_17.e&rgn=div9](http://www.ecfr.gov/cgi-bin/text-idx?SID=660d6a40f836aa6ddf213cba080c5b22&node=ap17.2.43_17.e&rgn=div9) for the external code list.

Type: **String**

Used in components: **UnderlyingStreamCommodity**

### **180.2.6713 UnderlyingStreamCommodityDesc**

Description of the commodity asset.

Type: **String**

Used in components: **UnderlyingStreamCommodity**



**180.2.6714 UnderlyingStreamCommodityExchange**

Identifies the exchange where the commodity is traded.

Type: **Exchange**

Used in components: **UnderlyingStreamCommodity**

**180.2.6715 UnderlyingStreamCommodityNearbySettlDayPeriod**

Time unit multiplier for the nearby settlement day.

Type: **int**

Used in components: **UnderlyingStreamCommodity**

**180.2.6716 UnderlyingStreamCommodityNearbySettlDayUnit**

Time unit associated with the nearby settlement day.

Type: **String**

Allowed values in StreamCommodityNearbySettlDayUnitCodeSet:

---

Code	Name	Description
Wk	Week	Week
Mo	Month	Month

---

Used in components: **UnderlyingStreamCommodity**

**180.2.6717 UnderlyingStreamCommodityPricingType**

Specifies how the pricing or rate setting of the trade is to be determined or based upon.

See [http://www.fixtradingcommunity.org/codelists#Commodity\\_Rate\\_Pricing\\_Type](http://www.fixtradingcommunity.org/codelists#Commodity_Rate_Pricing_Type) for code list of applicable commodity pricing types.

Type: **String**

Used in components: **UnderlyingStreamCommodity**

### **180.2.6718 UnderlyingStreamCommodityRateReferencePage**

Identifies the reference "page" from the rate source.

Type: **String**

Used in components: **UnderlyingStreamCommodity**

### **180.2.6719 UnderlyingStreamCommodityRateReferencePageHeading**

Identifies the page heading from the rate source.

Type: **String**

Used in components: **UnderlyingStreamCommodity**

### **180.2.6720 UnderlyingStreamCommodityRateSource**

Identifies the source of rate information used for commodities.

See [http://www.fixtradingcommunity.org/codelists#Commodity\\_Rate\\_Source](http://www.fixtradingcommunity.org/codelists#Commodity_Rate_Source) for code list of applicable sources.

Type: **int**

Used in components: **UnderlyingStreamCommodity**

### **180.2.6721 UnderlyingStreamCommoditySecurityID**

Specifies the market identifier for the commodity.

Type: **String**

Used in components: **UnderlyingStreamCommodity**

### **180.2.6722 UnderlyingStreamCommoditySecurityIDSource**

Identifies the class or source of the UnderlyingStreamCommoditySecurityIDSource(41966) value.

Type: **String**

Allowed values in SecurityIDSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
3	QUIK	QUIK
4	ISINNumber	ISIN
5	RICCode	RIC
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
7	ISOCountryCode	ISO Country Code
8	ExchangeSymbol	Exchange symbol
9	ConsolidatedTapeAssociation	Consolidated Tape Association (CTA) Symbol (SIAC CTS/CQS line format)
A	BloombergSymbol	Bloomberg Symbol
B	Wertpapier	Wertpapier
C	Dutch	Dutch
D	Valoren	Valoren
E	Sicovam	Sicovam
F	Belgian	Belgian
G	Common	"Common" (Clearstream and Euroclear)
H	ClearingHouse	Clearing house / Clearing organization
I	ISDAFpMLSpecification	ISDA/FpML product specification (XML in SecurityXML(1185))
J	OptionPriceReportingAuthority	Option Price Reporting Authority
K	ISDAFpMLURL	ISDA/FpML product URL (URL in SecurityID(48))
L	LetterOfCredit	Letter of credit
M	MarketplaceAssignedIdentifier	Marketplace-assigned Identifier
N	MarkitREDEntityCLIP	Markit RED entity CLIP
P	MarkitREDPairCLIP	Markit RED pair CLIP
Q	CFTCCommodityCode	CFTC commodity code
R	ISDACommodityReferencePrice	ISDA Commodity Reference Price
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
T	LegalEntityIdentifier	Legal entity identifier
U	Synthetic	Synthetic. Used to specify that the security identifier is synthetic for linking nested underliers when there is no market identifier for the collection.
V	FidessaInstrumentMnemonic	Fidessa Instrument Mnemonic (FIM)

Code	Name	Description
W	IndexName	Index name. Standard name of the index or rate index, e.g. "LIBOR" or "iTraxx Australia".
X	UniformSymbol	Uniform Symbol (UMTF Symbol)
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingStreamCommodity](#)

### 180.2.6723 UnderlyingStreamCommoditySettlBusinessCenter

The business center calendar used to adjust the commodity delivery date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in groups: [UnderlyingStreamCommoditySettlBusinessCenterGrp](#)

### 180.2.6724 UnderlyingStreamCommoditySettlBusinessCenterGrp

UnderlyingStreamCommoditySettlBusinessCenterGrp is a repeating subcomponent of the UnderlyingStreamCommodity component used to specify the set of business centers whose calendars drive date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingStreamCommoditySettlBusinessCenters</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingStreamCommoditySettlBusinessCenter</a>	[0..1]	String	Required if <a href="#">NoUnderlyingStreamCommoditySettlBusinessCenters</a> (41962) > 0.

Used in components: [UnderlyingStreamCommodity](#)

### 180.2.6725 UnderlyingStreamCommoditySettlCountry

Specifies the country where delivery takes place. Uses ISO 3166 2-character country code.

Type: [Country](#)

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

**180.2.6726 UnderlyingStreamCommoditySettlDateAdjusted**

The adjusted commodity delivery date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingStreamCommodity](#)

**180.2.6727 UnderlyingStreamCommoditySettlDateBusinessDayConvention**

The business day convention used to adjust the commodity delivery date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingStreamCommodity](#)

**180.2.6728 UnderlyingStreamCommoditySettlDateRollPeriod**

Time unit multiplier for the commodity delivery date roll.

Type: [int](#)

Used in components: [UnderlyingStreamCommodity](#)

**180.2.6729 UnderlyingStreamCommoditySettlDateRollUnit**

Time unit associated with the commodity delivery date roll.

Type: **String**

Allowed values in StreamCommoditySettlDateRollUnitCodeSet:

Code	Name	Description
D	Day	Day

Used in components: **UnderlyingStreamCommodity**

**180.2.6730 UnderlyingStreamCommoditySettlDateUnadjusted**

The unadjusted commodity delivery date.

Type: **LocalMktDate**

Used in components: **UnderlyingStreamCommodity**

**180.2.6731 UnderlyingStreamCommoditySettlDay**

Specifies the day or group of days for delivery.

Type: **int**

Allowed values in DeliveryScheduleSettlDayCodeSet:

Code	Name	Description
1	Monday	Monday
2	Tuesday	Tuesday
3	Wednesday	Wednesday
4	Thursday	Thursday
5	Friday	Friday
6	Saturday	Saturday
7	Sunday	Sunday
8	AllWeekdays	All weekdays
9	AllDays	All days

Code	Name	Description
10	AllWeekends	All weekends

Used in groups: [UnderlyingStreamCommoditySettlDayGrp](#)

### 180.2.6732 UnderlyingStreamCommoditySettlDayGrp

The UnderlyingStreamCommoditySettlDayGrp is a repeating subcomponent of the UnderlyingStreamCommoditySettlPeriodGrp component used to define the settlement days associated with the commodity contract.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingStreamCommoditySettlDays</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingStreamCommoditySettlDay</a>	[0..1]	CodeSet	Required if <a href="#">NoUnderlyingStreamCommoditySettlDays</a> (41996) > 0.
<a href="#">UnderlyingStreamCommoditySettlTotalHours</a>	[0..1]	int	
<a href="#">UnderlyingStreamCommoditySettlTimeGrp</a>	[0..*]	Group	

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

### 180.2.6733 UnderlyingStreamCommoditySettlDayType

Specifies the commodity delivery roll day type.

Type: [int](#)

Allowed values in ComplexEventDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business

Code	Name	Description
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingStreamCommodity](#)

#### **180.2.6734 UnderlyingStreamCommoditySettlEnd**

The end time for commodity settlement where delivery occurs over time. The time format is specified by the settlement time type.

Type: [String](#)

Used in groups: [UnderlyingStreamCommoditySettlTimeGrp](#)

#### **180.2.6735 UnderlyingStreamCommoditySettlFlowType**

Specifies the commodity delivery flow type.

Type: [int](#)

Allowed values in DeliveryScheduleSettlFlowTypeCodeSet:

Code	Name	Description
0	AllTimes	All times
1	OnPeak	On peak
2	OffPeak	Off peak
3	Base	Base
4	BlockHours	Block hours
5	Other	Other

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

#### **180.2.6736 UnderlyingStreamCommoditySettlHolidaysProcessingInstruction**

Indicates whether holidays are included in the settlement periods. Required for electricity contracts.

Type: [int](#)



Allowed values in DeliveryScheduleSettlHolidaysProcessingInstructionCodeSet:

Code	Name	Description
0	DoNotIncludeHolidays	Do not include holidays
1	IncludeHolidays	Include holidays

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

#### **180.2.6737 UnderlyingStreamCommoditySettlMonth**

Specifies a fixed single month for commodity delivery.

Type: [int](#)

Used in components: [UnderlyingStreamCommodity](#)

#### **180.2.6738 UnderlyingStreamCommoditySettlPeriodFrequencyPeriod**

Time unit multiplier for the settlement period frequency.

Type: [int](#)

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

#### **180.2.6739 UnderlyingStreamCommoditySettlPeriodFrequencyUnit**

Time unit associated with the settlement period frequency.

Type: [String](#)

Allowed values in ProtectionTermEventUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

**180.2.6740 UnderlyingStreamCommoditySettlPeriodGrp**

The UnderlyingStreamCommoditySettlPeriodGrp is a repeating subcomponent of the UnderlyingStreamCommodity component used to defined the settlement period details associated with the commodity contract.

Name	Mult.	Type	Description
NoUnderlyingStreamCommoditySettlPeriods	[1..1]	NumInGroup	
UnderlyingStreamCommoditySettlCountry	[0..1]	Country	Required if NoUnderlyingStreamCommoditySettlPeriods(42002) > 0.
UnderlyingStreamCommoditySettlTimeZone	[0..1]	String	
UnderlyingStreamCommoditySettlFlowType	[0..1]	CodeSet	
UnderlyingStreamCommoditySettlPeriodNotional	[0..1]	Qty	
UnderlyingStreamCommoditySettlPeriodNotionalUnitOfMeasure	[0..1]	CodeSet	
UnderlyingStreamCommoditySettlPeriodFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingStreamCommoditySettlPeriodFrequencyUnit(42009) is specified.
UnderlyingStreamCommoditySettlPeriodFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingStreamCommoditySettlPeriodFrequencyPeriod(42008) is specified.
UnderlyingStreamCommoditySettlPeriodPrice	[0..1]	Price	
UnderlyingStreamCommoditySettlPeriodPriceUnitOfMeasure	[0..1]	CodeSet	
UnderlyingStreamCommoditySettlPeriodPriceCurrency	[0..1]	Currency	
UnderlyingStreamCommoditySettlHolidaysProcessingInstruction	[0..1]	CodeSet	
UnderlyingStreamCommoditySettlDayGrp	[0..*]	Group	
UnderlyingStreamCommoditySettlPeriodXID	[0..1]	XID	
UnderlyingStreamCommoditySettlPeriodXIDRef	[0..1]	XIDREF	

Used in components: [UnderlyingStreamCommodity](#)

### **180.2.6741 UnderlyingStreamCommoditySettlPeriodNotional**

Specifies the delivery quantity associated with this settlement period.

Type: [Qty](#)

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

### **180.2.6742 UnderlyingStreamCommoditySettlPeriodNotionalUnitOfMeasure**

Specifies the unit of measure (UOM) of the delivery quantity associated with this settlement period.

Type: [String](#)

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes

Code	Name	Description
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre

Code	Name	Description
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

**180.2.6743 UnderlyingStreamCommoditySettlPeriodPrice**

The settlement period price.

Type: **Price**

Used in groups: **UnderlyingStreamCommoditySettlPeriodGrp**

**180.2.6744 UnderlyingStreamCommoditySettlPeriodPriceCurrency**

The currency of the settlement period price. Uses ISO 4217 currency codes.

Type: **Currency**

Used in groups: **UnderlyingStreamCommoditySettlPeriodGrp**

**180.2.6745 UnderlyingStreamCommoditySettlPeriodPriceUnitOfMeasure**

Specifies the settlement period price unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction

Code	Name	Description
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument

Code	Name	Description
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars



Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

#### **180.2.6746 UnderlyingStreamCommoditySettlPeriodXID**

Identifier of this settlement period for cross referencing elsewhere in the message.

Type: [XID](#)

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

#### **180.2.6747 UnderlyingStreamCommoditySettlPeriodXIDRef**

Cross reference to another settlement period for duplicating its properties.

Type: [XIDREF](#)

Used in groups: [UnderlyingStreamCommoditySettlPeriodGrp](#)

#### **180.2.6748 UnderlyingStreamCommoditySettlStart**

The start time for commodity settlement where delivery occurs over time. The time format is specified by the settlement time type.

Type: [String](#)

Used in groups: [UnderlyingStreamCommoditySettlTimeGrp](#)

#### **180.2.6749 UnderlyingStreamCommoditySettlTimeGrp**

The UnderlyingStreamCommoditySettlTimeGrp is a repeating subcomponent of the UnderlyingStreamCommoditySettlDayGrp component used to define the settlement time periods associated with the commodity contract.

Name	Mult.	Type	Description
<a href="#">NoUnderlyingStreamCommoditySettlTimes</a>	[1..1]	NumInGroup	
<a href="#">UnderlyingStreamCommoditySettlStart</a>	[0..1]	String	Required if <a href="#">NoUnderlyingStreamCommoditySettlTimes</a> (41999) > 0.
<a href="#">UnderlyingStreamCommoditySettlEnd</a>	[0..1]	String	Required if <a href="#">NoUnderlyingStreamCommoditySettlTimes</a> (41999) > 0.

Name	Mult.	Type	Description
<b>UnderlyingStreamCommoditySettlTimeType</b>	[0..1]	CodeSet	May be defaulted to market convention or bilaterally agreed if not specified.

Used in groups: **UnderlyingStreamCommoditySettlDayGrp**

### 180.2.6750 UnderlyingStreamCommoditySettlTimeType

Specifies the format of the commodity settlement start and end times.

Type: **int**

Allowed values in DeliveryScheduleSettlTimeTypeCodeSet:

Code	Name	Description
0	Hour	Hour of the day. Applicable for electricity contracts. Time value is expressed as an integer hour of the day (1-24). The delivery start/end hour is specified as the end of the included hour. For example, a start hour of "4" begins at 3 a.m.; an end hour of "20" ends at 8 p.m.; a start hour of "1" and end hour of "24" indicates midnight to midnight delivery.
1	Timestamp	HH:MM time format. Applicable for gas contracts. Time value is expressed using a 24-hour time format. For example, a time value of "13:30" is 1:30 p.m.

Used in groups: **UnderlyingStreamCommoditySettlTimeGrp**

### 180.2.6751 UnderlyingStreamCommoditySettlTimeZone

Commodity delivery timezone specified as "prevailing" rather than "standard" or "daylight".

See [http://www.fixtradingcommunity.org/codelists#Prevailing\\_Timezones](http://www.fixtradingcommunity.org/codelists#Prevailing_Timezones) for code list of applicable prevailing timezones.

Type: **String**

Used in groups: **UnderlyingStreamCommoditySettlPeriodGrp**

**180.2.6752 UnderlyingStreamCommoditySettlTotalHours**

Sum of the hours specified in UnderlyingStreamCommoditySettlTimeGrp.

Type: **int**

Used in groups: **UnderlyingStreamCommoditySettlDayGrp**

**180.2.6753 UnderlyingStreamCommodityType**

Specifies the type of commodity product.

For coal see <http://www.fpml.org/coding-scheme/commodity-coal-product-type> for values.

For metals see <http://www.fpml.org/coding-scheme/commodity-metal-product-type> for values.

For bullion see [http://www.fixtradingcommunity.org/codelists#Bullion\\_Types](http://www.fixtradingcommunity.org/codelists#Bullion_Types) for the external code list of bullion types.

Type: **String**

Used in components: **UnderlyingStreamCommodity**

**180.2.6754 UnderlyingStreamCommodityUnitOfMeasure**

The unit of measure (UOM) of the commodity asset.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours

Code	Name	Description
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)

Code	Name	Description
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile

Code	Name	Description
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [UnderlyingStreamCommodity](#)

#### **180.2.6755 UnderlyingStreamCommodityXID**

Identifier of this stream commodity for cross referencing elsewhere in the message.

Type: [XID](#)

Used in components: [UnderlyingStreamCommodity](#)

#### **180.2.6756 UnderlyingStreamCommodityXIDRef**

Reference to a stream commodity elsewhere in the message.

Type: [XIDREF](#)

Used in components: [UnderlyingStreamCommodity](#)

#### **180.2.6757 UnderlyingStreamCurrency**

Specifies the currency the UnderlyingStreamNotional(40545) is denominated in. Uses ISO 4217 currency codes.

Type: [Currency](#)

Used in groups: [UnderlyingStreamGrp](#)

#### **180.2.6758 UnderlyingStreamDataProvider**

Specifies the commodity data or information provider.

See <http://www.fpml.org/coding-scheme/commodity-information-provider> for values.

Type: **String**

Used in components: **UnderlyingStreamCommodity**

#### **180.2.6759 UnderlyingStreamDesc**

A short descriptive name given to payment stream. Eg. CDS, Fixed, Float, Float2, GBP. The description has no intrinsic meaning but should be arbitrarily chosen by the remitter as a reference.

Type: **String**

Used in groups: **UnderlyingStreamGrp**

#### **180.2.6760 UnderlyingStreamEffectiveDateAdjusted**

The adjusted effective date.

Type: **LocalMktDate**

Used in components: **UnderlyingStreamEffectiveDate**

#### **180.2.6761 UnderlyingStreamEffectiveDateBusinessCenter**

The business center calendar used to adjust the underlying instrument's stream's effective, or relative effective, date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingStreamEffectiveDateBusinessCenterGrp**

#### **180.2.6762 UnderlyingStreamEffectiveDateBusinessCenterGrp**

UnderlyingStreamEffectiveDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingStreamEffectiveDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Name	Mult.	Type	Description
NoUnderlyingStreamEffectiveDate-BusinessCenters	[1..1]	NumInGroup	
UnderlyingStreamEffectiveDateBusinessCenter	[0..1]	String	Required if NoUnderlyingStreamEffectiveDate-BusinessCenters(40975) > 0.

Used in components: [UnderlyingStreamEffectiveDate](#)

### 180.2.6763 UnderlyingStreamEffectiveDateBusinessDayConvention

The business day convention used to adjust the underlying instrument's stream's effective, or relative effective, date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingStreamEffectiveDate](#)

### 180.2.6764 UnderlyingStreamEffectiveDate

UnderlyingStreamEffectivedDate is a subcomponent of the UnderlyingStreamGrp component used to specify the effective date of the stream.



Name	Mult.	Type	Description
UnderlyingStreamEffectiveDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingStreamEffectiveDateBusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's stream effective dates.
UnderlyingStreamEffectiveDateBusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's stream effective dates.
UnderlyingStreamEffectiveDateRelativeTo	[0..1]	int	
UnderlyingStreamEffectiveDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingStreamEffectiveDateOffsetUnit(40062) is specified.
UnderlyingStreamEffectiveDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingStreamEffectiveDateOffsetPeriod(40061) is specified.
UnderlyingStreamEffectiveDateOffsetDayType	[0..1]	CodeSet	
UnderlyingStreamEffectiveDateAdjusted	[0..1]	LocalMktDate	

Used in groups: **UnderlyingStreamGrp**

### 180.2.6765 UnderlyingStreamEffectiveDateOffsetDayType

Specifies the day type of the relative effective date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar

Code	Name	Description
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingStreamEffectiveDate](#)

#### **180.2.6766 UnderlyingStreamEffectiveDateOffsetPeriod**

Time unit multiplier for the relative effective date offset.

Type: [int](#)

Used in components: [UnderlyingStreamEffectiveDate](#)

#### **180.2.6767 UnderlyingStreamEffectiveDateOffsetUnit**

Time unit associated with the relative effective date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingStreamEffectiveDate](#)

#### **180.2.6768 UnderlyingStreamEffectiveDateRelativeTo**

Specifies the anchor date when the effective date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: [int](#)

Used in components: [UnderlyingStreamEffectiveDate](#)

**180.2.6769 UnderlyingStreamEffectiveDateUnadjusted**

The unadjusted effective date.

Type: **LocalMktDate**

Used in components: **UnderlyingStreamEffectiveDate**

**180.2.6770 UnderlyingStreamFirstCompoundingPeriodEndDateUnadjusted**

The unadjusted end date of the initial compounding period.

Type: **LocalMktDate**

Used in components: **UnderlyingStreamCalculationPeriodDates**

**180.2.6771 UnderlyingStreamFirstPeriodStartDateAdjusted**

The adjusted first calculation period start date, if it is before the effective date.

Type: **LocalMktDate**

Used in components: **UnderlyingStreamCalculationPeriodDates**

**180.2.6772 UnderlyingStreamFirstPeriodStartDateBusinessCenter**

The business center calendar used to adjust the underlying instrument's stream's first calculation period start date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingStreamFirstPeriodStartDateBusinessCenterGrp**

**180.2.6773 UnderlyingStreamFirstPeriodStartDateBusinessCenterGrp**

**UnderlyingStreamFirstPeriodStartDateBusinessCenterGrp** is a repeating subcomponent within the **UnderlyingStreamCalculationPeriodDates** component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the **UnderlyingDateAdjustment** component within the **UnderlyingInstrument** component.

Name	Mult.	Type	Description
NoUnderlyingStreamFirstPeriodStartDateBusinessCenters	[1..1]	NumInGroup	
UnderlyingStreamFirstPeriodStartDateBusinessCenter	[0..1]	String	Required if NoUnderlyginstreamFirstPeriodStartDateBusinessCenters(40974) > 0.

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

### 180.2.6774 UnderlyingStreamFirstPeriodStartDateBusinessDayConvention

The business day convention used to adjust the underlying instrument's stream's first calculation period start date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

### 180.2.6775 UnderlyingStreamFirstPeriodStartDateUnadjusted

The unadjusted first calculation period start date if before the effective date.

Type: [LocalMktDate](#)

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

**180.2.6776 UnderlyingStreamFirstRegularPeriodStartDateUnadjusted**

The unadjusted first start date of the regular calculation period, if there is an initial stub period.

Type: **LocalMktDate**

Used in components: **UnderlyingStreamCalculationPeriodDates**

**180.2.6777 UnderlyingStreamGrp**

The UnderlyingStreamGrp is a repeating subcomponent of the UnderlyingInstrument component used to detail the swap streams associated with the instrument.

Name	Mult.	Type	Description
NoUnderlyingStreams	[1..1]	NumInGroup	
UnderlyingStreamType	[0..1]	CodeSet	Required if NoUnderlyingStreams(40540) > 0.
UnderlyingStreamXID	[0..1]	XID	
UnderlyingStreamDesc	[0..1]	String	
UnderlyingStreamVersion	[0..1]	String	
UnderlyingStreamVersionEffectiveDate	[0..1]	LocalMktDate	
UnderlyingStreamPaySide	[0..1]	CodeSet	
UnderlyingStreamReceiveSide	[0..1]	CodeSet	
UnderlyingStreamNotionalXIDRef	[0..1]	XIDREF	
UnderlyingStreamNotional	[0..1]	Amt	
UnderlyingStreamCurrency	[0..1]	Currency	
UnderlyingStreamNotionalDeterminationMethod	[0..1]	String	
UnderlyingStreamNotionalAdjustments	[0..1]	CodeSet	
UnderlyingStreamNotionalFrequencyPeriod	[0..1]	int	Conditionally required when UnderlyingStreamNotionalFrequencyUnit(42020) is specified.
UnderlyingStreamNotionalFrequencyUnit	[0..1]	CodeSet	Conditionally required when UnderlyingStreamNotionalFrequencyPeriod(42019) is specified.
UnderlyingStreamNotionalCommodityFrequency	[0..1]	CodeSet	
UnderlyingStreamNotionalUnitOfMeasure	[0..1]	CodeSet	
UnderlyingStreamTotalNotional	[0..1]	Qty	

Name	Mult.	Type	Description
UnderlyingStreamTotalNotionalUnitOfMeasure	[0..1]	CodeSet	
UnderlyingStreamCommodity	[0..1]	Component	
UnderlyingStreamEffectiveDate	[0..1]	Component	
UnderlyingStreamTerminationDate	[0..1]	Component	
UnderlyingStreamCalculationPeriodDates	[0..1]	Component	
UnderlyingPaymentStream	[0..1]	Component	
UnderlyingPaymentScheduleGrp	[0..*]	Group	
UnderlyingPaymentStubGrp	[0..*]	Group	
UnderlyingDeliveryStream	[0..1]	Component	
UnderlyingDeliveryScheduleGrp	[0..*]	Group	
UnderlyingStreamText	[0..1]	String	
EncodedUnderlyingStreamTextLen	[0..1]	Length	Must be set if EncodedUnderlyingStreamText(40989) field is specified and must immediately precede it.
EncodedUnderlyingStreamText	[0..1]	data	Encoded (non-ASCII characters) representation of the UnderlyingStreamText(40547) field in the encoded format specified via the MessageEncoding(347) field.

Used in components: [UnderlyingInstrument](#)

### 180.2.6778 UnderlyingStreamLastRegularPeriodEndDateUnadjusted

The unadjusted last regular period end date if there is a final stub period.

Type: [LocalMktDate](#)

Used in components: [UnderlyingStreamCalculationPeriodDates](#)

### 180.2.6779 UnderlyingStreamNotional

Notional, or initial notional value for the payment stream. Use SwapSchedule for steps.

Type: [Amt](#)

Used in groups: [UnderlyingStreamGrp](#)

**180.2.6780 UnderlyingStreamNotionalAdjustments**

For equity swaps this specifies the conditions that govern the adjustment to the number of units of the swap.

Type: **int**

Allowed values in StreamNotionalAdjustmentsCodeSet:

Code	Name	Description
0	Execution	Execution. The adjustments to the number of units are governed by an execution clause.
1	PortfolioRebalancing	Portfolio rebalancing. The adjustments to the number of units are governed by a portfolio rebalancing clause.
2	Standard	Standard. The adjustments to the number of units are not governed by any specific clause.

Used in groups: **UnderlyingStreamGrp**

**180.2.6781 UnderlyingStreamNotionalCommodityFrequency**

The commodity's notional or quantity delivery frequency.

Type: **int**

Allowed values in StreamNotionalCommodityFrequencyCodeSet:

Code	Name	Description
0	Term	Term
1	PerBusinessDay	Per business day
2	PerCalculationPeriod	Per calculation period
3	PerSettlPeriod	Per settlement period
4	PerCalendarDay	Per calendar day
5	PerHour	Per hour
6	PerMonth	Per month

Used in groups: **UnderlyingStreamGrp**

**180.2.6782 UnderlyingStreamNotionalDeterminationMethod**

Specifies the method for determining the floating notional value for equity swaps.

See <http://www.fpml.org/coding-scheme/determination-method> for values.

Type: **String**

Used in groups: **UnderlyingStreamGrp**

**180.2.6783 UnderlyingStreamNotionalFrequencyPeriod**

Time unit multiplier for the swap stream's notional frequency.

Type: **int**

Used in groups: **UnderlyingStreamGrp**

**180.2.6784 UnderlyingStreamNotionalFrequencyUnit**

Time unit associated with the swap stream's notional frequency.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in groups: **UnderlyingStreamGrp**



**180.2.6785 UnderlyingStreamNotionalUnitOfMeasure**

Specifies the delivery quantity unit of measure (UOM).

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams

Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [UnderlyingStreamGrp](#)

#### **180.2.6786 UnderlyingStreamNotionalXIDRef**

Cross reference to another UnderlyingStream notional for duplicating its properties.

Type: [XIDREF](#)

Used in groups: [UnderlyingStreamGrp](#)

#### **180.2.6787 UnderlyingStreamPaySide**

The side of the party paying the stream.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **UnderlyingStreamGrp**

#### **180.2.6788 UnderlyingStreamReceiveSide**

The side of the party receiving the stream.

Type: **int**

Allowed values in PaymentPaySideCodeSet:

Code	Name	Description
1	Buy	Buy
2	Sell	Sell

Used in groups: **UnderlyingStreamGrp**

#### **180.2.6789 UnderlyingStreamTerminationDateAdjusted**

The adjusted termination date.

Type: **LocalMktDate**

Used in components: **UnderlyingStreamTerminationDate**

#### **180.2.6790 UnderlyingStreamTerminationDateBusinessCenter**

The business center calendar used to adjust the underlying instrument's stream's termination, or relative termination, date, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: **String**

Used in groups: **UnderlyingStreamTerminationDateBusinessCenterGrp**

**180.2.6791 UnderlyingStreamTerminationDateBusinessCenterGrp**

UnderlyingStreamTerminationDateBusinessCenterGrp is a repeating subcomponent within the UnderlyingStreamTerminationDate component. It is used to specify the set of business centers whose calendars drive the date adjustment. Used only to override the business centers defined in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Name	Mult.	Type	Description
NoUnderlyingStreamTerminationDate-BusinessCenters	[1..1]	NumInGroup	
UnderlyingStreamTerminationDate-BusinessCenter	[0..1]	String	Required if NoUnderlyingStreamTerminationDate-BusinessCenters(40976) > 0.

Used in components: [UnderlyingStreamTerminationDate](#)

**180.2.6792 UnderlyingStreamTerminationDateBusinessDayConvention**

The business day convention used to adjust the underlying instrument's stream's termination, or relative termination, date. Used only to override the business day convention specified in the UnderlyingDateAdjustment component within the UnderlyingInstrument component.

Type: [int](#)

Allowed values in BusinessDayConventionCodeSet:

Code	Name	Description
0	NotApplicable	Not applicable. Business day convention is not applicable.
1	None	None (current day)
2	FollowingDay	Following day. The following business day.
3	FloatingRateNote	Floating rate note. The FRN business day convention.
4	ModifiedFollowingDay	Modified following day. The modified following business day.
5	PrecedingDay	Preceding day. The preceding business day.
6	ModifiedPrecedingDay	Modified preceding day. The modified preceding business day.
7	NearestDay	Nearest day. The nearest applicable business day.

Used in components: [UnderlyingStreamTerminationDate](#)

**180.2.6793 UnderlyingStreamTerminationDate**

UnderlyingStreamTerminationDate is a subcomponent of the UnderlyingStreamGrp component used to specify the termination date of the stream.

Name	Mult.	Type	Description
UnderlyingStreamTerminationDateUnadjusted	[0..1]	LocalMktDate	
UnderlyingStreamTerminationDate-BusinessDayConvention	[0..1]	CodeSet	When specified, this overrides the business day convention defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified value would be specific to this instance of the underlying instrument's termination date of the stream.
UnderlyingStreamTerminationDate-BusinessCenterGrp	[0..*]	Group	When specified, this overrides the business centers defined in the UnderlyingDateAdjustment component in UnderlyingInstrument. The specified values would be specific to this instance of the underlying instrument's termination date of the stream.
UnderlyingStreamTerminationDateRelativeTo	[0..1]	int	
UnderlyingStreamTerminationDateOffsetPeriod	[0..1]	int	Conditionally required when UnderlyingStreamTerminationDateOffsetUnit(40553) is specified.
UnderlyingStreamTerminationDateOffsetUnit	[0..1]	CodeSet	Conditionally required when UnderlyingPaymentTerminationDateOffsetPeriod(40552) is specified.
UnderlyingStreamTerminationDateOffsetDayType	[0..1]	CodeSet	
UnderlyingStreamTerminationDateAdjusted	[0..1]	LocalMktDate	

Used in groups: **UnderlyingStreamGrp**

**180.2.6794 UnderlyingStreamTerminationDateOffsetDayType**

Specifies the day type of the relative termination date offset.

Type: **int**

Allowed values in PaymentStreamPaymentDateOffsetDayTypeCodeSet:

Code	Name	Description
0	Business	Business
1	Calendar	Calendar
2	CommodityBusiness	Commodity business
3	CurrencyBusiness	Currency business
4	ExchangeBusiness	Exchange business
5	ScheduledTradingDay	Scheduled trading day

Used in components: [UnderlyingStreamTerminationDate](#)

#### **180.2.6795 UnderlyingStreamTerminationDateOffsetPeriod**

Time unit multiplier for the relative termination date offset.

Type: [int](#)

Used in components: [UnderlyingStreamTerminationDate](#)

#### **180.2.6796 UnderlyingStreamTerminationDateOffsetUnit**

Time unit associated with the relative termination date offset.

Type: [String](#)

Allowed values in PaymentStreamPaymentDateOffsetUnitCodeSet:

Code	Name	Description
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year

Used in components: [UnderlyingStreamTerminationDate](#)

#### **180.2.6797 UnderlyingStreamTerminationDateRelativeTo**

Specifies the anchor date when the termination date is relative to an anchor date.

See [http://www.fixtradingcommunity.org/codelists#Relative\\_To\\_Date](http://www.fixtradingcommunity.org/codelists#Relative_To_Date) for values.

Type: **int**

Used in components: **UnderlyingStreamTerminationDate**

### **180.2.6798 UnderlyingStreamTerminationDateUnadjusted**

The unadjusted termination date.

Type: **LocalMktDate**

Used in components: **UnderlyingStreamTerminationDate**

### **180.2.6799 UnderlyingStreamText**

Free form text to specify additional information or enumeration description when a standard value does not apply.

Type: **String**

Used in groups: **UnderlyingStreamGrp**

### **180.2.6800 UnderlyingStreamTotalNotional**

Specifies the total notional or delivery quantity over the term of the contract.

Type: **Qty**

Used in groups: **UnderlyingStreamGrp**

### **180.2.6801 UnderlyingStreamTotalNotionalUnitOfMeasure**

Specifies the unit of measure (UOM) for the total notional or delivery quantity over the term of the contract.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

---

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet

---



Code	Name	Description
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)

Code	Name	Description
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint

Code	Name	Description
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
Sqcm	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
Sqkm	SquareKilometer	Square kilometer
Sqm	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
Sqmm	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in groups: [UnderlyingStreamGrp](#)

### 180.2.6802 UnderlyingStreamType

Type of swap stream.

Type: [int](#)

Allowed values in StreamTypeCodeSet:

Code	Name	Description
0	PaymentCashSettlement	Payment / cash settlement
1	PhysicalDelivery	Physical delivery

Used in groups: [UnderlyingStreamGrp](#)

### 180.2.6803 UnderlyingStreamVersion

The stream version identifier when there have been modifications to the contract over time. Helps signal when there are embedded changes.

Type: **String**

Used in groups: **UnderlyingStreamGrp**

#### **180.2.6804 UnderlyingStreamVersionEffectiveDate**

The effective date of the UnderlyingStreamVersion(43083).

Type: **LocalMktDate**

Used in groups: **UnderlyingStreamGrp**

#### **180.2.6805 UnderlyingStreamXID**

Identifier of this UnderlyingStream for cross referencing elsewhere in the message.

Type: **XID**

Used in groups: **UnderlyingStreamGrp**

#### **180.2.6806 UnderlyingStrikeCurrency**

Currency in which the strike price of an underlying instrument is denominated

Type: **Currency**

Used in components: **UnderlyingInstrument**

#### **180.2.6807 UnderlyingStrikeCurrencyCodeSource**

Identifies class or source of the UnderlyingStrikeCurrency(941) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

---

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)

---

Code	Name	Description
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: [UnderlyingInstrument](#)

### **180.2.6808 UnderlyingStrikeIndex**

Specifies the index used to calculate the strike price.

Type: [String](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.6809 UnderlyingStrikeIndexCurvePoint**

The point on the floating rate index curve. Sample values:

M = combination of a number between 1-12 and an "M" for month, e.g. 3M

Y = combination of number between 1-100 and a "Y" for year, e.g. 10Y

10Y-OLD = see above, then add "-OLD" when appropriate

INTERPOLATED = the point is mathematically derived

2/2031 5 3/8 = the point is stated via a combination of maturity month / year and coupon.

Type: [String](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.6810 UnderlyingStrikeIndexQuote**

The quote side from which the index price is to be determined.

Type: [int](#)

Allowed values in StrikeIndexQuoteCodeSet:

Code	Name	Description
0	Bid	Bid.
1	Mid	Mid
2	Offer	Offer

Used in components: [UnderlyingInstrument](#)

### **180.2.6811 UnderlyingStrikeIndexSpread**

Specifies the strike price offset from the named index.

Type: [PriceOffset](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.6812 UnderlyingStrikeMultiplier**

Used for derivatives. Multiplier applied to the strike price for the purpose of calculating the settlement value.

Type: [float](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.6813 UnderlyingStrikePrice**

Underlying security's StrikePrice.

See StrikePrice (202) field for description

Type: [Price](#)

Used in components: [UnderlyingInstrument](#)

### **180.2.6814 UnderlyingStrikePriceBoundaryMethod**

Specifies the boundary condition to be used for the strike price relative to the underlying price at the point of option exercise.

Type: [int](#)

Allowed values in StrikePriceBoundaryMethodCodeSet:

Code	Name	Description
1	LessThan	Less than underlying price is in-the-money (ITM)
2	LessThanOrEqual	Less than or equal to the underlying price is in-the-money(ITM)
3	Equal	Equal to the underlying price is in-the-money(ITM)
4	GreaterThanOrEqual	Greater than or equal to underlying price is in-the-money(ITM)
5	GreaterThan	Greater than underlying is in-the-money(ITM)

Used in components: [UnderlyingInstrument](#)

### 180.2.6815 UnderlyingStrikePriceBoundaryPrecision

Used in combination with StrikePriceBoundaryMethod(1479) to specify the percentage of the strike price in relation to the underlying price. The percentage is generally 100 or greater for puts and 100 or less for calls.

Type: [Percentage](#)

Used in components: [UnderlyingInstrument](#)

### 180.2.6816 UnderlyingStrikePriceDeterminationMethod

Specifies how the strike price is determined at the point of option exercise. The strike may be fixed throughout the life of the option, set at expiration to the value of the underlying, set to the average value of the underlying , or set to the optimal value of the underlying.

Type: [int](#)

Allowed values in StrikePriceDeterminationMethodCodeSet:

Code	Name	Description
1	FixedStrike	Fixed strike (default if not specified)
2	StrikeSetAtExpiration	Strike set at expiration to underlying or other value (lookback floating)
3	StrikeSetToAverageAcrossLife	Strike set to average of underlying settlement price across the life of the option
4	StrikeSetToOptimalValue	Strike set to optimal value

Used in components: [UnderlyingInstrument](#)

**180.2.6817 UnderlyingStrikeUnitOfMeasure**

Used to express the unit of measure (UOM) of the price if different from the contract.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams



Code	Name	Description
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer

Code	Name	Description
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: **UnderlyingInstrument**

### **180.2.6818 UnderlyingStrikeValue**

Used for derivatives. The number of shares/units for the financial instrument involved in the option trade.

Type: **float**

Used in components: **UnderlyingInstrument**

**180.2.6819 UnderlyingSwapClass**

The type or classification of swap. Additional values may be used by mutual agreement of the counter-parties.

Type: **String**

Allowed values in SwapClassCodeSet:

Code	Name	Description
BS	BasisSwap	Basis swap
IX	IndexSwap	Index swap
BB	BroadBasedSecuritySwap	Broad-based security swap
SK	BasketSwap	Basket swap

Used in components: **UnderlyingInstrument**

**180.2.6820 UnderlyingSwapSubClass**

The sub-classification or notional schedule type of the swap.

Type: **String**

Allowed values in SwapSubClassCodeSet:

Code	Name	Description
AMTZ	Amortizing	Amortizing notional schedule
COMP	Compounding	Compounding
CNST	ConstantNotionalSchedule	Constant notional schedule
ACRT	AccretingNotionalSchedule	Accreting notional schedule
CUST	CustomNotionalSchedule	Custom notional schedule

Used in components: **UnderlyingInstrument**

**180.2.6821 UnderlyingSymbol**

Underlying security's Symbol.

See Symbol (55) field for description

Type: **String**

Used in components: **UnderlyingInstrument**

### **180.2.6822 UnderlyingSymbolPositionNumber**

Reference to the first or second currency or digital asset in UnderlyingSymbol(311) for FX-style trading.

Conditionally required when one or both symbols in UnderlyingSymbol(311) represent a digital asset.

Type: **int**

Used in groups: **UndSecAltIDGrp**

### **180.2.6823 UnderlyingSymbolSfx**

Underlying security's SymbolSfx.

See SymbolSfx (65) field for description

Type: **String**

Allowed values in SymbolSfxCodeSet:

Code	Name	Description
CD	EUCPWithLumpSumInterest	EUCP with lump-sum interest rather than discount price
WI	WhenIssued	"When Issued" for a security to be reissued under an old CUSIP or ISIN

Used in components: **UnderlyingInstrument**

### **180.2.6824 UnderlyingTimeUnit**

See TimeUnit(997) for complete definition.

Type: **String**

Allowed values in TimeUnitCodeSet:

Code	Name	Description
H	Hour	Hour
Min	Minute	Minute
S	Second	Second
D	Day	Day
Wk	Week	Week
Mo	Month	Month
Yr	Year	Year
Q	Quarter	Quarter
EOM	EndOfMonth	End of Month. End of Month identifies a relative time unit, e.g. until the third Friday of each month.
F	Flexible	Flexible. A flexible time unit indicates that a specific time unit for the contract is currently undetermined.

Used in components: [UnderlyingInstrument](#)

#### **180.2.6825 UnderlyingTotalIssuedAmount**

Specifies the total amount of the issue. Corresponds to the par value multiplied by the number of issued security.

Type: [Amt](#)

Used in components: [UnderlyingInstrument](#)

#### **180.2.6826 UnderlyingTradingSessionID**

Trading Session in which the underlying instrument trades

Type: [String](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

#### **180.2.6827 UnderlyingTradingSessionSubID**

Trading Session sub identifier in which the underlying instrument trades

Type: [String](#)

Used in messages: [TradeCaptureReport](#), [TradeCaptureReportAck](#)

**180.2.6828 UnderlyingTradingUnitPeriodMultiplier**

Indicates the number of contract periods associated with the minimum trading unit for a given contract duration resulting in the number of total traded contracts.

Type: **int**

Used in components: **UnderlyingInstrument**

**180.2.6829 UnderlyingUnitOfMeasure**

Underlying unit of measure.

See UnitOfMeasure(996) for complete definition.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes

Code	Name	Description
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre

Code	Name	Description
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [UnderlyingInstrument](#)



**180.2.6830 UnderlyingUnitOfMeasureCurrency**

Indicates the currency of the underlying unit of measure. Conditionally required when UnderlyingUnitOfMeasure(998) = Ccy

Type: **Currency**

Used in components: **UnderlyingInstrument**

**180.2.6831 UnderlyingUnitOfMeasureCurrencyCodeSource**

Identifies class or source of the UnderlyingUnitOfMeasureCurrency(1718) value.

Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **UnderlyingInstrument**

**180.2.6832 UnderlyingUnitOfMeasureQty**

Refer to definition of UnitOfMeasureQty(1147)

Type: **Qty**

Used in components: **UnderlyingInstrument**

**180.2.6833 UnderlyingUPICode**

Uniquely identifies the product of an underlying instrument using ISO 4914. See UPICode(2891) for further detail.

Type: **String**

Used in components: **UnderlyingInstrument**

#### **180.2.6834 UnderlyingValuationMethod**

Indicates type of valuation method used.

Type: **String**

Allowed values in ValuationMethodCodeSet:

Code	Name	Description
EQTY	PremiumStyle	premium style
FUT	FuturesStyleMarkToMarket	futures style mark-to-market
FUTDA	FuturesStyleWithAnAttachedCashAdjustment	futures style with an attached cash adjustment
CDS	CDSStyleCollateralization	CDS style collateralization of market to market and coupon
CDSO	CDSInDeliveryUseRecoveryRateToCalculate	CDS in delivery - use recovery rate to calculate obligation

Used in components: **UnderlyingInstrument**

#### **180.2.6835 UnderlyingValuationReferenceModel**

Specifies the methodology and/or assumptions used to generate the trade value.

Type: **String**

Used in components: **UnderlyingInstrument**

#### **180.2.6836 UnderlyingValuationSource**

Specifies the source of trade valuation data.

Type: **String**

Used in components: **UnderlyingInstrument**

**180.2.6837 UndInstrmtCollGrp**

Name	Mult.	Type	Description
NoUnderlyings	[1..1]	NumInGroup	Number of legs that make up the Security
UnderlyingInstrument	[0..1]	Component	Insert here the set of "Underlying Instrument" fields defined in "Common Components of Application Messages". Required if NoUnderlyings > 0
CollAction	[0..1]	CodeSet	Required if NoUnderlyings > 0

Used in messages: [CollateralAssignment](#), [CollateralRequest](#), [CollateralResponse](#)

**180.2.6838 UndInstrmtGrp**

Name	Mult.	Type	Description
NoUnderlyings	[1..1]	NumInGroup	Number of underlyings
UnderlyingInstrument	[0..1]	Component	Required if NoUnderlyings(711) > 0.

Used in groups: [InstrmtMDReqGrp](#), [InstrmtMatchSideGrp](#), [InstrmtStrkPxGrp](#), [ListOrdGrp](#), [MDIncGrp](#), [QuotCxlEntriesGrp](#), [QuotReqGrp](#), [QuotReqRjctGrp](#), [RFQReqGrp](#), [SecListGrp](#), [SecLstUpdRelSymGrp](#), [SecMassStatGrp](#)

Used in messages: [Advertisement](#), [AllocationInstruction](#), [AllocationInstructionAlert](#), [AllocationReport](#), [AssignmentReport](#), [CollateralInquiry](#), [CollateralInquiryAck](#), [CollateralReport](#), [Confirmation](#), [ContraryIntentionReport](#), [CrossOrderCancelReplaceRequest](#), [CrossOrderCancelRequest](#), [DontKnowTrade](#), [Email](#), [ExecutionAck](#), [ExecutionReport](#), [IOI](#), [MarketDataSnapshotFullRefresh](#), [MarketDataStatisticsReport](#), [MarketDataStatisticsRequest](#), [MultilegOrderCancelReplace](#), [NewOrderCross](#), [NewOrderMultileg](#), [NewOrderSingle](#), [News](#), [OrderCancelReplaceRequest](#), [OrderCancelRequest](#), [OrderStatusRequest](#), [PartyRiskLimitCheckRequest](#), [PartyRiskLimitCheckRequestAck](#), [PositionMaintenanceReport](#), [PositionMaintenanceRequest](#), [PositionTransferInstruction](#), [PositionTransferReport](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#), [QuoteStatusRequest](#), [RequestForPositions](#), [RequestForPositionsAck](#), [SecurityDefinition](#), [SecurityDefinitionRequest](#), [SecurityDefinitionUpdateReport](#), [SecurityListRequest](#), [SecurityStatus](#), [SecurityStatusRequest](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeCaptureReportRequest](#), [TradeCaptureReportRequestAck](#)

**180.2.6839 UndlyInstrumentParties**

The use of this component block is restricted to instrument definition only and is not permitted to contain transactional information. Only a specified subset of party roles will be supported within the InstrumentParty block.

Name	Mult.	Type	Description
NoUndlyInstrumentParties	[1..1]	NumInGroup	Repeating group below should contain unique combinations of UnderlyingInstrumentPartyID(1059), UnderlyingInstrumentPartyIDSource(1060) and UnderlyingInstrumentPartyRole(1061).
UnderlyingInstrumentPartyID	[0..1]	String	Used to identify the source of PartyID. Required if UnderlyingInstrumentPartyIDSource(1060) is specified. Required if NoUndlyInstrumentParties(1058) > 0.
UnderlyingInstrumentPartyIDSource	[0..1]	CodeSet	Used to identify class source of UnderlyingInstrumentPartyID(1059) value (e.g. BIC). Required if UnderlyingInstrumentPartyID(1059) is specified. Required if NoUndlyInstrumentParties(1058) > 0.
UnderlyingInstrumentPartyRole	[0..1]	CodeSet	Identifies the type of UnderlyingInstrumentPartyID(1059) (e.g. Executing Broker). Required if NoUndlyInstrumentParties(1058) > 0.
UnderlyingInstrumentPartyRoleQualifier	[0..1]	CodeSet	
UndlyInstrumentPtysSubGrp	[0..*]	Group	Repeating group of party sub-identifiers.

Used in components: [UnderlyingInstrument](#)

**180.2.6840 UndlyInstrumentPtysSubGrp**

Name	Mult.	Type	Description
NoUndlyInstrumentPartySubIDs	[1..1]	NumInGroup	
UnderlyingInstrumentPartySubID	[0..1]	String	
UnderlyingInstrumentPartySubIDType	[0..1]	CodeSet	

Used in groups: [UndlyInstrumentParties](#)

**180.2.6841 UndSecAltIDGrp**

Name	Mult.	Type	Description
NoUnderlyingSecurityAltID	[1..1]	NumInGroup	
UnderlyingSecurityAltID	[0..1]	String	
UnderlyingSecurityAltIDSource	[0..1]	CodeSet	
UnderlyingSymbolPositionNumber	[0..1]	int	

Used in components: [UnderlyingInstrument](#)

**180.2.6842 UnencodedAttachmentLen**

Unencoded content length in bytes. Can be used to validate successful unencoding.

Type: [int](#)

Used in groups: [AttachmentGrp](#)

**180.2.6843 UnitOfMeasure**

The unit of measure of the underlying commodity upon which the contract is based. Two groups of units of measure enumerations are supported.

Fixed Magnitude UOMs are primarily used in energy derivatives and specify a magnitude (such as, MM, Kilo, M, etc.) and the dimension (such as, watt hours, BTU's) to produce standard fixed measures (such as MWh - Megawatt-hours, MMBtu - One million BTUs).

The second group, Variable Quantity UOMs, specifies the dimension as a single unit without a magnitude (or more accurately a magnitude of one) and uses the UnitOfMeasureQty(1147) field to define the quantity of units per contract. Variable Quantity UOMs are used for both commodities (such as lbs of lean cattle, bushels of corn, ounces of gold) and financial futures.

Examples:

For lean cattle futures contracts, a UnitOfMeasure of 'lbs' with a UnitOfMeasureQty(1147) of 40,000, means each lean cattle futures contract represents 40,000 lbs of lean cattle.

For Eurodollars futures contracts, a UnitOfMeasure of Ccy with a UnitOfMeasureCurrency(1716) of USD and a UnitOfMeasureQty(1147) of 1,000,000, means a Eurodollar futures contract represents 1,000,000 USD.

For gold futures contracts, a UnitOfMeasure is oz\_tr (Troy ounce) with a UnitOfMeasureQty(1147) of 1,000, means each gold futures contract represents 1,000 troy ounces of gold.

Type: **String**

Allowed values in UnitOfMeasureCodeSet:

Code	Name	Description
Alw	Allowances	Allowances
Bcf	BillionCubicFeet	Billion cubic feet
Bbl	Barrels	Barrels. Equal to 42 US gallons
CBM	CubicMeters	Cubic Meters
BDFT	BoardFeet	Board feet. Equal to 144 cubic inches
GJ	Gigajoules	gigajoules
Bu	Bushels	Bushels
kHR	HeatRate	Heat rate. The number of BTUs required to produce one kilowatt hour of electricity, typically 3,412.14 BTUs per 1 kWh.
Ccy	Currency	Amount of currency
kWh	KilowattHours	Kilowatt hours
CDD	CoolingDegreeDay	Cooling degree day
MHR	MegaHeatRate	Mega heat rate. The number of million BTUs required to produce one megawatt hour of electricity, typically 3.41214 million BTUs per 1 MWh.
CER	CertifiedEmissionsReduction	Certified emissions reduction
MMBtu	OneMillionBTU	One Million BTU
CPD	CriticalPrecipDay	Critical precipitation day
MWh	MegawattHours	Megawatt hours
CRT	ClimateReserveTonnes	Climate reserve tonnes
thm	Therms	therms. Equal to 100,000 BTU
cwt	Hundredweight	Hundredweight(US). Equal to 100 lbs
tnCO2	TonsOfCarbonDioxide	Tons of carbon dioxide
day	Day	Days
dt	DryMetricTons	Dry metric tons
EnvAllwnc	EnvAllwncCert	Environmental allowance certificates
EnvCrd	EnvironmentalCredit	Environmental credit
EnvOfst	EnvironmentalOffset	Environmental Offset
g	Grams	Grams
Gal	Gallons	Gallons

Code	Name	Description
GT	GrossTons	Gross tons. Also known as long tons or imperial tons, equal to 2240 lbs
HDD	HeatingDegreeDay	Heating degree day
IPNT	IndexPoint	Index point
kg	Kilograms	Kilograms
kL	Kiloliters	kiloliters
kW-a	KilowattYear	Kilowatt year (electrical capacity)
kW-d	KilowattDay	Kilowatt day (electrical capacity)
kW-h	KilowattHour	Kilowatt hour (electrical capacity)
kW-M	KilowattMonth	Kilowatt month (electrical capacity)
kW-min	KilowattMinute	Kilowatt-Minute (electrical capacity)
L	Liters	liters
lbs	Pounds	pounds
MW-a	MegawattYear	Megawatt year (electrical capacity)
MW-d	MegawattDay	Megawatt day (electrical capacity)
MW-h	MegawattHour	Megawatt hour (electrical capacity)
MW-M	MegawattMonth	Megawatt month (electrical capacity)
MW-min	MegawattMinute	Megawatt minute (electrical capacity)
oz_tr	TroyOunces	Troy ounces
PRINC	PrincipalWithRelationToDebtInstrument	Principal with relation to debt instrument
t	MetricTons	Metric tons. Also known as Tonnes, equal to 1000 kg
tn	Tons	Tons (US). Equal to 2000 lbs
a	Are	Are
ac	Acre	Acre
cL	Centiliter	Centiliter
cM	Centimeter	Centimeter
DGE	DieselGallonEquivalent	Diesel gallon equivalent
ft	Foot	Foot
Gal_gb	GBGallon	GB Gallon
GGE	GasolineGallonEquivalent	Gasonline gallon equivalent
ha	Hectare	Hectare
in	Inch	Inch
kM	Kilometer	Kilometer
M	Meter	Meter

Code	Name	Description
mi	Mile	Mile
mL	Milliliter	Milliliter
mM	Millimeter	Millimeter
oz	USOunce	US ounce
pc	Piece	Piece
pt	USPint	US Pint
pt_gb	GBPint	GB pint
qt	USQuart	US Quart
qt_gb	GBQuart	GB Quart
SqcM	SquareCentimeter	Square centimeter
Sqft	SquareFoot	Square foot
Sqin	SquareInch	Square inch
SqkM	SquareKilometer	Square kilometer
SqM	SquareMeter	Square meter
Sqmi	SquareMile	Square mile
SqmM	SquareMillimeter	Square millimeter
Sqyd	SquareYard	Square yard
yd	Yard	Yard
MMbbl	MillionBarrels	Million Barrels
USD	USDollars	US Dollars

Used in components: [Instrument](#)

#### **180.2.6844 UnitOfMeasureCurrency**

Indicates the currency of the unit of measure. Conditionally required when UnitOfMeasure(996) = Ccy

Type: [Currency](#)

Used in components: [Instrument](#)

#### **180.2.6845 UnitOfMeasureCurrencyCodeSource**

Identifies class or source of the UnitOfMeasureCurrency(1716) value.



Type: **String**

Allowed values in CurrencyCodeSourceCodeSet:

Code	Name	Description
1	CUSIP	CUSIP
2	SEDOL	SEDOL
4	ISINNumber	ISIN
6	ISOCurrencyCode	ISO Currency Code (ISO 4217)
S	FinancialInstrumentGlobalIdentifier	Financial Instrument Global Identifier. An Object Management Group (OMG) standard. Also referred to as FIGI. Formerly known as "Bloomberg Open Symbolology BBGID".
Y	DigitalTokenIdentifier	Digital Token Identifier (ISO 24165)

Used in components: **Instrument**

#### 180.2.6846 UnitOfMeasureQty

Used to indicate the quantity of the underlying commodity unit of measure on which the contract is based, such as, 2500 lbs of lean cattle, 1000 barrels of crude oil, 1000 bushels of corn, etc. UnitOfMeasureQty is required for UnitOfMeasure(996) Variable Quantity UOMs enumerations. Refer to the definition of UnitOfMeasure(996) for more information on the use of UnitOfMeasureQty.

Type: **Qty**

Used in components: **Instrument**

#### 180.2.6847 UnsolicitedIndicator

Indicates whether or not message is being sent as a result of a subscription request or not.

Type: **Boolean**

Allowed values in UnsolicitedIndicatorCodeSet:

Code	Name	Description
N	MessagesBeingSentAsAResultOfAPriorRequest	Message is being sent as a result of a prior request
Y	MessagesBeingSentUnsolicited	Message is being sent unsolicited

Used in groups: [TrdSessLstGrp](#)

Used in messages: [MarginRequirementReport](#), [MarketDataStatisticsReport](#), [PartyRiskLimitsReport](#), [PositionReport](#), [RequestForPositionsAck](#), [SecurityMassStatus](#), [SecurityStatus](#), [TradeCaptureReport](#), [TradingSessionStatus](#)

#### **180.2.6848 UpfrontPrice**

Price used to determine upfront payment for swaps contracts.

Type: [Price](#)

Used in messages: [ExecutionReport](#), [NewOrderMultileg](#), [NewOrderSingle](#)

#### **180.2.6849 UpfrontPriceType**

Type of price used to determine upfront payment for swaps contracts.

Type: [int](#)

Allowed values in UpfrontPriceTypeCodeSet:

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
3	FixedAmount	Fixed amount (absolute value)

Used in messages: [ExecutionReport](#), [NewOrderMultileg](#), [NewOrderSingle](#), [TradeCaptureReport](#)

#### **180.2.6850 UPICode**

Uniquely identifies the product of a security using ISO 4914 standard, Unique Product Identifier (UPI). The DSB (Derivative Service Bureau Ltd) is acting as designated service provider for UPI System.

Type: [String](#)

Used in components: [Instrument](#)

Used in groups: [SecTypesGrp](#), [SettlInstGrp](#)

Used in messages: [SettlementInstructionRequest](#)

**180.2.6851 Urgency**

Urgency flag

Type: **char**

Allowed values in UrgencyCodeSet:

Code	Name	Description
0	Normal	Normal
1	Flash	Flash
2	Background	Background

Used in messages: **News**

**180.2.6852 URLLink**

A URI (Uniform Resource Identifier) or URL (Uniform Resource Locator) link to additional information (i.e. <http://www.XYZ.com/research.html>)

See "Appendix 6-B FIX Fields Based Upon Other Standards"

Type: **String**

Used in messages: **Advertisement, IOI, News**

**180.2.6853 Username**

Userid or username.

Type: **String**

Used in groups: **UsernameGrp**

Used in messages: **Logon, UserRequest, UserResponse**

**180.2.6854 UsernameGrp**

Name	Mult.	Type	Description
<b>NoUsernames</b>	[1..1]	NumInGroup	Number of usernames

Name	Mult.	Type	Description
Username	[0..1]	String	Recipient of the notification

Used in messages: [UserNotification](#)

### 180.2.6855 UserRequestID

Unique identifier for a User Request.

Type: [String](#)

Used in messages: [UserRequest](#), [UserResponse](#)

### 180.2.6856 UserRequestType

Indicates the action required by a User Request Message

Type: [int](#)

Allowed values in UserRequestTypeCodeSet:

Code	Name	Description
1	LogOnUser	Log On User
2	LogOffUser	Log Off User
3	ChangePasswordForUser	Change Password For User
4	RequestIndividualUserStatus	Request Individual User Status
5	RequestThrottleLimit	Request Throttle Limit

Used in messages: [UserRequest](#)

### 180.2.6857 UserStatus

Indicates the status of a user

Type: [int](#)

Allowed values in UserStatusCodeSet:

Code	Name	Description
1	LoggedIn	Logged In
2	NotLoggedIn	Not Logged In
3	UserNotRecognised	User Not Recognised
4	PasswordIncorrect	Password Incorrect
5	PasswordChanged	Password Changed
6	Other	Other
7	ForcedUserLogoutByExchange	Forced user logout by Exchange
8	SessionShutdownWarning	Session shutdown warning
9	ThrottleParametersChanged	Throttle parameters changed

Used in messages: [UserNotification](#), [UserResponse](#)

#### **180.2.6858 UserStatusText**

A text description associated with a user status.

Type: [String](#)

Used in messages: [UserResponse](#)

#### **180.2.6859 ValidUntilTime**

Indicates expiration time of indication message (always expressed in UTC (Universal Time Coordinated, also known as "GMT"))

Type: [UTCTimestamp](#)

Used in groups: [QuotEntryAckGrp](#), [QuotEntryGrp](#), [QuotReqGrp](#)

Used in messages: [IOI](#), [Quote](#), [QuoteResponse](#), [QuoteStatusReport](#)

#### **180.2.6860 ValuationBusinessCenter**

Identifies the business center whose calendar is used for valuation, e.g. "GBLO".

See <http://www.fpml.org/coding-scheme/business-center> for standard 4-character code values.

Type: [String](#)

Used in messages: [PositionMaintenanceReport](#), [PositionReport](#), [TradeCaptureReport](#)

**180.2.6861 ValuationDate**

The valuation date of the trade.

Type: **LocalMktDate**

Used in messages: **PositionMaintenanceReport**, **PositionReport**, **TradeCaptureReport**

**180.2.6862 ValuationMethod**

Specifies the type of valuation method applied.

Type: **String**

Allowed values in ValuationMethodCodeSet:

Code	Name	Description
EQTY	PremiumStyle	premium style
FUT	FuturesStyleMarkToMarket	futures style mark-to-market
FUTDA	FuturesStyleWithAnAttachedCashAdjustment	futures style with an attached cash adjustment
CDS	CDSStyleCollateralization	CDS style collateralization of market to market and coupon
CSDS	CDSInDeliveryUseRecoveryRateToCalculate	CDS in delivery - use recovery rate to calculate obligation

Used in components: **Instrument**

**180.2.6863 ValuationReferenceModel**

Specifies the methodology and/or assumptions used to generate the trade value.

Type: **String**

Used in components: **Instrument**

**180.2.6864 ValuationSource**

Specifies the source of trade valuation data.

Type: **String**

Used in components: **Instrument**

**180.2.6865 ValuationTime**

The valuation time of the trade.

Type: **LocalMktTime**

Used in messages: **PositionMaintenanceReport**, **PositionReport**, **TradeCaptureReport**

**180.2.6866 ValueCheckAction**

Action to be taken for the ValueCheckType(1869).

Type: **int**

Allowed values in ValueCheckActionCodeSet:

Code	Name	Description
0	DoNotCheck	Do not check. Checks will not be done for the specified ValueCheckType(1869).
1	Check	Check. Checks will be done for the specified ValueCheckType(1869)
2	BestEffort	Best effort. The market may or may not check the specified ValueCheckType(1869) depending on availability of reference data.

Used in groups: **ValueChecksGrp**

**180.2.6867 ValueChecksGrp**

This component can be used by the message submitter to provide a list of value types to be checked by the counterparty or message recipient.

Name	Mult.	Type	Description
<b>NoValueChecks</b>	[1..1]	NumInGroup	
<b>ValueCheckType</b>	[0..1]	CodeSet	Required if NoValueChecks(1868) > 0.
<b>ValueCheckAction</b>	[0..1]	CodeSet	Required if NoValueChecks(1868) > 0.

Used in messages: **ExecutionReport**, **MultilegOrderCancelReplace**, **NewOrderMultileg**, **NewOrderSingle**, **OrderCancelReplaceRequest**, **Quote**

**180.2.6868 ValueCheckType**

Type of value to be checked.

Type: **int**

Allowed values in ValueCheckTypeCodeSet:

Code	Name	Description
1	PriceCheck	Price check. In the context of ESMA RTS 6 Article 15(1)(a) investment firms are required to perform pre-trade controls using "price collars, which automatically block or cancel orders that do not meet set price parameters, differentiating between different financial instruments, both on an order-by-order basis and over a specified period of time".
2	NotionalValueCheck	Notional value check. In the context of ESMA RTS 6 Article 15(1)(b) investment firms are required to perform pre-trade controls using "maximum order values, which prevent orders with an uncommonly large order value from entering the order book".
3	QuantityCheck	Quantity check. In the context of ESMA RTS 6 Article 15(1)(c) investment firms are required to perform pre-trade controls using "maximum order volumes, which prevent orders with an uncommonly large order quantity from entering the order book".

Used in groups: **ValueChecksGrp**

**180.2.6869 ValueOfFutures**

Used in EFP trades

Type: **Amt**

Used in groups: **BidDescReqGrp**

**180.2.6870 Vega**

The security's price sensitivity to change in volatility of the underlying asset price.

Type: **float**

Used in groups: **SecurityRiskMetricGrp**



**180.2.6871 VegaMultiplier**

Constant value required for the calculation of the clearing quantity, e.g. for variance futures.

Type: **float**

Used in groups: **ClearingPriceParametersGrp**

**180.2.6872 VenueType**

Identifies the type of venue where a trade was executed.

Type: **char**

Allowed values in VenueTypeCodeSet:

Code	Name	Description
E	Electronic	Electronic exchange
P	Pit	Pit
X	ExPit	Ex-pit
C	ClearingHouse	Clearinghouse
R	RegisteredMarket	Registered market. Markets registered with regulators such as exchange, multilateral trading facility (MTF), swap execution facility (SEF). In the context of regulatory reporting (e.g. CFTC reporting), this is used for regulated markets, e.g. swap markets.
O	OffMarket	Off-market. Off-book, off-facility. In the context of regulatory reporting (e.g. CFTC reporting) this identifies trades conducted away from a regulated market.
B	CentralLimitOrderBook	Central limit order book
Q	QuoteDrivenMarket	Quote driven market
D	DarkOrderBook	Dark order book
A	AuctionDrivenMarket	Auction driven market. Markets where matching occurs only in scheduled auctions.
N	QuoteNegotiation	Quote negotiation. Discretionary quoting on request or "request for quote" market.
V	VoiceNegotiation	Voice negotiation. A trading system where transactions between members are arranged through voice negotiation.

Code	Name	Description
H	HybridMarket	Hybrid market. A hybrid system falling into two or more types of trading systems. In the context of ESMA reporting, this is for "Hybrid system." In the context of FCA reporting, this is for "Any other, including hybrid."
z	OtherMarket	Other market (lowercase "z"). A market that does not fall under any of the market types defined for VenueType(1430). In the context of ESMA reporting, this is for "Any other, excluding hybrid."

Used in messages: [AllocationInstruction](#), [AllocationReport](#), [ExecutionReport](#), [TradeCaptureReport](#), [TradeCaptureReportAck](#), [TradeMatchReport](#)

#### 180.2.6873 VerificationMethod

Indication of how a trade was verified.

Type: [int](#)

Allowed values in VerificationMethodCodeSet:

Code	Name	Description
0	NonElectronic	Non-electronic
1	Electronic	Electronic

Used in messages: [TradeCaptureReport](#)

#### 180.2.6874 VersusPurchaseDate

The effective acquisition date of the lot that would be used for gain-loss trade lot reporting. The versus purchase date used to identify the lot in situations where a custodial lot identifier is not available.

Type: [LocalMktDate](#)

Used in groups: [AllocAckGrp](#), [AllocGrp](#), [PreAllocGrp](#), [PreAllocMlegGrp](#), [TrdAllocGrp](#)

**180.2.6875 VersusPurchasePrice**

The versus purchase price used to identify the lot in situations where a custodial lot identifier is not available. The value should be calculated based on current cost basis / quantity held.

Type: **Price**

Used in groups: **AllocAckGrp, AllocGrp, PreAllocGrp, PreAllocMlegGrp, TrdAllocGrp**

**180.2.6876 Volatility**

Annualized volatility for option model calculations

Type: **float**

Used in groups: **ClearingPriceParametersGrp, SecurityRiskMetricGrp**

Used in messages: **ExecutionReport, TradeCaptureReport**

**180.2.6877 VolatilityTime**

Time at which volatility was computed.

Type: **UTCTimestamp**

Used in groups: **SecurityRiskMetricGrp**

**180.2.6878 VoluntaryRegulatoryReport**

Used in conjunction with RegulatoryReportType(1934) to indicate whether the trade report is a voluntary regulatory report. If not specified, the default for a regulatory report is "N".

When VoluntaryRegulatoryReport(1935)=Y it is recommended that one of the parties to the trade be identified as the voluntary reporting party through PartySubIDType(803) = 63 (Voluntary reporting entity).

Type: **Boolean**

Used in messages: **TradeCaptureReport**

**180.2.6879 WarningText**

Communicates the underlying condition when the request response indicates "warning".

Type: **String**

Used in messages: **CollateralResponse**

**180.2.6880 WireReference**

The reference to a wire transfer associated with the transaction. Wire references done via wire services such as Fedwire Output Message Accountability Data "OMAD" or SWIFT Output Sequence Number "OSN".

Type: **String**

Used in messages: **CollateralAssignment**, **CollateralReport**, **CollateralResponse**

**180.2.6881 WorkingIndicator**

Indicates if the order is currently being worked. Applicable only for OrdStatus = "New". For open outcry markets this indicates that the order is being worked in the crowd. For electronic markets it indicates that the order has transitioned from a contingent order to a market order.

Type: **Boolean**

Allowed values in WorkingIndicatorCodeSet:

Code	Name	Description
N	NotWorking	Order has been accepted but not yet in a working state
Y	Working	Order is currently being worked

Used in groups: **OrdListStatGrp**

Used in messages: **ExecutionReport**, **OrderCancelReject**

**180.2.6882 WtAverageLiquidity**

Overall weighted average liquidity expressed as a % of average daily volume. Represented as a percentage.

Type: **Percentage**

Used in messages: [BidRequest](#)

#### **180.2.6883 XmlData**

Actual XML data stream (e.g. FIXML). See appropriate XML reference (e.g. FIXML). Note: may contain embedded SOH characters.

Type: [XMLData](#)

Used in components: [StandardHeader](#)

#### **180.2.6884 XmlDataLen**

Length of the XmlData data block.

Type: [Length](#)

Used in components: [StandardHeader](#)

#### **180.2.6885 Yield**

Yield percentage.

(Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: [Percentage](#)

Used in components: [YieldData](#)

#### **180.2.6886 YieldCalcDate**

Include as needed to clarify yield irregularities associated with date, e.g. when it falls on a non-business day.

Type: [LocalMktDate](#)

Used in components: [YieldData](#)

#### **180.2.6887 YieldData**

The YieldData component block conveys yield information for a given Fixed Income security.

Name	Mult.	Type	Description
YieldType	[0..1]	CodeSet	
Yield	[0..1]	Percentage	
YieldCalcDate	[0..1]	LocalMktDate	
YieldRedemptionDate	[0..1]	LocalMktDate	
YieldRedemptionPrice	[0..1]	Price	
YieldRedemptionPriceType	[0..1]	CodeSet	

Used in groups: ListOrdGrp, MDFullGrp, MDIncGrp, QuotReqGrp, QuotReqRjctGrp, SecListGrp, SecLstUpdRelSymGrp

Used in messages: AllocationInstruction, AllocationInstructionAlert, AllocationReport, Confirmation, CrossOrderCancelReplaceRequest, ExecutionReport, IOI, NewOrderCross, NewOrderSingle, OrderCancelReplaceRequest, Quote, QuoteResponse, QuoteStatusReport, SecurityDefinition, SecurityDefinitionRequest, SecurityDefinitionUpdateReport, TradeCaptureReport

#### 180.2.6888 YieldRedemptionDate

Date to which the yield has been calculated (i.e. maturity, par call or current call, pre-refunded date).

Type: LocalMktDate

Used in components: YieldData

#### 180.2.6889 YieldRedemptionPrice

Price to which the yield has been calculated.

Type: Price

Used in components: YieldData

#### 180.2.6890 YieldRedemptionPriceType

The price type of the YieldRedemptionPrice (697)

See PriceType (423) for description and valid values.

Type: int

Allowed values in PriceTypeCodeSet:

Code	Name	Description
1	Percentage	Percentage (i.e. percent of par) (often called "dollar price" for fixed income)
2	PerUnit	Per unit (i.e. per share or contract)
3	FixedAmount	Fixed amount (absolute value)
4	Discount	Discount - percentage points below par
5	Premium	Premium - percentage points over par
6	Spread	Spread (basis points spread). Usually the difference in yield between two switched bonds or a corporate bond traded spread-to-benchmark.
7	TEDPrice	TED Price
8	TEDYield	TED Yield
9	Yield	Yield
10	FixedCabinetTradePrice	Fixed cabinet trade price (primarily for listed futures and options)
11	VariableCabinetTradePrice	Variable cabinet trade price (primarily for listed futures and options)
12	PriceSpread	Price spread. Price spread is expressed based on market convention for the asset being priced or traded. For example, the difference between the prices of a multileg switch or strategy expressed in basis points for a CDS or TBA roll; a price value to be added to a reference price, such as a "pay up" for specified pools
13	ProductTicksInHalves	Product ticks in halves
14	ProductTicksInFourths	Product ticks in fourths
15	ProductTicksInEighths	Product ticks in eighths
16	ProductTicksInSixteenths	Product ticks in sixteenths
17	ProductTicksInThirtySeconds	Product ticks in thirty-seconds
18	ProductTicksInSixtyFourths	Product ticks in sixty-fourths
19	ProductTicksInOneTwentyEighths	Product ticks in one-twenty-eighths
20	NormalRateRepresentation	Normal rate representation (e.g. FX rate)
21	InverseRateRepresentation	Inverse rate representation (e.g. FX rate)
22	BasisPoints	Basis points. When the price is not spread based.
23	UpfrontPoints	Up front points. Used specifically for CDS pricing.
24	InterestRate	Interest rate. When the price is an interest rate. For example, used with benchmark reference rate.
25	PercentageNotional	Percentage of notional

Used in components: [YieldData](#)

### 180.2.6891 YieldType

Type of yield. (Note tag # was reserved in FIX 4.1, added in FIX 4.3)

Type: [String](#)

Allowed values in YieldTypeCodeSet:

Code	Name	Description
AFTERTAX	AfterTaxYield	After Tax Yield (Municipals)
ANNUAL	AnnualYield	Annual Yield
ATISSUE	YieldAtIssue	Yield At Issue (Municipals)
AVGMATURITY	YieldToAverageMaturity	Yield To Avg Maturity
BOOK	BookYield	Book Yield
CALL	YieldToNextCall	Yield to Next Call
CHANGE	YieldChangeSinceClose	Yield Change Since Close
CLOSE	ClosingYield	Closing Yield
COMPOUND	CompoundYield	Compound Yield
CURRENT	CurrentYield	Current Yield
GOVTEQUIV	GvntEquivalentYield	Gvnt Equivalent Yield
GROSS	TrueGrossYield	True Gross Yield
INFLATION	YieldWithInflationAssumption	Yield with Inflation Assumption
INVERSEFLOATER	InverseFloaterBondYield	Inverse Floater Bond Yield
LASTCLOSE	MostRecentClosingYield	Most Recent Closing Yield
LASTMONTH	ClosingYieldMostRecentMonth	Closing Yield Most Recent Month
LASTQUARTER	ClosingYieldMostRecentQuarter	Closing Yield Most Recent Quarter
LASTYEAR	ClosingYieldMostRecentYear	Closing Yield Most Recent Year
LONGAVGLIFE	YieldToLongestAverageLife	Yield to Longest Average Life
MARK	MarkToMarketYield	Mark to Market Yield
MATURITY	YieldToMaturity	Yield to Maturity
NEXTREFUND	YieldToNextRefund	Yield to Next Refund (Sinking Fund Bonds)
OPENAVG	OpenAverageYield	Open Average Yield
PREVCLOSE	PreviousCloseYield	Previous Close Yield
PROCEEDS	ProceedsYield	Proceeds Yield
PUT	YieldToNextPut	Yield to Next Put



Code	Name	Description
SEMIANNUAL	SemiAnnualYield	Semi-annual Yield
SHORTAVGLIFE	YieldToShortestAverageLife	Yield to Shortest Average Life
SIMPLE	SimpleYield	Simple Yield
TAXEQUIV	TaxEquivalentYield	Tax Equivalent Yield
TENDER	YieldToTenderDate	Yield to Tender Date
TRUE	TrueYield	True Yield
VALUE1_32	YieldValueOf32nds	Yield Value Of 1/32
WORST	YieldToWorst	Yield To Worst

Used in components: [YieldData](#)